

Mr. Billy Burga
Nishikawa Standard, Inc.
501 High Road
Bremen, IN 46506

Re: Minor Source Modification No: 099-10577-00041

Dear Mr. Burga:

Nishikawa Standard, Inc. applied for a Part 70 operating permit on December 13, 1996 for the proposed surface coating equipment. An application to modify the source was received on January 29, 1999. Pursuant to 326 IAC 2-7-10.5 the following emission units are approved for construction at the source:

- (a) one (1) vertical HVLP spray application surface coating booth, identified as AS-1, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-4,
- (b) one (1) horizontal HVLP spray application surface coating booth, identified as AS-2, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-3, and
- (c) two (2) electric I/R cure ovens.

The proposed Minor Source Modification approval will be incorporated into the pending Part 70 permit application pursuant to 326 IAC 2-7-10.5(l)(3). The source may begin operation upon issuance of the source modification approval.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter call (800) 451-6027, press 0 and ask for Scott Fulton.

Sincerely,

Paul Dubenetzky, Chief
Permits Branch
Office of Air Management

Attachments
SDF

cc: File - Marshall County
U.S. EPA, Region V
Marshall County Health Department
Air Compliance Section Inspector Paul Karkiewicz
Compliance Data Section - Jerri Curless
Administrative and Development - Janet Mobley
Technical Support and Modeling - Nancy Landau

PART 70 MINOR SOURCE MODIFICATION OFFICE OF AIR MANAGEMENT

**Nishikawa Standard, Inc.
501 High Road
Bremen, IN 46506**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this approval.

This approval is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Minor Source Modification No.: 099-10577-00041	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

SECTION A SOURCE SUMMARY

This approval is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM). The information describing the emission units contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this approval pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates a surface coating operation.

Responsible Official: Billy Burga
Source Address: 501 High Road, Bremen, Indiana 46506
Mailing Address: 324 Morrow Street, Topeka, IN 46571
Phone Number: (219) 593-2156
SIC Code: 3069
County Location: Marshall
County Status: Attainment for all criteria pollutants
Source Status: Part 70 Permit Program

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source is approved to construct and operate the following emission units and pollution control devices:

- (a) one (1) vertical HVLP spray application surface coating booth, identified as AS-1, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-4,
- (b) one (1) horizontal HVLP spray application surface coating booth, identified as AS-2, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-3, and
- (c) two (2) electric I/R cure ovens.

A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because it is a major source, as defined in 326 IAC 2-7-1(22).

SECTION B GENERAL CONSTRUCTION CONDITIONS

B.1 Permit No Defense [IC 13]

This approval to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions [326 IAC 2-7-1]

Terms in this approval shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.

B.4 Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

SECTION C GENERAL OPERATION CONDITIONS

C.1 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]

- (a) Where specifically designated by this approval or required by an applicable requirement, any application form, report, or compliance certification submitted under this approval shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this approval, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this approval, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this approval, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM.

C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

(a) The Permittee must comply with the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this approval.

(b) Any application requesting an amendment or modification of this approval shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

C.4 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this approval:

(a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.

(b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

C.5 Operation of Equipment [326 IAC 2-7-6(6)]

All air pollution control equipment listed in this approval and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

Testing Requirements [326 IAC 2-7-6(1)]

C.6 Performance Testing [326 IAC 3-6]

(a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this approval, utilizing methods approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this approval, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.7 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend the compliance schedule an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.8 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5][326 IAC 2-7-6] [326 IAC 1-6]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
- (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of :
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and

- (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
 - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

C.9 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this approval exceed the level specified in any condition of this approval, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate approval conditions may be grounds for immediate revocation of the approval to operate the affected facility.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.10 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

(a) The Permittee shall submit an annual emission statement certified pursuant to the requirements of 326 IAC 2-6, that must be received by July 1 of each year and must comply with the minimum requirements specified in 326 IAC 2-6-4. The annual emission statement shall meet the following requirements:

- (1) Indicate actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
- (2) Indicate actual emissions of other regulated pollutants from the source, for purposes of Part 70 fee assessment.

(b) The annual emission statement covers the twelve (12) consecutive month time period starting January 1 and ending December 31. The annual emission statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

(c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

C.11 General Record Keeping Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-6]

(a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAM, representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

(b) Records of required monitoring information shall include, where applicable:

- (1) The date, place, and time of sampling or measurements;
- (2) The dates analyses were performed;
- (3) The company or entity performing the analyses;
- (4) The analytic techniques or methods used;
- (5) The results of such analyses; and

- (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this approval;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this approval, and whether a deviation from an approval condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of approval issuance.

C.12 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) The reports required by conditions in Section D of this approval shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (b) Unless otherwise specified in this approval, any notice, report, or other submission required by this approval shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) Unless otherwise specified in this approval, any quarterly report shall be submitted within thirty (30) days of the end of the reporting period. The report does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) The first report shall cover the period commencing on the date of issuance of this approval and ending on the last day of the reporting period.

Stratospheric Ozone Protection

C.13 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1 FACILITY OPERATION CONDITIONS

- (a) one (1) vertical HVLP spray application surface coating booth, identified as AS-1, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-4,
- (b) one (1) horizontal HVLP spray application surface coating booth, identified as AS-2, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-3, and
- (c) two (2) electric I/R cure ovens.

D.1.1 Particulate Matter (PM) [326 IAC 6-3-2(c)]

Pursuant to 326 IAC 6-3-2, the particulate matter (PM) from spray booths AS-1 and AS-2 shall be limited by the following:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The dry filter systems of spray booths AS-1 and AS-2 shall be in operation at all times the booths are in operation, in order to comply with this limit.

D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements

D.1.3 Testing Requirements [326 IAC 2-7-6(1),(6)][326 IAC 2-1.1-11]

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the particulate matter (PM) limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.4 Particulate Matter (PM)

The PM control devices shall be in operation at all times when Spray Booths AS-1 and AS-2 are in operation.

D.1.5 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks S-3 and S-4 while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.6 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 SOURCE MODIFICATION
CERTIFICATION**

Source Name: Nishikawa Standard, Inc.
Source Address: 501 High Road, Bremen, Indiana 46506
Mailing Address: 324 Morrow Street, Topeka, Indiana 46571
Source Modification No.: 099-10577-00041

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this approval.

Please check what document is being certified:

- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

Indiana Department of Environmental Management Office of Air Management

Technical Support Document (TSD) for a Source Modification to a Part 70 Operating Permit

Source Background and Description

Source Name: Nishikawa Standard, Inc.
 Source Location: 501 High Road, Bremen, Indiana 46571
 County: Marshall
 SIC Code: 3069
 Permit Reviewer: SDF
 Operation Permit No.: T-099-7539-00041
 Source Modification No.: 099-10577-00041

The Office of Air Management (OAM) has reviewed a modification application from Nishikawa Standard, Inc. relating to the construction and operation of the following surface coating equipment:

- (a) one (1) vertical HVLP spray application surface coating booth, identified as AS-1, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-4,
- (b) one (1) horizontal HVLP spray application surface coating booth, identified as AS-2, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-3, and
- (c) two (2) electric I/R cure ovens.

Existing Approvals

The source has a pending Part 70 Operating Permit (T-099-7539-00041) application submitted on December 12, 1996.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
S-3	Booth AS-2	36	1.5	10000	70
S-4	Booth AS-1	36	1.5	10000	70

Recommendation

The staff recommends to the Commissioner that the Minor Source Modification be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on January 27, 1999.

Emission Calculations

Potential Emissions:

The following lists the estimated potential emissions from the surface coating booths as determined using the attached standard combustion spreadsheets.

Unit	VOC ton/yr	PM ton/yr	PM10 ton/yr
Spray Booth AS-1	13.78	0.40	0.40
Spray Booth AS-2	2.52	0.07	0.07
Total	16.30	0.47	0.47

See Appendix A (Emissions Calculation Spreadsheets) for detailed calculations (1 page).

The electric curing ovens are ancillary equipment. No emissions are generated by these ovens.

Potential Emissions After Controls:

The PM/PM10 emissions from the surface coating booths are controlled by a dry filter system with a design control efficiency of 90%. The VOC emissions are uncontrolled.

$$\text{PM/PM10 Emissions Before Controls} * (1 - 0.90) = \text{PM/PM10 Emissions After Controls}$$

The following lists the potential emissions after controls:

Unit	VOC ton/yr	PM ton/yr	PM10 ton/yr
Spray Booth AS-1	13.78	0.04	0.04
Spray Booth AS-2	2.52	0.01	0.01
Total	16.30	0.05	0.05

Allowable Emissions:

The allowable emissions are determined to be equal to the potential emissions.

HAP Emissions:

The coatings applied in the proposed booths will not generate any hazardous air pollutants (HAP).

Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA.”

Pollutant	Potential To Emit (tons/year)
PM	22.24
PM-10	22.24
SO ₂	neg.
VOC	268.87
CO	4.35
NO _x	17.56

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of volatile organic compounds (VOC) are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.

Actual Emissions

No previous emission data has been received from the source.

County Attainment Status

The source is located in Marshall County.

Pollutant	Status
PM-10	attainment or unclassifiable
SO ₂	attainment or unclassifiable
NO ₂	attainment or unclassifiable
Ozone	attainment or unclassifiable
CO	attainment or unclassifiable
Lead	attainment or unclassifiable

Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Marshall County has been designated as attainment or unclassifiable for ozone.

Part 70 Permit Determination

326 IAC 2-7 (Part 70 Permit Program)

This existing source has submitted their Part 70 (T-099-7539-00041) application on December 12, 1996. The equipment being reviewed under this permit shall be incorporated in the submitted Part 70 application.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 20 and 40 CFR Part 61 and 63) applicable to this source.

State Rule Applicability

Applicable Section C Conditions:

326 IAC 2-6 (Emission Reporting):

This source is subject to 326 IAC 2-6 (Emission Reporting), because it has the potential to emit more than one hundred (100) tons per year of volatile organic compounds. Pursuant to this rule, the owner/operator of the source must annually submit an emission statement for the source. The annual statement must be received by July 1 of each year and contain the minimum requirement as specified in 326 IAC 2-6-4. The submittal should cover the period defined in 326 IAC 2-6-2(8)(Emission Statement Operating Year).

326 IAC 5-1 (Opacity Limitations):

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

Applicable Section D Conditions:

326 IAC 6-3-2 (Process Operations):

The proposed spray booths are subject to 326 IAC 6-3-2. Pursuant to 326 IAC 6-3-2, the particulate matter (PM) from spray booths AS-1 and AS-2 shall be limited by the following:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The dry filter systems of spray booths AS-1 and AS-2 shall be in operation at all times the booths are in operation, in order to comply with this limit.

326 IAC 8-1-6 (General Reduction Requirements):

Even though no other article 8 rules apply, 326 IAC 8-1-6 does not apply to proposed spray booths AS-1 and AS-2 because no facility VOC emissions (13.78 ton/yr or 2.52 ton/yr) exceed the applicable level of 25 tons per year.

326 IAC 2-1-3.4 (New Source Toxics Control):

The New Source Toxics Control rule does not apply because the source is not “construction” of a major source of hazardous air pollutants. The coatings applied by the proposed equipment will not emit HAPs.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source’s failure to take the appropriate corrective actions within a specific time period.

The surface coating spray booths AS-1 and AS-2 have applicable compliance monitoring conditions as specified below:

SECTION D.1 FACILITY OPERATION CONDITIONS

- | | |
|-----|---|
| (a) | one (1) vertical HVLP spray application surface coating booth, identified as AS-1, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-4, |
| (b) | one (1) horizontal HVLP spray application surface coating booth, identified as AS-2, with a maximum design throughput of 120 parts per hour, with PM/PM10 overspray emissions controlled by a dry filter system and emissions exhausted to Stack S-3, and |
| (c) | two (2) electric I/R cure ovens. |

D.1.1 Particulate Matter (PM) [326 IAC 6-3-2(c)]

Pursuant to 326 IAC 6-3-2, the particulate matter (PM) from spray booths AS-1 and AS-2 shall be limited by the following:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The dry filter systems of spray booths AS-1 and AS-2 shall be in operation at all times the booths are in operation, in order to comply with this limit.

D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements

D.1.3 Testing Requirements [326 IAC 2-7-6(1),(6)][326 IAC 2-1.1-11]

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the particulate matter (PM) limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.4 Particulate Matter (PM)

The PM control devices shall be in operation at all times when Spray Booths AS-1 and AS-2 are in operation.

D.1.5 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks S-3 and S-4 while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.6 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.

- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

These monitoring conditions are necessary because the dry filter systems of spray booths AS-1 and AS-2 must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-7 (Part 70).

Air Toxic Emissions

Indiana presently requests applicants to provide information on emissions of the 188 hazardous air pollutants (HAPs) set out in the Clean Air Act Amendments of 1990. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Management (OAM) Part 70 Application Form GSD-08.

None of the listed air toxics will be emitted from this proposed modification.

Conclusion

The operation of the surface coating spray booths and their associated curing ovens shall be subject to the conditions of the attached proposed Permit No. T-099-7539-00041 application submitted on December 12, 1996.

**Appendix A: Emissions Calculations
VOC and Particulate
From Surface Coating Operations**

TSD, Appendix A

Company Name: Nishikawa Standard, Inc.
Address City IN Zip: 501 High Road, Bremen, Indiana 46571
CP: 099-10577
Plt ID: 099-00041
Reviewer: SDF
Date: 2-2-99

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
N9206 for AS-1	6.8	83.81%	0.0%	83.8%	0.0%	12.49%	0.00460	120.000	5.70	5.70	3.15	75.50	13.78	0.40	45.63	85%
N9206 for AS-2	6.8	83.81%	0.0%	83.8%	0.0%	12.49%	0.00084	120.000	5.70	5.70	0.57	13.79	2.52	0.07	45.63	85%

State Potential Emissions	Add worst case coating to all solvents	3.72	89.29	16.30	0.47
----------------------------------	---	-------------	--------------	--------------	-------------

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1 - Volume % water)
Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)
Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)
Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)
Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1 - Weight % Volatiles) * (1 - Transfer efficiency) * (8760 hrs/yr) * (1 ton/2000 lbs)
Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)
Total = Worst Coating + Sum of all solvents used