



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

TO: Interested Parties / Applicant
DATE: April 12, 2005
RE: Monaco Coach Corporation / 039-15279-00017
FROM: Paul Dubenetzky
Chief, Permits Branch
Office of Air Quality

Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-17-3-4 and 326 IAC 2, this approval is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-7-3 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER-MOD.dot 1/10/05

April 12, 2005

Mr. Kurt Anderson
Monaco Coach Corporation
P.O. Box 465
Wakarusa, IN 46573

Re: 039-15279-00017
First Significant Permit Modification to
Part 70 No.: T 039-7559-00017

Dear Mr. Anderson:

Monaco Coach Corporation was issued a permit on June 21, 2004 for a multi-plant luxury motor home manufacturing operation. A letter requesting changes to this permit was received on December 13, 2001. Pursuant to the provisions of 326 IAC 2-7-12 a significant permit modification to this permit is hereby approved as described in the attached Technical Support Document.

Specifically, Monaco Coach Corporation has submitted a request to apply across category averaging to fiberglass units SV32-1, GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1, as allowed under 326 IAC 20-25.

Currently, within category averaging pursuant to 326 IAC 20-25 is used to demonstrate compliance with the monomer HAP content limits of unit SV32-1. Across category averaging pursuant to 326 IAC 8-1-6 is used to demonstrate compliance with the monomer HAP content limits of all of the other affected units (GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1).

This Significant Permit Modification will allow the use of across category averaging for all of the affected units pursuant to 326 IAC 20-25.

The Office of Air Quality has determined that the proposed changes are significant pursuant to 326 IAC 2-7-12(d) because the proposed changes do not qualify for an Administrative Amendment pursuant to 326 IAC 2-7-11 or a Minor Permit Modification pursuant to 326 IAC 2-7-12(b).

All other conditions of the permit shall remain unchanged and in effect. Please attach a copy of this modification and the following revised permit pages to the front of the original permit.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Scott Fulton, OAQ, 100 North Senate Avenue, P.O. Box 6015, Indianapolis, Indiana, 46206-6015, or call at (800) 451-6027, press 0 and ask for Scott Fulton or extension (3-5691), or dial (317) 233-5691.

Sincerely,

Original Signed by
Paul Dubenetzky, Chief
Permits Branch
Office of Air Quality

Attachments
SDF

cc: File - Elkhart County
U.S. EPA, Region V
Elkhart County Health Department
Northern Regional Office
Air Compliance Section Inspector - Paul Karkiewicz
Compliance Data Section
Administrative and Development

Monaco Coach Corporation
Elkhart, Indiana
Permit Reviewer: SDF

Page 2 of 2
039-15246-00182

PART 70 OPERATING PERMIT OFFICE OF AIR QUALITY

**Monaco Coach Corporation
606 Nelson's Parkway
Wakarusa, IN 46573**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17. **This permit also addresses certain New Source Review requirements for existing equipment and is intended to fulfill the new source review procedures pursuant to 326 IAC 2-2 and 326 IAC 2-7-10.5, applicable to those conditions.**

Operation Permit No.: T039-7559-00017	Date Issued: June 21, 2004 Expiration Date: June 21, 2009
Issued by: Janet G. McCabe, Assistant Commissioner, Office of Air Quality	

First Significant Permit Modification No.: 039-15279-00017	Affected Pages: 2-8, 60-79, 94
Issued by: Original Signed by Paul Dubenetzky, Branch Chief Office of Air Quality	April 12, 2005

TABLE OF CONTENTS

SECTION A SOURCE SUMMARY 9

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]
- A.2 Part 70 Source Definition [326 IAC 2-7-1(22)]
- A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
[326 IAC 2-7-5(15)]
- A.4 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]
- A.5 Part 70 Permit Applicability [326 IAC 2-7-2]

SECTION B GENERAL CONDITIONS 17

- B.1 Definitions [326 IAC 2-7-1]
- B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]
- B.3 Enforceability [326 IAC 2-7-7]
- B.4 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
- B.5 Severability [326 IAC 2-7-5(5)]
- B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]
- B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]
- B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3)and (13)][326 IAC 2-7-6(1)and(6)]
[326 IAC 1-6-3]
- B.11 Emergency Provisions [326 IAC 2-7-16]
- B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]
- B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5]
- B.14 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
- B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]
- B.16 Permit Renewal [326 IAC 2-7-4]
- B.17 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]
- B.18 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
[326 IAC 2-7-12(b)(2)]
- B.19 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]
- B.20 Source Modification Requirement [326 IAC 2-7-10.5]
- B.21 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC13-17-3-2] [IC 13-30-3-1] [IC 13-
17-3-2]
- B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]
- B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]
- B.24 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314]

SECTION C SOURCE OPERATION CONDITIONS 28

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates
[40 CFR 52 Subpart P] [326 IAC 6-3-2]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]

- C.6 Operation of Equipment [326 IAC 2-7-6(6)]
- C.7 Stack Height [326 IAC 1-7]
- C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

Testing Requirements [326 IAC 2-7-6(1)]

- C.9 Performance Testing [326 IAC 3-6]

Compliance Requirements [326 IAC 2-1.1-11]

- C.10 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.13 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
- C.16 Compliance Response Plan - Preparation, Implementation, Records, and Reports
- C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]
- C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection

- C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

MACT Application Submittal Requirement

- C.22 Application Requirements for Section 112(j) of the Clean Air Act [40 CFR 63.52(e)] [40 CFR 63.56(a)] [40 CFR 63.9(b)] [326 IAC 2-7-12]

SECTION D.1 FACILITY OPERATION CONDITIONS - Plant 1 36

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]
- D.1.2 Particulate Matter (PM) [40 CFR 52 Subpart P]
- D.1.3 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]
- D.1.4 Volatile Organic Compounds (VOC) Limitations [326 IAC 8-2-9]
- D.1.5 Volatile Organic Compound (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9]
- D.1.6 Particulate [326 IAC 6-3-2(d)]
- D.1.7 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.8 Particulate Control
- D.1.9 Volatile Organic Compounds (VOC) [326 IAC 8-1-2] [326 IAC 8-1-4]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.10 Operator Training Program
- D.1.11 Baghouse Inspections
- D.1.12 Broken or Failed Bag Detection

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.13 Record Keeping Requirements
- D.1.14 Reporting Requirements

SECTION D.2 FACILITY OPERATION CONDITIONS - Plant 2 41

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.2.1 Best Available Control Technology (BACT) and Maximum Control Technology (MACT) [326 IAC 2-2] [40 CFR 52.21][326 IAC 2-4.1]
- D.2.2 Particulate Matter (PM) [40 CFR Part 52 Subpart P]
- D.2.3 Volatile Organic Compounds [326 IAC 8-2-9]
- D.2.4 Particulate [326 IAC 6-3-2(d)]
- D.2.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.2.6 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.2.7 Operator Training Program

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.2.8 Record Keeping Requirements
- D.2.9 Reporting Requirements

SECTION D.3 FACILITY OPERATION CONDITIONS - Plant 20 48

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.3.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]
- D.3.2 Particulate Matter (PM) [40 CFR 52 Subpart P]

Compliance Determination Requirements

- D.3.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.3.4 Record Keeping Requirements
- D.3.5 Reporting Requirements

SECTION D.4 FACILITY OPERATION CONDITIONS Plant 22 50

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.4.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]
- D.4.2 Particulate Matter (PM) [40 CFR Part 52 Subpart P]
- D.4.3 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]
- D.4.4 Particulate [326 IAC 6-3-2(d)]
- D.4.5 Volatile Organic Compounds (VOC) Limitations [326 IAC 8-2-9]
- D.4.6 Volatile Organic Compound (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9]

D.4.7 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

D.4.8 Particulate Control

D.4.9 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.4.10 Operator Training Program

D.4.11 Cyclone Failure Detection

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.4.12 Record Keeping Requirements

D.4.13 Reporting Requirements

SECTION D.5 FACILITY OPERATION CONDITIONS - Plant 26 54

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.5.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

D.5.2 Particulate [326 IAC 6-3-2]

Compliance Determination Requirements

D.5.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.5.4 Record Keeping Requirements

D.5.5 Reporting Requirements

SECTION D.6 FACILITY OPERATION CONDITIONS - Plant 28 56

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.6.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

D.6.2 Volatile Organic Compounds [326 IAC 8-1-6]

Compliance Determination Requirements

D.6.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.6.4 Record Keeping Requirements

D.6.5 Reporting Requirements

SECTION D.7 FACILITY OPERATION CONDITIONS - Plant 29 58

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.7.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Compliance Determination Requirements

D.7.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.7.3 Record Keeping Requirements

D.7.4 Reporting Requirements

SECTION D.8 FACILITY OPERATION CONDITIONS - Plants 31 and 32 60

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.8.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]
- D.8.2 Particulate Matter [326 IAC 6-2-3]
- D.8.3 Particulate Matter (PM) [40 CFR 52 Subpart P]
- D.8.4 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]
- D.8.5 Particulate [326 IAC 6-3-2(d)]
- D.8.6 Volatile Organic Compounds [326 IAC 8-1-6]
- D.8.7 Emissions Standards for Reinforced Plastics Composites Fabricating [326 IAC 20-25-3]
- D.8.8 Work Practice Standards for Reinforced Plastic Composites Fabrication [326 IAC 20-25-4]
- D.8.9 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-25-8]
- D.8.10 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.8.11 Hazardous Air Pollutants (HAP) and Volatile Organic Compounds (VOC)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.8.12 Operator Training Program

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.8.13 Record Keeping Requirements
- D.8.14 Reporting Requirements

SECTION D.9 FACILITY OPERATION CONDITIONS - Plants 36 and 37 69

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.9.1 General Provisions Relating to NESHAP [326 IAC 20-1][40 CFR Part 63, Subpart A]
- D.9.2 National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production [40 CFR Part 63, Subpart WWWW][40 CFR 63.5805]
- D.9.3 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]
- D.9.4 Particulate Matter (PM) [40 CFR 52 Subpart P]
- D.9.5 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]
- D.9.6 Particulate [326 IAC 6-3-2(d)]
- D.9.7 Volatile Organic Compounds - Best Available Control Technology (BACT) [326 IAC 8-1-6]
- D.9.8 Emissions Standards for Reinforced Plastics Composites Fabricating [326 IAC 20-25-3]
- D.9.9 Work Practice Standards for Reinforced Plastic Composites Fabrication [326 IAC 20-25-4]
- D.9.10 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-25-8]
- D.9.11 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.9.12 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAP)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.9.13 Operator Training Program

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.9.14 National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites
Production- Notifications [40 CFR Part 63, Subpart WWWW][40 CFR 63.5905]

D.9.15 Record Keeping Requirements

D.9.16 Reporting Requirements

D.9.17 Requirement to Submit a Significant Permit Modification Application [326 IAC 2-7-12][326 IAC
2-7-5]

SECTION D.10 FACILITY OPERATION CONDITIONS - Plant 38 80

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.10.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Compliance Determination Requirements

D.10.2 Volatile Organic Compounds [326 IAC 8-5-5]

D.10.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.10.4 Record Keeping Requirements

D.10.5 Reporting Requirements

SECTION D.11 FACILITY OPERATION CONDITIONS - Plant 39 82

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.11.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

D.11.2 Particulate Matter (PM) [40 CFR Part 52 Subpart P]

D.11.3 Particulate [326 IAC 6-3-2(d)]

D.11.4 Volatile Organic Compounds [326 IAC 8-1-6]

D.11.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

D.11.6 Operator Training Program

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.11.7 Record Keeping Requirements

D.11.8 Reporting Requirements

SECTION E 85

Emission Limitations and Standards [326 IAC 2-7-5(1)]

E.1 General Provisions Relating to NESHAP [326 IAC 20-1][40 CFR Part 63, Subpart A]
[Table 2 to 40 CFR Part 63, Subpart MMMM][Table 12 to 40 CFR Part 63, Subpart PPPP]

E.2 National Emission Standards for Hazardous Air Pollutants: Surface Coating of
Miscellaneous Metal Parts and Products [40 CFR Part 63, Subpart MMMM][40 CFR
63.3882][40 CFR 63.3883][40 CFR 63.3890]

E.3 National Emission Standards for Hazardous Air Pollutants: Surface Coating of Plastic Parts and Products: Limitations and Requirements [40 CFR Part 63, Subpart PPPP][40 CFR 63.4481][40 CFR 63.4482]]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- E.4 National Emission Standards for Hazardous Air Pollutants: Surface Coating of Miscellaneous Metal Parts and Products - Notifications [40 CFR 63.3910]
- E.5 National Emission Standards for Hazardous Air Pollutants: Surface Coating of Plastic Parts and Products - Notifications [40 CFR 63.4510]
- E.6 Requirement to Submit a Significant Permit Modification Application [326 IAC 2-7-12][326 IAC 2-7-5]
- E.7 Requirement to Submit a Significant Permit Modification Application [326 IAC 2-7-12][326 IAC 2-7-5]

Certification	89
Emergency Occurrence Report	90
Quarterly Reports	92-94
Quarterly Deviation and Compliance Monitoring Report	95

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in Conditions A.1, A.3, and A.4 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary source that is a multiple-plant complex that assembles and paints high-quality, luxury motor homes that vary in floor plan and length.

Responsible Official: Chief Administrative Officer/ Senior Vice President
Source Address: 606 Nelson's Parkway, Wakarusa, IN 46573
Mailing Address: 606 Nelson's Parkway, Wakarusa, IN 46573
Source Phone Number: (260) 862-7347
SIC Code: 3716
County Location: Elkhart
Source Location Status: Nonattainment for ozone under the 8-hour standard;
Attainment for all other criteria pollutants
Source Status: Part 70 Permit Program
Major Source, under PSD and Nonattainment NSR
Major Source, Section 112 of the Clean Air Act
Not 1 of 28 Source Categories

A.2 Part 70 Source Definition [326 IAC 2-7-1(22)]

Pursuant to CP 039-8662-00017, issued January 9, 1998, Monaco Coach Corporation's Nelson's Parkway Complex consists of the following plants:

- (a) Plant 1 (formerly Plant 30): Motorized recreational vehicle assembly
- (b) Plant 2: Final Paint
- (c) Plant 20: Welding and adhesive application
- (d) Plant 22: Metal shop
- (e) Plants 23 & 24: Normal maintenance operations
- (f) Plant 25: Warehouse and Tile Floor Set
- (g) Plant 26: White glove inspection (formerly called Undercoating)
- (h) Plant 27: Storage
- (i) Plant 28: Formtec/Thermoforming
- (j) Plant 29: Towable service center (formerly called Molds research & development)
- (k) Plant 31: Sewing, warehouse, white glove and cap assembly (formerly a paint area)

- (l) Plant 32: R&D shop and warehouse
- (m) Plant 33: Compressor building
- (n) Plant 34: Fire pump
- (o) Plant 36: Fiberglass fabrication
- (p) Plant 37: Fiberglass molding
- (q) Plant 38: R&D machine shop and print shop
- (r) Plant 39: Training Center and Overflow Service Center
- (s) Plant 46: Dispatch

Since these twenty (20) plants are located on contiguous or adjacent properties, belong to the same industrial grouping, and under common control of the same entity, they are considered one (1) source.

A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
[326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

- (a) Plant 1 (formerly Plant 30): A motorized recreational vehicle assembly plant, consisting of:
 - (1) One (1) dip tank coating operation, identified as SV1-5, constructed in 1991 and reconstructed in 1997, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, and exhausting to stack SV1-5;
 - (2) Two (2) surface coating booths for chassis painting, identified as SV1-3 and SV1-4, each constructed in 1991 and reconstructed in 1997, each with a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, and exhausting to stacks SV1-3 and SV1-4, respectively;
 - (3) One (1) woodworking millroom, identified as D1-01, constructed in 1997, a maximum capacity of 2000 pounds of wood per hour, with emissions controlled by a baghouse, and exhausting to stack DV1-01;
 - (4) One (1) sidewall adhesive application process, identified as SV1-6, constructed in 1997, a maximum capacity of 1.5 units per hour, with emissions uncontrolled, and exhausting to stack SV1-6;
 - (5) Three (3) manual assembly lines, using caulks, sealants, cleaners, and various hand tools, identified as D1-04, each line constructed in 1997, a total maximum capacity of 3.5 units per hour, with emissions uncontrolled, and exhausting to general ventilation vent GV1-01;
 - (6) Eighty-four (84) welding stations, constructed in 1998, with a maximum capacity of 3.0 pounds of wire per station per hour, with emissions uncontrolled, exhausting to general ventilation vent GV1-02;

- (b) Plant 2: A final paint plant, consisting of:
- (1) One (1) Partial Paint Line A, constructed in 1997 and reconstructed in 2003, consisting of one (1) primer/basecoat booth, one (1) clearcoat booth, and one (1) clearcoat/bake booth, identified as SV2-27, SV2-28, and SV2-29, respectively, an aggregate maximum capacity of 10 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-27, SV2-28, and SV2-29, respectively;
 - (2) One Full Paint Line B, constructed in 1997 and reconstructed in 2003, consisting of:
 - (A) One (1) slideout paint and clear booth, one (1) seal and base booth, and one (1) paint stripe booth, identified as SV2-20, SV2-21, and SV2-22, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-20, SV2-21, and SV-22, respectively;
 - (B) One (1) prep and repair booth, one (1) clear and bake booth, one (1) sand and repair station, and one (1) reclear and bake booth, identified as SV2-23, SV2-24, SV2-25, and SV2-26, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-23A, SV2-23B, SV2-24A, SV2-24B, SV2-25A, SV2-25B, SV2-26A, and SV2-26B, respectively;
 - (3) One Full Paint Line C, constructed in 1997 and reconstructed in 2003, consisting of:
 - (A) One (1) slideout paint and clear booth, one (1) seal and base booth, and one (1) paint stripe booth, identified as SV2-13, SV2-14, and SV2-15, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-13, SV2-14, and SV2-15 respectively;
 - (B) One (1) prep and repair booth, one (1) clear and bake booth, one (1) sand and repair station, and one (1) reclear and bake booth, identified as SV2-16, SV2-17, SV2-18, and SV2-19, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-16A, SV2-16B, SV2-17A, SV2-17B, SV2-18A, SV2-18B, SV2-19A, and SV2-19B, respectively;
 - (4) One Full Paint Line D, constructed in 2003, consisting of:
 - (A) One (1) primer/basecoat booth and one (1) repair and stripe booth, identified as SV2-7 and SV2-8 respectively, a maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-7 and SV2-8, respectively;
 - (B) One (1) slideout booth, one (1) repair and clear booth, one (1) sand and repair station, and one (1) reclear booth, identified as SV2-9, SV2-10, SV2-11, and SV2-12, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-9A, SV2-9B, SV2-10A, SV2-10B, SV2-11A, SV2-11B, SV2-12A, and SV2-12B, respectively;

- (5) One Full Paint Line E, constructed in 2003, consisting of:
 - (A) One (1) primer/basecoat booth and one (1) repair and stripe booth, identified as SV2-1 and SV2-2 respectively, a maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-1 and SV2-2, respectively;
 - (B) One (1) slideout booth, one (1) repair and clear booth, one (1) sand and repair station, and one (1) reclear booth, identified as SV2-3, SV2-4, SV2-5, and SV2-6, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-3A, SV2-3B, SV2-4A, SV2-4B, SV2-5A, SV2-5B, SV2-6A, and SV2-6B, respectively;
- (6) One (1) repair area, consisting of:
 - (A) One (1) paint repair booth, identified as SV2-30, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-30;
 - (B) One (1) paint repair booth, identified as SV2-31, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-31;
 - (C) One (1) paint repair booth, identified as SV2-32, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-32;
 - (D) One (1) paint repair booth, identified as SV2-33, constructed in 2003, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-33; and
 - (E) One (1) paint repair booth, identified as SV2-34, constructed in 2003, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-34.
- (7) One (1) undercoating operation, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stacks SV2-UC1 and SV2-UC2; and
- (c) Plant 20: A welding and adhesive application plant, consisting of:
 - (1) One (1) adhesive application process, identified as EU-20A, constructed in the 1960s, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, exhausting to general ventilation stacks GV20-6 through GV20-10; and
 - (2) One (1) sidewall welding operation, identified as EU-20B, constructed prior to 1981, consisting of twenty-four (24) welding stations, with a maximum capacity of 3.0 pounds of wire per station per hour, with emissions uncontrolled, and exhausting to general ventilation stacks GV20-2 through GV20-5.

- (d) Plant 22: A metal shop, consisting of:
One (1) dash component production area which includes one (1) surface coating spray room, identified as GV22-3/GV22-4, constructed in the 1970s, a maximum capacity of 3.5 units per hour, using air-atomized spray application, with emissions controlled by dry filters, exhausting to stacks GV22-3 and GV22-4.
- (e) Plant 28: A Formtec (Thermoforming) plant, consisting of:
- (1) One (1) plastic dash component vinyl wrapping operation, identified as EU-28, constructed prior to 1985, a maximum capacity of 7000 units per year, with emissions uncontrolled, and exhausting to stack GV28-4; and
 - (2) One (1) tank cover chemical welding operation, identified as SV28-01, constructed prior to 1985, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, exhausting to stack SV28-01.
- (f) Plant 36: A fiberglass fabrication plant, consisting of:
- (1) Two (2) gelcoat booths, identified as GC36-1 and GC36-2, each constructed in 1986, each with a maximum capacity of 3.5 units per hour, gel applied using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV36-7;
 - (2) One (1) barrier coat spray station, identified as BC36-1, constructed in 2001, a maximum capacity of 4.0 units per hour, unfilled production resins applied using non-atomized spray application, with emissions controlled by dry filters and exhausting to stack SV36-14;
 - (3) Three (3) fiberglass chop booths, identified as SV36-1&2, SV36-3&4, and SV36-5&6, each constructed prior to 1985, each with a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, exhausting to stacks SV36-1, through SV36-6;
 - (4) Five (5) grinding stations, identified as GB36-1, GB36-2, GB36-3, GB36-4, and GB36-5, each constructed in 1994, each with a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, and each with a 100% recirculated air exhaust air stream;
 - (5) One (1) gelcoat booth, identified as GC36-3, constructed in 1994, a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, exhausting to stack SV36-12 and SV36-13;
 - (6) Two (2) fiberglass chop booths, identified as CS36-4 and CS36-5, constructed in 1994, each with a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, exhausting to stacks SV36-8 and SV36-9;
- (g) Plant 37: A fiberglass molding plant, consisting of:
- (1) One (1) fiberglass fabricating area, identified as CS37-1, constructed prior to 1985, a maximum capacity of 1.0 unit per hour, using air-atomized spray equipment, with emissions controlled by dry filters, and exhausting through general ventilation to stacks GV37-1 and GV37-2;

- (2) One (1) gel coat booth, identified as GC37-1, constructed prior to 1985, a maximum capacity of 1.0 unit per hour, with emissions controlled by dry filters, and exhausting through general ventilation to stacks GV37-1 and GV37-2;
- (h) Plant 39: Training Center and Overflow Service Center:
One (1) R&D paint booth, identified as PB39-1, constructed in 1989, used for training and repair, with emissions controlled by dry filters, and exhausting to stack SV39-1.

A.4 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Plant 1: (formerly Plant 30) Motorized recreational vehicle assembly plant, consisting of:
 - (1) Water-based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs. [326 IAC 2-2] [40 CFR 52.21]
 - (2) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations:

One (1) metal working area, identified as D1-02, constructed in 1997, a maximum capacity of 250 pounds per hour, with emissions controlled by a baghouse, exhausting through general ventilation to stacks GV1-1 and GV1-2; [326 IAC 6-3-2]
- (b) Plant 2: Final Paint
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
 - (1) Two (2) paint prep areas, utilizing solvents, cleaners, composites, and hand-sanding equipment, constructed in 1997 and reconstructed in 2003, a total maximum capacity of 4.5 units per hour, with emissions controlled by filtered exhaust identified as D2-1, exhausting through general ventilation stacks GV2-3 through GV2-7; [326 IAC 2-2] [40 CFR 52.21] [326 IAC 2-4.1]
 - (2) A paint storage and mixing area, exhausting to vents SV2-15 and SV2-16. [326 IAC 2-2] [40 CFR 52.21] [326 IAC 2-4.1] [40 CFR Part 63, Subpart M] [40 CFR Part 63, Subpart P]
 - (3) One (1) final inspection area utilizing hand-applied solvents, cleaners, sealants, adhesives, and paint, constructed in 1998, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, exhausting through general ventilation to stacks GV2-1 and GV2-2. [326 IAC 2-2] [40 CFR 52.21] [326 IAC 2-4.1] [40 CFR Part 63, Subpart M] [40 CFR Part 63, Subpart P]

- (c) Plant 22: A metal shop
Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and/or electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations:
- One (1) baggage door assembly area and metal cutting operation, identified as EU-22, constructed prior to 1989, a maximum capacity of 0.42 tons per hour, with emissions controlled by a cyclone, exhausting through general ventilation to stacks GV22-1 and GV22-2; [326 IAC 6-3-2]
- (d) Plant 26: A White glove inspection area
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
- Four (4) inspection bays, used to perform final vehicle inspection, constructed prior to 1981, a maximum capacity of 3.5 units per hour, using manually-applied cleaners and touch-up paint, with emissions exhausting through general ventilation to stacks GV26-1 through GV26-4; [40 CFR 52.21][326 IAC 2-2][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P]
- (e) Plant 28: Formtec/Thermoforming
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
- Four (4) plastic sheet component assembly (thermal forming) operations, identified as GV28-1, GV28-2, GV28-3, and GV28-8, constructed in 1979, 1980, 1983, and 1983, respectively, each with a maximum capacity of 7000 units per year, with emissions uncontrolled, and exhausting to stacks GV28-1, GV28-2, GV28-3, and GV28-8, respectively. Note that GV28-2 was converted to a rotary station unit in 2003; [40 CFR 52.21] [326 IAC 2-2]
- (f) Plant 29: Towable service center and bay count
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
- Thirteen (13) service bays used to perform manual vehicle inspection and repairs on customer owned units, constructed prior to 1989 and expanded in 2000, using some general cleaners and touch-up paint, with emissions exhausting through general ventilation to stacks GV29-1 through GV29-4. [40 CFR 52.21] [326 IAC 2-2][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P]
- (g) Plant 31: Sewing, warehouse, white glove and cap assembly
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
- (1) Fiberglass cap windshield set operations and repairs using adhesives and paints; [40 CFR 52.21][326 IAC 2-2] [40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P]

- (2) Sewing operations using some adhesives and cleaners; [40 CFR 52.21][326 IAC 2-2] [40 CFR Part 63, Subpart M MMM] [40 CFR Part 63, Subpart P PPP]
- (3) White glove inspections using some cleaners, caulks and touch-up paint; [40 CFR 52.21][326 IAC 2-2][40 CFR Part 63, Subpart M MMM][40 CFR Part 63, Subpart P PPP] and
- (4) One (1) natural gas-fired boiler with a heat input capacity of 12.0 MMBtu/hr. [326 IAC 6-2-3]

- (h) Plant 32: R&D (Research & Development) shop and warehouse
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
 - (1) one (1) R&D CNC router [326 IAC 6-3-2]
 - (2) one (1) R&D fiberglass spray booth, identified as SV32-1, with emissions controlled by dry filters [40 CFR 52.21][326 IAC 2-2][40 CFR 52 Subpart P] [326 IAC 6-3-2(d)] [326 IAC 20-25]

- (i) Plant 38: R&D machine shop and print shop
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

Three (3) printing presses (moved from Plant 45) which use low-VOC soy-based inks. [40 CFR 52.21] [326 IAC 2-2]

- (j) Plant 25: Warehouse and Tile Floor Set:
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

One (1) tile cutting operation; [326 IAC 6-3-2]

A.5 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.3 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.4 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

(a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.

(b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

(a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

(b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.

(c) A responsible official is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than April 15th of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
- (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]**

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information:

- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
- (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

The PMP extension notification does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall implement the PMPs, including any required record keeping, as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ,. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for the unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;

- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and the Northern Regional Office within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or
Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967
and
Telephone Number: 219-245-4870 (Northern Regional Office)
Facsimile Number: 219-245-4877

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
(B) Any steps taken to mitigate the emissions; and
(C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.

- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.

- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deletedby this permit.
- (b) All previous registrations and permits are superseded by this permit.

B.14 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)]

The notification by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.16 Permit Renewal [326 IAC 2-7-4]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

- (2) If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-7-3]
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.
- (d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]
If IDEM, OAQ, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.17 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]
- (d) No permit amendment or modification is required for the addition, operation or removal of a nonroad engine, as defined in 40 CFR 89.2.

B.18 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.19 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

(a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

(b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) Emission Trades [326 IAC 2-7-20(c)]

The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).

(d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]

The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

B.20 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

B.21 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC13-17-3-2] [IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.

- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)] [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

B.24 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314]

Notwithstanding the conditions of this permit that state specific methods that may be used to demonstrate compliance with, or a violation of, applicable requirements, any person (including the Permittee) may also use other credible evidence to demonstrate compliance with, or a violation of, any term or condition of this permit.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P] [326 IAC 6-3-2(c)]

- (a) Pursuant to [40 CFR 52 Subpart P], particulate matter emissions from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
- (b) Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour. This condition is not federally enforceable.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.7 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

The Permittee shall comply with the applicable requirements of 326 IAC 14-10, 326 IAC 18, and 40 CFR 61.140.

Testing Requirements [326 IAC 2-7-6(1)]

C.9 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.10 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.13 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ($\pm 2\%$) of full scale reading.
- (b) The Preventive Maintenance Plan for the pH meter shall include calibration using known standards. The frequency of calibration shall be adjusted such that the typical error found at calibration is less than one pH point.
- (c) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on April 29, 1999.
- (b) Upon direct notification by IDEM, OAQ., that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance as defined in 40 CFR 68 is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.16 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
- (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, and it will be ten (10) days or more until the unit or device will be shut down, then the Permittee shall promptly notify the IDEM, OAQ. The notification shall also include the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the response actions taken up to the time of notification.
 - (4) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
- (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.

- (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
- (3) An automatic measurement was taken when the process was not operating.
- (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when, in accordance with Section D, response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

**C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]**

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

- (a) The Permittee shall submit an emission statement certified pursuant to the requirements of 326 IAC 2-6. This statement must be received in accordance with the compliance schedule specified in 326 IAC 2-6-3 and must comply with the minimum requirements specified in 326 IAC 2-6. The emission statement shall meet the following requirements:

- (1) Indicate estimated actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
- (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1(32) ("Regulated pollutant which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

The emission statement does require the certification by the responsible official as defined by 326 IAC 2-1.1-1(1).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

- (a) Records of all required monitoring data, reports and support information required by this Permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

Stratospheric Ozone Protection

C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

Part 2 MACT Application Submittal Requirement

C.22 Application Requirements for Section 112(j) of the Clean Air Act [40 CFR 63.52(e)] [40 CFR 63.56(a)] [40 CFR 63.9(b)] [326 IAC 2-7-12]

- (a) The Permittee shall submit a Part 2 Maximum Achievable Control Technology (MACT) Application in accordance with 40 CFR 63.52(e)(1). The Part 2 MACT Application shall meet the requirements of 40 CFR 63.53(b).
- (b) Notwithstanding paragraph (a), the Permittee is not required to submit a Part 2 MACT Application if the Permittee no longer meets the applicability criteria of 40 CFR 63.50 by the application deadline in 40 CFR 63.52(e)(1). For example, the Permittee would not have to submit a Part 2 MACT Application if, by the application deadline:
 - (1) The source is no longer a major source of hazardous air pollutants, as defined in 40 CFR 63.2;
 - (2) The source no longer includes one or more units in an affected source category for which the U.S. EPA failed to promulgate an emission standard by May 15, 2002; or
 - (3) The MACT standard or standards for the affected source categories included at the source are promulgated.

- (c) Notwithstanding paragraph (a), pursuant to 40 CFR 63.56(a), the Permittee shall comply with an applicable promulgated MACT standard in accordance with the schedule provided in the MACT standard if the MACT standard is promulgated prior to the Part 2 MACT Application deadline or prior to the issuance of permit with a case-by-case Section 112(j) MACT determination. The MACT requirements include the applicable General Provisions requirements of 40 CFR 63, Subpart A. Pursuant to 40 CFR 63.9(b), the Permittee shall submit an initial notification not later than 120 days after the effective date of the MACT, unless the MACT specifies otherwise. The initial notification shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Director, Air and Radiation Division
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 1

- (a) Plant 1 (formerly Plant 30): A motorized recreational vehicle assembly plant, consisting of:
- (1) One (1) dip tank coating operation, identified as SV1-5, constructed in 1991 and reconstructed in 1997, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, and exhausting to stack SV1-5;
 - (2) Two (2) surface coating booths for chassis painting, identified as SV1-3 and SV1-4, each constructed in 1991 and reconstructed in 1997, each with a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, and exhausting to stacks SV1-3 and SV1-4, respectively;
 - (3) One (1) woodworking millroom, identified as D1-01, constructed in 1997, a maximum capacity of 2000 pounds of wood per hour, with emissions controlled by a baghouse, and exhausting to stack DV1-01;
 - (4) One (1) sidewall adhesive application process, identified as SV1-6, constructed in 1997, a maximum capacity of 1.5 units per hour, with emissions uncontrolled, and exhausting to stack SV1-6;
 - (5) Three (3) manual assembly lines, using caulks, sealants, cleaners, and various hand tools, identified as D1-04, each line constructed in 1997, a total maximum capacity of 3.5 units per hour, with emissions uncontrolled, and exhausting to general ventilation vent GV1-01;
 - (6) Eighty-four (84) welding stations, constructed in 1998, with a maximum capacity of 3.0 pounds of wire per station per hour, with emissions uncontrolled, exhausting to general ventilation vent GV1-02;

(specifically regulated insignificant activities:)

- (a) Plant 1: (formerly Plant 30) Motorized recreational vehicle assembly
- (1) Water-based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs. [326 IAC 2-2] [40 CFR 52.21][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P]
 - (2) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations:

One (1) metal working area, identified as D1-02, constructed in 1997, a maximum capacity of 250 pounds per hour, with emissions controlled by a baghouse, exhausting through general ventilation to stacks GV1-1 and GV1-2; [326 IAC 6-3-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.3.1, D.4.1, D.5.1, D.6.1, D.7.1, D.8.1, D.9.3, D.10.1, and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.1.2 Particulate Matter (PM) [40 CFR 52 Subpart P]

Pursuant to CP 039-7335-00017, issued on July 24, 1997, and 40 CFR Part 52 Subpart P, the particulate matter (PM) from surface coating booths SV1-3 and SV1-4 shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

D.1.3 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, and 326 IAC 6-3-2, the allowable particulate emission rate from:

- (a) Woodworking millroom D1-01 shall not exceed 4.10 pounds per hour based on a maximum process weight rate of 1.0 ton per hour.
- (b) Each of the Plant 1 manual assembly lines shall not exceed 2.03 pounds per hour based on a maximum process weight rate of 0.35 tons per hour each.
- (c) The welding operations shall not exceed, in aggregate, the allowable particulate emission rate of 1.02 pounds per hour based on a maximum process weight rate of 252 pounds per hour.
- (d) The insignificant metal working operation (D1-02) shall not exceed 1.02 pounds per hour based on a maximum process weight rate of 250 pounds per hour.

These pound per hour limitations were calculated with the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour of (a) through (d) above shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.1.4 Volatile Organic Compounds (VOC) Limitations [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coating applied to the metal components by surface coating booths SV1-3 and SV1-4, dip tank coating operation SV1-5, and sidewall adhesive application process SV1-6, shall not exceed 3.5 pounds of VOCs per gallon of coating as delivered to the applicator, excluding water, for forced warm air dried coatings.

D.1.5 Volatile Organic Compound (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9(f)]

Pursuant to 326 IAC 8-2-9(f), all solvents sprayed from the application equipment of booths SV1-3 and SV1-4 during cleanup or color changes shall be directed into containers. Said containers shall be closed as soon as the solvent spraying is complete. In addition, all waste solvent shall be disposed of in such a manner that minimizes evaporation.

D.1.6 Particulate [326 IAC 6-3-2(d)]

Pursuant to CP 039-7335-00017, issued on July 24, 1997 and 326 IAC 6-3-2(d), particulate from surface coating booths SV1-3 and SV1-4 shall be controlled by a dry particulate filter, and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.1.7 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.1.8 Particulate Control

In order to comply with Condition D.1.3, the baghouses shall be in operation and control particulate emissions from facilities D1-01 and D1-02 at all times the respective facilities are in operation.

D.1.9 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC content and usage limitations contained in Conditions D.1.1 and D.1.4 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.10 Operator Training Program

The Permittee shall implement an operator training program.

- (a) All operators that perform surface coating operations using spray equipment or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained upon permit issuance if training was not completed in the last twelve months. All new operators shall be trained within thirty (30) days of hiring or transfer.

- (b) Training shall include proper filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators and training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

D.1.11 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling particulate emissions from D1-01 when exhausting to the atmosphere. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.

D.1.12 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit. If operations continue after bag failure is observed and it will be 10 days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.
- (b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.13 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.3, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC content and usage limits established in Conditions D.1.1 and

D.1.3. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.

- (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis.
 - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (3) The total VOC usage for each month.
- (b) To document compliance with Condition D.1.10, the Permittee shall maintain copies of the training program, and the list of trained operators. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.
 - (c) To document compliance with Condition D.1.11, the Permittee shall maintain records of the inspections.
 - (d) To document compliance with Condition D.1.7, the Permittee shall maintain of records of any additional inspections prescribed by the Preventive Maintenance Plan.
 - (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.14 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 2

(b) Plant 2: A final paint plant, consisting of:

- (1) One (1) Partial Paint Line A, constructed in 1997 and reconstructed in 2003, consisting of one (1) primer/basecoat booth, one (1) clearcoat booth, and one (1) clearcoat/bake booth, identified as SV2-27, SV2-28, and SV2-29, respectively, an aggregate maximum capacity of 10 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-27, SV2-28, and SV2-29, respectively;
- (2) One Full Paint Line B, constructed in 1997 and reconstructed in 2003, consisting of:
 - (A) One (1) slideout paint and clear booth, one (1) seal and base booth, and one (1) paint stripe booth, identified as SV2-20, SV2-21, and SV2-22, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-20, SV2-21, and SV-22, respectively;
 - (B) One (1) prep and repair booth, one (1) clear and bake booth, one (1) sand and repair station, and one (1) reclear and bake booth, identified as SV2-23, SV2-24, SV2-25, and SV2-26, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-23A, SV2-23B, SV2-24A, SV2-24B, SV2-25A, SV2-25B, SV2-26A, and SV2-26B, respectively;
- (3) One Full Paint Line C, constructed in 1997 and reconstructed in 2003, consisting of:
 - (A) One (1) slideout paint and clear booth, one (1) seal and base booth, and one (1) paint stripe booth, identified as SV2-13, SV2-14, and SV2-15, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-13, SV2-14, and SV2-15 respectively;
 - (B) One (1) prep and repair booth, one (1) clear and bake booth, one (1) sand and repair station, and one (1) reclear and bake booth, identified as SV2-16, SV2-17, SV2-18, and SV2-19, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-16A, SV2-16B, SV2-17A, SV2-17B, SV2-18A, SV2-18B, SV2-19A, and SV2-19B, respectively;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Facility Description [326 IAC 2-7-5(15)]: Plant 2 (continued)

- (4) One Full Paint Line D, constructed in 2003, consisting of:
- (A) One (1) primer/basecoat booth and one (1) repair and stripe booth, identified as SV2-7 and SV2-8 respectively, a maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-7 and SV2-8, respectively;
 - (B) One (1) slideout booth, one (1) repair and clear booth, one (1) sand and repair station, and one (1) reclear booth, identified as SV2-9, SV2-10, SV2-11, and SV2-12, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-9A, SV2-9B, SV2-10A, SV2-10B, SV2-11A, SV2-11B, SV2-12A, and SV2-12B, respectively;
- (5) One Full Paint Line E, constructed in 2003, consisting of:
- (A) One (1) primer/basecoat booth and one (1) repair and stripe booth, identified as SV2-1 and SV2-2 respectively, a maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-1 and SV2-2, respectively;
 - (B) One (1) slideout booth, one (1) repair and clear booth, one (1) sand and repair station, and one (1) reclear booth, identified as SV2-3, SV2-4, SV2-5, and SV2-6, respectively, an aggregate maximum capacity of 5 units (motor homes) per day, using HVLP spray equipment or its equivalent, with emissions controlled by dry filters, exhausting to stacks SV2-3A, SV2-3B, SV2-4A, SV2-4B, SV2-5A, SV2-5B, SV2-6A, and SV2-6B, respectively;
- (6) One (1) repair area, consisting of:
- (A) One (1) paint repair booth, identified as SV2-30, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-30;
 - (B) One (1) paint repair booth, identified as SV2-31, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-31;
 - (C) One (1) paint repair booth, identified as SV2-32, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-32;
 - (D) One (1) paint repair booth, identified as SV2-33, constructed in 2003, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-33; and

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Facility Description [326 IAC 2-7-5(15)]: Plant 2 (continued)

(E) One (1) paint repair booth, identified as SV2-34, constructed in 2003, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV2-34.

(7) One (1) undercoating operation, constructed in 1998, a maximum capacity of 3.5 units per hour, using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stacks SV2-UC1 and SV2-UC2; and

(specifically regulated insignificant activities:)

(b) Plant 2: Final Paint

Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

(1) Two (2) paint prep areas, utilizing solvents, cleaners, composites, and hand-sanding equipment, constructed in 1997 and reconstructed in 2003, a total maximum capacity of 4.5 units per hour, with emissions controlled by filtered exhaust identified as D2-1, exhausting through general ventilation stacks GV2-3 through GV2-7; [326 IAC 2-2] [40 CFR 52.21][326 IAC 2-4.1]

(2) A paint storage and mixing area, exhausting to vents SV2-15 and SV2-16. [326 IAC 2-2] [40 CFR 52.21][326 IAC 2-4.1][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P][40 CFR Part 63, Subpart P][40 CFR Part 63, Subpart P]

(3) One (1) final inspection area utilizing hand-applied solvents, cleaners, sealants, adhesives, and paint, constructed in 1998, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, exhausting through general ventilation to stacks GV2-1 and GV2-2. [326 IAC 2-2][40 CFR 52.21][326 IAC 2-4.1][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P][40 CFR Part 63, Subpart P][40 CFR Part 63, Subpart P]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Best Available Control Technology (BACT) and Maximum Control Technology (MACT) [326 IAC 2-2] [40 CFR 52.21][326 IAC 2-4.1]

Pursuant to PSD SSM 039-15620-00017, issued December 11, 2002, 326 IAC 2-4.1, 40 CFR 52.21 and 326 IAC 2-2:

(a) All facilities located at Plant 2 (Partial Paint Line A, Full Paint Lines B through E, prep area, repair area, undercoating operation, and final inspection area) must comply with the following requirements:

(1) Lacquer thinners and preparation cleaners and solvents used on motor home exteriors will be hand-wiped and contain a maximum 6.5 pounds VOC per gallon of coating as applied.

- (2) Except as provided in (6) and (8) below, primers will be applied using high volume-low pressure (HVLP) spray equipment, or the equivalent, and contain a maximum of 3.5 pounds VOC per gallon of coating as applied.
 - (3) Except as provided in (6) and (8) below, base coats will be applied using HVLP spray equipment, or the equivalent, and contain a maximum VOC content of 6.5 pounds VOC per gallon of coating as applied.
 - (4) Except as provided in (6) and (8) below, clear coats will be applied using HVLP spray equipment, or the equivalent, and contain a maximum VOC content of 3.5 pounds VOC per gallon of coating as applied.
 - (5) Except as provided in (6) and (8) below, sealers will be applied using HVLP spray equipment, or the equivalent, and contain a maximum VOC content of 3.5 pounds VOC per gallon of coating as applied.
 - (6) As an alternative to complying with the individual VOC content limitations for base coats and clear coats, compliance may be determined by averaging the emissions from base coat and clear coat operations across affected lines. The average VOC content for the base coat/clear coat system shall be limited to less than or equal to 4.5 pounds VOC per gallon of coating as applied. This limitation is based on a ratio of two parts clear coat to one part base coat. Compliance will be demonstrated monthly based on the actual VOC content as applied of each coating and actual usage of base coats and clear coats during the month.
 - (7) Good housekeeping practices will be employed to minimize leaks, spills, and evaporative losses. These include: sealing lids on all containers not in use or in storage, the purging of guns and lines into approved containers, maintaining an organized spill response and clean-up operation, performing routine maintenance on spray equipment and pumps to prevent drips and seal leaks, the use of solvent recovery systems to recover reusable solvents for on-site or off-site recycling, and using aqueous, exempt solvents or citric cleaners where effective and practical.
 - (8) All coating materials, including primers, base coats, and clear coats, used in the repair booths will be applied with air-atomized spray equipment, or the equivalent.
 - (9) When necessary, motor home exteriors will be hand-wiped with cleaning solvent prior to painting.
 - (10) Collected solvents will be recycled on-site and/or off-site to recover reusable solvents and minimize waste.
 - (11) Motor homes will be undercoated with a waterborne-low VOC coating.
- (b) The surface coating operations in Partial Paint Line A and Full Paint Lines B through E shall use, in aggregate, less than 539 tons of VOC, including coatings, dilution solvents, and cleaning solvents, per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with these requirements and the VOC emissions from insignificant natural gas combustion is equivalent to VOC emissions (from Partial Paint Line A and Full Paint Lines B through E) of less than or equal to 540.4 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with these requirements will satisfy the requirements of 326 IAC 2-4.1 (MACT), 40 CFR 52.21, and 326 IAC 2-2 (Prevention of Significant Deterioration).

D.2.2 Particulate Matter (PM) [40 CFR Part 52 Subpart P]

Pursuant to 40 CFR Part 52 Subpart P, the particulate matter (PM) from the surface coating operations shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

D.2.3 Volatile Organic Compounds [326 IAC 8-2-9]

Any change or modification which may increase the maximum capacity of any paint line (partial paint line A and full paint lines B through E) to greater than 35 vehicles (motor homes) per day must be approved by the OAQ before any such change may occur.

D.2.4 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate from the surface coating operations shall be controlled by a dry particulate filter and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.2.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements

D.2.6 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC content and usage limitations contained in Condition D.2.3 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.7 Operator Training Program

The Permittee shall implement an operator training program.

- (a) All operators that perform surface coating operations using spray equipment or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained upon permit issuance if training was not completed in the last twelve months. All new operators shall be trained within thirty (30) days of hiring or transfer.

- (b) Training shall include proper filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators and training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.8 Record Keeping Requirements

- (a) To document compliance with Condition D.2.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC content and usage limits established in Condition D.2.1. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
 - (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis.
 - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (3) The total VOC usage for each month.
- (b) To document compliance with Condition D.2.3, the Permittee shall maintain daily records of the number of vehicles painted on each paint line in that day.
- (c) To document compliance with Condition D.2.7, the Permittee shall maintain copies of the training program, and the list of trained operators. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (d) To document compliance with Condition D.2.5, the Permittee shall maintain of records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2.9 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.2.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 20

- (c) Plant 20: Welding and adhesive application plant, consisting of:
- (1) One (1) adhesive application process, identified as EU-20A, constructed in the 1960s, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, exhausting to general ventilation stacks GV20-6 through GV20-10; and
 - (2) One (1) sidewall welding operation, identified as EU-20B, constructed prior to 1981, consisting of twenty-four (24) welding stations, with a maximum capacity of 3.0 pounds of wire per station per hour, with emissions uncontrolled, and exhausting to general ventilation stacks GV20-2 through GV20-5.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.4.1, D.5.1, D.6.1, D.7.1, D.8.1, D.9.3, D.10.1 and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.3.2 Particulate Matter (PM) [40 CFR 52 Subpart P]

Pursuant to CP 039-7335-00017, issued July 24, 1997 and 40 CFR 52 Subpart P, the particulate matter (PM) from the sidewall welding operation (EU-20B) shall not exceed 0.12 pounds per hour when operating at a maximum process weight rate of 3.0 pounds per hour.

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

Compliance Determination Requirements

D.3.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC usage limitation contained in Condition D.3.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets.

IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.3.4 Record Keeping Requirements

- (a) To document compliance with Condition D.3.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.3.1. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
- (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month.

D.3.5 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.3.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.4 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 22

- (d) Plant 22: A metal shop, consisting of:
One (1) dash component production area which includes one (1) surface coating spray room, identified as GV22-3/GV22-4, constructed in the 1970s, a maximum capacity of 3.5 units per hour, using air-atomized spray application, with emissions controlled by dry filters, exhausting to stacks GV22-3 and GV22-4.

(specifically regulated insignificant activities)

- (c) Plant 22: A metal shop
Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and/or electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations:

One (1) baggage door assembly area and metal cutting operation, identified as EU-22, constructed prior to 1989, a maximum capacity of 0.42 tons per hour, with emissions controlled by a cyclone, exhausting through general ventilation to stacks GV22-1 and GV22-2; [326 IAC 6-3-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.5.1, D.6.1, D.7.1, D.8.1, D.9.3, D.10.1, and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.4.2 Particulate Matter (PM) [40 CFR Part 52 Subpart P]

Pursuant to 40 CFR Part 52 Subpart P, the particulate matter (PM) from the dash production area (GV22-3/GV22-4) shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where

E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

D.4.3 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2, the allowable particulate emission rate from the insignificant baggage door assembly area and metal cutting operation (EU-22) shall not exceed 2.29 pounds per hour based on a maximum process weight rate of 0.42 tons per hour.

The pound per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

D.4.4 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate from the dash production area (GV22-3/GV22-4) shall be controlled by a dry particulate filter and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.4.5 Volatile Organic Compounds (VOC) Limitations [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coating applied to the metal components by the dash component production area (GV22-3/GV22-4) shall not exceed 3.5 pounds of VOCs per gallon of coating as delivered to the applicator, excluding water, for forced warm air dried coatings.

D.4.6 Volatile Organic Compound (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9(f), all solvents sprayed from the application equipment in the dash component production area (GV22-3/GV22-4) during cleanup or color changes shall be directed into containers. Said containers shall be closed as soon as the solvent spraying is complete. In addition, all waste solvent shall be disposed of in such a manner that minimizes evaporation.

D.4.7 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for GV22-3/GV22-4 and the dry filters.

Compliance Determination Requirements

D.4.8 Particulate Control

In order to comply with Condition D.4.3, the cyclone shall be in operation and control particulate emissions from facility EU-22 at all times the facility is in operation.

D.4.9 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC content and usage limitations contained in Conditions D.4.1 and D.4.5 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.4.10 Operator Training Program

The Permittee shall implement an operator training program.

- (a) All operators that perform surface coating operations using spray equipment or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained upon permit issuance if training was not completed in the last twelve months. All new operators shall be trained within thirty (30) days of hiring or transfer.
- (b) Training shall include proper filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators and training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

D.4.11 Cyclone Failure Detection

In the event that cyclone failure has been observed:

Failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions). Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.4.12 Record Keeping Requirements

- (a) To document compliance with Conditions D.4.1 and D.4.5, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC content and usage limits established in Conditions D.4.1 and D.4.5. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
 - (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis.
 - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (3) The total VOC usage for each month.

- (b) To document compliance with Condition D.4.10, the Permittee shall maintain copies of the training program, and the list of trained operators. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) To document compliance with Condition D.4.7, the Permittee shall maintain of records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.4.13 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.4.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.5

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plants 25 and 26

(specifically regulated insignificant activities)

- (c) Plant 26: A White glove inspection area
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

Four (4) inspection bays, used to perform final vehicle inspection, constructed prior to 1981, a maximum capacity of 3.5 units per hour, using manually-applied cleaners and touch-up paint, with emissions exhausting through general ventilation to stacks GV26-1 through GV26-4; [40 CFR 52.21][326 IAC 2-2][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P]

- (j) Plant 25: Warehouse and Tile Floor Set:
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

One (1) tile cutting operation; [326 IAC 6-3-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.5.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.4.1, D.6.1, D.7.1, D.8.1, D.9.3, D.10.1 and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.5.2 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2, the particulate emissions from the tile cutting operation shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where

E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

Compliance Determination Requirements

D.5.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC usage limitation contained in Condition D.5.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.5.4 Record Keeping Requirements

- (a) To document compliance with Condition D.5.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.5.1. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
- (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.5.5 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.5.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.6

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 28

(e) Plant 28: A Formtec (Thermoforming) plant, consisting of:

- (1) One (1) plastic dash component vinyl wrapping operation, identified as EU-28, constructed prior to 1985, a maximum capacity of 7000 units per year, with emissions uncontrolled, and exhausting to stack GV28-4; and
- (2) One (1) tank cover chemical welding operation, identified as SV28-01, constructed prior to 1985, a maximum capacity of 3.5 units per hour, with emissions uncontrolled, exhausting to stack SV28-01.

(specifically regulated insignificant activities)

(e) Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

Four (4) plastic sheet component assembly (thermal forming) operations, identified as GV28-1, GV28-2, GV28-3, and GV28-8, constructed in 1979, 1980, 1983, and 1983, respectively, each with a maximum capacity of 7000 units per year, with emissions uncontrolled, and exhausting to stacks GV28-1, GV28-2, GV28-3, and GV28-8, respectively. Note that GV28-2 was converted to a rotary station unit in 2003; [40 CFR 52.21] [326 IAC 2-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.6.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.4.1, D.5.1, D.7.1, D.8.1, D.9.3, D.10.1 and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.6.2 Volatile Organic Compounds [326 IAC 8-1-6]

- (a) Any change or modification which may increase the VOC potential to emit of the plastic dash component vinyl wrapping operation (EU-28) to 25 tons per year or more, shall require prior approval by the IDEM, OAQ before such changes may take place.
- (b) Any change or modification which may increase the VOC potential to emit of the tank cover chemical welding operation (SV28-01) to 25 tons per year or more, shall require prior approval by the IDEM, OAQ before such changes may take place.

Compliance Determination Requirements

D.6.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC usage limitation contained in Condition D.6.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.6.4 Record Keeping Requirements

(a) To document compliance with Conditions D.6.1 and D.6.2, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limits established in Conditions D.6.1 and D.6.2. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.

- (1) The VOC content of each coating material and solvent used less water.
- (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
- (3) The total VOC usage for each month.

D.6.5 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.6.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.7

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 29

(specifically regulated insignificant activities)

- (e) Plant 29: Towable service center and bay count
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

Thirteen (13) service bays used to perform manual vehicle inspection and repairs on customer owned units, constructed prior to 1989 and expanded in 2000, using some general cleaners and touch-up paint, with emissions exhausting through general ventilation to stacks GV29-1 through GV29-4. [40 CFR 52.21] [326 IAC 2-2][40 CFR Part 63, Subpart M] [40 CFR Part 63, Subpart P]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.7.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.4.1, D.5.1, D.6.1, D.8.1, D.9.3, D.10.1 and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

Compliance Determination Requirements

D.7.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC usage limitation contained in Condition D.7.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.7.3 Record Keeping Requirements

- (a) To document compliance with Condition D.7.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.7.1. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.

- (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.7.4 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.7.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.8

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 31 and Plant 32

(specifically regulated insignificant activities)

- (f) Plant 31: Sewing, warehouse, white glove and cap assembly
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
- (1) Fiberglass cap windshield set operations and repairs using adhesives and paints; [40 CFR 52.21][326 IAC 2-2][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P]
 - (2) Sewing operations using some adhesives and cleaners; [40 CFR 52.21][326 IAC 2-2][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P]
 - (3) White glove inspections using some cleaners, caulks and touch-up paint; [40 CFR 52.21][326 IAC 2-2][40 CFR Part 63, Subpart M][40 CFR Part 63, Subpart P] and
 - (4) One (1) natural gas-fired boiler with a heat input capacity of 12.0 MMBtu/hr. [326 IAC 6-2-3]
- (g) Plant 32: R&D (Research & Development) shop and warehouse
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:
- (1) one (1) R&D CNC router [326 IAC 6-3-2]
 - (2) one (1) R&D fiberglass spray booth, identified as SV32-1, with emissions controlled by dry filters [40 CFR 52.21] [326 IAC 2-2][40 CFR 52 Subpart P][326 IAC 6-3-2(d)][326 IAC 20-25]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.8.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.4.1, D.5.1, D.6.1, D.7.1, D.9.3, D.10.1 and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.8.2 Particulate Matter [326 IAC 6-2-3]

Pursuant to 326 IAC 6-2-3(e), the particulate matter (PM) emissions from the boiler shall not exceed 0.6 pounds per MMBtu heat input.

D.8.3 Particulate Matter (PM) [40 CFR 52 Subpart P]

Pursuant to CP 039-7335-00017, issued on July 24, 1997, and 40 CFR Part 52 Subpart P, the particulate matter (PM) from SV32-1 shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

D.8.4 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2, the allowable particulate emission rate from the insignificant R&D CNC router shall be limited by the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where} \quad \begin{array}{l} E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour} \end{array}$$

D.8.5 Particulate [326 IAC 6-3-2(d)]

Pursuant to CP 039-7335-00017, issued on July 24, 1997 and 326 IAC 6-3-2(d), particulate from SV32-1 shall be controlled by a dry particulate filter, and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.8.6 Volatile Organic Compounds [326 IAC 8-1-6]

Any change or modification which may increase the potential VOC emissions from SV32-1 to greater than 25 tons per year must be approved by the OAQ before any such change may occur.

D.8.7 Emissions Standards for Reinforced Plastics Composites Fabricating [326 IAC 20-25-3]

Pursuant to 326 IAC 20-25-3, the owner or operator shall, for units SV32-1, GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1, comply with the following provisions:

- (a) The total HAP monomer content of the following materials shall be limited based on the application method used and the products produced as specified in the following table:

	HAP Monomer Content, Weight Percent
Resin, Manual or Mechanical Application	
Production-Specialty Products	48*
Production-Noncorrosion Resistant Unfilled	35*
Production-Noncorrosion Resistant Filled (\$35% by weight)	38
Production, Noncorrosion Resistant, Applied to Thermoformed Thermoplastic Sheet	42

	HAP Monomer Content, Weight Percent
Production, Class I, Flame and Smoke	60*
Shrinkage Controlled	52
Tooling	43
Gel Coat Application	
Production-Pigmented	37
Clear Production	44
Tooling	45
Production-Pigmented, subject to ANSI ^a standards	45
Production-Clear, subject to ANSI ^a standards	50

^a American National Standards Institute.

* Categories that must use mechanical nonatomized application technology or manual application as stated in subsection (b).

Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis. If all of the resins and gel coats used during a month meet the specified HAP monomer content limits, then maintaining records of content and usage as specified under Condition D.8.13 is sufficient for demonstrating compliance with the HAP monomer content limits.

In lieu of meeting the HAP monomer content limits specified in this condition, the owner or operator may use monthly emission averaging across each resin and/or gel coat application category listed in subsection(a), provided that:

- (1) the actual HAP emissions of all the listed FRP production units are less than the sum of the allowable emissions as identified in the across category averaging equation listed below, and
- (2) the owner or operator uses any one (1) or a combination of the following emission reduction techniques:
 - (A) Resins or gel coats with HAP monomer contents lower than specified in subsection (a).
 - (B) Vapor suppressed resins.
 - (C) Vacuum bagging or other similar technique. This item does not include resin transfer molding or compression molding.
 - (D) Air pollution control equipment where the emissions are estimated based on parametric measurements or stack monitoring.
 - (E) Controlled spray used in combination with automated actuators or robots.
 - (F) Controlled spray that includes the following:
 - (1) Mold flanges.

- (2) Spray technique.
 - (3) Spray gun pressure.
 - (4) Means of verifying continuous use of the controlled spray technique, such as mass balance of materials and products (surface area and thickness of product), as approved by the commissioner prior to implementation.
- (G) Non-atomized application technology including flow coaters, flow choppers, pressure fed rollers, fluid impingement, or other non-spray application methods or equipment approved by IDEM, OAQ.
- (H) Other approved enforceable alternative emission reduction techniques that are at least equally protective of the environment as the emission standards listed in subsections (a) through (c) of this condition.

For averaging across categories:

$$E_{mA} < (M_R * E_{Ra}) + (M_G * E_{Ga})$$

Where:

- M_R = Total monthly mass of resins within each resin category
 M_G = Total monthly mass of gel coats within each gel coats category
 E_{Ra} = Emission factor for each resin based on allowable monomer content and allowable application method for each resin category.
 E_{Ga} = Emission factor for each gel coat based on allowable monomer content for each gel coat category
 E_{mA} = Actual monthly emissions from all resins and gel coats based on material specific emission factors, emission reduction techniques and emission controls

Units: mass = tons
 emission factor = lbs of monomer per ton of resin or gel coat
 emissions = lbs of monomer

Note: Fillers may not be included when averaging.

- (b) The following categories of materials in subsection (a) shall be applied using mechanical nonatomized application technology or manual application:
- (1) Production noncorrosion resistant, unfilled resins from all sources.
 - (2) Production, specialty product resins from all sources.
 - (3) Tooling resins used in the manufacture of watercraft.
 - (4) Production resin used for Class I flame and smoke products.

Nonatomized application equipment means the devices where resin or gel coat material does any of the following:

- (1) Flows from the applicator, in a steady state in a observable coherent flow, without droplets, for a minimum distance of three (3) inches from the applicator orifices such as flow coaters, flow choppers, and fluid impingement equipment.
- (2) Is mechanically dispensed within or on to a paint roller applicator such as pressure fed rollers.
- (3) Is deposited on fiber reinforcement moving through a resin or gel coat bath such as resin impregnators.

Nonatomized spray application technology includes flow coaters, flow choppers, pressure-fed rollers, fluid impingement, or other non-spray applications of a design and specifications approved by IDEM, OAQ.

Filled resins are resins containing greater than or equal to thirty-five percent (35%) by weight inert filler material, such as silica micro-spheres or micro-balloons, added to alter the density or other physical properties of the resin. The term "inert filler" does not include pigments.

- (c) Unless specified in subsection (b), gel coat application and mechanical application of resins shall be by any of the following spray technologies:
 - (1) Nonatomized application technology.
 - (2) Air-assisted airless.
 - (3) Airless.
 - (4) High volume, low pressure (HVLP).
 - (5) Equivalent emission reduction technologies to subdivisions (2) through (4).
- (d) The following cleaning operation standards for resin and gel coat application equipment shall apply:
 - (1) For routine flushing of resin and gel coat application equipment such as spray guns, flow coaters, brushes, rollers, and squeegees, a cleaning solvent shall contain no HAPs. This emission standard does not apply to solvents used for removing cured resin or gel coat from application equipment.
 - (2) A source must store HAP containing solvents used for removing cured resin or gel coat in containers with covers. The covers must have no visible gaps and must be in place at all times, except when equipment is placed in or removed from the container.
 - (3) Recycled cleaning solvents that contain less than or equal to five percent (5%) HAP by weight are considered to contain no HAP for the purposes of this subsection.

D.8.8 Work Practice Standards for Reinforced Plastic Composites Fabrication [326 IAC 20-25-4]

Pursuant to 326 IAC 20-25-4, the following work practice standards shall be implemented:

- (a) Non-atomizing spray equipment shall not be operated at pressures that atomize the material during the application process.
- (b) Except for mixing containers as described in item (g), HAP containing materials shall be kept in a closed container when not in use.
- (c) Solvents sprayed during cleanup and resin changes shall be directed into solvent collection containers.
- (d) Solvent collection containers shall be kept closed when not in use.
- (e) Clean-up rags with solvent shall be stored in closed containers.
- (f) Closed containers shall be used for the storage of the following:
 - (1) All production and tooling resins that contain HAPs.
 - (2) All production and tooling gel coats that contain HAPs.
 - (3) Waste resins and gel coats that contain HAPs.
 - (4) Cleaning materials, including waste cleaning materials.
 - (5) Other materials that contain HAPs.
- (g) All resin and gel coat mixing containers with a capacity equal to or greater than fifty-five (55) gallons must have a cover with no visible gaps in place at all times except when material is being added to or removed from a container, or when mixing or pumping equipment is being placed in or removed from a container.

D.8.9 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-25-8]

Pursuant to 326 IAC 20-25-8, all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and spray-like applications (for example, those applications that could result in excess emissions if performed improperly) shall be trained according to the following schedule:

- (a) All personnel hired after March 7, 2001 shall be trained within fifteen (15) days of hiring.
- (b) All personnel hired before March 7, 2001 shall be trained or evaluated by a supervisor within thirty (30) days of the start of operation.
- (c) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.
- (d) Personnel who have been trained by another owner or operator subject to 326 IAC 20-25 are exempt from subdivision (a) if written documentation that the employee's training is current is provided to the new employer.

- (e) If the result of an evaluation shows that training is needed, such training shall occur within fifteen (15) days of the evaluation.
- (f) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:
 - (1) Appropriate application techniques.
 - (2) Appropriate equipment cleaning procedures.
 - (3) Appropriate equipment setup and adjustment to minimize material usage and overspray.
- (g) The owner or operator shall maintain the following training records on site and available for inspection and review:
 - (1) A copy of the current training program.
 - (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training. Records of prior training programs and former personnel are not required to be maintained.

D.8.10 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for SV32-1 and the dry filters.

Compliance Determination Requirements

D.8.11 Hazardous Air Pollutants (HAP) and Volatile Organic Compounds (VOC)

Compliance with the HAP monomer content limitations in Condition D.8.7 shall be determined by one of the following:

- (a) The manufacturer's certified product data sheet.
- (b) The manufacturer's material safety data sheet.
- (c) Sampling and analysis, using any of the following test methods, as applicable:
 - (1) 40 CFR 60, Method 24, Appendix A (July 1, 1998), shall be used to measure the total volatile HAP and volatile organic compound (VOC) content of resins and gel coats. Method 24 may be modified for measuring the volatile HAP content of resins or gel coats to require that the procedure be performed on uncatalyzed resin or gel coat samples.
 - (2) 40 CFR 63, Method 311, Appendix A (July 1, 1998), shall be used to measure HAP content in resins and gel coats by direct injection into a gas chromatograph.
- (d) An alternate method approved by IDEM, OAQ.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.8.12 Operator Training Program

The Permittee shall implement an operator training program.

- (a) All operators that perform surface coating operations using spray equipment or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained upon permit issuance if training was not completed in the last twelve months. All new operators shall be trained within thirty (30) days of hiring or transfer.
- (b) Training shall include proper filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators and training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.8.13 Record Keeping Requirements

- (a) To document compliance with Condition D.8.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.8.1. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
 - (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month.
- (b) To document compliance with Condition D.8.7, the Permittee shall maintain records that are complete and sufficient to establish compliance with the HAP monomer content limits. Records maintained shall be taken monthly. Examples of such records include but are not limited to:
 - (1) The usage by weight and monomer content of each resin and gel coat used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS), manufacturer's certified product data sheets, and calculations necessary to verify the type, amount used, and HAP content of each resin or gel coat;

- (2) Method of application and other emission reduction techniques for each resin and gel coat used;
 - (3) Monthly calculations demonstrating compliance on an equivalent emissions mass basis if non-compliant resins or gel coats are used during that month.
- (c) To document compliance with Condition D.8.9, the Permittee shall maintain the following training records:
- (1) A copy of the current training program.
 - (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training. Records of prior training programs and former personnel are not required to be maintained.
- (d) To document compliance with Condition D.8.12, the Permittee shall maintain copies of the training program and the list of trained operators. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (e) In order to document compliance with Condition D.8.6, the Permittee shall keep records of the total VOC input to facility SV32-1 using the information required by (a) above.
- (f) To document compliance with Condition D.8.10, the Permittee shall maintain records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (g) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.8.14 Reporting Requirements

- (a) A quarterly summary of the information to document compliance with Condition D.8.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) On or after January 1, 2002, sources using monthly emissions averaging pursuant to 326 IAC 20-25-3(h)(2) and Condition D.8.7 shall submit a quarterly summary report and supporting calculations pursuant to 326 IAC 20-25-7(c). The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.9

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plants 36 and 37

- (f) Plant 36: A fiberglass fabrication plant, consisting of:
- (1) Two (2) gelcoat booths, identified as GC36-1 and GC36-2, each constructed in 1986, each with a maximum capacity of 3.5 units per hour, gel applied using air-atomized spray equipment, with emissions controlled by dry filters, exhausting to stack SV36-7;
 - (2) One (1) barrier coat spray station, identified as BC36-1, constructed in 2001, a maximum capacity of 4.0 units per hour, unfilled production resins applied using non-atomized spray application, with emissions controlled by dry filters and exhausting to stack SV36-14;
 - (3) Three (3) fiberglass chop booths, identified as SV36-1&2, SV36-3&4, and SV36-5&6, each constructed prior to 1985, each with a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, exhausting to stacks SV36-1, through SV36-6;
 - (4) Five (5) grinding stations, identified as GB36-1, GB36-2, GB36-3, GB36-4, and GB36-5, each constructed in 1994, each with a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, and each with a 100% recirculated air exhaust air stream;
 - (5) One (1) gelcoat booth, identified as GC36-3, constructed in 1994, a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, exhausting to stack SV36-12 and SV36-13;
 - (6) Two (2) fiberglass chop booths, identified as CS36-4 and CS36-5, constructed in 1994, each with a maximum capacity of 3.5 units per hour, with emissions controlled by dry filters, exhausting to stacks SV36-8 and SV36-9;
- (g) Plant 37: A fiberglass molding plant, consisting of:
- (1) One (1) fiberglass fabricating area, identified as CS37-1, constructed prior to 1985, a maximum capacity of 1.0 unit per hour, using air-atomized spray equipment, with emissions controlled by dry filters, and exhausting through general ventilation to stacks GV37-1 and GV37-2;
 - (2) One (1) gel coat booth, identified as GC37-1, constructed prior to 1985, a maximum capacity of 1.0 unit per hour, with emissions controlled by dry filters, and exhausting through general ventilation to stacks GV37-1 and GV37-2;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.9.1 General Provisions Relating to NESHAP [326 IAC 20-1][40 CFR Part 63, Subpart A]

- (a) The provisions of 40 CFR Part 63, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 20-1-1, apply to the affected source except when otherwise specified in 40 CFR Part 63, Subpart WWWW. The Permittee must comply with these requirements on and after April 21, 2003.

- (b) Since the applicable requirements associated with the compliance options are not included and specifically identified in this permit, the permit shield authorized by the B section of this permit in the condition titled Permit Shield, and set out in 326 IAC 2-7-15 does not apply to paragraph (a) of this condition.

D.9.2 National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production [40 CFR Part 63, Subpart WWWW][40 CFR 63.5805]

- (a) The reinforced plastic composites production affected source is subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Reinforced Plastic Composites Production, (40 CFR 63, Subpart WWWW), effective April 21, 2003. Pursuant to this rule, the Permittee must comply with Subpart WWWW by April 21, 2006, or accept and meet an enforceable HAP emissions limit below the major source threshold prior to April 21, 2006. Since the applicable requirements associated with the compliance options are not included and specifically identified in this permit, the permit shield authorized by the B section of this permit in the condition titled Permit Shield, and set out in 326 IAC 2-7-15 does not apply to paragraph (a) of this condition.
- (b) The following emissions units comprise the affected source that is subject to 40 CFR Part 63, Subpart WWWW:
- (1) Gelcoat booths GC36-1, GC36-2, GC36-3, GC37-1;
 - (2) Barrier coat spray station BC36-1;
 - (3) Fiberglass chop booths SV36-1&2, SV36-3&4, SV36-5&6, CS36-4, and CS36-5; and
 - (4) Fiberglass fabricating area CS37-1.
- (c) The definitions of 40 CFR 63, Subpart WWWW at 40 CFR 63.5935 are incorporated by reference.

D.9.3 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.4.1, D.5.1, D.6.1, D.7.1, D.8.1, D.10.1 and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.9.4 Particulate Matter (PM) [40 CFR 52 Subpart P]

Pursuant to CP 039-7335-00017, issued on July 24, 1997, and 40 CFR Part 52 Subpart P, the particulate matter (PM) from facilities GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1 shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
P = process weight rate in tons per hour

D.9.5 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997 and 326 IAC 6-3-2, the allowable particulate emission rate from the grinding stations (GB36-1, GB36-2, GB36-3, GB36-4, and GB36-5) shall not exceed 2.29 pounds per hour each when operating at a maximum process weight rate of 0.42 tons per hour each.

The pounds per hour limitations were calculated with the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
P = process weight rate in tons per hour

D.9.6 Particulate [326 IAC 6-3-2(d)]

Pursuant to CP 039-7335-00017, issued on July 24, 1997 and 326 IAC 6-3-2(d), particulate from GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1 shall be controlled by a dry particulate filter, and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.9.7 Volatile Organic Compounds - Best Available Control Technology (BACT) [326 IAC 8-1-6]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and 326 IAC 8-1-6, BACT for GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1 has been determined to be the following:

- (a) Use of resins and gel coats that contain styrene shall be limited such that the volatile organic HAP emissions from use of such resins and gel coats only shall be less than 249 tons per twelve (12) consecutive month period. Compliance with this limit shall be determined based upon the following criteria:
 - (1) Monthly usage by weight, weight percent content of monomer that is HAP, method of application, and other emission reduction techniques used for each gel coat and resin shall be recorded. Volatile organic HAP emissions shall be calculated by multiplying the usage of each gel coat and resin by the emission factor that is appropriate for the HAP monomer content, method of application, and other emission reduction techniques used for each gel coat and resin, and summing the emissions for all gel coats and resins. The emission factors used shall be approved by IDEM, OAQ.
 - (2) The emission factors approved for use by IDEM, OAQ shall be taken from the following reference: "Unified Emission Factors for Open Molding of Composites," Composites Fabricators Association, April 1999, with the exception of the emission factors for controlled spray application. This reference is included with this permit. For HAP-emitting operations not addressed by this reference, emission factors shall be taken from U.S. EPA's AP-42 document. For the purposes of these emission calculations, HAP monomer in resins and gel coats that is not styrene or methyl methacrylate shall be considered as styrene on an equivalent weight basis.

(b) Compliance with the requirements of Condition D.9.8.

D.9.8 Emissions Standards for Reinforced Plastics Composites Fabricating [326 IAC 20-25-3]

Pursuant to 326 IAC 20-25-3, the owner or operator shall, for units SV32-1, GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1, comply with the following provisions:

(a) The total HAP monomer content of the following materials shall be limited based on the application method used and the products produced as specified in the following table:

	HAP Monomer Content, Weight Percent
Resin, Manual or Mechanical Application	
Production-Specialty Products	48*
Production-Noncorrosion Resistant Unfilled	35*
Production-Noncorrosion Resistant Filled (\$35% by weight)	38
Production, Noncorrosion Resistant, Applied to Thermoformed Thermoplastic Sheet	42
Production, Class I, Flame and Smoke Shrinkage Controlled	60*
Tooling	52
Tooling	43
Gel Coat Application	
Production-Pigmented	37
Clear Production	44
Tooling	45
Production-Pigmented, subject to ANSI ^a standards	45
Production-Clear, subject to ANSI ^a standards	50

^a American National Standards Institute.

* Categories that must use mechanical nonatomized application technology or manual application as stated in subsection (b).

Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis. If all of the resins and gel coats used during a month meet the specified HAP monomer content limits, then maintaining records of content and usage as specified under Condition 9.15 is sufficient for demonstrating compliance with the HAP monomer content limits.

In lieu of meeting the HAP monomer content limits specified in this condition, the owner or operator may use monthly emission averaging across each resin and/or gel coat application category listed in subsection(a), provided that:

- (1) the actual HAP emissions of all the listed FRP production units are less than the sum of the allowable emissions as identified in the across category averaging equation listed below, and
- (2) the owner or operator uses any one (1) or a combination of the following emission reduction techniques:

- (A) Resins or gel coats with HAP monomer contents lower than specified in subsection (a).
- (B) Vapor suppressed resins.
- (C) Vacuum bagging or other similar technique. This item does not include resin transfer molding or compression molding.
- (D) Air pollution control equipment where the emissions are estimated based on parametric measurements or stack monitoring.
- (E) Controlled spray used in combination with automated actuators or robots.
- (F) Controlled spray that includes the following:
 - (1) Mold flanges.
 - (2) Spray technique.
 - (3) Spray gun pressure.
 - (4) Means of verifying continuous use of the controlled spray technique, such as mass balance of materials and products (surface area and thickness of product), as approved by the commissioner prior to implementation.
- (G) Non-atomized application technology including flow coaters, flow choppers, pressure fed rollers, fluid impingement, or other non-spray application methods or equipment approved by IDEM, OAQ.
- (H) Other approved enforceable alternative emission reduction techniques that are at least equally protective of the environment as the emission standards listed in subsections (a) through (c) of this condition.

For averaging across categories:

$$E_{mA} < (M_R * E_{Ra}) + (M_G * E_{Ga})$$

Where:

- M_R = Total monthly mass of resins within each resin category
- M_G = Total monthly mass of gel coats within each gel coats category
- E_{Ra} = Emission factor for each resin based on allowable monomer content and allowable application method for each resin category.
- E_{Ga} = Emission factor for each gel coat based on allowable monomer content for each gel coat category
- E_{mA} = Actual monthly emissions from all resins and gel coats based on material specific emission factors, emission reduction techniques and emission controls

Units: mass = tons
 emission factor = lbs of monomer per ton of resin or gel coat
 emissions = lbs of monomer

Note: Fillers may not be included when averaging.

- (b) The following categories of materials in subsection (a) shall be applied using mechanical nonatomized application technology or manual application:

- (1) Production noncorrosion resistant, unfilled resins from all sources.
- (2) Production, specialty product resins from all sources.
- (3) Tooling resins used in the manufacture of watercraft.
- (4) Production resin used for Class I flame and smoke products.

Nonatomized application equipment means the devices where resin or gel coat material does any of the following:

- (1) Flows from the applicator, in a steady state in a observable coherent flow, without droplets, for a minimum distance of three (3) inches from the applicator orifices such as flow coaters, flow choppers, and fluid impingement equipment.
- (2) Is mechanically dispensed within or on to a paint roller applicator such as pressure fed rollers.
- (3) Is deposited on fiber reinforcement moving through a resin or gel coat bath such as resin impregnators.

Nonatomized spray application technology includes flow coaters, flow choppers, pressure-fed rollers, fluid impingement, or other non-spray applications of a design and specifications approved by IDEM, OAQ.

Filled resins are resins containing greater than or equal to thirty-five percent (35%) by weight inert filler material, such as silica micro-spheres or micro-balloons, added to alter the density or other physical properties of the resin. The term "inert filler" does not include pigments.

- (c) Unless specified in subsection (b), gel coat application and mechanical application of resins shall be by any of the following spray technologies:
 - (1) Nonatomized application technology.
 - (2) Air-assisted airless.
 - (3) Airless.
 - (4) High volume, low pressure (HVLP).
 - (5) Equivalent emission reduction technologies to subdivisions (2) through (4).
- (d) The following cleaning operation standards for resin and gel coat application equipment shall apply:
 - (1) For routine flushing of resin and gel coat application equipment such as spray guns, flow coaters, brushes, rollers, and squeegees, a cleaning solvent shall contain no HAPs. This emission standard does not apply to solvents used for removing cured resin or gel coat from application equipment.

- (2) A source must store HAP containing solvents used for removing cured resin or gel coat in containers with covers. The covers must have no visible gaps and must be in place at all times, except when equipment is placed in or removed from the container.
- (3) Recycled cleaning solvents that contain less than or equal to five percent (5%) HAP by weight are considered to contain no HAP for the purposes of this subsection.

D.9.9 Work Practice Standards for Reinforced Plastic Composites Fabrication [326 IAC 20-25-4]

Pursuant to 326 IAC 20-25-4, the following work practice standards shall be implemented for all fiberglass operations:

- (a) Non-atomizing spray equipment shall not be operated at pressures that atomize the material during the application process.
- (b) Except for mixing containers as described in item (g), HAP containing materials shall be kept in a closed container when not in use.
- (c) Solvents sprayed during cleanup and resin changes shall be directed into solvent collection containers.
- (d) Solvent collection containers shall be kept closed when not in use.
- (e) Clean-up rags with solvent shall be stored in closed containers.
- (f) Closed containers shall be used for the storage of the following:
 - (1) All production and tooling resins that contain HAPs.
 - (2) All production and tooling gel coats that contain HAPs.
 - (3) Waste resins and gel coats that contain HAPs.
 - (4) Cleaning materials, including waste cleaning materials.
 - (5) Other materials that contain HAPs.
- (g) All resin and gel coat mixing containers with a capacity equal to or greater than fifty-five (55) gallons must have a cover with no visible gaps in place at all times except when material is being added to or removed from a container, or when mixing or pumping equipment is being placed in or removed from a container.

D.9.10 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-25-8]

Pursuant to 326 IAC 20-25-8, all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and spray-like applications (for example, those applications that could result in excess emissions if performed improperly) shall be trained according to the following schedule:

- (a) All personnel hired after March 7, 2001 shall be trained within fifteen (15) days of hiring.
- (b) All personnel hired before March 7, 2001 shall be trained or evaluated by a supervisor within thirty (30) days of the start of operation.

- (c) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.
- (d) Personnel who have been trained by another owner or operator subject to 326 IAC 20-25 are exempt from subdivision (a) if written documentation that the employee's training is current is provided to the new employer.
- (e) If the result of an evaluation shows that training is needed, such training shall occur within fifteen (15) days of the evaluation.
- (f) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:
 - (1) Appropriate application techniques.
 - (2) Appropriate equipment cleaning procedures.
 - (3) Appropriate equipment setup and adjustment to minimize material usage and overspray.
- (g) The owner or operator shall maintain the following training records on site and available for inspection and review:
 - (1) A copy of the current training program.
 - (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training. Records of prior training programs and former personnel are not required to be maintained.

D.9.11 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.9.12 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAP)

Compliance with the HAP monomer content limitations in condition D.9.8(a) shall be determined by one of the following:

- (a) The manufacturer's certified product data sheets.
- (b) The manufacturer's material safety data sheets.
- (c) Sampling and analysis, using any of the following test methods, as applicable:
 - (1) 40 CFR 60, Method 24, Appendix A (July 1, 1998), shall be used to measure the total volatile HAP and volatile organic compound (VOC) content of resins and gel coats. Method 24 may be modified for measuring the volatile HAP content of resins or gel coats to require that the procedure be performed on uncatalyzed resin or gel coat samples.

- (2) 40 CFR 63, Method 311, Appendix A (July 1, 1998), shall be used to measure HAP content in resins and gel coats by direct injection into a gas chromatograph.
- (d) An alternate method approved by IDEM, OAQ.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.9.13 Operator Training Program

The Permittee shall implement an operator training program.

- (a) All operators that perform surface coating operations using spray equipment or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained upon permit issuance if training was not completed in the last twelve months. All new operators shall be trained within thirty (30) days of hiring or transfer.
- (b) Training shall include proper filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators and training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.9.14 National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production- Notifications [40 CFR Part 63, Subpart WWWW][40 CFR 63.5905]

-
- (a) Pursuant to 40 CFR 63.5905, the Permittee shall submit all of the notifications in Table 13 of 40 CFR Part 63, Subpart WWWW that apply to the affected source and chosen compliance method by the dates specified. These notifications include, but are not limited to, the following:
 - (1) If complying with organic HAP emissions limit averaging provisions, the Permittee shall submit a Notification of Compliance Status, containing the information specified in 40 CFR 63.9(h).
 - (2) If complying with organic HAP content limits, application equipment requirements, or organic HAP emissions limit other than organic HAP emissions limit averaging, the Permittee shall submit a Notification of Compliance Status, containing the information specified in 40 CFR 63.9(h).
 - (3) If complying by using an add-on control device, the Permittee shall submit:
 - (A) A notification of intent to conduct a performance test as specified in 40 CFR 63.9(e), at least 60 calendar days before the performance test is scheduled to begin.

- (B) A notification of the date for the CMS performance evaluation, if required, as specified in 40 CFR 63.9(g), by the date of submission of the notification of intent to conduct a performance test.
 - (C) A Notification of Compliance Status as specified in 40 CFR 63.9(h), no later than 60 calendar days after the completion of the add-on control device performance test and CMS performance evaluation.
- (b) All notifications, required by (a) above, must be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Director, Air and Radiation Division
77 Jackson Boulevard
Chicago, Illinois 60604-3590

D.9.15 Record Keeping Requirements

- (a) To document compliance with Condition D.9.3, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.9.3. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
- (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month.
- (b) To document compliance with Condition D.9.8(a), the Permittee shall maintain records that are complete and sufficient to establish compliance with the HAP monomer content limits. Records maintained shall be taken monthly. Examples of such records include but are not limited to:
- (1) The usage by weight and monomer content of each resin and gel coat used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS), manufacturer's certified product data sheets, and calculations necessary to verify the type, amount used, and HAP content of each resin or gel coat;
 - (2) Method of application and other emission reduction techniques for each resin and gel coat used;

- (3) Monthly calculations demonstrating compliance on an equivalent emissions mass basis if non-compliant resins or gel coats are used during that month.
- (c) To document compliance with Condition D.9.10, the Permittee shall maintain the following training records:
 - (1) A copy of the current training program.
 - (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training. Records of prior training programs and former personnel are not required to be maintained.
- (d) To document compliance with Condition D.9.13, the Permittee shall maintain copies of the training programs and the lists of trained operators. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.9.16 Reporting Requirements

- (a) A quarterly summary of the information to document compliance with Condition D.9.3 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) Pursuant to 326 IAC 20-25-7(c), a quarterly summary of the information to document compliance with Condition D.9.8 along with supporting calculations shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting form located at the end of this permit, or its equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee requires certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

D.9.17 Requirement to Submit a Significant Permit Modification Application [326 IAC 2-7-12][326 IAC 2-7-5]

The Permittee shall submit an application for a significant permit modification to IDEM, OAQ to include information from the Notification Of Compliance Status (NOCS) in the Title V permit.

- (a) The significant permit modification application shall be consistent with 326 IAC 2-7-12, including information sufficient for IDEM, OAQ to incorporate into the Title V permit the applicable requirements of 40 CFR 63, Subpart WWWW a description of the affected source and activities subject to the standard, and a description of how the Permittee will meet the applicable requirements of the standard.
- (b) The significant permit modification application shall be submitted no later than July 21, 2005 and shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

SECTION D.10

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 38

(specifically regulated insignificant activities)

- (h) Plant 38: R&D machine shop and print shop
Activities with emissions equal to or less than the following thresholds: 5 lb/hr or 25 lb/day PM; 5 lb/hr or 25 lb/day SO₂; 5 lb/hr or 25 lb/day NO_x; 3 lb/hr or 15 lb/day VOC; 0.6 tons per year Pb; 1.0 ton/yr of a single HAP, or 2.5 ton/yr of any combination of HAPs:

Three (3) printing presses (moved from Plant 45) which use low-VOC soy-based inks. [40 CFR 52.21] [326 IAC 2-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.10.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.4.1, D.5.1, D.6.1, D.7.1, D.8.1, D.9.3 and D.11.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.10.2 Volatile Organic Compounds [326 IAC 8-5-5]

Any change or modification which may increase the total potential VOC emissions from any of the insignificant printing presses to greater than 25 tons per year must be approved by the OAQ before any such change may occur.

Compliance Determination Requirements

D.10.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]

Compliance with the VOC usage limitation contained in Condition D.10.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.10.4 Record Keeping Requirements

- (a) To document compliance with Condition D.10.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC content and usage limits established in Condition D.10.1.

Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.

- (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month.
- (b) In order to document compliance with Condition D.10.2, the Permittee shall keep records of the total VOC input to each of the printing presses.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.10.5 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.10.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.11

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Plant 39

- (h) Plant 39: Training Center and Overflow Service Center:
One (1) R&D paint booth, identified as PB39-1, constructed in 1989, used for training and repair, with emissions controlled by dry filters, and exhausting to stack SV39-1.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.11.1 Prevention of Significant Deterioration (PSD) [40 CFR 52.21] [326 IAC 2-2]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and as revised by this Part 70 permit, the combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, 38, and 39 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

Compliance with this limit (which is identical to Conditions D.1.3, D.3.1, D.4.1, D.5.1, D.6.1, D.7.1, D.8.1, D.9.3 and D.10.1) is equivalent to VOC emissions of less than 250 tons per year and will render the requirements of 40 CFR 52.21 and 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.11.2 Particulate Matter (PM) [40 CFR Part 52 Subpart P]

Pursuant to 40 CFR Part 52 Subpart P, the particulate matter (PM) from PB39-1 shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.11.3 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate from PB39-1 shall be controlled by a dry particulate filter and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.11.4 Volatile Organic Compounds [326 IAC 8-1-6]

Pursuant to Registration, issued January 16, 1989, any change or modification which may increase the VOC potential to emit of PB39-1 to greater than or equal to 25 tons per year must be approved by the OAQ before any such change may occur.

D.11.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for PB39-1 and the dry filters.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.11.6 Operator Training Program

The Permittee shall implement an operator training program.

- (a) All operators (except trainees) that perform surface coating operations using spray equipment or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained upon permit issuance if training was not completed in the last twelve months. All new operators shall be trained within thirty (30) days of hiring or transfer.
- (b) Training shall include proper filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators and training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.11.7 Record Keeping Requirements

- (a) To document compliance with Condition D.11.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC content and usage limits established in Condition D.10.1. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
 - (1) The VOC content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month.
- (b) In order to document compliance with Condition D.11.4, the Permittee shall keep records of the total VOC input to facility PB39-1 using the information required by (a) above.
- (c) To document compliance with Condition D.11.5, the Permittee shall maintain records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (d) To document compliance with Condition D.11.6, the Permittee shall maintain copies of the training program and the list of trained operators. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.

- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.11.8 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.11.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

Entire Source - for the purposes of 40 CFR Part 63, Subpart Mmmm and Subpart Pppp

Emission Limitations and Standards [326 IAC 2-7-5(1)]

E.1 General Provisions Relating to NESHAP [326 IAC 20-1][40 CFR Part 63, Subpart A][Table 2 to 40 CFR Part 63, Subpart Mmmm][Table 12 to 40 CFR Part 63, Subpart Pppp]

- (a) The provisions of 40 CFR Part 63, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 20-1-1, apply to the affected source except when otherwise specified in 40 CFR Part 63, Subpart Mmmm. The Permittee must comply with these requirements on and after January 2, 2004.
- (b) The provisions of 40 CFR Part 63, Subpart A - General Provisions, which are incorporated by reference as 326 IAC 20-1-1, apply to the affected source, except when otherwise specified in 40 CFR Part 63, Subpart Pppp. The Permittee must comply with these requirements on and after the effective date of 40 CFR Part 63, Subpart Pppp.
- (c) Since the applicable requirements associated with the compliance options are not included and specifically identified in this permit, the permit shield authorized by the B section of this permit in the condition titled Permit Shield, and set out in 326 IAC 2-7-15 does not apply to paragraphs (a) and (b) of this condition.

E.2 National Emission Standards for Hazardous Air Pollutants: Surface Coating of Miscellaneous Metal Parts and Products [40 CFR Part 63, Subpart Mmmm][40 CFR 63.3882][40 CFR 63.3883][40 CFR 63.3890]

- (a) The provisions of 40 CFR Part 63, Subpart Mmmm (National Emission Standards for Hazardous Air Pollutants: Surface Coating of Miscellaneous Metal Parts and Products) apply to the affected source (as defined in (c) below). A copy of this rule is available on the US EPA Air Toxics Website at <http://www.epa.gov/ttn/atw/misc/miscpg.html>. Pursuant to 40 CFR 63.3883(b), the Permittee must comply with these requirements on and after January 2, 2007.
- (b) Since the applicable requirements associated with the compliance options are not included and specifically identified in this permit, the permit shield authorized by the B section of this permit in the condition titled Permit Shield, and set out in 326 IAC 2-7-15 does not apply to paragraph (a) of this condition.
- (c) The affected source is the collection of all of the items listed in 40 CFR 63.3882, paragraphs (b)(1) through (b)(4), that are used for surface coating of miscellaneous metal parts and products within each subcategory as defined in 40 CFR 63.3881(a), paragraphs (2) through (6), which include:
 - (1) All coating operations as defined in 40 CFR 63.3981;
 - (2) All storage containers and mixing vessels in which coatings, thinners and/or other additives, and cleaning materials are stored or mixed;

- (3) All manual and automated equipment and containers used for conveying coatings thinners and/or other additives, and cleaning materials; and
 - (4) All storage containers and all manual and automated equipment and containers used for conveying waste materials generated by a coating operation.
- (d) Terminology used in this section are defined in the Clean Air Act, in 40 CFR Part 63, Section 63.2, and in 40 CFR 63.3981, which are incorporated by reference.

E.3 National Emission Standards for Hazardous Air Pollutants: Surface Coating of Plastic Parts and Products: Limitations and Requirements [40 CFR Part 63, Subpart PPPP][40 CFR 63.4481][40 CFR 63.4482]

- (a) The provisions of 40 CFR Part 63, Subpart PPPP (National Emission Standards for Hazardous Air Pollutants for Surface Coating of Plastic Parts and Products) apply to the affected source (as defined in (c) below). A copy of this rule is available on the US EPA Air Toxics Website at <http://www.epa.gov/ttn/atw/plastic/plasticpg.html>. Pursuant to 40 CFR 63.4483(b), the Permittee must comply with these requirements on and after three (3) years following the effective date of 40 CFR Part 63, Subpart PPPP.
- (b) Since the applicable requirements associated with the compliance options are not included and specifically identified in this permit, the permit shield authorized by the B section of this permit in the condition titled Permit Shield, and set out in 326 IAC 2-7-15 does not apply to paragraph (a) of this condition.
- (c) The following emission units comprise the affected source that is subject to 40 CFR Part 63, Subpart PPPP:
 - (1) All coating operations as defined in 40 CFR 63.4581;
 - (2) All storage containers and mixing vessels in which coatings, thinners and/or other additives, and cleaning materials are stored or mixed;
 - (3) All manual and automated equipment and containers used for conveying coatings, thinners and/or other additives, and cleaning materials; and
 - (4) All storage containers and all manual and automated equipment and containers used for conveying waste materials generated by a coating operation.
- (d) Terminology used in this section are defined in the Clean Air Act, in 40 CFR Part 63, Section 63.2, and in 40 CFR 63.4581, which are incorporated by reference.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

E.4 National Emission Standards for Hazardous Air Pollutants: Surface Coating of Miscellaneous Metal Parts and Products - Notifications [40 CFR 63.3910]

- (a) The Permittee must submit the applicable notifications in 40 CFR 63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) by the dates specified in those sections, and as provided in paragraphs (b) and (c) below.
- (b) The Permittee must submit the Initial Notification required by 40 CFR 63.9(b) and 40 CFR 63.3910(b) no later than January 2, 2005.

- (c) The Permittee must submit the Notification Of Compliance Status required by 40 CFR 63.9(h) and 40 CFR 63.3910(c) no later than March 1, 2008. The notification of compliance status must contain the information specified in 40 CFR 63.3910(c), paragraphs (1) through (11) and any additional information specified in 40 CFR 63.9(h).
- (d) All notifications, required by (a) through (c) above, must be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Director, Air and Radiation Division
77 Jackson Boulevard
Chicago, Illinois 60604-3590

E.5 National Emission Standards for Hazardous Air Pollutants: Surface Coating of Plastic Parts and Products - Notifications [40 CFR 63.4510]

- (a) The Permittee must submit the applicable notifications in 40 CFR 63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) by the dates specified in those sections, and as provided in paragraphs (b) and (c) below.
- (b) The Permittee must submit the Initial Notification required by 40 CFR 63.9(b) and 40 CFR 63.4510(b).
- (c) The Permittee must submit the Notification Of Compliance Status required by 40 CFR 63.9(h) and 40 CFR 63.4510(c). The notification of compliance status must contain the information specified in 40 CFR 63.4510, paragraphs (c)(1) through (11) and in 40 CFR 63.9(h).
- (d) All notifications, required by (a) through (c) above, must be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Director, Air and Radiation Division
77 Jackson Boulevard
Chicago, Illinois 60604-3590

E.6 Requirement to Submit a Significant Permit Modification Application [326 IAC 2-7-12][326 IAC 2-7-5]

The Permittee shall submit an application for a significant permit modification to IDEM, OAQ to include information from the Notification Of Compliance Status (NOCS) in the Title V permit.

- (a) The significant permit modification application shall be consistent with 326 IAC 2-7-12, including information sufficient for IDEM, OAQ to incorporate into the Title V permit the applicable requirements of 40 CFR Part 63, Subpart MMMM a description of the affected source and activities subject to the standard, and a description of how the Permittee will meet the applicable requirements of the standard.
- (b) The significant permit modification application shall be submitted no later than April 2, 2006 and shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

E.7 Requirement to Submit a Significant Permit Modification Application [326 IAC 2-7-12][326 IAC 2-7-5]

The Permittee shall submit an application for a significant permit modification to IDEM, OAQ to include information from the Notification Of Compliance Status (NOCS) in the Title V permit.

- (a) The significant permit modification application shall be consistent with 326 IAC 2-7-12, including information sufficient for IDEM, OAQ to incorporate into the Title V permit the applicable requirements of 40 CFR Part 63, Subpart PPPP a description of the affected source and activities subject to the standard, and a description of how the Permittee will meet the applicable requirements of each standard.
- (b) The significant permit modification application shall be submitted no later than twenty-seven (27) months following the effective date of 40 CFR Part 63, Subpart PPPP and shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

PART 70 OPERATING PERMIT CERTIFICATION

Source Name: Monaco Coach Corporation
Source Address: 400 Indiana Avenue, Wakarusa, IN 46573
Mailing Address: 400 Indiana Avenue, Wakarusa, IN 46573
Part 70 Permit No.: T039-7559-00017

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify) _____
- Report (specify) _____
- Notification (specify) _____
- Affidavit (specify) _____
- Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH
100 North Senate Avenue
P.O. Box 6015
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT**

Source Name: Monaco Coach Corporation
Source Address: 400 Indiana Avenue, Wakarusa, IN 46573
Mailing Address: 400 Indiana Avenue, Wakarusa, IN 46573
Part 70 Permit No.: T039-7559-00017

**This form consists of 2 pages
Page 1 of 2**

- 9** This is an emergency as defined in 326 IAC 2-7-1(12)
- The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
 - The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:

Control Equipment:

Permit Condition or Operation Limitation in Permit:

Description of the Emergency:

Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
Compliance Data Section**

Part 70 Quarterly Report

Source Name: Monaco Coach Corporation
Source Address: 400 Indiana Avenue, Wakarusa, IN 46573
Mailing Address: 400 Indiana Avenue, Wakarusa, IN 46573
Part 70 Permit No.: T039-7559-00017
Facility: Partial Paint Line A; Full Paint Lines B through E (Plant 2)
Parameter: VOC
Limit: The surface coating operations shall use less than 539 tons of VOC, including coatings, dilution solvents, and cleaning solvents, per twelve (12) consecutive month period with compliance determined at the end of each month.

YEAR: _____

Month	Total Amount of VOC used (tons)	Total Amount of VOC used (tons)	Total Amount of VOC used (tons)
	This Month	Previous 11 Months	12 Month Total
Month 1:			
Month 2:			
Month 3:			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
Compliance Data Section**

Part 70 Quarterly Report

Source Name: Monaco Coach Corporation
Source Address: 400 Indiana Avenue, Wakarusa, IN 46573
Mailing Address: 400 Indiana Avenue, Wakarusa, IN 46573
Part 70 Permit No.: T039-7559-00017
Facilities: Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, and 38
Parameter: VOC
Limit: The combined input of volatile organic compounds (VOC) to Plants 1, 20, 22, 26, 28, 29, 31, 32, 36, 37, and 38 shall not exceed 249 tons per twelve consecutive month period with compliance determined at the end of each month.

YEAR: _____

Month	VOC usage	VOC usage	VOC usage
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.

Deviation has been reported on: _____

Submitted by: _____

Title / Position: _____

Signature: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

Part 70 Quarterly Report

Source Name: Monaco Coach Corporation
Source Address: 400 Indiana Avenue, Wakarusa, IN 46573
Mailing Address: 400 Indiana Avenue, Wakarusa, IN 46573
Part 70 Permit No.: T039-7559-00017
Facility: Units SV32-1, GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1
Parameter: Actual and allowable HAP emissions from the FRP units
BACT Limit: Actual HAP emissions from the FRP less than the allowable HAP emissions

YEAR: _____

	Actual HAP Emissions (tons/month)	Allowable HAP Emissions (tons/month)
Month 1		
Month 2		
Month 3		

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.

Deviation has been reported on: _____

Submitted by: _____

Title / Position: _____

Signature: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 Compliance Data Section**

**PART 70 OPERATING PERMIT
 QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Monaco Coach Corporation
 Source Address: 400 Indiana Avenue, Wakarusa, IN 46573
 Mailing Address: 400 Indiana Avenue, Wakarusa, IN 46573
 Part 70 Permit No.: T039-7559-00017

Months: _____ **to** _____ **Year:** _____

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<p><input checked="" type="radio"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.</p>	
<p><input type="radio"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD</p>	
<p>Permit Requirement (specify permit condition #)</p>	
<p>Date of Deviation:</p>	<p>Duration of Deviation:</p>
<p>Number of Deviations:</p>	
<p>Probable Cause of Deviation:</p>	
<p>Response Steps Taken:</p>	
<p>Permit Requirement (specify permit condition #)</p>	
<p>Date of Deviation:</p>	<p>Duration of Deviation:</p>
<p>Number of Deviations:</p>	
<p>Probable Cause of Deviation:</p>	
<p>Response Steps Taken:</p>	

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed By: _____

Title/Position: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Significant Permit Modification to an Existing Part 70 Permit

Source Background and Description

Source Name:	Monaco Coach Corporation
Source Location:	400 Indiana Avenue, Wakarusa, IN 46573
County:	Elkhart
SIC Code:	3716, 3792, 3083, 3081, and 2752
Operation Permit No.:	T 039-7559-00017
Significant Permit Modification No.:	039-15279-00017
Permit Reviewer:	SDF

The Office of Air Quality (OAQ) has reviewed an application from Monaco Coach Corporation relating to the operation of their multi-plant luxury motor home manufacturing operation.

Justification for the Modification

Specifically, Monaco Coach Corporation has submitted a request to apply across category averaging to fiberglass units SV32-1, GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1, as allowed under 326 IAC 20-25.

Currently, within category averaging pursuant to 326 IAC 20-25 is used to demonstrate compliance with the monomer HAP content limits of unit SV32-1. Across category averaging pursuant to 326 IAC 8-1-6 is used to demonstrate compliance with the monomer HAP content limits of all of the other affected units (GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1).

This Significant Permit Modification will allow the use of across category averaging for all of the affected units pursuant to 326 IAC 20-25.

The Office of Air Quality has determined that the proposed changes are significant pursuant to 326 IAC 2-7-12(d) because the proposed changes do not qualify for an Administrative Amendment pursuant to 326 IAC 2-7-11 or a Minor Permit Modification pursuant to 326 IAC 2-7-12(b).

Significant permit modifications require public notification. While the changes proposed in this modification have already been through the public notification process, the Office of Air Quality has determined that re-public notification is required before further permit review can continue due to the changes that have been made after the public comment period.

Recommendation

The staff recommends to the Commissioner that the Significant Permit Modification be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

Changes to the Proposed Permit

To incorporate the proposed changes into the permit, the following changes shall be made. All added information is indicated in bold type. All deleted information is struck-out.

Existing Condition D.8.7:

Existing Condition D.8.7 shall be changed as follows to change the condition language to reflect the 326 IAC 20-25 "across" category averaging requirements.

D.8.7 Emissions Standards for Reinforced Plastics Composites Fabricating [326 IAC 20-25-3]

Pursuant to 326 IAC 20-25-3, the owners or operators of SV32-1 shall comply with the provisions of 326 IAC 20-25 on or after January 1, 2002, including:

- (a) ~~The total HAP monomer content of the following materials shall be limited based on the application method used and the products produced as specified in the following table:~~

<i>Fiber Reinforced Plastics Composites Products Except Watercraft</i>	HAP Monomer Content, Weight Percent
Resin, Manual or Mechanical Application	
— Production Specialty Products	48 ^a
— Production Noncorrosion Resistant Unfilled	35 ^a
— Production Noncorrosion Resistant Filled (≥35% by weight)	38
— Production, Noncorrosion Resistant, Applied to Thermoformed Thermoplastic Sheet	42
— Production, Class I, Flame and Smoke Shrinkage Controlled	60 ^a
— Tooling	52
— Tooling	43
Gel Coat Application	
— Production Pigmented	37
— Clear Production	44
— Tooling	45
— Production Pigmented, subject to ANSI^a standards	45
— Production Clear, subject to ANSI^a standards	50

^a American National Standards Institute.

^{*} Categories that must use mechanical nonatomized application technology or manual application as stated in subsection (c).

Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis. If all of the resins and gel coats used during a month meet the specified HAP monomer content limits, then maintaining records of content and usage as specified under Condition D.8.17 is sufficient for demonstrating compliance with the HAP monomer content limits.

Compliance with the limitations contained in this condition may be demonstrated using monthly emission averaging ~~within~~ each resin or gel coat application category listed in subsection (b) by the use of resins or gel coats with HAP monomer contents lower than the limits specified, and/or additional emission reduction techniques approved by IDEM, OAQ.

Examples of emission reduction techniques include, but are not limited to, using nonatomized application to apply resins or gelcoats within a category that does not require nonatomized application, lower monomer content resins and gel coats, vapor suppression, vacuum bagging, controlled spray (if approved by IDEM, OAQ) or installing a control device. This is allowed to meet the HAP monomer content limits for resins and gel coats within each category, and shall be calculated on an equivalent emissions mass basis monthly to demonstrate compliance as shown below:

For Averaging within a category:

$$Em_A \leq (M_R * E_a)$$

Where: _____

M_R = Total monthly mass of material within each category

E_a = Emission factor for each material based on allowable monomer content and allowable application method for each category.

Em_A = Actual monthly emissions from all materials used within a category based on material specific emission factors, emission reduction techniques and emission controls

Units: mass = tons

emission factor = lbs of monomer per ton of resin or gel coat

emissions = lbs of monomer

Note: Fillers may not be included when averaging.

(b) The following categories of materials in subsection (a) shall be applied using mechanical nonatomized application technology or manual application:

- (1) Production noncorrosion resistant, unfilled resins from all sources.
- (2) Production, specialty product resins from all sources.
- (3) Tooling resins used in the manufacture of watercraft.
- (4) Production resin used for Class I flame and smoke products.

Nonatomized application equipment means the devices where resin or gel coat material does any of the following:

- (1) Flows from the applicator, in a steady state in a observable coherent flow, without droplets, for a minimum distance of three (3) inches from the applicator orifices such as flow coaters, flow choppers, and fluid impingement equipment.
- (2) Is mechanically dispensed within or on to a paint roller applicator such as pressure fed rollers.
- (3) Is deposited on fiber reinforcement moving through a resin or gel coat bath such as resin impregnators.

Nonatomized spray application technology includes flow coaters, flow choppers, pressure-fed rollers, fluid impingement, or other non-spray applications of a design and specifications approved by IDEM, OAQ.

Filled resins are resins containing greater than or equal to thirty-five percent (35%) by weight inert filler material, such as silica micro-spheres or micro-balloons, added to alter the density or other physical properties of the resin. The term "inert filler" does not include pigments.

- (c) ~~Unless specified in subsection (b), gel coat application and mechanical application of resins shall be by any of the following spray technologies:~~
- ~~(1) Nonatomized application technology.~~
 - ~~(2) Air-assisted airless.~~
 - ~~(3) Airless.~~
 - ~~(4) High volume, low pressure (HVLP).~~
 - ~~(5) Equivalent emission reduction technologies to subdivisions (2) through (4).~~
- (d) ~~The following cleaning operation standards for resin and gel coat application equipment shall apply:~~
- ~~(1) For routine flushing of resin and gel coat application equipment such as spray guns, flow coaters, brushes, rollers, and squeegees, a cleaning solvent shall contain no HAPs. This emission standard does not apply to solvents used for removing cured resin or gel coat from application equipment.~~
 - ~~(2) A source must store HAP containing solvents used for removing cured resin or gel coat in containers with covers. The covers must have no visible gaps and must be in place at all times, except when equipment is placed in or removed from the container.~~
 - ~~(3) Recycled cleaning solvents that contain less than or equal to five percent (5%) HAP by weight are considered to contain no HAP for the purposes of this subsection.~~

Pursuant to 326 IAC 20-25-3, the owner or operator shall, for units SV32-1, GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1, comply with the following provisions:

- (a) The total HAP monomer content of the following materials shall be limited based on the application method used and the products produced as specified in the following table:

	HAP Monomer Content, Weight Percent
Resin, Manual or Mechanical Application	
Production-Specialty Products	48*
Production-Noncorrosion Resistant Unfilled	35*
Production-Noncorrosion Resistant Filled (≥35% by weight)	38
Production, Noncorrosion Resistant, Applied to Thermoformed Thermoplastic Sheet	42
Production, Class I, Flame and Smoke	60*
Shrinkage Controlled	52
Tooling	43
Gel Coat Application	
Production-Pigmented	37
Clear Production	44
Tooling	45
Production-Pigmented, subject to ANSI ^a standards	45
Production-Clear, subject to ANSI ^a standards	50

- ^a American National Standards Institute.
- * Categories that must use mechanical nonatomized application technology or manual application as stated in subsection (b).

Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis. If all of the resins and gel coats used during a month meet the specified HAP monomer content limits, then maintaining records of content and usage as specified under Condition 8.13 is sufficient for demonstrating compliance with the HAP monomer content limits.

In lieu of meeting the HAP monomer content limits specified in this condition, the owner or operator may use monthly emission averaging across each resin and/or gel coat application category listed in subsection (a), provided that:

- (1) the actual HAP emissions of all the listed FRP production units are less than the sum of the allowable emissions as identified in the across category averaging equation listed below, and
- (2) the owner or operator uses any one (1) or a combination of the following emission reduction techniques:
 - (A) Resins or gel coats with HAP monomer contents lower than specified in subsection (a).
 - (B) Vapor suppressed resins.
 - (C) Vacuum bagging or other similar technique. This item does not include resin transfer molding or compression molding.
 - (D) Air pollution control equipment where the emissions are estimated based on parametric measurements or stack monitoring.
 - (E) Controlled spray used in combination with automated actuators or robots.
 - (F) Controlled spray that includes the following:
 - (1) Mold flanges.
 - (2) Spray technique.
 - (3) Spray gun pressure.
 - (4) Means of verifying continuous use of the controlled spray technique, such as mass balance of materials and products (surface area and thickness of product), as approved by the commissioner prior to implementation.
 - (G) Non-atomized application technology including flow coaters, flow choppers, pressure fed rollers, fluid impingement, or other non-spray application methods or equipment approved by IDEM, OAQ.
 - (H) Other approved enforceable alternative emission reduction techniques that are at least equally protective of the environment as the emission standards listed in subsections (a) through (c) of this condition.

For averaging across categories:

$$E_{mA} < (M_R * E_{Ra}) + (M_G * E_{Ga})$$

Where:

- M_R** = Total monthly mass of resins within each resin category
M_G = Total monthly mass of gel coats within each gel coats category
E_{Ra} = Emission factor for each resin based on allowable monomer content and allowable application method for each resin category.
E_{Ga} = Emission factor for each gel coat based on allowable monomer content for each gel coat category
E_{mA} = Actual monthly emissions from all resins and gel coats based on material specific emission factors, emission reduction techniques and emission controls

- Units:** mass = tons
emission factor = lbs of monomer per ton of resin or gel coat
emissions = lbs of monomer

Note: Fillers may not be included when averaging.

(b) The following categories of materials in subsection (a) shall be applied using mechanical nonatomized application technology or manual application:

- (1) Production noncorrosion resistant, unfilled resins from all sources.
- (2) Production, specialty product resins from all sources.
- (3) Tooling resins used in the manufacture of watercraft.
- (4) Production resin used for Class I flame and smoke products.

Nonatomized application equipment means the devices where resin or gel coat material does any of the following:

- (1) Flows from the applicator, in a steady state in a observable coherent flow, without droplets, for a minimum distance of three (3) inches from the applicator orifices such as flow coaters, flow choppers, and fluid impingement equipment.
- (2) Is mechanically dispensed within or on to a paint roller applicator such as pressure fed rollers.
- (3) Is deposited on fiber reinforcement moving through a resin or gel coat bath such as resin impregnators.

Nonatomized spray application technology includes flow coaters, flow choppers, pressure-fed rollers, fluid impingement, or other non-spray applications of a design and specifications approved by IDEM, OAQ.

Filled resins are resins containing greater than or equal to thirty-five percent (35%) by weight inert filler material, such as silica micro-spheres or micro-balloons, added to alter the density or other physical properties of the resin. The term "inert filler" does not include pigments.

- (c) **Unless specified in subsection (b), gel coat application and mechanical application of resins shall be by any of the following spray technologies:**
- (1) **Nonatomized application technology.**
 - (2) **Air-assisted airless.**
 - (3) **Airless.**
 - (4) **High volume, low pressure (HVLP).**
 - (5) **Equivalent emission reduction technologies to subdivisions (2) through (4).**
- (d) **The following cleaning operation standards for resin and gel coat application equipment shall apply:**
- (1) **For routine flushing of resin and gel coat application equipment such as spray guns, flow coaters, brushes, rollers, and squeegees, a cleaning solvent shall contain no HAPs. This emission standard does not apply to solvents used for removing cured resin or gel coat from application equipment.**
 - (2) **A source must store HAP containing solvents used for removing cured resin or gel coat in containers with covers. The covers must have no visible gaps and must be in place at all times, except when equipment is placed in or removed from the container.**
 - (3) **Recycled cleaning solvents that contain less than or equal to five percent (5%) HAP by weight are considered to contain no HAP for the purposes of this subsection.**

Existing Condition D.8.11:

Existing Condition D.8.11 shall be removed because the determination requirements specified in the condition list methods that can be used to determine "content" limits; 326 IAC 8-1-4(a)(3), as applied and as supplied VOC data sheets, and Method 24 (there are no content limits in Condition D.8.1), and the condition lists the methods of 326 IAC 8-1-2 which are only to be used if compliance with the specific requirements under 326 IAC "8" cannot be achieved through conventional methods (the limit of Condition D.8.1 is established to avoid the PSD requirements under 326 IAC 2-2, not 326 IAC 8).

No replacement condition is required because the usage record keeping requirements of Condition D.8.13(a) are sufficient to ensure that compliance with the limit of Condition D.8.1 can be demonstrated.

~~D.8.11 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]~~

~~Compliance with the VOC usage limitation contained in Condition D.8.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAG, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.~~

Existing Condition D.9.7:

Part (b) of Condition D.9.7 shall be changed as follows to simply reference the requirements of 326 IAC 20-25 which are listed in new Condition D.9.8 because the 326 IAC 20-25 requirements are as stringent or more stringent than the existing BACT requirements listed in Part (b), Condition D.9.8 has been modified to include the additional 326 IAC 20-25 across category averaging requirements that are not in the existing BACT requirements, and because referencing the requirements of Condition D.9.8 eliminates duplication.

D.9.7 Volatile Organic Compounds - Best Available Control Technology (BACT) [326 IAC 8-1-6]

Pursuant to CP 039-7335-00017, issued July 24, 1997, SSM 039-12758-00017, issued May 15, 2001, and 326 IAC 8-1-6, BACT for GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1 has been determined to be the following:

- (a) Use of resins and gel coats that contain styrene shall be limited such that the volatile organic HAP emissions from use of such resins and gel coats only shall be less than 249 tons per twelve (12) consecutive month period. Compliance with this limit shall be determined based upon the following criteria:
 - (1) Monthly usage by weight, weight percent content of monomer that is HAP, method of application, and other emission reduction techniques used for each gel coat and resin shall be recorded. Volatile organic HAP emissions shall be calculated by multiplying the usage of each gel coat and resin by the emission factor that is appropriate for the HAP monomer content, method of application, and other emission reduction techniques used for each gel coat and resin, and summing the emissions for all gel coats and resins. The emission factors used shall be approved by IDEM, OAQ.
 - (2) The emission factors approved for use by IDEM, OAQ shall be taken from the following reference: "Unified Emission Factors for Open Molding of Composites," Composites Fabricators Association, April 1999, with the exception of the emission factors for controlled spray application. This reference is included with this permit. For HAP-emitting operations not addressed by this reference, emission factors shall be taken from U.S. EPA's AP-42 document. For the purposes of these emission calculations, HAP monomer in resins and gel coats that is not styrene or methyl methacrylate shall be considered as styrene on an equivalent weight basis.
- (b) **Compliance with the requirements of Condition D.9.8.** ~~The HAP monomer content of resins and gel coats used shall be limited to the following or their equivalent on an emissions mass basis:~~

Type of Gel Coat or Resin	HAP Monomer Content, % by weight
Production ¹ -Gel Coat	37
Tooling ² -Gel Coat	45
Production Resin, Manual or Mechanical Application, -- Non corrosion Resistant Filled (≥ 35% by weight)	38
Production Resin	35
Tooling Resin	43

¹ Production refers to the manufacture of parts.

² Tooling refers to the manufacture of the molds from which parts are manufactured.

~~HAP monomer contents shall be calculated on a neat basis, which means excluding any filler. Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis.~~

~~Gel coats or resins with HAP monomer contents lower than those specified in this subsection or additional emission reduction techniques approved by IDEM, OAM may be used to offset the use of gel coats or resins with HAP monomer contents higher than those specified in the table in this subsection. This is allowed to meet the HAP monomer content limits for resins and gel coats and shall be calculated on an equivalent emissions mass basis as shown below:~~

$$\text{Em}_A \leq (M_R * E_{Ra}) + (M_G * E_{Ga})$$

Where: _____

~~M_R = Total monthly mass of resins within each resin category~~

~~M_G = Total monthly mass of gel coats within each gel coats category~~

~~E_{Ra} = Emission factor for each resin based on allowable monomer content and allowable application method for each resin category.~~

~~E_{Ga} = Emission factor for each gel coat based on allowable monomer content for each gel coat category~~

~~Em_A = Actual monthly emissions from all resins and gelcoats based on material specific emission factors, emission reduction techniques and emission controls~~

~~Units: mass = tons~~

~~emission factor = lbs of monomer per ton of resin or gel coat~~

~~emissions = lbs of monomer~~

- ~~(c) Non-atomized spray application technology shall be used to apply unfilled production resins. Non-atomized spray application technology includes flow coaters, fluid impingement technology (FIT), resin impregnators, flow choppers, pressure-fed rollers, or other non-spray applications of a design and specifications approved by IDEM, OAQ. IDEM, OAQ approval of non-atomized spray application technologies is not required if the Permittee uses one or more of the non-atomized spray technologies identified above.~~

~~If it is not possible to apply a portion of unfilled resins with non-atomized spray application technology, equivalent emissions reductions must be obtained via use of other emission reduction techniques. Examples of other emission reduction techniques include, but are not limited to, lower HAP monomer content resins and gel coats, closed molding, vapor suppression, vacuum bagging/bonding, or installing a control device. Use of a certified controlled spray program or other emission reduction techniques not yet identified must be approved by IDEM, OAQ prior to use.~~

- ~~(d) Optimized spray techniques according to a manner approved by IDEM, OAQ shall be used for gel coats and filled resins (where fillers are required for corrosion or fire retardant purposes) at all times. Optimized spray techniques include, but are not limited to, the use of airless, air-assisted airless, high volume low pressure (HVLP), or other spray applicators demonstrated to the satisfaction of IDEM, OAQ, to be equivalent to the spray applicators listed above.~~

~~HVLP spray is the technology used to apply material to substrate by means of application equipment that operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.~~

- ~~(e) The listed work practices shall be followed:~~

~~(1) To the extent possible, a non-VOC, non-HAP material shall be used for cleanup solvent.~~

~~(2) For VOC and/or HAP-containing materials:~~

- ~~(i) Cleanup solvent containers shall be used to transport solvent from drums to work.~~
- ~~(ii) Cleanup stations shall be closed containers having soft-gasketed, spring-loaded closures and shall be kept completely closed when not in use.~~
- ~~(iii) Cleanup rags saturated with solvent shall be stored, transported, and disposed of in containers that are closed tightly.~~
- ~~(iv) The spray guns used shall be the type that can be cleaned without the need for spraying the solvent into the air.~~
- ~~(v) All solvent sprayed during cleanup or resin changes shall be directed into containers. Such containers shall be closed as soon as solvent spraying is complete and the waste solvent shall be disposed of in such a manner that evaporation is minimized.~~

~~(3) All VOC- and/or HAP-containing material storage containers shall be kept covered when not in use.~~

New Condition D.9.8:

New Condition D.9.8 shall be added to include the 326 IAC 20-25-3 requirements and modify the condition such that the requirements apply to "all" of the affected fiberglass units.

D.9.8 Emissions Standards for Reinforced Plastics Composites Fabricating [326 IAC 20-25-3]

Pursuant to 326 IAC 20-25-3, the owner or operator shall, for units SV32-1, GC36-1, GC36-2, BC36-1, SV36-1&2, SV36-3&4, SV36-5&6, GB36-1, GC36-3, CS36-4, CS36-5, CS37-1, and GC37-1, comply with the following provisions:

(a) The total HAP monomer content of the following materials shall be limited based on the application method used and the products produced as specified in the following table:

	HAP Monomer Content, Weight Percent
Resin, Manual or Mechanical Application	
Production-Specialty Products	48*
Production-Noncorrosion Resistant Unfilled	35*
Production-Noncorrosion Resistant Filled (≥35% by weight)	38
Production, Noncorrosion Resistant, Applied to Thermoformed Thermoplastic Sheet	42
Production, Class I, Flame and Smoke Shrinkage Controlled	60*
Tooling	52
Tooling	43
Gel Coat Application	
Production-Pigmented	37
Clear Production	44
Tooling	45
Production-Pigmented, subject to ANSI ^a standards	45
Production-Clear, subject to ANSI ^a standards	50

^a American National Standards Institute.

* Categories that must use mechanical nonatomized application technology or manual application as stated in subsection (b).

Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis. If all of the resins and gel coats used during a month meet the specified HAP monomer content limits, then maintaining records of content and usage as specified under Condition 9.15 is sufficient for demonstrating compliance with the HAP monomer content limits.

In lieu of meeting the HAP monomer content limits specified in this condition, the owner or operator may use monthly emission averaging across each resin and/or gel coat application category listed in subsection(a), provided that:

- (1) the actual HAP emissions of all the listed FRP production units are less than the sum of the allowable emissions as identified in the across category averaging equation listed below, and**
- (2) the owner or operator uses any one (1) or a combination of the following emission reduction techniques:**
 - (A) Resins or gel coats with HAP monomer contents lower than specified in subsection (a).**
 - (B) Vapor suppressed resins.**
 - (C) Vacuum bagging or other similar technique. This item does not include resin transfer molding or compression molding.**
 - (D) Air pollution control equipment where the emissions are estimated based on parametric measurements or stack monitoring.**
 - (E) Controlled spray used in combination with automated actuators or robots.**
 - (F) Controlled spray that includes the following:**
 - (1) Mold flanges.**
 - (2) Spray technique.**
 - (3) Spray gun pressure.**
 - (4) Means of verifying continuous use of the controlled spray technique, such as mass balance of materials and products (surface area and thickness of product), as approved by the commissioner prior to implementation.**
 - (G) Non-atomized application technology including flow coaters, flow choppers, pressure fed rollers, fluid impingement, or other non-spray application methods or equipment approved by IDEM, OAQ.**
 - (H) Other approved enforceable alternative emission reduction techniques that are at least equally protective of the environment as the emission standards listed in subsections (a) through (c) of this condition.**

For averaging across categories:

$$E_{mA} < (M_R * E_{Ra}) + (M_G * E_{Ga})$$

Where:

- M_R** = Total monthly mass of resins within each resin category
M_G = Total monthly mass of gel coats within each gel coats category
E_{Ra} = Emission factor for each resin based on allowable monomer content and allowable application method for each resin category.
E_{Ga} = Emission factor for each gel coat based on allowable monomer content for each gel coat category
E_{mA} = Actual monthly emissions from all resins and gel coats based on material specific emission factors, emission reduction techniques and emission controls

Units: mass = tons
emission factor = lbs of monomer per ton of resin or gel coat
emissions = lbs of monomer

Note: Fillers may not be included when averaging.

(b) The following categories of materials in subsection (a) shall be applied using mechanical nonatomized application technology or manual application:

- (1) Production noncorrosion resistant, unfilled resins from all sources.
- (2) Production, specialty product resins from all sources.
- (3) Tooling resins used in the manufacture of watercraft.
- (4) Production resin used for Class I flame and smoke products.

Nonatomized application equipment means the devices where resin or gel coat material does any of the following:

- (1) Flows from the applicator, in a steady state in a observable coherent flow, without droplets, for a minimum distance of three (3) inches from the applicator orifices such as flow coaters, flow choppers, and fluid impingement equipment.
- (2) Is mechanically dispensed within or on to a paint roller applicator such as pressure fed rollers.
- (3) Is deposited on fiber reinforcement moving through a resin or gel coat bath such as resin impregnators.

Nonatomized spray application technology includes flow coaters, flow choppers, pressure-fed rollers, fluid impingement, or other non-spray applications of a design and specifications approved by IDEM, OAQ.

Filled resins are resins containing greater than or equal to thirty-five percent (35%) by weight inert filler material, such as silica micro-spheres or micro-balloons, added to alter the density or other physical properties of the resin. The term "inert filler" does not include pigments.

- (c) **Unless specified in subsection (b), gel coat application and mechanical application of resins shall be by any of the following spray technologies:**
- (1) **Nonatomized application technology.**
 - (2) **Air-assisted airless.**
 - (3) **Airless.**
 - (4) **High volume, low pressure (HVLP).**
 - (5) **Equivalent emission reduction technologies to subdivisions (2) through (4).**
- (d) **The following cleaning operation standards for resin and gel coat application equipment shall apply:**
- (1) **For routine flushing of resin and gel coat application equipment such as spray guns, flow coaters, brushes, rollers, and squeegees, a cleaning solvent shall contain no HAPs. This emission standard does not apply to solvents used for removing cured resin or gel coat from application equipment.**
 - (2) **A source must store HAP containing solvents used for removing cured resin or gel coat in containers with covers. The covers must have no visible gaps and must be in place at all times, except when equipment is placed in or removed from the container.**
 - (3) **Recycled cleaning solvents that contain less than or equal to five percent (5%) HAP by weight are considered to contain no HAP for the purposes of this subsection.**

New Condition D.9.9:

New Condition D.9.9 shall be added as follows to include the 326 IAC 20-25-4 requirements.

D.9.9 Work Practice Standards for Reinforced Plastic Composites Fabrication [326 IAC 20-25-4]
Pursuant to 326 IAC 20-25-4, the following work practice standards shall be implemented for all fiberglass operations:

- (a) **Non-atomizing spray equipment shall not be operated at pressures that atomize the material during the application process.**
- (b) **Except for mixing containers as described in item (g), HAP containing materials shall be kept in a closed container when not in use.**
- (c) **Solvents sprayed during cleanup and resin changes shall be directed into solvent collection containers.**
- (d) **Solvent collection containers shall be kept closed when not in use.**
- (e) **Clean-up rags with solvent shall be stored in closed containers.**
- (f) **Closed containers shall be used for the storage of the following:**
 - (1) **All production and tooling resins that contain HAPs.**
 - (2) **All production and tooling gel coats that contain HAPs.**
 - (3) **Waste resins and gel coats that contain HAPs.**
 - (4) **Cleaning materials, including waste cleaning materials.**
 - (5) **Other materials that contain HAPs.**

- (g) All resin and gel coat mixing containers with a capacity equal to or greater than fifty-five (55) gallons must have a cover with no visible gaps in place at all times except when material is being added to or removed from a container, or when mixing or pumping equipment is being placed in or removed from a container.**

Existing Condition D.9.10:

Existing Condition D.9.10 shall be removed because the determination requirements specified in the condition list methods that can be used to determine VOC "content" limits; 326 IAC 8-1-4(a)(3), as applied and as supplied VOC data sheets, and Method 24 (Condition D.9.4 limits particulate matter (PM), not VOC or HAP, and there are no VOC content limits in Condition D.9.3), the condition lists the methods of 326 IAC 8-1-2 which are only to be used if compliance with the specific requirements under 326 IAC "8" cannot be achieved through conventional methods (the limit of Condition D.9.3 is established to avoid the PSD requirements under 326 IAC 2-2, not 326 IAC 8), and there are no HAP limits associated with Conditions D.9.3 and D.9.4.

No replacement condition is required because the usage record keeping requirements of Condition D.9.15(a) are sufficient to ensure that compliance with the VOC usage limit of Condition D.9.3 can be demonstrated.

~~**D.9.10 Volatile Organic Compounds (VOC) [326 IAC 8-1-2][326 IAC 8-1-4]**~~

~~Compliance with the VOC and HAP content limitations contained in Conditions D.9.3 and D.9.4 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing, or obtaining from the manufacturer, copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.~~

New Condition D.9.12:

New Condition D.9.12 shall be added as follows to include the determination requirements associated with the new 326 IAC 20-25 across category averaging requirements.

D.9.12 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAP)

Compliance with the HAP monomer content limitations in condition D.9.8(a) shall be determined by one of the following:

- (a) The manufacturer's certified product data sheets.**
- (b) The manufacturer's material safety data sheets.**
- (c) Sampling and analysis, using any of the following test methods, as applicable:**
 - (1) 40 CFR 60, Method 24, Appendix A (July 1, 1998), shall be used to measure the total volatile HAP and volatile organic compound (VOC) content of resins and gel coats. Method 24 may be modified for measuring the volatile HAP content of resins or gel coats to require that the procedure be performed on uncatalyzed resin or gel coat samples.**
 - (2) 40 CFR 63, Method 311, Appendix A (July 1, 1998), shall be used to measure HAP content in resins and gel coats by direct injection into a gas chromatograph.**
- (d) An alternate method approved by IDEM, OAQ.**

Existing Condition D.9.13:

Existing Condition D.9.13 (now Condition D.9.15) shall be changed as follows:

- (a) Part (a) of Condition D.9.13 (now Condition D.9.15) lists the record keeping requirements necessary to document compliance with the "VOC and HAP" usage limits. The only VOC or HAP usage limit is located in Condition D.9.3. Condition D.9.4 is a particulate matter emission limit. Further, there is no HAP content limit in Condition D.9.3. Therefore, the reference to Condition D.9.4 will be removed and the reference to the HAP content limit shall be removed.
- (b) New Part (b) shall be added to include the record keeping requirements necessary to document compliance with the 326 IAC 20-25 HAP monomer content limits.
- (c) New Part (c) shall be added to include the record keeping requirements necessary to document compliance with the 326 IAC 20-25 training requirements.
- (d) Existing Part (b) (now Part (d)) lists the record keeping requirements associated with the other training requirements. Part (b) (now Part (d)) correctly references the training requirements of Condition D.9.11 (now Condition D.9.13). However, Part (b) (now Part (d)) incorrectly references Condition D.9.5 which is a condition which limits particulate matter (no training). Therefore, the reference to Condition D.9.11 shall be changed to Condition D.9.13 and the reference to Condition D.9.5 removed.
- (e) New Part (e) shall be added to include the reference to the general record keeping requirements of Section C.

D.9.135 Record Keeping Requirements

- (a) To document compliance with Conditions D.9.3 ~~and D.9.4~~, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage ~~and HAP content~~ limits established in Conditions D.9.3 ~~and D.9.4~~. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
 - (1) The VOC ~~and HAP~~ content of each coating material and solvent used less water.
 - (2) The amount of coating material and solvent used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC ~~and HAP~~ usage for each month.
- (b) **To document compliance with Condition D.9.8(a), the Permittee shall maintain records that are complete and sufficient to establish compliance with the HAP monomer content limits. Records maintained shall be taken monthly. Examples of such records include but are not limited to:**
 - (1) **The usage by weight and monomer content of each resin and gel coat used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS), manufacturer's certified product data sheets, and calculations necessary to verify the type, amount used, and HAP content of each resin or gel coat;**
 - (2) **A log of the dates of use;**
 - (3) **Method of application and other emission reduction techniques for each resin and gel coat used;**

- (4) Monthly calculations demonstrating compliance on an equivalent emissions mass basis if non-compliant resins or gel coats are used during that month.**
- (c) To document compliance with Condition D.9.10, the Permittee shall maintain the following training records:**
 - (1) A copy of the current training program.**
 - (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training. Records of prior training programs and former personnel are not required to be maintained.**
- (bd) To document compliance with Conditions ~~D.9.5 and D.9.143~~, the Permittee shall maintain copies of the training programs and the lists of trained operators. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.**
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.**

Existing Condition D.9.14:

Existing Condition D.9.14 (now Condition D.9.16) shall be changed as follows to include the new 326 IAC 20-25 reporting requirements associated with across category averaging and remove the reference to the PM requirements of Condition D.9.3 because it does not belong in Part (a).

D.9.146 Reporting Requirements

- (a) A quarterly summary of the information to document compliance with Conditions D.9.3 and ~~D.9.4~~ shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).**
- (b) Pursuant to 326 IAC 20-25-7(c), a quarterly summary of the information to document compliance with Condition D.9.8 along with supporting calculations shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting form located at the end of this permit, or its equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee requires certification by the "responsible official" as defined by 326 IAC 2-7-1(34).**

New Quarterly Report:

A new quarterly report shall be added to provide the form necessary to achieve compliance with the 326 IAC 20-25 reporting requirements.

Table of Contents and Condition Numbering:

The table of contents and condition numbering shall be revised as necessary.

Conclusion

This permit modification shall be added to the conditions of the Part 70 permit as Significant Permit Modification 039-15279-00017.

Indiana Department of Environmental Management Office of Air Quality

Addendum to the Technical Support Document

Source Name: Monaco Coach Corporation
Source Location: 400 Indiana Avenue, Wakarusa, IN 46573
County: Elkhart
SIC Code: 3716, 3792, 3083, 3081, and 2752
Operation Permit No.: T 039-7559-00017
Significant Permit Modification No.: 039-15279-00017
Permit Reviewer: SDF

On December 20, 2004, the Office of Air Quality (OAQ) had a notice published in the Elkhart Truth, Elkhart, Indiana, stating that Monaco Coach Corporation had submitted a request to add the 326 IAC 20-25 requirements to their existing operating permit. The notice also stated that the OAQ proposed to issue a permit for the proposed changes and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

On February 4, 2005, Monaco Coach Corporation submitted comments on the proposed permit. A summary of the comments and corresponding responses are as follows:

1. Comments:

- (a) I also wish to incorporate by reference, the comments contained in the appeal of Title V Permit No. T039-7559-00017 (Cause No. 04-A-J-3387).
- (b) Permit Condition D.8.13(a), page 67 of 96: Permit Condition D.8.13(a) requires records to be available within thirty (30) days which is unduly burdensome on Monaco and not required by the underlying regulations. Therefore, Permit Condition D.8.13(a) should be revised as follows:
 - (a) To document compliance with Condition D.8.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.8.1. Records necessary to demonstrate compliance shall be available within ~~30~~ **60** days ~~if of~~ the end of each compliance period.
- (c) Permit Condition D.8.13(a)(2), Page 67 of 96: Permit Condition D.8.13(a)(2) identifies specific records and information that must be maintained. The burden is on Monaco to be able to document compliance and it should have the option to use any documents it believes are necessary to accomplish that task instead of being required to maintain certain information and records that may not be necessary. Therefore, permit Condition D.8.13(a)(2) should be revised as follows:
 - (2) The amount of coating material and solvent used on monthly basis. Records shall **be sufficient to demonstrate compliance and may** include purchase orders, invoices, and/or material safety data sheets (MSDSs) **as** necessary to verify the type and amount **of material** used.
- (d) Permit Condition D.8.13(e), page 68 of 96: Permit Condition D.8.13(e) imposes recordkeeping requirements to demonstrate compliance with a requirement that the Commissioner already has determined does not apply. Therefore, Permit Condition D.8.13(e) should be revised as follows:

~~(e) In order to document compliance with Condition D.8.6, the Permittee shall keep records of the total VOC input to facility SV32-1 using the information required by (a) above.~~

(e) Permit Condition D.8.14(a), page 68 of 96: Permit Condition D.8.14(a) requires the submission of quarterly reports and imposes a deadline of thirty (30) days by which those reports must be submitted. Submitting reports on a quarterly basis and requiring those reports to be submitted within thirty (30) days are unduly burdensome on Monaco and not required by the underlying regulations. Therefore, Permit Condition D.8.14(a) should be revised as follows:

(a) A ~~quarterly~~ **semi-annual** summary of the information to document compliance with Condition D.8.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within ~~thirty (30)~~ **sixty (60)** days after the end of the ~~quarter~~ **semi-annual period** being reported. The report submitted by the Permittee requires the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(f) Permit Condition D.9.7(a)(2), page 71 of 96: Permit Condition D.9.7(a)(2) refers to the Unified Emission Factors from April 1999. This document has been updated and is no longer available. The condition should reference the Unified Emission Factors from July, 2001. Therefore, Condition D.9.7(a)(2) should be revised as follows:

(2) The emission factors approved for use by IDEM, OAQ shall be taken from the following reference: "Unified Emission Factors for Open Molding of Composites," Composites Fabricators Association, ~~April 1999~~ **July 2001**.....

(g) Permit Condition D.9.11, page 76 of 96: Permit Condition D.9.11 requires the preparation of Preventive Maintenance Plans for facilities which exceeds the scope of the regulation and is inconsistent with a Title V permit issued by IDEM to another Monaco facility. Therefore, Permit Condition D.9.11 should be revised as follows:

D.9.11 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for **the control devices associated with** these facilities ~~and their control devices~~.

(h) Permit Condition D.9.15(a), page 78 of 96: Permit Condition D.9.15(a) requires records to be available within thirty (30) days which is unduly burdensome on Monaco and not required by the underlying regulations. Therefore, permit Condition D.9.15(a) should be revised as follows:

(a) To document compliance with Condition D.9.3, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.9.3. Records necessary to demonstrate compliance shall be available within ~~30~~ **60** days ~~if of~~ the end of each compliance period.

(i) Permit Condition D.9.15(a)(2), page 78 of 96: Permit Condition D.9.15(a)(2) identifies specific records and information that must be maintained. The burden is on Monaco to be able to document compliance and it should have the option to use any documents it believes necessary to accomplish that task instead of being required to maintain certain information and records that may or may not be necessary. Therefore, Permit Condition D.9.15(a)(2) should be revised as follows.

- (2) The amount of coating material and solvent used on monthly basis. Records shall **be sufficient to demonstrate compliance and may** include purchase orders, invoices, and/or material safety data sheets (MSDSs) **as** necessary to verify the type and amount **of material** used.
- (j) Permit Condition D.9.16(a), page 79 of 96: Permit Condition D.9.16(a) requires the submission of quarterly reports and imposes a deadline of thirty (30) days by which those reports must be submitted. Submitting reports on a quarterly basis and requiring those reports to be submitted within thirty (30) days are unduly burdensome on Monaco and not required by the underlying regulations. Therefore, permit Condition D.9.16(a) should be revised as follows:
- (a) A ~~quarterly~~ **semi-annual** summary of the information to document compliance with Condition D.9.3 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within ~~thirty-sixty (30)-(60)~~ **(60)** days after the end of the ~~quarter~~ **semi-annual period** being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Response:

In the public notification letter, the IDEM, OAQ stated "The changes proposed under this significant permit modification involve only a portion of this source's operation under the pending Part 70 permit. Therefore, only the changes proposed under this modification will be open for public comment at this time." The above listed comments pertain to existing conditions that are not related to this modification. Therefore, these comments will not be addressed at this time.

2. Comment:

Permit Condition D.8.13(b)(1), page 67 of 96: Permit Condition D.8.13(b)(1) identifies specific records and information that must be maintained. The burden is on Monaco to be able to document compliance and it should have the option to use any documents it believes are necessary to accomplish that task instead of being required to maintain certain information and records that may not be necessary. Therefore, permit Condition D.8.13(b)(1) should be revised as follows:

- (1) The usage by weight and monomer content of each resin and gel coat used. Records shall **be sufficient to demonstrate compliance and may** include purchase orders, invoices, and/or material safety data sheets (MSDSs), ~~manufacturer's certified product data sheets, and calculations~~ **as** necessary to verify the type, ~~amount used, and HAP content of each resin or gel coat and amount of material used;~~

Response:

The current draft language specified in Part (b)(1) of Condition D.8.13 accurately reflects the record keeping requirements associated with 326 IAC 20-25-6, clearly stating that the records need to be complete and sufficient, as specified in 326 IAC 20-25-6(a), and shall include the "appropriate" combination of records derived from the list specified in 326 IAC 20-25-6(a)(1) through (6). The language, as written does not require the Permittee to maintain any records that are not necessary. Therefore, no changes to Condition D.8.13(b) are necessary.

3. Comment:

Permit Condition D.8.13(b)(2), page 67 of 96: Permit Condition D.8.13(b)(2) requires Monaco to maintain a log of the dates that resins and gel coats are used. However, that log will not provide any additional information necessary to demonstrate compliance with the underlying Permit Condition. Therefore, Permit Condition D.8.13(b)(2) should be revised as follows and the remaining conditions should be renumbered:

~~(2) A log of the dates of use;~~

Response:

Condition D.8.7 requires the owner or operator to limit the HAP monomer content to the specified levels, or use across category averaging such that the total actual HAP emissions from the resins and gel coats and are equal to or lower than the total allowable HAP emissions from the resins and gel coats.

If compliant resins and gel coats are used, the owner or operator need only maintain copies of the material safety data sheets.

If compliance is achieved using across category averaging the owner or operator must determine the actual and allowable emissions. Calculating the emissions does require monitoring and keeping records of the monthly usage. However, the dates of use are not necessary because the monthly usage can be determined by subtracting the amount of material at the end of the month from the amount at the beginning of the month.

Therefore, since the date of use is not necessary, Condition D.8.13(b) shall be changed as follows:

D.8.13 Record Keeping Requirements

- (a) To document compliance with Condition D.8.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.8.1. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.
- (b) To document compliance with Condition D.8.7, the Permittee shall maintain records that are complete and sufficient to establish compliance with the HAP monomer content limits. Records maintained shall be taken monthly. Examples of such records include but are not limited to:
- (1) The usage by weight and monomer content of each resin and gel coat used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS), manufacturer's certified product data sheets, and calculations necessary to verify the type, amount used, and HAP content of each resin or gel coat;
 - (2) ~~A log of the dates of use;~~
 - (3) Method of application and other emission reduction techniques for each resin and gel coat used;
 - (4) Monthly calculations demonstrating compliance on an equivalent emissions mass basis if non-compliant resins or gel coats are used during that month.

4. Comment:

Permit Condition D.9.8(a), Page 72 of 96: Permit Condition D.9.8(a) requires that HAP monomer content be demonstrated on a monthly basis. Averaging should be allowed on a 12 month rolling basis. Therefore, Permit Condition D.9.8(a) should be revised as follows:

Compliance with these HAP monomer content limits shall be demonstrated on a **12 monthly rolling average** basis.

Response:

326 IAC 20-25 established HAP monomer content limits for the source's resins and gel coats. In lieu of using compliant resins and gel coats, the owner or operator may use across category averaging such that the total actual HAP emissions from the resins and gel coats are equal to or lower than the total allowable HAP emissions from the resins and gel coats. 326 IAC 20-25-3(g)(2) states that the across category averaging must be conducted on a monthly basis, not on a twelve (12) month rolling total basis. Therefore, no changes to the requirements of Condition D.9.8(a) will be made.

5. Comment:

Permit Condition D.9.10(a), page 75 of 96: Permit Condition D.9.10(a) requires the training of new personnel within fifteen (15) days of hiring. The fifteen day time period is too short and additional time should be allowed to train new personnel. Therefore, Permit Condition D.9.10(a) should be revised as follows:

(a) All personnel hired after March 7, 2001 shall be trained within ~~fifteen (15)~~ **thirty (30)** days of hiring.

Response:

326 IAC 20-25-8(a)(1) states specifically that all personnel hired after the effective date of this rule shall be trained within fifteen (15) days of hiring. Therefore, no changes to Condition D.9.10 will be made.

6. Comments:

(a) Permit Condition D.9.15(b), page 78 of 96: Permit Condition D.9.15(b) requires Monaco to maintain specific records. The burden is on Monaco to be able to document compliance and it should have the option to use any documents it believes are necessary to accomplish that task instead of being required to maintain certain information and records that may or may not be necessary. Therefore, permit condition D.9.15(b) should be revised as follows:

(b) To document compliance with Condition D.9.8(a), the Permittee shall maintain records that are complete and sufficient to establish compliance with the HAP monomer content limits. Records maintained shall be taken monthly. Examples of such records **may** include ~~but are not limited to:~~

(b) Permit Condition D.9.15(b)(1), page 78 of 96: Permit Condition D.9.15(b)(1) identifies specific records and information that must be maintained. The burden is on Monaco to be able to document compliance and it should have the option to use any documents it believes are necessary to accomplish that task instead of being required to maintain certain information and records that may or may not be necessary. Therefore, Permit Condition D.9.15(b)(1) should be revised as follows:

- (1) The usage by weight and monomer content of each resin and gel coat used. Records shall **be sufficient to demonstrate compliance and may** include purchase orders, invoices, and/or material safety data sheets (MSDSs), ~~manufacturer's certified product data sheets, and calculations as necessary to verify the type, amount used, and HAP content of each resin or gel coat and amount of material used;~~

Response:

The current draft language specified in Part (b)(1) of Condition D.9.15 accurately reflects the record keeping requirements associated with 326 IAC 20-25-6, clearly stating that the records need to be complete and sufficient, as specified in 326 IAC 20-25-6(a), and shall include the "appropriate" combination of records derived from the list specified in 326 IAC 20-25-6(a)(1) through (6). The language, as written does not require the Permittee to maintain any records that are not necessary. Therefore, no changes to Condition D.8.13(b) are necessary.

7. Comment:

Permit Condition D.9.15(b)(2), page 78 of 96: Permit Condition D.9.15(b)(2) requires Monaco to maintain a log of the dates that resin and gel coat are used. However, that log will not provide any additional information necessary to demonstrate compliance with the underlying Permit Condition. Therefore, Permit Condition D.9.15(b)(2) should be revised as follows and the remaining condition renumbered:

~~(2) A log of the dates used;~~

Response:

Condition D.9.8 requires the owner or operator to limit the HAP monomer content to the specified levels, or use across category averaging such that the total actual HAP emissions from the resins and gel coats and are equal to or lower than the total allowable HAP emissions from the resins and gel coats.

If compliant resins and gel coats are used, the owner or operator need only maintain copies of the material safety data sheets.

If compliance is achieved using across category averaging the owner or operator must determine the actual and allowable emissions. Calculating the emissions does require monitoring and keeping records of the monthly usage. However, the dates of use are not necessary because the monthly usage can be determined by subtracting the amount of material at the end of the month from the amount at the beginning of the month.

Therefore, since the date of use is not necessary, Condition D.8.15(b) shall be changed as follows:

D.9.15 Record Keeping Requirements

- (a) To document compliance with Condition D.9.3, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limit established in Condition D.9.3. Records necessary to demonstrate compliance shall be available within 30 days if the end of each compliance period.

- (b) To document compliance with Condition D.9.8(a), the Permittee shall maintain records that are complete and sufficient to establish compliance with the HAP monomer content limits. Records maintained shall be taken monthly. Examples of such records include but are not limited to:
- (1) The usage by weight and monomer content of each resin and gel coat used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS), manufacturer's certified product data sheets, and calculations necessary to verify the type, amount used, and HAP content of each resin or gel coat;
 - (2) ~~A log of the dates of use;~~
 - (3) Method of application and other emission reduction techniques for each resin and gel coat used;
 - (43) Monthly calculations demonstrating compliance on an equivalent emissions mass basis if non-compliant resins or gel coats are used during that month.

8. Comment:

Permit Condition D.9.16(b), page 79 of 96: Permit Condition D.9.16(b) imposes a deadline of thirty (30) days for submitting the quarterly reports required by 326 IAC 20-25-7(c). Submitting those reports within thirty (30) days is unduly burdensome on Monaco, not required by the underlying regulations, and inconsistent with another Permit Condition. Therefore, Permit Condition D.9.16(b) should be revised as follows:

- (a) A ~~quarterly~~ **semi-annual** summary of the information to document compliance with Condition D.9.8 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within ~~thirty-sixty (30)-(60)~~ **(60)** days after the end of the ~~quarter~~ **semi-annual period** being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Response:

326 IAC 2-7-5(3) requires that all Title V permits contain monitoring and related record keeping and reporting requirements which assure that all reasonable information is provided to evaluate continuous compliance with applicable requirements. IDEM, OAQ believes that a period of time longer than every quarter will not provide sufficient reporting of continuous compliance.

In addition, the IDEM, OAQ has determined that thirty (30) days after the reporting period is sufficient time to submit a report.

Therefore, no changes will be made to Condition D.9.16(b).

9. Comment:

Part 70 Quarterly Report, page 94 of 96: Submitting reports on a quarterly basis is unduly burdensome on Monaco and not required by the underlying regulations. Therefore, the Part 70 Quarterly Report should be revised to require semi-annual reporting.

Response:

326 IAC 2-7-5(3) requires that all Title V permits contain monitoring and related record keeping and reporting requirements which assure that all reasonable information is provided to evaluate continuous compliance with applicable requirements. IDEM, OAQ believes that a period of time longer than every quarter will not provide sufficient reporting of continuous compliance.

Therefore, no changes will be made to the quarterly report.