



Mitchell E. Daniels, Jr.  
Governor

Thomas W. Easterly  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
(800) 451-6027  
www.IN.gov/idem

TO: Interested Parties / Applicant  
DATE: May 27, 2005  
RE: New NGC, Inc dba National Gypsum Co. / 073-16714-00033  
FROM: Paul Dubenetzky  
Chief, Permits Branch  
Office of Air Quality

### Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures  
FNPER.dot 1/10/05



100 North Senate Avenue  
Mitchell E. Daniels,  
Jr.  
Governor

Indianapolis, Indiana 46204  
(317)

232-8603

(800) 451-6027  
www.IN.gov/idem

Thomas W. Easterly  
Commissioner

## FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) RENEWAL OFFICE OF AIR QUALITY

**New NGC, Inc d/b/a National Gypsum Company  
1325 East Maple Street, Lot 8 - Lintner Industrial Park  
Rensselaer, Indiana 47978**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

**The Permittee must comply with all conditions of this permit. Noncompliance with any provision of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; and denial of a permit renewal application. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.**

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F073-16714-00033	
Original signed by: Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date: May 27, 2005  Expiration Date: May 27, 2010



<b>SECTION A</b>	<b>SOURCE SUMMARY</b> .....	5
A.1	General Information [326 IAC 2-8-3(b)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]	
A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(l)]	
A.4	FESOP Applicability [326 IAC 2-8-2]	
A.5	Prior Permits Superseded [326 IAC 2-1.1-9.5]	
<b>SECTION B</b>	<b>GENERAL CONDITIONS</b> .....	8
B.1	Permit No Defense [IC 13]	
B.2	Definitions [326 IAC 2-8-1]	
B.3	Permit Term [326 IAC 2-8-4(2)][326 IAC 2-1.1-9.5]	
B.4	Enforceability [326 IAC 2-8-6]	
B.5	Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3(h)]	
B.6	Severability [326 IAC 2-8-4(4)]	
B.7	Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]	
B.8	Duty to Provide Information[326 IAC 2-8-4(5)(E)]	
B.9	Compliance Order Issuance [326 IAC 2-8-5(b)]	
B.10	Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]	
B.11	Annual Compliance Certification [326 IAC 2-8-5(a)(1)]	
B.12	Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]	
B.13	Emergency Provisions [326 IAC 2-8-12]	
B.14	Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]	
B.15	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)][326 IAC 2-8-7(a)][326 IAC 2-8-8]	
B.16	Permit Renewal [326 IAC 2-8-3(h)]	
B.17	Permit Amendment or Revision [326 IAC 2-8-10][326 IAC 2-8-11.1]	
B.18	Operational Flexibility [326 IAC 2-8-15][326 IAC 2-8-11.1]	
B.19	Permit Revision Requirement [326 IAC 2-8-11.1]	
B.20	Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2][IC 13-17-3-2][IC 13-30-3-1]	
B.21	Transfer of Ownership or Operational Control [326 IAC 2-8-10]	
B.22	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16][326 IAC 2-1.1-7]	
B.23	Credible Evidence [326 IAC 2-8-4(3)][326 IAC 2-8-5][62 FR 8314] [326 IAC 1-1-6]	
<b>SECTION C</b>	<b>SOURCE OPERATION CONDITIONS</b> .....	17
	<b>Emission Limitations and Standards [326 IAC 2-8-4(1)]</b>	
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]	
C.2	Overall Source Limit [326 IAC 2-8]	
C.3	Opacity [326 IAC 5-1]	
C.4	Open Burning [326 IAC 4-1][IC 13-17-9]	
C.5	Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]	
C.6	Fugitive Dust Emissions [326 IAC 6-4]	
C.7	Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]	
C.8	Operation of Equipment [326 IAC 2-8-5(a)(4)]	
C.9	Stack Height [326 IAC 1-7]	
C.10	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61 Subpart M]	
	<b>Testing Requirements [326 IAC 2-8-4(3)]</b>	
C.11	Performance Testing [326 IAC 3-6]	

**Compliance Requirements [326 IAC 2-1.1-11]**

C.12 Compliance Requirements [326 IAC 2-1.1-11]

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- C.13 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]
- C.14 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]
- C.15 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11]  
[326 IAC 2-8-4(3)][326 IAC 2-8-5(1)]

**Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5]**

- C.16 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.17 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]
- C.18 Compliance Response Plan -Preparation, Implementation, Records, and Reports  
[326 IAC 2-8-4][326 IAC 2-8-5]
- C.19 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]  
[326 IAC 2-8-5]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

- C.20 General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5]
- C.21 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

**Stratospheric Ozone Protection**

C.22 Compliance with 40 CFR 82 and 326 IAC 22-1

**SECTION D.1 FACILITY OPERATION CONDITIONS**

**Six (6) Storage Silos, (SV1, SV3 - SV7) ..... 25**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.1.1 PSD Minor Limit [326 IAC 2-2]
- D.1.2 Particulate Matter less than 10 Microns [326 IAC 2-8]
- D.1.3 Particulate Matter (PM) [326 IAC 6-3]
- D.1.4 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

**Compliance Determination Requirements**

D.1.5 Particulate Matter (PM)

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- D.1.6 Visible Emissions Notations
- D.1.7 Parametric Monitoring
- D.1.8 Baghouse Inspections
- D.1.9 Broken or Failed Bag Detection

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

D.1.10 Record Keeping Requirements

**SECTION D.2 FACILITY OPERATION CONDITIONS**

**Ready Mix (Liquid) Product Line, Dry Powder Product Line, and Joint Tape Process ..... 29**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.2.1 Volatile Organic Compounds (VOCs) [326 IAC 8-1-6]
- D.2.2 PSD Minor Limit [326 IAC 2-2]
- D.2.3 Particulate Matter less than 10 Microns [326 IAC 2-8]
- D.2.4 Particulate Matter (PM) [326 IAC 6-3]
- D.2.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

**Compliance Determination Requirements**

- D.2.6 Particulate Matter (PM)
- D.2.7 Volatile Organic Compounds (VOC)[326 IAC 8-1-4] [326 IAC 8-1-2(a)]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

- D.2.8 Record Keeping Requirements

<b>Certification Form .....</b>	<b>32</b>
<b>Emergency Occurrence Form .....</b>	<b>33</b>
<b>Quarterly Deviation and Compliance Monitoring Report Form .....</b>	<b>35</b>
<b>Attachment A .....</b>	<b>37</b>

## SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-8-3(b)]

---

The Permittee owns and operates a stationary gypsum wallboard related product manufacturing operation.

Authorized individual:	Plant Manager
Source Address:	1325 East Maple Street, Lot 8 - Lintner Industrial Park Rensselaer, Indiana 47978
Mailing Address:	2001 Rexford Road, Charlotte, North Carolina 28211-3498
General Source Phone:	(219) 866-7570
SIC Code:	3275
Source Location Status:	Jasper County
Source Status:	Attainment for all criteria pollutants Federally Enforceable State Operating Permit (FESOP) Minor Source, under PSD Rules; Minor Source, Section 112 of the Clean Air Act

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) ready-mix joint compound and dry powder product storage facility with a total maximum throughput of 97 tons of raw material per hour, and consisting of the following equipment:
  - (1) Six (6) storage silos, each separately controlled by a baghouse, utilizing pneumatic loading, and consisting of the following:
    - (A) one (1) limestone silo, identified as 1900, with a maximum throughput of 27 tons of limestone per hour, with a storage capacity of 33,000 cubic feet, exhausting at one (1) silo vent, identified as SV1,
    - (B) one (1) plaster of paris silo, identified as 1925, with a maximum throughput of 20 tons of plaster of paris per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV3,
    - (C) one (1) talc silo, identified as 1905, with a maximum throughput of 14 tons of talc per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV4,
    - (D) one (1) clay silo, identified as 1920, with a maximum throughput of 24 tons of clay per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV5,

- (E) one (1) mica silo, identified as 1910, with a maximum throughput of 6 tons of mica per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV6, and
  - (F) one (1) perlite silo, identified as 1915, with a maximum throughput of 6 tons of perlite per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV7.
- (b) One (1) Ready-Mix (Liquid) Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
- (1) Two (2) silo weigh receiving bins (ID Nos. PL1 and PL2) with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM1 and RM2), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins, (ID Nos. PL3 and PL4) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM3 and RM4), which exhaust inside the building;
  - (3) Two (2) mixers/limestone scale hoppers (ID Nos. PL5 and PL6) with a maximum throughput of 3,000 gallons per hour, controlled by two (2) baghouses (ID Nos. RM5 and RM6), which exhaust inside the building; and
  - (4) Two (2) bulk bag dumping stations (ID Nos. PL7 and PL8) with a maximum throughput of 10 tons per hour, controlled by four (4) baghouses (ID Nos. RM17, RM18, RM7 and RM8), which exhaust inside the building.
- (c) One (1) Dry Powder Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
- (1) Two (2) silo weigh receiving bins (ID Nos. PL9 and PL10), with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM9 and RM10), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins (ID Nos. PL11 and PL12) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM11 and RM12), which exhaust inside the building;
  - (3) Two (2) mixers/surge bins (ID Nos. PL13 and PL14) with a maximum throughput of 12 tons per hour, with a packer bagger operation that is controlled by one (1) baghouse (ID No. RM13), which exhausts inside the building;
  - (4) One (1) bag cleaner (ID No. PL15) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM14), which exhausts inside the building; and
  - (5) One (1) bulk bag dumping station (ID No. PL16) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM15 and RM16), which exhaust inside the building.

- (d) One (1) Joint Tape Process line consisting of one (1) buffer, one (1) slitter, and one (1) rewinder, each with a maximum capacity of 2000 pounds of joint tape per hour, controlled by the Joint Tape Baghouse (SV8), which exhausts inside the building.

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Propane or liquified petroleum gas, or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) Btu per hour;
- (b) Closed loop heating and cooling systems;
- (c) Paved and unpaved roads and parking lots with public access;
- (d) Equipment used to collect any material that might be released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separator, tanks, and fluid handling equipment; and

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) to renew a Federally Enforceable State Operating Permit (FESOP).

A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
  - (1) incorporated as originally stated,
  - (2) revised, or
  - (3) deletedby this permit.
- (b) All previous permits are superseded by this permit.

## **SECTION B GENERAL CONDITIONS**

### **B.1 Permit No Defense [IC 13]**

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

### **B.2 Definitions [326 IAC 2-8-1]**

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2, and 326 IAC 2-7) shall prevail.

### **B.3 Permit Term [326 IAC 2-8-4(2)][326 IAC 2-1.1-9.5]**

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

### **B.4 Enforceability [326 IAC 2-8-6]**

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

### **B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]**

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

### **B.6 Severability [326 IAC 2-8-4(4)]**

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### **B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]**

This permit does not convey any property rights of any sort, or any exclusive privilege.

### **B.8 Duty to Provide Information [326 IAC 2-8-4(5)(E)]**

(a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.

(b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

### **B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]**

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an authorized individual of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

B.11 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
  - (5) Such other facts as specified in Sections D of this permit, IDEM, OAQ may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.12 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs), including the following information on each facility:
  - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection

schedule for said items or conditions; and

- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs, including any required record keeping, as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.13 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
  - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section) or,  
Telephone No.: 317-233-5674 (ask for Compliance Section)  
Facsimile No.: 317-233-5967

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality

100 North Senate Avenue  
Indianapolis, Indiana 46204

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
  - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
  - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
    - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
    - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.14 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the “authorized individual” as defined by 326 IAC 2-1.1-1(1).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by the “authorized individual” as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
  - (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]

New NGC, Inc. d/b/a National Gypsum Company  
Rensselaer, Indiana  
Permit Reviewer: Linda Quigley/EVP

Page 13 of 37  
F073-16714-00033

- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

**B.16 Permit Renewal [326 IAC 2-8-3(h)]**

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, IN 46204

**(b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]**

- (1) A timely renewal application is one that is:
  - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
  - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (2) If IDEM, OAQ upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.

**(c) Right to Operate After Application for Renewal [326 IAC 2-8-9]**

If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as needed to process the application.

**B.17 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]**

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

Any such application shall be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]
- (d) No permit amendment or modification is required for the addition, operation or removal of a nonroad engine, as defined in 40 CFR 89.2.

B.18 Operational Flexibility [326 IAC 2-8-15][326 IAC 2-8-11.1]

(a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-8-15(b)(2), (c)(1), and (d).

(b) Emission Trades [326 IAC 2-8-15(c)]

The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).

- (c) **Alternative Operating Scenarios** [326 IAC 2-8-15(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ or U.S. EPA is required.

**B.19 Permit Revision Requirement** [326 IAC 2-8-11.1]

---

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-8-11.1.

**B.20 Inspection and Entry** [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2][IC 13-17-3-2][IC 13-30-3-1]

---

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

**B.21 Transfer of Ownership or Operational Control** [326 IAC 2-8-10]

---

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

The application which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.22 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4320 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.23 Credible Evidence [326 IAC 2-8-4(3)][326 IAC 2-8-5][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

## SECTION C SOURCE OPERATION CONDITIONS

Entire Source

### Emissions Limitations and Standards [326 IAC 2-8-4(1)]

#### C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds Per Hour [40 CFR 52 Subpart P][326 IAC 6-3-2]

- (a) Pursuant to 40 CFR 52 Subpart P, particulate matter emissions from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
- (b) Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

#### C.2 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

- (a) Pursuant to 326 IAC 2-8:
  - (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable.
  - (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
  - (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.
- (b) Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)), potential to emit particulate matter (PM) from the entire source shall be limited to less than two hundred fifty (250) tons per twelve (12) consecutive month period.
- (c) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.
- (d) Section D of this permit contains independently enforceable provisions to satisfy

this requirement.

### C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

### C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

### C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2.

### C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

### C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]

Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the plan submitted on September 21, 1998. The plan is included as Attachment A.

### C.8 Operation of Equipment [326 IAC 2-8-5(a)(4)]

Except as otherwise provided by statute, rule or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

### C.9 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

### C.10 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or

decreases by at least twenty percent (20%); or

- (2) If there is a change in the following:
  - (A) Asbestos removal or demolition start date;
  - (B) Removal or demolition contractor; or
  - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**  
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

### **Testing Requirements [326 IAC 2-8-4(3)]**

#### **C.11 Performance Testing [326 IAC 3-6]**

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

### **Compliance Requirements [326 IAC 2-1.1-11]**

#### **C.12 Compliance Requirements [326 IAC 2-1.1-11]**

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

### **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

#### **C.13 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]**

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented upon issuance of this permit. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

Unless otherwise specified in the approval for the new emissions unit, compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

#### **C.14 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63 or other approved methods as specified in this permit.

C.15 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-8-4(3)]  
[326 IAC 2-8-5(1)]

---

- (a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ( $\pm 2\%$ ) of full scale reading.
- (b) Whenever a condition in this permit requires the measurement of a temperature, flow rate, the instrument employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ( $\pm 2\%$ ) of full scale reading.
- (c) The Preventive Maintenance Plan for the pH meter shall include calibration using known standards. The frequency of calibration shall be adjusted such that the typical error found at calibration is less than one pH point.
- (d) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

**Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

C.16 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

---

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on June 25, 2003.
- (b) Upon direct notification by IDEM, OAQ that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.17 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]

---

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.18 Compliance Response Plan - Preparation, Implementation, Records, and Reports  
[326 IAC 2-8-4] [326 IAC 2-8-5]

---

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and is comprised of:
  - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected time frame for taking reasonable response steps.

- (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
  - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
  - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
  - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, and it will be ten (10) days or more until the unit or device will be shut down, then the Permittee shall promptly notify the IDEM, OAQ of the expected date of the shut down. The notification shall also include the status of the applicable compliance monitoring parameter with respect to normal, and the results of the response actions taken up to the time of notification.
  - (4) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
  - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
  - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied.
  - (3) An automatic measurement was taken when the process was not operating.
  - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.

- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-8-12 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

**C.19 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]  
[326 IAC 2-8-5]**

---

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

**C.20 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]**

---

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.21 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC2-1.1-1(1).
  
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) Reporting periods are based on calendar years.

### **Stratospheric Ozone Protection**

#### **C.22 Compliance with 40 CFR 82 and 326 IAC 22-1**

---

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

**SECTION D.1**

**FACILITY OPERATION CONDITIONS**

**Facility Description [326 IAC 2-8-4(10)]:**

- (a) One (1) ready-mix joint compound and dry powder product storage facility with a total maximum throughput of 97 tons of raw material per hour, and consisting of the following equipment:
- (1) Six (6) storage silos, each separately controlled by a baghouse, utilizing pneumatic loading, and consisting of the following:
- (A) one (1) limestone silo, identified as 1900, with a maximum throughput of 27 tons of limestone per hour, with a storage capacity of 33,000 cubic feet, exhausting at one (1) silo vent, identified as SV1,
  - (B) one (1) plaster of paris silo, identified as 1925, with a maximum throughput of 20 tons of plaster of paris per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV3,
  - (C) one (1) talc silo, identified as 1905, with a maximum throughput of 14 tons of talc per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV4,
  - (D) one (1) clay silo, identified as 1920, with a maximum throughput of 24 tons of clay per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV5,
  - (E) one (1) mica silo, identified as 1910, with a maximum throughput of 6 tons of mica per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV6, and
  - (F) one (1) perlite silo, identified as 1915, with a maximum throughput of 6 tons of perlite per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV7.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

**D.1.1 PSD Minor Limit [326 IAC 2-2]**

Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration), the baghouses controlling the six (6) storage silos (SV1, SV3 thru SV7) shall be in operation at all times and the PM emissions from the six (6) storage silos (SV1, SV3 thru SV7) shall be limited to less than 2.16 pounds per hour. This emission limit is necessary to limit the total source wide PM emissions to less than 250 tons per twelve consecutive month period. Compliance with this condition will render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration), not applicable.

**D.1.2 Particulate Matter less than 10 Microns [326 IAC 2-8]**

Pursuant to 326 IAC 2-8 (FESOP), the baghouses controlling the six (6) storage silos (SV1, SV3 thru SV7) shall be in operation at all times and the PM10 emissions from the six (6) storage silos (SV1, SV3 thru SV7) shall be limited to less than 2.16 pounds per hour. This emission limit is necessary to limit the total source wide PM10 emissions to less than 100 tons per twelve consecutive month period. Compliance with this condition will render the requirements of 326 IAC 2-7 (Part 70 Permits), not applicable.

**D.1.3 Particulate Matter (PM) [326 IAC 6-3]**

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the facilities listed under Section D.1 shall not exceed the emission rates listed below when the facilities are operated at the listed corresponding maximum process weight rate:

Emission Unit	Process Weight Rate (ton/hr)	326 IAC 6-3-2 Particulate Allowable (lb/hr)
one(1) limestone silo (SV1)	27.00	37.31
one (1) plaster of paris silo (SV3)	20.00	30.51
one (1) talc silo (SV4)	14.00	24.03
one (1) clay silo (SV5)	24.00	34.48
one (1) mica silo (SV6)	6.00	13.62
one (1) perlite silo (SV7)	6.00	13.62

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and } P = \text{process weight rate in tons per hour}$$

**D.1.4 Preventive Maintenance Plan [326 IAC 2-8-4(9)]**

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for each facility and any control devices.

**Compliance Determination Requirements**

**D.1.5 Particulate Matter (PM)**

In order to comply with D.1.1, D.1.2 and D.1.3, the baghouses for PM and PM10 control shall be in operation and control emissions from the ready-mix joint compound and dry powder product storage facility at all times that the ready-mix joint compound and dry powder product storage facility is in operation.

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

**D.1.6 Visible Emissions Notations**

- (a) Visible emission notations of the stack exhausts of all facilities listed under Section D.1 shall be performed once per day during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.

- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

#### D.1.7 Parametric Monitoring

The Permittee shall record the total static pressure drop across the baghouses used in conjunction with each of the storage silos, at least once per day when the storage silos are in operation and venting to the atmosphere. When for any one reading, the pressure drop across the baghouse is outside the normal range of 0.5 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge and Other Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ and shall be calibrated at least once every six (6) months.

#### D.1.8 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the six (6) storage silos when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.

#### D.1.9 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit. If operations continue after bag failure is observed and it will be 10 days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.
- (b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

#### **Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

D.1.10 Record Keeping Requirements

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain records of the daily visible emission notations the stack exhausts of all facilities listed under Section D.1.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain once per day records of the total static pressure drop during normal operation when venting to the atmosphere.
- (c) To document compliance with Condition D.1.8, the Permittee shall maintain records of the results of the inspections required under Condition D.1.8 and the dates the vents are redirected.
- (d) To document compliance with Condition D.1.4, the Permittee shall maintain of records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**SECTION D.2**

**FACILITY OPERATION CONDITIONS**

**Facility Description [326 IAC 2-8-4(10)]:**

- (b) One (1) Ready-Mix (Liquid) Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
  - (1) Two (2) silo weigh receiving bins (ID Nos. PL1 and PL2) with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM1 and RM2), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins, (ID Nos. PL3 and PL4) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM3 and RM4), which exhaust inside the building;
  - (3) Two (2) mixers/limestone scale hoppers (ID Nos. PL5 and PL6) with a maximum throughput of 3,000 gallons per hour, controlled by two (2) baghouses (ID Nos. RM5 and RM6), which exhaust inside the building; and
  - (4) Two (2) bulk bag dumping stations (ID Nos. PL7 and PL8) with a maximum throughput of 10 tons per hour, controlled by four (4) baghouses (ID Nos. RM17, RM18, RM7 and RM8), which exhaust inside the building.
  
- (c) One (1) Dry Powder Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
  - (1) Two (2) silo weigh receiving bins (ID Nos. PL9 and PL10), with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM9 and RM10), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins (ID Nos. PL11 and PL12) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM11 and RM12), which exhaust inside the building;
  - (3) Two (2) mixers/surge bins (ID Nos. PL13 and PL14) with a maximum throughput of 12 tons per hour, with a packer bagger operation that is controlled by one (1) baghouse (ID No. RM13), which exhausts inside the building;
  - (4) One (1) bag cleaner (ID No. PL15) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM14); which exhaust inside the building and
  - (5) One (1) bulk bag dumping station (ID No. PL16) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID No. RM15 and RM16), which exhaust inside the building.
  
- (d) One (1) Joint Tape Process line consisting of one (1) buffer, one (1) slitter, and one (1) rewinder, each with a maximum capacity of 2000 pounds of joint tape per hour, using the Joint Tape Baghouse (SV8) as control, which exhausts inside the building.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

**D.2.1 Volatile Organic Compounds (VOCs) [326 IAC 8-1-6]**

Any change or modification, for the two (2) ready-mix joint compound and dry powder product lines that would lead to an increase in source wide potential VOC emissions to 25 tons per year, shall be submitted to the Office of Air Quality (OAQ) for approval, as required by 326 IAC 8-1-6 before such change can occur.

D.2.2 PSD Minor Limit [326 IAC 2-2]

Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration), the baghouses controlling the one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line shall be in operation at all times and the PM emissions from the one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line shall be limited to 31.13 pounds per hour, 23.49 pounds per hour and 0.07 pounds per hour, respectively. These emission limits are necessary to limit the total source wide PM emissions to less than 250 tons per twelve (12) consecutive month period. Compliance with this condition will render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration), not applicable.

D.2.3 Particulate Matter less than 10 Microns [326 IAC 2-8]

one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line shall be in operation at all times and the PM10 emissions from the one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line shall be limited to 11.61 pounds per hour, 8.76 pounds per hour, and 0.07 pounds per hour, respectively. These emission limits are necessary to limit the total source wide PM10 emissions to less than 100 tons per twelve consecutive month period. Compliance with this condition will render the requirements of 326 IAC 2-7 (Part 70 Permits), not applicable.

D.2.4 Particulate Matter (PM) [326 IAC 6-3]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the facilities listed under Section D.2 shall not exceed the emission rates listed below when the facilities are operated at the listed corresponding maximum process weight rate:

Emission Unit	Process Weight Rate (ton/hr)	326 IAC 6-3-2 Particulate Allowable (lb/hr)
silos receiving bins (PL1 and PL2)	15.00	25.16
dry additive/short weigh receiving bins (PL3 and PL4)	10.00	19.18
bulk bag dumping stations (PL7 and PL8)	10.00	19.18
silos weigh receiving bins (PL9 and PL10)	15.00	25.16
dry additive/short weigh receiving bins (PL11 and PL12)	10.00	19.18
mixers/surge bins (PL13 and PL14)	12.00	21.67
bag cleaner (PL15)	12.00	21.67
bulk bag dumping station (PL16)	10.00	19.18
joint tape process: one(1) buffer, one (1) slitter, one (1) rewinder (SV8)	1.00	4.10

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

**D.2.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]**

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for each facility and its control device.

**Compliance Determination Requirements**

**D.2.6 Particulate Matter (PM)**

In order to comply with D.2.2, D.2.3 and D.2.4, the baghouses for PM and PM10 control shall be in operation and control emissions from the one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line at all times that the one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line are in operation.

**D.2.7 Volatile Organic Compounds (VOC)[326 IAC 8-1-4] [326 IAC 8-1-2(a)]**

Compliance with the VOC content and usage limitation contained in Condition D.2.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4

**Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

**D.2.8 Record Keeping Requirements**

- (a) To document compliance with Condition D.2.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken annually and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.2.1. Records necessary to demonstrate compliance shall be available within 30 days of the end of each compliance period.
- (1) The VOC content of each material.
  - (2) The amount of material containing VOC, less water used, on an annual basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
  - (3) The total VOC usage for each year.
- (b) To document compliance with Condition D.2.5, the Permittee shall maintain of records of any additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
CERTIFICATION**

Source Name: New NGC, Inc. d/b/a National Gypsum Company  
Source Address: 1325 East Maple Street, Lot 8 - Lintner Industrial Park  
Rensselaer, IN 47978  
Mailing Address: 2001 Rexford Road, Charlotte, NC 28211-3498  
FESOP No.: F073-16714-00033

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Affidavit (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE BRANCH  
100 North Senate Avenue  
Indianapolis, Indiana 46204  
Phone: 317-233-5674  
Fax: 317-233-5967**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
EMERGENCY OCCURRENCE REPORT**

Source Name: New NGC, Inc. d/b/a National Gypsum Company  
Source Address: 1325 East Maple Street, Lot 8 - Lintner Industrial Park  
Rensselaer, IN 47978  
Mailing Address: 2001 Rexford Road, Charlotte, NC 28211-3498  
FESOP No.: F073-16714-00033

**This form consists of 2 pages**

**Page 1 of 2**

- This is an emergency as defined in 326 IAC 2-7-1(12)
- The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
  - The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

**Page 2 of 2**

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency?    Y    N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by:  
Title / Position:  
Date:  
Phone:

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: New NGC, Inc. d/b/a National Gypsum Company  
Source Address: 1325 East Maple Street, Lot 8 - Lintner Industrial Park  
Rensselaer, IN 47978  
Mailing Address: 2001 Rexford Road, Charlotte, NC 28211-3498  
FESOP No.: F073-16714-00033

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

Page 1 of 2

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

Form Completed By:

Title/Position:

Date:

Phone:

Attach a signed certification to complete this report.

## **ATTACHMENT A**

### **FUGITIVE DUST CONTROL PLAN**

- (a) Fugitive particulate matter emissions from paved and unpaved roads shall be controlled by one or more of the following methods:
  - (1) Fugitive dust suppression on paved and unpaved roads will be accomplished through wet suppression and/or other means based on the service conditions at the site.
  - (2) If necessary a water truck will be employed to supply water to the working surfaces where fugitive dusts may be generated.
  
- (b) Fugitive particulate matter emissions from material handling shall be controlled by one or more of the following methods:
  - (1) Materials are transferred pneumatically from the silos to the mixers. The silos are controlled by baghouses that will be maintained and inspected per the manufacturer's's recommendations.
  - (2) The mixers, which are located in the building, are controlled by baghouses that emit to the interior of the building. All baghouses will be subject to EPA reference method 22 for visible emissions each day that they are operated.
  - (3) Inspection and maintenance procedures recommended by the manufacturer of these baghouses will be followed and modified if needed.

**Indiana Department of Environmental Management  
Office of Air Quality**

**Addendum to the  
Technical Support Document for a  
Federally Enforceable State Operating Permit (FESOP) Renewal**

**Source Background and Description**

**Source Name:** New NGC, Inc. d/b/a National Gypsum Company  
**Source Location:** 1325 East Maple Street, Lot 8  
Lintner Industrial Park, Rensselaer, Indiana 47978  
**County:** Jasper County  
**SIC Code:** 3275  
**Operation Permit No.:** F073-16714-00033  
**Permit Reviewer:** Linda Quigley/EVP

On May 7, 2004, the Office of Air Quality (OAQ) had a notice published in the Rensselaer Republican, Rensselaer, Indiana, stating that New NGC, Inc. – d/b/a National Gypsum Company had applied for a renewal of a Federally Enforceable State Operating Permit (FESOP) to operate a stationary gypsum wallboard related product manufacturing operation. The notice also stated that OAQ proposed to issue a FESOP for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

On June 14, 2004, New NGC, Inc. d/b/a National Gypsum Company submitted comments on the proposed FESOP renewal. The summary of comments and corresponding responses are as follows (bolded language has been added and the language with a line through it has been deleted):

**Comment 1**

Three (3) baghouses identical to RM7, RM8, and RM15 for bulk bag dumping stations for each of the ready mix and dry powder lines need to be added to the permit. The three (3) baghouses are identified as RM17 and RM18 for the two (2) bulk bag dumping stations (ID Nos. PL7 and PL8) and RM16 for the one (1) bag dumping station (ID No. PL16).

**Response 1**

Conditions A.2 and the descriptive information in Section D.2 have been revised to reflect the addition of the three (3) baghouses. In addition, Section D.2 has been revised to included the statement, "which exhaust inside the building", for each unit in the Ready-Mix Product Line and Dry Powder Line.

**A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]**

---

This stationary source consists of the following emission units and pollution control devices:

- (b) One (1) Ready-Mix (Liquid) Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
  - (1) Two (2) silo weigh receiving bins (ID Nos. PL1 and PL2) with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM1 and RM2), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins, (ID Nos. PL3 and PL4) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM3 and RM4), which exhaust inside the building;

- (3) Two (2) mixers/limestone scale hoppers (ID Nos. PL5 and PL6) with a maximum throughput of 3,000 gallons per hour, controlled by two (2) baghouses (ID Nos. RM5 and RM6), which exhaust inside the building; and
  - (4) Two (2) bulk bag dumping stations (ID Nos. PL7 and PL8) with a maximum throughput of 10 tons per hour, controlled by ~~two (2)~~ **four (4)** baghouses (ID Nos. **RM17, RM18**, RM7 and RM8), which exhaust inside the building.
- (c) One (1) Dry Powder Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
- (1) Two (2) silo weigh receiving bins (ID Nos. PL9 and PL10), with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM9 and RM10), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins (ID Nos. PL11 and PL12) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM11 and RM12), which exhaust inside the building;
  - (3) Two (2) mixers/surge bins (ID Nos. PL13 and PL14) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM13), which exhausts inside the building;
  - (4) One (1) bag cleaner (ID No. PL15) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM14), which exhausts inside the building; and
  - (5) One (1) bulk bag dumping station (ID No. PL16) with a maximum throughput of 10 tons per hour, controlled by ~~one (1)~~ **two (2)** baghouses (ID Nos. RM15 and **RM16**), which exhaust inside the building.

## SECTION D.2 FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-8-4(10)]:

- (b) One (1) Ready-Mix (Liquid) Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
- (1) Two (2) silo weigh receiving bins (ID Nos. PL1 and PL2) with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM1 and RM2), **which exhaust inside the building;**
  - (2) Two (2) dry additive/short weigh receiving bins, (ID Nos. PL3 and PL4) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM3 and RM4), **which exhaust inside the building;**
  - (3) Two (2) mixers/limestone scale hoppers (ID Nos. PL5 and PL6) with a maximum throughput of 3,000 gallons per hour, controlled by two (2) baghouses (ID Nos. RM5 and RM6), **which exhaust inside the building;** and
  - (4) Two (2) bulk bag dumping stations (ID Nos. PL7 and PL8) with a maximum throughput of 10 tons per hour, controlled by ~~two (2)~~ **four (4)** baghouses (ID Nos. **RM17, RM18**, RM7 and RM8), **which exhaust inside the building.**
- (c) One (1) Dry Powder Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
- (1) Two (2) silo weigh receiving bins (ID Nos. PL9 and PL10), with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM9 and RM10), **which exhaust inside the building;**
  - (2) Two (2) dry additive/short weigh receiving bins (ID Nos. PL11 and PL12) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM11 and RM12), **which exhaust inside the building;**

- (3) Two (2) mixers/surge bins (ID Nos. PL13 and PL14) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM13), **which exhausts inside the building;**
  - (4) One (1) bag cleaner (ID No. PL15) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM14), **which exhausts inside the building;** and
  - (5) One (1) bulk bag dumping station (ID No. PL16) with a maximum throughput of 10 tons per hour, controlled by ~~one (1)~~ **two (2)** baghouses (ID Nos. RM15 and RM16), **which exhaust inside the building.**
- (d) One (1) Joint Tape Process line consisting of one (1) buffer, one (1) slitter, and one (1) rewinder, each with a maximum capacity of 2000 pounds of joint tape per hour, using the Joint Tape Baghouse (SV8) as control, **which exhausts inside the building.**

### Comment 2

VOC record keeping (usage and emissions) requirements may be unnecessary and over burdensome.

### Response 2

Since the potential to emit of VOC for the two (2) ready-mix joint compound and dry powder product lines is less than twenty-five (25) tons per year, no limit was required to render the requirements of 326 IAC 8-1-6 (BACT) not applicable. However, any changes to the VOC content of the material used may increase VOC emissions to greater than twenty-five (25) tons per year. IDEM has determined that the VOC record keeping requirements can be changed to annual record keeping rather than monthly. In addition, it is not necessary for the Permittee to record the weight of VOCs emitted for each compliance period. Condition D.2.13 (Record Keeping Requirements) has been revised as follows:

### Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

#### D.2.13 Record Keeping Requirements

- (a) To document compliance with Condition D.2.1, the Permittee shall maintain records in accordance with (1) through ~~(4)~~ **(3)** below. Records maintained for (1) through ~~(4)~~ **(3)** shall be taken ~~monthly~~ **annually** and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.2.1. Records necessary to demonstrate compliance shall be available within 30 days of the end of each compliance period.
- (1) The VOC content of each material.
  - (2) The amount of material containing VOC, less water used, on an ~~monthly~~ **annual** basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
  - (3) The total VOC usage for each ~~month~~ **year**. ~~and~~
  - ~~(4) The weight of VOCs emitted for each compliance period.~~

### Comment 3

Visible emissions notations and parametric monitoring for each of the baghouses listed in Section D.2, may not be needed since the baghouses do not exhaust to the atmosphere and will not be redirected to the atmosphere.

### Response 3

IDEM, OAQ agrees that Compliance Monitoring is not necessary for the facilities which vent inside the building. The following revisions have been made in Section D.2:

#### Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

##### ~~D.2.9 Visible Emissions Notations~~

- ~~(a) Visible emission notations of the stack exhausts of all facilities listed under Section D.2 shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.~~
- ~~(b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.~~
- ~~(c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.~~
- ~~(d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.~~
- ~~(e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.~~

##### ~~D.2.10 Parametric Monitoring~~

~~The Permittee shall record the total static pressure drop across each of the baghouses used in conjunction with joint tape process line, the ready mix liquid product line and the dry powder product line, at least once per shift when the joint tape process line, the ready mix liquid product line or the dry powder product line are in operation and venting to the atmosphere. When for any one reading, the pressure drop across the baghouse is outside the normal range of 2.0 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.~~

~~The instrument used for determining the pressure shall comply with Section C - Pressure Gauge and Other Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated at least once every six (6) months.~~

##### ~~D.2.11 Baghouse Inspections~~

~~An inspection shall be performed each calendar quarter of all bags controlling the joint tape process line, the ready mix liquid product line and the dry powder product line when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.~~

##### ~~D.2.12 Broken or Failed Bag Detection~~

~~In the event that bag failure has been observed:~~

- ~~(a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) business hours of~~

~~the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C – Compliance Response Plan – Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit. If operations continue after bag failure is observed and it will be 10 days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.~~

- ~~(b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B – Emergency Provisions).~~

#### D.2.13 9 Record Keeping Requirements

- (a) To document compliance with Condition D.2.1, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken annually and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.2.1. Records necessary to demonstrate compliance shall be available within 30 days of the end of each compliance period.
- (1) The VOC content of each material.
  - (2) The amount of material containing VOC, less water used, on an annual basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
  - (3) The total VOC usage for each year.
- ~~(b) To document compliance with Condition D.2.9, the Permittee shall maintain records of the visible emission notations for the stack exhausts of all facilities listed under Section D.2.~~
- ~~(c) To document compliance with Condition D.2.10, the Permittee shall maintain once per shift records of the total static pressure drop during normal operation when venting to the atmosphere.~~
- ~~(d) To document compliance with Condition D.2.11, the Permittee shall maintain records of the results of the inspections required under Condition D.2.11 and the dates the vents are redirected.~~
- ~~(e)(b)~~ To document compliance with Condition D.2.5, the Permittee shall maintain of records of any additional inspections prescribed by the Preventive Maintenance Plan.
- ~~(f)(c)~~ All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

The Table of Contents has been revised accordingly.

**Comment 4**

The RM13 baghouse is designed to capture dust that escapes the bagging operation from the spout of the packers. During normal operation, the air-driven product flow causes dust to be generated in the area of the discharge spouts. RM13 generates a vacuum in this area to capture and transport the dust that has escaped the spout during transfer of material to the finished product bag through the associated dust collector. Therefore, a more accurate description would be to state that RM13 baghouse controls emissions from the packer bagger operation associated with the mixers/surge silos.

**Response 4**

The descriptive information in Section A.2 (c)(3) and D.2 (c)(3) have been revised to more accurately describe what the RM13 baghouse is controlling as follows:

- (c) One (1) Dry Powder Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
  - (1) Two (2) silo weigh receiving bins (ID Nos. PL9 and PL10), with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM9 and RM10), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins (ID Nos. PL11 and PL12) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM11 and RM12), which exhaust inside the building;
  - (3) Two (2) mixers/surge bins (ID Nos. PL13 and PL14) with a maximum throughput of 12 tons per hour, **with a packer bagger operation that is** controlled by one (1) baghouse (ID No. RM13), which exhausts inside the building;
  - (4) One (1) bag cleaner (ID No. PL15) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM14), which exhausts inside the building; and
  - (5) One (1) bulk bag dumping station (ID No. PL16) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM15 and RM16), which exhausts inside the building.

**SECTION D.2**

**FACILITY OPERATION CONDITIONS**

**Facility Description [326 IAC 2-8-4(10)]:**

- (b) One (1) Ready-Mix (Liquid) Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
  - (1) Two (2) silo weigh receiving bins (ID Nos. PL1 and PL2) with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM1 and RM2), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins, (ID Nos. PL3 and PL4) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM3 and RM4), which exhaust inside the building;
  - (3) Two (2) mixers/limestone scale hoppers (ID Nos. PL5 and PL6) with a maximum throughput of 3,000 gallons per hour, controlled by two (2) baghouses (ID Nos. RM5 and RM6), which exhaust inside the building; and
  - (4) Two (2) bulk bag dumping stations (ID Nos. PL7 and PL8) with a maximum throughput of 10 tons per hour, controlled by four (4) baghouses (ID Nos. RM17, RM18, RM7 and RM8), which exhaust inside the building.
- (c) One (1) Dry Powder Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:

- (1) Two (2) silo weigh receiving bins (ID Nos. PL9 and PL10), with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM9 and RM10), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins (ID Nos. PL11 and PL12) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM11 and RM12), which exhaust inside the building;
  - (3) Two (2) mixers/surge bins (ID Nos. PL13 and PL14) with a maximum throughput of 12 tons per hour, **with a packer bagger operation that is** controlled by one (1) baghouse (ID No. RM13), which exhausts inside the building;
  - (4) One (1) bag cleaner (ID No. PL15) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM14), which exhausts inside the building; and
  - (5) One (1) bulk bag dumping station (ID No. PL16) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM15 and RM16), which exhaust inside the building.
- (d) One (1) Joint Tape Process line consisting of one (1) buffer, one (1) slitter, and one (1) rewinder, each with a maximum capacity of 2000 pounds of joint tape per hour, using the Joint Tape Baghouse (SV8) as control, which exhausts inside the building.
- (The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Upon further review, the OAQ has decided to make the following changes to the FESOP. Bolded language has been added and the language with a line through it has been deleted.

1. Condition B.22 has been revised to reflect the name change of the Billing Section.

**B.22 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]~~[326 IAC 2-1.1-7]~~**

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
  - (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
  - (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, ~~I/M & Billing Section~~) **Billing, Licensing, and Training Section**, to determine the appropriate permit fee.
2. Indiana was required to incorporate credible evidence provisions into state rules consistent with the SIP call published by U.S. EPA in 1997 (62 FR 8314). Indiana has incorporated the credible evidence provision in 326 IAC 1-1-6. This rule is effective March 16, 2005; therefore, the condition reflecting this rule will be incorporated into the permit as follows:

**B.23 Credible Evidence [326 IAC 2-8-4(3)]~~[326 IAC 2-8-5]~~[62 FR 8314] [326 IAC 1-1-6]**

**For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.**

3. The Quarterly Deviation and Compliance Monitoring Report form has been revised for clarity as follows:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: New NGC, Inc. d/b/a National Gypsum Company  
Source Address: 1325 East Maple Street, Lot 8 - Lintner Industrial Park, Rensselaer, IN 47978  
Mailing Address: 2001 Rexford Road, Charlotte, NC 28211-3498  
FESOP No.: F073-16714-00033

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

Page 1 of 2

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. <del>Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report.</del> <b>A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.</b> Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

4. Condition D.2.8 (Testing Requirements) has been removed. Condition C.12 (Compliance Requirements) already states that the commissioner may require stack testing at any time to assure compliance with all applicable requirements.

~~D.2.8 Testing Requirements [326 IAC 2-8-5(a)(1),(4)]~~

---

~~The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, to verify the VOC flash-off percentage of 5.0%, it shall be determined by a performance test conducted in accordance with Section C - Performance Testing.~~

Condition D.2.9, Record Keeping, has been renumbered to D.2.8.

5. Conditions D.1.6 (Visible Emissions Notations), D.1.7 (Parametric Monitoring), and D.1.10 (Record Keeping), have been revised to reflect compliance monitoring requirements be performed once per day instead of once per shift.

D.1.6 Visible Emissions Notations

---

- (a) Visible emission notations of the stack exhausts of all facilities listed under Section D.1 shall be performed once per **shift day** during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.

D.1.7 Parametric Monitoring

---

The Permittee shall record the total static pressure drop across the baghouses used in conjunction with each of the storage silos, at least once per **shift day** when the storage silos are in operation and venting to the atmosphere. When for any one reading, the pressure drop across the baghouse is outside the normal range of 0.5 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.

D.1.10 Record Keeping Requirements

---

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain records of the **daily** visible emission notations the stack exhausts of all facilities listed under Section D.1.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain once per **shift day** records of the total static pressure drop during normal operation when venting to the atmosphere.

## Indiana Department of Environmental Management Office of Air Quality

### Technical Support Document (TSD) for a Federally Enforceable State Operating Permit (FESOP) Renewal

#### Source Background and Description

**Source Name:** New NGC, Inc. d/b/a National Gypsum Company  
**Source Location:** 1325 East Maple Street, Lot 8 - Lintner Industrial Park  
 Rensselaer, Indiana 47978  
**County:** Jasper  
**SIC Code:** 3275  
**Operation Permit No.:** F073-16714-00033  
**Permit Reviewer:** Linda Quigley/EVP

The Office of Air Quality (OAQ) has reviewed a FESOP renewal application from New NGC, Inc. d/b/a National Gypsum Company relating to the operation of a stationary gypsum wallboard related product manufacturing operation. New NGC, Inc. d/b/a National Gypsum Company was issued FESOP 073-9983-00033 on December 4, 1998.

#### Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) One (1) ready-mix joint compound and dry powder product storage facility with a total maximum throughput of 97 tons of raw material per hour, and consisting of the following equipment:
  - (1) Six (6) storage silos, each separately controlled by a baghouse, utilizing pneumatic loading, and consisting of the following:
    - (A) one (1) limestone silo, identified as 1900, with a maximum throughput of 27 tons of limestone per hour, with a storage capacity of 33,000 cubic feet, exhausting at one (1) silo vent, identified as SV1,
    - (B) one (1) plaster of paris silo, identified as 1925, with a maximum throughput of 20 tons of plaster of paris per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV3,
    - (C) one (1) talc silo, identified as 1905, with a maximum throughput of 14 tons of talc per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV4,
    - (D) one (1) clay silo, identified as 1920, with a maximum throughput of 24 tons of clay per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV5,
    - (E) one (1) mica silo, identified as 1910, with a maximum throughput of 6 tons of mica per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV6, and
    - (F) one (1) perlite silo, identified as 1915, with a maximum throughput of 6 tons of perlite per hour, with a storage capacity of 8,200 cubic feet, exhausting at one (1) silo vent, identified as SV7.
- (b) One (1) Ready-Mix (Liquid) Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:

- (1) Two (2) silo weigh receiving bins (ID Nos. PL1 and PL2) with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM1 and RM2), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins, (ID Nos. PL3 and PL4) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM3 and RM4), which exhaust inside the building;
  - (3) Two (2) mixers/limestone scale hoppers (ID Nos. PL5 and PL6) with a maximum throughput of 3,000 gallons per hour, controlled by two (2) baghouses (ID Nos. RM5 and RM6), which exhaust inside the building; and
  - (4) Two (2) bulk bag dumping stations (ID Nos. PL7 and PL8) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM7 and RM8), which exhaust inside the building.
- (c) One (1) Dry Powder Product Line, with a maximum throughput of 15 tons per hour, consisting of the following equipment:
- (1) Two (2) silo weigh receiving bins (ID Nos. PL9 and PL10), with a maximum throughput of 15 tons per hour, controlled by two (2) baghouses (ID Nos. RM9 and RM10), which exhaust inside the building;
  - (2) Two (2) dry additive/short weigh receiving bins (ID Nos. PL11 and PL12) with a maximum throughput of 10 tons per hour, controlled by two (2) baghouses (ID Nos. RM11 and RM12), which exhaust inside the building;
  - (3) Two (2) mixers/surge bins (ID Nos. PL13 and PL14) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM13), which exhausts inside the building;
  - (4) One (1) bag cleaner (ID No. PL15) with a maximum throughput of 12 tons per hour, controlled by one (1) baghouse (ID No. RM14), which exhausts inside the building; and
  - (5) One (1) bulk bag dumping station (ID No. PL16) with a maximum throughput of 10 tons per hour, controlled by one (1) baghouse (ID No. RM15), which exhausts inside the building.
- (d) One (1) Joint Tape Process line consisting of one (1) buffer, one (1) slitter, and one (1) rewriter, each with a maximum capacity of 2000 pounds of joint tape per hour, controlled by the Joint Tape Baghouse (SV8), which exhausts inside the building.

### **Unpermitted Emission Units and Pollution Control Equipment**

There are no unpermitted facilities operating at this source during this review process.

### **Insignificant Activities**

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Propane or liquified petroleum gas, or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) Btu per hour;
- (b) Closed loop heating and cooling systems;
- (c) Paved and unpaved roads and parking lots with public access;
- (d) Equipment used to collect any material that might be

released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separator, tanks, and fluid handling equipment; and

### Existing Approvals

The source has been operating under previous approvals including, but not limited to, the following:

- (a) F073-9983-00033, issued on December 4, 1998;
- (b) AA073-11626-00033, issued on January 26, 2000;
- (c) First Permit Reopening 073-13055-00033, issued on December 10, 2001; and
- (d) AA073-15473-00033, issued on January 28, 2002.

All conditions from previous approvals were incorporated into this FESOP renewal except the following:

- (a) Frequencies for parametric monitoring and visible emissions notations have been changed to once per shift.

*Reason changed:* Compliance monitoring conditions are in the permit in order to ensure continuous compliance with the requirements. Control device failure can occur suddenly; therefore monitoring of relevant operational parameters should be more frequent than weekly or even daily in such cases where a source operates more than one shift per day.

The OAQ believes that changing parametric monitoring and visible emissions notations to once per operating shift is necessary for the covered control device to assure the proper operation of the equipment. Therefore, the requirements to perform parametric monitoring and visible emissions notations have been changed from daily to once per shift.

- (b) All construction conditions from previously issued permits.

*Reason changed:* All facilities previously permitted have already been constructed; therefore, the construction conditions are no longer necessary as part of the operating permit. Any facilities that were previously permitted but have not yet been constructed would need new pre-construction approval before beginning construction.

- (c) All conditions related to the one (1) limestone storage silo, identified as SV2, have been removed.

*Reason changed:* The one (1) limestone storage silo, with a maximum capacity of 27 tons of limestone per hour, identified as SV2, has not and will not be constructed.

- (d) Pressure drop range of the baghouses controlling the six (6) storage silos has been changed from 2.0 - 6.0 inches of water to 0.5 - 6.0 inches of water.

*Reason changed:* The Permittee submitted documentation to the effect that the baghouses will operate normally in the range of 0.5 - 6.0 inches of water.

### Enforcement Issue

There are no enforcement actions pending.



## Recommendation

The staff recommends to the Commissioner that the FESOP renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP renewal application for the purposes of this review was received on January 21, 2003. Additional information was received on December 10, 2003 and January 7, 2004.

There was no notice of completeness letter mailed to the source.

## Emission Calculations

See Appendix A of this document for detailed emissions calculations, pages one (1) through five (5).

## Unrestricted Potential Emissions

This table reflects the unrestricted potential emissions of the source, excluding the emission limits that were contained in the previous FESOP.

Pollutant	Potential To Emit (tons/year)
PM	greater than 250
PM-10	greater than 250
SO <sub>2</sub>	less than 100
VOC	less than 100
CO	less than 100
NO <sub>x</sub>	less than 100

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Potential To Emit (tons/year)
Vinyl Acetate	less than 10
Acetaldehyde	less than 10
Ethylene Glycol	less than 10
Formaldehyde	less than 10
TOTAL	less than 25

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of PM10 is equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) Fugitive Emissions  
Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive emissions are not counted toward determination of PSD and Emission Offset applicability.

**Potential to Emit After Issuance**

The source, issued a FESOP on December 4, 1998, has opted to remain a FESOP source, rather than apply for a Part 70 Operating Permit. The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered enforceable only after issuance of this Federally Enforceable State Operating Permit and only to the extent that the effect of the control equipment is made practically enforceable in the permit. Since the source has not constructed any new emission units, the source's potential to emit is based on the emission units included in the original FESOP. (F073-9983-00033; issued on December 4, 1998).

Process/facility	Potential to Emit (tons/year)							
	PM	PM-10	SO <sub>2</sub>	VOC	CO	NO <sub>x</sub>	Single HAP	Total HAPs
Six (6) storage silos (SV1, SV3 - SV7) <sup>1</sup>	9.46	9.46	--	--	--	--	--	--
One (1) Joint Tape Process (SV8) <sup>1</sup>	0.30	0.30	--	--	--	--	--	--
two (2) silo weigh receiving bins (PL1 and PL2), two (2) dry additive/short weigh receiving bins (PL3 and PL4), two (2) mixers/limestone scale hoppers (PL5 and PL6), two (2) bulk bag dumping stations (PL7 and PL8)	136.37 <sup>3</sup>	50.87 <sup>2</sup>	--	4.14	--	--	0.58	1.025
two (2) silo weigh receiving bins (PL9 and PL10), two (2) dry additive/short weigh receiving bins (PL11 and PL12), two (2) mixers/surge bins (PL13 and PL14), one (1) bag cleaner (PL15), one (1) bulk bag dumping station (PL16)	102.87 <sup>3</sup>	38.38 <sup>2</sup>	--	4.14	--	--	0.58	1.025
<b>Total Emissions</b>	<b>249.00</b>	<b>99.00</b>	<b>--</b>	<b>8.28</b>	<b>--</b>	<b>--</b>	<b>1.15</b>	<b>2.05</b>

1. controlled PM/PM10 emissions based on baghouses each with 99.9% efficiency.
2. maximum allowable PM10 emissions to render the requirements of 326 IAC 2-7 not applicable.
3. maximum allowable PM emissions to render the requirements of 326 IAC 2-2 not applicable.
4. VOC and HAP emissions represent uncontrolled potential to emit.

### County Attainment Status

The source is located in Jasper County.

Pollutant	Status
PM-10	attainment
SO <sub>2</sub>	attainment
NO <sub>2</sub>	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Jasper County has been designated as attainment or unclassifiable for ozone. Therefore, VOC emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2. See the State Rule Applicability for the source section.
- (b) Jasper County has been classified as attainment or unclassifiable for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2. See the State Rule Applicability for the source section.

### Federal Rule Applicability

- (a) The four (4) dry additive receiving bins (PL3, PL4, PL11 and PL12) and four (4) silo weigh receiving bins (PL1, PL2, PL9 and PL10) are not subject to the New Source Performance Standard 326 IAC 12, 40 CFR 60.670 through 60.676, Subpart OOO, because this plant does not crush or grind nonmetallic minerals.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this source.
- (c) The requirements of Section 112(j) of the Clean Air Act (40 CFR Part 63.50 through 63.56) are not applicable to this source because the source has a potential to emit of less than 10 tons per year of a single HAP and less than 25 tons per year of the combination of HAPs.

### State Rule Applicability - Entire Source

#### 326 IAC 1-5-2 (Emergency Reduction Plans)

This source submitted an Emergency Reduction Plan (ERP) in accordance with 326 IAC 1-5-2 on June 25, 2003.

#### 326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

This source, constructed in 1998, is not subject to the requirements of these rules. As shown in the Potential to Emit After Issuance table on pages 4 and 5 above, the allowable emissions of all regulated pollutants, except PM, are less than 100 tons per year after application of all federally enforceable emission limits. The baghouses for controlling PM emissions have always been in operation since the plant started operation and shall continue to be in operation at all times in order to limit PM emissions to less than 250 tons per twelve (12) consecutive month period.

Compliance with the following is necessary to render PSD not applicable:

The baghouses controlling the six (6) storage silos (SV1, SV3 thru SV7), the one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line, shall be in operation at all times and the PM emissions from the six (6) storage silos (SV1, SV3 thru SV7), the one (1) ready-mix (liquid) product line, the one (1) dry powder product line, and the one (1) joint tape process line shall be limited as follows:

Emission Units/Process	Limited Particulate Matter (lb/hr)
six (6) storage silos	2.16
one (1) ready-mix (liquid) product line	31.13
one (1) dry powder product line	23.49
one (1) joint tape process line	0.07

These emission limits are necessary to limit the total source wide PM emissions to less than 250 tons per twelve consecutive month period. Compliance with these limits shall render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration), not applicable.

326 IAC 2-6 (Emission Reporting)

This source is located in Jasper County which is not one of the specifically listed counties, nor does this FESOP source have the potential to emit CO, VOC, NO<sub>x</sub>, PM<sub>10</sub> (including fugitive emissions), or SO<sub>2</sub> in amounts at or exceeding one-hundred (100) tons per year. Therefore, the requirements of 326 IAC 2-6 do not apply to the source.

326 IAC 2-8-4 (FESOP)

This source is subject to 326 IAC 2-8-4 (FESOP). Pursuant to this rule, the following limits shall apply:

- (a) The baghouses for the six (6) storage silos (SV1, SV3 - SV7) shall be in operation at all times and the PM<sub>10</sub> emissions from all silos combined shall be limited to less than 2.16 pounds per hour.
- (b) The baghouse for the one (1) joint tape process (SV8) shall be in operation at all times and the PM<sub>10</sub> emissions shall be limited to less than 0.07 pounds per hour.
- (c) The baghouses for the two (2) silo weigh receiving bins (PL1 and PL2), two (2) dry additive/short weigh receiving bins (PL3 and PL4), two (2) mixers/limestone scale hoppers (PL5 and PL6), two (2) bulk bag dumping stations (PL7 and PL8) shall be in operation at all times and the PM<sub>10</sub> emissions shall be limited to less than 11.61 pounds per hour.
- (d) The baghouses for the two (2) silo weigh receiving bins (PL9 and PL10), two (2) dry additive/short weigh receiving bins (PL11 and PL12), two (2) mixers/surge bins (PL13 and PL14), one (1) bag cleaner (PL15), and one (1) bulk bag dumping station (PL16) shall be in operation at all times and the PM<sub>10</sub> emissions shall be limited to less than 8.76 pounds per hour.

Therefore, the requirements of 326 IAC 2-7 do not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 6-4 (Fugitive Dust Emissions)

This source is subject to 326 IAC 6-4 for fugitive dust emissions. Pursuant to 326 IAC 6-4 (Fugitive Dust Emissions), fugitive dust shall not be visible crossing the boundary or property line of a source. Observances of visible emissions crossing property lines may be refuted by factual data expressed in 326 IAC 6-4-2(1), (2) or (3).

326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations)

This source is subject to 326 IAC 6-5 for fugitive particulate matter emissions because it was constructed in 1998, and pursuant to 326 IAC 6-5, for any new source which has not received all the necessary preconstruction approvals before December 13, 1985, a fugitive dust control plan must be submitted, reviewed and approved. The fugitive dust control plan for this source includes the following:

- (a) Fugitive particulate matter emissions from paved and unpaved roads shall be controlled by one or more of the following methods:
  - (1) Fugitive dust suppression on paved and unpaved roads will be accomplished through wet suppression and/or other means based on the service conditions at the site.
  - (2) If necessary a water truck will be employed to supply water to the working surfaces where fugitive dusts may be generated.
- (b) Fugitive particulate matter emissions from material handling shall be controlled by one or more of the following methods:
  - (1) Materials are transferred pneumatically from the silos to the mixers. The silos are controlled by baghouses that will be maintained and inspected per the manufacturer's recommendations.
  - (2) The mixers, which are located in the building, are controlled by baghouses that emit to the interior of the building. All baghouses will be subject to EPA reference method 22 for visible emissions each day that they are operated.
  - (3) Inspection and maintenance procedures recommended by the manufacturer of these baghouses will be followed and modified if needed.

**State Rule Applicability - Individual Facilities**

**326 IAC 2-4.1-1 (New Source Toxics Control)**

Pursuant to 326 IAC 2-4.1-1 (New Source Toxics Control), any new process or production unit, which in and of itself emits or has the PTE 10 tons per year of any HAP or 25 tons per year of the combination of HAPs, and is constructed or reconstructed after July 27, 1997, must be controlled using technologies consistent with Maximum Achievable Control Technology (MACT). No facilities with an uncontrolled PTE of 10 tons per year of any single HAP and 25 tons per year of the combination of HAPs have been constructed or reconstructed since July 27, 1997. Therefore, the requirements of 326 IAC 2-4.1-1 (New Source Toxics Control) do not apply to this source.

**326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)**

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes) the particulate from the processes listed in the table below shall be limited by the following:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

Emission Unit	Process Weight Rate (ton/hr)	326 IAC 6-3-2 Particulate Allowable (lb/hr)	Controlled/Limited Particulate Emissions (lb/hr)	In Compliance?
one(1) limestone silo (SV1)	27.00	37.31	0.10	Y
one (1) plaster of paris silo (SV3)	20.00	30.51	0.41	Y
one (1) talc silo (SV4)	14.00	24.03	0.41	Y
one (1) clay silo (SV5)	24.00	34.48	0.41	Y
one (1) mica silo (SV6)	6.00	13.62	0.41	Y
one (1) perlite silo (SV7)	6.00	13.62	0.41	Y
joint tape process: one(1) buffer, one (1) slitter, one (1) rewinder (SV8)	1.00	4.10	0.08	Y
silos receiving bins (PL1 and PL2)	15.00	25.16	0.12	Y
dry additive/short weigh receiving bins (PL3 and PL4)	10.00	19.18	0.20	Y
bulk bag dumping stations (PL7 and PL8)	10.00	19.18	0.11	Y
silos weigh receiving bins (PL9 and PL10)	15.00	25.16	0.30	Y
dry additive/short weigh receiving bins (PL11 and PL12)	10.00	19.18	0.20	Y
mixers/surge bins	12.00	21.67	0.17	Y

Emission Unit	Process Weight Rate (ton/hr)	326 IAC 6-3-2 Particulate Allowable (lb/hr)	Controlled/Limited Particulate Emissions (lb/hr)	In Compliance?
(PL13 and PL14)				
bag cleaner (PL15)	12.00	21.67	0.17	Y
bulk bag dumping station (PL16)	10.00	19.18	0.05	Y

The baghouses shall be in operation at all times the emission units are in operation, in order to comply with these limits.

**326 IAC 8-1-6 (New Facilities: General Reduction Requirements)**

Pursuant to 326 IAC 8-1-6 (New Facilities General Reduction Requirements), new facilities which have potential VOC emissions of 25 tons or more per year, located anywhere in the state, and which are not otherwise regulated by other provisions of this article (326 IAC 8), shall reduce VOC emissions using best available control technology (BACT). The two (2) mixers (PL5 and PL6) have unrestricted potential VOC emissions of less than 25 tons per year (see page 4 of 5, TSD App. A), therefore, the requirements of 326 IAC 8-1-6 do not apply.

**326 IAC 8-4-3 (Petroleum Liquid Storage Facilities)**

The source is not applicable to 326 IAC 8-4-3 (Petroleum Liquid Storage Facilities) because all VOC storage vessels at the source have capacities less than 39,000 gallons.

**Testing Requirements**

Pursuant to FESOP 073-9983-00033, the source conducted VOC testing on July 7, 1999. Testing was conducted in order to determine if the Permittee was in compliance with a VOC flash off factor of 5.0% on the ready-mix line. Although the final test report has not been issued, the test results have been preliminarily accepted. At this time the source will not be required to re-test. Should the final test report yield unacceptable results or recommend additional testing, the permit will be reopened at that time.

**Compliance Requirements**

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

1. The six (6) storage silos have applicable compliance monitoring conditions as specified below:
  - (a) Visible emissions notations of the six (6) storage silos stack exhausts shall be performed once per shift during normal daylight operations when the storage silos are in operation. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.
  - (b) The Permittee shall record the total static pressure drop across the baghouses used in conjunction with each of the storage silos, at least once per shift when the storage silos are in operation and venting to the atmosphere. When for any one reading, the pressure drop across the baghouse is outside the normal range of 0.5 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.
  - (c) An inspection shall be performed each calendar quarter of all bags controlling the six (6) storage silos when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.
  - (d) In the event that a bag failure has been observed:
    - (1) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit. If operations continue after bag failure is observed and it will be 10 days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.

- (2) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
2. The Joint Tape Process line, the Ready-Mix (Liquid) Product Line and the Dry Powder Product Line have applicable compliance monitoring conditions as specified below:
  - (a) Visible emissions notations of the joint tape process line, the ready-mix liquid product line and the dry powder product line stack exhausts shall be performed once per shift during normal daylight operations when the ready-mix liquid product line and the dry powder product line are in operation. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.
  - (b) The Permittee shall record the total static pressure drop across each of the baghouses used in conjunction with joint tape process line, the ready-mix liquid product line and the dry powder product line, at least once per shift when the joint tape process line, the ready-mix liquid product line or the dry powder product line are in operation and venting to the atmosphere. When for any one reading, the pressure drop across the baghouse is outside the normal range of 2.0 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.
  - (c) An inspection shall be performed each calendar quarter of all bags controlling the joint tape process line, the ready-mix liquid product line and the dry powder product line when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.

- (d) In the event that a bag failure has been observed:
- (1) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit. If operations continue after bag failure is observed and it will be 10 days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.
  - (2) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

These monitoring conditions are necessary because the baghouses for the storage silos, joint tape process line, the ready-mix liquid product line and the dry powder product line must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations), 326 IAC 2-8 (FESOP) and 326 IAC 2-2 (Prevention of Significant Deterioration).

## Conclusion

The operation of this stationary gypsum wallboard related product manufacturing operation shall be subject to the conditions of the attached proposed FESOP No.: F073-16714-00033.

**Appendix A: Summary of Emission Calculations**

**Company Name:** New NGC, Inc. d/b/a National Gypsum Company  
**Address City IN Zip:** 1325 East Maple Street, Lot 8 - Lintner Industrial Park, Rensselaer, IN 28211  
**FESOP:** 073-16714  
**Plt ID:** 073-00033  
**Reviewer:** LQ/EVP  
**Application Rec.:** January 21, 2003

**Uncontrolled Potential Emissions (tons/year)**

Emissions Generating Activity

Pollutant	Ready Mix VOC emissions tons per year	Ready Mix/Dry P. PM emissions tons per year	Ready Mix HAP Emission tons per year	Silo and Joint Tape PM emissions tons per year	<b>TOTAL</b> tons per year
PM	0.00	69,394.22	0.00	976.11	70,370.33
PM10	0.00	69,394.22	0.00	976.11	70,370.33
SO2	0.00	0.00	0.00	0.00	0.00
NOx	0.00	0.00	0.00	0.00	0.00
VOC	8.28	0.00	0.00	0.00	8.28
CO	0.00	0.00	0.00	0.00	0.00
total HAPs	0.00	0.00	2.05	0.00	2.05
worst case single HAP	0.00	0.00	1.15	0.00	1.15

Total emissions based on rated capacity at 8,760 hours/year, before control.

**Controlled Potential Emissions (tons/year)**

Emissions Generating Activity

Pollutant	Ready Mix VOC tons per year	Ready Mix/Dry P. PM emissions tons per year	Ready Mix HAP Emission tons per year	Silo and Joint Tape PM emissions tons per year	<b>TOTAL</b> tons per year
PM	0.00	6.94	0.00	9.76	16.70
PM10	0.00	6.94	0.00	9.76	16.70
SO2	0.00	0.00	0.00	0.00	0.00
NOx	0.00	0.00	0.00	0.00	0.00
VOC	8.28	0.00	0.00	0.00	8.28
CO	0.00	0.00	0.00	0.00	0.00
total HAPs	0.00	0.00	2.05	0.00	2.05
worst case single HAP	0.00	0.00	1.15	0.00	1.15

Total emissions based on rated capacity at 8,760 hours/year, before control.

**Particulate Emissions from Ready-Mix Joint Compound and Dry Powder Product Lines**

**Company Name:** New NGC, Inc. d/b/a National Gypsum Company  
**Address City IN Zip:** 1325 East Maple Street, Lot 8 - Lintner Industrial Park, Rensselaer, IN 28211  
**FESOP:** 073-16714  
**Plt ID:** 073-00033  
**Reviewer:** LQ/EVP  
**Application Rec.:** January 21, 2003

Uncontrolled Emissions (tons/year)						
<b>A. Baghouses</b>						
Baghouse I.D.	Process	No. of Units	Grain Loading per Standard Cubic Foot of Outlet Air	Gas or Air Flow Rate (acfm)	Control Efficiency	Total (tons/year*)
RM1 and RM2	Silo Weigh Receiving Bins	2	0.02000	347.0	99.99%	5,210.95
RM3 and RM4	Dry Additive Bins/Short Weigh Receiving Bins	2	0.02000	581.0	99.99%	8,724.96
RM5 and RM6	Mixers/Limestone Scale Hoppers	2	0.02000	755.0	99.99%	11,337.94
RM7	Bulk Bag Dumping	1	0.02000	320.0	99.99%	2,402.74
RM8	Bulk Bag Dumping	1	0.02000	320.0	99.99%	2,402.74
RM9 and RM10	Silo Weigh Receiving Bins	2	0.02000	877.0	99.99%	13,170.03
RM11 and RM12	Dry Additive Bins/Short Weigh Receiving Bins	2	0.02000	581.0	99.99%	8,724.96
RM13	Mixers/Surge Bins	1	0.02000	1000.0	99.99%	7,508.57
RM14	Bag Cleaner	1	0.02000	1000.0	99.99%	7,508.57
RM15	Bulk Bag Dumping	1	0.02000	320.0	99.99%	2,402.74
Total Emissions Based on Rated Capacity at 8,760 Hours/Year						<b>69,394.22</b>
Controlled Emissions (tons/year)						
<b>A. Baghouses</b>						
Baghouse I.D.	Process	No. of Units	Grain Loading per Standard Cubic Foot of Outlet Air	Gas or Air Flow Rate (acfm)	Control Efficiency	Total (tons/year*)
RM1 and RM2	Silo Weigh Receiving Bins	2	0.02000	347.0	99.99%	0.52
RM3 and RM4	Dry Additive Bins/Short Weigh Receiving Bins	2	0.02000	581.0	99.99%	0.87
RM5 and RM6	Mixers/Limestone Scale Hoppers	2	0.02000	755.0	99.99%	1.13
RM7	Bulk Bag Dumping	1	0.02000	320.0	99.99%	0.24
RM8	Bulk Bag Dumping	1	0.02000	320.0	99.99%	0.24
RM9 and RM10	Silo Weigh Receiving Bins	2	0.02000	877.0	99.99%	1.32
RM11 and RM12	Dry Additive Bins/Short Weigh Receiving Bins	2	0.02000	581.0	99.99%	0.87
RM13	Mixers/Surge Bins	1	0.02000	1000.0	99.99%	0.75
RM14	Bag Cleaner	1	0.02000	1000.0	99.99%	0.75
RM15	Bulk Bag Dumping	1	0.02000	320.0	99.99%	0.24
Total Emissions Based on Rated Capacity at 8,760 Hours/Year						<b>6.94</b>

Uncontrolled:

Baghouse (tons/year\*) = No. Units \* Loading (grains/ascf) \* Gas or Air Flow Rate (acfm) \* 1 lb/7,000 grains \* 60 min/hr \* 8760 hr/yr \* 1 ton/2,000 lbs \*(1/(1-Control Efficiency))

Controlled:

Baghouse (tons/year\*) = No. Units \* Loading (grains/ascf) \* Gas or Air Flow Rate (acfm) \* 1 lb/7,000 grains \* 60 min/hr \* 8760 hr/yr \* 1 ton/2,000 lbs

Baghouse control efficiency based on data supplied by the applicant.

**HAP Emission Calculations**

**Company Name:** New NGC, Inc. d/b/a National Gypsum Company  
**Address City IN Zip:** 1325 East Maple Street, Lot 8 - Lintner Industrial Park, Rensselaer, IN 28211  
**FESOP:** 073-16714  
**Pit ID:** 073-00033  
**Reviewer:** LQ/EVP  
**Application Rec.:** January 21, 2003

Material	Density (Lb/Gal)	Gal of Mat (gal/unit)	Maximum (unit/hour)	Flash-Off Percentage	Weight % Vinyl Acetate	Weight % Formaldehyde	Weight % Acetaldehyde	Weight % Ethylene Glycol	Vinyl Acetate Emissions (ton/yr)	Formaldehyde Emissions (ton/yr)	Acetaldehyde Emissions (ton/yr)	Ethylene Glycol Emissions (ton/yr)
Confidential Information -1	10.01	<b>175.45</b>	<b>1.00</b>	<b>5.00%</b>	0.30%	0.05%	0.03%	0.00%	1.15	0.19	0.12	0.00
Confidential Information -2	9.33	<b>143.5</b>	<b>1.00</b>	<b>5.00%</b>	0.00%	0.00%	0.00%	0.20%	0.00	0.00	0.00	0.59

Single HAP Potential Emissions **1.15      0.19      0.12      0.59**

Total HAP Potential Emissions **2.05**

**METHODOLOGY**

HAPS emission rate (tons/yr) = Density (lb/gal) \* Gal of Material (gal/unit) \* Maximum (unit/hr) \* Weight % HAP \* 8760 hrs/yr \* 1 ton/2000 lbs\*flash-off percentage

Liquid mixing agents are confidential information.

Flash-off percentage based on information determined by the applicant.

**Appendix A: Emission Calculations  
VOC and Particulate  
From Ready Mix line**

**Company Name:** New NGC, Inc. d/b/a National Gypsum Company  
**Address City IN Zip:** 1325 East Maple Street, Lot 8 - Lintner Industrial Park, Rensselaer, IN 28211  
**FESOP:** 073-16714  
**Plt ID:** 073-00033  
**Reviewer:** LQ/EVP  
**Application Rec.:** January 21, 2003

State Potential Emissions (uncontrolled):																			
Material (as applied)	Process	Density (Lb/Gal)	Weight % Volatile (H2O& Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Vol (solids)	Gal of Mat (gal/unit)	Maximum (unit/hour)	Flash-off Percentage	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential ton/yr	lb VOC /gal solids	Transfer Efficiency	
Confidential Information -1	Ready-Mix	10.01	40.00%	38.00%	2.00%	45.58%	0.00%	175.45	1.00	5.00%	0.4	0.20	1.76	42.15	7.69	0.00	n/a	100.00%	
Confidential Information -2	Ready-Mix	9.33	0.20%	0.00%	0.20%	0.00%	0.00%	143.5	1.00	5.00%	0.0	0.02	0.13	3.21	0.59	0.00	n/a	100.00%	
<b>Potential Emissions:</b>													<b>1.89</b>	<b>45.36</b>	<b>8.28</b>	<b>0.00</b>			
Controlled Emissions:																			
												Control Efficiency:		Controlled VOC lbs per Hour	Controlled VOC lbs per Day	Controlled VOC tons per Year	Controlled PM tons/yr		
												VOC	PM						
<b>Total Controlled Emissions:</b>												0.00%	95.00%	<b>1.89</b>	<b>45.36</b>	<b>8.28</b>	<b>0.00</b>		

Methodology:

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) \* Weight % Organics) / (1-Volume % water)  
 Pounds of VOC per Gallon Coating = (Density (lb/gal) \* Weight % Organics)  
 Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) \* Gal of Material (gal/unit) \* Maximum (units/hr)\*flash-off percentage  
 Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) \* Gal of Material (gal/unit) \* Maximum (units/hr) \* (24 hr/day)\* flash off percentage  
 Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) \* Gal of Material (gal/unit) \* Maximum (units/hr) \* (8760 hr/yr) \* (1 ton/2000 lbs)\* flash-off percentage  
 Particulate Potential Tons per Year = (units/hour) \* (gal/unit) \* (lbs/gal) \* (1- Weight % Volatiles) \* (1-Transfer efficiency) \*(8760 hrs/yr) \*(1 ton/2000 lbs)  
 Pounds VOC per Gallon of Solids = (Density (lbs/gal) \* Weight % organics) / (Volume % solids) \* Transfer Efficiency  
 Total = Worst Coating + Sum of all solvents used  
 Controlled emission rate = uncontrolled emission rate \* (1 - control efficiency)  
 Liquid Mix agents are confidential information.

**Appendix A: Particulate Emissions from Silo and Joint Tape Process Baghouses**

**Company Name:** New NGC, Inc. d/b/a National Gypsum Company  
**Address City IN Zip:** 1325 East Maple Street, Lot 8 - Lintner Industrial Park, Rensselaer, IN 28211  
**FESOP:** 073-16714  
**Plt ID:** 073-00033  
**Reviewer:** LQ/EVP  
**Application Rec.:** January 21, 2003

<b>Uncontrolled Emissions (tons/year)</b>					
<b>A. Baghouses</b>					
Process	No. of Units	Grain Loading per Standard Cubic Foot of Outlet Air	Gas or Air Flow Rate (acfm)	Control Efficiency	Total (tons/year*)
Silo 1	1	0.00400	3000.0	99.00%	45.05
Silos 3 through 7	5	0.04000	1200.0	99.00%	901.03
Joint Tape (SV8)	1	0.00100	8000.0	99.00%	30.03
Total Emissions Based on Rated Capacity at 8,760 Hours/Year					<b>976.11</b>
<b>Controlled Emissions (tons/year)</b>					
<b>A. Baghouses</b>					
Process	No. of Units	Grain Loading per Standard Cubic Foot of Outlet Air	Gas or Air Flow Rate (acfm)	Control Efficiency	Total (tons/year*)
Silo 1	1	0.00400	3000.0	99.00%	0.45
Silos 3 through 7	5	0.04000	1200.0	99.00%	9.01
Joint Tape (SV8)	1	0.00100	8000.0	99.00%	0.30
Total Emissions Based on Rated Capacity at 8,760 Hours/Year					<b>9.76</b>

Uncontrolled:

Baghouse (tons/year\*) = No. Units \* Loading (grains/ascf) \* Gas or Air Flow Rate (acfm) \* 1 lb/7,000 grains \* 60 min/hr \* 8760 hr/yr \* 1 ton/2,000 lbs \*(1/(1-Control Efficiency))

Controlled:

Baghouse (tons/year\*) = No. Units \* Loading (grains/ascf) \* Gas or Air Flow Rate (acfm) \* 1 lb/7,000 grains \* 60 min/hr \* 8760 hr/yr \* 1 ton/2,000 lbs

Baghouse control efficiency based on data supplied by the applicant.