



Joseph E. Kernan  
Governor

Lori F. Kaplan  
Commissioner

September 1, 2004

100 North Senate Avenue  
P.O. Box 6015  
Indianapolis, Indiana 46206-6015  
(317) 232-8603  
(800) 451-6027  
www.in.gov/idem

TO: Interested Parties / Applicant

RE: Brooks Construction Company / 003-19156-05190

FROM: Paul Dubenetzky  
Chief, Permits Branch  
Office of Air Quality

### Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures  
FNPER.dot 9/16/03



Joseph E. Kernan  
Governor

Lori F. Kaplan  
Commissioner

100 North Senate Avenue  
P.O. Box 6015  
Indianapolis, Indiana 46206-6015  
(317) 232-8603  
(800) 451-6027  
www.in.gov/idem

**FEDERALLY ENFORCEABLE STATE  
OPERATING PERMIT (FESOP) RENEWAL  
OFFICE OF AIR QUALITY**

**Brooks Construction Company, Inc.  
5536 Hoagland Road  
Poe, IN 46745  
(Portable)**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

**The Permittee must comply with all conditions of this permit. Noncompliance with any provision of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; and denial of a permit renewal application. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.**

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F003-19156-05190	
Issued by: Original Signed by Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date: September 1, 2004 Expiration Date: September 1, 2009

**SECTION A SOURCE SUMMARY ..... 5**

- A.1 General Information [326 IAC 2-8-3(b)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]
- A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(l)]
- A.4 FESOP Applicability [326 IAC 2-8-2]
- A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

**SECTION B GENERAL CONDITIONS ..... 7**

- B.1 Permit No Defense [IC 13]
- B.2 Definitions [326 IAC 2-8-1]
- B.3 Permit Term [326 IAC 2-8-4(2)][326 IAC 2-1.1-9.5]
- B.4 Enforceability [326 IAC 2-8-6]
- B.5 Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3(h)]
- B.6 Severability [326 IAC 2-8-4(4)]
- B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]
- B.8 Duty to Provide Information[326 IAC 2-8-4(5)(E)]
- B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]
- B.10 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]
- B.11 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]
- B.12 Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]
- B.13 Emergency Provisions [326 IAC 2-8-12]
- B.14 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]
- B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)][326 IAC 2-8-7(a)][326 IAC 2-8-8]
- B.16 Permit Renewal [326 IAC 2-8-3(h)]
- B.17 Permit Amendment or Revision [326 IAC 2-8-10][326 IAC 2-8-11.1]
- B.18 Operational Flexibility [326 IAC 2-8-15][326 IAC 2-8-11.1]
- B.19 Permit Revision Requirement [326 IAC 2-8-11.1]
- B.20 Inspection and Entry [326 IAC 2-8-5(a)(2)][IC13-14-2-2][IC 13-17-3-2][IC13-30-3-1]
- B.21 Transfer of Ownership or Operational Control [326 IAC 2-8-10]
- B.22 Annual Fee Payment [326 IAC 2-7-19][326 IAC 2-8-4(6)] [326 IAC 2-8-16] [326 IAC 2-1.1-7]

**SECTION C SOURCE OPERATION CONDITIONS ..... 16**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]
- C.2 Overall Source Limit [326 IAC 2-8]
- C.3 Opacity [326 IAC 5-1]
- C.4 Open Burning [326 IAC 4-1][IC 13-17-9]
- C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]
- C.6 Fugitive Dust Emissions [326 IAC 6-4]
- C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]
- C.8 Operation of Equipment [326 IAC 2-8-5(a)(4)]
- C.9 Stack Height [326 IAC 1-7]
- C.10 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61 Subpart M]

**Testing Requirements [326 IAC 2-8-4(3)]**

- C.11 Performance Testing [326 IAC 3-6]

**Compliance Requirements [326 IAC 2-1.1-11]**

- C.12 Compliance Requirements [326 IAC 2-1.1-11]

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- C.13 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]
- C.14 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]

- C.15 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11]  
[326 IAC 2-8-4(3)][326 IAC 2-8-5(1)]

**Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5]**

- C.16 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]
- C.17 Compliance Response Plan -Preparation, Implementation, Records, and Reports  
[326 IAC 2-8-4][326 IAC 2-8-5]
- C.18 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]  
[326 IAC 2-8-5]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

- C.19 General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5]
- C.20 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

**Portable Source Requirement**

- C.21 Relocation of Portable Sources [326 IAC 2-14-4]

**Stratospheric Ozone Protection**

- C.22 Compliance with 40 CFR 82 and 326 IAC 22-1

**SECTION D.1 FACILITY OPERATION CONDITIONS**

**One (1) Drum Mix Aggregate Dryer and Conveying ..... 24**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.1.1 General Provisions Relating to NSPS [326 IAC 12-1][40 CFR Part 60, Subpart A]
- D.1.2 Particulate Matter (PM) [326 IAC 12][40 CFR 60.90, Subpart I]
- D.1.3 Particulate Matter (PM) [326 IAC 6-1-2][326 IAC 2-2]
- D.1.4 Particulate Matter 10 Microns (PM-10) [326 IAC 2-8-4][326 IAC 2-2]  
[326 IAC 2-3]
- D.1.5 Opacity [326 IAC 12] [40 CFR 60.90, Subpart I]
- D.1.6 Sulfur Dioxide (SO<sub>2</sub>) [326 IAC 7-1.1-1][326 IAC 7-2-1]
- D.1.7 No. 4 Distillate Fuel Oil and Equivalent Fuel Usage [326 IAC 2-8-4]  
[326 IAC 2-2][326 IAC 2-3]
- D.1.8 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

**Compliance Determination Requirements**

- D.1.9 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]
- D.1.10 Sulfur Dioxide Emissions and Sulfur Content
- D.1.11 Particulate Matter (PM) and PM-10

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- D.1.12 Visible Emissions Notations
- D.1.13 Parametric Monitoring
- D.1.14 Baghouse Inspections
- D.1.15 Broken or Failed Bag Detection

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

- D.1.16 Record Keeping Requirements
- D.1.17 Reporting Requirements

**SECTION D.2 FACILITY OPERATION CONDITIONS**

**Cold-Mix (Stockpile Mix) Asphalt Storage Piles ..... 30**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.2.1 Volatile Organic Compounds (VOC) [326 IAC 8-5-2] [326 IAC 2-8-4] [326 IAC 2-2]
- D.2.2 Cold-Mix (Stockpile Mix) VOC Usage [326 IAC 2-8-4] [326 IAC 2-2] [326 IAC 2-1.1-5]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

- D.2.3 Record Keeping Requirements
- D.2.4 Reporting Requirements

**SECTION D.3 FACILITY OPERATION CONDITIONS**

**One (1) 30,000 gallon Liquid Asphalt Storage Tank ..... 32**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.3.1 Volatile Organic Compounds [326 IAC 12] [40 CFR 60.110b, Subpart Kb]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

- D.3.2 Record Keeping Requirements

**Certification Form ..... 33**  
**Emergency Occurrence Form ..... 34**  
**FESOP Quarterly Report Forms(II) ..... 36-37**  
**Quarterly Deviation and Compliance Monitoring Report Form ..... 38**  
**Attachment A ..... 40**

## SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-8-3(b)]

---

The Permittee owns and operates a portable drum mix asphalt plant.

Authorized individual:	Plant Operations Superintendent
Source Address:	5536 Hoagland Road, Poe, Indiana, 46745
Mailing Address:	P.O. Box 9560, 6525 Ardmore Ave., Fort Wayne, Indiana 46899
General Source Phone:	(260) 478-1990
SIC Code:	2951
Initial Source Location Status:	Allen
Source Status:	Non-attainment for ozone under the 8-hour standard Attainment for all other criteria pollutants Federally Enforceable State Operating Permit (FESOP) Minor Source, under PSD and Emission Offset Rules; Minor Source, Section 112 of the Clean Air Act

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

---

This portable source consists of the following emission units and pollution control devices:

- (a) One (1) asphalt parallel flow drum mix dryer capable of processing 400 tons per hour of raw material, equipped with one (1) 120 million (MM) British thermal units (Btu) per hour No. 2 distillate fuel oil fired burner, with one (1) jet pulse baghouse for particulate matter (PM) control, exhausting at one (1) stack (ID No. S/V-1);
- (b) Cold-mix (stockpile mix) asphalt storage piles; and
- (c) One (1) 30,000 gallon liquid asphalt storage tank (ID No. Tank 10), constructed in 1989.

### A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

---

This portable source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Fuel oil-fired combustion sources with heat input equal to or less than two (2) million Btu per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight including:
  - (1) One (1) hot oil heater, with a maximum rated capacity of 0.7 MMBtu per hour, exhausting through one (1) stack (ID No. S/V-2).
- (b) Combustion source flame safety purging on startup.
- (c) A petroleum fuel other than gasoline, dispensing facility, having a storage capacity of less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.

- (d) Other categories with emissions below insignificant thresholds:
- (1) Cutting, welding, and grinding operations for repair and maintenance only;
  - (2) One (1) 8,000 gallon fuel oil storage tank (ID No. Tank 11);
  - (3) One (1) drag slat conveyor;
  - (4) One (1) cold feed system consisting of four (4) compartments with a total aggregate holding capacity of 100 tons;
  - (5) One (1) hot mix storage silo with a maximum storage capacity of 100 tons; and
  - (6) One (1) recycled asphalt pavement (RAP) feed bin with a maximum holding capacity of 25 tons.

A.4 FESOP Applicability [326 IAC 2-8-2]

This portable source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) to renew a Federally Enforceable State Operating Permit (FESOP).

A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
- (1) incorporated as originally stated,
  - (2) revised, or
  - (3) deleted
- by this permit.
- (b) All previous registrations and permits are superseded by this permit.

## **SECTION B GENERAL CONDITIONS**

### **B.1 Permit No Defense [IC 13]**

---

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

### **B.2 Definitions [326 IAC 2-8-1]**

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2, and 326 IAC 2-7) shall prevail.

### **B.3 Permit Term [326 IAC 2-8-4(2)][326 IAC 2-1.1-9.5]**

---

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

### **B.4 Enforceability [326 IAC 2-8-6]**

---

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

### **B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]**

---

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

### **B.6 Severability [326 IAC 2-8-4(4)]**

---

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### **B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]**

---

This permit does not convey any property rights of any sort, or any exclusive privilege.

### **B.8 Duty to Provide Information [326 IAC 2-8-4(5)(E)]**

- 
- (a) The Permittee shall furnish to IDEM, OAQ within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1 when furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

### **B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]**

---

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an authorized individual of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

B.11 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than April 15 of each year to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
  - (5) Such other facts as specified in Sections D of this permit, IDEM, OAQ may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.12 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs), including the following information on each facility:

- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs, including any required record keeping, as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

**B.13 Emergency Provisions [326 IAC 2-8-12]**

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section) or,  
Telephone No.: 317-233-5674 (ask for Compliance Section)  
Facsimile No.: 317-233-5967

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
  - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
  - (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
  - (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
  - (g) Operations may continue during an emergency only if the following conditions are met:
    - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
    - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
      - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
      - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of

capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

**B.14** Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

**B.15** Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
  - (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]

- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

**B.16 Permit Renewal [326 IAC 2-8-3(h)]**

---

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]
- (1) A timely renewal application is one that is:
- (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
- (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (2) If IDEM, OAQ upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-8-9]  
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as needed to process the application.

**B.17 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]**

---

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality

100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]
- (d) No permit amendment or modification is required for the addition, operation or removal of a nonroad engine, as defined in 40 CFR 89.2.

B.18 Operational Flexibility [326 IAC 2-8-15][326 IAC 2-8-11.1]

(a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-8-15(b)(2), (c)(1), and (d).

- (b) Emission Trades [326 IAC 2-8-15(c)]

The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).

- (c) Alternative Operating Scenarios [326 IAC 2-8-15(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ or U.S. EPA is required.

**B.19 Permit Revision Requirement [326 IAC 2-8-11.1]**

---

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-8-11.1.

**B.20 Inspection and Entry [326 IAC 2-8-5(a)(2)][IC 13-14-2-2][IC 13-17-3-2][IC 13-17-3-2][IC 13-30-3-1]**

---

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

**B.21 Transfer of Ownership or Operational Control [326 IAC 2-8-10]**

---

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.22 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4320 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

## SECTION C SOURCE OPERATION CONDITIONS

Entire Source

### Emissions Limitations and Standards [326 IAC 2-8-4(1)]

#### C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]

- (1) Pursuant to 40 CFR 52 Subpart P, particulate matter emissions from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
- (2) Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

#### C.2 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

- (a) Pursuant to 326 IAC 2-8:
  - (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) and 326 IAC 2-3 (Emission Offset) not applicable;
  - (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
  - (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.
  - (4) The potential to emit of particulate matter (PM), from the entire source shall be limited to less than 250 tons per twelve (12) consecutive month period.
- (b) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.
- (c) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

#### C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of thirty percent (30%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

**C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]**

---

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

**C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]**

---

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2.

**C.6 Fugitive Dust Emissions [326 IAC 6-4]**

---

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

**C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]**

---

Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the plan submitted on November 17, 1998. The plan is included as Attachment A.

**C.8 Operation of Equipment [326 IAC 2-8-5(a)(4)]**

---

Except as otherwise provided by statute, rule or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission unit vented to the control equipment is in operation.

**C.9 Stack Height [326 IAC 1-7]**

---

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

**C.10 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]**

---

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:

- (A) Asbestos removal or demolition start date;
  - (B) Removal or demolition contractor; or
  - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and renovation**  
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

### **Testing Requirements [326 IAC 2-8-4(3)]**

#### **C.11 Performance Testing [326 IAC 3-6]**

---

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

### **Compliance Requirements [326 IAC 2-1.1-11]**

#### **C.12 Compliance Requirements [326 IAC 2-1.1-11]**

---

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

### **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

#### **C.13 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]**

---

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented upon issuance of this permit. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

Unless otherwise specified in the approval for the new emissions unit, compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

#### **C.14 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

---

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63 or other approved methods as specified in this permit.

#### **C.15 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-8-4(3)] [326 IAC 2-8-5(1)]**

---

- (a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (" 2%) of full scale reading.
- (b) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

**Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

C.16 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]

---

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.17 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-8-4] [326 IAC 2-8-5]

---

(a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and is comprised of:

- (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected time frame for taking reasonable response steps.
- (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.

(b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:

- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
- (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
- (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, and it will be ten (10) days or more until the unit or device will be shut down, then the Permittee shall promptly notify the IDEM, OAQ of the expected date of the shut down. The notification shall also include the status of the applicable compliance monitoring parameter with respect to normal, and the results of the response actions taken up to the time of notification.

(4) Failure to take reasonable response steps shall be considered a deviation from the permit.

(c) The Permittee is not required to take any further response steps for any of the following reasons:

- (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.

- (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied.
  - (3) An automatic measurement was taken when the process was not operating.
  - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-8-12 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

**C.18 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4][326 IAC 2-8-5]**

---

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

**C.19 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]**

---

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

**C.20 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]**

---

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) Reporting periods are based on calendar years.

**Portable Source Requirement**

**C.21 Relocation of Portable Sources [326 IAC 2-14-4]**

---

- (a) This permit is approved for operation in all areas of Indiana except in severe nonattainment areas for ozone (at the time of this permit's issuance these areas were Lake and Porter Counties). This determination is based on the requirements of Prevention of Significant Deterioration in 326 IAC 2-2, and Emission Offset requirements in 326 IAC 2-3. Prior to locating in any severe nonattainment area, the Permittee must submit a request and obtain a permit modification.
- (b) A request to relocate shall be submitted to IDEM, OAQ at least thirty (30) days prior to the intended date of relocation. This submittal shall include the following:
  - (1) A list of governmental officials entitled to receive notice of application to relocate. IC 13-15-3-1
  - (2) A list of adjacent landowners that the Permittee will send written notice to not more than ten (10) days after submission of the request to relocate. IC 13-15-8The notification by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) A "Relocation Site Approval" letter shall be obtained prior to relocating.

- (d) The Permittee shall also notify the applicable local air pollution control agency when relocating to, or from, one the following:
  - (1) Madison County - (Anderson Office of Air Management)
  - (2) City of Evansville plus four (4) miles beyond the corporate limits but not outside Vanderburgh County - (Evansville EPA)
  - (3) City of Gary - (Gary Department of Environmental Affairs)
  - (4) City of Hammond - (Hammond Department of Environmental Management)
  - (5) Marion County - (Indianapolis Office of Environmental Services)
  - (6) St. Joseph County - (St. Joseph County Health Department)
  - (7) Vigo County - (Vigo County Air Pollution Control)
- (e) A valid operation permit consists of this document and any subsequent "Relocation Site Approval" letter specifying the current location of the portable plant.

### **Stratospheric Ozone Protection**

#### **C.22 Compliance with 40 CFR 82 and 326 IAC 22-1**

---

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

**Facility Description [326 IAC 2-8-4(10)]:**

- (a) One (1) asphalt parallel flow drum mix dryer capable of processing 400 tons per hour of raw material, equipped with one (1) 120 million (MM) British thermal units (Btu) per hour No. 2 distillate fuel oil fired burner, with one (1) jet pulse baghouse for particulate matter (PM) control, exhausting at one (1) stack (ID No. S/V-1);

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

D.1.1 General Provisions Relating to NSPS [326 IAC 12-1][40 CFR Part 60, Subpart A]

The provisions of 40 CFR Part 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 60, Subpart I.

D.1.2 Particulate Matter (PM) [326 IAC 12] [40 CFR 60.90, Subpart I]

Pursuant to 326 IAC 12, (40 CFR Part 60.90, Subpart I) "Standards of Performance for Hot Mix Asphalt Facilities", the particulate matter emissions from the mixing and drying operations shall be limited to 0.04 grains per dry standard cubic foot (gr/dscf). This is equivalent to a particulate matter emission rate of 17.61 pounds per hour. Based on 8,760 hours of operation per 12 consecutive month period, this limits PM emissions from the mixing and drying operations to 77.71 tons per year for a source-wide total potential to emit of less than 250 tons per year.

D.1.3 Particulate Matter (PM) [326 IAC 6-1-2][326 IAC 2-2]

Pursuant to 326 IAC 6-1-2(a)(Nonattainment Area Particulate Limitations), particulate matter (PM) emissions from the drum-mix dryer shall be limited to 0.03 grains per dry standard cubic foot (gr/dscf). This is equivalent to a particulate matter emission rate of 13.20 pounds per hour. Based on 8,760 hours of operation per 12 consecutive month period, this limits PM emissions from the aggregate mixing and drying operation to 57.83 tons per year for a source-wide total potential to emit of less than 250 tons per year. Therefore, this limit will also render 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable.

D.1.4 Particulate Matter 10 Microns (PM-10) [326 IAC 2-8-4][326 IAC 2-2][326 IAC 2-3]

Pursuant to 326 IAC 2-8-4, particulate matter 10 microns emissions from the aggregate mixing and drying operation shall not exceed 0.041 pound of PM-10 per ton of asphalt mix. This is equivalent to a PM-10 emission limit of 18.61 pounds per hour, including both filterable and condensable fractions. Based on 8,760 hours of operation per 12 consecutive month period, this limits PM-10 emissions from the aggregate mixing and drying operation to 81.5 tons per year for a source-wide total potential to emit of less than 100 tons per year. Therefore, compliance with this limit will satisfy 326 IAC 2-8-4, and will render the Part 70 rules (326 IAC 2-7) not applicable. This limit will also render 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) and 326 IAC 2-3 (Emission Offset) not applicable.

D.1.5 Opacity [326 IAC 12] [40 CFR 60.90, Subpart I]

Pursuant to 326 IAC 12, (40 CFR Part 60.92, Subpart I) "Standards of Performance for Hot Mix Asphalt Facilities", the mixing and drying operations shall not discharge or cause the discharge into the atmosphere any gases which exhibit 20% opacity or greater.

**D.1.6 Sulfur Dioxide (SO<sub>2</sub>) [326 IAC 7-1.1-1][326 IAC 7-2-1]**

---

- (a) Pursuant to 326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations), sulfur dioxide emissions from the 120 million Btu per hour burner for the aggregate dryer shall be limited to 0.5 pounds per million Btu heat input or a sulfur content of less than or equal to 0.5% when using distillate oil.
- (b) Pursuant to 326 IAC 7-2-1, compliance shall be demonstrated on a calendar month average.

**D.1.7 No. 2 Distillate Fuel Oil Usage [326 IAC 2-8-4][326 IAC 2-2][326 IAC 2-3]**

---

Pursuant to 326 IAC 2-8-4(1), the following limits shall apply:

The usage of No. 2 distillate fuel oil with a limited sulfur content of 0.5% in the 120 MMBtu/hr aggregate dryer burner shall not exceed 2,505,732 U.S. gallons per twelve (12) consecutive month period, with compliance determined at the end of each month, so that SO<sub>2</sub> emissions are limited to less than 100 tons per year. Therefore, the requirements of 326 IAC 2-7 will not apply. This limitation will also render 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) and 326 IAC 2-3 (Emission Offset) not applicable.

**D.1.8 Preventive Maintenance Plan [326 IAC 2-8-4(9)]**

---

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

**Compliance Determination Requirements**

**D.1.9 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11]**

---

- (a) In order to demonstrate compliance with Conditions D.1.2, D.1.3, D.1.4, and D.1.5 the Permittee shall perform PM and PM-10 testing utilizing Methods as approved by the Commissioner, at least once every five years from October 25, 2000, the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

**D.1.10 Sulfur Dioxide Emissions and Sulfur Content**

---

Compliance shall be determined utilizing one of the following options.

- (a) Pursuant to 326 IAC 3-7-4, the Permittee shall demonstrate that the sulfur dioxide emissions do not exceed five-tenths (0.5) pounds per million Btu heat input when burning No. 2 distillate fuel oil:
  - (1) Providing vendor analysis of fuel delivered, if accompanied by a vendor certification; or
  - (2) Analyzing the oil sample to determine the sulfur content of the oil via the procedures in 40 CFR 60, Appendix A, Method 19.
    - (A) Oil samples may be collected from the fuel tank immediately after the fuel tank is filled and before any oil is combusted; and
    - (B) If a partially empty fuel tank is refilled, a new sample and analysis would be required upon filling.

- (b) Compliance may also be determined by conducting a stack test for sulfur dioxide emissions from the 120 MMBtu per hour burner for the aggregate dryer, using 40 CFR 60, Appendix A, Method 6 in accordance with the procedures in 326 IAC 3-6.

A determination of noncompliance pursuant to any of the methods specified in (a) or (b) above shall not be refuted by evidence of compliance pursuant to the other method.

#### D.1.11 Particulate Matter (PM) and PM-10

---

In order to comply with conditions D.1.2, D.1.3, D.1.4, and D.1.5, the baghouse for PM and PM-10 control shall be in operation and control emissions at all times when aggregate mixing and drying are in operation.

### **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

#### D.1.12 Visible Emissions Notations

---

- (a) Visible emission notations of the asphalt drum mixer burner baghouse stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.

#### D.1.13 Parametric Monitoring

---

The Permittee shall record the total static pressure drop across the baghouse used in conjunction with the aggregate mixing and drying operation, at least once per shift when the process is in operation when venting to the atmosphere. When or any one reading, the pressure drop across the baghouse is outside the normal range of 2.0 and 8.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge and Other Instruments Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated at least once every six (6) months.

#### D.1.14 Baghouse Inspections

---

An inspection shall be performed each calendar quarter of all bags controlling the process when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.

#### D.1.15 Broken or Failed Bag Detection

---

In the event that bag failure has been observed:

- (a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit. If operations continue after bag failure is observed and it will be 10 days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.
- (b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

## Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

### D.1.16 Record Keeping Requirements

---

- (a) To document compliance with Conditions D.1.6 and D.1.7, the Permittee shall maintain records in accordance with (1) through (6) below.
- (1) Calendar dates covered in the compliance determination period;
  - (2) Actual No. 2 distillate fuel oil and No. 2 distillate fuel oil equivalent usage in the 120 MMBtu per hour burner for the aggregate dryer per month since last compliance determination period and equivalent SO<sub>2</sub> emissions;
  - (3) A certification, signed by the owner or operator, that the records of the fuel supplier certifications represent all of the fuel combusted during the period; and

If the fuel supplier certification is used to demonstrate compliance the following, as a minimum, shall be maintained:

- (4) Fuel supplier certifications.
- (5) The name of the fuel supplier; and
- (6) A statement from the fuel supplier that certifies the sulfur content of the fuel oil.

The Permittee shall retain records of all recording/monitoring data and support information for a period of five (5) years, or longer if specified elsewhere in this permit, from the date of the monitoring sample, measurement, or report. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit.

- (b) The Permittee shall maintain records sufficient to verify compliance with the procedures specified in condition D.1.10. Records shall be maintained for a period of five (5) years and shall be made available upon request by IDEM.
- (c) To document compliance with Condition D.1.12, the Permittee shall maintain records of visible emission notations of the aggregate dryer/burner baghouse stack exhaust once per shift.
- (d) To document compliance with Condition D.1.13, the Permittee shall maintain records once per shift of the total static pressure drop during normal operation when venting to the atmosphere.
- (e) To document compliance with Condition D.1.14, the Permittee shall maintain records of the results of the inspections required under Condition D.1.14 and the dates the vents are redirected.
- (f) To document compliance with Condition D.1.8, the Permittee shall maintain of records of any additional inspections prescribed by the Preventive Maintenance Plan.

- (g) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.1.17 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.7 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

## SECTION D.2 FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-8-4(10)]:

- (b) Cold-mix (stockpile mix) asphalt storage piles;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-8-4(1)]

#### D.2.1 Volatile Organic Compound (VOC) [326 IAC 8-5-2] [326 IAC 2-8-4][326 IAC 2-2]

- (a) Pursuant to 326 IAC 8-5-2 (Miscellaneous Operations: Asphalt Paving), the use of cutback asphalt or asphalt emulsion shall not contain more than seven percent (7%) oil distillate by volume of emulsion for any paving application except the following purposes:
- (1) Penetrating prime coating;
  - (2) Stockpile storage;
  - (3) Application during the months of November, December, January, February and March.

#### D.2.2 Cold-Mix (Stockpile Mix) VOC Usage [326 IAC 2-8-4] [326 IAC 2-2] [326 IAC 2-1.1-5]

- (a) The usage of diluent in the production of cold mix (stockpile mix) asphalt shall be limited to 92.26 tons per twelve (12) consecutive month period, with compliance determined at the end of each month. The total for each month shall not exceed the difference between the annual usage limit minus the sum of actual usage from the previous eleven (11) months. This is equivalent to a VOC emission limit of 87.65 tons per twelve (12) consecutive month period in the production of cold mix (stockpile mix) asphalt. During the first twelve (12) months of operation under this permit, the usage of diluent shall be limited such that the total usage divided by the accumulated months of operation shall not exceed 7.68 tons per month.
- (b) The volume percent of diluent in the cutback asphalt shall not exceed 35%.
- (c) The VOC content of the diluent shall not exceed 95% by weight.

Compliance with this limit also satisfies the requirements of 326 IAC 2-1.1-5.

Compliance with this limit also renders the requirements of 326 IAC 2-2 not applicable.

### Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

#### D.2.3 Record Keeping Requirements

To document compliance with Condition D.2.2, the Permittee shall maintain records in accordance with (a) through (d) below. Records maintained for (a) through (d) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC emission limit established in Condition D.2.2.

- (a) Diluent used in production of cold mix asphalt per month;
- (b) Amount of diluent used last twelve (12) months;;
- (c) Type of liquid binder used; and

(d) Percent diluent (oil distillate) in liquid binder.

All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.2.4 Reporting Requirements

---

A quarterly summary of the information to document compliance with Condition D.2.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**SECTION D.3**

**FACILITY OPERATION CONDITIONS**

**Facility Description [326 IAC 2-8-4(10)]:**

(h) One (1) 30,000 gallon liquid asphalt storage tank (ID No. TANK 10), constructed in 1989.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

**D.3.1 Volatile Organic Compounds (VOCs) [326 IAC 12] [40 CFR 60.110b, Subpart Kb]**

Pursuant to 40 CFR Part 60.110b, Subpart Kb (Standards of Performance for Volatile Organic Liquid Storage Vessels), the 30,000 gallon liquid asphalt storage tank, with a vapor pressure of less than 15.0 kPa, is subject to 40 CFR Part 60.116b, paragraphs (a), (b) which require record keeping.

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

**D.3.2 Record Keeping Requirements**

- (a) To document compliance with Condition D.3.1, the Permittee shall maintain permanent records at the source in accordance with (1) through (3) below:
- (1) The dimension of the storage vessel;
  - (2) An analysis showing the capacity of the storage vessel; and
  - (3) The true vapor pressure of each VOC stored, indicating that the maximum true vapor pressure of VOC is less than 15.0 kPa.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
CERTIFICATION**

Source Name: Brooks Construction Company, Inc.  
Initial Source Address: 5536 Hoagland Road, Poe, Indiana  
Mailing Address: P.O. Box 9560, 6525 Ardmore Ave., Fort Wayne, Indiana 46899  
FESOP No.: F003-19156-05190

**This certification shall be included when submitting monitoring, testing reports/results  
or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify) \_\_\_\_\_
- Report (specify) \_\_\_\_\_
- Notification (specify) \_\_\_\_\_
- Affidavit (specify) \_\_\_\_\_
- Other (specify) \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE BRANCH  
P.O. Box 6015  
100 North Senate Avenue  
Indianapolis, Indiana 46206-6015  
Phone: 317-233-5674  
Fax: 317-233-5967**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
EMERGENCY OCCURRENCE REPORT**

Source Name: Brooks Construction Company, Inc.  
Initial Source Address: 5536 Hoagland Road, Poe, Indiana  
Mailing Address: P.O. Box 9560, 6525 Ardmore Ave., Fort Wayne, Indiana 46899  
FESOP No.: F003-19156-05190

**This form consists of 2 pages**

**Page 1 of 2**

<input type="checkbox"/> This is an emergency as defined in 326 IAC 2-7-1(12) <ul style="list-style-type: none"><li>• The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and</li><li>• The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16</li></ul>
---

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

**Page 2 of 2**

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency?    Y    N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

A certification is not required for this report.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

### FESOP Quarterly Report

Source Name: Brooks Construction Company, Inc.  
 Initial Source Address: 5536 Hoagland Road, Poe, Indiana  
 Mailing Address: P.O. Box 9560, 6525 Ardmore Ave., Fort Wayne, Indiana 46899  
 FESOP No.: F003-19156-05190  
 Facility: 120.0 MMBtu per hour burner for the aggregate dryer  
 Parameter: Sulfur Dioxide (SO<sub>2</sub>)  
 Limit: the input of No. 2 distillate fuel oil with a maximum sulfur content of 0.5% to the 120.0 MMBtu per hour burner for the aggregate dryer shall be limited to 2,505,732 U.S. gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.

YEAR: \_\_\_\_\_

Month	Column 1	Column 2	Column 1 + Column 2
	No. 2 Fuel Oil Usage This Month (gallons)	No. 2 Fuel Oil Usage Previous 11 Months (gallons)	12 Month Total No. 2 Fuel Oil Usage (gallons)

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.  
 Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

### FESOP Quarterly Report

Source Name: Brooks Construction Company, Inc.  
 Initial Source Address: 5536 Hoagland Road, Poe, Indiana  
 Mailing Address: P.O. Box 9560, Fort Wayne, Indiana 46899  
 FESOP No.: F003-10386-05190  
 Facility: Cold-Mix (Stockpile Mix) Asphalt Storage piles  
 Parameter: Volatile Organic Compounds (VOC)  
 Limit: The VOC usage in the production of cold mix (stockpile mix) asphalt shall be limited to 87.65 tons per twelve (12) consecutive month period, with compliance determined at the end of each month. The total for each month shall not exceed the difference between the annual usage limit minus the sum of actual usage from the previous eleven (11) months. This is equivalent to 92.26 tons of diluent used per twelve (12) consecutive month period in the production of cold mix (stockpile mix) asphalt based on 95% volatilization. During the first twelve (12) months of operation under this permit, the usage of diluent shall be limited such that the total usage divided by the accumulated months of operation shall not exceed 7.68 tons per month.

YEAR: \_\_\_\_\_

Month	Column 1	Column 2	Column 1 + Column 2
	Diluent Usage This Month (tons)	Diluent Usage Previous 11 Months (tons)	12 Month Total Diluent Usage (tons)

**9** No deviation occurred in this quarter.

**9** Deviation/s occurred in this quarter.  
 Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Brooks Construction Company, Inc.  
Initial Source Address: 5536 Hoagland Road, Poe, Indiana  
Mailing Address: P.O. Box 9560, 6525 Ardmore Ave., Fort Wayne, Indiana 46899  
FESOP No.: F003-19156-05190

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

Page 1 of 2

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<p><input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.</p>	
<p><input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD</p>	
<p><b>Permit Requirement</b> (specify permit condition #)</p>	
<p><b>Date of Deviation:</b></p>	<p><b>Duration of Deviation:</b></p>
<p><b>Number of Deviations:</b></p>	
<p><b>Probable Cause of Deviation:</b></p>	
<p><b>Response Steps Taken:</b></p>	
<p><b>Permit Requirement</b> (specify permit condition #)</p>	
<p><b>Date of Deviation:</b></p>	<p><b>Duration of Deviation:</b></p>
<p><b>Number of Deviations:</b></p>	
<p><b>Probable Cause of Deviation:</b></p>	
<p><b>Response Steps Taken:</b></p>	

<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

Form Completed By: \_\_\_\_\_

Title/Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

## Attachment A

### BROOKS CONSTRUCTION COMPANY, INC.

#### ASPHALT PLANT SITE FUGITIVE DUST CONTROL PLAN

- (a) Fugitive particulate matter emissions from paved roads, unpaved roads, and parking lots shall be controlled by one or more of the following methods:
- Paved roads and parking lots:
- (1) Cleaning by vacuum sweeping on an as needed basis (monthly at a minimum);
  - (2) Power brooming while wet either from rain or application of water.
- Unpaved roads and parking lots:
- (1) Paving with asphalt;
  - (2) Treating with emulsified asphalt on an as needed basis;
  - (3) Treating with water on an as needed basis;
  - (4) Double chip and seal the road surface and maintained on an as needed basis.
- (b) Fugitive particulate matter emissions from aggregate stockpiles shall be controlled by one or more of the following methods on an as needed basis:
- (1) Maintaining minimum size and number of stock piles of aggregate;
  - (2) Treating around the stockpile area with emulsified asphalt;
  - (3) Treating around the stockpile area with water;
  - (4) Treating the stockpiles with water.
- (c) Fugitive particulate matter emissions from outdoor conveying of aggregates shall be controlled by the following method on an as needed basis:
- (1) Applying water at the feed and the intermediate points.
- (d) Fugitive particulate matter emissions from the transfer of aggregates shall be controlled by one of the following methods:
- (1) Minimize the vehicular distance between transfer points;
  - (2) Enclose the transfer points;
  - (3) Apply water on transfer points on an as needed basis.
- (e) Fugitive particulate matter emissions from transportation of aggregate by truck, front end loader, etc. shall be controlled by one of the following methods:
- (1) Tarping the aggregate hauling vehicles;

- (2) Maintain vehicle bodies in a condition to prevent leakage;
  - (3) Spray the aggregates with water;
  - (4) Maintain a 10 MPH speed limit in the yard.
- (f) Fugitive particulate matter emissions from the loading and unloading of aggregate shall be controlled by one of the following methods:
- (1) Reduce free fall distance to a minimum;
  - (2) Reduce the rate of discharge of the aggregate;
  - (3) Spray the aggregate with water on an as needed basis.

**Indiana Department of Environmental Management  
Office of Air Quality**

Technical Support Document (TSD) for a Federally Enforceable State Operating Permit  
(FESOP) Renewal

**Source Background and Description**

<b>Source Name:</b>	<b>Brooks Construction Company, Inc.</b>
<b>Source Location:</b>	<b>5536 Hoagland Road, Poe, Indiana, 46745</b>
<b>County:</b>	<b>Allen</b>
<b>SIC Code:</b>	<b>2951</b>
<b>Operation Permit No.:</b>	<b>F003-10386-05190</b>
<b>Operation Permit Issuance Date:</b>	<b>March 11, 1999</b>
<b>Permit Renewal No.:</b>	<b>003-19156-05190</b>
<b>Permit Reviewer:</b>	<b>SR/EVP</b>

The Office of Air Quality (OAQ) has reviewed a FESOP renewal application from Brooks Construction Company, Inc. relating to the operation of a portable drum mix asphalt plant.

**Permitted Emission Units and Pollution Control Equipment**

The source consists of the following permitted emission units and pollution control devices:

- (a) One (1) asphalt parallel flow drum mix dryer capable of processing 400 tons per hour of raw material, equipped with one (1) 120 million (MM) British thermal units (Btu) per hour No. 2 distillate fuel oil fired burner, with one (1) jet pulse baghouse for particulate matter (PM) control, exhausting at one (1) stack (ID No. S/V-1);
- (b) Cold-mix (stockpile mix) asphalt storage piles; and
- (c) One (1) 30,000 gallon liquid asphalt storage tank (ID No. Tank 10), constructed in 1989.

**Unpermitted Emission Units and Pollution Control Equipment**

There are no unpermitted emission units operating at this source during this review process.

**Insignificant Activities**

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Fuel oil-fired combustion sources with heat input equal to or less than two (2) million Btu per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight including:
  - (1) One (1) hot oil heater, with a maximum rated capacity of 0.7 MMBtu per hour, exhausting through one (1) stack (ID No. S/V-2).
- (b) Combustion source flame safety purging on startup.

- (c) A petroleum fuel other than gasoline, dispensing facility, having a storage capacity of less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.
- (d) Other categories with emissions below insignificant thresholds:
  - (1) Cutting, welding, and grinding operations for repair and maintenance only;
  - (2) One (1) 8,000 gallon fuel oil storage tank (ID No. Tank 11);
  - (3) One (1) drag slat conveyor;
  - (4) One (1) cold feed system consisting of four (4) compartments with a total aggregate holding capacity of 100 tons;
  - (5) One (1) hot mix storage silo with a maximum storage capacity of 100 tons; and
  - (6) One (1) recycled asphalt pavement (RAP) feed bin with a maximum holding capacity of 25 tons.

### **Existing Approvals**

The source has been operating under the previous FESOP F003-10386-05190 issued on March 11, 1999 and the following amendments and revisions:

- (a) First Significant Permit Revision 085-15073-05190 issued on January 22, 2002.

All conditions from previous approvals were incorporated into this FESOP.

### **Enforcement Issue**

- (a) IDEM is aware that the source did not apply for a FESOP renewal in a timely manner. IDEM is reviewing this matter and will take appropriate action.

### **Recommendation**

The staff recommends to the Commissioner that the FESOP renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP renewal application for the purposes of this review was received on May 6, 2004.

There was no notice of completeness letter mailed to the source.

### **Emission Calculations**

See Appendix A of this document for detailed emission calculations (pages 1 through 7).

### **Unrestricted Potential Emissions**

This table reflects the unrestricted potential emissions of the source, excluding the emission limits that were contained in the previous FESOP.

Pollutant	Unrestricted Potential Emissions (tons/yr)
PM	Greater than 250
PM-10	Greater than 250
SO <sub>2</sub>	Greater than 250
VOC	Greater than 250
CO	Less than 100
NO <sub>x</sub>	Less than 100

HAPs	Unrestricted Potential Emissions (tons/yr)
Acetaldehyde	Less than 10
Acrolein	Less than 10
Arsenic	Less than 10
Benzene	Less than 10
Beryllium	Less than 10
Cadmium	Less than 10
Chromium	Less than 10
Ethylbenzene	Less than 10
Formaldehyde	Less than 10
Lead	Less than 10
Manganese	Less than 10
Mercury	Less than 10
Methyl Ethyl Ketone	Less than 10
Nickel	Less than 10
Propionaldehyde	Less than 10
Quinone	Less than 10
Toluene	Less than 10
POM	Less than 10
Xylene	Less than 10
Total	Less than 25

- (a) The potential to emit (as defined in 326 IAC 2-7-1(29)) of PM-10, SO<sub>2</sub>, and VOC are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 2-7. The source will be issued a FESOP because the source will limit its emissions below the Title V levels.
- (b) Fugitive Emissions  
 Since there are applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive emissions are counted toward determination of PSD and Emission Offset applicability. This type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2.

**Potential to Emit After Issuance**

The source has opted to remain a FESOP source. The table below summarizes the potential to emit, reflecting all limits of the emission units. Any control equipment is considered enforceable only after issuance of this FESOP and only to the extent that the effect of the control equipment is made practically enforceable in the permit. Since the source has not constructed any new emission units, the source's potential to emit is based on the emission units included in the original FESOP.

Process/facility	Limited Potential to Emit (tons/year)						
	PM	PM-10	SO <sub>2</sub>	VOC	CO	NO <sub>x</sub>	HAPs
Aggregate Drying <sup>(1)</sup>	57.83 <sup>(2)</sup>	81.5 <sup>(3)</sup>	98.35	11.32	6.26	30.07	11.13
Conveying/Handling	4.70	2.22	0.0	0.0	0.0	0.0	0.0
Cold Mix Storage	0.0	0.0	0.0	87.65	0.0	0.0	0.0
Unpaved Roads <sup>(4)</sup>	63.06	16.07	0.0	0.0	0.0	0.0	0.0
Storage Piles	0.13	0.04	0.0	0.0	0.0	0.0	0.0
Insignificant Activities	0.04	0.07	1.55	0.01	0.11	0.44	0.0
<b>Total Emissions</b>	<b>130.47</b>	<b>99.0</b>	<b>99.0</b>	<b>99.0</b>	<b>6.97</b>	<b>27.89</b>	<b>11.13</b>

- (1) Limited PTE based on No.2 distillate fuel oil with a sulfur content of 0.5%, usage limitation of 2,505,732 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month to comply with 326 IAC 2-8 (FESOP).
- (2) Maximum allowable PM emissions pursuant to 326 IAC 6-1-2 limit and 8760 hours per year of operation.
- (3) Maximum allowable PM10 emissions in order to comply with 326 IAC 2-8 (FESOP).
- (4) Potential to emit after controls.

**County Attainment Status**

The source is located in Allen County.

Pollutant	Status
PM-10	Attainment
SO <sub>2</sub>	Attainment
NO <sub>2</sub>	Attainment
1-hour Ozone	Attainment
8-hour Ozone	Non-attainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and Nitrogen Oxides (NOx) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NOx emissions are considered when evaluating the rule applicability relating to the ozone standards. Allen County has been designated as nonattainment for the 8-hour ozone standard. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for nonattainment new source review.
- (b) Allen County has been classified as attainment or unclassifiable in Indiana for the remaining criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2. See the State Rule Applicability for the source section.

### Portable Source

- (a) Initial Location  
This is a portable source and its initial location is 5536 Hoagland Road, Poe, Indiana, 46745.
- (b) PSD and Emission Offset Requirements  
The emissions from this portable source were reviewed under the requirements of the Prevention of Significant Deterioration (PSD) 326 IAC 2-2 and Emission Offset 326 IAC 2-3.
- (c) Fugitive Emissions  
Since there are applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are counted toward determination of PSD and Emission Offset applicability. This type of operation is not one of the twenty-eight (28) listed sources under 326 IAC 2-2.

### Source Status

Existing Source FESOP Definition (emissions after controls, based on 8760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/yr)
PM	123.24
PM-10	26.44
SO <sub>2</sub>	99.00
VOC	99.00
CO	18.88
NO <sub>x</sub>	27.89
Single HAP	<10
Combination HAPs	<25

- (a) This existing source is **not** a major stationary source because no attainment regulated pollutant is emitted at a rate of 250 tons per year or greater and it is not in one of the 28 listed source categories.
- (b) This existing source is **not** a major stationary source because no nonattainment regulated pollutant is emitted at a rate of 100 tons per year or greater, and it is not in one of the 28 listed source categories.

### Federal Rule Applicability

- (a) This source is subject to the New Source Performance Standard, 326 IAC 12, (40 CFR 60.90, Subpart I) because it meets the definition of a hot mix asphalt facility pursuant to the rule and it was constructed after the June 11, 1973 rule applicability date. This rule limits particulate matter emissions to 0.04 grains per dry standard cubic foot (gr/dscf) and also limits visible emissions to 20% opacity. This is equivalent to a particulate matter emission rate of 17.61 pounds per hour. Based on 8,760 hours of operation per 12 consecutive month period, this limits PM emissions from the aggregate mixing and drying operation to 77.11 tons per year. The source will comply with this rule by using a baghouse to limit particulate matter emissions to less than 0.04 gr/dscf (see Appendix A, page 7 of 7, for detailed calculations).

- (b) The one (1) 30,000 gallon liquid asphalt storage tank (Tank 10) is not subject to the requirements of the New Source Performance Standard, 326 IAC 12, (40 CFR 60.110b, Subpart Kb) "Standards of Performance for Volatile Organic Liquid Storage Vessels". Although it was constructed after July 23, 1984, and has a storage capacity greater than 75 cubic meters, it has a storage capacity greater than 75 cubic meters but less than 151 cubic meters each, and the liquid asphalt stored in the tank has a maximum true vapor pressure of less than 15.0 kPa. Therefore, pursuant to 40 CFR 60.110b(b), as amended in the October 15, 2003 Federal Register, this tank is not subject to this rule.

However, Tank 10 is subject to the requirements of 40 CFR 60.116b(a) and (b) under 326 IAC 12 due to the state rules not yet reflecting the October 15, 2003 changes made to this NSPS.

- (c) The one (1) 8,000 gallon fuel oil storage tank (Tank 11) is not subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.110b, Subpart Kb) "Standards of Performance for Volatile Organic Liquid Storage Vessels" since it has a storage capacity of less than 75 cubic meters.
- (d) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs), 40 CFR Part 63, applicable to this source.
- (e) The requirements of 40 CFR Part 64, Compliance Assurance Monitoring, are not applicable to this source. Generally, such requirements apply to a Part 70 source that involves a pollutant-specific emissions unit (PSEU), as defined in 40 CFR 64.1, which meets the following criteria:
- (1) The unit is subject to an emission limitation or standard for an applicable regulated air pollutant;
  - (2) The unit uses a control device as defined in 40 CFR 64.1 to comply with that emission limitation or standard; and
  - (3) The unit has a potential to emit before controls equal to or greater than the applicable Part 70 major source threshold for the regulated pollutant.

As a FESOP source, this source has accepted federally enforceable limits such that the requirements of 326 IAC 2-7 (Part 70) do not apply. Therefore, the requirements of 40 CFR 64, Compliance Assurance Monitoring, are not applicable to this source.

### **State Rule Applicability – Entire Source**

#### **326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) and 326 IAC 2-3 (Emission Offset)**

This source is not subject to the requirements of these rules. As shown in the Potential to Emit After Issuance table, the allowable emissions of all regulated pollutants are less than 100 tons per year after application of all federally enforceable emission limits. PM emissions are limited to less than 250 tons per year. The requirements of 326 IAC 2-3 (Emission Offset) apply to major sources or major modifications constructed in an area designated as nonattainment. Since this source is approved for operation in all areas of Indiana except in severe nonattainment areas for ozone (at this time these areas are Lake and Porter Counties), the applicability threshold for 326 IAC 2-3 (Emission Offset) is 100 tons per year for PM-10, SO<sub>2</sub>, VOC, NO<sub>x</sub>, and CO. Therefore the requirements of 326 IAC 2-2 (PSD) and 326 IAC 2-3 (Emission Offset) do not apply.

326 IAC 2-4.1-1 (New Source Toxics Control)

Pursuant to 326 IAC 2-4.1-1 (New Source Toxics Control), any new process or production unit, which in and of itself emits or has the PTE 10 tons per year of any HAP or 25 tons per year of the combination of HAPs, and is constructed or reconstructed after July 27, 1997, must be controlled using technologies consistent with Maximum Achievable Control Technology (MACT).

This source has potential single HAP and total HAP emissions of less than 10 and 25 tons per year, respectively, therefore, this rule does not apply.

326 IAC 2-6 (Emission Reporting)

Since this source is complying with 326 IAC 2-8 (FESOP) and is not required to have an operating permit under 326 IAC 2-7, Part 70 Permit Program, this source is not subject to 326 IAC 2-6 (Emission Reporting).

326 IAC 2-8-4 (FESOP)

This source is subject to 326 IAC 2-8-4 (FESOP). Pursuant to this rule, the following limits shall apply:

- (a) The usage of No. 2 distillate fuel oil with a limited sulfur content of 0.5% in the 120 MMBtu/hr aggregate dryer burner shall not exceed 2,505,732 U.S. gallons per twelve (12) consecutive month period, with compliance determined at the end of each month, so that SO<sub>2</sub> emissions are limited to less than 100 tons per year.
- (b) The VOC usage in the production of cold mix (stockpile mix) asphalt shall be limited to 87.65 tons per twelve (12) consecutive month period, rolled on a monthly basis. This is equivalent to 92.26 tons of diluent used per twelve (12) month period in the production of cold mix (stockpile mix) asphalt based on 95% volatilization.
- (c) PM-10 emissions from the aggregate dryer shall be limited to 0.041 pound PM-10 per ton of asphalt mix equivalent to 18.61 pounds per hour, based on a maximum throughput of 400 tons of asphalt mix per hour. Based on 8,760 hours of operation per 12 consecutive month period, this limits PM-10 emissions from the aggregate mixing and drying operation to 81.5 tons per year for a source-wide total potential to emit of less than 100 tons per year. The source will comply with the PM-10 emission limit by utilizing a baghouse for controlling PM-10 emissions to less than 18.61 pounds per hour from the aggregate dryer.

This operation is approved for operation in all areas of Indiana except in severe nonattainment areas for ozone (at this time these areas are Lake and Porter Counties). Therefore, these limits will render the requirements of 326 IAC 2-7 (Part 70), 326 IAC 2-2 (PSD) and 326 IAC 2-3 (Emission Offset) not applicable.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of thirty percent (30%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 6-1-2 (Particulate Emissions Limitations)

The source is subject to the requirements of 326 IAC 6-1-2 (Particulate Emissions Limitations) because as a portable source it can operate in any of the counties specifically listed under 326 IAC 6-1-7 (except in Lake County). For asphalt plants constructed after June 11, 1973, the rule requires that the particulate matter emissions be limited to 0.03 gr/dscf. This is equivalent to a particulate matter emission rate of 13.2 pounds per hour from the aggregate dryer. Based on 8,760 hours of operation per 12 consecutive month period, this limits PM emissions from the aggregate mixing and drying operation to 57.83 tons per year. The baghouse for the aggregate dryer shall be in operation at all times the aggregate dryer is in operation, in order to comply with this limit (see Appendix A, page 7 of 7, for detailed calculations). This limit will also render the requirements of 326 IAC 2-2 (PSD) not applicable.

326 IAC 6-4 (Fugitive Dust Emissions)

This source is subject to 326 IAC 6-4 for fugitive dust emissions. Pursuant to 326 IAC 6-4 (Fugitive Dust Emissions), fugitive dust shall not be visible crossing the boundary or property line of a source. Observances of visible emissions crossing property lines may be refuted by factual data expressed in 326 IAC 6-4-2(1), (2) or (3).

326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations)

This source is subject to 326 IAC 6-5 for fugitive particulate matter emissions. Pursuant to 326 IAC 6-5, for any new source which has not received all the necessary preconstruction approvals before December 13, 1985, a fugitive dust control plan must be submitted, reviewed and approved. The fugitive dust control plan for this source includes the following:

- (a) Fugitive particulate matter emissions from paved roads, unpaved roads, and parking lots shall be controlled by one or more of the following methods:
  - Paved roads and parking lots:
    - (1) Cleaning by vacuum sweeping on an as needed basis (monthly at a minimum);
    - (2) Power brooming while wet either from rain or application of water.
  - Unpaved roads and parking lots:
    - (1) Paving with asphalt;
    - (2) Treating with emulsified asphalt on an as needed basis;
    - (3) Treating with water on an as needed basis;
    - (4) Double chip and seal the road surface and maintained on an as needed basis.
- (b) Fugitive particulate matter emissions from aggregate stockpiles shall be controlled by one or more of the following methods on an as needed basis:
  - (1) Maintaining minimum size and number of stockpiles of aggregate;
  - (2) Treating around the stockpile area with emulsified asphalt;
  - (3) Treating around the stockpile area with water;
  - (4) Treating the stockpiles with water.

- (c) Fugitive particulate matter emissions from outdoor conveying of aggregates shall be controlled by the following method on an as needed basis:
  - (1) Applying water at the feed and the intermediate points.
- (d) Fugitive particulate matter emissions from the transfer of aggregates shall be controlled by one of the following methods:
  - (1) Minimize the vehicular distance between transfer points;
  - (2) Enclose the transfer points;
  - (3) Apply water on transfer points on an as needed basis.
- (e) Fugitive particulate matter emissions from transportation of aggregate by truck, front end loader, etc. shall be controlled by one of the following methods:
  - (1) Tarping the aggregate hauling vehicles;
  - (2) Maintain vehicle bodies in a condition to prevent leakage;
  - (3) Spray the aggregates with water;
  - (4) Maintain a 10 MPH speed limit in the yard.
- (f) Fugitive particulate matter emissions from the loading and unloading of aggregate shall be controlled by one of the following methods:
  - (1) Reduce free fall distance to a minimum;
  - (2) Reduce the rate of discharge of the aggregate;
  - (3) Spray the aggregate with water on an as needed basis.

### **State Rule Applicability – Individual Facilities**

#### **326 IAC 6-3-2 (Process Operations)**

The aggregate mixing and drying operation is not subject to the requirements of 326 IAC 6-3-2. This rule does not apply if the limitation established in the rule is less stringent than applicable limitations in 326 IAC 6-1 or 326 IAC 12. Since the applicable PM emission limits established by 326 IAC 6-1-2 (13.20 pounds per hour) and 326 IAC 12, 40 CFR 60, Subpart I (17.61 pounds per hour), are lower than the PM limit that would be established by 326 IAC 6-3-2 (66.31 pounds per hour, see Appendix A, page 7 of 7, the more stringent limits apply and the limit pursuant to 326 IAC 6-3-2 does not apply.

#### **326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations)**

This rule applies to all facilities with a potential to emit greater than twenty-five (25) tons per year or ten (10) pounds per hour of sulfur dioxide. The 120 MMBtu/hr dryer burning distillate oil is subject to the requirements of this rule because the potential sulfur dioxide emissions from this facility is greater than twenty-five (25) tons per year. Therefore, pursuant to this rule the sulfur dioxide emissions from the 120 MMBtu/hr dryer burning distillate oil shall be limited to 0.5 lb/MMBtu heat input. This equates to a fuel oil sulfur content limit of 0.5%. Therefore, the sulfur content of the fuel must be less than or equal to 0.5% in order to comply with this rule (See Appendix A, Page 7 of 7 for detailed calculations). The source will comply with this rule by using No. 2 distillate oil with a sulfur content of 0.5% or less in the dryer.

The 0.7 MMBtu/hr hot oil heater is not subject to the requirements of this rule because potential SO<sub>2</sub> emissions from this unit is less than 25 tons per year.

326 IAC 7-2-1 (Sulfur Dioxide Reporting Requirements)

This source is subject to 326 IAC 7-2-1 (Reporting Requirements) because it has a potential to emit greater than twenty-five (25) tons per year of sulfur dioxide. This rule requires the source to submit to the Office of Air Quality upon request records of sulfur content, heat content, fuel consumption, and sulfur dioxide emission rates based on a calendar-month average.

326 IAC 8-1-6 (New Facilities, General Reduction Requirements)

This source is not subject to the provisions of 326 IAC 8-1-6. This rule requires all facilities constructed after January 1, 1980, which have potential VOC emission rates of greater than or equal to 25 tons per year, and which are not otherwise regulated by other provisions of 326 IAC 8, to reduce VOC emissions using Best Available Control Technology (BACT). The source is subject to the requirements of 326 IAC 8-5-2 (Miscellaneous Operations: Asphalt Paving), therefore, it is not subject to the requirements of this rule.

326 IAC 8-4-3 (Petroleum Liquid Storage Facilities)

The storage tanks at this source are not subject to 326 IAC 8-4-3 because the tanks have storage capacities less than 39,000 gallons each.

326 IAC 8-5-2 (Miscellaneous Operations: Asphalt Paving)

This rule applies to any paving application constructed after January 1, 1980 located anywhere in the state. No person shall cause or allow the use of cutback asphalt or asphalt emulsion containing more than seven percent (7%) oil distillate by volume of emulsion for any paving application except the following purposes:

- (a) Penetrating prime coating;
- (b) Stockpile storage;
- (c) Application during the months of November, December, January, February and March.

This source manufactures stockpile mix for stockpile storage only, therefore, there is no limit on the % of oil distillate in the liquid asphalt used. The source is in compliance with 326 IAC 8-5-2.

326 IAC 12 (New Source Performance Standards)

- (a) The one (1) 30,000 gallon liquid asphalt storage tank (Tank 10) is subject to the requirements of the New Source Performance Standard, 326 IAC 12, (40 CFR 60.110b, Subpart Kb) "Standards of Performance for Volatile Organic Liquid Storage Vessels" because it was constructed after July 23, 1984, and has a storage capacity greater than 40 cubic meters. However, since the tank has a storage capacity greater than 75 cubic meters but less than 151 cubic meters, and the liquid asphalt stored in the tank has a maximum true vapor pressure of less than 15.0 kPa, the tank is subject to only 40 CFR 60.116b, paragraphs (a) and (b) which require record keeping.
- (b) The one (1) 8,000 gallon fuel oil storage tank (Tank 11) is not subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.110b, Subpart Kb) "Standards of Performance for Volatile Organic Liquid Storage Vessels" since it has a storage capacity of less than 40 cubic meters.

## Testing Requirements

All testing requirements from FESOP No. F003-10386-05190, issued on March 11, 1999, are incorporated into this FESOP Renewal, as follows:

The Permittee shall perform PM and PM-10 testing utilizing Methods as approved by the Commissioner, at least once every five years from October 25, 2000, the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

Previous stack tests to comply with this requirement were conducted on October 25, 2000.

## Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

- (a) The asphalt drum mixer burner has applicable compliance monitoring conditions as specified below:
  - (1) Visible emission notations of the asphalt drum mixer burner baghouse stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
  - (2) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
  - (3) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
  - (4) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.

- (5) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.
- (6) The Permittee shall record the total static pressure drop across the baghouse used in conjunction with the asphalt drum mixer burner, at least once per shift when the process is in operation when venting to the atmosphere. When or any one reading, the pressure drop across the baghouse is outside the normal range of 2.0 and 8.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan -Failure to Take Response. A pressure reading that is outside the above-mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge and Other Instruments Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated at least once every six (6) months.

- (7) An inspection shall be performed each calendar quarter of all bags controlling the process when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.
- (8) In the event that bag failure has been observed:
- (A) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan -Preparation, Implementation, Records, and Reports, shall be considered a deviation from this permit. If operations continue after bag failure is observed and it will be 10 days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.

- (B) For single compartment baghouses, if failure is indicated by a significant drop in the baghouses pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

These monitoring conditions are necessary because the baghouse for the asphalt drum mixer burner must operate properly to ensure compliance with 40 CFR Part 60.90 (Subpart I-Standards of Performance for Hot Mix Asphalt Facilities), 326 IAC 6-1-2 (Particulate Emissions Limitations), 326 IAC 2-8 (FESOP) and 326 IAC 2-2 (PSD).

### **Conclusion**

The renewed operation of this portable drum mix asphalt plant shall be subject to the conditions of the attached proposed FESOP Renewal No.: F003-19156-05190.

Company Name: Brooks Construction Company, Inc.  
 Plant Location: 5536 Hoagland Road, Poe, Indiana 46745  
 County: Allen  
 Permit Reviewer: Seema Roy

**\*\* aggregate dryer burner\*\***

The following calculations determine the amount of emissions created by the combustion of #2 distillate fuel oil  
 @ 0.50 % sulfur, from the aggregate dryer burner, based on 8,760 hours of use and  
 US EPA's AP-42, 5th Edition, Section 1.3 - Fuel Oil Combustion, Tables 1.3-1, 1.3-2, and 1.3-5.

Criteria Pollutant:	$\frac{120 \text{ MMBtu/hr} * 8,760 \text{ hr/yr}}{140,000 \text{ Btu/gal} * 2,000 \text{ lb/ton}}$	* Ef (lb/1,000 gal) = (ton/yr)
<b>P M:</b>	2.0 lb/1000 gal =	<b>7.51 ton/yr</b>
<b>P M-10:</b>	3.3 lb/1000 gal =	<b>12.39 ton/yr</b>
<b>S O 2:</b>	78.5 lb/1000 gal =	<b>294.71 ton/yr</b>
<b>N O x:</b>	24.0 lb/1000 gal =	<b>90.10 ton/yr</b>
<b>V O C:</b>	0.20 lb/1000 gal =	<b>0.75 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal =	<b>18.77 ton/yr</b>

**\*\*hot oil heater\*\***

The following calculations determine the amount of emissions created by the combustion of #2 distillate fuel oil  
 @ 0.50 % sulfur, from hot oil heater, based on 8760 hours of use and US EPA's AP-42,  
 5th Edition, Section 1.3 - Fuel Oil Combustion, Tables 1.3-1, 1.3-2, and 1.3-6.

Criteria Pollutant:	$\frac{0.7 \text{ MMBtu/hr} * 8,760 \text{ hr/yr}}{140,000 \text{ Btu/gal} * 2,000 \text{ lb/ton}}$	* Ef (lb/1,000 gal) = (ton/yr)
<b>P M:</b>	2.0 lb/1000 gal =	<b>0.04 ton/yr</b>
<b>P M-10:</b>	3.3 lb/1000 gal =	<b>0.07 ton/yr</b>
<b>S O 2:</b>	71.0 lb/1000 gal =	<b>1.55 ton/yr</b>
<b>N O x:</b>	20.0 lb/1000 gal =	<b>0.44 ton/yr</b>
<b>V O C:</b>	0.34 lb/1000 gal =	<b>0.01 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal =	<b>0.11 ton/yr</b>

**\*\* aggregate drying: drum-mix plant \*\***

The following calculations determine the amount of worst case emissions created by aggregate drying before controls,  
 based on 8,760 hours of use and USEPA's AP-42, 5th Edition, Section 11.1 - Hot Mix Asphalt Plants, Tables 11.1-5 and 11.1-10  
 for a drum mix dryer which has the capability of combusting fuel oil:

Pollutant:	Ef	lb/ton x	400	ton/hr x	8,760	hr/yr
			2,000	lb/ton		

Criteria Pollutant:	Ef	lb/ton =	(ton/yr)
<b>P M:</b>	19	lb/ton =	<b>33,288.00 ton/yr</b>
<b>P M-10:</b>	4.3	lb/ton =	<b>7,533.60 ton/yr</b>
<b>VOC:</b>	0.006317	lb/ton =	<b>11.07 ton/yr</b>

The VOC emission factor for aggregate drying includes HAP emissions which are assumed to be VOC.

**\*\* conveying / handling \*\***

The following calculations determine the amount of emissions created by material handling, based on 8,760 hours of use and AP-42, Section 13.2.4, Equation 1. The emission factor for calculating PM emissions is calculated as follows:

PM-10 Emissions:

$$E = k \cdot (0.0032)^k \cdot \left( \frac{U}{5} \right)^{1.3} \cdot \left( \frac{M}{2} \right)^{1.4}$$

= 1.27E-03 lb PM-10/ton  
 2.68E-03 lb PM/ton

where k = 0.35 (particle size multiplier for <10um)  
 0.74 (particle size multiplier for <30um)  
 U = 12 mph mean wind speed  
 M = 4.1 average material moisture content (%)

$$\frac{400 \text{ ton/hr} \cdot 8,760 \text{ hrs/yr} \cdot E_f \text{ (lb/ton of material)}}{2,000 \text{ lb/ton}} = \text{(ton/yr)}$$

**Total PM 10 Emissions: 2.22 tons/yr**  
**Total PM Emissions: 4.70 tons/yr**

**\*\* unpaved roads \*\***

The following calculations determine the amount of emissions created by vehicle traffic on unpaved roads, based on 8,760 hours of use and AP-42, Ch 13.2.2.

I. Front End Loader

48 trip/hr x  
 0.038 mile/trip x  
 2 (round trip) x  
 8,760 hr/yr = 31956.48 miles per year

$$E_f = k \cdot (s/12)^a \cdot (W/3)^b$$

= 2.01 lb PM-10/mile  
 = 7.89 lb PM/mile

where k = 1.5 (particle size multiplier for PM-10)  
 k = 4.9 (particle size multiplier for PM)  
 s = 4.8 mean % silt content of unpaved roads  
 a = 0.9 Constant for PM-10  
 a = 0.7 Constant for PM  
 b = 0.45 Constant for PM and PM-10  
 W = 36 tons average vehicle weight

PM:  $\frac{7.89 \text{ lb/mi} \times 31956.48 \text{ mi/yr}}{2000 \text{ lb/ton}} = 126.12 \text{ tons/yr}$

PM-10:  $\frac{2.01 \text{ lb/mi} \times 31956.48 \text{ mi/yr}}{2000 \text{ lb/ton}} = 32.14 \text{ tons/yr}$

**Total PM Emissions From Unpaved Roads = 126.12 tons/yr**  
**Total PM-10 Emissions From Unpaved Roads = 32.14 tons/yr**

**\*\* storage \*\***

The following calculations determine the amount of emissions created by wind erosion of storage stockpiles, based on 8,760 hours of use and USEPA's AP-42 (Pre 1983 Edition), Section 11.2.3.

Material	Silt Content (wt %)	Pile Size (acres)	Storage Capacity (tons)	PM Emissions tons/yr	PM-10 Emissions tons/yr
Slag	1.0	0.200	1,000	0.04	0.01
RAP	0.8	0.500	20,000	0.08	0.03
<b>Total</b>				<b>0.13</b>	<b>0.04</b>

Sample Calculation:

$$E_f = 1.7 \cdot (s/1.5) \cdot (365-p)/235 \cdot (f/15)$$

$$= 1.16 \text{ lb/acre/day}$$

where s = 1 % silt  
 p = 125 days of rain greater than or equal to 0.01 inches  
 f = 15 % of wind greater than or equal to 12 mph

Note: PM-10 emissions are approximately 35% of PM emissions

**\*\*cold mix VOC storage emissions \*\***

The following calculations determine the amount of worst case VOC emissions created by the application of cutback asphalt with a typical value of 35% by volume of diluent, based on 8,760 hours of use and USEPA's AP-42, 5th Edition, Section 4.5, Table 4.5-1.

VOC Emission Factor = 1.7% weight percent flash-off of cold mix  
 Potential Throughput (tons/yr) = 3,504,000 tons/yr stockpile mix

Potential VOC Emissions (tons/yr) = Potential Throughput (tons/yr) \* wt percent flash-off  
**Potential VOC Emissions = 58,867.20 tons/yr**

\* Weight percent flash-off is based on a 7.0 percent by weight of cutback asphalt in stockpile mix, of which 24% evaporates based on the cutback asphalt containing 35% by volume of diluent of which 95% evaporates (from Table 4.5-1).

**\*\* summary of source emissions before controls \*\***

Criteria Pollutants:

<b>P M:</b>	<b>33,426.50 ton/yr</b>	
<b>P M-10:</b>	<b>7,580.47 ton/yr</b>	
<b>S O 2:</b>	<b>296.27 ton/yr</b>	
<b>N O x:</b>	<b>90.54 ton/yr</b>	
<b>V O C:</b>	<b>58,879.03 ton/yr</b>	(VOCs include HAPs from aggregate drying operation)
<b>C O:</b>	<b>18.88 ton/yr</b>	

**\*\* source emissions after controls \*\***

In order to qualify for the FESOP program, this facility must limit PM-10, SO<sub>2</sub>, and VOC emissions to 99.9 tons per year. Consequently, SO<sub>2</sub> emissions from the aggregate dryer must be limited to 98.35 tons per year (99.9 ton/yr - 1.55 ton/yr from the hot oil heater).

\* Emissions of PM and PM-10 from aggregate drying operations are controlled with a 99.900 % control efficiency.

The following calculations determine the amount of emissions created by No.2 distillate fuel oil @ 0.50 % sulfur based on a fuel usage limitation of 2,505,732 gal/yr:

**No. 2 Distillate Oil:**  $\frac{2,505,732 \text{ gal/yr}}{2,000 \text{ lb/ton}}$  \* Ef (lb/1,000 gal) = (ton/yr)

<b>P M:</b>	2.0 lb/1000 gal =	<b>2.51E-03 ton/yr *</b>
<b>P M-10:</b>	3.3 lb/1000 gal =	<b>4.13E-03 ton/yr *</b>
<b>S O 2:</b>	78.5 lb/1000 gal =	<b>98.35 ton/yr</b>
<b>N O x:</b>	24.0 lb/1000 gal =	<b>30.07 ton/yr</b>
<b>V O C:</b>	0.20 lb/1000 gal =	<b>0.25 ton/yr</b>
<b>C O:</b>	5.0 lb/1000 gal =	<b>6.26 ton/yr</b>

**Primary Fuel Usage Limitations**

Fuel Oil: #2 distillate fuel oil

$\frac{98.35 \text{ tons SO}_2/\text{year limited}}{294.71 \text{ tons SO}_2/\text{year potential}} \times 7508.57 \frac{\text{Kgals}}{\text{year potential}} = 2505.73 \frac{\text{Kgals}}{\text{year limited}}$

**\*\* source emissions after controls \*\***

hot oil heater:		nonfugitive	
<b>P M:</b>	0.04 ton/yr x	100.00% emitted after controls =	<b>0.04 ton/yr</b>
<b>P M-10:</b>	0.07 ton/yr x	100.00% emitted after controls =	<b>0.07 ton/yr</b>
aggregate drying:		nonfugitive	
<b>P M:</b>	33,288.00 ton/yr x	0.10% emitted after controls =	<b>33.29 ton/yr</b>
<b>P M-10:</b>	7,533.60 ton/yr x	0.10% emitted after controls =	<b>7.53 ton/yr</b>
<b>VOC:</b>	11.07 ton/yr x	100.00% emitted after controls =	<b>11.07 ton/yr</b>
conveying/handling:		fugitive	
<b>P M:</b>	4.70 ton/yr x	50% emitted after controls =	<b>2.35 ton/yr</b>
<b>P M-10:</b>	2.22 ton/yr x	50% emitted after controls =	<b>1.11 ton/yr</b>
unpaved roads:		fugitive	
<b>P M:</b>	126.12 ton/yr x	50% emitted after controls =	<b>63.06 ton/yr</b>
<b>P M-10:</b>	32.14 ton/yr x	50% emitted after controls =	<b>16.07 ton/yr</b>
storage piles:		fugitive	
<b>P M:</b>	0.13 ton/yr x	50% emitted after controls =	<b>0.06 ton/yr</b>
<b>P M-10:</b>	0.04 ton/yr x	50% emitted after controls =	<b>0.02 ton/yr</b>
cold mix VOC storage:		fugitive	
<b>VOC:</b>	58,867.20 ton/yr	92.26 Limited Diluent Throughput (tons/yr) :	<b>87.65 ton/yr</b>

**\*\* summary of source emissions after controls \*\***

<b>Criteria Pollutant:</b>	<b>Non-Fugitive</b>	<b>Fugitive</b>	<b>Total</b>
<b>PM:</b>	<b>33.33 ton/yr</b>	<b>65.48 ton/yr</b>	<b>98.81 ton/yr</b>
<b>PM-10:</b>	<b>7.61 ton/yr</b>	<b>17.21 ton/yr</b>	<b>24.82 ton/yr</b>
<b>S O 2:</b>	<b>99.90 ton/yr</b>	<b>0.00 ton/yr</b>	<b>99.90 ton/yr</b>
<b>N O x:</b>	<b>30.51 ton/yr</b>	<b>0.00 ton/yr</b>	<b>30.51 ton/yr</b>
<b>V O C:</b>	<b>11.33 ton/yr</b>	<b>87.65 ton/yr</b>	<b>98.98 ton/yr</b>
<b>C O:</b>	<b>6.37 ton/yr</b>	<b>0.00 ton/yr</b>	<b>6.37 ton/yr</b>

**Hazardous Air Pollutants (HAPs)**

**\*\* aggregate dryer burner\*\***

The following calculations determine the amount of HAP emissions created by the combustion of distillate fuel oil before & after controls @ 0.50 % sulfur, from the aggregate dryer burner, based on 8,760 hours of use and US EPA's AP-42, 5th Edition, Section 1.3 - Fuel Oil Combustion, Table 1.3-11.

Hazardous Air Pollutants (HAPs):	<u>120 MMBtu/hr * 8760 hr/yr</u> 2,000 lb/ton	* Ef (lb/10 <sup>12</sup> Btu) = (ton/yr)	
		Potential To Emit	Limited Emissions
<b>Arsenic:</b>	4.2 lb/10 <sup>12</sup> Btu =	2.21E-03 ton/yr	2.21E-06 ton/yr
<b>Beryllium:</b>	2.5 lb/10 <sup>12</sup> Btu =	1.31E-03 ton/yr	1.31E-06 ton/yr
<b>Cadmium:</b>	11 lb/10 <sup>12</sup> Btu =	5.78E-03 ton/yr	5.78E-06 ton/yr
<b>Chromium:</b>	67 lb/10 <sup>12</sup> Btu =	3.52E-02 ton/yr	3.52E-05 ton/yr
<b>Lead:</b>	8.9 lb/10 <sup>12</sup> Btu =	4.68E-03 ton/yr	4.68E-06 ton/yr
<b>Manganese:</b>	14 lb/10 <sup>12</sup> Btu =	7.36E-03 ton/yr	7.36E-06 ton/yr
<b>Mercury:</b>	3 lb/10 <sup>12</sup> Btu =	1.58E-03 ton/yr	1.58E-06 ton/yr
<b>Nickel:</b>	18 lb/10 <sup>12</sup> Btu =	9.46E-03 ton/yr	9.46E-06 ton/yr
	Total HAPs =	6.76E-02 ton/yr	6.76E-05 ton/yr

**\*\* aggregate drying: drum-mix plant \*\***

The following calculations determine the amount of HAP emissions created by aggregate drying before & after controls, based on 8,760 hours of use and USEPA's AP-42, 5th Edition, Section 11.1 - Hot Mix Asphalt Plants, Table 11.1-10 for a drum mix dryer which can be fired with fuel oil.

Pollutant:	<u>Ef</u>	<u>lb/ton x</u>	<u>400</u>	<u>ton/hr x</u>	<u>8760 hr/yr</u>	
			2000	lb/ton		
Hazardous Air Pollutants (HAPs):					Potential To Emit	Limited Emissions
<b>Acetaldehyde:</b>	1.30E-03	lb/ton =			2.28 ton/yr	2.28 ton/yr
<b>Acrolein:</b>	2.60E-05	lb/ton =			0.05 ton/yr	0.05 ton/yr
<b>Benzene:</b>	4.10E-04	lb/ton =			0.72 ton/yr	0.72 ton/yr
<b>Ethylbenzene:</b>	3.80E-04	lb/ton =			0.67 ton/yr	0.67 ton/yr
<b>Formaldehyde:</b>	2.40E-03	lb/ton =			4.20 ton/yr	4.20 ton/yr
<b>Methyl Ethyl Ketone:</b>	2.00E-05	lb/ton =			0.04 ton/yr	0.04 ton/yr
<b>Propionaldehyde:</b>	1.30E-04	lb/ton =			0.23 ton/yr	0.23 ton/yr
<b>Quinone:</b>	1.60E-04	lb/ton =			0.28 ton/yr	0.28 ton/yr
<b>Toluene:</b>	7.50E-04	lb/ton =			1.31 ton/yr	1.31 ton/yr
<b>**Total Polycyclic Organic Matter (POM):</b>	5.810E-04	lb/ton =			1.02 ton/yr	1.02 ton/yr
<b>Xylene:</b>	1.60E-04	lb/ton =			0.28 ton/yr	0.28 ton/yr
					Total HAPs =	11.07 ton/yr

\*\* total POM includes 2-Methylnaphthalene, Acenaphthylene, Anthracene, Fluorene, Naphthalene, Phenanthrene, and Pyrene.

**\*\* summary of source HAP emissions potential to emit \*\***

Hazardous Air Pollutants (HAPs):

Acetaldehyde:	<b>2.278</b>	ton/yr
Acrolein:	<b>0.046</b>	ton/yr
Arsenic:	<b>0.002</b>	ton/yr
Benzene:	<b>0.718</b>	ton/yr
Beryllium:	<b>0.001</b>	ton/yr
Cadmium:	<b>0.006</b>	ton/yr
Chromium:	<b>0.035</b>	ton/yr
Ethylbenzene:	<b>0.666</b>	ton/yr
Formaldehyde:	<b>4.205</b>	ton/yr
Lead:	<b>0.005</b>	ton/yr
Manganese:	<b>0.007</b>	ton/yr
Mercury:	<b>0.002</b>	ton/yr
Methyl Ethyl Ketone:	<b>0.035</b>	ton/yr
Nickel:	<b>0.009</b>	ton/yr
Propionaldehyde:	<b>0.228</b>	ton/yr
Quinone:	<b>0.280</b>	ton/yr
Toluene:	<b>1.314</b>	ton/yr
Total POM:	<b>1.018</b>	ton/yr
Xylene:	<b>0.280</b>	ton/yr
<b>Total:</b>	<b>11.13</b>	<b>ton/yr</b>

**\*\* summary of source HAP limited emissions \*\***

Hazardous Air Pollutants (HAPs):

Acetaldehyde:	<b>2.278</b>	ton/yr
Acrolein:	<b>0.046</b>	ton/yr
Arsenic:	<b>0.000</b>	ton/yr
Benzene:	<b>0.718</b>	ton/yr
Beryllium:	<b>0.000</b>	ton/yr
Cadmium:	<b>0.000</b>	ton/yr
Chromium:	<b>0.000</b>	ton/yr
Ethylbenzene:	<b>0.666</b>	ton/yr
Formaldehyde:	<b>4.205</b>	ton/yr
Lead:	<b>0.000</b>	ton/yr
Manganese:	<b>0.000</b>	ton/yr
Mercury:	<b>0.000</b>	ton/yr
Methyl Ethyl Ketone:	<b>0.035</b>	ton/yr
Nickel:	<b>0.000</b>	ton/yr
Propionaldehyde:	<b>0.228</b>	ton/yr
Quinone:	<b>0.280</b>	ton/yr
Toluene:	<b>1.314</b>	ton/yr
Total Polycyclic Organic Matter:	<b>1.018</b>	ton/yr
Xylene:	<b>0.280</b>	ton/yr
<b>Total:</b>	<b>11.07</b>	<b>ton/yr</b>

**\*\* miscellaneous \*\***

**326 IAC 7 Compliance Calculations:**

The following calculations determine the maximum sulfur content of distillate fuel oil allowable by 326 IAC 7:

$$\begin{array}{rcl} 0.5 \text{ lb/MMBtu} \times & 140,000 \text{ Btu/gal} = & 70 \text{ lb/1000gal} \\ 70 \text{ lb/1000gal} / & 142 \text{ lb/1000 gal} = & 0.5 \% \end{array}$$

Sulfur content must be less than or equal to 0.5% to comply with 326 IAC 7.

**326 IAC 6-3-2 Compliance Calculations:**

The following calculations determine compliance with 326 IAC 6-3-2 for process weight rates in excess of 30 tons per hour:

$$\text{limit} = 55 * ( 400 ^{0.11} ) - 40 = 66.31 \text{ lb/hr or } 290.45 \text{ ton/yr}$$

Since this emission limit exceeds the PSD source definition of 250 tons/yr, the Subpart I allowable emission limit of 77.11 tons/yr, and the 326 IAC 6-1-2 allowable emission limit of 57.83 tons/yr, compliance with the PM limit pursuant to 326 IAC 6-1-2 will satisfy the requirements of 326 IAC 6-3-2 and will exempt the source from the requirements of 326 IAC 2-2 (PSD).

**PM-10 Emission Limit for Aggregate Dryer:**

$$(99.9 \text{ tons PM-10/yr} - 18.4 \text{ tons PM-10/yr from other sources}) = 81.5 \text{ tons PM-10/yr} = 18.61 \text{ lbs/hr}$$

PM-10 emissions from the aggregate dryer are controlled to 1.72 lbs/hr < 11.7 lbs/hr (Will comply)

**Compliance with NSPS (326 IAC 12; 40 CFR 60.90 to 60.93, Subpart I) and 326 IAC 6-1-2**

The following calculations determine compliance with 326 IAC 6-1-2 (for counties listed in 326 IAC 6-1-7) and NSPS, which limits stack emissions from asphalt plants to 0.03 gr/dscf (when in counties listed in 326 IAC 6-1-7), and 0.04 gr/dscf (when not located in those counties):

$$\frac{33.29 \text{ ton/yr} * 2000 \text{ lb/ton} * 7000 \text{ gr/lb}}{525,600 \text{ min/yr} * 51,348 \text{ dscf/min}} = 0.017 \text{ gr/dscf} \quad (\text{will comply})$$

Allowable particulate emissions under 326 IAC 6-1-2 equate to	57.83 tons per year, or	13.20 lbs/hr.
Allowable particulate emissions under NSPS equate to	77.11 tons per year, or	17.61 lbs/hr.

Note:

$$\begin{array}{rcl} \text{SCFM} = & 72,000 \text{ acfm} * (460 + 68) * (1 - 0.041) / (460 + 250) \\ = & 51,348 \text{ dscfm} \end{array}$$

Assumes exhaust gas temperature of 250F, exhaust gas moisture content of 4.1% and exhaust gas flow of 72,000 acfm.