



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

TO: Interested Parties / Applicant
DATE: March 2, 2007
RE: Masterfab, Inc. / 039-19842-00001
FROM: Nisha Sizemore
Chief, Permits Branch
Office of Air Quality

Notice of Decision: Approval – Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-6-1(b) or IC 13-15-6-1(a) require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204.

For an **initial Title V Operating Permit**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **thirty (30)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(b).

For a **Title V Operating Permit renewal**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **fifteen (15)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(a).

The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

Pursuant to 326 IAC 2-7-18(d), any person may petition the U.S. EPA to object to the issuance of an initial Title V operating permit, permit renewal, or modification within sixty (60) days of the end of the forty-five (45) day EPA review period. Such an objection must be based only on issues that were raised with reasonable specificity during the public comment period, unless the petitioner demonstrates that it was impracticable to raise such issues, or if the grounds for such objection arose after the comment period.

To petition the U.S. EPA to object to the issuance of a Title V operating permit, contact:

U.S. Environmental Protection Agency
401 M Street
Washington, D.C. 20406

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

PART 70 OPERATING PERMIT RENEWAL OFFICE OF AIR QUALITY

**Masterfab, Inc.
16618 Maple City Drive
Goshen, Indiana 46526**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T039-19842-00001	
Original signed by: Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: March 2, 2007 Expiration Date: March 2, 2012

TABLE OF CONTENTS

A	SOURCE SUMMARY	5
A.1	General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]	
A.3	Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.4	Part 70 Permit Applicability [326 IAC 2-7-2]	
B	GENERAL CONDITIONS.....	7
B.1	Definitions [326 IAC 2-7-1]	
B.2	Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]	
B.3	Term of Conditions [326 IAC 2-1.1-9.5]	
B.4	Enforceability [326 IAC 2-7-7]	
B.5	Severability [326 IAC 2-7-5(5)]	
B.6	Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	
B.7	Duty to Provide Information [326 IAC 2-7-5(6)(E)]	
B.8	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]	
B.9	Annual Compliance Certification [326 IAC 2-7-6(5)]	
B.10	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3)and (13)][326 IAC 2-7-6(1)and(6)] [326 IAC 1-6-3]	
B.11	Emergency Provisions [326 IAC 2-7-16]	
B.12	Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]	
B.13	Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]	
B.14	Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]	
B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]	
B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]	
B.17	Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]	
B.18	Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]	
B.19	Permit Revision under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]	
B.20	Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]	
B.21	Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2-3-2]	
B.22	Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]	
B.23	Transfer of Ownership or Operational Control [326 IAC 2-7-11]	
B.24	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]	
B.25	Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]	
C	SOURCE OPERATION CONDITIONS	16
	Emission Limitations and Standards [326 IAC 2-7-5(1)]	
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2	Opacity [326 IAC 5-1]	
C.3	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.4	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.5	Fugitive Dust Emissions [326 IAC 6-4]	
C.6	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	Testing Requirements [326 IAC 2-7-6(1)]	
C.7	Performance Testing [326 IAC 3-6]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.8	Compliance Requirements [326 IAC 2-1.1-11]	

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.10 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.11 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.12 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
- C.13 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]
- C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-3]
- C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-3]

Stratospheric Ozone Protection

- C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

D.1 FACILITY OPERATION CONDITIONS – Coating Booths.....23

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Best Available Control Technology (BACT) and Volatile Organic Compounds (VOCs) [326 IAC 8-1-6] [326 IAC 2-2]
- D.1.2 Particulate [326 IAC 6-3-2(d)]
- D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.4 Volatile Organic Compounds (VOC) [326 IAC 8-1-4] [326 IAC 8-1-2(a)]
- D.1.5 Hazardous Air Pollutants (HAP) and Volatile Organic Compounds (VOC)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.6 Monitoring
- D.1.7 Visible Emissions Notations

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.8 Record Keeping Requirements
- D.1.9 Reporting Requirements
- D.1.10 General Provisions Relating to National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production under 40 CFR Part 63 [326 IAC 20-1][40 CFR Part 63, Subpart A]
- D.1.11 NESHAP WWW Requirements [40 CFR Part 63, Subpart WWW]
- D.1.12 State Only Reinforced Plastic Composites National Emission Standards for Hazardous Air Pollutants for Reinforced Plastic Composites Production (NESHAP) Requirements [326 IAC 20-56]
- D.1.13 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-56-2]
- D.1.14 One Time Deadlines Relating to NESHAP for Reinforced Plastic Composites Production [40 CFR Part 63, Subpart WWW]

D.2 FACILITY OPERATION CONDITIONS – Insignificant Activities66

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.2.1 Particulate Emission Limitations for Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2(e)]

Certification.....	67
Emergency Occurrence Report.....	68
Quarterly Report	70
Quarterly Deviation and Compliance Monitoring Report	71

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.4 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary fiberglass parts manufacturing plant.

Responsible Official:	Christy E. Miller
Source Address:	16618 Maple City Drive, Goshen, IN 46526
Mailing Address:	PO Box 463, Goshen, IN 46526
General Source Phone Number:	574-642-4888
SIC Code:	3089
County Location:	Elkhart
Source Location Status:	Basic Nonattainment for 8 hour Ozone Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Minor Source, under PSD; Major Source, under Emission Offset Rule; Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) gelcoat booth, constructed in 1990, using airless-air assisted application as a form of HVLP application, with a maximum capacity of 110 pounds per hour of gelcoat, using dry filters as control, and exhausting to stack 1.2(a) through 1.2(c).
- (b) One (1) lamination booth, constructed in 1990, using non-atomized spray for application, with a maximum capacity of 414 pounds per hour of resin, using dry filters as control, and exhausting to stack 1.3(a) through 1.3(e).
- (c) Mold and pattern shop area, constructed in 1990, using non-atomized spray for resin application and airless or air assisted airless as a form of HVLP application for gelcoat with a maximum capacity of coating resin of 2.07 pounds per hour, and maximum capacity of coating gelcoat of 0.67 pounds per hour using dry filters for particulate control, and exhausting to stack 1.5
- (d) Final finish & specialty products area, constructed in 1990, with a maximum capacity of coating resin of 0.32 pounds per hour, and maximum capacity of coating gelcoat of 0.91 pounds per hour using dry filters for particulate control, no direct exhaust.
- (e) Mold preparation area with no direct exhaust.

Under NESHAP, Subpart WWWW, the gelcoat booth, lamination booth, mold and pattern shop area, final finish & specialty products area and mold preparation area, are considered an existing affected source because the construction of the source commenced prior to August 2, 2001 and the source is not reconstructed.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Grinding and machining operations controlled with fabric filters scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations.
 - (1) One (1) grinding area, with a maximum capacity of 1104 pounds per hour, using bag filters for particulate control, and exhausting to stack 1.4(a) through stack 1.4(h). [326 IAC 6-3-2 (e)]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]

- (a) This permit, T039-19842-00001, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than April 15 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) The Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) for the source as described in 326 IAC 1-6-3. At a minimum, the PMPs shall include:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in

- inventory for quick replacement.
- (b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
 - (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality,
Compliance Section), or
Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967
Northern Regional Office:
Telephone Number: 574-245-4870
Facsimile Number: 574-245-4877

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and

(C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.

- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (d) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]

- (a) All terms and conditions of permits established prior to T039-19842-00001 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised under 326 IAC 2-7-10.5, or
 - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit.

B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
 - (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on

or before the date it is due.

- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.

B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request.
[326 IAC 2-7-11(c)(3)]

B.19 Permit Revision under Economic Incentives and Other Programs [326 IAC 2-7-5(8)][326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.

- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b), (c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.21 Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2-3-2]

- (a) A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

- (b) Any modification at an existing major source is governed by the requirements of 326 IAC 2-3-2.

B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations for Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;

- (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.7 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by

- the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.8 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.10 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.11 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on December 30, 1996.
- (b) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level.
[326 IAC 1-5-3]

C.12 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.13 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
 - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records;
 - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
 - (1) monitoring data;
 - (2) monitor performance data, if applicable; and
 - (3) corrective actions taken.

C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting

deadline.

- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

- (a) In accordance with the compliance schedule specified in 326 IAC 2-6-3(b)(1), starting in 2007 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:
- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
 - (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1(32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-3]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.
- (c) If there is a reasonable possibility that a "project" (as defined in 326 IAC 2-3-1 (II)) at an existing emissions unit, other than projects at a Clean Unit, which is not part of a "major modification" (as defined in 326 IAC 2-3-1 (z)) may result in significant emissions increase and the Permittee elects to utilize the "projected actual emissions" (as defined in 326 IAC 2-3-1 (mm)), the Permittee shall comply with following:
- (1) Before beginning actual construction of the "project" (as defined in 326 IAC 2-3-1 (II)) at

an existing emissions unit, document and maintain the following records:

- (A) A description of the project.
 - (B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.
 - (C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:
 - (i) Baseline actual emissions;
 - (ii) Projected actual emissions;
 - (iii) Amount of emissions excluded under section 326 IAC 2-3-1(mm)(2)(A)(3); and
 - (iv) An explanation for why the amount was excluded, and any netting calculations, if applicable.
- (2) Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and
- (3) Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR pollutant at the emissions unit.

C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-3]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.
- (f) If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any "project" (as defined in 326 IAC 2-3-1 (II)) at an existing emissions unit, and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:

- (1) The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as defined in 326 IAC 2-3-1 (qq), for that regulated NSR pollutant, and
 - (2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).
- (g) The report for a project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:
- (1) The name, address, and telephone number of the major stationary source.
 - (2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.
 - (3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-3-2(c)(3).
 - (4) Any other information that the Permittee deems fit to include in this report,

Reports required in this part shall be submitted to:

Indiana Department of Environmental Management
Air Compliance Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.

Stratospheric Ozone Protection

C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) One (1) gelcoat booth, constructed in 1990, using airless-air assisted application as a form of HVLP application, with a maximum capacity of 110 pounds per hour of gelcoat, using dry filters as control, and exhausting to stack 1.2(a) through 1.2(c);
- (b) One (1) lamination booth, constructed in 1990, using non-atomized spray for application, with a maximum capacity of 414 pounds per hour of resin, using dry filters as control, and exhausting to stack 1.3(a) through 1.3(e);
- (c) Mold and pattern shop area, constructed in 1990, using non-atomized spray for resin application and airless or air assisted airless as a form of HVLP application for gelcoat with a maximum capacity of coating resin of 2.07 pounds per hour, and maximum capacity of coating gelcoat of 0.67 pounds per hour using dry filters for particulate control, and exhausting to stack 1.5;
- (d) Final finish & specialty products area, constructed in 1990, using non-atomized spray for application, with a maximum capacity of coating resin of 0.32 pounds per hour, and maximum capacity of coating gelcoat of 0.91 pounds per hour using dry filters for particulate control, no direct exhaust; and
- (e) Mold preparation area with no direct exhaust

Under NESHAP, Subpart WWWW, the gelcoat booth, lamination booth, mold and pattern shop area, final finish & specialty products area and mold preparation area, are considered an existing affected source because the construction of the source commenced prior to August 2, 2001 and the source is not reconstructed.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Best Available Control Technology (BACT) and Volatile Organic Compounds (VOCs) [326 IAC 8-1-6] [326 IAC 2-2]

Pursuant to 326 IAC 8-1-6 and OP 20-10-93-0693 issued on June 18, 1990, the Best Available Control Technology (BACT) shall consist of the following for the one (1) gelcoat booth, one (1) lamination booth, Mold and shop pattern area, Final finish & specialty products area:

- (a) Use of resins, gel coats and solvents shall be limited such that the potential to emit (PTE) volatile organic compounds from resins, gel coats and solvents only shall be limited to less than or equal to 100 tons per twelve (12) consecutive months. Compliance with this limit shall be determined based upon the following criteria:
 - (1) Monthly usage by weight, monomer content, method of application, and other emission reduction techniques for each gel coat and resin shall be recorded. VOC emissions shall be calculated by multiplying the usage of each gel coat and resin by the emission factor that is appropriate for the monomer content, method of application, and other emission reduction techniques for each gel coating and resin, and summing the emissions for all gel coats and resins. Emission factors shall be obtained from the reference approved by IDEM, OAQ.

- (2) Until Such time that new emissions information is available by U.S. EPA in its AP-42 document or other U.S. EPA-approved form, emission factors shall be taken from the following reference approved by IDEM, OAQ: CFA Unified Emissions Factors for Open Molding of Composites July 23, 2001, and shall not exceed 32.3% styrene emitter per weight of gel coat applied and 17.7% styrene emitted per weight of resin applied. For the purposes of these emission calculations, monomer in resins and gel coats that is not styrene shall be considered as styrene on an equivalent basis.
- (3) Monthly usage by weight and VOC content of each solvent shall be recorded.
- (b) Lower Styrene resins less than 42%.
- (c) Use higher transfer efficiency guns.
- (d) Improved housekeeping.

Compliance with Condition D.1.1 (a) also renders the requirements of 326 IAC 2-2 not applicable.

D.1.2 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate from the one (1) gelcoat booth, one (1) lamination booth, Mold and shop pattern area, Final finish & specialty products area, and Mold preparation area, shall be controlled by a dry particulate filter and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for the gelcoat booth, lamination booth, mold and pattern shop area, final finish & specialty products area and mold preparation area.

Compliance Determination Requirements

D.1.4 Volatile Organic Compounds (VOC) [326 IAC 8-1-4] [326 IAC 8-1-2(a)]

Compliance with the VOC content and usage limitations contained in Condition D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets and using the CFA Unified Emissions Factors. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.5 Hazardous Air Pollutants (HAP) and Volatile Organic Compounds (VOC)

Compliance with the HAP monomer content limitations in conditions D.1.1 and D.1.2 shall be determined by one of the following:

- (a) The manufacturer's certified product data sheet.
- (b) The manufacturer's material safety data sheet.
- (c) Sampling and analysis, using any of the following test methods, as applicable:
 - (1) 40 CFR 60, Method 24, Appendix A (July 1, 1998), shall be used to measure the total volatile HAP and volatile organic compound (VOC) content of resins and gel coats. Method 24 may be modified for measuring the volatile HAP content of resins or gel coats to require that the procedure be performed on uncatalyzed resin or gel coat samples.
 - (2) 40 CFR 63, Method 311, Appendix A (July 1, 1998), shall be used to measure HAP content in resins and gel coats by direct injection into a gas chromatograph.
- (d) An alternate method approved by IDEM, OAQ.

Compliance Monitoring Requirements

D.1.6 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stack(s) (S1, S2, S3) while one or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

D.1.7 Visible Emissions Notations

- (a) Visible emission notations of the fiberglass facilities stack exhaust shall be performed once per week during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C- Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements

D.1.8 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.1. Records necessary to demonstrate compliance shall be available within 30 days of the end of each compliance period.
 - (1) The VOC content of each coating material and solvent used.
 - (2) The amount of coating material and solvent less water used on monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The total VOC usage for each month; and
 - (4) The weight of VOCs emitted for each compliance period.

- (b) To document compliance with Condition D.1.2, the Permittee shall maintain records that are complete and sufficient to establish compliance with the HAP monomer content limits. Records maintained shall be taken monthly. Examples of such records include but are not limited to:
 - (1) The usage by weight and monomer content of each resin and gel coat used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS), manufacturer's certified product data sheets, and calculations necessary to verify the type, amount used, and HAP content of each resin or gel coat;
 - (2) A log of the dates of use;
 - (3) Method of application and other emission reduction techniques for each resin and gel coat used;
 - (4) Monthly calculations demonstrating compliance on an equivalent emissions mass basis if non-compliant resins or gel coats are used during that month.
- (c) To document compliance with Condition D.1.4, the Permittee shall maintain the following training records:
 - (1) A copy of the current training program.
 - (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training. Records of prior training programs and former personnel are not required to be maintained.
- (d) To document compliance with Condition D.1.9, the Permittee shall maintain a log of monthly overspray observations, daily inspections of the filters.
- (e) To document compliance with Condition D.1.10, the Permittee shall maintain records of weekly visible emission notations of the fiberglass operations' stack exhaust.
- (f) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.9 Reporting Requirements

- (a) On or after January 1, 2002 until April 21, 2006, sources using monthly emissions averaging pursuant to 326 IAC 20-25-3(h)(2) and Condition D.1.5(a) shall submit a quarterly summary report and supporting calculations pursuant to 326 IAC 20-25-7(c). The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) A quarterly summary of the information to document compliance with Conditions D.1.1 and D.1.2(a) shall be submitted to the addresses listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]

D.1.10 General Provisions Relating to National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production under 40 CFR Part 63 [326 IAC 20-1][40 CFR Part 63, Subpart A]

- (a) Pursuant to 40 CFR 63.5925, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1, as specified in Table 15 of 40 CFR Part 63, Subpart WWWW in accordance with schedule in 40 CFR 63 Subpart WWWW.

- (b) Pursuant to 40 CFR 63.10, the Permittee shall submit all required notifications and reports to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

D.1.11 NESHAP WWWW Requirements [40 CFR Part 63, Subpart WWWW]

Pursuant to CFR Part 63, Subpart WWWW, the Permittee shall comply with the provisions of 40 CFR Part 63.5780, as specified as follows:

§63.5785 Am I subject to this subpart?

(a) You are subject to this subpart if you own or operate a reinforced plastic composites production facility that is located at a major source of HAP emissions. Reinforced plastic composites production is limited to operations in which reinforced and/or nonreinforced plastic composites or plastic molding compounds are manufactured using thermoset resins and/or gel coats that contain styrene to produce plastic composites. The resins and gel coats may also contain materials designed to enhance the chemical, physical, and/or thermal properties of the product. Reinforced plastic composites production also includes cleaning, mixing, HAP-containing materials storage, and repair operations associated with the production of plastic composites.

§63.5790 What parts of my plant does this subpart cover?

(a) This subpart applies to each new or existing affected source at reinforced plastic composites production facilities.

(b) The affected source consists of all parts of your facility engaged in the following operations: open molding, closed molding, centrifugal casting, continuous lamination, continuous casting, polymer casting, pultrusion, sheet molding compound (SMC) manufacturing, bulk molding compound (BMC) manufacturing, mixing, cleaning of equipment used in reinforced plastic composites manufacture, HAP-containing materials storage, and repair operations on parts you also manufacture.

(c) The following operations are specifically excluded from any requirements in this subpart: application of mold sealing and release agents; mold stripping and cleaning; repair of parts that you did not manufacture, including non-routine manufacturing of parts; personal activities that are not part of the manufacturing operations (such as hobby shops on military bases); prepreg materials as defined in Sec. 63.5935; non-gel coat surface coatings; application of putties, polyputties, and adhesives; repair or production materials that do not contain resin or gel coat; research and development operations as defined in section 112(c)(7) of the CAA; polymer casting; and closed molding operations (except for compression/injection molding). Note that the exclusion of certain operations from any requirements applies only to operations specifically listed in this paragraph. The requirements for any co-located operations still apply.

(d) Production resins that must meet military specifications are allowed to meet the organic HAP limit contained in that specification. In order for this exemption to be used, you must supply to the permitting authority the specifications certified as accurate by the military procurement officer, and those specifications must state a requirement for a specific resin, or a specific resin HAP content. Production resins for which this exemption is used must be applied with nonatomizing resin application equipment unless you can demonstrate this is infeasible. You must keep a record of the resins for which you are using this exemption.

§63.5795 How do I know if my reinforced plastic composites production facility is a new affected source or an existing affected source?

(a) A reinforced plastic composites production facility is a new affected source if it meets all the criteria in paragraphs (a)(1) and (2) of this section.

(1) You commence construction of the source after August 2, 2001.

(2) You commence construction, and no other reinforced plastic composites production source exists at that site.

(b) For the purposes of this subpart, an existing affected source is any affected source that is not a new affected source.

§63.5796 What are the organic HAP emissions factor equations in Table 1 to this subpart, and how are they used in this subpart?

Emissions factors are used in this subpart to determine compliance with certain organic HAP emissions limits in Tables 3 and 5 to this subpart. You may use the equations in Table 1 to this subpart to calculate your emissions factors. Equations are available for each open molding operation and centrifugal casting operation and have units of pounds of organic HAP emitted per ton (lb/ton) of resin or gel coat applied. These equations are intended to provide a method for you to demonstrate compliance without the need to conduct for a HAP emissions test. In lieu of these equations, you can elect to use site-specific organic HAP emissions factors to demonstrate compliance provided your site-specific organic HAP emissions factors are incorporated in the facility's air emissions permit and are based on actual facility HAP emissions test data. You may also use the organic HAP emissions factors calculated using the equations in Table 1 to this subpart, combined with resin and gel coat use data, to calculate your organic HAP emissions.

63.5797 How do I determine the organic HAP content of my resins and gel coats?

In order to determine the organic HAP content of resins and gel coats, you may rely on information provided by the material manufacturer, such as manufacturer's formulation data and material safety data sheets (MSDS), using the procedures specified in paragraphs (a) through (c) of this section, as applicable.

(a) Include in the organic HAP total each organic HAP that is present at 0.1 percent by mass or more for Occupational Safety and Health Administration-defined carcinogens, as specified in 29 CFR

1910.1200(d)(4) and at 1.0 percent by mass or more for other organic HAP compounds.

(b) If the organic HAP content is provided by the material supplier or manufacturer as a range, you must use the upper limit of the range for determining compliance. If a separate measurement of the total organic HAP content, such as an analysis of the material by EPA Method 311 of appendix A to 40 CFR part 63, exceeds the upper limit of the range of the total organic HAP content provided by the material supplier or manufacturer, then you must use the measured organic HAP content to determine compliance.

(c) If the organic HAP content is provided as a single value, you may use that value to determine compliance. If a separate measurement of the total organic HAP content is made and is less than 2 percentage points higher than the value for total organic HAP content provided by the material supplier or manufacturer, then you still may use the provided value to demonstrate compliance. If the measured total organic HAP content exceeds the provided value by 2 percentage points or more, then you must use the measured organic HAP content to determine compliance.

§63.5798 What if I want to use, or I manufacture, an application technology (new or existing) whose organic HAP emissions characteristics are not represented by the equations in Table 1 to this subpart?

If you wish to use a resin or gel coat application technology (new or existing), whose emission characteristics are not represented by the equations in Table 1 to this subpart, you may use the procedures in paragraphs (a) or (b) of this section to establish an organic HAP emissions factor. This organic HAP emissions factor may then be used to determine compliance with the emission limits in this subpart, and to calculate facility organic HAP emissions.

(a) Perform a organic HAP emissions test to determine a site-specific organic HAP emissions factor using the test procedures in §63.5850.

(b) Submit a petition to the Administrator for administrative review of this subpart. This petition must contain a description of the resin or gel coat application technology and supporting organic HAP emissions test data obtained using EPA test methods or their equivalent. The emission test data should be obtained using a range of resin or gel coat HAP contents to demonstrate the effectiveness of the technology under the different conditions, and to demonstrate that the technology will be effective at different sites. We will review the submitted data, and, if appropriate, update the equations in Table 1 to this subpart.

§63.5799 How do I calculate my facility's organic HAP emissions on a tpy basis for purposes of determining which paragraphs of §63.5805 apply?

To calculate your facility's organic HAP emissions in tpy for purposes of determining which paragraphs in §63.5805 apply to you, you must use the procedures in either paragraph (a) of this section for new facilities prior to startup, or paragraph (b) of this section for existing facilities and new facilities after startup. You are not required to calculate or report emissions under this section if you are an existing facility that does not have centrifugal casting or continuous lamination/casting operations, or a new facility that does not have any of the following operations: open molding, centrifugal casting, continuous lamination/casting, pultrusion, SMC and BMC manufacturing, and mixing. Emissions calculation and emission reporting procedures in other sections of this subpart still apply. Calculate organic HAP emissions prior to any add-on control device, and do not include organic HAP emissions from any resin or

gel coat used in operations subject to the Boat Manufacturing NESHAP, 40 CFR part 63, subpart VVVV, or from the manufacture of large parts as defined in §63.5805(d)(2). For centrifugal casting operations at existing facilities, do not include any organic HAP emissions where resin or gel coat is applied to an open centrifugal mold using open molding application techniques. Table 1 and the Table 1 footnotes to this subpart present more information on calculating centrifugal casting organic HAP emissions. The timing and reporting of these calculations is discussed in paragraph (c) of this section.

(b) For existing facilities and new facilities after startup, you may use the procedures in either paragraph (b)(1) or (2) of this section. If the emission factors for an existing facility have changed over the period of time prior to their initial compliance date due to incorporation of pollution-prevention control techniques, existing facilities may base the average emission factor on their operations as they exist on the compliance date. If an existing facility has accepted an enforceable permit limit that would result in less than 100 tpy of HAP measured prior to any add-on controls, and can demonstrate that they will operate at that level subsequent to the compliance date, they can be deemed to be below the 100 tpy threshold.

(1) Use a calculated emission factor. Calculate a weighted average organic HAP emissions factor on a lbs/ton of resin and gel coat basis. Base the weighted average on the prior 12 months of operation. Multiply the weighted average organic HAP emissions factor by resin and gel coat use over the same period. You may calculate this organic HAP emissions factor based on the equations in Table 1 to this subpart, or you may use any organic HAP emissions factor approved by us, such as factors from AP-42, or sitespecific organic HAP emissions factors if they are supported by HAP emissions test data.

(2) Conduct performance testing. Conduct performance testing using the test procedures in §63.5850 to determine a site-specific organic HAP emissions factor in units of lbs/ton of resin and gel coat used. Conduct the test under conditions expected to result in the highest possible organic HAP emissions. Multiply this factor by annual resin and gel coat use to determine annual organic HAP emissions. This calculation must be repeated and reported annually.

(c) Existing facilities must initially perform this calculation based on their 12 months of operation prior to the effective date of this subpart, and include this information with their initial notification report. Existing facilities must repeat the calculation based on their resin and gel coat use in the 12 months prior to their initial compliance date, and submit this information with their initial compliance report. After their initial compliance date, existing and new facilities must recalculate organic HAP emissions over the 12-month period ending June 30 or December 31, whichever date is the first date following their compliance date specified in §63.5800. Subsequent calculations should cover the periods in the semiannual compliance reports.

Compliance Dates and Standards

§ 63.5800 When do I have to comply with this subpart?

You must comply with the standards in this subpart by the dates specified in Table 2 to this subpart. Facilities meeting a organic HAP emissions standard based on a 12-month rolling average must begin collecting data on the compliance date in order to demonstrate compliance.

§ 63.5805 What standards must I meet to comply with this subpart?

You must meet the requirements of paragraphs (a) through (h) of this section that apply to you. You may elect to comply using any options to meeting these standards described in §§63.5810 through 63.5830. Use the procedures in §63.5799 to determine if you meet or exceed the 100 tpy threshold.

(b) All operations at existing facilities not listed in paragraph (a) of this section must meet the organic HAP emissions limit in Table 3 to this subpart and the work practice standards in Table 4 to this subpart that apply, regardless of the quantity of HAP emitted.

(g) If you have repair operations subject to this subpart as defined in § 63.5785, these repair operations must meet the requirements in Tables 3 and 4 to this subpart and are not required to meet the 95 percent organic HAP emissions reduction requirements in paragraph (a)(1) or (d) of this section.

Options for Meeting Standards

§ 63.5810 What are my options for meeting the standards for open molding and centrifugal casting operations at new and existing sources?

You must use one of the following methods in paragraphs (a) through (d) of this section to meet the standards for open molding or centrifugal casting operations in Table 3 or 5 to this subpart. You may use any control method that reduces organic HAP emissions, including reducing resin and gel coat organic

HAP content, changing to nonatomized mechanical application, using covered curing techniques, and routing part or all of your emissions to an add-on control. You may use different compliance options for the different operations listed in Table 3 or 5 to this subpart. The necessary calculations must be completed within 30 days after the end of each month. You may switch between the compliance options in paragraphs (a) through (d) of this section. When you change to an option based on a 12-month rolling average, you must base the average on the previous 12 months of data calculated using the compliance option you are changing to, unless you were previously using an option that did not require you to maintain records of resin and gel coat use. In this case, you must immediately begin collecting resin and gel coat use data and demonstrate compliance 12 months after changing options.

(a) Demonstrate that an individual resin or gel coat, as applied, meets the applicable emission limit in Table 3 or 5 to this subpart.

- (1) Calculate your actual organic HAP emissions factor for each different process stream within each operation type. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 to this subpart for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in § 63.5796. The emission factor calculation should include any and all emission reduction techniques used including any add-on controls. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.
- (2) If the calculated emission factor is less than or equal to the appropriate emission limit, you have demonstrated that this process stream complies with the emission limit in Table 3 to this subpart. It is not necessary that all your process streams, considered individually, demonstrate compliance to use this option for some process streams. However, for any individual resin or gel coat you use, if any of the process streams that include that resin or gel coat are to be used in any averaging calculations described in paragraphs (b) through (d) of this section, then all process streams using that individual resin or gel coat must be included in the averaging calculations.

(b) Demonstrate that, on average, you meet the individual organic HAP emissions limits for each combination of operation type and resin application method or gel coat type.

Demonstrate that on average you meet the individual organic HAP emissions limits for each unique combination of operation type and resin application method or gel coat type shown in Table 3 to this subpart that applies to you.

(1)(i) Group the process streams described in paragraph (a) to this section by operation type and resin application method or gel coat type listed in Table 3 to this subpart and then calculate a weighted average emission factor based on the amounts of each individual resin or gel coat used for the last 12 months. To do this, sum the product of each individual organic HAP emissions factor calculated in paragraph (a)(1) of this section and the amount of neat resin plus and neat gel coat plus usage that corresponds to the individual factors and divide the numerator by the total amount of neat resin plus and neat gel coat plus used in that operation type as shown in Equation 2 of this section.

$$\text{Actual Operation Organic HAP Emissions Factor} = \frac{\sum_{i=1}^n (\text{Actual Process Stream } EF_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 2})$$

Where:

Actual Process Stream EF_i =actual organic HAP emissions factor for process stream i , lbs/ton

Material_i =neat resin plus or neat gel coat plus used during the last 12 calendar months for process stream i , tons

n =number of process streams where you calculated an organic HAP emissions factor.

(ii) You may, but are not required to, include process streams where you have demonstrated compliance as described in paragraph (a) of this section, subject to the limitations described in paragraph (a)(2) of this

section, and you are not required to and should not include process streams for which you will demonstrate compliance using the procedures in paragraph (d) of this section.

(2) Compare each organic HAP emissions factor calculated in paragraph (b)(1) of this section with its corresponding organic HAP emissions limit in Table 3 or 5 to this subpart. If all emissions factors are equal to or less than their corresponding emission limits, then you are in compliance.

(d) Meet the organic HAP emissions limit for one application method and use the same resin(s) for all application methods of that resin type.

General Compliance Requirements

§ 63.5835 What are my general requirements for complying with this subpart?

(a) You must be in compliance at all times with the work practice standards in Table 4 to this subpart, as well as the organic HAP emissions limits in Tables 3, or 5, or the organic HAP content limits in Table 7 to this subpart, as applicable, that you are meeting without the use of add-on controls.

(c) You must always operate and maintain your affected source, including air pollution control and monitoring equipment, according to the provisions in §63.6(e)(1)(i).

Testing and Initial Compliance Requirements

§ 63.5840 By what date must I conduct a performance test or other initial compliance demonstration?

You must conduct performance tests, performance evaluations, design evaluations, capture efficiency testing, and other initial compliance demonstrations by the compliance date specified in Table 2 to this subpart, with three exceptions. Open molding and centrifugal casting operations that elect to meet a organic HAP emissions limit on a 12-month rolling average must initiate collection of the required data on the compliance date, and demonstrate compliance 1 year after the compliance date. New sources that use add-on controls to initially meet compliance must demonstrate compliance within 180 days after their compliance date.

§ 63.5860 How do I demonstrate initial compliance with the standards?

(a) You demonstrate initial compliance with each organic HAP emissions standard in paragraphs (a) through (h) of §63.5805 that applies to you by using the procedures shown in Tables 8 and 9 to this subpart.

Continuous Compliance Requirements

§ 63.5895 How do I monitor and collect data to demonstrate continuous compliance?

(b) You must monitor and collect data as specified in paragraphs (b)(1) through (4) of this section.

(1) Except for monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), you must conduct all monitoring in continuous operation (or collect data at all required intervals) at all times that the affected source is operating.

(2) You may not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities for purposes to this subpart, including data averages and calculations, or fulfilling a minimum data availability requirement, if applicable. You must use all the data collected during all other periods in assessing the operation of the control device and associated control system.

(3) At all times, you must maintain necessary parts for routine repairs of the monitoring equipment.

(4) A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring equipment to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions.

(c) You must collect and keep records of resin and gel coat use, organic HAP content, and operation where the resin is used if you are meeting any organic HAP emissions limits based on an organic HAP emissions limit in Tables 3 or 5 to this Subpart. You must collect and keep records of resin and gel coat use, organic HAP content, and operation where the resin is used if you are meeting any organic HAP content limits in Table 7 to this subpart if you are averaging organic HAP contents. Resin use records may be based on purchase records if you can reasonably estimate how the resin is applied. The organic HAP content records may be based on MSDS or on resin specifications supplied by the resin supplier.

- (d) Resin and gel coat use records are not required for the individual resins and gel coats that are demonstrated, as applied, to meet their applicable emission as defined in § 63.5810(a). However, you must retain the records of resin and gel coat organic HAP content, and you must include the list of these resins and gel coats and identify their application methods in your semiannual compliance reports. If after you have initially demonstrated that a specific combination of an individual resin or gel coat, application method, and controls meets its applicable emission limit, and the resin or gel coat changes or the organic HAP content increases, or you change the application method or controls, then you again must demonstrate that the individual resin or gel coat meets its emission limit as specified in paragraph (a) of § 63.5810. If any of the previously mentioned changes results in a situation where an individual resin or gel coat now exceeds its applicable emission limit in Table 3 or 5 of this subpart, you must begin collecting resin and gel coat use records and calculate compliance using one of the averaging options on a 12-month rolling average.

§ 63.5900 How do I demonstrate continuous compliance with the standards?

- (a) You must demonstrate continuous compliance with each standard in §63.5805 that applies to you according to the methods specified in paragraphs (a)(1) through (3) of this section.
- (2) Compliance with organic HAP emissions limits is demonstrated by maintaining an organic HAP emissions factor value less than or equal to the appropriate organic HAP emissions limit listed in Table 3 or 5 to this subpart, on a 12-month rolling average, and/or by including in each compliance report a statement that individual resins and gel coats, as applied, meet the appropriate organic HAP emissions limits, as discussed in § 63.5895(d).
- (3) Compliance with organic HAP content limits in Table 7 to this subpart is demonstrated by maintaining an average organic HAP content value less than or equal to the appropriate organic HAP contents listed in Table 7 to this subpart, on a 12-month rolling average, and/or by including in each compliance report a statement that resins and gel coats individually meet the appropriate organic HAP content limits in Table 7 to this subpart, as discussed in § 63.5895(d).
- (4) Compliance with the work practice standards in Table 4 to this subpart is demonstrated by performing the work practice required for your operation.
- (b) You must report each deviation from each standard in §63.5805 that applies to you. The deviations must be reported according to the requirements in §63.5910.
- (c) Except as provided in paragraph (d) of this section, during periods of startup, shutdown or malfunction, you must meet the organic HAP emissions limits and work practice standards that apply to you.
- (e) Consistent with §§63.6(e) and 63.7(e)(1), deviations that occur during a period of malfunction for those affected sources and standards specified in paragraph (d) of this section are not violations if you demonstrate to the Administrator's satisfaction that you were operating in accordance with the startup, shutdown, and malfunction plan. The Administrator will determine whether deviations that occur during a period of startup, shutdown, and malfunction are violations, according to the provisions in §63.6(e).

Notifications, Reports, and Records

§ 63.5905 What notifications must I submit and when?

- (a) You must submit all of the notifications in Table 13 to this subpart that apply to you by the dates specified in Table 13 to this subpart. The notifications are described more fully in 40 CFR 63, subpart A, referenced in Table 13 to this subpart.
- (b) If you change any information submitted in any notification, you must submit the changes in writing to the Administrator within 15 calendar days after the change.

§ 63.5910 What reports must I submit and when?

- (a) You must submit each report in Table 14 to this subpart that applies to you.
- (b) Unless the Administrator has approved a different schedule for submission of reports under §63.10(a), you must submit each report by the date specified in Table 14 to this subpart and according to paragraphs (b)(1) through (5) of this section.
- (1) The first compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.5800 and ending on June 30 or December 31, whichever date is the first date following the end of the first calendar half after the compliance date that is specified for your source in §63.5800.

- (2) The first compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date follows the end of the first calendar half after the compliance date that is specified for your affected source in §63.5800.
 - (3) Each subsequent compliance report must cover the semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.
 - (4) Each subsequent compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.
 - (5) For each affected source that is subject to permitting requirements pursuant to 40 CFR part 70 or 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to §70.6 (a)(3)(iii)(A) or §71.6(a)(3)(iii)(A), you may submit the first and subsequent compliance reports according to the dates the permitting authority has established instead of according to the dates in paragraphs (b)(1) through (4) of this section.
- (c) The compliance report must contain the information in paragraphs (c)(1) through (6) of this section:
- (1) Company name and address.
 - (2) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.
 - (3) Date of the report and beginning and ending dates of the reporting period.
 - (4) If you had a startup, shutdown, or malfunction during the reporting period and you took actions consistent with your startup, shutdown, and malfunction plan, the compliance report must include the information in §63.10(d)(5)(i).
 - (5) If there are no deviations from any organic HAP emissions limitations (emissions limit and operating limit) that apply to you, and there are no deviations from the requirements for work practice standards in Table 4 to this subpart, a statement that there were no deviations from the organic HAP emissions limitations or work practice standards during the reporting period.
 - (6) If there were no periods during which the continuous monitoring system (CMS), including a continuous emissions monitoring system (CEMS) and an operating parameter monitoring system were out of control, as specified in §63.8(c)(7), a statement that there were no periods during which the CMS was out of control during the reporting period.
- (d) For each deviation from a organic HAP emissions limitation (*i.e.*, emissions limit and operating limit) and for each deviation from the requirements for work practice standards that occurs at an affected source where you are not using a CMS to comply with the organic HAP emissions limitations or work practice standards in this subpart, the compliance report must contain the information in paragraphs (c)(1) through (4) of this section and in paragraphs (d)(1) and (2) of this section. This includes periods of startup, shutdown, and malfunction.
- (1) The total operating time of each affected source during the reporting period.
 - (2) Information on the number, duration, and cause of deviations (including unknown cause, if applicable), as applicable, and the corrective action taken.
- (e) For each deviation from a organic HAP emissions limitation (*i.e.*, emissions limit and operating limit) occurring at an affected source where you are using a CMS to comply with the organic HAP emissions limitation in this subpart, you must include the information in paragraphs (c)(1) through (4) of this section and in paragraphs (e)(1) through (12) of this section. This includes periods of startup, shutdown, and malfunction.
- (1) The date and time that each malfunction started and stopped.
 - (2) The date and time that each CMS was inoperative, except for zero (low-level) and high-level checks.
 - (3) The date, time, and duration that each CMS was out of control, including the information in § 63.8(c)(8).
 - (4) The date and time that each deviation started and stopped, and whether each deviation occurred during a period of startup, shutdown, or malfunction, or during another period.
 - (5) A summary of the total duration of the deviation during the reporting period and the total duration as a percent of the total source operating time during that reporting period.
 - (6) A breakdown of the total duration of the deviations during the reporting period into those that are due to startup, shutdown, control equipment problems, process problems, other known causes, and other unknown causes.
 - (7) A summary of the total duration of CMS downtime during the reporting period and the total duration of CMS downtime as a percent of the total source operating time during that reporting period.
 - (8) An identification of each organic HAP that was monitored at the affected source.
 - (9) A brief description of the process units.

- (10) A brief description of the CMS.
 - (11) The date of the latest CMS certification or audit.
 - (12) A description of any changes in CMS, processes, or controls since the last reporting period.
- (g) Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by §70.6(a)(3)(iii)(A) or §71.6(a)(3)(iii)(A). If an affected source submits a compliance report pursuant to Table 14 to this subpart along with, or as part of, the semiannual monitoring report required by §70.6(a)(3)(iii)(A) or §71.6(a)(3)(iii)(A), and the compliance report includes all required information concerning deviations from any organic HAP emissions limitation (including any operating limit) or work practice requirement in this subpart, submission of the compliance report shall be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permitting authority.
- (h) Submit compliance reports and startup, shutdown, and malfunction reports based on the requirements in Table 14 to this subpart, and not based on the requirements in §63.999.

§ 63.5915 What records must I keep?

- (a) You must keep the records listed in paragraphs (a)(1) through (3) of this section.
- (1) A copy of each notification and report that you submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status that you submitted, according to the requirements in §63.10(b)(2)(xiv).
 - (2) The records in §63.6(e)(3)(iii) through (v) related to startup, shutdown, and malfunction.
 - (3) Records of performance tests, design, and performance evaluations as required in §63.10(b)(2).
- (c) You must keep all data, assumptions, and calculations used to determine organic HAP emissions factors or average organic HAP contents for operations listed in Tables 3, 5, and 7 to this subpart.
- (d) You must keep a certified statement that you are in compliance with the work practice requirements in Table 4 to this subpart, as applicable.

§ 63.5920 In what form and how long must I keep my records?

- (a) You must maintain all applicable records in such a manner that they can be readily accessed and are suitable for inspection according to §63.10(b)(1).
- (b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.
- (c) You must keep each record onsite for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1). You can keep the records offsite for the remaining 3 years.
- (d) You may keep records in hard copy or computer readable form including, but not limited to, paper, microfilm, computer floppy disk, magnetic tape, or microfiche.

Other Requirements and Information

§ 63.5925 What parts of the General Provisions apply to me?

Table 15 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you.

§ 63.5930 Who implements and enforces this subpart?

- (a) This subpart can be administered by us, the EPA, or a delegated authority such as your State, local, or tribal agency. If the EPA Administrator has delegated authority to your State, local, or tribal agency, then that agency has the authority to administer and enforce this subpart. You should contact your EPA Regional Office to find out if this subpart is delegated to your State, local, or tribal agency.
- (b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under 40 CFR part 63, subpart E, the authorities contained in paragraph (c) of this section are not delegated.
- (c) The authorities that will not be delegated to State, local, or tribal agencies are listed in paragraphs (c)(1) through (4) of this section:
- (1) Approval of alternatives to the organic HAP emissions standards in §63.5805 under §63.6(g).
 - (2) Approval of major changes to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.
 - (3) Approval of major changes to monitoring under §63.8(f) and as defined in §63.90.
 - (4) Approval of major changes to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

§ 63.5935 What definitions apply to this subpart?

Terms used in this subpart are defined in the CAA, in 40 CFR 63.2, and in this section as follows:

Atomized mechanical application means application of resin or gel coat with spray equipment that separates the liquid into a fine mist. This fine mist may be created by forcing the liquid under high pressure through an elliptical orifice, bombarding a liquid stream with directed air jets, or a combination of these techniques.

Bulk molding compound (BMC) means a putty-like molding compound containing resin(s) in a form that is ready to mold. In addition to resins, BMC may contain catalysts, fillers, and reinforcements. Bulk molding compound can be used in compression molding and injection molding operations to manufacture reinforced plastic composites products.

BMC manufacturing means a process that involves the preparation of BMC.

Centrifugal casting means a process for fabricating cylindrical composites, such as pipes, in which composite materials are positioned inside a rotating hollow mandrel and held in place by centrifugal forces until the part is sufficiently cured to maintain its physical shape.

Charge means the amount of SMC or BMC that is placed into a compression or injection mold necessary to complete one mold cycle.

Cleaning means removal of composite materials, such as cured and uncured resin from equipment, finished surfaces, floors, hands of employees, or any other surfaces.

Clear production gel coat means an unpigmented, quick-setting resin used to improve the surface appearance and/or performance of composites. It can be used to form the surface layer of any composites other than those used for molds in tooling operations.

Closed molding means a grouping of processes for fabricating composites in a way that HAP-containing materials are not exposed to the atmosphere except during the material loading stage (*e.g.*, compression molding, injection molding, and resin transfer molding). Processes where the mold is covered with plastic (or equivalent material) prior to resin application, and the resin is injected into the covered mold are also considered closed molding.

Composite means a shaped and cured part produced by using composite materials.

Composite materials means the raw materials used to make composites. The raw materials include styrene containing resins. They may also include gel coat, monomer, catalyst, pigment, filler, and reinforcement.

Compression molding means a closed molding process for fabricating composites in which composite materials are placed inside matched dies that are used to cure the materials under heat and pressure without exposure to the atmosphere. The addition of mold paste or in-mold coating is considered part of the closed molding process. The composite materials used in this process are generally SMC or BMC.

Compression/injection molding means a grouping of processes that involves the use of compression molding and/or injection molding.

Continuous casting means a continuous process for fabricating composites in which composite materials are placed on an in-line conveyor belt to produce cast sheets that are cured in an oven.

Continuous lamination means a continuous process for fabricating composites in which composite materials are typically sandwiched between plastic films, pulled through compaction rollers, and cured in an oven. This process is generally used to produce flat or corrugated products on an in-line conveyor.

Continuous lamination/casting means a grouping of processes that involves the use of continuous lamination and/or continuous casting.

Controlled emissions means those organic HAP emissions that are vented from a control device to the atmosphere.

Corrosion-resistant gel coat means a gel coat used on a product made with a corrosion-resistant resin that has a corrosion-resistant end-use application.

Corrosion-resistant end-use applications means applications where the product is manufactured specifically for an application that requires a level of chemical inertness or resistance to chemical attack above that required for typical reinforced plastic composites products. These applications include, but are not limited to, chemical processing and storage; pulp and paper production; sewer and wastewater treatment; power generation; potable water transfer and storage; food and drug processing; pollution or odor control; metals production and plating; semiconductor manufacturing; petroleum production, refining, and storage; mining; textile production; nuclear materials storage; swimming pools; and cosmetic production, as well as end-use applications that require high strength resins.

Corrosion-resistant industry standard includes the following standards: ASME RTP-1 or Sect. X; ASTM D5364, D3299, D4097, D2996, D2997, D3262, D3517, D3754, D3840, D4024, D4160, D4161, D4162, D4184, D3982, or D3839; ANSI/AWWA C950; UL 215, 1316 or 1746, IAPMO PS-199, or written customer requirements for resistance to specified chemical environments.

Corrosion-resistant product means a product made with a corrosion-resistant resin and is manufactured to a corrosion-resistant industry standard, or a food contact industry standard, or is manufactured for corrosion-resistant end-use applications involving continuous or temporary chemical exposures.

Corrosion-resistant resin means a resin that either:

- (1) Displays substantial retention of mechanical properties when undergoing ASTM C-581 coupon testing, where the resin is exposed for 6 months or more to one of the following materials: Material with a pH \geq 12.0 or \leq 3.0, oxidizing or reducing agents, organic solvents, or fuels or additives as defined in 40 CFR 79.2. In the coupon testing, the exposed resin needs to demonstrate a minimum of 50 percent retention of the relevant mechanical property compared to the same resin in unexposed condition. In addition, the exposed resin needs to demonstrate an increased retention of the relevant mechanical property of at least 20 percentage points when compared to a similarly exposed general-purpose resin. For example, if the general-purpose resin retains 45 percent of the relevant property when tested as specified above, then a corrosion-resistant resin needs to retain at least 65 percent (45 percent plus 20 percent) of its property. The general-purpose resin used in the test needs to have an average molecular weight of greater than 1,000, be formulated with a 1:2 ratio of maleic anhydride to phthalic anhydride and 100 percent diethylene glycol, and a styrene content between 43 to 48 percent; or
- (2) Complies with industry standards that require specific exposure testing to corrosive media, such as UL 1316, UL 1746, or ASTM F-1216.

Doctor box means the box or trough on an SMC machine into which the liquid resin paste is delivered before it is metered onto the carrier film.

Filament application means an open molding process for fabricating composites in which reinforcements are fed through a resin bath and wound onto a rotating mandrel. The materials on the mandrel may be rolled out or worked by using nonmechanical tools prior to curing. Resin application to the reinforcement on the mandrel by means other than the resin bath, such as spray guns, pressure-fed rollers, flow coaters, or brushes is not considered filament application.

Filled Resin means that fillers have been added to a resin such that the amount of inert substances is at least 10 percent by weight of the total resin plus filler mixture. Filler putty made from a resin is considered a filled resin.

Fillers means inert substances dispersed throughout a resin, such as calcium carbonate, alumina trihydrate, hydrous aluminum silicate, mica, feldspar, wollastonite, silica, and talc. Materials that are not considered to be fillers are glass fibers or any type of reinforcement and microspheres.

Fire retardant gel coat means a gel coat used for products for which low-flame spread/low-smoke resin is used.

Fluid impingement technology means a spray gun that produces an expanding non-misting curtain of liquid by the impingement of low-pressure uninterrupted liquid streams.

Food contact industry standard means a standard related to food contact application contained in Food and Drug Administration's regulations at 21 CFR 177.2420.

Gel Coat means a quick-setting resin used to improve surface appearance and/or performance of composites. It can be used to form the surface layer of any composites other than those used for molds in tooling operations.

Gel coat application means a process where either clear production, pigmented production, white/off-white or tooling gel coat is applied.

HAP-containing materials storage means an ancillary process which involves keeping HAP-containing materials, such as resins, gel coats, catalysts, monomers, and cleaners, in containers or bulk storage tanks for any length of time. Containers may include small tanks, totes, vessels, and buckets.

High Performance gel coat means a gel coat used on products for which National Sanitation Foundation, United States Department of Agriculture, ASTM, durability, or other property testing is required.

High strength gel coat means a gel coat applied to a product that requires high strength resin.

High strength resins means polyester resins which have a casting tensile strength of 10,000 pounds per square inch or more and which are used for manufacturing products that have high strength requirements such as structural members and utility poles.

Injection molding means a closed molding process for fabricating composites in which composite materials are injected under pressure into a heated mold cavity that represents the exact shape of the product. The composite materials are cured in the heated mold cavity.

Low Flame Spread/Low Smoke Products means products that meet the following requirements. The products must meet both the applicable flame spread requirements and the applicable smoke requirements. Interior or exterior building application products must meet an ASTM E-84 Flame Spread Index of less than or equal to 25, and Smoke Developed Index of less than or equal to 450, or pass National Fire Protection Association 286 Room Corner Burn Test with no flash over and total smoke released not exceeding 1000 meters square. Mass transit application products must meet an ASTM E-162 Flame Spread Index of less than or equal to 35 and ASTM E662 Smoke Density Ds @ 1.5 minutes less than or equal to 100 and Ds @ 4 minutes less than or equal to 200. Duct application products must meet ASTM E084 Flame Spread Index less than or equal to 25 and Smoke Developed Index less than or equal to 50 on the interior and/or exterior of the duct.

Manual resin application means an open molding process for fabricating composites in which composite materials are applied to the mold by pouring or by using hands and nonmechanical tools, such as brushes and rollers. Materials are rolled out or worked by using nonmechanical tools prior to curing. The use of pressure-fed rollers and flow coaters to apply resin is not considered manual resin application.

Mechanical resin application means an open molding process for fabricating composites in which composite materials (except gel coat) are applied to the mold by using mechanical tools such as spray guns, pressure-fed rollers, and flow coaters. Materials are rolled out or worked by using nonmechanical tools prior to curing.

Mixing means the blending or agitation of any HAP-containing materials in vessels that are 5.00 gallons (18.9 liters) or larger, and includes the mixing of putties or polyputties. Mixing may involve the blending of resin, gel coat, filler, reinforcement, pigments, catalysts, monomers, and any other additives.

Mold means a cavity or matrix into or onto which the composite materials are placed and from which the product takes its form.

Neat gel coat means the resin as purchased for the supplier, but not including any inert fillers.

Neat gel coat plus means neat gel coat plus any organic HAP-containing materials that are added to the gel coat by the supplier or the facility, excluding catalysts and promoters. Neat gel coat plus does include any additions of styrene or methyl methacrylate monomer in any form, including in catalysts and promoters.

Neat resin means the resin as purchased from the supplier, but not including any inert fillers.

Neat resin plus means neat resin plus any organic HAP-containing materials that are added to the resin by the supplier or the facility. Neat resin plus does not include any added filler, reinforcements, catalysts, or promoters. Neat resin plus does include any additions of styrene or methyl methacrylate monomer in any form,

including in catalysts and promoters.

Nonatomized mechanical application means the use of application tools other than brushes to apply resin and gel coat where the application tool has documentation provided by its manufacturer or user that this design of the application tool has been organic HAP emissions tested, and the test results showed that use of this application tool results in organic HAP emissions that are no greater than the organic HAP emissions predicted by the applicable nonatomized application equation(s) in Table 1 to this subpart. In addition, the device must be operated according to the manufacturer's directions, including instructions to prevent the operation of the device at excessive spray pressures. Examples of nonatomized application include flow coaters, pressure fed rollers, and fluid impingement spray guns.

Noncorrosion-resistant resin means any resin other than a corrosion-resistant resin or a tooling resin.

Noncorrosion-resistant product means any product other than a corrosion-resistant product or a mold.

Non-routine manufacture means that you manufacture parts to replace worn or damaged parts of a reinforced plastic composites product, or a product containing reinforced plastic composite parts, that was originally manufactured in another facility. For a part to qualify as non-routine manufacture, it must be used for repair or replacement, and the manufacturing schedule must be based on the current or anticipated repair needs of the reinforced plastic composites product, or a product containing reinforced plastic composite parts.

Operation means a specific process typically found at a reinforced plastic composites facility. Examples of operations are noncorrosion-resistant manual resin application, corrosion-resistant mechanical resin application, pigmented gel coat application, mixing and HAP-containing materials storage.

Operation group means a grouping of individual operations based primarily on mold type. Examples are open molding, closed molding, and centrifugal casting.

Open molding means a process for fabricating composites in a way that HAP-containing materials are exposed to the atmosphere. Open molding includes processes such as manual resin application, mechanical resin application, filament application, and gel coat application. Open molding also includes application of resins and gel coats to parts that have been removed from the open mold.

Pigmented gel coat means a gel coat that has a color, but does not contain 10 percent or more titanium dioxide by weight. It can be used to form the surface layer of any composites other than those used for molds in tooling operations.

Polymer casting means a process for fabricating composites in which composite materials are ejected from a casting machine or poured into an open, partially open, or closed mold and cured. After the composite materials are poured into the mold, they are not rolled out or worked while the mold is open, except for smoothing the material and/or vibrating the mold to remove bubbles. The composite materials may or may not include reinforcements. Products produced by the polymer casting process include cultured marble products and polymer concrete.

Preform Injection means a form of pultrusion where liquid resin is injected to saturate reinforcements in an enclosed system containing one or more chambers with openings only large enough to admit reinforcements. Resin, which drips out of the chamber(s) during the process, is collected in closed piping or covered troughs and then into a covered reservoir for recycle. Resin storage vessels, reservoirs, transfer systems, and collection systems are covered or shielded from the ambient air. Preform injection differs from direct die injection in that the injection chambers are not directly attached to the die.

Prepreg materials means reinforcing fabric received precoated with resin which is usually cured through the addition of heat.

Pultrusion means a continuous process for manufacturing composites that have a uniform cross-sectional shape. The process consists of pulling a fiber-reinforcing material through a resin impregnation chamber or bath and through a shaping die, where the resin is subsequently cured. There are several types of pultrusion equipment, such as open bath, resin injection, and direct die injection equipment.

Repair means application of resin or gel coat to a part to correct a defect, where the resin or gel coat application occurs after the part has gone through all the steps of its typical production process, or the application occurs outside the normal production area. For purposes of this subpart, rerouting a part back through the normal production line, or part of the normal production line, is not considered repair.

Resin transfer molding means a process for manufacturing composites whereby catalyzed resin is transferred or injected into a closed mold in which fiberglass reinforcement has been placed.

Sheet molding compound (SMC) means a ready-to-mold putty-like molding compound that contains resin(s) processed into sheet form. The molding compound is sandwiched between a top and a bottom film. In addition to resin(s), it may also contain catalysts, fillers, chemical thickeners, mold release agents, reinforcements, and other ingredients. Sheet molding compound can be used in compression molding to manufacture reinforced plastic composites products.

Shrinkage controlled resin means a resin that when promoted, catalyzed, and filled according to the resin manufacturer's recommendations demonstrates less than 0.3 percent linear shrinkage when tested according to ASTM D2566.

SMC manufacturing means a process which involves the preparation of SMC.

Tooling gel coat means a gel coat that is used to form the surface layer of molds. Tooling gel coats generally have high heat distortion temperatures, low shrinkage, high barcol hardness, and high dimensional stability.

Tooling resin means a resin that is used to produce molds. Tooling resins generally have high heat distortion temperatures, low shrinkage, high barcol hardness, and high dimensional stability.

Uncontrolled oven organic HAP emissions means those organic HAP emissions emitted from the oven through closed vent systems to the atmosphere and not to a control device. These organic HAP emissions do not include organic HAP emissions that may escape into the workplace through the opening of panels or doors on the ovens or other similar fugitive organic HAP emissions in the workplace.

Uncontrolled wet-out area organic HAP emissions means any or all of the following: Organic HAP emissions from wet-out areas that do not have any capture and control, organic HAP emissions that escape from wet-out area enclosures, and organic HAP emissions from wet-out areas that are captured by an enclosure but are vented to the atmosphere and not to an add-on control device.

Unfilled means that there has been no addition of fillers to a resin or that less than 10 percent of fillers by weight of the total resin plus filler mixture has been added.

Vapor suppressant means an additive, typically a wax, that migrates to the surface of the resin during curing and forms a barrier to seal in the styrene and reduce styrene emissions.

Vapor-suppressed resin means a resin containing a vapor suppressant added for the purpose of reducing styrene emissions during curing.

White and off-white gel coat means a gel coat that contains 10 percent of more titanium dioxide by weight.

Table 1 to Subpart WWWW of Part 63—Equations to Calculate Organic HAP Emissions Factors for Specific Open Molding and Centrifugal Casting Process Streams¹

As specified in §63.5810, use the equations in the following table to calculate organic HAP emissions factors for specific open molding and centrifugal casting process streams:

If your operation type is a new or existing. . .	And you use. . .	With. . .	Use this organic HAP Emissions Factor (EF) Equation for materials with less than 33 percent organic HAP (19 percent organic HAP for nonatomized gel coat) ^{2 3 4}	Use this organic HAP emissions Factor (EF) Equation for materials with 33 percent or more organic HAP (19 percent for nonatomized gel coat) ^{2 3 4}
1. open molding operation	a. manual resin application	i. nonvapor-suppressed resin	EF = 0.126 x %HAP x 2000	EF = ((0.286 x %HAP) – 0.0529) x 2000
		ii. vapor-suppressed resin	EF = 0.126 x %HAP x 2000 x (1-(0.5 x VSE Factor))	EF = ((0.286 x %HAP)-0.0529) x 2000 x (1-(0.5 x VSE Factor))
		iii. vacuum bagging/closed-mold curing with roll out	EF = 0.126 x %HAP x 2000 x 0.5	EF = ((0.286 x %HAP)-0.0529) x 2000 x 0.8
		iv. vacuum bagging/closed-mold curing without roll out	EF = (0.126 x %HAP x 2000 x 0.5	EF = ((0.286 x %HAP) – 0.0529) x 2000 x 0.5
	c. nonatomized mechanical resin application	i. nonvapor-suppressed resin	EF = 0.107 x %HAP x 2000	EF = ((0.157 x %HAP) – 0.0165) x 2000
		ii. vapor-suppressed resin	EF = 0.107 x %HAP x 2000 x (1-(0.45 x VSE Factor))	EF = ((0.157 x %HAP) – 0.0165) x 2000 x (1-(0.45 x VSE Factor))
		iii. closed-mold curing with roll out	EF = 0.107 x %HAP x 2000 x 0.85	EF = ((0.157 x %HAP) - 0.0165) x 2000 x 0.85
		iv. vacuum bagging/closed-mold curing without roll out	EF = (0.107 x %HAP x 2000 x 0.55	EF = ((0.157 x %HAP) – 0.0165) x 2000 x 0.55
	e. filament application ⁶	i. nonvapor-suppressed resin	EF = 0.184 x %HAP x 2000	EF = ((0.2746 x %HAP) – 0.0298) x 2000
		ii. vapor-suppressed resin	EF = 0.12 x %HAP x 2000	EF = ((0.2746 x %HAP) – 0.0298) x 2000 x 0.65
	g. nonatomized spray gel coat application	nonvapor-suppressed gel coat	EF = 0.185 x %HAP x 2000	EF = ((0.4506 x %HAP) – 0.0505) x 2000

Footnotes to Table 1

¹ The equations in this table are intended for use in calculating emission factors to demonstrate compliance with the emission limits in subpart WWWW. These equations may not be the most appropriate method to calculate emission estimates for other purposes. However, this does not preclude a facility from using the equations in this table to calculate emission factors for purposes other than rule compliance if these equations are the most accurate available.

² To obtain the organic HAP emissions factor value for an operation with an add-on control device multiply the EF above by the add-on control factor calculated using Equation 1 of §63.5810. The organic HAP emissions factors have units of lbs of organic HAP per ton of resin or gel coat applied.

³ Percent HAP means total weight percent of organic HAP (styrene, methyl methacrylate, and any other organic HAP) in the resin or gel coat prior to the addition of fillers, catalyst, and promoters. Input the percent HAP as a decimal, i.e., 33 percent HAP should be input as 0.33, not 33.

⁴ The VSE factor means the percent reduction in organic HAP emissions expressed as a decimal measured by the VSE test method of appendix A to this subpart.

⁵ This equation is based on a organic HAP emissions factor equation developed for mechanical atomized controlled spray. It may only be used for automated or robotic spray systems with automated spray. All spray operations using hand held spray guns must use the appropriate mechanical atomized or mechanical nonatomized organic HAP emissions factor equations. Automated or robotic spray systems using nonatomized spray should use the appropriate nonatomized mechanical resin application equation.

⁶ Applies only to filament application using an open resin bath. If resin is applied manually or with a spray gun, use the appropriate manual or mechanical application organic HAP emissions factor equation.

Table 2 to Subpart WWWW of Part 63—Compliance Dates for New and Existing Reinforced Plastic Composites Facilities

As required in §§63.5800 and 63.5840 you must demonstrate compliance with the standards by the dates in the following table:

If your facility is. . .	And. . .	Then you must comply by this date. . .
1. An existing source. . .	a. Is a major source on or before the publication date of this subpart.	i. April 21, 2006, or ii. You must accept and meet an enforceable HAP emissions limit below the major source threshold prior to April 21, 2006.

Table 3 to Subpart WWWW of Part 63—Organic HAP Emissions Limits for Existing Open Molding Sources, New Open Molding Sources Emitting Less Than 100 TPY of HAP, and New and Existing Centrifugal Casting and Continuous Lamination/Casting Sources that Emit Less Than 100 TPY of HAP

As required in §§63.5796, 63.5805 (a) through (c) and (g), 63.5810(a), (b), and (d), 63.5820(c), 63.5830, 63.5835(a), 63.5895(c) and (d), 63.5900(a)(2), and 63.5915(c), you must meet the appropriate organic HAP emissions limits in the following table:

If your operation type is. . .	And you use. . .	¹Your organic HAP emissions limit is. . .
1. open molding – corrosion-resistant and/or high strength (CR/HS).	a. mechanical resin application	113 lb/ton
	b. filament application	171 lb/ton
	c. manual resin application	123 lb/ton
2. open molding – non-CR/HS	a. mechanical resin application	88 lb/ton
	b. filament application	188 lb/ton
	c. manual resin application	87 lb/ton
3. open molding – tooling	a. mechanical resin application	254 lb/ton
	b. manual resin application	157 lb/ton
4. open molding – low-flame spread/low-smoke products	a. mechanical resin application	497 lb/ton
	b. filament application	270 lb/ton
	c. manual resin application	238 lb/ton
5. open molding – shrinkage controlled resins ²	a. mechanical resin application	354 lb/ton
	b. filament application	215 lb/ton
	c. manual resin application	180 lb/ton
6. open molding – gel coat ³	a. tooling gel coating	440 lb/ton
	b. white/off white pigmented gel coating	267 lb/ton
	c. all other pigmented gel coating	377 lb/ton
	d. CR/HS or high performance gel coat	605 lb/ton
	e. fire retardant gel coat	854 lb/ton
	f. clear production gel coat	522 lb/ton

¹ Organic HAP emissions limits for open molding and centrifugal casting are expressed as lb/ton. You must be at or below these values based on a 12-month rolling average.

² This emission limit applies regardless of whether the shrinkage controlled resin is used as a production resin or a tooling resin.

³ If you only apply gel coat with manual application, for compliance purposes treat the gel coat as if it were applied using atomized spray guns to determine both emission limits and emission factors. If you use multiple application methods and any portion of a specific gel coat is applied using nonatomized spray, you may use the nonatomized spray gel coat equation to calculate any emission factor for the manually applied portion of that gel coat. Otherwise, use the atomized spray gel coat equation to calculate emission factors.

Table 4 to Subpart WWWW of Part 63—Work Practice Standards

[As required in §§63.5805 (a) through (d) and (g), 63.5835(a), 63.5900(a)(3), 63.5910(c)(5), and 63.5915(d), you must meet the appropriate work practice standards in the following table:]

For . . .	You must . . .
1. a new or existing closed molding operation using compression/injection molding.	Uncover, unwrap or expose only one charge per mold cycle per compression/injection molding machine. For machines with multiple molds, one charge means sufficient material to fill all molds for one cycle. For machines with robotic loaders, no more than one charge may be exposed prior to the loader. For machines fed by hoppers, sufficient material may be uncovered to fill the hopper. Hoppers must be closed when not adding materials. Materials may be uncovered to feed to slitting machines. Materials must be recovered after slitting.
2. a new or existing cleaning operation	Not use cleaning solvents that contain HAP, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.
3. a new or existing materials HAP-containing materials storage operation	Keep containers that store HAP-containing materials closed or covered except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

¹ containers of 5 gallons or less may be open when active mixing is taking place, or during periods when they are in process (i.e., they are actively being used to apply resin). For polymer casting mixing operations, containers with a surface area of 500 square inches or less may be open while active mixing is taking place.

Table 5 to Subpart WWWW of Part 63 – Alternative Organic HAP Emissions limits for Open Molding, Centrifugal Casting, and SMC Manufacturing Operations where the standard is based on a 95 percent reduction requirement

[As specified in §§63.5796, 63.5805(b) and (d), 6.5810(a) and (b), 63.5895(c), 63.5900(a)(2), and 63.5915(c), as an alternative to the 95 percent organic HAP emissions reductions requirement, you may meet the appropriate organic HAP emissions limits in the following table:]

If your operation type is . . .	And you use . . .	Your organic HAP emissions limit is ¹
1. Open molding – corrosion-resistant and/or high strength (CR/HS).	a. Mechanical resin application b. Filament application c. Manual resin application	6 lb/ton 9 lb/ton 7 lb/ton
2. Open molding – non-CR/HS	a. Mechanical resin application b. Filament application c. Manual resin application	13 lb/ton 10 lb/ton 5 lb/ton
3. Open molding - tooling	a. Mechanical resin application b. Filament application	13 lb/ton 8 lb/ton
4. Open molding – low flame spread/low smoke products	a. Mechanical resin application b. Filament application c. Manual resin application	25 lb/ton 14 lb/ton 12 lb/ton
5. Open molding – shrinkage controlled resins	a. Mechanical resin application b. Filament application c. Manual resin application	18 lb/ton 11 lb/ton 9 lb/ton
6. Open molding – gel coat ²	a. Tooling gel coating b. White/off white pigmented gel coating c. All other pigmented gel coating d. CR/HS or high performance gel coat e. Fire retardant gel coat	22 lb/ton 22 lb/ton 19 lb/ton 31 lb/ton 43 lb/ton

	f. Clear production gel coat	27 lb/ton
--	------------------------------	-----------

¹ Organic HAP emissions limits for open molding and centrifugal casting expressed as lb/ton are calculated using the equations shown in Table 1 to this subpart. You must be at or below these values based on a 12-month rolling average.

² These limits are for spray application of gel coat. Manual gel coat application must be included as part of spray gel coat application for compliance purposes using the same organic HAP emissions factor equation and organic HAP emissions limit. If you only apply gel coat with manual application, treat the manually applied gel coat as if it were applied with atomized spray for compliance determinations.

Table 7 to Subpart WWWW of Part 63—Options Allowing Use of the Same Resin Across Different Operations That Use the Same Resin Type

As specified in § 63.5810(d), when electing to use the same resin(s) for multiple resin application methods, you may use any resin(s) with an organic HAP content less than or equal to the values shown in the following table, or any combination of resins whose weighted average organic HAP content based on a 12-month rolling average is less than or equal to the values shown the following table:

If your facility has the following resin type and application method . . .	The highest resin weight is* * * percent organic HAP content, or weighted average weight percent organic HAP content, you can use for . .	Is . . .
2. CR/HS resins, nonatomized mechanical	b. CR/HS filament application	46.4
	c. CR/HS manual	46.4
5. Non-CR/HS resins, nonatomized mechanical	a. Non-CR/HS manual	38.5
	b. non-CR/HS centrifugal casting ^{1 2}	38.5
7. Tooling resins, nonatomized mechanical	Tooling manual	91.4
8. Tooling resins, manual	Tooling atomized mechanical	45.9

Table 8 to Subpart WWWW of Part 63—Initial Compliance with Organic HAP Emissions Limits

As required in §63.5860(a), you must demonstrate initial compliance with organic HAP emissions limits as specified in the following table:

For . . .	That must meet the following organic HAP emissions limit. . .	You have demonstrated initial compliance if. . .
1. open molding and centrifugal casting operations.	a. an organic HAP emissions limit shown in Tables 3 and 5 to this subpart, or an organic HAP content limit shown in Table 7 to this subpart.	i. you have met the appropriate organic HAP emissions limits for these operations as calculated using the procedures in § 63.5810 on a 12-month rolling average 1 year after the appropriate compliance date, and/or ii. you demonstrate that any individual resins or get coats not included in (i) above, as applied, meet their applicable emission limits, or iii. you demonstrate using the appropriate values in Table 7 to this subpart that the weighted average of all resins and gel coats for each resin type and application method meet the appropriate organic HAP contents.
2. open molding centrifugal casting, continuous lamination/casting, SMC and BMC manufacturing, and mixing operations.	a. reduce total organic HAP emissions by at least 95 percent by weight.	Total organic HAP emissions, based on the results of the capture efficiency and destruction efficiency testing specified in Table 6 to this Subpart, are reduced by at least 95 percent by weight.

Table 9 to Subpart WWWW of Part 63—Initial Compliance with Work Practice Standards

As required in §63.5860(a), you must demonstrate initial compliance with work practice standards as specified in the following table:

For . . .	That must meet the following standards. . .	You have demonstrated initial compliance if. . .
1. a new or existing closed molding operation using compression/injection molding.	Uncover, unwrap or expose only one charge per mold cycle per compression/injection molding machine. For machines with multiple molds, one charge means sufficient material to fill all molds for one cycle. For machines with robotic loaders, no more than one charge may be exposed prior to the loader. For machines fed by hoppers, sufficient material may be uncovered to fill the hopper. Hoppers must be closed when not adding materials. Materials may be uncovered to feed to slitting machines. Materials must be recovered after slitting.	The owner or operator submits a certified statement in the notice of compliance status that only one charge is uncovered, unwrapped, or exposed per mold cycle per compression/injection molding machine, or prior to the loader, hoppers are closed except when adding materials, and materials are recovered after slitting.
2. a new or existing cleaning operation	Not use cleaning solvents that contain HAP, except that styrene may be used in closed systems, and organic HAP containing materials may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin between storage and applying resin to the mold or reinforcement.	The owner or operator submits a certified statement in the notice of compliance status that all cleaning materials, except styrene contained in closed systems, or materials used to clean cured resin from application equipment, contain no HAP.
3. a new or existing materials HAP-containing materials storage operation.	Keep containers that store HAP-containing materials closed or covered except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.	The owner or operator submits a certified statement in the notice of compliance status that all HAP-containing storage containers are kept closed or covered except when adding or removing material, and that any bulk storage tanks are vented only as necessary for safety.

Table 13 to Subpart WWWW of Part 63—Applicability and Timing of Notifications

As required in §63.5905(a), you must determine the applicable notifications and submit them by the dates shown in the following table:

If your facility . . .	You must submit . . .	By this date . . .
1. Is an existing source subject to this subpart	An Initial Notification containing the information specified in § 63.9(b)(2).	No later than the dates specified in § 63.9(b)(2).
2. Qualifies for a compliance extension as specified in § 63.9(c).	A request for a compliance extension as specified in § 63.9(c).	No later than the dates specified in § 63.6(i).
3. Is complying with organic HAP emissions limit averaging provisions.	A Notification of Compliance Status as specified in § 63.9(h).	No later than 1 year plus 30 days after your facility's compliance date.

4. Is complying with organic HAP content limits, application equipment requirements, or organic HAP emissions limit other than organic HAP emissions limit averaging.	A Notification of Compliance Status as specified in § 63.9(h).	No later than 30 calendar days after your facility's compliance date.
---	--	---

Table 14 to Subpart WWWW of Part 63—Requirements for Reports

As required in §63.5910(a), (b), (g), and (h), you must submit reports on the schedule shown in the following table:

You must submit a(n)	The report must contain . . .	You must submit the report . . .
1. Compliance report	a. A statement that there were no deviations during that reporting period if there were no deviations from any emission limitations (emission limit, operating limit, opacity limit, and visible emission limit) that apply to you and there were no deviations from the requirements for work practice standards in Table 4 to this subpart that apply to you. If there were no periods during which the CMS, including CEMS, and operating parameter monitoring systems, was out of control as specified in § 63.8(c)(7), the report must also contain a statement that there were no periods during which the CMS was out of control during the reporting period.	Semiannually according to the requirements in § 63.5910(b).
	b. The information in § 63.5910(d) if you have a deviation from any emission limitation (emission limit, operating limit, or work practice standard) during the reporting period. If there were periods during which the CMS, including CEMS, and operating parameter monitoring systems, was out of control, as specified in § 63.8(c)(7), the report must contain the information in § 63.5910(e).	Semiannually according to the requirements in § 63.5910(b).
	c. The information in §63.10(d)(5)(i) if you had a startup, shutdown or malfunction during the reporting period, and you took actions consistent with your startup, shutdown, and malfunction plan.	Semiannually according to the requirements in § 63.5910(b).
2. An immediate startup, shutdown, and malfunction report if you had a startup, shutdown, or malfunction during the reporting period that is not consistent with your startup, shutdown, and malfunction plan.	a. Actions taken for the event	By fax or telephone within 2 working days after starting actions inconsistent with the plan.
	b. The information in § 63.10(d)(5)(ii)	By letter within 7 working days after the end of the event unless you have made alternative arrangements with the permitting authority. (§ 63.10(d)(5)(ii)).

Table 15 to Subpart WWWW of Part 63—Applicability of General Provisions to Subpart WWWW of Part 63

As specified in Sec.63.5925, the parts of the General Provisions which apply to you are shown in the following table:]

The general provisions reference. . .	That addresses . . .	And applies to subpart WWWW of part 63 . . .	Subject to the following additional information . . .
Sec. 63.1(a)(1).....	General applicability of the general provisions.	Yes.....	Additional terms defined in subpart WWWW of Part 63, when overlap between subparts A and WWWW of Part 63 of this part, subpart WWWW of Part 63 takes precedence.
Sec. 63.1(a)(2) through (4).....	General applicability of the general provisions.	Yes.....	
Sec. 63.1(a)(5).....	Reserved.....	No.....	
Sec. 63.1(a)(6).....	General applicability of the general provisions.	Yes.....	
Sec. 63.1(a)(7) through (9).....	Reserved.....	No.....	
Sec. 63.1(a)(10) through (14).....	General applicability of the general provisions.	Yes.....	
Sec. 63.1(b)(1).....	Initial applicability determination.	Yes.....	Subpart WWWW of Part 63 clarifies the applicability in Sec. 63.5780 and 63.5785.
Sec. 63.1(b)(2).....	Reserved.....	No.....	
Sec. 63.1(b)(3).....	Record of the applicability determination.	Yes.....	
Sec. 63.1(c)(1).....	Applicability of this part after a relevant standard has been set under this part.	Yes.....	Subpart WWWW of Part 63 clarifies the applicability of each paragraph of subpart A

				to sources subject to subpart WWWW of Part 63.
Sec.	63.1(c)(2).....	Title V operating permit requirement.	Yes.....	All major affected sources are required to obtain a title V operating permit. Area sources are not subject to subpart WWWW of Part 63.
Sec.	63.1(c)(3) and (4).....	Reserved.....	No.....	
Sec.	63.1(c)(5).....	Notification requirements for an area source that increases HAP emissions to major source levels.	Yes.....	
Sec.	63.1(d).....	Reserved.....	No.....	
Sec.	63.1(e).....	Applicability of permit program before a relevant standard has been set under this part.	Yes.....	
Sec.	63.2.....	Definitions.....	Yes.....	Subpart WWWW of Part 63 defines terms in Sec. 63.5935. When overlap between subparts A and WWWW of Part 63 occurs, you must comply with the subpart WWWW of Part 63 definitions, which take precedence over the subpart A definitions.
Sec.	63.3.....	Units and abbreviations	Yes.....	Other units and abbreviations used in subpart WWWW of Part 63 are defined in subpart WWWW of Part 63.
Sec.	63.4.....	Prohibited activities	Yes.....	Sec. 63.4(a)(3)

		and circumvention.		through (5) is reserved and does not apply.
Sec. 63.5(a)(1) and (2)	Applicability of construction and reconstruction.	Yes	Existing facilities do not become reconstructed under subpart WWWW of Part 63.	
Sec. 63.5(b)(1)	Relevant standards for new sources upon construction.	Yes	Existing facilities do not become reconstructed under subpart WWWW of Part 63.	
Sec. 63.5(b)(2)	Reserved.	No		
Sec. 63.5(b)(3)	New construction/reconstruction.	Yes	Existing facilities do not become reconstructed under subpart WWWW of Part 63.	
Sec. 63.5(b)(4)	Construction/reconstruction notification.	Yes	Existing facilities do not become reconstructed under subpart WWWW of Part 63.	
Sec. 63.5(b)(5)	Reserved.	No		
Sec. 63.5(b)(6)	Equipment addition or process change.	Yes	Existing facilities do not become reconstructed under subpart WWWW of Part 63.	
Sec. 63.5(c)	Reserved.	No		
Sec. 63.5(d)(1)	General application for approval of construction or reconstruction.	Yes	Existing facilities do not become reconstructed under subpart WWWW of Part 63.	
Sec. 63.5(d)(2)	Application for approval of construction.	Yes		
Sec. 63.5(d)(3)	Application for approval of reconstruction.	No		

Sec. 63.5(d)(4).....	Additional information.	Yes.....	
Sec. 63.5(e)(1) through (5).....	Approval of construction or reconstruction.	Yes.....	
Sec. 63.5(f)(1) and (2).....	Approval of construction or reconstruction based on prior State preconstruction review.	Yes.....	
Sec. 63.6(a)(1).....	Applicability of compliance with standards and maintenance requirements.	Yes.....	
Sec. 63.6(a)(2).....	Applicability of area sources that increase HAP emissions to become major sources.	Yes.....	
Sec. 63.6(b)(1) through (5).....	Compliance dates for new and reconstructed sources.	Yes.....	Subpart WWWW of Part 63 clarifies compliance dates in Sec. 63.5800.
Sec. 63.6(b)(6).....	Reserved.....	No.....	
Sec. 63.6(b)(7).....	Compliance dates for new operations or equipment that cause an area source to become a major source.	Yes.....	New operations at an existing facility are not subject to new source standards.
Sec. 63.6(c)(1) and (2).....	Compliance dates for existing sources.	Yes.....	Subpart WWWW of Part 63 clarifies compliance dates in Sec. 63.5800.
Sec. 63.6(c)(3) and (4).....	Reserved.....	No.....	
Sec. 63.6(c)(5).....	Compliance dates for existing area sources that become major.	Yes.....	Subpart WWWW of Part 63 clarifies compliance dates in Sec. 63.5800.
Sec. 63.6(d).....	Reserved.....	No.....	
Sec. 63.6(e)(1) and (2).....	Operation & maintenance requirements.	Yes.....	
Sec. 63.6(e)(3).....	Startup, shutdown, and malfunction plan and	Yes.....	Subpart WWWW of Part 63 requires a startup,

		recordkeeping.		shutdown, and malfunction plan only for sources using add-on controls.
Sec.	63.6(f)(1).....	Compliance except during periods of startup, shutdown, and malfunction.	No.....	Subpart WWWW of Part 63 requires compliance during periods of startup, shutdown, and malfunction, except startup, shutdown, and malfunctions for sources using add-on controls.
Sec.	63.6(f)(2) and (3).....	Methods for determining compliance.	Yes.....	
Sec.	63.6(g)(1) through (3).....	Alternative standard...	Yes.....	
Sec.	63.6(h).....	Opacity and visible emission Standards.	No.....	Subpart WWWW of Part 63 does not contain opacity or visible emission standards.
Sec.	63.6(i)(1) through (14).....	Compliance extensions..	Yes.....	
Sec.	63.6(i)(15).....	Reserved.....	No.....	
Sec.	63.6(i)(16).....	Compliance extensions..	Yes.....	
Sec.	63.6(j).....	Presidential compliance exemption.	Yes.....	
Sec.	63.7(a)(1).....	Applicability of performance testing requirements.	Yes.....	
Sec.	63.7(a)(2).....	Performance test dates.	No.....	Subpart WWWW of Part 63 initial compliance requirements are in Sec. 63.5840.
Sec.	63.7(a)(3).....	CAA Section 114 authority.	Yes.....	
Sec.	63.7(b)(1).....	Notification of performance test.	Yes.....	
Sec.	63.7(b)(2).....	Notification rescheduled performance test.	Yes.....	
Sec.	63.7(c).....	Quality assurance program, including test plan.	Yes.....	Except that the test plan must be submitted with the notification

				of the performance test.
Sec. 63.7(d)	Performance testing facilities.	Yes		
Sec. 63.7(e)	Conditions for conducting performance tests.	Yes		Performance test requirements are contained in Sec. 63.5850. Additional requirements for conducting performance tests for continuous lamination/casting are included in Sec. 63.5870.
Sec. 63.7(f)	Use of alternative test method.	Yes		
Sec. 63.7(g)	Performance test data analysis, recordkeeping, and reporting.	Yes		
Sec. 63.7(h)	Waiver of performance tests.	Yes		
Sec. 63.8(a)(1) and (2)	Applicability of monitoring requirements.	Yes		
Sec. 63.8(a)(3)	Reserved.	No		
Sec. 63.8(a)(4)	Monitoring requirements when using flares.	Yes		
Sec. 63.8(b)(1)	Conduct of monitoring exceptions.	Yes		
Sec. 63.8(b)(2) and (3)	Multiple effluents and multiple monitoring systems.	Yes		
Sec. 63.8(c)(1)	Compliance with CMS operation and maintenance requirements.	Yes		This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.
Sec. 63.8(c)(2) and (3)	Monitoring system installation.	Yes		This section applies if you elect to use a CMS to demonstrate

				continuous compliance with an emission limit.
Sec. 63.8(c)(4)	CMS requirements	Yes	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.	
Sec. 63.8(c)(5)	Continuous Opacity Monitoring System (COMS) minimum procedures.	No	Subpart WWWW of Part 63 does not contain opacity standards.	
Sec. 63.8(c)(6) through (8)	CMS calibration and periods CMS is out of control.	Yes	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.	
Sec. 63.8(d)	CMS quality control program, including test plan and all previous versions.	Yes	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.	
Sec. 63.8(e)(1)	Performance evaluation of CMS.	Yes	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.	
Sec. 63.8(e)(2)	Notification of performance evaluation.	Yes	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.	
Sec. 63.8(e)(3) and (4)	CMS requirements/alternatives.	Yes	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.	

Sec. 63.8(e)(5)(i)	Reporting performance evaluation results.	Yes	limit. This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.
Sec. 63.8(e)(5)(ii)	Results of COMS performance evaluation.	No	Subpart WWWW of Part 63 does not contain opacity standards.
Sec. 63.8(f)(1) through (3)	Use of an alternative monitoring method.	Yes	
Sec. 63.8(f)(4)	Request to use an alternative monitoring method.	Yes	
Sec. 63.8(f)(5)	Approval of request to use an alternative monitoring method.	Yes	
Sec. 63.8(f)(6)	Request for alternative to relative accuracy test and associated records.	Yes	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.
Sec. 63.8(g)(1) through (5)	Data reduction	Yes	
Sec. 63.9(a)(1) through (4)	Notification requirements and general information.	Yes	
Sec. 63.9(b)(1)	Initial notification applicability.	Yes	
Sec. 63.9(b)(2)	Notification for affected source with initial startup before effective date of standard.	Yes	
Sec. 63.9(b)(3)	Reserved	No	
Sec. 63.9(b)(4)(i)	Notification for a new or reconstructed major affected source with initial startup after effective date for which an application	Yes	

		for approval of construction or reconstruction is required.		
Sec.	63.9(b)(4)(ii) through (iv)...	Reserved.....	No.....	
Sec.	63.9(b)(4)(v).....	Notification for a new or reconstructed major affected source with initial startup after effective date for which an application for approval of construction or reconstruction is required.	Yes.....	Existing facilities do not become reconstructed under subpart WWWW of Part 63.
Sec.	63.9(b)(5).....	Notification that you are subject to this subpart for new or reconstructed affected source with initial startup after effective date and for which an application for approval of construction or reconstruction is not required.	Yes.....	Existing facilities do not become reconstructed under subpart WWWW of Part 63.
Sec.	63.9(c).....	Request for compliance extension.	Yes.....	
Sec.	63.9(d).....	Notification of special compliance requirements for new source.	Yes.....	
Sec.	63.9(e).....	Notification of performance test.	Yes.....	
Sec.	63.9(f).....	Notification of opacity and visible emissions observations.	No.....	Subpart WWWW of Part 63 does not contain opacity or visible emission standards.
Sec.	63.9(g)(1).....	Additional notification requirements for sources using CMS.	Yes.....	This section applies if you elect to use a CMS to demonstrate

				continuous compliance with an emission limit.
Sec.	63.9(g)(2).....	Notification of compliance with opacity emission standard.	No.....	Subpart WWWW of Part 63 does not contain opacity emission standards.
Sec.	63.9(g)(3).....	Notification that criterion to continue use of alternative to relative accuracy testing has been exceeded.	Yes.....	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.
Sec.	63.9(h)(1) through (3).....	Notification of compliance status.	Yes.....	
Sec.	63.9(h)(4).....	Reserved.....	No.....	
Sec.	63.9(h)(5) and (6).....	Notification of compliance status.	Yes.....	
Sec.	63.9(i).....	Adjustment of submittal deadlines.	Yes.....	
Sec.	63.9(j).....	Change in information provided.	Yes.....	
Sec.	63.10(a).....	Applicability of recordkeeping and reporting.	Yes.....	
Sec.	63.10(b)(1).....	Records retention.....	Yes.....	
Sec.	63.10(b)(2)(i) through (v)....	Records related to startup, shutdown, and malfunction.	Yes.....	Only applies to facilities that use an add-on control device.
Sec.	63.10(b)(2)(vi) through (xi)..	CMS records, data on performance tests, CMS performance evaluations, measurements necessary to determine conditions of performance tests, and performance evaluations.	Yes.....	
Sec.	63.10(b)(2)(xii).....	Record of waiver of recordkeeping and reporting.	Yes.....	

Sec. 63.10(b)(2)(xiii).....	Record for alternative to the relative accuracy test.	Yes.....	
Sec. 63.10(b)(2)(xiv).....	Records supporting initial notification and notification of compliance status.	Yes.....	
Sec. 63.10(b)(3).....	Records for applicability determinations.	Yes.....	
Sec. 63.10(c)(1).....	CMS records.....	Yes.....	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.
Sec. 63.10(c)(2) through (4).....	Reserved.....	No.....	
Sec. 63.10(c)(5) through (8).....	CMS records.....	Yes.....	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.
Sec. 63.10(c)(9).....	Reserved.....	No.....	
Sec. 63.10(c)(10) through (15).....	CMS records.....	Yes.....	This section applies if you elect to use a CMS to demonstrate continuous compliance with an emission limit.
Sec. 63.10(d)(1).....	General reporting requirements.	Yes.....	
Sec. 63.10(d)(2).....	Report of performance test results.	Yes.....	
Sec. 63.10(d)(3).....	Reporting results of opacity or visible emission observations.	No.....	Subpart WWWW of Part 63 does not contain opacity or visible emission standards.
Sec. 63.10(d)(4).....	Progress reports as part of extension of compliance.	Yes.....	
Sec. 63.10(d)(5).....	Startup, shutdown, and	Yes.....	Only applies if you use

		malfunction reports.		an add-on control device.
Sec. 63.10(e)(1) through (3).....	Additional reporting requirements for CMS.		Yes.....	This section applies if you have an add-on control device and elect to use a CEM to demonstrate continuous compliance with an emission limit.
Sec. 63.10(e)(4).....	Reporting COMS data....		No.....	Subpart WWWW of Part 63 does not contain opacity standards.
Sec. 63.10(f).....	Waiver for recordkeeping or reporting.		Yes.....	
Sec. 63.11.....	Control device requirements.		Yes.....	Only applies if you elect to use a flare as a control device.
Sec. 63.12.....	State authority and delegations.		Yes.....	
Sec. 63.13.....	Addresses of State air pollution control agencies and EPA Regional Offices.		Yes.....	
Sec. 63.14.....	Incorporations by reference.		Yes.....	
Sec. 63.15.....	Availability of information and confidentiality.		Yes.....	

D.1.12 State Only Reinforced Plastic Composites National Emission Standards for Hazardous Air Pollutants for Reinforced Plastic Composites Production (NESHAP) Requirements
[326 IAC 20-56]

Pursuant to 326 IAC 20-56, the Permittee shall comply with the previous version of 40 CFR 63, Subpart WWWW, published in 68 FR 19402, April 21, 2003, for the fiberglass reinforced plastic component manufacturing operations, and all activities associated with the production of plastic composites, with a compliance date of April 21, 2006. Compliance with the requirements specified in Condition D.2.11 shall satisfy the requirements of 326 IAC 20-56, with the exception of the requirements listed under 40 CFR 63.5810, 40 CFR 63.5895(d) and Tables 1, 3, and 7 in that condition. In place of those requirements, to satisfy 326 IAC 20-56 only, the Permittee shall comply with the following:

Options for Meeting Standard

§ 63.5810 What are my options for meeting the standards for open molding and centrifugal casting operations at new and existing source

You must use one of the following methods in paragraphs (a) through (d) of this section to meet the standards in 63.5805. When you are complying with an emission limit in Table 3 to this subpart, you may use any control method that reduces organic HAP emissions, including reducing resin and gel coat organic HAP content, changing to non-atomized mechanical application, and covered curing techniques. The necessary calculations must be completed within 30 days after the end of each month. You may switch between the compliance options in paragraphs (a) through (d) of this section. When you change to an option based on a 12-month rolling average, you must base the average on the previous 12 months of data calculated using the compliance option you are currently using unless you were using the compliant materials option in paragraph (d) of this section. In this case, you must immediately begin collecting resin and gel coat use data and demonstrate compliance 12 months after changing option.

(a) *Meet the individual organic HAP emissions limits for each operation.* Demonstrate that you meet the individual organic HAP emissions limits for each open molding operation and for each centrifugal casting operation type in Tables 3, or 5 to this subpart that apply to you. This is done in two steps. First, determine an organic HAP factor for each individual resin and gel coat, application method, and control method you use in a particular operation. Second, calculate, for each particular operation type, a weighted average of those organic HAP emissions factors based on resin and gel coat use. Your calculated organic HAP emissions factor must either be at or below the applicable organic HAP emissions limit in Tables 3 or 5 to this subpart based on a 12-month rolling average. Use the procedures described in paragraphs (a)(1) through (3) of this section to calculate average organic HAP emissions factors for each of your operations.

(1) Calculate your actual organic HAP emissions factor for each different process stream within each operation type. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 to this subpart for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in 40 CFR 63.5796. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness by conducting testing according to the procedures specified of Appendix A to 40 CFR 63, Subpart WWWW.

(2) Calculate your actual operation organic HAP emissions factor for the last 12 months for each open molding operation type and for each centrifugal casting operation type by calculating the weighted average of the individual process stream organic HAP emissions factors within each respective operation. To do this, sum the product of each individual organic HAP emissions factor calculated in 40 CFR 63.5810(a)(1) and the amount of neat resin plus and neat gel coat plus usage that correspond to the individual factors and divide the numerator by the total amount of neat resin plus and neat gel coat plus used in that operation type. Use the following equation to calculate your actual organic HAP emissions factor for each

open molding operation type and each centrifugal casting operation type.

$$\text{Average organic HAP Emissions Factor} = \frac{\sum_{i=1}^n (\text{Actual Process Stream } EF_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 2})$$

Where:

Actual Process Stream EF_i = actual organic HAP emissions factor for process stream i , lbs/ton
 Material $_i$ = neat resin plus or neat gel coat plus used during the last 12 calendar months for process stream i , tons

n = number of process streams where you calculated an organic HAP emissions factor

(3) Compare each organic HAP emissions factor calculated in paragraph (b)(2) of this section with its corresponding organic HAP emissions limit in Tables 3 or 5 to this subpart. If all emissions factors are equal to or less than their corresponding emission limits, then you are in compliance.

(b) *HAP Emission Factor averaging option.* Demonstrate each month that you meet each weighted average of the organic HAP emissions limits in Tables 3 or 5 to 40 CFR 63, Subpart WWWW that apply to you. When using this option, you must demonstrate compliance with the weighted average organic HAP emissions limit for all your open molding operations. The Permittee shall demonstrate compliance using the procedures specified in paragraphs (b)(1) – (3) of this section:

(1) Each month, calculate the weighted average organic HAP emissions limit for all open molding operations for your facility for the last 12-month period to determine the organic HAP emissions limit you must meet. To do this, multiply the individual organic HAP emissions limits in Tables 3 or 5 to this subpart for each open molding operation type by the amount of neat resin plus or neat gel coat plus used in the last 12 months for each open molding operation type, sum these results, and then divide this sum by the total amount of neat resin plus and neat gel coat plus used in open molding over the last 12 months. Use the following equation to calculate the weighted average organic HAP emissions limit for all open molding operations.

$$\text{Weighted Average Emission Limit} = \frac{\sum_{i=1}^n (EL_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 3})$$

Where:

EL_i = organic HAP emissions limit for operation type i , lbs/ ton from Tables 3, 5 or 7 to this subpart
 Material $_i$ =neat resin plus or neat gel coat plus used during the last 12-month period for operation type i , tons

n = number of operations

(2) Each month, calculate your actual weighted average organic HAP emissions factor for open molding. To do this, multiply your actual open molding operation organic HAP emissions factors and the amount of neat resin plus and neat gel coat plus used in each open molding operation type, sum the results, and divide this sum by the total amount of neat resin plus and neat gel coat plus used in open molding operations. You must calculate your actual individual HAP emissions factors for each operation type as described in 40 CFR 63.5810(a)(1) and (2). Use the following equation to calculate your actual weighted average organic HAP emissions factor.

$$\frac{\text{Actual Weighted Average organic HAP Emissions Factor}}{\text{Factor}} = \frac{\sum_{i=1}^n (\text{Actual Operation } EF_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 4})$$

Where:

Actual Individual EF_i = Actual organic HAP emissions factor for operation type i , lbs/ton

Material_i = neat resin plus or neat gel coat plus used during the last 12 calendar months for operation type i , tons

n = number of operations

(3) Compare the values calculated in 40 CFR 63.5810(b)(1) and (2). If each 12-month rolling average organic HAP emissions factor is less than or equal to the corresponding 12-month rolling average organic HAP emissions limit, then you are in compliance.

(c) If you have multiple operation types, meet the organic HAP emission limits for one operation type, and use the same resin(s) for all operations of that resin type. If you have more than one operation type, you may meet the emission limit for one of those operations, and use the same resin(s) in all other open molding and centrifugal casting operations.

(1) This option is limited to resins of the same type. The resin types for which this option may be used are noncorrosion-resistant, corrosion-resistant and/or high strength, and tooling.

(2) For any combination of manual resin application, mechanical resin application, filament application, or centrifugal casting, you may elect to meet the organic HAP emissions limit for any one of these operations and use that operation's same resin in all of the resin operations listed in this paragraph. Table 7 to this subpart presents the possible combinations based on a facility selecting the application process that results in the highest allowable organic HAP content resin. If your resin organic HAP content is below the applicable values shown in Table 7 to this subpart, you are in compliance.

(3) You may also use a weighted average organic HAP content for each operation described in paragraph (c)(2) of this section to this subpart. Use equation 2 in 63.5810(a)(2) except substitute organic HAP content for organic HAP emission factors.

You are in compliance if the weighted average organic HAP content based on the last 12 months of resin use is less than or equal to the applicable organic HAP contents in Table 7 to this subpart.

(4) You may simultaneously use the averaging provisions in paragraph (b) to demonstrate compliance for any operations and/or resins you do not include in your compliance demonstrations under paragraphs (c)(2) and (3) of this section. However, any resins for which you claim compliance under the option in (c)(2) and (3) of this section may not be included in any of the averaging calculations described in paragraphs (a) or (b) of this section used for resins for which you are not claiming compliance under this option.

(d) Use resins and gel coats that do not exceed the maximum organic HAP contents shown in Table 3 to this subpart.

Continuous Compliance Requirements

§63.5895 How do I monitor and collect data to demonstrate continuous compliance?

(d) If you initially demonstrate that all resins and gel coats individually meet the applicable organic HAP emissions limits, or organic HAP content limits, then resin and gel coat use records are not required. However, you must include a statement in each compliance report that all resins and gel coats still meet

the organic HAP limits for compliant resins and gel coats shown in Tables 3 or 7 of this subpart. If after this initial demonstration, you change to a higher organic HAP resin or gel coat, or increase the resin or gel coat organic HAP content, or change to a higher-emitting resin or gel coat application method, then you must either again demonstrate that all resins and gel coats still meet the applicable organic HAP emissions limits, or begin collecting resin and gel coat use records and calculate compliance on a 12-month rolling average.

Table 1 to Subpart WWWW of Part 63--Equations to Calculate Organic HAP Emissions Factors for Specific Open Molding and Centrifugal Casting Process Streams as required in Sec. 63.5796, 63.5799(a)(1) and (b), and 63.5810(a)(1), to calculate organic HAP emissions factors for specific open molding and centrifugal casting process streams you must use the equations in the following table:]

If your operation type is a new or existing ...	And you use ...	With ...	Use this organic HAP Emissions Factor (EF) Equation for materials with less than 33 percent organic HAP (19 percent organic HAP for nonatomized gel coat) ^{1 2 3} ...	Use this organic HAP Emissions Factor (EF) Equation for materials with 33 percent or more organic HAP (19 percent for nonatomized gel coat) ^{1 2 3} ...
1. Open molding operation	a. Manual resin application	i. Nonvapor-suppressed resin. ii. vapor-suppressed resin. iii. vacuum bagging/closed-mold curing with roll out. iv. vacuum bagging/closed-mold curing without roll out	$EF = 0.126 \times \%HAP \times 2000$ $EF = 0.126 \times \%HAP \times 2000 \times (1 - (0.5 \times VSE \text{ Factor}))$ $EF = 0.126 \times \%HAP \times 2000 \times 0.8$ $EF = (0.126 \times \%HAP \times 2000 \times 0.5)$	$EF = ((0.286 \times \%HAP) - 0.0529) \times 2000$ $EF = ((0.286 \times \%HAP) - 0.0529) \times 2000 \times (1 - (0.5 \times VSE \text{ Factor}))$ $EF = ((0.286 \times \%HAP) - 0.0529) \times 2000 \times 0.8$ $EF = ((0.286 \times \%HAP) - 0.0529) \times 2000 \times 0.5$
	c. nonatomized mechanical resin application	v. nonvapor-suppressed resin vi. vapor-suppressed resin vii. closed-mold curing with roll out viii. vacuum bagging/closed-mold curing without roll out	$EF = 0.107 \times \%HAP \times 2000$ $EF = 0.107 \times \%HAP \times 2000 \times (1 - (0.45 \times VSE \text{ Factor}))$ $EF = 0.107 \times \%HAP \times 2000 \times 0.85$ $EF = (0.107 \times \%HAP \times 2000 \times 0.55)$	$EF = ((0.157 \times \%HAP) - 0.0165) \times 2000$ $EF = ((0.157 \times \%HAP) - 0.0165) \times 2000 \times (1 - (0.45 \times VSE \text{ Factor}))$ $EF = ((0.157 \times \%HAP) - 0.0165) \times 2000 \times 0.85$ $EF = ((0.157 \times \%HAP) - 0.0165) \times 2000 \times 0.55$
	e. filament application ⁵	i. nonvapor-suppressed resin ii. vapor-suppressed resin	$EF = 0.184 \times \%HAP \times 2000$ $EF = 0.12 \times \%HAP \times 2000$	$EF = ((0.2746 \times \%HAP) - 0.0298) \times 2000$ $EF = ((0.2746 \times \%HAP) - 0.0298) \times 2000 \times 0.65$

	g. nonatomized spray gel coat application	nonvapor-suppressed gel coat	$EF = 0.185 \times \% \text{ HAP} \times 2000$	$EF = ((0.4506 \times \% \text{ HAP}) - 0.0505) \times 2000$
--	---	------------------------------	--	--

Footnotes to Table 1

\1\ To obtain the organic HAP emissions factor value for an operation with an add-on control device multiply the EF above by the add-on control factor calculated using Equation 1 of Sec. 63.5810. The organic HAP emissions factors have units of lbs of organic HAP per ton of resin or gel coat applied.

\2\ Percent HAP means total weight percent of organic HAP (styrene, methyl methacrylate, and any other organic HAP) in the resin or gel coat prior to the addition of fillers, catalyst, and promoters. Input the percent HAP as a decimal, i.e. 33 percent HAP should be input as 0.33, not 33.

\3\ The VSE factor means the percent reduction in organic HAP emissions expressed as a decimal measured by the VSE test method of appendix A to this subpart.

\5\ Applies only to filament application using an open resin bath. If resin is applied manually or with a spray gun, use the appropriate manual or mechanical application organic HAP emissions factor equation.

Table 3 to Subpart WWWW of Part 63.--Organic HAP Emissions Limits for Existing Open Molding Sources, New Open Molding Sources Emitting Less Than 100 TPY of HAP, and New and Existing Centrifugal Casting and Continuous Lamination/Casting Sources that Emit Less Than 100 TPY of HAP As required in Sec. Sec. 63.5796, 63.5805 (a) through (c) and (g), 63.5810(a), (b), and (d), 63.5820(c), 63.5830, 63.5835(a), 63.5895(c) and (d), 63.5900(a)(2), and 63.5915(c), you must meet the appropriate organic HAP emissions limits in the following table:]

If your operation is ...	And you use ...	Your organic HAP emissions limit is ¹ ...	And the highest organic HAP content for a compliant resin or gel coat is ² ...
1. Open molding-corrosion-resistant and/or high strength (CR/HS)	a. mechanical resin application	112 lb/ton	46.2 with nonatomized resin application.
	b. filament application	171 lb/ton	42.0
	c. manual resin application	123 lb/ton	40.0
2. Open molding – non-CR/HS	a. mechanical resin application	87 lb/ton	38.4 with nonatomized resin application.
	b. filament application	188 lb/ton	45.0
	c. manual resin application	87 lb/ton	33.6
3. Open molding-tooling	a. mechanical resin application	254 lb/ton	43.0 with atomized application, 91.4 with nonatomized application.
	b. manual resin application	157 lb/ton	45.9
4. Open molding – low-flame spread/low-smoke products	a. mechanical resin application	497 lb/ton	60.0
	b. filament application	270 lb/ton	60.0
	c. manual resin application	238 lb/ton	60.0
5. Open molding – shrinkage controlled resins	a. mechanical resin application	354 lb/ton	50.0
	b. filament application	215 lb/ton	50.0
	c. manual resin application	180 lb/ton	50.0
6. Open molding-gel coat ³	a. Tooling gel coating	437 lb/ton	40.0
	b. White/ off white pigmented gel coating	267 lb/ton	30.0
	c. all other pigmented gel coating	377 lb/ton	37.0
	d. CR/HS or high performance gel coat	605 lb/ton	48.0
	e. fire retardant gel coat	854 lb/ton	60.0
	f. clear production gel coat	522 lb/ton	44.0

Footnotes to Table 3

1 Organic HAP emissions limits for open molding and centrifugal casting are expressed as lb/ton. You must be at or below these values based on a 12-month rolling average.

2 A compliant resin or gel coat means that if its organic HAP content is used to calculate an organic HAP emissions factor, the factor calculated does not exceed the appropriate organic HAP emissions limit shown in the table.

3 These limits are for spray application of gel coat. Manual gel coat application must be included as part of spray gel coat application for compliance purposes using the same organic HAP emissions factor equation and organic HAP emissions limit. If you only apply gel coat with manual application, treat the manually applied gel coat as if it were applied with atomized spray for compliance determinations.

Table 7 to Subpart WWWW of Part 63.--Options Allowing Use of the Same Resin Across Different Operations That Use the Same Resin Type [As required in Sections. 63.5810(a) through (d), 63.5835(a), 63.5895(c), and 63.5900(a)(2), when electing to use the same resin(s) for multiple resin application methods you may use any resin(s) with an organic HAP contents less than or equal to the values shown in the following table, or any combination of resins whose weighted average organic HAP content based on a 12-month rolling average is less than or equal to the values shown the following table:]

If your facility has the following resin type and application method ...	The highest resin weight percent organic HAP content, or weighted average weight percent organic HAP content, you can use for . . .	Is . . .
2. CR/HS resins, nonatomized mechanical	a. CR/HS filament application	46.2
	b. CR/HS manual	46.2
5. Non-CR/HS resins, nonatomized mechanical	a. Non-CR/HS manual	38.4
	b. non-CR/HS centrifugal casting	38.4
7. Tooling resins, nonatomized mechanical	Tooling manual	91.4
8. Tooling resins, manual	Tooling atomized mechanical.	45.9

The requirements of 326 IAC 20-56 listed in this condition are not federally enforceable.

D.1.13 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-56-2]

Pursuant to 326 IAC 20-56-2, the Permittee shall comply with the following operator training requirements:

- (a) Each owner or operator shall train all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and applications that could result in excess emissions if performed improperly according to the following schedule:
 - (1) All personnel hired shall be trained within thirty (30) days of hiring.
 - (2) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.
 - (3) Personnel who have been trained by another owner or operator subject to this rule are exempt from paragraph (1) if written documentation that the employee's training is current is provided to the new employer.

- (b) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:
 - (1) Appropriate application techniques.
 - (2) Appropriate equipment cleaning procedures.
 - (3) Appropriate equipment setup and adjustment to minimize material usage and overspray.

- (c) The owner or operator shall maintain the following training records on site and make them available for inspection and review:
 - (1) A copy of the current training program.
 - (2) A list of the following:
 - (A) All current personnel, by name, that are required to be trained.
 - (B) The date the person was trained or date of most recent refresher training, whichever is later.
- (d) Records of prior training programs and former personnel are not required to be maintained.

D.1.14 One Time Deadlines Relating to NESHAP for Reinforced Plastic Composites Production [40 CFR Part 63, Subpart WWWW]

- (a) Pursuant to 40 CFR 63.5905, the Permittee must submit an Initial Notification by August 19, 2003.
- (b) The Permittee must submit a Notification of Compliance status report for source by May 21, 2007.

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

Insignificant Activity

- (a) Grinding and machining operations controlled with fabric filters scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations.
- (1) One (1) grinding area, with a maximum capacity of 1104 pounds per hour, using bag filters for particulate control, and exhausting to stack 1.4(a) through stack 1.4(h). [326 IAC 6-3-2(e)]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Particulate Emission Limitations for Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2(e)]

Pursuant to 326 IAC 6-3-2(e), the allowable particulate emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour. This includes the following operations:

- (1) One (1) grinding area, with a maximum capacity of 1104 pounds per hour, using bag filters for particulate control, and exhausting to stack 1.4(a) through stack 1.4(h). [326 IAC 6-3-2(e)]

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

PART 70 OPERATING PERMIT CERTIFICATION

Source Name: Masterfab, Inc.
Source Address: 16618 Maple City Drive, Goshen, IN 46526
Mailing Address: PO Box 463 Goshen, IN 46526
Part 70 Permit No.: T039-19842-00001

**This certification shall be included when submitting monitoring, testing reports/results
or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Affidavit (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY**

**COMPLIANCE BRANCH
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
Phone: 317-233-5674
Fax: 317-233-5967**

**PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT**

Source Name: Masterfab, Inc.
Source Address: 16618 Maple City Drive, Goshen, IN 46526
Mailing Address: PO Box 463 Goshen, IN 46526
Part 70 Permit No.: T039-19842-00001

This form consists of 2 pages

Page 1 of 2

- | |
|--|
| <input type="checkbox"/> This is an emergency as defined in 326 IAC 2-7-1(12) |
| X The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and |
| X The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16. |

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by:

Title / Position:

Date:

Phone:

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

Part 70 Quarterly Report

Source Name: Masterfab, Inc.
Source Address: 16618 Maple City Drive, Goshen, IN 46526
Mailing Address: PO Box 463 Goshen, IN 46526
Part 70 Permit No.: T039-19842-00001
Facility: One (1) gelcoat booth, one (1) lamination booth, Mold and shop pattern area and Final Finish & specialty products area
Parameter: VOC usage
Limit: Use of resins, gelcoats and solvents shall be limited such that the potential to emit (PTE) of volatile organic compounds from resins, gel coats and solvents only shall be limited to less than or equal to 100 tons per twelve (12) consecutive months.

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.
Deviation has been reported on:

Submitted by:
Title / Position:
Signature:
Date:
Phone:

Attach a signed certification to complete this report

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Masterfab, Inc.
Source Address: 16618 Maple City Drive, Goshen, IN 46526
Mailing Address: PO Box 463 Goshen, IN 46526
Part 70 Permit No.: T039-19842-00001

Months: _____ to _____ Year: _____

Page 1 of 2

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed By:

Title/Position:

Date:

Phone:

Attach a signed certification to complete this report.

**Indiana Department of Environmental Management
Office of Air Quality**

**Addendum to the Technical Support Document (TSD) for a
Title V Renewal Operating Permit**

Source Background and Description

Source Name:	Masterfab, Inc.
Source Location:	16618 Maple City Drive, Goshen, IN 46526
County:	Elkhart
SIC Code:	3089
Operation Permit No.:	T039-7117-00001
Operation Permit Issuance Date:	May 11, 2000
Permit Renewal No.:	T039-19842-00001
Permit Reviewer:	Ganesh Srinivasan/EVP

On February 23, 2006, the Office of Air Quality (OAQ) had a notice published in the Goshen News, Goshen, Indiana, stating that Masterfab, Inc. had applied for a Title V Renewal Permit T039-19842-00001. The notice also stated that OAQ proposed to issue a permit for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

No Comments were received during the comment period. However, IDEM, OAQ has decided to make the following changes:

Changes made to the permit as a result of the comments are shown in bold and deleted permit language is shown with a line through it. Subsequent conditions have been renumbered without repetition. Any permit changes affecting the permit's Table of Contents are also revised without replication herein.

IDEM, OAQ Change 1: The title page was updated with the current Branch Chief information.

Operation Permit No.: T039-19842-00001	
Issued by: Paul Dubenetzky, Assistant Commissioner Office of Air Quality Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: Expiration Date:

IDEM, OAQ Change 2:

Rule 326 IAC 9-1-2 is federally enforceable, therefore, Condition C.4 has been revised to reflect this change as follows:

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. ~~326 IAC 9-1-2 is not federally enforceable.~~

IDEM, OAQ Change 3: Pursuant to 326 IAC 20-25-1(d), since this source is subject to 326 IAC 20-56, concerning emission standards for hazardous air pollutants from reinforced plastic composites production, it is exempt from 326 IAC 20-25 after April 21, 2006, because it is a major source that existed on or before August 2, 2001. Therefore the Conditions D.1.2, D.1.3 and D.1.4 have been deleted since rule 326 IAC 20-25 is no longer applicable.

~~D.1.2 Emissions Standards for Reinforced Plastics Composites Fabricating [326 IAC 20-25-3]~~

~~This rule 326 IAC 20-25-3 will apply to the fiberglass operations at this source until April 21, 2006, the compliance date for 40 CFR 63 Subpart WWWW.~~

~~(a) The total HAP monomer content of the following materials shall be limited based on the application method used and the products produced as specified in the following table:~~

Fiber Reinforced Plastics Composites Products Except Watercraft	HAP Monomer Content, Weight Percent
<i>Resin, Manual or Mechanical Application</i>	
Production Specialty Products	48*
Production Noncorrosion Resistant Unfilled	35*
Production Noncorrosion Resistant Filled (35% by weight)	38
Production, Noncorrosion Resistant, Applied to Thermoformed Thermoplastic Sheet	42
Production, Class I, Flame and Smoke Shrinkage Controlled Tooling	60*
52	43
<i>Gel Coat Application</i>	
Production Pigmented	37
Clear Production	44
Tooling	45
Production Pigmented, subject to ANSI^a standards	45
Production Clear, subject to ANSI^a standards	50

^aAmerican National Standards Institute.

* Categories that must use mechanical nonatomized application technology or manual application as stated in subsection (c). Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis. If all of the resins and gel coats used during a month meet the specified HAP monomer content limits, then maintaining records of content and usage as specified under Condition D.1.15(b) is sufficient for demonstrating compliance with the HAP monomer content limits.

~~Cross-Averaging~~

~~Compliance with the limitations contained in this condition may be demonstrated using monthly emission averaging across categories of each resin or gel coat application category listed in subsection (b) by the use of resins or gel coats with HAP monomer contents lower than the limits specified, and/or additional emission reduction techniques approved by IDEM, OAQ.~~

~~Examples of emission reduction techniques include, but are not limited to, using nonatomized application to apply resins or gelcoats within a category that does not require nonatomized application, lower monomer content resins and gel coats, vapor suppression, vacuum bagging, controlled spraying, or installing a control device. This is allowed to meet the HAP monomer content~~

limits for resins and gel coats within each category.

Cross-averaging between categories have been approved by IDEM, OAQ for this source. In these instances, the HAP monomer content limits for resins and gel shall be calculated on an equivalent emissions mass basis monthly to demonstrate compliance as shown below:

For Averaging within a category:

$$\sum Em_A \leq \sum (M_R * E_a)$$

Where: _____

_____ M_R = Total monthly mass of material within each category

_____ E_a = Emission factor for each material based on allowable monomer content and allowable application method for each category.

_____ Em_A = Actual monthly emissions from all materials used within a category based on material specific emission factors, emission reduction techniques and emission controls

_____ *Units: mass = tons*

_____ *emission factor = lbs of monomer per ton of resin or gel coat*

_____ *emissions = lbs of monomer*

Note: Fillers may not be included when averaging.

(b) _____ The following categories of materials in subsection (a) shall be applied using mechanical nonatomized application technology or manual application:

- (1) _____ Production noncorrosion resistant, unfilled resins from all sources.
- (2) _____ Production, specialty product resins from all sources.
- (3) _____ Tooling resins used in the manufacture of watercraft.
- (4) _____ Production resin used for Class I flame and smoke products.

Nonatomized application equipment means the devices where resin or gel coat material does any of the following:

- (1) _____ Flows from the applicator, in a steady state in a observable coherent flow, without droplets, for a minimum distance of three (3) inches from the applicator orifices such as flow coaters, flow choppers, and fluid impingement equipment.
- (2) _____ Is mechanically dispensed within or on to a paint roller applicator such as pressure fed rollers.
- (3) _____ Is deposited on fiber reinforcement moving through a resin or gel coat bath such as resin impregnators.

Nonatomized spray application technology includes flow coaters, flow choppers, pressure fed rollers, fluid impingement, or other non-spray applications of a design and specifications approved by IDEM, OAQ.

Filled resins are resins containing greater than or equal to thirty five percent (35%) by weight inert filler material, such as silica micro-spheres or micro-balloons, added to alter the density or other physical properties of the resin. The term "inert filler" does not include pigments.

- ~~(c) Unless specified in subsection (b), gel coat application and mechanical application of resins shall be by any of the following spray technologies:~~
- ~~(1) Nonatomized application technology.~~
 - ~~(2) Air-assisted airless.~~
 - ~~(3) Airless.~~
 - ~~(4) High volume, low pressure (HVLP).~~
 - ~~(5) Equivalent emission reduction technologies to subdivisions (2) through (4).~~
- ~~(d) The following cleaning operation standards for resin and gel coat application equipment shall apply:~~
- ~~(1) For routine flushing of resin and gel coat application equipment such as spray guns, flow coaters, brushes, rollers, and squeegees, a cleaning solvent shall contain no HAPs. This emission standard does not apply to solvents used for removing cured resin or gel coat from application equipment.~~
 - ~~(2) A source must store HAP containing solvents used for removing cured resin or gel coat in containers with covers. The covers must have no visible gaps and must be in place at all times, except when equipment is placed in or removed from the container.~~
 - ~~(3) Recycled cleaning solvents that contain less than or equal to five percent (5%) HAP by weight are considered to contain no HAP for the purposes of this subsection.~~

D.1.3 Work Practice Standards for Reinforced Plastic Composites Fabrication [326 IAC 20-25-4]

~~On and before April 21, 2006, pursuant to 326 IAC 20-25-4, the following work practice standards shall be implemented until April 21, 2006:~~

- ~~(a) Non-atomizing spray equipment shall not be operated at pressures that atomize the material during the application process.~~
- ~~(b) Except for mixing containers as described in item (g), HAP-containing materials shall be kept in a closed container when not in use.~~
- ~~(c) Solvents sprayed during cleanup and resin changes shall be directed into solvent collection containers.~~
- ~~(d) Solvent collection containers shall be kept closed when not in use.~~
- ~~(e) Clean-up rags with solvent shall be stored in closed containers.~~
- ~~(f) Closed containers shall be used for the storage of the following:~~
 - ~~(1) All production and tooling resins that contain HAPs.~~
 - ~~(2) All production and tooling gel coats that contain HAPs.~~
 - ~~(3) Waste resins and gel coats that contain HAPs.~~
 - ~~(4) Cleaning materials, including waste cleaning materials.~~
 - ~~(5) Other materials that contain HAPs.~~

- ~~(g) All resin and gel coat mixing containers with a capacity equal to or greater than fifty-five (55) gallons must have a cover with no visible gaps in place at all times except when material is being added to or removed from a container, or when mixing or pumping equipment is being placed in or removed from a container.~~

~~D.1.4 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-25-8]~~

~~On and before April 21, 2006, pursuant to 326 IAC 20-25-8, all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and spray-like applications (for example, those applications that could result in excess emissions if performed improperly) shall be trained according to the following schedule until April 21, 2006:~~

- ~~(a) All personnel hired after March 7, 2001 shall be trained within fifteen (15) days of hiring.~~
- ~~(b) All personnel hired before March 7, 2001 shall be trained or evaluated by a supervisor within thirty (30) days of the start of operation.~~
- ~~(c) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.~~
- ~~(d) Personnel who have been trained by another owner or operator subject to 326 IAC 20-25 are exempt from subdivision (a) if written documentation that the employee's training is current is provided to the new employer.~~
- ~~(e) If the result of an evaluation shows that training is needed, such training shall occur within fifteen (15) days of the evaluation.~~
- ~~(f) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:~~
- ~~(1) Appropriate application techniques.~~
- ~~(2) Appropriate equipment cleaning procedures.~~
- ~~(3) Appropriate equipment setup and adjustment to minimize material usage and overspray.~~

IDEM, OAQ Change 4: The source is subject to 326 IAC 20-56 (Reinforced Plastic Composites Production) because it is subject to the requirements of 40 CFR 63, Subpart WWWW (National Emission Standard for Hazardous Air Pollutants: Reinforced Plastic Composites Production). 326 IAC 20-56 incorporates by reference the previous version of 40 CFR 63, Subpart WWWW, from 68 FR 19402, April 21, 2003. The requirements of this rule are the same for this source as the requirements of the current version of the rule, except for the following:

- a. 40 CFR 63.5810; and
- b. 40 CFR 63.5895(d).

There are also changes in Tables 1, 3, and 7 that change the requirements of the rule for this source.

As such, the permit has been revised to include the requirements of 40 CFR 63, Subpart WWWW that existed before April 21, 2003 that have since been revised in the most recent version of 40 CFR 63, Subpart WWWW. The following changes have been made to the permit:

D.1.12 State Only Reinforced Plastic Composites National Emission Standards for Hazardous Air Pollutants for Reinforced Plastic Composites Production (NESHAP) Requirements [326 IAC 20-56]

Pursuant to 326 IAC 20-56, the Permittee shall comply with the previous version of 40 CFR 63, Subpart WWWW, published in 68 FR 19402, April 21, 2003, for the fiberglass reinforced plastic component manufacturing operations, and all activities associated with the production of plastic composites, with a compliance date of April 21, 2006. Compliance with the requirements specified in Condition D.2.11 shall satisfy the requirements of 326 IAC 20-56, with the exception of the requirements listed under 40 CFR 63.5810, 40 CFR 63.5895(d) and Tables 1, 3, and 7 in that condition. In place of those requirements, to satisfy 326 IAC 20-56 only, the Permittee shall comply with the following:

Options for Meeting Standard

§ 63.5810 What are my options for meeting the standards for open molding and centrifugal casting operations at new and existing source

You must use one of the following methods in paragraphs (a) through (d) of this section to meet the standards in 63.5805. When you are complying with an emission limit in Table 3 to this subpart, you may use any control method that reduces organic HAP emissions, including reducing resin and gel coat organic HAP content, changing to non-atomized mechanical application, and covered curing techniques. The necessary calculations must be completed within 30 days after the end of each month. You may switch between the compliance options in paragraphs (a) through (d) of this section. When you change to an option based on a 12-month rolling average, you must base the average on the previous 12 months of data calculated using the compliance option you are currently using unless you were using the compliant materials option in paragraph (d) of this section. In this case, you must immediately begin collecting resin and gel coat use data and demonstrate compliance 12 months after changing option.

(a) Meet the individual organic HAP emissions limits for each operation. Demonstrate that you meet the individual organic HAP emissions limits for each open molding operation and for each centrifugal casting operation type in Tables 3, or 5 to this subpart that apply to you. This is done in two steps. First, determine an organic HAP factor for each individual resin and gel coat, application method, and control method you use in a particular operation. Second, calculate, for each particular operation type, a weighted average of those organic HAP emissions factors based on resin and gel coat use. Your calculated organic HAP emissions factor must either be at or below the applicable organic HAP emissions limit in Tables 3 or 5 to this subpart based on a 12-month rolling average. Use the procedures described in paragraphs (a)(1) through (3) of this section to calculate average organic HAP emissions factors for each of your operations.

(1) Calculate your actual organic HAP emissions factor for each different process stream within each operation type. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 to this subpart for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in 40 CFR 63.5796. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness by conducting testing according to the procedures specified of Appendix A to 40 CFR 63, Subpart WWWW.

(2) Calculate your actual operation organic HAP emissions factor for the last 12 months for each open molding operation type and for each centrifugal casting operation type by calculating the weighted average of the individual process stream organic HAP emissions factors within each respective operation. To do this, sum the product of each individual organic HAP emissions factor calculated in 40 CFR 63.5810(a)(1) and the amount of neat resin plus and neat gel coat plus usage that correspond to the individual factors and divide the numerator by the total amount of neat resin plus and neat gel coat plus used in that operation type. Use the following equation to calculate your actual organic HAP emissions factor for each open molding operation type and each centrifugal casting operation type.

$$\text{Average organic HAP Emissions Factor} = \frac{\sum_{i=1}^n (\text{Actual Process Stream } EF_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 2})$$

Where:

Actual Process Stream EF_i = actual organic HAP emissions factor for process stream i , lbs/ton
 Material $_i$ = neat resin plus or neat gel coat plus used during the last 12 calendar months for process stream i , tons
 n = number of process streams where you calculated an organic HAP emissions factor

(3) Compare each organic HAP emissions factor calculated in paragraph (b)(2) of this section with its corresponding organic HAP emissions limit in Tables 3 or 5 to this subpart. If all emissions factors are equal to or less than their corresponding emission limits, then you are in compliance.

(b) *HAP Emission Factor averaging option.* Demonstrate each month that you meet each weighted average of the organic HAP emissions limits in Tables 3 or 5 to 40 CFR 63, Subpart WWWW that apply to you. When using this option, you must demonstrate compliance with the weighted average organic HAP emissions limit for all your open molding operations. The Permittee shall demonstrate compliance using the procedures specified in paragraphs (b)(1) – (3) of this section:

(1) Each month, calculate the weighted average organic HAP emissions limit for all open molding operations for your facility for the last 12-month period to determine the organic HAP emissions limit you must meet. To do this, multiply the individual organic HAP emissions limits in Tables 3 or 5 to this subpart for each open molding operation type by the amount of neat resin plus or neat gel coat plus used in the last 12 months for each open molding operation type, sum these results, and then divide this sum by the total amount of neat resin plus and neat gel coat plus used in open molding over the last 12 months. Use the following equation to calculate the weighted average organic HAP emissions limit for all open molding operations.

$$\text{Weighted Average Emission Limit} = \frac{\sum_{i=1}^n (EL_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 3})$$

Where:

EL_i = organic HAP emissions limit for operation type i , lbs/ ton from Tables 3, 5 or 7 to this subpart
 Material $_i$ =neat resin plus or neat gel coat plus used during the last 12-month period for operation type i , tons
 n = number of operations

(2) Each month, calculate your actual weighted average organic HAP emissions factor for open molding. To do this, multiply your actual open molding operation organic HAP emissions factors and the amount of neat resin plus and neat gel coat plus used in each open molding operation type, sum the results, and divide this sum by the total amount of neat resin plus and neat gel coat plus used in open molding operations. You must calculate your actual individual HAP emissions factors for each operation type as described in 40 CFR 63.5810(a)(1) and (2). Use the following equation to calculate your actual weighted average organic HAP emissions factor.

$$\text{Actual Weighted Average organic HAP Emissions Factor} = \frac{\sum_{i=1}^n (\text{Actual Operation } EF_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 4})$$

Where:

Actual Individual EF_i = Actual organic HAP emissions factor for operation type i , lbs/ton

Material_i = neat resin plus or neat gel coat plus used during the last 12 calendar months for operation type i , tons

n = number of operations

(3) Compare the values calculated in 40 CFR 63.5810(b)(1) and (2). If each 12-month rolling average organic HAP emissions factor is less than or equal to the corresponding 12-month rolling average organic HAP emissions limit, then you are in compliance.

(c) If you have multiple operation types, meet the organic HAP emission limits for one operation type, and use the same resin(s) for all operations of that resin type. If you have more than one operation type, you may meet the emission limit for one of those operations, and use the same resin(s) in all other open molding and centrifugal casting operations.

(1) This option is limited to resins of the same type. The resin types for which this option may be used are noncorrosion-resistant, corrosion-resistant and/or high strength, and tooling.

(2) For any combination of manual resin application, mechanical resin application, filament application, or centrifugal casting, you may elect to meet the organic HAP emissions limit for any one of these operations and use that operation's same resin in all of the resin operations listed in this paragraph. Table 7 to this subpart presents the possible combinations based on a facility selecting the application process that results in the highest allowable organic HAP content resin. If your resin organic HAP content is below the applicable values shown in Table 7 to this subpart, you are in compliance.

(3) You may also use a weighted average organic HAP content for each operation described in paragraph (c)(2) of this section to this subpart. Use equation 2 in 63.5810(a)(2) except substitute organic HAP content for organic HAP emission factors.

You are in compliance if the weighted average organic HAP content based on the last 12 months of resin use is less than or equal to the applicable organic HAP contents in Table 7 to this subpart.

(4) You may simultaneously use the averaging provisions in paragraph (b) to demonstrate compliance for any operations and/or resins you do not include in your compliance demonstrations under paragraphs (c)(2) and (3) of this section. However, any resins for which you claim compliance under the option in (c)(2) and (3) of this section may not be included in any of the averaging calculations described in paragraphs (a) or (b) of this section used for resins for which you are not claiming compliance under this option.

(d) Use resins and gel coats that do not exceed the maximum organic HAP contents shown in Table 3 to this subpart.

Continuous Compliance Requirements

§63.5895 How do I monitor and collect data to demonstrate continuous compliance?

(d) If you initially demonstrate that all resins and gel coats individually meet the applicable organic HAP emissions limits, or organic HAP content limits, then resin and gel coat use records are not required. However, you must include a statement in each compliance report that all resins and gel coats still meet the organic HAP limits for compliant resins and gel coats shown in Tables 3 or 7 of this subpart. If after this initial demonstration, you change to a higher organic HAP resin or gel coat, or increase the resin or gel coat organic HAP content, or change to a higher-emitting resin or gel coat application method, then you must either again demonstrate that all resins and gel coats still meet the applicable organic HAP emissions limits, or begin collecting resin and gel coat use records and calculate compliance on a 12-month rolling average.

Table 1 to Subpart WWWW of Part 63--Equations to Calculate Organic HAP Emissions Factors for Specific Open Molding and Centrifugal Casting Process Streams as required in Sec. 63.5796, 63.5799(a)(1) and (b), and 63.5810(a)(1), to calculate organic HAP emissions factors for specific open molding and centrifugal casting process streams you must use the equations in the following table:]

If your operation type is a new or existing ...	And you use ...	With ...	Use this organic HAP Emissions Factor (EF) Equation for materials with less than 33 percent organic HAP (19 percent organic HAP for nonatomized gel coat) ^{1 2 3} ...	Use this organic HAP Emissions Factor (EF) Equation for materials with 33 percent or more organic HAP (19 percent for nonatomized gel coat) ^{1 2 3} ...
1. Open molding operation	a. Manual resin application	i. Nonvapor-suppressed resin. ii. vapor-suppressed resin. iii. vacuum bagging/closed-mold curing with roll out. iv. vacuum bagging/closed-mold curing without roll out	$EF = 0.126 \times \%HAP \times 2000$ $EF = 0.126 \times \%HAP \times 2000 \times (1 - (0.5 \times VSE \text{ Factor}))$ $EF = 0.126 \times \%HAP \times 2000 \times 0.8$ $EF = (0.126 \times \%HAP \times 2000 \times 0.5)$	$EF = ((0.286 \times \%HAP) - 0.0529) \times 2000$ $EF = ((0.286 \times \%HAP) - 0.0529) \times 2000 \times (1 - (0.5 \times VSE \text{ Factor}))$ $EF = ((0.286 \times \%HAP) - 0.0529) \times 2000 \times 0.8$ $EF = ((0.286 \times \%HAP) - 0.0529) \times 2000 \times 0.5$
	c. nonatomized mechanical resin application	v. nonvapor-suppressed resin vi. vapor-suppressed resin vii. closed-mold curing with roll out	$EF = 0.107 \times \%HAP \times 2000$ $EF = 0.107 \times \%HAP \times 2000 \times (1 - (0.45 \times VSE \text{ Factor}))$ $EF = 0.107 \times \%HAP \times 2000 \times 0.85$	$EF = ((0.157 \times \%HAP) - 0.0165) \times 2000$ $EF = ((0.157 \times \%HAP) - 0.0165) \times 2000 \times (1 - (0.45 \times VSE \text{ Factor}))$ $EF = ((0.157 \times \%HAP) - 0.0165) \times 2000 \times$

		viii. vacuum bagging/closed-mold curing without roll out	$EF = (0.107 \times \%HAP \times 2000 \times 0.55)$	0.85 $EF = ((0.157 \times \%HAP) - 0.0165) \times 2000 \times 0.55$
	e. filament application ⁵	i. nonvapor-suppressed resin	$EF = 0.184 \times \%HAP \times 2000$	$EF = ((0.2746 \times \%HAP) - 0.0298) \times 2000$
		ii. vapor-suppressed resin	$EF = 0.12 \times \%HAP \times 2000$	$EF = ((0.2746 \times \%HAP) - 0.0298) \times 2000 \times 0.65$
	g. nonatomized spray gel coat application	nonvapor-suppressed gel coat	$EF = 0.185 \times \% HAP \times 2000$	$EF = ((0.4506 \times \%HAP)-0.0505) \times 2000$

Footnotes to Table 1

\1\ To obtain the organic HAP emissions factor value for an operation with an add-on control device multiply the EF above by the add-on control factor calculated using Equation 1 of Sec. 63.5810. The organic HAP emissions factors have units of lbs of organic HAP per ton of resin or gel coat applied.

\2\ Percent HAP means total weight percent of organic HAP (styrene, methyl methacrylate, and any other organic HAP) in the resin or gel coat prior to the addition of fillers, catalyst, and promoters. Input the percent HAP as a decimal, i.e. 33 percent HAP should be input as 0.33, not 33.

\3\ The VSE factor means the percent reduction in organic HAP emissions expressed as a decimal measured by the VSE test method of appendix A to this subpart.

\5\ Applies only to filament application using an open resin bath. If resin is applied manually or with a spray gun, use the appropriate manual or mechanical application organic HAP emissions factor equation.

Table 3 to Subpart WWWW of Part 63.--Organic HAP Emissions Limits for Existing Open Molding Sources, New Open Molding Sources Emitting Less Than 100 TPY of HAP, and New and Existing Centrifugal Casting and Continuous Lamination/Casting Sources that Emit Less Than 100 TPY of HAP As required in Sec. Sec. 63.5796, 63.5805 (a) through (c) and (g), 63.5810(a), (b), and (d), 63.5820(c), 63.5830, 63.5835(a), 63.5895(c) and (d), 63.5900(a)(2), and 63.5915(c), you must meet the appropriate organic HAP emissions limits in the following table:]

If your operation is ...	And you use ...	Your organic HAP emissions limit is¹ ...	And the highest organic HAP content for a compliant resin or gel coat is² ...
1. Open molding-corrosion-resistant and/or high strength (CR/HS)	a. mechanical resin application	112 lb/ton	46.2 with nonatomized resin application.
	b. filament application	171 lb/ton	42.0
	c. manual resin application	123 lb/ton	40.0
2. Open molding – non-CR/HS	a. mechanical resin application	87 lb/ton	38.4 with nonatomized resin application.
	b. filament application	188 lb/ton	45.0
	c. manual resin application	87 lb/ton	33.6
3. Open molding-tooling	a. mechanical resin application	254 lb/ton	43.0 with atomized application, 91.4 with nonatomized application.
	b. manual resin application	157 lb/ton	45.9
4. Open molding – low-flame spread/low-smoke products	a. mechanical resin application	497 lb/ton	60.0
	b. filament application	270 lb/ton	60.0
	c. manual resin application	238 lb/ton	60.0
5. Open molding – shrinkage controlled resins	a. mechanical resin application	354 lb/ton	50.0
	b. filament application	215 lb/ton	50.0

	c. manual resin application	180 lb/ton	50.0
6. Open molding-gel coat³	a. Tooling gel coating	437 lb/ton	40.0
	b. White/ off white pigmented gel coating	267 lb/ton	30.0
	c. all other pigmented gel coating	377 lb/ton	37.0
	d. CR/HS or high performance gel coat	605 lb/ton	48.0
	e. fire retardant gel coat	854 lb/ton	60.0
	f. clear production gel coat	522 lb/ton	44.0

Footnotes to Table 3

1 Organic HAP emissions limits for open molding and centrifugal casting are expressed as lb/ton. You must be at or below these values based on a 12-month rolling average.

2 A compliant resin or gel coat means that if its organic HAP content is used to calculate an organic HAP emissions factor, the factor calculated does not exceed the appropriate organic HAP emissions limit shown in the table.

3 These limits are for spray application of gel coat. Manual gel coat application must be included as part of spray gel coat application for compliance purposes using the same organic HAP emissions factor equation and organic HAP emissions limit. If you only apply gel coat with manual application, treat the manually applied gel coat as if it were applied with atomized spray for compliance determinations.

Table 7 to Subpart WWWW of Part 63.--Options Allowing Use of the Same Resin Across Different Operations That Use the Same Resin Type [As required in Sections. 63.5810(a) through (d), 63.5835(a), 63.5895(c), and 63.5900(a)(2), when electing to use the same resin(s) for multiple resin application methods you may use any resin(s) with an organic HAP contents less than or equal to the values shown in the following table, or any combination of resins whose weighted average organic HAP content based on a 12-month rolling average is less than or equal to the values shown the following table:]

If your facility has the following resin type and application method ...	The highest resin weight percent organic HAP content, or weighted average weight percent organic HAP content, you can use for . . .	Is . . .
2. CR/HS resins, nonatomized mechanical	a. CR/HS filament application	46.2
	b. CR/HS manual	46.2
5. Non-CR/HS resins, nonatomized mechanical	a. Non-CR/HS manual	38.4
	b. non-CR/HS centrifugal casting	38.4
7. Tooling resins, nonatomized mechanical	Tooling manual	91.4
8. Tooling resins, manual	Tooling atomized mechanical.	45.9

The requirements of 326 IAC 20-56 listed in this condition are not federally enforceable.

IDEM, OAQ Change 5: Condition D.1.13 has been added to include the Operator Training for Reinforced Plastic Composites Fabrication requirements under 326 IAC 20-56.

D.1.13 Operator Training for Reinforced Plastic Composites Fabrication [326 IAC 20-56-2]

Pursuant to 326 IAC 20-56-2, the Permittee shall comply with the following operator training requirements:

- (a) Each owner or operator shall train all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and applications that could result in excess emissions if performed improperly according to the following schedule:
 - (1) All personnel hired shall be trained within thirty (30) days of hiring.

- (2) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.
 - (3) Personnel who have been trained by another owner or operator subject to this rule are exempt from paragraph (1) if written documentation that the employee's training is current is provided to the new employer.
- (b) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:
- (1) Appropriate application techniques.
 - (2) Appropriate equipment cleaning procedures.
 - (3) Appropriate equipment setup and adjustment to minimize material usage and overspray.
- (c) The owner or operator shall maintain the following training records on site and make them available for inspection and review:
- (1) A copy of the current training program.
 - (2) A list of the following:
 - (A) All current personnel, by name, that are required to be trained.
 - (B) The date the person was trained or date of most recent refresher training, whichever is later.
- (d) Records of prior training programs and former personnel are not required to be maintained.

IDEM, OAQ Change 6: Upon further review, Condition D.1.16 (now renumbered as D.1.14) was modified to the one-time deadlines that apply to this source.

D.1.1416 One Time Deadlines Relating to NESHAP for Reinforced Plastic Composites Production [40 CFR Part 63, Subpart WWWW]

~~The Permittee must conduct the initial performance tests by April 21, 2007.~~

- (a) Pursuant to 40 CFR 63.5905, the Permittee must submit an Initial Notification by August 19, 2003.
- (b) The Permittee must submit a Notification of Compliance status report for source by May 21 20, 2007.

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Part 70 Operating Permit Renewal

Source Background and Description

Source Name:	Masterfab, Inc.
Source Location:	16618 Maple City Drive, Goshen, IN 46526
County:	Elkhart
SIC Code:	3089
Operation Permit No.:	T039-7117-00001
Operation Permit Issuance Date:	May 11, 2000
Permit Renewal No.:	T039-19842-00001
Permit Reviewer:	Ganesh Srinivasan/EVP

The Office of Air Quality (OAQ) has reviewed a Part 70 Operating Permit Renewal application from Masterfab, Inc. relating to the operation of a fiberglass parts manufacturing plant.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) One (1) gelcoat booth, constructed in 1990, using airless-air assisted application as a form of HVLP application, with a maximum capacity of 110 pounds per hour of gelcoat, using dry filters as control, and exhausting to stack 1.2(a) through 1.2(c) .
- (b) One (1) lamination booth, constructed in 1990, using non-atomized spray for application, with a maximum capacity of 414 pounds per hour of resin, using dry filters as control, and exhausting to stack 1.3(a) through 1.3(e).
- (c) Mold and pattern shop area, constructed in 1990, using non-atomized spray for resin application and airless or air assisted airless as a form of HVLP application for gelcoat with a maximum capacity of coating resin of 2.07 pounds per hour, and maximum capacity of coating gelcoat of 0.67 pounds per hour using dry filters for particulate control, and exhausting to stack 1.5.
- (d) Final finish & specialty products area, constructed in 1990, using non-atomized spray for application, with a maximum capacity of coating resin of 0.32 pounds per hour, and maximum capacity of coating gelcoat of 0.91 pounds per hour using dry filters for particulate control, no direct exhaust.
- (e) Mold preparation area with no direct exhaust.

Under NESHAP, Subpart WWWW, the gelcoat booth, lamination booth, mold and pattern shop area, final finish & specialty products area and mold preparation area, are considered an existing affected source because the construction of the source commenced prior to August 2, 2001 and the source is not reconstructed.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted emission units operating at this source during this review process.

Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million Btu per hour:
 - (1) Nineteen (19) natural gas fired radiant heaters with each one rated at 0.10 MMBtu per hour.
- (b) A gas fuel, other than gasoline, dispensing facility, having a storage capacity of less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.
- (c) Storage tanks with capacity less than or equal to 1,000 gallons and annual through puts less than 12,000 gallons.
- (d) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids.
- (e) Application of oils, greases, lubricants or other nonvolatile materials applied as temporary protective coatings.
- (f) Cleaners and solvents characterized as following:
 - (1) Having a vapor pressure equal to or less than 2 kPa; 15mm Hg; or 0.3 psi measures at 38 degrees C (100 F) or;
 - (2) Having a vapor pressure equal to of less than 0.7 kPa; 5mm Hg; or 0.1 psi measured as 20 C (68 f); the use of which for all cleaners and solvents combined does not exceed 145 gallons per 12 months.
- (g) The following equipment related to manufacturing activities not resulting in the emission of haps: brazing equipment, cutting torches, soldering equipment, welding equipment.
- (h) Any operation using aqueous solutions less than 1% by weight of VOCs excluding HAPs.
- (i) Water based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs.
- (j) Trimmers that do not produce fugitive emissions and that are equipped with a dust collector or trim material recovery device such as a bag filter or cyclone.
- (k) Paved and unpaved roads and parking lots with public access.
- (l) On-site fire and emergency response training approved by the department.
- (m) Emergency generators as follows:
 - 1) Gasoline generators not exceeding 110 horsepower.
 - 2) Diesel generators not exceeding 1600 horsepower.
- (n) Other emergency equipment like stationary fire pumps.
- (o) Grinding and machining operations controlled with fabric filters scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations.

- (1) One (1) grinding area, with a maximum capacity of 1104 pounds per hour, using bag filters for particulate control, and exhausting to stack 1.4(a) through stack 1.4(h). [326 IAC 6-3-2 (e)]
- (p) Mold release agents using low volatile products (vapor pressure less than or equal to kilopascals measured at 38 degrees C).

Existing Approvals

The source has constructed or has been operating under the following previous approvals:

- (a) Part 70 Permit No. 039-7117-00001, issued on May 11, 2000;
- (b) First Reopening No. 039-13258-00001, issued on January 29, 2002;
- (b) First Administrative Amendment No. 039-15645-00001, issued on April 1, 2002;
- (c) Second Administrative Amendment No. 039-18846-00001, issued on May 27, 2004; and
- (d) Third Administrative Amendment No. 039-19364-00001, issued on August 5, 2004.

All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the Part 70 permit be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete Part 70 permit renewal application for the purposes of this review was received on August 16, 2004. Additional information was received on June 20, 2005.

Emission Calculations

See Appendix A of this document for detailed emission calculations (pages 1 through 7 of Appendix A).

Potential to Emit of the Source

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA."

The source was issued a Part 70 Operating Permit on May 11, 2000. The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered enforceable only after issuance of the original Part 70 operating Permit and only to the extent that the effect of the control equipment is made practically enforceable in the permit.

Process/emission unit	Potential to Emit (tons/year)							
	PM	PM-10	SO ₂	VOC	CO	NO _x	HAPs	
							Single	Total
Fiberglass Processes Emissions	10.09	10.09	0.00	99.99	0.00	0.00	23.70	37.97
Mold Preparation Area	0.00	0.00	0.00	16.45	0.00	0.00	16.45*	16.45*
Insignificant Activities (Grinding and Natural Gas Combustion Emissions)	0.02	0.06	0.00	0.05	0.70	0.83	0.014	0.02
Total PTE	10.11	10.15	0.00	116.49	0.70	0.83	23.70	37.99

Note: * It is assumed that VOC is equal to HAP as a worst case scenario.

- (a) The potential to emit (as defined in 326 IAC 2-7-1(29)) of volatile organic compounds (VOC) is equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) The potential to emit (as defined in 326 IAC 2-7-1(29)) of any single HAP is equal to or greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination of HAPs is equal to or greater than twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (c) Fugitive Emissions
 Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are not counted toward determination of PSD and Emission Offset applicability.

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the 2003 OAQ emission data.

Pollutant	Actual Emissions (tons/year)
PM	No Data
PM-10	0.00
SO ₂	No Data
VOC	58.00
CO	No Data
NO _x	No Data
HAP (specify)	No Data

County Attainment Status

The source is located in Elkhart County.

Pollutant	Status
PM2.5	Attainment
PM-10	Attainment
SO ₂	Attainment
NO ₂	Attainment
1-hour Ozone	Attainment
8-hour Ozone	Basic Nonattainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and Nitrogen Oxides (NOx) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NOx emissions are considered when evaluating the rule applicability relating to the ozone standards. Elkhart County has been designated as nonattainment for the 8-hour ozone standard. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for Emission Offset, 326 IAC 2-3. See the State Rule Applicability for the source section.
- (b) Elkhart County has been classified as unclassifiable or attainment for PM2.5. U.S. EPA has not yet established the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 for PM 2.5 emissions. Therefore, until the U.S.EPA adopts specific provisions for PSD review for PM2.5 emissions, it has directed states to regulate PM10 emissions as surrogate for PM2.5 emissions. See the State Rule Applicability for the source section.
- (c) Elkhart County has been classified as attainment or unclassifiable in Indiana for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2. See the State Rule Applicability for the source section.

Part 70 Permit Conditions

This source is subject to the requirements of 326 IAC 2-7, pursuant to which the source has to meet the following:

- (a) Emission limitations and standards, including those operational requirements and limitations that assure compliance with all applicable requirements at the time of issuance of Part 70 permits.
- (b) Monitoring and related record keeping requirements which assure that all reasonable information is provided to evaluate continuous compliance with the applicable requirements.

Federal Rule Applicability

- (a) This Part 70 source is not subject to the provisions of 40 CFR 64, Compliance Assurance Monitoring. In order for this rule to apply, a pollutant specific emissions unit as defined in 40 CFR 64.1 must meet the following three criteria for a given pollutant:

- (1) The unit has the potential to emit, of the applicable regulated air pollutant, equal or greater than 100 percent of the amount required for a source to be classified as a major source;
- (2) The unit is subject to an emission limitation or standard for the applicable regulated air pollutant; and
- (3) The unit uses a control device to achieve compliance with any such emission limitation or standard.

The pollutant-specific emission units at this source are related to Fiberglass Processes and are not subject to the requirements of 40 CFR 64, because each related unit is subject to the MACT standards of 40 CFR 63, and pursuant to 40 CFR 64.2(b)(1)(i), these units are exempt from the requirements of 40 CFR 64.

No other unit for the source has the potential to emit, of the applicable regulated air pollutant, equal or greater than 100 percent of the amount required for a source to be classified as a major source. Therefore, this source is not subject to the requirements of 40 CFR 64.

- (b) There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) included in this permit.
- (c) This source performs reinforced plastic composites production and is a major source of Hazardous Air Pollutants (HAPs). Therefore, this source is subject to the National Emissions Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production, 40 CFR 63.5780, Subpart WWWW. Construction of this source commenced prior to August 2, 2001. Therefore, this is an existing affected source.

On August 25, 2005, US EPA issued revisions to 40 CFR 63, Subpart WWWW as published in the Federal Register of August 25, 2005. The following conditions applicable to the source were revised:

- (1) 40 CFR 63.5805 (b)
- (2) 40 CFR 63.5810 (a) (b) and (d)
- (3) 40 CFR 63.5895 (d)
- (4) 40 CFR 63.5900(a) (2) (3)
- (5) 40 CFR 63.5935

Under NESHAP, Subpart WWWW, the gelcoat booth, lamination booth, mold and pattern shop area, final finish & specialty products area and mold preparation area, are considered an existing affected source because the construction of the source commenced prior to August 2, 2001 and the source is not reconstructed.

Pursuant to 40 CFR 63.5800, the Permittee shall comply with the requirements of 40 CFR 63, Subpart WWWW by April 21, 2006.

Non applicable portions of the NESHAP will not be included in the permit. This source is subject to the following portions of Subpart WWWW.

- (a) 40 CFR 63.5785(a)
- (b) 40 CFR 63.5790
- (c) 40 CFR 63.5795
- (d) 40 CFR 63.5796
- (e) 40 CFR 63.5797
- (f) 40 CFR 63.5798
- (g) 40 CFR 63.5799
- (h) 40 CFR 63.5800
- (i) 40 CFR 63.5805 (b)
- (j) 40 CFR 63.5810 (a) (b) and (d)
- (k) 40 CFR 63.5835(a) and (c)
- (l) 40 CFR 63.5840
- (m) 40 CFR 63.5860(a)
- (n) 40 CFR 63.5895(b) (c) and (d)
- (o) 40 CFR 63.5900(a) (2) (3) (4), (b), (c) and (e)
- (p) 40 CFR 63.5905
- (q) 40 CFR 63.5910(a), (b), (c), (d), (e), (g) and (h)
- (r) 40 CFR 63.5915(a), (c) and (d)
- (s) 40 CFR 63.5920
- (t) 40 CFR 63.5925
- (u) 40 CFR 63.5930
- (v) 40 CFR 63.5935

The provisions of 40 CFR 63 Subpart A – General Provisions, which are incorporated as 326 IAC 20-1-1, apply to the facility described in this section except when otherwise specified in 40 CFR 63 Subpart WWWW.

- (d) This source is not subject to the National Emission Standards for Hazardous Air Pollutants, 40 CFR 63.4480, Subpart PPPP because the source does not perform surface coating operations at the facility. The source uses open molding for fiberglass production. Therefore, the requirements of National Emission Standards for Hazardous Air Pollutants for Plastic Parts and Products, (40 CFR 63.4480, Subpart PPPP) are not included in the permit.

State Rule Applicability – Entire Source

326 IAC 2-2 (Prevention of Significant Deterioration)

This source is not subject to 326 IAC 2-2 (PSD). This rule applies to sources, which are not one of the 28 source categories, with potential emissions of any criteria pollutant greater than or equal to 250 tons per year. The source was constructed in 1990; after the 326 IAC 2-2 applicability date of August 7, 1977, and is not one of the 28 source categories. Pursuant to T039-7117-00001, issued on May 11, 2000, the source agreed to limit its VOC emissions from the fiberglass coating operations to less than 100 tpy to satisfy the 326 IAC 8-1-6 (BACT) requirements. The source has always limited source-wide VOC emissions to less than 250 tons per year since it started the operation and will continue to limit coating and solvent usage in the gelcoat booth, lamination booth, mold and pattern shop area, and final finish & specialty products area as described under 326 IAC 8-1-6 such that associated VOC emissions are limited to less than 100 tons per year. Therefore, the requirements of 326 IAC 2-2 do not apply.

326 IAC 2-3 (Emission Offset)

On April 15, 2004, the United States Environmental Protection Agency (U.S. EPA) named 23 Indiana counties and one partial county nonattainment for the new 8-hour ozone standard. The designations became effective on June 15, 2004. Elkhart County has been designated as nonattainment for the 8-hour ozone standard. Currently, the source wide potential to emit of NO_x and VOC is 0.83 and 116.49 (including the mold preparation area and insignificant activities) tons per year, respectively. The source did not have any new constructions or modification after April 15, 2005. Therefore, the requirements of Emissions Offset 326 IAC 2-3 do not apply; however, the source is classified as major for the purpose of Emissions Offset.

326 IAC 1-6-3 (Preventive Maintenance Plan)

The source has submitted a Preventive Maintenance Plan (PMP) on December 30, 1996. This PMP has been verified to fulfill the requirements of 326 IAC 1-6-3 (Preventive Maintenance Plan).

326 IAC 1-5-2 (Emergency Reduction Plans)

The source has submitted an Emergency Reduction Plan (ERP) on December 30, 1996. The ERP has been verified to fulfill the requirements of 326 IAC 1-5-2 (Emergency Reduction Plans).

326 IAC 2-6 (Emission Reporting)

Since this source is required to have an operating permit under 326 IAC 2-7, Part 70 Permit Program, this source is subject to 326 IAC 2-6 (Emission Reporting). In accordance with the compliance schedule in 326 IAC 2-6-3, an emission statement must be submitted triennially by July 1 beginning in 2007 and every 3 years after. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 2-4.1 (New Source Toxics Control)

Pursuant to 326 IAC 2-4.1 (New Source Toxics Control), any new process or production unit, which in and of itself emits or has the potential to emit (PTE) 10 tons per year of any HAP or 25 tons per year of any combination of HAPs, must be controlled using technologies consistent with Maximum Achievable Control Technology (MACT). This source is subject to the National Emissions Standards for Hazardous Air Pollutants 40 CFR Part 63, Subpart WWWW. Compliance with 40 CFR Part 63, Subpart WWWW, as an applicable standard issued pursuant to Section 112(d) of the Clean Air Act, makes the requirements of 326 IAC 2-4.1 not applicable.

326 IAC 8-6 (Organic Solvent Emission Limitations)

This rule applies to sources commencing operation after October 7, 1974 and prior to January 1, 1980, located anywhere in the state, with potential solvent VOC emissions of 100 tons per year or more, and not regulated by any other provision of Article 8. This source was constructed after January 1, 1980. Therefore, this rule does not apply to this source.

326 IAC 20-25-3 (Emissions Standards for Reinforced Plastics Composites Fabricating)

This source is subject to the requirements of 326 IAC 20-25-3 because it is a major source of HAPs with the potential to emit of any single hazardous air pollutant (HAP) and any combination of HAPs being greater than ten (10) tons per year and twenty-five (25) tons per year, respectively, and meets all of the following criteria:

- (a) Manufacture reinforced plastics composites parts, products, or watercrafts;
- (b) Have an emission unit where resins and gel coats that contain styrene are applied and cure using open molding process;
- (c) Have actual emissions of styrene equal or greater than three (3) tons per year.

Pursuant to 326 IAC 20-25-1(d), since this source is subject to 326 IAC 20-56, concerning emission standards for hazardous air pollutants from reinforced plastic composites production, it is exempt from this rule after April 21, 2006, because it is a major source that existed on or before August 2, 2001. The Permittee shall comply with the provisions of the rule until April 21, 2006 including:

- (a) The total HAP monomer content of the following materials shall be limited based on the application method used and the products produced as specified in the following table:

<i>Fiber Reinforced Plastics Composites Products Except Watercraft</i>	HAP Monomer Content, Weight Percent
<i>Resin, Manual or Mechanical Application</i>	
Production-Specialty Products	48*
Production-Noncorrosion Resistant Unfilled	35*
Production-Noncorrosion Resistant Filled (35% by weight)	38
Production, Noncorrosion Resistant, Applied to Thermoformed Thermoplastic Sheet	42
Production, Class I, Flame and Smoke	60*
Shrinkage Controlled	52
Tooling	43
<i>Gel Coat Application</i>	

Production-Pigmented	37
Clear Production	44
Tooling	45
Production-Pigmented, subject to ANSI ^a standards	45
Production-Clear, subject to ANSI ^a standards	50

^aAmerican National Standards Institute.

* Categories that must use mechanical nonatomized application technology or manual application as stated in subsection (c).

Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis. If all of the resins and gel coats used during a month meet the specified HAP monomer content limits, then maintaining records of content and usage is sufficient for demonstrating compliance with the HAP monomer content limits.

Compliance with the limitations contained in this condition may be demonstrated using monthly emission averaging within each resin or gel coat application category listed in subsection(b) by the use of resins or gel coats with HAP monomer contents lower than the limits specified, and/or additional emission reduction techniques approved by IDEM, OAQ.

Examples of emission reduction techniques include, but are not limited to, using nonatomized application to apply resins or gelcoats within a category that does not require nonatomized application, lower monomer content resins and gel coats, vapor suppression, vacuum bagging, controlled spraying, or installing a control device. This is allowed to meet the HAP monomer content limits for resins and gel coats within each category, and shall be calculated on an equivalent emissions mass basis monthly to demonstrate compliance as shown below:

For Averaging within a category:

$$\sum Em_A \leq \sum (M_R * E_a)$$

Where:

M_R = Total monthly mass of material within each category

E_a = Emission factor for each material based on allowable monomer content and allowable application method for each category.

Em_A = Actual monthly emissions from all materials used within a category based on material specific emission factors, emission reduction techniques and emission controls

Units: mass = tons

emission factor = lbs of monomer per ton of resin or gel coat

emissions = lbs of monomer

Note: Fillers may not be included when averaging.

(b) The following categories of materials in subsection (a) shall be applied using mechanical nonatomized application technology or manual application:

- (1) Production noncorrosion resistant, unfilled resins from all sources.
- (2) Production, specialty product resins from all sources.

- (3) Tooling resins used in the manufacture of watercraft.
- (4) Production resin used for Class I flame and smoke products.

Nonatomized application equipment means the devices where resin or gel coat material does any of the following:

- (1) Flows from the applicator, in a steady state in a observable coherent flow, without droplets, for a minimum distance of three (3) inches from the applicator orifices such as flow coaters, flow choppers, and fluid impingement equipment.
- (2) Is mechanically dispensed within or on to a paint roller applicator such as pressure fed rollers.
- (3) Is deposited on fiber reinforcement moving through a resin or gel coat bath such as resin impregnators.

Nonatomized spray application technology includes flow coaters, flow choppers, pressure-fed rollers, fluid impingement, or other non-spray applications of a design and specifications approved by IDEM, OAQ.

Filled resins are resins containing greater than or equal to thirty-five percent (35%) by weight inert filler material, such as silica micro-spheres or micro-balloons, added to alter the density or other physical properties of the resin. The term "inert filler" does not include pigments.

- (c) Unless specified in subsection (b), gel coat application and mechanical application of resins shall be by any of the following spray technologies:
 - (1) Nonatomized application technology.
 - (2) Air-assisted airless.
 - (3) Airless.
 - (4) High volume, low pressure (HVLP).
 - (5) Equivalent emission reduction technologies to subdivisions (2) through (4).
- (d) The following cleaning operation standards for resin and gel coat application equipment shall apply:
 - (1) For routine flushing of resin and gel coat application equipment such as spray guns, flow coaters, brushes, rollers, and squeegees, a cleaning solvent shall contain no HAPs. This emission standard does not apply to solvents used for removing cured resin or gel coat from application equipment.
 - (2) A source must store HAP containing solvents used for removing cured resin or gel coat in containers with covers. The covers must have no visible gaps and must be in place at all times, except when equipment is placed in or removed from the container.
 - (3) Recycled cleaning solvents that contain less than or equal to five percent (5%) HAP by weight are considered to contain no HAP for the purposes of this subsection.

326 IAC 20-56 (Reinforced Plastic Composites Production)

This rule applies to sources as provided in 40 CFR 63.5785, Subpart WWWW. The requirements of 40 CFR 63.5780, Subpart WWWW are included in Section D.15 of the permit. See the Federal Rule Applicability for the applicable requirements.

On August 25, 2005, US EPA issued revisions to 40 CFR 63, Subpart WWWW as published in the Federal Register of August 25, 2005. The revisions to the NESHAP have not yet been approved into the Indiana State Implementation Plan (SIP). Hence, in order to be in compliance with this rule, the source has to comply with the version of 40 CFR 63, Subpart WWWW that existed prior to the revised rule published in the Federal Register on August 25, 2005. Therefore, condition D.1.16 has been added to the Title V permit and includes only the sections of the previous version of Subpart WWWW that were revised on August 25, 2005.

Pursuant to 326 IAC 20-56-2, the Permittee shall comply with the following operator training requirements:

- (a) Each owner or operator shall train all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and applications that could result in excess emissions if performed improperly according to the following schedule:
 - (1) All personnel hired shall be trained within thirty (30) days of hiring.
 - (2) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.
 - (3) Personnel who have been trained by another owner or operator subject to this rule are exempt from paragraph (1) if written documentation that the employee's training is current is provided to the new employer.
- (b) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:
 - (1) Appropriate application techniques.
 - (2) Appropriate equipment cleaning procedures.
 - (3) Appropriate equipment setup and adjustment to minimize material usage and overspray.
- (c) The owner or operator shall maintain the following training records on site and make them available for inspection and review:
 - (1) A copy of the current training program.
 - (2) A list of the following:
 - (A) All current personnel, by name, that are required to be trained.
 - (B) The date the person was trained or date of most recent refresher training, whichever is later.
- (d) Records of prior training programs and former personnel are not required to be maintained.

326 IAC 20-25-4 (Work Practice Standards for Reinforced Plastic Composites Fabrication)

On and before April 21, 2006, pursuant to 326 IAC 20-25-4, the following work practice standards shall be implemented:

- (a) Non-atomizing spray equipment shall not be operated at pressures that atomize the material during the application process.
- (b) Except for mixing containers as described in item (g), HAP containing materials shall be kept in a closed container when not in use.
- (c) Solvents sprayed during cleanup and resin changes shall be directed into solvent collection containers.

- (d) Solvent collection containers shall be kept closed when not in use.
- (e) Clean-up rags with solvent shall be stored in closed containers.
- (f) Closed containers shall be used for the storage of the following:
 - (1) All production and tooling resins that contain HAPs.
 - (2) All production and tooling gel coats that contain HAPs.
 - (3) Waste resins and gel coats that contain HAPs.
 - (4) Cleaning materials, including waste cleaning materials.
 - (5) Other materials that contain HAPs.
- (g) All resin and gel coat mixing containers with a capacity equal to or greater than fifty-five (55) gallons must have a cover with no visible gaps in place at all times except when material is being added to or removed from a container, or when mixing or pumping equipment is being placed in or removed from a container.

326 IAC 20-25-8 (Operator Training for Reinforced Plastic Composites Fabrication)

On and before April 21, 2006, pursuant to 326 IAC 20-25-8, all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and spray-like applications (for example, those applications that could result in excess emissions if performed improperly) shall be trained according to the following schedule:

- (a) All personnel hired after March 7, 2001 shall be trained within fifteen (15) days of hiring.
- (b) All personnel hired before March 7, 2001 shall be trained or evaluated by a supervisor within thirty (30) days of the start of operation.
- (c) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.
- (d) Personnel who have been trained by another owner or operator subject to 326 IAC 20-25 are exempt from subdivision (a) if written documentation that the employee's training is current is provided to the new employer.
- (e) If the result of an evaluation shows that training is needed, such training shall occur within fifteen (15) days of the evaluation.
- (f) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:
 - (1) Appropriate application techniques.
 - (2) Appropriate equipment cleaning procedures.
 - (3) Appropriate equipment setup and adjustment to minimize material usage and overspray.
- (g) The owner or operator shall maintain the following training records on site and available for inspection and review:

- (1) A copy of the current training program.
- (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training. Records of prior training programs and former personnel are not required to be maintained.

State Rule Applicability – Individual Facilities

326 IAC 6-3-2 (e) (Particulate Emissions Limitations for manufacturing Process)

- (a) Pursuant to 326 IAC 6-3-2(e), the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour (please see page 6 of Appendix A for calculations). This includes the following equipment listed under insignificant activities (each is limited to particulate emissions of 0.551 pounds per hour):
 - (1) One (1) grinding area, with a maximum capacity of 1104 pounds per hour, using bag filters for particulate control, and exhausting to stack 1.4(a) through stack 1.4(h).
- (b) Pursuant to 326 IAC 6-3-1(b)(9), the welding operations listed under insignificant activities as “the following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment” are exempt from the requirements of 326 IAC 6-3-2, because each welding operation consumes less than 625 pounds of rod or wire per day.
- (c) Pursuant to 326 IAC 6-3-1(b)(14), trimming operations listed under insignificant activities as “Trimmers that do not produce fugitive emissions and that are equipped with a dust collector or trim material recovery device such as a bag filter or cyclone” are exempt from the requirements of 326 IAC 6-3-2, because their potential emissions are less than 0.551 pounds per hour.

326 IAC 8-1-6 (Volatile Organic Compounds (VOC) and Best Available Control Technology (BACT)) Pursuant to 326 IAC 8-1-6 (General Provisions relating VOC rules: general reduction requirements for new facilities), this facility shall reduce the VOC emissions using best available control technology (BACT). The fiberglass production line comprises of one (1) gelcoat booth, one (1) lamination booth, Mold and pattern shop area, and Final finish & specialty products area. All the above listed units were constructed after 1980, therefore rule 326 IAC 8-1-6 is applicable to these facilities. The Mold preparation area is exempt from the BACT requirements since the potential VOC emissions are less than 25 tons per year. Pursuant to OP 20-10-93-0693 issued on June 18, 1990, the source shall comply with the following BACT determined for the fiberglass production line:

- (a) Use of resins, gel coats and solvents shall be limited such that the potential to emit (PTE) volatile organic compounds from resins, gel coats and solvents only shall be limited to less than or equal to 100 tons per twelve (12) consecutive months. Compliance with this limit shall be determined based upon the following criteria:
 - (1) Monthly usage by weight, monomer content, method of application, and other emission reduction techniques for each gel coat and resin shall be recorded. VOC emissions shall be calculated by multiplying the usage of each gel coat and resin by the emission factor that is appropriate for the monomer content, method of application, and other emission reduction techniques for each gel coating and resin, and summing the emissions for all gel coats and resins. Emission factors shall be obtained from the reference approved by IDEM, OAQ.

- (2) Until Such time that new emissions information is available by U.S. EPA in its AP-42 document or other U.S. EPA-approved form, emission factors shall be taken from the following reference approved by IDEM, OAQ: CFA Unified Emissions Factors for Open Molding of Composites July 23, 2001, and shall not exceed 32.3% styrene emitter per weight of gel coat applied and 17.7% styrene emitted per weight of resin applied. For the purposes of these emission calculations, monomer in resins and gel coats that is not styrene shall be considered as styrene on an equivalent basis.
- (3) Monthly usage by weight and VOC content of each solvent shall be recorded.
- (b) Lower Styrene resins less than 42%.
- (c) Use higher transfer efficiency guns.
- (d) Improved housekeeping.

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

1. The one (1) gelcoat booth, one (1) lamination booth, Mold and pattern shop area, and Final finish & specialty products area, have applicable compliance monitoring conditions as specified below:
 - (a) Daily inspections shall be performed to verify that the water level of the water spray meet the manufacturer's recommended level. To monitor the performance of the water spray, the water level of the pans shall be maintained weekly at a level where surface agitation indicates impact of the air flow. Water shall be kept free of solids and floating material that reduces the capture efficiency of the water spray. To monitor the performance of the baffles, weekly inspections of the baffle panels shall be conducted to verify placement and configuration meet recommendations of the manufacturer. In addition, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to

take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

- (b) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances
- (c) Weekly visible emission notations of the fiberglass facilities' stack exhaust shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (d) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (e) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (f) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.

These monitoring conditions are necessary to ensure compliance with 326 IAC 6-3-2 (Particulate Emissions Limitations for Manufacturing Process) and 326 IAC 2-7 (Part 70).

Conclusion

The operation of this fiberglass coating plant shall be subject to the conditions of this Part 70 permit **T039-19842-00001**.

Appendix A: Emissions Calculations

Summary of Emissions Calculations

Company Name: Masterfab, Inc.
Address City IN Zip: 16618 Maple City Drive, Goshen, Indiana 46526
Permit Number: T039-19842-00001
Reviewer: GSN/EVP
Date: 01/10/06

Uncontrolled Potential Emissions (tons/year)				
Emissions Generating Activity				
Pollutant	Fiberglass Processes Emissions	Mold Preparation Area	Natural Gas Combustion & Grinding Insignificant	TOTAL
PM	631.76	0.00	4.53	636.29
PM10	631.76	0.00	4.57	636.33
SO2	0.00	0.00	0.00	0.00
NOx	0.00	0.00	0.83	0.83
VOC	331.89	16.45	0.05	348.39
CO	0.00	0.00	0.70	0.70
total HAPs	118.85	0.00	0.02	118.87
worst case single HAP	74.16 (Styrene)	0.00	0.014 (Hexane)	74.16 (Styrene)
Total emissions based on rated capacity at 8,760 hours/year.				
Controlled Potential Emissions (tons/year)				
Emissions Generating Activity				
Pollutant	Fiberglass Processes Emissions	Mold Preparation Area	Natural Gas Combustion & Grinding Insignificant	TOTAL
PM	10.09	0.00	0.02	10.11
PM10	10.09	0.00	0.06	10.15
SO2	0.00	0.00	0.00	0.00
NOx	0.00	0.00	0.83	0.83
VOC	99.99	16.45	0.05	116.49
CO	0.00	0.00	0.70	0.70
total HAPs	37.97	0.00	0.02	37.99
worst case single HAP	23.70 (Styrene)	0.00	0.014 (Hexane)	23.70 (Styrene)
Total emissions based on rated capacity at 8,760 hours/year, after control.				

Appendix A: Emissions Calculations
VOC and Particulate
From Gel and Resin Coating Operations
Reinforced Plastics and Composites Fiberglass Processes

Company Name: Masterfab, Inc.
 Address City IN Zip: 16618 Maple City Drive, Goshen, Indiana 46526
 Permit Number: T039-19842-00001
 Reviewer: GSN/EVP
 Date: 01/10/06

Gel Coat											
Material/Unit ID	Density (Lb/Gal)	Weight % Styrene Monomer or VOC	Pounds of Mat. (lb/unit)	Maximum (unit/hour)	Ton Processed per hour	CFA Unified Emission Factor (lb/ton) *	Potential VOC pounds per hour	Potential Pounds of VOC per day	Potential VOC tons per year	Particulate Potential (ton/yr)	Transfer Efficiency ⁽²⁾
Hyline Grey Gelcoat * (Styrene)	9.17	34.42%	15.000	8.33	0.06248	214.0	13.37	106.96	58.56	348.10	89%
Hyline Grey Gelcoat * (MMA)	9.17	2.55%	15.000	8.33	0.06248	45.0	2.81	22.49	12.31	0.00	89%
DDM 9 (Catalyst)	9.04	97.70%	1.200	8.33	0.00500	N/A	9.77	78.13	42.78	1.00	89%

Gelcoat is applied using non-atomized technology.

* Above information depicts the worst case scenario as the gelcoat material and part size varies from product to product.

Resin											
Material/Unit ID	Density (Lb/Gal)	Weight % Styrene Monomer or VOC	Pounds of Mat. (lb/unit)	Maximum (unit/hour)	Ton Processed per hour	CFA Unified Emission Factor (lb/ton) *	Potential VOC pounds per hour	Potential Pounds of VOC per day	Potential VOC tons per year	Particulate Potential (ton/yr)	Transfer Efficiency
H8354V *	9.13	36.92%	65.000	8.33	0.27073	83.0	22.47	179.76	98.42	273.16	98%
DDm 9 (Catalyst)	9.04	97.70%	1.200	8.33	0.00500	N/A	9.77	78.13	42.78	0.18	98%

Resin is applied using non-atomized technology.

* Above information depicts the worst case scenario as the gelcoat material and part size varies from product to product.

Mold and Pattern Shop Area											
Material/Unit ID	Density (Lb/Gal)	Weight % Styrene Monomer or VOC	Material Usage (gal/hr)	Ton Processed per hour	CFA Unified Emission Factor (lb/ton)	Potential VOC pounds per hour	Potential Pounds of VOC per day	Potential VOC tons per year	Particulate Potential (ton/yr)	Transfer Efficiency	
Gelcoat	10.0	37.00%	0.020	0.00010	232.00	0.02	0.19	0.82	0.06	89%	
E8234V (Resin)	9.03	37.20%	0.556	0.00251	83.0	0.21	1.67	7.30	0.28	98%	
Polycor Grey (Tooling gel) [Styrene]	9.24	34.56%	0.556	0.00257	214.0	0.55	4.40	19.26	1.62	89%	
Polycor Grey (Tooling gel) [MMA]	9.24	4.48%	1.556	0.00719	67.5	0.49	3.88	17.00	6.62	89%	
E704-FD (Tooling Resin)	9.12	60.00%	0.223	0.00102	155.4	0.16	1.26	5.54	0.07	98%	
Doeskin (Resin) [Styrene]	10.92	24.10%	0.003	0.00001	51.6	0.00	0.01	0.02	0.00	98%	
Doeskin (Resin) [MMA]	10.92	9.00%	0.003	0.00002	135.0	0.00	0.02	0.08	0.00	98%	
Polycor Orange (Tooling gel)	9.01	43.00%	0.060	0.00027	287.0	0.08	0.62	2.72	0.15	89%	
Polycor Orange (Tooling gel)	9.01	4.74%	0.060	0.00027	75.0	0.02	0.16	0.71	0.25	89%	
Polycor Black (Tooling gel)	10.01	36.00%	0.060	0.00030	223.0	0.07	0.54	2.35	0.19	89%	
DDM 9 (Catalyst)	9.04	76.00%	0.005	0.00002	N/A	0.03	0.28	1.22	0.01	89%	
DDM 30 (Catalyst)	8.60	48.00%	0.005	0.00002	N/A	0.02	0.17	0.72	0.01	89%	

Final Finish & Specialty Products Area											
Material/Unit ID	Density (Lb/Gal)	Weight % Styrene Monomer or VOC	Material Usage (gal/hr)	Ton Processed per hour	CFA Unified Emission Factor (lb/ton)	Potential VOC pounds per hour	Potential Pounds of VOC per day	Potential VOC tons per year	Particulate Potential (ton/yr)	Transfer Efficiency	
Gelcoat	8.20	37.00%	0.020	0.00008	232.0	0.02	0.15	0.08	0.05	89%	
Resin	9.08	37.20%	0.020	0.00009	83.0	0.01	0.06	0.27	0.01	98%	

Total Potential Emissions						59.86	478.86	312.93	631.76	
Material Usage Limitations								31.95%	31.95%	
Control Efficiency								0.00%	95.00%	
Controlled Total Potential Emissions								99.98	10.09	

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)
 Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)
 Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)
 Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)
 Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)
 Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1-Weight % Volatiles) * (1-Transfer efficiency) * (8760 hrs/yr) * (1 ton/2000 lbs)
 Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)
 Total = Worst Coating + Sum of all solvents used

NOTES

Emission factors are based on Composite Fabricators Association (CFA) Unified Emission Factors.
 Coating operations are mutually exclusive, therefore worst case emissions are to determine the total potential emission

**Appendix A: Emission Calculations
Miscellaneous VOC Emissions**

Company Name: Masterfab, Inc.
Address City IN Zip: 16618 Maple City Drive, Goshen, Indiana 46526
Permit No.: T039-19842-00001
Reviewer: GSN/EVP
Date: 01/10/06

Miscellaneous VOC Emissions from Mold and Pattern Shop Area *

Material	Density (lb/gal)	Maximum Usage (gal/hr)	Weight Percent VOC (%)	Potential emission rate (TPY)
TR # 307	10.25	0.0202	50.00%	0.453
Evercoat	10.00	0.0202	14.36%	0.127
Styrene Monomer	9.10	0.0024	99.80%	0.096
TF100	9.00	0.0008	88.00%	0.027
MEK	7.00	0.0010	100.00%	0.030
3M Finess	8.30	0.0126	90.00%	0.412
DBF	13.00	0.0202	18.00%	0.207
			Total VOC/HAP ⁽¹⁾	1.353

* Few materials are not listed above as the emissions are negligible (less than 0.01 ton per year)

Miscellaneous VOC Emissions from Final Finish and Specialty Products Area **

Material	Density (lb/gal)	Maximum Usage (gal/hr)	Weight Percent VOC (%)	Potential emission rate (TPY)
Patch Booster	8.20	0.0101	69.86%	0.253
DBF	13.00	0.0505	18.00%	0.518
P2843	10.10	0.0101	44.05%	0.197
Paste	8.20	0.0101	50.75%	0.184
			Total VOC/HAP ⁽¹⁾	1.152

** Few materials are not listed above as the emissions are negligible (less than 0.01 ton per year)

Miscellaneous VOC Emissions from Mold Prep Area

Material	Average Density (lb/gal)	Combined Maximum Usage (gal/hr)	Weight Percent VOC (%) ***	Potential emission rate (TPY)
Different Materials	8.65	0.4343	100.00%	16.454
			Total VOC/HAP ⁽¹⁾	16.454

*** Assuming worst case emissions (100% VOC content)

(1) It is assumed that VOC is equal to HAP as a worst case scenario as the HAP content of materials is not available.

**Appendix A: Emissions Calculations
Natural Gas Combustion Only
MM BTU/HR <100**

Company Name: Masterfab, Inc.
Address City IN Zip: 16618 Maple City Drive, Goshen, Indiana 46526
Permit Number: T039-19842-00001
Reviewer: GSN/EVP
Date: 01/10/06

Heat Input Capacity
MMBtu/hr
1.9

Potential Throughput
MMCF/yr
16.6

Facilities	MMBtu/hr
Nineteen (19) natural gas fired radiant heater with each one rated at 0.10 MMBtu/hr.	1.9
Total	1.9

	Pollutant					
	PM*	PM10*	SO2	NOx	VOC	CO
Emission Factor in lb/MMCF	1.9	7.6	0.6	100.0 **see below	5.5	84.0
Potential Emission in tons/yr	0.02	0.06	0.00	0.83	0.05	0.70

*PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

**Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03

(SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

Note: Check the applicable rules and test methods for PM and PM10 when using the above emission factors to confirm that the correct factor is used (i.e., condensable included/not included).

**Appendix A: Emissions Calculations
 Natural Gas Combustion Only
 MM Btu/hr 0.3 - < 100**

HAPs Emissions

Company Name: Masterfab, Inc.
Address City IN Zip: 16618 Maple City Drive, Goshen, Indiana 46526
Permit Number: T039-19842-00001
Reviewer: GSN/EVP
Date: 01/10/06

HAPs - Organics

	Benzene	Dichlorobenzene	Formaldehyde	Hexane	Toluene
Emission Factor in lb/MMcf	2.1E-03	1.2E-03	7.5E-02	1.8E+00	3.4E-03
Potential Emission in tons/yr	1.748E-05	9.986E-06	6.242E-04	1.498E-02	2.829E-05

HAPs - Metals

	Lead	Cadmium	Chromium	Manganese	Nickel
Emission Factor in lb/MMcf	5.0E-04	1.1E-03	1.4E-03	3.8E-04	2.1E-03
Potential Emission in tons/yr	4.161E-06	9.154E-06	1.165E-05	3.162E-06	1.748E-05

Methodology is the same as page 16.

The five highest organic and metal HAPs emission factors are provided above.
 Additional HAPs emission factors are available in AP-42, Chapter 1.4.

**Appendix A: Emissions Calculations
Particulate Matter (PM) Emissions**

Company Name: Masterfab, Inc.
Address City IN Zip: 16618 Maple City Drive, Goshen, Indiana 46526
Permit Number: T039-19842-00001
Reviewer: GSN/EVP
Date: 01/10/06

Particulate Matter Emissions from Grinding Area (Insignificant Activity)

S/V ID 1.4

PM/PM10: 3.30E-05 gr/acf outlet x 4000 acf/min x 60 min/hr / 7000 gr/lb x 4.38 ton/yr / lb/hr / 0.001 (1- control efficiency) = **4.51 tons/yr (uncontrolled)**
where the baghouse control efficiency is listed at 99.89% **0.00 tons/yr (controlled)**

Methodology

Uncontrolled PM/PM10 = grain loading (gr/acf outlet) * Flow rate (acfm) * (60 min/hr) * (1 lb/7000 gr) * 4.38 (tons/yr / lb/hr) / (1- control efficiency %)

Appendix A: Emission Calculations
HAP Emissions - Potential to Emit

Company Name: Masterfab, Inc.
Address City IN Zip: 16618 Maple City Drive, Goshen, Indiana 46526
Permit Number: T039-19842-00001
Reviewer: GSN/EVP
Date: 01/10/06

Potential To Emit												
Material	Maximum Usage (lb/hr)	Weight % MEK	Weight % Styrene	Weight % Dimethyl Phthalate	Weight % Methyl Methacrylate	Weight % Glycol Ethers	MEK Emissions (tons/yr)	Styrene Emissions (tons/yr)	Dimethyl Phthalate Emissions (tons/yr)	Methyl Methacrylate Emissions (tons/yr)	Glycol Ethers Emissions (tons/yr)	TOTAL HAP Emissions (tons/yr)
Gel Coat												
Hyline Grey Gelcoat *	124.95	0.00%	34.42%	0.00%	2.55%	0.00%	0.00	58.56	0.00	12.31	0.00	70.87
DDM 9 (Catalyst)	9.99	3.00%	0.00%	32.00%	0.00%	0.00%	1.31	0.00	14.00	1.64	0.00	16.96
Resin												
H8354V *	54.145	0.00%	36.92%	0.00%	0.00%	0.00%	0.00	15.30	0.00	0.00	0.00	15.30
DDM 9 (Catalyst)	9.996	3.00%	0.00%	32.00%	0.00%	0.00%	1.31	0.00	14.01	0.00	0.00	15.32
Mold and Pattern Shop Area												
Gelcoat	0.020	0.00%	34.42%	0.00%	2.55%	0.00%	0.00	0.02	0.00	0.00	0.00	0.02
E8234V (Resin)	0.556	0.00%	36.92%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Polycor Grey (Tooling gel)	0.556	0.00%	43.43%	0.00%	4.48%	0.00%	0.00	0.26	0.00	0.08	0.00	0.34
E704-FD (Tooling Resin)	0.223	0.00%	50.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Doeskin (Resin)	0.003	0.00%	24.11%	0.00%	9.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Polycor Orange (Tooling gel)	0.060	0.00%	42.38%	0.00%	4.74%	0.00%	0.00	0.03	0.00	0.00	0.00	0.03
Polycor Black (Tooling gel)	0.060	0.00%	36.77%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
DDM 9 (Catalyst)	0.005	3.00%	0.00%	32.00%	0.00%	0.00%	0.00	0.00	0.01	0.00	0.00	0.01
DDM 30 (Catalyst)	0.005	1.90%	0.00%	20.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Final Finish & Specialty Products Area												
Gelcoat		0.00%	34.42%	0.00%	2.55%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Resin		0.00%	36.92%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Worst Case Single HAP Emission							2.63	74.16	28.02	14.04	0.00	
Worst Case Single HAP Emission (with material usage limitation of 31.95%)								23.70				
Total Combined HAPs Potential Emissions												118.85
Total Combined HAPs Potential Emissions (with material usage limitation of 31.95%)												37.97

Methodology:

For Styrene and Methyl Methacrylate (MMA):

HAPs emission rate (tons/yr) = density (lb/gal) * (gal/unit) * (units/hour) * Styrene or MMA Rate (lb/ton) * (8,760 hrs/yr) * (1 ton/2,000 lb)

Others:

HAPs emission rate (tons/yr) = density (lb/gal) * (gal/unit) * (units/hour) * weight % HAP * (8,760 hrs/yr) * (1 ton/2,000 lb)