



Mitchell E. Daniels, Jr.  
Governor

Thomas W. Easterly  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
(800) 451-6027  
www.IN.gov/idem

TO: Interested Parties / Applicant  
DATE: April 12, 2007  
RE: Argue Automotive Accessories, LLC / 039-20456-00320  
FROM: Nisha Sizemore  
Chief, Permits Branch  
Office of Air Quality

### Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures  
FNPER.dot 03/23/06



Mitchell E. Daniels, Jr.  
Governor

Thomas W. Easterly  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204-2251  
(317) 232-8603  
(800) 451-6027  
www.in.gov/idem

## Federally Enforceable State Operating Permit OFFICE OF AIR QUALITY

**Argue Automotive Accessories, LLC  
910 Summa Drive  
Elkhart, Indiana 46516**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

**The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.**

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70, Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F 039-20456-00320	
Issued by: <i>Original document signed by</i> Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: April 12, 2007  Expiration Date: April 12, 2012

## TABLE OF CONTENTS

<b>SECTION A</b>	<b>SOURCE SUMMARY</b> .....	4
A.1	General Information [326 IAC 2-8-3(b)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]	
A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]	
A.4	FESOP Applicability [326 IAC 2-8-2]	
<b>SECTION B</b>	<b>GENERAL CONDITIONS</b> .....	6
B.1	Definitions [326 IAC 2-8-1]	
B.2	Permit Term [326 IAC 2-8-4(2)] [326 IAC 2-1.1-9.5] [IC 13-15-3-6(a)]	
B.3	Term of Conditions [326 IAC 2-1.1-9.5]	
B.4	Enforceability [326 IAC 2-8-6]	
B.5	Severability [326 IAC 2-8-4(4)]	
B.6	Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]	
B.7	Duty to Provide Information [326 IAC 2-8-4(5)(E)]	
B.8	Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]	
B.9	Annual Compliance Certification [326 IAC 2-8-5(a)(1)]	
B.10	Compliance Order Issuance [326 IAC 2-8-5(b)]	
B.11	Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]	
B.12	Emergency Provisions [326 IAC 2-8-12]	
B.13	Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.14	Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]	
B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]	
B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]	
B.17	Permit Renewal [326 IAC 2-8-3(h)]	
B.18	Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]	
B.19	Operational Flexibility [326 IAC 2-8-15] [326 IAC 2-8-11.1]	
B.20	Source Modification Requirement [326 IAC 2-8-11.1]	
B.21	Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2] [IC 13-17-3-2] [IC 13-30-3-1]	
B.22	Transfer of Ownership or Operational Control [326 IAC 2-8-10]	
B.23	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16] [326 IAC 2-1.1-7]	
B.24	Credible Evidence [326 IAC 2-8-4(3)] [326 IAC 2-8-5] [62 FR 8314] [326 IAC 1-1-6]	
<b>SECTION C</b>	<b>SOURCE OPERATION CONDITIONS</b> .....	15
	<b>Emission Limitations and Standards [326 IAC 2-8-4(1)]</b>	
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2	Overall Source Limit [326 IAC 2-8]	
C.3	Opacity [326 IAC 5-1]	
C.4	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.5	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.6	Fugitive Dust Emissions [326 IAC 6-4]	
C.7	Stack Height [326 IAC 1-7]	
C.8	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	<b>Testing Requirements [326 IAC 2-8-4(3)]</b>	
C.9	Performance Testing [326 IAC 3-6]	
	<b>Compliance Requirements [326 IAC 2-1.1-11]</b>	
C.10	Compliance Requirements [326 IAC 2-1.1-11]	

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- C.11 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]
- C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.13 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-8-4(3)] [326 IAC 2-8-5(1)]

**Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- C.14 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]
- C.15 Response to Excursions or Exceedances [326 IAC 2-8-4] [326 IAC 2-8-5]
- C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4] [326 IAC 2-8-5]

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

- C.17 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]
- C.18 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

**Stratospheric Ozone Protection**

- C.19 Compliance with 40 CFR 82 and 326 IAC 22-1

**SECTION D.1 FACILITY OPERATION CONDITIONS: Surface Coating and Sanding Operations ..... 22**

**Emission Limitations and Standards [326 IAC 2-8-4(1)]**

- D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]
- D.1.2 Hazardous Air Pollutants (HAPs) [326 IAC 2-8]
- D.1.3 Particulate [326 IAC 6-3-2(d)]
- D.1.4 Particulate [326 IAC 6-3-2]
- D.1.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.1.6 Volatile Organic Compounds (VOC) [326 IAC 8-1-4] [326 IAC 8-1-2(a)]

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

- D.1.7 Monitoring

**Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

- D.1.8 Record Keeping Requirements
- D.1.9 Reporting Requirements

<b>Certification Form .....</b>	<b>25</b>
<b>Emergency Occurrence Report .....</b>	<b>26</b>
<b>Quarterly Reports .....</b>	<b>28, 29</b>
<b>Quarterly Deviation and Compliance Monitoring Report .....</b>	<b>31</b>

## SECTION A

## SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in Conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-8-3(b)]

---

The Permittee owns and operates a van and recreational vehicle parts custom painting source.

Source Address:	910 Summa Drive, Elkhart, Indiana 46516
Mailing Address:	52896 CR 113, Elkhart, Indiana 46514
General Source Phone Number:	574 - 970 - 0505
SIC Code:	3711
County Location:	Elkhart
Source Location Status:	Nonattainment for 8-hour ozone Attainment for all other criteria pollutants
Source Status:	Federally Enforceable State Operating Permit Program Minor Source, under PSD and Emission Offset Rules Minor Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) Three (3) paint booths, identified as Paint Booths 1 through 3, each constructed in 1983, each using high volume, low pressure (HVLP) and air assisted airless spray guns, equipped with dry filters for particulate control and exhausting to Stacks V1 through V6, capacity: 2.0 kits of plastic vehicle parts per hour, total.
- (b) One (1) parts repair spray booth, identified as Repair Booth 4, constructed in 1998, using high volume, low pressure (HVLP) and air assisted airless spray guns, equipped with dry filters for particulate control and exhausting to Stack V8, capacity: 2.0 kits of plastic vehicle parts per hour.
- (c) Two (2) parts sanding booths, identified as Sanding Booths 5 and 6, each constructed in 1998, equipped with dry filters for particulate control and exhausting to Stacks V9 and V10, respectively, capacity: 75 parts per hour, each, and 0.72 tons per hour, each.

### A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

---

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million British thermal units per hour.
- (b) The following VOC and HAP storage containers:
  - (1) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons.
  - (2) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids.

- (c) Cleaners and solvents characterized as follows:
  - (1) having a vapor pressure equal to or less than 2 kPa; 15 mm Hg; or 0.3 psi measured at 38 degrees C (100 degrees F); or
  - (2) having a vapor pressure equal to or less than 0.7 kPa; 5 mm Hg; or 0.1 psi measured at 20 degrees C (68 degrees F); the use of which for all cleaners and solvents combined does not exceed 145 gallons per 12 months.
- (d) Closed loop heating and cooling systems.
- (e) Any operation using aqueous solutions containing less than one percent (1%) by weight of VOC excluding HAPs.
- (e) Paved and unpaved roads and parking lots with public access.
- (f) On-site fire and emergency response training approved by the department.

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 Permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) for a Federally Enforceable State Operating Permit (FESOP).

## **SECTION B GENERAL CONDITIONS**

### **B.1 Definitions [326 IAC 2-8-1]**

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

### **B.2 Permit Term [326 IAC 2-8-4(2)] [326 IAC 2-1.1-9.5] [IC 13-15-3-6(a)]**

- 
- (a) This permit, 039-20456-00320, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, until the renewal permit has been issued or denied.

### **B.3 Term of Conditions [326 IAC 2-1.1-9.5]**

---

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

### **B.4 Enforceability [326 IAC 2-8-6]**

---

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

### **B.5 Severability [326 IAC 2-8-4(4)]**

---

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### **B.6 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]**

---

This permit does not convey any property rights of any sort or any exclusive privilege.

### **B.7 Duty to Provide Information [326 IAC 2-8-4(5)(E)]**

- 
- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U.S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an "authorized individual" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) An "authorized individual" is defined at 326 IAC 2-1.1-1(1).

B.9 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than April 15 of each year to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
  - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.10 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.11 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

The PMP extension notification does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.12 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;

- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ and Northern Regional Office within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or  
Telephone Number: 317-233-0178 (ask for Compliance Section)  
Facsimile Number: 317-233-6865  
Northern Regional Office phone: (574) 245-4870; fax: (574) 245-4877

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:

- (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
  - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
  - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of permits established prior to 039-20456-00320 and issued pursuant to permitting programs approved into the state implementation plan have been either:
  - (1) incorporated as originally stated,
  - (2) revised, or
  - (3) deleted.
- (b) All previous registrations and permits are superseded by this permit.

B.14 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

**B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]**

---

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Federally Enforceable State Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
  - (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

**B.17 Permit Renewal [326 IAC 2-8-3(h)]**

---

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:

- (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
- (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.

**B.18 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]**

---

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251  
  
Any such application shall be certified by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10 (b)(3)]

**B.19 Operational Flexibility [326 IAC 2-8-15] [326 IAC 2-8-11.1]**

---

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-8-15(b) through (d) without a prior permit revision, if each of the following conditions is met:
  - (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
  - (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
  - (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
  - (4) The Permittee notifies the:  
  
Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251  
  
and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-8-15(b) through (d). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-8-15(b)(2), (c)(1), and (d).

- (b) Emission Trades [326 IAC 2-8-15(c)]  
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).
- (c) Alternative Operating Scenarios [326 IAC 2-8-15(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (d) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

**B.20 Source Modification Requirement [326 IAC 2-8-11.1]**

---

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-8-11.1.

**B.21 Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2] [IC 13-17-3-2] [IC13-30-3-1]**

---

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-8-10]

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.

- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16] [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.

- (b) Failure to pay may result in administrative enforcement action or revocation of this permit.

- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.24 Credible Evidence [326 IAC 2-8-4(3)] [326 IAC 2-8-5] [62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

## SECTION C SOURCE OPERATION CONDITIONS

Entire Source

### Emission Limitations and Standards [326 IAC 2-8-4(1)]

#### C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

#### C.2 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

(a) Pursuant to 326 IAC 2-8:

- (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one hundred (100) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) and 326 IAC 2-3 (Emission Offset) not applicable;
- (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
- (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.

(b) The potential to emit particulate matter (PM) from the entire source shall be limited to less than two hundred fifty (250) tons per twelve (12) consecutive month period. This limitation shall make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable.

(c) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.

(d) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

#### C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or

fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

**C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]**

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

**C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]**

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

**C.6 Fugitive Dust Emissions [326 IAC 6-4]**

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

**C.7 Stack Height [326 IAC 1-7]**

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

**C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]**

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:
    - (A) Asbestos removal or demolition start date;
    - (B) Removal or demolition contractor; or
    - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**  
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos.

### **Testing Requirements [326 IAC 2-8-4(3)]**

#### **C.9 Performance Testing [326 IAC 3-6]**

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

### **Compliance Requirements [326 IAC 2-1.1-11]**

#### **C.10 Compliance Requirements [326 IAC 2-1.1-11]**

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.

### **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

#### **C.11 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]**

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

#### **C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

#### **C.13 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-8-4(3)] [326 IAC 2-8-5(1)]**

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

### **Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

#### **C.14 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]**

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.15 Response to Excursions or Exceedances [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
  - (1) initial inspection and evaluation
  - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
  - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
  - (1) monitoring results;
  - (2) review of operation and maintenance procedures and records;
  - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
  - (1) monitoring data;
  - (2) monitor performance data, if applicable; and
  - (3) corrective actions taken.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.

- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

### **Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

#### C.17 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

#### C.18 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

### **Stratospheric Ozone Protection**

#### C.19 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor

vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

## SECTION D.1

## EMISSIONS UNIT OPERATION CONDITIONS

### Facility Description [326 IAC 2-8-4(10)]: Surface Coating and Sanding Operations

- (a) Three (3) paint booths, identified as Paint Booths 1 through 3, each constructed in 1983, each using high volume, low pressure (HVLV) and air assisted airless spray guns, equipped with dry filters for particulate control and exhausting to Stacks V1 through V6, capacity: 2.0 kits of plastic vehicle parts per hour, total.
- (b) One (1) parts repair spray booth, identified as Repair Booth 4, constructed in 1998, using high volume, low pressure (HVLV) and air assisted airless spray guns, equipped with dry filters for particulate control and exhausting to Stack V8, capacity: 2.0 kits of plastic vehicle parts per hour.
- (c) Two (2) parts sanding booths, identified as Sanding Booths 5 and 6, each constructed in 1998, equipped with dry filters for particulate control and exhausting to Stacks V9 and V10, respectively, capacity: 75 parts per hour, each, and 0.72 tons per hour, each.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-8-4(1)]

#### D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]

Pursuant to T 039-7510-00320, issued on September 6, 2000, and 326 IAC 8-1-6 (New facilities; General reduction requirements), the Best Available Control Technology (BACT) shall be used for the three (3) paint booths (Paint Booths 1 through 3), the one (1) parts repair spray booth (Repair Booth 4) and the two (2) parts sanding booths (Sanding Booths 5 and 6). BACT for these facilities has been determined to be the following:

- (a) All coatings will be applied using high volume, low pressure (HVLV) spray equipment or a spray applicator as efficient or more efficient than a HVLV spray applicator.
- (b) The total VOC usage in coatings and cleanup solvents used at the surface coating facilities, minus the VOC recovered, shall be limited to less than 95 tons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- (c) The listed work practices as follows:
  - (1) Cleanup solvent containers used to transport solvent from bulk containers to workstations shall be closed containers having soft gasketed spring-loaded closures.
  - (2) Cleanup rags saturated with solvent shall be stored, transported, and disposed of in containers that are closed tightly.
  - (3) The spray guns used shall be the type that can be cleaned without the need for spraying the solvent into the air.
  - (4) Solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as solvent spraying is complete. The waste solvent shall be handled in such a manner that evaporation is minimized.
  - (5) Storage containers used to store VOC and/or HAP containing materials shall be kept covered when not in use.

- (6) The application equipment operators shall be instructed and trained in the methods and practices utilized to minimize overspray.

D.1.2 Hazardous Air Pollutants (HAPs) [326 IAC 2-8]

- (a) The use of any single HAP, including coatings, dilution solvents, and cleaning solvents at the three (3) paint booths (Paint Booths 1 through 3), the one (1) parts repair spray booth (Repair Booth 4) and the two (2) parts sanding booths (Sanding Booths 5 and 6) shall be limited to less than a total of 9.0 tons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- (b) The total use of HAP, including coatings, dilution solvents, and cleaning solvents at the three (3) paint booths (Paint Booths 1 through 3), the one (1) parts repair spray booth (Repair Booth 4) and the two (2) parts sanding booths (Sanding Booths 5 and 6) shall be limited to less than a total of 24.0 tons per twelve (12) consecutive month period, with compliance determined at the end of each month.

These usage limits are required to limit the source-wide potential to emit of HAP to less than ten (10) tons per year for any single HAP, and less than twenty-five (25) tons per year for any combination of HAPs. Compliance with these limits makes 326 IAC 2-7 (Part 70) not applicable.

D.1.3 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate from the three (3) paint booths (Paint Booths 1 through 3) and the one (1) parts repair spray booth (Repair Booth 4) shall be controlled by a dry particulate filter, waterwash, or an equivalent control device, and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.1.4 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the particulate emission rate from the two (2) parts sanding booths (Sanding Booths 5 and 6) shall not exceed 3.29 pounds per hour, each, when operating at a process weight rate of 1,440 pounds per hour (0.72 tons per hour), each

The pounds per hour limitations were calculated with the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.1.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

**Compliance Determination Requirements**

D.1.6 Volatile Organic Compounds (VOC) [326 IAC 8-1-4] [326 IAC 8-1-2(a)]

Compliance with the VOC and HAP usage limitations contained in Conditions D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

## **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

### **D.1.7 Monitoring**

---

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks (Stacks V1 through V6 and V8) while one or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

## **Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

### **D.1.8 Record Keeping Requirements**

---

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC and HAP usage limits established in Conditions D.1.1 and D.1.2. Records necessary to demonstrate compliance shall be available within thirty (30) days of the end of each compliance period.
  - (1) The VOC and HAP content of each coating material and solvent used.
  - (2) The amount of coating material and solvent less water used on monthly basis.
    - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
    - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents.
  - (3) The total amount of each HAP used for each month; and
  - (4) The total VOC and HAPs usage for each month.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain a log of weekly overspray observations, and daily and monthly inspections.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

### **D.1.9 Reporting Requirements**

---

A quarterly summary of the information to document compliance with Conditions D.1.1 and D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
CERTIFICATION**

Source Name: Argue Automotive Accessories, LLC  
Source Address: 910 Summa Drive, Elkhart, Indiana 46516  
Mailing Address: 52896 CR 113, Elkhart, Indiana 46514  
FESOP No.: F 039-20456-00320

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify) \_\_\_\_\_
- Report (specify) \_\_\_\_\_
- Notification (specify) \_\_\_\_\_
- Affidavit (specify) \_\_\_\_\_
- Other (specify) \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE BRANCH  
100 North Senate Avenue  
Indianapolis, Indiana 46204-2251  
Phone: 317-233-0178  
Fax: 317-233-6865**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
EMERGENCY OCCURRENCE REPORT**

Source Name: Argue Automotive Accessories, LLC  
Source Address: 910 Summa Drive, Elkhart, Indiana 46516  
Mailing Address: 52896 CR 113, Elkhart, Indiana 46514  
FESOP No.: F 039-20456-00320

**This form consists of 2 pages**

**Page 1 of 2**

<input type="checkbox"/> This is an emergency as defined in 326 IAC 2-7-1(12) <ul style="list-style-type: none"><li>• The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and</li><li>• The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16</li></ul>
---

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

**Page 2 of 2**

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency?    Y    N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**FESOP Quarterly Report**

Source Name: Argue Automotive Accessories, LLC  
Source Address: 910 Summa Drive, Elkhart, Indiana 46516  
Mailing Address: 52896 CR 113, Elkhart, Indiana 46514  
FESOP No.: F 039-20456-00320  
Facilities: Paint Booths 1 through 3, Repair Booth 4, Sanding Booths 5 and 6  
Parameter: VOC usage  
Limit: Less than a total of 95 tons per twelve (12) consecutive month period, with compliance determined at the end of each month

YEAR: \_\_\_\_\_

Month	VOC Usage (tons)	VOC Usage (tons)	VOC Usage (tons)
	This Month	Previous 11 Months	12 Month Total

- No deviation occurred in this month.
- Deviation/s occurred in this month.  
Deviation has been reported on \_\_\_\_\_

Submitted by: \_\_\_\_\_

Title/Position: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**FESOP Quarterly Report**

Source Name: Argue Automotive Accessories, LLC  
Source Address: 910 Summa Drive, Elkhart, Indiana 46516  
Mailing Address: 52896 CR 113, Elkhart, Indiana 46514  
FESOP No.: F 039-20456-00320  
Facilities: Paint Booths 1 through 3, Repair Booth 4, Sanding Booths 5 and 6  
Parameter: Worst case single HAP usage  
Limit: Less than a total of 9.0 tons per twelve (12) consecutive month period, with compliance determined at the end of each month

YEAR: \_\_\_\_\_

Month	Worst Case Single HAP Usage (tons)	Worst Case Single HAP Usage (tons)	Worst Case Single HAP Usage (tons)
	This Month	Previous 11 Months	12 Month Total

- No deviation occurred in this month.
- Deviation/s occurred in this month.  
Deviation has been reported on \_\_\_\_\_

Submitted by: \_\_\_\_\_

Title/Position: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 COMPLIANCE DATA SECTION**

**FESOP Quarterly Report**

Source Name: Argue Automotive Accessories, LLC  
 Source Address: 910 Summa Drive, Elkhart, Indiana 46516  
 Mailing Address: 52896 CR 113, Elkhart, Indiana 46514  
 FESOP No.: F 039-20456-00320  
 Facilities: Paint Booths 1 through 3, Repair Booth 4, Sanding Booths 5 and 6  
 Parameter: Combined HAP usage  
 Limit: Less than a total of 24.0 tons of combined HAP per twelve (12) consecutive month period, with compliance determined at the end of each month

YEAR: \_\_\_\_\_

Month	Combined HAP Usage (tons)	Combined HAP Usage (tons)	Combined HAP Usage (tons)
	This Month	Previous 11 Months	12 Month Total

- No deviation occurred in this month.
- Deviation/s occurred in this month.  
 Deviation has been reported on \_\_\_\_\_

Submitted by: \_\_\_\_\_  
 Title/Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Argue Automotive Accessories, LLC  
Source Address: 910 Summa Drive, Elkhart, Indiana 46516  
Mailing Address: 52896 CR 113, Elkhart, Indiana 46514  
FESOP No.: F 039-20456-00320

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

Page 1 of 2

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period@."</p>	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

A certification is not required for this report.

**Indiana Department of Environmental Management  
Office of Air Quality**

Technical Support Document (TSD) for a  
Federally Enforceable State Operating Permit (FESOP)

**Source Background and Description**

<b>Source Name:</b>	<b>Argue Automotive Accessories, LLC</b>
<b>Source Location:</b>	<b>910 Summa Drive, Elkhart, Indiana 46516</b>
<b>County:</b>	<b>Elkhart</b>
<b>SIC Code:</b>	<b>3711</b>
<b>Operation Permit No.:</b>	<b>T 039-7510-00320</b>
<b>Operation Permit Issuance Date:</b>	<b>September 6, 2000</b>
<b>Transition to FESOP Permit No.:</b>	<b>F 039-20456-00320</b>
<b>Permit Reviewer:</b>	<b>Edward A. Longenberger</b>

The Office of Air Quality (OAQ) has reviewed a FESOP application from Argue Automotive Accessories, LLC relating to the operation of a van and recreational vehicle parts custom painting source. This source had been operating under the Part 70 Operating Permit program, and has requested to transition to the FESOP permit program. At the time the original Part 70 permit was issued, this source was known as Prodesign Paint, Plant 820.

**Permitted Emission Units and Pollution Control Equipment**

The source consists of the following permitted emission units and pollution control devices:

- (a) Three (3) paint booths, identified as Paint Booths 1 through 3, each constructed in 1983, each using high volume, low pressure (HVLP) and air assisted airless spray guns, equipped with dry filters for particulate control and exhausting to Stacks V1 through V6, capacity: 2.0 kits of plastic vehicle parts per hour, total.
- (b) One (1) parts repair spray booth, identified as Repair Booth 4, constructed in 1998, using high volume, low pressure (HVLP) and air assisted airless spray guns, equipped with dry filters for particulate control and exhausting to Stack V8, capacity: 2.0 kits of plastic vehicle parts per hour.
- (c) Two (2) parts sanding booths, identified as Sanding Booths 5 and 6, each constructed in 1998, equipped with dry filters for particulate control and exhausting to Stacks V9 and V10, respectively, capacity: 75 parts per hour, each, and 0.72 tons per hour, each.

**Unpermitted Emission Units and Pollution Control Equipment**

There are no unpermitted emission units operating at this source during this review process.

**Insignificant Activities**

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million British thermal units per hour.
- (b) The following VOC and HAP storage containers:
  - (1) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons.

- (2) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids.
- (c) Cleaners and solvents characterized as follows:
  - (1) having a vapor pressure equal to or less than 2 kPa; 15 mm Hg; or 0.3 psi measured at 38 degrees C (100 degrees F); or
  - (2) having a vapor pressure equal to or less than 0.7 kPa; 5 mm Hg; or 0.1 psi measured at 20 degrees C (68 degrees F); the use of which for all cleaners and solvents combined does not exceed 145 gallons per 12 months.
- (d) Closed loop heating and cooling systems.
- (e) Any operation using aqueous solutions containing less than one percent (1%) by weight of VOC excluding HAPs.
- (e) Paved and unpaved roads and parking lots with public access.
- (f) On-site fire and emergency response training approved by the department.

### Existing Approvals

The source has been operating under T 039-7510-00320, issued on September 6, 2000.

All terms and conditions from previous approvals were either incorporated as originally stated, revised or deleted by this FESOP. The following terms and conditions have been revised:

T 039-7510-00320, issued on September 6, 2000

Condition D.1.1: This condition limited the VOC usage at the surface coating booths to less than fifteen (15) pounds per day, when coating metal, in order to ensure that the requirements of 326 IAC 8-2-9 do not apply.

Reason not incorporated: This source no longer applies coatings to metal parts, therefore, this limit is not needed.

### Enforcement Issue

There are no enforcement actions pending.

### Recommendation

The staff recommends to the Commissioner that the FESOP be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete and timely Part 70 renewal application for the purposes of this review was received on December 7, 2004. On December 21, 2006, an application was received which requested a transition to the FESOP permit program.

There was no notice of completeness letter mailed to the source.

### Emission Calculations

See pages 1 through 3 of Appendix A of this document for detailed emission calculations. According to the previous operating permit (T 039-7510-00320) emissions from insignificant activities are as estimated to be 5.00 tons per year for PM, PM<sub>10</sub>, VOC and CO; 2.00 tons per year for SO<sub>2</sub> and NO<sub>x</sub>; and 1.00 ton per year for total HAPs.

### Potential to Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emissions unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U.S. EPA, the department, or the appropriate local air pollution control agency.”

Pollutant	Potential to Emit (tons/yr)
PM	32.76
PM <sub>10</sub>	32.76
SO <sub>2</sub>	2.00
VOC	86.24
CO	5.00
NO <sub>x</sub>	2.00

HAPs	Potential to Emit (tons/yr)
Ethyl Benzene	4.81
Isocyanate	0.024
Methanol	0.399
MIBK	1.25
Toluene	3.14
Xylene	17.6
Styrene	0.013
Total	27.2

The potential to emit (as defined in 326 IAC 2-7-1(29)) of any single HAP is greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination of HAPs is greater than twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7. The source will be issued a FESOP because the source will limit its emissions below the Title V levels.

**Potential to Emit After Issuance**

The source has elected to operate as a FESOP source. The table below summarizes the potential to emit, reflecting all limits of the emission units. Any control equipment is considered enforceable only after issuance of this FESOP and only to the extent that the effect of the control equipment is made practically enforceable in the permit.

Process/emission unit	Potential To Emit (tons/year)						
	PM	PM <sub>10</sub>	SO <sub>2</sub>	VOC	CO	NO <sub>x</sub>	HAPs
Paint Booths 1 through 3	0.686	0.686	-	Less than 95.0	-	-	Single less than 9.0
Repair Booth 4	0.069	0.069	-		-	-	Total less than 24.0
Sanding Booths 5 and 6	3.04	3.04	-		-	-	
Insignificant Activities	5.00	5.00	2.00	5.00	5.00	2.00	1.00
Total Emissions	8.80	8.80	2.00	Less than 100	5.00	2.00	Single less than 10.0  Total less than 25.0

- (a) The limit of less than 95.0 tons per year of VOC from booths 1 through 6 is pursuant to the BACT determination under 326 IAC 8-1-6.
- (b) The HAP limit for booths 1 through 6 is necessary to render the requirements of 326 IAC 2-7 (Part 70) not applicable.

**County Attainment Status**

The source is located in Elkhart County.

Pollutant	Status
PM <sub>2.5</sub>	Attainment
PM <sub>10</sub>	Attainment
SO <sub>2</sub>	Attainment
NO <sub>2</sub>	Attainment
8-Hour Ozone	Basic nonattainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and nitrogen oxides (NO<sub>x</sub>) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NO<sub>x</sub> emissions are considered when evaluating the rule applicability relating to the ozone standards. Elkhart County has been designated as nonattainment for the 8-hour ozone standard. Therefore, VOC

and NO<sub>x</sub> emissions were reviewed pursuant to the requirements of 326 IAC 2-3, Emission Offset. See the State Rule Applicability - Entire Source section of this document.

- (b) Elkhart County has been classified as unclassifiable or attainment for PM<sub>2.5</sub>. U.S. EPA has not yet established the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 for PM<sub>2.5</sub> emissions. Therefore, until the U.S. EPA adopts specific provisions for PSD review for PM<sub>2.5</sub> emissions, it has directed states to regulate PM<sub>10</sub> emissions as a surrogate for PM<sub>2.5</sub> emissions. See the State Rule Applicability - Entire Source Section of this document.
- (c) Elkhart County has been classified as attainment or unclassifiable in Indiana for all remaining criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2. See the State Rule Applicability - Entire Source section of this document.
- (d) On October 25, 2006, the Indiana Air Pollution Control Board finalized a rule revision to 326 IAC 1-4-1 redesignating Delaware, Greene, Jackson, Vanderburgh, Vigo and Warrick Counties to attainment for the eight-hour ozone standard, redesignating Lake County to attainment for the sulfur dioxide standard, and revoking the one-hour ozone standard in Indiana.
- (e) Fugitive Emissions  
Since this type of operation is not one of the 28 listed source categories under 326 IAC 2-2 or 2-3 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are not counted toward determination of PSD and Emission Offset applicability. Pursuant to 326 IAC 2-7-2(e), all fugitive emissions are counted toward the determination of Part 70 Applicability.

### Source Status

Existing Source PSD, Part 70, or FESOP Definition (emissions after controls, based on 8,760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/yr)
PM	8.51
PM <sub>10</sub>	8.51
SO <sub>2</sub>	2.00
VOC	Less than 100
CO	5.00
NO <sub>x</sub>	2.00
Single HAP	Less than 10
Combination HAPs	Less than 25

- (a) This existing source is **not** a major stationary source under 326 IAC 2-2 (PSD) because no attainment regulated pollutant is emitted at a rate of two hundred fifty (250) tons per year or greater and it is not in one of the twenty-eight (28) listed source categories.

- (b) This existing source is **not** a major stationary source under 326 IAC 2-3 (Emission Offset) because no nonattainment regulated pollutant is emitted at a rate of one hundred (100) tons per year or greater, and it is not in one of the twenty-eight (28) listed source categories.

### **Federal Rule Applicability**

- (a) There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) included in the permit for this source.
- (b) The requirements of the National Emissions Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production (326 IAC 20-81 and 40 CFR 63, Subpart PPPP) are not included in the permit for this source. This source is not a major source of HAPs as defined in 40 CFR 63.2.

### **State Rule Applicability – Entire Source**

#### 326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

The unrestricted potential emissions of each attainment criteria pollutant are less than two hundred fifty (250) tons per year. Therefore, this source, which is not one of the twenty-eight (28) listed source categories, is a minor source under 326 IAC 2-2, PSD.

#### 326 IAC 2-3 (Emission Offset)

The unrestricted potential NO<sub>x</sub> emissions are less than one hundred (100) tons per year. As a result of the VOC limit pursuant to T 039-7510-00320, issued on September 6, 2000 and 326 IAC 8-1-6, the VOC emissions from this source are limited to less than one hundred (100) tons per year. Therefore, this source is a minor source under 326 IAC 2-3, Emission Offset.

#### 326 IAC 2-4.1-1 (New source toxics control)

The operation of this van and recreational vehicle parts custom painting source will emit less than ten (10) tons per year of a single HAP and less than twenty-five (25) tons per year of a combination of HAPs. Therefore, 326 IAC 2-4.1 does not apply.

#### 326 IAC 2-6 (Emission Reporting)

This source is not located in Lake or Porter County, does not emit five (5) tons per year or more of lead and does not require a Part 70 Operating Permit. Therefore, the requirements of 326 IAC 2-6 do not apply.

#### 326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity limitations), except as provided in 326 IAC 5-1-3 (Temporary alternative opacity limitations), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

### State Rule Applicability – Individual Facilities

#### 326 IAC 6-3-2(d) (Particulate emission limitations, work practices and control technologies)

Pursuant to 326 IAC 6-3-2(d), the dry filters for particulate control shall be operation in accordance with manufacturer's specifications and control emissions from the three (3) paint booths (Paint Booths 1 through 3) and the one (1) parts repair spray booth (Repair Booth 4), at all times when any of these facilities are in operation.

The surface coating operations at the two (2) parts sanding booths (Sanding Booths 5 and 6) result in particulate emissions less than 0.551 pounds per hour, therefore, pursuant to 326 IAC 6-3-1(b)(14), the requirements of 326 IAC 6-3-2(d) are not applicable to the two (2) parts sanding booths (Sanding Booths 5 and 6).

#### 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

Pursuant to 326 IAC 6-3-2, the allowable particulate emission rate from the two (2) parts sanding booths (Sanding Booths 5 and 6), shall not exceed 3.29 pounds per hour, each, when operating at a process weight rate of 1,440 pounds per hour (0.72 tons per hour), each.

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

As stated on page 3 of Appendix A, the potential particulate emissions before control from each sanding booth are 2.31 pounds per hour. Therefore, each of the two (2) parts sanding booths (Sanding Booths 5 and 6) can comply with this rule, without the use of a control device.

#### 326 IAC 8-1-6 (New facilities; general reduction requirements)

The three (3) paint booths (Paint Booths 1 through 3) were constructed after January 1, 1980. The potential to emit VOC from these booths is greater than twenty-five (25) tons per year and no other Article 8 rules apply to surface coating of plastic parts. Therefore, the requirements of 326 IAC 8-1-6 apply to Paint Booths 1 through 3.

The potential to emit VOC from the one (1) parts repair spray booth (Repair Booth 4) is less than twenty-five (25) tons per year and the potential to emit VOC from each of the two (2) sanding booths (Sanding Booths 5 and 6) is less than twenty-five (25) tons per year. However, because these facilities can operate in series with the three (3) paint booths (Paint Booths 1 through 3) and to facilitate record keeping, the applicant requested that the BACT be determined for all surface coating operations at this source. Therefore, the BACT determination from the previous operating permit (T 039-7510-00320, issued on September 6, 2000) has been incorporated as follows:

Pursuant to T 039-7510-00320, issued on September 6, 2000, and 326 IAC 8-1-6 (New facilities; General reduction requirements), the Best Available Control Technology (BACT) shall be used for the three (3) paint booths, one (1) parts repair spray booth and two (2) parts sanding booths. BACT for these facilities has been determined to be the following:

- (a) All coatings will be applied using high volume, low pressure (HVLP) spray equipment or a spray applicator as efficient or more efficient than a HVLP spray applicator.

- (b) The total VOC usage in coatings and cleanup solvents used at the surface coating facilities, minus the VOC recovered, shall be limited to less than 95 tons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- (c) The listed work practices as follows:
  - (1) Cleanup solvent containers used to transport solvent from bulk containers to workstations shall be closed containers having soft gasketed spring-loaded closures.
  - (2) Cleanup rags saturated with solvent shall be stored, transported, and disposed of in containers that are closed tightly.
  - (3) The spray guns used shall be the type that can be cleaned without the need for spraying the solvent into the air.
  - (4) Solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as solvent spraying is complete. The waste solvent shall be handled in such a manner that evaporation is minimized.
  - (5) Storage containers used to store VOC and/or HAP containing materials shall be kept covered when not in use.
  - (6) The application equipment operators shall be instructed and trained in the methods and practices utilized to minimize overspray.

#### 326 IAC 8-2-9 (Miscellaneous Metal Coating)

This source does not apply coatings to metal parts. Therefore, the requirements of 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations) are not applicable.

#### Testing Requirements

All emission calculations are based on AP-42 emission factors or the MSDS for the coatings and solvents. The previous operating permit (T 039-7510-00320) did not contain any specific testing requirements. No testing requirements are proposed.

#### Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforce-

ment action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

The four (4) surface coating booths (Paint Booths 1 through 3 and Repair Booth 4) have applicable compliance monitoring conditions as specified below:

Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks (Stacks V1 through V6 and V8) while one or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

These monitoring conditions are necessary because the dry filters for the surface coating booths must operate properly to ensure compliance with 326 IAC 6-3-2(d) (Particulate emission limitations, work practices and control technologies) and 326 IAC 2-8 (FESOP).

## Conclusion

The operation of this van and recreational vehicle parts custom painting source shall be subject to the conditions of the **FESOP 039-20456-00320**.

**Appendix A: Emissions Calculations  
VOC and Particulate  
From Surface Coating Operations**

**Company Name:** Argue Automotive Accessories, LLC  
**Address City IN Zip:** 910 Summa Drive, Elkhart, Indiana 46516  
**FESOP:** 039-20456-00320  
**Pit ID:** 039-00320  
**Reviewer:** Edward A. Longenberger  
**Application Date:** December 7, 2004

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
<b>Paint Booths 1, 2 and 3</b>																
Chroma Premier 42440S	12.86	33.44%	0.00%	33.44%	0.00%	40.54%	0.15385	2.000	4.30	4.30	1.32	31.76	5.80	2.88	10.61	75%
Chroma Premier 12305S	8.45	35.50%	0.00%	35.50%	0.00%	56.94%	0.03846	2.000	3.00	3.00	0.23	5.54	1.01	0.46	5.27	75%
Chroma Premier 42475S	7.68	82.03%	0.00%	82.03%	0.00%	18.51%	0.05769	2.000	6.30	6.30	0.73	17.45	3.18	0.17	34.04	75%
ChromaBase Basecoat 845J	7.91	72.06%	0.00%	72.06%	0.00%	20.84%	0.24752	2.000	5.70	5.70	2.82	67.72	12.36	1.20	27.35	75%
Basemaker 7175S	6.64	99.40%	9.04%	90.36%	9.08%	0.13%	0.24752	2.000	6.60	6.00	2.97	71.28	13.01	0.02	4615.31	75%
Chroma Premier 12305S	8.45	35.50%	0.00%	35.50%	0.00%	56.94%	0.00495	2.000	3.00	3.00	0.03	0.71	0.13	0.06	5.27	75%
ChromaClear 4700S	8.05	48.45%	0.00%	48.45%	0.00%	44.48%	0.15000	2.000	3.90	3.90	1.17	28.08	5.12	1.36	8.77	75%
ChromaClear 4507S	8.84	27.15%	0.00%	27.15%	0.00%	66.95%	0.05000	2.000	2.40	2.40	0.24	5.76	1.05	0.71	3.58	75%
Chroma Premier 12375S	7.09	100.00%	0.00%	100.00%	0.00%	0.00%	0.05000	2.000	7.09	7.09	0.71	17.02	3.11	0.00	NA	75%
Pure Grade Lacquer (Cleanup)	7.07	100.00%	0.00%	100.00%	0.00%	0.00%	0.06250	2.000	7.07	7.07	0.88	21.21	3.87	0.00	NA	75%

PM Control Efficiency: 90.00%  
**Uncontrolled** 11.11 266.53 48.64 6.86  
**Controlled** 11.11 266.53 48.64 6.86

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
<b>Repair Booth 4</b>																
Chroma Premier 42440S	12.86	33.44%	0.00%	33.44%	0.00%	40.54%	0.01539	2.000	4.30	4.30	0.13	3.18	0.58	0.29	10.61	75%
Chroma Premier 12305S	8.45	35.50%	0.00%	35.50%	0.00%	56.94%	0.00385	2.000	3.00	3.00	0.02	0.55	0.10	0.05	5.27	75%
Chroma Premier 42475S	7.68	82.03%	0.00%	82.03%	0.00%	18.51%	0.00577	2.000	6.30	6.30	0.07	1.74	0.32	0.02	34.04	75%
ChromaBase Basecoat 845J	7.91	72.06%	0.00%	72.06%	0.00%	20.84%	0.02475	2.000	5.70	5.70	0.28	6.77	1.24	0.12	27.35	75%
Basemaker 7175S	6.64	99.40%	9.04%	90.36%	9.08%	0.13%	0.02475	2.000	6.60	6.00	0.30	7.13	1.30	0.00	4615.31	75%
Chroma Premier 12305S	8.45	35.50%	0.00%	35.50%	0.00%	56.94%	0.00050	2.000	3.00	3.00	0.00	0.07	0.01	0.01	5.27	75%
ChromaClear 4700S	8.05	48.45%	0.00%	48.45%	0.00%	44.48%	0.01500	2.000	3.90	3.90	0.12	2.81	0.51	0.14	8.77	75%
ChromaClear 4507S	8.84	27.15%	0.00%	27.15%	0.00%	66.95%	0.00500	2.000	2.40	2.40	0.02	0.58	0.11	0.07	3.58	75%
Chroma Premier 12375S	7.09	100.00%	0.00%	100.00%	0.00%	0.00%	0.00500	2.000	7.09	7.09	0.07	1.70	0.31	0.00	NA	75%
Pure Grade Lacquer (Cleanup)	7.07	100.00%	0.00%	100.00%	0.00%	0.00%	0.00625	2.000	7.07	7.07	0.09	2.12	0.39	0.00	NA	75%

PM Control Efficiency: 90.00%  
**Uncontrolled** 1.11 26.65 4.86 0.686  
**Controlled** 1.11 26.65 4.86 0.686

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
<b>Sanding Booths 5 and 6</b>																
Solvent Wipe	6.33	100.00%	0.00%	100.00%	0.00%	0.00%	0.50000	2.000	6.33	6.33	6.33	151.92	27.73	0.00	NA	100%
Glazecoat	15.00	25.00%	0.00%	25.00%	0.00%	75.00%	0.00040	2.000	3.75	3.75	0.00	0.07	0.01	0.01	5.00	75%

PM Control Efficiency: 85.00%  
**Uncontrolled** 6.33 151.99 27.74 0.010  
**Controlled** 6.33 151.99 27.74 0.001

**METHODOLOGY**

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) \* Weight % Organics) / (1-Volume % water)  
Pounds of VOC per Gallon Coating = (Density (lb/gal) \* Weight % Organics)  
Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) \* Gal of Material (gal/unit) \* Maximum (units/hr)  
Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) \* Gal of Material (gal/unit) \* Maximum (units/hr) \* (24 hr/day)  
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) \* Gal of Material (gal/unit) \* Maximum (units/hr) \* (8760 hr/yr) \* (1 ton/2000 lbs)  
Particulate Potential Tons per Year = (units/hour) \* (gal/unit) \* (lbs/gal) \* (1- Transfer efficiency) \* (8760 hrs/yr) \* (1 ton/2000 lbs)  
Pounds VOC per Gallon of Solids = (Density (lbs/gal) \* Weight % organics) / (Volume % solids)

**Appendix A: Emission Calculations  
HAP Emission Calculations**

**Company Name: Argue Automotive Accessories, LLC  
Address City IN Zip: 910 Summa Drive, Elkhart, Indiana 46516  
FESOP: 039-20456-00320  
Pit ID: 039-00320  
Reviewer: Edward A. Longenberger  
Application Date: December 7, 2004**

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Weight % Ethyl Benzene	Weight % Isocyanate Compounds	Weight % Methanol	Weight % MIBK	Weight % Toluene	Weight % Xylene	Ethyl Benzene Emissions (ton/yr)	Isocyanate Emissions (ton/yr)	Methanol Emissions (ton/yr)	MIBK Emissions (ton/yr)	Toluene Emissions (ton/yr)	Xylene Emissions (ton/yr)	Total HAPs Emissions (ton/yr)
<b>Paint Booths 1, 2 and 3</b>																
Chroma Premier 42440S	12.86	0.15385	2.000	4.20%	0.10%	0.00%	0.00%	0.00%	15.00%	0.73	0.02	0.00	0.00	0.00	2.60	3.35
Chroma Premier 12305S	8.45	0.03846	2.000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Chroma Premier 42475S	7.68	0.05769	2.000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ChromaBase Basecoat 845J	7.91	0.24752	2.000	13.00%	0.00%	0.00%	0.00%	0.00%	47.00%	2.23	0.00	0.00	0.00	0.00	8.06	10.29
Basemaker 7175S	6.64	0.24752	2.000	3.00%	0.00%	0.00%	5.00%	2.00%	11.00%	0.43	0.00	0.00	0.00	0.72	0.29	1.58
Chroma Premier 12305S	8.45	0.00495	2.000	0.00%	0.10%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ChromaClear 4700S	8.05	0.15000	2.000	7.40%	0.00%	0.00%	1.00%	0.00%	27.00%	0.78	0.00	0.00	0.11	0.00	2.86	3.74
ChromaClear 4507S	8.84	0.05000	2.000	0.00%	0.10%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Chroma Premier 12375S	7.09	0.05000	2.000	6.30%	0.00%	0.00%	10.00%	0.00%	23.00%	0.20	0.00	0.00	0.31	0.00	0.71	1.22
Pure Grade Lacquer (Cleanup)	7.07	0.06250	2.000	0.00%	0.00%	9.38%	0.00%	66.28%	5.59%	0.00	0.00	0.36	0.00	2.57	0.22	3.15
										<b>4.37</b>	<b>0.022</b>	<b>0.363</b>	<b>1.14</b>	<b>2.85</b>	<b>16.03</b>	<b>24.77</b>

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Weight % Ethyl Benzene	Weight % Isocyanate Compounds	Weight % Methanol	Weight % MIBK	Weight % Toluene	Weight % Xylene	Ethyl Benzene Emissions (ton/yr)	Isocyanate Emissions (ton/yr)	Methanol Emissions (ton/yr)	MIBK Emissions (ton/yr)	Toluene Emissions (ton/yr)	Xylene Emissions (ton/yr)	Total HAPs Emissions (ton/yr)
<b>Repair Booth 4</b>																
Chroma Premier 42440S	12.86	0.01539	2.000	4.20%	0.10%	0.00%	0.00%	0.00%	15.00%	0.07	0.00	0.00	0.00	0.00	0.26	0.33
Chroma Premier 12305S	8.45	0.00385	2.000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Chroma Premier 42475S	7.68	0.00577	2.000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ChromaBase Basecoat 845J	7.91	0.02475	2.000	13.00%	0.00%	0.00%	0.00%	0.00%	47.00%	0.22	0.00	0.00	0.00	0.00	0.81	1.03
Basemaker 7175S	6.64	0.02475	2.000	3.00%	0.00%	0.00%	5.00%	2.00%	11.00%	0.04	0.00	0.00	0.07	0.03	0.16	0.30
Chroma Premier 12305S	8.45	0.00050	2.000	0.00%	0.10%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ChromaClear 4700S	8.05	0.01500	2.000	7.40%	0.00%	0.00%	1.00%	0.00%	27.00%	0.08	0.00	0.00	0.01	0.00	0.29	0.37
ChromaClear 4507S	8.84	0.00500	2.000	0.00%	0.10%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Chroma Premier 12375S	7.09	0.00500	2.000	6.30%	0.00%	0.00%	10.00%	0.00%	23.00%	0.02	0.00	0.00	0.03	0.00	0.07	0.12
Pure Grade Lacquer (Cleanup)	7.07	0.00625	2.000	0.00%	0.00%	9.38%	0.00%	66.28%	5.59%	0.00	0.00	0.04	0.00	0.26	0.02	0.31
										<b>0.437</b>	<b>0.002</b>	<b>0.036</b>	<b>0.114</b>	<b>0.285</b>	<b>1.60</b>	<b>2.48</b>

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Weight % Styrene	Weight % Isocyanate Compounds	Weight % Methanol	Weight % MIBK	Weight % Toluene	Weight % Xylene	Styrene Emissions (ton/yr)	Isocyanate Emissions (ton/yr)	Methanol Emissions (ton/yr)	MIBK Emissions (ton/yr)	Toluene Emissions (ton/yr)	Xylene Emissions (ton/yr)	Total HAPs Emissions (ton/yr)
<b>Sanding Booths 5 and 6</b>																
Solvent Wipe	6.33	0.50000	2.000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Glazecoat	15.00	0.00040	2.000	25.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.013	0.00	0.00	0.00	0.00	0.00	0.013
										<b>0.013</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.013</b>

**METHODOLOGY**

HAPS emission rate (tons/yr) = Density (lb/gal) \* Gal of Material (gal/unit) \* Maximum (unit/hr) \* Weight % HAP \* 8760 hrs/yr \* 1 ton/2000 lbs

**Appendix A: Emission Calculations  
Parts Sanding Booths 5 and 6**

**Company Name: Argue Automotive Accessories, LLC**  
**Address City IN Zip: 910 Summa Drive, Elkhart, Indiana 46516**  
**FESOP: 039-20456-00320**  
**Plt ID: 039-00320**  
**Reviewer: Edward A. Longenberger**  
**Application Date: December 7, 2004**

Unit ID	Control Efficiency (%)	Grain Loading per Actual Cubic foot of Outlet Air (grains/cub. ft.)	Gas or Air Flow Rate (acfm.)	PM Emission Rate before Controls (lb/hr)	PM Emission Rate before Controls (tons/yr)	PM Emission Rate after Controls (lb/hr)	PM Emission Rate after Controls (tons/yr)
Sanding Booth 5 (Stack V9)	85.0%	0.0270	1,500	2.31	10.1	0.3471	1.520
Sanding Booth 6 (Stack V10)	85.0%	0.0270	1,500	2.31	10.1	0.3471	1.520

**Methodology**

Emission Rate in lbs/hr (after controls) = (grains/cub. ft.) (cub. ft./min.) (60 min/hr) (lb/7000 grains)

Emission Rate in tons/yr = (lbs/hr) (8760 hr/yr) (ton/2000 lb)

Emission Rate in lbs/hr (before controls) = Emission Rate (after controls)(lbs/hr) / (1-control efficiency)

Emission Rate in tons/yr = (lbs/hr) (8760 hr/yr) (ton/2000 lb)

**Allowable Rate of Emissions (326 IAC 6-3-2)**

Process Rate (lbs/hr)	Process Weight Rate (tons/hr)	Allowable Emissions (lbs/hr)
1,440	0.72	3.29

**Methodology**

Allowable Emissions = 4.10(Process Weight Rate)<sup>0.67</sup>