

TO: William J. Day  
RE: Marathon Petroleum LLC / 097-21222-00159  
FROM: Felicia A. Robinson  
Manager of Environmental Planning

## Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within fifteen (15) calendar days from the receipt of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Indianapolis Office of Environmental Services, Air Permits at (317) 327-2234.

Enclosures

September 14, 2005



Certified Mail: 7000 0600 0023 5187 2162

William J. Day  
Marathon Petroleum Company LLC  
1304 Olin Avenue  
Indianapolis, IN. 46222

Re: 097-21222-00159  
First Administrative Amendment to  
Part 70 Operating Permit  
097-16068-00159

Dear Mr. Day:

Marathon Ashland Petroleum LLC (MAP) was issued a Part 70 Operating Permit T097-16068-00159 on October 6, 2003 for operation of a petroleum distribution terminal. A letter requesting an Administrative Amendment to modify the descriptive language in the permit was received on May 13, 2005. The source included a request to construct a geodesic dome on Tank 135-1. The installation of a geodesic dome on Tank 135-1 will not be subject to New Source Performance Standards (NSPS) and 40 CFR 60.116b, subpart Kb requirements because the tank was constructed in 1959 prior to the rule applicability date of July 23, 1984, and because the cost for the installation of the geodesic dome will be less than 50% of the replacement cost of the tank. In addition this is not a Title I modification under the Clean Air Act and does not involve significant changes to existing monitoring, reporting or record keeping requirements in the existing Part 70 permit. Therefore, pursuant to 326 IAC 2-7-12(b)(1), the permit is hereby amended as follows: (the bold language is new language that has been added, and the language with a line through it has been taken out).

1. To reflect the equipment changes at the source, Condition A.2 and the Facility Description in Section D.2 have been changed as follows:

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]  
[326 IAC 2-7-5(15)]

---

This stationary source consists of the following emission units and pollution control devices:

- (b) One (1) storage tank, identified as Storage Tank 135-1 (formerly T1351), constructed in 1959, with a maximum capacity of 5,670,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with ~~an~~ **a geodesic dome and internal floating roof.** ~~external double deck steel welded floating roof with a primary mechanical shoe seal and a secondary rim mounted wiper seal.~~

Department of Public Works  
Office of Environmental Services  
2700 South Belmont Avenue (317) 327-2234  
Indianapolis, Indiana 46221 (fax) 327-2274  
**(TDD) 325-5186**  
www.indygov.org

## SECTION D.2

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]: Storage Tanks

- (b) One (1) storage tank, identified as Storage Tank 135-1 (formerly T1351), constructed in 1959, with a maximum capacity of 5,670,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with ~~an~~ a **geodesic dome and internal floating roof**:~~external double deck steel welded floating roof with a primary mechanical shoe seal and a secondary rim mounted wiper seal.~~

2. Marion County has been designated as nonattainment for the 8-hour ozone standard and PM2.5. Condition A.1 has been updated to reflect the aforementioned changes.

#### A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary petroleum distribution terminal.

Responsible Official:	District Manager or TT&M Manager
Source Address:	4955 Robison Road, Indianapolis, Indiana 46268
Mailing Address:	HESS-TT&M 539 S. Main Street, Findlay, Ohio 45840
General Source Phone Number:	(317) 244-9551
SIC Code:	5171
County Location:	Marion
Source Location Status:	<b>Nonattainment for 8 hour ozone and PM 2.5;</b> Attainment for all <b>other</b> criteria pollutants
Source Status:	Part 70 Permit Program Minor Source under PSD <b>and Emission Offset</b> Minor Source, Section 112 of the Clean Air Act 1 of 28 Source Categories

3. Change to IDEM, OAQ address is acknowledged and incorporated into the permit as follows:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue ~~P.O. Box 6015~~  
Indianapolis, IN **46204** ~~46206-6015~~

All other conditions of the permit shall remain unchanged and in effect. Please attach a copy of this amendment and the following revised permit pages to the front of the original permit.

4. As per a letter received on August 12, 2005 requesting name change of the source to Marathon Petroleum Company LLC, the permit is revised accordingly.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact TJ Edwards at (317) 327-2283.

Sincerely,

Original Signed by

Felicia A. Robinson  
Manager of Environmental Planning

Attachments: Revised Permit  
FAR/tle

cc: Air Permits-2  
Air Compliance – Matt Mosier  
IDEM, OAQ – Mindy Hahn  
US EPA Region 5  
Marion County Health Dept.

**INDIANA DEPARTMENT OF ENVIRONMENTAL  
MANAGEMENT**

**PART 70 OPERATING PERMIT RENEWAL**

**OFFICE OF AIR QUALITY  
AND  
CITY OF INDIANAPOLIS,  
OFFICE OF ENVIRONMENTAL SERVICES**

**Marathon Petroleum Company LLC  
4955 Robison Road  
Indianapolis, Indiana 46268**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T097-16068-00159	
Issued by: Originally signed by Janet G. McCabe Janet G. McCabe, Assistant Commissioner, OAQ  Originally signed by John B. Chavez John B. Chavez, Administrator, OES	Issuance Date: October 6, 2003  Expiration Date: October 6, 2008

**First Significant Permit Modification: SPM 097-19125-00159**

First Administrative Amendment No. 097-21222-00159	Conditions Affected: A.1 General Information A.2 Emission Units and Pollution Control Equipment
Issued by:  Original Signed by  Felicia A. Robinson Manager of Environmental Planning	Issuance Date: September 14, 2005

## TABLE OF CONTENTS

<b>SECTION A</b>	<b>SOURCE SUMMARY</b> .....	5
A.1	General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]	
A.3	Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.4	Part 70 Permit Applicability [326 IAC 2-7-2]	
<b>SECTION B</b>	<b>GENERAL CONDITIONS</b> .....	7
B.1	Definitions [326 IAC 2-7-1]	
B.2	Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]	
B.3	Enforceability [326 IAC 2-7-7]	
B.4	Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]	
B.5	Severability [326 IAC 2-7-5(5)]	
B.6	Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	
B.7	Duty to Provide Information [326 IAC 2-7-5(6)(E)]	
B.8	Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]	
B.9	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]	
B.10	Annual Compliance Certification [326 IAC 2-7-6(5)]	
B.11	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3)and (13)][326 IAC 2-7-6(1)and(6)] [326 IAC 1-6-3]	
B.12	Emergency Provisions [326 IAC 2-7-16]	
B.13	Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]	
B.14	Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]	
B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]	
B.17	Permit Renewal [326 IAC 2-7-4]	
B.18	Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]	
B.19	Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12(b)(2)]	
B.20	Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]	
B.21	Source Modification Requirement [326 IAC 2-7-10.5]	
B.22	Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1]	
B.23	Transfer of Ownership or Operational Control [326 IAC 2-7-11]	
B.24	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]	
<b>SECTION C</b>	<b>SOURCE OPERATION CONDITIONS</b> .....	18
	<b>Emission Limitations and Standards [326 IAC 2-7-5(1)]</b>	
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less than One Hundred (100) Pounds per Hour [40 CFR 52, Subpart P][326 IAC 6-3-2]	
C.2	Opacity [326 IAC 5-1]	
C.3	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.4	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.5	Fugitive Dust Emissions [326 IAC 6-4]	
C.6	Operation of Equipment [326 IAC 2-7-6(6)]	
C.7	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	<b>Testing Requirements [326 IAC 2-7-6(1)]</b>	
C.8	Performance Testing [326 IAC 3-6]	

**TABLE OF CONTENTS (Continued)**

**Compliance Requirements [326 IAC 2-1.1-11]**

C.9 Compliance Requirements [326 IAC 2-1.1-11]

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

C.14 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5] [326 IAC 2-7-6]

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

C.16 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]

C.17 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

C.18 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

**Stratospheric Ozone Protection**

C.19 Compliance with 40 CFR 82 and 326 IAC 22-1

**SECTION D.1 FACILITY OPERATION CONDITIONS - Loading Rack ..... 26**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.1.1 General Provisions Relating to NSPS [326 IAC 12-1] [40 CFR 60, Subpart A]

D.1.2 Volatile Organic Compounds (VOC) [326 IAC 12] [40 CFR 60, Subpart XX]

D.1.3 Hazardous Air Pollutants (HAPs) [326 IAC 20][40 CFR 63, Subpart R]

D.1.4 Volatile Organic Compounds (VOC) [326 IAC 8-4-4]

D.1.5 Leaks from Transports and Vapor Collection Systems [326 IAC 8-4-9]

D.1.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

D.1.7 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAP)

D.1.8 Testing Requirements [326 IAC 2-7-6(1),(6)][326 IAC 2-1.1-11]

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.1.9 Monitoring

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.1.10 Record Keeping Requirements

D.1.11 Reporting Requirements

**SECTION D.2 FACILITY OPERATION CONDITIONS - Storage Tanks ..... 32**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.2.1 General Provisions Relating to NSPS [326 IAC 12-1] [40 CFR 60, Subpart A]

D.2.2 Storage Vessels [326 IAC 12] [40 CFR 60, Subpart K]

D.2.3 Storage Vessels [326 IAC 12] [40 CFR 60, Subpart Kb]

D.2.4 Hazardous Air Pollutants [326 IAC 20] [40 CFR 63, Subpart R]

D.2.5 Storage Vessels [326 IAC 8-4-3]

**TABLE OF CONTENTS (Continued)**

D.2.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.2.7 Monitoring [326 IAC 12] [40 CFR 60, Subpart Kb]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.2.8 Record Keeping Requirements

D.2.9 Reporting Requirements

**SECTION D.3 FACILITY OPERATION CONDITIONS - Insignificant Activities . . . . . 37**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.3.1 General Provisions Relating to NSPS [326 IAC 12-1] [40 CFR 60, Subpart A]

D.3.2 Storage Vessels [326 IAC 12] [40 CFR 60, Subpart Kb]

D.3.3 Particulate Emission Limitations [40 CFR 52, Subpart P][326 IAC 6-3-2]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.3.4 Record Keeping Requirements

D.3.5 Reporting Requirements

Certification . . . . . 39

Emergency Occurrence Report . . . . . 40

Quarterly Report . . . . . 42

Quarterly Report . . . . . 43

Quarterly Deviation and Compliance Monitoring Report . . . . . 44

Attachment A . . . . . 46

## SECTION A

## SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ), and the City of Indianapolis, Office of Environmental Services (OES). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

---

The Permittee owns and operates a stationary petroleum distribution terminal.

Responsible Official:	District Manager or TT&M Manager
Source Address:	4955 Robison Road, Indianapolis, Indiana 46268
Mailing Address:	HESS-TT&M 539 S. Main Street, Findlay, Ohio 45840
General Source Phone Number:	(317) 244-9551
SIC Code:	5171
County Location:	Marion
Source Location Status:	Nonattainment for 8 hour ozone and PM 2.5; Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Minor Source under PSD and Emission Offset Minor Source, Section 112 of the Clean Air Act 1 of 28 Source Categories

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) gasoline loading rack with (3) three lanes, installed in 1992, with a maximum loading capacity of 136,000 gallons per hour, with VOC emissions controlled by one (1) carbon adsorber equipped with two (2) fixed beds as the primary control device, exhausting to stack S1, or one (1) trailer mounted vapor combustor as the backup control device, exhausting to stack S2.
- (b) One (1) storage tank, identified as Storage Tank 135-1 (formerly T1351), constructed in 1959, with a maximum capacity of 5,670,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with a geodesic dome and internal floating roof.
- (c) One (1) storage tank, identified as Storage Tank 135-2 (formerly T1352), constructed in 1976, with a maximum capacity of 5,670,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (d) One (1) storage tank, identified as Storage Tank 25-7 (formerly T257), constructed in 1955, with a maximum capacity of 1,050,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (e) One (1) storage tank, identified as Storage Tank 25-9 (formerly T259), constructed in 1959, with a maximum capacity of 1,050,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal and a secondary rim mounted wiper seal, and equipped with a geodesic dome in 2000.
- (f) One (1) storage tank, identified as Storage Tank 50-1 (formerly T501), constructed in 1991, with a maximum capacity of 2,184,000 gallons, storing gasoline, distillate, or neat ethanol,

and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.

- (g) One (1) storage tank, identified as Storage Tank 55-3 (formerly T502), constructed in 1991, with a maximum capacity of 2,100,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (h) One (1) storage tank, identified as Storage Tank 55-4 (formerly T554), constructed in 1948, with a maximum capacity of 2,310,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (i) One (1) storage tank, identified as Storage Tank 400-1 (formerly T4001), constructed in 1977, with a maximum capacity of 16,800,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal aluminum floating roof with a primary mechanical shoe seal in 1998.
- (j) One (1) storage tank, identified as Storage Tank 80-2 (formerly T802), constructed in 1952, with a maximum capacity of 3,360,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]  
[326 IAC 2-7-5(15)]

---

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Paved and unpaved roads. [326 IAC 6-4]
- (b) The following equipment related to manufacturing activities not resulting in the emissions of HAPs; brazing equipment, cutting torches, soldering equipment, welding equipment. [326 IAC 6-3-2]
- (c) Emission units with PM and PM10 emissions less than five (5) tons per year, SO<sub>2</sub>, NO<sub>x</sub>, and VOC emissions less than ten (10) tons per year, CO emissions less than twenty-five (25) tons per year, lead emissions less than two-tenths (0.2) tons per year, single HAP emissions less than one (1) ton per year, and combination of HAPs emissions less than two and a half (2.5) tons per year:
  - (1) One (1) storage tank, identified as O-7-1, constructed in 1992, with a maximum capacity of 294,000 gallons, storing ethanol, equipped with an internal floating roof tank. [326 IAC 12] [40 CFR 60, Subpart Kb]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

---

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

## SECTION B

## GENERAL CONDITIONS

### B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

### B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

### B.3 Enforceability [326 IAC 2-7-7]

(a) Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, OES, the United States Environmental Protection Agency (U.S. EPA), and by citizens in accordance with the Clean Air Act.

(b) The Indianapolis Air Pollution Control Board (IAPCB) has adopted by reference state rules listed in Attachment A of this permit. The version adopted by reference includes all amendments, additions and repeals filed with the Secretary of State through August 10, 1997 and published in the Indiana Register September 1, 1997, unless otherwise indicated in the adoption by reference. For the purposes of this permit, all state rules adopted by reference by the IAPCB are enforceable by OES using local enforcement procedures. Unless otherwise stated, all terms and conditions in this permit that are local requirements, including any provisions designed to limit the source's potential to emit, are enforceable by OES.

### B.4 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

### B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

### B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

(a) The Permittee shall furnish to IDEM, OAQ, and OES within a reasonable time, any information that IDEM, OAQ, and OES may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, and OES copies of records required to be kept by this permit.

(b) For information furnished by the Permittee to IDEM, OAQ and OES, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

### B.8 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]

(a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for:

- (1) Enforcement action;
  - (2) Permit termination, revocation and reissuance, or modification; or
  - (3) Denial of a permit renewal application.
- (b) Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act.
  - (c) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
  - (d) An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

B.9 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.10 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than April 15 of each year to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on

the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and OES on or before the date it is due.

- (c) The annual compliance certification report shall include the following:
- (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
  - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, and OES may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

**B.11 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]**  
**[326 IAC 1-6-3]**

---

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) within (90) days after issuance of this permit, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs, including any required record keeping, as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, and OES upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ, and OES. IDEM, OAQ, and OES may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for the unit within a reasonable time.

**B.12 Emergency Provisions [326 IAC 2-7-16]**

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the

affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and OES within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

IDEM, OAQ

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or

Telephone Number: 317-233-5674 (ask for Compliance Section)

Facsimile Number: 317-233-5967

OES

Telephone No.: 317-327-2234 (ask for Data Compliance)

Facsimile No.: 317-327-2274

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAQ, and OES may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, and OES by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.13 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, or OES shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
  - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;

- (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
  - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
  - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
  - (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, or OES has issued the modifications. [326 IAC 2-7-12(c)(7)]
  - (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, or OES has issued the modification. [326 IAC 2-7-12(b)(8)]

B.14 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
  - (1) incorporated as originally stated,
  - (2) revised, or
  - (3) deletedby this permit.
- (b) All previous registrations and permits are superseded by this permit.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

**B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination**  
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, or OES determines any of the following:
- (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, or OES to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, or OES at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, or OES may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

**B.17 Permit Renewal** [326 IAC 2-7-4]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and OES and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]

- (1) A timely renewal application is one that is:
  - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
  - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and OES on or before the date it is due.
- (2) If IDEM, OAQ, and OES upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-7-3]  
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, and OES takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, and OES any additional information identified as being needed to process the application.
- (d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]  
If IDEM, OAQ, and OES fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204  
  
and  
  
City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221  
  
Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

- (d) No permit amendment or modification is required for the addition, operation or removal of a nonroad engine, as defined in 40 CFR 89.2.

**B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]**  
**[326 IAC 2-7-12 (b)(2)]**

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

**B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]**

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b),

(c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, and OES in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

(b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) **Emission Trades [326 IAC 2-7-20(c)]**  
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) **Alternative Operating Scenarios [326 IAC 2-7-20(d)]**  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

**B.21 Source Modification Requirement [326 IAC 2-7-10.5]**

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

**B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1]**

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, and OES U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)] [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, and OES within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, and OES the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, I/M and Billing Section), to determine the appropriate permit fee.

## SECTION C

## SOURCE OPERATION CONDITIONS

Entire Source

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P] [326 IAC 6-3-2]
- (a) Pursuant to 40 CFR 52 Subpart P, particulate matter emissions from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
- (b) Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods of 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour. This condition is not federally enforceable.
- C.2 Opacity [326 IAC 5-1]
- Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:
- (a) Opacity shall not exceed an average of thirty percent (30%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.
- C.6 Operation of Equipment [326 IAC 2-7-6(6)]
- Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.
- C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]
- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326

IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:
    - (A) Asbestos removal or demolition start date;
    - (B) Removal or demolition contractor; or
    - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and renovation**  
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**

The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

### **Testing Requirements [326 IAC 2-7-6(1)]**

#### **C.8 Performance Testing [326 IAC 3-6]**

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ and OES not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, and OES if the source submits to IDEM, OAQ, and OES a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

### **Compliance Requirements [326 IAC 2-1.1-11]**

#### **C.9 Compliance Requirements [326 IAC 2-1.1-11]**

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

### **Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

#### **C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within thirty (30) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within thirty (30) days, the Permittee may extend the

compliance schedule related to the equipment for an additional thirty (30) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

in writing, prior to the end of the initial thirty (30) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

**C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

**C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

within ninety (90) days after the date of issuance of this permit.

The ERP does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) If the ERP is disapproved by IDEM, OAQ, and OES the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.
- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAQ, and OES that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the source must comply with the applicable requirements of 40 CFR 68.

C.14 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. If a Permittee is required to have an Operation, Maintenance and Monitoring (OMM) Plan under 40 CFR 60/63, such plans shall be deemed to satisfy the requirements for a CRP for those compliance monitoring conditions. A CRP shall be submitted to IDEM, OAQ and OES upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
  - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
  - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan to include such response steps taken.

The OMM Plan shall be submitted within the time frames specified by the applicable 40 CFR60/63 requirement.

- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
  - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan; or
  - (2) If none of the reasonable response steps listed in the Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.

- (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
- (4) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
  - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
  - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
  - (3) An automatic measurement was taken when the process was not operating.
  - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when, in accordance with Section D, response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]  
[326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

## **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

### **C.16 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]**

---

- (a) Pursuant to 326 IAC 2-6-3(b)(2), starting in 2005 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:
- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
  - (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management  
Technical Support and Modeling Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204

and

Office of Environmental Services  
Air Quality Management Section  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and OES on or before the date it is due.

### **C.17 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]**

---

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner or OES makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner or OES within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

### **C.18 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]**

---

- (a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
Indianapolis, Indiana 46204  
  
and  
  
City of Indianapolis  
Office of Environmental Services  
2700 South Belmont Avenue  
Indianapolis, Indiana 46221
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and OES on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).
- (e) Reporting periods are based on calendar years.

### **Stratospheric Ozone Protection**

#### **C.19 Compliance with 40 CFR 82 and 326 IAC 22-1**

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

## SECTION D.1

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]: Loading Rack

- (a) One (1) gasoline loading rack with (3) three lanes, installed in 1992, with a maximum loading capacity of 136,000 gallons per hour, with VOC emissions controlled by one (1) carbon adsorber equipped with two (2) fixed beds as the primary control device, exhausting to stack S1, or one (1) trailer mounted vapor combustor as the backup control device, exhausting to stack S2.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.1.1 General Provisions Relating to NSPS [326 IAC 12-1] [40 CFR 60, Subpart A]

The provisions of 40 CFR 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to the loading rack except when otherwise specified in 40 CFR 60, Subpart XX.

#### D.1.2 Volatile Organic Compound (VOC) [326 IAC 12] [40 CFR 60, Subpart XX]

Pursuant to 40 CFR 60, Subpart XX (Standards of Performance for Bulk Gasoline Terminals), the following requirements apply:

- (a) Each affected facility shall be equipped with a vapor collection system designed to collect the total organic compounds vapors displaced from tank trucks during product loading.
- (b) The emissions to the atmosphere from the vapor collection system due to the loading of liquid product into gasoline tank trucks are not to exceed thirty five (35) milligrams of total organic compounds per liter of gasoline loaded, except as noted in paragraph (c) of 40 CFR 60.502.
- (c) Each vapor collection system shall be designed to prevent any total organic compounds vapors collected at one loading rack from passing to another loading rack.
- (d) Loadings of liquid product into gasoline tank trucks shall be limited to vapor-tight gasoline tank trucks using the following procedures:
- (1) The Permittee shall obtain the vapor tightness documentation described in 40 CFR 60.505(b) for each gasoline tank truck which is to be loaded at the affected facility.
  - (2) The Permittee shall cross-check each tank identification number obtained in paragraph (e)(2) of 40 CFR 60.502 with the file of tank vapor tightness documentation within 2 weeks after the corresponding tank is loaded.
  - (3) The Permittee shall notify the owner or operator of each nonvapor-tight gasoline tank truck loaded at the affected facility within 3 weeks after the loading has occurred.
  - (4) The Permittee shall take steps assuring that the nonvapor-tight gasoline tank truck will not be reloaded at the affected facility until vapor tightness documentation for that tank is obtained.
  - (5) Alternate procedures to those described in paragraphs (e)(1) through (5) of 40 CFR 60.502 for limiting gasoline tank truck loadings may be used upon application to, and approval by, the IDEM, OAQ.

- (e) The Permittee shall act to assure that loadings of gasoline tank trucks at the affected facility are made only into tanks equipped with vapor collection equipment that is compatible with the terminal's vapor collection system.
- (f) The Permittee shall act to assure that the terminal's and the tank truck's vapor collection systems are connected during each loading of a gasoline tank truck at the affected facility. Examples of actions to accomplish this include training drivers in the hookup procedures and posting visible reminder signs at the affected loading racks.
- (g) The vapor collection and liquid loading equipment shall be designed and operated to prevent gauge pressure in the delivery tank from exceeding 4,500 pascals (450 mm of water) during product loading. This level is not to be exceeded when measured by the procedures specified in 40 CFR 60.503(d).
- (h) No pressure-vacuum vent in the bulk gasoline terminal's vapor collection system shall begin to open at a system pressure less than 4,500 pascals (450 mm of water).
- (i) Each calendar month, the vapor collection system, the vapor processing system, and each loading rack handling gasoline shall be inspected during the loading of gasoline tank trucks for total organic compounds liquid or vapor leaks. For purposes of this paragraph, detection methods incorporating sight, sound, or smell are acceptable.

D.1.3 Hazardous Air Pollutants (HAPs) [326 IAC 20] [40 CFR 63, Subpart R]

The throughput of normal gasoline and oxygenated/reformulated gasoline without MTBE to the loading rack shall not exceed 560,000,000 gallons per twelve (12) consecutive month period with compliance determined at the end of each month. The single HAP emissions from the loading rack shall not exceed 0.66 pounds per hour and the emissions of any combination of HAPs emitted from the loading rack shall not exceed 2.13 pounds per hour. These limits are equivalent to combination HAP emissions of 9.34 tons per twelve (12) consecutive month period from the loading rack and single HAP emissions of 2.87 tons per twelve (12) consecutive month period from the loading rack.

The loading rack currently does not process gasoline with MTBE. Therefore, compliance with this limit and the limit in Condition D.2.4 ensures that source wide emissions of a single HAP remain less than ten (10) tons per twelve (12) consecutive month period and emissions of any combination of HAPs remain less than twenty-five (25) tons per twelve (12) consecutive month period. This renders the requirements of 40 CFR 63, Subpart R not applicable.

Any change or modification which allows the loading rack to process gasoline with MTBE must be approved by the Office of Air Quality and OES before any such change may occur.

D.1.4 Volatile Organic Compounds (VOC) [326 IAC 8-4-4]

Pursuant to 326 IAC 8-4-4 (Petroleum Sources - Bulk Gasoline Terminals), no owner or operator of a bulk gasoline terminal shall permit the loading of gasoline into any transport, excluding railroad tank cars, or barges, unless:

- (a) The bulk gasoline terminal is equipped with a vapor control system, in good working order, in operation and consisting of one of the following:
  - (1) An adsorber or condensation system which processes and recovers vapors and gases from the equipment being controlled, releasing no more than 80 mg/l of VOC to the atmosphere.
  - (2) A vapor collection system which directs all vapors to a fuel gas system or incinerator.
  - (3) An approved control system, demonstrated to have control efficiency equivalent to or greater than clause (1) above.

- (b) Displaced vapors and gases are vented only to the vapor control system.
- (c) A means is provided to prevent liquid drainage from the loading device when it is not in use or to accomplish complete drainage before the loading device is disconnected.
- (d) All loading and vapor lines are equipped with fittings which make vapor-tight connections and which will be closed upon disconnection.
- (e) If employees of the owner of the bulk gasoline terminal are not present during loading, it shall be the responsibility of the owner of the transport to make certain the vapor control system is attached to the transport. The owner of the terminal shall take all reasonable steps to insure that owners of transports loading at the terminal during unsupervised times comply with this section.

#### D.1.5 Leaks from Transports and Vapor Collection Systems [326 IAC 8-4-9]

Pursuant to 326 IAC 8-4-9 (Petroleum Sources - Leaks from Transports and Vapor Collection Systems; Records):

- (a) No person shall allow a gasoline transport that is subject to this rule and that has a capacity of two thousand (2,000) gallons or more to be filled or emptied unless the gasoline transport completes the following:
  - (1) Annual leak detection testing before the end of the twelfth calendar month following the previous year's test, according to test procedures contained in 40 CFR 63.425(e), as follows:
    - (A) Conduct the pressure and vacuum tests for the transport's cargo tank using a time period of five (5) minutes. The initial pressure for the pressure test shall be four hundred sixty (460) millimeters H<sub>2</sub>O (eighteen (18) inches H<sub>2</sub>O) gauge. The initial vacuum for the vacuum test shall be one hundred fifty (150) millimeters H<sub>2</sub>O (six (6) inches H<sub>2</sub>O) gauge. The maximum allowable pressure or vacuum change is twenty-five (25) millimeters H<sub>2</sub>O (one (1) inch H<sub>2</sub>O) in five (5) minutes.
    - (B) Conduct the pressure test of the cargo tank's internal vapor valve as follows:
      - (i) After completing the test under clause (A), use the procedures in 40 CFR 60, Appendix A, Method 27 to repressurize the tank to four hundred sixty (460) millimeters H<sub>2</sub>O (eighteen (18) inches H<sub>2</sub>O) gauge. Close the transport's internal vapor valve or valves, thereby isolating the vapor return line and manifold from the tank.
      - (ii) Relieve the pressure in the vapor return line to atmospheric pressure, then reseal the line. After five (5) minutes, record the gauge pressure in the vapor return line and manifold. The maximum allowable five (5) minute pressure increase is one hundred thirty (130) millimeters H<sub>2</sub>O (five (5) inches H<sub>2</sub>O).
  - (2) Repairs by the gasoline transport owner or operator, if the transport does not meet the criteria of subdivision (1), and retesting to prove compliance with the criteria of subdivision (1).
- (b) The annual test data remain valid until the end of the twelfth calendar month following the test. The owner of the gasoline transport shall be responsible for compliance with subsection (a) and shall provide the owner of the loading facility with the most recent valid modified 40 CFR 60, Appendix A, Method 27 test results upon request. The owner of the loading facility shall take all reasonable steps, including reviewing the test date and tester's signature, to ensure that gasoline transports loading at its facility comply with subsection (a).

- (c) The Permittee shall:
- (1) Design and operate the applicable system and the gasoline loading equipment in a manner that prevents:
    - (A) Gauge pressure from exceeding four thousand five hundred (4,500) pascals (eighteen (18) inches of H<sub>2</sub>O) and a vacuum from exceeding one thousand five hundred (1,500) Pascals (six (6) inches of H<sub>2</sub>O) in the gasoline transport.
    - (B) Except for sources subject to 40 CFR 60.503(b) or 40 CFR 63.425 requirements, a reading equal to or greater than twenty-one thousand (21,000) parts per million as propane, from all points on the perimeter of a potential leak source when measured by the method reference in 40 CFR 60, Appendix A, Method 21, or an equivalent procedure approved by the commissioner during loading or unloading operations at gasoline dispensing facilities, bulk plants, and bulk terminals.
    - (C) Avoidable visible liquid leaks during loading or unloading operations at gasoline dispensing facilities, bulk plants, and bulk terminals.
  - (2) Within fifteen (15) days, repair and retest a vapor balance, collection, or control system that exceeds the limits in subdivision (1).
- (d) The department may, at any time, monitor a gasoline transport, vapor balance, or vapor control system to confirm continuing compliance with (a) and (c).
- (e) If the commissioner allows alternative test procedures, such method shall be submitted to the U.S. EPA as a SIP revision.
- (f) During compliance tests conducted under 326 IAC 3-6 (Stack Testing), each vapor balance or control system shall be tested applying the standards described in subsection (c)(1)(B). Testers shall use 40 CFR 60, Appendix A, Method 21 to determine if there are any leaks from hatches and the flanges of the gasoline transports. If any leak is detected, the transport cannot be sued for the capacity of the compliance test of the bulk terminal. The threshold for leaks shall be ten thousand (10,000) parts per million methane.

D.1.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

**Compliance Determination Requirements**

D.1.7 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAP)

In order to comply with Conditions D.1.2, D.1.3, D.1.4, and D.1.5, the carbon adsorber or vapor combustor for VOC and HAP control shall be in operation at all times when loading operations are taking place.

D.1.8 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) During the period between 30 and 36 months after issuance of this permit, in order to demonstrate compliance with single HAP emission limit of 0.66 pounds per hour and the combination HAP emission limit of 2.13 pounds per hour in Condition D.1.3, the Permittee shall perform HAP testing on the carbon adsorber utilizing methods as approved by the Commissioner. Testing shall be conducted in accordance with Section C- Performance Testing.
- (b) To demonstrate compliance with Condition D.1.5, the Permittee shall perform testing required in Condition D.1.5.

- (c) If the commissioner allows alternative test procedures in Condition D.1.5, such methods shall be submitted to the U.S. EPA as a SIP revision.

### **Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

#### **D.1.9 Monitoring**

- (a) When operating the carbon adsorber to control VOC and HAP emissions during loading at the truck loading rack, the Permittee shall monitor and continuously record the carbon bed pressure on a recording device indicating the regeneration cycle. The carbon bed shall be regenerated once every fifteen (15) minutes during active loading or once every five (5) tanker trucks loaded during slack periods when the carbon adsorber is in idle mode.

The Permittee shall operate and maintain an automated system to monitor the number of trucks loaded since the last regeneration cycle of the carbon bed. Whenever the carbon adsorber is in idle mode, the automated system shall shut down the loading rack if the carbon adsorber fails to go through a regeneration cycle after loading five (5) tanker trucks.

Each scheduled workday, the Permittee shall conduct an inspection of the carbon bed pressure records for any deviations in the carbon bed regeneration cycle time mentioned above since the last daily inspection. The Permittee shall maintain an automated system which prevents the loading of gasoline and alerts the facility's operators when the carbon bed regeneration cycle time exceeds fifteen (15) minutes. The Compliance Response Plan for this unit shall contain troubleshooting contingency and corrective actions for when the regeneration cycle is outside the above mentioned range for any one (1) reading. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

- (b) When operating the vapor combustor (flare) to control VOC and HAP emissions, the Permittee shall install and maintain a monitor to detect the presence of a flame at the flare tip. The presence of a flame at the flare tip shall be monitored at all times when the vapors are being vented to the flare. The monitor shall be equipped with an automatic alarm which activates when the presence of a flame is not detected during periods when gasoline vapors are being vented to the flare. The Compliance Response Plan for this unit shall contain troubleshooting contingency and corrective actions for when the presence of a flame is not detected. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

#### **D.1.10 Record Keeping Requirements**

- (a) To document compliance with Condition D.1.2, the Permittee shall maintain records of the following:
- (1) The tank identification number of each gasoline tank truck that is loaded at the affected facility.
  - (2) The results of the inspections required under Condition D.1.2. The records shall include each detected leak and its respective repair date.
- (b) To document compliance with Condition D.1.3, the Permittee shall maintain records of the gasoline and oxygenated/reformulated gasoline without MTBE throughput to the loading rack.

- (c) To document compliance with Condition D.1.5, the Permittee shall maintain records of all certification testing. The records shall identify the following:
- (1) The vapor balance, vapor collection, or vapor control system;
  - (2) The date of the test and, if applicable, retest; and
  - (3) The results of the test and, if applicable, retest.

The records shall be maintained in a legible, readily available condition for at least two (2) years after the date the testing and, if applicable, retesting were completed.

- (d) To document compliance with Condition D.1.5, the owner or operator of a gasoline transport shall keep a legible copy of the transport's most recent valid annual modified 40 CFR 60, Appendix A, Method 27 test either in the cab of the transport or affixed to the transport trailer. The test record shall identify the following:
- (1) The gasoline transport.
  - (2) The type and date of the test and, if applicable, date of retest.
  - (3) The test methods, test data, and results certified to be true, accurate, and in compliance with this regulation by the person who performs the test.

This copy shall be made available immediately upon request to the department and to the owner of the loading facility for inspection and review. The department shall be allowed to make copies of the test results.

- (e) To document compliance with Condition D.1.5, the Permittee shall maintain records of the following:
- (1) Certification testing required under Condition D.1.5(e).
  - (2) Test required under Condition D.1.5(f).
- (f) When the carbon adsorber is in operation, to document compliance with Condition D.1.9(a), the Permittee shall maintain the continuous recording of the carbon bed pressure and records of all corrective actions implemented.
- (g) When the vapor combustor is in operation, to document compliance with Condition D.1.9(b), the Permittee shall maintain records of the date and time of an automated alarm and records of all corrective actions implemented.
- (h) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.1.11 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.3 shall be submitted to the addresses listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

## SECTION D.2

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]: Storage Tanks

- (b) One (1) storage tank, identified as Storage Tank 135-1 (formerly T1351), constructed in 1959, with a maximum capacity of 5,670,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with a geodesic dome and internal floating roof.
- (c) One (1) storage tank, identified as Storage Tank 135-2 (formerly T1352), constructed in 1976, with a maximum capacity of 5,670,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (d) One (1) storage tank, identified as Storage Tank 25-7 (formerly T257), constructed in 1955, with a maximum capacity of 1,050,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (e) One (1) storage tank, identified as Storage Tank 25-9 (formerly T259), constructed in 1959, with a maximum capacity of 1,050,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal and a secondary rim mounted wiper seal, and equipped with a geodesic dome in 2000.
- (f) One (1) storage tank, identified as Storage Tank 50-1 (formerly T501), constructed in 1991, with a maximum capacity of 2,184,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (g) One (1) storage tank, identified as Storage Tank 55-3 (formerly T502), constructed in 1991, with a maximum capacity of 2,100,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (h) One (1) storage tank, identified as Storage Tank 55-4 (formerly T554), constructed in 1948, with a maximum capacity of 2,310,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.
- (i) One (1) storage tank, identified as Storage Tank 400-1 (formerly T4001), constructed in 1977, with a maximum capacity of 16,800,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal aluminum floating roof with a primary mechanical shoe seal in 1998.
- (j) One (1) storage tank, identified as Storage Tank 80-2 (formerly T802), constructed in 1952, with a maximum capacity of 3,360,000 gallons, storing gasoline, distillate, or neat ethanol, and equipped with an internal steel welded floating roof with a primary mechanical shoe seal.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.2.1 General Provisions Relating to NSPS [326 IAC 12-1] [40 CFR 60, Subpart A]

- (a) The provisions of 40 CFR 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to storage tanks 135-2 and 400-1 except when otherwise specified in 40 CFR 60, Subpart K.
- (b) The provisions of 40 CFR 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to storage tanks 50-1 and 55-3 except when otherwise specified in 40 CFR 60, Subpart Kb.

D.2.2 Storage Vessels [326 IAC 12] [40 CFR 60, Subpart K]

Pursuant to 40 CFR 60.112(a)(1), storage tanks 135-2 and 400-1 shall be equipped with a floating roof.

D.2.3 Storage Vessels [326 IAC 12] [40 CFR 60, Subpart Kb]

Pursuant to 40 CFR 60.112b(a), storage tanks 50-1, 55-3 and 135-1 shall be equipped with a fixed roof in combination with an internal floating roof meeting the following:

- (a) The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage tank is completely emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.
- (b) Each internal floating roof shall be equipped with a closure seal, or seals, to close the space between the rood edge and tank wall unless the source has been retrofitted with an equally effective control which has been approved.
- (c) Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
- (d) Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e.; no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- (e) Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.
- (f) Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.
- (g) Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- (h) Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- (i) Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

D.2.4 Hazardous Air Pollutants (HAPs) [326 IAC 20] [40 CFR 63, Subpart R]

The throughput of normal gasoline and oxygenated/reformulated gasoline without MTBE to the storage tanks shall not exceed 900,000,000 gallons per twelve (12) consecutive month period with compliance determined at the end of each month. This limit is equivalent to single HAP emissions of 1.09 tons per twelve (12) consecutive month period and combination HAP emissions of 3.53 tons per twelve (12) consecutive month period from the tanks.

The storage tanks currently do not store gasoline with MTBE. Therefore, compliance with this limit and the limit in Condition D.1.3 ensures that source wide emissions of a single HAP remain less than ten (10) tons per twelve (12) consecutive month period and emissions of any combination of HAPs remain less than twenty-five (25) tons per twelve (12) consecutive month period. This renders the requirements of 40 CFR 63, Subpart R not applicable.

Any change or modification which results in the storage tanks storing gasoline with MTBE must be approved by the Office of Air Quality and OES before any such change may occur.

#### D.2.5 Storage Vessels [326 IAC 8-4-3]

- (a) Pursuant to 326 IAC 8-4-3(b), the owner or operator of storage tanks 135-2, 25-7, 25-9, 50-1, 55-3, 55-4, 400-1, and 80-2 shall permit the use of such facility unless:
- (1) The facility has been retrofitted with an internal floating roof equipped with a closure seal, or seals, to close the space between the roof edge and tank wall unless the source has been retrofitted with equally effective alternative control which has been approved.
  - (2) The facility is maintained such that there are no visible holes, tears, or other openings in the seal or any seal fabric or materials.
  - (3) All openings, except stub drains, are equipped with covers, lids, or seals such that:
    - (A) The cover, lid, or seal is in the closed position at all times except when in actual use;
    - (B) Automatic bleeder vents are closed at all times except when the roof is floated off or landed on the roof leg supports;
    - (C) Rim vents, if provided, are set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting.
- (b) Pursuant to 326 IAC 8-9-4(c), the owner or operator of external floating roof storage tanks shall not permit the use of such facility unless:
- (1) The facility has been fitted with:
    - (A) A continuous secondary seal extending from the floating roof to the tank wall (rim-mounted secondary seal); or
    - (B) A closure or other device approved by the commissioner which is equally effective.
  - (2) All seal closure devices meet the following requirements:
    - (A) There are no visible holes, tears, or other openings in the seal(s) or seal fabric;
    - (B) The seal(s) are intact and uniformly in place around the circumference of the floating roof between the floating roof and the tank wall.
    - (C) For vapor mounted primary seals, the accumulated gap area around the circumference of the secondary seal where a gap exceeding one-eighth ( $\frac{1}{8}$ ) inch exists between the secondary seal and the tank wall shall not exceed 1.0 square inch per foot of tank diameter. There shall be no gaps exceeding one-half ( $\frac{1}{2}$ ) inch between the secondary seal and the tank wall of welded tanks and no gaps exceeding one (1) inch between the secondary seal and the tank wall of riveted tanks.
  - (3) All openings in the external floating roof, except for automatic bleeder vents, rim space vents, and leg sleeves, are:
    - (A) Equipped with covers, seals, or lids in the closed position except when the openings are in actual use; and

- (B) Equipped with projections into the tank which remain below the liquid surface at all times.
- (4) Automatic bleeder vents are closed at all times except when the roof is floated off or landed on the roof leg supports;
- (5) Rim vents are set to open when the roof is being floated off the leg supports or at the manufacturer's recommended setting; and
- (6) Emergency roof drains are provided with slotted membrane fabric covers or equivalent covers which cover at least ninety percent (90%) of the area of the opening.

#### D.2.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities.

### **Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

#### D.2.7 Monitoring [326 IAC 12] [40 CFR 60, Subpart Kb]

Pursuant to 40 CFR 60.113b(a), the owner or operator of storage tanks 50-1 and 55-3 shall:

- (a) Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to the filling of the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the Permittee shall repair the items before filling the storage vessel.
- (b) Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the Permittee shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in 40 CFR 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions that the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
- (c) Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), gaskets, slotted membranes, and sleeve seals (if any) each time the storage vessel is emptied or degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the Permittee shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years.
- (d) Notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraph (a) and (c) of this section to afford the Administrator the opportunity to have an observer present. If the inspection required by (c) of this section is not planned and the Permittee could not have known about the inspection 30 days in advance of refilling the tank, the Permittee shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the

inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to refilling.

## **Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

### **D.2.8 Record Keeping Requirements**

- (a) Pursuant to 40 CFR 60.113(a), the Permittee shall maintain a record of the petroleum liquid stored in storage tanks 135-2 and 400-1, the period of storage, and the maximum true vapor pressure of that liquid during the respective storage period.
- (b) Pursuant to 40 CFR 60.115b(a), the Permittee shall:
  - (1) Keep a record of each inspection performed as required under Condition D.2.7. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed conditions of each component of the control equipment (seals, internal floating roof, and fittings).
  - (2) If any of the conditions described in 40 CFR 60.113(a)(2) and Condition D.2.7(b) are detected during the annual visual inspection required by 40 CFR 60.113(a)(2) and Condition D.2.7(b), a report shall be furnished to the administrator within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
- (c) Pursuant to 40 CFR 60.116b, the Permittee shall maintain records showing the dimensions of storage tanks 50-1 and 55-3 and an analysis showing the capacity of each storage vessel, the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.
- (d) To document compliance with Condition D.2.4, the Permittee shall maintain records of the gasoline and oxygenated/reformulated gasoline without MTBE throughput to the tanks.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

### **D.2.9 Reporting Requirements**

A quarterly summary of the information to document compliance with Condition D.2.4 shall be submitted to the addresses listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

### SECTION D.3

### FACILITY OPERATION CONDITIONS

#### Facility Description [326 IAC 2-7-5(15)]: Insignificant Activities

- (a) Paved and unpaved roads. [326 IAC 6-4]
- (b) The following equipment related to manufacturing activities not resulting in the emissions of HAPs; brazing equipment, cutting torches, soldering equipment, welding equipment. [326 IAC 6-3-2]
- (c) Emission units with PM and PM10 emissions less than five (5) tons per year, SO<sub>2</sub>, NO<sub>x</sub>, and VOC emissions less than ten (10) tons per year, CO emissions less than twenty-five (25) tons per year, lead emissions less than two-tenths (0.2) tons per year, single HAP emissions less than one (1) ton per year, and combination of HAPs emissions less than two and a half (2.5) tons per year:
  - (1) One (1) storage tank, identified as O-7-1, constructed in 1992, with a maximum capacity of 294,000 gallons, storing ethanol, equipped with an internal floating roof tank. [326 IAC 12] [40 CFR 60, Subpart Kb]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

#### Emission Limitations and Standards [326 IAC 2-7-5(1)]

##### D.3.1 General Provisions Relating to NSPS [326 IAC 12-1] [40 CFR 60, Subpart A]

The provisions of 40 CFR 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to tank O-7-1 except when otherwise specified in 40 CFR 60, Subpart Kb.

##### D.3.2 Storage Vessels [326 IAC 12] [40 CFR 60, Subpart Kb]

Pursuant to 40 CFR 60, Subpart Kb, there are no limits applicable to tank O-7-1; however, the source must comply with the applicable record keeping requirements specified in Condition D.3.4 of this section.

##### D.3.3 Particulate Emission Limitations [40 CFR 52 Subpart P] [326 IAC 6-3-2]

- (a) Pursuant to 40 CFR 52 Subpart P, the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which already has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
- (b) Pursuant to 326 IAC 6-3-2(e)(2), the allowable particulate emissions rate from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods of 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour. This condition is not federally enforceable.

#### Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

##### D.3.4 Record Keeping Requirements

- (a) Pursuant to 40 CFR 60, Subpart Kb, the Permittee shall maintain a record showing the dimension of tank O-7-1 and an analysis showing the capacity of the storage vessel.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

##### D.3.5 Reporting Requirements

Pursuant to 40 CFR 60, Subpart Kb, the Permittee shall notify the Administrator when the maximum true vapor pressure of the liquid exceeds 5.2kPa.

Marathon Petroleum Company LLC  
Indianapolis, Indiana  
Permit Reviewer: ERG/AO

First Administrative Amendment  
097-21222-00159  
Modified by: TLE

Page 38 of 47  
T097-16068-00159

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
and  
Indianapolis Office of Environmental Services  
AIR QUALITY MANAGEMENT SECTION  
DATA COMPLIANCE**

**PART 70 OPERATING PERMIT  
CERTIFICATION**

Source Name: Marathon Petroleum Company LLC  
Source Address: 4955 Robison Road, Indianapolis, Indiana 46268  
Mailing Address: HESS-TT&M 539 S. Main Street, Findlay, Ohio 45840  
Part 70 Permit No.: T097-16068-00159

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify) \_\_\_\_\_
- Report (specify) \_\_\_\_\_
- Notification (specify) \_\_\_\_\_
- Affidavit (specify) \_\_\_\_\_
- Other (specify) \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE BRANCH  
100 North Senate Avenue  
Indianapolis, Indiana 46204  
Phone: 317-233-5674  
Fax: 317-233-5967  
and  
INDIANAPOLIS OFFICE OF ENVIRONMENTAL SERVICES  
AIR QUALITY MANAGEMENT SECTION  
2700 South Belmont Ave.  
Indianapolis, Indiana 46221  
Phone: 317-327-2234  
Fax: 317-327-2274**

**PART 70 OPERATING PERMIT  
EMERGENCY OCCURRENCE REPORT**

Source Name: Marathon Petroleum Company LLC  
Source Address: 4955 Robison Road, Indianapolis, Indiana 46268  
Mailing Address: HESS-TT&M 539 S. Main Street, Findlay, Ohio 45840  
Part 70 Permit No.: T097-16068-00159

**This form consists of 2 pages**

**Page 1 of 2**

- 9** This is an emergency as defined in 326 IAC 2-7-1(12)
- The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
  - The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency?    Y    N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 Compliance Data Section  
 and  
 Indianapolis Office of Environmental Services  
 AIR QUALITY MANAGEMENT SECTION  
 DATA COMPLIANCE**

**Part 70 Quarterly Report**

Source Name: Marathon Petroleum Company LLC  
 Source Address: 4955 Robison Road, Indianapolis, Indiana 46268  
 Mailing Address: HESS-TT&M 539 S. Main Street, Findlay, Ohio 45840  
 Part 70 Permit No.: T097-16068-00159  
 Facility: Loading Rack  
 Parameter: Gasoline and oxygenated/reformulated gasoline without MTBE throughput  
 Limit: The throughput of normal gasoline and oxygenated/reformulated gasoline without MTBE to the loading rack shall not exceed 560,000,000 gallons per twelve (12) consecutive month period with compliance determined at the end of each month.

YEAR: \_\_\_\_\_

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.  
 Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 Compliance Data Section  
 and  
 Indianapolis Office of Environmental Services  
 AIR QUALITY MANAGEMENT SECTION  
 DATA COMPLIANCE**

**Part 70 Quarterly Report**

Source Name: Marathon Petroleum Company LLC  
 Source Address: 4955 Robison Road, Indianapolis, Indiana 46268  
 Mailing Address: HESS-TT&M 539 S. Main Street, Findlay, Ohio 45840  
 Part 70 Permit No.: T097-16068-00159  
 Facility: Tanks  
 Parameter: Gasoline and oxygenated/reformulated gasoline without MTBE throughput  
 Limit: The throughput of normal gasoline and oxygenated/reformulated gasoline without MTBE to the storage tanks shall not exceed 900,000,000 gallons per twelve (12) consecutive month period with compliance determined at the end of each month.

YEAR: \_\_\_\_\_

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.  
 Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
Compliance Data Section  
and  
Indianapolis Office of Environmental Services  
AIR QUALITY MANAGEMENT SECTION  
DATA COMPLIANCE**

**PART 70 OPERATING PERMIT  
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Marathon Petroleum Company LLC  
Source Address: 4955 Robison Road, Indianapolis, Indiana 46268  
Mailing Address: HESS-TT&M 539 S. Main Street, Findlay, Ohio 45840  
Part 70 Permit No.: T097-16068-00159

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

Page 1 of 2

This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

Form Completed By: \_\_\_\_\_

Title/Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

## Attachment A

The following state rules have been adopted by reference by the Indianapolis Air Pollutant Control Board and are enforceable by Indianapolis Office of Environmental Services (OES) using local enforcement procedures.

- (1) 326 IAC 1-1 through 1-1-3 and 1-1-5;
- (2) 326 IAC 2-1 through 1-2-91 (In addition, the IAPCB has adopted several local definitions);
- (3) 326 IAC 1-3-1 through 1-3-4;
- (4) 326 IAC 1-4-1 (The IAPCB added to the adoption by reference a citation to 61 CFR 58482 (November 15, 1996));
- (5) 326 IAC 1-5-1 through 1-5-5;
- (6) 326 IAC 1-6-1 through 1-6-6;
- (7) 326 IAC 1-7-1 through 1-7-5;
- (8) 326 IAC 2-3-1 through 2-3-5;
- (9) 326 IAC 2-4-1 through 2-4-6;
- (10) 326 IAC 2-6-1 through 2-6-4;
- (11) 326 IAC 2-7-1 through 2-7-18, 2-7-20 through 2-7-25;
- (12) 326 IAC 2-8-1 through 2-8-15, 2-8-17 through 2-8-10;
- (13) 326 IAC 2-9-1 through 2-9-14;
- (14) 326 IAC 2-10-1 through 2-20-5 (The IAPCB adoption adds the language "state or local" immediately after the word "federal" in 326 IAC 2-10-1);
- (15) 326 IAC 2-11-1, 2-11-3 and 2-11-4 (The IAPCB adoption adds the language "federal, state or local" immediately after the word "by" in 326 IAC 2-11-1);
- (16) 326 IAC 3-1.1-1 through 3-1.1-5;
- (17) 326 IAC 3-2.1-1 through 3-2.1-5;
- (18) 326 IAC 3-3-1 through 3-3-5;
- (19) 326 IAC 4-2-1 through 4-2-2;
- (20) 326 IAC 5-1-1(a), (b), and (c)(5), 5-1-2(1), (2)(A), (2)(C), (4), 5-1-3 through 5-1-5, 5-1-7;
- (21) 326 IAC 7-1.1-1 and 7-1.1-2;
- (22) 326 IAC 7-2-1;
- (23) 326 IAC 7-3-1 and 7-3-2;
- (24) 326 IAC 7-4-2(28) through (31) (Instead of adopting by reference 7-4-2(1) through (27), the IAPCB regulation substitutes the same requirements listed in a format in which the companies are alphabetized and emission points known to no longer exist have been deleted);
- (25) 326 IAC 8-1-0.5 except (b), 8-1-1 through 8-1-2, 8-1-3 except (c), (g) and (i), 8-1-5 through 8-1-12;
- (26) 326 IAC 8-2-1 through 8-2-12 (The IAPCB adoption by reference of 8-2-5 adds additional language specific to Zimmer Paper Products, Incorporated as subpart (c);
- (27) 326 IAC 8-3-1 through 8-3-7;
- (28) 326 IAC 8-4-1 through 8-4-5, 8-4-6(a)(6), (a)(8) and (a)(14) and 8-4-6(b)(1), (b)(3) and 8-4-6(c) (In place of 8-4-6(b)(2), which was not adopted, the IAPCB adopted language requiring a pressure relief valve set to release at no less than four and eight-tenths (4.8) Kilo Pascals (seven-tenths (0.7) pounds per square inch)), 8-4-7 except (e), 8-4-4 and 8-4-9;
- (29) 326 IAC 8-5-4 through 8-5-4, 8-5-5 except (a)(3) and (d)(3);
- (30) 326 IAC 8-6-1 and 8-6-2;
- (31) 326 IAC 9-1-1 through 9-1-2;
- (32) 326 IAC 11-1-1 through 11-1-2;
- (33) 326 IAC 11-2-1 through 11-2-3;

- (34) 326 IAC 11-3-1 through 11-3-6;
- (35) 326 IAC 14-1-1 through 14-1-4;
- (36) 326 IAC 14-2-1 except 40 CFR 61.145;
- (37) 326 IAC 14-3-1;
- (38) 326 IAC 14-4-1;
- (39) 326 IAC 14-5-1;
- (40) 326 IAC 14-6-1;
- (41) 326 IAC 14-7-1;
- (42) 326 IAC 14-8-1 through 14-8-5;
- (43) 326 IAC 15-1-1, 15-1-2(a)(1), (a)(2) and (a)(8), 15-1-3 and 15-1-4;
- (44) 326 IAC 20-1-1 through 20-1-4 (In 20-1-3(b)(2), the adoption states that "permitting authority" means the commissioner of IDEM or the administrator of OES, whichever is applicable);
- (45) 326 IAC 20-2-1;
- (46) 326 IAC 20-3-1;
- (47) 326 IAC 20-4-1;
- (48) 326 IAC 20-5-1;
- (49) 326 IAC 20-6-1;
- (50) 326 IAC 20-7-1;
- (51) 326 IAC 20-8-1;
- (52) 326 IAC 20-9-1;
- (53) 326 IAC 20-14-1;
- (54) 326 IAC 20-15-1;
- (55) 326 IAC 20-16-1;
- (56) 326 IAC 20-17-1;
- (57) 326 IAC 20-18-1;
- (58) 326 IAC 20-19-1;
- (59) 326 IAC 20-20-1;
- (60) 326 IAC 20-21-1;
- (61) 326 IAC 21-1-1 (The adoption states that "or the administrator of OES" is added in (b)); and
- (62) 326 IAC 22-1-1 (The adoption states that "or the administrator of OES" is added in (b)).