



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

TO: Interested Parties / Applicant
DATE: March 10, 2006
RE: Flexcel / 037-22586-00048
FROM: Paul Dubenetzky
Chief, Permits Branch
Office of Air Quality

Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days from the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER-AM.dot 1/10/05



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We make Indiana a cleaner, healthier place to live.

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

Ron Rothgerber
flexcel – Jasper 11th Avenue
340 East 11th Avenue
Jasper, Indiana 47549

March 10, 2006

Re: 037-22586-00048
Third Administrative Amendment to
Part 70 Permit 037-6953-00048

Dear Mr. Rothgerber:

flexcel - Jasper 11th Avenue was issued a permit on February 4, 2003 for a stationary wood office furniture manufacturing plant. A letter requesting the replacement of two existing insignificant dust collection units with two new insignificant dust collection units was received on January 13, 2006. Pursuant to the provisions of 326 IAC 2-7-11, the permit is hereby administratively amended as follows:

Two (2) existing Moldow dust collection units, identified as MBH-1 and MBH-2, will be replaced with two (2) new Torit dust collection units, identified as TBH-1 and TBH-2. A third closed cap cyclone will be added (CY-3) and it will exhaust to stack TBH-3. The new dust collection units will collect particulate emissions from the same woodworking emission units that the existing dust collection units now control. These new dust collection units are deemed an insignificant activity under 326 IAC 2-7-1(21)(G)(xxix) because the units have an air exhaust rate less than 125,000 cubic feet per minute and an outlet grain loading less than 0.003 grains per standard cubic foot of exhaust air. There is no increase in potential to emit due to this modification. Pursuant to the provisions of 326 IAC 2-7-10, the permit is hereby administratively amended as follows:

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Woodworking facilities equipped with a baghouse with an air flow rate no greater than 125,000 cubic feet of air per minute and a grain loading no greater than 0.003 grains per dry standard cubic feet of outlet air: Three (3) woodworking operations, identified as EU-1, EU-2, and EU-3, equipped with three baghouses ~~MBH-1, MBH-2, and TBH-3~~, **TBH-1, TBH-2, and TBH-3**, and ~~two~~**three** cyclones, identified as ~~CY-1 and, CY-2, and CY-3~~, **CY-1, CY-2, and CY-3**, exhausting to stacks ~~MBH-1, MBH-2, and TBH-3~~, **TBH-1, TBH-2, and TBH-3**. [326 IAC 2-7-1(21)(G)(xxix)]

...

SECTION D.3

FACILITY OPERATION CONDITIONS

<p>Facility Description [326 IAC 2-7-5(15)]: Insignificant Woodworking operations:</p> <p>(a) Woodworking facilities equipped with a baghouse with an air flow rate no greater than 125,000 cubic feet of air per minute and a grain loading no greater than 0.003 grains per dry standard cubic feet of outlet air: Three (3) woodworking operations, identified as EU-1, EU-2, and EU-3, equipped with three baghouses MBH-1, MBH-2, and MBH-3, MBH-1, MBH-2, and MBH-3, and twothree cyclones, identified as CY-1 and CY-2, CY-1, CY-2, and CY-3, exhausting to stacks MBH-1, MBH-2, and MBH-3, MBH-1, MBH-2, and MBH-3. [326 IAC 2-7-1(21)(G)(xxix)]</p> <p>(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)</p>

Upon further review, IDEM, OAQ has decided to make the following revision to the permit (bolded language has been added, the language with a line through it has been deleted).

1. The mailing address for IDEM, OAQ has been changed throughout the permit.

Indiana Department of Environmental Management
100 North Senate Avenue, ~~P.O. Box 6015~~
Indianapolis, Indiana ~~46206-6015~~ **46204-2251**

2. Dubois County was designated as non-attainment for the PM2.5 standard on January 5, 2005. Also the Responsible Official information has been updated. Section A.1 of the permit has been changed as follows:

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary wood office furniture manufacturing plant.

Responsible Official:	General Manager Director of Upholstery Units
Public Contract:	Rhoda Scherer; (812) 634-3520
Source Address:	340 East 11 th Avenue, Jasper, Indiana 47549
Mailing Address:	340 East 11 th Avenue, Jasper, Indiana 47549
SIC Code:	2521
County Location:	Dubois
Source Location Status:	Nonattainment for the PM2.5 standard Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Minor Source, under PSD and Nonattainment NSR Major Source, Section 112 of the Clean Air Act

All other conditions of the permit shall remain unchanged and in effect. Please find a copy of the revised permit.

Pursuant to Contract No. A305-5-65, IDEM, OAQ has assigned the processing of this application to Eastern Research Group, Inc., (ERG). Therefore, questions should be directed to Stephen Treimel, ERG, 1600 Perimeter Park Drive, Morrisville, North Carolina 27560, or call (919) 468-7902 to speak directly to Mr. Treimel. Questions may also be directed to Duane Van Laningham at IDEM, OAQ, 100 North Senate Avenue, Indianapolis, Indiana, 46204-2251, or call (800) 451-6027, and ask for Duane Van Laningham or extension 3-6878, or dial (317) 233-6878.

Sincerely,

Original Signed By:
Kathy Moore, Section Chief
Permits Branch
Office of Air Quality

Attachments

ERG/ST

cc: File - Dubois County
U.S. EPA, Region V
Dubois County Health Department
Southwest Regional Office
Air Compliance Section Inspector – Gene Kelso
Compliance Data Section
Administrative and Development
Technical Support and Modeling - Michele Boner



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

PART 70 OPERATING PERMIT OFFICE OF AIR QUALITY

**Flexcel - Jasper 11th Ave.
340 East 11th Avenue
Jasper, Indiana 47549**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; and denial of a permit renewal application. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in condition B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T037-6953-00048	
Issued by: Janet G. McCabe, Assistant Commissioner Office of Air Quality	Issuance Date: February 4, 2003 Expiration Date: February 4, 2008

First Administrative Amendment No.: 037-17241-00048, issued May 21, 2003
Second Administrative Amendment No.: 037-20074-00048, October 13, 2004

Third Administrative Amendment No.: 037-22586-00048	Pages Affected: 5, 6, 34
Issued by: Original Signed By: Kathy Moore, Section Chief Permits Branch Office of Air Quality	Issuance Date: March 10, 2006 Expiration Date: February 4, 2008



TABLE OF CONTENTS

SECTION A	SOURCE SUMMARY	5
A.1	General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]	
A.3	Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.4	Part 70 Permit Applicability [326 IAC 2-7-2]	
SECTION B	GENERAL CONDITIONS	7
B.1	Definitions [326 IAC 2-7-1]	
B.2	Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]	
B.3	Enforceability [326 IAC 2-7-7]	
B.4	Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]	
B.5	Severability [326 IAC 2-7-5(5)]	
B.6	Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	
B.7	Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)] [326 IAC 2-7-6(6)]	
B.8	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]	
B.9	Annual Compliance Certification [326 IAC 2-7-6(5)]	
B.10	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3)and (13)] [326 IAC 2-7-6(1)and(6)] [326 IAC 1-6-3]	
B.11	Emergency Provisions [326 IAC 2-7-16]	
B.12	Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]	
B.13	Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.14	Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]	
B.15	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]	
B.16	Permit Renewal [326 IAC 2-7-4]	
B.17	Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]	
B.18	Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]	
B.19	Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]	
B.20	Source Modification Requirement [326 IAC 2-7-10.5]	
B.21	Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2]	
B.22	Transfer of Ownership or Operation [326 IAC 2-7-11]	
B.23	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]	
SECTION C	SOURCE OPERATION CONDITIONS	17
	Emission Limitations and Standards [326 IAC 2-7-5(1)]	
C.1	Opacity [326 IAC 5-1]	
C.2	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.3	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.4	Fugitive Dust Emissions [326 IAC 6-4]	
C.5	Operation of Equipment [326 IAC 2-7-6(6)]	
C.6	Stack Height [326 IAC 1-7]	
C.7	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	Testing Requirements [326 IAC 2-7-6(1)]	
C.8	Performance Testing [326 IAC 3-6]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.9	Compliance Requirements [326 IAC 2-1.1-11]	

TABLE OF CONTENTS (Continued)

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.12 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]
- C.15 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]
- C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

Part 2 MACT Application Submittal Requirement

- C.20 Application Requirements for Section 112(j) of the Clean Air Act [40 CFR 63.52(e)] [40 CFR 63.56(a)] [40 CFR 63.9(b)] [326 IAC 2-7-12]

Stratospheric Ozone Protection

- C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS25

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 PSD Minor Limit [326 IAC 2-2] [40 CFR 52.21]
- D.1.2 General Provisions Relating to HAPs [326 IAC 20-14] [40 CFR 63, Subpart A]
- D.1.3 Wood Furniture Manufacturing Operations NESHAP [40 CFR 63, Subpart JJ] [326 IAC 20-14-1]
- D.1.4 Work Practice Standards for Wood Furniture Manufacturing Operations [40 CFR 63, Subpart JJ]
- D.1.5 Volatile Organic Compounds (VOC): Best Available Control Technology (BACT) [326 IAC 8-1-6]
- D.1.6 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]
- D.1.7 Particulate Matter (PM) [326 IAC 6-1-2]
- D.1.8 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.9 Volatile Organic Compounds (VOC)
- D.1.10 VOC Emissions
- D.1.11 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.12 Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.13 Record Keeping Requirements
- D.1.14 Reporting Requirements

TABLE OF CONTENTS (Continued)

SECTION D.2 FACILITY OPERATION CONDITIONS31

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.2.1 Particulate Matter (PM) [326 IAC 6-1-2]
D.2.2 Sulfur Dioxide Emission Limitations [326 IAC 7-1.1-2]
D.2.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements
D.2.4 Sulfur Dioxide
D.2.5 Sulfur Dioxide Emissions and Sulfur Content [326 IAC 2-7-5(3)(A)] [326 IAC 2-7-6]
D.2.6 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]
D.2.7 Visible Emissions Notations
D.2.8 Cyclone Inspections
D.2.9 Cyclone Failure Detection

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]
D.2.10 Record Keeping Requirements
D.2.11 Reporting Requirements

SECTION D.3 FACILITY OPERATION CONDITIONS34

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.3.1 Baghouse Limitations [326 IAC 2-7-1(21)(G)(xxix)]
D.3.2 Particulate Matter (PM) [326 IAC 6-1-2]
D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements
D.3.4 Particulate Matter (PM) [326 IAC 2-7-1(21)(G)(xxix)(DD)]
D.3.5 Baghouse Inspections [326 IAC 2-7-21(1)(G)(xxix)(FF)]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]
D.3.6 Visible Emissions Notations [326 IAC 2-7-1(21)(G)(xxix)(EE)]
D.3.7 Broken or Failed Bag Detection

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]
D.3.8 Record Keeping Requirements

SECTION D.4 FACILITY OPERATION CONDITIONS37

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.4.1 Particulate Matter [326 IAC 6-1-2]

Certification38
Quarterly Report39
Emergency Occurrence Report40
Semi-Annual Natural Gas Fired Boiler Certification42
Semi-Annual VOC and VHAP Usage Wood Furniture NESHAP Report43
Quarterly Deviation and Compliance Monitoring Report44

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary wood office furniture manufacturing plant.

Responsible Official:	Director of Upholstery Units
Source Address:	340 East 11 th Avenue, Jasper, Indiana 47549
Mailing Address:	340 East 11 th Avenue, Jasper, Indiana 47549
SIC Code:	2521
County Location:	Dubois
Source Location Status:	Nonattainment for the PM2.5 standard Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Minor Source, under PSD and Nonattainment NSR Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

- (a) Twenty-seven (27) surface coating booths consisting of the following:
 - (1) Line #1, consisting of booths (each equipped with HVLP spray guns):
 - (A) SB-4, constructed in 1979 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-4;
 - (B) SB-5, SB-7, SB-8AB, SB-11AB, and SB-12 constructed in 1977 and reconstructed in 1980, using waterpans for particulate control, exhausting to S-5, S-7, S-8AB, S-11AB, and S-12, respectively;
 - (C) SB6-AB, constructed in 1977 and reconstructed in 1980, using waterpans and dry filters for particulate control, exhausting to stack S-6AB; and
 - (D) SB-9, SB-10, and SB-13, constructed in 1977 and reconstructed in 1980, using dry filters for particulate control, exhausting to stacks S-9, S-10, and S-13, respectively.
 - (2) Line #2, consisting of booths (each equipped with HVLP spray guns):
 - (A) SB-14 and SB-15, constructed in 1981, using dry filters for particulate control, exhausting to stacks S-14 and S-15, respectively; and
 - (B) SB-16, SB-17AB, and SB-18AB, constructed in 1981, using waterpans for particulate control, exhausting to stacks S-16, S-17AB, and S-18AB, respectively.
 - (3) Line #3, consisting of booths (each equipped with HVLP spray guns):
 - (A) SB-2, constructed in 1979 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-2;

- (B) SB-20, constructed in 1978 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-20;
- (C) SB-22, SB-23AB, SB-24AB, and SB-25, constructed in 1978 and reconstructed in 1980, using waterpans for particulate control, and exhausting to stacks S-22, S-23AB, S-24AB, and S-25, respectively.
- (4) Six (6) glue booths, consisting of (each equipped with HVLP spray guns):
 - (A) SB-1, constructed in 1979 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-1;
 - (B) SB-19, constructed in 1981, using baffles for particulate control, exhausting to stack S-19;
 - (C) SB-41, SB-42, constructed in 2001, using dry filters for particulate control, exhausting to stacks S-41 and S-42, respectively; and
 - (D) SB-43, SB-44, to be constructed by March 14, 2003, using dry filters for particulate control, exhausting to stacks S-43 and S-44, respectively.
- (b) Two (2) CNB Boilers wood or natural gas-fired (under grate ram-stoker plus burners) each with a heat input capacity of 10.487 MMBtu per hour, identified as Boilers 1 and 2, constructed in 1977 and 1978, respectively, exhausting to stack/vent BS-1 and BS-2.
- (c) One (1) Leclde chain grate coal and wood fired boiler, identified as Boiler 3, constructed in 1981, with a heat input capacity of 20.978 MMBtu per hour, controlled by a Breslove Centrifical Precipitator, exhausting to stack/vent BS-3.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Woodworking facilities equipped with a baghouse with an air flow rate no greater than 125,000 cubic feet of air per minute and a grain loading no greater than 0.003 grains per dry standard cubic feet of outlet air: Three (3) woodworking operations, identified as EU-1, EU-2, and EU-3, equipped with three baghouses TBH-1, TBH-2, and TBH-3, and three cyclones, identified as CY-1, CY-2, and CY-3, exhausting to stacks TBH-1, TBH-2, and TBH-3. [326 IAC 2-7-1(21)(G)(xxix)]
- (b) Activities with emissions equal to or less than the following thresholds: 5 tons per year PM or PM10, 10 tons per year SO₂, NO_x, or VOC, 0.2 tons per year Pb, 1.0 tons per year of a single HAP, or 2.5 tons per year of any combination of HAPs: Three (3) Wood chip/dust storage bins; hand sanding booths B27 through B40. [326 IAC 6-1-2]
- (c) Coal bunker and coal scale exhausts and associated dust collector vents. [326 IAC 6-1-2]
- (d) Paved and unpaved roads and parking lots with public access. [326 IAC 6-4]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.3 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.4 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)] [326 IAC 2-7-6(6)]

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall furnish to IDEM, OAQ within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.
- (c) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by

a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]**

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each facility:

- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
- (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The PMP extension notification does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and the southwest regional office, within four (4) daytime business hours

after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or
Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967

and

Southwest Regional Office Phone: 1-888-672-8323 or (812) 436-2570
Southwest Regional Office Fax: (812) 436-2572

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
 - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
 - (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
 - (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
 - (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

- (h) The permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.
- This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.
- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
- (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
- (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted
- by this permit.
- (b) All previous registrations and permits are superseded by this permit.

B.14 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:
- Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
- using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
- (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]

- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.16 Permit Renewal [326 IAC 2-7-4]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]

(1) A timely renewal application is one that is:

- (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
- (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(2) If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

- (c) Right to Operate After Application for Renewal [326 IAC 2-7-3]
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.
- (d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]
If IDEM, OAQ, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.17 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality

100 North Senate Avenue
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

**B.18 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
[326 IAC 2-7-12 (b)(2)]**

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.19 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
- (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

B.20 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

B.21 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy any records that must be kept under the conditions of this permit;
- (c) Inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.2 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.3 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.4 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.5 Operation of Equipment [326 IAC 2-7-6(6)]

Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.6 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted. The provisions of 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4(d), (e), and (f), and 326 IAC 1-7-5(d) are not federally enforceable.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work

or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:

- (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
- (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited, pursuant to the provisions of 40 CFR 61, Subpart M, is federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.8 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality

100 North Senate Avenue
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.12 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that

- the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (" 2%) of full scale reading.
- (b) Whenever a condition in this permit requires the measurement of a temperature or flow rate, the instrument employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (" 2%) of full scale reading.
 - (c) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within ninety (90) days after the date of issuance of this permit.

The ERP does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) If the ERP is disapproved by IDEM, OAQ, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.
- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall submit:

- (a) A compliance schedule for meeting the requirements of 40 CFR 68; or
- (b) As a part of the annual compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP);

All documents submitted pursuant to this condition shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.15 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5]
[326 IAC 2-7-6]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
- (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
 - (4) Failure to take reasonable response steps shall constitute a violation of the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
- (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the

Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.

- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

**C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]**

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

**C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)]
[326 IAC 2-6]**

- (a) In accordance with the compliance schedule specified in 326 IAC 2-6-3(b)(1), starting in 2006 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:
 - (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
 - (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the

private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

- (a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

- (a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

Part 2 MACT Application Submittal Requirement

C.20 Application Requirements for Section 112(j) of the Clean Air Act [40 CFR 63.52(e)] [40 CFR 63.56(a)] [40 CFR 63.9(b)] [326 IAC 2-7-12]

- (a) The Permittee shall submit a Part 2 MACT Application in accordance with 40 CFR 63.52(e)(1). The Part 2 MACT Application shall meet the requirements of 40 CFR 63.53(b).
- (b) Notwithstanding paragraph (a), the Permittee is not required to submit a Part 2 MACT Application if the Permittee no longer meets the applicability criteria of 40 CFR 63.50 by the application deadline in 40 CFR 63.52(e)(1). For example, the Permittee would not have to submit a Part 2 MACT Application if, by the application deadline:

- (1) The source is no longer a major source of hazardous air pollutants, as defined in 40 CFR 63.2;
 - (2) The source no longer includes one or more units in an affected source category for which the U.S. EPA failed to promulgate an emission standard by May 15, 2002; or
 - (3) The MACT standard or standards for the affected source categories included at the source are promulgated.
- (c) Notwithstanding paragraph (a), pursuant to 40 CFR 63.56(a), the Permittee shall comply with an applicable promulgated MACT standard in accordance with the schedule provided in the MACT standard if the MACT standard is promulgated prior to the Part 2 MACT Application deadline or prior to the issuance of permit with a case-by-case Section 112(j) MACT determination. The MACT requirements include the applicable General Provisions requirements of 40 CFR 63, Subpart A. Pursuant to 40 CFR 63.9(b), the Permittee shall submit an initial notification not later than 120 days after the effective date of the MACT, unless the MACT specifies otherwise. The initial notification shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Director, Air and Radiation Division
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

Stratospheric Ozone Protection

C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Surface Coating:

- (a) Twenty-seven (27) surface coating booths consisting of the following:
 - (1) Line #1, consisting of the following booths (each equipped with HVLP spray guns):
 - (A) SB-4, constructed in 1979 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-4;
 - (B) SB-5, SB-7, SB-8AB, SB-11AB, and SB-12 constructed in 1977 and reconstructed in 1980, using waterpans for particulate control, exhausting to S-5, S-7, S-8AB, S-11AB, and S-12, respectively;
 - (C) SB6-AB, constructed in 1977 and reconstructed in 1980, using waterpans and dry filters for particulate control, exhausting to stack S-6AB; and
 - (D) SB-9, SB-10, and SB-13, constructed in 1977 and reconstructed in 1980, using dry filters for particulate control, exhausting to stacks S-9, S-10, and S-13, respectively.
 - (2) Line #2, consisting of the following booths (each equipped with HVLP spray guns):
 - (A) SB-14 and SB-15, constructed in 1981, using dry filters for particulate control, exhausting to stacks S-14 and S-15, respectively; and
 - (B) SB-16, SB-17AB, and SB-18AB, constructed in 1981, using waterpans for particulate control, exhausting to stacks S-16, S-17AB, and S-18AB, respectively.
 - (3) Line #3, consisting of the following booths (each equipped with HVLP spray guns):
 - (A) SB-2, constructed in 1979 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-2;
 - (B) SB-20, constructed in 1978 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-20;
 - (C) SB-22, SB-23AB, SB-24AB, and SB-25, constructed in 1978 and reconstructed in 1980, using waterpans for particulate control, and exhausting to stacks S-22, S-23AB, S-24AB, and S-25, respectively.
 - (4) Six (6) glue booths, consisting of the following booths (each equipped with HVLP spray guns):
 - (A) SB-1, constructed in 1979 and reconstructed in 1980, using dry filters for particulate control, exhausting to stack S-1;
 - (B) SB-19, constructed in 1981, using baffles for particulate control, exhausting to stack S-19;
 - (C) SB-41, SB-42, constructed in 2001, using dry filters for particulate control, exhausting to stacks S-41 and S-42, respectively; and
 - (D) SB-43, SB-44, not yet constructed, using dry filters for particulate control, exhausting to stacks S-43 and S-44, respectively.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 PSD Minor Limit [326 IAC 2-2] [40 CFR 52.21]

The surface coating operations (booths SB-1, SB-2, SB-4, SB-5, SB-6AB, SB-7, SB-8AB, SB-9, SB-10, SB-11AB, SB-12, SB-13, SB-14, SB-15, SB-16, SB-17AB, SB-18AB, SB-19, SB-20, SB-22, SB-23AB, SB-24AB, SB-25, and SB-41 through SB-44) shall use less than 246 tons of VOC (250 tpy less the maximum VOC emissions from the boilers), including coatings, dilution solvents, and cleaning solvents, per twelve (12) consecutive month period with compliance determined at the end of each month.

This usage limit is required to limit the total source potential to emit of VOC to less than 250 tons per twelve (12) consecutive month period with compliance determined at the end of each month. Compliance with this limit renders the requirements of 326 IAC 2-2 and 40 CFR 52.21 (Prevention of Significant Deterioration) not applicable.

D.1.2 General Provisions Relating to HAPs [326 IAC 20-14] [40 CFR 63, Subpart A]

The provisions of 40 CFR 63, Subpart A - General Provisions, which are incorporated as 326 IAC 20-14, apply to the facility described in this section except when otherwise specified in 40 CFR 63, Subpart JJ.

D.1.3 Wood Furniture Manufacturing Operations NESHAP [40 CFR 63, Subpart JJ] [326 IAC 20-14-1]

- (a) The wood furniture manufacturing operations are subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP), 40 CFR 63, Subpart JJ, incorporated by reference as 326 IAC 20-14-1, with a compliance date of November 21, 1997.
- (b) Pursuant to 40 CFR 63, Subpart JJ, the wood furniture coating operations shall comply with the following conditions:
 - (1) Limit the Volatile Hazardous Air Pollutants (VHAP) emissions from finishing operations as follows:
 - (A) Achieve a weighted average volatile hazardous air pollutant (VHAP) content across all coatings of one (1.0) pound VHAP per pound solids, as applied; or
 - (B) Use compliant finishing materials in which all stains, washcoats, sealers, topcoats, basecoats and enamels have a maximum VHAP content of one (1.0) pound VHAP per pound solid, as applied. Thinners used for on-site formulation of washcoats, basecoats, and enamels have a three percent (3.0%) maximum VHAP content by weight. All other thinners have a ten percent (10.0%) maximum VHAP content by weight; or
 - (C) Use a control device to limit emissions to one (1.0) pound VHAP per pound solids; or
 - (D) Use any combination of (A), (B), and (C).
 - (2) Limit VHAP emissions from contact adhesives as follows:
 - (A) For foam adhesives used in products that meet the upholstered seating flammability requirements, the VHAP content shall not exceed 1.8 pound VHAP per pound solids;
 - (B) For all other contact adhesives (except aerosols and contact adhesives applied to nonporous substrates) the VHAP content shall not exceed one (1.0) pound VHAP per pound solids;
 - (C) Use a control device to limit emissions to one (1.0) pound VHAP per pound solids.

- (3) The strippable spray booth material shall have a maximum VOC content of eight-tenths (0.8) pounds VOC per pound solids, as applied.

D.1.4 Work Practice Standards for Wood Furniture Manufacturing Operations [40 CFR 63, Subpart JJ]

The owner or operator of an affected source subject to this subpart shall maintain a written work practice implementation plan, as required by 40 CFR 63.803(a). The work practice implementation plan must define environmentally desirable work practices for each wood furniture manufacturing operation and at a minimum address each of the following work practice standards as defined under 40 CFR 63.803:

- (a) Operator training course.
- (b) Leak inspection and maintenance plan.
- (c) Cleaning and washoff solvent accounting system.
- (d) Chemical composition of cleaning and washoff solvents.
- (e) Spray booth cleaning.
- (f) Storage requirements.
- (g) Conventional air spray guns shall only be used under the circumstances defined under 40 CFR 63.803(h).
- (h) Line cleaning.
- (i) Gun cleaning.
- (j) Washoff operations.
- (k) Formulation assessment plan for finishing operations.

D.1.5 Volatile Organic Compounds (VOC): Best Available Control Technology (BACT) [326 IAC 8-1-6]

Pursuant to 326 IAC 8-1-6, spray booths SB-1, SB-2, SB-4, SB-5, SB-6AB, SB-7, SB-8AB, SB-9, SB-10, SB-11AB, SB-12, SB-13, SB-14, SB-15, SB-16, SB-17AB, SB-18AB, SB-19, SB-20, SB-22, SB-23AB, SB-24AB and SB-25 shall utilize one of the following application methods:

- Airless Spray Application
- Air Assisted Airless Spray Application
- Electrostatic Spray Application
- Electrostatic Bell or Disc Application
- Heated Airless Spray Application
- Roller Coating
- Brush or Wipe Application
- Dip-and-Drain Application
- High Volume Low Pressure (HVLP) Spray Application

High Volume Low Pressure (HVLP) Spray Application is an accepted alternative method of application for Air Assisted Airless Spray Application. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

D.1.6 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]

Pursuant to MSM 037-14674-00048, issued September 14, 2001, the surface coating applied to wood office furniture from booths SB-41, SB-42, SB-43, and SB-44 shall utilize one of the following application methods:

- Airless Spray Application

Air Assisted Airless Spray Application
Electrostatic Spray Application
Electrostatic Bell or Disc Application
Heated Airless Spray Application
Roller Coating
Brush or Wipe Application
Dip-and-Drain Application

High Volume Low Pressure (HVLP) Spray Application is an accepted alternative method of application for Air Assisted Airless Spray Application. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

D.1.7 Particulate Matter (PM) [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2(a), the particulate emissions from each of the surface coating stack exhausts shall not exceed 0.03 grains per dry cubic standard foot (gr/dscf).

D.1.8 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.1.9 Volatile Organic Compounds (VOC)

Compliance with the VOC content and usage limitations contained in Condition D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.10 VOC Emissions

Compliance with Condition D.1.1 shall be demonstrated within 30 days of the end of each month based on the total volatile organic compound usage for the month.

D.1.11 Particulate Matter (PM)

In order to comply with Condition D.1.7, the dry filters, baffles, and water pans for particulate matter (PM) overspray control shall be in operation and control emissions from the paint booths at all times the paint booths are in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.12 Monitoring

The Permittee shall implement an operator training program.

- (a) All operators that perform surface coating operations using spray equipment or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained within 60 days of the date of permit issuance. All new operators shall be trained upon hiring or transfer.
- (b) Training shall include proper filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators and training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.13 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC emission limits established in Condition D.1.1.
- (1) The VOC content of each coating material and solvent used.
 - (2) The amount of coating material and solvent less water used on a monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The volume weighted VOC content of the coatings used for each month;
 - (4) The total VOC usage for each month; and
 - (5) The weight of VOCs emitted for each compliance period.
- (b) To document compliance with Condition D.1.3, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be complete and sufficient to establish compliance with the VHAP usage limits established in Condition D.1.3.
- (1) Certified Product Data Sheet for each finishing material, thinner, contact adhesive and strippable booth coating.
 - (2) The VHAP content in pounds of VHAP per pounds of solids, as applied, for all finishing materials and contact adhesives used.
 - (3) The VOC content in pounds of VOC per pounds of solids, as applied, for each strippable spray booth coating used.
 - (4) The VHAP content in weight percent of each thinner used.
 - (5) When the averaging compliance method is used, copies of the averaging calculations for each month as well as the data on the quantity of coating and thinners used to calculate the average.
- (c) To document compliance with Condition D.1.4, the Permittee shall maintain records demonstrating actions have been taken to fulfill the Work Practice Implementation Plan.
- (d) To document compliance with Condition D.1.12, the Permittee shall maintain copies of the training program, the list of trained operators, and additional inspections prescribed by the Preventive Maintenance Plan. Training records shall be maintained on site or available within 1 hour for inspection by IDEM.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.14 Reporting Requirements

- (a) A quarterly summary of the information to document compliance with Condition D.1.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

- (b) A semi-annual Continuous Compliance Report to document compliance with Condition D.1.3 and the Certification form, shall be submitted to the addresses listed in section C- General Reporting Requirements- of this permit, within thirty (30) days after the end of the six (6) months being reported.

The six (6) month periods shall cover the following months:

- (1) January 1 through June 30.
 - (2) July 1 through December 31.
- (c) The report required by (b) of this condition shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Boilers:

- (b) Two (2) CNB Boilers wood or natural gas-fired (under grate ram-stoker plus burners) each with a heat input capacity of 10.487 MMBtu per hour, identified as Boilers 1 and 2, constructed in 1977 and 1978, respectively, exhausting to stack/vent BS-1 and BS-2.
- (c) One (1) Leclde chain grate coal and wood fired boiler, identified as Boiler 3, constructed in 1981, with a heat input capacity of 20.978 MMBtu per hour, controlled by a Breslove Centrifical Precipitator, exhausting to stack/vent BS-3.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Particulate Matter [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2 (Particulate Emissions Limitations), the particulate emissions from Boiler 1, Boiler 2, and Boiler 3 shall not exceed:

- (a) Six tenths (0.6) pounds per MMBtu when combusting coal or wood; and
- (b) One hundredths (0.01) grains per dry standard cubic foot when combusting natural gas.

D.2.2 Sulfur Dioxide Emission Limitations [326 IAC 7-1.1-2]

Pursuant to 326 IAC 7-1.1-2 (SO₂ Emissions Limitations), the SO₂ emissions from Boiler 3 shall not exceed six (6.0) pounds per MMBtu heat input, when burning coal.

D.2.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and the Breslove Centrifical Precipitator.

Compliance Determination Requirements

D.2.4 Sulfur Dioxide

Pursuant to 326 IAC 7-2-1, compliance shall be demonstrated on a calendar month average. 326 IAC 7-1.1 and 326 IAC 7-2-1 are not federally enforceable.

D.2.5 Sulfur Dioxide Emissions and Sulfur Content [326 IAC 2-7-5(3)(A)] [326 IAC 2-7-6]

Pursuant to 326 IAC 7-2, the Permittee shall demonstrate that the sulfur dioxide emissions do not exceed six (6.0) pounds per MMBtu. Compliance shall be determined utilizing one of the following options:

- (a) Providing vendor analysis of coal delivered, if accompanied by a certification from the fuel supplier as described under 40 CFR 60.48c(f)(3). The certification shall include:
 - (1) The name of the coal supplier;
 - (2) The location of the coal when the sample was collected for analysis to determine the properties of the coal, specifically including whether the coal was sampled as delivered to the affected facility or whether the coal was collected from coal in storage at the mine, at a coal preparation plant, at a coal supplier's facility, or at another location. The certification shall include the name of the coal mine (and coal seam), coal storage facility, or coal preparation plant (where the sample was collected); and

- (3) The results of the analysis of the coal from which the shipment came (or of the shipment itself) including the sulfur content, moisture content, ash content, and heat content;
- (4) The methods used to determine the properties of the coal; or
- (b) Sampling and analyzing the coal using one of the following procedures:
 - (1) Minimum Coal Sampling Requirements and Analysis Methods:
 - (A) The coal sample acquisition point shall be at a location where representative samples of the total coal flow to be combusted by the facility or facilities may be obtained. A single as-bunkered or as-burned sampling station may be used to represent the coal to be combusted by multiple facilities using the same stockpile feed system;
 - (B) Coal shall be sampled at least one (1) time per day;
 - (C) Minimum sample size shall be five hundred (500) grams;
 - (D) Samples shall be composited and analyzed at the end of each calendar quarter;
 - (E) Preparation of the coal sample, heat content analysis, and sulfur content analysis shall be determined pursuant to 326 IAC 3-7-2(c), (d), (e);
 - (F) Sample and analyze the coal pursuant to 326 IAC 3-7-3; or
 - (2) Sample and analyze the coal pursuant to 326 IAC 3-7-3;
- (c) Compliance may also be determined by conducting a stack test for sulfur dioxide emissions from the boiler, using 40 CFR 60, Appendix A, Method 6 in accordance with the procedures in 326 IAC 3-6, which is conducted with such frequency as to generate the amount of information required by (a) or (b) above. [326 IAC 7-2-1(b)]

A determination of noncompliance pursuant to any of the methods specified in (a), (b), or (c) above shall not be refuted by evidence of compliance pursuant to the other method.

D.2.6 Particulate Matter (PM)

In order to comply with condition D.2.1, the Breslove Centrifugal Precipitator for PM control shall be in operation at all times Boiler 3 is in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.7 Visible Emissions Notations

- (a) Visible emission notations of the boilers' stack exhaust, BS-1, BS-2, and BS-3, shall be performed once per shift during normal daylight operations, when burning wood or coal. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.

- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

D.2.8 Cyclone Inspections

An inspection shall be performed during the last month of each calendar quarter of the Bresolve Centrifugal Precipitator controlling the PM emissions from Boiler 3 when venting to the atmosphere. A cyclone inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors.

D.2.9 Cyclone Failure Detection

In the event that cyclone failure has been observed:

Failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions). Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.10 Record Keeping Requirements

- (a) To document compliance with Conditions D.2.2 and D.2.5, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the emission limits established in Conditions D.2.2 and D.2.5.
 - (1) Calendar dates covered in the compliance determination period;
 - (2) Actual coal usage since last compliance determination period;
 - (3) Sulfur content, heat content, and ash content;
 - (4) Sulfur dioxide emission rates; and
 - (5) Vendor analysis of coal and coal supplier certification.
- (b) To document compliance with Condition D.2.7, the Permittee shall maintain records of once per shift visible emission notations of Boilers 1 and 2 stack exhaust.
- (c) To document compliance with Condition D.2.8, the Permittee shall maintain records of the results of the inspections required under Condition D.2.8.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2.11 Reporting Requirements

- (a) The natural gas boiler certification shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or its equivalent, within thirty (30) days after the end of the six (6) month period being reported. The natural gas-fired boiler certification does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Insignificant Woodworking operations:

- (a) Woodworking facilities equipped with a baghouse with an air flow rate no greater than 125,000 cubic feet of air per minute and a grain loading no greater than 0.003 grains per dry standard cubic feet of outlet air: Three (3) woodworking operations, identified as EU-1, EU-2, and EU-3, equipped with three baghouses TBH-1, TBH-2, and TBH-3, and three cyclones, identified as CY-1, CY-2, and CY-3, exhausting to stacks TBH-1, TBH-2, and TBH-3. [326 IAC 2-7-1(21)(G)(xxix)]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Baghouse Limitations [326 IAC 2-7-1(21)(G)(xxix)]

The woodworking operations controlled by a baghouse shall be an insignificant activity for Title V permitting purposes provided that the baghouse operations meet the requirements of 326 IAC 2-7-1(21)(G)(xxix), including the following:

- (a) Each woodworking baghouse shall not exhaust to the atmosphere greater than one hundred twenty-five thousand (125,000) cubic feet of air per minute and shall not emit particulate matter with a diameter less than ten (10) microns in excess of three-thousandths (0.003) grain per dry standard cubic foot of outlet air.
- (b) The opacity from each baghouse shall not exceed ten percent (10%).
- (c) Visible emissions from the baghouse shall be observed daily using procedures in accordance with Method 22 and normal or abnormal emissions are recorded. In the event abnormal emissions are observed for greater than six (6) minutes in duration, the following shall occur:
- (1) The baghouse shall be inspected.
 - (2) Corrective actions, such as replacing or reseating bags, are initiated, when necessary.

D.3.2 Particulate Matter (PM) [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2(a), the particulate emissions from the woodworking exhaust shall not exceed 0.03 grains per dry cubic standard foot (gr/dscf). Compliance with 326 IAC 2-7-1(21)(G)(xxix) will satisfy the requirements of this rule.

D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their baghouses.

Compliance Determination Requirements

D.3.4 Particulate Matter (PM) [326 IAC 2-7-1(21)(G)(xxix)(DD)]

In order to comply with Conditions D.3.1 and D.3.2, the baghouses for PM control shall be in operation and control emissions from the woodworking facilities at all times that the woodworking facilities are in operation.

D.3.5 Baghouse Inspections [326 IAC 2-7-21(1)(G)(xxix)(FF)]

An inspection shall be performed during the last month of each calendar quarter of all bags controlling the woodworking operation when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. All defective bags shall be repaired or replaced.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.3.6 Visible Emissions Notations [326 IAC 2-7-1(21)(G)(xxix)(EE)]

Should the source elect to not have the woodworking operations considered an insignificant activity for Title V permitting purposes, the Method 22 readings required in Condition D.3.1(c) are not required, and will be replaced by the following:

- (a) Visible emission notations of each baghouse exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

D.3.7 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if there are no visible emissions or if the event qualifies as an emergency and the Permittee satisfies the emergency provisions of this permit (Section B- Emergency Provisions). Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.3.8 Record Keeping Requirements

- (a) To document compliance with Conditions D.3.1(c) and D.3.6, the Permittee shall maintain records of daily visible emission notations of the baghouse exhaust.
- (b) To document compliance with Condition D.3.5, the Permittee shall maintain records of the results of the inspections required under Condition D.3.5 and the dates the vents are redirected.
- (c) The Permittee shall maintain records of corrective actions to document compliance with 326 IAC 2-7-21(1)(G)(xxix)(GG)(dd).
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

SECTION D.4

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Specifically regulated insignificant activities:

- (b) Activities with emissions equal to or less than the following thresholds: 5 tons per year PM or PM10, 10 tons per year SO₂, NO_x, or VOC, 0.2 tons per year Pb, 1.0 tons per year of a single HAP, or 2.5 tons per year of any combination of HAPs: Three (3) Wood chip/dust storage bins; hand sanding booths B27 through B40. [326 IAC 6-1-2]
- (c) Coal bunker and coal scale exhausts and associated dust collector vents. [326 IAC 6-1-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.1 Particulate Matter [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2(a), the particulate matter (PM) emissions from the hand sanding booths (B27 through B40), wood chip/dust storage bins, and coal bunker/coal scale exhausts and associated dust collector vents shall not exceed 0.03 grains per dry cubic standard foot (gr/dscf).

**INDIANA DEPARTMENT OF ENVIRONMENTAL
MANAGEMENT
OFFICE OF AIR QUALITY**

**PART 70 OPERATING PERMIT
CERTIFICATION**

Source Name: Flexcel - Jasper 11th Ave.
Source Address: 340 East 11th Avenue, Jasper, Indiana 47549
Mailing Address: 340 East 11th Avenue, Jasper, Indiana 47549
Part 70 Permit No.: 037-6953-00048

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Affidavit (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

Indiana Department of Environmental Management Office of Air Quality Compliance Data Section

Quarterly Report

Source Name: Flexcel - Jasper 11th Ave.
Source Address: 340 East 11th Avenue, Jasper, Indiana 47549
Mailing Address: 340 East 11th Avenue, Jasper, Indiana 47549
Part 70 Permit No.: T037-6953-00048
Facility: Surface Coating Operations: booths SB-1, SB-2, SB-4, SB-5, SB-6AB, SB-7, SB-8AB, SB-9, SB-10, SB-11AB, SB-12, SB-13, SB-14, SB-15, SB-16, SB-17AB, SB-18AB, SB-19, SB-20, SB-22, SB-23AB, SB-24AB, SB-25, and SB-41 through SB-44
Parameter: VOC usage: including coatings, dilution solvents, and cleaning solvents
Limit: Less than 246 tons per 12 consecutive month period with compliance determined at the end of each month

Year: _____

Month	VOC Usage This Month (tons)	VOC Usage for Past 11 Months (tons)	VOC Usage for Previous 12 Month Period (tons)

Submitted by: _____
Title/Position: _____
Signature: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH
100 North Senate Avenue
P.O. Box 6015
Indianapolis, Indiana 46204-2251
Phone: 317-233-5674
Fax: 317-233-5967**

**PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT**

Source Name: Flexcel - Jasper 11th Ave.
Source Address: 340 East 11th Avenue, Jasper, Indiana 47549
Mailing Address: 340 East 11th Avenue, Jasper, Indiana 47549
Part 70 Permit No.: 037-6953-00048

This form consists of 2 pages

Page 1 of 2

- 9** This is an emergency as defined in 326 IAC 2-7-1(12)
- C The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
 - C The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:

Control Equipment:

Permit Condition or Operation Limitation in Permit:

Description of the Emergency:

Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
Compliance Data Section**

**PART 70 OPERATING PERMIT
SEMI-ANNUAL NATURAL GAS FIRED BOILER CERTIFICATION**

Source Name: Flexcel - Jasper 11th Ave.
Source Address: 340 East 11th Avenue, Jasper, Indiana 47549
Mailing Address: 340 East 11th Avenue, Jasper, Indiana 47549
Part 70 Permit No.: 037-6953-00048

9 Natural Gas Only
9 Alternate Fuel burned
From: _____ To: _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
Signature:
Printed Name:
Title/Position:
Phone:
Date:

A certification by the responsible official as defined by 326 IAC 2-7-1(34) is required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL
 MANAGEMENT
 OFFICE OF AIR QUALITY
 Compliance Branch
 PART 70 OPERATING PERMIT
 Semi-Annual Report
 VOC and VHAP Usage - Wood Furniture NESHAP**

Source Name: Flexcel - Jasper 11th Ave.
 Source Address: 340 East 11th Avenue, Jasper, Indiana 47549
 Mailing Address: 340 East 11th Avenue, Jasper, Indiana 47549
 Part 70 Permit No.: 037-6953-00048
 Facilities: Surface coating booths: SB-1, SB-2, SB-4, SB-SB-5, SB-6AB, SB-7, SB-8AB, SB-9, SB-10, SB-11AB, SB-12, SB-13, SB-14, SB-15, SB-16, SB-17AB, SB-18AB, SB-19, SB-20, SB-22, SB-23AB, SB-24AB, SB-25, and SB-41 through SB-44
 Parameter: VOC and VHAPs - NESHAP
 Limit: (1) Finishing operations -1.0 lb VHAP/lb Solids
 (2) Thinners used for on-site formulation of washcoats, basecoats and enamels - 3% VHAP content by weight
 (3) All other thinners - 10% VHAP content by weight
 (4) Foam adhesives meeting the upholstered seating flammability requirements - 1.8 lb VHAP/lb Solids
 (5) All other contact adhesives - 1.0 lb VHAP/lb Solids
 (6) Strippable spray booth material - 0.8 pounds VOC per pound solids

Month	Finishing Operations (lb VHAP/lb Solid)	Thinners (% by weight)	Thinner/Solvent mixtures (% by weight)	Foam adhesives (upholstered) (lb VHAP/lb Solid)	Contact adhesives (lb VHAP/lb Solid)	Strippable spray booth material (lb VOC/lb Solid)
1						
2						
3						
4						
5						
6						

9 No deviation occurred in this six month period.
 9 Deviation/s occurred in this six month period.
 Deviation has been reported

on: _____
 Submitted by: _____
 Title/Position: _____
 Signature: _____
 Date: _____
 Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
Compliance Branch**

**PART 70 OPERATING PERMIT
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Flexcel - Jasper 11th Ave.
Source Address: 340 East 11th Avenue, Jasper, Indiana 47549
Mailing Address: 340 East 11th Avenue, Jasper, Indiana 47549
Part 70 Permit No.: 037-6953-00048

Months: _____ to _____ Year: _____

Page 1 of 2

This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.