



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

TO: Interested Parties / Applicant
DATE: August 17, 2006
RE: Rea Magnet Wire Company, Inc. / 003-22964-00013
FROM: Nisha Sizemore
Chief, Permits Branch
Office of Air Quality

Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER.dot 03/23/06



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
We make Indiana a cleaner, healthier place to live.

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

Brett Kauser August 17, 2006
Rea Magnet Wire Company, Inc.
4300 New Haven Avenue
Fort Wayne, Indiana 46803

Re: 003-22964-00013
First Significant Source Modification to:
Part 70 permit No.: T003-6925-00013

Dear Mr. Kauser:

Rea Magnet Wire Company, Inc. was issued Part 70 operating permit T003-6925-00013 on October 10, 2002 for a stationary magnet wire coating plant. An application to modify the source was received on April 17, 2006. Pursuant to 326 IAC 2-7-10.5 the following emission units are approved for construction at the source:

- (gg) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.
- (hh) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.

The following construction conditions are applicable to the proposed project:

1. General Construction Conditions
The data and information supplied with the application shall be considered part of this source modification approval. Prior to any proposed change in construction which may affect the potential to emit (PTE) of the proposed project, the change must be approved by the Office of Air Quality (OAQ).
2. This approval to construct does not relieve the permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.
3. Effective Date of the Permit
Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.
4. Pursuant to 326 IAC 2-1.1-9 and 326 IAC 2-7-10.5(i), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.
5. All requirements and conditions of this construction approval shall remain in effect unless modified in a manner consistent with procedures established pursuant to 326 IAC 2.

6. Pursuant to 326 IAC 2-7-10.5(l) the emission units constructed under this approval shall not be placed into operation prior to revision of the source=s Part 70 Operating Permit to incorporate the required operation conditions.

This significant source modification authorizes construction of the new emission units. Operating conditions shall be incorporated into the Part 70 operating permit as a significant permit modification in accordance with 326 IAC 2-7-10.5(l)(2) and 326 IAC 2-7-12. Operation is not approved until the significant permit modification has been issued.

Pursuant to Contract No. A305-5-65, IDEM, OAQ has assigned the processing of this application to Eastern Research Group, Inc., (ERG). Therefore, questions should be directed to Stephen Treimel, ERG, 1600 Perimeter Park Drive, Morrisville, North Carolina 27560, or call (919) 468-7902 to speak directly to Mr. Stephen Treimel. Questions may also be directed to Duane Van Laningham at IDEM, OAQ, 100 North Senate Avenue, Indianapolis, Indiana, 46204-2251, or call (800) 451-6027 and ask for Duane Van Laningham or extension 3-6878, or dial (317) 233-6878.

Sincerely,

Original signed by

Nisha Sizemore, Chief
Permits Branch
Office of Air Quality

Attachments

Permit, Technical Source Document, Appendix A (calculations)

ERG/ST

cc: File - Allen County
Allen County Health Department
Air Compliance Section Inspector – Patrick Burton
Compliance Data Section
Administrative and Development
Technical Support and Modeling - Michele Boner



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

PART 70 OPERATING PERMIT OFFICE OF AIR QUALITY

**Rea Magnet Wire Company, Inc.
4300 New Haven Avenue
Fort Wayne, Indiana 46803**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; and denial of a permit renewal application. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in condition B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T003-6925-00013	
Issued by: Janet G. McCabe, Assistant Commissioner Office of Air Quality	Issuance Date: October 10, 2002 Expiration Date: October 10, 2007

First Administrative Amendment No.: 003-22399-00013 Issued on October March 15, 2006

First Significant Source Modification No.: 003-22964-00013	
Original signed by: Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: August 17, 2006 Expiration Date: October 10, 2007



TABLE OF CONTENTS

SECTION A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)][326 IAC 2-7-5(15)]
- A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)]
- A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

SECTION B GENERAL CONDITIONS

- B.1 Definitions [326 IAC 2-7-1]
- B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]
- B.3 Term of Conditions [326 IAC 2-1.1-9.5]
- B.4 Enforceability [326 IAC 2-7-7]
- B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
- B.6 Severability [326 IAC 2-7-5(5)]
- B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)] [326 IAC 2-7-6(6)]
- B.9 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]
- B.10 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.11 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]
- B.12 Emergency Provisions [326 IAC 2-7-16]
- B.13 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]
- B.14 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]
- B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
- B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]
- B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]
- B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]
- B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)][326 IAC 2-7-12 (b)(2)]
- B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]
- B.21 Source Modification Requirement [326 IAC 2-7-10.5]
- B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2]
- B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]
- B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]
- B.25 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 FR 8314] [326 IAC 1-1-6]

SECTION C SOURCE OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Matter Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2(c)]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

Testing Requirements [326 IAC 2-7-6(1)]

- C.7 Performance Testing [326 IAC 3-6]

Compliance Requirements [326 IAC 2-1.1-11]

- C.8 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.10 Maintenance of Emission Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]
- C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.12 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]
- C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5][326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)][326 IAC 2-6]
- C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]
- C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

Stratospheric Ozone Protection

- C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Volatile Organic Compound (VOC)
- D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]
- D.1.4 Thermal Oxidizer Operation
- D.1.5 Testing Requirements [326 IAC 2-7-6(1),(6)]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.6 Parametric Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.7 Record Keeping Requirements

SECTION D.2 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.2.1 Volatile Organic Compound (VOC)
- D.2.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]
- D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Compliance Determination Requirements

- D.2.4 Thermal Oxidizer Operation
- D.2.5 Testing Requirements [326 IAC 2-7-6(1),(6)]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.2.6 Parametric Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.2.7 Record Keeping Requirements

SECTION D.3 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.3.1 Volatile Organic Compounds [326 IAC 8-2-8]
- D.3.2 PSD Limit [326 IAC 2-2]
- D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.3.4 Volatile Organic Compounds (VOC)
- D.3.5 Testing Requirements [326 IAC 2-7-6(1), (6)][326 IAC 2-1.1-11]
- D.3.6 VOC Emissions

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.3.7 Thermal Oxidizer Operation
- D.3.8 Parametric Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.3.9 Record Keeping Requirements
- D.3.10 Reporting Requirements

SECTION D.4 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.4.1 Volatile Organic Compounds [326 IAC 8-2-8]
- D.4.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.4.3 Volatile Organic Compounds (VOC)
- D.4.4 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.4.5 Thermal Oxidizer Operation
- D.4.6 Parametric Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.4.7 Record Keeping Requirements

SECTION D.5 FACILITY CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.5.1 Volatile Organic Compound (VOC)
- D.5.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.5.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]
- D.5.4 Thermal Oxidizer Operation
- D.5.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.5.6 Parametric Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.5.7 Record Keeping Requirements

SECTION D.6 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.6.1 Volatile Organic Compound (VOC)

D.6.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

D.6.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

D.6.4 Thermal Oxidizer

D.6.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)][326 IAC 2-7-5(1)]

D.6.6 Thermal Oxidizer Operation

D.6.7 Parametric Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.6.8 Record Keeping Requirements

SECTION D.7 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.7.1 PSD Limit [326 IAC 2-2]

D.7.2 Volatile Organic Compounds (VOC)

D.7.3 Volatile Organic Compounds (VOC)

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.7.4 Record Keeping Requirements

D.7.5 Reporting Requirements

SECTION D.8 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.8.1 Particulate Matter (PM) [326 IAC 6-2-3]

SECTION D.9 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.9.1 Particulate Matter [326 IAC 6-3-2]

SECTION D.10 FACILITY OPERATION CONDITIONS

D.10.1 Volatile Organic Compounds [326 IAC 8-2-8]

D.10.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

D.10.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

D.10.4 Oxidizer Operation

D.10.5 Testing Requirements [326 IAC 2-7-6(1), (6)][326 IAC 2-1.1-11]

D.10.6 Parametric Monitoring

D.10.7 Record Keeping Requirements

SECTION E National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]

E.1 General Provisions Relating to NESHAP Subpart M (National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products [326 IAC 20-1] [40 CFR Part 63, Subpart A])

E.2 NESHAP Subpart M Requirements [40 CFR 63, Subpart M]

E.3 One Time Deadlines Relating to NESHAP Subpart M

Certification

Emergency Occurrence Report

Quarterly Report Forms

Quarterly Deviation and Compliance Monitoring Report

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates magnet wire coating processes.

Responsible Official: Plant Manager
Source Address: 4300 New Haven Avenue, Ft. Wayne, Indiana 46803
Mailing Address: 4300 New Haven Avenue, Ft. Wayne, Indiana 46803
SIC Code: 3357
County Location: Allen
County Status: Nonattainment for ozone under the 8-hour standard
Attainment for all other criteria pollutants
Source Status: Part 70 Permit Program
Major Source, under PSD and Emission Offset Rules
Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

Under the Miscellaneous Metal Parts and Products Coating NESHAP (40 CFR 63, Subpart Mmmm), the following emission units are considered to be part of an existing magnet wire coating affected source.

- (a) Three (3) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 701-702, 703-704 and 705-706, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0023.
- (b) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 707-708 and 709-710, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0020.
- (c) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit numbers 804 and 805, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral), with ovens 804 and 805 exhausted at Stack/Vent 0033.

Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 808 and 809, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0396.
- (d) One (1) Quartz Fabric wire enameling oven, installed before 1977, emission unit number 810, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.
- (e) Four (4) Lepel Fabric wire enameling ovens, installed before 1980, emission unit numbers 807, 806, 803, and 802, each with a maximum capacity of 80 pounds of magnet wire per

hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0397.

- (f) One (1) Quartz Fabric wire enameling oven, installed 1992, emission unit number 811, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.
- (g) One (1) SICME ES enameling oven, installed March 1991, emission unit number 695, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0066.
- (h) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 690, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0068.
- (i) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 605, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0069.
- (j) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 600, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0071.
- (k) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 610, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0091.
- (l) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 640, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0113.
- (m) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 620, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0118.
- (n) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 670, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0122.
- (o) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 680, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0133.
- (p) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 351-352, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0172.
- (q) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 353-354, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0173.
- (r) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 355-356, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall

- be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0174.
- (s) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 367-368, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0175.
 - (t) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 365-366, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0176.
 - (u) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 363-364, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0177.
 - (v) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 373-374, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0196.
 - (w) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 371-372, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0197.
 - (x) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 369-370, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0198.
 - (y) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 357-358, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0199.
 - (z) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 359-360, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0200.
 - (aa) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 361-362, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0201.
 - (bb) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.
 - (cc) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.

Under the Miscellaneous Metal Parts and Products Coating NESHAP (40 CFR 63, Subpart MMMM), the following emission unit is considered to be a storage and mixing operation that is

considered to be part of an existing magnet wire coating affected source.

- (dd) One (1) applicator cleaning area, installed in January 1991, consisting of tanks 1 through 7, exhausted through stacks 0299, 0300 and 0301, capacity: 150 gallons each for tanks 1 and 2, 650 gallons for tank 3, 500 gallons each for tanks 4 and 5, 400 gallons for tank 6 and 500 gallons for tank 7.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1 (21):

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour [326 IAC 6-2-4]:
 - (1) One (1) 7.54 MMBtu natural gas fired boiler, designated as Boiler 1, installed in 1971, exhausting at Stack/Vent 0218.
 - (2) One (1) 7.54 MMBtu natural gas fired boiler, designated as Boiler 2, installed in 1971, exhausting at Stack/Vent 0222.
- (b) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment [326 IAC 6-3-2].
- (c) Emergency generator as follows: Natural gas turbines or reciprocating engines not exceeding 16,000 horsepower: One (1) Cummins 395 HP natural gas emergency generator exhausting to stack 415. This is an insignificant activity with no specifically applicable requirements. (Equipment referenced in Condition D.10.2).

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]

(a) This permit, T003-6925-00013, is issued for a fixed term of five (5) years from the original date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit or of permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control).

(b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

(a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act, or

(b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.6 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)] [326 IAC 2-7-6(6)]

(a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The submittal by the Permittee does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the responsible official as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit or, for information claimed to be confidential, the Permittee may furnish such records directly to the U. S. EPA along with a claim of confidentiality. [326 IAC 2-7-5(6)(E)]
- (c) The Permittee may include a claim of confidentiality in accordance with 326 IAC 17. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.9 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.10 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;

- (2) The compliance status;
- (3) Whether compliance was continuous or intermittent;
- (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
- (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the Δ responsible official \textcircled{a} as defined by 326 IAC 2-7-1(34).

**B.11 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]**

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee=s control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The PMP and the PMP extension notification do not require the certification by the Δ responsible official \textcircled{a} as defined by 326 IAC 2-7-1(34).

- (b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the Δ responsible official \textcircled{a} as defined by 326 IAC 2-7-1(34).
- (c) To the extent the Permittee is required by 40 CFR 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for the unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.12 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or
Telephone Number: 317-233-0178 (ask for Compliance Section)
Facsimile Number: 317-233-6865

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
 - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
 - (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations or emissions. However, IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(10) be revised in response to an emergency.

- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

B.13 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.
- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).

- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(7)]

B.14 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]

- (a) All terms and conditions of permits issued established prior to T003-6925-00013 and pursuant to permitting programs approved into the state implementation plan have been either
 - (1) incorporated as originally stated,
 - (2) revised under 326 IAC 2-7-10.5, or
 - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this combined permit, all previous registrations and permits are superseded by this Part 70 operating permit, except for permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control).

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.
- (c) Emergencies shall be included in the Quarterly Deviation and Compliance Monitoring Report.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
 - (1) That this permit contains a material mistake.

- (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
- (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
 - (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.

B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue

Indianapolis, Indiana 46204-2251

Any such application should be certified by the responsible official as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
[326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
- (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

B.21 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by 326 IAC 2 and 326 IAC 2-7-10.5.

B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy any records that must be kept under the conditions of this permit;
- (c) Inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.

- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Matter Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2(c)]

Pursuant to 326 IAC 6-3-2(c), the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:

- (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited, pursuant to the provisions of 40 CFR 61, Subpart M, is federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.7 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.8 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the Responsible official as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.10 Maintenance of Emission Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]

- (a) In the event that a breakdown of the emission monitoring equipment occurs, a record shall be made of the times and reasons of the breakdown and efforts made to correct the problem. To the extent practicable, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less frequent than required in Section D of this permit until such time as the monitoring equipment is back in operation. In the case of continuous monitoring, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less often than once an hour until such time as the continuous monitor is back in operation.
- (b) The Permittee shall install, calibrate, quality assure, maintain, and operate all necessary monitors and related equipment. In addition, prompt corrective action shall be initiated whenever indicated.

C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other

approved methods as specified in this permit.

C.12 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on February 27, 1998.
- (b) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level.
[326 IAC 1-5-3]

C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall submit:

- (a) A compliance schedule for meeting the requirements of 40 CFR 68; or
- (b) As a part of the annual compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP).

All documents submitted pursuant to this condition shall include the certification by the responsible official as defined by 326 IAC 2-7-1(34).

C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
 - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.

- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records;
 - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
 - (1) monitoring data;
 - (2) monitor performance data, if applicable; and
 - (3) corrective actions taken.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]

- (a) Pursuant to 326 IAC 2-6(a)(1), the Permittee shall submit by July 1 of each year an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:
 - (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
 - (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes Section 19 of this rule") from the source for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.
- (c) If there is a reasonable possibility that a "project" (as defined in 326 IAC 2-2-1 (qq) and 326 IAC 2-3-1(II)) at an existing emissions unit, other than projects at a Clean Unit, which is not part of a "major modification" (as defined in 326 IAC 2-2-1 (ee) and 326 IAC 2-3-1 (z)) may result in significant emissions increase and the Permittee elects to utilize the "projected actual emissions" (as defined in 326 IAC 2-2-1 (rr) and 326 IAC 2-3-1 (mm)), the Permittee shall comply with following:
 - (1) Before beginning actual construction of the "project" (as defined in 326 IAC 2-2-1 (qq) and 326 IAC 2-3-1 (II)) at an existing emissions unit, document and maintain the following records:
 - (A) A description of the project.
 - (B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.
 - (C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:
 - (i) Baseline actual emissions;
 - (ii) Projected actual emissions;
 - (iii) Amount of emissions excluded under section 326 IAC 2-2-1(rr)(2)(A)(iii) and 326 IAC 2-3-1(mm)(2)(A)(3); and
 - (iv) An explanation for why the amount was excluded, and any netting calculations, if applicable.
 - (2) Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and

- (3) Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR pollutant at the emissions unit.

C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.
- (f) If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any "project" (as defined in 326 IAC 2-2-1 (qq) and 326 IAC 2-3-1(II)) at an existing emissions unit, and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:
 - (1) The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as defined in 326 IAC 2-2-1 (xx) and 326 IAC 2-3-1 (qq), for that regulated NSR pollutant, and
 - (2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).
- (g) The report for project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:
 - (1) The name, address, and telephone number of the major stationary source.

- (2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.
- (3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-2-2(d)(3) and 326 IAC 2-3-2(c)(3).
- (4) Any other information that the Permittee deems fit to include in this report.

Reports required in this part shall be submitted to:

Indiana Department of Environmental Management
Air Compliance Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.

Stratospheric Ozone Protection

C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) Three (3) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 701-702, 703-704 and 705-706, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0023.
- (b) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 707-708 and 709-710, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0020.
- (c) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit numbers 804 and 805, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral), with ovens 804 and 805 exhausted at Stack/Vent 0033.

Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 808 and 809, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0396.
- (d) One (1) Quartz Fabric wire enameling oven, installed before 1977, emission unit number 810, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Volatile Organic Compound (VOC)

- (a) Pursuant to 326 IAC 8-6 (Organic Solvent Emission Limitations), the VOC emitted from the ten (10) Quartz Fabric wire enameling ovens, emission units 701-702, 703-704, 705-706, 707-708, 709-710, 804, 805, 808, 809 and 810, shall be reduced by at least eighty-five percent (85%).
- (b) Any change or modification which may increase potential emissions from the ten (10) Quartz Fabric wire enameling ovens shall require prior approval from the OAQ before such change may occur.

D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.1.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to 326 IAC 8-1-2(a), the Permittee shall operate the thermal oxidizers to achieve compliance with Condition D.1.1.

D.1.4 Thermal Oxidizer Operation

- (a) Pursuant to the Construction Permit issued on October 17, 1997 (CP 003-8609-00013), the thermal oxidizers shall operate at all times that the ten (10) Quartz Fabric ovens are in operation. When operating, the thermal oxidizers shall maintain a minimum 3 hour average temperature of 1150 deg F or the 3 hour block average minimum temperature

determined in the latest compliance testing to maintain a destruction efficiency of not less than ninety percent (90%) of volatile organic compound (VOC) in order to demonstrate compliance with Condition D.1.1.

- (b) In order to satisfy the requirements of 326 IAC 8-6 and Condition D.1.1, the external thermal oxidizers must operate with a minimum destruction efficiency of ninety percent (90%) and a minimum capture efficiency such that the overall control efficiency is at least eighty-five percent (85%).

D.1.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Conditions D.1.1, D.3.1 and D.3.2, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Conditions D.1.3 and D.3.4 for the thermal oxidizers using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative thermal oxidizer from the five oxidizers controlling the eleven (11) Quartz Fabric enamel ovens listed in Sections D.1 and D.3 shall be tested. The thermal oxidizer tested shall be the oxidizer in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.1.3 for the thermal oxidizers using methods approved by the Commissioner.
- (d) For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:
 - (1) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (2) Calculate the current maximum VOC loading ($L_{current}$);
 - (3) If L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within

thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.

- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.7 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.6, the Permittee shall maintain:
- (1) Records of the VOC emitted based on: VOC delivered to the applicators x (1 - % overall control efficiency/100).
 - (2) Continuous temperature records and 3 hour average temperature records.
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

SECTION D.2 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (e) Four (4) Lepel Fabric wire enameling ovens, installed before 1980, emission unit numbers 807, 806, 803, and 802, each with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0397.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Volatile Organic Compound (VOC)

- (a) Pursuant to 326 IAC 8-6 (Organic Solvent Emission Limitations), the VOC emitted from the four (4) Lepel Fabric wire enameling ovens, emission units 807, 806, 803 and 802 shall be reduced by at least eighty-five percent (85%).
- (b) Any change or modification which may increase potential emissions from the four (4) Lepel Fabric wire enameling ovens shall require prior approval from the OAQ before such change may occur.

D.2.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to 326 IAC 8-1-2(a), the Permittee shall operate the thermal oxidizers to achieve compliance with Condition D.2.1.

D.2.4 Thermal Oxidizer Operation

- (a) Pursuant to the Construction Permit issued on October 17, 1997 (CP 003-8609-00013), the external thermal oxidizer shall operate at all times that the four (4) Lepel Fabric ovens are in operation. When operating, the external thermal oxidizer shall maintain a minimum 3 hour average temperature of 1150 deg F or the 3 hour block average minimum temperature determined in the latest compliance testing to maintain a destruction efficiency of not less than ninety percent (90%) of volatile organic compound (VOC) captured in order to demonstrate compliance with Condition D.2.1.
- (b) In order to ensure compliance with Condition D.2.1 and (a) above, the external thermal oxidizer must operate with a minimum destruction efficiency of ninety percent (90%) and a minimum capture efficiency such that the overall control efficiency is at least eighty-five percent (85%).

D.2.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.2.1, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.2.3 for the thermal oxidizer using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) The oxidizer that controls the four (4) Lepel Quartz Fabric enamel ovens shall be tested. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.

- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.2.3 for the thermal oxidizer using methods approved by the Commissioner.
- (d) For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:
 - (1) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (2) Calculate the current maximum VOC loading ($L_{current}$);
 - (3) If L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.7 Record Keeping Requirements

- (a) To document compliance with Condition D.2.1 and D.2.6, the Permittee shall maintain:
 - (1) Records of the VOC emitted based on: VOC delivered to the applicators x (1 - % overall control efficiency/100).
 - (2) Continuous temperature records and 3 hour average temperature records.
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (f) One (1) Quartz Fabric wire enameling oven, installed 1992, emission unit number 811, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Volatile Organic Compounds [326 IAC 8-2-8]

- (a) Pursuant to 326 IAC 8-2-8 (Magnet Wire Coating Operations) and CP 003-8609-00013 issued on October 17, 1997, the owner or operator shall not allow the discharge into the atmosphere of VOC in excess of 1.7 pounds VOC per gallon of coating, excluding water, as delivered to the applicator.
- (b) The equivalent pounds of VOC per gallon of coating solids (as applied) shall be limited to less than 2.21, when L is equal to 1.7 pounds of VOC per gallon of coating and D is equal to 7.36 pounds of VOC per gallon of coating.
- (c) Pursuant to 326 IAC 8-1-2 (b), the enameling oven's VOC emission shall be limited to no greater than the equivalent emissions, expressed as pounds of VOC per gallon coating solids, allowed in (a).

This equivalency was determined by the following equation:

$$E = L / (1 - (L/D))$$

Where

- L= Applicable emission limit from 326 IAC 8 in pounds of VOC per gallon of coating
D= Density of VOC in coating in pounds per gallon of VOC
E= Equivalent emission limit in pounds of VOC per gallon of coating solids as applied

Actual solvent density shall be used to determine compliance of surface coating operation using the compliance methods in 326 IAC 8-1-2 (a).

- (d) Pursuant to 326 IAC 8-1-2(c), the equivalent overall control efficiency of the thermal oxidizer shall be no less than 91.1% or the required destruction efficiency demonstrated by the most recent stack test, for the worst case VOC coating currently used; for a higher VOC content coating, the overall control efficiency of these units shall be no less than the estimated control efficiency required to achieve compliance with the VOC limit in Condition D.3.1(a).

The overall control efficiency (O) of the thermal oxidizers shall be calculated by the following equation:

$$O = \frac{V - E}{V} \times 100$$

Where:

- V = The actual VOC content of the coating or, if multiple coatings are used, the daily weighted average VOC content of all coatings, as applied to the subject coating line as determined by the applicable test methods and procedures specified in 326 IAC 8-1-4 in units of pounds of VOC per gallon of coating solids as applied.
- E = Equivalent emission limit in pounds of VOC per gallon of coating solids as applied.
- O = Equivalent overall control efficiency of the capture system and control device as a percentage.

D.3.2 PSD Limit [326 IAC 2-2]

Pursuant to CP 003-8609-00013 issued on October 17, 1997, the VOC emissions from the Quartz Fabric oven (emission unit 811)(Section D.3), and the applicator cleaning area (Section D.7) shall be limited to less than 40 tons VOC per twelve (12) consecutive month period. Compliance with this limit shall render 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control device.

Compliance Determination Requirements

D.3.4 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to CP 003-8609-00013, issued October 17, 1997 and 326 IAC 8-1-2(a), the Permittee shall operate the external thermal oxidizer to achieve compliance with Conditions D.3.1 and D.3.2.

D.3.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Conditions D.1.1, D.3.1 and D.3.2, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Conditions D.1.3 and D.3.4 for the thermal oxidizer using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative thermal oxidizer from the five oxidizers controlling the eleven (11) Quartz Fabric enamel ovens listed in Sections D.1 and D.3 shall be tested. The thermal oxidizer tested shall be the oxidizer in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.3.1 for the thermal oxidizer using methods approved by the Commissioner.
- (d) For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:
- (1) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (3) Calculate the current maximum VOC loading ($L_{current}$);
 - (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

D.3.6 VOC Emissions

Compliance with Condition D.3.2 shall be demonstrated within 30 days of the end of each month. This shall be based on the total volatile organic compound emitted for the previous month, and adding it to previous 11 months total VOC emitted so as to arrive at VOC emission for 12

consecutive months period. The VOC emissions for a month can be arrived at using the following equation for VOC usage:

$$\text{VOC emitted} = [(\text{VOC input}) \times ((100 - \% \text{control efficiency})/100)] + [\text{uncontrolled VOC input}]$$

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.3.7 Thermal Oxidizer Operation

- (a) From the date of issuance of the Part 70 permit until the approved stack test results are available, the Permittee shall operate the thermal oxidizer 3 hour average temperature at or above the temperature of 1150 deg F.
- (b) The Permittee shall determine the 3 hour block average minimum temperature from the most recent valid stack test that demonstrates compliance with limits in Conditions D.3.1 and D.3.2, as approved by IDEM.
- (c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizer at or above the 3 hour block average minimum temperature as observed during the compliant stack test.

D.3.8 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.3.9 Record Keeping Requirements

- (a) To document compliance with Conditions D.3.1 and D.3.2, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC content limits and/or the VOC emission limits established in Conditions D.3.1 and D.3.2.
 - (1) The VOC content of each coating material and solvent used less water.

- (2) Records shall include material balance calculations, purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) The monthly cleanup solvent usage.
 - (4) The total VOC usage for each month.
 - (5) The VOC emitted based on: $\text{VOC delivered to the applicators} \times (1 - \% \text{ overall control efficiency}/100) + \text{VOC in cleaning solvent}$.
- (b) To document compliance with Condition D.3.8, the Permittee shall maintain the continuous temperature records and 3 hour average temperature records.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.3.10 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.3.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.4

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (g) One (1) SICME ES enameling oven, installed March 1991, emission unit number 695, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0066.
- (h) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 690, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0068.
- (i) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 605, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0069.
- (j) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 600, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0071.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.1 Volatile Organic Compounds [326 IAC 8-2-8]

- (a) Pursuant to 326 IAC 8-2-8 (Magnet Wire Coating Operations), and CP 003-6199-00013 issued on February 11, 1997, the owner or operator shall not allow the discharge into the atmosphere of VOC in excess of 1.7 pounds VOC per gallon of coating, excluding water, as delivered to the applicator.
- (b) The equivalent pounds of VOC per gallon of coating solids (as applied) shall be limited to less than 2.21, when L is equal to 1.7 pounds of VOC per gallon of coating and D is equal to 7.36 pounds of VOC per gallon of coating.
- (c) Pursuant to 326 IAC 8-1-2 (b), the enameling ovens= VOC emission shall be limited to no greater than the equivalent emissions, expressed as pounds of VOC per gallon coating solids, allowed in (a).

This equivalency was determined by the following equation:

$$E = L / (1 - (L/D))$$

Where

- L= Applicable emission limit from 326 IAC 8 in pounds of VOC per gallon of coating
- D= Density of VOC in coating in pounds per gallon of VOC
- E= Equivalent emission limit in pounds of VOC per gallon of coating solids as applied

Actual solvent density shall be used to determine compliance of surface coating operation using the compliance methods in 326 IAC 8-1-2 (a).

- (d) Pursuant to 326 IAC 8-1-2(c), the equivalent overall control efficiency of the thermal oxidizers shall be no less than 96.7% or the required destruction efficiency demonstrated by the most recent stack test, for the worst case VOC coating currently used; for a higher VOC content coating, the overall control efficiency of these units shall be no less than the

estimated control efficiency required to achieve compliance with the VOC limit in Condition D.4.1(a).

The overall control efficiency (O) of the thermal oxidizers shall be calculated by the following equation:

$$O = \frac{V - E}{V} \times 100$$

Where:

- V = The actual VOC content of the coating or, if multiple coatings are used, the daily weighted average VOC content of all coatings, as applied to the subject coating line as determined by the applicable test methods and procedures specified in 326 IAC 8-1-4 in units of pounds of VOC per gallon of coating solids as applied.
- E = Equivalent emission limit in pounds of VOC per gallon of coating solids as applied.
- O = Equivalent overall control efficiency of the capture system and control device as a percentage.

D.4.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.4.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to CP 003-8609-00013, issued October 17, 1997 and 326 IAC 8-1-2(a), the Permittee shall operate the internal thermal oxidizers to achieve compliance with Condition D.4.1.

D.4.4 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.4.1, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.4.1 for the thermal oxidizers using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative oven from the four (4) SICME ES enamel ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.4.1 for the thermal oxidizers using methods approved by the Commissioner.
- (d) For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:
- (1) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (3) Calculate the current maximum VOC loading ($L_{current}$);

- (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than L_{current} , Permittee shall be allowed to use the higher VOC content enamel.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.4.5 Thermal Oxidizer Operation

- (a) From the date of issuance of the Part 70 permit until the approved stack test results are available, the Permittee shall operate the thermal oxidizers 3 hour average temperature at or above the temperature of 1400 deg F.
- (b) The Permittee shall determine the 3 hour block average minimum temperature from the most recent valid stack test that demonstrates compliance with limits in Condition D.4.1, as approved by IDEM.
- (c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizer at or above the 3 hour block average minimum temperature as observed during the compliant stack test.

D.4.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the integral thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.4.7 Record Keeping Requirements

- (a) To document compliance with Condition D.4.1, the Permittee shall maintain records in accordance with (1) through (2) below. Records maintained for (1) through (2) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC content limits and/or the VOC emission limits established in Conditions D.4.1.
- (1) The VOC content of each coating material and solvent used less water.
- (2) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.

- (b) To document compliance with Condition D.4.6, the Permittee shall maintain the continuous temperature records and 3 hour average temperature records.
- (c) All records shall be maintained in accordance with Section C- General Record Keeping Requirements, of this permit.

SECTION D.5

FACILITY CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (k) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 610, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0091.
- (l) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 640, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0113.
- (m) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 620, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0118.
- (n) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 670, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0122.
- (o) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 680, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0133.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.5.1 Volatile Organic Compound (VOC)

- (a) Pursuant to 326 IAC 8-6 (Organic Solvent Emission Limitations), the VOC emitted from the five (5) Square/Rectangular wire enameling ovens, emission units 610, 640, 620, 670, and 680 shall be reduced by at least eighty-five percent (85%).
- (b) Any change or modification which may increase potential emissions from the five (5) Square/Rectangular wire enameling ovens shall require prior approval from the OAQ before such change may occur.

D.5.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.5.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to 326 IAC 8-1-2(a), the Permittee shall operate the thermal oxidizers to achieve compliance with Condition D.5.1.

D.5.4 Thermal Oxidizer Operation

To ensure compliance with Condition D.5.1, the external thermal oxidizers shall operate at all times that the five (5) square/rectangular ovens are in operation. When operating, the external thermal oxidizers shall maintain a minimum 3 hour average temperature of 1100 deg F or the 3 hour block average minimum temperature determined in the latest compliance testing to maintain a volatile organic compound (VOC) overall control efficiency of not less than eighty-five percent (85%) to demonstrate compliance with Condition D.5.1.

D.5.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.5.1, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.5.3 for the thermal oxidizer using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative oven from the five (5) Square/Rectangular enamel ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.5.3 for the thermal oxidizers using methods approved by the Commissioner.
- (d) For a higher VOC content coating, the following procedure shall be followed:
 - (1) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (3) Calculate the current maximum VOC loading ($L_{current}$);
 - (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.5.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.5.7 Record Keeping Requirements

- (a) To document compliance with Conditions D.5.1 and D.5.6, the Permittee shall maintain:
 - (1) Records of the VOC emitted based on: VOC delivered to the applicators x (1 - % overall control efficiency/100).
 - (2) Continuous temperature records and 3 hour average temperature records.
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

SECTION D.6

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (p) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 351-352, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0172.
- (q) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 353-354, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0173.
- (r) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 355-356, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0174.
- (s) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 367-368, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0175.
- (t) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 365-366, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0176.
- (u) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 363-364, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0177.
- (v) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 373-374, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0196.
- (w) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 371-372, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0197.
- (x) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 369-370, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0198.
- (y) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 357-358, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0199.
- (z) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 359-360, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0200.
- (aa) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 361-362, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0201.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.6.1 Volatile Organic Compound (VOC)

- (a) Pursuant to 326 IAC 8-6 (Organic Solvent Emission Limitations), the VOC emitted from the twelve (12) MOCO wire enameling ovens, emission units 351-352, 353-354, 355-356, 367-368, 365-366, 363-364, 373-374, 371-372, 369-370, 357-358, 359-360, and 361-362 shall be reduced by at least eighty-five percent (85%).

- (b) Any change or modification which may increase potential emissions from the twelve (12) MOCO wire enameling ovens shall require prior approval from the OAQ before such change may occur.

D.6.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.6.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to 326 IAC 8-1-2(a), the Permittee shall operate the thermal oxidizers to achieve compliance with Condition D.6.1.

D.6.4 Thermal Oxidizer

In order to satisfy the requirements of 326 IAC 8-6 and Condition D.6.1, the external thermal oxidizers must operate such that the overall control efficiency is at least eighty-five percent (85%).

D.6.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.6.1, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.6.3 for the thermal oxidizers using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative oven from the twelve (12) MOCO enamel ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.6.3 for the thermal oxidizers using methods approved by the Commissioner.
- (d) For a higher VOC content coating, the following procedure shall be followed:
 - (1) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (3) Calculate the current maximum VOC loading ($L_{current}$);
 - (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.6.6 Thermal Oxidizer Operation

- (a) From the date of issuance of the Part 70 permit until the approved stack test results are available, the Permittee shall operate the thermal oxidizers 3 hour average temperature at or above the temperature of 1100 deg F.
- (b) The Permittee shall determine the 3 hour block average minimum temperature from the most recent valid stack test that demonstrates compliance with limits in Condition D.6.1, as approved by IDEM.

- (c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizers at or above the 3 hour block average minimum temperature as observed during the compliant stack test.

D.6.7 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.6.8 Record Keeping Requirements

- (a) To document compliance with Conditions D.6.1 and D.6.7, the Permittee shall maintain:
 - (1) Records of the VOC emitted based on: VOC delivered to the applicators x (1 – % overall control efficiency/100).
 - (2) Continuous temperature records and 3 hour average temperature records.
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

SECTION D.7

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (dd) One (1) applicator cleaning area, installed January 1991 consisting of tanks 1 through 7, exhausted through stacks 0299, 0300 and 0301, capacity: 150 gallons each for tanks 1 and 2, 650 gallons for tank 3, 500 gallons each for tanks 4 and 5, 400 gallons for tank 6 and 500 gallons for tank 7.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.7.1 PSD Limit [326 IAC 2-2]

Pursuant to CP 003-8609-00013 issued on October 17, 1997, the VOC emissions from the Quartz Fabric oven (emission unit 811)(Section D.3), and the applicator cleaning area (Section D.7) shall be limited to less than 40 tons per twelve (12) consecutive months of VOC. Compliance with this limit shall render 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.7.2 Volatile Organic Compounds (VOC)

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations) for cold cleaner operations constructed after January 1980, the owner or operator shall:

- (a) Equip the cleaner with a cover;
- (b) Equip the cleaner with a facility for draining cleaned parts;
- (c) Close the degreaser cover whenever parts are not being handled in the cleaner;
- (d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;
- (e) Provide a permanent, conspicuous label summarizing the operation requirements;
- (f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

D.7.3 Volatile Organic Compounds (VOC)

(a) Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaner degreaser facility construction of which commenced after July 1, 1990 shall ensure that the following control equipment requirements are met:

- (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:
 - (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F));
 - (B) The solvent is agitated; or
 - (C) The solvent is heated.
- (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32)

millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.

- (3) Provide a permanent, conspicuous label which lists the operating requirements outlined in subsection (b).
- (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure which does not cause excessive splashing.
- (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):
 - (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
 - (B) A water cover when solvent is used is insoluble in, and heavier than, water.
 - (C) Other systems of demonstrated equivalent control such as a refrigerated chiller of carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.7.4 Record Keeping Requirements

- (a) To document compliance with Condition D.7.1, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC emission limits established in Conditions D.7.1.
 - (1) The VOC content of each cleanup solvent used less water.
 - (2) The amount of cleanup solvent used on a monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (3) Records of waste solvents shipped offsite for treatment.
 - (4) The total net VOC usage for each month.
 - (5) The weight of VOCs emitted for each compliance period.
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements, of this permit.

D.7.5 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.7.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.8

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour [326 IAC 6-2-4]:
- (1) One (1) 7.54 MMBtu natural gas fired boiler, designated as Boiler 1, installed in 1971, exhausting at Stack/Vent 0218.
 - (2) One (1) 7.54 MMBtu natural gas fired boiler, designated as Boiler 2, installed in 1971, exhausting at Stack/Vent 0222.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.8.1 Particulate Matter (PM) [326 IAC 6-2-3]

Pursuant to 326 IAC 6-2-3(d) (Particulate Matter Emission Limitations for Sources of Indirect Heating) the PM emissions from each boiler shall be limited to 0.80 pounds per MMBtu heat input.

SECTION D.9

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (b) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.9.1 Particulate Matter (PM) [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Process Operations), the allowable PM emission rate for each of the manufacturing activities shall not exceed allowable PM emission rate based on the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

SECTION D.10 FACILITY CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (bb) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.
- (cc) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.10.1 Volatile Organic Compound (VOC) [326 IAC 8-2-8]

- (a) Pursuant to 326 IAC 8-2-8 (Magnet Wire Coating Operations), the Permittee shall not allow the discharge into the atmosphere of VOC in excess of 1.7 pounds VOC per gallon of coating, excluding water, as delivered to the applicator.
- (b) The equivalent pounds of VOC per gallon of coating solids (as applied) shall be limited to less than 2.21, when L is equal to 1.7 pounds of VOC per gallon of coating and D is equal to 7.36 pounds of VOC per gallon of coating.
- (c) Pursuant to 326 IAC 8-1-2 (b), the enameling ovens VOC emission shall be limited to no greater than the equivalent emissions, expressed as pounds of VOC per gallon coating solids, allowed in (a).

This equivalency was determined by the following equation:

$$E = L / (1 - (L/D))$$

Where

- L= Applicable emission limit from 326 IAC 8 in pounds of VOC per gallon of coating
- D= Density of VOC in coating in pounds per gallon of VOC
- E= Equivalent emission limit in pounds of VOC per gallon of coating solids as applied

Actual solvent density shall be used to determine compliance of the surface coating operation using the compliance methods in 326 IAC 8-1-2 (a).

- (d) Pursuant to 326 IAC 8-1-2(c), the equivalent overall control efficiency of the internal integral catalytic oxidizers and the external thermal oxidizers shall be no less than 95.9% or the required overall control efficiency demonstrated by the most recent stack test, for the worst case VOC coating currently used; for a higher VOC content coating, the overall control efficiency of these units shall be no less than the estimated control efficiency required to achieve compliance with the VOC limit in Condition D.10.1(a).

The overall control efficiency (O) of the internal integral catalytic oxidizers and the external thermal oxidizers shall be calculated by the following equation:

$$O = \frac{V - E}{V} \times 100$$

Where:

- V = The actual VOC content of the coating or, if multiple coatings are used, the daily weighted average VOC content of all coatings, as applied to the subject coating line as determined by the applicable test methods and procedures specified in 326 IAC 8-1-4 in units of pounds of VOC per gallon of coating solids as applied.
- E = Equivalent emission limit in pounds of VOC per gallon of coating solids as applied.
- O = Equivalent overall control efficiency of the capture system and control device as a percentage.

D.10.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.10.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to 326 IAC 8-1-2(a), the Permittee shall operate the catalytic and thermal oxidizers to achieve compliance with Condition D.10.1.

D.10.4 Oxidizer Operation

To ensure compliance with Condition D.10.1, the internal catalytic oxidizers and the external thermal oxidizers shall operate at all times that the two (2) wire enameling ovens are in operation. When operating, the internal catalytic oxidizers and the external thermal oxidizer shall maintain a 3 hour average temperature of 1100 deg F or the 3 hour block average minimum temperature determined in the latest compliance testing to maintain a volatile organic compound (VOC) overall control efficiency of not less than 95.9% to demonstrate compliance with Condition D.10.1.

D.10.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.10.1, within one hundred and eighty (180) days after initial startup, the Permittee shall conduct performance tests to verify VOC control efficiency for the internal catalytic oxidizer and the external thermal oxidizer using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative oven from the two (2) wire enameling ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency for the oxidizers using methods approved by the Commissioner.
- (d) For a higher VOC content coating, the following procedure shall be followed:
- (1) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (3) Calculate the current maximum VOC loading ($L_{current}$);
 - (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.10.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the oxidizers for measuring operating temperature of the internal catalytic oxidizers and the external thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the oxidizers are in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the oxidizers. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizers shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.10.7 Record Keeping Requirements

- (a) To document compliance with Conditions D.10.1 and D.10.6, the Permittee shall maintain records in accordance with (1) through (2) below. Records maintained for (1) through (2) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC content limits and/or the VOC emission limits established in Conditions D.4.1.
 - (1) The VOC content of each coating material and solvent used less water.
 - (2) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
- (b) To document compliance with Condition D.10.6, the Permittee shall maintain the continuous temperature records and 3 hour average temperature records.
- (c) All records shall be maintained in accordance with Section C- General Record Keeping Requirements, of this permit.

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

Under the Miscellaneous Metal Parts and Products Coating NESHAP (40 CFR 63, Subpart Mmmm), the following emission units are considered to be part of an existing magnet wire coating affected source.

- (a) Three (3) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 701-702, 703-704 and 705-706, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0023.
- (b) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 707-708 and 709-710, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0020.
- (c) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit numbers 804 and 805, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral), with ovens 804 and 805 exhausted at Stack/Vent 0033.

Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 808 and 809, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0396.
- (d) One (1) Quartz Fabric wire enameling oven, installed before 1977, emission unit number 810, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.
- (e) Four (4) Lepel Fabric wire enameling ovens, installed before 1980, emission unit numbers 807, 806, 803, and 802, each with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0397.
- (f) Four (4) Lepel Fabric wire enameling ovens, installed before 1980, emission unit number 802,803, 806 and 807, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0397.
- (g) One (1) SICME ES enameling oven, installed March 1991, emission unit number 695, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0066.
- (h) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 690, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0068.
- (i) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 605, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0069.
- (j) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 600, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0071.
- (k) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 610, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0091.
- (l) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 640, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0113.
 - (m) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 620, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0118.
 - (n) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 670, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0122.
 - (o) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 680, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0133.
 - (p) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 351-352, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0172.
 - (q) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 353-354, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0173.
 - (r) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 355-356, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0174.
 - (s) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 367-368, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0175.
 - (t) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 365-366, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0176.
 - (u) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 363-364, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0177.
 - (v) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 373-374, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0196.
 - (w) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 371-372, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0197.
 - (x) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 369-370, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0198.
 - (y) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 357-358, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0199.

- (z) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 359-360, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0200.
- (aa) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 361-362, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0201.
- (bb) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.
- (cc) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.

Under the Miscellaneous Metal Parts and Products Coating NESHAP (40 CFR 63, Subpart M MMM), the following emission unit is considered to be a storage and mixing operation that is considered to be part of an existing magnet wire coating affected source.

- (dd) One (1) applicator cleaning area, installed in January 1991, consisting of tanks 1 through 7, exhausted through stacks 0299, 0300 and 0301, capacity: 150 gallons each for tanks 1 and 2, 650 gallons for tank 3, 500 gallons each for tanks 4 and 5, 400 gallons for tank 6 and 500 gallons for tank 7.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]

- E.1 General Provisions Relating to NESHAP Subpart M MMM (National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products [326 IAC 20-1] [40 CFR Part 63, Subpart A])

Pursuant to 40 CFR 63.3901, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1 as specified in Table 2 of 40 CFR Part 63, Subpart M MMM in accordance with schedule in 40 CFR 63 Subpart M MMM

- E.2 NESHAP Subpart M MMM Requirements [40 CFR 63, Subpart M MMM]

Pursuant to 40 CFR 63, Subpart M MMM, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart M MMM, for the entire source, beginning January 2, 2007, as follows:

§ 63.3880 What is the purpose of this subpart?

This subpart establishes national emission standards for hazardous air pollutants (NESHAP) for miscellaneous metal parts and products surface coating facilities. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations.

§ 63.3881(a)(4) and (b) Am I subject to this subpart?

(a) Miscellaneous metal parts and products include, but are not limited to, metal components of the following types of products as well as the products themselves: motor vehicle parts and accessories, bicycles and sporting goods, recreational vehicles, extruded aluminum structural components, railroad cars, heavy duty trucks, medical equipment, lawn and garden equipment, electronic equipment, magnet wire, steel drums, industrial machinery, metal pipes, and numerous other industrial, household, and consumer products. Except as provided in paragraph (c) of this section, the source category to which this subpart applies is the surface coating of any miscellaneous metal parts or products, as described in paragraph (a)(1) of this section, and it includes the subcategories listed in paragraphs (a)(2) through (6) of this section.

(1) – (3) ****

(4) The magnet wire coating subcategory includes surface coating operations that are performed using coatings that meet the definition of magnet wire coatings in §63.3981.

(b) You are subject to this subpart if you own or operate a new, reconstructed, or existing affected source, as defined in §63.3882, that uses 946 liters (250 gallons (gal)) per year, or more, of coatings that contain hazardous air pollutants (HAP) in the surface coating of miscellaneous metal parts and products defined in paragraph (a) of this section; and that is a major source, is located at a major source, or is part of a major source of emissions of HAP. A major source of HAP emissions is any stationary source or group of stationary sources located within a contiguous area and under common control that emits or has the potential to emit any single HAP at a rate of 9.07 megagrams (Mg) (10 tons) or more per year or any combination of HAP at a rate of 22.68 Mg (25 tons) or more per year. You do not need to include coatings that meet the definition of non-HAP coating contained in §63.3981 in determining whether you use 946 liters (250 gal) per year, or more, of coatings in the surface coating of miscellaneous metal parts and products.

§ 63.3882 What parts of my plant does this subpart cover?

(a) This subpart applies to each new, reconstructed, and existing affected source within each of the four subcategories listed in §63.3881(a).

(b) The affected source is the collection of all of the items listed in paragraphs (b)(1) through (4) of this section that are used for surface coating of miscellaneous metal parts and products within each subcategory.

(1) All coating operations as defined in §63.3981;

(2) All storage containers and mixing vessels in which coatings, thinners and/or other additives, and cleaning materials are stored or mixed;

(3) All manual and automated equipment and containers used for conveying coatings, thinners and/or other additives, and cleaning materials; and

(4) All storage containers and all manual and automated equipment and containers used for conveying waste materials generated by a coating operation.

(c) An affected source is a new affected source if you commenced its construction after August 13, 2002 and the construction is of a completely new miscellaneous metal parts and products surface coating facility where previously no miscellaneous metal parts and products surface coating facility had existed.

(d) An affected source is reconstructed if it meets the criteria as defined in §63.2.

(e) An affected source is existing if it is not new or reconstructed.

§ 63.3883(b) and (d) When do I have to comply with this subpart?

The date by which you must comply with this subpart is called the compliance date. The compliance date for each type of affected source is specified in paragraphs (a) through (c) of this section. The compliance

date begins the initial compliance period during which you conduct the initial compliance demonstration described in §§63.3940, 63.3950, and 63.3960.

(a) ****

(b) For an existing affected source, the compliance date is the date 3 years after January 2, 2004.

(c) ****

(d) You must meet the notification requirements in §63.3910 according to the dates specified in that section and in subpart A of this part. Some of the notifications must be submitted before the compliance dates described in paragraphs (a) through (c) of this section.

§ 63.3890 What emission limits must I meet?

(a) ****

(b) For an existing affected source, you must limit organic HAP emissions to the atmosphere from the affected source to the applicable limit specified in paragraphs (b)(1) through (5) of this section, except as specified in paragraph (c) of this section, determined according to the requirements in §63.3941, §63.3951, or §63.3961.

(1) ****

(2) ****

(3) For each existing magnet wire coating affected source, limit organic HAP emissions to no more than 0.12 kg (1.0 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(4) ****

(5) ****

(c) If your facility's surface coating operations meet the applicability criteria of more than one of the subcategory emission limits specified in paragraphs (a) or (b) of this section, you may comply separately with each subcategory emission limit or comply using one of the alternatives in paragraph (c)(1) or (2) of this section.

(1) If the general use or magnet wire surface coating operations subject to only one of the emission limits specified in paragraphs (a)(1), (3), (b)(1), or (3) of this section account for 90 percent or more of the surface coating activity at your facility (*i.e.*, it is the predominant activity at your facility), then compliance with that one emission limitations in this subpart for all surface coating operations constitutes compliance with the other applicable emission limits. You must use liters (gal) of solids used as a measure of relative surface coating activity over a representative period of operation. You may estimate the relative volume of coating solids used from parameters other than coating consumption and volume solids content (*e.g.*, design specifications for the parts or products coated and the number of items produced). The determination of predominant activity must accurately reflect current and projected coating operations and must be verifiable through appropriate documentation. The use of parameters other than coating consumption and volume solids content must be approved by the Administrator. You may use data for any reasonable time period of at least 1 year in determining the relative amount of coating activity, as long as they represent the way the source will continue to operate in the future and are approved by the Administrator. You must determine the predominant activity at your facility and submit the results of that determination with the initial notification required by §63.3910(b). Additionally, you must determine the facility's predominant activity annually and include the determination in the next semi-annual compliance report required by §63.3920(a).

(2) You may calculate and comply with a facility-specific emission limit as described in paragraphs (c)(2)(i) through (iii) of this section. If you elect to comply using the facility-specific emission limit alternative, then compliance with the facility-specific emission limit and the emission limitations in this subpart for all surface coating operations constitutes compliance with this and other applicable surface coating NESHAP. In calculating a facility-specific emission limit, you must include coating activities that meet the applicability

criteria of the other subcategories and constitute more than 1 percent of total coating activities. Coating activities that meet the applicability criteria of other surface coating NESHAP but comprise less than 1 percent of coating activities need not be included in the determination of predominant activity but must be included in the compliance calculation.

(i) You are required to calculate the facility-specific emission limit for your facility when you submit the notification of compliance status required in §63.3910(c), and on a monthly basis afterward using the coating data for the relevant 12-month compliance period.

(ii) Use Equation 1 of this section to calculate the facility-specific emission limit for your surface coating operations for each 12-month compliance period.

$$\text{Facility Specific Emission Unit} = \frac{\sum_{i=1}^n (\text{Limit}_i)(\text{Solid}_i)}{\sum_{i=1}^n (\text{Solid}_i)}$$

Where:

Facility-specific emission limit = Facility-specific emission limit for each 12-month compliance period, kg (lb) organic HAP per kg (lb) coating solids used.

Limit_i = The new source or existing source emission limit applicable to coating operation, i, included in the facility-specific emission limit, converted to kg (lb) organic HAP per kg (lb) coating solids used, if the emission limit is not already in those units. All emission limits included in the facility-specific emission limit must be in the same units.

Solids_i = The liters (gal) of solids used in coating operation, i, in the 12-month compliance period that is subject to emission limit, i. You may estimate the volume of coating solids used from parameters other than coating consumption and volume solids content (e.g., design specifications for the parts or products coated and the number of items produced). The use of parameters other than coating consumption and volume solids content must be approved by the Administrator.

n = The number of different coating operations included in the facility-specific emission limit.

(iii) ****

§ 63.3891(c) What are my options for meeting the emission limits?

You must include all coatings (as defined in §63.3981), thinners and/or other additives, and cleaning materials used in the affected source when determining whether the organic HAP emission rate is equal to or less than the applicable emission limit in §63.3890. To make this determination, you must use at least one of the three compliance options listed in paragraphs (a) through (c) of this section. You may apply any of the compliance options to an individual coating operation, or to multiple coating operations as a group, or to the entire affected source. You may use different compliance options for different coating operations, or at different times on the same coating operation. You may employ different compliance options when different coatings are applied to the same part, or when the same coating is applied to different parts. However, you may not use different compliance options at the same time on the same coating operation. If you switch between compliance options for any coating operation or group of coating operations, you must document this switch as required by §63.3930(c), and you must report it in the next semiannual compliance report required in §63.3920.

(a) ****

(b) ****

(c) *Emission rate with add-on controls option.* Demonstrate that, based on the coatings, thinners and/or other additives, and cleaning materials used in the coating operation(s), and the emissions reductions achieved by emission capture systems and add-on controls, the organic HAP emission rate for the coating operation(s) is less than or equal to the applicable emission limit in §63.3890, calculated as a rolling 12-month emission rate and determined on a monthly basis. If you use this compliance option, you must also demonstrate that all emission capture systems and add-on control devices for the coating operation(s) meet the operating limits required in §63.3892, except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), and that you meet the work practice standards required in §63.3893. You must meet all the requirements of §§63.3960 through 63.3968 to demonstrate compliance with the emission limits, operating limits, and work practice standards using this option.

§ 63.3892(b) and (c) What operating limits must I meet?

(a) ****

(b) For any controlled coating operation(s) on which you use the emission rate with add-on controls option, except those for which you use a solvent recovery system and conduct a liquid-liquid material balance according to §63.3961(j), you must meet the operating limits specified in Table 1 to this subpart. These operating limits apply to the emission capture and control systems on the coating operation(s) for which you use this option, and you must establish the operating limits during the performance test according to the requirements in §63.3967. You must meet the operating limits at all times after you establish them.

(c) If you use an add-on control device other than those listed in Table 1 to this subpart, or wish to monitor an alternative parameter and comply with a different operating limit, you must apply to the Administrator for approval of alternative monitoring under §63.8(f).

§ 63.3893(b) What work practice standards must I meet?

(a) ****

(b) If you use the emission rate with add-on controls option, you must develop and implement a work practice plan to minimize organic HAP emissions from the storage, mixing, and conveying of coatings, thinners and/or other additives, and cleaning materials used in, and waste materials generated by the controlled coating operation(s) for which you use this option; or you must meet an alternative standard as provided in paragraph (c) of this section. The plan must specify practices and procedures to ensure that, at a minimum, the elements specified in paragraphs (b)(1) through (5) of this section are implemented.

(1) All organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be stored in closed containers.

(2) Spills of organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be minimized.

(3) Organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be conveyed from one location to another in closed containers or pipes.

(4) Mixing vessels which contain organic-HAP-containing coatings and other materials must be closed except when adding to, removing, or mixing the contents.

(5) Emissions of organic HAP must be minimized during cleaning of storage, mixing, and conveying equipment.

(c) As provided in §63.6(g), we, the U.S. Environmental Protection Agency, may choose to grant you permission to use an alternative to the work practice standards in this section.

§ 63.3900(a)(2), (b) and (c) What are my general requirements for complying with this subpart?

(a) You must be in compliance with the emission limitations in this subpart as specified in paragraphs (a)(1) and (2) of this section.

(1) ****

(2) Any coating operation(s) for which you use the emission rate with add-on controls option, as specified in §63.3891(c), must be in compliance with the emission limitations as specified in paragraphs (a)(2)(i) through (iii) of this section.

(i) The coating operation(s) must be in compliance with the applicable emission limit in §63.3890 at all times except during periods of startup, shutdown, and malfunction.

(ii) The coating operation(s) must be in compliance with the operating limits for emission capture systems and add-on control devices required by §63.3892 at all times except during periods of startup, shutdown, and malfunction, and except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j).

(iii) The coating operation(s) must be in compliance with the work practice standards in §63.3893 at all times.

(b) You must always operate and maintain your affected source, including all air pollution control and monitoring equipment you use for purposes of complying with this subpart, according to the provisions in §63.6(e)(1)(i).

(c) If your affected source uses an emission capture system and add-on control device, you must develop a written startup, shutdown, and malfunction plan according to the provisions in §63.6(e)(3). The plan must address the startup, shutdown, and corrective actions in the event of a malfunction of the emission capture system or the add-on control device. The plan must also address any coating operation equipment that may cause increased emissions or that would affect capture efficiency if the process equipment malfunctions, such as conveyors that move parts among enclosures.

§ 63.3901 What parts of the General Provisions apply to me?

Table 2 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you.

§ 63.3910 What notifications must I submit?

(a) *General.* You must submit the notifications in §§63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) that apply to you by the dates specified in those sections, except as provided in paragraphs (b) and (c) of this section.

(b) *Initial Notification.* You must submit the initial notification required by §63.9(b) for a new or reconstructed affected source no later than 120 days after initial startup or 120 days after January 2, 2004, whichever is later. For an existing affected source, you must submit the initial notification no later than 1 year after January 2, 2004. If you are using compliance with the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (subpart IIII of this part) as provided for under §63.3881(d) to constitute compliance with this subpart for any or all of your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations. If you are complying with another NESHAP that constitutes the predominant activity at your facility under §63.3881(e)(2) to constitute compliance with this subpart for your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations.

(c) *Notification of compliance status.* You must submit the notification of compliance status required by §63.9(h) no later than 30 calendar days following the end of the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source. The notification of compliance status must contain the information specified in paragraphs (c)(1) through (11) of this section and in §63.9(h).

(1) Company name and address.

(2) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(3) Date of the report and beginning and ending dates of the reporting period. The reporting period is the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source.

(4) Identification of the compliance option or options specified in §63.3891 that you used on each coating operation in the affected source during the initial compliance period.

(5) Statement of whether or not the affected source achieved the emission limitations for the initial compliance period.

(6) If you had a deviation, include the information in paragraphs (c)(6)(i) and (ii) of this section.

(i) A description and statement of the cause of the deviation.

(ii) If you failed to meet the applicable emission limit in §63.3890, include all the calculations you used to determine the kg (lb) of organic HAP emitted per liter (gal) coating solids used. You do not need to submit information provided by the materials' suppliers or manufacturers, or test reports.

(7) For each of the data items listed in paragraphs (c)(7)(i) through (iv) of this section that is required by the compliance option(s) you used to demonstrate compliance with the emission limit, include an example of how you determined the value, including calculations and supporting data. Supporting data may include a copy of the information provided by the supplier or manufacturer of the example coating or material, or a summary of the results of testing conducted according to §63.3941(a), (b), or (c). You do not need to submit copies of any test reports.

(i) Mass fraction of organic HAP for one coating, for one thinner and/or other additive, and for one cleaning material.

(ii) Volume fraction of coating solids for one coating.

(iii) Density for one coating, one thinner and/or other additive, and one leaning material, except that if you use the compliant material option, only the example coating density is required.

(iv) The amount of waste materials and the mass of organic HAP contained in the waste materials for which you are claiming an allowance in Equation 1 of §63.3951.

(8) The calculation of kg (lb) of organic HAP emitted per liter (gal) coating solids used for the compliance option(s) you used, as specified in paragraphs (c)(8)(i) through (iii) of this section.

(i) For the compliant material option, provide an example calculation of the organic HAP content for one coating, using Equation 2 of §63.3941.

(ii) For the emission rate without add-on controls option, provide the calculation of the total mass of organic HAP emissions for each month; the calculation of the total volume of coating solids used each month; and the calculation of the 12-month organic HAP emission rate using Equations 1 and 1A through 1C, 2, and 3, respectively, of §63.3951.

(iii) For the emission rate with add-on controls option, provide the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month, using Equations 1 and 1A through 1C of §63.3951; the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; the mass of organic HAP emission reduction each month by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961 and Equations 2, 3, and 3A through 3C of §63.3961 as applicable; the calculation of the total mass of organic HAP emissions each month using Equation 4 of §63.3961; and the calculation of the 12-month organic HAP emission rate using Equation 5 of §63.3961.

(9) For the emission rate with add-on controls option, you must include the information specified in paragraphs (c)(9)(i) through (iv) of this section, except that the requirements in paragraphs (c)(9)(i) through (iii) of this section do not apply to solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j).

(i) For each emission capture system, a summary of the data and copies of the calculations supporting the determination that the emission capture system is a permanent total enclosure (PTE) or a measurement of

the emission capture system efficiency. Include a description of the protocol followed for measuring capture efficiency, summaries of any capture efficiency tests conducted, and any calculations supporting the capture efficiency determination. If you use the data quality objective (DQO) or lower confidence limit (LCL) approach, you must also include the statistical calculations to show you meet the DQO or LCL criteria in appendix A to subpart KK of this part. You do not need to submit complete test reports.

(ii) A summary of the results of each add-on control device performance test. You do not need to submit complete test reports.

(iii) A list of each emission capture system's and add-on control device's operating limits and a summary of the data used to calculate those limits.

(iv) A statement of whether or not you developed and implemented the work practice plan required by §63.3893.

(10) If you are complying with a single emission limit representing the predominant activity under §63.3890(c)(1), include the calculations and supporting information used to demonstrate that this emission limit represents the predominant activity as specified in §63.3890(c)(1).

(11) If you are complying with a facility-specific emission limit under §63.3890(c)(2), include the calculation of the facility-specific emission limit and any supporting information as specified in §63.3890(c)(2).

§ 63.3920 What reports must I submit?

(a) *Semiannual compliance reports.* You must submit semiannual compliance reports for each affected source according to the requirements of paragraphs (a)(1) through (7) of this section. The semiannual compliance reporting requirements may be satisfied by reports required under other parts of the Clean Air Act (CAA), as specified in paragraph (a)(2) of this section.

(1) *Dates.* Unless the Administrator has approved or agreed to a different schedule for submission of reports under §63.10(a), you must prepare and submit each semiannual compliance report according to the dates specified in paragraphs (a)(1)(i) through (iv) of this section. Note that the information reported for each of the months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(i) The first semiannual compliance report must cover the first semiannual reporting period which begins the day after the end of the initial compliance period described in §63.3940, §63.3950, or §63.3960 that applies to your affected source and ends on June 30 or December 31, whichever date is the first date following the end of the initial compliance period.

(ii) Each subsequent semiannual compliance report must cover the subsequent semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(iii) Each semiannual compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(iv) For each affected source that is subject to permitting regulations pursuant to 40 CFR part 70 or 40 CFR part 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), you may submit the first and subsequent compliance reports according to the dates the permitting authority has established instead of according to the date specified in paragraph (a)(1)(iii) of this section.

(2) *Inclusion with title V report.* Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 40 CFR part 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a semiannual compliance report pursuant to this section along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the semiannual compliance report includes all required information concerning deviations from any emission limitation in this subpart, its submission will be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a semiannual compliance report

shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permitting authority.

(3) *General requirements.* The semiannual compliance report must contain the information specified in paragraphs (a)(3)(i) through (vii) of this section, and the information specified in paragraphs (a)(4) through (7) and (c)(1) of this section that is applicable to your affected source.

(i) Company name and address.

(ii) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(iii) Date of report and beginning and ending dates of the reporting period. The reporting period is the 6-month period ending on June 30 or December 31. Note that the information reported for each of the 6 months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(iv) Identification of the compliance option or options specified in §63.3891 that you used on each coating operation during the reporting period. If you switched between compliance options during the reporting period, you must report the beginning and ending dates for each option you used.

(v) If you used the emission rate without add-on controls or the emission rate with add-on controls compliance option (§63.3891(b) or (c)), the calculation results for each rolling 12-month organic HAP emission rate during the 6-month reporting period.

(vi) If you used the predominant activity alternative (§63.3890(c)(1)), include the annual determination of predominant activity if it was not included in the previous semi-annual compliance report.

(vii) If you used the facility-specific emission limit alternative (§63.3890(c)(2)), include the calculation of the facility-specific emission limit for each 12-month compliance period during the 6-month reporting period.

(4) *No deviations.* If there were no deviations from the emission limitations in §§63.3890, 63.3892, and 63.3893 that apply to you, the semiannual compliance report must include a statement that there were no deviations from the emission limitations during the reporting period. If you used the emission rate with add-on controls option and there were no periods during which the continuous parameter monitoring systems (CPMS) were out-of-control as specified in §63.8(c)(7), the semiannual compliance report must include a statement that there were no periods during which the CPMS were out-of-control during the reporting period.

(5) ****

(6) ****

(7) *Deviations: Emission rate with add-on controls option.* If you used the emission rate with add-on controls option and there was a deviation from an emission limitation (including any periods when emissions bypassed the add-on control device and were diverted to the atmosphere), the semiannual compliance report must contain the information in paragraphs (a)(7)(i) through (xiv) of this section. This includes periods of startup, shutdown, and malfunction during which deviations occurred.

(i) The beginning and ending dates of each compliance period during which the 12-month organic HAP emission rate exceeded the applicable emission limit in §63.3890.

(ii) The calculations used to determine the 12-month organic HAP emission rate for each compliance period in which a deviation occurred. You must provide the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1 and 1A through 1C of §63.3951; and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4); the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; the calculation of the mass of organic HAP emission reduction each month by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961, and Equations 2, 3, and 3A through 3C of §63.3961, as applicable; the calculation of the total mass of organic HAP emissions each month using Equation 4 of §63.3961; and the

calculation of the 12-month organic HAP emission rate using Equation 5 of §63.3961. You do not need to submit the background data supporting these calculations (e.g., information provided by materials suppliers or manufacturers, or test reports).

- (iii) The date and time that each malfunction started and stopped.
 - (iv) A brief description of the CPMS.
 - (v) The date of the latest CPMS certification or audit.
 - (vi) The date and time that each CPMS was inoperative, except for zero (low-level) and high-level checks.
 - (vii) The date, time, and duration that each CPMS was out-of-control, including the information in §63.8(c)(8).
 - (viii) The date and time period of each deviation from an operating limit in Table 1 to this subpart; date and time period of any bypass of the add-on control device; and whether each deviation occurred during a period of startup, shutdown, or malfunction or during another period.
 - (ix) A summary of the total duration of each deviation from an operating limit in Table 1 to this subpart and each bypass of the add-on control device during the semiannual reporting period, and the total duration as a percent of the total source operating time during that semiannual reporting period.
 - (x) A breakdown of the total duration of the deviations from the operating limits in Table 1 of this subpart and bypasses of the add-on control device during the semiannual reporting period into those that were due to startup, shutdown, control equipment problems, process problems, other known causes, and other unknown causes.
 - (xi) A summary of the total duration of CPMS downtime during the semiannual reporting period and the total duration of CPMS downtime as a percent of the total source operating time during that semiannual reporting period.
 - (xii) A description of any changes in the CPMS, coating operation, emission capture system, or add-on control device since the last semiannual reporting period.
 - (xiii) For each deviation from the work practice standards, a description of the deviation, the date and time period of the deviation, and the actions you took to correct the deviation.
 - (xiv) A statement of the cause of each deviation.
- (b) *Performance test reports.* If you use the emission rate with add-on controls option, you must submit reports of performance test results for emission capture systems and add-on control devices no later than 60 days after completing the tests as specified in §63.10(d)(2).
- (c) *Startup, shutdown, malfunction reports.* If you used the emission rate with add-on controls option and you had a startup, shutdown, or malfunction during the semiannual reporting period, you must submit the reports specified in paragraphs (c)(1) and (2) of this section.
- (1) If your actions were consistent with your startup, shutdown, and malfunction plan, you must include the information specified in §63.10(d) in the semiannual compliance report required by paragraph (a) of this section.
- (2) If your actions were not consistent with your startup, shutdown, and malfunction plan, you must submit an immediate startup, shutdown, and malfunction report as described in paragraphs (c)(2)(i) and (ii) of this section.
- (i) You must describe the actions taken during the event in a report delivered by facsimile, telephone, or other means to the Administrator within 2 working days after starting actions that are inconsistent with the plan.

(ii) You must submit a letter to the Administrator within 7 working days after the end of the event, unless you have made alternative arrangements with the Administrator as specified in §63.10(d)(5)(ii). The letter must contain the information specified in §63.10(d)(5)(ii).

§ 63.3930 What records must I keep?

You must collect and keep records of the data and information specified in this section. Failure to collect and keep these records is a deviation from the applicable standard.

(a) A copy of each notification and report that you submitted to comply with this subpart, and the documentation supporting each notification and report. If you are using the predominant activity alternative under §63.3890(c), you must keep records of the data and calculations used to determine the predominant activity. If you are using the facility-specific emission limit alternative under §63.3890(c), you must keep records of the data used to calculate the facility-specific emission limit for the initial compliance demonstration. You must also keep records of any data used in each annual predominant activity determination and in the calculation of the facility-specific emission limit for each 12-month compliance period included in the semi-annual compliance reports.

(b) A current copy of information provided by materials suppliers or manufacturers, such as manufacturer's formulation data, or test data used to determine the mass fraction of organic HAP and density for each coating, thinner and/or other additive, and cleaning material, and the volume fraction of coating solids for each coating. If you conducted testing to determine mass fraction of organic HAP, density, or volume fraction of coating solids, you must keep a copy of the complete test report. If you use information provided to you by the manufacturer or supplier of the material that was based on testing, you must keep the summary sheet of results provided to you by the manufacturer or supplier. You are not required to obtain the test report or other supporting documentation from the manufacturer or supplier.

(c) For each compliance period, the records specified in paragraphs (c)(1) through (4) of this section.

(1) A record of the coating operations on which you used each compliance option and the time periods (beginning and ending dates and times) for each option you used.

(2) ****

(3) ****

(4) For the emission rate with add-on controls option, records of the calculations specified in paragraphs (c)(4)(i) through (v) of this section.

(i) The calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1 and 1A through 1C of §63.3951 and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4);

(ii) The calculation of the total volume of coating solids used each month using Equation 2 of §63.3951;

(iii) The calculation of the mass of organic HAP emission reduction by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961 and Equations 2, 3, and 3A through 3C of §63.3961, as applicable;

(iv) The calculation of each month's organic HAP emission rate using Equation 4 of §63.3961; and

(v) The calculation of each 12-month organic HAP emission rate using Equation 5 of §63.3961.

(d) A record of the name and volume of each coating, thinner and/or other additive, and cleaning material used during each compliance period. If you are using the compliant material option for all coatings at the source, you may maintain purchase records for each material used rather than a record of the volume used.

(e) A record of the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each compliance period unless the material is tracked by weight.

(f) A record of the volume fraction of coating solids for each coating used during each compliance period.

(g) If you use either the emission rate without add-on controls or the emission rate with add-on controls compliance option, the density for each coating, thinner and/or other additive, and cleaning material used during each compliance period.

(h) If you use an allowance in Equation 1 of §63.3951 for organic HAP contained in waste materials sent to or designated for shipment to a treatment, storage, and disposal facility (TSDF) according to §63.3951(e)(4), you must keep records of the information specified in paragraphs (h)(1) through (3) of this section.

(1) The name and address of each TSDF to which you sent waste materials for which you use an allowance in Equation 1 of §63.3951; a statement of which subparts under 40 CFR parts 262, 264, 265, and 266 apply to the facility; and the date of each shipment.

(2) Identification of the coating operations producing waste materials included in each shipment and the month or months in which you used the allowance for these materials in Equation 1 of §63.3951.

(3) The methodology used in accordance with §63.3951(e)(4) to determine the total amount of waste materials sent to or the amount collected, stored, and designated for transport to a TSDF each month; and the methodology to determine the mass of organic HAP contained in these waste materials. This must include the sources for all data used in the determination, methods used to generate the data, frequency of testing or monitoring, and supporting calculations and documentation, including the waste manifest for each shipment.

(i) [Reserved]

(j) You must keep records of the date, time, and duration of each deviation.

(k) If you use the emission rate with add-on controls option, you must keep the records specified in paragraphs (k)(1) through (8) of this section.

(1) For each deviation, a record of whether the deviation occurred during a period of startup, shutdown, or malfunction.

(2) The records in §63.6(e)(3)(iii) through (v) related to startup, shutdown, and malfunction.

(3) The records required to show continuous compliance with each operating limit specified in Table 1 to this subpart that applies to you.

(4) ****

(5) ****

(6) The records specified in paragraphs (k)(6)(i) and (ii) of this section for each add-on control device organic HAP destruction or removal efficiency determination as specified in §63.3966.

(i) Records of each add-on control device performance test conducted according to §§63.3964 and 63.3966.

(ii) Records of the coating operation conditions during the add-on control device performance test showing that the performance test was conducted under representative operating conditions.

(7) Records of the data and calculations you used to establish the emission capture and add-on control device operating limits as specified in §63.3967 and to document compliance with the operating limits as specified in Table 1 to this subpart.

(8) A record of the work practice plan required by §63.3893 and documentation that you are implementing the plan on a continuous basis.

§ 63.3931 In what form and for how long must I keep my records?

(a) Your records must be in a form suitable and readily available for expeditious review, according to §63.10(b)(1). Where appropriate, the records may be maintained as electronic spreadsheets or as a database.

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record on-site for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record according to §63.10(b)(1). You may keep the records off-site for the remaining 3 years.

Compliance Requirements for the Emission Rate With Add-On Control Options

§ 63.3960 By what date must I conduct performance tests and other initial compliance demonstrations?

(a) New and reconstructed *affected sources*. For a new or reconstructed affected source, you must meet the requirements of paragraphs (a)(1) through (4) of this section.

(1) All emission capture systems, add-on control devices, and CPMS must be installed and operating no later than the applicable compliance date specified in §63.3883. Except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), you must conduct a performance test of each capture system and add-on control device according to §§63.3964, 63.3965, and 63.3966 and establish the operating limits required by §63.3892 no later than 180 days after the applicable compliance date specified in §63.3883. For a solvent recovery system for which you conduct liquid-liquid material balances according to §63.3961(j), you must initiate the first material balance no later than the applicable compliance date specified in §63.3883. For magnet wire coating operations you may, with approval, conduct a performance test of one representative magnet wire coating machine for each group of identical or very similar magnet wire coating machines.

(2) You must develop and begin implementing the work practice plan required by §63.3893 no later than the compliance date specified in §63.3883.

(3) You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3961. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coatings solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the results of emission capture system and add-on control device performance tests conducted according to §§63.3964, 63.3965, and 63.3966; results of liquid-liquid material balances conducted according to §63.3961(j); calculations according to §63.3961 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.3890; the operating limits established during the performance tests and the results of the continuous parameter monitoring required by §63.3968; and documentation of whether you developed and implemented the work practice plan required by §63.3893.

(4) You do not need to comply with the operating limits for the emission capture system and add-on control device required by §63.3892 until after you have completed the performance tests specified in paragraph (a)(1) of this section. Instead, you must maintain a log detailing the operation and maintenance of the emission capture system, add-on control device, and continuous parameter monitors during the period between the compliance date and the performance test. You must begin complying with the operating limits for your affected source on the date you complete the performance tests specified in paragraph (a)(1) of this section. For magnet wire coating operations, you must begin complying with the operating limits for all identical or very similar magnet wire coating machines on the date you complete the performance test of a representative magnet wire coating machine. The requirements in this paragraph (a)(4) do not apply to solvent recovery systems for which you conduct liquid-liquid material balances according to the requirements in §63.3961(j).

(b) *Existing affected sources.* For an existing affected source, you must meet the requirements of paragraphs (b)(1) through (3) of this section.

(1) All emission capture systems, add-on control devices, and CPMS must be installed and operating no later than the applicable compliance date specified in §63.3883. Except for magnet wire coating operations and solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), you must conduct a performance test of each capture system and add-on control device according to the procedures in §§63.3964, 63.3965, and 63.3966 and establish the operating limits required by §63.3892 no later than the compliance date specified in §63.3883. For magnet wire coating operations, you may, with approval, conduct a performance test of a single magnet wire coating machine that represents identical or very similar magnet wire coating machines. For a solvent recovery system for which you conduct liquid-liquid material balances according to §63.3961(j), you must initiate the first material balance no later than the compliance date specified in §63.3883.

(2) You must develop and begin implementing the work practice plan required by §63.3893 no later than the compliance date specified in §63.3883.

(3) You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3961. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coatings solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the results of emission capture system and add-on control device performance tests conducted according to §§63.3964, 63.3965, and 63.3966; results of liquid-liquid material balances conducted according to §63.3961(j); calculations according to §63.3961 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.3890; the operating limits established during the performance tests and the results of the continuous parameter monitoring required by §63.3968; and documentation of whether you developed and implemented the work practice plan required by §63.3893.

(c) You are not required to conduct an initial performance test to determine capture efficiency or destruction efficiency of a capture system or control device if you receive approval to use the results of a performance test that has been previously conducted on that capture system or control device. Any such previous tests must meet the conditions described in paragraphs (c)(1) through (3) of this section.

(1) The previous test must have been conducted using the methods and conditions specified in this subpart.

(2) Either no process or equipment changes have been made since the previous test was performed or the owner or operator must be able to demonstrate that the results of the performance test, reliably demonstrate compliance despite process or equipment changes.

(3) Either the required operating parameters were established in the previous test or sufficient data were collected in the previous test to establish the required operating parameters.

§ 63.3961 How do I demonstrate initial compliance?

(a) You may use the emission rate with add-on controls option for any coating operation, for any group of coating operations in the affected source, or for all of the coating operations in the affected source. You may include both controlled and uncontrolled coating operations in a group for which you use this option. You must use either the compliant material option or the emission rate without add-on controls option for any coating operation in the affected source for which you do not use the emission rate with add-on controls option. To demonstrate initial compliance, the coating operation(s) for which you use the emission rate with add-on controls option must meet the applicable emission limitations in §§63.3890, 63.3892, and 63.3893. You must conduct a separate initial compliance demonstration for each general use, magnet wire, rubber-to-metal, and extreme performance fluoropolymer coating operation, unless you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c). If you are demonstrating compliance with a predominant activity or facility-specific emission

limit as provided in §63.4490(c), you must demonstrate that all coating operations included in the predominant activity determination or calculation of the facility-specific emission limit comply with that limit. You must meet all the requirements of this section. When calculating the organic HAP emission rate according to this section, do not include any coatings, thinners and/or other additives, or cleaning materials used on coating operations for which you use the compliant material option or the emission rate without add-on controls option. You do not need to redetermine the mass of organic HAP in coatings, thinners and/or other additives, or cleaning materials that have been reclaimed onsite (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coatings operation(s) for which you use the emission rate with add-on controls option. If you use coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site, the amount of each used in a month may be reduced by the amount of each that is reclaimed. That is, the amount used may be calculated as the amount consumed to account for materials that are reclaimed.

(b) *Compliance with operating limits.* Except as provided in §63.3960(a)(4), and except for solvent recovery systems for which you conduct liquid-liquid material balances according to the requirements of paragraph (j) of this section, you must establish and demonstrate continuous compliance during the initial compliance period with the operating limits required by §63.3892, using the procedures specified in §§63.3967 and 63.3968.

(c) *Compliance with work practice requirements.* You must develop, implement, and document your implementation of the work practice plan required by §63.3893 during the initial compliance period, as specified in §63.3930.

(d) *Compliance with emission limits.* You must follow the procedures in paragraphs (e) through (n) of this section to demonstrate compliance with the applicable emission limit in §63.3890 for each affected source in each subcategory.

(e) *Determine the mass fraction of organic HAP, density, volume used, and volume fraction of coating solids.* Follow the procedures specified in §63.3951(a) through (d) to determine the mass fraction of organic HAP, density, and volume of each coating, thinner and/or other additive, and cleaning material used during each month; and the volume fraction of coating solids for each coating used during each month.

(f) *Calculate the total mass of organic HAP emissions before add-on controls.* Using Equation 1 of §63.3951, calculate the total mass of organic HAP emissions before add-on controls from all coatings, thinners and/or other additives, and cleaning materials used during each month in the coating operation or group of coating operations for which you use the emission rate with add-on controls option.

(g) *Calculate the organic HAP emission reduction for each controlled coating operation.* Determine the mass of organic HAP emissions reduced for each controlled coating operation during each month. The emission reduction determination quantifies the total organic HAP emissions that pass through the emission capture system and are destroyed or removed by the add-on control device. Use the procedures in paragraph (h) of this section to calculate the mass of organic HAP emission reduction for each controlled coating operation using an emission capture system and add-on control device other than a solvent recovery system for which you conduct liquid-liquid material balances. For each controlled coating operation using a solvent recovery system for which you conduct a liquid-liquid material balance, use the procedures in paragraph (j) of this section to calculate the organic HAP emission reduction.

(h) *Calculate the organic HAP emission reduction for each controlled coating operation not using liquid-liquid material balance.* Use Equation 1 of this section to calculate the organic HAP emission reduction for each controlled coating operation using an emission capture system and add-on control device other than a solvent recovery system for which you conduct liquid-liquid material balances. The calculation applies the emission capture system efficiency and add-on control device efficiency to the mass of organic HAP contained in the coatings, thinners and/or other additives, and cleaning materials that are used in the coating operation served by the emission capture system and add-on control device during each month. You must assume zero efficiency for the emission capture system and add-on control device for any period of time a deviation specified in §63.3963(c) or (d) occurs in the controlled coating operation, including a deviation during a period of startup, shutdown, or malfunction, unless you have other data indicating the actual efficiency of the emission capture system and add-on control device and the use of

these data is approved by the Administrator. Equation 1 of this section treats the materials used during such a deviation as if they were used on an uncontrolled coating operation for the time period of the deviation.

$$H_C = (A_C + B_C + C_C - R_W - H_{UNC}) \left(\frac{CE}{100} \times \frac{DRE}{100} \right) \quad (Eq. 1)$$

Where:

H_C = Mass of organic HAP emission reduction for the controlled coating operation during the month, kg.

A_C = Total mass of organic HAP in the coatings used in the controlled coating operation during the month, kg, as calculated in Equation 1A of this section.

B_C = Total mass of organic HAP in the thinners and/or other additives used in the controlled coating operation during the month, kg, as calculated in Equation 1B of this section.

C_C = Total mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg, as calculated in Equation 1C of this section.

R_W = Total mass of organic HAP in waste materials sent or designated for shipment to a hazardous waste TSDF for treatment or disposal during the compliance period, kg, determined according to §63.3951(e)(4). (You may assign a value of zero to R_W if you do not wish to use this allowance.)

H_{UNC} = Total mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used during all deviations specified in §63.3963(c) and (d) that occurred during the month in the controlled coating operation, kg, as calculated in Equation 1D of this section.

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent. Use the test methods and procedures specified in §§63.3964 and 63.3965 to measure and record capture efficiency.

DRE = Organic HAP destruction or removal efficiency of the add-on control device, percent. Use the test methods and procedures in §§63.3964 and 63.3966 to measure and record the organic HAP destruction or removal efficiency.

(1) Calculate the mass of organic HAP in the coatings used in the controlled coating operation, kg (lb), using Equation 1A of this section:

$$A_C = \sum_{i=1}^m (Vol_{c,i}) (D_{c,i}) (W_{c,i}) \quad (Eq. 1A)$$

Where:

A_C = Total mass of organic HAP in the coatings used in the controlled coating operation during the month, kg.

$Vol_{c,i}$ = Total volume of coating, i, used during the month, liters.

$D_{c,i}$ = Density of coating, i, kg per liter.

$W_{c,i}$ = Mass fraction of organic HAP in coating, i, kg per kg. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

m = Number of different coatings used.

(2) Calculate the mass of organic HAP in the thinners and/or other additives used in the controlled coating operation, kg (lb), using Equation 1B of this section:

$$B_C = \sum_{j=1}^n (Vol_{t,j})(D_{t,j})(W_{t,j}) \quad (Eq. 1B)$$

Where:

B_C = Total mass of organic HAP in the thinners and/or other additives used in the controlled coating operation during the month, kg.

$Vol_{t,j}$ = Total volume of thinner and/or other additive, j, used during the month, liters.

$D_{t,j}$ = Density of thinner and/or other additive, j, kg per liter.

$W_{t,j}$ = Mass fraction of organic HAP in thinner and/or other additive, j, kg per kg. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

n = Number of different thinners and/or other additives used.

(3) Calculate the mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg (lb), using Equation 1C of this section:

$$C_C = \sum_{k=1}^p (Vol_{s,k})(D_{s,k})(W_{s,k}) \quad (Eq. 1C)$$

Where:

C_C = Total mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg.

$Vol_{s,k}$ = Total volume of cleaning material, k, used during the month, liters.

$D_{s,k}$ = Density of cleaning material, k, kg per liter.

$W_{s,k}$ = Mass fraction of organic HAP in cleaning material, k, kg per kg.

p = Number of different cleaning materials used.

(4) Calculate the mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used in the controlled coating operation during deviations specified in §63.3963(c) and (d), using Equation 1D of this section:

$$H_{UNC} = \sum_{k=1}^q (Vol_k)(D_k)(W_k) \quad (Eq. 1D)$$

Where:

H_{UNC} = Total mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used during all deviations specified in §63.3963(c) and (d) that occurred during the month in the controlled coating operation, kg.

Vol_h = Total volume of coating, thinner and/or other additive, or cleaning material, h, used in the controlled coating operation during deviations, liters.

D_h = Density of coating, thinner and/or other additives, or cleaning material, h, kg per liter.

W_h = Mass fraction of organic HAP in coating, thinner and/or other additives, or cleaning material, h, kg organic HAP per kg coating. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

q = Number of different coatings, thinners and/or other additives, and cleaning materials used.

(i) [Reserved]

(j) ****

§ 63.3963 How do I demonstrate continuous compliance with the emission limitations?

(a) To demonstrate continuous compliance with the applicable emission limit in §63.3890, the organic HAP emission rate for each compliance period, determined according to the procedures in §63.3961, must be equal to or less than the applicable emission limit in §63.3890. A compliance period consists of 12 months. Each month after the end of the initial compliance period described in §63.3960 is the end of a compliance period consisting of that month and the preceding 11 months. You must perform the calculations in §63.3961 on a monthly basis using data from the previous 12 months of operation. If you are complying with a facility-specific emission limit under §63.3890(c), you must also perform the calculation using Equation 1 in §63.3890(c)(2) on a monthly basis using the data from the previous 12 months of operation.

(b) If the organic HAP emission rate for any 12-month compliance period exceeded the applicable emission limit in §63.3890, this is a deviation from the emission limitation for that compliance period that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(c) You must demonstrate continuous compliance with each operating limit required by §63.3892 that applies to you, as specified in Table 1 to this subpart, when the coating line is in operation.

(1) If an operating parameter is out of the allowed range specified in Table 1 to this subpart, this is a deviation from the operating limit that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(2) If an operating parameter deviates from the operating limit specified in Table 1 to this subpart, then you must assume that the emission capture system and add-on control device were achieving zero efficiency during the time period of the deviation, unless you have other data indicating the actual efficiency of the emission capture system and add-on control device and the use of these data is approved by the Administrator.

(d) You must meet the requirements for bypass lines in §63.3968(b) for controlled coating operations for which you do not conduct liquid-liquid material balances. If any bypass line is opened and emissions are diverted to the atmosphere when the coating operation is running, this is a deviation that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7). For the purposes of completing the compliance calculations specified in §§63.3961(h), you must treat the materials used during a deviation on a controlled coating operation as if they were used on an uncontrolled coating operation for the time period of the deviation as indicated in Equation 1 of §63.3961.

(e) You must demonstrate continuous compliance with the work practice standards in §63.3893. If you did not develop a work practice plan, or you did not implement the plan, or you did not keep the records required by §63.3930(k)(8), this is a deviation from the work practice standards that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(f) As part of each semiannual compliance report required in §63.3920, you must identify the coating operation(s) for which you used the emission rate with add-on controls option. If there were no deviations from the emission limitations, submit a statement that you were in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable emission limit in §63.3890, and you achieved the operating limits required by §63.3892 and the work practice standards required by §63.3893 during each compliance period.

(g) [Reserved]

(h) [Reserved]

(i) [Reserved]

(j) You must maintain records as specified in §§63.3930 and 63.3931.

(k) *Calculate the total volume of coating solids used.* Determine the total volume of coating solids used, liters, which is the combined volume of coating solids for all the coatings used during each month in the coating operation or group of coating operations for which you use the emission rate with add-on controls option, using Equation 2 of §63.3951.

(l) Calculate the mass of organic HAP emissions for each month. Determine the mass of organic HAP emissions, kg, during each month, using Equation 4 of this section:

$$H_{HAP} = H_e - \sum_{i=1}^q (H_{c,i}) - \sum_{j=1}^r (H_{CSR,j}) \quad (Eq. 4)$$

where:

H_{HAP} = Total mass of organic HAP emissions for the month, kg.

H_e = Total mass of organic HAP emissions before add-on controls from all the coatings, thinners and/or other additives, and cleaning materials used during the month, kg, determined according to paragraph (f) of this section.

$H_{c,i}$ = Total mass of organic HAP emission reduction for controlled coating operation, i, not using a liquid-liquid material balance, during the month, kg, from Equation 1 of this section.

$H_{CSR,j}$ = Total mass of organic HAP emission reduction for coating operation, j, controlled by a solvent recovery system using a liquid-liquid material balance, during the month, kg, from Equation 3 of this section.

q = Number of controlled coating operations not controlled by a solvent recovery system using a liquid-liquid material balance.

r = Number of coating operations controlled by a solvent recovery system using a liquid-liquid material balance.

(m) Calculate the organic HAP emission rate for the compliance period. Determine the organic HAP emission rate for the compliance period, kg (lb) of organic HAP emitted per liter (gal) coating solids used, using Equation 5 of this section:

$$H_{annual} = \frac{\sum_{y=1}^n H_{HAP,y}}{\sum_{y=1}^n V_{st,y}} \quad (Eq. 5)$$

Where:

H_{annual} = Organic HAP emission rate for the compliance period, kg organic HAP emitted per liter coating solids used.

$H_{HAP,y}$ = Organic HAP emissions for month, y, kg, determined according to Equation 4 of this section.

$V_{st,y}$ = Total volume of coating solids used during month, y, liters, from Equation 2 of §63.3951.

y = Identifier for months.

n = Number of full or partial months in the compliance period (for the initial compliance period, n equals 12 if the compliance date falls on the first day of a month; otherwise n equals 13; for all following compliance periods, n equals 12).

(n) *Compliance demonstration.* The organic HAP emission rate for the initial compliance period, calculated using Equation 5 of this section, must be less than or equal to the applicable emission limit for each subcategory in §63.3890 or the predominant activity or facility-specific emission limit allowed in §63.3890(c). You must keep all records as required by §§63.3930 and 63.3931. As part of the notification of compliance status required by §63.3910, you must identify the coating operation(s) for which you used the emission rate with add-on controls option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because the organic HAP emission rate was less than or equal to the applicable emission limit in §63.3890, and you achieved the operating limits required by §63.3892 and the work practice standards required by §63.3893.

§ 63.3964 What are the general requirements for performance tests?

(a) You must conduct each performance test required by §63.3960 according to the requirements in §63.7(e)(1) and under the conditions in this section, unless you obtain a waiver of the performance test according to the provisions in §63.7(h).

(1) *Representative coating operation operating conditions.* You must conduct the performance test under representative operating conditions for the coating operation. Operations during periods of startup, shutdown, or malfunction and during periods of nonoperation do not constitute representative conditions. You must record the process information that is necessary to document operating conditions during the test and explain why the conditions represent normal operation.

(2) *Representative emission capture system and add-on control device operating conditions.* You must conduct the performance test when the emission capture system and add-on control device are operating at a representative flow rate, and the add-on control device is operating at a representative inlet concentration. You must record information that is necessary to document emission capture system and add-on control device operating conditions during the test and explain why the conditions represent normal operation.

(b) You must conduct each performance test of an emission capture system according to the requirements in §63.3965. You must conduct each performance test of an add-on control device according to the requirements in §63.3966.

§ 63.3965 How do I determine the emission capture system efficiency?

You must use the procedures and test methods in this section to determine capture efficiency as part of the performance test required by §63.3960.

(a) *Assuming 100 percent capture efficiency.* You may assume the capture system efficiency is 100 percent if both of the conditions in paragraphs (a)(1) and (2) of this section are met:

(1) The capture system meets the criteria in Method 204 of appendix M to 40 CFR part 51 for a PTE and directs all the exhaust gases from the enclosure to an add-on control device.

(2) All coatings, thinners and/or other additives, and cleaning materials used in the coating operation are applied within the capture system; coating solvent flash-off, curing, and drying occurs within the capture system; and the removal or evaporation of cleaning materials from the surfaces they are applied to occurs within the capture system. For example, this criterion is not met if parts enter the open shop environment when being moved between a spray booth and a curing oven.

(b) *Measuring capture efficiency.* If the capture system does not meet both of the criteria in paragraphs (a)(1) and (2) of this section, then you must use one of the three protocols described in paragraphs (c), (d), and (e) of this section to measure capture efficiency. The capture efficiency measurements use TVH capture efficiency as a surrogate for organic HAP capture efficiency. For the protocols in paragraphs (c) and (d) of this section, the capture efficiency measurement must consist of three test runs. Each test run must be at least 3 hours duration or the length of a production run, whichever is longer, up to 8 hours. For the purposes of this test, a production run means the time required for a single part to go from the beginning to the end of the production, which includes surface preparation activities and drying and curing time.

(c) *Liquid-to-uncaptured-gas protocol using a temporary total enclosure or building enclosure.* The liquid-to-uncaptured-gas protocol compares the mass of liquid TVH in materials used in the coating operation to the mass of TVH emissions not captured by the emission capture system. Use a temporary total enclosure or a building enclosure and the procedures in paragraphs (c)(1) through (6) of this section to measure emission capture system efficiency using the liquid-to-uncaptured-gas protocol.

(1) Either use a building enclosure or construct an enclosure around the coating operation where coatings, thinners and/or other additives, and cleaning materials are applied, and all areas where emissions from these applied coatings and materials subsequently occur, such as flash-off, curing, and drying areas. The areas of the coating operation where capture devices collect emissions for routing to an add-on control device, such as the entrance and exit areas of an oven or spray booth, must also be inside the enclosure.

The enclosure must meet the applicable definition of a temporary total enclosure or building enclosure in Method 204 of appendix M to 40 CFR part 51.

(2) Use Method 204A or 204F of appendix M to 40 CFR part 51 to determine the mass fraction of TVH liquid input from each coating, thinner and/or other additive, and cleaning material used in the coating operation during each capture efficiency test run. To make the determination, substitute TVH for each occurrence of the term VOC in the methods.

(3) Use Equation 1 of this section to calculate the total mass of TVH liquid input from all the coatings, thinners and/or other additives, and cleaning materials used in the coating operation during each capture efficiency test run:

$$TVH_{used} = \sum_{i=1}^n (TVH_i)(Vol_i)(D_i) \quad (Eq. 1)$$

Where:

TVH_{used} = Mass of liquid TVH in materials used in the coating operation during the capture efficiency test run, kg.

TVH_i = Mass fraction of TVH in coating, thinner and/or other additive, or cleaning material, i, that is used in the coating operation during the capture efficiency test run, kg TVH per kg material.

Vol_i = Total volume of coating, thinner and/or other additive, or cleaning material, i, used in the coating operation during the capture efficiency test run, liters.

D_i = Density of coating, thinner and/or other additive, or cleaning material, i, kg material per liter material.

n = Number of different coatings, thinners and/or other additives, and cleaning materials used in the coating operation during the capture efficiency test run.

(4) Use Method 204D or 204E of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions that are not captured by the emission capture system. They are measured as they exit the temporary total enclosure or building enclosure during each capture efficiency test run. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) Use Method 204D of appendix M to 40 CFR part 51 if the enclosure is a temporary total enclosure.

(ii) Use Method 204E of appendix M to 40 CFR 51 if the enclosure is a building enclosure. During the capture efficiency measurement, all organic compound emitting operations inside the building enclosure, other than the coating operation for which capture efficiency is being determined, must be shut down, but all fans and blowers must be operating normally.

(5) For each capture efficiency test run, determine the percent capture efficiency of the emission capture system using Equation 2 of this section:

$$CE = \frac{(TVH_{used} - TVH_{uncaptured})}{TVH_{used}} \times 100 \quad (Eq. 2)$$

Where:

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent.

TVH_{used} = Total mass of TVH liquid input used in the coating operation during the capture efficiency test run, kg.

$TVH_{uncaptured}$ = Total mass of TVH that is not captured by the emission capture system and that exits from the temporary total enclosure or building enclosure during the capture efficiency test run, kg.

(6) Determine the capture efficiency of the emission capture system as the average of the capture efficiencies measured in the three test runs.

(d) *Gas-to-gas protocol using a temporary total enclosure or a building enclosure.* The gas-to-gas protocol compares the mass of TVH emissions captured by the emission capture system to the mass of TVH emissions not captured. Use a temporary total enclosure or a building enclosure and the procedures in paragraphs (d)(1) through (5) of this section to measure emission capture system efficiency using the gas-to-gas protocol.

(1) Either use a building enclosure or construct an enclosure around the coating operation where coatings, thinners and/or other additives, and cleaning materials are applied, and all areas where emissions from these applied coatings and materials subsequently occur, such as flash-off, curing, and drying areas. The areas of the coating operation where capture devices collect emissions generated by the coating operation for routing to an add-on control device, such as the entrance and exit areas of an oven or a spray booth, must also be inside the enclosure. The enclosure must meet the applicable definition of a temporary total enclosure or building enclosure in Method 204 of appendix M to 40 CFR part 51.

(2) Use Method 204B or 204C of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions captured by the emission capture system during each capture efficiency test run as measured at the inlet to the add-on control device. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) The sampling points for the Method 204B or 204C measurement must be upstream from the add-on control device and must represent total emissions routed from the capture system and entering the add-on control device.

(ii) If multiple emission streams from the capture system enter the add-on control device without a single common duct, then the emissions entering the add-on control device must be simultaneously measured in each duct and the total emissions entering the add-on control device must be determined.

(3) Use Method 204D or 204E of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions that are not captured by the emission capture system; they are measured as they exit the temporary total enclosure or building enclosure during each capture efficiency test run. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) Use Method 204D of appendix M to 40 CFR part 51 if the enclosure is a temporary total enclosure.

(ii) Use Method 204E of appendix M to 40 CFR part 51 if the enclosure is a building enclosure. During the capture efficiency measurement, all organic compound emitting operations inside the building enclosure, other than the coating operation for which capture efficiency is being determined, must be shut down, but all fans and blowers must be operating normally.

(4) For each capture efficiency test run, determine the percent capture efficiency of the emission capture system using Equation 3 of this section:

$$CE = \frac{TVH_{\text{captured}}}{(TVH_{\text{captured}} + TVH_{\text{uncaptured}})} \times 100 \quad (\text{Eq. 3})$$

Where:

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent.

TVH_{captured} = Total mass of TVH captured by the emission capture system as measured at the inlet to the add-on control device during the emission capture efficiency test run, kg.

$TVH_{\text{uncaptured}}$ = Total mass of TVH that is not captured by the emission capture system and that exits from the temporary total enclosure or building enclosure during the capture efficiency test run, kg.

(5) Determine the capture efficiency of the emission capture system as the average of the capture efficiencies measured in the three test runs.

(e) *Alternative capture efficiency protocol.* As an alternative to the procedures specified in paragraphs (c) and (d) of this section and subject to the approval of the Administrator, you may determine capture

efficiency using any other capture efficiency protocol and test methods that satisfy the criteria of either the DQO or LCL approach as described in appendix A to subpart KK of this part.

§ 63.3966 How do I determine the add-on control device emission destruction or removal efficiency?

You must use the procedures and test methods in this section to determine the add-on control device emission destruction or removal efficiency as part of the performance test required by §63.3960. You must conduct three test runs as specified in §63.7(e)(3) and each test run must last at least 1 hour. If the source is a magnet wire coating machine, you may use the procedures in section 3.0 of appendix A to this subpart as an alternative.

(a) For all types of add-on control devices, use the test methods specified in paragraphs (a)(1) through (5) of this section.

(1) Use Method 1 or 1A of appendix A to 40 CFR part 60, as appropriate, to select sampling sites and velocity traverse points.

(2) Use Method 2, 2A, 2C, 2D, 2F, or 2G of appendix A to 40 CFR part 60, as appropriate, to measure gas volumetric flow rate.

(3) Use Method 3, 3A, or 3B of appendix A to 40 CFR part 60, as appropriate, for gas analysis to determine dry molecular weight.

(4) Use Method 4 of appendix A to 40 CFR part 60, to determine stack gas moisture.

(5) Methods for determining gas volumetric flow rate, dry molecular weight, and stack gas moisture must be performed, as applicable, during each test run.

(b) Measure total gaseous organic mass emissions as carbon at the inlet and outlet of the add-on control device simultaneously, using either Method 25 or 25A of appendix A to 40 CFR part 60.

(1) Use Method 25 if the add-on control device is an oxidizer and you expect the total gaseous organic concentration as carbon to be more than 50 parts per million (ppm) at the control device outlet.

(2) Use Method 25A if the add-on control device is an oxidizer and you expect the total gaseous organic concentration as carbon to be 50 ppm or less at the control device outlet.

(3) Use Method 25A if the add-on control device is not an oxidizer.

(c) If two or more add-on control devices are used for the same emission stream, then you must measure emissions at the outlet to the atmosphere of each device. For example, if one add-on control device is a concentrator with an outlet to the atmosphere for the high-volume dilute stream that has been treated by the concentrator, and a second add-on control device is an oxidizer with an outlet to the atmosphere for the low-volume concentrated stream that is treated with the oxidizer, you must measure emissions at the outlet of the oxidizer and the high volume dilute stream outlet of the concentrator.

(d) For each test run, determine the total gaseous organic emissions mass flow rates for the inlet and the outlet of the add-on control device, using Equation 1 of this section. If there is more than one inlet or outlet to the add-on control device, you must calculate the total gaseous organic mass flow rate using Equation 1 of this section for each inlet and each outlet and then total all of the inlet emissions and total all of the outlet emissions:

$$M_f = Q_{sd} C_c (12) (0.0416) (10^{-6}) \quad (Eq. 1)$$

Where:

M_f = Total gaseous organic emissions mass flow rate, kg per hour (h).

C_c = Concentration of organic compounds as carbon in the vent gas, as determined by Method 25 or Method 25A, parts per million by volume (ppmv), dry basis.

Q_{sd} = Volumetric flow rate of gases entering or exiting the add-on control device, as determined by Method 2, 2A, 2C, 2D, 2F, or 2G, dry standard cubic meters/hour (dscmh).

0.0416 = Conversion factor for molar volume, kg-moles per cubic meter (mol/m^3) (@ 293 Kelvin (K) and 760 millimeters of mercury (mmHg).

(e) For each test run, determine the add-on control device organic emissions destruction or removal efficiency, using Equation 2 of this section:

$$DRE = \frac{M_{fi} - M_{fo}}{M_{fi}} \times 100 \quad (\text{Eq. 2})$$

Where:

DRE = Organic emissions destruction or removal efficiency of the add-on control device, percent.

M_{fi} = Total gaseous organic emissions mass flow rate at the inlet(s) to the add-on control device, using Equation 1 of this section, kg/h.

M_{fo} = Total gaseous organic emissions mass flow rate at the outlet(s) of the add-on control device, using Equation 1 of this section, kg/h.

(f) Determine the emission destruction or removal efficiency of the add-on control device as the average of the efficiencies determined in the three test runs and calculated in Equation 2 of this section.

§ 63.3967 How do I establish the emission capture system and add-on control device operating limits during the performance test?

During the performance test required by §63.3960 and described in §§63.3964, 63.3965, and 63.3966, you must establish the operating limits required by §63.3892 according to this section, unless you have received approval for alternative monitoring and operating limits under §63.8(f) as specified in §63.3892.

(a) *Thermal oxidizers.* If your add-on control device is a thermal oxidizer, establish the operating limits according to paragraphs (a)(1) and (2) of this section.

(1) During the performance test, you must monitor and record the combustion temperature at least once every 15 minutes during each of the three test runs. You must monitor the temperature in the firebox of the thermal oxidizer or immediately downstream of the firebox before any substantial heat exchange occurs.

(2) Use the data collected during the performance test to calculate and record the average combustion temperature maintained during the performance test. This average combustion temperature is the minimum operating limit for your thermal oxidizer.

(b) *Catalytic oxidizers.* If your add-on control device is a catalytic oxidizer, establish the operating limits according to either paragraphs (b)(1) and (2) or paragraphs (b)(3) and (4) of this section. If the source is a magnet wire coating machine, you may use the procedures in section 3.0 of appendix A to this subpart as an alternative.

(1) During the performance test, you must monitor and record the temperature just before the catalyst bed and the temperature difference across the catalyst bed at least once every 15 minutes during each of the three test runs.

(2) Use the data collected during the performance test to calculate and record the average temperature just before the catalyst bed and the average temperature difference across the catalyst bed maintained during the performance test. These are the minimum operating limits for your catalytic oxidizer.

(3) You must monitor the temperature at the inlet to the catalyst bed and implement a site-specific inspection and maintenance plan for your catalytic oxidizer as specified in paragraph (b)(4) of this section. During the performance test, you must monitor and record the temperature just before the catalyst bed at least once every 15 minutes during each of the three test runs. Use the data collected during the

performance test to calculate and record the average temperature just before the catalyst bed during the performance test. This is the minimum operating limit for your catalytic oxidizer.

(4) You must develop and implement an inspection and maintenance plan for your catalytic oxidizer(s) for which you elect to monitor according to paragraph (b)(3) of this section. The plan must address, at a minimum, the elements specified in paragraphs (b)(4)(i) through (iii) of this section.

(i) Annual sampling and analysis of the catalyst activity (*i.e.*, conversion efficiency) following the manufacturer's or catalyst supplier's recommended procedures. If problems are found during the catalyst activity test, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations.

(ii) Monthly external inspection of the catalytic oxidizer system, including the burner assembly and fuel supply lines for problems and, as necessary, adjust the equipment to assure proper air-to-fuel mixtures.

(iii) Annual internal inspection of the catalyst bed to check for channeling, abrasion, and settling. If problems are found during the annual internal inspection of the catalyst, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations. If the catalyst bed is replaced and is not of like or better kind and quality as the old catalyst then you must conduct a new performance test to determine destruction efficiency according to §63.3966. If a catalyst bed is replaced and the replacement catalyst is of like or better kind and quality as the old catalyst, then a new performance test to determine destruction efficiency is not required and you may continue to use the previously established operating limits for that catalytic oxidizer.

(f) *Emission capture systems.* For each capture device that is not part of a PTE that meets the criteria of §63.3965(a), establish an operating limit for either the gas volumetric flow rate or duct static pressure, as specified in paragraphs (f)(1) and (2) of this section. The operating limit for a PTE is specified in Table 1 to this subpart. If the source is a magnet wire coating machine, you may use the procedures in section 2.0 of appendix A to this subpart as an alternative.

(1) During the capture efficiency determination required by §63.3960 and described in §§63.3964 and 63.3965, you must monitor and record either the gas volumetric flow rate or the duct static pressure for each separate capture device in your emission capture system at least once every 15 minutes during each of the three test runs at a point in the duct between the capture device and the add-on control device inlet.

(2) Calculate and record the average gas volumetric flow rate or duct static pressure for the three test runs for each capture device. This average gas volumetric flow rate or duct static pressure is the minimum operating limit for that specific capture device.

§ 63.3968 What are the requirements for continuous parameter monitoring system installation, operation, and maintenance?

(a) *General.* You must install, operate, and maintain each CPMS specified in paragraphs (c), (e), (f), and (g) of this section according to paragraphs (a)(1) through (6) of this section. You must install, operate, and maintain each CPMS specified in paragraphs (b) and (d) of this section according to paragraphs (a)(3) through (5) of this section.

(1) The CPMS must complete a minimum of one cycle of operation for each successive 15-minute period. You must have a minimum of four equally spaced successive cycles of CPMS operation in 1 hour.

(2) You must determine the average of all recorded readings for each successive 3 hour period of the emission capture system and add-on control device operation.

(3) You must record the results of each inspection, calibration, and validation check of the CPMS.

(4) You must maintain the CPMS at all times and have available necessary parts for routine repairs of the monitoring equipment.

(5) You must operate the CPMS and collect emission capture system and add-on control device parameter data at all times that a controlled coating operation is operating, except during monitoring

malfunctions, associated repairs, and required quality assurance or control activities (including, if applicable, calibration checks and required zero and span adjustments).

(6) You must not use emission capture system or add-on control device parameter data recorded during monitoring malfunctions, associated repairs, out-of-control periods, or required quality assurance or control activities when calculating data averages. You must use all the data collected during all other periods in calculating the data averages for determining compliance with the emission capture system and add-on control device operating limits.

(7) A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the CPMS to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions. Any period for which the monitoring system is out-of-control and data are not available for required calculations is a deviation from the monitoring requirements.

(b) *Capture system bypass line.* You must meet the requirements of paragraphs (b)(1) and (2) of this section for each emission capture system that contains bypass lines that could divert emissions away from the add-on control device to the atmosphere.

(1) You must monitor or secure the valve or closure mechanism controlling the bypass line in a nondiverting position in such a way that the valve or closure mechanism cannot be opened without creating a record that the valve was opened. The method used to monitor or secure the valve or closure mechanism must meet one of the requirements specified in paragraphs (b)(1)(i) through (v) of this section.

(i) *Flow control position indicator.* Install, calibrate, maintain, and operate according to the manufacturer's specifications a flow control position indicator that takes a reading at least once every 15 minutes and provides a record indicating whether the emissions are directed to the add-on control device or diverted from the add-on control device. The time of occurrence and flow control position must be recorded, as well as every time the flow direction is changed. The flow control position indicator must be installed at the entrance to any bypass line that could divert the emissions away from the add-on control device to the atmosphere.

(ii) *Car-seal or lock-and-key valve closures.* Secure any bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. You must visually inspect the seal or closure mechanism at least once every month to ensure that the valve is maintained in the closed position, and the emissions are not diverted away from the add-on control device to the atmosphere.

(iii) *Valve closure monitoring.* Ensure that any bypass line valve is in the closed (nondiverting) position through monitoring of valve position at least once every 15 minutes. You must inspect the monitoring system at least once every month to verify that the monitor will indicate valve position.

(iv) *Automatic shutdown system.* Use an automatic shutdown system in which the coating operation is stopped when flow is diverted by the bypass line away from the add-on control device to the atmosphere when the coating operation is running. You must inspect the automatic shutdown system at least once every month to verify that it will detect diversions of flow and shut down the coating operation.

(v) *Flow direction indicator.* Install, calibrate, maintain, and operate according to the manufacturer's specifications a flow direction indicator that takes a reading at least once every 15 minutes and provides a record indicating whether the emissions are directed to the add-on control device or diverted from the add-on control device. Each time the flow direction changes, the next reading of the time of occurrence and flow direction must be recorded. The flow direction indicator must be installed in each bypass line or air makeup supply line that could divert the emissions away from the add-on control device to the atmosphere.

(2) If any bypass line is opened, you must include a description of why the bypass line was opened and the length of time it remained open in the semiannual compliance reports required in §63.3920.

(c) *Thermal oxidizers and catalytic oxidizers.* If you are using a thermal oxidizer or catalytic oxidizer as an add-on control device (including those used with concentrators or with carbon adsorbers to treat desorbed concentrate streams), you must comply with the requirements in paragraphs (c)(1) through (3) of this section:

(1) For a thermal oxidizer, install a gas temperature monitor in the firebox of the thermal oxidizer or in the duct immediately downstream of the firebox before any substantial heat exchange occurs.

(2) For a catalytic oxidizer, install gas temperature monitors upstream and/or downstream of the catalyst bed as required in §63.3967(b).

(3) For all thermal oxidizers and catalytic oxidizers, you must meet the requirements in paragraphs (a) and (c)(3)(i) through (v) of this section for each gas temperature monitoring device.

(i) Locate the temperature sensor in a position that provides a representative temperature.

(ii) Use a temperature sensor with a measurement sensitivity of 5 degrees Fahrenheit or 1.0 percent of the temperature value, whichever is larger.

(iii) Before using the sensor for the first time or when relocating or replacing the sensor, perform a validation check by comparing the sensor output to a calibrated temperature measurement device or by comparing the sensor output to a simulated temperature.

(iv) Conduct an accuracy audit every quarter and after every deviation. Accuracy audit methods include comparisons of sensor output to redundant temperature sensors, to calibrated temperature measurement devices, or to temperature simulation devices.

(v) Conduct a visual inspection of each sensor every quarter if redundant temperature sensors are not used.

(d) *****

(e) *****

(f) *****

(g) *Emission capture systems.* The capture system monitoring system must comply with the applicable requirements in paragraphs (g)(1) and (2) of this section. If the source is a magnet wire coating machine, you may use the procedures in section 2.0 of appendix A to this subpart as an alternative.

(1) For each flow measurement device, you must meet the requirements in paragraphs (a) and (g)(1)(i) through (vii) of this section.

(i) Locate a flow sensor in a position that provides a representative flow measurement in the duct from each capture device in the emission capture system to the add-on control device.

(ii) Use a flow sensor with an accuracy of at least 10 percent of the flow.

(iii) Perform an initial sensor calibration in accordance with the manufacturer's requirements.

(iv) Perform a validation check before initial use or upon relocation or replacement of a sensor. Validation checks include comparison of sensor values with electronic signal simulations or via relative accuracy testing.

(v) Conduct an accuracy audit every quarter and after every deviation. Accuracy audit methods include comparisons of sensor values with electronic signal simulations or via relative accuracy testing.

(vi) Perform leak checks monthly.

(vii) Perform visual inspections of the sensor system quarterly if there is no redundant sensor.

(2) For each pressure drop measurement device, you must comply with the requirements in paragraphs (a) and (g)(2)(i) through (vii) of this section.

(i) Locate the pressure sensor(s) in or as close to a position that provides a representative measurement of the pressure drop across each opening you are monitoring.

(ii) Use a pressure sensor with an accuracy of at least 0.5 inches of water column or 5 percent of the measured value, whichever is larger.

(iii) Perform an initial calibration of the sensor according to the manufacturer's requirements.

(iv) Conduct a validation check before initial operation or upon relocation or replacement of a sensor. Validation checks include comparison of sensor values to calibrated pressure measurement devices or to pressure simulation using calibrated pressure sources.

(v) Conduct accuracy audits every quarter and after every deviation. Accuracy audits include comparison of sensor values to calibrated pressure measurement devices or to pressure simulation using calibrated pressure sources.

(vi) Perform monthly leak checks on pressure connections. A pressure of at least 1.0 inches of water column to the connection must yield a stable sensor result for at least 15 seconds.

(vii) Perform a visual inspection of the sensor at least monthly if there is no redundant sensor.

§ 63.3980 Who implements and enforces this subpart?

(a) This subpart can be implemented and enforced by us, the U.S. Environmental Protection Agency (EPA), or a delegated authority such as your State, local, or tribal agency. If the Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the EPA) has the authority to implement and enforce this subpart. You should contact your EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are listed in paragraphs (c)(1) through (4) of this section:

(1) Approval of alternatives to the requirements in §63.3881 through 3883 and §63.3890 through 3893.

(2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.

(3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.

(4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

§ 63.3981 What definitions apply to this subpart?

Terms used in this subpart are defined in the CAA, in 40 CFR 63.2, and in this section as follows:

Additive means a material that is added to a coating after purchase from a supplier (e.g., catalysts, activators, accelerators).

Add-on control means an air pollution control device, such as a thermal oxidizer or carbon adsorber, that reduces pollution in an air stream by destruction or removal before discharge to the atmosphere.

Adhesive, adhesive coating means any chemical substance that is applied for the purpose of bonding two surfaces together. Products used on humans and animals, adhesive tape, contact paper, or any other product with an adhesive incorporated onto or in an inert substrate shall not be considered adhesives under this subpart.

Assembled on-road vehicle coating means any coating operation in which coating is applied to the surface of some component or surface of a fully assembled motor vehicle or trailer intended for on-road use including, but not limited to, components or surfaces on automobiles and light-duty trucks that have been repaired after a collision or otherwise repainted, fleet delivery trucks, and motor homes and other

recreational vehicles (including camping trailers and fifth wheels). Assembled on-road vehicle coating includes the concurrent coating of parts of the assembled on-road vehicle that are painted off-vehicle to protect systems, equipment, or to allow full coverage. Assembled on-road vehicle coating does not include surface coating operations that meet the applicability criteria of the automobiles and light-duty trucks NESHAP. Assembled on-road vehicle coating also does not include the use of adhesives, sealants, and caulks used in assembling on-road vehicles.

Capture device means a hood, enclosure, room, floor sweep, or other means of containing or collecting emissions and directing those emissions into an add-on air pollution control device.

Capture efficiency or capture system efficiency means the portion (expressed as a percentage) of the pollutants from an emission source that is delivered to an add-on control device.

Capture system means one or more capture devices intended to collect emissions generated by a coating operation in the use of coatings or cleaning materials, both at the point of application and at subsequent points where emissions from the coatings and cleaning materials occur, such as flashoff, drying, or curing. As used in this subpart, multiple capture devices that collect emissions generated by a coating operation are considered a single capture system.

Cleaning material means a solvent used to remove contaminants and other materials, such as dirt, grease, oil, and dried or wet coating (e.g., depainting or paint stripping), from a substrate before or after coating application or from equipment associated with a coating operation, such as spray booths, spray guns, racks, tanks, and hangers. Thus, it includes any cleaning material used on substrates or equipment or both.

Coating means a material applied to a substrate for decorative, protective, or functional purposes. Such materials include, but are not limited to, paints, sealants, liquid plastic coatings, caulks, inks, adhesives, and maskants. Decorative, protective, or functional materials that consist only of protective oils for metal, acids, bases, or any combination of these substances, or paper film or plastic film which may be pre-coated with an adhesive by the film manufacturer, are not considered coatings for the purposes of this subpart. A liquid plastic coating means a coating made from fine particle-size polyvinyl chloride (PVC) in solution (also referred to as a plastisol).

Coating operation means equipment used to apply cleaning materials to a substrate to prepare it for coating application (surface preparation) or to remove dried coating; to apply coating to a substrate (coating application) and to dry or cure the coating after application; or to clean coating operation equipment (equipment cleaning). A single coating operation may include any combination of these types of equipment, but always includes at least the point at which a given quantity of coating or cleaning material is applied to a given part and all subsequent points in the affected source where organic HAP are emitted from the specific quantity of coating or cleaning material on the specific part. There may be multiple coating operations in an affected source. Coating application with handheld, non-refillable aerosol containers, touch-up markers, or marking pens is not a coating operation for the purposes of this subpart.

Coatings solids means the nonvolatile portion of the coating that makes up the dry film.

Continuous parameter monitoring system (CPMS) means the total equipment that may be required to meet the data acquisition and availability requirements of this subpart, used to sample, condition (if applicable), analyze, and provide a record of coating operation, or capture system, or add-on control device parameters.

Controlled coating operation means a coating operation from which some or all of the organic HAP emissions are routed through an emission capture system and add-on control device.

Deviation means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

(1) Fails to meet any requirement or obligation established by this subpart including but not limited to, any emission limit or operating limit or work practice standard;

(2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or

(3) Fails to meet any emission limit, or operating limit, or work practice standard in this subpart during startup, shutdown, or malfunction, regardless of whether or not such failure is permitted by this subpart.

Emission limitation means the aggregate of all requirements associated with a compliance option including emission limit, operating limit, work practice standard, etc.

Enclosure means a structure that surrounds a source of emissions and captures and directs the emissions to an add-on control device.

Exempt compound means a specific compound that is not considered a VOC due to negligible photochemical reactivity. The exempt compounds are listed in 40 CFR 51.100(s).

Extreme performance fluoropolymer coating means coatings that are formulated systems based on fluoropolymer resins which often contain bonding matrix polymers dissolved in non-aqueous solvents as well as other ingredients. Extreme performance fluoropolymer coatings are typically used when one or more critical performance criteria are required including, but not limited to a nonstick low-energy surface, dry film lubrication, high resistance to chemical attack, extremely wide operating temperature, high electrical insulating properties, or that the surface comply with government (e.g., USDA, FDA) or third party specifications for health, safety, reliability, or performance. Once applied to a substrate, extreme performance fluoropolymer coatings undergo a curing process that typically requires high temperatures, a chemical reaction, or other specialized technology.

Facility maintenance means the routine repair or renovation (including the surface coating) of the tools, equipment, machinery, and structures that comprise the infrastructure of the affected facility and that are necessary for the facility to function in its intended capacity.

General use coating means any material that meets the definition of coating but does not meet the definition of high performance coating, rubber-to-metal coating, magnet wire coating, or extreme performance fluoropolymer coating as defined in this section.

High performance architectural coating means any coating applied to architectural subsections which is required to meet the specifications of Architectural Aluminum Manufacturer's Association's publication number AAMA 605.2-2000.

High performance coating means any coating that meets the definition of high performance architectural coating or high temperature coating in this section.

High temperature coating means any coating applied to a substrate which during normal use must withstand temperatures of at least 538 degrees Celsius (1000 degrees Fahrenheit).

Hobby shop means any surface coating operation, located at an affected source, that is used exclusively for personal, noncommercial purposes by the affected source's employees or assigned personnel.

Magnet wire coatings, commonly referred to as magnet wire enamels, are applied to a continuous strand of wire which will be used to make turns (windings) in electrical devices such as coils, transformers, or motors. Magnet wire coatings provide high dielectric strength and turn-to-turn conductor insulation. This allows the turns of an electrical device to be placed in close proximity to one another which leads to increased coil effectiveness and electrical efficiency.

Magnet wire coating machine means equipment which applies and cures magnet wire coatings.

Manufacturer's formulation data means data on a material (such as a coating) that are supplied by the material manufacturer based on knowledge of the ingredients used to manufacture that material, rather than based on testing of the material with the test methods specified in §63.3941. Manufacturer's formulation data may include, but are not limited to, information on density, organic HAP content, volatile organic matter content, and coating solids content.

Mass fraction of organic HAP means the ratio of the mass of organic HAP to the mass of a material in which it is contained, expressed as kg of organic HAP per kg of material.

Month means a calendar month or a pre-specified period of 28 days to 35 days to allow for flexibility in recordkeeping when data are based on a business accounting period.

Non-HAP coating means, for the purposes of this subpart, a coating that contains no more than 0.1 percent by mass of any individual organic HAP that is an OSHA-defined carcinogen as specified in 29 CFR 1910.1200(d)(4) and no more than 1.0 percent by mass for any other individual HAP.

Organic HAP content means the mass of organic HAP emitted per volume of coating solids used for a coating calculated using Equation 2 of §63.3941. The organic HAP content is determined for the coating in the condition it is in when received from its manufacturer or supplier and does not account for any alteration after receipt. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, organic HAP content is the mass of organic HAP that is emitted, rather than the organic HAP content of the coating as it is received.

Permanent total enclosure (PTE) means a permanently installed enclosure that meets the criteria of Method 204 of appendix M, 40 CFR part 51, for a PTE and that directs all the exhaust gases from the enclosure to an add-on control device.

Personal watercraft means a vessel (boat) which uses an inboard motor powering a water jet pump as its primary source of motive power and which is designed to be operated by a person or persons sitting, standing, or kneeling on the vessel, rather than in the conventional manner of sitting or standing inside the vessel.

Protective oil means an organic material that is applied to metal for the purpose of providing lubrication or protection from corrosion without forming a solid film. This definition of protective oil includes, but is not limited to, lubricating oils, evaporative oils (including those that evaporate completely), and extrusion oils. Protective oils used on miscellaneous metal parts and products include magnet wire lubricants and soft temporary protective coatings that are removed prior to installation or further assembly of a part or component.

Reactive adhesive means adhesive systems composed, in part, of volatile monomers that react during the adhesive curing reaction, and, as a result, do not evolve from the film during use. These volatile components instead become integral parts of the adhesive through chemical reaction. At least 70 percent of the liquid components of the system, excluding water, react during the process.

Research or laboratory facility means a facility whose primary purpose is for research and development of new processes and products, that is conducted under the close supervision of technically trained personnel, and is not engaged in the manufacture of final or intermediate products for commercial purposes, except in a *de minimis* manner.

Responsible official means responsible official as defined in 40 CFR 70.2.

Rubber-to-metal coatings are coatings that contain heat-activated polymer systems in either solvent or water that, when applied to metal substrates, dry to a non-tacky surface and react chemically with the rubber and metal during a vulcanization process.

Startup, initial means the first time equipment is brought online in a facility.

Surface preparation means use of a cleaning material on a portion of or all of a substrate. This includes use of a cleaning material to remove dried coating, which is sometimes called depainting.

Temporary total enclosure means an enclosure constructed for the purpose of measuring the capture efficiency of pollutants emitted from a given source as defined in Method 204 of appendix M, 40 CFR part 51.

Thinner means an organic solvent that is added to a coating after the coating is received from the supplier.

Total volatile hydrocarbon (TVH) means the total amount of nonaqueous volatile organic matter determined according to Methods 204 and 204A through 204F of appendix M to 40 CFR part 51 and

substituting the term TVH each place in the methods where the term VOC is used. The TVH includes both VOC and non-VOC.

Uncontrolled coating operation means a coating operation from which none of the organic HAP emissions are routed through an emission capture system and add-on control device.

Volatile organic compound (VOC) means any compound defined as VOC in 40 CFR 51.100(s).

Volume fraction of coating solids means the ratio of the volume of coating solids (also known as the volume of nonvolatiles) to the volume of a coating in which it is contained; liters (gal) of coating solids per liter (gal) of coating.

Wastewater means water that is generated in a coating operation and is collected, stored, or treated prior to being discarded or discharged.

Table 1 to Subpart M of Part 63—Operating Limits if Using the Emission Rate With Add-On Controls Option

For the following device . . .	You must meet the following operating limit	And you must demonstrate continuous compliance with the operating limit by
1. Thermal oxidizer	a. The average Combustion temperature in any 3-hour period must not fall below the combustion temperature limit established according to §63.3967(a).	i. Collecting the combustion temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average Combustion temperature at or above the temperature limit.
2. Catalytic oxidizer	a. The average Temperature measured just before the catalyst bed in any 3-hour period must not fall below the limit established according to §63.3967(b) (for magnet wire coating machines, temperature can be monitored before or after the catalyst bed); and either b. Ensure that the average temperature difference across the catalyst bed in any 3-hour period does not fall below the temperature difference limit established according to §63.3967(b) (2); or c. Develop and implement an inspection and maintenance plan according to §63.3967(b)(4) or for magnet wire coating machines according to section 3.0 of appendix A to this subpart.	i. Collecting the temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average temperature before (or for magnet wire coating machines after) the catalyst bed at or above the temperature limit. i. Collecting the temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average Temperature difference at or above the temperature difference limit. i. Maintaining and up-to-date inspection and maintenance plan, records of annual catalyst activity checks, records of monthly inspections of the oxidizer system, and records of the annual internal inspections of the catalyst bed. If a problem is discovered during a monthly or annual inspection required by §63.3967(b)(4) or for magnet wire coating machines by section 3.0 of appendix A to this subpart, you must take corrective action as soon as practicable consistent with the manufacturer's recommendations.
3. Regenerative carbon adsorber.	a. The total regeneration desorbing gas (e.g., steam or nitrogen) mass flow for each carbon bed	i. Measuring the total regeneration desorbing gas (e.g., steam or nitrogen) mass flow for each regeneration cycle

Table 1 to Subpart M of Part 63—Operating Limits if Using the Emission Rate With Add-On Controls Option

For the following device . . .	You must meet the following operating limit	And you must demonstrate continuous compliance with the operating limit by
	<p>regeneration cycle must not fall below the total regeneration desorbing gas mass flow limit established according to §63.3967(c); and</p> <p>b. The temperature of the carbon bed, after completing each regeneration and any cooling cycle, must not exceed the carbon bed temperature limit established according to § 63.3967(c).</p>	<p>according to §63.3968(d); and</p> <p>ii. Maintaining the total regeneration desorbing gas mass flow at or above the mass flow limit.</p> <p>i. Measuring the temperature of the carbon bed after completing each regeneration and any cooling cycle according to §63.3968(d); and</p> <p>ii. Operating the carbon beds such that each carbon bed is not returned to service until completing each regeneration and any cooling cycle until the recorded temperature of the carbon bed is at or below the temperature limit.</p>
<p>4. Condenser</p>	<p>a. The average condenser outlet (product side) gas temperature in any 3-hour period must not exceed the temperature limit established according to §63.3967(d).</p>	<p>i. Collecting the condenser outlet (product side) gas Temperature according to §63.3968(e);</p> <p>ii. Reducing the data to 3-hour block averages; and</p> <p>iii. Maintaining the 3-hour average gas temperature at the outlet at or below the temperature limit.</p>
<p>5. Concentrators, including zeolite wheels and rotary carbon adsorbers.</p>	<p>a. The average gas temperature of the desorption concentrate stream in any 3-hour period must not fall below the limit established according to §63.3967(e); and</p> <p>b. The average pressure drop of the dilute stream across the concentrator in any 3-hour period must not fall below the limit established according to §63.3967(e). pressure drop at or above the pressure drop limit.</p>	<p>i. Collecting the temperature data according to 63.3968(f);</p> <p>ii. Reducing the data to 3-hour block averages; and</p> <p>iii. Maintaining the 3-hour average temperature at or above the temperature limit.</p> <p>i. Collecting the pressure drop data according to 63.3968(f);</p> <p>ii. Reducing the pressure drop data to 3-hour block averages; and</p> <p>iii. Maintaining the 3-hour average</p>
<p>6. Emission capture system that is a PTE according to §63.3965(a).</p>	<p>a. The direction of the air flow at all times must be into the enclosure; and either</p>	<p>i. Collecting the direction of air flow, and either the facial velocity of air through all natural draft openings according to §63.3968(b)(1) or the pressure drop across the enclosure according to §63.3968(g)(2); and</p> <p>ii. Maintaining the facial velocity of air flow through all natural draft openings or the pressure drop at or above the facial velocity limit or pressure drop limit, and maintaining the direction of air flow into the enclosure at all times.</p>

Table 1 to Subpart M of Part 63—Operating Limits if Using the Emission Rate With Add-On Controls Option

For the following device . . .	You must meet the following operating limit	And you must demonstrate continuous compliance with the operating limit by
7. Emission capture system that is not a PTE according to §63.3965(a).	<p>b. The average facial velocity of air through all natural draft openings in the enclosure must be at least 200 feet per minutes; or</p> <p>c. The pressure drop across the enclosure must be at least 0.007 inch H₂O, as established in Method 204 of appendix M to 40 CFR part 51.</p> <p>a. The average gas volumetric flow rate or duct static pressure in each duct between a capture device and add-on control device inlet in any 3-hour period must not fall below the average volumetric flow rate or duct static pressure limit established for that capture device according to §63.3967(f).</p>	<p>i. See items 6.a.i and 6.a.ii.</p> <p>i. See items 6.a.i and 6.a.ii.</p> <p>i. Collecting the gas volumetric flow rate or duct static pressure for each capture device according to §63.3968(g);</p> <p>ii. Reducing the data to 3-hour block averages; and</p> <p>iii. Maintaining the 3-hour average gas volumetric flow rate or duct static pressure for each capture device at or above the gas volumetric flow rate or duct static pressure limited.</p>

Table 2 to Subpart M of Part 63—Applicability of General Provisions to Subpart M of Part 63

Citation	Subject	Applicable to subpart M	Explanation
§ 63.1(a)(1)-(14)	General Applicability.	Yes.	
§ 63.1(b)(1)-(3)	Initial Applicability Determination.	Yes	Applicability to subpart M is also specified in §63.3881.
§ 63.1(c)(1)	Applicability After Standard Established.	Yes.	
§ 63.1(c)(2)-(3)	Applicability of Permit Program for Area Sources.	No	Area sources are not subject to subpart M.
§ 63.1(c)(4)-(5)	Extensions and Notifications.	Yes.	
§ 63.1(e)	Applicability of Permit Program Before Relevant Standard is Set.	Yes.	
§ 63.2	Definitions	Yes	Additional definitions are specified in §63.3981.
§ 63.1(a)-(c)	Units and Abbreviations.	Yes.	
§ 63.4(a)(1)-(5)	Prohibited Activities.	Yes.	
§ 63.4(b)-(c).	Circumvention/ Severability.	Yes.	

Table 2 to Subpart M MMM of Part 63—Applicability of General Provisions to Subpart M MMM of Part 63

Citation	Subject	Applicable to subpart M MMM	Explanation
§ 63.5(a)	Construction/Reconstruction.	Yes.	
§ 63.5(b)(1)-(6)	Requirements for Existing, Newly Constructed, and Reconstructed Sources.	Yes.	
§ 63.5(d)	Application for Approval of Construction/Reconstruction.	Yes.	
§ 63.5(e)	Approval of Construction/Reconstruction.	Yes.	
§ 63.5(f)	Approval of Construction/Reconstruction Based on Prior State Review.	Yes.	
§ 63.6(a)	Compliance With Standards and Maintenance Requirements -Applicability.	Yes.	
§ 63.6(b)(1)-(7).	Compliance Dates for New and Reconstructed Sources	Yes	Section 63.3883 specifies the compliance dates.
§ 63.6(c)(1)-(5)	Compliance Dates for Existing Sources.	Yes	Section 63.3883 specifies the compliance dates.
§ 63.6(e)(1)-(2)	Operation and Maintenance.	Yes.	
§ 63.6(e)(3)	Startup, Shutdown, and Malfunction Plan.	Yes	Only sources using an add-on control device to comply with the standard must complete startup, shutdown, and malfunction plans.
§ 63.6(f)(1)	Compliance Except During Startup, Shutdown, and Malfunction.	Yes	Applies only to sources using an add-on control device to comply with the standard.
§ 63.6(f)(2)-(3).	Methods for Determining Compliance..	Yes.	
§ 63.6(g)(1)-(3)	Use of an Alternative Standard.	Yes	
§ 63.6(h)	Compliance With Opacity/Visible Emission Standards	No	Subpart M MMM does not establish opacity standards and does not require continuous opacity monitoring systems (COMS).
§ 63.6(i)(1)-(16)	Extension of Compliance.	Yes.	
§ 63.6(j)	Presidential Compliance Exemption.	Yes.	
§ 63.7(a)(1).	Performance Test Requirements - Applicability.	Yes	Applies to all affected sources. Additional requirements for performance testing are specified in §§ 63.3964, 63.3965, and 63.3966.

Table 2 to Subpart M MMM of Part 63—Applicability of General Provisions to Subpart M MMM of Part 63

Citation	Subject	Applicable to subpart M MMM	Explanation
§ 63.7(a)(2)	Performance Test Requirements - Dates.	Yes	Applies only to performance tests for capture system and control device efficiency at sources using these to comply with the standard. Section 63.3960 specifies the schedule for performance test requirements that are earlier than those specified in §63.7(a)(2).
§ 63.7(a)(3).	Performance Tests Required By the Administrator.	Yes.	
§ 63.7(b)-(e)	Performance Test Requirements - Notification, Quality Assurance, Facilities Necessary for Safe Testing, Conditions During Test.	Yes	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.7(f)	Performance Test Requirements - Use of Alternative Test Method. efficiency.	Yes	Applies to all test methods except those used to determine capture system
§ 63.7(g)-(h)	Performance Test Requirements - Data Analysis, Recordkeeping, Reporting, Waiver of Test.	Yes	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.8(a)(1)-(3)	Monitoring Requirements - Applicability.	Yes	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for monitoring are specified in §63.3968.
§ 63.8(a)(4)	Additional Monitoring Requirements.	No	Subpart M MMM does not have monitoring requirements for flares.
§ 63.8(b)	Conduct of Monitoring.	Yes.	
§ 63.8(c)(1)-(3)	Continuous Monitoring Systems (CMS) Operation and Maintenance.	Yes	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for CMS operations and maintenance are specified in §63.3968.
§ 63.8(c)(4).	CMS	No	§ 63.3968 specifies the requirements for the operation of CMS for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(5)	COMS	No	Subpart M MMM does not have opacity or visible emission standards.

Table 2 to Subpart M MMM of Part 63—Applicability of General Provisions to Subpart M MMM of Part 63

Citation	Subject	Applicable to subpart M MMM	Explanation
§ 63.8(c)(6).	CMS Requirements	No	Section 63.3968 specifies the requirements for monitoring systems for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(7)	CMS Out-of-Control Periods.	Yes.	
§ 63.8(c)(8).	CMS Out-of-Control Periods and Reporting.	No	§ 63.3920 requires reporting of CMS out-of-control periods.
§ 63.8(d)-(e)	Quality Control Program and CMS Performance Evaluation.	No	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§ 63.8(f)(1)-(5)	Use of an Alternative Monitoring Method.	Yes.	
§ 63.8(f)(6)	Alternative to Relative Accuracy Test.	No	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§ 63.8(g)(1)-(5)	Data Reduction.	No	Sections 63.3967 and 63.3968 specify monitoring data reduction.
§ 63.9(a)-(d).	Notification Requirements.	Yes.	
§ 63.9(e)	Notification of Performance Test.	Yes	Applies only to capture system and add-on control device performance tests at sources using these to comply with the standard.
§ 63.9(f).	Notification of Visible Emissions/Opacity Test.	No	Subpart M MMM does not have opacity or visible emissions standards.
§ 63.9(g)(1)-(3)	Additional Notifications When Using CMS	No	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§ 63.9(h).	Notification of Compliance Status.	Yes	Section 63.3910 specifies the dates for submitting the notification of compliance status.
§ 63.9(i).	Adjustment of Submittal Deadlines.	Yes.	
§ 63.9(j).	Change in Previous Information.	Yes.	
§ 63.10(a).	Recordkeeping/ Reporting Applicability and General Information.	Yes.	
§ 63.10(b)(1).	General Recordkeeping Requirements.	Yes	Additional requirements are specified in §§ 63.3930 and 63.3931.

Table 2 to Subpart M MMM of Part 63—Applicability of General Provisions to Subpart M MMM of Part 63

Citation	Subject	Applicable to subpart M MMM	Explanation
§ 63.10(b)(2) (i)-(v)	Recordkeeping Relevant to Startup, Shutdown, and Malfunction Periods and CMS.	Yes	Requirements for startup, shutdown, and malfunction records only apply to add-on control devices used to comply with the standard.
§ 63.10(b)(2) (vi)-(xi)	...	Yes.	
§ 63.10(b)(2) (xii)	Records	Yes.	
§ 63.10(b)(2) (xiii)	...	No	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§ 63.10(b)(2) (xiv)	...	Yes.	
§ 63.10(b)(3).	Recordkeeping Requirements for Applicability Determinations.	Yes.	
§ 63.10(c) (1)-(6)	Additional Recordkeeping Requirements for Sources with CMS.	Yes.	
§ 63.10(c) (7)-(8).	...	No	The same records are required in §63.3920(a)(7).
§ 63.10(c) (9)-(15)	...	Yes.	
§ 63.10(d)(1)	General Reporting Requirements.	Yes	Additional requirements are specified in §63.3920.
§ 63.10(d)(2)	Report of Performance Test Results.	Yes	Additional requirements are specified in §63.3920(b).
§ 63.10(d)(3)	Reporting Opacity or Visible Emissions Observations.	No	Subpart M MMM does not require opacity or visible emissions observations.
§ 63.10(d)(4)..	Progress Reports for Sources With Compliance Extensions.	Yes.	
§ 63.10(d)(5).	Startup, Shutdown, and Malfunction Reports.	Yes	Applies only to add-on control devices at sources using these to comply with the standard.
§ 63.10(e) (1)-(2)	Additional CMS Reports	No	Subpart M MMM does not continuous emissions monitoring systems.
§ 63.10(e) (3).	Excess Emissions/CMS Performance Reports.	No	Section 63.3920 (b) specifies the contents of periodic compliance reports.
§ 63.10(e) (4).	COMS Data Reports	No	Subpart M MMM does not specify requirements for opacity or COMS.

Table 2 to Subpart M MMM of Part 63—Applicability of General Provisions to Subpart M MMM of Part 63

Citation	Subject	Applicable to subpart M MMM	Explanation
§ 63.10(f).	Recordkeeping/ Reporting Waiver.	Yes.	
§ 63.11.	Control Device Requirements/Flares.	No	Subpart M MMM does not specify use of flares for compliance.
§ 63.12	State Authority and Delegations.	Yes.	
§ 63.13..	Addresses	Yes.	
§ 63.14..	Incorporation by Reference.	Yes.	
§ 63.15..	Availability of Information/ Confidentiality.	Yes.	

Table 3 to Subpart M MMM of Part 63—Default Organic HAP Mass Fraction for Solvents and Solvent Blends

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data and which match either the solvent blend name or the chemical abstract series (CAS) number. If a solvent blend matches both the name and CAS number for an entry, that entry's organic HAP mass fraction must be used for that solvent blend. Otherwise, use the organic HAP mass fraction for the entry matching either the solvent blend name or CAS number, or use the organic HAP mass fraction from table 4 to this subpart if neither the name or CAS number match.

Solvent/solvent blend	CAS. No.	Average organic HAP mass fraction	Typical organic HAP, percent by mass
1. Toluene.....	108-88-3	1.0	Toluene.
2. Xylene(s).....	1330-20-7	1.0	Xylenes, ethylbenzene.
3. Hexane.....	110-54-3	0.5	n-hexane.
4. n-Hexane.....	110-54-3	1.0	n-hexane.
5. Ethylbenzene.....	100-41-4	1.0	Ethylbenzene.
6. Aliphatic 140.....	0	None.
7. Aromatic 100.....	0.02	1% xylene, 1% cumene.
8. Aromatic 150.....	0.09	Naphthalene.
9. Aromatic naphtha.....	64742-95-6	0.02	1% xylene, 1% cumene.
10. Aromatic solvent.....	64742-94-5	0.1	Naphthalene.
11. Exempt mineral spirits.....	8032-32-4	0	None.
12. Ligroines (VM & P).....	8032-32-4	0	None.
13. Lactol spirits.....	64742-89-6	0.15	Toluene.
14. Low aromatic white spirit....	64742-82-1	0	None.
15. Mineral spirits.....	64742-88-7	0.01	Xylenes.
16. Hydrotreated naphtha.....	64742-48-9	0	None.
17. Hydrotreated light distillate.	64742-47-8	0.001	Toluene.
18. Stoddard solvent.....	8052-41-3	0.01	Xylenes.
19. Super high-flash naphtha....	64742-95-6	0.05	Xylenes.
20. Varsol ® solvent.....	8052-49-3	0.01	0.5% xylenes, 0.5% ethylbenzene.
21. VM & P naphtha.....	64742-89-8	0.06	3% toluene, 3% xylene.
22. Petroleum distillate mixture..	68477-31-6	0.08	4% naphthalene, 4% biphenyl.

Table 4 to Subpart MMMM of Part 63—Default Organic HAP Mass Fraction for Petroleum Solvent Groups^a

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data.

Solvent type	Average organic HAP mass fraction	Typical organic HAP, percent by mass
Aliphatic ^b	0.03	1% Xylene, 1% Toluene, and 1% Ethylbenzene.
Aromatic ^c	0.06	4% Xylene, 1% Toluene, and 1% Ethylbenzene.

a Use this table only if the solvent blend does not match any of the solvent blends in Table 3 to this subpart by either solvent blend name or CAS number and you only know whether the blend is aliphatic or aromatic.

b Mineral Spirits 135, Mineral Spirits 150 EC, Naphtha, Mixed Hydrocarbon, Aliphatic Hydrocarbon, Aliphatic Naphtha, Naphthol Spirits, Petroleum Spirits, Petroleum Oil, Petroleum Naphtha, Solvent Naphtha, Solvent Blend.

c Medium-flash Naphtha, High-flash Naphtha, Aromatic Naphtha, Light Aromatic Naphtha, Light Aromatic Hydrocarbons, Aromatic Hydrocarbons, Light Aromatic Solvent.

Appendix A to Subpart MMMM of Part 63—Alternative Capture Efficiency and Destruction Efficiency Measurement and Monitoring Procedures for Magnet Wire Coating Operations

1.0 Introduction.

1.1 These alternative procedures for capture efficiency and destruction efficiency measurement and monitoring are intended principally for newer magnet wire coating machines where the control device is internal and integral to the oven so that it is difficult or infeasible to make gas measurements at the inlet to the control device.

1.2 In newer gas fired magnet wire ovens with thermal control (no catalyst), the burner tube serves as the control device (thermal oxidizer) for the process. The combustion of solvents in the burner tube is the principal source of heat for the oven.

1.3 In newer magnet wire ovens with a catalyst there is either a burner tube (gas fired ovens) or a tube filled with electric heating elements (electric heated oven) before the catalyst. A large portion of the solvent is often oxidized before reaching the catalyst. The combustion of solvents in the tube and across the catalyst is the principal source of heat for the oven. The internal catalyst in these ovens cannot be accessed without disassembly of the oven. This disassembly includes removal of the oven insulation. Oven reassembly often requires the installation of new oven insulation.

1.4 Some older magnet wire ovens have external afterburners. A significant portion of the solvent is oxidized within these ovens as well.

1.5 The alternative procedure for destruction efficiency determines the organic carbon content of the volatiles entering the control device based on the quantity of coating used, the carbon content of the volatile portion of the coating and the efficiency of the capture system. The organic carbon content of the control device outlet (oven exhaust for ovens without an external afterburner) is determined using Method 25 or 25A.

1.6 When it is difficult or infeasible to make gas measurements at the inlet to the control device, measuring capture efficiency with a gas-to-gas protocol (see §63.3965(d)) which relies on direct measurement of the captured gas stream will also be difficult or infeasible. In these situations, capture efficiency measurement is more appropriately done with a procedure which does not rely on direct measurement of the captured gas stream.

1.7 Magnet wire ovens are relatively small compared to many other coating ovens. The exhaust rate from an oven is low and varies as the coating use rate and solvent loading rate change from job to job. The air balance in magnet wire ovens is critical to product quality. Magnet wire ovens must be operated under negative pressure to avoid smoke and odor in the workplace, and the exhaust rate must be sufficient to prevent over heating within the oven.

1.8 The liquid and gas measurements needed to determine capture efficiency and control device efficiency using these alternative procedures may be made simultaneously.

1.9 Magnet wire facilities may have many (e.g., 20 to 70 or more) individual coating lines each with its own capture and control system. With approval, representative capture efficiency and control device efficiency testing of one magnet wire coating machine out of a group of identical or very similar magnet wire coating machines may be performed rather than testing every individual magnet wire coating machine. The operating parameters must be established for each tested magnet wire coating machine during each capture efficiency test and each control device efficiency test. The operating parameters established for each tested magnet wire coating machine also serve as the operating parameters for untested or very similar magnet wire coating machines represented by a tested magnet wire coating machine.

2.0 Capture Efficiency.

2.1 If the capture system is a permanent total enclosure as described in §63.3965(a), then its capture efficiency may be assumed to be 100 percent.

2.2 If the capture system is not a permanent total enclosure, then capture efficiency must be determined using the liquid-to-uncaptured-gas protocol using a temporary total enclosure or building enclosure in §63.3965(c), or an alternative capture efficiency protocol (see §63.3965(e)) which does not rely on direct measurement of the captured gas stream.

2.3 As an alternative to establishing and monitoring the capture efficiency operating parameters in §63.3967(f), the monitoring described in either section 2.4 or 2.5, and the monitoring described in sections 2.6 and 2.7 may be used for magnet wire coating machines.

2.4 Each magnet wire oven must be equipped with an interlock mechanism which will stop or prohibit the application of coating either when any exhaust fan for that oven is not operating or when the oven experiences an over limit temperature condition.

2.5 Each magnet wire oven must be equipped with an alarm which will be activated either when any oven exhaust fan is not operating or when the oven experiences an over limit temperature condition.

2.6 If the interlock in 2.4 or the alarm in 2.5 is monitoring for over limit temperature conditions, then the temperature(s) that will trigger the interlock or the alarm must be included in the start-up, shutdown and malfunction plan and the interlock or alarm must be set to be activated when the oven reaches that temperature.

2.7 Once every 6 months, each magnet wire oven must be checked using a smoke stick or equivalent approach to confirm that the oven is operating at negative pressure compared to the surrounding atmosphere.

3.0 Control Device Efficiency.

3.1 Determine the weight fraction carbon content of the volatile portion of each coating, thinner, additive, or cleaning material used during each test run using either the procedure in section 3.2 or 3.3.

3.2 Following the procedures in Method 204F, distill a sample of each coating, thinner, additive, or cleaning material used during each test run to separate the volatile portion. Determine the weight fraction carbon content of each distillate using ASTM Method D5291-02, "Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants" (incorporated by reference, see §63.14).

3.3 Analyze each coating, thinner, additive or cleaning material used during each test run using Method 311. For each volatile compound detected in the gas chromatographic analysis of each coating, thinner, additive, or cleaning material calculate the weight fraction of that whole compound in the coating, thinner, additive, or cleaning material. For each volatile compound detected in the gas chromatographic analysis of each coating, thinner, additive, or cleaning material calculate the weight fraction of the carbon in that compound in the coating, thinner, additive, or cleaning material. Calculate the weight fraction carbon

content of each coating, thinner, additive, or cleaning material as the ratio of the sum of the carbon weight fractions divided by the sum of the whole compound weight fractions.

3.4 Determine the mass fraction of total volatile hydrocarbon (TVH_i) in each coating, thinner, additive, or cleaning material, *i*, used during each test run using Method 24. The mass fraction of total volatile hydrocarbon equals the weight fraction volatile matter (W_v in Method 24) minus the weight fraction water (W_w in Method 24), if any, present in the coating. The ASTM Method D6053–00, “Standard Test Method for Determination of Volatile Organic Compound (VOC) Content of Electrical Insulating Varnishes” (incorporated by reference, see §63.14), may be used as an alternative to Method 24 for magnet wire enamels. The specimen size for testing magnet wire enamels with ASTM Method D6053–00 must be 2.0 ±0.1 grams.

3.5 Determine the volume (VOL_i) or mass (MASS_i) of each coating, thinner, additive, or cleaning material, *i*, used during each test run.

3.6 Calculate the total volatile hydrocarbon input (TVHC_{inlet}) to the control device during each test run, as carbon, using Equation 1:

$$TVHC_{inlet} = \sum_{i=1}^n (TVH_i \times VOL_i \times D_i \times CD_i) \quad (Eq. 1)$$

where:

TVH_i = Mass fraction of TVH in coating, thinner, additive, or cleaning material, *i*, used in the coating operation during the test run.

VOL_i = Volume of coating, thinner, additive, or cleaning material, *i*, used in the coating operation during the test run, liters.

D_i = Density of coating, thinner, additive, or cleaning material, *i*, used in the coating operation during the test run, kg per liter.

CD_i = Weight fraction carbon content of the distillate from coating, thinner, additive, or cleaning material, *i*, used in the coating operation during the test run, percent.

n = Number of coating, thinner, additive, and cleaning materials used in the coating operation during the test run.

3.7 If the mass, MASS_i, of each coating, solvent, additive, or cleaning material, *i*, used during the test run is measured directly then MASS_i can be substituted for VOL_i × D_i in Equation 1 in section 3.6.

3.8 Determine the TVHC output (TVHC_{outlet}) from the control device, as carbon, during each test run using the methods in §63.3966(a) and the procedure for determining M_{fo} in §63.3966(d). TVHC_{outlet} equals M_{fo} times the length of the test run in hours.

3.9 Determine the control device efficiency (DRE) for each test run using Equation 2:

$$DRE = \frac{(TVHC_{inlet} - TVHC_{outlet})}{TVHC_{inlet}} \times 100 \quad (Eq. 2)$$

3.10 The efficiency of the control device is the average of the three individual test run values determined in section 3.9.

3.11 As an alternative to establishing and monitoring the destruction efficiency operating parameters for catalytic oxidizers in §63.3967(b), the monitoring described in sections 3.12 and 3.13 may be used for magnet wire coating machines equipped with catalytic oxidizers.

3.12 During the performance test, you must monitor and record the temperature either just before or just after the catalyst bed at least once every 15 minutes during each of the three test runs. Use the data collected during the performance test to calculate and record the average temperature either just before or just after the catalyst bed during the performance test. This is the minimum operating limit for your

catalytic oxidizer and for the catalytic oxidizers in identical or very similar magnet wire coating machines represented by the tested magnet wire coating machine.

3.13 You must develop and implement an inspection and maintenance plan for your catalytic oxidizer(s). The plan must address, at a minimum, the elements specified in sections 3.14 and 3.15, and the elements specified in either (a) section 3.16 or (b) sections 3.17 and 3.18.

3.14 You must conduct a monthly external inspection of each catalytic oxidizer system, including the burner assembly and fuel supply lines for problems and, as necessary, adjust the equipment to assure proper air-to-fuel mixtures.

3.15 You must conduct an annual internal inspection of each accessible catalyst bed to check for channeling, abrasion, and settling. If problems are found, you must replace the catalyst bed or take corrective action consistent with the manufacturer's recommendations. This provision does not apply to internal catalysts which cannot be accessed without disassembling the magnet wire oven.

3.16 You must take a sample of each catalyst bed and perform an analysis of the catalyst activity (*i.e.*, conversion efficiency) following the manufacturer's or catalyst supplier's recommended procedures. This sampling and analysis must be done within the time period shown in Table 1 below of the most recent of the last catalyst activity test or the last catalyst replacement. For example, if the warranty for the catalyst is 3 years and the catalyst was more recently replaced then the sampling and analysis must be done within the earlier of 26,280 operating hours or 5 calendar years of the last catalyst replacement. If the warranty for the catalyst is 3 years and the catalyst was more recently tested then the sampling and analysis must be done within the earlier of 13,140 operating hours or 3 calendar years of the last catalyst activity test. If problems are found during the catalyst activity test, you must replace the catalyst bed or take corrective action consistent with the manufacturer's recommendations.

Table 1_Catalyst Monitoring Requirements

If the catalyst was last (more recently) replaced and the warranty period is . . .	Then the time between catalyst replacement and the next catalyst activity test cannot exceed the earlier of . . .	And the catalyst was more recently tested, then the time between catalyst activity tests cannot exceed the earlier of . . .
1 year.....	8,760 operating hours or 5 calendar years.	8,760 operating hours or 3 calendar years.
2 years.....	15,520 operating hours or 5 calendar years.	8,760 operating hours or 3 calendar years.
3 years.....	26,280 operating hours or 5 calendar years.	13,100 operating hours or 3 calendar years.
4 years.....	35,040 operating hours or 5 calendar years.	17,520 operating hours or 3 calendar years.
5 or more years.....	43,800 operating hours or 5 calendar years.	21,900 operating hours or 3 calendar years.

3.17 During the performance test, you must determine the average concentration of organic compounds as carbon in the magnet wire oven exhaust stack gases (C_c in Equation 1 in §63.3966(d)) and the destruction efficiency of the catalytic oxidizer, and calculate the operating limit for oven exhaust stack gas concentration as follows. You must identify the highest organic HAP content coating used on this magnet wire coating machine or any identical or very similar magnet wire coating machines to which the same destruction efficiency test results will be applied. Calculate the percent emission reduction necessary to meet the magnet wire coating emission limit when using this coating. Calculate the average concentration

of organic compounds as carbon in the magnet wire oven exhaust stack gases that would be equivalent to exactly meeting the magnet wire coating emissions limit when using the highest organic HAP content coating. The maximum operating limit for oven exhaust stack gas concentration equals 90 percent of this calculated concentration.

3.18 For each magnet wire coating machine equipped with a catalytic oxidizer you must perform an annual 10 minute test of the oven exhaust stack gases using EPA Method 25A. This test must be performed under steady state operating conditions similar to those at which the last destruction efficiency test for equipment of that type (either the specific magnet wire coating machine or an identical or very similar magnet wire coating machine) was conducted. If the average exhaust stack gas concentration during the annual test of a magnet wire coating machine equipped with a catalytic oxidizer is greater than the operating limit established in section 3.17 then that is a deviation from the operating limit for that catalytic oxidizer. If problems are found during the annual 10-minute test of the oven exhaust stack gases, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations.

3.19 If a catalyst bed is replaced and the replacement catalyst is not of like or better kind and quality as the old catalyst, then you must conduct a new performance test to determine destruction efficiency according to §63.3966 and establish new operating limits for that catalytic oxidizer unless destruction efficiency test results and operating limits for an identical or very similar unit (including consideration of the replacement catalyst) are available and approved for use for the catalytic oxidizer with the replacement catalyst.

3.20 If a catalyst bed is replaced and the replacement catalyst is of like or better kind and quality as the old catalyst, then a new performance test to determine destruction efficiency is not required and you may continue to use the previously established operating limits for that catalytic oxidizer.

E.3 One Time Deadlines Relating to NESHAP Subpart M

The Permittee shall comply with the following requirements by the dates listed:

Requirement	Rule Cite	Affected Facility	Deadline
Submit Initial Notification	40 CFR 63.3910(b)	Entire Source	January 2, 2005
Conduct Initial Compliance Demonstrations	40 CFR 63.3940, 63.3950, 63.3960	Entire Source	January 31, 2008
Submit Notification of Intent to Conduct a Performance Test	40 CFR 63.7(b) and 63.9(e)	Ovens that Undergo Performance Test	November 3, 2006
Conduct Performance Test	40 CFR 63.3960(b)(1)	Ovens that Undergo Performance Test	January 2, 2007
Develop and Implement Work Practice Plan	40 CFR 63.3960(b)(2)	Entire Source	January 2, 2007
Results of Initial Performance Tests	40 CFR 63.3920(b)	Ovens that Undergo Performance Test	March 3, 2007
Notification of Compliance Status	40 CFR 63.3910(c)	Entire Source	March 1, 2008
First Semiannual Compliance Report	40 CFR 63.3920(a)(1)	Entire Source	July 31, 2008

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION
PART 70 OPERATING PERMIT
CERTIFICATION**

Source Name: Rea Magnet Wire Company, Inc.
Source Address: 4300 New Haven Avenue, Fort Wayne, In 46803
Mailing Address: 4300 New Haven Avenue, Fort Wayne, In 46803
Part 70 Permit No.: T003-6925-00013

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify)
- 9 Report (specify)
- 9 Notification (specify)
- 9 Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
Phone: 317-233-0178
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT**

Source Name: Rea Magnet Wire Company, Inc.
Source Address: 4300 New Haven Avenue, Fort Wayne, In 46803
Mailing Address: 4300 New Haven Avenue, Fort Wayne, In 46803
Part 70 Permit No.: T003-6925-00013

This form consists of 2 pages

Page 1 of 2

<p>9 This is an emergency as defined in 326 IAC 2-7-1(12)</p> <p>X The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and</p> <p>X The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.</p>

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:
Form Completed By:
Title/Position:
Date:
Phone:

A certification is not required for this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

Part 70 Quarterly Report

Source Name: Rea Magnet Wire Company, Inc.
 Source Address: 4300 New Haven Avenue, Fort Wayne, Indiana 46803
 Mailing Address: 4300 New Haven Avenue, Fort Wayne, In 46803
 Part 70 Permit No.: T003-6925-00013
 Facility: Quartz Fabric oven 811 and the applicator cleaning area
 Parameter: VOC emissions
 Limit: Less than 40 tons per 12 consecutive months

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.
 Deviation has been reported on:

Submitted by:
Title/Position:
Signature:
Date:
Phone:

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Rea Magnet Wire Company, Inc.
Source Address: 4300 New Haven Avenue, Fort Wayne, In 46803
Mailing Address: 4300 New Haven Avenue, Fort Wayne, In 46803
Part 70 Permit No.: T003-6925-00013

Months: _____ to _____ Year: _____

Page 1 of 2

This report is an affirmation that the source has met all the requirements stated in this permit. This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked <input type="checkbox"/> No deviations occurred this reporting period.	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Page 2 of 2

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed By:
Title/Position:
Date:
Phone:

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Part 70 Significant Source Modification and a Part 70 Significant Permit Modification

Source Description and Location

Source Name: Rea Magnet Wire Company, Inc.
Source Location: 4300 New Haven Avenue, Fort Wayne, Indiana 46803
County: Allen
SIC Code: 3357
Operation Permit No.: T003-6925-00013
Operation Permit Issuance Date: October 10, 2002
Significant Source Modification No.: 003-22964-00013
Significant Permit Modification No.: 003-22935-00013
Permit Reviewer: ERG/ST

Existing Approvals

The source was issued Part 70 Operating Permit No. 003-6925-00013, on October 10, 2002. The source has since received the following approvals:

- (a) Administrative Amendment 003-22399-00013, issued on March 15, 2006.

County Attainment Status

The source is located in Allen County.

Pollutant	Status
PM10	Attainment
PM2.5	Attainment
SO ₂	Attainment
NO ₂	Attainment
1-hour Ozone	Attainment
8-hour Ozone	Nonattainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and nitrogen oxides (NO_x) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Allen County has been designated as nonattainment for the 8-hour ozone standard. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Emission Offset, 326 IAC 2-3.
- (b) Allen County has been classified as attainment for PM2.5. U.S. EPA has not yet established the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-

2 for PM_{2.5} emissions. Therefore, until the U.S.EPA adopts specific provisions for PSD review for PM_{2.5} emissions, it has directed states to regulate PM₁₀ emissions as a surrogate for PM_{2.5} emissions.

- (c) Allen County has been classified as attainment or unclassifiable for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (d) Fugitive Emissions
 Since this type of operation is not in one of the twenty-eight (28) listed source categories under 326 IAC 2-2 or 326 IAC 2-3, fugitive emissions are not counted toward the determination of PSD and Emission Offset applicability.

Source Status

The table below summarizes the potential to emit of the entire source, prior to the proposed modification, after consideration of all enforceable limits established in the effective permits:

Pollutant	Emissions (tons/year)
PM	Less than 100
PM ₁₀	Less than 100
SO ₂	Less than 100
VOC	Greater than 250
CO	Less than 100
NO _x	Less than 100

Note: These PTE figures are from TSD for T003-6925-00013, issued on October 10, 2002.

- (a) This existing source is a major stationary source, under PSD (326 IAC 2-2), because a regulated pollutant is emitted at a rate of 250 tons per year or more, and it is not in one of the twenty-eight (28) listed source categories, as specified in 326 IAC 2-2-1(gg)(1).
- (b) This existing source is a major stationary source under Emission Offset (326 IAC 2-3) because VOC, a nonattainment regulated pollutant, is emitted at a rate of 100 tons per year or more.

The table below summarizes the potential to emit HAPs for the entire source, prior to the proposed modification, after consideration of all enforceable limits established in the effective permits:

HAPs	Potential To Emit (tons/year)
Single HAP	Greater than 10
Combination HAPs	Greater than 25

Note: These PTE figures are from TSD for T003-6925-00013, issued on October 10, 2002.

This existing source is a major source of HAPs, as defined in 40 CFR 63.41, because HAP emissions are greater than ten (10) tons per year for a single HAP and greater than twenty-five (25) tons per year for a combination of HAPs. Therefore, this source is a major source under Section 112 of the Clean Air Act (CAA).

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the 2003 OAQ emission data.

Pollutant	Actual Emissions (tons/year)
PM10	2
PM2.5	2
SO ₂	0
VOC	124
CO	20
NO _x	24
HAP	Not reported

Description of Proposed Modification

The Office of Air Quality (OAQ) has reviewed a modification application, submitted by Rea Magnet Wire Company, Inc. on April 17, 2006, relating to the construction of two (2) new magnet wire coating ovens. The following is a list of the proposed emission units and pollution control devices:

- (gg) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.
- (hh) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.

"Integral Part of the Process" Determination

The Permittee has submitted the following information to justify why the internal catalytic oxidizer be considered an integral part of the wire coating process:

- (a) The VOCs will be oxidized using only the process heat supplied by the curing ovens.
- (b) The processes could not operate without the oxidizers, because the oxidizers supply the heat needed for curing the wire coating.
- (c) The oxidizers serve a primary purpose other than pollution control. The oxidizers supply the heat needed for curing the wire coating.

IDEM, OAQ has evaluated the justifications and agreed that the catalytic oxidation systems on ovens 615 and 635 will be considered as an integral part of the wire coating process. However, the control efficiency of the catalytic oxidizers is dependent on temperature and the quality of the catalyst. Therefore, the permitting level will be determined using the potential to emit before controls. Operating conditions in the proposed permit will specify that this catalytic oxidizer shall operate at all times when the wire coating process is in operation.

Enforcement Issues

There are no pending enforcement actions related to this modification.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
418	Oven 615 Process Exhaust	70	1.25	2,000	1,150
419	Oven 615 Wire Cooler	66	1.25	1,000	120
420	Oven 635 Process Exhaust	70	1.25	2,000	1,150
421	Oven 635 Wire Cooler	66	1.25	100	120
422	Annealer	40	0.5	200	Ambient

Emission Calculations

See Appendix A of this document for detailed emission calculations (pages 1 through 3).

Permit Level Determination – Part 70

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emission unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, IDEM, or the appropriate local air pollution control agency.”

The following table is used to determine the appropriate permit level under 326 IAC 2-7-10.5. This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	0.01
PM10	0.05
SO ₂	Negligible
VOC	238
CO	0.50
NO _x	0.60

HAPs	Potential To Emit (tons/year)
Single HAP (Highest)	3.70
TOTAL	6.98

The PTE of VOC in the table above is calculated before the effect of the internal catalytic oxidizers. Although the internal catalytic oxidizers are necessary for the proper operation of the ovens, the destruction efficiency of the oxidizers depend on the temperature and the quality of the catalyst.

This source modification is subject to 326 IAC 2-7-10.5(f)(4) because the uncontrolled potential to emit of VOC is greater than twenty-five (25) tons per year. Additionally, the modification will be incorporated into the Part 70 Operating Permit through a significant permit modification issued pursuant to 326 IAC 2-7-12(d), because the permit modification incorporates the requirements for the NESHAP (40 CFR 63, Subpart M) into the operating permit.

Permit Level Determination – PSD or Emission Offset

The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered federally enforceable only after issuance of this Part 70 source modification, and only to the extent that the effect of the control equipment is made practically enforceable in the permit.

Process/Emission Unit	Potential to Emit (tons/year)					
	PM	PM10	SO ₂	VOC	CO	NO _x
Oven 615	0.006	0.023	negligible	1.79	0.25	0.30
Oven 635	0.006	0.023	negligible	1.79	0.25	0.30
Total for Modification	0.012	0.046	negligible	3.60	0.50	0.60
Significant Level or Major Source Threshold	250	250	250	100	250	100

This modification to an existing major stationary source is not major because the increase in emissions due to this modification is less than the PSD and Emission Offset significant levels. Therefore, pursuant to 326 IAC 2-2 and 326 IAC 2-3, the PSD and Emission Offset requirements do not apply.

Federal Rule Applicability Determination

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) included in this proposed modification.
- (b) This source is subject to the National Emission Standards for Hazardous Air Pollutants for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR Part 63, Subpart Mmmm). The metal parts surface coating operations (identified below) and associated operations are subject to 40 CFR Part 63, Subpart Mmmm because they are located at a major source of HAPs and perform the surface coating of metal parts and products (defined by 40 CFR 63.3981(a)).

Pursuant to 40 CFR 63.3982(b), the affected source is the collection of all of the items listed in (1) through (4) below that are used for surface coating of metal parts and products within each subcategory.

- (1) All coating operations as defined in 40 CFR 63.3981;
- (2) All storage containers and mixing vessels in which coatings, thinners and/or other additives, and cleaning materials are stored or mixed;
- (3) All manual and automated equipment and containers used for conveying coatings, thinners and/or other additives, and cleaning materials; and
- (4) All storage containers and all manual and automated equipment and containers used for conveying waste materials generated by a coating operation.

The facilities subject to this rule include all of the magnet wire coating ovens, and associated solvent cleaning and coating mixing operations.

The existing affected source associated with the surface coating of metal parts and products is subject to the following sections of 40 CFR Part 63, Subpart Mmmm. Non applicable portions of the NESHAP are not included in the permit.

- 40 CFR 63.3880
- 40 CFR 63.3881(a)(4) and (b)
- 40 CFR 63.3882
- 40 CFR 63.3883(b) and (d)
- 40 CFR 63.3890(a), (b)(3), (c)(1), and (c)(2)(i – ii)
- 40 CFR 63.3891(c)
- 40 CFR 63.3892(b) and (c)
- 40 CFR 63.3893(b) and (c)

- 40 CFR 63.3900(a)(2), (b), and (c)
- 40 CFR 63.3901
- 40 CFR 63.3910
- 40 CFR 63.3920
- 40 CFR 63.3930
- 40 CFR 63.3931
- 40 CFR 63.3960
- 40 CFR 63.3961
- 40 CFR 63.3963
- 40 CFR 63.3964
- 40 CFR 63.3965
- 40 CFR 63.3966
- 40 CFR 63.3967(a), (b), and (f)
- 40 CFR 63.3968(a), (b), (c), (d), and (g)
- 40 CFR 63.3980
- 40 CFR 63.3981
- Tables 1, 2, 3, and 4 of 40 CFR 63, Subpart M

- (c) Pursuant to 40 CFR 64.2, Compliance Assurance Monitoring (CAM) is applicable to new or modified emission units that involve a pollutant-specific emission unit and meet the following criteria:
- (1) has a potential to emit before controls equal to or greater than the major source threshold for the pollutant involved;
 - (2) is subject to an emission limitation or standard for that pollutant; and
 - (3) uses a control device, as defined in 40 CFR 64.1, to comply with that emission limitation or standard.

The following table is used to identify the applicability of each of the criteria, under 40 CFR 64.1, to each new or modified emission unit involved:

Emission Unit	Control Device Used	Emission Limitation (Y/N)	Uncontrolled PTE of VOC (tons/year)	Controlled PTE of VOC (tons/year)	Major Source Threshold (tons/year)	CAM Applicable (Y/N)	Large Unit (Y/N)
Oven 615	Thermal and Catalytic oxidizers	Yes	119	1.8	100	Y	N
Oven 635	Thermal and Catalytic oxidizers	Yes	119	1.8	100	Y	N

Based on this evaluation, the requirements of 40 CFR Part 64, CAM are applicable to the new units as part of this modification. The pollutant-specific emission unit is not a "large unit" as described in 40 CFR 64.5. Therefore, the Permittee shall submit a CAM plan pursuant to 40 CFR 64 as part of the Part 70 renewal application.

State Rule Applicability Determination

The following state rules are applicable to the source due to the modification:

326 IAC 2-2 and 2-3 (PSD and Emission Offset)

PSD and Emission Offset applicability is discussed under the Permit Level Determination - PSD and Emission Offset section.

326 IAC 2-6 (Emission Reporting)

Since this source is required to have an operating permit under 326 IAC 2-7, Part 70 Permit Program, this source is subject to 326 IAC 2-6 (Emission Reporting). In accordance with the compliance schedule in 326 IAC 2-6-3, an emission statement must be submitted triennially. The

first report is due no later than July 1, 2007, and subsequent reports are due every three (3) years thereafter. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

The application of coatings to the magnet wire is done with die or felt application methods and the surface coating material is applied to the wire with 100% transfer efficiency. Pursuant to 326 IAC 6-3-2(b)(5), the requirements of 326 IAC 6-3 do not apply.

326 IAC 8-1-6 (Volatile Organic Compounds)

The two (2) wire enameling ovens (615 and 635) are not subject to the requirements of 326 IAC 8-1-6 because they are subject to another Article 8 rule.

326 IAC 8-2-8 (Magnet Wire Coating Operations)

Pursuant to 326 IAC 8-2-8, the Permittee shall not allow the discharge into the atmosphere of any volatile organic compounds (VOCs) in excess of 1.7 pounds per gallon of coating, excluding water, delivered to the applicator from magnet wire coating operations.

Pursuant to 326 IAC 8-1-2(b), the magnet wire emission unit's VOC emissions shall be limited to no greater than the equivalent emissions, expressed as pounds of VOC per pound of coating solids, as allowed in 326 IAC 8-2-8. This equivalency is determined using the following equation:

$$E = L / (1 - (L / D)) = 1.7 / (1 - (1.7 / 7.36)) = 2.21 \text{ lbs VOC / gal coating solids}$$

Where:

E = Equivalent emission limit in pounds of VOC per gallon of coating solids, as applied.
L = Applicable emission limit from 326 IAC 8-2-8 in pounds of VOC per gallon of coating.
D = Baseline solvent density of VOC in the coating and shall be equal to seven and thirty-six hundredths (7.36) pounds of VOC per gallon of solvent.

The pounds of VOC per gallon of coating solids shall be limited to less than 2.21.

Pursuant to 326 IAC 8-1-2(c), the overall efficiency of the internal integral catalytic oxidizer and external thermal oxidizer determined by the test methods and procedures specified in 326 IAC 8-1-4 shall be no less than the equivalent overall efficiency (O), which is calculated using the following equation:

$$O = ((V - E) / V) \times 100 = ((53.75 - 2.21) / 53.75) \times 100 = 95.9\%$$

Where:

V = The weighted average VOC content of all coatings, as applied to the subject coating line as determined by the applicable test methods and procedures specified in 326 IAC 8-1-4 in units of pounds of VOC per gallon of coating solids as applied.

[V = (8.22 lbs basecoat/gal basecoat x 0.837 lbs VOC/lb basecoat x 1 gal basecoat/0.128 gal solids) = 53.75 lbs VOC/gal coating solids]

E = Equivalent emission limit in pounds of VOC per gallon of coating solids as applied.
O = Equivalent overall efficiency of the capture system and control device as a percentage.

The overall efficiency of the internal integral catalytic oxidizer and external thermal oxidizer will be required to be greater than 95.9%.

The internal integral catalytic oxidizer and external thermal oxidizer associated with facilities 615 and 635 will be required to operate with an overall efficiency of at least 95.9% in order to comply with this limit.

326 IAC 8-6 (Organic Solvent Emission Limitations)

The two (2) wire enameling ovens (615 and 635) will be constructed after January 1, 1980. Therefore, the requirements of 326 IAC 8-6 do not apply to these facilities.

Compliance Determination and Monitoring Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with all applicable state and federal rules on a continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, Compliance Determination Requirements are included in the permit. The Compliance Determination Requirements in Section D of the permit are those conditions that are found directly within state and federal rules and the violation of which serves as grounds for enforcement action.

If the Compliance Determination Requirements are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The Compliance Determination Requirements applicable to this modification are as follows:

1. The wire enameling ovens (615 and 635) have applicable compliance determination conditions as specified below:
 - (a) To ensure compliance with 326 IAC 8-2-8, the internal catalytic oxidizers and the external thermal oxidizer shall operate at all times that the two (2) wire enameling ovens are in operation. When operating, the oxidizers shall maintain a 3 hour average minimum temperature of 1100 deg F or the 3 hour block average temperature determined in the latest compliance testing to maintain a volatile organic compound (VOC) overall control efficiency of not less than 95.9%.
 - (b) A continuous monitoring system shall be calibrated, maintained, and operated on the oxidizers for measuring operating temperature of the oxidizers. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the oxidizers are in operation.
 - (c) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the oxidizers. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.

- (d) The oxidizers shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken to return the oxidizers to at least the required minimum temperature setpoint within 15 minutes. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action, or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.

The actions described in section (d) above must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances.

- (e) In order to demonstrate compliance with 326 IAC 8-2-8, within one hundred and eighty (180) days after initial startup, the Permittee shall conduct performance tests to verify VOC control efficiency for the internal catalytic oxidizer and the external thermal oxidizer using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (f) One representative oven from the two (2) wire enamel ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.

Emission Unit	Control Device	Timeframe for Testing	Pollutant	Frequency of Testing	Limit or Requirement
Oven 615	Internal Catalytic and External Thermal Oxidizer	Within 180 days after initial startup	VOC	One oven every five years	326 IAC 8-2-8: 2.21 lbs VOC per gallon of coating solids
Oven 635	Internal Catalytic and External Thermal Oxidizer				

These compliance determination and monitoring conditions are necessary because the internal catalytic oxidizers and the external thermal oxidizers must operate properly in order to ensure compliance with 326 IAC 8-2-8.

Proposed Changes

The changes listed below have been made to Part 70 Operating Permit No. 003-6925-00013. Deleted language appears as ~~strike throughs~~ and new language appears in **bold**:

1. Section A.2 (items (ii) through (II)) and the facility description in Section D.1 through D.7 have been modified as follows to delete the equipment removed in 2004. In addition, Rea Magnet has requested that the catalytic ovens identified as MAG VEL 6, MAG VEL 8, and MAG HZ 4, included in Section D.7 of the permit, be deleted from the permit, as these ovens are no longer in operation and will be removed from the facility. Section D.7 has been deleted in its entirety, and the subsequent D sections have been renumbered.
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
 [326 IAC 2-7-5(15)]
-
- (a) Three (3) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 701-702, 703-704 and 705-706, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by **an** external thermal oxidizers (not integral) exhausted at Stack/Vent ID 0023.
 - (b) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number

707-708 and 709-710, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by **an** external thermal oxidizers (not integral) exhausted at Stack/Vent ID 0020.

- (c) ~~Four (4) Quartz~~ **Two (2) Quartz** Fabric wire enameling ovens, installed before 1977, emission unit numbers ~~804 and 805, 808, and 809,~~ with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by **an** external thermal oxidizers (not integral), **with ovens 804 and 805 and** exhausted at Stack/Vent 0033.
- Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 808 and 809, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0396.**
- (d) One (1) Quartz Fabric wire enameling oven, installed before 1977, emission unit number 810, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.
- (e) ~~One (1)~~ **Four (4)** Lepel Fabric wire enameling ovens, installed before 1980, emission unit numbers ~~807, 806, 803, and 802,~~ **each** with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ~~0027~~ **0397**.
- ~~(f) One (1) Lepel Fabric wire enameling oven, installed before 1980, emission unit number 806, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0028.~~
- ~~(g) One (1) Lepel Fabric wire enameling oven, installed before 1980, emission unit number 803, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0030.~~
- ~~(h) One (1) Lepel Fabric wire enameling oven, installed before 1980, emission unit number 802, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0031.~~
- (i f) One (1) Quartz Fabric wire enameling oven, installed 1992, emission unit number 811, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.
- (j g) One (1) SICME ES enameling oven, installed March 1991, emission unit number 695, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer (~~not integral~~) exhausted at Stack/Vent ID 0066.
- (k h) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 690, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer (~~not integral~~) exhausted at Stack/Vent ID 0068.
- (l i) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 605, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer (~~not integral~~) exhausted at Stack/Vent ID 0069.
- (m j) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 600, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer (~~not integral~~) exhausted at Stack/Vent ID 0071.

- (~~h~~ k) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 610, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0091.
- (~~e~~ l) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 640, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0113.
- (~~p~~ m) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 620, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0118.
- (~~q~~ n) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 670, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0122.
- (~~f~~ o) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 680, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0133.
- ~~(s) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 660, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0140.~~
- (~~t~~ p) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 351-352, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0172.
- (~~u~~ q) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 353-354, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0173.
- (~~v~~ r) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 355-356, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0174.
- (~~w~~ s) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 367-368, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0175.
- (~~x~~ t) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 365-366, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0176.
- (~~y~~ u) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 363-364, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID

0177.

- (z v) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 373-374, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0196.
- (aaw) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 371-372, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0197.
- (bbx) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 369-370, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0198.
- (cey) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 357-358, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0199.
- (dez) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 359-360, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0200.
- (eaa) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 361-362, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0201.
- ~~(ff) One (1) MAG VEL 6 wire enameling pilot oven with an integral internal catalytic oxidizer, installed November 11, 1993, and a maximum capacity of 133.33 pounds of magnet wire per hour. Emissions shall be exhausted at Stack/Vent 1041-1044.~~
- ~~(gg) One (1) MAG VEL 8 wire enameling pilot oven with an integral internal catalytic oxidizer, installed November 11, 1993, and a maximum capacity of 133.33 pounds of magnet wire per hour. Emissions shall be exhausted at Stack/Vent 1048-1051.~~
- ~~(hh) One (1) MAG HZ 4 wire enameling pilot oven with an integral internal catalytic oxidizer, installed November 11, 1993, and a maximum capacity of 133.33 pounds of magnet wire per hour. Emissions shall be exhausted at Stack/Vent 1053.~~
- ~~(ii) Equipment removed January 2004.~~
- ~~(jj) Equipment removed January 2004.~~
- ~~(kk) Equipment removed January 2004.~~
- (bb) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.**
- (cc) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.**

- ~~(#)(dd)~~ One (1) applicator cleaning area, installed in January 1991, consisting of tanks 1 through 7, exhausted through stacks 0299, 0300 and 0301, capacity: 150 gallons each for tanks 1 and 2, 650 gallons for tank 3, 500 gallons each for tanks 4 and 5, 400 gallons for tank 6 and 500 gallons for tank 7.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) Three (3) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 701-702, 703-704 and 705-706, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by **an** external thermal oxidizers (not integral) exhausted at Stack/Vent ID 0023.
- (b) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 707-708 and 709-710, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by **an** external thermal oxidizers (not integral) exhausted at Stack/Vent ID 0020.
- (c) ~~Four (4) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 804, 805, 808, and 809, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by external thermal oxidizers (not integral) exhausted at Stack/Vent ID 0033.~~

Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit numbers 804 and 805, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral), with ovens 804 and 805 exhausted at Stack/Vent 0033.

Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 808 and 809, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0396.

- (d) One (1) Quartz Fabric wire enameling oven, installed before 1977, emission unit number 810, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

SECTION D.2 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- ~~(e) One (1) Lepel Fabric wire enameling oven, installed before 1980, emission unit number 807, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0027.~~
- (e) **Four (4) Lepel Fabric wire enameling ovens, installed before 1980, emission unit numbers 807, 806, 803, and 802, each with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0397.**
- ~~(f) One (1) Lepel Fabric wire enameling oven, installed before 1980, emission unit number 806, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled~~

~~by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0028.~~

~~(g) One (1) Lepel Fabric wire enameling oven, installed before 1980, emission unit number 803, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0030.~~

~~(h) One (1) Lepel Fabric wire enameling oven, installed before 1980, emission unit number 802, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0031.~~

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

(i f) One (1) Quartz Fabric wire enameling oven, installed 1992, emission unit number 811, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

SECTION D.4 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

(j g) One (1) SICME ES enameling oven, installed March 1991, emission unit number 695, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer ~~(not integral)~~ exhausted at Stack/Vent ID 0066.

~~(k h)~~ One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 690, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer ~~(not integral)~~ exhausted at Stack/Vent ID 0068.

~~(l i)~~ One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 605, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer ~~(not integral)~~ exhausted at Stack/Vent ID 0069.

~~(m j)~~ One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 600, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an ~~internal~~ **integral** thermal oxidizer ~~(not integral)~~ exhausted at Stack/Vent ID 0071.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

SECTION D.5 FACILITY CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

~~(n k)~~ One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number

610, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0091.

- (e l) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 640, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0113.
- (p m) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 620, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0118.
- (q n) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 670, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0122.
- (f o) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 680, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0133.
- ~~(s) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 660, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0140.~~

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

SECTION D.6

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (t p) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 351-352, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0172.
- (u q) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 353-354, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0173.
- (v r) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 355-356, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0174.
- (w s) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 367-368, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0175.
- (x t) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 365-366, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0176.
- (y u) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 363-364, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0177.
- (z v) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 373-374, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0196.
- (aa w) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 371-372, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be

controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0197.

- (x bb) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 369-370, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0198.
- (ee y) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 357-358, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0199.
- (dd z) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 359-360, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0200.
- (ee aa) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 361-362, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0201.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

2. OAQ's Compliance Data section has indicated that stack testing should be conducted at maximum VOC emission loading in pounds of VOC per hour. The VOC content of the coating used is not the best indicator of the VOC loading of the ovens due to variations in the amount of coating used, the diameter of the wire, and the line speed of the system. Therefore, the testing requirements in the permit have been modified as shown below. In order to allow the source flexibility in terms of VOC content of coatings used, but at the same time assure that the VOC loading after the coating change does not exceed the VOC loading at the stack testing (which could lead to a reduction in destruction efficiency achieved compared to the stack test), the emission limitations and standards conditions and/or testing conditions have been modified as follows.

The enamel ovens that were constructed before 1980 and are subject to 326 IAC 8-6 with a minimum control efficiency requirement only, will be allowed to switch to a higher VOC content enamel as long as the VOC loading after the switch does not exceed the VOC loading at the time of stack testing. The enamel ovens that are subject to VOC limitations in pounds of VOC per gallon of coating, under 326 IAC 8-2-8, will be allowed to switch to a higher VOC content coating only if both the VOC loading remains below that at stack testing, and the new required minimum destruction efficiency remains below that determined at the stack test.

D.1.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.1.1, within fifty (50) months after issuance of **the Part 70 permit** ~~this permit~~, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.1.3 for the thermal oxidizers using methods approved by the Commissioner. **Stack testing shall be performed in accordance with 326 IAC 3-6.**
- (b) One representative thermal oxidizer from the ~~two~~ **five** oxidizers controlling the ten (10) Quartz Fabric enamel ovens shall be tested. The thermal oxidizer tested shall be the oxidizer in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating ~~with that would lead to a higher VOC content loading in pounds per hour~~ **than what was used during the stack test required in (a) above**, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.1.3 for **the** thermal oxidizers using methods approved by the Commissioner.
- (d) **For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:**

- (1) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
- (2) Calculate the current maximum VOC loading ($L_{current}$);
- (3) If L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

D.2.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.2.1, within fifty (50) months after issuance of the **Part 70 permit** ~~this permit~~, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.2.3 for ~~the~~ thermal oxidizer using methods approved by the Commissioner. **Stack testing shall be performed in accordance with 326 IAC 3-6.**
- (b) **The oxidizer that controls** the four (4) Lepel Quartz Fabric enamel ovens shall be tested. ~~The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test.~~ This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating **that would lead to a higher VOC loading in pounds per hour with a higher VOC content** than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.2.3 for ~~the~~ thermal oxidizers using methods approved by the Commissioner.
- (d) **For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:**
 - (1) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (2) Calculate the current maximum VOC loading ($L_{current}$);
 - (3) If L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

D.3.1 Volatile Organic Compounds [326 IAC 8-2-8]

- ...
- (d) Pursuant to 326 IAC 8-1-2(c), the equivalent overall control efficiency of the thermal oxidizer shall be no less than 91.1% **or the required destruction efficiency demonstrated by the most recent stack test, for the worst case VOC coating currently used; for a higher VOC content coating, the overall control efficiency of these units shall be no less than the estimated control efficiency required to achieve compliance with the VOC limit in Condition D.3.1(a).**

The overall control efficiency (O) of the thermal oxidizers shall be calculated by the following equation:

$$O = \frac{V - E}{V} \times 100$$

Where:

V = The actual VOC content of the coating or, if multiple coatings are used, the daily weighted average VOC content of all coatings, as applied to the subject coating line as determined by the applicable test methods and procedures specified in 326 IAC 8-1-4 in units of pounds of VOC per gallon of coating solids as applied.

- E = Equivalent emission limit in pounds of VOC per gallon of coating solids as applied.
- O = Equivalent overall control efficiency of the capture system and control device as a percentage.

D.3.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Conditions D.3.1 and D.3.2, within fifty (50) months after issuance of **the Part 70 permit** ~~this permit~~, the Permittee shall conduct performance tests to verify VOC control efficiency as per Conditions D.3.1 for **the** thermal oxidizers using methods approved by the Commissioner. **Stack testing shall be performed in accordance with 326 IAC 3-6.**
- (b) Before using a coating ~~with that would lead to a higher VOC content~~ **loading in pounds per hour** than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.3.1 for **the** thermal oxidizers using methods approved by the Commissioner.
- (c) **For a higher VOC content coating, the following procedure shall be followed:**
- (1) **Calculate the new minimum required control efficiency for the new coating (E_{new});**
 - (2) **Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;**
 - (3) **Calculate the current maximum VOC loading ($L_{current}$);**
 - (4) **If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.**

D.4.1 Volatile Organic Compounds [326 IAC 8-2-8]

- ...
- (d) Pursuant to 326 IAC 8-1-2(c), the equivalent overall control efficiency of the thermal oxidizers shall be no less than 96.7% **or the required control efficiency demonstrated by the most recent stack test, for the worst case VOC coating currently used; for a higher VOC content coating, the overall control efficiency of these units shall be no less than the estimated control efficiency required to achieve compliance with the VOC limit in Condition D.4.1(a).**

The overall control efficiency (O) of the thermal oxidizers shall be calculated by the following equation:

$$O = \frac{V - E}{V} \times 100$$

Where:

- V = The actual VOC content of the coating or, if multiple coatings are used, the daily weighted average VOC content of all coatings, as applied to the subject coating line as determined by the applicable test methods and procedures specified in 326 IAC 8-1-4 in units of pounds of VOC per gallon of coating solids as applied.
- E = Equivalent emission limit in pounds of VOC per gallon of coating solids as applied.
- O = Equivalent overall control efficiency of the capture system and control device as a percentage.

D.4.4 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.4.1, within fifty (50) months after issuance of **the Part 70 permit** ~~this permit~~, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.4.1 for **the** thermal oxidizers using

methods approved by the Commissioner. **Stack testing shall be performed in accordance with 326 IAC 3-6.**

- (b) One representative oven from the four (4) SICME ES enamel ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating **that would lead to a higher VOC loading in pounds per hour with a higher VOC content** than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.4.1 for **the** thermal oxidizers using methods approved by the Commissioner.
- (d) **For a higher VOC content coating, the following procedure shall be followed:**
 - (1) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (3) Calculate the current maximum VOC loading ($L_{current}$);
 - (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

D.5.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.5.1, **within fifty (50) months after issuance of the Part 70 permit** ~~within sixty (60) days after issuance of this permit~~, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.5.3 for **the** thermal oxidizer using methods approved by the Commissioner. **Stack testing shall be performed in accordance with 326 IAC 3-6.**
- (b) One representative oven from the ~~six (6)~~ **five (5)** Square/Rectangular enamel ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating **that would lead to a higher VOC loading in pounds per hour with a higher VOC content** than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.5.3 for **the** thermal oxidizers using methods approved by the Commissioner.
- (d) **For a higher VOC content coating, the following procedure shall be followed:**
 - (1) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (3) Calculate the current maximum VOC loading ($L_{current}$);
 - (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

D.6.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.6.1, **within fifty (50) months after issuance of the Part 70 permit** ~~within sixty (60) days after issuance of this permit~~, the Permittee shall conduct performance tests to verify VOC control efficiency as per Condition D.6.3 for **the** thermal oxidizers using methods approved by the Commissioner. **Stack testing shall be performed in accordance with 326 IAC 3-6.**

- (b) One representative oven from the twelve (12) MOCO enamel ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
 - (c) Before using a coating **that would lead to a higher VOC loading in pounds per hour with a higher VOC content** than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.6.3 for **the** thermal oxidizers using methods approved by the Commissioner.
 - (d) **For a higher VOC content coating, the following procedure shall be followed:**
 - (1) **Calculate the new minimum required control efficiency for the new coating (E_{new});**
 - (2) **Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;**
 - (3) **Calculate the current maximum VOC loading ($L_{current}$);**
 - (4) **If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.**
3. Upon further review, OAQ has determined that the fan amperage and duct pressure requirements for the thermal oxidizers are not necessary, therefore these conditions have been deleted as follows. The temperature requirement has been modified as shown below. Duplicate requirements titled "Thermal Oxidizer" and "Thermal Oxidizer Operation" have been combined into one condition in some D sections. Since the temperature is recorded in degrees Fahrenheit, the minimum temperature requirements have been converted accordingly.

D.1.4 Thermal Oxidizer Operation

- (a) Pursuant to the Construction Permit issued on October 17, 1997 (CP 003-8609-00013), the thermal oxidizers shall operate at all times that the ten (10) Quartz Fabric ovens are in operation. When operating, the thermal oxidizers shall maintain a minimum **3 hour average operating temperature of 621 degrees Celsius 1150 deg F or the 3 hour block average minimum temperature determined in the latest compliance testing to maintain** ~~or a temperature, fan amperage, or duct pressure, determined in the compliance testing to maintain~~ a destruction efficiency of not less than ninety percent (90%) of volatile organic compound (VOC) **in order to demonstrate compliance with Condition D.1.1.**
- (b) In order to satisfy the requirements of 326 IAC 8-6 and Condition D.1.1, the external thermal oxidizers must operate with a minimum destruction efficiency of ninety percent (90%) and a minimum capture efficiency such that the overall control efficiency is at least eighty-five percent (85%).

~~D.1.6 Thermal Oxidizer~~

- ~~(a) From the date of issuance of this permit until the approved stack test results are available, the Permittee shall operate the thermal oxidizers at or above the hourly average temperature of 621 degrees Celsius.~~
- ~~(b) The Permittee shall determine the temperature and fan amperage, or duct pressure, from the most recent valid stack test that demonstrates compliance with limits in Condition D.1.1, as approved by IDEM.~~
- ~~(c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizers at or above the hourly average temperature and fan amperage, or duct pressure as observed during the compliant stack test.~~

D.2.4 Thermal Oxidizer Operation

- (a) Pursuant to the Construction Permit issued on October 17, 1997 (CP 003-8609-00013), the external thermal oxidizers shall operate at all times that the four (4) Lepel Fabric ovens are in operation. When operating, the external thermal oxidizers shall maintain a minimum **3 hour average** operating temperature of ~~621 degrees Celsius~~ **1150 deg F or the 3 hour block average minimum temperature determined in the latest compliance testing** or a temperature and fan amperage, or duct pressure, determined in the compliance testing to maintain a destruction efficiency of not less than ninety percent (90%) of volatile organic compound (VOC) captured **in order to demonstrate compliance with Condition D.2.1.**
- (b) In order to ensure compliance with Condition D.2.1 and (a) above, the external thermal oxidizers must operate with a minimum destruction efficiency of ninety percent (90%) and a minimum capture efficiency such that the overall control efficiency is at least eighty-five percent (85%).

D.2.6 Thermal Oxidizer

- ~~(a) From the date of issuance of this permit until the approved stack test results are available, the Permittee shall operate the thermal oxidizers at or above the hourly average temperature of 621 degrees Celsius.~~
- ~~(b) The Permittee shall determine the temperature and fan amperage, or duct pressure, from the most recent valid stack test that demonstrates compliance with limits in Condition D.2.3, as approved by IDEM.~~
- ~~(c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizers at or above the hourly average temperature and fan amperage, or duct pressure, as observed during the compliant stack test.~~

D.3.7 Thermal Oxidizer Operation

- (a) From the date of issuance of **the Part 70 permit** ~~this permit~~ until the approved stack test results are available, the Permittee shall operate the thermal oxidizer **3 hour average temperature** at or above the ~~hourly average~~ temperature of ~~621 degrees Celsius~~ **1150 deg F.**
- (b) The Permittee shall determine the **3 hour block average minimum** temperature ~~and fan amperage, or duct pressure,~~ from the most recent valid stack test that demonstrates compliance with limits in Conditions D.3.1 and D.3.2, as approved by IDEM.
- (c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizer at or above the ~~hourly~~ **3 hour block average minimum** temperature ~~and fan amperage, or the duct pressure,~~ as observed during the compliant stack test.

D.4.5 Thermal Oxidizer Operation

- (a) From the date of issuance of **this the Part 70 permit** until the approved stack test results are available, the Permittee shall operate the thermal oxidizers **3 hour average temperature** at or above the ~~hourly average~~ temperature of ~~760 degrees Celsius~~ **1400 deg F.**
- (b) The Permittee shall determine the **3 hour block average minimum** temperature ~~and fan amperage, or duct pressure,~~ from the most recent valid stack test that demonstrates compliance with limits in Condition D.4.1, as approved by IDEM.
- (c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizer at or above the ~~hourly~~ **3 hour block average minimum** temperature ~~and fan amperage, or duct pressure,~~ as observed during the compliant stack test.

D.5.4 Thermal Oxidizer Operation

To ensure compliance with Condition D.5.1, the external thermal oxidizers shall operate at all times that the ~~six (6)~~ **five (5)** square/rectangular ovens are in operation. When operating, the external thermal oxidizers shall maintain a minimum **3 hour average operating** temperature of ~~593 degrees Celsius~~ **1100 deg F or the 3 hour block average minimum temperature determined in the latest compliance testing to maintain** ~~or a temperature and fan amperage, or duct pressure, determined in the compliance testing to maintain~~ a volatile organic compound (VOC) overall control efficiency of not less than eighty-five percent (85%) **to demonstrate compliance with Condition D.5.1.**

~~D.5.6 Thermal Oxidizer~~

- ~~(a) From the date of issuance of this permit until the approved stack test results are available, the Permittee shall operate the thermal oxidizer at or above the hourly average temperature of 593 degrees Celsius.~~
- ~~(b) The Permittee shall determine the temperature and fan amperage, or duct pressure, from the most recent valid stack test that demonstrates compliance with limits in Condition D.5.1 as approved by IDEM.~~
- ~~(c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizer at or above the hourly average temperature and fan amperage, or duct pressure, as observed during the compliant stack test.~~

D.6.6 Thermal Oxidizer **Operation**

- (a) From the date of issuance of ~~this~~ **the Part 70** permit until the approved stack test results are available, the Permittee shall operate the thermal oxidizers **3 hour average temperature** at or above the ~~hourly average~~ temperature of ~~593 degrees Celsius~~ **1100 deg F.**
 - (b) The Permittee shall determine the **3 hour block average minimum** temperature ~~and fan amperage, or duct pressure~~, from the most recent valid stack test that demonstrates compliance with limits in Condition D.6.1, as approved by IDEM.
 - (c) From the date of the approved stack test results are available, the Permittee shall operate the thermal oxidizers at or above the **3 hour block** ~~hourly average~~ **minimum** temperature ~~and fan amperage, or duct pressure~~, as observed during the compliant stack test.
4. Upon further review, OAQ has determined that the fan amperage and duct pressure requirements for the thermal oxidizers are not necessary, therefore the parametric monitoring condition requiring duct pressure and fan amperage has been deleted as follows. A condition has been added for monitoring the 3-hour average temperature (pursuant to the temperature monitoring requirement in the NESHAP for Miscellaneous Metal Parts Coating, 40 CFR 63, Subpart Mmmm), and the necessary response steps following a departure from the minimum required oven temperature.

~~D.1.7 Parametric Monitoring~~

- ~~(a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizers for measuring operating temperature. The output of this system shall be recorded, and that temperature shall be at or above the hourly average temperature used to demonstrate compliance during the most recent compliance stack test. If the continuous monitoring system is not in operation, the temperature will be recorded manually once every 15-minute period.~~
- ~~(b) The duct pressure or fan amperage shall be observed at least once per day when the thermal oxidizers are in operation. When for any one reading, the duct pressure or fan amperage is outside the normal range as indicated by the manufacturer or as established in most recent compliant stack test, the Permittee shall take reasonable response steps in accordance with Section C Compliance Response Plan Preparation, Implementation, Records, and Reports. A reading that is outside the above mentioned range is not a~~

~~deviation from this permit. Failure to take response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.~~

D.1.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperature shall be recorded whenever the thermal oxidizer is in operation.**
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.**
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.**
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.**

D.2.7 ~~Parametric Monitoring~~

- ~~(a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizers for measuring operating temperature. The output of this system shall be recorded, and that temperature shall be at or above the hourly average temperature used to demonstrate compliance during the most recent compliance stack test. If the continuous monitoring system is not in operation, the temperature will be recorded manually once every 15-minute period.~~
- ~~(b) The duct pressure or fan amperage shall be observed at least once per day when the thermal oxidizers are in operation. When for any one reading, the duct pressure or fan amperage is outside the normal range as indicated by the manufacturer or as established in most recent compliant stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.~~

D.2.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.**

- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.**
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.**
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.**

~~D.3.8 Parametric Monitoring~~

- ~~(a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature. The output of this system shall be recorded, and that temperature shall be at or above the hourly average temperature used to demonstrate compliance during the most recent compliance stack test. If the continuous monitoring system is not in operation, the temperature will be recorded manually once every 15-minute period.~~
- ~~(b) The duct pressure or fan amperage shall be observed at least once per day when the thermal oxidizer is in operation. When for any one reading, the duct pressure or fan amperage is outside the normal range as indicated by the manufacturer or as established in most recent compliant stack test, the Permittee shall take reasonable response steps in accordance with Section C Compliance Response Plan Preparation, Implementation, Records, and Reports. A reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C Compliance Response Plan Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.~~

D.3.8 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.**
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.**
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or**

above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.

- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.**

D.4.6 Parametric Monitoring

- ~~(a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature. The output of this system shall be recorded, and that temperature shall be at or above the hourly average temperature used to demonstrate compliance during the most recent compliance stack test. If the continuous monitoring system is not in operation, the temperature will be recorded manually once every 15-minute period.~~
- ~~(b) The duct pressure or fan amperage shall be observed at least once per day when the thermal oxidizer is in operation. When for any one reading, the duct pressure or fan amperage is outside the normal range as indicated by the manufacturer or as established in most recent compliant stack test, the Permittee shall take reasonable response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports. A reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.~~

D.4.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the integral thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.**
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.**
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.**
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.**

D.5.7 Parametric Monitoring

- ~~(a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizers for measuring operating temperature. The output of this system shall be~~

~~recorded, and that temperature shall be at or above the hourly average temperature used to demonstrate compliance during the most recent compliance stack test. If the continuous monitoring system is not in operation, the temperature will be recorded manually once every 15-minute period.~~

- ~~(b) The duct pressure or fan amperage shall be observed at least once per day when the thermal oxidizers are in operation. When for any one reading, the duct pressure or fan amperage is outside the normal range as indicated by the manufacturer or as established in most recent compliant stack test, the Permittee shall take reasonable response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports. A reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.~~

D.5.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.**
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.**
- (c) The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.**
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.**

D.6.7 Parametric Monitoring

- ~~(a) A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizers for measuring operating temperature. The output of this system shall be recorded, and that temperature shall be at or above the hourly average temperature used to demonstrate compliance during the most recent compliance stack test. If the continuous monitoring system is not in operation, the temperature will be recorded manually once every 15-minute period.~~
- ~~(b) The duct pressure or fan amperage shall be observed at least once per day when the thermal oxidizers are in operation. When for any one reading, the duct pressure or fan amperage is outside the normal range as indicated by the manufacturer or as established in most recent compliant stack test, the Permittee shall take reasonable response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports. A reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C -~~

~~Compliance Response Plan – Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.~~

D.6.7 Parametric Monitoring

- (a) **A continuous monitoring system shall be calibrated, maintained, and operated on the thermal oxidizer for measuring operating temperature of the thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the thermal oxidizer is in operation.**
 - (b) **If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the integral thermal oxidizer. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.**
 - (c) **The oxidizer shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.**
 - (d) **Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.**
5. Upon further review, OAQ has realized that Section D – Recordkeeping Requirements only takes into account the destruction efficiency and does not account for capture efficiency. In addition, the condition should include records of 3 hour averages rather than one hour averages, and the duct pressure or fan amperage daily recording is not necessary. Therefore, the Section D – Record Keeping Requirements have been modified as follows. In addition, the record keeping requirement for clean up solvents have been deleted in all D sections except for that in sections D.3 and the new section D.7 in this permit modification, since these D sections include emissions limits for clean up solvents only. Section D.7 includes the applicator cleanup area only, therefore record keeping requirement for coating solvents have been deleted from this section.

D.1.87 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.7, the Permittee shall maintain:
 - (1) Records of the VOC emitted based on: $\text{VOC delivered to the applicators} \times (1 - \% \text{ overall control efficiency destruction efficiency}/100) + \text{VOC in cleaning solvent}$.
 - (2) Continuous temperature records **and 3 hour average temperature records** ~~(on an hourly average basis) for the thermal oxidizer and the hourly average temperature used to demonstrate compliance during the most recent compliant stack test.~~
 - (3) ~~Daily records of the duct pressure or fan amperage.~~
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

D.2.87 Record Keeping Requirements

- (a) To document compliance with Condition D.2.1 and D.2.7, the Permittee shall maintain:
- (1) Records of the VOC emitted based on: $\text{VOC delivered to the applicators} \times (1 - \% \text{ overall control efficiency destruction efficiency}/100) + \text{VOC in cleaning solvent}$.
 - (2) Continuous temperature records and **3 hour average temperature records** ~~(on an hourly average basis) for the thermal oxidizer and the hourly average temperature used to demonstrate compliance during the most recent compliant stack test.~~
 - ~~(3) Daily records of the duct pressure or fan amperage.~~
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

D.3.9 Record Keeping Requirements

- (a) To document compliance with Conditions D.3.1 and D.3.2, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC content limits and/or the VOC emission limits established in Conditions D.3.1 and D.3.2.
- (1) The VOC content of each coating material and solvent used less water.
 - (2) ~~The amount of coating material and solvent used on a monthly basis.~~
 - ~~(A) Records shall include **material balance calculations**, purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.~~
 - ~~(B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents.~~
 - (3) The monthly cleanup solvent usage.
 - (4) The total VOC usage for each month.
 - (5) The VOC emitted based on: $\text{VOC delivered to the applicators} \times (1 - \% \text{ overall control efficiency destruction efficiency}/100) + \text{VOC in cleaning solvent}$.
- (b) To document compliance with Condition D.3.8, the Permittee shall maintain:
- ~~(1) the C~~continuous temperature records and **3 hour average temperature records** ~~(on an hourly average basis) for the thermal oxidizer and the hourly average temperature used to demonstrate compliance during the most recent compliant stack test.~~
 - ~~(2) Daily records of the duct pressure or fan amperage.~~
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.4.7 Record Keeping Requirements

- (a) To document compliance with Condition D.4.1, the Permittee shall maintain records in accordance with (1) through ~~(4)~~**(2)** below. Records maintained for (1) through ~~(4)~~**(2)** shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC content limits and/or the VOC emission limits established in Conditions D.4.1

- (1) The VOC content of each coating material and solvent used less water.
 - (2) ~~The amount of coating material and solvent used on a monthly basis.~~
 - (A) ~~Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.~~
 - (B) ~~Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents.~~
 - (3) ~~The monthly cleanup solvent usage.~~
 - (4) ~~The total VOC usage for each month.~~
 - (5) ~~The VOC emitted (in tons per year) based on: VOC delivered x (1 - % destruction efficiency/100) + VOC in cleaning solvent.~~
- (b) To document compliance with Condition D.4.6, the Permittee shall maintain: (1) ~~the C~~ **continuous temperature records and 3 hour average temperature records.** ~~(on an hourly average basis) for the thermal oxidizer and the hourly average temperature used to demonstrate compliance during the most recent compliant stack test.~~
- (2) ~~Daily records of the duct pressure or fan amperage.~~
- (c) All records shall be maintained in accordance with Section C- General Record Keeping Requirements, of this permit.

D.5.87 Record Keeping Requirements

- (a) To document compliance with Conditions D.5.1 and D.5.7, the Permittee shall maintain:
- (1) Records of the VOC emitted based on: VOC delivered to the applicators x (1 - % **overall control efficiency** ~~destruction efficiency/100~~) + VOC in cleaning solvent.
 - (2) Continuous temperature records **and 3 hour average temperature records** ~~(on an hourly average basis) for the thermal oxidizer and the hourly average temperature used to demonstrate compliance during the most recent compliant stack test.~~
 - (3) ~~Daily records of the duct pressure or fan amperage.~~
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

D.6.8 Record Keeping Requirements

- (a) To document compliance with Conditions D.6.1 and D.6.7, the Permittee shall maintain:
- (1) Records of the VOC emitted based on: VOC delivered to the applicators x (1 - % **overall control efficiency** ~~destruction efficiency/100~~) + VOC in cleaning solvent.
 - (2) Continuous temperature records **and 3 hour average temperature records** ~~(on an hourly average basis) for the thermal oxidizer and the hourly average temperature used to demonstrate compliance during the most recent compliant stack test.~~
 - (3) ~~Daily records of the duct pressure or fan amperage.~~

- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements of this permit.

D.7.4 Record Keeping Requirements

- (a) To document compliance with Condition D.7.1, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC emission limits established in Conditions D.7.1.
- (1) The VOC content of each ~~coating material and~~ **cleanup** solvent used less water.
- (2) The amount of ~~coating material and~~ **cleanup** solvent used on a monthly basis.
- ~~(a) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.~~
- ~~(b) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents.~~
- (3) ~~The monthly cleanup solvent usage;~~ and **Records of waste solvents shipped offsite for treatment;**
- (4) The total **net** VOC usage for each month;
- (5) The weight of VOCs emitted for each compliance period.
- (b) All records shall be maintained in accordance with Section C- General Record Keeping Requirements, of this permit.

6. The following changes have been made in order to clarify the PSD applicability condition in sections D.3 and D.8. Rule 326 IAC 2-2 has been SIP approved, so references to 40 CFR 52.21 have been deleted.

D.3.2 PSD Limit [326 IAC 2-2] [40 CFR 52.21]

Pursuant to CP 003-8609-00013 issued on October 17, 1997, the VOC emissions from the Quartz Fabric oven (emission unit 811)(Section D.3), and the applicator cleaning area (Section ~~D.7 D.8~~) shall be limited to less than 40 tons VOC per twelve (12) consecutive month period. ~~An increase in total VOC emissions from these equipment above 40 tons per year shall require a PSD permit pursuant to 326 IAC 2-2 and 40 CFR 52.21 before such change may occur.~~ **Compliance with this limit shall render 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.**

D.7-8.1 PSD Limit [326 IAC 2-2] [40 CFR 52.21]

Pursuant to CP 003-8609-00013 issued on October 17, 1997, the VOC emissions from the Quartz Fabric oven (emission unit 811)(Section D.3), and the applicator cleaning area (Section ~~D.7 8~~) shall be limited to less than 40 tons per twelve (12) consecutive months of VOC. ~~An increase in total VOC emissions from these equipment above 40 tons per year shall require a PSD permit pursuant to 326 IAC 2-2 and 40 CFR 52.21 before such change may occur.~~ **Compliance with this limit shall render 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.**

7. Condition D.3.6 has been modified as follows to clarify the methodology:

D.3.6 VOC Emissions

Compliance with Condition D.3.2 shall be demonstrated within 30 days of the end of each month. This shall be based on the total volatile organic compound emitted for the previous month, and adding it to previous 11 months total VOC emitted so as to arrive at VOC emission for 12 consecutive months period. The VOC emissions for a month can be arrived at using the following equation for VOC usage:

$$\text{VOC emitted} = [(\text{VOC input}) \times ((100 - \% \text{control efficiency})/100)] + [\text{uncontrolled VOC input}]$$

8. The following changes have been made to Conditions D.1.5 and D.3.5 in order to clarify the testing requirements for the thermal oxidizers controlling the wire enameling ovens in Sections D.1 and D.3. Oven 810 (Section D.1) and Oven 811 (Section D.3) are both controlled by the same thermal oxidizer and exhaust to the same stack (stack 0024).

D.1.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Conditions **D.1.1, D.3.1 and D.3.2**, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Conditions **D.1.3 and D.3.4** for the thermal oxidizers using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative thermal oxidizer from the ~~two~~ **five** oxidizers controlling the ~~ten~~ **eleven** (~~40~~ **11**) Quartz Fabric enamel ovens **listed in Sections D.1 and D.3** shall be tested. The thermal oxidizer tested shall be the oxidizer in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.1.3 for thermal oxidizers using methods approved by the Commissioner.
- (d) For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:
- (1) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (2) Calculate the current maximum VOC loading ($L_{current}$);
 - (3) If L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

D.3.5 Testing Requirements [326 IAC 2-7-6(1),(6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Conditions **D.1.1, D.3.1, and D.3.2**, within fifty (50) months after issuance of the Part 70 permit, the Permittee shall conduct performance tests to verify VOC control efficiency as per Conditions **D.1.3 and D.3.4** for thermal oxidizers using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) **One representative thermal oxidizer from the five oxidizers controlling the eleven (11) Quartz Fabric enamel ovens listed in Sections D.1 and D.3 shall be tested. The thermal oxidizer tested shall be the oxidizer in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.**
- (~~b~~c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency as per Condition D.3.1 for thermal oxidizers using methods approved by the Commissioner.
- (~~e~~d) For a higher VOC content coating than that used during the stack test in (a) above, the following procedure shall be followed:
- (5) Calculate the new minimum required control efficiency for the new coating (E_{new});
 - (6) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
 - (7) Calculate the current maximum VOC loading ($L_{current}$);

- (8) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than $L_{current}$, Permittee shall be allowed to use the higher VOC content enamel.

Upon further review, IDEM, OAQ has decided to make the following changes:

1. The Section B conditions, B.2 (Permit Term), B.13 (Prior Permits Superseded), and B.17 (Permit Renewal) have been modified to clarify these conditions. In addition, B.3 (Term of Conditions) has been added as follows:

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]

- (a) This permit, **T003-6925-00013**, is issued for a fixed term of five (5) years from the original date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments **of this permit do not affect the expiration date of this permit or of permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control)**.
- (b) **If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.**

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) **the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act, or**
- (b) **the emission unit to which the condition pertains permanently ceases operation.**

B.414 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]

- (a) All terms and conditions of previous permits established prior to T003-6925-00013 and issued pursuant to permitting programs approved into the state implementation plan have been either
- (1) incorporated as originally stated,
 - (2) revised **under 326 IAC 2-7-10.5**, or
 - (3) deleted **under 326 IAC 2-7-10.5**.
- ~~by this permit.~~
- (b) **All Provided that all terms and conditions are accurately reflected in this combined permit, all previous registrations and permits are superseded by this Part 70 operating permit, except for permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control).**

B.417 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

(b) ~~Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]~~

~~(1) — A timely renewal application is one that is:~~

~~(A)-(1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and~~

~~(B)-(2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.~~

~~(2) — If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.~~

(c) ~~Right to Operate After Application for Renewal [326 IAC 2-7-3]~~

~~If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.~~

(d) ~~United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]~~

~~If IDEM, OAQ, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.~~

2. IDEM has determined that the Permittee is not required to keep records of all preventive maintenance. However, where the Permittee seeks to demonstrate that an emergency has occurred, the Permittee must provide, upon request, records of preventive maintenance in order to establish that the lack of proper maintenance did not cause or contribute to the deviation. Therefore, IDEM has deleted paragraph (b) of Section B – Preventive Maintenance, and has amended the Section B – Emergency Provisions condition as follows:

B.4011 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and

- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6045
Indianapolis, Indiana ~~46206-6045~~ **46204-2251**

The PMP and the PMP extension notification do not require the certification by the Responsible official as defined by 326 IAC 2-7-1(34).

- ~~(b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.~~
- ~~(e)~~ (b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the Responsible official as defined by 326 IAC 2-7-1(34).
- ~~(d)~~ (c) ~~Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.~~ **To the extent the Permittee is required by 40 CFR 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for the unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.**

B.4412 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;
Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or
Telephone Number: 317-233-~~5674~~**40178** (ask for Compliance Section)

Facsimile Number: 317-233-5967**6865**

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the Responsible official[®] as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) **The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations or emissions. However, IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(10) be revised in response to an emergency.**

...

3. IDEM has clarified the Section B – Operational Flexibility condition as follows:

B.49 20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:
 - (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
 - (3) The changes do not result in emissions which exceed the **limitations provided in emissions allowable under** this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, **on a rolling five (5) year basis**, which document, ~~on a rolling five (5) year basis~~, all such changes and emissions ~~trades trading~~ that are subject to 326 IAC 2-7-20(b), (c), or (e). **The Permittee shall make and makes** such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
- (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the ~~A~~responsible official[®] as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade **emissions** increases and decreases ~~in emissions in~~ at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

4. Indiana has incorporated the credible evidence provision in 326 IAC 1-1-6. This rule has been effective since March 16, 2005; therefore, the condition reflecting this rule will be incorporated into the permit as follows:

B.25 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

5. Condition C.6 (Operation of Equipment) is the same condition requiring operation of control equipment at all times that the emissions unit is in operation, included in all the D sections. To avoid duplication, C.6 has been deleted, and the remaining Section C conditions are renumbered.

~~C.6 Operation of Equipment [326 IAC 2-7-6(6)]~~

~~Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission unit vented to the control equipment is in operation.~~

6. IDEM realizes that the instrument specifications can only be practically applied to analog units, and has therefore clarified the condition to state that the condition only applies to analog units. Upon further review, IDEM has also determined that the accuracy of the instruments is not nearly as important as whether the instrument has a range that is appropriate for the normal expected reading of the parameter. Therefore, the accuracy requirements have been removed from the condition.

~~C.4312 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]~~

~~(a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed~~ **When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum normal reading for the normal range shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ($\pm 2\%$) of full scale reading.**

~~(b) Whenever a condition in this permit requires the measurement of a temperature, the instrument employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ($\pm 2\%$) of full scale reading.~~

~~(c)~~ **(b)** The Permittee may request **that** the IDEM, OAQ approve the use of a pressure gauge or other **an** instrument that does not meet the above specifications provided the Permittee can demonstrate **that** an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of ~~pressure drop or other~~ **the** parameters.

7. IDEM has reconsidered the requirement to develop and follow a Compliance Response Plan. The Permittee will still be required to take reasonable response steps when a compliance monitoring parameter is determined to be out of range or abnormal. Replacing the requirement to develop and follow a Compliance Response Plan with a requirement to take reasonable response steps will ensure that the control equipment is returned to proper operation as soon as practicable, while still allowing the Permittee the flexibility to respond to situations that were not anticipated. The following changes have been made to the Section C condition:

~~C.4615 Compliance Response Plan Preparation, Implementation, Records, and Reports Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]~~

~~(a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP-s shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this~~

~~permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and is comprised of:~~

- ~~(1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.~~
- ~~(2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.~~
- ~~(b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
 - ~~(1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or~~

~~_____ If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.~~
 - ~~(3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.~~
 - ~~(4) Failure to take reasonable response steps shall constitute a violation of the permit.~~~~
- ~~(c) The Permittee is not required to take any further response steps for any of the following reasons:
 - ~~(1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.~~
 - ~~(2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.~~
 - ~~(3) An automatic measurement was taken when the process was not operating.~~
 - ~~(4) The process has already returned or is returning to operating within a normal parameters and no response steps are required.~~~~
- ~~(d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.~~
- ~~(e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.~~

- ~~(f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.~~
- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.**
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:**
- (1) initial inspection and evaluation;**
 - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or**
 - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.**
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:**
- (1) monitoring results;**
 - (2) review of operation and maintenance procedures and records;**
 - (3) inspection of the control device, associated capture system, and the process.**
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.**
- (e) The Permittee shall maintain the following records:**
- (1) monitoring data;**
 - (2) monitor performance data, if applicable; and**
 - (3) corrective actions taken.**

8. This source is a major source under 326 IAC 2-2 (PSD) and 326 IAC 2-3 (Emission Offset rules). Therefore, the following changes have been made to the Section C – Recordkeeping and Reporting requirements in order to reflect NSR reform provisions at a major NSR source.

C.4918 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]

-
- ~~(a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the~~

~~Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.~~

- ~~(b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.~~
- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.**
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.**
- (c) If there is a reasonable possibility that a “project” (as defined in 326 IAC 2-2-1 (qq) and 326 IAC 2-3-1(II)) at an existing emissions unit, other than projects at a Clean Unit, which is not part of a “major modification” (as defined in 326 IAC 2-2-1 (ee) and 326 IAC 2-3-1 (z)) may result in significant emissions increase and the Permittee elects to utilize the “projected actual emissions” (as defined in 326 IAC 2-2-1 (rr) and 326 IAC 2-3-1 (mm)), the Permittee shall comply with following:**
- (1) Before beginning actual construction of the “project” (as defined in 326 IAC 2-2-1 (qq) and 326 IAC 2-3-1 (II)) at an existing emissions unit, document and maintain the following records:**
- (A) A description of the project.**
- (B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.**
- (C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:**
- (i) Baseline actual emissions;**
- (ii) Projected actual emissions;**
- (iii) Amount of emissions excluded under section 326 IAC 2-2-1(rr)(2)(A)(iii) and 326 IAC 2-3-1(mm)(2)(A)(3); and**
- (iv) An explanation for why the amount was excluded, and any netting calculations, if applicable.**
- (2) Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and**
- (3) Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR**

pollutant at the emissions unit.

C.2019 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

~~(a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the responsible official as defined by 326 IAC 2-7-1(34).~~

~~(b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:~~

~~Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251~~

~~(c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.~~

~~(d) Unless otherwise specified in this permit, any quarterly report required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The report does require the certification by the responsible official as defined by 326 IAC 2-7-1(34).~~

~~(e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.~~

(a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

**Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251**

(c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period.

All reports do require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

- (e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit “calendar year” means the twelve (12) month period from January 1 to December 31 inclusive.**
- (f) If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any “project” (as defined in 326 IAC 2-2-1 (qq) and 326 IAC 2-3-1(II)) at an existing emissions unit, and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:
 - (1) The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as defined in 326 IAC 2-2-1 (xx) and 326 IAC 2-3-1 (qq), for that regulated NSR pollutant, and**
 - (2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).****
- (g) The report for project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:
 - (1) The name, address, and telephone number of the major stationary source.**
 - (2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.**
 - (3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-2-2(d)(3) and 326 IAC 2-3-2(c)(3).**
 - (4) Any other information that the Permittee deems fit to include in this report.****

Reports required in this part shall be submitted to:

**Indiana Department of Environmental Management
Air Compliance Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251**

- (h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.**

9. The mailing address for IDEM, OAQ has been changed throughout the permit.

Indiana Department of Environmental Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana ~~46206-6015~~ **46204-2251**

10. Section D.10 has been added to the permit to include the conditions for the new magnet wire coating ovens.

SECTION D.10 FACILITY CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (bb) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.
- (cc) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.10.1 Volatile Organic Compound (VOC) [326 IAC 8-2-8]

- (a) Pursuant to 326 IAC 8-2-8 (Magnet Wire Coating Operations), the Permittee shall not allow the discharge into the atmosphere of VOC in excess of 1.7 pounds VOC per gallon of coating, excluding water, as delivered to the applicator.
- (b) The equivalent pounds of VOC per gallon of coating solids (as applied) shall be limited to less than 2.21, when L is equal to 1.7 pounds of VOC per gallon of coating and D is equal to 7.36 pounds of VOC per gallon of coating.
- (c) Pursuant to 326 IAC 8-1-2 (b), the enameling ovens VOC emission shall be limited to no greater than the equivalent emissions, expressed as pounds of VOC per gallon coating solids, allowed in (a).

This equivalency was determined by the following equation:

$$E = L / (1 - (L/D))$$

Where

- L= Applicable emission limit from 326 IAC 8 in pounds of VOC per gallon of coating
D= Density of VOC in coating in pounds per gallon of VOC
E= Equivalent emission limit in pounds of VOC per gallon of coating solids as applied

Actual solvent density shall be used to determine compliance of the surface coating operation using the compliance methods in 326 IAC 8-1-2 (a).

- (d) Pursuant to 326 IAC 8-1-2(c), the equivalent overall control efficiency of the internal integral catalytic oxidizers and the external thermal oxidizers shall be no less than 95.9% or the required overall control efficiency demonstrated by the most recent stack test, for the worst case VOC coating currently used; for a higher VOC content coating, the overall control efficiency of these units shall be no less than the estimated control efficiency required to achieve compliance with the VOC limit in Condition D.10.1(a).

The overall control efficiency (O) of the internal integral catalytic oxidizers and the external thermal oxidizers shall be calculated by the following equation:

$$O = \frac{V - E}{V} \times 100$$

Where:

- V = The actual VOC content of the coating or, if multiple coatings are used, the daily weighted average VOC content of all coatings, as applied to the subject coating line as determined by the applicable test methods and procedures specified in 326 IAC 8-1-4 in units of pounds of VOC per gallon of coating solids as applied.
- E = Equivalent emission limit in pounds of VOC per gallon of coating solids as applied.
- O = Equivalent overall control efficiency of the capture system and control device as a percentage.

D.10.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.10.3 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]

Pursuant to 326 IAC 8-1-2(a), the Permittee shall operate the catalytic and thermal oxidizers to achieve compliance with Condition D.10.1.

D.10.4 Oxidizer Operation

To ensure compliance with Condition D.10.1, the internal catalytic oxidizers and the external thermal oxidizers shall operate at all times that the two (2) wire enameling ovens are in operation. When operating, the internal catalytic oxidizers and the external thermal oxidizer shall maintain a 3 hour average temperature of 1100 deg F or the 3 hour block average minimum temperature determined in the latest compliance testing to maintain a volatile organic compound (VOC) overall control efficiency of not less than 95.9% to demonstrate compliance with Condition D.10.1.

D.10.5 Testing Requirements [326 IAC 2-7-6(1), (6)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Condition D.10.1, within one hundred and eighty (180) days after initial startup, the Permittee shall conduct performance tests to verify VOC control efficiency for the internal catalytic oxidizer and the external thermal oxidizer using methods approved by the Commissioner. Stack testing shall be performed in accordance with 326 IAC 3-6.
- (b) One representative oven from the two (2) wire enameling ovens shall be tested. The oven tested shall be the oven in which the longest amount of time has elapsed since its previous test. This test shall be repeated at least once every five years from the date of this valid compliance demonstration.
- (c) Before using a coating that would lead to a higher VOC loading in pounds per hour than what was used during the stack test required in (a) above, the Permittee shall conduct a performance test to verify VOC control efficiency for the oxidizers using methods approved by the Commissioner.
- (d) For a higher VOC content coating, the following procedure shall be followed:
 - (1) Calculate the new minimum required control efficiency for the new coating

(E_{new});

- (2) Calculate the new maximum VOC loading (L_{new}) for the higher VOC content enamel;
- (3) Calculate the current maximum VOC loading (L_{current});
- (4) If E_{new} is lower than the last stack test control efficiency, and L_{new} is lower than L_{current} , Permittee shall be allowed to use the higher VOC content enamel.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.10.6 Parametric Monitoring

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on the oxidizers for measuring operating temperature of the internal catalytic oxidizers and the external thermal oxidizer. For the purposes of this condition, continuous monitoring shall mean no less often than once per fifteen (15) minutes. The output from this monitoring system and the three hour average temperatures shall be recorded whenever the oxidizers are in operation.
- (b) If the primary continuous monitoring system is not in operation, the oxidizer temperature will be recorded using some manner of secondary system, such as with back-up electro-mechanical hardware or manually if necessary. Nothing in this permit shall excuse the Permittee from complying with the requirement to continuously monitor the temperature of the oxidizers. Continuous monitoring shall mean no less often than once per fifteen (15) minutes.
- (c) The oxidizers shall operate such that if the three-hour average temperature falls below the 3 hour block average minimum required temperature (setpoint) as determined by the latest stack test, corrective actions shall be taken within 15 minutes to return oxidizer temperature to at least the required minimum temperature setpoint. Corrective action must return oxidizer temperature to or above the minimum temperature setpoint within thirty (30) minutes of the corrective action, or the enamel flow to the oven shall be shut off. Failure to take corrective action or failure to shut off the enamel flow as stated above shall be considered a deviation from this permit.
- (d) Any action taken must be in accordance and consistent with Section C.15 - Response to Excursions and Exceedances and failure to take action consistent with Section C.15 shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.10.7 Record Keeping Requirements

- (a) To document compliance with Conditions D.10.1 and D.10.6, the Permittee shall maintain records in accordance with (1) through (2) below. Records maintained for (1) through (2) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC content limits and/or the VOC emission limits established in Conditions D.4.1
 - (1) The VOC content of each coating material and solvent used less water.
 - (2) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.

- (b) To document compliance with Condition D.10.6, the Permittee shall maintain the continuous temperature records and 3 hour average temperature records.
- (c) All records shall be maintained in accordance with Section C- General Record Keeping Requirements, of this permit.

11. Section E has been added to the permit, which includes requirements under the NESHAP for Miscellaneous Metal Coating Operations, 40 CFR 63, Subpart MMMM. According to the 40 CFR 63 and 65 Amendment effective April 20, 2006 (FR Volume 71, No. 76, Pages 20495-20472), 40 CFR 63.3963(g) has been amended to delete the requirement to operate in accordance with the startup, shutdown, and malfunction plan during periods of startup, shutdown or malfunction.

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

Under the Miscellaneous Metal Parts and Products Coating NESHAP (40 CFR 63, Subpart MMMM), the following emission units are considered to be part of an existing magnet wire coating affected source.

- (a) Three (3) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 701-702, 703-704 and 705-706, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0023.
- (b) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 707-708 and 709-710, with a maximum capacity of 33 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0020.
- (c) Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit numbers 804 and 805, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral), with ovens 804 and 805 exhausted at Stack/Vent 0033.

Two (2) Quartz Fabric wire enameling ovens, installed before 1977, emission unit number 808 and 809, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0396.
- (d) One (1) Quartz Fabric wire enameling oven, installed before 1977, emission unit number 810, with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0024.
- (e) Four (4) Lepel Fabric wire enameling ovens, installed before 1980, emission unit numbers 807, 806, 803, and 802, each with a maximum capacity of 80 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0397.
- (f) Four (4) Lepel Fabric wire enameling ovens, installed before 1980, emission unit number 802,803, 806 and 807, with a maximum capacity of 80 pounds of magnet wire per hour each. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent 0397.
- (g) One (1) SICME ES enameling oven, installed March 1991, emission unit number 695, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0066.

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (h) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 690, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0068.
- (i) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 605, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0069.
- (j) One (1) SICME ES wire enameling oven, installed March 1991, emission unit number 600, with a maximum capacity of 90 pounds of magnet wire per hour. Emissions shall be controlled by an integral thermal oxidizer exhausted at Stack/Vent ID 0071.
- (k) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 610, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0091.
- (l) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 640, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0113.
- (m) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 620, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0118.
- (n) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 670, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0122.
- (o) One (1) Square/Rectangular wire enameling oven, installed before 1980, emission unit number 680, with a maximum capacity of 66.67 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0133.
- (p) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 351-352, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0172.
- (q) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 353-354, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0173.
- (r) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 355-356, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0174.
- (s) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 367-368, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0175.

- (t) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 365-366, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0176.
- (u) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 363-364, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0177.
- (v) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 373-374, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0196.
- (w) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 371-372, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0197.
- (x) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 369-370, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0198.
- (y) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 357-358, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0199.
- (z) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 359-360, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0200.
- (aa) One (1) MOCO wire enameling oven, installed before 1980, emission unit number 361-362, with a maximum capacity of 33.33 pounds of magnet wire per hour. Emissions shall be controlled by an external thermal oxidizer (not integral) exhausted at Stack/Vent ID 0201.
- (bb) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 615, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 418.
- (cc) One (1) GE-M wire enameling oven, constructed in 2006, emission unit number 635, with a maximum capacity of 614.6 pounds of magnet wire per hour, with an internal integral catalytic oxidizer, with emissions controlled by a natural gas-fired external thermal oxidizer with a maximum heat input of 0.7 MMBtu per hour, and exhausting to Stack/Vent ID 420.

SECTION E FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

Under the Miscellaneous Metal Parts and Products Coating NESHAP (40 CFR 63, Subpart Mmmm), the following emission unit is considered to be a storage and mixing operation that is considered to be part of an existing magnet wire coating affected source.

- (dd) One (1) applicator cleaning area, installed in January 1991, consisting of tanks 1 through 7, exhausted through stacks 0299, 0300 and 0301, capacity: 150 gallons each for tanks 1 and 2, 650 gallons for tank 3, 500 gallons each for tanks 4 and 5, 400 gallons for tank 6 and 500 gallons for tank 7.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]

E.1 General Provisions Relating to NESHAP Subpart Mmmm (National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products [326 IAC 20-1] [40 CFR Part 63, Subpart A])

Pursuant to 40 CFR 63.3901, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1 as specified in Table 2 of 40 CFR Part 63, Subpart Mmmm in accordance with schedule in 40 CFR 63 Subpart Mmmm

E.2 NESHAP Subpart Mmmm Requirements [40 CFR 63, Subpart Mmmm]

Pursuant to 40 CFR 63, Subpart Mmmm, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart Mmmm, for the entire source, beginning January 2, 2007, as follows:

§ 63.3880 What is the purpose of this subpart?

This subpart establishes national emission standards for hazardous air pollutants (NESHAP) for miscellaneous metal parts and products surface coating facilities. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations.

§ 63.3881(a)(4) and (b) Am I subject to this subpart?

(a) Miscellaneous metal parts and products include, but are not limited to, metal components of the following types of products as well as the products themselves: motor vehicle parts and accessories, bicycles and sporting goods, recreational vehicles, extruded aluminum structural components, railroad cars, heavy duty trucks, medical equipment, lawn and garden equipment, electronic equipment, magnet wire, steel drums, industrial machinery, metal pipes, and numerous other industrial, household, and consumer products. Except as provided in paragraph (c) of this section, the source category to which this subpart applies is the surface coating of any miscellaneous metal parts or products, as described in paragraph (a)(1) of this section, and it includes the subcategories listed in paragraphs (a)(2) through (6) of this section.

(1) ****

(2) ****

(3) ****

(4) The magnet wire coating subcategory includes surface coating operations that are performed using coatings that meet the definition of magnet wire coatings in §63.3981.

(b) You are subject to this subpart if you own or operate a new, reconstructed, or existing affected source, as defined in §63.3882, that uses 946 liters (250 gallons (gal)) per year, or more, of coatings that contain hazardous air pollutants (HAP) in the surface coating of miscellaneous metal parts and products defined in paragraph (a) of this section; and that is a major source, is located at a major source, or is part of a major source of emissions of HAP. A major source of HAP emissions is any stationary source or group of stationary sources located within a contiguous area and under common control that emits or has the potential to emit any single HAP at a rate of 9.07 megagrams (Mg) (10 tons) or more per year or any combination of HAP at a rate of 22.68 Mg (25 tons) or more per year. You do not need to include coatings that meet the definition of non-HAP coating contained in §63.3981 in determining whether you use 946 liters (250 gal) per year, or more, of coatings in the surface coating of miscellaneous metal parts and products.

§ 63.3882 What parts of my plant does this subpart cover?

(a) This subpart applies to each new, reconstructed, and existing affected source within each of the four subcategories listed in §63.3881(a).

(b) The affected source is the collection of all of the items listed in paragraphs (b)(1) through (4) of this section that are used for surface coating of miscellaneous metal parts and products within each subcategory.

(1) All coating operations as defined in §63.3981;

(2) All storage containers and mixing vessels in which coatings, thinners and/or other additives, and cleaning materials are stored or mixed;

(3) All manual and automated equipment and containers used for conveying coatings, thinners and/or other additives, and cleaning materials; and

(4) All storage containers and all manual and automated equipment and containers used for conveying waste materials generated by a coating operation.

(c) An affected source is a new affected source if you commenced its construction after August 13, 2002 and the construction is of a completely new miscellaneous metal parts and products surface coating facility where previously no miscellaneous metal parts and products surface coating facility had existed.

(d) An affected source is reconstructed if it meets the criteria as defined in §63.2.

(e) An affected source is existing if it is not new or reconstructed.

§ 63.3883(b) and (d) When do I have to comply with this subpart?

The date by which you must comply with this subpart is called the compliance date. The compliance date for each type of affected source is specified in paragraphs (a) through (c) of this section. The compliance date begins the initial compliance period during which you conduct the initial compliance demonstration described in §§63.3940, 63.3950, and 63.3960.

(a) ****

(b) For an existing affected source, the compliance date is the date 3 years after January 2, 2004.

(c) ****

(d) You must meet the notification requirements in §63.3910 according to the dates specified in that section and in subpart A of this part. Some of the notifications must be submitted before the compliance dates described in paragraphs (a) through (c) of this section.

§ 63.3890 What emission limits must I meet?

(a) ****

(b) For an existing affected source, you must limit organic HAP emissions to the atmosphere from the affected source to the applicable limit specified in paragraphs (b)(1) through (5) of this section,

except as specified in paragraph (c) of this section, determined according to the requirements in §63.3941, §63.3951, or §63.3961.

(1) ****

(2) ****

(3) For each existing magnet wire coating affected source, limit organic HAP emissions to no more than 0.12 kg (1.0 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(4) ****

(5) ****

(c) If your facility's surface coating operations meet the applicability criteria of more than one of the subcategory emission limits specified in paragraphs (a) or (b) of this section, you may comply separately with each subcategory emission limit or comply using one of the alternatives in paragraph (c)(1) or (2) of this section.

(1) If the general use or magnet wire surface coating operations subject to only one of the emission limits specified in paragraphs (a)(1), (3), (b)(1), or (3) of this section account for 90 percent or more of the surface coating activity at your facility (*i.e.*, it is the predominant activity at your facility), then compliance with that one emission limitations in this subpart for all surface coating operations constitutes compliance with the other applicable emission limits. You must use liters (gal) of solids used as a measure of relative surface coating activity over a representative period of operation. You may estimate the relative volume of coating solids used from parameters other than coating consumption and volume solids content (*e.g.*, design specifications for the parts or products coated and the number of items produced). The determination of predominant activity must accurately reflect current and projected coating operations and must be verifiable through appropriate documentation. The use of parameters other than coating consumption and volume solids content must be approved by the Administrator. You may use data for any reasonable time period of at least 1 year in determining the relative amount of coating activity, as long as they represent the way the source will continue to operate in the future and are approved by the Administrator. You must determine the predominant activity at your facility and submit the results of that determination with the initial notification required by §63.3910(b). Additionally, you must determine the facility's predominant activity annually and include the determination in the next semi-annual compliance report required by §63.3920(a).

(2) You may calculate and comply with a facility-specific emission limit as described in paragraphs (c)(2)(i) through (iii) of this section. If you elect to comply using the facility-specific emission limit alternative, then compliance with the facility-specific emission limit and the emission limitations in this subpart for all surface coating operations constitutes compliance with this and other applicable surface coating NESHAP. In calculating a facility-specific emission limit, you must include coating activities that meet the applicability criteria of the other subcategories and constitute more than 1 percent of total coating activities. Coating activities that meet the applicability criteria of other surface coating NESHAP but comprise less than 1 percent of coating activities need not be included in the determination of predominant activity but must be included in the compliance calculation.

(i) You are required to calculate the facility-specific emission limit for your facility when you submit the notification of compliance status required in §63.3910(c), and on a monthly basis afterward using the coating data for the relevant 12-month compliance period.

(ii) Use Equation 1 of this section to calculate the facility-specific emission limit for your surface coating operations for each 12-month compliance period.

$$\text{Facility Specific Emission Unit} = \frac{\sum_{i=1}^n (\text{Limit}_i)(\text{Solid}_i)}{\sum_{i=1}^n (\text{Solid}_i)}$$

Where:

Facility-specific emission limit = Facility-specific emission limit for each 12-month compliance period, kg (lb) organic HAP per kg (lb) coating solids used.

Limit_i = The new source or existing source emission limit applicable to coating operation, i, included in the facility-specific emission limit, converted to kg (lb) organic HAP per kg (lb) coating solids used, if the emission limit is not already in those units. All emission limits included in the facility-specific emission limit must be in the same units.

Solids_i = The liters (gal) of solids used in coating operation, i, in the 12-month compliance period that is subject to emission limit, i. You may estimate the volume of coating solids used from parameters other than coating consumption and volume solids content (e.g., design specifications for the parts or products coated and the number of items produced). The use of parameters other than coating consumption and volume solids content must be approved by the Administrator.

n = The number of different coating operations included in the facility-specific emission limit.

(iii) ****

§ 63.3891(c) What are my options for meeting the emission limits?

You must include all coatings (as defined in §63.3981), thinners and/or other additives, and cleaning materials used in the affected source when determining whether the organic HAP emission rate is equal to or less than the applicable emission limit in §63.3890. To make this determination, you must use at least one of the three compliance options listed in paragraphs (a) through (c) of this section. You may apply any of the compliance options to an individual coating operation, or to multiple coating operations as a group, or to the entire affected source. You may use different compliance options for different coating operations, or at different times on the same coating operation. You may employ different compliance options when different coatings are applied to the same part, or when the same coating is applied to different parts. However, you may not use different compliance options at the same time on the same coating operation. If you switch between compliance options for any coating operation or group of coating operations, you must document this switch as required by §63.3930(c), and you must report it in the next semiannual compliance report required in §63.3920.

(a) ****

(b) ****

(c) *Emission rate with add-on controls option.* Demonstrate that, based on the coatings, thinners and/or other additives, and cleaning materials used in the coating operation(s), and the emissions reductions achieved by emission capture systems and add-on controls, the organic HAP emission rate for the coating operation(s) is less than or equal to the applicable emission limit in §63.3890, calculated as a rolling 12-month emission rate and determined on a monthly basis. If you use this compliance option, you must also demonstrate that all emission capture systems and add-on control devices for the coating operation(s) meet the operating limits required in §63.3892, except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), and that you meet the work practice standards required in §63.3893. You must meet all the requirements of §§63.3960 through 63.3968 to demonstrate compliance with the emission limits, operating limits, and work practice standards using this option.

§ 63.3892(b) and (c) What operating limits must I meet?

(a) ****

(b) For any controlled coating operation(s) on which you use the emission rate with add-on controls option, except those for which you use a solvent recovery system and conduct a liquid-liquid material balance according to §63.3961(j), you must meet the operating limits specified in Table 1 to this subpart. These operating limits apply to the emission capture and control systems on the coating operation(s) for which you use this option, and you must establish the operating limits during the performance test according to the requirements in §63.3967. You must meet the operating limits at all times after you establish them.

(c) If you use an add-on control device other than those listed in Table 1 to this subpart, or wish to monitor an alternative parameter and comply with a different operating limit, you must apply to the Administrator for approval of alternative monitoring under §63.8(f).

§ 63.3893(b) What work practice standards must I meet?

(a) ****

(b) If you use the emission rate with add-on controls option, you must develop and implement a work practice plan to minimize organic HAP emissions from the storage, mixing, and conveying of coatings, thinners and/or other additives, and cleaning materials used in, and waste materials generated by the controlled coating operation(s) for which you use this option; or you must meet an alternative standard as provided in paragraph (c) of this section. The plan must specify practices and procedures to ensure that, at a minimum, the elements specified in paragraphs (b)(1) through (5) of this section are implemented.

(1) All organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be stored in closed containers.

(2) Spills of organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be minimized.

(3) Organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be conveyed from one location to another in closed containers or pipes.

(4) Mixing vessels which contain organic-HAP-containing coatings and other materials must be closed except when adding to, removing, or mixing the contents.

(5) Emissions of organic HAP must be minimized during cleaning of storage, mixing, and conveying equipment.

(c) As provided in §63.6(g), we, the U.S. Environmental Protection Agency, may choose to grant you permission to use an alternative to the work practice standards in this section.

§ 63.3900(a)(2), (b) and (c) What are my general requirements for complying with this subpart?

(a) You must be in compliance with the emission limitations in this subpart as specified in paragraphs (a)(1) and (2) of this section.

(1) ****

(2) Any coating operation(s) for which you use the emission rate with add-on controls option, as specified in §63.3891(c), must be in compliance with the emission limitations as specified in paragraphs (a)(2)(i) through (iii) of this section.

(i) The coating operation(s) must be in compliance with the applicable emission limit in §63.3890 at all times except during periods of startup, shutdown, and malfunction.

(ii) The coating operation(s) must be in compliance with the operating limits for emission capture systems and add-on control devices required by §63.3892 at all times except during periods of startup, shutdown, and malfunction, and except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j).

(iii) The coating operation(s) must be in compliance with the work practice standards in §63.3893 at all times.

(b) You must always operate and maintain your affected source, including all air pollution control and monitoring equipment you use for purposes of complying with this subpart, according to the provisions in §63.6(e)(1)(i).

(c) If your affected source uses an emission capture system and add-on control device, you must develop a written startup, shutdown, and malfunction plan according to the provisions in §63.6(e)(3). The plan must address the startup, shutdown, and corrective actions in the event of a malfunction of the emission capture system or the add-on control device. The plan must also address any coating operation equipment that may cause increased emissions or that would affect capture efficiency if the process equipment malfunctions, such as conveyors that move parts among enclosures.

§ 63.3901 What parts of the General Provisions apply to me?

Table 2 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you.

§ 63.3910 What notifications must I submit?

(a) *General.* You must submit the notifications in §§63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) that apply to you by the dates specified in those sections, except as provided in paragraphs (b) and (c) of this section.

(b) *Initial Notification.* You must submit the initial notification required by §63.9(b) for a new or reconstructed affected source no later than 120 days after initial startup or 120 days after January 2, 2004, whichever is later. For an existing affected source, you must submit the initial notification no later than 1 year after January 2, 2004. If you are using compliance with the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (subpart IIII of this part) as provided for under §63.3881(d) to constitute compliance with this subpart for any or all of your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations. If you are complying with another NESHAP that constitutes the predominant activity at your facility under §63.3881(e)(2) to constitute compliance with this subpart for your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations.

(c) *Notification of compliance status.* You must submit the notification of compliance status required by §63.9(h) no later than 30 calendar days following the end of the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source. The notification of compliance status must contain the information specified in paragraphs (c)(1) through (11) of this section and in §63.9(h).

(1) Company name and address.

(2) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(3) Date of the report and beginning and ending dates of the reporting period. The reporting period is the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source.

(4) Identification of the compliance option or options specified in §63.3891 that you used on each coating operation in the affected source during the initial compliance period.

(5) Statement of whether or not the affected source achieved the emission limitations for the initial compliance period.

(6) If you had a deviation, include the information in paragraphs (c)(6)(i) and (ii) of this section.

(i) A description and statement of the cause of the deviation.

(ii) If you failed to meet the applicable emission limit in §63.3890, include all the calculations you used to determine the kg (lb) of organic HAP emitted per liter (gal) coating solids used. You do not need to submit information provided by the materials' suppliers or manufacturers, or test reports.

(7) For each of the data items listed in paragraphs (c)(7)(i) through (iv) of this section that is required by the compliance option(s) you used to demonstrate compliance with the emission limit, include an example of how you determined the value, including calculations and supporting data. Supporting data may include a copy of the information provided by the supplier or manufacturer of the example coating or material, or a summary of the results of testing conducted according to §63.3941(a), (b), or (c). You do not need to submit copies of any test reports.

(i) Mass fraction of organic HAP for one coating, for one thinner and/or other additive, and for one cleaning material.

(ii) Volume fraction of coating solids for one coating.

(iii) Density for one coating, one thinner and/or other additive, and one leaning material, except that if you use the compliant material option, only the example coating density is required.

(iv) The amount of waste materials and the mass of organic HAP contained in the waste materials for which you are claiming an allowance in Equation 1 of §63.3951.

(8) The calculation of kg (lb) of organic HAP emitted per liter (gal) coating solids used for the compliance option(s) you used, as specified in paragraphs (c)(8)(i) through (iii) of this section.

(i) For the compliant material option, provide an example calculation of the organic HAP content for one coating, using Equation 2 of §63.3941.

(ii) For the emission rate without add-on controls option, provide the calculation of the total mass of organic HAP emissions for each month; the calculation of the total volume of coating solids used each month; and the calculation of the 12-month organic HAP emission rate using Equations 1 and 1A through 1C, 2, and 3, respectively, of §63.3951.

(iii) For the emission rate with add-on controls option, provide the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month, using Equations 1 and 1A through 1C of §63.3951; the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; the mass of organic HAP emission reduction each month by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961 and Equations 2, 3, and 3A through 3C of §63.3961 as applicable; the calculation of the total mass of organic HAP emissions each month using Equation 4 of §63.3961; and the calculation of the 12-month organic HAP emission rate using Equation 5 of §63.3961.

(9) For the emission rate with add-on controls option, you must include the information specified in paragraphs (c)(9)(i) through (iv) of this section, except that the requirements in paragraphs (c)(9)(i) through (iii) of this section do not apply to solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j).

(i) For each emission capture system, a summary of the data and copies of the calculations supporting the determination that the emission capture system is a permanent total enclosure (PTE) or a measurement of the emission capture system efficiency. Include a description of the protocol followed for measuring capture efficiency, summaries of any capture efficiency tests conducted, and any calculations supporting the capture efficiency determination. If you use the data quality objective (DQO) or lower confidence limit (LCL) approach, you must also include the statistical calculations to show you meet the DQO or LCL criteria in appendix A to subpart KK of this part. You do not need to submit complete test reports.

(ii) A summary of the results of each add-on control device performance test. You do not need to submit complete test reports.

(iii) A list of each emission capture system's and add-on control device's operating limits and a summary of the data used to calculate those limits.

(iv) A statement of whether or not you developed and implemented the work practice plan required by §63.3893.

(10) If you are complying with a single emission limit representing the predominant activity under §63.3890(c)(1), include the calculations and supporting information used to demonstrate that this emission limit represents the predominant activity as specified in §63.3890(c)(1).

(11) If you are complying with a facility-specific emission limit under §63.3890(c)(2), include the calculation of the facility-specific emission limit and any supporting information as specified in §63.3890(c)(2).

§ 63.3920 What reports must I submit?

(a) *Semiannual compliance reports.* You must submit semiannual compliance reports for each affected source according to the requirements of paragraphs (a)(1) through (7) of this section. The semiannual compliance reporting requirements may be satisfied by reports required under other parts of the Clean Air Act (CAA), as specified in paragraph (a)(2) of this section.

(1) *Dates.* Unless the Administrator has approved or agreed to a different schedule for submission of reports under §63.10(a), you must prepare and submit each semiannual compliance report according to the dates specified in paragraphs (a)(1)(i) through (iv) of this section. Note that the information reported for each of the months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(i) The first semiannual compliance report must cover the first semiannual reporting period which begins the day after the end of the initial compliance period described in §63.3940, §63.3950, or §63.3960 that applies to your affected source and ends on June 30 or December 31, whichever date is the first date following the end of the initial compliance period.

(ii) Each subsequent semiannual compliance report must cover the subsequent semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(iii) Each semiannual compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(iv) For each affected source that is subject to permitting regulations pursuant to 40 CFR part 70 or 40 CFR part 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), you may submit the first and subsequent compliance reports according to the dates the permitting authority has established instead of according to the date specified in paragraph (a)(1)(iii) of this section.

(2) *Inclusion with title V report.* Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 40 CFR part 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a semiannual compliance report pursuant to this section along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the semiannual compliance report includes all required information concerning deviations from any emission limitation in this subpart, its submission will be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a semiannual compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permitting authority.

(3) *General requirements.* The semiannual compliance report must contain the information specified in paragraphs (a)(3)(i) through (vii) of this section, and the information specified in paragraphs (a)(4) through (7) and (c)(1) of this section that is applicable to your affected source.

(i) Company name and address.

(ii) **Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.**

(iii) **Date of report and beginning and ending dates of the reporting period. The reporting period is the 6-month period ending on June 30 or December 31. Note that the information reported for each of the 6 months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.**

(iv) **Identification of the compliance option or options specified in §63.3891 that you used on each coating operation during the reporting period. If you switched between compliance options during the reporting period, you must report the beginning and ending dates for each option you used.**

(v) **If you used the emission rate without add-on controls or the emission rate with add-on controls compliance option (§63.3891(b) or (c)), the calculation results for each rolling 12-month organic HAP emission rate during the 6-month reporting period.**

(vi) **If you used the predominant activity alternative (§63.3890(c)(1)), include the annual determination of predominant activity if it was not included in the previous semi-annual compliance report.**

(vii) **If you used the facility-specific emission limit alternative (§63.3890(c)(2)), include the calculation of the facility-specific emission limit for each 12-month compliance period during the 6-month reporting period.**

(4) **No deviations.** If there were no deviations from the emission limitations in §§63.3890, 63.3892, and 63.3893 that apply to you, the semiannual compliance report must include a statement that there were no deviations from the emission limitations during the reporting period. If you used the emission rate with add-on controls option and there were no periods during which the continuous parameter monitoring systems (CPMS) were out-of-control as specified in §63.8(c)(7), the semiannual compliance report must include a statement that there were no periods during which the CPMS were out-of-control during the reporting period.

(5) ****

(6) ****

(7) **Deviations: Emission rate with add-on controls option.** If you used the emission rate with add-on controls option and there was a deviation from an emission limitation (including any periods when emissions bypassed the add-on control device and were diverted to the atmosphere), the semiannual compliance report must contain the information in paragraphs (a)(7)(i) through (xiv) of this section. This includes periods of startup, shutdown, and malfunction during which deviations occurred.

(i) **The beginning and ending dates of each compliance period during which the 12-month organic HAP emission rate exceeded the applicable emission limit in §63.3890.**

(ii) **The calculations used to determine the 12-month organic HAP emission rate for each compliance period in which a deviation occurred. You must provide the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1 and 1A through 1C of §63.3951; and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4); the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; the calculation of the mass of organic HAP emission reduction each month by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961, and Equations 2, 3, and 3A through 3C of §63.3961, as applicable; the calculation of the total mass of organic HAP emissions each month using Equation 4 of §63.3961; and the calculation of the 12-month organic HAP emission rate using Equation 5 of §63.3961. You do not need to submit the background data supporting these calculations (e.g., information provided by materials suppliers or manufacturers, or test reports).**

(iii) **The date and time that each malfunction started and stopped.**

(iv) A brief description of the CPMS.

(v) The date of the latest CPMS certification or audit.

(vi) The date and time that each CPMS was inoperative, except for zero (low-level) and high-level checks.

(vii) The date, time, and duration that each CPMS was out-of-control, including the information in §63.8(c)(8).

(viii) The date and time period of each deviation from an operating limit in Table 1 to this subpart; date and time period of any bypass of the add-on control device; and whether each deviation occurred during a period of startup, shutdown, or malfunction or during another period.

(ix) A summary of the total duration of each deviation from an operating limit in Table 1 to this subpart and each bypass of the add-on control device during the semiannual reporting period, and the total duration as a percent of the total source operating time during that semiannual reporting period.

(x) A breakdown of the total duration of the deviations from the operating limits in Table 1 of this subpart and bypasses of the add-on control device during the semiannual reporting period into those that were due to startup, shutdown, control equipment problems, process problems, other known causes, and other unknown causes.

(xi) A summary of the total duration of CPMS downtime during the semiannual reporting period and the total duration of CPMS downtime as a percent of the total source operating time during that semiannual reporting period.

(xii) A description of any changes in the CPMS, coating operation, emission capture system, or add-on control device since the last semiannual reporting period.

(xiii) For each deviation from the work practice standards, a description of the deviation, the date and time period of the deviation, and the actions you took to correct the deviation.

(xiv) A statement of the cause of each deviation.

(b) *Performance test reports.* If you use the emission rate with add-on controls option, you must submit reports of performance test results for emission capture systems and add-on control devices no later than 60 days after completing the tests as specified in §63.10(d)(2).

(c) *Startup, shutdown, malfunction reports.* If you used the emission rate with add-on controls option and you had a startup, shutdown, or malfunction during the semiannual reporting period, you must submit the reports specified in paragraphs (c)(1) and (2) of this section.

(1) If your actions were consistent with your startup, shutdown, and malfunction plan, you must include the information specified in §63.10(d) in the semiannual compliance report required by paragraph (a) of this section.

(2) If your actions were not consistent with your startup, shutdown, and malfunction plan, you must submit an immediate startup, shutdown, and malfunction report as described in paragraphs (c)(2)(i) and (ii) of this section.

(i) You must describe the actions taken during the event in a report delivered by facsimile, telephone, or other means to the Administrator within 2 working days after starting actions that are inconsistent with the plan.

(ii) You must submit a letter to the Administrator within 7 working days after the end of the event, unless you have made alternative arrangements with the Administrator as specified in §63.10(d)(5)(ii). The letter must contain the information specified in §63.10(d)(5)(ii).

§ 63.3930 What records must I keep?

You must collect and keep records of the data and information specified in this section. Failure to collect and keep these records is a deviation from the applicable standard.

(a) A copy of each notification and report that you submitted to comply with this subpart, and the documentation supporting each notification and report. If you are using the predominant activity alternative under §63.3890(c), you must keep records of the data and calculations used to determine the predominant activity. If you are using the facility-specific emission limit alternative under §63.3890(c), you must keep records of the data used to calculate the facility-specific emission limit for the initial compliance demonstration. You must also keep records of any data used in each annual predominant activity determination and in the calculation of the facility-specific emission limit for each 12-month compliance period included in the semi-annual compliance reports.

(b) A current copy of information provided by materials suppliers or manufacturers, such as manufacturer's formulation data, or test data used to determine the mass fraction of organic HAP and density for each coating, thinner and/or other additive, and cleaning material, and the volume fraction of coating solids for each coating. If you conducted testing to determine mass fraction of organic HAP, density, or volume fraction of coating solids, you must keep a copy of the complete test report. If you use information provided to you by the manufacturer or supplier of the material that was based on testing, you must keep the summary sheet of results provided to you by the manufacturer or supplier. You are not required to obtain the test report or other supporting documentation from the manufacturer or supplier.

(c) For each compliance period, the records specified in paragraphs (c)(1) through (4) of this section.

(1) A record of the coating operations on which you used each compliance option and the time periods (beginning and ending dates and times) for each option you used.

(2) ****

(3) ****

(4) For the emission rate with add-on controls option, records of the calculations specified in paragraphs (c)(4)(i) through (v) of this section.

(i) The calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1 and 1A through 1C of §63.3951 and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4);

(ii) The calculation of the total volume of coating solids used each month using Equation 2 of §63.3951;

(iii) The calculation of the mass of organic HAP emission reduction by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961 and Equations 2, 3, and 3A through 3C of §63.3961, as applicable;

(iv) The calculation of each month's organic HAP emission rate using Equation 4 of §63.3961; and

(v) The calculation of each 12-month organic HAP emission rate using Equation 5 of §63.3961.

(d) A record of the name and volume of each coating, thinner and/or other additive, and cleaning material used during each compliance period. If you are using the compliant material option for all coatings at the source, you may maintain purchase records for each material used rather than a record of the volume used.

(e) A record of the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each compliance period unless the material is tracked by weight.

(f) A record of the volume fraction of coating solids for each coating used during each compliance period.

(g) If you use either the emission rate without add-on controls or the emission rate with add-on controls compliance option, the density for each coating, thinner and/or other additive, and cleaning material used during each compliance period.

(h) If you use an allowance in Equation 1 of §63.3951 for organic HAP contained in waste materials sent to or designated for shipment to a treatment, storage, and disposal facility (TSDF) according to §63.3951(e)(4), you must keep records of the information specified in paragraphs (h)(1) through (3) of this section.

(1) The name and address of each TSDF to which you sent waste materials for which you use an allowance in Equation 1 of §63.3951; a statement of which subparts under 40 CFR parts 262, 264, 265, and 266 apply to the facility; and the date of each shipment.

(2) Identification of the coating operations producing waste materials included in each shipment and the month or months in which you used the allowance for these materials in Equation 1 of §63.3951.

(3) The methodology used in accordance with §63.3951(e)(4) to determine the total amount of waste materials sent to or the amount collected, stored, and designated for transport to a TSDF each month; and the methodology to determine the mass of organic HAP contained in these waste materials. This must include the sources for all data used in the determination, methods used to generate the data, frequency of testing or monitoring, and supporting calculations and documentation, including the waste manifest for each shipment.

(i) [Reserved]

(j) You must keep records of the date, time, and duration of each deviation.

(k) If you use the emission rate with add-on controls option, you must keep the records specified in paragraphs (k)(1) through (8) of this section.

(1) For each deviation, a record of whether the deviation occurred during a period of startup, shutdown, or malfunction.

(2) The records in §63.6(e)(3)(iii) through (v) related to startup, shutdown, and malfunction.

(3) The records required to show continuous compliance with each operating limit specified in Table 1 to this subpart that applies to you.

(4) ****

(5) ****

(6) The records specified in paragraphs (k)(6)(i) and (ii) of this section for each add-on control device organic HAP destruction or removal efficiency determination as specified in §63.3966.

(i) Records of each add-on control device performance test conducted according to §§63.3964 and 63.3966.

(ii) Records of the coating operation conditions during the add-on control device performance test showing that the performance test was conducted under representative operating conditions.

(7) Records of the data and calculations you used to establish the emission capture and add-on control device operating limits as specified in §63.3967 and to document compliance with the operating limits as specified in Table 1 to this subpart.

(8) A record of the work practice plan required by §63.3893 and documentation that you are implementing the plan on a continuous basis.

§ 63.3931 In what form and for how long must I keep my records?

(a) Your records must be in a form suitable and readily available for expeditious review, according to §63.10(b)(1). Where appropriate, the records may be maintained as electronic spreadsheets or as a database.

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record on-site for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record according to §63.10(b)(1). You may keep the records off-site for the remaining 3 years.

Compliance Requirements for the Emission Rate With Add-On Control Options

§ 63.3960 By what date must I conduct performance tests and other initial compliance demonstrations?

(a) *New and reconstructed affected sources.* For a new or reconstructed affected source, you must meet the requirements of paragraphs (a)(1) through (4) of this section.

(1) All emission capture systems, add-on control devices, and CPMS must be installed and operating no later than the applicable compliance date specified in §63.3883. Except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), you must conduct a performance test of each capture system and add-on control device according to §§63.3964, 63.3965, and 63.3966 and establish the operating limits required by §63.3892 no later than 180 days after the applicable compliance date specified in §63.3883. For a solvent recovery system for which you conduct liquid-liquid material balances according to §63.3961(j), you must initiate the first material balance no later than the applicable compliance date specified in §63.3883. For magnet wire coating operations you may, with approval, conduct a performance test of one representative magnet wire coating machine for each group of identical or very similar magnet wire coating machines.

(2) You must develop and begin implementing the work practice plan required by §63.3893 no later than the compliance date specified in §63.3883.

(3) You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3961. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coatings solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the results of emission capture system and add-on control device performance tests conducted according to §§63.3964, 63.3965, and 63.3966; results of liquid-liquid material balances conducted according to §63.3961(j); calculations according to §63.3961 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.3890; the operating limits established during the performance tests and the results of the continuous parameter monitoring required by §63.3968; and documentation of whether you developed and implemented the work practice plan required by §63.3893.

(4) You do not need to comply with the operating limits for the emission capture system and add-on control device required by §63.3892 until after you have completed the performance tests specified in paragraph (a)(1) of this section. Instead, you must maintain a log detailing the

operation and maintenance of the emission capture system, add-on control device, and continuous parameter monitors during the period between the compliance date and the performance test. You must begin complying with the operating limits for your affected source on the date you complete the performance tests specified in paragraph (a)(1) of this section. For magnet wire coating operations, you must begin complying with the operating limits for all identical or very similar magnet wire coating machines on the date you complete the performance test of a representative magnet wire coating machine. The requirements in this paragraph (a)(4) do not apply to solvent recovery systems for which you conduct liquid-liquid material balances according to the requirements in §63.3961(j).

(b) Existing affected sources. For an existing affected source, you must meet the requirements of paragraphs (b)(1) through (3) of this section.

(1) All emission capture systems, add-on control devices, and CPMS must be installed and operating no later than the applicable compliance date specified in §63.3883. Except for magnet wire coating operations and solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), you must conduct a performance test of each capture system and add-on control device according to the procedures in §§63.3964, 63.3965, and 63.3966 and establish the operating limits required by §63.3892 no later than the compliance date specified in §63.3883. For magnet wire coating operations, you may, with approval, conduct a performance test of a single magnet wire coating machine that represents identical or very similar magnet wire coating machines. For a solvent recovery system for which you conduct liquid-liquid material balances according to §63.3961(j), you must initiate the first material balance no later than the compliance date specified in §63.3883.

(2) You must develop and begin implementing the work practice plan required by §63.3893 no later than the compliance date specified in §63.3883.

(3) You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3961. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coatings solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the results of emission capture system and add-on control device performance tests conducted according to §§63.3964, 63.3965, and 63.3966; results of liquid-liquid material balances conducted according to §63.3961(j); calculations according to §63.3961 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.3890; the operating limits established during the performance tests and the results of the continuous parameter monitoring required by §63.3968; and documentation of whether you developed and implemented the work practice plan required by §63.3893.

(c) You are not required to conduct an initial performance test to determine capture efficiency or destruction efficiency of a capture system or control device if you receive approval to use the results of a performance test that has been previously conducted on that capture system or control device. Any such previous tests must meet the conditions described in paragraphs (c)(1) through (3) of this section.

(1) The previous test must have been conducted using the methods and conditions specified in this subpart.

(2) Either no process or equipment changes have been made since the previous test was performed or the owner or operator must be able to demonstrate that the results of the performance test, reliably demonstrate compliance despite process or equipment changes.

(3) Either the required operating parameters were established in the previous test or sufficient data were collected in the previous test to establish the required operating parameters.

§ 63.3961 How do I demonstrate initial compliance?

(a) You may use the emission rate with add-on controls option for any coating operation, for any group of coating operations in the affected source, or for all of the coating operations in the affected source. You may include both controlled and uncontrolled coating operations in a group for which you use this option. You must use either the compliant material option or the emission rate without add-on controls option for any coating operation in the affected source for which you do not use the emission rate with add-on controls option. To demonstrate initial compliance, the coating operation(s) for which you use the emission rate with add-on controls option must meet the applicable emission limitations in §§63.3890, 63.3892, and 63.3893. You must conduct a separate initial compliance demonstration for each general use, magnet wire, rubber-to-metal, and extreme performance fluoropolymer coating operation, unless you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c). If you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.4490(c), you must demonstrate that all coating operations included in the predominant activity determination or calculation of the facility-specific emission limit comply with that limit. You must meet all the requirements of this section. When calculating the organic HAP emission rate according to this section, do not include any coatings, thinners and/or other additives, or cleaning materials used on coating operations for which you use the compliant material option or the emission rate without add-on controls option. You do not need to redetermine the mass of organic HAP in coatings, thinners and/or other additives, or cleaning materials that have been reclaimed onsite (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coatings operation(s) for which you use the emission rate with add-on controls option. If you use coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site, the amount of each used in a month may be reduced by the amount of each that is reclaimed. That is, the amount used may be calculated as the amount consumed to account for materials that are reclaimed.

(b) *Compliance with operating limits.* Except as provided in §63.3960(a)(4), and except for solvent recovery systems for which you conduct liquid-liquid material balances according to the requirements of paragraph (j) of this section, you must establish and demonstrate continuous compliance during the initial compliance period with the operating limits required by §63.3892, using the procedures specified in §§63.3967 and 63.3968.

(c) *Compliance with work practice requirements.* You must develop, implement, and document your implementation of the work practice plan required by §63.3893 during the initial compliance period, as specified in §63.3930.

(d) *Compliance with emission limits.* You must follow the procedures in paragraphs (e) through (n) of this section to demonstrate compliance with the applicable emission limit in §63.3890 for each affected source in each subcategory.

(e) *Determine the mass fraction of organic HAP, density, volume used, and volume fraction of coating solids.* Follow the procedures specified in §63.3951(a) through (d) to determine the mass fraction of organic HAP, density, and volume of each coating, thinner and/or other additive, and cleaning material used during each month; and the volume fraction of coating solids for each coating used during each month.

(f) *Calculate the total mass of organic HAP emissions before add-on controls.* Using Equation 1 of §63.3951, calculate the total mass of organic HAP emissions before add-on controls from all coatings, thinners and/or other additives, and cleaning materials used during each month in the coating operation or group of coating operations for which you use the emission rate with add-on controls option.

(g) *Calculate the organic HAP emission reduction for each controlled coating operation.* Determine the mass of organic HAP emissions reduced for each controlled coating operation during each month. The emission reduction determination quantifies the total organic HAP emissions that pass through the emission capture system and are destroyed or removed by the add-on control device. Use the procedures in paragraph (h) of this section to calculate the mass of organic HAP emission

reduction for each controlled coating operation using an emission capture system and add-on control device other than a solvent recovery system for which you conduct liquid-liquid material balances. For each controlled coating operation using a solvent recovery system for which you conduct a liquid-liquid material balance, use the procedures in paragraph (j) of this section to calculate the organic HAP emission reduction.

(h) Calculate the organic HAP emission reduction for each controlled coating operation not using liquid-liquid material balance. Use Equation 1 of this section to calculate the organic HAP emission reduction for each controlled coating operation using an emission capture system and add-on control device other than a solvent recovery system for which you conduct liquid-liquid material balances. The calculation applies the emission capture system efficiency and add-on control device efficiency to the mass of organic HAP contained in the coatings, thinners and/or other additives, and cleaning materials that are used in the coating operation served by the emission capture system and add-on control device during each month. You must assume zero efficiency for the emission capture system and add-on control device for any period of time a deviation specified in §63.3963(c) or (d) occurs in the controlled coating operation, including a deviation during a period of startup, shutdown, or malfunction, unless you have other data indicating the actual efficiency of the emission capture system and add-on control device and the use of these data is approved by the Administrator. Equation 1 of this section treats the materials used during such a deviation as if they were used on an uncontrolled coating operation for the time period of the deviation.

$$H_C = (A_C + B_C + C_C - R_W - H_{UNC}) \left(\frac{CE}{100} \times \frac{DRE}{100} \right) \quad (Eq. 1)$$

Where:

H_C = Mass of organic HAP emission reduction for the controlled coating operation during the month, kg.

A_C = Total mass of organic HAP in the coatings used in the controlled coating operation during the month, kg, as calculated in Equation 1A of this section.

B_C = Total mass of organic HAP in the thinners and/or other additives used in the controlled coating operation during the month, kg, as calculated in Equation 1B of this section.

C_C = Total mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg, as calculated in Equation 1C of this section.

R_W = Total mass of organic HAP in waste materials sent or designated for shipment to a hazardous waste TSDF for treatment or disposal during the compliance period, kg, determined according to §63.3951(e)(4). (You may assign a value of zero to R_W if you do not wish to use this allowance.)

H_{UNC} = Total mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used during all deviations specified in §63.3963(c) and (d) that occurred during the month in the controlled coating operation, kg, as calculated in Equation 1D of this section.

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent. Use the test methods and procedures specified in §§63.3964 and 63.3965 to measure and record capture efficiency.

DRE = Organic HAP destruction or removal efficiency of the add-on control device, percent. Use the test methods and procedures in §§63.3964 and 63.3966 to measure and record the organic HAP destruction or removal efficiency.

(1) Calculate the mass of organic HAP in the coatings used in the controlled coating operation, kg (1b), using Equation 1A of this section:

$$A_C = \sum_{i=1}^n (Vol_{c,i}) (D_{c,i}) (W_{c,i}) \quad (Eq. 1A)$$

Where:

A_C = Total mass of organic HAP in the coatings used in the controlled coating operation during the month, kg.

$Vol_{c,i}$ = Total volume of coating, i, used during the month, liters.

$D_{c,i}$ = Density of coating, i, kg per liter.

$W_{c,i}$ = Mass fraction of organic HAP in coating, i, kg per kg. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

m = Number of different coatings used.

(2) Calculate the mass of organic HAP in the thinners and/or other additives used in the controlled coating operation, kg (lb), using Equation 1B of this section:

$$B_C = \sum_{j=1}^n (Vol_{t,j}) (D_{t,j}) (W_{t,j}) \quad (Eq. 1B)$$

Where:

B_C = Total mass of organic HAP in the thinners and/or other additives used in the controlled coating operation during the month, kg.

$Vol_{t,j}$ = Total volume of thinner and/or other additive, j, used during the month, liters.

$D_{t,j}$ = Density of thinner and/or other additive, j, kg per liter.

$W_{t,j}$ = Mass fraction of organic HAP in thinner and/or other additive, j, kg per kg. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

n = Number of different thinners and/or other additives used.

(3) Calculate the mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg (lb), using Equation 1C of this section:

$$C_C = \sum_{k=1}^p (Vol_{s,k}) (D_{s,k}) (W_{s,k}) \quad (Eq. 1C)$$

Where:

C_C = Total mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg.

$Vol_{s,k}$ = Total volume of cleaning material, k, used during the month, liters.

$D_{s,k}$ = Density of cleaning material, k, kg per liter.

$W_{s,k}$ = Mass fraction of organic HAP in cleaning material, k, kg per kg.

p = Number of different cleaning materials used.

(4) Calculate the mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used in the controlled coating operation during deviations specified in §63.3963(c) and (d), using Equation 1D of this section:

$$H_{TWC} = \sum_{k=1}^q (Vol_k) (D_k) (W_k) \quad (Eq. 1D)$$

Where:

H_{UNC} = Total mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used during all deviations specified in §63.3963(c) and (d) that occurred during the month in the controlled coating operation, kg.

Vol_h = Total volume of coating, thinner and/or other additive, or cleaning material, h, used in the controlled coating operation during deviations, liters.

D_h = Density of coating, thinner and/or other additives, or cleaning material, h, kg per liter.

W_h = Mass fraction of organic HAP in coating, thinner and/or other additives, or cleaning material, h, kg organic HAP per kg coating. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

q = Number of different coatings, thinners and/or other additives, and cleaning materials used.

(i) [Reserved]

(j) ****

§ 63.3963 How do I demonstrate continuous compliance with the emission limitations?

(a) To demonstrate continuous compliance with the applicable emission limit in §63.3890, the organic HAP emission rate for each compliance period, determined according to the procedures in §63.3961, must be equal to or less than the applicable emission limit in §63.3890. A compliance period consists of 12 months. Each month after the end of the initial compliance period described in §63.3960 is the end of a compliance period consisting of that month and the preceding 11 months. You must perform the calculations in §63.3961 on a monthly basis using data from the previous 12 months of operation. If you are complying with a facility-specific emission limit under §63.3890(c), you must also perform the calculation using Equation 1 in §63.3890(c)(2) on a monthly basis using the data from the previous 12 months of operation.

(b) If the organic HAP emission rate for any 12-month compliance period exceeded the applicable emission limit in §63.3890, this is a deviation from the emission limitation for that compliance period that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(c) You must demonstrate continuous compliance with each operating limit required by §63.3892 that applies to you, as specified in Table 1 to this subpart, when the coating line is in operation.

(1) If an operating parameter is out of the allowed range specified in Table 1 to this subpart, this is a deviation from the operating limit that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(2) If an operating parameter deviates from the operating limit specified in Table 1 to this subpart, then you must assume that the emission capture system and add-on control device were achieving zero efficiency during the time period of the deviation, unless you have other data indicating the actual efficiency of the emission capture system and add-on control device and the use of these data is approved by the Administrator.

(d) You must meet the requirements for bypass lines in §63.3968(b) for controlled coating operations for which you do not conduct liquid-liquid material balances. If any bypass line is opened and emissions are diverted to the atmosphere when the coating operation is running, this is a deviation that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7). For the purposes of completing the compliance calculations specified in §§63.3961(h), you must treat the materials used during a deviation on a controlled coating operation as if they were used on an uncontrolled coating operation for the time period of the deviation as indicated in Equation 1 of §63.3961.

(e) You must demonstrate continuous compliance with the work practice standards in §63.3893. If you did not develop a work practice plan, or you did not implement the plan, or you did not keep

the records required by §63.3930(k)(8), this is a deviation from the work practice standards that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(f) As part of each semiannual compliance report required in §63.3920, you must identify the coating operation(s) for which you used the emission rate with add-on controls option. If there were no deviations from the emission limitations, submit a statement that you were in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable emission limit in §63.3890, and you achieved the operating limits required by §63.3892 and the work practice standards required by §63.3893 during each compliance period.

(g) [Reserved]

(h) [Reserved]

(i) [Reserved]

(j) You must maintain records as specified in §§63.3930 and 63.3931.

(k) *Calculate the total volume of coating solids used.* Determine the total volume of coating solids used, liters, which is the combined volume of coating solids for all the coatings used during each month in the coating operation or group of coating operations for which you use the emission rate with add-on controls option, using Equation 2 of §63.3951.

(l) *Calculate the mass of organic HAP emissions for each month.* Determine the mass of organic HAP emissions, kg, during each month, using Equation 4 of this section:

$$H_{HAP} = H_e - \sum_{i=1}^q (H_{c,i}) - \sum_{j=1}^r (H_{CSR,j}) \quad (Eq. 4)$$

where:

H_{HAP} = Total mass of organic HAP emissions for the month, kg.

H_e = Total mass of organic HAP emissions before add-on controls from all the coatings, thinners and/or other additives, and cleaning materials used during the month, kg, determined according to paragraph (f) of this section.

$H_{c,i}$ = Total mass of organic HAP emission reduction for controlled coating operation, i, not using a liquid-liquid material balance, during the month, kg, from Equation 1 of this section.

$H_{CSR,j}$ = Total mass of organic HAP emission reduction for coating operation, j, controlled by a solvent recovery system using a liquid-liquid material balance, during the month, kg, from Equation 3 of this section.

q = Number of controlled coating operations not controlled by a solvent recovery system using a liquid-liquid material balance.

r = Number of coating operations controlled by a solvent recovery system using a liquid-liquid material balance.

(m) *Calculate the organic HAP emission rate for the compliance period.* Determine the organic HAP emission rate for the compliance period, kg (lb) of organic HAP emitted per liter (gal) coating solids used, using Equation 5 of this section:

$$H_{\text{annual}} = \frac{\sum_{y=1}^n H_{HAP,y}}{\sum_{y=1}^n V_{st,y}} \quad (Eq. 5)$$

Where:

H_{annual} = Organic HAP emission rate for the compliance period, kg organic HAP emitted per liter coating solids used.

$H_{\text{HAP},y}$ = Organic HAP emissions for month, y, kg, determined according to Equation 4 of this section.

$V_{\text{st},y}$ = Total volume of coating solids used during month, y, liters, from Equation 2 of §63.3951.

y = Identifier for months.

n = Number of full or partial months in the compliance period (for the initial compliance period, n equals 12 if the compliance date falls on the first day of a month; otherwise n equals 13; for all following compliance periods, n equals 12).

(n) **Compliance demonstration.** The organic HAP emission rate for the initial compliance period, calculated using Equation 5 of this section, must be less than or equal to the applicable emission limit for each subcategory in §63.3890 or the predominant activity or facility-specific emission limit allowed in §63.3890(c). You must keep all records as required by §§63.3930 and 63.3931. As part of the notification of compliance status required by §63.3910, you must identify the coating operation(s) for which you used the emission rate with add-on controls option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because the organic HAP emission rate was less than or equal to the applicable emission limit in §63.3890, and you achieved the operating limits required by §63.3892 and the work practice standards required by §63.3893.

§ 63.3964 What are the general requirements for performance tests?

(a) You must conduct each performance test required by §63.3960 according to the requirements in §63.7(e)(1) and under the conditions in this section, unless you obtain a waiver of the performance test according to the provisions in §63.7(h).

(1) **Representative coating operation operating conditions.** You must conduct the performance test under representative operating conditions for the coating operation. Operations during periods of startup, shutdown, or malfunction and during periods of nonoperation do not constitute representative conditions. You must record the process information that is necessary to document operating conditions during the test and explain why the conditions represent normal operation.

(2) **Representative emission capture system and add-on control device operating conditions.** You must conduct the performance test when the emission capture system and add-on control device are operating at a representative flow rate, and the add-on control device is operating at a representative inlet concentration. You must record information that is necessary to document emission capture system and add-on control device operating conditions during the test and explain why the conditions represent normal operation.

(b) You must conduct each performance test of an emission capture system according to the requirements in §63.3965. You must conduct each performance test of an add-on control device according to the requirements in §63.3966.

§ 63.3965 How do I determine the emission capture system efficiency?

You must use the procedures and test methods in this section to determine capture efficiency as part of the performance test required by §63.3960.

(a) **Assuming 100 percent capture efficiency.** You may assume the capture system efficiency is 100 percent if both of the conditions in paragraphs (a)(1) and (2) of this section are met:

(1) The capture system meets the criteria in Method 204 of appendix M to 40 CFR part 51 for a PTE and directs all the exhaust gases from the enclosure to an add-on control device.

(2) All coatings, thinners and/or other additives, and cleaning materials used in the coating operation are applied within the capture system; coating solvent flash-off, curing, and drying

occurs within the capture system; and the removal or evaporation of cleaning materials from the surfaces they are applied to occurs within the capture system. For example, this criterion is not met if parts enter the open shop environment when being moved between a spray booth and a curing oven.

(b) *Measuring capture efficiency.* If the capture system does not meet both of the criteria in paragraphs (a)(1) and (2) of this section, then you must use one of the three protocols described in paragraphs (c), (d), and (e) of this section to measure capture efficiency. The capture efficiency measurements use TVH capture efficiency as a surrogate for organic HAP capture efficiency. For the protocols in paragraphs (c) and (d) of this section, the capture efficiency measurement must consist of three test runs. Each test run must be at least 3 hours duration or the length of a production run, whichever is longer, up to 8 hours. For the purposes of this test, a production run means the time required for a single part to go from the beginning to the end of the production, which includes surface preparation activities and drying and curing time.

(c) *Liquid-to-uncaptured-gas protocol using a temporary total enclosure or building enclosure.* The liquid-to-uncaptured-gas protocol compares the mass of liquid TVH in materials used in the coating operation to the mass of TVH emissions not captured by the emission capture system. Use a temporary total enclosure or a building enclosure and the procedures in paragraphs (c)(1) through (6) of this section to measure emission capture system efficiency using the liquid-to-uncaptured-gas protocol.

(1) Either use a building enclosure or construct an enclosure around the coating operation where coatings, thinners and/or other additives, and cleaning materials are applied, and all areas where emissions from these applied coatings and materials subsequently occur, such as flash-off, curing, and drying areas. The areas of the coating operation where capture devices collect emissions for routing to an add-on control device, such as the entrance and exit areas of an oven or spray booth, must also be inside the enclosure. The enclosure must meet the applicable definition of a temporary total enclosure or building enclosure in Method 204 of appendix M to 40 CFR part 51.

(2) Use Method 204A or 204F of appendix M to 40 CFR part 51 to determine the mass fraction of TVH liquid input from each coating, thinner and/or other additive, and cleaning material used in the coating operation during each capture efficiency test run. To make the determination, substitute TVH for each occurrence of the term VOC in the methods.

(3) Use Equation 1 of this section to calculate the total mass of TVH liquid input from all the coatings, thinners and/or other additives, and cleaning materials used in the coating operation during each capture efficiency test run:

$$TVH_{used} = \sum_{i=1}^n (TVH_i)(Vol_i)(D_i) \quad (Eq. 1)$$

Where:

TVH_{used} = Mass of liquid TVH in materials used in the coating operation during the capture efficiency test run, kg.

TVH_i = Mass fraction of TVH in coating, thinner and/or other additive, or cleaning material, i, that is used in the coating operation during the capture efficiency test run, kg TVH per kg material.

Vol_i = Total volume of coating, thinner and/or other additive, or cleaning material, i, used in the coating operation during the capture efficiency test run, liters.

D_i = Density of coating, thinner and/or other additive, or cleaning material, i, kg material per liter material.

n = Number of different coatings, thinners and/or other additives, and cleaning materials used in the coating operation during the capture efficiency test run.

(4) Use Method 204D or 204E of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions that are not captured by the emission capture system. They are measured as they exit the temporary total enclosure or building enclosure during each capture efficiency test run. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) Use Method 204D of appendix M to 40 CFR part 51 if the enclosure is a temporary total enclosure.

(ii) Use Method 204E of appendix M to 40 CFR 51 if the enclosure is a building enclosure. During the capture efficiency measurement, all organic compound emitting operations inside the building enclosure, other than the coating operation for which capture efficiency is being determined, must be shut down, but all fans and blowers must be operating normally.

(5) For each capture efficiency test run, determine the percent capture efficiency of the emission capture system using Equation 2 of this section:

$$CE = \frac{(TVH_{used} - TVH_{uncaptured})}{TVH_{used}} \times 100 \quad (\text{Eq. 2})$$

Where:

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent.

TVH_{used} = Total mass of TVH liquid input used in the coating operation during the capture efficiency test run, kg.

TVH_{uncaptured} = Total mass of TVH that is not captured by the emission capture system and that exits from the temporary total enclosure or building enclosure during the capture efficiency test run, kg.

(6) Determine the capture efficiency of the emission capture system as the average of the capture efficiencies measured in the three test runs.

(d) *Gas-to-gas protocol using a temporary total enclosure or a building enclosure.* The gas-to-gas protocol compares the mass of TVH emissions captured by the emission capture system to the mass of TVH emissions not captured. Use a temporary total enclosure or a building enclosure and the procedures in paragraphs (d)(1) through (5) of this section to measure emission capture system efficiency using the gas-to-gas protocol.

(1) Either use a building enclosure or construct an enclosure around the coating operation where coatings, thinners and/or other additives, and cleaning materials are applied, and all areas where emissions from these applied coatings and materials subsequently occur, such as flash-off, curing, and drying areas. The areas of the coating operation where capture devices collect emissions generated by the coating operation for routing to an add-on control device, such as the entrance and exit areas of an oven or a spray booth, must also be inside the enclosure. The enclosure must meet the applicable definition of a temporary total enclosure or building enclosure in Method 204 of appendix M to 40 CFR part 51.

(2) Use Method 204B or 204C of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions captured by the emission capture system during each capture efficiency test run as measured at the inlet to the add-on control device. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) The sampling points for the Method 204B or 204C measurement must be upstream from the add-on control device and must represent total emissions routed from the capture system and entering the add-on control device.

(ii) If multiple emission streams from the capture system enter the add-on control device without a single common duct, then the emissions entering the add-on control device must be

simultaneously measured in each duct and the total emissions entering the add-on control device must be determined.

(3) Use Method 204D or 204E of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions that are not captured by the emission capture system; they are measured as they exit the temporary total enclosure or building enclosure during each capture efficiency test run. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) Use Method 204D of appendix M to 40 CFR part 51 if the enclosure is a temporary total enclosure.

(ii) Use Method 204E of appendix M to 40 CFR part 51 if the enclosure is a building enclosure. During the capture efficiency measurement, all organic compound emitting operations inside the building enclosure, other than the coating operation for which capture efficiency is being determined, must be shut down, but all fans and blowers must be operating normally.

(4) For each capture efficiency test run, determine the percent capture efficiency of the emission capture system using Equation 3 of this section:

$$CE = \frac{TVH_{\text{captured}}}{(TVH_{\text{captured}} + TVH_{\text{uncaptured}})} \times 100 \quad (\text{Eq. 3})$$

Where:

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent.

TVH_{captured} = Total mass of TVH captured by the emission capture system as measured at the inlet to the add-on control device during the emission capture efficiency test run, kg.

$TVH_{\text{uncaptured}}$ = Total mass of TVH that is not captured by the emission capture system and that exits from the temporary total enclosure or building enclosure during the capture efficiency test run, kg.

(5) Determine the capture efficiency of the emission capture system as the average of the capture efficiencies measured in the three test runs.

(e) *Alternative capture efficiency protocol.* As an alternative to the procedures specified in paragraphs (c) and (d) of this section and subject to the approval of the Administrator, you may determine capture efficiency using any other capture efficiency protocol and test methods that satisfy the criteria of either the DQO or LCL approach as described in appendix A to subpart KK of this part.

§ 63.3966 How do I determine the add-on control device emission destruction or removal efficiency?

You must use the procedures and test methods in this section to determine the add-on control device emission destruction or removal efficiency as part of the performance test required by §63.3960. You must conduct three test runs as specified in §63.7(e)(3) and each test run must last at least 1 hour. If the source is a magnet wire coating machine, you may use the procedures in section 3.0 of appendix A to this subpart as an alternative.

(a) For all types of add-on control devices, use the test methods specified in paragraphs (a)(1) through (5) of this section.

(1) Use Method 1 or 1A of appendix A to 40 CFR part 60, as appropriate, to select sampling sites and velocity traverse points.

(2) Use Method 2, 2A, 2C, 2D, 2F, or 2G of appendix A to 40 CFR part 60, as appropriate, to measure gas volumetric flow rate.

(3) Use Method 3, 3A, or 3B of appendix A to 40 CFR part 60, as appropriate, for gas analysis to determine dry molecular weight.

(4) Use Method 4 of appendix A to 40 CFR part 60, to determine stack gas moisture.

(5) Methods for determining gas volumetric flow rate, dry molecular weight, and stack gas moisture must be performed, as applicable, during each test run.

(b) Measure total gaseous organic mass emissions as carbon at the inlet and outlet of the add-on control device simultaneously, using either Method 25 or 25A of appendix A to 40 CFR part 60.

(1) Use Method 25 if the add-on control device is an oxidizer and you expect the total gaseous organic concentration as carbon to be more than 50 parts per million (ppm) at the control device outlet.

(2) Use Method 25A if the add-on control device is an oxidizer and you expect the total gaseous organic concentration as carbon to be 50 ppm or less at the control device outlet.

(3) Use Method 25A if the add-on control device is not an oxidizer.

(c) If two or more add-on control devices are used for the same emission stream, then you must measure emissions at the outlet to the atmosphere of each device. For example, if one add-on control device is a concentrator with an outlet to the atmosphere for the high-volume dilute stream that has been treated by the concentrator, and a second add-on control device is an oxidizer with an outlet to the atmosphere for the low-volume concentrated stream that is treated with the oxidizer, you must measure emissions at the outlet of the oxidizer and the high volume dilute stream outlet of the concentrator.

(d) For each test run, determine the total gaseous organic emissions mass flow rates for the inlet and the outlet of the add-on control device, using Equation 1 of this section. If there is more than one inlet or outlet to the add-on control device, you must calculate the total gaseous organic mass flow rate using Equation 1 of this section for each inlet and each outlet and then total all of the inlet emissions and total all of the outlet emissions:

$$M_f = Q_{sd} C_c (12) (0.0416) (10^{-6}) \quad (\text{Eq. 1})$$

Where:

M_f = Total gaseous organic emissions mass flow rate, kg per hour (h).

C_c = Concentration of organic compounds as carbon in the vent gas, as determined by Method 25 or Method 25A, parts per million by volume (ppmv), dry basis.

Q_{sd} = Volumetric flow rate of gases entering or exiting the add-on control device, as determined by Method 2, 2A, 2C, 2D, 2F, or 2G, dry standard cubic meters/hour (dscm/h).

0.0416 = Conversion factor for molar volume, kg-moles per cubic meter (mol/m^3) (@ 293 Kelvin (K) and 760 millimeters of mercury (mmHg)).

(e) For each test run, determine the add-on control device organic emissions destruction or removal efficiency, using Equation 2 of this section:

$$DRE = \frac{M_{fi} - M_{fo}}{M_{fi}} \times 100 \quad (\text{Eq. 2})$$

Where:

DRE = Organic emissions destruction or removal efficiency of the add-on control device, percent.

M_{fi} = Total gaseous organic emissions mass flow rate at the inlet(s) to the add-on control device, using Equation 1 of this section, kg/h.

M_{fo} = Total gaseous organic emissions mass flow rate at the outlet(s) of the add-on control device, using Equation 1 of this section, kg/h.

(f) Determine the emission destruction or removal efficiency of the add-on control device as the average of the efficiencies determined in the three test runs and calculated in Equation 2 of this section.

§ 63.3967 How do I establish the emission capture system and add-on control device operating limits during the performance test?

During the performance test required by §63.3960 and described in §§63.3964, 63.3965, and 63.3966, you must establish the operating limits required by §63.3892 according to this section, unless you have received approval for alternative monitoring and operating limits under §63.8(f) as specified in §63.3892.

(a) *Thermal oxidizers.* If your add-on control device is a thermal oxidizer, establish the operating limits according to paragraphs (a)(1) and (2) of this section.

(1) During the performance test, you must monitor and record the combustion temperature at least once every 15 minutes during each of the three test runs. You must monitor the temperature in the firebox of the thermal oxidizer or immediately downstream of the firebox before any substantial heat exchange occurs.

(2) Use the data collected during the performance test to calculate and record the average combustion temperature maintained during the performance test. This average combustion temperature is the minimum operating limit for your thermal oxidizer.

(b) *Catalytic oxidizers.* If your add-on control device is a catalytic oxidizer, establish the operating limits according to either paragraphs (b)(1) and (2) or paragraphs (b)(3) and (4) of this section. If the source is a magnet wire coating machine, you may use the procedures in section 3.0 of appendix A to this subpart as an alternative.

(1) During the performance test, you must monitor and record the temperature just before the catalyst bed and the temperature difference across the catalyst bed at least once every 15 minutes during each of the three test runs.

(2) Use the data collected during the performance test to calculate and record the average temperature just before the catalyst bed and the average temperature difference across the catalyst bed maintained during the performance test. These are the minimum operating limits for your catalytic oxidizer.

(3) You must monitor the temperature at the inlet to the catalyst bed and implement a site-specific inspection and maintenance plan for your catalytic oxidizer as specified in paragraph (b)(4) of this section. During the performance test, you must monitor and record the temperature just before the catalyst bed at least once every 15 minutes during each of the three test runs. Use the data collected during the performance test to calculate and record the average temperature just before the catalyst bed during the performance test. This is the minimum operating limit for your catalytic oxidizer.

(4) You must develop and implement an inspection and maintenance plan for your catalytic oxidizer(s) for which you elect to monitor according to paragraph (b)(3) of this section. The plan must address, at a minimum, the elements specified in paragraphs (b)(4)(i) through (iii) of this section.

(i) Annual sampling and analysis of the catalyst activity (*i.e.*, conversion efficiency) following the manufacturer's or catalyst supplier's recommended procedures. If problems are found during the catalyst activity test, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations.

(ii) Monthly external inspection of the catalytic oxidizer system, including the burner assembly and fuel supply lines for problems and, as necessary, adjust the equipment to assure proper air-to-fuel mixtures.

(iii) Annual internal inspection of the catalyst bed to check for channeling, abrasion, and settling. If problems are found during the annual internal inspection of the catalyst, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations. If the catalyst bed is replaced and is not of like or better kind and quality as the old catalyst then you must conduct a new performance test to determine destruction efficiency according to §63.3966. If a catalyst bed is replaced and the replacement catalyst is of like or better kind and quality as the old catalyst, then a new performance test to determine destruction efficiency is not required and you may continue to use the previously established operating limits for that catalytic oxidizer.

(f) *Emission capture systems.* For each capture device that is not part of a PTE that meets the criteria of §63.3965(a), establish an operating limit for either the gas volumetric flow rate or duct static pressure, as specified in paragraphs (f)(1) and (2) of this section. The operating limit for a PTE is specified in Table 1 to this subpart. If the source is a magnet wire coating machine, you may use the procedures in section 2.0 of appendix A to this subpart as an alternative.

(1) During the capture efficiency determination required by §63.3960 and described in §§63.3964 and 63.3965, you must monitor and record either the gas volumetric flow rate or the duct static pressure for each separate capture device in your emission capture system at least once every 15 minutes during each of the three test runs at a point in the duct between the capture device and the add-on control device inlet.

(2) Calculate and record the average gas volumetric flow rate or duct static pressure for the three test runs for each capture device. This average gas volumetric flow rate or duct static pressure is the minimum operating limit for that specific capture device.

§ 63.3968 What are the requirements for continuous parameter monitoring system installation, operation, and maintenance?

(a) *General.* You must install, operate, and maintain each CPMS specified in paragraphs (c), (e), (f), and (g) of this section according to paragraphs (a)(1) through (6) of this section. You must install, operate, and maintain each CPMS specified in paragraphs (b) and (d) of this section according to paragraphs (a)(3) through (5) of this section.

(1) The CPMS must complete a minimum of one cycle of operation for each successive 15-minute period. You must have a minimum of four equally spaced successive cycles of CPMS operation in 1 hour.

(2) You must determine the average of all recorded readings for each successive 3-hour period of the emission capture system and add-on control device operation.

(3) You must record the results of each inspection, calibration, and validation check of the CPMS.

(4) You must maintain the CPMS at all times and have available necessary parts for routine repairs of the monitoring equipment.

(5) You must operate the CPMS and collect emission capture system and add-on control device parameter data at all times that a controlled coating operation is operating, except during monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, if applicable, calibration checks and required zero and span adjustments).

(6) You must not use emission capture system or add-on control device parameter data recorded during monitoring malfunctions, associated repairs, out-of-control periods, or required quality assurance or control activities when calculating data averages. You must use all the data collected during all other periods in calculating the data averages for determining compliance with the emission capture system and add-on control device operating limits.

(7) A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the CPMS to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions. Any period for which the monitoring system is out-of-

control and data are not available for required calculations is a deviation from the monitoring requirements.

(b) Capture system bypass line. You must meet the requirements of paragraphs (b)(1) and (2) of this section for each emission capture system that contains bypass lines that could divert emissions away from the add-on control device to the atmosphere.

(1) You must monitor or secure the valve or closure mechanism controlling the bypass line in a nondiverting position in such a way that the valve or closure mechanism cannot be opened without creating a record that the valve was opened. The method used to monitor or secure the valve or closure mechanism must meet one of the requirements specified in paragraphs (b)(1)(i) through (v) of this section.

(i) Flow control position indicator. Install, calibrate, maintain, and operate according to the manufacturer's specifications a flow control position indicator that takes a reading at least once every 15 minutes and provides a record indicating whether the emissions are directed to the add-on control device or diverted from the add-on control device. The time of occurrence and flow control position must be recorded, as well as every time the flow direction is changed. The flow control position indicator must be installed at the entrance to any bypass line that could divert the emissions away from the add-on control device to the atmosphere.

(ii) Car-seal or lock-and-key valve closures. Secure any bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. You must visually inspect the seal or closure mechanism at least once every month to ensure that the valve is maintained in the closed position, and the emissions are not diverted away from the add-on control device to the atmosphere.

(iii) Valve closure monitoring. Ensure that any bypass line valve is in the closed (nondiverting) position through monitoring of valve position at least once every 15 minutes. You must inspect the monitoring system at least once every month to verify that the monitor will indicate valve position.

(iv) Automatic shutdown system. Use an automatic shutdown system in which the coating operation is stopped when flow is diverted by the bypass line away from the add-on control device to the atmosphere when the coating operation is running. You must inspect the automatic shutdown system at least once every month to verify that it will detect diversions of flow and shut down the coating operation.

(v) Flow direction indicator. Install, calibrate, maintain, and operate according to the manufacturer's specifications a flow direction indicator that takes a reading at least once every 15 minutes and provides a record indicating whether the emissions are directed to the add-on control device or diverted from the add-on control device. Each time the flow direction changes, the next reading of the time of occurrence and flow direction must be recorded. The flow direction indicator must be installed in each bypass line or air makeup supply line that could divert the emissions away from the add-on control device to the atmosphere.

(2) If any bypass line is opened, you must include a description of why the bypass line was opened and the length of time it remained open in the semiannual compliance reports required in §63.3920.

(c) Thermal oxidizers and catalytic oxidizers. If you are using a thermal oxidizer or catalytic oxidizer as an add-on control device (including those used with concentrators or with carbon adsorbers to treat desorbed concentrate streams), you must comply with the requirements in paragraphs (c)(1) through (3) of this section:

(1) For a thermal oxidizer, install a gas temperature monitor in the firebox of the thermal oxidizer or in the duct immediately downstream of the firebox before any substantial heat exchange occurs.

(2) For a catalytic oxidizer, install gas temperature monitors upstream and/or downstream of the catalyst bed as required in §63.3967(b).

(3) For all thermal oxidizers and catalytic oxidizers, you must meet the requirements in paragraphs (a) and (c)(3)(i) through (v) of this section for each gas temperature monitoring device.

- (i) Locate the temperature sensor in a position that provides a representative temperature.**
- (ii) Use a temperature sensor with a measurement sensitivity of 5 degrees Fahrenheit or 1.0 percent of the temperature value, whichever is larger.**
- (iii) Before using the sensor for the first time or when relocating or replacing the sensor, perform a validation check by comparing the sensor output to a calibrated temperature measurement device or by comparing the sensor output to a simulated temperature.**
- (iv) Conduct an accuracy audit every quarter and after every deviation. Accuracy audit methods include comparisons of sensor output to redundant temperature sensors, to calibrated temperature measurement devices, or to temperature simulation devices.**
- (v) Conduct a visual inspection of each sensor every quarter if redundant temperature sensors are not used.**
- (d) *******
- (e) *******
- (f) *******
- (g) *Emission capture systems.* The capture system monitoring system must comply with the applicable requirements in paragraphs (g)(1) and (2) of this section. If the source is a magnet wire coating machine, you may use the procedures in section 2.0 of appendix A to this subpart as an alternative.**
- (1) For each flow measurement device, you must meet the requirements in paragraphs (a) and (g)(1)(i) through (vii) of this section.**
 - (i) Locate a flow sensor in a position that provides a representative flow measurement in the duct from each capture device in the emission capture system to the add-on control device.**
 - (ii) Use a flow sensor with an accuracy of at least 10 percent of the flow.**
 - (iii) Perform an initial sensor calibration in accordance with the manufacturer's requirements.**
 - (iv) Perform a validation check before initial use or upon relocation or replacement of a sensor. Validation checks include comparison of sensor values with electronic signal simulations or via relative accuracy testing.**
 - (v) Conduct an accuracy audit every quarter and after every deviation. Accuracy audit methods include comparisons of sensor values with electronic signal simulations or via relative accuracy testing.**
 - (vi) Perform leak checks monthly.**
 - (vii) Perform visual inspections of the sensor system quarterly if there is no redundant sensor.**
- (2) For each pressure drop measurement device, you must comply with the requirements in paragraphs (a) and (g)(2)(i) through (vii) of this section.**
 - (i) Locate the pressure sensor(s) in or as close to a position that provides a representative measurement of the pressure drop across each opening you are monitoring.**
 - (ii) Use a pressure sensor with an accuracy of at least 0.5 inches of water column or 5 percent of the measured value, whichever is larger.**
 - (iii) Perform an initial calibration of the sensor according to the manufacturer's requirements.**

(iv) Conduct a validation check before initial operation or upon relocation or replacement of a sensor. Validation checks include comparison of sensor values to calibrated pressure measurement devices or to pressure simulation using calibrated pressure sources.

(v) Conduct accuracy audits every quarter and after every deviation. Accuracy audits include comparison of sensor values to calibrated pressure measurement devices or to pressure simulation using calibrated pressure sources.

(vi) Perform monthly leak checks on pressure connections. A pressure of at least 1.0 inches of water column to the connection must yield a stable sensor result for at least 15 seconds.

(vii) Perform a visual inspection of the sensor at least monthly if there is no redundant sensor.

§ 63.3980 Who implements and enforces this subpart?

(a) This subpart can be implemented and enforced by us, the U.S. Environmental Protection Agency (EPA), or a delegated authority such as your State, local, or tribal agency. If the Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the EPA) has the authority to implement and enforce this subpart. You should contact your EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are listed in paragraphs (c)(1) through (4) of this section:

(1) Approval of alternatives to the requirements in §63.3881 through 3883 and §63.3890 through 3893.

(2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.

(3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.

(4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

§ 63.3981 What definitions apply to this subpart?

Terms used in this subpart are defined in the CAA, in 40 CFR 63.2, and in this section as follows:

Additive means a material that is added to a coating after purchase from a supplier (e.g., catalysts, activators, accelerators).

Add-on control means an air pollution control device, such as a thermal oxidizer or carbon adsorber, that reduces pollution in an air stream by destruction or removal before discharge to the atmosphere.

Adhesive, adhesive coating means any chemical substance that is applied for the purpose of bonding two surfaces together. Products used on humans and animals, adhesive tape, contact paper, or any other product with an adhesive incorporated onto or in an inert substrate shall not be considered adhesives under this subpart.

Assembled on-road vehicle coating means any coating operation in which coating is applied to the surface of some component or surface of a fully assembled motor vehicle or trailer intended for on-road use including, but not limited to, components or surfaces on automobiles and light-duty trucks that have been repaired after a collision or otherwise repainted, fleet delivery trucks, and motor homes and other recreational vehicles (including camping trailers and fifth wheels). Assembled on-road vehicle coating includes the concurrent coating of parts of the assembled on-road vehicle that are painted off-vehicle to protect systems, equipment, or to allow full coverage.

Assembled on-road vehicle coating does not include surface coating operations that meet the applicability criteria of the automobiles and light-duty trucks NESHAP. Assembled on-road vehicle coating also does not include the use of adhesives, sealants, and caulks used in assembling on-road vehicles.

***Capture device* means a hood, enclosure, room, floor sweep, or other means of containing or collecting emissions and directing those emissions into an add-on air pollution control device.**

***Capture efficiency or capture system efficiency* means the portion (expressed as a percentage) of the pollutants from an emission source that is delivered to an add-on control device.**

***Capture system* means one or more capture devices intended to collect emissions generated by a coating operation in the use of coatings or cleaning materials, both at the point of application and at subsequent points where emissions from the coatings and cleaning materials occur, such as flashoff, drying, or curing. As used in this subpart, multiple capture devices that collect emissions generated by a coating operation are considered a single capture system.**

***Cleaning material* means a solvent used to remove contaminants and other materials, such as dirt, grease, oil, and dried or wet coating (e.g., depainting or paint stripping), from a substrate before or after coating application or from equipment associated with a coating operation, such as spray booths, spray guns, racks, tanks, and hangers. Thus, it includes any cleaning material used on substrates or equipment or both.**

***Coating* means a material applied to a substrate for decorative, protective, or functional purposes. Such materials include, but are not limited to, paints, sealants, liquid plastic coatings, caulks, inks, adhesives, and maskants. Decorative, protective, or functional materials that consist only of protective oils for metal, acids, bases, or any combination of these substances, or paper film or plastic film which may be pre-coated with an adhesive by the film manufacturer, are not considered coatings for the purposes of this subpart. A liquid plastic coating means a coating made from fine particle-size polyvinyl chloride (PVC) in solution (also referred to as a plastisol).**

***Coating operation* means equipment used to apply cleaning materials to a substrate to prepare it for coating application (surface preparation) or to remove dried coating; to apply coating to a substrate (coating application) and to dry or cure the coating after application; or to clean coating operation equipment (equipment cleaning). A single coating operation may include any combination of these types of equipment, but always includes at least the point at which a given quantity of coating or cleaning material is applied to a given part and all subsequent points in the affected source where organic HAP are emitted from the specific quantity of coating or cleaning material on the specific part. There may be multiple coating operations in an affected source. Coating application with handheld, non-refillable aerosol containers, touch-up markers, or marking pens is not a coating operation for the purposes of this subpart.**

***Coatings solids* means the nonvolatile portion of the coating that makes up the dry film.**

***Continuous parameter monitoring system (CPMS)* means the total equipment that may be required to meet the data acquisition and availability requirements of this subpart, used to sample, condition (if applicable), analyze, and provide a record of coating operation, or capture system, or add-on control device parameters.**

***Controlled coating operation* means a coating operation from which some or all of the organic HAP emissions are routed through an emission capture system and add-on control device.**

***Deviation* means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:**

- (1) Fails to meet any requirement or obligation established by this subpart including but not limited to, any emission limit or operating limit or work practice standard;**
- (2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or**

(3) Fails to meet any emission limit, or operating limit, or work practice standard in this subpart during startup, shutdown, or malfunction, regardless of whether or not such failure is permitted by this subpart.

Emission limitation means the aggregate of all requirements associated with a compliance option including emission limit, operating limit, work practice standard, etc.

Enclosure means a structure that surrounds a source of emissions and captures and directs the emissions to an add-on control device.

Exempt compound means a specific compound that is not considered a VOC due to negligible photochemical reactivity. The exempt compounds are listed in 40 CFR 51.100(s).

Extreme performance fluoropolymer coating means coatings that are formulated systems based on fluoropolymer resins which often contain bonding matrix polymers dissolved in non-aqueous solvents as well as other ingredients. Extreme performance fluoropolymer coatings are typically used when one or more critical performance criteria are required including, but not limited to a nonstick low-energy surface, dry film lubrication, high resistance to chemical attack, extremely wide operating temperature, high electrical insulating properties, or that the surface comply with government (e.g., USDA, FDA) or third party specifications for health, safety, reliability, or performance. Once applied to a substrate, extreme performance fluoropolymer coatings undergo a curing process that typically requires high temperatures, a chemical reaction, or other specialized technology.

Facility maintenance means the routine repair or renovation (including the surface coating) of the tools, equipment, machinery, and structures that comprise the infrastructure of the affected facility and that are necessary for the facility to function in its intended capacity.

General use coating means any material that meets the definition of coating but does not meet the definition of high performance coating, rubber-to-metal coating, magnet wire coating, or extreme performance fluoropolymer coating as defined in this section.

High performance architectural coating means any coating applied to architectural subsections which is required to meet the specifications of Architectural Aluminum Manufacturer's Association's publication number AAMA 605.2-2000.

High performance coating means any coating that meets the definition of high performance architectural coating or high temperature coating in this section.

High temperature coating means any coating applied to a substrate which during normal use must withstand temperatures of at least 538 degrees Celsius (1000 degrees Fahrenheit).

Hobby shop means any surface coating operation, located at an affected source, that is used exclusively for personal, noncommercial purposes by the affected source's employees or assigned personnel.

Magnet wire coatings, commonly referred to as magnet wire enamels, are applied to a continuous strand of wire which will be used to make turns (windings) in electrical devices such as coils, transformers, or motors. Magnet wire coatings provide high dielectric strength and turn-to-turn conductor insulation. This allows the turns of an electrical device to be placed in close proximity to one another which leads to increased coil effectiveness and electrical efficiency.

Magnet wire coating machine means equipment which applies and cures magnet wire coatings.

Manufacturer's formulation data means data on a material (such as a coating) that are supplied by the material manufacturer based on knowledge of the ingredients used to manufacture that material, rather than based on testing of the material with the test methods specified in §63.3941. Manufacturer's formulation data may include, but are not limited to, information on density, organic HAP content, volatile organic matter content, and coating solids content.

Mass fraction of organic HAP means the ratio of the mass of organic HAP to the mass of a material in which it is contained, expressed as kg of organic HAP per kg of material.

Month means a calendar month or a pre-specified period of 28 days to 35 days to allow for flexibility in recordkeeping when data are based on a business accounting period.

Non-HAP coating means, for the purposes of this subpart, a coating that contains no more than 0.1 percent by mass of any individual organic HAP that is an OSHA-defined carcinogen as specified in 29 CFR 1910.1200(d)(4) and no more than 1.0 percent by mass for any other individual HAP.

Organic HAP content means the mass of organic HAP emitted per volume of coating solids used for a coating calculated using Equation 2 of §63.3941. The organic HAP content is determined for the coating in the condition it is in when received from its manufacturer or supplier and does not account for any alteration after receipt. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, organic HAP content is the mass of organic HAP that is emitted, rather than the organic HAP content of the coating as it is received.

Permanent total enclosure (PTE) means a permanently installed enclosure that meets the criteria of Method 204 of appendix M, 40 CFR part 51, for a PTE and that directs all the exhaust gases from the enclosure to an add-on control device.

Personal watercraft means a vessel (boat) which uses an inboard motor powering a water jet pump as its primary source of motive power and which is designed to be operated by a person or persons sitting, standing, or kneeling on the vessel, rather than in the conventional manner of sitting or standing inside the vessel.

Protective oil means an organic material that is applied to metal for the purpose of providing lubrication or protection from corrosion without forming a solid film. This definition of protective oil includes, but is not limited to, lubricating oils, evaporative oils (including those that evaporate completely), and extrusion oils. Protective oils used on miscellaneous metal parts and products include magnet wire lubricants and soft temporary protective coatings that are removed prior to installation or further assembly of a part or component.

Reactive adhesive means adhesive systems composed, in part, of volatile monomers that react during the adhesive curing reaction, and, as a result, do not evolve from the film during use. These volatile components instead become integral parts of the adhesive through chemical reaction. At least 70 percent of the liquid components of the system, excluding water, react during the process.

Research or laboratory facility means a facility whose primary purpose is for research and development of new processes and products, that is conducted under the close supervision of technically trained personnel, and is not engaged in the manufacture of final or intermediate products for commercial purposes, except in a *de minimis* manner.

Responsible official means responsible official as defined in 40 CFR 70.2.

Rubber-to-metal coatings are coatings that contain heat-activated polymer systems in either solvent or water that, when applied to metal substrates, dry to a non-tacky surface and react chemically with the rubber and metal during a vulcanization process.

Startup, initial means the first time equipment is brought online in a facility.

Surface preparation means use of a cleaning material on a portion of or all of a substrate. This includes use of a cleaning material to remove dried coating, which is sometimes called depainting.

Temporary total enclosure means an enclosure constructed for the purpose of measuring the capture efficiency of pollutants emitted from a given source as defined in Method 204 of appendix M, 40 CFR part 51.

Thinner means an organic solvent that is added to a coating after the coating is received from the supplier.

Total volatile hydrocarbon (TVH) means the total amount of nonaqueous volatile organic matter determined according to Methods 204 and 204A through 204F of appendix M to 40 CFR part 51 and substituting the term TVH each place in the methods where the term VOC is used. The TVH includes both VOC and non-VOC.

Uncontrolled coating operation means a coating operation from which none of the organic HAP emissions are routed through an emission capture system and add-on control device.

Volatile organic compound (VOC) means any compound defined as VOC in 40 CFR 51.100(s).

Volume fraction of coating solids means the ratio of the volume of coating solids (also known as the volume of nonvolatiles) to the volume of a coating in which it is contained; liters (gal) of coating solids per liter (gal) of coating.

Wastewater means water that is generated in a coating operation and is collected, stored, or treated prior to being discarded or discharged.

Table 1 to Subpart MMMM of Part 63—Operating Limits if Using the Emission Rate With Add-On Controls Option

For the following device . . .	You must meet the following operating limit	And you must demonstrate continuous compliance with the operating limit by
1. Thermal oxidizer	a. The average Combustion temperature in any 3-hour period must not fall below the combustion temperature limit established according to §63.3967(a).	i. Collecting the combustion temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average Combustion temperature at or above the temperature limit.
2. Catalytic oxidizer	a. The average Temperature measured just before the catalyst bed in any 3-hour period must not fall below the limit established according to §63.3967(b) (for magnet wire coating machines, temperature can be monitored before or after the catalyst bed); and either b. Ensure that the average temperature difference across the catalyst bed in any 3-hour period does not fall below the temperature difference limit established according to §63.3967(b) (2); or c. Develop and implement an inspection and maintenance plan according to §63.3967(b)(4) or for magnet wire coating machines according to section 3.0 of appendix A to this subpart.	i. Collecting the temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average temperature before (or for magnet wire coating machines after) the catalyst bed at or above the temperature limit. i. Collecting the temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average Temperature difference at or above the temperature difference limit. i. Maintaining and up-to-date inspection and maintenance plan, records of annual catalyst activity checks, records of monthly inspections of the oxidizer system, and records of the annual internal inspections of the catalyst bed. If a problem is discovered during a monthly or annual inspection required by §63.3967(b)(4) or for magnet wire coating machines by section 3.0 of appendix A to this subpart, you must take corrective action as soon as practicable consistent with the manufacturer's recommendations.
3. Regenerative carbon adsorber.	a. The total regeneration desorbing gas (e.g., steam or nitrogen) mass flow for each carbon bed regeneration cycle must not fall below the total regeneration desorbing gas mass flow limit established according to	i. Measuring the total regeneration desorbing gas (e.g., steam or nitrogen) mass flow for each regeneration cycle according to §63.3968(d); and ii. Maintaining the total regeneration desorbing gas mass flow at or above the mass flow limit.

Table 1 to Subpart MMMM of Part 63—Operating Limits if Using the Emission Rate With Add-On Controls Option

For the following device . . .	You must meet the following operating limit	And you must demonstrate continuous compliance with the operating limit by
	<p>§63.3967(c); and</p> <p>b. The temperature of the carbon bed, after completing each regeneration and any cooling cycle, must not exceed the carbon bed temperature limit established according to § 63.3967(c).</p>	<p>i. Measuring the temperature of the carbon bed after completing each regeneration and any cooling cycle according to §63.3968(d); and</p> <p>ii. Operating the carbon beds such that each carbon bed is not returned to service until completing each regeneration and any cooling cycle until the recorded temperature of the carbon bed is at or below the temperature limit.</p>
4. Condenser	<p>a. The average condenser outlet (product side) gas temperature in any 3-hour period must not exceed the temperature limit established according to §63.3967(d).</p>	<p>i. Collecting the condenser outlet (product side) gas Temperature according to §63.3968(e);</p> <p>ii. Reducing the data to 3-hour block averages; and</p> <p>iii. Maintaining the 3-hour average gas temperature at the outlet at or below the temperature limit.</p>
5. Concentrators, including zeolite wheels and rotary carbon adsorbers.	<p>a. The average gas temperature of the desorption concentrate stream in any 3-hour period must not fall below the limit established according to §63.3967(e); and</p> <p>b. The average pressure drop of the dilute stream across the concentrator in any 3-hour period must not fall below the limit established according to §63.3967(e). pressure drop at or above the pressure drop limit.</p>	<p>i. Collecting the temperature data according to 63.3968(f);</p> <p>ii. Reducing the data to 3-hour block averages; and</p> <p>iii. Maintaining the 3-hour average temperature at or above the temperature limit.</p> <p>i. Collecting the pressure drop data according to 63.3968(f);</p> <p>ii. Reducing the pressure drop data to 3-hour block averages; and</p> <p>iii. Maintaining the 3-hour average</p>
6. Emission capture system that is a PTE according to §63.3965(a).	<p>a. The direction of the air flow at all times must be into the enclosure; and either</p> <p>b. The average facial velocity of air through all natural draft openings in the enclosure must be at least 200 feet per minutes; or</p> <p>c. The pressure drop across the enclosure must be at least 0.007 inch H₂O, as established in Method 204 of appendix M to 40 CFR part 51.</p>	<p>i. Collecting the direction of air flow, and either the facial velocity of air through all natural draft openings according to §63.3968(b)(1) or the pressure drop across the enclosure according to §63.3968(g)(2); and</p> <p>ii. Maintaining the facial velocity of air flow through all natural draft openings or the pressure drop at or above the facial velocity limit or pressure drop limit, and maintaining the direction of air flow into the enclosure at all times.</p> <p>i. See items 6.a.i and 6.a.ii.</p> <p>i. See items 6.a.i and 6.a.ii.</p>

Table 1 to Subpart MMMM of Part 63—Operating Limits if Using the Emission Rate With Add-On Controls Option

For the following device . . .	You must meet the following operating limit	And you must demonstrate continuous compliance with the operating limit by
7. Emission capture system that is not a PTE according to §63.3965(a).	a. The average gas volumetric flow rate or duct static pressure in each duct between a capture device and add-on control device inlet in any 3-hour period must not fall below the average volumetric flow rate or duct static pressure limit established for that capture device according to §63.3967(f).	i. Collecting the gas volumetric flow rate or duct static pressure for each capture device according to §63.3968(g); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average gas volumetric flow rate or duct static pressure for each capture device at or above the gas volumetric flow rate or duct static pressure limited.

Table 2 to Subpart MMMM of Part 63—Applicability of General Provisions to Subpart MMMM of Part 63

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.1(a)(1)-(14)	General Applicability.	Yes.	
§ 63.1(b)(1)-(3)	Initial Applicability Determination.	Yes.....	Applicability to subpart MMMM is also specified in §63.3881.
§ 63.1(c)(1)	Applicability After Standard Established.	Yes.	
§ 63.1(c)(2)-(3)	Applicability of Permit Program for Area Sources.	No	Area sources are not subject to subpart MMMM.
§ 63.1(c)(4)-(5)	Extensions and Notifications.	Yes.	
§ 63.1(e)	Applicability of Permit Program Before Relevant Standard is Set.	Yes.	
§ 63.2	Definitions	Yes.....	Additional definitions are specified in §63.3981.
§ 63.1(a)-(c)	Units and Abbreviations.	Yes.	
§ 63.4(a)(1)-(5)	Prohibited Activities.	Yes.	
§ 63.4(b)-(c).	Circumvention/ Severability.	Yes.	
§ 63.5(a)	Construction/ Reconstruction.	Yes.	
§ 63.5(b)(1)-(6)	Requirements for Existing, Newly Constructed, and Reconstructed Sources.	Yes.	
§ 63.5(d)	Application for Approval of Construction/Reconstruction.	Yes.	

Table 2 to Subpart MMMM of Part 63—Applicability of General Provisions to Subpart MMMM of Part 63

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.5(e)	Approval of Construction/Reconstruction.	Yes.	
§ 63.5(f)	Approval of Construction/Reconstruction Based on Prior State Review.	Yes.	
§ 63.6(a)	Compliance With Standards and Maintenance Requirements - Applicability.	Yes.	
§ 63.6(b)(1)-(7).	Compliance Dates for New and Reconstructed Sources	Yes.....	Section 63.3883 specifies the compliance dates.
§ 63.6(c)(1)-(5)	Compliance Dates for Existing Sources.	Yes.....	Section 63.3883 specifies the compliance dates.
§ 63.6(e)(1)-(2)	Operation and Maintenance.	Yes.	
§ 63.6(e)(3)	Startup, Shutdown, and Malfunction Plan.	Yes.....	Only sources using an add-on control device to comply with the standard must complete startup, shutdown, and malfunction plans.
§ 63.6(f)(1)	Compliance Except During Startup, Shutdown, and Malfunction.	Yes.....	Applies only to sources using an add-on control device to comply with the standard.
§ 63.6(f)(2)-(3).	Methods for Determining Compliance..	Yes.	
§ 63.6(g)(1)-(3)	Use of an Alternative Standard.	Yes	
§ 63.6(h)	Compliance With Opacity/Visible Emission Standards	No	Subpart MMMM does not establish opacity standards and does not require continuous opacity monitoring systems (COMS).
§ 63.6(i)(1)-(16)	Extension of Compliance.	Yes.	
§ 63.6(j)	Presidential Compliance Exemption.	Yes.	
§ 63.7(a)(1).	Performance Test Requirements - Applicability.	Yes.....	Applies to all affected sources. Additional requirements for performance testing are specified in §§ 63.3964, 63.3965, and 63.3966.
§ 63.7(a)(2)	Performance Test Requirements - Dates.	Yes.....	Applies only to performance tests for capture system and control device efficiency at sources using these to comply with the standard. Section 63.3960 specifies the schedule for performance test requirements that are earlier than those specified in §63.7(a)(2).

Table 2 to Subpart MMMM of Part 63—Applicability of General Provisions to Subpart MMMM of Part 63

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.7(a)(3).	Performance Tests Required By the Administrator.	Yes.	
§ 63.7(b)-(e)	Performance Test Requirements - Notification, Quality Assurance, Facilities Necessary for Safe Testing, Conditions During Test.	Yes.....	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.7(f)	Performance Test Requirements - Use of Alternative Test Method. efficiency.	Yes.....	Applies to all test methods except those used to determine capture system
§ 63.7(g)-(h)	Performance Test Requirements - Data Analysis, Recordkeeping, Reporting, Waiver of Test.	Yes.....	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.8(a)(1)-(3)	Monitoring Requirements - Applicability.	Yes.....	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for monitoring are specified in §63.3968.
§ 63.8(a)(4)	Additional Monitoring Requirements.	No	Subpart MMMM does not have monitoring requirements for flares.
§ 63.8(b)	Conduct of Monitoring.	Yes.	
§ 63.8(c)(1)-(3)	Continuous Monitoring Systems (CMS) Operation and Maintenance.	Yes.....	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for CMS operations and maintenance are specified in §63.3968.
§ 63.8(c)(4).	CMS	No	§ 63.3968 specifies the requirements for the operation of CMS for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(5)	COMS	No	Subpart MMMM does not have opacity or visible emission standards.
§ 63.8(c)(6).	CMS Requirements	No	Section 63.3968 specifies the requirements for monitoring systems for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(7)	CMS Out-of-Control Periods.	Yes.	
§ 63.8(c)(8).	CMS Out-of-Control Periods and Reporting.	No	§ 63.3920 requires reporting of CMS out-of-control periods.
§ 63.8(d)-(e)	Quality Control Program and CMS Performance Evaluation.	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.

Table 2 to Subpart MMMM of Part 63—Applicability of General Provisions to Subpart MMMM of Part 63

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.8(f)(1)-(5)	Use of an Alternative Monitoring Method.	Yes.	
§ 63.8(f)(6)	Alternative to Relative Accuracy Test.	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§ 63.8(g)(1)-(5)	Data Reduction.	No	Sections 63.3967 and 63.3968 specify monitoring data reduction.
§ 63.9(a)-(d).	Notification Requirements.	Yes.	
§ 63.9(e)	Notification of Performance Test.	Yes.....	Applies only to capture system and add-on control device performance tests at sources using these to comply with the standard.
§ 63.9(f).	Notification of Visible Emissions/Opacity Test.	No	Subpart MMMM does not have opacity or visible emissions standards.
§ 63.9(g)(1)-(3)	Additional Notifications When Using CMS	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§ 63.9(h).	Notification of Compliance Status.	Yes.....	Section 63.3910 specifies the dates for submitting the notification of compliance status.
§ 63.9(i).	Adjustment of Submittal Deadlines.	Yes.	
§ 63.9(j).	Change in Previous Information.	Yes.	
§ 63.10(a).	Recordkeeping/ Reporting Applicability and General Information.	Yes.	
§ 63.10(b)(1).	General Recordkeeping Requirements.	Yes.....	Additional requirements are specified in §§ 63.3930 and 63.3931.
§ 63.10(b)(2) (i)-(v)	Recordkeeping Relevant to Startup, Shutdown, and Malfunction Periods and CMS.	Yes.....	Requirements for startup, shutdown, and malfunction records only apply to add-on control devices used to comply with the standard.
§ 63.10(b)(2) (vi)-(xi)	...	Yes.	
§ 63.10(b)(2) (xii)	Records	Yes.	
§ 63.10(b)(2) (xiii)	...	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§ 63.10(b)(2) (xiv)	...	Yes.	
§ 63.10(b)(3).	Recordkeeping Requirements for Applicability Determinations.	Yes.	

Table 2 to Subpart Mmmm of Part 63—Applicability of General Provisions to Subpart Mmmm of Part 63

Citation	Subject	Applicable to subpart Mmmm	Explanation
§ 63.10(c) (1)-(6)	Additional Recordkeeping Requirements for Sources with CMS.	Yes.	
§ 63.10(c) (7)-(8).	...	No	The same records are required in §63.3920(a)(7).
§ 63.10(c) (9)-(15)	Yes.	
§ 63.10(d)(1)	General Reporting Requirements.	Yes.....	Additional requirements are specified in §63.3920.
§ 63.10(d)(2)	Report of Performance Test Results.	Yes.....	Additional requirements are specified in §63.3920(b).
§ 63.10(d)(3)	Reporting Opacity or Visible Emissions Observations.	No	Subpart Mmmm does not require opacity or visible emissions observations.
§ 63.10(d)(4)..	Progress Reports for Sources With Compliance Extensions.	Yes.	
§ 63.10(d)(5).	Startup, Shutdown, and Malfunction Reports.	Yes.....	Applies only to add-on control devices at sources using these to comply with the standard.
§ 63.10(e) (1)-(2)	Additional CMS Reports	No	Subpart Mmmm does not continuous emissions monitoring systems.
§ 63.10(e) (3).	Excess Emissions/CMS Performance Reports.	No	Section 63.3920 (b) specifies the contents of periodic compliance reports.
§ 63.10(e) (4).	COMS Data Reports	No	Subpart Mmmm does not specify requirements for opacity or COMS.
§ 63.10(f).	Recordkeeping/ Reporting Waiver.	Yes.	
§ 63.11.	Control Device Requirements/Flares.	No	Subpart Mmmm does not specify use of flares for compliance.
§ 63.12	State Authority and Delegations.	Yes.	
§ 63.13..	Addresses	Yes.	
§ 63.14..	Incorporation by Reference.	Yes.	
§ 63.15..	Availability of Information/ Confidentiality.	Yes.	

Table 3 to Subpart Mmmm of Part 63—Default Organic HAP Mass Fraction for Solvents and Solvent Blends

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data and which match either the solvent blend name or the chemical abstract series (CAS) number. If a solvent blend matches both the name and CAS number for an entry, that entry's organic HAP mass fraction must be used for that solvent blend. Otherwise, use the organic HAP mass fraction for the entry matching either the solvent blend name or CAS number, or use the organic HAP mass fraction from table 4 to this subpart if neither the name or CAS number match.

Solvent/solvent blend	CAS. No.	Average organic HAP mass fraction	Typical organic HAP, percent by mass
1. Toluene.....	108-88-3	1.0	Toluene.
2. Xylene(s).....	1330-20-7	1.0	Xylenes, ethylbenzene.
3. Hexane.....	110-54-3	0.5	n-hexane.
4. n-Hexane.....	110-54-3	1.0	n-hexane.
5. Ethylbenzene.....	100-41-4	1.0	Ethylbenzene.
6. Aliphatic 140.....		0	None.
7. Aromatic 100.....		0.02	1% xylene, 1% cumene.
8. Aromatic 150.....		0.09	Naphthalene.
9. Aromatic naphtha.....	64742-95-6	0.02	1% xylene, 1% cumene.
10. Aromatic solvent.....	64742-94-5	0.1	Naphthalene.
11. Exempt mineral spirits.....	8032-32-4	0	None.
12. Lignoines (VM & P).....	8032-32-4	0	None.
13. Lactol spirits.....	64742-89-6	0.15	Toluene.
14. Low aromatic white spirit..	64742-82-1	0	None.
15. Mineral spirits.....	64742-88-7	0.01	Xylenes.
16. Hydrotreated naphtha.....	64742-48-9	0	None.
17. Hydrotreated light distillate.	64742-47-8	0.001	Toluene.
18. Stoddard solvent.....	8052-41-3	0.01	Xylenes.
19. Super high-flash naphtha....	64742-95-6	0.05	Xylenes.
20. Varsol ® solvent.....	8052-49-3	0.01	0.5% xylenes, 0.5% ethylbenzene.
21. VM & P naphtha.....	64742-89-8	0.06	3% toluene, 3% xylene.
22. Petroleum distillate mixture..	68477-31-6	0.08	4% naphthalene, 4% biphenyl.

Table 4 to Subpart MMMM of Part 63—Default Organic HAP Mass Fraction for Petroleum Solvent Groups ^a

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data.

Solvent type	Average organic HAP mass fraction	Typical organic HAP, percent by mass
Aliphatic ^b	0.03	1% Xylene, 1% Toluene, and 1% Ethylbenzene.
Aromatic ^c	0.06	4% Xylene, 1% Toluene, and 1% Ethylbenzene.

^a Use this table only if the solvent blend does not match any of the solvent blends in Table 3 to this subpart by either solvent blend name or CAS number and you only know whether the blend is aliphatic or aromatic.

b Mineral Spirits 135, Mineral Spirits 150 EC, Naphtha, Mixed Hydrocarbon, Aliphatic Hydrocarbon, Aliphatic Naphtha, Naphthol Spirits, Petroleum Spirits, Petroleum Oil, Petroleum Naphtha, Solvent Naphtha, Solvent Blend.

c Medium-flash Naphtha, High-flash Naphtha, Aromatic Naphtha, Light Aromatic Naphtha, Light Aromatic Hydrocarbons, Aromatic Hydrocarbons, Light Aromatic Solvent.

Appendix A to Subpart MMMM of Part 63—Alternative Capture Efficiency and Destruction Efficiency Measurement and Monitoring Procedures for Magnet Wire Coating Operations

1.0 Introduction.

1.1 These alternative procedures for capture efficiency and destruction efficiency measurement and monitoring are intended principally for newer magnet wire coating machines where the control device is internal and integral to the oven so that it is difficult or infeasible to make gas measurements at the inlet to the control device.

1.2 In newer gas fired magnet wire ovens with thermal control (no catalyst), the burner tube serves as the control device (thermal oxidizer) for the process. The combustion of solvents in the burner tube is the principal source of heat for the oven.

1.3 In newer magnet wire ovens with a catalyst there is either a burner tube (gas fired ovens) or a tube filled with electric heating elements (electric heated oven) before the catalyst. A large portion of the solvent is often oxidized before reaching the catalyst. The combustion of solvents in the tube and across the catalyst is the principal source of heat for the oven. The internal catalyst in these ovens cannot be accessed without disassembly of the oven. This disassembly includes removal of the oven insulation. Oven reassembly often requires the installation of new oven insulation.

1.4 Some older magnet wire ovens have external afterburners. A significant portion of the solvent is oxidized within these ovens as well.

1.5 The alternative procedure for destruction efficiency determines the organic carbon content of the volatiles entering the control device based on the quantity of coating used, the carbon content of the volatile portion of the coating and the efficiency of the capture system. The organic carbon content of the control device outlet (oven exhaust for ovens without an external afterburner) is determined using Method 25 or 25A.

1.6 When it is difficult or infeasible to make gas measurements at the inlet to the control device, measuring capture efficiency with a gas-to-gas protocol (see §63.3965(d)) which relies on direct measurement of the captured gas stream will also be difficult or infeasible. In these situations, capture efficiency measurement is more appropriately done with a procedure which does not rely on direct measurement of the captured gas stream.

1.7 Magnet wire ovens are relatively small compared to many other coating ovens. The exhaust rate from an oven is low and varies as the coating use rate and solvent loading rate change from job to job. The air balance in magnet wire ovens is critical to product quality. Magnet wire ovens must be operated under negative pressure to avoid smoke and odor in the workplace, and the exhaust rate must be sufficient to prevent over heating within the oven.

1.8 The liquid and gas measurements needed to determine capture efficiency and control device efficiency using these alternative procedures may be made simultaneously.

1.9 Magnet wire facilities may have many (e.g., 20 to 70 or more) individual coating lines each with its own capture and control system. With approval, representative capture efficiency and control device efficiency testing of one magnet wire coating machine out of a group of identical or very

similar magnet wire coating machines may be performed rather than testing every individual magnet wire coating machine. The operating parameters must be established for each tested magnet wire coating machine during each capture efficiency test and each control device efficiency test. The operating parameters established for each tested magnet wire coating machine also serve as the operating parameters for untested or very similar magnet wire coating machines represented by a tested magnet wire coating machine.

2.0 Capture Efficiency.

2.1 If the capture system is a permanent total enclosure as described in §63.3965(a), then its capture efficiency may be assumed to be 100 percent.

2.2 If the capture system is not a permanent total enclosure, then capture efficiency must be determined using the liquid-to-uncaptured-gas protocol using a temporary total enclosure or building enclosure in §63.3965(c), or an alternative capture efficiency protocol (see §63.3965(e)) which does not rely on direct measurement of the captured gas stream.

2.3 As an alternative to establishing and monitoring the capture efficiency operating parameters in §63.3967(f), the monitoring described in either section 2.4 or 2.5, and the monitoring described in sections 2.6 and 2.7 may be used for magnet wire coating machines.

2.4 Each magnet wire oven must be equipped with an interlock mechanism which will stop or prohibit the application of coating either when any exhaust fan for that oven is not operating or when the oven experiences an over limit temperature condition.

2.5 Each magnet wire oven must be equipped with an alarm which will be activated either when any oven exhaust fan is not operating or when the oven experiences an over limit temperature condition.

2.6 If the interlock in 2.4 or the alarm in 2.5 is monitoring for over limit temperature conditions, then the temperature(s) that will trigger the interlock or the alarm must be included in the start-up, shutdown and malfunction plan and the interlock or alarm must be set to be activated when the oven reaches that temperature.

2.7 Once every 6 months, each magnet wire oven must be checked using a smoke stick or equivalent approach to confirm that the oven is operating at negative pressure compared to the surrounding atmosphere.

3.0 Control Device Efficiency.

3.1 Determine the weight fraction carbon content of the volatile portion of each coating, thinner, additive, or cleaning material used during each test run using either the procedure in section 3.2 or 3.3.

3.2 Following the procedures in Method 204F, distill a sample of each coating, thinner, additive, or cleaning material used during each test run to separate the volatile portion. Determine the weight fraction carbon content of each distillate using ASTM Method D5291-02, "Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants" (incorporated by reference, see §63.14).

3.3 Analyze each coating, thinner, additive or cleaning material used during each test run using Method 311. For each volatile compound detected in the gas chromatographic analysis of each coating, thinner, additive, or cleaning material calculate the weight fraction of that whole compound in the coating, thinner, additive, or cleaning material. For each volatile compound detected in the gas chromatographic analysis of each coating, thinner, additive, or cleaning material calculate the weight fraction of the carbon in that compound in the coating, thinner, additive, or cleaning material. Calculate the weight fraction carbon content of each coating, thinner, additive, or cleaning material as the ratio of the sum of the carbon weight fractions divided by the sum of the whole compound weight fractions.

3.4 Determine the mass fraction of total volatile hydrocarbon (TVH_i) in each coating, thinner, additive, or cleaning material, i, used during each test run using Method 24. The mass fraction of total volatile hydrocarbon equals the weight fraction volatile matter (W_v in Method 24) minus the weight fraction water (W_w in Method 24), if any, present in the coating. The ASTM Method D6053–00, “Standard Test Method for Determination of Volatile Organic Compound (VOC) Content of Electrical Insulating Varnishes” (incorporated by reference, see §63.14), may be used as an alternative to Method 24 for magnet wire enamels. The specimen size for testing magnet wire enamels with ASTM Method D6053–00 must be 2.0 ±0.1 grams.

3.5 Determine the volume (VOL_i) or mass (MASS_i) of each coating, thinner, additive, or cleaning material, i, used during each test run.

3.6 Calculate the total volatile hydrocarbon input (TVHC_{inlet}) to the control device during each test run, as carbon, using Equation 1:

$$TVHC_{inlet} = \sum_{i=1}^n (TVH_i \times VOL_i \times D_i \times CD_i) \quad (Eq. 1)$$

where:

TVH_i = Mass fraction of TVH in coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run.

VOL_i = Volume of coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run, liters.

D_i = Density of coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run, kg per liter.

CD_i = Weight fraction carbon content of the distillate from coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run, percent.

n = Number of coating, thinner, additive, and cleaning materials used in the coating operation during the test run.

3.7 If the mass, MASS_i, of each coating, solvent, additive, or cleaning material, i, used during the test run is measured directly then MASS_i can be substituted for VOL_i × D_i in Equation 1 in section 3.6.

3.8 Determine the TVHC output (TVHC_{outlet}) from the control device, as carbon, during each test run using the methods in §63.3966(a) and the procedure for determining M_{fo} in §63.3966(d). TVHC_{outlet} equals M_{fo} times the length of the test run in hours.

3.9 Determine the control device efficiency (DRE) for each test run using Equation 2:

$$DRE = \frac{(TVHC_{inlet} - TVHC_{outlet})}{TVHC_{inlet}} \times 100 \quad (Eq. 2)$$

3.10 The efficiency of the control device is the average of the three individual test run values determined in section 3.9.

3.11 As an alternative to establishing and monitoring the destruction efficiency operating parameters for catalytic oxidizers in §63.3967(b), the monitoring described in sections 3.12 and 3.13 may be used for magnet wire coating machines equipped with catalytic oxidizers.

3.12 During the performance test, you must monitor and record the temperature either just before or just after the catalyst bed at least once every 15 minutes during each of the three test runs. Use the data collected during the performance test to calculate and record the average temperature either just before or just after the catalyst bed during the performance test. This is the minimum operating limit for your catalytic oxidizer and for the catalytic oxidizers in identical or very similar magnet wire coating machines represented by the tested magnet wire coating machine.

3.13 You must develop and implement an inspection and maintenance plan for your catalytic oxidizer(s). The plan must address, at a minimum, the elements specified in sections 3.14 and 3.15, and the elements specified in either (a) section 3.16 or (b) sections 3.17 and 3.18.

3.14 You must conduct a monthly external inspection of each catalytic oxidizer system, including the burner assembly and fuel supply lines for problems and, as necessary, adjust the equipment to assure proper air-to-fuel mixtures.

3.15 You must conduct an annual internal inspection of each accessible catalyst bed to check for channeling, abrasion, and settling. If problems are found, you must replace the catalyst bed or take corrective action consistent with the manufacturer's recommendations. This provision does not apply to internal catalysts which cannot be accessed without disassembling the magnet wire oven.

3.16 You must take a sample of each catalyst bed and perform an analysis of the catalyst activity (i.e., conversion efficiency) following the manufacturer's or catalyst supplier's recommended procedures. This sampling and analysis must be done within the time period shown in Table 1 below of the most recent of the last catalyst activity test or the last catalyst replacement. For example, if the warranty for the catalyst is 3 years and the catalyst was more recently replaced then the sampling and analysis must be done within the earlier of 26,280 operating hours or 5 calendar years of the last catalyst replacement. If the warranty for the catalyst is 3 years and the catalyst was more recently tested then the sampling and analysis must be done within the earlier of 13,140 operating hours or 3 calendar years of the last catalyst activity test. If problems are found during the catalyst activity test, you must replace the catalyst bed or take corrective action consistent with the manufacturer's recommendations.

Table 1_Catalyst Monitoring Requirements

If the catalyst was last (more recently) replaced and the warranty period is . . .	Then the time between catalyst replacement and the next catalyst activity test cannot exceed the earlier of . . .	And the Catalyst was more recently tested, then the time between catalyst activity tests cannot exceed the earlier of....
1 year.....	8,760 operating hours or 5 calendar years.	8,760 operating hours or 3 calendar years.
2 years.....	15,520 operating hours or 5 calendar years.	8,760 operating hours or 3 calendar years.
3 years.....	26,280 operating hours or 5 calendar years.	13,100 operating hours or 3 calendar years.
4 years.....	35,040 operating hours or 5 calendar years.	17,520 operating hours or 3 calendar years.
5 or more years.....	43,800 operating hours or 5 calendar years.	21,900 operating hours or 3 calendar years.

3.17 During the performance test, you must determine the average concentration of organic compounds as carbon in the magnet wire oven exhaust stack gases (C_c in Equation 1 in §63.3966(d)) and the destruction efficiency of the catalytic oxidizer, and calculate the operating limit for oven exhaust stack gas concentration as follows. You must identify the highest organic HAP content coating used on this magnet wire coating machine or any identical or very similar magnet wire coating machines to which the same destruction efficiency test results will be applied. Calculate the percent emission reduction necessary to meet the magnet wire coating emission limit when using this coating. Calculate the average concentration of organic compounds as carbon in the magnet wire oven exhaust stack gases that would be equivalent to exactly meeting the magnet wire coating emissions limit when using the highest organic HAP content coating. The maximum operating limit for oven exhaust stack gas concentration equals 90 percent of this calculated concentration.

3.18 For each magnet wire coating machine equipped with a catalytic oxidizer you must perform an annual 10 minute test of the oven exhaust stack gases using EPA Method 25A. This test must be performed under steady state operating conditions similar to those at which the last destruction efficiency test for equipment of that type (either the specific magnet wire coating machine or an identical or very similar magnet wire coating machine) was conducted. If the average exhaust stack gas concentration during the annual test of a magnet wire coating machine equipped with a catalytic oxidizer is greater than the operating limit established in section 3.17 then that is a deviation from the operating limit for that catalytic oxidizer. If problems are found during the annual 10-minute test of the oven exhaust stack gases, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations.

3.19 If a catalyst bed is replaced and the replacement catalyst is not of like or better kind and quality as the old catalyst, then you must conduct a new performance test to determine destruction efficiency according to §63.3966 and establish new operating limits for that catalytic oxidizer unless destruction efficiency test results and operating limits for an identical or very similar unit (including consideration of the replacement catalyst) are available and approved for use for the catalytic oxidizer with the replacement catalyst.

3.20 If a catalyst bed is replaced and the replacement catalyst is of like or better kind and quality as the old catalyst, then a new performance test to determine destruction efficiency is not required and you may continue to use the previously established operating limits for that catalytic oxidizer.

E.3 One Time Deadlines Relating to NESHAP Subpart MMMM

The Permittee shall comply with the following requirements by the dates listed:

Requirement	Rule Cite	Affected Facility	Deadline
Submit Initial Notification	40 CFR 63.3910(b)	Entire Source	January 2, 2005
Conduct Initial Compliance Demonstrations	40 CFR 63.3940, 63.3950, 63.3960	Entire Source	January 31, 2008
Submit Notification of Intent to Conduct a Performance Test	40 CFR 63.7(b) and 63.9(e)	Ovens that Undergo Performance Test	November 3, 2006
Conduct Performance Test	40 CFR 63.3960(b)(1)	Ovens that Undergo Performance Test	January 2, 2007
Develop and Implement Work Practice Plan	40 CFR 63.3960(b)(2)	Entire Source	January 2, 2007
Results of Initial Performance Tests	40 CFR 63.3920(b)	Ovens that Undergo Performance Test	March 3, 2007

Notification of Compliance Status	40 CFR 63.3910(c)	Entire Source	March 1, 2008
First Semiannual Compliance Report	40 CFR 63.3920(a)(1)	Entire Source	July 31, 2008

Conclusion and Recommendation

The construction and operation of this proposed modification shall be subject to the conditions of the attached proposed Part 70 Significant Source Modification No. 003-22964-00013 and Significant Permit Modification 003-22935-00013. The staff recommend to the Commissioner that this Part 70 Significant Source and Significant Permit Modification be approved.

**Appendix A: Emission Calculations
Magnet Wire Coating Ovens**

Company Name: Rea Magnet Wire Company, Inc.
Address: 4300 New Haven Avenue, Fort Wayne, Indiana 46803
SSM and SPM 003-22964-00013 and 003-22935-00013
Reviewer: ERG/ST
Date: July 11, 2006

Oven Model	Oven ID Number	Material	Density (lbs/gal)	Weight Percent VOC (%)	Usage (gal/unit)	Maximum Throughput (unit/hour)
GE-M	615	P D 10635 Formvar	8.22	83.7%	0.0064	614.6
GE-M	635	P D 10635 Formvar	8.22	83.7%	0.0064	614.6

Potential to Emit of VOC											
Before Integral Oxidizer			Before Thermal Oxidizer					After Thermal Oxidizer			
326 IAC 8-2-8 PTE (lbs/gal)	PTE VOC per oven (lbs/hr)	PTE VOC per oven (tons/yr)	Integral Oxidizer Efficiency (%)	326 IAC 8-2-8 PTE (lbs/gal)	PTE VOC per oven (lbs/hr)	PTE VOC per oven (lbs/day)	PTE VOC per oven (tons/yr)	Thermal Oxidizer Efficiency (%)	PTE VOC per oven (lbs/hr)	PTE VOC per oven (lbs/day)	PTE VOC per oven (tons/yr)
6.88	27.2	119	95%	0.34	1.36	32.6	5.96	70.0%	0.41	9.79	1.79
6.88	27.2	119	95%	0.34	1.36	32.6	5.96	70.0%	0.41	9.79	1.79

The transfer efficiency for all wire coating operations is 100%. There is no particulate potential from the magnet wire coating operations. These wire enameling ovens utilize integral internal catalytic oxidizers. Assume control efficiency of 95%. VOC emissions are controlled with external thermal oxidizers. Assume efficiency of 70%.
 One unit is equivalent to one pound of wire.

Methodology

326 IAC 8-2-8 PTE (lbs/gal) (Before Integral Oxidizers) = Density (lbs/gal) x Weight Percent VOC (%)
 PTE VOC per oven (Before Integral Oxidizers) (lbs/hr) = Density (lbs/gal) x Weight Percent VOC (%) x Usage (gal/unit) x Maximum Throughput (units/hr)
 PTE VOC per oven (Before Integral Oxidizers) (tons/yr) = PTE VOC per oven (Before Integral Oxidizers) (lbs/hr) x 8760 (hrs/yr) x 1 ton/2,000 lbs
 326 IAC 8-2-8 PTE (lbs/gal) (Before Thermal Oxidizers) = Density (lbs/gal) x Weight Percent VOC (%) x (1 - Catalytic Oxidizer Efficiency %)
 PTE VOC per oven (Before Thermal Oxidizers) (lbs/hr) = Density (lbs/gal) x Weight Percent VOC (%) x Usage (gal/unit) x Maximum Throughput (units/hr) x (1 - Catalytic Oxidizer Efficiency %)
 PTE VOC per oven (Before Thermal Oxidizers) (lbs/day) = PTE VOC per oven (Before Thermal Oxidizers) (lbs/hr) x 24 (hrs/day)
 PTE VOC per oven (Before Thermal Oxidizers) (tons/yr) = PTE VOC per oven (Before Thermal Oxidizers) (lbs/hr) x 8760 (hrs/yr) x 1 ton/2,000 lbs
 PTE VOC per oven (After Thermal Oxidizers) (lbs/hr) = PTE VOC per oven (Before Thermal Oxidizers) (lbs/hr) x (1- Thermal Oxidizer Efficiency(%))
 PTE VOC per oven (After Thermal Oxidizers) (lbs/day) = PTE VOC per oven (After Thermal Oxidizers) (lbs/hr) x 24 (hrs/day)
 PTE VOC per oven (After Thermal Oxidizers) (tons/yr) = PTE VOC per oven (After Thermal Oxidizers) (lbs/hr) x 8760 (hrs/yr) x 1 ton/2,000 lbs

**Appendix A: Emission Calculations
Magnet Wire Coating Ovens**

Company Name: Rea Magnet Wire Company, Inc.
Address: 4300 New Haven Avenue, Fort Wayne, Indiana 46803
SSM and SPM: 003-22964-00013 and 003-22935-00013
Reviewer: ERG/ST
Date: July 11, 2006

Oven	Material	Density (lbs/gal)	Usage (gal/unit)	Maximum Throughput (unit/hour)	Weight Percent Ethyl benzene (%)	Weight Percent Xylene (%)	Weight Percent Cumene (%)	Weight Percent Phenol (%)	Weight Percent M-Cresol (%)	Weight Percent P-Cresol (%)
615	P D 10635 Formvar	8.22	0.0064	614.6	4.0%	3.0%	3.0%	26.0%	7.0%	6.0%
635	P D 10635 Formvar	8.22	0.0064	614.6	4.0%	3.0%	3.0%	26.0%	7.0%	6.0%

Potential to Emit Before Thermal Oxidizer (tons/year)

Oven	Material	Density (lbs/gal)	Usage (gal/unit)	Maximum Throughput (unit/hour)	PTE of Ethyl benzene	PTE of Xylene	PTE of Cumene	PTE of Phenol	PTE of M-Cresol	PTE of P-Cresol	PTE of Total HAPs
615	P D 10635 Formvar	(same as above)			0.285	0.214	0.214	1.851	0.498	0.427	6.98
635	P D 10635 Formvar				0.285	0.214	0.214	1.851	0.498	0.427	

These wire enameling ovens utilize integral internal catalytic oxidizers. Assume a control efficiency of 95%. VOC emissions are controlled with external thermal oxidizers. Assume a control efficiency of 70%.

One unit is equivalent to one pound of wire.

Methodology

PTE HAP per oven (Before Thermal Oxidizers) (tons/yr) = Density (lbs/gal) x Weight Percent VOC (%) x Usage (gal/unit) x Maximum Throughput (units/hr) x (1 - Catalytic Oxidizer Efficiency %) x 8760 (hrs/yr) x 1 ton/2,000 lbs

**Appendix A: Emission Calculations
Combustion Emissions for Natural Gas Fired Oxidizers**

**Company Name: Rea Magnet Wire Company, Inc.
Address: 4300 New Haven Avenue, Fort Wayne, Indiana 46803
SSM and SPM: 003-22964-00013 and 003-22935-00013
Reviewer: ERG/ST
Date: July 11, 2006**

Emission Unit Description	Emission Unit ID	Heat Input Capacity (MMBtu/hr)	Maximum Potential Throughput (MMCF/yr)
Natural Gas-Fired Oxidizer	615	0.7	6.0
Natural Gas-Fired Oxidizer	635	0.7	6.0

Pollutant Emission Factors (lbs/MMCF)						
PM*	PM10*	SO ₂	NO _x **	CO	VOC	HAPs
1.9	7.6	0.6	100	84.0	5.5	1.89

Potential To Emit (tons/yr)							
Emission Unit ID	PM	PM10	SO ₂	NO _x	CO	VOC	HAPs
615	0.006	0.023	0.00	0.30	0.25	0.02	0.01
635	0.006	0.023	0.00	0.30	0.25	0.02	0.01
TOTALS	0.011	0.046	0.004	0.60	0.50	0.03	0.01

* PM10 emission factor is for condensable and filterable PM and PM10 combined. PM emission factor is for filterable PM only.

**Emission factor for NO_x: Uncontrolled = 100 lb/MMCF

Emission factors are from AP-42, Chapter 1.4 - Natural Gas Combustion, Tables 1.4-1, 1.4-2, 1.4-3 and 1.4-4. SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03. (AP-42 Supplement D 7/98)

1 MMBtu = 1,000,000 Btu

1 MMCF = 1,000,000 cubic feet of gas

All emission factors are based on normal firing.

Methodology

Max. Potential Throughput (MMCF/year) = Heat Input Capacity (MMBtu/hour) x 8,760 (hours/year) x 1 MMCF/1,020 MMBtu

PTE (tons/year) = Max. Potential Throughput (MMCF/year) x Emission Factor (lbs/MMCF) x 1 ton/2,000 lbs