



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

TO: Interested Parties / Applicant
DATE: October 17, 2006
RE: Twin Bridges Recycling (Waste Management of Indiana) / 063-23080-00029
FROM: Nisha Sizemore
Chief, Permits Branch
Office of Air Quality

Notice of Decision: Approval – Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-17-3-4 and 326 IAC 2, this permit modification is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-7-3 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

Pursuant to 326 IAC 2-7-18(d), any person may petition the U.S. EPA to object to the issuance of a Title V operating permit or modification within sixty (60) days of the end of the forty-five (45) day EPA review period. Such an objection must be based only on issues that were raised with reasonable specificity during the public comment period, unless the petitioner demonstrates that it was impracticable to raise such issues, or if the grounds for such objection arose after the comment period.

To petition the U.S. EPA to object to the issuance of a Title V operating permit, contact:

U.S. Environmental Protection Agency
401 M Street
Washington, D.C. 20406

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
We make Indiana a cleaner, healthier place to live.

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

Mr. Barry Ledbetter
Twin Bridges Recycling (Waste Management of Indiana)
124 East Twin Bridges Road
Danville, IN 46122

October 17, 2006

Re: **063-23080-00029**
Significant Permit Modification to
Part 70 No.: **T 063-7998-00029**

Dear Mr. Ledbetter:

Twin Bridges Recycling (Waste Management of Indiana) was issued a Part 70 Operating Permit (T 063-7998-00029) on July 28, 1999 for stationary municipal solid waste landfill (MSLWLF). A letter requesting changes to this permit was received on May 11, 2006. Pursuant to the provisions of 326 IAC 2-7-12 a significant permit modification to this permit is hereby approved as described in the attached Technical Support Document.

The modification consists of revising the compliance determination and monitoring requirements, and incorporating the applicable requirements of the National Emissions Standards for Hazardous Air Pollutants (NESHAP) for Municipal Solid Waste Landfills (40 CFR Part 63, Subpart AAAA).

All other conditions of the permit shall remain unchanged and in effect. Please find attached the entire Part 70 Operating Permit as modified.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Jenny Acker, OAQ, 100 North Senate Avenue, Indianapolis, Indiana, 46204-2251, or call at (800) 451-6027, and ask for Jenny Acker or extension 2-8253, or dial (317) 232-8253.

Sincerely,

Original signed by
Nisha Sizemore, Chief
Permits Branch
Office of Air Quality

Attachments

JLA

cc: File – Hendricks County
Hendricks County Health Department
Air Compliance Section Inspector – Vaughn Ison
Compliance Branch
Administrative and Development
Billing, Licensing and Training



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

PART 70 OPERATING PERMIT OFFICE OF AIR QUALITY

Twin Bridges Recycling (Waste Management of Indiana) 124 East Twin Bridges Road Danville, IN 46122

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 and 326 IAC 2-1-3.2 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T063-7998-00029	
Issued by: Original signed by Janet G. McCabe, Assistant Commissioner Office of Air Quality	Issuance Date: July 28, 1999 Expiration Date: July 28, 2004
Significant Permit Modification No.: 063-14743-00029, issued December 18, 2001 Administrative Amendment No.: 063-20086-00029, issued November 12, 2004 Administrative Amendment No.: 063-20666-00029, issued April 19, 2005 Administrative Amendment No.: 063-22523-00029, issued July 19, 2005 Minor Permit Modification No.: 063-22317-00029, issued on April 21, 2006	
Significant Permit Modification No.: 063-23080-00029	
Original signed by: Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: October 17, 2006

TABLE OF CONTENTS

SECTION A	SOURCE SUMMARY	5
A.1	General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]	
A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.4	Part 70 Permit Applicability [326 IAC 2-7-2]	
SECTION B	GENERAL CONDITIONS	9
B.1	Definitions [326 IAC 2-7-1]	
B.2	Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]	
B.3	Term of Conditions [326 IAC 2-1.1-9.5]	
B.4	Enforceability [326 IAC 2-7-7(a)]	
B.5	Severability [326 IAC 2-7-5(5)]	
B.6	Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	
B.7	Duty to Supplement and Provide Information [326 IAC 2-7-5(6)(E)]	
B.8	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]	
B.9	Annual Compliance Certification [326 IAC 2-7-6(5)]	
B.10	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]	
B.11	Emergency Provisions [326 IAC 2-7-16]	
B.12	Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]	
B.13	Prior Permits Superseded [326 IAC 2-1.1-9-5] [326 IAC 2-7-10.5]	
B.14	Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]	
B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]	
B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]	
B.17	Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]	
B.18	Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]	
B.19	Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12(b)(2)]	
B.20	Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]	
B.21	Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2-2] [326 IAC 2-3]	
B.22	Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]	
B.23	Transfer of Ownership or Operation [326 IAC 2-7-11]	
B.24	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)] [[326 IAC 2-1.1-7]	
B.25	Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 FR 8314] [326 IAC 1-1-6]	
SECTION C	SOURCE OPERATION CONDITIONS	19
	Emission Limitations and Standards [326 IAC 2-7-5(1)]	
C.1	Particulate Matter Emission Limitations For Processes with Process Weight Rates less than One Hundred (100) Pounds Per Hour [326 IAC 6-3-2]	
C.2	Opacity [326 IAC 5-1]	
C.3	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.4	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.5	Fugitive Dust Emissions [326 IAC 6-4]	
C.6	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]	
	Testing Requirements [326 IAC 2-7-6(1)]	
C.7	Performance Testing [326 IAC 3-6]	
	Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]	
C.8	Compliance Schedule [326 IAC 2-7-6(3)]	

- C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.10 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.11 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]
- C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]
- C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]
- C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

Stratospheric Ozone Protection

- C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS - stationary municipal solid waste landfill, and flare 26

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 General Provisions Relating to NSPS [326 IAC 12-1] [326 IAC 8-8.1] [[40 CFR Part 60, Subpart A] [326 IAC 20-1-1] [40 CFR 63, Subpart A] [326 IAC 14-1-1] [40 CFR Part 61, Subpart A]
- D.1.2 Municipal Solid Waste Landfill NESHAP [40 CFR 63, Subpart AAAA] [326 IAC 20-67]
- D.1.3 Municipal Solid Waste Landfill NSPS [40 CFR 60.752] [326 IAC 8-8.1] [326 IAC 12]
- D.1.4 Operational Standards for Collection and Control Systems [40 CFR 60.753] [326 IAC 8-8.1] [326 IAC 12]
- D.1.5 NESHAP for Active Waste Disposal Sites [40 CFR 61.154] [326 IAC 14]

Compliance Determination Requirements

- D.1.6 Testing Requirements [326 IAC 2-7-6(1),(6)] [40 CFR 60.754(b)] [326 IAC 8-8.1] [326 IAC 12]
- D.1.7 Compliance Determination [40 CFR 63.1960] [40 CFR 63.1965] [326 IAC 20-67]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.8 Monitoring [40 CFR 60.756] [326 IAC 8-8.1] [326 IAC 12]
- D.1.9 Compliance Provisions [40 CFR 60.755] [326 IAC 8-8.1] [326 IAC 12]

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.10 Calculation of Non-methane Organic Compound (NMOC) Rate [40 CFR 60.754] [326 IAC 8-8.1] [326 IAC 12]
- D.1.11 Reporting Requirements [40 CFR 60.757] [326 IAC 8-8.1] [326 IAC 12]
- D.1.12 Recordkeeping for NESHAP for Active Waste Disposal Sites [40 CFR 61.154] [326 IAC 14]
- D.1.13 Record Keeping and Reporting Requirements for NSPS for Municipal Solid Waste Landfills [326 IAC 12] [40 CFR 60.758]
- D.1.14 Record Keeping Requirements and Reporting Requirements for NESHAP for Municipal Solid Waste Landfills [40 CFR 63.1980] [326 IAC 20-67]

SECTION D.2 FACILITY OPERATION CONDITIONS - Engine/generator sets..... 42

SECTION D.3 FACILITY OPERATION CONDITIONS - Degreasing Operations..... 43

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]

D.3.2 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]

D.3.3 Hazardous Air Pollutants (HAPs)

Certification 45

Emergency/Deviation Occurrence Report..... 46

Semi-Annual Compliance Monitoring Report 48

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary municipal solid waste landfill (MSLWLF)

Responsible Official:	Director of Operations
Source Address:	124 East Twin Bridges Road, Danville, IN 46122
Mailing Address:	124 East Twin Bridges Road, Danville, IN 46122
SIC Code:	4953
County Location:	Hendricks
Source Location Status:	Nonattainment for ozone under the 8-hour standard Nonattainment for PM 2.5 Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Minor Source under PSD and Major Source under Emission Offset Rules Major Source, Section 112 of the Clean Air Act Not in 1 of 28 source categories

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units:

- (a) One (1) solid waste disposal facility having the meaning described in 40 CFR 60.751 pertaining to all contiguous land and structures, other appurtenances (including haul roads), and improvements on the land used for disposal of solid waste that opened in 1970 and has a design capacity of 29,569,038 Megagrams.
- (b) One (1) open flare, identified as FL2 to be constructed in 2006, with a rated capacity of 2100 standard cubic feet per minute (scfm) and exhausting to stack FL2S. This flare does not have a bypass.
- (c) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG1 through EG4, and a single fuel gas compressor. The generators are rated at 800 kilowatts each, and were installed in 1994 and 1996.
- (d) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG5 through EG8, rated at 800 kilowatts each and exhausting to stacks ES5 through ES8, respectively.
- (e) One (1) gas treatment system that processes the collected gas pursuant to 40 CFR 60.752(b)(2)(iii)(C).

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities as defined in 326 IAC 2-7-1(21):

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment.
- (b) Any of the following structural steel and bridge fabrication activities:
 - (1) Cutting 200,000 linear feet or less of one inch (10) plate or equivalent.
 - (2) Using 80 tons or less of welding consumables.
- (c) Space heaters, process heaters, or boilers using the following fuels:
 - (1) Propane or liquefied petroleum gas, or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) Btu per hour.
 - (2) Fuel oil-fired combustion sources with heat input equal to or less than two million (2,000,000) Btu per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight.
- (d) Equipment powered by internal combustion engines of capacity equal to or less than 500,000 Btu/hour, except where total capacity of equipment operated by one stationary source exceeds 2,000,000 Btu/hour.
- (e) A gasoline fuel transfer and dispensing operation handling less than or equal to 1,300 gallons per day, such as filling of tanks, locomotives, automobiles, having a storage capacity less than or equal to 10,500 gallons.
- (f) A petroleum fuel, other than gasoline, dispensing facility having a storage capacity less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.
- (g) The following VOC and HAP storage containers:
 - (1) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughput less than 12,000 gallons.
 - (2) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids.
- (h) Application of oils, greases, lubricants, or other nonvolatile materials applied as temporary protective coatings.
- (i) Cleaners and solvents characterized as follows:
 - (1) Having a vapor pressure equal to or less than 2 kPa; 15 mm Hg; or 0.3 psi measured at 38 degrees C (100°F) or;
 - (2) Having a vapor pressure equal to or less than 0.7 kPa; 5mm Hg; or 0.1 psi measured at 20°C (68°F); the use of which for all cleaners and solvents combined does not exceed 145 gallons per 12 months.
- (j) Activities associated with the treatment of wastewater streams with an oil and grease content less than or equal to 1% by volume.
- (k) Activities associated with the transportation and treatment of sanitary sewage, provided discharge to the treatment plant is under the control of the owner/operator, that is, an on-site sewage treatment facility.

- (l) Any operation using aqueous solutions containing less than 1% by weight of VOCs, excluding HAPs.
- (m) Water based adhesives that are less than or equal to 5% by volume of VOCs, excluding HAPs.
- (n) Stockpiled soils from soil remediation activities that are covered and waiting transportation for disposal.
- (o) Paved and unpaved roads and parking lots with public access.
- (p) Asbestos abatement projects regulated by 326 IAC 14-10.
- (q) Purging of gas lines and vessels that is related to routing maintenance and repair of buildings, structures, or vehicles at the source where air emissions from those activities would not be associated with any production process.
- (r) Equipment used to collect any material that might be released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separators, tanks, and fluid handling equipment.
- (s) On-site fire and emergency response training approved by the department.
- (t) Emergency generators as follows:
 - (1) Gasoline generators not exceeding 110 horsepower.
 - (2) Diesel generators not exceeding 1600 horsepower.
- (u) Farm Operations
- (v) Other activities or categories not previously identified:
 - (1) Leachate/Condensate Storage Tank #1
 - (2) Leachate/Condensate Storage Tank #2
 - (3) Leachate/Condensate Storage Tank #3
 - (4) Crankcase Breather Vent
 - (5) Spray Painting
 - (6) Parts Washing
 - (7) Leachate Recirculation
 - (8) Soil Screening
 - (9) Soil Bioremediation Piles
 - (10) Solidification Activities
 - (11) Passive Gas Flare
- (w) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. [326 IAC 8-3-2] [326 IAC 8-3-5]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS**B.1 Definitions [326 IAC 2-7-1]**

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]

- (a) This permit, 063-7998-00029, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by the "responsible official" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) The "responsible official" is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]**

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation .
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality,
Compliance Section), or

Telephone Number: 317-233-0178 (ask for Compliance Section)

Facsimile Number: 317-233-6865

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
 - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
 - (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
 - (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
 - (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (h) The Permittee shall include all emergencies in the Semi-Annual Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a

determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]

- (a) All terms and conditions of permits established prior to 063-7998-00029 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised under 326 IAC 2-7-10.5, or

(3) deleted under 326 IAC 2-7-10.5.

(b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit.

B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within ten (10) calendar days from the date of the discovery of the deviation except as allowed for in 40 CFR 60, Subpart WWW or approved variances contained within the Collection and Control System Design Plan required pursuant to this rule.

(b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:

- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
- (2) An emergency as defined in 326 IAC 2-7-1(12); or
- (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
- (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.

(c) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

(d) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

(a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-

5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
- (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
- (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12] [40 CFR 72]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:
- Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
- Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12(b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b),(c), or (e) without a prior permit revision, if each of the following conditions is met:
- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
 - (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
 - (4) The Permittee notifies the:
- Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b),(c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade emissions increases and decreases at in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.21 Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2-2] [326 IAC 2-3]

- (a) A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.
- (b) Any modification at an existing major source is governed by the requirements of 326 IAC 2-2-2 and/or 326 IAC 2-3-2.

B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, and U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)] [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.

- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 9-1-2 is not federally enforceable.

C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:

- (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
- (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
 Asbestos Section, Office of Air Quality
 100 North Senate Avenue
 Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
 The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
 The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**
 The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.7 Performance Testing [326 IAC 3-6]

-
- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.8 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]

C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit, except as otherwise provided for in 40 CFR 60, Subpart WWW or approved variances contained within the Collection and Control System Design Plan required pursuant to this rule. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend compliance schedule an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.10 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.11 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]**C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on October 22, 1999.
- (b) Upon direct notification by IDEM, OAQ that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level.
[326 IAC 1-5-3]

C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]**

- (a) Pursuant to 326 IAC 2-6-3(b)(2), starting in 2005 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:

- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
- (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2]
[326 IAC 2-3]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.
- (c) If there is a reasonable possibility that a "project" (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1 (ll)) at an existing emissions unit, other than projects at a Clean Unit, which is not part of a "major modification" (as defined in 326 IAC 2-2-1 (ee) and/or 326 IAC 2-3-1 (z)) may result in significant emissions increase and the Permittee elects to utilize the "projected actual emissions" (as defined in 326 IAC 2-2-1 (rr) and/or 326 IAC 2-3-1 (mm)), the Permittee shall comply with following:
 - (1) Before beginning actual construction of the "project" (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1 (ll)) at an existing emissions unit, document and maintain the following records:
 - (A) A description of the project.
 - (B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.
 - (C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:
 - (i) Baseline actual emissions;
 - (ii) Projected actual emissions;
 - (iii) Amount of emissions excluded under section 326 IAC 2-2-1(rr)(2)(A)(iii) and/or 326 IAC 2-3-1(mm)(2)(A)(iii); and

- (iv) An explanation for why the amount was excluded, and any netting calculations, if applicable.
- (2) Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and
- (3) Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR pollutant at the emissions unit.
- C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]**
-
- (a) The Permittee shall submit the attached Semi-Annual Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Semi-Annual Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:
- Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.
- (f) If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any "project" (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1 (ll)), and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:
- (1) The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as defined in 326 IAC 2-2-1 (xx) and/or 326 IAC 2-3-1 (qq), for that regulated NSR pollutant, and
- (2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).

- (g) The report for project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:
- (1) The name, address, and telephone number of the major stationary source.
 - (2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.
 - (3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-2-2(d)(3) and/or 326 IAC 2-3-2(c)(3).
 - (4) Any other information that the Permittee deems fit to include in this report,

Reports required in this part shall be submitted to:

Indiana Department of Environmental Management
Air Compliance Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.

Stratospheric Ozone Protection

C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1**FACILITY OPERATION CONDITIONS****Facility Description [326 IAC 2-7-5(15)]**

- (a) One (1) solid waste disposal facility having the meaning described in 40 CFR 60.751 pertaining to all contiguous land and structures, other appurtenances (including haul roads), and improvements on the land used for disposal of solid waste that opened in 1970 and has a design capacity of 29,569,038 Megagrams.
- (b) One (1) open flare, identified as FL2, to be constructed in 2006, with a rated capacity of 2100 standard cubic feet per minute (scfm) and exhausting to stack FLS2. This flare does not have a bypass.
- (e) One (1) gas treatment system that processes the collected gas pursuant to 40 CFR 60.752(b)(2)(iii)(C).

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 General Provisions Relating to NSPS and NESHAP [326 IAC 12-1] [326 IAC 8-8.1] [40 CFR Part 60, Subpart A] [326 IAC 20-1-1] [40 CFR 63, Subpart A] [326 IAC 14-1-1] [40 CFR Part 61, Subpart A]

- (a) The provisions of 40 CFR Part 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 60, Subpart WWW.
- (b) The provisions of 40 CFR Part 63, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 20-1-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 63, Subpart AAAA.
- (c) The provisions of 40 CFR Part 61, Subpart A - General Provisions, which are incorporated as 326 IAC 14-1-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 61, Subpart M.

D.1.2 Municipal Solid Waste Landfill NESHAP [40 CFR 63, Subpart AAAA] [326 IAC 20-67]

Pursuant to 40 CFR 63.1955, the Permittee shall:

- (a) Comply with the requirements of 40 CFR 60, Subpart WWW.
- (b) The Permittee required by 40 CFR 60.752(b)(2) to install a collection and control system shall comply with the general and continuing compliance requirements in 40 CFR 63.1960 through 40 CFR 63.1985.
- (c) The Permittee shall comply with the Startup, Shutdown, and Malfunction (SSM) requirements in Subpart A of 40 CFR 63 as specified in Table 1 of 40 CFR 63, Subpart AAAA and all affected sources must submit compliance reports every six (6) months as specified in 40 CFR 63.1980(a) and (b), including information on all deviations that occurred during the six (6)-month reporting period. Deviations (as defined in 40 CFR 63.1965) for continuous emission monitors or numerical continuous parameter monitors must be determined using a three (3) hour monitoring block average (as defined in 40 CFR 63.1975).

D.1.3 Municipal Solid Waste Landfill NSPS [40 CFR 60.752] [326 IAC 8-8.1] [326 IAC 12]

The municipal solid waste landfill has a design capacity greater than 2.5 million megagrams (Mg) and shall either comply with 40 CFR 60.752 (b)(2) or calculate the non methane organic compound (NMOC) emission rate for the landfill using the procedures specified in 40 CFR 60.754.

D.1.4 Operational Standards for Collection and Control Systems [40 CFR 60.753] [326 IAC 8-8.1] [326 IAC 12]

In order to comply with 40 CFR 60.752 (b)(2)(ii) the Permittee shall:

- (a) Operate the collection system such that gas is collected from each area, cell, or group of cells in the municipal solid waste landfill in which solid waste has been in place for five years if active or 2 years or more if closed or at final grade.
- (b) Operate the collection system with negative pressure at each wellhead except under the following conditions:
 - (1) Fire or increased well temperature. The Permittee shall record instances when positive pressure occurs in efforts to avoid a fire. These records shall be submitted with the annual reports as provided in 40 CFR 60.757(f)(1).
 - (2) Use of a geomembrane or synthetic cover. The Permittee shall develop acceptable pressure limits in the design plan.
 - (3) A decommissioned well. A well may experience a static positive pressure after shut down to accommodate for declining flows. All design changes shall be approved by the Office of Air Quality (OAQ).
- (c) Pursuant to 40 CFR 60.753(c), the Permittee shall operate each interior wellhead in the collection system within the following ranges:
 - (1) A landfill gas temperature equal to or less than 135°F (57.2°C) for wells #58, 71, 86, 89, 97, 100, and 103.
 - (2) A landfill gas temperature less than 140°F (60.0°C) for well #79.
 - (3) A landfill gas temperature less than 150°F (65.6°C) for well #99.
 - (4) A landfill gas temperature less than 160°F (71.1°C) for well #98.
 - (5) A landfill gas temperature less than 131°F (55°C) for all other wells.
 - (6) A nitrogen level less than 20 percent or an oxygen level less than 5 percent.

The Permittee may establish a higher operating temperature, nitrogen, or oxygen value at a particular well. The Permittee has shown supporting data that the elevated parameter does not cause fires or significantly inhibit anaerobic decomposition by killing methanogens.

The nitrogen level shall be determined using Method 3C, unless an alternative method is established as allowed by 40 CFR 60.752 (b)(2)(i).

Unless an alternative test method is established as allowed by 40 CFR 60.752 (b)(2)(i), the oxygen shall be determined by an oxygen meter using Method 3A except that; the span shall be set so that the regulatory limit is between 20 and 50 percent of the span; a data recorder is not required; only two calibration gases are required, a zero and span,

and ambient air may be used as the span; a calibration error check is not required; the allowable sample bias, zero drift, and calibration drift are ± 10 percent.

- (d) Operate the collection system so that the methane concentration is less than 500 parts per million above background at the surface of the landfill. To determine if this level is exceeded, the Permittee shall conduct surface testing around the perimeter of the collection area and along a pattern that traverses the landfill at 30 meter intervals and where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover. The Permittee may establish an alternative traversing pattern that ensures equivalent coverage. A surface monitoring design plan shall be developed that includes a topographical map with the monitoring route and the rationale for any site-specific deviations from the 30 meter intervals.

Areas with steep slopes or other dangerous areas may be excluded from the surface testing.

- (e) Operate the system such that all collected gases are vented to a control system designed and operated in compliance with 40 CFR 60.752(b)(2)(iii). In the event the collection or control system is inoperable, the gas mover system shall be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere shall be closed within one hour.
- (f) Operate the control system at all times when the collected gas is routed to the system.
- (g) If monitoring demonstrates that the operational requirements in 40 CFR 60.753(b), (c), or (d) are not met, corrective action shall be taken as specified in 40 CFR 60.755(a)(3) through (5) or 40 CFR 60.755(c). If corrective actions are taken as specified in 40 CFR 60.755, the monitored exceedance is not a violation of the operational requirements in 40 CFR 60.753.

D.1.5 NESHAP for Asbestos Active Waste Disposal Sites [40 CFR 61.154] [326 IAC 14]

In order to comply with 40 CFR 61.154 the Permittee must comply with the following:

- (a) Allow no visible emissions to the outside air from any active waste disposal site where asbestos-containing waste material has been deposited, or comply with (2) or (3) below.
- (b) At least once every 24-hour period, asbestos-containing waste material that has been deposited during the previous 24-hour period must:
 - (1) be covered with at least 15 centimeters (6 inches) of compacted nonasbestos containing material, or
 - (2) be covered with a resinous or petroleum-based dust suppression agent that effectively binds dust and controls wind erosion. Such an agent shall be used in the manner and frequency recommended for the particular dust by the dust suppression agent manufacturer to achieve and maintain dust control. Other equally effective dust suppression agents may be used upon prior approval by the Administrator. Any used, spent, or other waste oil is not considered a dust suppression agent.
- (c) Use an alternate emissions control method that has received prior written approval by the Administrator.
- (d) Also, unless a natural barrier deters access by the general public, warning signs and fencing must be installed or the requirements of paragraph (2)(a) above must be met.

Compliance Determination Requirements

D.1.6 Testing Requirements [326 IAC 2-7-6(1),(6)] [40 CFR 60.754(b)] [326 IAC 8-8.1] [326 IAC 12]

- (a) After installation of a collection and control system in compliance with 40 CFR 60.755, the Permittee shall calculate the non methane organic compound (NMOC) emission rate for purposes of determining when the system can be removed using the following equation:

$$M_{\text{NMOC}} = 1.89 \times 10^{-3} Q_{\text{LFG}} C_{\text{NMOC}}$$

where,

M_{NMOC} = mass emission rate of NMOC, megagrams per year

Q_{LFG} = flow rate of landfill gas, cubic meters per minute

C_{NMOC} = NMOC concentration, parts per million by volume as hexane

- (1) The flow rate of landfill gas, Q_{LFG} , shall be determined by measuring the total landfill gas flow rate at the common header pipe that leads to the control device using a gas flow measuring device calibrated according to the provisions of section 4 of Method 2E of appendix A of 40 CFR 60.
 - (2) The average NMOC concentration, C_{NMOC} , shall be determined by collecting and analyzing landfill gas sampled from the common header pipe before the gas moving or condensate removal equipment using the procedures in Method 25C or Method 18 of appendix A of 40 CFR 60. If using Method 18 of Appendix A of 40 CFR 60, the minimum list of compounds to be tested shall be those published in the most recent Compilation of Air Pollutant Emission Factors (AP-42). The sample location on the common header pipe shall be before any condensate removal or other gas refining units. The Permittee shall divide the NMOC concentration from Method 25C of Appendix A of 40 CFR 60 by six to convert from C_{NMOC} as carbon to C_{NMOC} as hexane.
 - (3) The Permittee may use another method to determine landfill gas flow rate and NMOC concentration if the method has been approved by the Office of Air Quality (OAQ).
- (b) Pursuant to 40 CFR 60.754(d):

For the performance testing required in 40 CFR 60.752(b)(2)(iii)(B), Method 25 or Method 18 of appendix A of 40 CFR 60 shall be used to determine compliance with 98% reduction weight percent efficiency of NMOC from the control device or the 20 ppmv hexane on a dry basis at 3% oxygen outlet concentration level, or if the control device is an open flare, 40 CFR 60.18 procedures can be used, unless another method to demonstrate compliance has been approved by the Office of Air Quality (OAQ) as provided by 40 CFR 60.752(b)(2)(i)(B). If using Method 18 of appendix A, the minimum list of compounds to be tested shall be those published in the most recent Compilation of Air Pollutant Emission Factors (AP-42). The following equation shall be used to calculate efficiency:

$$\text{Control Efficiency} = (\text{NMOC}_{\text{in}} - \text{NMOC}_{\text{out}}) / (\text{NMOC}_{\text{in}})$$

where,

NMOC_{in} = mass of NMOC entering the control device

NMOC_{out} = mass of NMOC exiting control device

D.1.7 Compliance Determination [40 CFR 63.1960] [40 CFR 63.1965] [326 IAC 20-67]

- (a) Pursuant to 40 CFR 63.1960 and 40 CFR 63.1965, as amended (effective April 20, 2006), compliance with 40 CFR 63, Subpart AAAA is determined by the following:

- (1) The same way it is determined for 40 CFR 60, Subpart WWW, including performance testing, monitoring of the collection system, continuous parameter monitoring, and other credible evidence.
 - (2) Continuous parameter monitoring data, collected under 40 CFR 60.756(b)(1), (c)(1), and (d) of 40 CFR 60, Subpart WWW, are used to demonstrate compliance with the operating conditions for control systems. If a deviation (as defined in 40 CFR 63.1965) occurs, the Permittee has failed to meet the control device operating conditions described in 40 CFR 60, Subpart WWW and has deviated from the requirements of 40 CFR 63, Subpart AAAA.
 - (3) The Permittee must develop a written Startup, Shutdown and Malfunction (SSM) plan according to the provisions in 40 CFR 63.6(e)(3). A copy of the SSM plan must be maintained on site. Failure to write or maintain a copy of the SSM plan is a deviation from the requirements of 40 CFR 63, Subpart AAAA.
- (b) Pursuant to 326 IAC 20-67, the Permittee shall comply with the previous version of 40 CFR 63, Subpart AAAA, published in 68 FR 2238, January 16, 2003. Compliance with the requirements specified in Condition D.1.7(a) shall satisfy the requirements of 326 IAC 20-67, with the exception of the requirements listed in Condition D.1.7(a)(3). In order to satisfy 326 IAC 20-67, the Permittee shall comply with the following:
- (1) The Permittee must develop and implement a written Startup, Shutdown and Malfunction (SSM) plan according to the provisions in 40 CFR 63.6(e)(3). A copy of the SSM plan must be maintained on site. Failure to write, implement, or maintain a copy of the SSM plan is a deviation from the requirements of 40 CFR 63, Subpart AAAA.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.8 Monitoring [40 CFR 60.756] [326 IAC 8-8.1] [326 IAC 12]

Except as provided in 40 CFR 60.752(b)(2)(i)(B),

- (a) The Permittee seeking to comply with 40 CFR 60.752(b)(2)(ii)(A) for an active gas collection shall install a sampling port and a thermometer, other temperature measuring device or an access port for temperature measurements at each wellhead and:
 - (1) Measure the gauge pressure in the gas collection header on a monthly basis as provided in 40 CFR 60.755(a)(3);
 - (2) Monitor nitrogen or oxygen concentration in the landfill gas on a monthly basis as provided in 40 CFR 60.755(a)(5); and
 - (3) Monitor temperature of the landfill gas on a monthly basis as provided in 40 CFR 60.755(a)(5).
- (b) The Permittee seeking to comply with 40 CFR 60.752(b)(2)(iii) using an open flare shall install, calibrate, maintain, and operate according to the manufacturer's specifications the following equipment:
 - (1) Heat sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light or the flame itself to indicate the continuous presence of a flame.
- (c) The Permittee seeking to comply with 40 CFR 60.752(b)(2)(iii) using a device other than an open flare or an enclosed combustor shall provide information satisfactory to the Office of Air Quality (OAQ) as provided in 40 CFR 60.752(b)(2)(i)(B) describing the operation of

the control device, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Office of Air Quality (OAQ) shall review the information and either approve it, or request that additional information be submitted. The Office of Air Quality (OAQ) may specify additional monitoring procedures.

- (d) The Permittee seeking to install a collection system that does not meet the specifications in 40 CFR 60.759 or seeking to monitor alternative parameters to those required by 40 CFR 60.753 through 40 CFR 60.756 shall provide information satisfactory to the Office of Air Quality (OAQ) as provided in 40 CFR 60.752(b)(2)(i)(B) and (C) describing the design and operation of the collection system, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Office of Air Quality (OAQ) may specify additional appropriate monitoring procedures.
- (e) The Permittee seeking to demonstrate compliance with 40 CFR 60.755(c), shall monitor surface concentrations of methane according to the instrument specifications and procedures provided in 40 CFR 60.755(d). Any closed landfill that has no monitored exceedances of the operational standard in three consecutive quarterly monitoring periods may skip to annual monitoring. Any methane reading of 500 ppm or more above background detected during the annual monitoring returns the frequency for that landfill to quarterly monitoring.

D.1.9 Compliance Provisions [40 CFR 60.755] [326 IAC 8-8.1] [326 IAC 12]

- (a) Except as provided in 40 CFR 60.752(b)(2)(i)(B), the specified methods below shall be used to determine whether the gas collection system is in compliance with 40 CFR 60.752(b)(2)(i).
 - (1) For the purpose of calculating the maximum expected gas generation flow rate from the landfill to determine compliance with 60.752(b)(2)(ii)(A)(1), one of the following equations shall be used. The k and L_o kinetic factors should be those published in the most recent Compilation of Air Pollution Emission Factors (AP-42) or other site-specific values demonstrated to be appropriate and approved by the Office of Air Quality (OAQ). If k has been determined as specified in 40 CFR 60.754(a)(4), the value of k determined from the test shall be used. A value of no more than 15 years shall be used for the intended use period of the gas mover equipment. The active life of the landfill is the age of the landfill plus the estimated number of years until closure.

For sites with unknown year-to-year solid waste acceptance rate:

$$Q_m = 2L_o R (e^{-kc} - e^{-kt})$$

where,

Q_m = maximum expected gas generation flow rate, cubic meters per year

L_o = methane generation potential, cubic meters per megagram solid waste

R = average annual acceptance rate, megagrams per year

k = methane generation rate constant, year⁻¹

t = age of the landfill at equipment installation plus the time the owner or operator intends to use the gas mover equipment or active life of the landfill, whichever is less. If the equipment is installed after closure, t is the age of the landfill at installation, years.

c = time since closure, years (for an active landfill $c = 0$ and $e^{-kc} = 1$)

For sites with known year-to-year solid waste acceptance rate:

$$Q_M = \sum_{i=1}^n 2 k L_o M_i (e^{-kt_i})$$

where,

Q_M = maximum expected gas generation flow rate, cubic meters per year

k = methane generation rate constant, year⁻¹

L_0 = methane generation potential, cubic meters per megagram solid waste

M_i = mass of solid waste in the i^{th} section, megagrams

t_i = age of the i^{th} section, years

If a collection and control system has been installed, actual flow data may be used to project the maximum expected gas generation flow rate instead of, or in conjunction with, the equations in 40 CFR 60.755(a)(1)(i) and (ii). If the landfill is still accepting waste, the actual measured flow data will not equal the maximum expected gas generation rate, so calculations using the equations in 40 CFR 60.755(a)(1)(i) or (ii) or other methods shall be used to predict the maximum expected gas generation rate over the intended period of use of the gas control system equipment.

- (2) For the purposes of determining sufficient density of gas collector for compliance with 40 CFR 60.752 (b)(2)(ii)(A)(2), the Permittee shall design a system of vertical wells, horizontal collectors, or other collection devices, satisfactory to the Office of Air Quality (OAQ), capable of controlling and extracting gas from all portions of the landfill sufficient to meet all operational and performance standards.
 - (3) For the purpose of demonstrating whether the gas collection system flow rate is sufficient to determine compliance with 40 CFR 60.752(b)(2)(ii)(A)(3), the Permittee shall measure gauge pressure in the gas collection header at each individual well, monthly. If a positive pressure exists, action shall be initiated to correct the exceedance within five (5) calendar days, except for the three conditions allowed under 40 CFR 60.753(b). If negative pressure cannot be achieved without excess air infiltration within fifteen (15) calendar days of the first measurement, the gas collection system shall be expanded to correct the exceedance within 120 days of the initial measurement of positive pressure. Any attempted corrective measure shall not cause exceedances of other operational or performance standards. An alternative timeline for correcting the exceedance may be submitted to the Administrator for approval.
 - (4) The Permittee is not required to expand the system as required in 40 CFR 60.755(a)(3) during the first 180 days after gas collection system start-up.
 - (5) For the purpose of identifying whether excess air infiltration into the landfill is occurring, the Permittee shall monitor each well monthly for temperature and nitrogen or oxygen as provided in 40 CFR 60.753(c). If a well exceeds one of these operating parameters, action shall be initiated to correct the exceedance within five (5) calendar days. If correction of the exceedance cannot be achieved within fifteen (15) calendar days of the first measurement, the gas collection system shall be expanded to correct the exceedance within 120 days of the initial exceedance. Any attempted corrective measure shall not cause exceedances of other operational or performance standards. An alternative timeline for correcting the exceedance may be submitted to the Administrator for approval.
 - (6) If the Permittee seeks to demonstrate compliance with 40 CFR 60.752(b)(2)(ii)(A)(4) through the use of a collection system not conforming to the specifications provided in 40 CFR 60.759 shall provide information satisfactory to the Office of Air Quality (OAQ) as specified in 40 CFR 60.752 (b)(2)(i)(C) demonstrating that off-site migration is being controlled.
- (b) For purposes of compliance with 40 CFR 60.753(a), the Permittee shall place each well or design component of a controlled landfill as specified in the approved design plan as provided in 40 CFR 60.752(b)(2)(i). Each well shall be installed no later than 60 days

after the date on which the initial solid waste has been in place for a period of five (5) years or more if active or two (2) years or more if closed or at final grade.

- (c) The following procedures shall be used for compliance with the surface methane operational standard as provided in 40 CFR 60.753 (d):
- (1) After installation of the collection system, the Permittee shall monitor surface concentrations of methane along the entire perimeter of the collection area and along a pattern that traverses the landfill at 30 meter intervals (or a site-specific established spacing) for each collection area on a quarterly basis using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in 40 CFR 60.755(d).
 - (2) The background concentration shall be determined by moving the probe inlet upwind and downwind outside the boundary of the landfill at a distance of at least 30 meters from perimeter wells.
 - (3) Surface emission monitoring shall be performed in accordance with section 4.3.1 of Method 21 of appendix A of 40 CFR60, except that the probe inlet shall be placed within five (5) to ten (10) centimeters of the ground. Monitoring shall be performed during typical meteorological conditions.
 - (4) Any reading of 500 parts per million or more above background at any location shall be recorded as a monitored exceedance and the actions specified in 40 CFR 60.755(c)(4)(i) through (v) should be taken. As long as the specified actions are taken, the exceedance is not a violation of the operational requirements of 40 CFR 60.753(d).

The location of each monitored exceedance shall be marked and the location recorded.

Cover maintenance or adjustments to the vacuum of the adjacent wells to increase the gas collection in the vicinity of each exceedance shall be made and the location shall be re-monitored with ten (10) calendar days of detecting the exceedance.

If the re-monitoring of the location shows a second exceedance, additional corrective action shall be taken and the location shall be monitored again within ten (10) days of the second exceedance. If re-monitoring shows a third exceedance for the same location, the action specified in paragraph 40 CFR 60.755(c)(4)(v) shall be taken, and no further monitoring of that location is required until the action specified in 40 CFR 60.755(c)(4)(v) has been taken.

Any location that initially showed an exceedance but has a methane concentration less than 500 ppm methane above background at the 10-day re-monitoring specified in 40 CFR 60.755(c)(4)(ii) or (iii) shall be re-monitored one (1) month from the initial exceedance. If the one (1)-month re-monitoring shows a concentration less than 500 parts per million above background, no further monitoring of that location is required until the next quarterly monitoring period. If the one (1)-month re-monitoring shows an exceedance, the actions specified in 40 CFR 60.755(c)(4)(iii) or (v) shall be taken.

For any location where monitored methane concentration equals or exceeds 500 parts per million above background three times within a quarterly period, a new well or other collection device shall be installed within 120 calendar of the initial exceedance. An alternative remedy to the exceedance, such as upgrading the

blower, header pipes or control device, and a corresponding timeline for installation may be submitted to the Office of Air Quality (OAQ) for approval.

- (5) The Permittee shall implement a program to monitor for cover integrity and implement cover repairs as necessary on a monthly basis.
- (d) The Permittee seeking to comply with the provisions of 40 CFR 60.755(c) shall comply with the following instrumentation specifications and procedures for surface emission monitoring devices:
 - (1) The portable analyzer shall meet the instrument specifications provided in section 3 of Method 21 of appendix A of 40 CFR 60, except that "methane" shall replace all references to volatile organic compound (VOC).
 - (2) The calibration gas shall be methane, diluted to a nominal concentration of 500 parts per million in air.
 - (3) To meet the performance evaluation requirements in section 3.1.3 of Method 21 of appendix A of 40 CFR 60, the instrument evaluation procedures of section 4.4 of Method 21 of appendix A of 40 CFR 60 shall be used.
 - (4) The calibration procedures provided in section 4.2 of Method 21 of appendix A of 40 CFR 60 shall be followed immediately before commencing a surface monitoring survey.
- (e) The provisions of 40 CFR 60.755 shall apply at all times, except during periods of startup, shutdown, or malfunction, provided that the duration of start-up, shutdown, or malfunction, shall not exceed five (5) days for collection systems and shall not exceed one (1) hour for treatment or control devices.

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.10 Calculation of Non-methane Organic Compound (NMOC) Rate [40 CFR 60.754] [326 IAC 8-8.1] [326 IAC 12]

Pursuant to 40 CFR 60.754 the Permittee shall:

- (a) Calculate the non methane organic compound (NMOC) emission rate using either equation provided in 40 CFR 60.754(a)(1)(i) or the equation provided in 40 CFR 60.754(a)(1)(ii). Both equations may be used if the actual year-to-year solid waste acceptance rate is known, as specified in 40 CFR 754(a)(1)(i), for part of the life of the landfill and the actual year-to-year solid waste acceptance rate is unknown, as specified in 40 CFR 754(a)(1)(i), for part of the life of the landfill. The values to be used in both equations are 0.05 per year for k, 170 cubic meters per megagram for L_0 , and 4,000 parts per million by volume as hexane for the C_{NMOC} . For landfills located in geographical areas with a thirty year annual average precipitation of less than 25 inches, as measured at the nearest representative official meteorologic site, the k value to be used is 0.02 per year.

The following equation shall be used if the actual year-to-year solid waste acceptance rate is known:

$$M_{NMOC} = \sum_{i=1}^n 2 k L_0 M_i (e^{-kt_i}) (C_{NMOC}) (3.6 \times 10^9)$$

where,

M_{NMOC} = Total NMOC emission rate from the landfill, megagrams per year
k = methane generation rate constant, year⁻¹

L_o = methane generation potential, cubic meters per megagram solid waste

M_i = mass of solid waste in the i^{th} section, megagrams

t_i = age of the i^{th} section, years

C_{NMOC} = concentration of NMOC, parts per million by volume as hexane

3.6×10^{-9} = conversion factor

The mass of the nondegradable solid waste may be subtracted from the total mass of solid waste in a particular section of the landfill when calculating the value for M_i if the documentation provisions of 40 CFR 60.758(d)(2) are followed.

The following equation shall be used if the actual year-to-year solid waste acceptance rate is unknown:

$$M_{\text{NMOC}} = 2 L_o R (e^{-kc} - e^{-kt})(C_{\text{NMOC}})(3.6 \times 10^{-9})$$

where,

M_{NMOC} = mass emission rate of NMOC, megagrams per year

L_o = methane generation potential, cubic meters per megagram solid waste

R = average annual acceptance rate, megagrams per year

k = methane generation rate constant, year⁻¹

t = age of landfill, years

C_{NMOC} = concentration of NMOC, parts per million by volume as hexane

c = time since closure, years. For active landfill $c = 0$ and $e^{-kc} = 1$

3.6×10^{-9} = conversion factor

The mass of the nondegradable solid waste may be subtracted from the total mass of solid waste in a particular section of the landfill when calculating the value for M_i if the documentation provisions of 40 CFR 60.758(d)(2) are followed.

If the calculated non methane organic compound (NMOC) emission rate is equal to or greater than 50 megagrams per year, then the Permittee shall either comply with the provisions of 40 CFR 60.752 (b)(2) or determine a site-specific non methane organic compound (NMOC) emission rate using the procedures described in 40 CFR 60.754 (a)(3).

- (b) Tier 1. The Permittee shall compare the calculated NMOC mass emission rate to the standard of 50 megagrams per year.

If the NMOC emission rate calculated in 40 CFR 60.754(a)(1) is less than 50 megagrams per year, then the landfill owner shall submit an emission rate report as provided in 40 CFR 60.757(b)(1), and shall recalculate the NMOC mass emission rate annually as required under 40 CFR 60.752(b)(1). If the calculated NMOC emission rate is equal to or greater than 50 megagrams per year, then the Permittee shall either comply with 40 CFR 60.752(b)(2), or determine a site-specific NMOC concentration and recalculate the NMOC emission rate using the procedures provided in 40 CFR 60.754(a)(3).

Tier 2. The Permittee shall determine the NMOC concentration using the following sampling procedure. The Permittee shall install at least two sample probes per hectare of landfill surface that has retained waste for at least 2 years. If the landfill is larger than 25 hectares in area, only 50 samples are required. The sample probes should be located to avoid known areas of nondegradable solid waste. The Permittee shall collect and analyze one sample of landfill gas from each probe to determine the NMOC concentration using Method 25C of appendix A of 40 CFR 60 or Method 18 of appendix A of 40 CFR 60. If using Method 18 of appendix A of 40 CFR 60, the minimum list of compounds to be tested shall be those published in the most recent Compilation of Air Pollutant Emission Factors

(AP-42). If composite sampling is used, equal volumes shall be taken from each sample probe. If more than the required number of samples are taken, all samples shall be used in analysis. The Permittee shall divide the NMOC concentration from Method 25C of appendix A by six to convert from C_{NMOC} as carbon to C_{NMOC} as hexane.

The Permittee shall recalculate the NMOC mass emission rate using the equations provided in 40 CFR 60.754(a)(1)(i) and (a)(1)(ii) and using the average NMOC concentration from the collected samples instead of the default value in the equation provided in 40 CFR 60.754(a)(1).

If the resulting mass emission rate calculated using the site-specific NMOC concentration is equal to or greater than 50 megagrams per year, then the Permittee shall either comply with 40 CFR 60.752(b)(2), or determine the site-specific methane generation rate constant and recalculate the NMOC emission rate using the site-specific methane generation rate using the procedure specified in 40 CFR 60.754(a)(4).

If the resulting NMOC mass emission rate is less than 50 megagrams per year, the Permittee shall submit a periodic estimate of the emission rate report as provided in 40 CFR 60.757(b)(1) and retest the site-specific NMOC concentration every five (5) years using the methods in 40 CFR 60.754(a)(3).

Tier 3. The site-specific methane generation rate constant shall be determined using the procedures provided in Method 2E of appendix A of 40 CFR 60.

The Permittee shall estimate the NMOC mass emission rate using equations in 40 CFR 60.754(a)(1)(i) or (a)(1)(ii) and using a site-specific methane generation rate constant k , and the site-specific NMOC concentration as determined in 40 CFR 60.754(a)(3) instead of the default values provided in 40 CFR 60.754(a)(1). The Permittee shall compare the resulting NMOC mass emission rate to the standard of 50 megagrams per year.

If the NMOC mass emission rate as calculated using the site-specific methane generation rate and concentration of NMOC is equal to or greater than 50 megagrams per year, the Permittee shall comply with 40 CFR 60.752(b)(2).

If the NMOC mass emission rate is less than 50 megagrams per year, then the Permittee shall submit a periodic emission rate report as provided in 40 CFR 60.757(b)(1) and shall recalculate the NMOC mass emission rate annually, as provided in 40 CFR 60.757(b)(1) using the equations in 40 CFR 60.754(a)(1) and using the site-specific methane generation rate constant and NMOC concentration obtained in 40 CFR 60.754(a)(3). The calculation of the methane generation rate constant is performed only once, and the value obtained from this test shall be used in all subsequent annual NMOC emission rate calculations.

The Permittee may use other methods to determine the NMOC concentration or a site-specific k as an alternative to the methods required in 40 CFR 60.754(a)(3) and (a)(4) if the method has been approved by the Administrator as provided in 40 CFR 60.752(b)(2)(i)(B).

- (c) The Permittee subject to 40 CFR 60.754 shall estimate the NMOC emission rate for comparison to the PSD major source and significance levels in 40 CFR 51.166 or 40 CFR 52.21 using AP-42 or other approved measurement procedures. If a collection system, which complies with the provisions of 40 CFR 60.752(b)(2) is already installed, the Permittee shall estimate the NMOC emission rate using the procedures provided in 40 CFR 60.754(b).

Pursuant to 40 CFR 60.757, except as provided in 40 CFR 60.752(b)(2)(i)(B), the Permittee shall:

- (a) Submit an initial design capacity report to the Office of Air Quality (OAQ) no later than 90 days after October 8, 1997. An amended design capacity report shall be submitted to the Office of Air Quality (OAQ) providing notification of any increase in the design capacity of the landfill. The Permittee submitted the initial design report on June 17, 1996.
- (b) Submit a non methane organic compound (NMOC) emission rate report to the Office of Air Quality initially and annually thereafter, except as provided for in 40 CFR 60.757(b)(1)(ii) or (b) (3). The Office of Air Quality (OAQ) may request such additional information as may be necessary to verify the reported NMOC emission rate. The report should contain an annual or 5-year estimate of the non methane organic compound (NMOC) emission rate using the formula and procedures provided in 40 CFR 60.754 (a) or (b), as applicable. The initial NMOC emission rate report may be combined with the initial design capacity report required in 40 CFR 60.757(a) and shall be submitted no later than indicated in 40 CFR 60.757(b)(1)(i)(A) and (B). June 10, 1996 for landfills that commenced construction, modification, or reconstruction on or after May 30, 1991, but before March 12, 1996, or ninety days after the date of commenced construction, modification, or reconstruction for landfills that commenced construction, modification, or reconstruction on or after March 12, 1996.

Subsequent NMOC emission rate reports shall be submitted annually thereafter, except as provided in 40 CFR 60.757(b)(1)(ii) and (b)(3). If the estimated NMOC emission rate as reported in the annual report to the Office of Air Quality (OAQ) is less than 50 megagrams per year in each of the next five (5) consecutive years, the Permittee may elect to submit an estimate of the NMOC emission rate for the next five (5) year period in lieu of the annual report. This estimate shall include the current amount of solid waste-in-place and the estimated waste acceptance rate for each year of the five (5) years for which an NMOC emission rate is estimated. All data and calculations upon which this estimate is based shall be provided to the Office of Air Quality (OAQ). This estimate shall be revised at least once every five (5) years. If the actual waste acceptance rate exceeds the estimated waste acceptance rate in any year reported in the five (5) year estimate, a revised five (5) year estimate shall be submitted to the Office of Air Quality. The revised estimate shall cover the five (5) year period beginning with the year in which the actual waste acceptance rate exceeded the estimated waste acceptance rate. The NMOC emission rate report shall include all the data, calculations, sample reports, and measurements used to estimate the annual or five (5) year emission rate. The Permittee is exempted from the requirements of 40 CFR 60.757(b)(1) and (2) after the installation of a collection and control system in compliance with 40 CFR 60.752 (b)(2), during such time as the system is in operation and in compliance with 40 CFR 60.753 and 60.755.

- (c) Submit a collection and control system design plan to the Office of Air Quality (OAQ) within one (1) year of the first non methane organic compound (NMOC) emission rate report, required under 40 CFR 60.757(b), in which NMOC emission rate exceeds 50 megagrams (Mg) per year; except if the Permittee elects to recalculate the NMOC emission rate after Tier 2 sampling and analysis as provided in 40 CFR 60.754(a)(3) and the resulting rate is less than 50 megagrams per year, annual periodic reporting shall be resumed, using the Tier 2 determined site-specific NMOC concentration, until the calculated emission rate is equal to or greater than 50 megagrams per year or the landfill is closed. The revised NMOC emission rate report, with the recalculated emission rate based on NMOC sampling and analysis, shall be submitted within 180 days of the first calculated exceedance of 50 megagrams per year. If the Permittee elects to recalculate the NMOC emission rate after determining a site-specific methane generation rate constant (k), as provided in Tier 3 in 40 CFR 60.754(a)(4), and the resulting NMOC emission rate is less than 50 megagrams per year, annual periodic reporting shall be resumed. The resulting site-specific methane generation rate constant (k) shall be used in the emission rate calculation until such time as the emissions rate calculation results in

an exceedance. The revised NMOC emission rate report based on the provisions of 40 CFR 60.754(a)(4) and the resulting site-specific methane generation rate constant (k) shall be submitted to the Office of Air Quality (OAQ) within one (1) year of the first calculated emission rate exceeding 50 megagrams per year.

- (d) Submit a closure report to the Office of Air Quality (OAQ) within thirty days of waste acceptance cessation. The Office of Air Quality (OAQ) may request additional information as may be necessary to verify that permanent closure has taken place in accordance with the requirements of 40 CFR 258.60. If a closure report has been submitted to the Office of Air Quality (OAQ), no additional wastes may be placed into the landfill without filing a notification of modification as described under 40 CFR 60.7(a)(4).
- (e) Submit an equipment removal report to the Office of Air Quality (OAQ) thirty (30) days prior to removal or cessation of operation of the control equipment. The equipment removal report shall contain all of the following items: a copy of the closure report submitted in accordance with 40 CFR 60.757(d), a copy of the initial performance test report demonstrating that the fifteen (15) year minimum control period has expired, and dated copies of three (3) successive NMOC emission rate reports demonstrating that the landfill is no longer producing 50 megagrams or greater of NMOC per year. The Office of Air Quality (OAQ) may request such additional information as may be necessary to verify that all of the conditions for removal in 40 CFR 60.752(b)(2)(v) have been met.
- (f) Annual reports of the following recorded information. The initial annual report shall be submitted within 180 days of installation and start-up of the collection and control system, and shall include the initial performance test report required under 40 CFR 60.8. For enclosed combustion devices and flares, reportable exceedances are defined under 40 CFR 60.758(c).
 - (1) Value and length of time for exceedance of applicable parameters monitored under 40 CFR 60.756(a), (b), (c), and (d).
 - (2) Description and duration of all periods when the control device was not operating for a period exceeding one (1) hour and length of time the control device was not operating.
 - (3) All periods when the collection system was not operating in excess of five (5) days.
 - (4) Location of each exceedance of the 500 parts per million methane concentration as provided in 40 CFR 60.753(d) and the concentration recorded at each location for which an exceedance was recorded in the previous month.
 - (5) Date of installation and the location of each well or collection system expansion added pursuant to 40 CFR 60.755(a)(3), (b), and (c)(4).
- (g) The Permittee seeking to comply with 40 CFR 40.752(b)(2)(iii) shall include the following information with the initial performance test report required under 40 CFR 60.8:
 - (1) A diagram of the collection system showing collection system positioning including all wells, horizontal collectors, surface collectors, or other gas extraction devices, including the locations of any areas excluded from collection and the proposed sites for the future collection system expansion.
 - (2) The data upon which the sufficient density of wells, horizontal collectors, surface collectors, or other gas extraction devices and the gas mover equipment sizing are based.

- (3) The documentation of the presence of asbestos or nondegradable material for each area from which collection wells have been excluded based on the presence of asbestos or nondegradable material.
- (4) The sum of the gas generation flow rates for all areas from which collection wells have been excluded based on nonproductivity and the calculations of gas generation flow rate for each excluded area.
- (5) The provisions for increasing gas mover equipment capacity with increased gas generation flow rate, if the present gas mover equipment is inadequate to move the maximum flow rate expected over the life of the landfill
- (6) The provisions for the control of off-site migration.
- (h) A summary of the above information shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit.

D.1.12 Recordkeeping for NESHAP for Active Waste Disposal Sites [40 CFR 61.154] [326 IAC 14]

- (a) For all asbestos containing waste material received, the owner or operator of the active waste disposal site shall:
 - (1) Maintain waste shipment records, using a form similar to that shown in figure 4 of 40 CFR 61, Subpart M, and include the following information
 - (A) The name, address, and telephone number of the waste generator;
 - (B) The name, address, and telephone number of the transporter(s);
 - (C) The quantity of the asbestos containing waste material in cubic meters (cubic yards).
 - (D) The presence of improperly enclosed or uncovered waste, or any asbestos-containing waste material not sealed in leak-tight containers. Report in writing to the local, State, or EPA Regional office responsible for administering the asbestos NESHAP program for the waste generator (identified in the waste shipment record), and if different, the local, State, or EPA Regional office responsible for administering the asbestos NESHAP program for the disposal site, by the following working day, the presence of a significant amount of improperly enclosed or uncovered waste. Submit a copy of the waste shipment record along with the report.
 - (E) The date of the receipt.
 - (2) As soon as possible and no longer than 30 days after receipt of the waste, send a copy of the signed waste shipment record to the waste generator.
 - (3) Upon discovering a discrepancy between the quantity of waste designated on the waste shipment records and the quantity actually received, attempt to reconcile the discrepancy with the waste generator. If the discrepancy is not resolved within 15 days after receiving the waste, immediately report in writing to the local, State, or EPA Regional office responsible for administering the asbestos NESHAP program for the waste generator (identified in the waste shipment record), and if different, the local, State, or EPA Regional office responsible for administering the asbestos NESHAP program for the disposal site. Describe the discrepancy and attempts to reconcile it, and submit a copy of the waste shipment record along with the report.

- (4) Retain a copy of all records and reports required by this paragraph for at least 2 years.
- (b) Maintain until closure, records of the location, depth and area, and quantity in cubic meters (cubic yards) of asbestos-containing waste material within the disposal site on a map or diagram of the disposal area.
- (c) Upon closure, comply with all the provisions of 40 CFR 61.151.
- (d) Submit to the Administrator, upon closure of the facility, a copy of records of asbestos waste disposal locations and quantities.
- (e) Furnish upon request, and make available during normal business hours for inspection by the Administrator, all records required under this section.
- (f) Notify the Administrator in writing at least 45 days prior to excavating or otherwise disturbing any asbestos-containing waste material that has been deposited at a waste disposal site and is covered. If the excavation will begin on a date other than the one contained in the original notice, notice of the new start date must be provided to the Administrator at least 10 working days before excavation begins and in no event shall excavation begin earlier than the date specified in the original notification. Include the following information in the notice:
 - (1) Scheduled starting and completion dates.
 - (2) Reason for disturbing the waste.
 - (3) Procedures to be used to control emissions during the excavation, storage, transport, and ultimate disposal of the excavated asbestos-containing waste material. If deemed necessary, the Administrator may require changes in the emission control procedures to be used.
 - (4) Location of any temporary storage site and the final disposal site.

D.1.13 Record Keeping and Reporting Requirements for NSPS for Municipal Solid Waste Landfills [40 CFR 60.758] [326 IAC 8-8.1] [326 IAC 12]

-
- (a) Except as provided in 40 CFR 60.752(b)(2)(i)(B) the Permittee subject to 40 CFR 60.752(b) shall keep for at least five years up-to-date, readily accessible, continuous on-site records of the design capacity report which triggered 40 CFR 60.752(b), the current amount of solid waste in-place, and the year-by-year waste acceptance rate. Off-site records may be maintained if they are retrievable within four (4) hours. Either paper copy or electronic formats are acceptable.
 - (b) Except as provided in 40 CFR 60.752(b)(2)(i)(B) the Permittee of a controlled landfill shall keep up-to-date, readily accessible records for the life of the control equipment listed in (a) through (d) below as measured during the initial performance test or compliance determination. Records of subsequent tests or monitoring shall be maintained for a minimum of five (5) years. Records of control device vendor specifications shall be maintained until removal.
 - (1) Where the Permittee subject to the provisions of 40 CFR 60.758 seeks to demonstrate compliance with 40 CFR 60.752(b)(2)(ii):

The maximum expected gas generation flow rate as calculated in 40 CFR 60.755(a)(1). The Permittee may use another method to determine the maximum gas generation flow rate, if the method has been approved by the Office of Air Quality (OAQ).

The density of wells, horizontal collectors, surface collectors, or other gas extraction devices determined using the procedures specified in 40 CFR 60.759(a)(1).

- (2) Where the Permittee subject to the provisions of 40 CFR 60.758 seeks to demonstrate compliance with 40 CFR 60.752(b)(2)(iii)(A) through use of an open flare, the flare type (i.e., steam-assisted, air -assisted, or nonassisted), all visible emission readings, heat content determination, flow rate or bypass flow rate measurements, and exit velocity determinations made during the performance test as specified in 40 CFR 60.18; continuous records of the flare pilot flame or flare flame monitoring and records of all periods of operations during which the pilot flame of the flare flame is absent.
- (c) Except as provided in 40 CFR 60.752(b)(2)(i)(B) the Permittee of a controlled landfill subject to the provisions of this subpart shall keep for five years up-to-date, readily accessible, continuous on-site records of the equipment operating parameters specified to be monitored in 40 CFR 60.756 as well as up-to-date, readily accessible records for periods of operation during which the parameter boundaries established during the most recent performance test are exceeded.
 - (1) The Permittee seeking to comply with the provisions of 40 CFR 60.758 by use of an open flare shall keep up-to-date, readily accessible continuous records of the flame or flare pilot flame monitoring specified under 40 CFR 60.756(c), and up-to-date, readily accessible records of all periods of operation in which the flame or flare pilot flame is absent.
- (d) Except as provided in 40 CFR 60.752(b)(2)(i)(B) the Permittee subject to the provisions of this subpart shall keep for the life of the collection system an up-to-date, readily accessible plot map showing each existing and planned collector in the system and providing a unique identification location label for each collector.
 - (1) The Permittee subject to the provisions of 40 CFR 60.758 shall keep up-to-date, readily accessible records of the installation date and location of all newly installed collectors as specified in 40 CFR 60.755 (b).
 - (2) The Permittee subject to the provisions of 40 CFR 60.758 shall keep readily accessible documentation of the nature, date of deposition, amount, and location of asbestos-containing or nondegradable waste excluded from collection as provided in 40 CFR 60.759 (a)(3)(i) as well as any non-productive areas excluded from collection as provided in 40 CFR 60.759 (a)(3)(ii).
- (e) Except as provided in 40 CFR 60.752(b)(2)(i)(B) the Permittee subject to the provisions of this subpart shall keep for at least five years up-to-date, readily accessible records of all collection and control system exceedances of the operational standards in 40 CFR 60.753, the reading in the subsequent month whether or not the second reading is an exceedance, and the location of each exceedance.
- (f) Permittees who convert design capacity from volume to mass or mass to volume to demonstrate that landfill design capacity is less than 2.5 million megagrams or 2.5 million cubic meters, as provided in the definition of "design capacity", shall keep readily accessible, on-site records of the annual recalculation of site-specific density, design capacity, and the supporting documentation. Off-site records may be maintained if they are retrievable within 4 hours. Either paper copy or electronic formats are acceptable.

D.1.14 Record Keeping and Reporting Requirements for NESHAP for Municipal Solid Waste Landfills [40 CFR 63.1980] [326 IAC 20-37]

Pursuant to 40 CFR 63.1980, the Permittee shall:

- (a) Keep records and reports as specified in 40 CFR 60, Subpart WWW, with one exception: The Permittee must submit the annual report described in 40 CFR 60.757(f) and Condition D.1.11(f) every six (6) months.
- (b) Keep records and reports as specified in the general provisions of 40 CFR 60 and 40 CFR 63 as shown in Table 1 of 40 CFR 63, Subpart AAAA. Applicable records in the general provisions include items such as SSM plans and the SSM plan reports. The SSM Plan report shall be submitted semi-annually to IDEM, OAQ.

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (c) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG1 through EG5, and a single fuel gas compressor. The generators are rated at 800 kilowatts each, and were installed in 1994 and 1996.
- (d) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG5 through EG8, rated at 800 kilowatts each and exhausting to stacks ES5 through ES8, respectively.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

There are no applicable state or federal requirements for these emission units.

SECTION D.3

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)] Insignificant Activities

- (w) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. [326 IAC 8-3-2] [326 IAC 8-3-5]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations), the owner or operator shall:

- (a) Equip the cleaner with a cover;
- (b) Equip the cleaner with a facility for draining cleaned parts;
- (c) Close the degreaser cover whenever parts are not being handled in the cleaner;
- (d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;
- (e) Provide a permanent, conspicuous label summarizing the operation requirements;
- (f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

D.3.2 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]

- (a) Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaner degreaser facility shall ensure that the following control equipment requirements are met:
 - (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:
 - (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)));
 - (B) The solvent is agitated; or
 - (C) The solvent is heated.
 - (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury) or six-tenths (0.6) pounds per square inch measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.

- (3) Provide a permanent, conspicuous label which lists the operating requirements outlined in subsection (b).
 - (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure which does not cause excessive splashing.
 - (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury) or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38^oC) (one hundred degrees Fahrenheit (100^oF)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9^oC) (one hundred twenty degrees Fahrenheit (120^oF)):
 - (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
 - (B) A water cover when solvent is used is insoluble in, and heavier than, water.
 - (C) Other systems of demonstrated equivalent control such as a refrigerated chiller or carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.
- (b) Pursuant to 326 IAC 8-3-5(b) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaning facility shall ensure that the following operating requirements are met:
- (1) Close the cover whenever articles are not being handled in the degreaser.
 - (2) Drain cleaned articles for at least fifteen (15) seconds or until dripping ceases.
 - (3) Store waste solvent only in covered containers and prohibit the disposal or transfer of waste solvent in any manner in which greater than twenty percent (20%) of the waste solvent by weight could evaporate.

D.3.3 Hazardous Air Pollutants (HAPs)

Pursuant to the 40 CFR Part 63 National Emission Standards for Hazardous Air Pollutants: Halogenated Solvent Cleaning, Subpart T, the solvent used in the parts washers shall not contain any of the following halogenated solvents in concentrations greater than five percent by weight: methylene chloride, 1,1,1-trichloroethane, trichloroethylene, perchloroethylene, carbon tetrachloride, or chloroform.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION

PART 70 OPERATING PERMIT
CERTIFICATION**

Source Name: Twin Bridges Recycling (Waste Management of Indiana)
Source Address: 124 East Twin Bridges Road, Danville, IN 46122
Mailing Address: 124 East Twin Bridges Road, Danville, IN 46122
Part 70 Permit No.: T063-7998-00029

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION
100 North Senate Avenue
Indianapolis, Indiana 46204-2251
Phone: 317-233-0178
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: Twin Bridges Recycling (Waste Management of Indiana)
Source Address: 124 East Twin Bridges Road, Danville, IN 46122
Mailing Address: 124 East Twin Bridges Road, Danville, IN 46122
Part 70 Permit No.: T063-7998-00029

This form consists of 2 pages

Page 1 of 2

Check either No. 1 or No.2
<input type="checkbox"/> 1. This is an emergency as defined in 326 IAC 2-7-1(12) <ul style="list-style-type: none">• The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and• The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16
<input type="checkbox"/> 2. This is a deviation, reportable per 326 IAC 2-7-5(3)(c) <ul style="list-style-type: none">• The Permittee must submit notice in writing within ten (10) calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency/Deviation:
Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by:
Title / Position:
Date:
Phone:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
SEMI-ANNUAL COMPLIANCE MONITORING REPORT**

Source Name: Twin Bridges Recycling (Waste Management of Indiana)
Source Address: 124 East Twin Bridges Road, Danville, IN 46122
Mailing Address: 124 East Twin Bridges Road, Danville, IN 46122
Part 70 Permit No.: T063-7998-00029

Months: _____ to _____ Year: _____

This report is an affirmation that the source has met all the compliance monitoring requirements stated in this permit. This report shall be submitted semi-annually. Any deviation from the compliance monitoring requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify in the box marked ΔNo deviations occurred this reporting period@.

NO DEVIATIONS OCCURRED THIS REPORTING PERIOD

THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD.

Compliance Monitoring Requirement (e.g. Permit Condition D.1.3)	Number of Deviations	Date of each Deviation

Form Completed By:
Title/Position:
Date:
Phone:

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Quality

Addendum to the Technical Support Document for a Significant Permit Modification to a Part 70 Operating Permit

Source Name:	Twin Bridges Recycling (Waste Management of Indiana)
Source Location:	124 East Twin Bridges Road, Danville, IN 46122
County:	Hendricks
SIC Code:	4953
Operation Permit No.:	T063-7998-00029
Significant Permit Modification No.:	063-23080-00029
Permit Reviewer:	Jenny Acker

On July 20, 2006, the Office of Air Quality (OAQ) had a notice published in the Hendricks County Flyer, Plainfield, Indiana, stating that Twin Bridges Recycling (Waste Management of Indiana) had applied for a Significant Permit Modification to a Part 70 Operating Permit relating to the revision of compliance determination and monitoring requirements. The notice also stated that OAQ proposed to issue a permit for this modification and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

Upon further review, the OAQ has decided to make the following revisions to the permit (bolded language has been added, the language with a line through it has been deleted).

1. 326 IAC 9 was approved into the Indiana SIP on November 30, 2004, with an effective date of January 31, 2005. Therefore, Condition C.4 – Incineration is now federally enforceable. Condition C.4 - Incineration has been revised as follows:

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. ~~326 IAC 9-1-2 is not federally enforceable.~~

2. On August 7, 2006, a temporary emergency rule took effect redesignating Delaware, Greene, Jackson, Vanderburgh, Vigo and Warrick Counties to attainment for the eight-hour ozone standard, redesignating Lake County to attainment for the sulfur dioxide standard, and revoking the one-hour ozone standard in Indiana. The Indiana Air Pollution Control Board has approved a permanent rule revision to incorporate these changes into 326 IAC 1-4-1. The permanent revision to 326 IAC 1-4-1 will take effect prior to the expiration of the emergency rule.

No change will be made to the original TSD. The OAQ prefers that the TSD reflect the permit that was on public notice. Changes to the technical support material that occur after the public notice are documented in this Addendum to the Technical Support Document. This accomplishes the desired result of ensuring that these types of concerns are documented and part of the record regarding this permit decision. The following changes document the revised County Attainment Status:

County Attainment Status

The source is located in Hendricks County.

Pollutant	Status
PM10	Attainment
PM2.5	Nonattainment
SO ₂	Attainment
NO ₂	Attainment
1-hour Ozone	Attainment
8-hour Ozone	Nonattainment
CO	Attainment
Lead	Attainment

**Indiana Department of Environmental Management
Office of Air Quality**

**Technical Support Document (TSD) for a Part 70
Significant Permit Modification**

Source Description and Location
--

Source Name:	Twin Bridges Recycling (Waste Management of Indiana)
Source Location:	124 East Twin Bridges Road, Danville, Indiana 46122
County:	Hendricks
SIC Code:	4953
Operation Permit No.:	T 063-7998-00029
Operation Permit Issuance Date:	July 28, 1999
Significant Permit Modification No.:	063-23080-00029
Permit Reviewer:	Jenny Acker

Existing Approvals

The source was issued Part 70 Operating Permit No. 063-7998-00029 on July 28, 1999. The source has since received the following approvals:

- (a) Minor Source Modification No: 063-14598-00029, issued October 18, 2001
- (b) Significant Permit Modification No: 063-14743-00029, issued December 18, 2001
- (c) Administrative Amendment No.: 063-20086-00029, issued November 12, 2004
- (d) Administrative Amendment No.: 063-20666-00029, issued April 19, 2005
- (e) Administrative Amendment No.: 063-21523-00029, issued July 19, 2005
- (f) Minor Source Modification No.: 063-22322-00029, issued January 20, 2006
- (g) Minor Permit Modification No.: 063-22317-00029, issued on April 21, 2006

The source submitted an application for a Part 70 Operating Permit Renewal on October 28, 2003. At this time, this application (063-18240-00029) is still under review.

County Attainment Status

The source is located in Hendricks County.

Pollutant	Status
PM10	Attainment
PM2.5	Nonattainment
SO ₂	Attainment
NO ₂	Attainment
1-hour Ozone	Attainment
8-hour Ozone	Nonattainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and nitrogen oxides (NO_x) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Hendricks County has been designated as nonattainment for the 8-hour ozone standard. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Emission Offset, 326 IAC 2-3.
- (b) U.S. EPA, in the Federal Register Notice 70 FR 943 dated January 5, 2005, has designated Hendricks County as nonattainment for PM_{2.5}. On March 7, 2005 the Indiana Attorney General's Office, on behalf of IDEM, filed a law suit with the Court of Appeals for the District of Columbia Circuit challenging U.S. EPA's designation of nonattainment areas without sufficient data. However, in order to ensure that sources are not potentially liable for a violation of the Clean Air Act, the OAQ is following the U.S. EPA's guidance to regulate PM₁₀ emissions as a surrogate for PM_{2.5} emissions pursuant to the requirements of Emission Offset, 326 IAC 2-3.
- (c) Hendricks County has been classified as attainment or unclassifiable for PM₁₀, SO₂, NO₂, CO, Lead, and Ozone under the 1-hour standard. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (d) Fugitive Emissions
 Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 or 326 IAC 2-3, fugitive emissions are not counted toward the determination of PSD and Emission Offset applicability.

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the 2004 OAQ emission data.

Pollutant	Actual Emissions (tons/year)
PM	Not Reported
PM10	4
SO ₂	18
VOC	14
CO	131
NO _x	198
HAP	Not reported

Description of Proposed Modification

The Office of Air Quality (OAQ) has reviewed a modification application, submitted by Twin Bridges Recycling & Disposal Facility on May 11, 2006, requesting IDEM, OAQ, to re-evaluate the compliance determination and monitoring requirements. Additionally, the applicable requirements of 40 CFR 63, Subpart AAAAA (National Emission Standards for Hazardous Air Pollutants (NESHAP) for Municipal Solid Waste Landfills) will be incorporated into the Title V permit (063-7998-00029).

This modification does not include any physical change to the source.

Enforcement Issues

There are no pending enforcement actions.

Permit Level Determination – Part 70

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emission unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, IDEM, or the appropriate local air pollution control agency.”

There is no increase in the potential to emit of any regulated pollutants associated with this modification.

This modification to the Part 70 Operating Permit will be through a significant permit modification issued pursuant to 326 IAC 2-7-12 (d), because the modification requires significant changes in existing monitoring Part 70 permit terms and conditions, and requires relaxing recordkeeping permit terms and conditions.

Federal Rule Applicability Determination

- (a) This source is subject to the National Emission Standards for Hazardous Air Pollutants for Municipal Solid Waste (MSW) Landfills, Subpart AAAAA, which is incorporated by reference as 326 IAC 20-67, because the MSW landfill has accepted waste since 1987.
- (b) The eight (8) landfill gas fueled engine/generator sets, identified as EG1 through EG8, are not subject to the requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Stationary Reciprocating Internal Combustion Engines, Subpart ZZZZ, because they are existing engines that combust landfill gas equivalent to 10 percent or more of gross heat input on an annual basis.

State Rule Applicability Determination

There are no new state rules applicable to the source due to this modification.

Compliance Determination and Monitoring Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with all applicable state and federal rules on a continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, Compliance Determination Requirements are included in the permit. The Compliance Determination Requirements in Section D of the permit are those conditions that are found directly within state and federal rules and the violation of which serves as grounds for enforcement action.

If the Compliance Determination Requirements are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

New compliance determination and monitoring requirements per 40 CFR 63, Subpart AAAA, are incorporated in Section D.1 of the permit. Changes to the compliance determination and monitoring requirements are detailed in the Proposed Changes section of this document.

Proposed Changes

- (a) All references to the IDEM, OAQ, Compliance Section telephone number have been revised as follows: ~~317-233-5674~~ **317-233-0178**.

All references to the IDEM, OAQ, Compliance Section facsimile number have been revised as follows: ~~317-233-5967~~ **317-233-6865**.
- (b) To clarify the permit term and the term of the conditions, Conditions B.2 (formerly B.3) - Permit Term and B.17 - Permit Renewal have been modified. Additionally, new Section B conditions, B.3 - Term of Conditions and B.13 - Prior Permits Superseded have been added.
- (c) IDEM has determined that the Permittee is not required to keep records of all preventive maintenance. However, where the Permittee seeks to demonstrate that an emergency has occurred, the Permittee must provide, upon request records of preventive maintenance in order to establish that the lack of proper maintenance did not cause or contribute to the deviation. Therefore, IDEM has deleted paragraph (b) of Condition B.10 (formerly B.11) – Preventive Maintenance and has amended Condition B.11 (formerly B.12) – Emergency Provisions.
- (d) For clarification purposes, Condition B.20 (formerly B.21) - Operational Flexibility has been revised.
- (e) Indiana has incorporated the credible evidence provision in 326 IAC 1-1-6. This rule became effective on March 16, 2005; therefore the condition reflecting this rule will be incorporated into the permit as condition B.25.
- (f) In order to avoid duplication of requirements which may be included in D sections, Condition C.6 – Operation of Equipment has been removed from the permit.
- (g) IDEM realizes that the specifications of Condition C.11 (formerly C.13) - Pressure Gauge Specifications, can only be practically applied to analog units, and has therefore clarified

the condition to state that the condition only applies to analog units. Upon further review, IDEM has also determined that the accuracy of the instruments is not nearly as important as whether the instrument has a range that is appropriate for the normal expected reading of the parameter. Therefore, the language in Condition C.11 (formerly C.13) has been revised.

- (h) The Permittee submitted an Emergency Reduction Plan on May 17, 2002. Therefore, Condition C.12 (formerly Condition C.14) - Emergency Reduction Plans has been revised to reflect the submittal date.
- (i) Revisions to have been made to the Section C – General Recordkeeping and Section C – General Reporting Requirements to reflect NSR (New Source Review) reform provisions at the major sources.

The changes listed below have been made to Part 70 Operating Permit No.: 063-7998-00029. Deleted language appears as ~~strikethroughs~~ and new language appears in **bold**:

SECTION B ~~GENERAL CONDITIONS~~

~~B.1 Permit No Defense [326 IAC 2-1-10] [IC 13]~~

- ~~(a) Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7.~~
- ~~(b) This prohibition shall not apply to alleged violations of applicable requirements for which the Commissioner has granted a permit shield in accordance with 326 IAC 2-1-3.2 or 326 IAC 2-7-15, as set out in this permit in the Section B condition entitled "Permit Shield".~~

~~B.2 Definitions [326 IAC 2-7-1]~~

~~Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.~~

~~B.3 Permit Term [326 IAC 2-7-5(2)]~~

~~This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.~~

~~B.4 Enforceability [326 IAC 2-7-7(a)]~~

- ~~(a) All terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM.~~
- ~~(b) Unless otherwise stated, terms and conditions of this permit, including any provisions to limit the source's potential to emit, are enforceable by the United States Environmental Protection Agency (U.S. EPA) and citizens under the Clean Air Act.~~

~~B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]~~

~~The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).~~

~~B.6 Severability [326 IAC 2-7-5(5)]~~

~~The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.~~

~~B.7 — Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]~~

~~This permit does not convey any property rights of any sort, or any exclusive privilege.~~

~~B.8 — Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]~~

~~(a) — The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:~~

~~Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

~~(b) — The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit.~~

~~(c) — Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit. If the Permittee wishes to assert a claim of confidentiality over any of the furnished records, the Permittee must furnish such records to IDEM, OAQ, along with a claim of confidentiality under 326 IAC 17. If requested by IDEM, OAQ, or the U.S. EPA, to furnish copies of requested records directly to U. S. EPA, and if the Permittee is making a claim of confidentiality regarding the furnished records, then the Permittee must furnish such confidential records directly to the U.S. EPA along with a claim of confidentiality under 40 CFR 2, Subpart B.~~

~~B.9 — Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]~~

~~(a) — Any application form, report, or compliance certification submitted under this permit shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this permit, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.~~

~~(b) — One (1) certification shall be included, on the attached Certification Form, with each submittal.~~

~~(c) — A responsible official is defined at 326 IAC 2-7-1(34).~~

~~B.10 — Annual Compliance Certification [326 IAC 2-7-6(5)]~~

~~(a) — The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:~~

~~Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

~~and~~

~~United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch—Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590~~

- (b) ~~The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.~~
- (c) ~~The annual compliance certification report shall include the following:~~
- (1) ~~The identification of each term or condition of this permit that is the basis of the certification;~~
 - (2) ~~The compliance status;~~
 - (3) ~~Whether compliance was continuous or intermittent;~~
 - (4) ~~The methods used for determining compliance of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3);~~
 - (5) ~~Any insignificant activity that has been added without a permit revision; and~~
 - (6) ~~Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.~~

~~The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

~~B.11 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]~~

-
- (a) ~~If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each facility:~~
- (1) ~~Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;~~
 - (2) ~~A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;~~
 - (3) ~~Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.~~

~~If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:~~

~~Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

- (b) ~~The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.~~
- (c) ~~PMP's shall be submitted to IDEM, OAQ, upon request and shall be subject to review and approval by IDEM, OAQ.~~

~~B.12 Emergency Provisions [326 IAC 2-7-16]~~

~~(a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-7-16.~~

~~(b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:~~

~~(1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;~~

~~(2) The permitted facility was at the time being properly operated;~~

~~(3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;~~

~~(4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;~~

~~Telephone Number: 1-800-451-6027 (ask for Office of Air Quality,
Compliance Section), or~~

~~Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967~~

~~(5) For each emergency lasting one (1) hour or more, the Permittee submitted notice, either in writing or facsimile, of the emergency to:~~

~~Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

~~within two (2) working days of the time when emission limitations were exceeded due to the emergency.~~

~~The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:~~

~~(A) A description of the emergency;~~

~~(B) Any steps taken to mitigate the emissions; and~~

~~(C) Corrective actions taken.~~

~~The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

~~(6) The Permittee immediately took all reasonable steps to correct the emergency.~~

~~(c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.~~

- (d) ~~This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.~~
- (e) ~~IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4 (c)(9) be revised in response to an emergency.~~
- (f) ~~Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.~~
- (g) ~~Operations may continue during an emergency only if the following conditions are met:~~
 - (1) ~~If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.~~
 - (2) ~~If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:~~
 - (A) ~~The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and~~
 - (B) ~~Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value.~~

~~Any operation shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.~~

~~B.13 Permit Shield [326 IAC 2-7-15]~~

- (a) ~~This condition provides a permit shield as addressed in 326 IAC 2-7-15.~~
- (b) ~~This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits. Compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that:~~
 - (1) ~~The applicable requirements are included and specifically identified in this permit;~~
~~or~~
 - (2) ~~The permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable.~~
- (c) ~~If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.~~
- (d) ~~No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application.~~

- (e) ~~Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:~~
- (1) ~~The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;~~
 - (2) ~~The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;~~
 - (3) ~~The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and~~
 - (4) ~~The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.~~
- (f) ~~This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).~~
- (g) ~~This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]~~
- (h) ~~This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]~~

B.14 ~~Multiple Exceedances [326 IAC 2-7-5(1)(E)]~~

~~Any exceedance of a permit limitation or condition contained in this permit, except as allowed for in 40 CFR 60, Subpart WWW or approved variances contained within the Collection and Control System Design Plan required pursuant to this rule, which occurs contemporaneously with an exceedance of an associated surrogate or operating parameter established to detect or assure compliance with that limit or condition, both arising out of the same act or occurrence, shall constitute a single potential violation of this permit.~~

B.15 ~~Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]~~

- (a) ~~Deviations from any permit requirements (for emergencies see Section B – Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:~~

~~Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

~~within ten (10) calendar days from the date of the discovery of the deviation except as allowed for in 40 CFR 60, Subpart WWW or approved variances contained within the Collection and Control System Design Plan required pursuant to this rule.~~

- (b) ~~A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:~~
- (1) ~~An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or~~
 - (2) ~~An emergency as defined in 326 IAC 2-7-1(12); or~~
 - (3) ~~Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.~~

- (4) ~~Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.~~

~~A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.~~

- (c) ~~Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).~~
- (d) ~~Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.~~

~~B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]~~

- (a) ~~This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)]~~
- (b) ~~This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:~~
- (1) ~~That this permit contains a material mistake.~~
- (2) ~~That inaccurate statements were made in establishing the emissions standards or other terms or conditions.~~
- (3) ~~That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]~~
- (c) ~~Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]~~
- (d) ~~The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]~~

~~B.17 Permit Renewal [326 IAC 2-7-4]~~

- (a) ~~The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40).~~

~~Request for renewal shall be submitted to:~~

~~Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

- (b) ~~Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]~~
- (1) ~~A timely renewal application is one that is:~~

- (A) ~~Submitted at least nine (9) months prior to the date of the expiration of this permit; and~~
- (B) ~~If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due. [326 IAC 2-5-3]~~
- (2) ~~If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.~~
- (c) ~~Right to Operate After Application for Renewal [326 IAC 2-7-3]
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.~~
- (d) ~~United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]
If IDEM, OAQ, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.~~

~~B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]~~

- (a) ~~The Permittee must comply with the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.~~
- (b) ~~Any application requesting an amendment or modification of this permit shall be submitted to:~~
- ~~Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251~~
- ~~Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule~~
- (c) ~~The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]~~

~~B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]~~

- (a) ~~No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.~~
- (b) ~~Notwithstanding 326 IAC 2-7-12(b)(1)(D)(i) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are~~

explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

~~B.20 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-7-20(b)]~~

~~The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a) and the following additional conditions:~~

- ~~(a) For each such change, the required written notification shall include a brief description of the change within the source, the date on which the change will occur, any change in emissions, and any permit term or condition that is no longer applicable as a result of the change.~~
- ~~(b) The permit shield, described in 326 IAC 2-7-15, shall not apply to any change made under 326 IAC 2-7-20(b).~~

~~B.21 Operational Flexibility [326 IAC 2-7-20]~~

~~(a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:~~

- ~~(1) The changes are not modifications under any provision of Title I of the Clean Air Act;~~
- ~~(2) Any approval required by 326 IAC 2-1 has been obtained;~~
- ~~(3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);~~
- ~~(4) The Permittee notifies the:~~

~~Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

~~and~~

~~United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590~~

~~in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and~~

- ~~(5) The Permittee maintains records on site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e) and makes such records available, upon reasonable request, for public review.~~

~~Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b), (c)(1), and (e)(2).~~

- ~~(b) For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:~~

- (1) ~~— A brief description of the change within the source;~~
- (2) ~~— The date on which the change will occur;~~
- (3) ~~— Any change in emissions; and~~
- (4) ~~— Any permit term or condition that is no longer applicable as a result of the change.~~

~~The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

- (c) ~~— Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).~~
- (d) ~~— Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.~~
- (e) ~~— Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.~~

~~B.22 Construction Permit Requirement [326 IAC 2]~~

~~Except as allowed by Indiana P.L. 130-1996 Section 12, as amended by P.L. 244-1997, modification, construction, or reconstruction shall be approved as required by and in accordance with 326 IAC 2.~~

~~B.23 Inspection and Entry [326 IAC 2-7-6(2)]~~

~~Upon presentation of proper identification cards, credentials, and other documents as may be required by law, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:~~

- (a) ~~— Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;~~
- (b) ~~— Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;~~
- (c) ~~— Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;~~
- (d) ~~— Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and~~
- (e) ~~— Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements. [326 IAC 2-7-6(6)]~~
 - (1) ~~— The Permittee may assert a claim that, in the opinion of the Permittee, information removed or about to be removed from the source by IDEM, OAQ, or an authorized representative, contains information that is confidential under IC 5-14-3-4(a). The claim shall be made in writing before or at the time the information is~~

~~removed from the source. In the event that a claim of confidentiality is so asserted, neither IDEM, OAQ, nor an authorized representative, may disclose the information unless and until IDEM, OAQ, makes a determination under 326 IAC 17-1-7 through 326 IAC 17-1-9 that the information is not entitled to confidential treatment and that determination becomes final. [IC 5-14-3-4; IC 13-14-11-3; 326 IAC 17-1-7 through 326 IAC 17-1-9]~~

- ~~(2) The Permittee, IDEM, OAQ, acknowledge that the federal law applies to claims of confidentiality made by the Permittee with regard to information removed or about to be removed from the source by U.S. EPA. [40 CFR Part 2, Subpart B]~~

~~B.24 Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11]~~

~~Pursuant to 326 IAC 2-1-6 and 326 IAC 2-7-11:~~

- ~~(a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAQ, Permits Branch, within thirty (30) days of the change. Notification shall include a written agreement containing a specific date for transfer of permit responsibility, coverage, and liability between the Permittee and the new owner.~~
- ~~(b) The written notification shall be sufficient to transfer the permit to the new owner by an administrative amendment pursuant to 326 IAC 2-7-11. The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~
- ~~(c) IDEM, OAQ, shall reserve the right to issue a new permit.~~

~~B.25 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]~~

- ~~(a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. If the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.~~
- ~~(b) Failure to pay may result in administrative enforcement action, or revocation of this permit.~~
- ~~(c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing and Training Section), to determine the appropriate permit fee.~~

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Matter Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate matter emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2][326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

All air pollution control equipment listed in this permit and used to comply with an applicable requirement for the landfill emissions unit shall be operated at all times when gas is extracted from the emission unit.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or

~~before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:~~

- ~~(1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or~~
- ~~(2) If there is a change in the following:
 - ~~(A) Asbestos removal or demolition start date;~~
 - ~~(B) Removal or demolition contractor; or~~
 - ~~(C) Waste disposal site.~~~~
- ~~(c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).~~
- ~~(d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).~~

~~All required notifications shall be submitted to:~~

~~Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251~~

~~The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

- ~~(e) Procedures for Asbestos Emission Control
The Permittee shall comply with the emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are mandatory for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.~~
- ~~(f) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.~~

Testing Requirements [326 IAC 2-7-6(1)]

C.8 Performance Testing [326 IAC 3-6]

- ~~(a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing methods approved by IDEM, OAQ.~~

~~A test protocol, except as provided elsewhere in this permit, shall be submitted to:~~

~~Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251~~

~~no later than thirty five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.~~

- ~~(b) All test reports must be received by IDEM, OAQ within forty five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAQ, a reasonable written explanation within five (5) days prior to the end of the initial forty five (45) day period.~~

~~The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

Compliance Monitoring Requirements ~~[326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]~~

~~C.9 Compliance Schedule [326 IAC 2-7-6(3)]~~

~~The Permittee:~~

- ~~(a) Has certified that all facilities at this source are in compliance with all applicable requirements; and~~
- ~~(b) Has submitted a statement that the Permittee will continue to comply with such requirements; and~~
- ~~(c) Will comply with such applicable requirements that become effective during the term of this permit except where such applicable requirements cause the Permittee to violate other terms and conditions included herein.~~

~~C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]~~

~~Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit, except as otherwise provided for in 40 CFR 60, Subpart WWW or approved variances contained within the Collection and Control System Design Plan required pursuant to this rule. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend compliance schedule an additional ninety (90) days provided the Permittee notifies:~~

~~Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254~~

~~in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.~~

~~The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

~~C.11 Maintenance of Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]~~

- ~~(a) In the event that a breakdown of the monitoring equipment occurs, a record shall be made of the times and reasons of the breakdown and efforts made to correct the problem. To the extent practicable, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less frequent than required in Section D of this permit until such time as the monitoring equipment is back in operation. In the case of continuous monitoring, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less than twenty four (24) hours until such time as the continuous monitor is back in operation.~~

- (b) ~~The Permittee shall install, calibrate, quality assure, maintain, and operate all necessary monitors and related equipment. In addition, prompt corrective action shall be initiated whenever indicated.~~

~~C.12 Monitoring Methods [326 IAC 3]~~

~~Any monitoring or testing performed to meet the applicable requirements of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.~~

~~C.13 Pressure Gauge Specifications~~

~~Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (2%) of full scale reading.~~

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

~~C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]~~

~~Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):~~

- (a) ~~The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.~~
- (b) ~~These ERPs shall be submitted for approval to:~~
- ~~Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251~~
- ~~within ninety (90) days after the date of issuance of this permit.~~
- ~~The ERP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~
- (c) ~~If the ERP is disapproved by IDEM, OAQ, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.~~
- (d) ~~These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.~~
- (e) ~~Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.~~
- (f) ~~Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]~~

~~C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]~~

~~If a regulated substance, subject to 40 CFR 68, is present in a process in more than the threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall:~~

- (a) ~~Submit:~~
- ~~(1) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or~~

- (2) ~~As a part of the compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and~~
- (3) ~~A verification to IDEM, OAQ, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.~~
- (b) ~~Provide annual certification to IDEM, OAQ, that the Risk Management Plan is being properly implemented.~~

~~All documents submitted pursuant to this condition shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

~~C.16 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5][326 IAC 2-7-6] [326 IAC 1-6]~~

- (a) ~~The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:~~
 - (1) ~~This condition;~~
 - (2) ~~The Compliance Determination Requirements in Section D of this permit;~~
 - (3) ~~The Compliance Monitoring Requirements in Section D of this permit;~~
 - (4) ~~The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and~~
 - (5) ~~A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP=s shall be submitted to IDEM, OAQ upon request and shall be subject to review and approval by IDEM, OAQ. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of:~~
 - (A) ~~Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and~~
 - (B) ~~A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.~~
- (b) ~~For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.~~
- (c) ~~After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:~~
 - (1) ~~The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.~~

- (2) ~~The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;~~
- (3) ~~An automatic measurement was taken when the process was not operating; or~~
- (4) ~~The process has already returned to operating within "normal" parameters and no response steps are required.~~
- (d) ~~Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.~~

~~C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]~~

- (a) ~~When the results of a stack test performed in conformance with Section C – Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAQ shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAQ within thirty (30) days of receipt of the notice of deficiency. IDEM, OAQ reserves the authority to use enforcement activities to resolve noncompliant stack tests.~~
- (b) ~~A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected facility.~~

~~The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

~~C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]~~

- (a) ~~In accordance with the compliance schedule specified in 326 IAC 2-6-3(b)(2), starting in 2005 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:~~
 - (1) ~~Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);~~
 - (2) ~~Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source for purpose of fee assessment.~~

~~The statement must be submitted to:~~

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2254

~~The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).~~

- (b) ~~The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.~~

~~C.19 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]~~

- (a) ~~With the exception of performance tests conducted in accordance with Section C- Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.~~
- (b) ~~As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.~~
- (c) ~~If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.~~
- (d) ~~If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.~~
- (e) ~~At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.~~
- (f) ~~Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.~~

~~C.20 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]~~

- (a) ~~Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAQ, representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.~~
- (b) ~~Records of required monitoring information shall include, where applicable:~~
- ~~(1) The date, place, and time of sampling or measurements;~~
 - ~~(2) The dates analyses were performed;~~
 - ~~(3) The company or entity performing the analyses;~~
 - ~~(4) The analytic techniques or methods used;~~

- ~~(5) — The results of such analyses; and~~
- ~~(6) — The operating conditions existing at the time of sampling or measurement.~~
- ~~(c) — Support information shall include, where applicable:
 - ~~(1) — Copies of all reports required by this permit;~~
 - ~~(2) — All original strip chart recordings for continuous monitoring instrumentation;~~
 - ~~(3) — All calibration and maintenance records;~~
 - ~~(4) — Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C— Compliance Monitoring Plan— Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.~~~~
- ~~(d) — All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.~~

~~G.21 — General Reporting Requirements [326 IAC 2-7-5(3)(C)]~~

- ~~(a) — To affirm that the source has met all the compliance monitoring requirements stated in this permit the source shall submit a Semi-annual Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported.~~
- ~~(b) — The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251~~
- ~~(c) — Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.~~
- ~~(d) — Unless otherwise specified in this permit, any report shall be submitted within thirty (30) days of the end of the reporting period.~~
- ~~(e) — All instances of deviations as described in Section B— Deviations from Permit Requirements Conditions must be clearly identified in such reports.~~
- ~~(f) — Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.~~
- ~~(g) — The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.~~

~~The documents submitted pursuant to this condition do not require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).~~

Stratospheric Ozone Protection

~~C.22 Compliance with 40 CFR 82 and 326 IAC 22-1~~

~~Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:~~

- ~~(a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.~~
- ~~(b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.~~
- ~~(c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.~~

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)][326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)][IC 13-15-3-6(a)]

- (a) This permit, 063-7998-00029, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by the "responsible official" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) The "responsible official" is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) **The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.**
- (c) **The annual compliance certification report shall include the following:**
 - (1) **The appropriate identification of each term or condition of this permit that is the basis of the certification;**
 - (2) **The compliance status;**
 - (3) **Whether compliance was continuous or intermittent;**
 - (4) **The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and**
 - (5) **Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.**

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)][326 IAC 1-6-3]

- (a) **If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:**
 - (1) **Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;**
 - (2) **A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and**
 - (3) **Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.**
- (b) **A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).**
- (c) **To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.**

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) **An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation .**
- (b) **An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation**

if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;**
- (2) The permitted facility was at the time being properly operated;**
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;**
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;**

**Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or
Telephone Number: 317-233-0178 (ask for Compliance Section)
Facsimile Number: 317-233-6865**

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:**

**Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251**

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;**
- (B) Any steps taken to mitigate the emissions; and**
- (C) Corrective actions taken.**

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.**
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.**
 - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.**

- (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (h) The Permittee shall include all emergencies in the Semi-Annual Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15][326 IAC 2-7-20][326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;

- (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
- (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
- (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]

- (a) All terms and conditions of permits established prior to 063-7998-00029 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised under 326 IAC 2-7-10.5, or
 - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit.

B.14 Termination of Right to Operate [326 IAC 2-7-10][326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

within ten (10) calendar days from the date of the discovery of the deviation except as allowed for in 40 CFR 60, Subpart WWW or approved variances contained within the Collection and Control System Design Plan required pursuant to this rule.

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:

- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
- (2) An emergency as defined in 326 IAC 2-7-1(12); or
- (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
- (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.

- (c) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)][326 IAC 2-7-8(a)][326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4][326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at

this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

**Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251**

- (b) A timely renewal application is one that is:**
- (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and**
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.**
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.**

B.18 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12][40 CFR 72]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.**
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:**
- Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251**
- Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).**
- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request.
[326 IAC 2-7-11(c)(3)]**

B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)][326 IAC 2-7-12(b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.**

- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20][326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b),(c), or (e) without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b),(c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;

- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

- (c) **Emission Trades [326 IAC 2-7-20(c)]**
The Permittee may trade emissions increases and decreases at in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) **Alternative Operating Scenarios [326 IAC 2-7-20(d)]**
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) **Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.**

B.21 Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2-2] [326 IAC 2-3]

- (a) A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.
- (b) Any modification at an existing major source is governed by the requirements of 326 IAC 2-2-2 and 326 IAC 2-3-2.

B.22 Inspection and Entry [326 IAC 2-7-6][IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee’s right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, and U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 9-1-2 is not federally enforceable.

C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:

- (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.7 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality

**100 North Senate Avenue
Indianapolis, Indiana 46204-2251**

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.8 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]

C.9 Compliance Monitoring [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit, except as otherwise provided for in 40 CFR 60, Subpart WWW or approved variances contained within the Collection and Control System Design Plan required pursuant to this rule. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend compliance schedule an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.10 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.11 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall

have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.

- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]

C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on October 22, 1999.
- (b) Upon direct notification by IDEM, OAQ that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5][326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

- (a) Pursuant to 326 IAC 2-6-3(b)(2), starting in 2005 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:
 - (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);

- (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) (“Regulated pollutant, which is used only for purposes of Section 19 of this rule”) from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

C.16 General Record Keeping Requirements[326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.
- (c) If there is a reasonable possibility that a “project” (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1 (II)) at an existing emissions unit, other than projects at a Clean Unit, which is not part of a “major modification” (as defined in 326 IAC 2-2-1 (ee) and/or 326 IAC 2-3-1 (z)) may result in significant emissions increase and the Permittee elects to utilize the “projected actual emissions” (as defined in 326 IAC 2-2-1 (rr) and/or 326 IAC 2-3-1 (mm)), the Permittee shall comply with following:
- (1) Before beginning actual construction of the “project” (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1 (II)) at an existing emissions unit, document and maintain the following records:
- (A) A description of the project.
- (B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.
- (C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:
- (i) Baseline actual emissions;
- (ii) Projected actual emissions;
- (iii) Amount of emissions excluded under section 326 IAC 2-2-1(rr)(2)(A)(iii) and/or 326 IAC 2-3-1(mm)(2)(A)(iii); and

- (iv) **An explanation for why the amount was excluded, and any netting calculations, if applicable.**
- (2) **Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and**
- (3) **Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR pollutant at the emissions unit.**

C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

- (a) **The Permittee shall submit the attached Semi-Annual Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Semi-Annual Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).**
- (b) **The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:**

**Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251**
- (c) **Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.**
- (d) **Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).**
- (e) **Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.**
- (f) **If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any "project" (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1 (II)), and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:**
 - (1) **The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as**

defined in 326 IAC 2-2-1 (xx) and/or 326 IAC 2-3-1 (qq), for that regulated NSR pollutant, and

- (2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).
- (g) The report for project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:
 - (1) The name, address, and telephone number of the major stationary source.
 - (2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.
 - (3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-2-2(d)(3) and/or 326 IAC 2-3-2(c)(3).
 - (4) Any other information that the Permittee deems fit to include in this report,

Reports required in this part shall be submitted to:

Indiana Department of Environmental Management
Air Compliance Section, Office of Air Quality
100 North Senate Avenue
Indianapolis, Indiana 46204-2251

- (h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.

Stratospheric Ozone Protection

C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

Ambient Monitoring Requirements [326 IAC 7-3]

C.19 Ambient Monitoring [326 IAC 7-3]

- (a) The Permittee shall operate continuous ambient sulfur dioxide air quality monitors and a meteorological data acquisition system according to a monitoring plan submitted to the commissioner for approval. The monitoring plan shall include

requirements listed in 326 IAC 7-3-2(a)(1), 326 IAC 7-3-2(a)(2) and 326 IAC 7-3-2(a)(3).

- (b) The Permittee and other operators subject to the requirements of this rule, located in the same county, may submit a joint monitoring plan to satisfy the requirements of this rule. [326 IAC 7-3-2(c)]**
- (c) The Permittee may petition the commissioner for an administrative waiver of all or some of the requirements of 326 IAC 7-3 if such owner or operator can demonstrate that ambient monitoring is unnecessary to determine continued maintenance of the sulfur dioxide ambient air quality standards in the vicinity of the source. [326 IAC 7-3-2(d)]**

Modification No. 1:

Section A.3 (Specifically Regulated Insignificant Activities): With the exception of solvent-based cleaning, none of the activities listed in this section are “specifically regulated”; i.e., have applicable requirements associated with them. Therefore, the reference “specifically regulated” has been removed from Section A.3 and the applicable rule citation has been placed in brackets following the specifically regulated Insignificant Activities. Section A.3 and D.3 (formerly D.4) have been modified as follows:

A.3 ~~Specifically Regulated~~ Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities ~~which are specifically regulated~~, as defined in 326 IAC 2-7-1(21):

....

- (w) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. **[326 IAC 8-3-2] [326 IAC 8-3-5]**

SECTION ~~D.4~~ D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)] Insignificant Activities

- (w) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. **[326 IAC 8-3-2] [326 IAC 8-3-5]**

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Modification No. 2:

Pursuant to 326 IAC 6-3-1(b)(9) and (10), welding, provided that less than six hundred twenty five (625) pounds of rod or wire is consumed per day, and torch cutting, provided that less than three thousand four hundred (3,400) inches per hour of stock one (1) inch thickness or less is cut, are exempt from the requirements of 326 IAC 6-3-2. Therefore, Sections D.2 and D.3, which contained the requirements of 326 IAC 6-3-2, have been removed from the permit.

SECTION ~~D.2~~ FACILITY OPERATION CONDITIONS

~~Facility Description [326 IAC 2-7-5(15)] Insignificant Activities:~~

- ~~(a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment.~~

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Particulate Matter (PM) [326 IAC 6-3]

Pursuant to 326 IAC 6-3 (Process Operations), the allowable PM emission rate from each of the above listed facilities shall not exceed the pounds per hour emission rate as calculated with the following equation:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \text{ where } E = \text{rate of emission in pounds per hour; and } P = \text{process weight rate in tons per hour}$$

Compliance Determination Requirements

D.2.2 Testing Requirements [326 IAC 2-7-6(1),(6)]

The Permittee is not required to test these facilities by this permit. However IDEM may require compliance testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.2.1 shall be determined by a performance test conducted in accordance with Section C- Performance Testing.

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)] Insignificant Activities:

(b) Any of the following structural steel and bridge fabrication activities:

- (1) Cutting 200,000 linear feet or less of one inch (10) plate or equivalent.
- (2) Using 80 tons or less of welding consumables.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Particulate Matter (PM) [326 IAC 6-3]

Pursuant to 326 IAC 6-3 (Process Operations), the allowable PM emission rate from each of the above listed facilities shall not exceed the pounds per hour emission rate as calculated with the following equation:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \text{ where } E = \text{rate of emission in pounds per hour; and } P = \text{process weight rate in tons per hour}$$

Compliance Determination Requirements

~~D.3.2 Testing Requirements [326 IAC 2-7-6(1),(6)]~~

~~The Permittee is not required to test these facilities by this permit. However IDEM may require compliance testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.3.1 shall be determined by a performance test conducted in accordance with Section C- Performance Testing.~~

Modification No. 3:

Pursuant to 40 CFR 60.752(b)(2)(iii), the source is required to route all collected gas to a control system that complies with the following requirements: an open flare (40 CFR 60.752(b)(2)(iii)(A); or, a control system or enclosed combustor designed to reduce MNOC (40 CFR 60.752(b)(2)(iii)(B); or, a treatment system that processes the collected gas for subsequent sale or use (40 CFR 60.752(b)(2)(iii)(C)).

Pursuant to a letter (dated March 15, 2004) authored by George Czerniak of Region 5 of the U.S. EPA (ADI Control No.: 0400028), compression, de-watering, and filtering the landfill gas down to at least 10 microns is considered treatment for the purposes of 40 CFR 60.752(b)(2)(iii)(C). The letter further stated that the EPA made the same determination previously in ADI Control Nos. 0200019, 0200028, and 0300121.

Prior to combustion in the engines/generator sets, the landfill gas from the source has always been processed in a treatment system that meets the requirements of the 40 CFR 60.752(b)(2)(iii)(C). Therefore, once treated, the gas and equipment combusting the treated gas are not subject to the requirements of the NSPS for Municipal Solid Waste Landfills, 40 CFR 60, Subpart WWW. However, emissions from any atmospheric vent from the gas treatment system, including any compressor, are subject to the requirements of 40 CFR 60, Subpart WWW.

Additionally, the U.S. EPA has stated in USEPA Municipal Solid Waste Landfill New Source Performance Standards (NSPS) and Emission Guidelines (EG) – Questions and Answers, dated November 1998 (Revised May 2002), page 38, if a control device has been designed without any physical means of bypass, then the requirements of 40 CFR 60.756(c)(2) do not apply.

Therefore the following changes have been made to Sections A.2, D.1 and D.2:

- A source description of the gas treatment system has been added and the source description of the flare has been modified in Sections A.2 and D.1.
- Condition D.1.1(c) is no longer required and has been removed from the permit.
- The former Conditions D.1.7(b), D.1.7(c)(2), D.1.10(f)(2), D.1.12(b)(2) and (3), and D.1.12(c)(1),(2) and (3), which pertain to enclosed combustion units and/or bypass of the flare are no longer applicable, and have been removed from the permit.
- Since there are no applicable requirements for the engine/generator sets, the engine/generator sets will no longer be included in Section D.1 and will be listed in Section D.2.

Additionally, the former Condition D.1.2 has been removed from the permit, and the applicable requirements of the NESHAP, Subpart AAAA, have been incorporated into the permit as Conditions D.1.1, D.1.2, D.1.7, and D.1.14.

The changes listed below have been made to Part 70 Operating Permit No.: 063-7998-00029. Deleted language appears as ~~strikethroughs~~ and new language appears in **bold**:

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
[326 IAC 2-7-5(15)]

This stationary source consists of the following emission units:

.....

- (b) One (1) **open** flare, identified as FL2 to be constructed in 2006, with a rated capacity of 2100 standard cubic feet per minute (scfm) and exhausting to stack FL2S. **This flare does not have a bypass.**

.....

- (e) **One (1) gas treatment system that processes the collected gas pursuant to 40 CFR 60.752(b)(2)(iii)(C).**

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (a) One (1) solid waste disposal facility having the meaning described in 40 CFR 60.751 pertaining to all contiguous land and structures, other appurtenances (including haul roads), and improvements on the land used for disposal of solid waste that opened in 1970 and has a design capacity of 29,569,038 Megagrams.
- (b) One (1) **open** flare, identified as FL2, to be constructed in 2006, with a rated capacity of 2100 standard cubic feet per minute (scfm) and exhausting to stack FLS2. **This flare does not have a bypass.**
- ~~(c) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG1 through EG5, and a single fuel gas compressor. The generators are rated at 800 kilowatts each, and were installed in 1994 and 1996.~~
- ~~(d) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG5 through EG8, rated at 800 kilowatts each and exhausting to stacks ES5 through ES8, respectively..~~
- (e) **One (1) gas treatment system that processes the collected gas pursuant to 40 CFR 60.752(b)(2)(iii)(C).**

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 General Provisions Relating to NSPS and NESHAP [326 IAC 12-1] **[326 IAC 8-8.1]** [40 CFR Part 60, Subpart A] **[326 IAC 20-1-1] [40 CFR 63, Subpart A]** and to HAPs [326 IAC 14-1-1] [40 CFR Part 61, Subpart A]

- (a) The provisions of 40 CFR Part 60, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 12-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 60, Subpart WWW.
- (b) **The provisions of 40 CFR Part 63, Subpart A - General Provisions, which are incorporated by reference in 326 IAC 20-1-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 63, Subpart AAAA.**
- ~~(b)(c)~~ The provisions of 40 CFR Part 61, Subpart A - General Provisions, which are incorporated as 326 IAC 14-1-1, apply to the facility described in this section except when otherwise specified in 40 CFR Part 61, Subpart M.

- ~~(c) Pursuant to a letter from EPA Region V (dated February 10, 2004), the existing eight (8) landfill gas fueled engine/generators (EG1 through EG8) at Twin Bridges Recycling & Disposal Facility that combust treated landfill gas are not subject to the testing requirements in 40 CFR 60.754, the monitoring requirements in 40 CFR 60.756, or the record keeping requirements in 40 CFR 60.758.~~

~~D.1.2 Non-applicability Determination~~

~~The municipal solid waste landfill is not subject to the provisions of the following 40 CFR Part 60 Subparts: Cc, D, Da, Db, Dc, E, Ea, Eb, K, Ka, Kb, O, Gg, and Ooo.~~

D.1.2 Municipal Solid Waste Landfill NESHAP [40 CFR 63, Subpart AAAAA] [326 IAC 20-67]

Pursuant to 40 CFR 63.1955, the Permittee shall:

- (a) Comply with the requirements of 40 CFR 60, Subpart WWW.
- (b) The Permittee required by 40 CFR 60.752(b)(2) to install a collection and control system shall comply with the general and continuing compliance requirements in 40 CFR 63.1960 through 40 CFR 63.1985.
- (c) The Permittee shall comply with the Startup, Shutdown, and Malfunction (SSM) requirements in Subpart A of 40 CFR 63 as specified in Table 1 of 40 CFR 63, Subpart AAAAA and all affected sources must submit compliance reports every six (6) months as specified in 40 CFR 63.1980(a) and (b), including information on all deviations that occurred during the six (6)-month reporting period. Deviations (as defined in 40 CFR 63.1965) for continuous emission monitors or numerical continuous parameter monitors must be determined using a three (3) hour monitoring block average (as defined in 40 CFR 63.1975).

Compliance Determination Requirements

D.1.7 Compliance Determination [40 CFR 63.1960] [40 CFR 63.1965] [326 IAC 20-67]

- (a) Pursuant to 40 CFR 63.1960 and 40 CFR 63.1965, as amended (effective April 20, 2006), compliance with 40 CFR 63, Subpart AAAAA is determined by the following:
 - (1) The same way it is determined for 40 CFR 60, Subpart WWW, including performance testing, monitoring of the collection system, continuous parameter monitoring, and other credible evidence.
 - (2) Continuous parameter monitoring data, collected under 40 CFR 60.756(b)(1), (c)(1), and (d) of 40 CFR 60, Subpart WWW, are used to demonstrate compliance with the operating conditions for control systems. If a deviation (as defined in 40 CFR 63.1965) occurs, the Permittee has failed to meet the control device operating conditions described in 40 CFR 60, Subpart WWW and has deviated from the requirements of 40 CFR 63, Subpart AAAAA.
 - (3) The Permittee must develop a written Startup, Shutdown and Malfunction (SSM) plan according to the provisions in 40 CFR 63.6(e)(3). A copy of the SSM plan must be maintained on site. Failure to write or maintain a copy of the SSM plan is a deviation from the requirements of 40 CFR 63, Subpart AAAAA.
- (b) Pursuant to 326 IAC 20-67, the Permittee shall comply with the previous version of 40 CFR 63, Subpart AAAAA, published in 68 FR 2238, January 16, 2003. Compliance with the requirements specified in Condition D.1.7(a) shall satisfy the requirements of 326 IAC 20-67, with the exception of the requirements listed in Condition

D.1.7(a)(3). In order to satisfy 326 IAC 20-67, the Permittee shall comply with the following:

- (1) The Permittee must develop and implement a written Startup, Shutdown and Malfunction (SSM) plan according to the provisions in 40 CFR 63.6(e)(3). A copy of the SSM plan must be maintained on site. Failure to write, implement, or maintain a copy of the SSM plan is a deviation from the requirements of 40 CFR 63, Subpart AAAA.**

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

~~D.1.7D.1.8~~ Monitoring [40 CFR 60.756] [326 IAC 8-8.1] [326 IAC 12]

Except as provided in 40 CFR 60.752(b)(2)(i)(B),

....

~~(b) The Permittee seeking to comply with 40 CFR 60.752(b)(2)(iii) using an enclosed combustor shall calibrate, maintain, and operate according to the manufacturer's specifications, the following equipment:~~

~~(1) A temperature monitoring device equipped with a continuous recorder and having a minimum accuracy of ± 1 percent of the temperature being measured expressed in degrees Celsius or $\pm 0.5^{\circ}\text{C}$, whichever is greater. A temperature monitoring device is not required for boilers or process heaters with design heat input capacity greater than 44 megawatts.~~

~~(2) A device that records flow to or bypass of the control device. The Permittee shall either; install, calibrate, and maintain a gas flow rate measuring device that shall record the flow to the control device at least every fifteen (15) minutes; or secure the bypass line valve in the closed position with a car seal or a lock and key type configuration. A visual inspection of the seal or closure mechanism shall be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.~~

~~(c)(b) The Permittee seeking to comply with 40 CFR 60.752(b)(2)(iii) using an open flare shall install, calibrate, maintain, and operate according to the manufacturer's specifications the following equipment:~~

~~(1) Heat sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light or the flame itself to indicate the continuous presence of a flame~~

~~(2) A device that records flow to or bypass of the flare.~~

~~The Permittee shall either install, calibrate, and maintain a gas flow rate measuring device that shall record the flow to the control device at least every fifteen minutes; or secure the bypass line valve in the closed position with a car seal or a lock and key type configuration. A visual inspection of the seal or closure of the seal or closure mechanism shall be performed at least once every month to ensure that the valve is maintained in the closed position and that the gas flow is not diverted through the bypass line.~~

~~(c)(c) The Permittee seeking to comply with 40 CFR 60.752(b)(2)(iii) using a device other than an open flare or an enclosed combustor shall provide information satisfactory to the Office of Air Quality (OAQ) as provided in 40 CFR 60.752(b)(2)(i)(B) describing the operation of the control device, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Office of Air Quality (OAQ) shall review the~~

information and either approve it, or request that additional information be submitted. The Office of Air Quality (OAQ) may specify additional monitoring procedures.

- (e)(d) The Permittee seeking to install a collection system that does not meet the specifications in 40 CFR 60.759 or seeking to monitor alternative parameters to those required by 40 CFR 60.753 through 40 CFR 60.756 shall provide information satisfactory to the Office of Air Quality (OAQ) as provided in 40 CFR 60.752(b)(2)(i)(B) and (C) describing the design and operation of the collection system, the operating parameters that would indicate proper performance, and appropriate monitoring procedures. The Office of Air Quality (OAQ) may specify additional appropriate monitoring procedures.
- (f)(e) The Permittee seeking to demonstrate compliance with 40 CFR 60.755(c), shall monitor surface concentrations of methane according to the instrument specifications and procedures provided in 40 CFR 60.755(d). Any closed landfill that has no monitored exceedances of the operational standard in three consecutive quarterly monitoring periods may skip to annual monitoring. Any methane reading of 500 ppm or more above background detected during the annual monitoring returns the frequency for that landfill to quarterly monitoring.

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.10D.1.11 Reporting Requirements [40 CFR 60.757] [326 IAC 8-8.1] [326 IAC 12]

Pursuant to 40 CFR 60.757, except as provided in 40 CFR 60.752(b)(2)(i)(B), the Permittee shall:

....

- (f) Annual reports of the following recorded information. The initial annual report shall be submitted within 180 days of installation and start-up of the collection and control system, and shall include the initial performance test report required under 40 CFR 60.8. For enclosed combustion devices and flares, reportable exceedances are defined under 40 CFR 60.758(c).
 - (1) Value and length of time for exceedance of applicable parameters monitored under 40 CFR 60.756(a), (b), (c), and (d).
 - ~~(2) Description and duration of all periods when the gas stream is diverted from the control device through a bypass line or the indication of bypass flow as specified under 40 CFR 60.756.~~
 - ~~(3)~~(2) Description and duration of all periods when the control device was not operating for a period exceeding one (1) hour and length of time the control device was not operating.
 - ~~(4)~~(3) All periods when the collection system was not operating in excess of five (5) days.
 - ~~(5)~~(4) Location of each exceedance of the 500 parts per million methane concentration as provided in 40 CFR 60.753(d) and the concentration recorded at each location for which an exceedance was recorded in the previous month.
 - ~~(6)~~(5) Date of installation and the location of each well or collection system expansion added pursuant to 40 CFR 60.755(a)(3), (b), and (c)(4).

....

D.1.12D.1.13 Record Keeping Requirements [40 CFR 60.758] [326 IAC 8-8.1] [326 IAC 12]

....

- (b) Except as provided in 40 CFR 60.752(b)(2)(i)(B) the Permittee of a controlled landfill shall keep up-to-date, readily accessible records for the life of the control equipment listed in (a) through (d) below as measured during the initial performance test or compliance determination. Records of subsequent tests or monitoring shall be maintained for a minimum of five (5) years. Records of control device vendor specifications shall be maintained until removal.

.....
~~(2) Where the Permittee subject to the provisions of 40 CFR 60.758 seeks to demonstrate compliance with 40 CFR 60.752(b)(2)(iii) through use of an enclosed combustion device other than a boiler or process heater with a design heat input capacity greater than 44 megawatts:~~

~~The average combustion temperature measured at least every fifteen (15) minutes and averaged over the same time period of the performance test.~~

~~The percent reduction of NMOC determined as specified in 40 CFR 60.752(b)(2)(iii)(B) achieved by the control device.~~

~~(3) Where the Permittee subject to the provisions of 40 CFR 60.758 seeks to demonstrate compliance with 40 CFR 60.752(b)(2)(iii)(B)(1) through use of a boiler or process heater of any size: a description of the location at which the collected gas vent stream is introduced into the boiler or process heater over the same time period of the performance testing.~~

~~(4)(2) Where the Permittee subject to the provisions of 40 CFR 60.758 seeks to demonstrate compliance with 40 CFR 60.752(b)(2)(iii)(A) through use of an open flare, the flare type (i.e., steam-assisted, air -assisted, or nonassisted), all visible emission readings, heat content determination, flow rate or bypass flow rate measurements, and exit velocity determinations made during the performance test as specified in 40 CFR 60.18; continuous records of the flare pilot flame or flare flame monitoring and records of all periods of operations during which the pilot flame of the flare flame is absent.~~

- (c) Except as provided in 40 CFR 60.752(b)(2)(i)(B) the Permittee of a controlled landfill subject to the provisions of this subpart shall keep for five years up-to-date, readily accessible, continuous on-site records of the equipment operating parameters specified to be monitored in 40 CFR 60.756 as well as up-to-date, readily accessible records for periods of operation during which the parameter boundaries established during the most recent performance test are exceeded.

~~(1) The following constitute exceedances that shall be recorded and reported under 40 CFR 60.757(f):~~

~~For enclosed combustors except for boilers and process heaters with design heat input capacity of 44 megawatts (150 million British thermal unit per hour) or greater, all 3-hour periods of operation during which the average combustion temperature was more than 28°C below the average combustion temperature during the most recent performance test at which compliance with 40 CFR 60.752(b)(2)(iii) was determined.~~

~~For boilers or process heaters, whenever there is a change in the location at which the vent stream is introduced into the flame zone as required under 40 CFR 60.758(b)(3)(i) of this section.~~

~~(2) The Permittee subject to 40 CFR 60.758 shall keep up-to-date, readily accessible continuous records of the indication of flow to the control device or the indication~~

~~of bypass flow or records of monthly inspections of car seals or lock and key configurations used to seal bypass lines, specified under 40 CFR 60.756.~~

~~(3) The Permittee subject to the provisions of 40 CFR 60.758 who uses a boiler or process heater with a design heat input capacity of 44 megawatts or greater to comply with 40 CFR 60.752(b)(2)(iii) shall keep an up-to-date, readily accessible record of all periods of operation of the boiler or process heater. (Examples of such records could include records of steam use, fuel use, or monitoring data collected pursuant to other State, local, Tribal or Federal regulatory requirements.)~~

~~(4)(1) The Permittee seeking to comply with the provisions of 40 CFR 60.758 by use of an open flare shall keep up-to-date, readily accessible continuous records of the flame or flare pilot flame monitoring specified under 40 CFR 60.756(c), and up-to-date, readily accessible records of all periods of operation in which the flame or flare pilot flame is absent.~~

....

D.1.14 Record Keeping and Reporting Requirements for NESHP for Municipal Solid Waste Landfills [40 CFR 63.1980] [326 IAC 20-67]

Pursuant to 40 CFR 63.1980, the Permittee shall:

- (a) Keep records and reports as specified in 40 CFR 60, Subpart WWW, with one exception: The Permittee must submit the annual report described in 40 CFR 60.757(f) and Condition D.1.11(f) every six (6) months.
- (b) Keep records and reports as specified in the general provisions of 40 CFR 60 and 40 CFR 63 as shown in Table 1 of 40 CFR 63, Subpart AAAA. Applicable records in the general provisions include items such as SSM plans and the SSM plan reports. The SSM Plan report shall be submitted semi-annually to IDEM, OAQ.

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (c) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG1 through EG5, and a single fuel gas compressor. The generators are rated at 800 kilowatts each, and were installed in 1994 and 1996.
- (d) Four (4) Caterpillar 3516 landfill gas fueled engine/generator sets, identified as EG5 through EG8, rated at 800 kilowatts each and exhausting to stacks ES5 through ES8, respectively.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

There are no applicable state or federal requirements for these emission units.

Modification No. 4:

Condition D.3.4 –Testing Requirements (326 IAC 2-7-6(1),(6)) (formerly D.4.4) is not required. Therefore, this condition has been removed from the permit.

Compliance Determination Requirements

~~D.4.4 Testing Requirements [326 IAC 2-7-6(1),(6)]~~

~~The Permittee is not required to test these facilities by this permit. However IDEM may require compliance testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.4.1 shall be determined by a performance test conducted in accordance with Section C- Performance Testing.~~

Modification No. 5:

The Table of Contents has been revised to reflect modifications made to the Part 70 permit (063-7998-00029), and section numbers and condition numbers have been renumbered where appropriate.

Conclusion and Recommendation

The source shall be subject to the conditions of the attached proposed Part 70 Significant Permit Modification No. 063-23080-00029. The staff recommend to the Commissioner that this Part 70 Significant Permit Modification be approved.