



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: December 3, 2008

RE: Phillips Products / 039-23429-00128

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER.dot12/03/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Minor Source Operating Permit Renewal OFFICE OF AIR QUALITY

**Philips Products
3221 Magnum Drive
Elkhart, Indiana 46516**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages.

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a MSOP under 326 IAC 2-6.1.

Operation Permit No.: M039-23429-00128	
Issued by/Original Signed By: Alfred C. Dumauval, Ph. D., Section Chief Permits Branch Office of Air Quality	Issuance Date: December 3, 2008 Expiration Date: December 3, 2018

TABLE OF CONTENTS

A. SOURCE SUMMARY.....	4
A.1 General Information [326 IAC 2-5.1-3(c)][326 IAC 2-6.1-4(a)]	
A.2 Emission Units and Pollution Control Equipment Summary	
B. GENERAL CONDITIONS	6
B.1 Definitions [326 IAC 2-1.1-1]	
B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]	
B.3 Term of Conditions [326 IAC 2-1.1-9.5]	
B.4 Enforceability	
B.5 Severability	
B.6 Property Rights or Exclusive Privilege	
B.7 Duty to Provide Information	
B.8 Certification	
B.9 Annual Notification [326 IAC 2-6.1-5(a)(5)]	
B.10 Preventive Maintenance Plan [326 IAC 1-6-3]	
B.11 Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.12 Termination of Right to Operate [326 IAC 2-6.1-7(a)]	
B.13 Permit Renewal [326 IAC 2-6.1-7]	
B.14 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]	
B.15 Source Modification Requirement	
B.16 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2] [IC 13-17-3-2][IC 13-30-3-1]	
B.17 Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]	
B.18 Annual Fee Payment [326 IAC 2-1.1-7]	
B.19 Credible Evidence [326 IAC 1-1-6]	
C. SOURCE OPERATION CONDITIONS	11
Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]	
C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2 Permit Revocation [326 IAC 2-1.1-9]	
C.3 Opacity [326 IAC 5-1]	
C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.6 Fugitive Dust Emissions [326 IAC 6-4]	
C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
Testing Requirements [326 IAC 2-6.1-5(a)(2)]	
C.8 Performance Testing [326 IAC 3-6]	
Compliance Requirements [326 IAC 2-1.1-11]	
C.9 Compliance Requirements [326 IAC 2-1.1-11]	
Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]	
C.10 Compliance Monitoring [326 IAC 2-1.1-11]	
C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]	
C.12 Instrument Specifications [326 IAC 2-1.1-11]	
Corrective Actions and Response Steps	
C.13 Response to Excursions or Exceedances	
C.14 Actions Related to Noncompliance Demonstrated by a Stack Test	
Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]	
C.15 Malfunctions Report [326 IAC 1-6-2]	

- C.16 General Record Keeping Requirements [326 IAC 2-6.1-5]
- C.17 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2]
[IC 13-14-1-13]

D.1. EMISSIONS UNIT OPERATION CONDITIONS..... 17

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

- D.1.1 Volatile Organic Compounds (VOCs) [326 IAC 8-2-9]
- D.1.2 Particulate Emissions (PM) [326 IAC 6-3-2]
- D.1.3 Preventative Maintenance Plan [326 IAC 1-6-3]

Compliance Determination Requirements

- D.1.4 Volatile Organic Compounds (VOCs)
- D.1.5 Particulate Control

Compliance Monitoring Requirements [326 IAC 2-8-4]

- D.1.6 Visible Emissions Notations
- D.1.7 Baghouse Inspections
- D.1.8 Broken or Failed Bag Detection

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

- D.1.9 Record Keeping Requirements
- D.1.10 Reporting Requirements

Annual Notification 20
MSOP Certification..... 21
MSOP Quarterly Report..... 22
Malfunction Report..... 23

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 and A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)][326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary steel doors, RV doors, storm doors and vinyl windows manufacturing plant.

Source Address:	3221 Magnum Drive, Elkhart, Indiana 46516
Mailing Address:	3221 Magnum Drive, Elkhart, IN 46516
General Source Phone Number:	574-296-0151
SIC Code:	3089
County Location:	Elkhart
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Minor Source Operating Permit Program Minor Source, under PSD and Emission Offset Rules Minor Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) RV doors production line, permitted in 2001, with a maximum production rate of 70 units per hour. PM/PM10 emissions from the MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations are controlled by dust collectors DC2 (located outdoors) and DC3. This line includes the following operations:
 - (1) Inner frame steel cutting with a maximum cutting rate of 240 pounds per hour;
 - (2) Skin foam cutting with a maximum cutting rate of 120 pounds per hour;
 - (3) Outer frame aluminum cutting with a maximum cutting rate of 890 pounds per hour;
 - (4) Surface coating using aerosol and plews cans at a maximum rate of 70 units per hour

- (b) One (1) vinyl windows production line for RVs and homes, permitted in 2001, with a maximum production rate of 75 units per hour. PM/PM10 emissions from the MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations are controlled by dust collectors DC2 (located outdoors) and DC3. This line includes the following operations:
 - (1) Spacer cutting with a maximum cutting rate of 75 pounds per hour;
 - (2) Grid cutting with a maximum cutting rate of 25 pounds per hour;
 - (3) Glass cutting with a maximum cutting rate of 1400 pounds per hour;
 - (4) Frame parts cutting with a maximum cutting rate of 200 pounds per hour;
 - (5) Sash parts cutting with a maximum cutting rate of 100 pounds per hour;
 - (6) Weld frame through head fusion and surface coating
 - (7) Surface coating using aerosol and plews cans at a maximum rate of 70 units per hour

- (c) One (1) home HTD/storm door production line, permitted in 2001, with a maximum production rate of 20 units per hour. This line includes: metal cutting with a maximum cutting rate of 450 pounds per hour, application of sealant, surface coating using aerosol and plews cans at a maximum rate of 70 units per hour, and woodworking operation which is controlled by baghouse DC1;
- (d) One (1) natural gas-fired applied air heating unit, identified as S7, with a heat input capacity of 3.125 million British Thermal Units per hour (MMBtu/hr);
- (e) One (1) natural gas-fired rapid air make-up unit, identified as S9 with a heat input capacity of 3.3 MMBtu/hr; and

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-1.1-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-1.1-1) shall prevail.

B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]

- (a) This permit, M039-23429-00128, is issued for a fixed term of ten (10) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an "authorized individual" of truth, accuracy, and completeness. This

certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) An "authorized individual" is defined at 326 IAC 2-1.1-1(1).

B.9 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) An annual notification shall be submitted by an authorized individual to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) The annual notice shall be submitted in the format attached no later than March 1 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, IN 46204-2251
- (c) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

B.10 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of permits established prior to M039-23429-00128 and issued pursuant to permitting programs approved into the state implementation plan have been either:

- (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted.
- (b) All previous registrations and permits are superseded by this permit.

B.12 Termination of Right to Operate [326 IAC 2-6.1-7(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least ninety (90) days prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-6.1-7.

B.13 Permit Renewal [326 IAC 2-6.1-7]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-6.1-7. Such information shall be included in the application for each emission unit at this source. The renewal application does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
- (1) Submitted at least ninety (90) days prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-6.1 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.14 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application shall be certified by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

B.15 Source Modification Requirement

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

B.16 Inspection and Entry

[326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2][IC 13-17-3-2][IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.17 Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]

- (a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement notice-only changes addressed in the request for a notice-only change immediately upon submittal of the request. [326 IAC 2-6.1-6(d)(3)]

B.18 Annual Fee Payment [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing.
- (b) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.19 Credible Evidence [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation of Permits), this permit to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
- (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
- (2) If there is a change in the following:
- (A) Asbestos removal or demolition start date;
- (B) Removal or demolition contractor; or
- (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue
MC 61-52 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) Procedures for Asbestos Emission Control
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.

- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Licensed Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Licensed Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-6.1-5(a)(2)]

C.8 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]

C.10 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.12 Instrument Specifications [326 IAC 2-1.1-11]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps

C.13 Response to Excursions or Exceedances

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
 - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records; and/or
 - (3) inspection of the control device, associated capture system, and the process.

- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
 - (1) monitoring data;
 - (2) monitor performance data, if applicable; and
 - (3) corrective actions taken.

C.14 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

C.15 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.16 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.17 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description:

- (a) One (1) RV doors production line, permitted in 2001, with a maximum production rate of 70 units per hour. PM/PM10 emissions from the MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations are controlled by dust collectors DC2 (located outdoors) and DC3. This line includes the following operations:
- (1) Inner frame steel cutting with a maximum cutting rate of 240 pounds per hour;
 - (2) Skin foam cutting with a maximum cutting rate of 120 pounds per hour;
 - (3) Outer frame aluminum cutting with a maximum cutting rate of 890 pounds per hour;
 - (4) Surface coating using aerosol and plevs cans at a maximum rate of 70 units per hour
- (b) One (1) vinyl windows production line for RVs and homes, permitted in 2001, with a maximum production rate of 75 units per hour. PM/PM10 emissions from the MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations are controlled by dust collectors DC2 (located outdoors) and DC3. This line includes the following operations:
- (1) Spacer cutting with a maximum cutting rate of 75 pounds per hour;
 - (2) Grid cutting with a maximum cutting rate of 25 pounds per hour;
 - (3) Glass cutting with a maximum cutting rate of 1400 pounds per hour;
 - (4) Frame parts cutting with a maximum cutting rate of 200 pounds per hour;
 - (5) Sash parts cutting with a maximum cutting rate of 100 pounds per hour;
 - (6) Weld frame through head fusion and surface coating
 - (7) Surface coating using aerosol and plevs cans at a maximum rate of 70 units per hour
- (c) One (1) home HTD/storm door production line, permitted in 2001, with a maximum production rate of 20 units per hour. This line includes: metal cutting with a maximum cutting rate of 450 pounds per hour, application of sealant, surface coating using aerosol and plevs cans at a maximum rate of 70 units per hour, and woodworking operation which is controlled by baghouse DC1;

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

D.1.1 Volatile Organic Compounds (VOCs) [326 IAC 8-2-9]

The actual VOC input, including solvents, to the RV door production line shall be less than fifteen (15) pounds per day in order to render the requirements of 326 IAC 8-2-9 not applicable.

D.1.2 Particulate Emissions (PM) [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2, the particulate from the welding, woodworking, cutting and routing facilities shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
P = process weight rate in tons per hour

Emissions Unit	Process Weight Rate (ton/hr)	PM Allowable (lb/hr)
Welding*	0.0008	0.551
Storm and RV Doors Woodworking	0.01	0.551
Material Cutting and Routing	0.985	4.05

Note: * - for process weight rate less than 100 lb/hr (0.05 ton/hr), the PM emission limit is 0.551 lb/hr.

D.1.3 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan, in accordance with Section C - Preventive Maintenance Plan, of this permit, is required for this emissions unit and any control devices.

Compliance Determination Requirements

D.1.4 Volatile Organic Compounds (VOC)

Compliance with the VOC content and usage limitations contained in Conditions D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.5 Particulate Control

To comply with Condition D.1.2, baghouses (DC1, DC2, and DC3) for particulate control shall be in operation and control emissions from the RV doors production line, the vinyl windows production line, and the home HTD/storm door production line at all times when the facilities exhausting to the corresponding baghouse is in operation.

Compliance Monitoring Requirements [326 IAC 2-8-4]

D.1.6 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the vinyl windows production line. All defective bags shall be replaced.

D.1.7 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) For a single compartment baghouse controlling emissions from a process operated continuously, a failed unit and the associated process shall be shut down immediately until the failed unit has been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit has been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in the line. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

D.1.8 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.1.

- (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each day;
 - (4) The total VOC usage each day for coatings used in the RV door production line;
 - (5) The weight of VOCs emitted for each compliance period for coatings used in the RV door production line.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.
- (c) To document compliance with Condition D.1.6, the Permittee shall maintain records of visible emission notations of the stack (DC2) exhaust once daily. On dates that visible emissions notations are not taken, the Permittee shall include a notation of the reason the visible emission were not taken (e.g. the emissions unit was not in operation on that date).
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.9 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH**

**MINOR SOURCE OPERATING PERMIT
ANNUAL NOTIFICATION**

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

Company Name:	Philips Products
Address:	3221 Magnum Drive
City:	Elkhart, Indiana 46516
Phone #:	574-296-0151
MSOP #:	M039-23429-00128

I hereby certify that Philips Products is :

still in operation.

I hereby certify that Philips Products is :

no longer in operation.

in compliance with the requirements of MSOP M039-23429-00128.

not in compliance with the requirements of MSOP M039-23429-00128.

Authorized Individual (typed):
Title:
Signature:
Date:

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

Noncompliance:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY**

**MINOR SOURCE OPERATING PERMIT (MSOP)
CERTIFICATION**

Source Name: Philips Products
Source Address: 3221 Magnum Drive, Elkhart, Indiana 46516
Mailing Address: 3221 Magnum Drive, Elkhart, Indiana 46516
MSOP No.: M039-23429-00128

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- Annual Compliance Notification
- Test Result (specify) _____
- Report (specify) _____
- Notification (specify) _____
- Affidavit (specify) _____
- Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**MSOP Quarterly Report
(submit one form per booth for each month in the quarter)**

Source Name: Philips Products
Source Address: 3221 Magnum Drive, Elkhart, Indiana 46516
Mailing Address: 3221 Magnum Drive, Elkhart, Indiana 46516
FESOP Permit No.: M039-23429-00128
Facility: RV door production line
Parameter: VOC
Limit: The total input usage of VOC delivered to the applicators in the RV door production line and during clean-up shall be limited to less than 15 pounds per day.*

YEAR: _____ MONTH: _____

Day	VOC usage	Day	VOC usage
1		17	
2		18	
3		19	
4		20	
5		21	
6		22	
7		23	
8		24	
9		25	
10		26	
11		27	
12		28	
13		29	
14		30	
15		31	
16			

*A notation must be made to indicate days on which surface coating was not conducted.

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

MALFUNCTION REPORT

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY FAX NUMBER - 317 233-6865

This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4.

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?____, 25 TONS/YEAR SULFUR DIOXIDE ?____, 25 TONS/YEAR NITROGEN OXIDES?____, 25 TONS/YEAR VOC ?____, 25 TONS/YEAR HYDROGEN SULFIDE ?____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?____, 25 TONS/YEAR FLUORIDES ?____, 100 TONS/YEAR CARBON MONOXIDE ?____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF "MALFUNCTION" AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: _____ PHONE NO. () _____
LOCATION: (CITY AND COUNTY) _____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP: _____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/20____ _____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: _____

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/20____ _____ AM/PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____

CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____

CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____

INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

*SEE PAGE 2

Please note - This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4.

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

***Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

Indiana Department of Environmental Management
Office of Air Quality

Addendum to the Technical Support Document for a Minor Source Operating Permit
(MSOP)

Source Background and Description

Source Name: Philips Products
Source Location: 3221 Magnum Drive, Elkhart, Indiana 46516
County: Elkhart
SIC Code: 3442, 3089
FESOP Permit No.: M039-23429-00128
Permit Reviewer: Summer Keown

On October 9, 2008, the Office of Air Quality (OAQ) sent a Public Notice to The Elkhart Truth stating that Philips Products had applied for a Minor Source Operating Permit to operate a steel doors, RV doors, storm doors and vinyl windows manufacturing plant. The notice also stated that OAQ proposed to issue a Minor Source Operating Permit for this operation and provided information on how the public could review the proposed Minor Source Operating Permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this Minor Source Operating Permit should be issued as proposed.

On October 21, 2008, on behalf of Philips Products, Lauren Pecina submitted comments on the proposed Minor Source Operating Permit. The comments are as follows: The permit language, if changed, has deleted language as ~~strikeouts~~ and new language **bolded**.

Comment 1:

Section D.1.6 of the permit regards visible emissions notations for DC2. The dust collector venting to DC2 captures pieces of foam from cutting operations. Hence, there would be no "abnormal emissions" coming from the stack. The pieces of foam captured in the dust collection system are quite large and would not cause any sort of dust in the air. I would like this requirement to be taken out of the permit if possible.

Compliance Monitoring Requirements [326 IAC 2-8-4]

D.1.6 Visible Emissions Notations

-
- (a) Visible emission notations of the stack (DC2) exhaust shall be performed once per day during normal daylight operations. A trained employee shall record whether emissions are normal or abnormal.
 - (b) For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not including startup or shutdown time.
 - (c) In the case of batch or discontinuous operations, reading shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
 - (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
 - (e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take

response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

Response 1:

Because the emissions for the controlled pollutant do not exceed ten pounds per hour, the visible emissions notations are not required. D.1.6 has been removed from the permit and the following permit conditions have been renumbered accordingly.

~~D.1.6 Visible Emissions Notations~~

- ~~(a) Visible emission notations of the stack (DC2) exhaust shall be performed once per day during normal daylight operations. A trained employee shall record whether emissions are normal or abnormal.~~
- ~~(b) For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not including startup or shutdown time.~~
- ~~(c) In the case of batch or discontinuous operations, reading shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.~~
- ~~(d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.~~
- ~~(e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.~~

~~D.1.76 Baghouse Inspections~~

~~An inspection shall be performed each calendar quarter of all bags controlling the vinyl windows production line. All defective bags shall be replaced.~~

Comment 2:

Section D.1.8(a) requires that records should be taken monthly, however, there is a daily VOC usage limit in the permit. Also, D.1.8(a)(5) should state, "the weight of VOC's emitted for each compliance period FOR COATINGS USED ON THE RV DOOR PRODUCTION LINE". This will distinguish the requirement from having to record emissions on the other lines.

~~D.1.8 Record Keeping Requirements~~

- ~~(a) To document compliance with Condition D.1.1, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.1.
 - ~~(1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;~~
 - ~~(2) A log of the dates of use;~~~~

- (3) The cleanup solvent usage for each day;
 - (4) The total VOC usage each day for coatings used in the RV door production line;
 - (5) The weight of VOCs emitted for each compliance period **for coatings used in the RV door production line.**
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.
 - (c) To document compliance with Condition D.1.6, the Permittee shall maintain records of visible emission notations of the stack (DC2) exhaust once daily. On dates that visible emissions notations are not taken, the Permittee shall include a notation of the reason the visible emission were not taken (e.g. the emissions unit was not in operation on that date).
 - (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

Response 2:

The following changes have been made to Condition D.1.8, pages 18-19 of the permit:

D.1.8 Record Keeping Requirements

- (a) To document compliance with Condition D.1.1, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) ~~shall be taken monthly and~~ shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.1.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each day;
 - (4) The total VOC usage each day for coatings used in the RV door production line;
 - (5) The weight of VOCs emitted for each compliance period.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.
- (c) To document compliance with Condition D.1.6, the Permittee shall maintain records of visible emission notations of the stack (DC2) exhaust once daily. On dates that visible emissions notations are not taken, the Permittee shall include a notation of the reason the visible emission were not taken (e.g. the emissions unit was not in operation on that date).
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

Indiana Department of Environmental Management
Office of Air Quality

Technical Support Document (TSD) for a Minor Source Operating Permit Renewal

Source Background and Description

Source Name:	Philips Products
Source Location:	3221 Magnum Drive, Elkhart, Indiana 46516
County:	Elkhart
SIC Code:	3442, 3089
Permit Renewal No.:	M039-23429-00128
Permit Reviewer:	Summer Keown

The Office of Air Quality (OAQ) has reviewed the operating permit renewal application from Philips Products relating to the operation of a steel doors, RV doors, storm doors and vinyl windows manufacturing plant.

On July 28, 2006, Philips Products submitted an application to the OAQ requesting to renew its operating permit. Philips Products was issued MSOP No. M039-14462-00128 on October 25, 2001.

Permitted Emission Units and Pollution Control Equipment

- (a) One (1) RV doors production line, permitted in 2001, with a maximum production rate of 70 units per hour. PM/PM10 emissions from the MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations are controlled by dust collectors DC2 (located outdoors) and DC3, venting indoors. This line includes the following operations:
 - (1) Inner frame steel cutting with a maximum cutting rate of 240 pounds per hour;
 - (2) Skin foam cutting with a maximum cutting rate of 120 pounds per hour;
 - (3) Outer frame aluminum cutting with a maximum cutting rate of 890 pounds per hour;
 - (4) Surface coating using aerosol and plews cans at a maximum rate of 70 units per hour

- (b) One (1) vinyl windows production line for RVs and homes, permitted in 2001, with a maximum production rate of 75 units per hour. PM/PM10 emissions from the MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations are controlled by dust collectors DC2 (located outdoors) and DC3. This line includes the following operations:
 - (1) Spacer cutting with a maximum cutting rate of 75 pounds per hour;
 - (2) Grid cutting with a maximum cutting rate of 25 pounds per hour;
 - (3) Glass cutting with a maximum cutting rate of 1400 pounds per hour;
 - (4) Frame parts cutting with a maximum cutting rate of 200 pounds per hour;
 - (5) Sash parts cutting with a maximum cutting rate of 100 pounds per hour;
 - (6) Weld frame through head fusion and surface coating
 - (7) Surface coating using aerosol and plews cans at a maximum rate of 70 units per hour

- (c) One (1) home HTD/storm door production line, permitted in 2001, with a maximum production rate of 20 units per hour. This line includes: metal cutting with a maximum cutting rate of 450 pounds per hour, application of sealant, surface coating using aerosol and plews cans at a maximum rate of 70 units per hour, and woodworking operation which is controlled by baghouse DC1;
- (d) One (1) natural gas-fired applied air heating unit, identified as S7, with a heat input capacity of 3.125 million British Thermal Units per hour (MMBtu/hr);
- (e) One (1) natural gas-fired rapid air make-up unit, identified as S9 with a heat input capacity of 3.3 MMBtu/hr; and

Emission Units and Pollution Control Equipment Removed From the Source

- (a) One (1) natural gas-fired applied air heating unit, identified as S3, with a heat input capacity of 3.125 million British Thermal Units per hour (MMBtu/hr)

Existing Approvals

Since the issuance of the MSOP (M039-14462-00128) on October 25, 2001, the source has constructed or has been operating under the following approval as well:

- (a) Notice-Only Change No. 039-18721-00128 issued on March 15, 2004

All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

Enforcement Issue

There are no enforcement actions pending.

Emission Calculations

See Appendix A, pages 1 through 7, of this document for detailed emission calculations.

County Attainment Status

The source is located in Elkhart County

Pollutant	Designation
SO ₂	Better than national standards.
CO	Unclassifiable or attainment effective November 15, 1990.
O ₃	Attainment effective July 19, 2007, for the 8-hour ozone standard. ¹
PM ₁₀	Unclassifiable effective November 15, 1990.
NO ₂	Cannot be classified or better than national standards.
Pb	Not designated.

¹Attainment effective October 18, 2000, for the 1-hour ozone standard for the South Bend-Elkhart area, including Elkhart County, and is a maintenance area for the 1-hour National Ambient Air Quality Standards (NAAQS) for purposes of 40 CFR 51, Subpart X*. The 1-hour standard was revoked effective June 15, 2005.
Unclassifiable or attainment effective April 5, 2005, for PM2.5.

(a) Ozone Standards

- (1) On October 25, 2006, the Indiana Air Pollution Control Board finalized a rule revision to 326 IAC 1-4-1 revoking the one-hour ozone standard in Indiana.
- (2) On September 6, 2007, the Indiana Air Pollution Control Board finalized a temporary emergency rule to re-designate Allen, Clark, Elkhart, Floyd, LaPorte, and St. Joseph as attainment for the 8-hour ozone standard.
- (3) On November 9, 2007, the Indiana Air Pollution Control Board finalized a temporary emergency rule to re-designate Boone, Clark, Elkhart, Floyd, LaPorte, Hamilton, Hancock, Hendricks, Johnson, Madison, Marion, Morgan, Shelby, and St. Joseph as attainment for the 8-hour ozone standard.
- (4) Volatile organic compounds (VOC) and Nitrogen Oxides (NOx) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NOx emissions are considered when evaluating the rule applicability relating to ozone. Elkhart County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

(b) PM2.5

Elkhart County has been classified as attainment for PM2.5. On May 8, 2008 U.S. EPA promulgated the requirements for Prevention of Significant Deterioration (PSD) for PM2.5 emissions, and the effective date of these rules was July 15th, 2008. Indiana has three years from the publication of these rules to revise its PSD rules, 326 IAC 2-2, to include those requirements. The May 8, 2008 rule revisions require IDEM to regulate PM10 emissions as a surrogate for PM2.5 emissions until 326 IAC 2-2 is revised.

(c) Other Criteria Pollutants

Elkhart County has been classified as attainment or unclassifiable in Indiana for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

(d) Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 or 326 IAC 2-3, fugitive emissions are not counted toward the determination of PSD and Emission Offset applicability.

Unrestricted Potential Emissions

Appendix A, pages 1 through 7, of this TSD reflects the unrestricted potential emissions of the source.

- (a) The potential to emit (as defined in 326 IAC 2-7-1(29)) of all criteria pollutants is still less than 100 tons per year. The source is not subject to the provisions of 326 IAC 2-7. Therefore, the source will be issued a MSOP Renewal.
- (b) The potential to emit (as defined in 326 IAC 2-7-1(29)) of any single HAP is less than ten (10) tons per year and/or the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination of HAPs is less than twenty-five (25) tons per year.

- (c) Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-7, fugitive emissions are not counted toward the determination of Part 70 applicability.

Potential to Emit After Issuance

Process/ Emission Unit	Potential To Emit (tons/year)								
	PM	PM ₁₀	PM _{2.5}	SO ₂	VOC	CO	NO _x	Single HAP	Total HAPs
Surface Coating - HTD Storm Door Production Line	0.03	0.03	0.03	0.00	2.09	0.00	0.00	2.09 (toluene)	2.11
Surface Coating - RV Door Production Line	4.13	4.13	4.13	0.00	<2.74*	0.00	0.00	2.74 (toluene)	2.75
Surface Coating - Vinyl Windows Line	0.01	0.01	0.01	0.00	0.38	0.00	0.00	0.19 (toluene)	0.2
Natural Gas Combustion	0.05	0.21	0.21	0.02	0.15	2.36	2.81	0.05 (hexane)	0.05
Welding	0.03	0.03	0.03	0.00	0.00	0.00	0.00	0.02 (Mn)	0.02
HTD/storm door production lines with Baghouse DC1	4.09	4.09	4.09	0.00	0.00	0.00	0.00	0.00	0.00
MH/RV line with Baghouses DC2 and DC3	35.07	35.07	35.07	0.00	0.00	0.00	0.00	0.00	0.00
Total Emissions	4.64	4.80	4.80	0.02	<5.36	2.36	2.81	5.02 (toluene)	5.13

*The source has agreed to limit their VOC emissions from the RV Door Production Line to less than 15 pounds per day, which is equivalent to 2.74 tons per year, to avoid being subject to 326 IAC 8-2-9.

- (a) This existing stationary source is not major for PSD because the emissions of each criteria pollutant are less than two hundred fifty (<250) tons per year, and it is not one of the twenty-eight (28) listed source categories.
- (b) Fugitive Emissions
 Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 or 326 IAC 2-3, fugitive emissions are not counted toward the determination of PSD and Emission Offset applicability.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) included in the permit for this source.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAP) (326 IAC 14, 326 IAC 20 and 40 CFR Part 63) included in this permit renewal.
- (d) The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Surface Coating of Wood Building Products, 40 CFR 63.4860 through 40 CFR 63.4781, Subpart QQQQ (326 IAC 20-79), are not included in the permit, since the RV doors production line and the HTD/storm door production line are not a major sources, and are not located at a major source emissions of hazardous air pollutants (HAPs).
- (e) The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Surface Coating of Plastic Parts and Products, 40 CFR 63.4480 through 40 CFR 63.4581, Subpart PPPP (326 IAC 20-81), are not included in the permit, since the RV doors production line, the vinyl windows production line, and the home HTD/storm

door production line are not major sources, and are not located at a major source of emissions of hazardous air pollutants (HAPs).

- (f) The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63.3880 through 40 CFR 63.3981, Subpart M (326 IAC 20-80), are not included in the permit, since the RV doors production line, the vinyl windows production line, and the HTD/storm door production line are not major sources, and are not located at a major source of emissions of hazardous air pollutants (HAPs).

State Rule Applicability - Entire Source

326 IAC 2-6 (Emission Reporting)

This source is located in Elkhart County and the potential to emit of each criteria pollutant is less than one hundred (100) tons per year. Therefore, 326 IAC 2-6 does not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability – Individual Facilities

326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP))

The operation of the RV doors production line, the vinyl windows production line, and the HTD/storm door production line will emit less than 10 tons per year of a single HAP and less than 25 tons per year of a combination of HAPs. Therefore, 326 IAC 2-4.1 does not apply.

326 IAC 6-2 (Particulate Emissions Limitations for Sources of Indirect Heating)

The one (1) natural gas-fired applied air heating unit, identified as S7, and the one (1) natural gas-fired rapid air make-up unit, identified as S9, are not sources of indirect heating. Therefore, 326 IAC 6-2-4 is not applicable to these units.

326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes)

The surface coating operations associated with the RV doors production line, the vinyl windows production line, and the HTD/storm door production line use less than five (5) gallons per day. Therefore, pursuant to 326 IAC 6-3-1(15), this rule does not apply to the surface coating operations.

326 IAC 6-3-2 (Particulate Emission Limitations, Work Practices, and Control Technologies)

Pursuant to 326 IAC 6-3-2, the particulate from the welding, woodworking, cutting and routing facilities shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
P = process weight rate in tons per hour

Emissions Unit	Process Weight Rate (ton/hr)	PM Allowable (lb/hr)
Welding*	0.0008	0.551
Storm and RV Doors Woodworking*	0.01	0.551
Material Cutting and Routing	0.985	4.05

Note: * - for process weight rate less than 100 lb/hr (0.05 ton/hr), the PM emission limit is 0.551 lb/hr.

326 IAC 8-1-6 (New Facilities; General Reduction Requirements)

326 IAC 8-1-6 is applicable to new facilities that have potential VOC emissions of twenty-five (25) tons per year or more. The vinyl window production line has potential VOC emissions of less than twenty-five (25) tons per year. Therefore, 326 IAC 8-1-6 is not applicable.

326 IAC 8-2-2 (Automobile and Light Duty Truck Coating Operations)

326 IAC 8-2-2 establishes emission limitations for automobile and light duty truck surface coating. This source applies surface coatings to RV doors. Because recreational vehicles (RVs) are not considered automobiles or light duty trucks, this rule is not applicable to the source.

326 IAC 8-2-9 (Miscellaneous Metal Coating)

- (1) The potential to emit of VOC from the RV door production line is greater than fifteen (15) pounds per day. However, the source has opted to limit the VOC input to less than fifteen (15) pounds per day in order to render the requirements of 326 IAC 8-2-9 not applicable. Therefore, the owner or operator of this source shall comply with the following:
 - (a) The actual VOC input for the RV door production line shall be less than 15.0 pounds per day. Compliance with this limit renders the requirements of 326 IAC 8-2-9 not applicable.
 - (b) To document compliance with this limit, the owner or operator of this source shall maintain records for the total VOC input for the RV door production line each day. These records shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC emission limit for the RV door production line:
 - (i) The amount and VOC content of each coating material, dilution solvent, and cleanup solvent used for each day. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount of materials used.
 - (ii) The total VOC input for each day.
 - (c) Records of all required monitoring data, reports and support information required by this exemption shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the owner or operator of this source, the owner or operator of this source shall furnish the records to the Commissioner within a reasonable time.
 - (d) Unless otherwise specified in this exemption, all record keeping requirements not already legally required shall be implemented within ninety (90) days of the approval date of this exemption.

- (2) The HTD storm door production line has potential VOC emissions of less than fifteen (15) pounds per day, before add-on controls. Therefore, it is not subject to 326 IAC 8-2-9.
- (2) The vinyl windows production line has potential VOC emissions of less than fifteen (15) pounds per day and does not coat metal. Therefore, it is not subject to 326 IAC 8-2-9.

Compliance Determination and Monitoring Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with all applicable state and federal rules on a continuous basis. All state and federal rules contain compliance provisions; however, these provisions do not always fulfill the requirement for a continuous demonstration. When this occurs, IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, Compliance Determination Requirements are included in the permit. The Compliance Determination Requirements in Section D of the permit are those conditions that are found directly within state and federal rules and the violation of which serves as grounds for enforcement action.

If the Compliance Determination Requirements are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

The operations controlled by dust collector DC2 have applicable compliance determination conditions as specified below. Dust collectors DC1 and DC3 vent indoors. Therefore, they are not subject to Visible Emissions Notations.

(a) Visible Emissions Notations

- (1) Visible emission notations of the stack (DC2) exhaust shall be performed once per day during normal daylight operations. A trained employee shall record whether emissions are normal or abnormal.
- (2) For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not including startup or shutdown time.
- (3) In the case of batch or discontinuous operations, reading shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (4) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (5) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

(b) Baghouse Monitoring

An inspection shall be performed each calendar quarter of all bags controlling the machining and woodworking operation. In the vent that bag failure has occurred:

- (1) For a single compartment baghouse controlling emissions from a process operated continuously, a failed unit and the associated process shall be shut down immediately until the failed unit has been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (2) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit has been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in the line. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Bag failure can be indicated by a significant drop in the baghouse's pressure reading with abnormal visible emissions, by an opacity violation, or by other means such as gas temperature, flow rate, air infiltration, leaks or dust traces.

Recommendation

The staff recommends to the Commissioner that the MSOP Renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on July 26, 2006.

Conclusion

The operation of this steel doors, RV doors, storm doors and vinyl windows manufacturing plant shall be subject to the conditions of the attached MSOP Renewal No. 039-23429-00128.

Company Name: Philips Products
Address City IN Zip: 3221 Magnum Drive, Elkhart, IN 46516
Permit Number: 039-23429-00128
Reviewer: Summer Keown
Date: July 3, 2008

Uncontrolled Emissions

Emissions Unit	PM	PM10	PM2.5	VOC	NOx	SO ²	CO	Single HAP	Total HAPs
Surface Coating - HTD Storm Door Production Line	0.03	0.03	0.03	2.09	0.00	0.00	0.00	2.09 (toluene)	2.11
Surface Coating - RV Door Production Line	4.13	4.13	4.13	3.54	0.00	0.00	0.00	3.54 (toluene)	3.55
Surface Coating - Vinyl Windows Line	0.01	0.01	0.01	0.38	0.00	0.00	0.00	0.19 (toluene)	0.2
Natural Gas Combustion	0.05	0.21	0.21	0.15	2.81	0.02	2.36	0.05 (hexane)	0.05
Welding	0.03	0.03	0.03	0	0	0	0	0.02 (Mn)	0.02
HTD/storm door production line with Baghouse DC1	4.09	4.09	4.09	0.00	0.00	0.00	0.00	0.00	0.00
MH/RV line with Baghouses DC2 and DC3	35.07	35.07	35.07	0.00	0.00	0.00	0.00	0.00	0.00
Total	43.41	43.57	43.57	6.16	2.81	0.02	2.36	5.82 (toluene)	5.93

Controlled Emissions

Emissions Unit	PM	PM10	PM2.5	VOC	NOx	SO ²	CO	Single HAP	Total HAPs
Surface Coating - HTD Storm Door Production Line	0.03	0.03	0.03	2.09	0.00	0.00	0.00	2.09 (toluene)	2.11
Surface Coating - RV Door Production Line	4.13	4.13	4.13	<2.74*	0.00	0.00	0.00	2.74 (toluene)	2.75
Surface Coating - Vinyl Windows Line	0.01	0.01	0.01	0.38	0.00	0.00	0.00	0.19 (toluene)	0.2
Natural Gas Combustion	0.05	0.21	0.21	0.15	2.81	0.02	2.36	0.05 (hexane)	0.05
Welding	0.03	0.03	0.03	0	0	0	0	0.02 (Mn)	0.02
HTD/storm door production line with Baghouse DC1	0.04	0.04	0.04	0.00	0.00	0.00	0.00	0.00	0.00
MH/RV line with Baghouses DC2 and DC3	0.35	0.35	0.35	0.00	0.00	0.00	0.00	0.00	0.00
Total	4.64	4.80	4.80	<5.36	2.81	0.02	2.36	5.02 (toluene)	5.13

*The source has agreed to limit their VOC emissions from the RV Door Production Line to less than 15 pounds per day, which is equivalent to 2.74 tons per year, to avoid being subject to 326 IAC 8-2-9.

**Appendix A: Emissions Calculations
VOC and Particulate
From Surface Coating Operations**

**Company Name: Philips Products
Address City IN Zip: 3221 Magnum Drive, Elkhart, IN 46516
Permit Number: 039-23429-00128
Reviewer: Summer Keown
Date: July 3, 2008**

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
HTD Storm Door Production Line																
(HTD Main Line) SM5504	8.3	42.00%	0.0%	42.0%	0.0%	57.00%	0.00200	20.000	3.47	3.47	0.14	3.33	0.61	0.00	6.09	100%
(HTD 7000) SM5504	8.3	42.00%	0.0%	42.0%	0.0%	57.00%	0.00344	20.000	3.47	3.47	0.24	5.73	1.05	0.00	6.09	100%
(HTD 87) SM5504	8.3	42.00%	0.0%	42.0%	0.0%	57.00%	0.00687	20.000	3.47	3.47	0.48	11.44	2.09	0.00	6.09	100%
SM5504	8.3	42.00%	0.0%	42.0%	0.0%	57.00%	0.00025	70.000	3.47	3.47	0.06	1.46	0.27	0.00	6.09	100%
Raabe Paint	7.4	92.00%	0.0%	92.0%	0.0%	8.00%	0.00030	130.000	6.81	6.81	0.27	6.37	1.16	0.03	85.10	75%
RV Door Production Line																
SM5504	8.3	42.00%	0.0%	42.0%	0.0%	57.00%	0.00333	70.000	3.47	3.47	0.81	19.41	3.54	0.00	6.09	100%
3M Super 77	8.8	75.00%	0.0%	75.0%	0.0%	25.00%	0.00128	70.000	6.60	6.60	0.59	14.19	2.59	0.22	26.40	75%
Perma Lok MM15	8.9	1.00%	0.0%	1.0%	0.0%	99.00%	0.00002	70.000	0.09	0.09	0.00	0.00	0.00	0.01	0.09	75%
Raabe Paint	7.4	92.00%	0.0%	92.0%	0.0%	8.00%	0.00030	70.000	6.81	6.81	0.14	3.43	0.63	0.01	85.10	75%
Purfect Lok 34-9022	8.8	2.00%	0.0%	2.0%	0.0%	0.00%	0.00625	70.000	0.18	0.18	0.08	1.85	0.34	4.13	N/A	75%
Vinyl Windows for RVs & Homes																
Raabe Paint	7.4	92.00%	0.0%	92.0%	0.0%	8.00%	0.00017	75.000	6.81	6.81	0.09	2.08	0.38	0.01	85.10	75%
SM5504	8.3	42.00%	0.0%	42.0%	0.0%	57.00%	0.00030	75.000	3.47	3.47	0.08	1.87	0.34	0.00	6.09	100%

Total for worst case materials: 32.93 6.01 4.16

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)
Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)
Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)
Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)
Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)
Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)
Total = Worst Coating + Sum of all solvents used

Appendix A: Emission Calculations
HAP Emission Calculations

Company Name: Philips Products
Address City IN Zip: 3221 Magnum Drive, Elkhart, IN 46516
Permit Number: 039-23429-00128
Permit Reviewer: Summer Keown
Date: July 3, 2008

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Weight % Xylene	Weight % Toluene	Weight % MDI	Weight % Hexane	Weight % Glycol Ethers	Weight % Methanol	Xylene Emissions (ton/yr)	Toluene Emissions (ton/yr)	MDI Emissions (ton/yr)	Hexane Emissions (ton/yr)	Glycol Ethers Emissions (ton/yr)	Methanol Emissions (ton/yr)
HTD Storm Door Production Line															
(HTD Main Line) SM5504	8.26	0.00200	20.000	0.00%	42.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.61	0.00	0.00	0.00	0.00
(HTD 7000) SM5504	8.26	0.00344	20.000	0.00%	42.00%	0.00%	0.00%	0.00%	0.00%	0.00	1.05	0.00	0.00	0.00	0.00
(HTD 87) SM5504	8.26	0.00687	20.000	0.00%	42.00%	0.00%	0.00%	0.00%	0.00%	0.00	2.09	0.00	0.00	0.00	0.00
SM5504	8.26	0.00025	70.000	0.00%	42.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.27	0.00	0.00	0.00	0.00
Raabe Paint	7.40	0.00030	130.000	1.30%	9.23%	0.00%	0.00%	0.00%	0.00%	0.02	0.12	0.00	0.00	0.00	0.00
RV Door Production Line															
SM5504	8.26	0.00333	70.000	0.00%	42.00%	0.00%	0.00%	0.00%	0.00%	0.00	3.54	0.00	0.00	0.00	0.00
3M Super 77	8.80	0.00128	70.000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Perma Lok MM15	8.90	0.00002	70.000	0.00%	0.00%	2.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Raabe Paint	7.40	0.00030	70.000	1.30%	9.23%	0.00%	0.00%	0.00%	0.00%	0.01	0.06	0.00	0.00	0.00	0.00
Purfect Lok 34-9022	8.80	0.00625	70.000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00
Vinyl Windows for RVs & Homes															
Raabe Paint	7.40	0.00030	75.000	1.30%	9.23%	0.00%	0.00%	0.00%	0.00%	0.01	0.07	0.00	0.00	0.00	0.00
SM5504	8.26	0.00017	75.000	0.00%	42.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.19	0.00	0.00	0.00	0.00

Total State Potential Emissions **0.03 5.82 0.00 0.00 0.00 0.00**

METHODOLOGY

Total HAPs: 5.85

HAPS emission rate (tons/yr) = Density (lb/gal) * Gal of Material (gal/unit) * Maximum (unit/hr) * Weight % HAP * 8760 hrs/yr * 1 ton/2000 lbs

**Appendix A: Emissions Calculations
Natural Gas Combustion Only
MM BTU/HR <100**

1 applied air heating unit
@ 3.125 MMBtu/hr
1 rapid air make-up unit
@ 3.3 MMBtu/hr

Company Name: Philips Products
Address City IN Zip: 3221 Magnum Drive, Elkhart, IN 46516
Permit Number: 039-23429-00128
Reviewer: Summer Keown
Date: July 3, 2008

Heat Input Capacity
MMBtu/hr

Potential Throughput
MMCF/yr

6.425

56.3

Emission Factor in lb/MMCF	Pollutant					
	PM*	PM10*	PM2.5*	SO2	NOx	VOC
	1.9	7.6	7.6	0.6	100.0 **see below	5.5
Potential Emission in tons/yr	0.05	0.21	0.21	0.02	2.81	0.15

*PM emission factor is filterable PM only. PM10 and PM2.5 emission factors are filterable and condensable PM10 combined.

**Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

See page 5 for HAPs emissions calculations.

Appendix A: Emissions Calculations

Natural Gas Combustion Only

MM BTU/HR <100

HAPs Emissions

Company Name: Philips Products

Address City IN Zip: 3221 Magnum Drive, Elkhart, IN 46516

Permit Number: 039-23429-00128

Reviewer: Summer Keown

Date: July 3, 2008

HAPs - Organics					
Emission Factor in lb/MMcf	Benzene 2.1E-03	Dichlorobenzene 1.2E-03	Formaldehyde 7.5E-02	Hexane 1.8E+00	Toluene 3.4E-03
Potential Emission in tons/yr	5.910E-05	3.377E-05	2.111E-03	5.065E-02	9.568E-05

HAPs - Metals					
Emission Factor in lb/MMcf	Lead 5.0E-04	Cadmium 1.1E-03	Chromium 1.4E-03	Manganese 3.8E-04	Nickel 2.1E-03
Potential Emission in tons/yr	1.407E-05	3.096E-05	3.940E-05	1.069E-05	5.910E-05

Methodology is the same as page 1.

Total HAPs: 0.05

The five highest organic and metal HAPs emission factors are provided above. Additional HAPs emission factors are available in AP-42, Chapter 1.4.

**Appendix A: Emissions Calculations
Welding and Thermal Cutting**

Company Name: Philips Products
Address City IN Zip: 3221 Magnum Drive, Elkhart, IN 46516
Permit Number: 039-23429-00128
Reviewer: Summer Keown
Date: July 3, 2008

PROCESS	Number of Stations	Max. electrode consumption per station (lbs/hr)	EMISSION FACTORS* (lb pollutant/lb electrode)				EMISSIONS (lbs/hr)				HAPS (lbs/hr)
			PM = PM10 = PM2.5	Mn	Ni	Cr	PM = PM10	Mn	Ni	Cr	
WELDING											
Steel E70S	1	1.2	0.0052	0.00318	0.00001	0.00001	0.006	0.004	0.000	0.000012	0.004
Aluminim ER5356	1	0.4	0.0041	0	0	0	0.002	0.000	0.000	0	0.000
EMISSION TOTALS											
Potential Emissions lbs/hr							0.01	0.00	0.00	0.00	0.00
Potential Emissions lbs/day							0.19	0.09	0.00	0.00	0.09
Potential Emissions tons/year							0.03	0.02	0.00	0.00	0.02

METHODOLOGY

Welding emissions, lb/hr: (# of stations)(max. lbs of electrode used/hr/station)(emission factor, lb. pollutant/lb. of electrode used)

Emissions, lbs/day = emissions, lbs/hr x 24 hrs/day

Emissions, tons/yr = emissions, lb/hr x 8,760 hrs/year x 1 ton/2,000 lb

Emissions factors for Steel E70S are from AP-42 12.19-1 SCC 3-09-052

Emission factors for Aluminum ER5356 provided by source.

Appendix A: Emissions Calculations

Company Name: Philips Products
Address City IN Zip: 3221 Magnum Drive, Elkhart, IN 46516
Permit Number: 039-23429-00128
Reviewer: Summer Keown
Date: July 3, 2008

Baghouse DC1 (Home HTD/ storm door production line - Metal cutting and woodworking operation):

Outlet grain loading: 0.00033 gr/dscf
Air flow: 3300 cfm
Efficiency: 99%

PM/PM10/PM2.5 Controlled emissions: 0.01 lb/hr
0.04 tons/yr

PM/PM10/PM2.5 Uncontrolled emissions: 0.93 lb/hr
4.09 tons/yr

Baghouse DC2 (MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations):

Outlet grain loading: 0.00455 gr/dscf
Air flow: 2000 cfm
Efficiency: 99%

PM/PM10/PM2.5 Controlled emissions: 0.08 lb/hr
0.34 tons/yr

PM/PM10/PM2.5 Uncontrolled emissions: 7.8 lb/hr
34.16 tons/yr

Baghouse DC3 (MH/RV fiberglass, steel, aluminum, foam cutting, routing and woodworking operations):

Outlet grain loading: 0.00048 gr/dscf
Air flow: 500 cfm
Efficiency: 99%

PM/PM10/PM2.5 Controlled emissions: 0.002 lb/hr
0.01 tons/yr

PM/PM10/PM2.5 Uncontrolled emissions: 0.21 lb/hr
0.90 tons/yr

Total PM/PM10/PM2.5 Controlled Emissions for
DC2 and DC3: 0.35 tons/yr
Total PM/PM10/PM2.5 Uncontrolled Emissions for
DC2 and DC3: 35.07 tons/yr