



*Mitchell E. Daniels, Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
(800) 451-6027  
www.IN.gov/idem

TO: Interested Parties / Applicant

DATE: November 24, 2008

RE: Batesville Manufacturing, Inc. / 137 - 24390 - 00016

FROM: Matthew Stuckey, Deputy Branch Chief  
Permits Branch  
Office of Air Quality

### **Notice of Decision: Approval – Effective Immediately**

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-6-1(b) or IC 13-15-6-1(a) require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204.

For an **initial Title V Operating Permit**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **thirty (30)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(b).

For a **Title V Operating Permit renewal**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **fifteen (15)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(a).

The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

Pursuant to 326 IAC 2-7-18(d), any person may petition the U.S. EPA to object to the issuance of an initial Title V operating permit, permit renewal, or modification within sixty (60) days of the end of the forty-five (45) day EPA review period. Such an objection must be based only on issues that were raised with reasonable specificity during the public comment period, unless the petitioner demonstrates that it was impracticable to raise such issues, or if the grounds for such objection arose after the comment period.

To petition the U.S. EPA to object to the issuance of a Title V operating permit, contact:

U.S. Environmental Protection Agency  
401 M Street  
Washington, D.C. 20406

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

## Part 70 Operating Permit Renewal OFFICE OF AIR QUALITY

**Batesville, Manufacturing, Inc  
1000 East Pearl Street  
Batesville, Indiana 47006**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

**The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.**

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T137-24390-00016	
Issued by: <i>Original Signed By:</i>	Issuance Date: November 24, 2008
Tripurari P. Sinha, Ph. D., Section Chief Permits Branch Office of Air Quality	Expiration Date: November 24, 2013

## TABLE OF CONTENTS

A. SOURCE SUMMARY .....	5
A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]	
A.2 Part 70 Source Definition [326 IAC 2-7-1(22)]	
A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]	
A.4 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.5 Part 70 Permit Applicability [326 IAC 2-7-2]	
B. GENERAL CONDITIONS .....	8
B.1 Definitions [326 IAC 2-7-1]	
B.2 Permit Term [326 IAC 2-7-5(2)][326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]	
B.3 Term of Conditions [326 IAC 2-1.1-9.5]	
B.4 Enforceability [326 IAC 2-7-7]	
B.5 Severability [326 IAC 2-7-5(5)]	
B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	
B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]	
B.8 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]	
B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]	
B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]	
B.11 Emergency Provisions [326 IAC 2-7-16]	
B.12 Permit Shield [326 IAC 2-7-15][326 IAC 2-7-20][326 IAC 2-7-12]	
B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]	
B.14 Termination of Right to Operate [326 IAC 2-7-10][326 IAC 2-7-4(a)]	
B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]	
B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)][326 IAC 2-7-8(a)][326 IAC 2-7-9]	
B.17 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4][326 IAC 2-7-8(e)]	
B.18 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12] [40 CFR 72]	
B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12(b)(2)]	
B.20 Operational Flexibility [326 IAC 2-7-20][326 IAC 2-7-10.5]	
B.21 Source Modification Requirement [326 IAC 2-7-10.5]	
B.22 Inspection and Entry [326 IAC 2-7-6][IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]	
B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]	
B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]	
B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]	
C. SOURCE OPERATION CONDITIONS .....	19
<b>Emission Limitations and Standards [326 IAC 2-7-5(1)]</b>	
C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2 Opacity [326 IAC 5-1]	
C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.5 Fugitive Dust Emissions [326 IAC 6-4]	
C.6 Stack Height [326 IAC 1-7]	
C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	

**Testing Requirements [326 IAC 2-7-6(1)]**

- C.8 Performance Testing [326 IAC 3-6]

**Compliance Requirements [326 IAC 2-1.1-11]**

- C.9 Compliance Requirements [326 IAC 2-1.1-11]

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]**

- C.10 Compliance Monitoring [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]
- C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.12 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)]  
[326 IAC 2-7-6(1)]

**Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]**

- C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
- C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]  
[326 IAC 2-7-6]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]
- C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

**Stratospheric Ozone Protection**

- C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

D.1. EMISSIONS UNIT OPERATION CONDITIONS ..... 28

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.1.1 PSD Minor Limits [326 IAC 2-2]
- D.1.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]
- D.1.3 Particulate Emission Limitation, Work Practices, and Control Technologies  
[326 IAC 6-3-2(d)]
- D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.1.5 Volatile Organic Compounds (VOCs)

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]**

- D.1.6 Operator-Training Program

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- D.1.7 Record Keeping Requirement
- D.1.8 Reporting Requirement

D.2. EMISSIONS UNIT OPERATION CONDITIONS ..... 32

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.2.1 PSD Minor Limits [326 IAC 2-2]
- D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]
- D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]
- D.2.4 Particulate Emission Limitation, Work Practices, and Control Technologies  
[326 IAC 6-3-2(d)]

- D.2.5 Hazardous Air Pollutants (HAPs) Limits [326 IAC 2-4.1-1]
- D.2.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.2.7 Volatile Organic Compounds (VOCs)

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]**

- D.2.8 Operator-Training Program

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- D.2.9 Record Keeping Requirement
- D.2.10 Reporting Requirement

D.3. EMISSIONS UNIT OPERATION CONDITIONS ..... 35

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.3.1 Particulate Emission Limitation for Manufacturing Processes [326 IAC 6-3-2]

**Compliance Determination Requirements**

- D.3.2 Particulate Matter (PM)

D.4. EMISSIONS UNIT OPERATION CONDITIONS ..... 36

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.4.1 Particulate Emission Limitation for Manufacturing Processes [326 IAC 6-3-2]

**Compliance Determination Requirements**

- D.4.2 Particulate Matter (PM)

E.1. EMISSIONS UNIT OPERATION CONDITIONS ..... 37

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- E.1.1 General Provisions Relating to National Emission Standards for Hazardous Air Pollutants Under 40 CFR part 63 [326 IAC 20-1][40 CFR Part 63, Subpart A]
- E.1.2 Miscellaneous Metal Part and Products Surface Coating requirements [40 CFR Part 63, Subpart M]

Certification ..... 40  
Emergency Occurrence Report ..... 41  
Quarterly Report.....43-48  
Quarterly Deviation and Compliance Monitoring Report ..... 49

## SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]

---

The Permittee owns and operates a stationary burial casket manufacturing operation.

Source Address:	(1) 1000 East Pearl Street, Batesville, Indiana 47006
	(2) Options Plant 705 East Pearl Street, Batesville, IN 47006
	(3) Stamping Plant 100 Eastern Avenue, Batesville, IN 47006
Mailing Address:	1000 East Pearl Street, Batesville, IN 47006
General Source Phone Number:	812-934-8297
SIC Code:	3995
County Location:	Ripley
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Part 70 Operating Permit Program Major Source, under PSD Rules Major Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

### A.2 Part 70 Source Definition [326 IAC 2-7-1(22)]

---

This metal caskets manufacturing source consists of three (3) plants:

- (1) Plant #1 (Assembly Plant) is located at 1000 East Pearl Street, Batesville, Indiana 47006.
- (2) Plant #2 (Options Plant) is located at 705 East Pearl Street, Batesville, Indiana 47006.
- (3) Plant #3 (Stamping Plant) is located at 100 Eastern Avenue, Batesville, Indiana 47006.

IDEM has determined that Plants #2 and #3 are located contiguous to each other and Plant #1 is located adjacent (nearby, within 0.5 miles distance). The three (3) plants are owned and operated by one (1) company, have the same SIC codes, and more than 50% of the products in Plant #2 are shipped to Plant #1. Therefore, the term "source" in the Part 70 documents refers to the three (3) plants as one (1) source.

### A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)][326 IAC 2-7-5(15)]

---

This stationary source consists of the following emission units and pollution control devices:  
Plant #1 (Assembly Plant, commenced operation in late 1950's):

- (a) One (1) electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat), constructed in 1981, capable of processing approximately 50 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 14-EF-40;

- (b) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-5455 (Topcoat/Shade), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-54 and 21-EF-55;
- (c) One (1) electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 21-EF-57;
- (d) One (1) high volume low pressure (HVLP)/air atomization/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through three (3) stacks identified as 21-EF-5, 21-EF-6 and 21-EF-52;
- (e) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-2324 (Color), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-23 and 21-EF-24;
- (f) Two (2) air atomization spray booths, identified as B-60-33 (Ear) and B-60-35 (Corner) respectively, constructed in the 1960s, each using dry filters for overspray control, and each exhausting through one (1) stack identified as 60-EF-33 and 60-EF-35 respectively;
- (g) Two (2) air atomization/electrostatic disk spray booths, identified as B-60-20 (E-Room) and B-60-21 (E-Room), respectively, constructed in 1972, each using dry filters for overspray control, and each exhausting through four (4) stacks identified as 60-EF-20/60-EF-20A and 60-EF-21/60-EF-21A, respectively;
- (h) Two (2) air atomization/electrostatic spray booths, identified as B-61P-5 (Copper Line) and B-61P-11 (Copper Line), respectively, constructed in early 1972, each using waterwash for overspray control, and each exhausting through one (1) stack identified as 61P-EF-5 and 61P-EF-11, respectively;
- (i) One (1) brush sander, with a process weight rate of 2.66 tons per hour, equipped with a jet pulse baghouse, exhausting through one (1) stack inside the building, identified as S2;

Plant #2 (Options Plant):

- (j) One (1) metal urn surface coating line capable of coating approximately 36 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-M-1 and P-M-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-M-1;
- (k) One (1) wood urn surface coating line capable of coating approximately 32 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-W-1 and P-W-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-W-1; and

Plant #3 (Stamping Plant, commenced operation in the early 1950s):

- (l) Miscellaneous clean-up solvents usage throughout the plant.

A.4 Specifically Regulated Insignificant Activities  
326 IAC 2-7-1(21)][326 IAC 2-7-4(c)][326 IAC 2-7-5(15)]

---

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment;
- (b) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 cubic feet per minute, including the following; deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations;
- (c) Woodworking operations woodworking operations in Options Plant controlled by baghouse BW-1 and exhausting inside the building.

A.5 Part 70 Permit Applicability [326 IAC 2-7-2]

---

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

## SECTION B GENERAL CONDITIONS

### B.1 Definitions [326 IAC 2-7-1]

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

### B.2 Permit Term [326 IAC 2-7-5(2)][326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)][IC 13-15-3-6(a)]

---

- (a) This permit, T137-24390-00016, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit or of permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control).
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

### B.3 Term of Conditions [326 IAC 2-1.1-9.5]

---

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

### B.4 Enforceability [326 IAC 2-7-7]

---

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

### B.5 Severability [326 IAC 2-7-5(5)]

---

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

---

This permit does not convey any property rights of any sort or any exclusive privilege.

### B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

---

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by the "responsible official" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form or its equivalent, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) A "responsible official" is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
  - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)][326 IAC 1-6-3]

---

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality,  
Compliance Section), or  
Telephone Number: 317-233-0178 (ask for Compliance Section)

Facsimile Number: 317-233-6865

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
  - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
  - (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
  - (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
  - (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
  - (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

**B.12 Permit Shield [326 IAC 2-7-15][326 IAC 2-7-20][326 IAC 2-7-12]**

---

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
- (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
  - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
  - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
  - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

**B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]**

---

- (a) All terms and conditions of permits established prior to T137-24390-00016 and issued pursuant to permitting programs approved into the state implementation plan have been either:
- (1) incorporated as originally stated,
  - (2) revised under 326 IAC 2-7-10.5, or
  - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit, except for permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control)

**B.14 Termination of Right to Operate [326 IAC 2-7-10][326 IAC 2-7-4(a)]**

---

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

**B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]**

---

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

**B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)][326 IAC 2-7-8(a)][326 IAC 2-7-9]**

---

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:

- (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4][326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
- (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
  - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.18 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12] [40 CFR 72]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

(b) Pursuant to 326 IAC 2-7-11(b) and 326 IAC 2-7-12(a), administrative Part 70 operating permit amendments and permit modifications for purposes of the acid rain portion of a Part 70 permit shall be governed by regulations promulgated under Title IV of the Clean Air Act. [40 CFR 72]

(c) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

(d) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.19 Permit Revision Under Economic Incentives and Other Programs  
[326 IAC 2-7-5(8)][326 IAC 2-7-12(b)(2)]

---

(a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.

(b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20][326 IAC 2-7-10.5]

---

(a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b),(c), or (e) without a prior permit revision, if each of the following conditions is met:

(1) The changes are not modifications under any provision of Title I of the Clean Air Act;

(2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;

(3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

(4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue

MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b),(c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]  
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.
- (f) This condition does not apply to emission trades of SO<sub>2</sub> or NO<sub>x</sub> under 326 IAC 21 or 326 IAC 10-4.

**B.21 Source Modification Requirement [326 IAC 2-7-10.5]**

---

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

**B.22 Inspection and Entry [326 IAC 2-7-6][IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]**

---

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

**B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]**

---

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

## SECTION C SOURCE OPERATION CONDITIONS

Entire Source

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]
- 
- Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.
- C.2 Opacity [326 IAC 5-1]
- 
- Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:
- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
  - (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- 
- The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- 
- The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- 
- The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.
- C.6 Stack Height [326 IAC 1-7]
- 
- The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted by using ambient air quality modeling pursuant to 326 IAC 1-7-4. The provisions of 326 IAC 1-7-1(3), 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4, and 326 IAC 1-7-5(a), (b), and (d) are not federally enforceable.
- C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]
- 
- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least

thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:
    - (A) Asbestos removal or demolition start date;
    - (B) Removal or demolition contractor; or
    - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-52 IGCN 1003  
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**  
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Licensed Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to

thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Licensed Asbestos inspector is not federally enforceable.

### **Testing Requirements [326 IAC 2-7-6(1)]**

#### **C.8 Performance Testing [326 IAC 3-6]**

---

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

### **Compliance Requirements [326 IAC 2-1.1-11]**

#### **C.9 Compliance Requirements [326 IAC 2-1.1-11]**

---

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

### **Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]**

#### **C.10 Compliance Monitoring [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]**

---

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003

Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

**C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

---

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

**C.12 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

---

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

**Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]**

**C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

---

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on.
- (b) Upon direct notification by IDEM, OAQ that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

**C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]**

---

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

**C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]**

---

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:

- (1) initial inspection and evaluation;
  - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
  - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
- (1) monitoring results;
  - (2) review of operation and maintenance procedures and records; and/or
  - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
- (1) monitoring data;
  - (2) monitor performance data, if applicable; and
  - (3) corrective actions taken.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5][326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

## Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

### C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]

---

- (a) Pursuant to 326 IAC 2-6-3(a)(1), the Permittee shall submit by July 1 of each year an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:
- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
  - (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management  
Technical Support and Modeling Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-50 IGCN 1003  
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

### C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2]

---

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.
- (c) If there is a reasonable possibility (as defined in 40 CFR 51.165 (a)(6)(vi)(A), 40 CFR 51.165 (a)(6)(vi)(B), 40 CFR 51.166 (r)(6)(vi)(a), and/or 40 CFR 51.166 (r)(6)(vi)(b)) that a "project" (as defined in 326 IAC 2-2-1(qq) and 326 IAC 2-3-1(II)) at an existing emissions unit, other than projects at a source with a Plantwide Applicability Limitation (PAL), which is not part of a "major modification" (as defined in 326 IAC 2-2-1(ee) and 326 IAC 2-3-1(z)) and the Permittee elects to utilize the "projected actual emissions" (as defined in 326 IAC 2-2-1(rr) and 326 IAC 2-3-1(mm)), the Permittee shall comply with following:

- (1) Before beginning actual construction of the "project" (as defined in 326 IAC 2-2-1 (qq)) and/or 326 IAC 2-3-1 (ll) at an existing emissions unit, document and maintain the following records:
  - (A) A description of the project.
  - (B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.
  - (C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:
    - (i) Baseline actual emissions;
    - (ii) Projected actual emissions;
    - (iii) Amount of emissions excluded under section 326 IAC 2-2-1(rr)(2)(A)(iii) and/or 326 IAC 2-3-1(mm)(2)(A)(3); and
    - (iv) An explanation for why the amount was excluded, and any netting calculations, if applicable.
- (d) If there is a reasonable possibility (as defined in 40 CFR 51.165 (a)(6)(vi)(A) and/or 40 CFR 51.166 (r)(6)(vi)(a)) that a "project" (as defined in 326 IAC 2-2-1(qq) and/or 326 IAC 2-3-1(ll)) at an existing emissions unit, other than projects at a source with a Plantwide Applicability Limitation (PAL), which is not part of a "major modification" (as defined in 326 IAC 2-2-1(ee) and/or 326 IAC 2-3-1(z)) may result in significant emissions increase and the Permittee elects to utilize the "projected actual emissions" (as defined in 326 IAC 2-2-1(rr) and/or 326 IAC 2-3-1(mm)), the Permittee shall comply with following:
  - (1) Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and
  - (2) Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR pollutant at the emissions unit.

C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.
- (f) If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any "project" (as defined in 326 IAC 2-2-1 (qq)) and/or 326 IAC 2-3-1 (ll) at an existing emissions unit, and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:
  - (1) The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as defined in 326 IAC 2-2-1 (xx)) and/or 326 IAC 2-3-1 (qq), for that regulated NSR pollutant, and
  - (2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).

The report for project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:

- (1) The name, address, and telephone number of the major stationary source.
- (2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.
- (3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-2-2(d)(3) and/or 326 IAC 2-3-2(c)(3).
- (4) Any other information that the Permittee deems fit to include in this report,

Reports required in this part shall be submitted to:

Indiana Department of Environmental Management  
Air Compliance Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (g) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ.
- (h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.

### **Stratospheric Ozone Protection**

#### **C.20 Compliance with 40 CFR 82 and 326 IAC 22-1**

---

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

## SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

### Emissions Unit Description:

- (a) One (1) electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat), constructed in 1981, capable of processing approximately 50 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 14-EF-40;
- (b) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-5455 (Topcoat/Shade), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-54 and 21-EF-55;
- (c) One (1) electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 21-EF-57;
- (d) One (1) high volume low pressure (HVLP)/air atomization/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through three (3) stacks identified as 21-EF-5, 21-EF-6 and 21-EF-52;
- (e) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-2324 (Color), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-23 and 21-EF-24;
- (f) Two (2) air atomization spray booths, identified as B-60-33 (Ear) and B-60-35 (Corner) respectively, constructed in the 1960s, each using dry filters for overspray control, and each exhausting through one (1) stack identified as 60-EF-33 and 60-EF-35 respectively;
- (g) Two (2) air atomization/electrostatic disk spray booths, identified as B-60-20 (E-Room) and B-60-21 (E-Room), respectively, constructed in 1972, each using dry filters for overspray control, and each exhausting through four (4) stacks identified as 60-EF-20/60-EF-20A and 60-EF-21/60-EF-21A, respectively;
- (h) Two (2) air atomization/electrostatic spray booths, identified as B-61P-5 (Copper Line) and B-61P-11 (Copper Line), respectively, constructed in early 1972, each using waterwash for overspray control, and each exhausting through one (1) stack identified as 61P-EF-5 and 61P-EF-11, respectively;

Plant #3 (Stamping Plant, commenced operation in the early 1950s):

- (i) Miscellaneous clean-up solvents usage throughout the plant.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.1.1 PSD Minor Limits [326 IAC 2-2]

- (a) Pursuant to CP 137-2381-00004, issued on June 25, 1992, the use of VOC solvents at the booth, identified as B-21-5652 (Prime) in Plant #1 shall not exceed 96 tons per twelve (12) consecutive month period with compliance determined at the end of each month. This limit effectively restricts the net contemporaneous VOC emission increase from the booth to

less than 40 tons per year. Compliance with the above limit will render 326 IAC 2-2 (PSD) not applicable to 1992 modification.

- (b) Pursuant to CP 137-2866-00004, issued on May 26, 1993, the VOC input to the spray booth, identified as B-21-57 (Topcoat 2) shall be limited to less than 88.3 tons per twelve (12) consecutive month period with compliance determined at the end of each month. This limit effectively restricts the net contemporaneous VOC emission increase from the booth to less than 40 tons per year. Compliance with the above limit will render 326 IAC 2-2 (PSD) not applicable to the 1993 modification.

#### D.1.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]

The usage of VOC in the surface coating booths shall be limited as follows:

- (a) Pursuant to MSM 137-14731-00016, issued on October 9, 2001, the VOC emissions from the electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat) shall be limited to less than 25 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with this limit will limit the VOC emissions to less than 25 tons per year and render the requirements of 326 IAC 8-1-6 not applicable to the electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat).

- (b) Pursuant to 326 IAC 8-1-6 and CP137-2381-00004, issued on June 25, 1992, the HVLP/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992 shall be using coating materials with VOC contents, as applied to the casket, not exceeding 4.6 pounds per gallon less water, expressed as a daily volume-weighted average.

This daily volume weighted average shall be determined by the following equation:

$$A = \frac{\sum [(Dc \times Wo \times G) / (1 - Vw \times (Dc/Dw))]}{\sum G}$$

Where:

A is the daily volume weighted average in pounds VOC per gallon less water as applied;

Wo is the VOC content of the coating in weight % organic;

G is the gallon of material (gal/unit);

Vw is the volume % of water in coating;

Dc is the density of coating (lb/gal); and

Dw is the density of water (lb/gal).

- (c) Pursuant to 326 IAC 8-1-6 and CP137-2866-00004, issued on May 26, 1993, the electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993 shall be:
- (1) Using the coating materials with VOC content, as applied to the caskets not exceeding 4.7 pounds per gallon less water. When using coating that exceed 4.7 pounds of VOC per gallon coating, less water, compliance with the limit shall be expressed as a daily volume weighted average;
  - (2) Using electrostatic rotary atomizer spray equipment.

**D.1.3 Particulate Emission Limitation, Work Practices, and Control Technologies [326 IAC 6-3-2(d)]**

---

Pursuant to 326 IAC 6-3-2(d), the particulate matter (PM) from the spray booths, identified as B-60-33 (Ear), B-60-35 (Corner), B-60-20 (E-Room), B-60-21 (E-Room), B-14-40 (Brush Seal Coat), B-21-5455 (Topcoat/Shade), B-21-57 (Topcoat 2), B-21-5652 (Prime), B-21-2324 (Color), B-61P-5 (Copper Line) and B-61P-11(Copper Line) shall be controlled by dry filter or water wash curtain and the Permittee shall operate the filters and water wash curtain in accordance with manufacturer's specifications.

**D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]**

---

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control devices.

**Compliance Determination Requirements**

**D.1.5 Volatile Organic Compounds (VOCs)**

---

Compliance with the VOC limitations contained in Conditions D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]**

**D.1.6 Operator-Training Program**

---

Batesville Manufacturing shall implement an operator-training program

- (a) All operators that perform paint spray operations or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained annually. All new operators shall be trained upon hiring or transfer.
- (b) Training shall include proper waterwash flow pattern and flow rate, filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators, and training records shall be maintained on site or available within one hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

**D.1.7 Record Keeping Requirement**

---

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken daily and shall be complete and sufficient to establish compliance with the VOC content and usage limits, and the VOC emission limits established in Conditions D.1.1 and D.1.2.
  - (1) The amount of VOC in each coating material and solvent used.
  - (2) The amount of coating material and solvent less water used in booths B-21-5652 (Prime) and B-21-57 (Topcoat 2) on a daily basis.

- (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
- (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
- (3) The volume weighted VOC content of the coating in booths B-21-5652 (Prime) and B-21-57 (Topcoat 2) used for each day;
- (4) The cleanup solvent usage for each month; and
- (5) The total VOC usage for each month.
- (b) To document compliance with Condition D.1.6, the Permittee shall maintain a copy of the operator-training program, training records, and the inspections required by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.1.8 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.1.1(a), (b) and D.1.2(a) shall be submitted to the address listed in Section C – General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

## SECTION D.2 EMISSIONS UNIT OPERATION CONDITIONS

### Emissions Unit Description:

Plant #2 (Options Plant):

- (j) One (1) metal urn surface coating line capable of coating approximately 36 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-M-1 and P-M-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-M-1; and
- (k) One (1) wood urn surface coating line capable of coating approximately 32 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-W-1 and P-W-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-W-1.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.2.1 PSD Minor Limit [326 IAC 2-2]

Pursuant to CP 137-10452-00016, issued on April 29, 1999, the wood urn surface coating line and metal urn surface coating line shall use less than 40 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve (12) consecutive month period, with compliance determined at the end of each month period.

Compliance with the above limit will limit the VOC emissions from the wood urn surface coating line and metal urn surface coating line to less than 40 tons per year and render 326 IAC 2-2 (PSD) not applicable to 1999 modification.

#### D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]

Pursuant to CP 137-10452-00016, issued on April 29, 1999, the metal urn surface coating line shall use less than 25 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve (12) consecutive month period, with compliance determined at the end of each month.

Compliance with the above limits will limit the VOC emissions from the metal urn surface coating line to less than 25 tons per year and render 326 IAC 8-1-6 not applicable to the metal urn surface coating line.

#### D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]

Pursuant to 326 IAC 8-2-12 (Wood Furniture and Cabinet Coating), the wood urn surface coating line, identified as P-W-1 and P-W-2 shall utilize one of the following application methods:

- (1) Airless Spray Application
- (2) Air Assisted Airless Spray Application
- (3) Electrostatic Spray Application
- (4) Electrostatic Bell or Disc Application
- (5) Heated Airless Spray Application
- (6) Roller Coating
- (7) Brush or Wipe Application
- (8) Dip-and-Drain Application

High Volume Low Pressure (HVLP) Spray Application is an accepted alternative method of application

for Air Assisted Airless Spray Application. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

**D.2.4 Particulate Emission Limitation, Work Practices, and Control Technologies [326 IAC 6-3-2(d)]**

---

Pursuant to 326 IAC 6-3-2(d), the particulate matter (PM) from the two (2) spray booths, identified as P-M-1, P-M-2, P-W-1 and P-W-2 Shall be controlled by dry filters and the Permittee shall operate the filters in accordance with manufacturer's specifications.

**D.2.5 Hazardous Air Pollutants (HAPs) Limits [326 IAC 2-4.1-1]**

---

Pursuant to CP137-10452-00016, issued on April 29, 1999, the wood urn surface coating line shall use less than 10 tons of any single HAP and less than 25 tons of total HAPs, per twelve (12) consecutive month period, with compliance determined at the end of each month.

Compliance with these limits will limit the single HAP and total HAPs of the wood urn surface coating line to less than 10 and 25 tons per year, respectively and will render the requirements of 326 IAC 2-4.1-1 not applicable to this emission unit.

**D.2.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]**

---

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control devices.

**Compliance Determination Requirements**

**D.2.7 Volatile Organic Compounds (VOCs)**

---

Compliance with the VOC limitations contained in Conditions D.2.1 and D.2.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]**

**D.2.8 Operator-Training Program**

---

Batesville Manufacturing shall implement an operator-training program.

- (a) All operators that perform paint spray operations or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained annually. All new operators shall be trained upon hiring or transfer.
- (b) Training shall include filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators, and training records shall be maintained on site or available within one hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

## **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

### **D.2.9 Record Keeping Requirement**

---

- (a) To document compliance with Conditions D.2.1, D.2.2 and D.2.5, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC and HAPs content and usage limits, and the VOC and HAPs emission limits established in Conditions D.2.1 and D.2.2.
- (1) The amount of VOC and HAPs in each coating material and solvent used.
  - (2) The amount of coating material and solvent less water used on a monthly basis.
    - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
    - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
  - (3) The cleanup solvent usage for each month; and
  - (4) The total VOC and HAPs usage for each month.
- (b) To document compliance with Condition D.2.7, the Permittee shall maintain a copy of the operator-training program, training records, and the inspections required by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

### **D.2.10 Reporting Requirements**

---

A quarterly summary of the information to document compliance with Conditions D.2.1, D.2.2 and D.2.5 shall be submitted to the address listed in Section C – General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

## SECTION D.3 EMISSIONS UNIT OPERATION CONDITIONS

### Emissions Unit Description:

- (i) One (1) brush sander, with a process weight rate of 2.66 tons per hour, equipped with a jet pulse baghouse, exhausting through one (1) stack inside the building, identified as S2;

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.3.1 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2, (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate matter (PM) emission rate from the brush sander shall not exceed 7.90 pounds per hour when operating at a process weight rate of less than 2.66 tons per hour.

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and  
P = process weight rate in tons per hour

### Compliance Determination Requirements

#### D.3.2 Particulate Matter (PM)

The baghouse for PM control shall be in operation and control emissions from the brush sander at all times that the brush sander is in operation.

## SECTION D.4 EMISSIONS UNIT OPERATION CONDITIONS

### Emissions Unit Description:

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment;
- (b) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 cubic feet per minute, including the following; deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations;
- (c) Woodworking operations woodworking operations in Options Plant controlled by baghouse BW-1 and exhausting inside the building.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.4.1 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2, the particulate emissions from the insignificant activities, wood working brazing equipment, cutting torches, soldering equipment and welding equipment and grinding and machining operation shall be limited by the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

Where:

E = rate of emission in pounds per hour and  
P = process weight rate in tons per hour

### Compliance Determination Requirements

#### D.4.2 Particulate Matter (PM)

The baghouse for PM control shall be in operation and control emissions from the wood working at all times that the wood working is in operation.

## SECTION E.1 EMISSIONS UNIT OPERATION CONDITIONS

### Emissions Unit Description:

- (a) One (1) electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat), constructed in 1981, capable of processing approximately 50 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 14-EF-40;
- (b) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-5455 (Topcoat/Shade), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-54 and 21-EF-55;
- (c) One (1) electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 21-EF-57;
- (d) One (1) high volume low pressure (HVLP)/air atomization/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through three (3) stacks identified as 21-EF-5, 21-EF-6 and 21-EF-52;
- (e) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-2324 (Color), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-23 and 21-EF-24;
- (f) Two (2) air atomization spray booths, identified as B-60-33 (Ear) and B-60-35 (Corner) respectively, constructed in the 1960s, each using dry filters for overspray control, and each exhausting through one (1) stack identified as 60-EF-33 and 60-EF-35 respectively;
- (g) Two (2) air atomization/electrostatic disk spray booths, identified as B-60-20 (E-Room) and B-60-21 (E-Room), respectively, constructed in 1972, each using dry filters for overspray control, and each exhausting through four (4) stacks identified as 60-EF-20/60-EF-20A and 60-EF-21/60-EF-21A, respectively;
- (h) Two (2) air atomization/electrostatic spray booths, identified as B-61P-5 (Copper Line) and B-61P-11 (Copper Line), respectively, constructed in early 1972, each using waterwash for overspray control, and each exhausting through one (1) stack identified as 61P-EF-5 and 61P-EF-11, respectively;
- (i) One (1) brush sander, with a process weight rate of 2.66 tons per hour, equipped with a jet pulse baghouse, exhausting through one (1) stack inside the building, identified as S2;

### Plant #2 (Options Plant):

- (j) One (1) metal urn surface coating line capable of coating approximately 36 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-M-1 and P-M-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-M-1;

Plant #3 (Stamping Plant, commenced operation in the early 1950s):

- (k) Miscellaneous clean-up solvents usage throughout the plant.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

### **National Emission Standards for Hazardous Air Pollutants Requirements [326 IAC 2-7-5(1)]**

#### **E.1.1 General Provisions Relating to NESHAP Subpart M MMM (National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products [326 IAC 20-1] [40 CFR Part 63, Subpart A])**

- (a) Pursuant to 40 CFR 63.3901, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1 as specified in Table 2 of 40 CFR Part 63, Subpart M MMM in accordance with schedule in 40 CFR 63 Subpart M MMM.
- (b) Pursuant to 40 CFR 63.10, the Permittee shall submit all required notifications and reports to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

And

Director  
U.S. EPA Region V  
Air and Radiation Division  
Chicago, IL 60604-3507

#### **E.1.2 NESHAP Subpart M MMM Requirements [40 CFR 63, Subpart M MMM]**

Pursuant to 40 CFR 63, Subpart M MMM, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart M MMM (included as Attachment A), which was incorporated by reference as 326 IAC 20-1-1, for the entire affected source (consisting of all of the spray booths, identified as B-14-40 (Brush Seal Coat), B-21-5455 (Topcoat/Shade), B-21-57 (Topcoat 2), B-21-5652 (Prime), B-21-2324 (Color), B-61P-5 (Copper Line), B-61P-11 (Copper Line), B-60-33 (Ear), B-60-35 (Corner), B-60-20 (E-Room), B-60-21(E-Room), P-M-1, P-M-2 and associated solvent cleaning and coating mixing operations) beginning January 2, 2007, as follows:

The existing affected source associated with the surface coating of metal parts and products is subject to the following sections of 40 CFR Part 63, Subpart M MMM.

- 40 CFR 63.3880
- 40 CFR 63.3881(a)(1-3), (b)
- 40 CFR 63.3882
- 40 CFR 63.3883, (b), (d)
- 40 CFR 63.3890(b)(1-2), (c)
- 40 CFR 63.3891, (a)(b)

40 CFR 63.3892(a)  
40 CFR 63.3893(a)  
40 CFR 63.3900(a)(1), (b)  
40 CFR 63.3901  
40 CFR 63.3910(a), (b), (c)(1-7), (c)(8)(i), (c)(10-11)  
40 CFR 63.3920(a)(1-2), (a)(3)(i-iv, vi-vii), (a)(4-5)  
40 CFR 63.3930, (a-b), (c)(1-2), (d-g), (h-j)  
40 CFR 63.3931  
40 CFR 63.3940  
40 CFR 63.3941  
40 CFR 63.3942  
40 CFR 63.3950  
40 CFR 63.3951  
40 CFR 63.3952  
40 CFR 63.3980  
40 CFR 63.3981  
Applicable portions of Tables 1, 2, 3, and 4 of 40 CFR 63, Subpart MMMM

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
PART 70 OPERATING PERMIT  
CERTIFICATION**

Source Name: Batesville, Manufacturing, Inc  
Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
(2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
(3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
Part 70 Permit No.: T137-24390-00016

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Affidavit (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE BRANCH  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251  
Phone: 317-233-0178  
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT  
EMERGENCY OCCURRENCE REPORT**

Source Name: Batesville, Manufacturing, Inc  
Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
(2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
(3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
Part 70 Permit No.: T137-24390-00016

**This form consists of 2 pages**

**Page 1 of 2**

- This is an emergency as defined in 326 IAC 2-7-1(12)
- The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and
  - The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency?    Y    N
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

A certification is not required for this report.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

### Part 70 Quarterly Report

Source Name: Batesville, Manufacturing, Inc  
Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
(2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
(3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
Part 70 Permit No.: T137-24390-00016  
Facility: Booth B-21-5652 (Prime) in Plant #1  
Parameter: VOC  
Limit: Use of VOC solvent limited to less than 96 tons per twelve (12) consecutive month period

QUARTER :

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
Deviation has been reported on:

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

## Part 70 Quarterly Report

Source Name: Batesville, Manufacturing, Inc  
Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
(2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
(3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
Part 70 Permit No.: T137-24390-00016  
Facility: Spry Booth B-21-57 (Topcoat 2) in Plant #1  
Parameter: VOC  
Limit: VOC usage less than 88.3 tons per twelve (12) consecutive month period

QUARTER :

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
Deviation has been reported on:

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**Part 70 Quarterly Report**

Source Name: Batesville, Manufacturing, Inc  
Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
(2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
(3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
Part 70 Permit No.: T137-24390-00016  
Facility: Spray booth B-14-40 (Brush Seal Coat)  
Parameter: VOC  
Limit: Less than 25 tons per twelve (12) consecutive month period

QUARTER :

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
Deviation has been reported on:

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**Part 70 Quarterly Report**

Source Name: Batesville, Manufacturing, Inc  
Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
(2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
(3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
Part 70 Permit No.: T137-24390-00016  
Facility: Metal and Wood urn surface coating line in Plant #2  
Parameter: VOC  
Limit: Less than 40 tons per twelve (12) consecutive month period

QUARTER :

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
Deviation has been reported on:

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

### Part 70 Quarterly Report

Source Name: Batesville, Manufacturing, Inc  
 Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
 (2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
 (3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
 Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
 Part 70 Permit No.: T137-24390-00016  
 Facility: Metal urn surface coating line in Plant #2  
 Parameter: VOC  
 Limit: Less than 25 tons per twelve (12) consecutive month period

QUARTER :

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
 Deviation has been reported on:

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

### Part 70 Quarterly Report

Source Name: Batesville, Manufacturing, Inc  
 Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
 (2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
 (3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
 Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
 Part 70 Permit No.: T137-24390-00016  
 Facility: Wood urn surface coating line in Plant #2  
 Parameter: HAPs  
 Limit: Less than 10 tons for any single HAP and less than 25 tons for total HAPs per twelve consecutive month period.

YEAR: \_\_\_\_\_

Month	Column 1		Column 2		Column 1 + Column 2	
	This Month		Previous 11 Months		12 Month Total	
Month 1	Single HAP (tons)	Total HAPs (tons)	Single HAP (tons)	Total HAPs (tons)	Single HAP (tons)	Total HAPs (tons)
Month 2						
Month 3						

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.  
 Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 COMPLIANCE DATA SECTION  
 PART 70 OPERATING PERMIT  
 QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Batesville, Manufacturing, Inc  
 Source Address: (1) Assembly Plant - 1000 East Pearl Street, Batesville, IN 47006  
 (2) Options Plant - 705 East Pearl Street, Batesville, IN 47006  
 (3) Stamping Plant- 100 Eastern Avenue, Batesville, IN 47006  
 Mailing Address: 1000 East Pearl Street, Batesville, IN 47006  
 Part 70 Permit No.: T137-24390-00016

**Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_**

This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
<b>Permit Requirement (specify permit condition #)</b>	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement (specify permit condition #)</b>	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

<b>Permit Requirement (specify permit condition #)</b>	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement (specify permit condition #)</b>	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement (specify permit condition #)</b>	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**Attachment A**  
**to a Part 70 Operating Permit Renewal**

**40 CFR 63, Subpart MMMM—National Emission Standards for Hazardous  
Air Pollutants for Surface Coating of Miscellaneous Metal Parts and  
Products**

Source Name:	Batesville Manufacturing, Inc
Source Location:	(1) Assembly Plant 1000 East Pearl Street, Batesville, IN 47006
	(2) Options Plant 705 East Pearl Street, Batesville, IN 47006
	(3) Stamping Plant 100 Eastern Avenue, Batesville, IN 47006
County:	Ripley
SIC Code:	3995
Title V Operating Permit Renewal No.:	137-24390-00016
Permit Reviewer:	Josiah Balogun

**§ 63.3880 What is the purpose of this subpart?**

This subpart establishes national emission standards for hazardous air pollutants (NESHAP) for miscellaneous metal parts and products surface coating facilities. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations.

**§ 63.3881 Am I subject to this subpart?**

(a) Miscellaneous metal parts and products include, but are not limited to, metal components of the following types of products as well as the products themselves: motor vehicle parts and accessories, bicycles and sporting goods, recreational vehicles, extruded aluminum structural components, railroad cars, heavy duty trucks, medical equipment, lawn and garden equipment, electronic equipment, magnet wire, steel drums, industrial machinery, metal pipes, and numerous other industrial, household, and consumer products. Except as provided in paragraph (c) of this section, the source category to which this subpart applies is the surface coating of any miscellaneous metal parts or products, as described in paragraph (a)(1) of this section, and it includes the subcategories listed in paragraphs (a)(2) through (6) of this section.

(1) Surface coating is the application of coating to a substrate using, for example, spray guns or dip tanks. When application of coating to a substrate occurs, then surface coating also includes associated activities, such as surface preparation, cleaning, mixing, and storage. However, these activities do not comprise surface coating if they are not directly related to the application of the coating. Coating application with handheld, non-refillable aerosol containers, touch-up markers, marking pens, or the application of paper film or plastic film which may be pre-coated with an adhesive by the manufacturer are not coating operations for the purposes of this subpart.

(2) The general use coating subcategory includes all surface coating operations that are not high performance, magnet wire, rubber-to-metal, or extreme performance fluoropolymer coating operations.

(3) The high performance coating subcategory includes surface coating operations that are performed using coatings that meet the definition of high performance architectural coating or high temperature coating in §63.3981.

(4) The magnet wire coating subcategory includes surface coating operations that are performed using coatings that meet the definition of magnet wire coatings in §63.3981.

(5) The rubber-to-metal coatings subcategory includes surface coating operations that are performed using coatings that meet the definition of rubber-to-metal coatings in §63.3981.

(6) The extreme performance fluoropolymer coatings subcategory includes surface coating operations that are performed using coatings that meet the definition of extreme performance fluoropolymer coatings in §63.3981.

(b) You are subject to this subpart if you own or operate a new, reconstructed, or existing affected source, as defined in §63.3882, that uses 946 liters (250 gallons (gal)) per year, or more, of coatings that contain hazardous air pollutants (HAP) in the surface coating of miscellaneous metal parts and products defined in paragraph (a) of this section; and that is a major source, is located at a major source, or is part of a major source of emissions of HAP. A major source of HAP emissions is any stationary source or group of stationary sources located within a contiguous area and under common control that emits or has the potential to emit any single HAP at a rate of 9.07 megagrams (Mg) (10 tons) or more per year or any combination of HAP at a rate of 22.68 Mg (25 tons) or more per year. You do not need to include coatings that meet the definition of non-HAP coating contained in §63.3981 in determining whether you use 946 liters (250 gal) per year, or more, of coatings in the surface coating of miscellaneous metal parts and products.

(c) This subpart does not apply to surface coating or a coating operation that meets any of the criteria of paragraphs (c)(1) through (17) of this section.

(1) A coating operation conducted at a facility where the facility uses only coatings, thinners and other additives, and cleaning materials that contain no organic HAP, as determined according to §63.3941(a).

(2) Surface coating operations that occur at research or laboratory facilities, or is part of janitorial, building, and facility maintenance operations, or that occur at hobby shops that are operated for noncommercial purposes.

(3) Coatings used in volumes of less than 189 liters (50 gal) per year, provided that the total volume of coatings exempt under this paragraph does not exceed 946 liters (250 gal) per year at the facility.

(4) The surface coating of metal parts and products performed on-site at installations owned or operated by the Armed Forces of the United States (including the Coast Guard and the National Guard of any such State) or the National Aeronautics and Space Administration, or the surface coating of military munitions manufactured by or for the Armed Forces of the United States (including the Coast Guard and the National Guard of any such State).

(5) Surface coating where plastic is extruded onto metal wire or cable or metal parts or products to form a coating.

(6) Surface coating of metal components of wood furniture that meet the applicability criteria for wood furniture manufacturing (subpart JJ of this part).

(7) Surface coating of metal components of large appliances that meet the applicability criteria for large appliance surface coating (subpart NNNN of this part).

(8) Surface coating of metal components of metal furniture that meet the applicability criteria for metal furniture surface coating (subpart RRRR of this part).

(9) Surface coating of metal components of wood building products that meet the applicability criteria for wood building products surface coating (subpart QQQQ of this part).

(10) Surface coating of metal components of aerospace vehicles that meet the applicability criteria for aerospace manufacturing and rework (40 CFR part 63, subpart GG).

(11) Surface coating of metal parts intended for use in an aerospace vehicle or component using specialty coatings as defined in appendix A to subpart GG of this part.

(12) Surface coating of metal components of ships that meet the applicability criteria for shipbuilding and ship repair (subpart II of this part).

(13) Surface coating of metal using a web coating process that meets the applicability criteria for paper and other web coating (subpart JJJJ of this part).

(14) Surface coating of metal using a coil coating process that meets the applicability criteria for metal coil coating (subpart SSSS of this part).

(15) Surface coating of boats or metal parts of boats (including, but not limited to, the use of assembly adhesives) where the facility meets the applicability criteria for boat manufacturing facilities (subpart VVVV of this part), except where the surface coating of the boat is a metal coating operation performed on personal watercraft or parts of personal watercraft. This subpart does apply to metal coating operations performed on personal watercraft and parts of personal watercraft.

(16) Surface coating of assembled on-road vehicles that meet the applicability criteria for the assembled on-road vehicle subcategory in plastic parts and products surface coating (40 CFR part 63, subpart PPPP).

(17) Surface coating of metal components of automobiles and light-duty trucks that meets the applicability criteria in §63.3082(b) for the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (40 CFR part 63, subpart IIII) at a facility that meets the applicability criteria in §63.3081(b).

(d) If your facility meets the applicability criteria in §63.3081(b) of the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (40 CFR part 63, subpart IIII), and you perform surface coating of metal parts or products that meets both the applicability criteria in §63.3082(c) and the applicability criteria of the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR part 63, subpart MMMM), then for the surface coating of any or all of your metal parts or products that meets the applicability criteria in §63.3082(c), you may choose to comply with the requirements of subpart IIII of this part in lieu of complying with the Surface Coating of Miscellaneous Metal Parts and Products NESHAP. Surface coating operations on metal parts or products (e.g., parts for motorcycles or lawnmowers) not intended for use in automobiles, light-duty trucks, or other motor vehicles as defined in §63.3176 cannot be made part of your affected source under subpart IIII of this part.

(e) If you own or operate an affected source that meets the applicability criteria of this subpart and at the same facility you also perform surface coating that meets the applicability criteria of any other final surface coating NESHAP in this part you may choose to comply as specified in paragraph (e)(1), (2), or (3) of this section.

(1) You may have each surface coating operation that meets the applicability criteria of a separate NESHAP comply with that NESHAP separately.

(2) You may comply with the emission limitation representing the predominant surface coating activity at your facility, as determined according to paragraphs (e)(2)(i) and (ii) of this section. However, you may not establish high performance, rubber-to-metal, or extreme performance fluoropolymer coating operations as the predominant activity. You must not consider any surface coating activity that is subject to the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (40 CFR part 63, subpart IIII) in determining the predominant surface coating activity at your facility.

(i) If a surface coating operation accounts for 90 percent or more of the surface coating activity at your facility (that is, the predominant activity), then compliance with the emission limitations of the predominant activity for all surface coating operations constitutes compliance with these and other applicable surface coating NESHAP. In determining predominant activity, you must include coating activities that meet the applicability criteria of other surface coating NESHAP and constitute more than 1 percent of total coating activities at your facility. Coating activities that meet the applicability criteria of other surface coating NESHAP but comprise less than 1 percent of coating activities need not be included in the determination of predominant activity but must be included in the compliance calculation.

(ii) You must use liters (gal) of solids used as a measure of relative surface coating activity over a representative period of operation. You may estimate the relative volume of coating solids used from parameters other than coating consumption and volume solids content ( e.g., design specifications for the parts or products coated and the number of items produced). The determination of predominant activity must accurately reflect current and projected coating operations and must be verifiable through appropriate documentation. The use of parameters other than coating consumption and volume solids content must be approved by the Administrator. You may use data for any reasonable time period of at least 1 year in determining the relative amount of coating activity, as long as they represent the way the source will continue to operate in the future and are approved by the Administrator. You must determine the predominant activity at your facility and submit the results of that determination with the initial notification required by §63.3910(b). You must also determine predominant activity annually and include the determination in the next semi-annual compliance report required by §63.3920(a).

(3) You may comply with a facility-specific emission limit calculated from the relative amount of coating activity that is subject to each emission limit. If you elect to comply using the facility-specific emission limit alternative, then compliance with the facility-specific emission limit and the emission limitations in this subpart for all surface coating operations constitutes compliance with this and other applicable surface coating NESHAP. The procedures for calculating the facility-specific emission limit are specified in §63.3890. In calculating a facility-specific emission limit, you must include coating activities that meet the applicability criteria of other surface coating NESHAP and constitute more than 1 percent of total coating activities at your facility. You must not consider any surface coating activity that is subject to the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (40 CFR part 63, subpart IIII) in determining a facility-specific emission limit for your facility. Coating activities that meet the applicability criteria of other surface coating NESHAP but comprise less than 1 percent of total coating activities need not be included in the calculation of the facility-specific emission limit but must be included in the compliance calculations.

[69 FR 157, Jan. 2, 2004, as amended at 69 FR 22660, Apr. 26, 2004; 71 FR 76927, Dec. 22, 2006]

### **§ 63.3882 What parts of my plant does this subpart cover?**

(a) This subpart applies to each new, reconstructed, and existing affected source within each of the four subcategories listed in §63.3881(a).

(b) The affected source is the collection of all of the items listed in paragraphs (b)(1) through (4) of this section that are used for surface coating of miscellaneous metal parts and products within each subcategory.

(1) All coating operations as defined in §63.3981;

- (2) All storage containers and mixing vessels in which coatings, thinners and/or other additives, and cleaning materials are stored or mixed;
  - (3) All manual and automated equipment and containers used for conveying coatings, thinners and/or other additives, and cleaning materials; and
  - (4) All storage containers and all manual and automated equipment and containers used for conveying waste materials generated by a coating operation.
- (c) An affected source is a new affected source if you commenced its construction after August 13, 2002 and the construction is of a completely new miscellaneous metal parts and products surface coating facility where previously no miscellaneous metal parts and products surface coating facility had existed.
- (d) An affected source is reconstructed if it meets the criteria as defined in §63.2.
- (e) An affected source is existing if it is not new or reconstructed.

**§ 63.3883 When do I have to comply with this subpart?**

The date by which you must comply with this subpart is called the compliance date. The compliance date for each type of affected source is specified in paragraphs (a) through (c) of this section. The compliance date begins the initial compliance period during which you conduct the initial compliance demonstration described in §§63.3940, 63.3950, and 63.3960.

(a) For a new or reconstructed affected source, the compliance date is the applicable date in paragraph (a)(1) or (2) of this section:

(1) If the initial startup of your new or reconstructed affected source is before January 2, 2004, the compliance date is January 2, 2004.

(2) If the initial startup of your new or reconstructed affected source occurs after January 2, 2004, the compliance date is the date of initial startup of your affected source.

(b) For an existing affected source, the compliance date is the date 3 years after January 2, 2004.

(c) For an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP emissions, the compliance date is specified in paragraphs (c)(1) and (2) of this section.

(1) For any portion of the source that becomes a new or reconstructed affected source subject to this subpart, the compliance date is the date of initial startup of the affected source or January 2, 2004, whichever is later.

(2) For any portion of the source that becomes an existing affected source subject to this subpart, the compliance date is the date 1 year after the area source becomes a major source or 3 years after January 2, 2004, whichever is later.

(d) You must meet the notification requirements in §63.3910 according to the dates specified in that section and in subpart A of this part. Some of the notifications must be submitted before the compliance dates described in paragraphs (a) through (c) of this section.

## Emission Limitations

### § 63.3890 What emission limits must I meet?

(a) For a new or reconstructed affected source, you must limit organic HAP emissions to the atmosphere from the affected source to the applicable limit specified in paragraphs (a)(1) through (5) of this section, except as specified in paragraph (c) of this section, determined according to the requirements in §63.3941, §63.3951, or §63.3961.

(1) For each new general use coating affected source, limit organic HAP emissions to no more than 0.23 kilograms (kg) (1.9 pound (lb)) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(2) For each new high performance coating affected source, limit organic HAP emissions to no more than 3.3 kg (27.5 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(3) For each new magnet wire coating affected source, limit organic HAP emissions to no more than 0.050 kg (0.44 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(4) For each new rubber-to-metal coating affected source, limit organic HAP emissions to no more than 0.81 kg (6.8 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(5) For each new extreme performance fluoropolymer coating affected source, limit organic HAP emissions to no more than 1.5 kg (12.4 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(b) For an existing affected source, you must limit organic HAP emissions to the atmosphere from the affected source to the applicable limit specified in paragraphs (b)(1) through (5) of this section, except as specified in paragraph (c) of this section, determined according to the requirements in §63.3941, §63.3951, or §63.3961.

(1) For each existing general use coating affected source, limit organic HAP emissions to no more than 0.31 kg (2.6 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(2) For each existing high performance coating affected source, limit organic HAP emissions to no more than 3.3 kg (27.5 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(3) For each existing magnet wire coating affected source, limit organic HAP emissions to no more than 0.12 kg (1.0 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(4) For each existing rubber-to-metal coating affected source, limit organic HAP emissions to no more than 4.5 kg (37.7 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(5) For each existing extreme performance fluoropolymer coating affected source, limit organic HAP emissions to no more than 1.5 kg (12.4 lbs) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

(c) If your facility's surface coating operations meet the applicability criteria of more than one of the subcategory emission limits specified in paragraphs (a) or (b) of this section, you may comply separately

with each subcategory emission limit or comply using one of the alternatives in paragraph (c)(1) or (2) of this section.

(1) If the general use or magnet wire surface coating operations subject to only one of the emission limits specified in paragraphs (a)(1), (3), (b)(1), or (3) of this section account for 90 percent or more of the surface coating activity at your facility ( *i.e.*, it is the predominant activity at your facility), then compliance with that one emission limitations in this subpart for all surface coating operations constitutes compliance with the other applicable emission limits. You must use liters (gal) of solids used as a measure of relative surface coating activity over a representative period of operation. You may estimate the relative volume of coating solids used from parameters other than coating consumption and volume solids content ( *e.g.*, design specifications for the parts or products coated and the number of items produced). The determination of predominant activity must accurately reflect current and projected coating operations and must be verifiable through appropriate documentation. The use of parameters other than coating consumption and volume solids content must be approved by the Administrator. You may use data for any reasonable time period of at least 1 year in determining the relative amount of coating activity, as long as they represent the way the source will continue to operate in the future and are approved by the Administrator. You must determine the predominant activity at your facility and submit the results of that determination with the initial notification required by §63.3910(b). Additionally, you must determine the facility's predominant activity annually and include the determination in the next semi-annual compliance report required by §63.3920(a).

(2) You may calculate and comply with a facility-specific emission limit as described in paragraphs (c)(2)(i) through (iii) of this section. If you elect to comply using the facility-specific emission limit alternative, then compliance with the facility-specific emission limit and the emission limitations in this subpart for all surface coating operations constitutes compliance with this and other applicable surface coating NESHAP. In calculating a facility-specific emission limit, you must include coating activities that meet the applicability criteria of the other subcategories and constitute more than 1 percent of total coating activities. Coating activities that meet the applicability criteria of other surface coating NESHAP but comprise less than 1 percent of coating activities need not be included in the determination of predominant activity but must be included in the compliance calculation.

(i) You are required to calculate the facility-specific emission limit for your facility when you submit the notification of compliance status required in §63.3910(c), and on a monthly basis afterward using the coating data for the relevant 12-month compliance period.

(ii) Use Equation 1 of this section to calculate the facility-specific emission limit for your surface coating operations for each 12-month compliance period.

$$\text{Facility-Specific Emission Limit} = \frac{\sum_{i=1}^n (\text{Limit}_i)(\text{Solids}_i)}{\sum_{i=1}^n (\text{Solids}_i)} \quad (\text{Eq. 1})$$

Where:

Facility-specific emission limit = Facility-specific emission limit for each 12-month compliance period, kg (lb) organic HAP per kg (lb) coating solids used.

Limit<sub>i</sub>= The new source or existing source emission limit applicable to coating operation, *i*, included in the facility-specific emission limit, converted to kg (lb) organic HAP per kg (lb) coating solids used, if the emission limit is not already in those units. All emission limits included in the facility-specific emission limit must be in the same units.

Solids<sub>i</sub>= The liters (gal) of solids used in coating operation, i, in the 12-month compliance period that is subject to emission limit, i. You may estimate the volume of coating solids used from parameters other than coating consumption and volume solids content ( e.g., design specifications for the parts or products coated and the number of items produced). The use of parameters other than coating consumption and volume solids content must be approved by the Administrator.

n = The number of different coating operations included in the facility-specific emission limit.

(iii) If you need to convert an emission limit in another surface coating NESHAP from kg (lb) organic HAP per kg (lb) coating solids used to kg (lb) organic HAP per liter (gal) coating solids used, you must use the default solids density of 1.26 kg solids per liter coating solids (10.5 lb solids per gal solids).

### **§ 63.3891 What are my options for meeting the emission limits?**

You must include all coatings (as defined in §63.3981), thinners and/or other additives, and cleaning materials used in the affected source when determining whether the organic HAP emission rate is equal to or less than the applicable emission limit in §63.3890. To make this determination, you must use at least one of the three compliance options listed in paragraphs (a) through (c) of this section. You may apply any of the compliance options to an individual coating operation, or to multiple coating operations as a group, or to the entire affected source. You may use different compliance options for different coating operations, or at different times on the same coating operation. You may employ different compliance options when different coatings are applied to the same part, or when the same coating is applied to different parts. However, you may not use different compliance options at the same time on the same coating operation. If you switch between compliance options for any coating operation or group of coating operations, you must document this switch as required by §63.3930(c), and you must report it in the next semiannual compliance report required in §63.3920.

(a) Compliant material option. Demonstrate that the organic HAP content of each coating used in the coating operation(s) is less than or equal to the applicable emission limit in §63.3890, and that each thinner and/or other additive, and cleaning material used contains no organic HAP. You must meet all the requirements of §§63.3940, 63.3941, and 63.3942 to demonstrate compliance with the applicable emission limit using this option.

(b) Emission rate without add-on controls option. Demonstrate that, based on the coatings, thinners and/or other additives, and cleaning materials used in the coating operation(s), the organic HAP emission rate for the coating operation(s) is less than or equal to the applicable emission limit in §63.3890, calculated as a rolling 12-month emission rate and determined on a monthly basis. You must meet all the requirements of §§63.3950, 63.3951, and 63.3952 to demonstrate compliance with the emission limit using this option.

(c) Emission rate with add-on controls option. Demonstrate that, based on the coatings, thinners and/or other additives, and cleaning materials used in the coating operation(s), and the emissions reductions achieved by emission capture systems and add-on controls, the organic HAP emission rate for the coating operation(s) is less than or equal to the applicable emission limit in §63.3890, calculated as a rolling 12-month emission rate and determined on a monthly basis. If you use this compliance option, you must also demonstrate that all emission capture systems and add-on control devices for the coating operation(s) meet the operating limits required in §63.3892, except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), and that you meet the work practice standards required in §63.3893. You must meet all the requirements of §§63.3960 through 63.3968 to demonstrate compliance with the emission limits, operating limits, and work practice standards using this option.

### **§ 63.3892 What operating limits must I meet?**

(a) For any coating operation(s) on which you use the compliant material option or the emission rate without add-on controls option, you are not required to meet any operating limits.

(b) For any controlled coating operation(s) on which you use the emission rate with add-on controls option, except those for which you use a solvent recovery system and conduct a liquid-liquid material balance according to §63.3961(j), you must meet the operating limits specified in Table 1 to this subpart. These operating limits apply to the emission capture and control systems on the coating operation(s) for which you use this option, and you must establish the operating limits during the performance test according to the requirements in §63.3967. You must meet the operating limits at all times after you establish them.

(c) If you use an add-on control device other than those listed in Table 1 to this subpart, or wish to monitor an alternative parameter and comply with a different operating limit, you must apply to the Administrator for approval of alternative monitoring under §63.8(f).

### **§ 63.3893 What work practice standards must I meet?**

(a) For any coating operation(s) on which you use the compliant material option or the emission rate without add-on controls option, you are not required to meet any work practice standards.

(b) If you use the emission rate with add-on controls option, you must develop and implement a work practice plan to minimize organic HAP emissions from the storage, mixing, and conveying of coatings, thinners and/or other additives, and cleaning materials used in, and waste materials generated by the controlled coating operation(s) for which you use this option; or you must meet an alternative standard as provided in paragraph (c) of this section. The plan must specify practices and procedures to ensure that, at a minimum, the elements specified in paragraphs (b)(1) through (5) of this section are implemented.

(1) All organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be stored in closed containers.

(2) Spills of organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be minimized.

(3) Organic-HAP-containing coatings, thinners and/or other additives, cleaning materials, and waste materials must be conveyed from one location to another in closed containers or pipes.

(4) Mixing vessels which contain organic-HAP-containing coatings and other materials must be closed except when adding to, removing, or mixing the contents.

(5) Emissions of organic HAP must be minimized during cleaning of storage, mixing, and conveying equipment.

(c) As provided in §63.6(g), we, the U.S. Environmental Protection Agency, may choose to grant you permission to use an alternative to the work practice standards in this section.

### **General Compliance Requirements**

### **§ 63.3900 What are my general requirements for complying with this subpart?**

(a) You must be in compliance with the emission limitations in this subpart as specified in paragraphs (a)(1) and (2) of this section.

(1) Any coating operation(s) for which you use the compliant material option or the emission rate without add-on controls option, as specified in §63.3891(a) and (b), must be in compliance with the applicable emission limit in §63.3890 at all times.

(2) Any coating operation(s) for which you use the emission rate with add-on controls option, as specified in §63.3891(c), must be in compliance with the emission limitations as specified in paragraphs (a)(2)(i) through (iii) of this section.

(i) The coating operation(s) must be in compliance with the applicable emission limit in §63.3890 at all times except during periods of startup, shutdown, and malfunction.

(ii) The coating operation(s) must be in compliance with the operating limits for emission capture systems and add-on control devices required by §63.3892 at all times except during periods of startup, shutdown, and malfunction, and except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j).

(iii) The coating operation(s) must be in compliance with the work practice standards in §63.3893 at all times.

(b) You must always operate and maintain your affected source, including all air pollution control and monitoring equipment you use for purposes of complying with this subpart, according to the provisions in §63.6(e)(1)(i).

(c) If your affected source uses an emission capture system and add-on control device, you must develop a written startup, shutdown, and malfunction plan according to the provisions in §63.6(e)(3). The plan must address the startup, shutdown, and corrective actions in the event of a malfunction of the emission capture system or the add-on control device. The plan must also address any coating operation equipment that may cause increased emissions or that would affect capture efficiency if the process equipment malfunctions, such as conveyors that move parts among enclosures.

[69 FR 157, Jan. 2, 2004, as amended at 71 FR 20465, Apr. 20, 2006]

### **§ 63.3901 What parts of the General Provisions apply to me?**

Table 2 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you.

### **Notifications, Reports, and Records**

#### **§ 63.3910 What notifications must I submit?**

(a) *General.* You must submit the notifications in §§63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) that apply to you by the dates specified in those sections, except as provided in paragraphs (b) and (c) of this section.

(b) *Initial Notification.* You must submit the initial notification required by §63.9(b) for a new or reconstructed affected source no later than 120 days after initial startup or 120 days after January 2, 2004, whichever is later. For an existing affected source, you must submit the initial notification no later than 1 year after January 2, 2004. If you are using compliance with the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (subpart IIII of this part) as provided for under §63.3881(d) to constitute compliance with this subpart for any or all of your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations. If you are complying with another NESHAP that constitutes the predominant activity at your facility under §63.3881(e)(2) to constitute compliance with this

subpart for your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations.

(c) *Notification of compliance status.* You must submit the notification of compliance status required by §63.9(h) no later than 30 calendar days following the end of the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source. The notification of compliance status must contain the information specified in paragraphs (c)(1) through (11) of this section and in §63.9(h).

(1) Company name and address.

(2) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(3) Date of the report and beginning and ending dates of the reporting period. The reporting period is the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source.

(4) Identification of the compliance option or options specified in §63.3891 that you used on each coating operation in the affected source during the initial compliance period.

(5) Statement of whether or not the affected source achieved the emission limitations for the initial compliance period.

(6) If you had a deviation, include the information in paragraphs (c)(6)(i) and (ii) of this section.

(i) A description and statement of the cause of the deviation.

(ii) If you failed to meet the applicable emission limit in §63.3890, include all the calculations you used to determine the kg (lb) of organic HAP emitted per liter (gal) coating solids used. You do not need to submit information provided by the materials' suppliers or manufacturers, or test reports.

(7) For each of the data items listed in paragraphs (c)(7)(i) through (iv) of this section that is required by the compliance option(s) you used to demonstrate compliance with the emission limit, include an example of how you determined the value, including calculations and supporting data. Supporting data may include a copy of the information provided by the supplier or manufacturer of the example coating or material, or a summary of the results of testing conducted according to §63.3941(a), (b), or (c). You do not need to submit copies of any test reports.

(i) Mass fraction of organic HAP for one coating, for one thinner and/or other additive, and for one cleaning material.

(ii) Volume fraction of coating solids for one coating.

(iii) Density for one coating, one thinner and/or other additive, and one leaning material, except that if you use the compliant material option, only the example coating density is required.

(iv) The amount of waste materials and the mass of organic HAP contained in the waste materials for which you are claiming an allowance in Equation 1 of §63.3951.

(8) The calculation of kg (lb) of organic HAP emitted per liter (gal) coating solids used for the compliance option(s) you used, as specified in paragraphs (c)(8)(i) through (iii) of this section.

(i) For the compliant material option, provide an example calculation of the organic HAP content for one coating, using Equation 2 of §63.3941.

(ii) For the emission rate without add-on controls option, provide the calculation of the total mass of organic HAP emissions for each month; the calculation of the total volume of coating solids used each month; and the calculation of the 12-month organic HAP emission rate using Equations 1 and 1A through 1C, 2, and 3, respectively, of §63.3951.

(iii) For the emission rate with add-on controls option, provide the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month, using Equations 1 and 1A through 1C of §63.3951; the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; the mass of organic HAP emission reduction each month by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961 and Equations 2, 3, and 3A through 3C of §63.3961 as applicable; the calculation of the total mass of organic HAP emissions each month using Equation 4 of §63.3961; and the calculation of the 12-month organic HAP emission rate using Equation 5 of §63.3961.

(9) For the emission rate with add-on controls option, you must include the information specified in paragraphs (c)(9)(i) through (iv) of this section, except that the requirements in paragraphs (c)(9)(i) through (iii) of this section do not apply to solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j).

(i) For each emission capture system, a summary of the data and copies of the calculations supporting the determination that the emission capture system is a permanent total enclosure (PTE) or a measurement of the emission capture system efficiency. Include a description of the protocol followed for measuring capture efficiency, summaries of any capture efficiency tests conducted, and any calculations supporting the capture efficiency determination. If you use the data quality objective (DQO) or lower confidence limit (LCL) approach, you must also include the statistical calculations to show you meet the DQO or LCL criteria in appendix A to subpart KK of this part. You do not need to submit complete test reports.

(ii) A summary of the results of each add-on control device performance test. You do not need to submit complete test reports.

(iii) A list of each emission capture system's and add-on control device's operating limits and a summary of the data used to calculate those limits.

(iv) A statement of whether or not you developed and implemented the work practice plan required by §63.3893.

(10) If you are complying with a single emission limit representing the predominant activity under §63.3890(c)(1), include the calculations and supporting information used to demonstrate that this emission limit represents the predominant activity as specified in §63.3890(c)(1).

(11) If you are complying with a facility-specific emission limit under §63.3890(c)(2), include the calculation of the facility-specific emission limit and any supporting information as specified in §63.3890(c)(2).

[69 FR 157, Jan. 2, 2004, as amended at 69 FR 22660, Apr. 26, 2004]

## § 63.3920 What reports must I submit?

(a) *Semiannual compliance reports.* You must submit semiannual compliance reports for each affected source according to the requirements of paragraphs (a)(1) through (7) of this section. The semiannual compliance reporting requirements may be satisfied by reports required under other parts of the Clean Air Act (CAA), as specified in paragraph (a)(2) of this section.

(1) *Dates.* Unless the Administrator has approved or agreed to a different schedule for submission of reports under §63.10(a), you must prepare and submit each semiannual compliance report according to the dates specified in paragraphs (a)(1)(i) through (iv) of this section. Note that the information reported for each of the months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(i) The first semiannual compliance report must cover the first semiannual reporting period which begins the day after the end of the initial compliance period described in §63.3940, §63.3950, or §63.3960 that applies to your affected source and ends on June 30 or December 31, whichever date is the first date following the end of the initial compliance period.

(ii) Each subsequent semiannual compliance report must cover the subsequent semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(iii) Each semiannual compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(iv) For each affected source that is subject to permitting regulations pursuant to 40 CFR part 70 or 40 CFR part 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), you may submit the first and subsequent compliance reports according to the dates the permitting authority has established instead of according to the date specified in paragraph (a)(1)(iii) of this section.

(2) *Inclusion with title V report.* Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 40 CFR part 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a semiannual compliance report pursuant to this section along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the semiannual compliance report includes all required information concerning deviations from any emission limitation in this subpart, its submission will be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a semiannual compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permitting authority.

(3) *General requirements.* The semiannual compliance report must contain the information specified in paragraphs (a)(3)(i) through (vii) of this section, and the information specified in paragraphs (a)(4) through (7) and (c)(1) of this section that is applicable to your affected source.

(i) Company name and address.

(ii) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(iii) Date of report and beginning and ending dates of the reporting period. The reporting period is the 6-month period ending on June 30 or December 31. Note that the information reported for each of the 6

months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(iv) Identification of the compliance option or options specified in §63.3891 that you used on each coating operation during the reporting period. If you switched between compliance options during the reporting period, you must report the beginning and ending dates for each option you used.

(v) If you used the emission rate without add-on controls or the emission rate with add-on controls compliance option (§63.3891(b) or (c)), the calculation results for each rolling 12-month organic HAP emission rate during the 6-month reporting period.

(vi) If you used the predominant activity alternative (§63.3890(c)(1)), include the annual determination of predominant activity if it was not included in the previous semi-annual compliance report.

(vii) If you used the facility-specific emission limit alternative (§63.3890(c)(2)), include the calculation of the facility-specific emission limit for each 12-month compliance period during the 6-month reporting period.

(4) No deviations. If there were no deviations from the emission limitations in §§63.3890, 63.3892, and 63.3893 that apply to you, the semiannual compliance report must include a statement that there were no deviations from the emission limitations during the reporting period. If you used the emission rate with add-on controls option and there were no periods during which the continuous parameter monitoring systems (CPMS) were out-of-control as specified in §63.8(c)(7), the semiannual compliance report must include a statement that there were no periods during which the CPMS were out-of-control during the reporting period.

(5) Deviations: Compliant material option. If you used the compliant material option and there was a deviation from the applicable organic HAP content requirements in §63.3890, the semiannual compliance report must contain the information in paragraphs (a)(5)(i) through (iv) of this section.

(i) Identification of each coating used that deviated from the applicable emission limit, and each thinner and/or other additive, and cleaning material used that contained organic HAP, and the dates and time periods each was used.

(ii) The calculation of the organic HAP content (using Equation 2 of §63.3941) for each coating identified in paragraph (a)(5)(i) of this section. You do not need to submit background data supporting this calculation ( e.g., information provided by coating suppliers or manufacturers, or test reports).

(iii) The determination of mass fraction of organic HAP for each thinner and/or other additive, and cleaning material identified in paragraph (a)(5)(i) of this section. You do not need to submit background data supporting this calculation ( e.g., information provided by material suppliers or manufacturers, or test reports).

(iv) A statement of the cause of each deviation.

(6) Deviations: Emission rate without add-on controls option. If you used the emission rate without add-on controls option and there was a deviation from the applicable emission limit in §63.3890, the semiannual compliance report must contain the information in paragraphs (a)(6)(i) through (iii) of this section.

(i) The beginning and ending dates of each compliance period during which the 12-month organic HAP emission rate exceeded the applicable emission limit in §63.3890.

(ii) The calculations used to determine the 12-month organic HAP emission rate for the compliance period in which the deviation occurred. You must submit the calculations for Equations 1, 1A through 1C, 2, and 3 of §63.3951; and if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4). You do not need to submit background data supporting these calculations ( e.g., information provided by materials suppliers or manufacturers, or test reports).

(iii) A statement of the cause of each deviation.

(7) Deviations: Emission rate with add-on controls option. If you used the emission rate with add-on controls option and there was a deviation from an emission limitation (including any periods when emissions bypassed the add-on control device and were diverted to the atmosphere), the semiannual compliance report must contain the information in paragraphs (a)(7)(i) through (xiv) of this section. This includes periods of startup, shutdown, and malfunction during which deviations occurred.

(i) The beginning and ending dates of each compliance period during which the 12-month organic HAP emission rate exceeded the applicable emission limit in §63.3890.

(ii) The calculations used to determine the 12-month organic HAP emission rate for each compliance period in which a deviation occurred. You must provide the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1 and 1A through 1C of §63.3951; and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4); the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; the calculation of the mass of organic HAP emission reduction each month by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961, and Equations 2, 3, and 3A through 3C of §63.3961, as applicable; the calculation of the total mass of organic HAP emissions each month using Equation 4 of §63.3961; and the calculation of the 12-month organic HAP emission rate using Equation 5 of §63.3961. You do not need to submit the background data supporting these calculations ( e.g., information provided by materials suppliers or manufacturers, or test reports).

(iii) The date and time that each malfunction started and stopped.

(iv) A brief description of the CPMS.

(v) The date of the latest CPMS certification or audit.

(vi) The date and time that each CPMS was inoperative, except for zero (low-level) and high-level checks.

(vii) The date, time, and duration that each CPMS was out-of-control, including the information in §63.8(c)(8).

(viii) The date and time period of each deviation from an operating limit in Table 1 to this subpart; date and time period of any bypass of the add-on control device; and whether each deviation occurred during a period of startup, shutdown, or malfunction or during another period.

(ix) A summary of the total duration of each deviation from an operating limit in Table 1 to this subpart and each bypass of the add-on control device during the semiannual reporting period, and the total duration as a percent of the total source operating time during that semiannual reporting period.

(x) A breakdown of the total duration of the deviations from the operating limits in Table 1 of this subpart and bypasses of the add-on control device during the semiannual reporting period into those that were due to startup, shutdown, control equipment problems, process problems, other known causes, and other unknown causes.

(xi) A summary of the total duration of CPMS downtime during the semiannual reporting period and the total duration of CPMS downtime as a percent of the total source operating time during that semiannual reporting period.

(xii) A description of any changes in the CPMS, coating operation, emission capture system, or add-on control device since the last semiannual reporting period.

(xiii) For each deviation from the work practice standards, a description of the deviation, the date and time period of the deviation, and the actions you took to correct the deviation.

(xiv) A statement of the cause of each deviation.

(b) Performance test reports. If you use the emission rate with add-on controls option, you must submit reports of performance test results for emission capture systems and add-on control devices no later than 60 days after completing the tests as specified in §63.10(d)(2).

(c) Startup, shutdown, malfunction reports. If you used the emission rate with add-on controls option and you had a startup, shutdown, or malfunction during the semiannual reporting period, you must submit the reports specified in paragraphs (c)(1) and (2) of this section.

(1) If your actions were consistent with your startup, shutdown, and malfunction plan, you must include the information specified in §63.10(d) in the semiannual compliance report required by paragraph (a) of this section.

(2) If your actions were not consistent with your startup, shutdown, and malfunction plan, you must submit an immediate startup, shutdown, and malfunction report as described in paragraphs (c)(2)(i) and (ii) of this section.

(i) You must describe the actions taken during the event in a report delivered by facsimile, telephone, or other means to the Administrator within 2 working days after starting actions that are inconsistent with the plan.

(ii) You must submit a letter to the Administrator within 7 working days after the end of the event, unless you have made alternative arrangements with the Administrator as specified in §63.10(d)(5)(ii). The letter must contain the information specified in §63.10(d)(5)(ii).

### **§ 63.3930 What records must I keep?**

You must collect and keep records of the data and information specified in this section. Failure to collect and keep these records is a deviation from the applicable standard.

(a) A copy of each notification and report that you submitted to comply with this subpart, and the documentation supporting each notification and report. If you are using the predominant activity alternative under §63.3890(c), you must keep records of the data and calculations used to determine the predominant activity. If you are using the facility-specific emission limit alternative under §63.3890(c), you must keep records of the data used to calculate the facility-specific emission limit for the initial compliance demonstration. You must also keep records of any data used in each annual predominant activity determination and in the calculation of the facility-specific emission limit for each 12-month compliance period included in the semi-annual compliance reports.

(b) A current copy of information provided by materials suppliers or manufacturers, such as manufacturer's formulation data, or test data used to determine the mass fraction of organic HAP and density for each coating, thinner and/or other additive, and cleaning material, and the volume fraction of

coating solids for each coating. If you conducted testing to determine mass fraction of organic HAP, density, or volume fraction of coating solids, you must keep a copy of the complete test report. If you use information provided to you by the manufacturer or supplier of the material that was based on testing, you must keep the summary sheet of results provided to you by the manufacturer or supplier. You are not required to obtain the test report or other supporting documentation from the manufacturer or supplier.

(c) For each compliance period, the records specified in paragraphs (c)(1) through (4) of this section.

(1) A record of the coating operations on which you used each compliance option and the time periods (beginning and ending dates and times) for each option you used.

(2) For the compliant material option, a record of the calculation of the organic HAP content for each coating, using Equation 2 of §63.3941.

(3) For the emission rate without add-on controls option, a record of the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1, 1A through 1C, and 2 of §63.3951; and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4); the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; and the calculation of each 12-month organic HAP emission rate using Equation 3 of §63.3951.

(4) For the emission rate with add-on controls option, records of the calculations specified in paragraphs (c)(4)(i) through (v) of this section.

(i) The calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1 and 1A through 1C of §63.3951 and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4);

(ii) The calculation of the total volume of coating solids used each month using Equation 2 of §63.3951;

(iii) The calculation of the mass of organic HAP emission reduction by emission capture systems and add-on control devices using Equations 1 and 1A through 1D of §63.3961 and Equations 2, 3, and 3A through 3C of §63.3961, as applicable;

(iv) The calculation of each month's organic HAP emission rate using Equation 4 of §63.3961; and

(v) The calculation of each 12-month organic HAP emission rate using Equation 5 of §63.3961.

(d) A record of the name and volume of each coating, thinner and/or other additive, and cleaning material used during each compliance period. If you are using the compliant material option for all coatings at the source, you may maintain purchase records for each material used rather than a record of the volume used.

(e) A record of the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each compliance period unless the material is tracked by weight.

(f) A record of the volume fraction of coating solids for each coating used during each compliance period.

(g) If you use either the emission rate without add-on controls or the emission rate with add-on controls compliance option, the density for each coating, thinner and/or other additive, and cleaning material used during each compliance period.

(h) If you use an allowance in Equation 1 of §63.3951 for organic HAP contained in waste materials sent to or designated for shipment to a treatment, storage, and disposal facility (TSDF) according to §63.3951(e)(4), you must keep records of the information specified in paragraphs (h)(1) through (3) of this section.

(1) The name and address of each TSDF to which you sent waste materials for which you use an allowance in Equation 1 of §63.3951; a statement of which subparts under 40 CFR parts 262, 264, 265, and 266 apply to the facility; and the date of each shipment.

(2) Identification of the coating operations producing waste materials included in each shipment and the month or months in which you used the allowance for these materials in Equation 1 of §63.3951.

(3) The methodology used in accordance with §63.3951(e)(4) to determine the total amount of waste materials sent to or the amount collected, stored, and designated for transport to a TSDF each month; and the methodology to determine the mass of organic HAP contained in these waste materials. This must include the sources for all data used in the determination, methods used to generate the data, frequency of testing or monitoring, and supporting calculations and documentation, including the waste manifest for each shipment.

(i) [Reserved]

(j) You must keep records of the date, time, and duration of each deviation.

(k) If you use the emission rate with add-on controls option, you must keep the records specified in paragraphs (k)(1) through (8) of this section.

(1) For each deviation, a record of whether the deviation occurred during a period of startup, shutdown, or malfunction.

(2) The records in §63.6(e)(3)(iii) through (v) related to startup, shutdown, and malfunction.

(3) The records required to show continuous compliance with each operating limit specified in Table 1 to this subpart that applies to you.

(4) For each capture system that is a PTE, the data and documentation you used to support a determination that the capture system meets the criteria in Method 204 of appendix M to 40 CFR part 51 for a PTE and has a capture efficiency of 100 percent, as specified in §63.3965(a).

(5) For each capture system that is not a PTE, the data and documentation you used to determine capture efficiency according to the requirements specified in §§63.3964 and 63.3965(b) through (e), including the records specified in paragraphs (k)(5)(i) through (iii) of this section that apply to you.

(i) Records for a liquid-to-uncaptured gas protocol using a temporary total enclosure or building enclosure. Records of the mass of total volatile hydrocarbon (TVH) as measured by Method 204A or 204F of appendix M to 40 CFR part 51 for each material used in the coating operation, and the total TVH for all materials used during each capture efficiency test run, including a copy of the test report. Records of the mass of TVH emissions not captured by the capture system that exited the temporary total enclosure or building enclosure during each capture efficiency test run, as measured by Method 204D or 204E of appendix M to 40 CFR part 51, including a copy of the test report. Records documenting that the enclosure used for the capture efficiency test met the criteria in Method 204 of appendix M to 40 CFR part 51 for either a temporary total enclosure or a building enclosure.

(ii) Records for a gas-to-gas protocol using a temporary total enclosure or a building enclosure. Records of the mass of TVH emissions captured by the emission capture system as measured by Method 204B or 204C of appendix M to 40 CFR part 51 at the inlet to the add-on control device, including a copy of the test report. Records of the mass of TVH emissions not captured by the capture system that exited the temporary total enclosure or building enclosure during each capture efficiency test run as measured by Method 204D or 204E of appendix M to 40 CFR part 51, including a copy of the test report. Records documenting that the enclosure used for the capture efficiency test met the criteria in Method 204 of appendix M to 40 CFR part 51 for either a temporary total enclosure or a building enclosure.

(iii) Records for an alternative protocol. Records needed to document a capture efficiency determination using an alternative method or protocol as specified in §63.3965(e), if applicable.

(6) The records specified in paragraphs (k)(6)(i) and (ii) of this section for each add-on control device organic HAP destruction or removal efficiency determination as specified in §63.3966.

(i) Records of each add-on control device performance test conducted according to §§63.3964 and 63.3966.

(ii) Records of the coating operation conditions during the add-on control device performance test showing that the performance test was conducted under representative operating conditions.

(7) Records of the data and calculations you used to establish the emission capture and add-on control device operating limits as specified in §63.3967 and to document compliance with the operating limits as specified in Table 1 to this subpart.

(8) A record of the work practice plan required by §63.3893 and documentation that you are implementing the plan on a continuous basis.

### **§ 63.3931 In what form and for how long must I keep my records?**

(a) Your records must be in a form suitable and readily available for expeditious review, according to §63.10(b)(1). Where appropriate, the records may be maintained as electronic spreadsheets or as a database.

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record on-site for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record according to §63.10(b)(1). You may keep the records off-site for the remaining 3 years.

### **Compliance Requirements for the Compliant Material Option**

#### **§ 63.3940 By what date must I conduct the initial compliance demonstration?**

You must complete the initial compliance demonstration for the initial compliance period according to the requirements in §63.3941. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through that month plus the next 12 months. The initial compliance demonstration includes the calculations according to §63.3941 and supporting documentation showing that during the initial compliance period, you used no coating with an organic HAP content that exceeded the applicable

emission limit in §63.3890, and that you used no thinners and/or other additives, or cleaning materials that contained organic HAP as determined according to §63.3941(a).

### **§ 63.3941 How do I demonstrate initial compliance with the emission limitations?**

You may use the compliant material option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected source. You must use either the emission rate without add-on controls option or the emission rate with add-on controls option for any coating operation in the affected source for which you do not use this option. To demonstrate initial compliance using the compliant material option, the coating operation or group of coating operations must use no coating with an organic HAP content that exceeds the applicable emission limits in §63.3890 and must use no thinner and/or other additive, or cleaning material that contains organic HAP as determined according to this section. Any coating operation for which you use the compliant material option is not required to meet the operating limits or work practice standards required in §§63.3892 and 63.3893, respectively. You must conduct a separate initial compliance demonstration for each general use, high performance, magnet wire, rubber-to-metal, and extreme performance fluoropolymer coating operation unless you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c). If you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c), you must demonstrate that all coating operations included in the predominant activity determination or calculation of the facility-specific emission limit comply with that limit. You must meet all the requirements of this section. Use the procedures in this section on each coating, thinner and/or other additive, and cleaning material in the condition it is in when it is received from its manufacturer or supplier and prior to any alteration. You do not need to redetermine the organic HAP content of coatings, thinners and/or other additives, and cleaning materials that are reclaimed on-site (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coating operation for which you use the compliant material option, provided these materials in their condition as received were demonstrated to comply with the compliant material option.

(a) Determine the mass fraction of organic HAP for each material used. You must determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during the compliance period by using one of the options in paragraphs (a)(1) through (5) of this section.

(1) Method 311 (appendix A to 40 CFR part 63). You may use Method 311 for determining the mass fraction of organic HAP. Use the procedures specified in paragraphs (a)(1)(i) and (ii) of this section when performing a Method 311 test.

(i) Count each organic HAP that is measured to be present at 0.1 percent by mass or more for Occupational Safety and Health Administration (OSHA)-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is measured to be 0.5 percent of the material by mass, you do not have to count it. Express the mass fraction of each organic HAP you count as a value truncated to four places after the decimal point ( e.g., 0.3791).

(ii) Calculate the total mass fraction of organic HAP in the test material by adding up the individual organic HAP mass fractions and truncating the result to three places after the decimal point ( e.g., 0.763).

(2) Method 24 (appendix A to 40 CFR part 60). For coatings, you may use Method 24 to determine the mass fraction of nonaqueous volatile matter and use that value as a substitute for mass fraction of organic HAP. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, you may use the alternative method contained in appendix A to subpart P of this part, rather than Method 24. You may use the volatile fraction that is emitted, as measured by the alternative method in appendix A to subpart P of this part, as a substitute for the mass fraction of organic HAP.

(3) Alternative method. You may use an alternative test method for determining the mass fraction of organic HAP once the Administrator has approved it. You must follow the procedure in §63.7(f) to submit an alternative test method for approval.

(4) Information from the supplier or manufacturer of the material. You may rely on information other than that generated by the test methods specified in paragraphs (a)(1) through (3) of this section, such as manufacturer's formulation data, if it represents each organic HAP that is present at 0.1 percent by mass or more for OSHA-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is 0.5 percent of the material by mass, you do not have to count it. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, you may rely on manufacturer's data that expressly states the organic HAP or volatile matter mass fraction emitted. If there is a disagreement between such information and results of a test conducted according to paragraphs (a)(1) through (3) of this section, then the test method results will take precedence unless, after consultation, you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(5) Solvent blends. Solvent blends may be listed as single components for some materials in data provided by manufacturers or suppliers. Solvent blends may contain organic HAP which must be counted toward the total organic HAP mass fraction of the materials. When test data and manufacturer's data for solvent blends are not available, you may use the default values for the mass fraction of organic HAP in these solvent blends listed in Table 3 or 4 to this subpart. If you use the tables, you must use the values in Table 3 for all solvent blends that match Table 3 entries according to the instructions for Table 3, and you may use Table 4 only if the solvent blends in the materials you use do not match any of the solvent blends in Table 3 and you know only whether the blend is aliphatic or aromatic. However, if the results of a Method 311 (appendix A to 40 CFR part 63) test indicate higher values than those listed on Table 3 or 4 to this subpart, the Method 311 results will take precedence unless, after consultation, you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(b) Determine the volume fraction of coating solids for each coating. You must determine the volume fraction of coating solids (liters (gal) of coating solids per liter (gal) of coating) for each coating used during the compliance period by a test, by information provided by the supplier or the manufacturer of the material, or by calculation, as specified in paragraphs (b)(1) through (4) of this section. If test results obtained according to paragraph (b)(1) of this section do not agree with the information obtained under paragraph (b)(3) or (4) of this section, the test results will take precedence unless, after consultation, you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(1) ASTM Method D2697–86 (Reapproved 1998) or ASTM Method D6093–97 (Reapproved 2003). You may use ASTM Method D2697–86 (Reapproved 1998), "Standard Test Method for Volume Nonvolatile Matter in Clear or Pigmented Coatings" (incorporated by reference, see §63.14), or ASTM Method D6093–97 (Reapproved 2003), "Standard Test Method for Percent Volume Nonvolatile Matter in Clear or Pigmented Coatings Using a Helium Gas Pycnometer" (incorporated by reference, see §63.14), to determine the volume fraction of coating solids for each coating. Divide the nonvolatile volume percent obtained with the methods by 100 to calculate volume fraction of coating solids.

(2) Alternative method. You may use an alternative test method for determining the solids content of each coating once the Administrator has approved it. You must follow the procedure in §63.7(f) to submit an alternative test method for approval.

(3) Information from the supplier or manufacturer of the material. You may obtain the volume fraction of coating solids for each coating from the supplier or manufacturer.

(4) Calculation of volume fraction of coating solids. You may determine the volume fraction of coating solids using Equation 1 of this section:

$$V_s = 1 - \frac{m_{\text{volatiles}}}{D_{\text{avg}}} \quad (\text{Eq. 1})$$

Where:

$V_s$ = Volume fraction of coating solids, liters (gal) coating solids per liter (gal) coating.

$m_{\text{volatiles}}$ = Total volatile matter content of the coating, including HAP, volatile organic compounds (VOC), water, and exempt compounds, determined according to Method 24 in appendix A of 40 CFR part 60, grams volatile matter per liter coating.

$D_{\text{avg}}$ = Average density of volatile matter in the coating, grams volatile matter per liter volatile matter, determined from test results using ASTM Method D1475–98, “Standard Test Method for Density of Liquid Coatings, Inks, and Related Products” (incorporated by reference, see §63.14), information from the supplier or manufacturer of the material, or reference sources providing density or specific gravity data for pure materials. If there is disagreement between ASTM Method D1475–98 test results and other information sources, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(c) Determine the density of each coating. Determine the density of each coating used during the compliance period from test results using ASTM Method D1475–98, “Standard Test Method for Density of Liquid Coatings, Inks, and Related Products” (incorporated by reference, see §63.14), information from the supplier or manufacturer of the material, or specific gravity data for pure chemicals. If there is disagreement between ASTM Method D1475–98 test results and the supplier's or manufacturer's information, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(d) Determine the organic HAP content of each coating. Calculate the organic HAP content, kg (lb) of organic HAP emitted per liter (gal) coating solids used, of each coating used during the compliance period using Equation 2 of this section:

$$H_c = \frac{(D_c)(W_c)}{V_s} \quad (\text{Eq. 2})$$

Where:

$H_c$ = Organic HAP content of the coating, kg organic HAP emitted per liter (gal) coating solids used.

$D_c$ = Density of coating, kg coating per liter (gal) coating, determined according to paragraph (c) of this section.

$W_c$ = Mass fraction of organic HAP in the coating, kg organic HAP per kg coating, determined according to paragraph (a) of this section.

$V_s$ = Volume fraction of coating solids, liter (gal) coating solids per liter (gal) coating, determined according to paragraph (b) of this section.

(e) *Compliance demonstration.* The calculated organic HAP content for each coating used during the initial compliance period must be less than or equal to the applicable emission limit in §63.3890; and each thinner and/or other additive, and cleaning material used during the initial compliance period must contain no organic HAP, determined according to paragraph (a) of this section. You must keep all records

required by §§63.3930 and 63.3931. As part of the notification of compliance status required in §63.3910, you must identify the coating operation(s) for which you used the compliant material option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because you used no coatings for which the organic HAP content exceeded the applicable emission limit in §63.3890, and you used no thinners and/or other additives, or cleaning materials that contained organic HAP, determined according to the procedures in paragraph (a) of this section.

#### **§ 63.3942 How do I demonstrate continuous compliance with the emission limitations?**

(a) For each compliance period to demonstrate continuous compliance, you must use no coating for which the organic HAP content (determined using Equation 2 of §63.3941) exceeds the applicable emission limit in §63.3890, and use no thinner and/or other additive, or cleaning material that contains organic HAP, determined according to §63.3941(a). A compliance period consists of 12 months. Each month, after the end of the initial compliance period described in §63.3940, is the end of a compliance period consisting of that month and the preceding 11 months. If you are complying with a facility-specific emission limit under §63.3890(c), you must also perform the calculation using Equation 1 in §63.3890(c)(2) on a monthly basis using the data from the previous 12 months of operation.

(b) If you choose to comply with the emission limitations by using the compliant material option, the use of any coating, thinner and/or other additive, or cleaning material that does not meet the criteria specified in paragraph (a) of this section is a deviation from the emission limitations that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(5).

(c) As part of each semiannual compliance report required by §63.3920, you must identify the coating operation(s) for which you used the compliant material option. If there were no deviations from the applicable emission limit in §63.3890, submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because you used no coatings for which the organic HAP content exceeded the applicable emission limit in §63.3890, and you used no thinner and/or other additive, or cleaning material that contained organic HAP, determined according to §63.3941(a).

(d) You must maintain records as specified in §§63.3930 and 63.3931.

#### **Compliance Requirements for the Emission Rate Without Add-On Controls Option**

##### **§ 63.3950 By what date must I conduct the initial compliance demonstration?**

You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3951. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coating solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the calculations according to §63.3951 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.3890.

### § 63.3951 How do I demonstrate initial compliance with the emission limitations?

You may use the emission rate without add-on controls option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected source. You must use either the compliant material option or the emission rate with add-on controls option for any coating operation in the affected source for which you do not use this option. To demonstrate initial compliance using the emission rate without add-on controls option, the coating operation or group of coating operations must meet the applicable emission limit in §63.3890, but is not required to meet the operating limits or work practice standards in §§63.3892 and 63.3893, respectively. You must conduct a separate initial compliance demonstration for each general use, magnet wire, rubber-to-metal, and extreme performance fluoropolymer coating operation unless you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c). If you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c), you must demonstrate that all coating operations included in the predominant activity determination or calculation of the facility-specific emission limit comply with that limit. You must meet all the requirements of this section. When calculating the organic HAP emission rate according to this section, do not include any coatings, thinners and/or other additives, or cleaning materials used on coating operations for which you use the compliant material option or the emission rate with add-on controls option. You do not need to redetermine the mass of organic HAP in coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coating operation for which you use the emission rate without add-on controls option. If you use coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site, the amount of each used in a month may be reduced by the amount of each that is reclaimed. That is, the amount used may be calculated as the amount consumed to account for materials that are reclaimed.

(a) Determine the mass fraction of organic HAP for each material. Determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each month according to the requirements in §63.3941(a).

(b) Determine the volume fraction of coating solids. Determine the volume fraction of coating solids (liter (gal) of coating solids per liter (gal) of coating) for each coating used during each month according to the requirements in §63.3941(b).

(c) Determine the density of each material. Determine the density of each liquid coating, thinner and/or other additive, and cleaning material used during each month from test results using ASTM Method D1475–98, “Standard Test Method for Density of Liquid Coatings, Inks, and Related Products” (incorporated by reference, see §63.14), information from the supplier or manufacturer of the material, or reference sources providing density or specific gravity data for pure materials. If you are including powder coatings in the compliance determination, determine the density of powder coatings, using ASTM Method D5965–02, “Standard Test Methods for Specific Gravity of Coating Powders” (incorporated by reference, see §63.14), or information from the supplier. If there is disagreement between ASTM Method D1475–98 or ASTM Method D5965–02 test results and other such information sources, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct. If you purchase materials or monitor consumption by weight instead of volume, you do not need to determine material density. Instead, you may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, 1C, and 2 of this section.

(d) Determine the volume of each material used. Determine the volume (liters) of each coating, thinner and/or other additive, and cleaning material used during each month by measurement or usage records. If you purchase materials or monitor consumption by weight instead of volume, you do not need to determine the volume of each material used. Instead, you may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, and 1C of this section.

(e) Calculate the mass of organic HAP emissions. The mass of organic HAP emissions is the combined mass of organic HAP contained in all coatings, thinners and/or other additives, and cleaning materials used during each month minus the organic HAP in certain waste materials. Calculate the mass of organic HAP emissions using Equation 1 of this section.

$$H_e = A + B + C - R_w \quad (\text{Eq. 1})$$

Where:

$H_e$  = Total mass of organic HAP emissions during the month, kg.

A = Total mass of organic HAP in the coatings used during the month, kg, as calculated in Equation 1A of this section.

B = Total mass of organic HAP in the thinners and/or other additives used during the month, kg, as calculated in Equation 1B of this section.

C = Total mass of organic HAP in the cleaning materials used during the month, kg, as calculated in Equation 1C of this section.

$R_w$  = Total mass of organic HAP in waste materials sent or designated for shipment to a hazardous waste TSDF for treatment or disposal during the month, kg, determined according to paragraph (e)(4) of this section. (You may assign a value of zero to  $R_w$  if you do not wish to use this allowance.)

(1) Calculate the kg organic HAP in the coatings used during the month using Equation 1A of this section:

$$A = \sum_{i=1}^m (Vol_{c,i}) (D_{c,i}) (W_{c,i}) \quad (\text{Eq. 1A})$$

Where:

A = Total mass of organic HAP in the coatings used during the month, kg.

$Vol_{c,i}$  = Total volume of coating, i, used during the month, liters.

$D_{c,i}$  = Density of coating, i, kg coating per liter coating.

$W_{c,i}$  = Mass fraction of organic HAP in coating, i, kg organic HAP per kg coating. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

m = Number of different coatings used during the month.

(2) Calculate the kg of organic HAP in the thinners and/or other additives used during the month using Equation 1B of this section:

$$B = \sum_{j=1}^n (Vol_{t,j}) (D_{t,j}) (W_{t,j}) \quad (\text{Eq. 1B})$$

Where:

B = Total mass of organic HAP in the thinners and/or other additives used during the month, kg.

Vol<sub>t,j</sub> = Total volume of thinner and/or other additive, j, used during the month, liters.

D<sub>t,j</sub> = Density of thinner and/or other additive, j, kg per liter.

W<sub>t,j</sub> = Mass fraction of organic HAP in thinner and/or other additive, j, kg organic HAP per kg thinner and/or other additive. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

n = Number of different thinners and/or other additives used during the month.

(3) Calculate the kg organic HAP in the cleaning materials used during the month using Equation 1C of this section:

$$C = \sum_{k=1}^p (Vol_{s,k}) (D_{s,k}) (W_{s,k}) \quad (Eq. 1C)$$

Where:

C = Total mass of organic HAP in the cleaning materials used during the month, kg.

Vol<sub>s,k</sub> = Total volume of cleaning material, k, used during the month, liters.

D<sub>s,k</sub> = Density of cleaning material, k, kg per liter.

W<sub>s,k</sub> = Mass fraction of organic HAP in cleaning material, k, kg organic HAP per kg material.

p = Number of different cleaning materials used during the month.

(4) If you choose to account for the mass of organic HAP contained in waste materials sent or designated for shipment to a hazardous waste TSDF in Equation 1 of this section, then you must determine the mass according to paragraphs (e)(4)(i) through (iv) of this section.

(i) You may only include waste materials in the determination that are generated by coating operations in the affected source for which you use Equation 1 of this section and that will be treated or disposed of by a facility that is regulated as a TSDF under 40 CFR part 262, 264, 265, or 266. The TSDF may be either off-site or on-site. You may not include organic HAP contained in wastewater.

(ii) You must determine either the amount of the waste materials sent to a TSDF during the month or the amount collected and stored during the month and designated for future transport to a TSDF. Do not include in your determination any waste materials sent to a TSDF during a month if you have already included them in the amount collected and stored during that month or a previous month.

(iii) Determine the total mass of organic HAP contained in the waste materials specified in paragraph (e)(4)(ii) of this section.

(iv) You must document the methodology you use to determine the amount of waste materials and the total mass of organic HAP they contain, as required in §63.3930(h). If waste manifests include this

information, they may be used as part of the documentation of the amount of waste materials and mass of organic HAP contained in them.

(f) Calculate the total volume of coating solids used. Determine the total volume of coating solids used, liters, which is the combined volume of coating solids for all the coatings used during each month, using Equation 2 of this section:

$$V_{st} = \sum_{i=1}^m (Vol_{c,i}) (V_{s,i}) \quad (Eq. 2)$$

Where:

$V_{st}$  = Total volume of coating solids used during the month, liters.

$Vol_{c,i}$  = Total volume of coating, i, used during the month, liters.

$V_{s,i}$  = Volume fraction of coating solids for coating, i, liter solids per liter coating, determined according to §63.3941(b).

m = Number of coatings used during the month.

(g) Calculate the organic HAP emission rate. Calculate the organic HAP emission rate for the compliance period, kg (lb) organic HAP emitted per liter (gal) coating solids used, using Equation 3 of this section:

$$H_{yr} = \frac{\sum_{y=1}^n H_e}{\sum_{y=1}^n V_{st}} \quad (Eq. 3)$$

Where:

$H_{yr}$  = Average organic HAP emission rate for the compliance period, kg organic HAP emitted per liter coating solids used.

$H_e$  = Total mass of organic HAP emissions from all materials used during month, y, kg, as calculated by Equation 1 of this section.

$V_{st}$  = Total volume of coating solids used during month, y, liters, as calculated by Equation 2 of this section.

y = Identifier for months.

n = Number of full or partial months in the compliance period (for the initial compliance period, n equals 12 if the compliance date falls on the first day of a month; otherwise n equals 13; for all following compliance periods, n equals 12).

(h) Compliance demonstration. The organic HAP emission rate for the initial compliance period calculated using Equation 3 of this section must be less than or equal to the applicable emission limit for each subcategory in §63.3890 or the predominant activity or facility-specific emission limit allowed in §63.3890(c). You must keep all records as required by §§63.3930 and 63.3931. As part of the notification

of compliance status required by §63.3910, you must identify the coating operation(s) for which you used the emission rate without add-on controls option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because the organic HAP emission rate was less than or equal to the applicable emission limit in §63.3890, determined according to the procedures in this section.

#### **§ 63.3952 How do I demonstrate continuous compliance with the emission limitations?**

(a) To demonstrate continuous compliance, the organic HAP emission rate for each compliance period, determined according to §63.3951(a) through (g), must be less than or equal to the applicable emission limit in §63.3890. A compliance period consists of 12 months. Each month after the end of the initial compliance period described in §63.3950 is the end of a compliance period consisting of that month and the preceding 11 months. You must perform the calculations in §63.3951(a) through (g) on a monthly basis using data from the previous 12 months of operation. If you are complying with a facility-specific emission limit under §63.3890(c), you must also perform the calculation using Equation 1 in §63.3890(c)(2) on a monthly basis using the data from the previous 12 months of operation.

(b) If the organic HAP emission rate for any 12-month compliance period exceeded the applicable emission limit in §63.3890, this is a deviation from the emission limitation for that compliance period and must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(6).

(c) As part of each semiannual compliance report required by §63.3920, you must identify the coating operation(s) for which you used the emission rate without add-on controls option. If there were no deviations from the emission limitations, you must submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable emission limit in §63.3890, determined according to §63.3951(a) through (g).

(d) You must maintain records as specified in §§63.3930 and 63.3931.

#### **Compliance Requirements for the Emission Rate With Add-On Controls Option**

#### **§ 63.3960 By what date must I conduct performance tests and other initial compliance demonstrations?**

(a) New and reconstructed affected sources. For a new or reconstructed affected source, you must meet the requirements of paragraphs (a)(1) through (4) of this section.

(1) All emission capture systems, add-on control devices, and CPMS must be installed and operating no later than the applicable compliance date specified in §63.3883. Except for solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), you must conduct a performance test of each capture system and add-on control device according to §§63.3964, 63.3965, and 63.3966 and establish the operating limits required by §63.3892 no later than 180 days after the applicable compliance date specified in §63.3883. For a solvent recovery system for which you conduct liquid-liquid material balances according to §63.3961(j), you must initiate the first material balance no later than the applicable compliance date specified in §63.3883. For magnet wire coating operations you may, with approval, conduct a performance test of one representative magnet wire coating machine for each group of identical or very similar magnet wire coating machines.

(2) You must develop and begin implementing the work practice plan required by §63.3893 no later than the compliance date specified in §63.3883.

(3) You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3961. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coatings solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the results of emission capture system and add-on control device performance tests conducted according to §§63.3964, 63.3965, and 63.3966; results of liquid-liquid material balances conducted according to §63.3961(j); calculations according to §63.3961 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.3890; the operating limits established during the performance tests and the results of the continuous parameter monitoring required by §63.3968; and documentation of whether you developed and implemented the work practice plan required by §63.3893.

(4) You do not need to comply with the operating limits for the emission capture system and add-on control device required by §63.3892 until after you have completed the performance tests specified in paragraph (a)(1) of this section. Instead, you must maintain a log detailing the operation and maintenance of the emission capture system, add-on control device, and continuous parameter monitors during the period between the compliance date and the performance test. You must begin complying with the operating limits for your affected source on the date you complete the performance tests specified in paragraph (a)(1) of this section. For magnet wire coating operations, you must begin complying with the operating limits for all identical or very similar magnet wire coating machines on the date you complete the performance test of a representative magnet wire coating machine. The requirements in this paragraph (a)(4) do not apply to solvent recovery systems for which you conduct liquid-liquid material balances according to the requirements in §63.3961(j).

(b) Existing affected sources. For an existing affected source, you must meet the requirements of paragraphs (b)(1) through (3) of this section.

(1) All emission capture systems, add-on control devices, and CPMS must be installed and operating no later than the applicable compliance date specified in §63.3883. Except for magnet wire coating operations and solvent recovery systems for which you conduct liquid-liquid material balances according to §63.3961(j), you must conduct a performance test of each capture system and add-on control device according to the procedures in §§63.3964, 63.3965, and 63.3966 and establish the operating limits required by §63.3892 no later than the compliance date specified in §63.3883. For magnet wire coating operations, you may, with approval, conduct a performance test of a single magnet wire coating machine that represents identical or very similar magnet wire coating machines. For a solvent recovery system for which you conduct liquid-liquid material balances according to §63.3961(j), you must initiate the first material balance no later than the compliance date specified in §63.3883.

(2) You must develop and begin implementing the work practice plan required by §63.3893 no later than the compliance date specified in §63.3883.

(3) You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3961. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coatings solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the results of emission capture system and add-on control device performance tests conducted according to §§63.3964, 63.3965, and 63.3966; results of liquid-liquid material balances conducted according to §63.3961(j); calculations according to §63.3961 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission

limit in §63.3890; the operating limits established during the performance tests and the results of the continuous parameter monitoring required by §63.3968; and documentation of whether you developed and implemented the work practice plan required by §63.3893.

(c) You are not required to conduct an initial performance test to determine capture efficiency or destruction efficiency of a capture system or control device if you receive approval to use the results of a performance test that has been previously conducted on that capture system or control device. Any such previous tests must meet the conditions described in paragraphs (c)(1) through (3) of this section.

(1) The previous test must have been conducted using the methods and conditions specified in this subpart.

(2) Either no process or equipment changes have been made since the previous test was performed or the owner or operator must be able to demonstrate that the results of the performance test, reliably demonstrate compliance despite process or equipment changes.

(3) Either the required operating parameters were established in the previous test or sufficient data were collected in the previous test to establish the required operating parameters.

#### **§ 63.3961 How do I demonstrate initial compliance?**

(a) You may use the emission rate with add-on controls option for any coating operation, for any group of coating operations in the affected source, or for all of the coating operations in the affected source. You may include both controlled and uncontrolled coating operations in a group for which you use this option. You must use either the compliant material option or the emission rate without add-on controls option for any coating operation in the affected source for which you do not use the emission rate with add-on controls option. To demonstrate initial compliance, the coating operation(s) for which you use the emission rate with add-on controls option must meet the applicable emission limitations in §§63.3890, 63.3892, and 63.3893. You must conduct a separate initial compliance demonstration for each general use, magnet wire, rubber-to-metal, and extreme performance fluoropolymer coating operation, unless you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c). If you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.4490(c), you must demonstrate that all coating operations included in the predominant activity determination or calculation of the facility-specific emission limit comply with that limit. You must meet all the requirements of this section. When calculating the organic HAP emission rate according to this section, do not include any coatings, thinners and/or other additives, or cleaning materials used on coating operations for which you use the compliant material option or the emission rate without add-on controls option. You do not need to redetermine the mass of organic HAP in coatings, thinners and/or other additives, or cleaning materials that have been reclaimed onsite (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coatings operation(s) for which you use the emission rate with add-on controls option. If you use coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site, the amount of each used in a month may be reduced by the amount of each that is reclaimed. That is, the amount used may be calculated as the amount consumed to account for materials that are reclaimed.

(b) Compliance with operating limits. Except as provided in §63.3960(a)(4), and except for solvent recovery systems for which you conduct liquid-liquid material balances according to the requirements of paragraph (j) of this section, you must establish and demonstrate continuous compliance during the initial compliance period with the operating limits required by §63.3892, using the procedures specified in §§63.3967 and 63.3968.

(c) Compliance with work practice requirements. You must develop, implement, and document your implementation of the work practice plan required by §63.3893 during the initial compliance period, as specified in §63.3930.

(d) Compliance with emission limits. You must follow the procedures in paragraphs (e) through (n) of this section to demonstrate compliance with the applicable emission limit in §63.3890 for each affected source in each subcategory.

(e) Determine the mass fraction of organic HAP, density, volume used, and volume fraction of coating solids. Follow the procedures specified in §63.3951(a) through (d) to determine the mass fraction of organic HAP, density, and volume of each coating, thinner and/or other additive, and cleaning material used during each month; and the volume fraction of coating solids for each coating used during each month.

(f) Calculate the total mass of organic HAP emissions before add-on controls. Using Equation 1 of §63.3951, calculate the total mass of organic HAP emissions before add-on controls from all coatings, thinners and/or other additives, and cleaning materials used during each month in the coating operation or group of coating operations for which you use the emission rate with add-on controls option.

(g) Calculate the organic HAP emission reduction for each controlled coating operation. Determine the mass of organic HAP emissions reduced for each controlled coating operation during each month. The emission reduction determination quantifies the total organic HAP emissions that pass through the emission capture system and are destroyed or removed by the add-on control device. Use the procedures in paragraph (h) of this section to calculate the mass of organic HAP emission reduction for each controlled coating operation using an emission capture system and add-on control device other than a solvent recovery system for which you conduct liquid-liquid material balances. For each controlled coating operation using a solvent recovery system for which you conduct a liquid-liquid material balance, use the procedures in paragraph (j) of this section to calculate the organic HAP emission reduction.

(h) Calculate the organic HAP emission reduction for each controlled coating operation not using liquid-liquid material balance. Use Equation 1 of this section to calculate the organic HAP emission reduction for each controlled coating operation using an emission capture system and add-on control device other than a solvent recovery system for which you conduct liquid-liquid material balances. The calculation applies the emission capture system efficiency and add-on control device efficiency to the mass of organic HAP contained in the coatings, thinners and/or other additives, and cleaning materials that are used in the coating operation served by the emission capture system and add-on control device during each month. You must assume zero efficiency for the emission capture system and add-on control device for any period of time a deviation specified in §63.3963(c) or (d) occurs in the controlled coating operation, including a deviation during a period of startup, shutdown, or malfunction, unless you have other data indicating the actual efficiency of the emission capture system and add-on control device and the use of these data is approved by the Administrator. Equation 1 of this section treats the materials used during such a deviation as if they were used on an uncontrolled coating operation for the time period of the deviation.

$$H_C = (A_C + B_C + C_C - R_W - H_{VMC}) \left( \frac{CE}{100} \times \frac{DRE}{100} \right) \quad (Eq. 1)$$

Where:

$H_C$  = Mass of organic HAP emission reduction for the controlled coating operation during the month, kg.

$A_C$  = Total mass of organic HAP in the coatings used in the controlled coating operation during the month, kg, as calculated in Equation 1A of this section.

$B_C$  = Total mass of organic HAP in the thinners and/or other additives used in the controlled coating operation during the month, kg, as calculated in Equation 1B of this section.

$C_C$  = Total mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg, as calculated in Equation 1C of this section.

$R_W$  = Total mass of organic HAP in waste materials sent or designated for shipment to a hazardous waste TSDF for treatment or disposal during the compliance period, kg, determined according to §63.3951(e)(4). (You may assign a value of zero to  $R_W$  if you do not wish to use this allowance.)

$H_{UNC}$  = Total mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used during all deviations specified in §63.3963(c) and (d) that occurred during the month in the controlled coating operation, kg, as calculated in Equation 1D of this section.

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent. Use the test methods and procedures specified in §§63.3964 and 63.3965 to measure and record capture efficiency.

DRE = Organic HAP destruction or removal efficiency of the add-on control device, percent. Use the test methods and procedures in §§63.3964 and 63.3966 to measure and record the organic HAP destruction or removal efficiency.

(1) Calculate the mass of organic HAP in the coatings used in the controlled coating operation, kg (lb), using Equation 1A of this section:

$$A_C = \sum_{i=1}^m (Vol_{c,i}) (D_{c,i}) (W_{c,i}) \quad (Eq. 1A)$$

Where:

$A_C$  = Total mass of organic HAP in the coatings used in the controlled coating operation during the month, kg.

$Vol_{c,i}$  = Total volume of coating, i, used during the month, liters.

$D_{c,i}$  = Density of coating, i, kg per liter.

$W_{c,i}$  = Mass fraction of organic HAP in coating, i, kg per kg. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

$m$  = Number of different coatings used.

(2) Calculate the mass of organic HAP in the thinners and/or other additives used in the controlled coating operation, kg (lb), using Equation 1B of this section:

$$B_C = \sum_{j=1}^n (Vol_{t,j}) (D_{t,j}) (W_{t,j}) \quad (Eq. 1B)$$

Where:

$B_C$  = Total mass of organic HAP in the thinners and/or other additives used in the controlled coating operation during the month, kg.

$Vol_{t,j}$  = Total volume of thinner and/or other additive, j, used during the month, liters.

$D_{t,j}$  = Density of thinner and/or other additive, j, kg per liter.

$W_{t,j}$  = Mass fraction of organic HAP in thinner and/or other additive, j, kg per kg. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

n = Number of different thinners and/or other additives used.

(3) Calculate the mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg (lb), using Equation 1C of this section:

$$C_C = \sum_{k=1}^p (Vol_{s,k})(D_{s,k})(W_{s,k}) \quad (Eq. 1C)$$

Where:

$C_C$  = Total mass of organic HAP in the cleaning materials used in the controlled coating operation during the month, kg.

$Vol_{s,k}$  = Total volume of cleaning material, k, used during the month, liters.

$D_{s,k}$  = Density of cleaning material, k, kg per liter.

$W_{s,k}$  = Mass fraction of organic HAP in cleaning material, k, kg per kg.

p = Number of different cleaning materials used.

(4) Calculate the mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used in the controlled coating operation during deviations specified in §63.3963(c) and (d), using Equation 1D of this section:

$$H_{UNC} = \sum_{k=1}^q (Vol_k)(D_k)(W_k) \quad (Eq. 1D)$$

Where:

$H_{UNC}$  = Total mass of organic HAP in the coatings, thinners and/or other additives, and cleaning materials used during all deviations specified in §63.3963(c) and (d) that occurred during the month in the controlled coating operation, kg.

$Vol_h$  = Total volume of coating, thinner and/or other additive, or cleaning material, h, used in the controlled coating operation during deviations, liters.

$D_h$  = Density of coating, thinner and/or other additives, or cleaning material, h, kg per liter.

$W_h$  = Mass fraction of organic HAP in coating, thinner and/or other additives, or cleaning material, h, kg organic HAP per kg coating. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

q = Number of different coatings, thinners and/or other additives, and cleaning materials used.

(i) [Reserved]

(j) Calculate the organic HAP emission reduction for each controlled coating operation using liquid-liquid material balances. For each controlled coating operation using a solvent recovery system for which you conduct liquid-liquid material balances, calculate the organic HAP emission reduction by applying the volatile organic matter collection and recovery efficiency to the mass of organic HAP contained in the coatings, thinners and/or other additives, and cleaning materials that are used in the coating operation controlled by the solvent recovery system during each month. Perform a liquid-liquid material balance for each month as specified in paragraphs (j)(1) through (6) of this section. Calculate the mass of organic HAP emission reduction by the solvent recovery system as specified in paragraph (j)(7) of this section.

(1) For each solvent recovery system, install, calibrate, maintain, and operate according to the manufacturer's specifications, a device that indicates the cumulative amount of volatile organic matter recovered by the solvent recovery system each month. The device must be initially certified by the manufacturer to be accurate to within  $\pm 2.0$  percent of the mass of volatile organic matter recovered.

(2) For each solvent recovery system, determine the mass of volatile organic matter recovered for the month, based on measurement with the device required in paragraph (j)(1) of this section.

(3) Determine the mass fraction of volatile organic matter for each coating, thinner and/or other additive, and cleaning material used in the coating operation controlled by the solvent recovery system during the month, kg volatile organic matter per kg coating. You may determine the volatile organic matter mass fraction using Method 24 of 40 CFR part 60, appendix A, or an EPA approved alternative method, or you may use information provided by the manufacturer or supplier of the coating. In the event of any inconsistency between information provided by the manufacturer or supplier and the results of Method 24 of 40 CFR part 60, appendix A, or an approved alternative method, the test method results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(4) Determine the density of each coating, thinner and/or other additive, and cleaning material used in the coating operation controlled by the solvent recovery system during the month, kg per liter, according to §63.3951(c).

(5) Measure the volume of each coating, thinner and/or other additive, and cleaning material used in the coating operation controlled by the solvent recovery system during the month, liters.

(6) Each month, calculate the solvent recovery system's volatile organic matter collection and recovery efficiency, using Equation 2 of this section:

$$R_{VR} = 100 \frac{M_{VR}}{\sum_{i=1}^m Vol_i D_i W_{c,i} + \sum_{j=1}^n Vol_j D_j W_{t,j} + \sum_{k=1}^p Vol_k D_k W_{s,k}} \quad (Eq. 2)$$

Where:

$R_V$  = Volatile organic matter collection and recovery efficiency of the solvent recovery system during the month, percent.

$M_{VR}$  = Mass of volatile organic matter recovered by the solvent recovery system during the month, kg.

$Vol_i$  = Volume of coating, i, used in the coating operation controlled by the solvent recovery system during the month, liters.

$D_i$  = Density of coating, i, kg per liter.

$WV_{c,i}$  = Mass fraction of volatile organic matter for coating, i, kg volatile organic matter per kg coating. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

$Vol_j$  = Volume of thinner and/or other additive, j, used in the coating operation controlled by the solvent recovery system during the month, liters.

$D_j$  = Density of thinner and/or other additive, j, kg per liter.

$WV_{t,j}$  = Mass fraction of volatile organic matter for thinner and/or other additive, j, kg volatile organic matter per kg thinner and/or other additive. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

$Vol_k$  = Volume of cleaning material, k, used in the coating operation controlled by the solvent recovery system during the month, liters.

$D_k$  = Density of cleaning material, k, kg per liter.

$WV_{s,k}$  = Mass fraction of volatile organic matter for cleaning material, k, kg volatile organic matter per kg cleaning material.

$m$  = Number of different coatings used in the coating operation controlled by the solvent recovery system during the month.

$n$  = Number of different thinners and/or other additives used in the coating operation controlled by the solvent recovery system during the month.

$p$  = Number of different cleaning materials used in the coating operation controlled by the solvent recovery system during the month.

(7) Calculate the mass of organic HAP emission reduction for the coating operation controlled by the solvent recovery system during the month, using Equation 3 of this section and according to paragraphs (j)(7)(i) through (iii) of this section:

$$H_{CSR} = (A_{CSR} + B_{CSR} + C_{CSR}) \left( \frac{R_V}{100} \right) \quad (Eq. 3)$$

Where:

$H_{CSR}$  = Mass of organic HAP emission reduction for the coating operation controlled by the solvent recovery system using a liquid-liquid material balance during the month, kg.

$A_{CSR}$  = Total mass of organic HAP in the coatings used in the coating operation controlled by the solvent recovery system, kg, calculated using Equation 3A of this section.

$B_{CSR}$  = Total mass of organic HAP in the thinners and/or other additives used in the coating operation controlled by the solvent recovery system, kg, calculated using Equation 3B of this section.

$C_{CSR}$  = Total mass of organic HAP in the cleaning materials used in the coating operation controlled by the solvent recovery system, kg, calculated using Equation 3C of this section.

$R_V$  = Volatile organic matter collection and recovery efficiency of the solvent recovery system, percent, from Equation 2 of this section.

(i) Calculate the mass of organic HAP in the coatings used in the coating operation controlled by the solvent recovery system, kg, using Equation 3A of this section.

$$A_{CSR} = \sum_{i=1}^m (Vol_{c,i})(D_{c,i})(W_{c,i}) \quad (Eq. 3A)$$

Where:

$A_{CSR}$  = Total mass of organic HAP in the coatings used in the coating operation controlled by the solvent recovery system during the month, kg.

$Vol_{c,i}$  = Total volume of coating, i, used during the month in the coating operation controlled by the solvent recovery system, liters.

$D_{c,i}$  = Density of coating, i, kg per liter.

$W_{c,i}$  = Mass fraction of organic HAP in coating, i, kg organic HAP per kg coating. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

$m$  = Number of different coatings used.

(ii) Calculate the mass of organic HAP in the thinners and/or other additives used in the coating operation controlled by the solvent recovery system, kg, using Equation 3B of this section:

$$B_{CSR} = \sum_{j=1}^n (Vol_{t,j})(D_{t,j})(W_{t,j}) \quad (Eq. 3B)$$

Where:

$B_{CSR}$  = Total mass of organic HAP in the thinners and/or other additives used in the coating operation controlled by the solvent recovery system during the month, kg.

$Vol_{t,j}$  = Total volume of thinner and/or other additive, j, used during the month in the coating operation controlled by the solvent recovery system, liters.

$D_{t,j}$  = Density of thinner and/or other additive, j, kg per liter.

$W_{t,j}$  = Mass fraction of organic HAP in thinner and/or other additive, j, kg lb organic HAP per kg thinner and/or other additive. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

n = Number of different thinners and/or other additives used.

(iii) Calculate the mass of organic HAP in the cleaning materials used in the coating operation controlled by the solvent recovery system during the month, kg, using Equation 3C of this section:

$$C_{CSR} = \sum_{k=1}^p (Vol_{s,k}) (D_{s,k}) (W_{s,k}) \quad (Eq. 3C)$$

Where:

$C_{CSR}$  = Total mass of organic HAP in the cleaning materials used in the coating operation controlled by the solvent recovery system during the month, kg.

$Vol_{s,k}$  = Total volume of cleaning material, k, used during the month in the coating operation controlled by the solvent recovery system, liters.

$D_{s,k}$  = Density of cleaning material, k, kg per liter.

$W_{s,k}$  = Mass fraction of organic HAP in cleaning material, k, kg organic HAP per kg cleaning material.

p = Number of different cleaning materials used.

(k) Calculate the total volume of coating solids used. Determine the total volume of coating solids used, liters, which is the combined volume of coating solids for all the coatings used during each month in the coating operation or group of coating operations for which you use the emission rate with add-on controls option, using Equation 2 of §63.3951.

(l) Calculate the mass of organic HAP emissions for each month. Determine the mass of organic HAP emissions, kg, during each month, using Equation 4 of this section:

$$H_{HAP} = H_e - \sum_{i=1}^q (H_{c,i}) - \sum_{j=1}^r (H_{CSR,j}) \quad (Eq. 4)$$

where:

$H_{HAP}$  = Total mass of organic HAP emissions for the month, kg.

$H_e$  = Total mass of organic HAP emissions before add-on controls from all the coatings, thinners and/or other additives, and cleaning materials used during the month, kg, determined according to paragraph (f) of this section.

$H_{C,i}$  = Total mass of organic HAP emission reduction for controlled coating operation, i, not using a liquid-liquid material balance, during the month, kg, from Equation 1 of this section.

$H_{CSR,j}$  = Total mass of organic HAP emission reduction for coating operation, j, controlled by a solvent recovery system using a liquid-liquid material balance, during the month, kg, from Equation 3 of this section.

q = Number of controlled coating operations not controlled by a solvent recovery system using a liquid-liquid material balance.

r = Number of coating operations controlled by a solvent recovery system using a liquid-liquid material balance.

(m) Calculate the organic HAP emission rate for the compliance period. Determine the organic HAP emission rate for the compliance period, kg (lb) of organic HAP emitted per liter (gal) coating solids used, using Equation 5 of this section:

$$H_{\text{annual}} = \frac{\sum_{y=1}^n H_{\text{HAP},y}}{\sum_{y=1}^n V_{\text{st},y}} \quad (\text{Eq. 5})$$

Where:

$H_{\text{annual}}$  = Organic HAP emission rate for the compliance period, kg organic HAP emitted per liter coating solids used.

$H_{\text{HAP},y}$  = Organic HAP emissions for month, y, kg, determined according to Equation 4 of this section.

$V_{\text{st},y}$  = Total volume of coating solids used during month, y, liters, from Equation 2 of §63.3951.

y = Identifier for months.

n = Number of full or partial months in the compliance period (for the initial compliance period, n equals 12 if the compliance date falls on the first day of a month; otherwise n equals 13; for all following compliance periods, n equals 12).

(n) Compliance demonstration. The organic HAP emission rate for the initial compliance period, calculated using Equation 5 of this section, must be less than or equal to the applicable emission limit for each subcategory in §63.3890 or the predominant activity or facility-specific emission limit allowed in §63.3890(c). You must keep all records as required by §§63.3930 and 63.3931. As part of the notification of compliance status required by §63.3910, you must identify the coating operation(s) for which you used the emission rate with add-on controls option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because the organic HAP emission rate was less than or equal to the applicable emission limit in §63.3890, and you achieved the operating limits required by §63.3892 and the work practice standards required by §63.3893.

**§ 63.3962 [Reserved]**

**§ 63.3963 How do I demonstrate continuous compliance with the emission limitations?**

(a) To demonstrate continuous compliance with the applicable emission limit in §63.3890, the organic HAP emission rate for each compliance period, determined according to the procedures in §63.3961, must be equal to or less than the applicable emission limit in §63.3890. A compliance period consists of 12 months. Each month after the end of the initial compliance period described in §63.3960 is the end of a compliance period consisting of that month and the preceding 11 months. You must perform the calculations in §63.3961 on a monthly basis using data from the previous 12 months of operation. If you are complying with a facility-specific emission limit under §63.3890(c), you must also perform the calculation using Equation 1 in §63.3890(c)(2) on a monthly basis using the data from the previous 12 months of operation.

(b) If the organic HAP emission rate for any 12-month compliance period exceeded the applicable emission limit in §63.3890, this is a deviation from the emission limitation for that compliance period that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(c) You must demonstrate continuous compliance with each operating limit required by §63.3892 that applies to you, as specified in Table 1 to this subpart, when the coating line is in operation.

(1) If an operating parameter is out of the allowed range specified in Table 1 to this subpart, this is a deviation from the operating limit that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(2) If an operating parameter deviates from the operating limit specified in Table 1 to this subpart, then you must assume that the emission capture system and add-on control device were achieving zero efficiency during the time period of the deviation, unless you have other data indicating the actual efficiency of the emission capture system and add-on control device and the use of these data is approved by the Administrator.

(d) You must meet the requirements for bypass lines in §63.3968(b) for controlled coating operations for which you do not conduct liquid-liquid material balances. If any bypass line is opened and emissions are diverted to the atmosphere when the coating operation is running, this is a deviation that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7). For the purposes of completing the compliance calculations specified in §63.3961(h), you must treat the materials used during a deviation on a controlled coating operation as if they were used on an uncontrolled coating operation for the time period of the deviation as indicated in Equation 1 of §63.3961.

(e) You must demonstrate continuous compliance with the work practice standards in §63.3893. If you did not develop a work practice plan, or you did not implement the plan, or you did not keep the records required by §63.3930(k)(8), this is a deviation from the work practice standards that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(7).

(f) As part of each semiannual compliance report required in §63.3920, you must identify the coating operation(s) for which you used the emission rate with add-on controls option. If there were no deviations from the emission limitations, submit a statement that you were in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable emission limit in §63.3890, and you achieved the operating limits required by §63.3892 and the work practice standards required by §63.3893 during each compliance period.

(g)—(i) [Reserved]

(j) You must maintain records as specified in §§63.3930 and 63.3931.

[69 FR 157, Jan. 2, 2004, as amended at 71 FR 20465, Apr. 20, 2006]

**§ 63.3964 What are the general requirements for performance tests?**

(a) You must conduct each performance test required by §63.3960 according to the requirements in §63.7(e)(1) and under the conditions in this section, unless you obtain a waiver of the performance test according to the provisions in §63.7(h).

(1) Representative coating operation operating conditions. You must conduct the performance test under representative operating conditions for the coating operation. Operations during periods of startup, shutdown, or malfunction and during periods of nonoperation do not constitute representative conditions. You must record the process information that is necessary to document operating conditions during the test and explain why the conditions represent normal operation.

(2) Representative emission capture system and add-on control device operating conditions. You must conduct the performance test when the emission capture system and add-on control device are operating at a representative flow rate, and the add-on control device is operating at a representative inlet concentration. You must record information that is necessary to document emission capture system and add-on control device operating conditions during the test and explain why the conditions represent normal operation.

(b) You must conduct each performance test of an emission capture system according to the requirements in §63.3965. You must conduct each performance test of an add-on control device according to the requirements in §63.3966.

**§ 63.3965 How do I determine the emission capture system efficiency?**

You must use the procedures and test methods in this section to determine capture efficiency as part of the performance test required by §63.3960.

(a) Assuming 100 percent capture efficiency. You may assume the capture system efficiency is 100 percent if both of the conditions in paragraphs (a)(1) and (2) of this section are met:

(1) The capture system meets the criteria in Method 204 of appendix M to 40 CFR part 51 for a PTE and directs all the exhaust gases from the enclosure to an add-on control device.

(2) All coatings, thinners and/or other additives, and cleaning materials used in the coating operation are applied within the capture system; coating solvent flash-off, curing, and drying occurs within the capture system; and the removal or evaporation of cleaning materials from the surfaces they are applied to occurs within the capture system. For example, this criterion is not met if parts enter the open shop environment when being moved between a spray booth and a curing oven.

(b) Measuring capture efficiency. If the capture system does not meet both of the criteria in paragraphs (a)(1) and (2) of this section, then you must use one of the three protocols described in paragraphs (c), (d), and (e) of this section to measure capture efficiency. The capture efficiency measurements use TVH capture efficiency as a surrogate for organic HAP capture efficiency. For the protocols in paragraphs (c) and (d) of this section, the capture efficiency measurement must consist of three test runs. Each test run must be at least 3 hours duration or the length of a production run, whichever is longer, up to 8 hours. For the purposes of this test, a production run means the time required for a single part to go from the beginning to the end of the production, which includes surface preparation activities and drying and curing time.

(c) Liquid-to-uncaptured-gas protocol using a temporary total enclosure or building enclosure. The liquid-to-uncaptured-gas protocol compares the mass of liquid TVH in materials used in the coating operation to the mass of TVH emissions not captured by the emission capture system. Use a temporary total enclosure or a building enclosure and the procedures in paragraphs (c)(1) through (6) of this section to measure emission capture system efficiency using the liquid-to-uncaptured-gas protocol.

(1) Either use a building enclosure or construct an enclosure around the coating operation where coatings, thinners and/or other additives, and cleaning materials are applied, and all areas where emissions from these applied coatings and materials subsequently occur, such as flash-off, curing, and drying areas. The areas of the coating operation where capture devices collect emissions for routing to an add-on control device, such as the entrance and exit areas of an oven or spray booth, must also be inside the enclosure. The enclosure must meet the applicable definition of a temporary total enclosure or building enclosure in Method 204 of appendix M to 40 CFR part 51.

(2) Use Method 204A or 204F of appendix M to 40 CFR part 51 to determine the mass fraction of TVH liquid input from each coating, thinner and/or other additive, and cleaning material used in the coating operation during each capture efficiency test run. To make the determination, substitute TVH for each occurrence of the term VOC in the methods.

(3) Use Equation 1 of this section to calculate the total mass of TVH liquid input from all the coatings, thinners and/or other additives, and cleaning materials used in the coating operation during each capture efficiency test run:

$$TVH_{used} = \sum_{i=1}^n (TVH_i)(Vol_i)(D_i) \quad (Eq. 1)$$

Where:

$TVH_{used}$  = Mass of liquid TVH in materials used in the coating operation during the capture efficiency test run, kg.

$TVH_i$  = Mass fraction of TVH in coating, thinner and/or other additive, or cleaning material, i, that is used in the coating operation during the capture efficiency test run, kg TVH per kg material.

$Vol_i$  = Total volume of coating, thinner and/or other additive, or cleaning material, i, used in the coating operation during the capture efficiency test run, liters.

$D_i$  = Density of coating, thinner and/or other additive, or cleaning material, i, kg material per liter material.

n = Number of different coatings, thinners and/or other additives, and cleaning materials used in the coating operation during the capture efficiency test run.

(4) Use Method 204D or 204E of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions that are not captured by the emission capture system. They are measured as they exit the temporary total enclosure or building enclosure during each capture efficiency test run. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) Use Method 204D of appendix M to 40 CFR part 51 if the enclosure is a temporary total enclosure.

(ii) Use Method 204E of appendix M to 40 CFR 51 if the enclosure is a building enclosure. During the capture efficiency measurement, all organic compound emitting operations inside the building enclosure,

other than the coating operation for which capture efficiency is being determined, must be shut down, but all fans and blowers must be operating normally.

(5) For each capture efficiency test run, determine the percent capture efficiency of the emission capture system using Equation 2 of this section:

$$CE = \frac{(TVH_{used} - TVH_{uncaptured})}{TVH_{used}} \times 100 \quad (\text{Eq. 2})$$

Where:

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent.

$TVH_{used}$  = Total mass of TVH liquid input used in the coating operation during the capture efficiency test run, kg.

$TVH_{uncaptured}$  = Total mass of TVH that is not captured by the emission capture system and that exits from the temporary total enclosure or building enclosure during the capture efficiency test run, kg.

(6) Determine the capture efficiency of the emission capture system as the average of the capture efficiencies measured in the three test runs.

(d) Gas-to-gas protocol using a temporary total enclosure or a building enclosure. The gas-to-gas protocol compares the mass of TVH emissions captured by the emission capture system to the mass of TVH emissions not captured. Use a temporary total enclosure or a building enclosure and the procedures in paragraphs (d)(1) through (5) of this section to measure emission capture system efficiency using the gas-to-gas protocol.

(1) Either use a building enclosure or construct an enclosure around the coating operation where coatings, thinners and/or other additives, and cleaning materials are applied, and all areas where emissions from these applied coatings and materials subsequently occur, such as flash-off, curing, and drying areas. The areas of the coating operation where capture devices collect emissions generated by the coating operation for routing to an add-on control device, such as the entrance and exit areas of an oven or a spray booth, must also be inside the enclosure. The enclosure must meet the applicable definition of a temporary total enclosure or building enclosure in Method 204 of appendix M to 40 CFR part 51.

(2) Use Method 204B or 204C of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions captured by the emission capture system during each capture efficiency test run as measured at the inlet to the add-on control device. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) The sampling points for the Method 204B or 204C measurement must be upstream from the add-on control device and must represent total emissions routed from the capture system and entering the add-on control device.

(ii) If multiple emission streams from the capture system enter the add-on control device without a single common duct, then the emissions entering the add-on control device must be simultaneously measured in each duct and the total emissions entering the add-on control device must be determined.

(3) Use Method 204D or 204E of appendix M to 40 CFR part 51 to measure the total mass, kg, of TVH emissions that are not captured by the emission capture system; they are measured as they exit the

temporary total enclosure or building enclosure during each capture efficiency test run. To make the measurement, substitute TVH for each occurrence of the term VOC in the methods.

(i) Use Method 204D of appendix M to 40 CFR part 51 if the enclosure is a temporary total enclosure.

(ii) Use Method 204E of appendix M to 40 CFR part 51 if the enclosure is a building enclosure. During the capture efficiency measurement, all organic compound emitting operations inside the building enclosure, other than the coating operation for which capture efficiency is being determined, must be shut down, but all fans and blowers must be operating normally.

(4) For each capture efficiency test run, determine the percent capture efficiency of the emission capture system using Equation 3 of this section:

$$CE = \frac{TVH_{\text{captured}}}{(TVH_{\text{captured}} + TVH_{\text{uncaptured}})} \times 100 \quad (\text{Eq. 3})$$

Where:

CE = Capture efficiency of the emission capture system vented to the add-on control device, percent.

$TVH_{\text{captured}}$  = Total mass of TVH captured by the emission capture system as measured at the inlet to the add-on control device during the emission capture efficiency test run, kg.

$TVH_{\text{uncaptured}}$  = Total mass of TVH that is not captured by the emission capture system and that exits from the temporary total enclosure or building enclosure during the capture efficiency test run, kg.

(5) Determine the capture efficiency of the emission capture system as the average of the capture efficiencies measured in the three test runs.

(e) Alternative capture efficiency protocol. As an alternative to the procedures specified in paragraphs (c) and (d) of this section and subject to the approval of the Administrator, you may determine capture efficiency using any other capture efficiency protocol and test methods that satisfy the criteria of either the DQO or LCL approach as described in appendix A to subpart KK of this part.

### **§ 63.3966 How do I determine the add-on control device emission destruction or removal efficiency?**

You must use the procedures and test methods in this section to determine the add-on control device emission destruction or removal efficiency as part of the performance test required by §63.3960. You must conduct three test runs as specified in §63.7(e)(3) and each test run must last at least 1 hour. If the source is a magnet wire coating machine, you may use the procedures in section 3.0 of appendix A to this subpart as an alternative.

(a) For all types of add-on control devices, use the test methods specified in paragraphs (a)(1) through (5) of this section.

(1) Use Method 1 or 1A of appendix A to 40 CFR part 60, as appropriate, to select sampling sites and velocity traverse points.

(2) Use Method 2, 2A, 2C, 2D, 2F, or 2G of appendix A to 40 CFR part 60, as appropriate, to measure gas volumetric flow rate.

(3) Use Method 3, 3A, or 3B of appendix A to 40 CFR part 60, as appropriate, for gas analysis to determine dry molecular weight.

(4) Use Method 4 of appendix A to 40 CFR part 60, to determine stack gas moisture.

(5) Methods for determining gas volumetric flow rate, dry molecular weight, and stack gas moisture must be performed, as applicable, during each test run.

(b) Measure total gaseous organic mass emissions as carbon at the inlet and outlet of the add-on control device simultaneously, using either Method 25 or 25A of appendix A to 40 CFR part 60.

(1) Use Method 25 if the add-on control device is an oxidizer and you expect the total gaseous organic concentration as carbon to be more than 50 parts per million (ppm) at the control device outlet.

(2) Use Method 25A if the add-on control device is an oxidizer and you expect the total gaseous organic concentration as carbon to be 50 ppm or less at the control device outlet.

(3) Use Method 25A if the add-on control device is not an oxidizer.

(c) If two or more add-on control devices are used for the same emission stream, then you must measure emissions at the outlet to the atmosphere of each device. For example, if one add-on control device is a concentrator with an outlet to the atmosphere for the high-volume dilute stream that has been treated by the concentrator, and a second add-on control device is an oxidizer with an outlet to the atmosphere for the low-volume concentrated stream that is treated with the oxidizer, you must measure emissions at the outlet of the oxidizer and the high volume dilute stream outlet of the concentrator.

(d) For each test run, determine the total gaseous organic emissions mass flow rates for the inlet and the outlet of the add-on control device, using Equation 1 of this section. If there is more than one inlet or outlet to the add-on control device, you must calculate the total gaseous organic mass flow rate using Equation 1 of this section for each inlet and each outlet and then total all of the inlet emissions and total all of the outlet emissions:

$$M_f = Q_{sd} C_c (12) (0.0416) (10^{-6}) \quad (Eq. 1)$$

Where:

$M_f$  = Total gaseous organic emissions mass flow rate, kg per hour (h).

$C_c$  = Concentration of organic compounds as carbon in the vent gas, as determined by Method 25 or Method 25A, parts per million by volume (ppmv), dry basis.

$Q_{sd}$  = Volumetric flow rate of gases entering or exiting the add-on control device, as determined by Method 2, 2A, 2C, 2D, 2F, or 2G, dry standard cubic meters/hour (dscm/h).

0.0416 = Conversion factor for molar volume, kg-moles per cubic meter ( $\text{mol/m}^3$ ) (@ 293 Kelvin (K) and 760 millimeters of mercury (mmHg)).

(e) For each test run, determine the add-on control device organic emissions destruction or removal efficiency, using Equation 2 of this section:

$$DRE = \frac{M_{fi} - M_{fo}}{M_{fi}} \times 100 \quad (\text{Eq. 2})$$

Where:

DRE = Organic emissions destruction or removal efficiency of the add-on control device, percent.

$M_{fi}$  = Total gaseous organic emissions mass flow rate at the inlet(s) to the add-on control device, using Equation 1 of this section, kg/h.

$M_{fo}$  = Total gaseous organic emissions mass flow rate at the outlet(s) of the add-on control device, using Equation 1 of this section, kg/h.

(f) Determine the emission destruction or removal efficiency of the add-on control device as the average of the efficiencies determined in the three test runs and calculated in Equation 2 of this section.

**§ 63.3967 How do I establish the emission capture system and add-on control device operating limits during the performance test?**

During the performance test required by §63.3960 and described in §§63.3964, 63.3965, and 63.3966, you must establish the operating limits required by §63.3892 according to this section, unless you have received approval for alternative monitoring and operating limits under §63.8(f) as specified in §63.3892.

(a) Thermal oxidizers. If your add-on control device is a thermal oxidizer, establish the operating limits according to paragraphs (a)(1) and (2) of this section.

(1) During the performance test, you must monitor and record the combustion temperature at least once every 15 minutes during each of the three test runs. You must monitor the temperature in the firebox of the thermal oxidizer or immediately downstream of the firebox before any substantial heat exchange occurs.

(2) Use the data collected during the performance test to calculate and record the average combustion temperature maintained during the performance test. This average combustion temperature is the minimum operating limit for your thermal oxidizer.

(b) Catalytic oxidizers. If your add-on control device is a catalytic oxidizer, establish the operating limits according to either paragraphs (b)(1) and (2) or paragraphs (b)(3) and (4) of this section. If the source is a magnet wire coating machine, you may use the procedures in section 3.0 of appendix A to this subpart as an alternative.

(1) During the performance test, you must monitor and record the temperature just before the catalyst bed and the temperature difference across the catalyst bed at least once every 15 minutes during each of the three test runs.

(2) Use the data collected during the performance test to calculate and record the average temperature just before the catalyst bed and the average temperature difference across the catalyst bed maintained during the performance test. These are the minimum operating limits for your catalytic oxidizer.

(3) You must monitor the temperature at the inlet to the catalyst bed and implement a site-specific inspection and maintenance plan for your catalytic oxidizer as specified in paragraph (b)(4) of this section. During the performance test, you must monitor and record the temperature just before the catalyst bed at least once every 15 minutes during each of the three test runs. Use the data collected during the

performance test to calculate and record the average temperature just before the catalyst bed during the performance test. This is the minimum operating limit for your catalytic oxidizer.

(4) You must develop and implement an inspection and maintenance plan for your catalytic oxidizer(s) for which you elect to monitor according to paragraph (b)(3) of this section. The plan must address, at a minimum, the elements specified in paragraphs (b)(4)(i) through (iii) of this section.

(i) Annual sampling and analysis of the catalyst activity ( i.e., conversion efficiency) following the manufacturer's or catalyst supplier's recommended procedures. If problems are found during the catalyst activity test, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations.

(ii) Monthly external inspection of the catalytic oxidizer system, including the burner assembly and fuel supply lines for problems and, as necessary, adjust the equipment to assure proper air-to-fuel mixtures.

(iii) Annual internal inspection of the catalyst bed to check for channeling, abrasion, and settling. If problems are found during the annual internal inspection of the catalyst, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations. If the catalyst bed is replaced and is not of like or better kind and quality as the old catalyst then you must conduct a new performance test to determine destruction efficiency according to §63.3966. If a catalyst bed is replaced and the replacement catalyst is of like or better kind and quality as the old catalyst, then a new performance test to determine destruction efficiency is not required and you may continue to use the previously established operating limits for that catalytic oxidizer.

(c) Regenerative carbon adsorbers. If your add-on control device is a regenerative carbon adsorber, establish the operating limits according to paragraphs (c)(1) and (2) of this section.

(1) You must monitor and record the total regeneration desorbing gas ( e.g., steam or nitrogen) mass flow for each regeneration cycle, and the carbon bed temperature after each carbon bed regeneration and cooling cycle for the regeneration cycle either immediately preceding or immediately following the performance test.

(2) The operating limits for your regenerative carbon adsorber are the minimum total desorbing gas mass flow recorded during the regeneration cycle and the maximum carbon bed temperature recorded after the cooling cycle.

(d) Condensers. If your add-on control device is a condenser, establish the operating limits according to paragraphs (d)(1) and (2) of this section.

(1) During the performance test, you must monitor and record the condenser outlet (product side) gas temperature at least once every 15 minutes during each of the three test runs.

(2) Use the data collected during the performance test to calculate and record the average condenser outlet (product side) gas temperature maintained during the performance test. This average condenser outlet gas temperature is the maximum operating limit for your condenser.

(e) Concentrators. If your add-on control device includes a concentrator, you must establish operating limits for the concentrator according to paragraphs (e)(1) through (4) of this section.

(1) During the performance test, you must monitor and record the desorption concentrate stream gas temperature at least once every 15 minutes during each of the three runs of the performance test.

(2) Use the data collected during the performance test to calculate and record the average temperature. This is the minimum operating limit for the desorption concentrate gas stream temperature.

(3) During the performance test, you must monitor and record the pressure drop of the dilute stream across the concentrator at least once every 15 minutes during each of the three runs of the performance test.

(4) Use the data collected during the performance test to calculate and record the average pressure drop. This is the minimum operating limit for the dilute stream across the concentrator.

(f) Emission capture systems. For each capture device that is not part of a PTE that meets the criteria of §63.3965(a), establish an operating limit for either the gas volumetric flow rate or duct static pressure, as specified in paragraphs (f)(1) and (2) of this section. The operating limit for a PTE is specified in Table 1 to this subpart. If the source is a magnet wire coating machine, you may use the procedures in section 2.0 of appendix A to this subpart as an alternative.

(1) During the capture efficiency determination required by §63.3960 and described in §§63.3964 and 63.3965, you must monitor and record either the gas volumetric flow rate or the duct static pressure for each separate capture device in your emission capture system at least once every 15 minutes during each of the three test runs at a point in the duct between the capture device and the add-on control device inlet.

(2) Calculate and record the average gas volumetric flow rate or duct static pressure for the three test runs for each capture device. This average gas volumetric flow rate or duct static pressure is the minimum operating limit for that specific capture device.

#### **§ 63.3968 What are the requirements for continuous parameter monitoring system installation, operation, and maintenance?**

(a) General. You must install, operate, and maintain each CPMS specified in paragraphs (c), (e), (f), and (g) of this section according to paragraphs (a)(1) through (6) of this section. You must install, operate, and maintain each CPMS specified in paragraphs (b) and (d) of this section according to paragraphs (a)(3) through (5) of this section.

(1) The CPMS must complete a minimum of one cycle of operation for each successive 15-minute period. You must have a minimum of four equally spaced successive cycles of CPMS operation in 1 hour.

(2) You must determine the average of all recorded readings for each successive 3-hour period of the emission capture system and add-on control device operation.

(3) You must record the results of each inspection, calibration, and validation check of the CPMS.

(4) You must maintain the CPMS at all times and have available necessary parts for routine repairs of the monitoring equipment.

(5) You must operate the CPMS and collect emission capture system and add-on control device parameter data at all times that a controlled coating operation is operating, except during monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, if applicable, calibration checks and required zero and span adjustments).

(6) You must not use emission capture system or add-on control device parameter data recorded during monitoring malfunctions, associated repairs, out-of-control periods, or required quality assurance or control activities when calculating data averages. You must use all the data collected during all other

periods in calculating the data averages for determining compliance with the emission capture system and add-on control device operating limits.

(7) A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the CPMS to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions. Any period for which the monitoring system is out-of-control and data are not available for required calculations is a deviation from the monitoring requirements.

(b) Capture system bypass line. You must meet the requirements of paragraphs (b)(1) and (2) of this section for each emission capture system that contains bypass lines that could divert emissions away from the add-on control device to the atmosphere.

(1) You must monitor or secure the valve or closure mechanism controlling the bypass line in a nondiverting position in such a way that the valve or closure mechanism cannot be opened without creating a record that the valve was opened. The method used to monitor or secure the valve or closure mechanism must meet one of the requirements specified in paragraphs (b)(1)(i) through (v) of this section.

(i) Flow control position indicator. Install, calibrate, maintain, and operate according to the manufacturer's specifications a flow control position indicator that takes a reading at least once every 15 minutes and provides a record indicating whether the emissions are directed to the add-on control device or diverted from the add-on control device. The time of occurrence and flow control position must be recorded, as well as every time the flow direction is changed. The flow control position indicator must be installed at the entrance to any bypass line that could divert the emissions away from the add-on control device to the atmosphere.

(ii) Car-seal or lock-and-key valve closures. Secure any bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. You must visually inspect the seal or closure mechanism at least once every month to ensure that the valve is maintained in the closed position, and the emissions are not diverted away from the add-on control device to the atmosphere.

(iii) Valve closure monitoring. Ensure that any bypass line valve is in the closed (nondiverting) position through monitoring of valve position at least once every 15 minutes. You must inspect the monitoring system at least once every month to verify that the monitor will indicate valve position.

(iv) Automatic shutdown system. Use an automatic shutdown system in which the coating operation is stopped when flow is diverted by the bypass line away from the add-on control device to the atmosphere when the coating operation is running. You must inspect the automatic shutdown system at least once every month to verify that it will detect diversions of flow and shut down the coating operation.

(v) Flow direction indicator. Install, calibrate, maintain, and operate according to the manufacturer's specifications a flow direction indicator that takes a reading at least once every 15 minutes and provides a record indicating whether the emissions are directed to the add-on control device or diverted from the add-on control device. Each time the flow direction changes, the next reading of the time of occurrence and flow direction must be recorded. The flow direction indicator must be installed in each bypass line or air makeup supply line that could divert the emissions away from the add-on control device to the atmosphere.

(2) If any bypass line is opened, you must include a description of why the bypass line was opened and the length of time it remained open in the semiannual compliance reports required in §63.3920.

(c) Thermal oxidizers and catalytic oxidizers. If you are using a thermal oxidizer or catalytic oxidizer as an add-on control device (including those used with concentrators or with carbon adsorbers to treat

desorbed concentrate streams), you must comply with the requirements in paragraphs (c)(1) through (3) of this section:

(1) For a thermal oxidizer, install a gas temperature monitor in the firebox of the thermal oxidizer or in the duct immediately downstream of the firebox before any substantial heat exchange occurs.

(2) For a catalytic oxidizer, install gas temperature monitors upstream and/or downstream of the catalyst bed as required in §63.3967(b).

(3) For all thermal oxidizers and catalytic oxidizers, you must meet the requirements in paragraphs (a) and (c)(3)(i) through (v) of this section for each gas temperature monitoring device.

(i) Locate the temperature sensor in a position that provides a representative temperature.

(ii) Use a temperature sensor with a measurement sensitivity of 5 degrees Fahrenheit or 1.0 percent of the temperature value, whichever is larger.

(iii) Before using the sensor for the first time or when relocating or replacing the sensor, perform a validation check by comparing the sensor output to a calibrated temperature measurement device or by comparing the sensor output to a simulated temperature.

(iv) Conduct an accuracy audit every quarter and after every deviation. Accuracy audit methods include comparisons of sensor output to redundant temperature sensors, to calibrated temperature measurement devices, or to temperature simulation devices.

(v) Conduct a visual inspection of each sensor every quarter if redundant temperature sensors are not used.

(d) Regenerative carbon adsorbers. If you are using a regenerative carbon adsorber as an add-on control device, you must monitor the total regeneration desorbing gas ( e.g., steam or nitrogen) mass flow for each regeneration cycle, the carbon bed temperature after each regeneration and cooling cycle, and comply with paragraphs (a)(3) through (5) and (d)(1) through (3) of this section.

(1) The regeneration desorbing gas mass flow monitor must be an integrating device having a measurement sensitivity of plus or minus 10 percent capable of recording the total regeneration desorbing gas mass flow for each regeneration cycle.

(2) The carbon bed temperature monitor must be capable of recording the temperature within 15 minutes of completing any carbon bed cooling cycle.

(3) For all regenerative carbon adsorbers, you must meet the requirements in paragraphs (c)(3)(i) through (v) of this section for each temperature monitoring device.

(e) Condensers. If you are using a condenser, you must monitor the condenser outlet (product side) gas temperature and comply with paragraphs (a) and (e)(1) and (2) of this section.

(1) The temperature monitor must provide a gas temperature record at least once every 15 minutes.

(2) For all condensers, you must meet the requirements in paragraphs (c)(3)(i) through (v) of this section for each temperature monitoring device.

(f) Concentrators. If you are using a concentrator, such as a zeolite wheel or rotary carbon bed concentrator, you must comply with the requirements in paragraphs (f)(1) and (2) of this section.

(1) You must install a temperature monitor in the desorption gas stream. The temperature monitor must meet the requirements in paragraphs (a) and (c)(3) of this section.

(2) You must install a device to monitor pressure drop across the zeolite wheel or rotary carbon bed. The pressure monitoring device must meet the requirements in paragraphs (a) and (g)(2) of this section.

(g) Emission capture systems. The capture system monitoring system must comply with the applicable requirements in paragraphs (g)(1) and (2) of this section. If the source is a magnet wire coating machine, you may use the procedures in section 2.0 of appendix A to this subpart as an alternative.

(1) For each flow measurement device, you must meet the requirements in paragraphs (a) and (g)(1)(i) through (vii) of this section.

(i) Locate a flow sensor in a position that provides a representative flow measurement in the duct from each capture device in the emission capture system to the add-on control device.

(ii) Use a flow sensor with an accuracy of at least 10 percent of the flow.

(iii) Perform an initial sensor calibration in accordance with the manufacturer's requirements.

(iv) Perform a validation check before initial use or upon relocation or replacement of a sensor. Validation checks include comparison of sensor values with electronic signal simulations or via relative accuracy testing.

(v) Conduct an accuracy audit every quarter and after every deviation. Accuracy audit methods include comparisons of sensor values with electronic signal simulations or via relative accuracy testing.

(vi) Perform leak checks monthly.

(vii) Perform visual inspections of the sensor system quarterly if there is no redundant sensor.

(2) For each pressure drop measurement device, you must comply with the requirements in paragraphs (a) and (g)(2)(i) through (vii) of this section.

(i) Locate the pressure sensor(s) in or as close to a position that provides a representative measurement of the pressure drop across each opening you are monitoring.

(ii) Use a pressure sensor with an accuracy of at least 0.5 inches of water column or 5 percent of the measured value, whichever is larger.

(iii) Perform an initial calibration of the sensor according to the manufacturer's requirements.

(iv) Conduct a validation check before initial operation or upon relocation or replacement of a sensor. Validation checks include comparison of sensor values to calibrated pressure measurement devices or to pressure simulation using calibrated pressure sources.

(v) Conduct accuracy audits every quarter and after every deviation. Accuracy audits include comparison of sensor values to calibrated pressure measurement devices or to pressure simulation using calibrated pressure sources.

(vi) Perform monthly leak checks on pressure connections. A pressure of at least 1.0 inches of water column to the connection must yield a stable sensor result for at least 15 seconds.

(vii) Perform a visual inspection of the sensor at least monthly if there is no redundant sensor.

### **Other Requirements and Information**

#### **§ 63.3980 Who implements and enforces this subpart?**

(a) This subpart can be implemented and enforced by us, the U.S. Environmental Protection Agency (EPA), or a delegated authority such as your State, local, or tribal agency. If the Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the EPA) has the authority to implement and enforce this subpart. You should contact your EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are listed in paragraphs (c)(1) through (4) of this section:

(1) Approval of alternatives to the requirements in §63.3881 through 3883 and §63.3890 through 3893.

(2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.

(3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.

(4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

#### **§ 63.3981 What definitions apply to this subpart?**

Terms used in this subpart are defined in the CAA, in 40 CFR 63.2, and in this section as follows:

**Additive** means a material that is added to a coating after purchase from a supplier ( e.g., catalysts, activators, accelerators).

**Add-on control** means an air pollution control device, such as a thermal oxidizer or carbon adsorber, that reduces pollution in an air stream by destruction or removal before discharge to the atmosphere.

**Adhesive, adhesive coating** means any chemical substance that is applied for the purpose of bonding two surfaces together. Products used on humans and animals, adhesive tape, contact paper, or any other product with an adhesive incorporated onto or in an inert substrate shall not be considered adhesives under this subpart.

**Assembled on-road vehicle coating** means any coating operation in which coating is applied to the surface of some component or surface of a fully assembled motor vehicle or trailer intended for on-road use including, but not limited to, components or surfaces on automobiles and light-duty trucks that have been repaired after a collision or otherwise repainted, fleet delivery trucks, and motor homes and other recreational vehicles (including camping trailers and fifth wheels). Assembled on-road vehicle coating includes the concurrent coating of parts of the assembled on-road vehicle that are painted off-vehicle to

protect systems, equipment, or to allow full coverage. Assembled on-road vehicle coating does not include surface coating operations that meet the applicability criteria of the automobiles and light-duty trucks NESHAP. Assembled on-road vehicle coating also does not include the use of adhesives, sealants, and caulks used in assembling on-road vehicles.

Capture device means a hood, enclosure, room, floor sweep, or other means of containing or collecting emissions and directing those emissions into an add-on air pollution control device.

Capture efficiency or capture system efficiency means the portion (expressed as a percentage) of the pollutants from an emission source that is delivered to an add-on control device.

Capture system means one or more capture devices intended to collect emissions generated by a coating operation in the use of coatings or cleaning materials, both at the point of application and at subsequent points where emissions from the coatings and cleaning materials occur, such as flashoff, drying, or curing. As used in this subpart, multiple capture devices that collect emissions generated by a coating operation are considered a single capture system.

Cleaning material means a solvent used to remove contaminants and other materials, such as dirt, grease, oil, and dried or wet coating ( e.g., depainting or paint stripping), from a substrate before or after coating application or from equipment associated with a coating operation, such as spray booths, spray guns, racks, tanks, and hangers. Thus, it includes any cleaning material used on substrates or equipment or both.

Coating means a material applied to a substrate for decorative, protective, or functional purposes. Such materials include, but are not limited to, paints, sealants, liquid plastic coatings, caulks, inks, adhesives, and maskants. Decorative, protective, or functional materials that consist only of protective oils for metal, acids, bases, or any combination of these substances, or paper film or plastic film which may be pre-coated with an adhesive by the film manufacturer, are not considered coatings for the purposes of this subpart. A liquid plastic coating means a coating made from fine particle-size polyvinyl chloride (PVC) in solution (also referred to as a plastisol).

Coating operation means equipment used to apply cleaning materials to a substrate to prepare it for coating application (surface preparation) or to remove dried coating; to apply coating to a substrate (coating application) and to dry or cure the coating after application; or to clean coating operation equipment (equipment cleaning). A single coating operation may include any combination of these types of equipment, but always includes at least the point at which a given quantity of coating or cleaning material is applied to a given part and all subsequent points in the affected source where organic HAP are emitted from the specific quantity of coating or cleaning material on the specific part. There may be multiple coating operations in an affected source. Coating application with handheld, non-refillable aerosol containers, touch-up markers, or marking pens is not a coating operation for the purposes of this subpart.

Coatings solids means the nonvolatile portion of the coating that makes up the dry film.

Continuous parameter monitoring system (CPMS) means the total equipment that may be required to meet the data acquisition and availability requirements of this subpart, used to sample, condition (if applicable), analyze, and provide a record of coating operation, or capture system, or add-on control device parameters.

Controlled coating operation means a coating operation from which some or all of the organic HAP emissions are routed through an emission capture system and add-on control device.

Deviation means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

(1) Fails to meet any requirement or obligation established by this subpart including but not limited to, any emission limit or operating limit or work practice standard;

(2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or

(3) Fails to meet any emission limit, or operating limit, or work practice standard in this subpart during startup, shutdown, or malfunction, regardless of whether or not such failure is permitted by this subpart.

Emission limitation means the aggregate of all requirements associated with a compliance option including emission limit, operating limit, work practice standard, etc.

Enclosure means a structure that surrounds a source of emissions and captures and directs the emissions to an add-on control device.

Exempt compound means a specific compound that is not considered a VOC due to negligible photochemical reactivity. The exempt compounds are listed in 40 CFR 51.100(s).

Extreme performance fluoropolymer coating means coatings that are formulated systems based on fluoropolymer resins which often contain bonding matrix polymers dissolved in non-aqueous solvents as well as other ingredients. Extreme performance fluoropolymer coatings are typically used when one or more critical performance criteria are required including, but not limited to a nonstick low-energy surface, dry film lubrication, high resistance to chemical attack, extremely wide operating temperature, high electrical insulating properties, or that the surface comply with government ( e.g., USDA, FDA) or third party specifications for health, safety, reliability, or performance. Once applied to a substrate, extreme performance fluoropolymer coatings undergo a curing process that typically requires high temperatures, a chemical reaction, or other specialized technology.

Facility maintenance means the routine repair or renovation (including the surface coating) of the tools, equipment, machinery, and structures that comprise the infrastructure of the affected facility and that are necessary for the facility to function in its intended capacity.

General use coating means any material that meets the definition of coating but does not meet the definition of high performance coating, rubber-to-metal coating, magnet wire coating, or extreme performance fluoropolymer coating as defined in this section.

High performance architectural coating means any coating applied to architectural subsections which is required to meet the specifications of Architectural Aluminum Manufacturer's Association's publication number AAMA 605.2-2000.

High performance coating means any coating that meets the definition of high performance architectural coating or high temperature coating in this section.

High temperature coating means any coating applied to a substrate which during normal use must withstand temperatures of at least 538 degrees Celsius (1000 degrees Fahrenheit).

Hobby shop means any surface coating operation, located at an affected source, that is used exclusively for personal, noncommercial purposes by the affected source's employees or assigned personnel.

Magnet wire coatings, commonly referred to as magnet wire enamels, are applied to a continuous strand of wire which will be used to make turns (windings) in electrical devices such as coils, transformers, or motors. Magnet wire coatings provide high dielectric strength and turn-to-turn conductor insulation. This

allows the turns of an electrical device to be placed in close proximity to one another which leads to increased coil effectiveness and electrical efficiency.

Magnet wire coating machine means equipment which applies and cures magnet wire coatings.

Manufacturer's formulation data means data on a material (such as a coating) that are supplied by the material manufacturer based on knowledge of the ingredients used to manufacture that material, rather than based on testing of the material with the test methods specified in §63.3941. Manufacturer's formulation data may include, but are not limited to, information on density, organic HAP content, volatile organic matter content, and coating solids content.

Mass fraction of organic HAP means the ratio of the mass of organic HAP to the mass of a material in which it is contained, expressed as kg of organic HAP per kg of material.

Month means a calendar month or a pre-specified period of 28 days to 35 days to allow for flexibility in recordkeeping when data are based on a business accounting period.

Non-HAP coating means, for the purposes of this subpart, a coating that contains no more than 0.1 percent by mass of any individual organic HAP that is an OSHA-defined carcinogen as specified in 29 CFR 1910.1200(d)(4) and no more than 1.0 percent by mass for any other individual HAP.

Organic HAP content means the mass of organic HAP emitted per volume of coating solids used for a coating calculated using Equation 2 of §63.3941. The organic HAP content is determined for the coating in the condition it is in when received from its manufacturer or supplier and does not account for any alteration after receipt. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, organic HAP content is the mass of organic HAP that is emitted, rather than the organic HAP content of the coating as it is received.

Permanent total enclosure (PTE) means a permanently installed enclosure that meets the criteria of Method 204 of appendix M, 40 CFR part 51, for a PTE and that directs all the exhaust gases from the enclosure to an add-on control device.

Personal watercraft means a vessel (boat) which uses an inboard motor powering a water jet pump as its primary source of motive power and which is designed to be operated by a person or persons sitting, standing, or kneeling on the vessel, rather than in the conventional manner of sitting or standing inside the vessel.

Protective oil means an organic material that is applied to metal for the purpose of providing lubrication or protection from corrosion without forming a solid film. This definition of protective oil includes, but is not limited to, lubricating oils, evaporative oils (including those that evaporate completely), and extrusion oils. Protective oils used on miscellaneous metal parts and products include magnet wire lubricants and soft temporary protective coatings that are removed prior to installation or further assembly of a part or component.

Reactive adhesive means adhesive systems composed, in part, of volatile monomers that react during the adhesive curing reaction, and, as a result, do not evolve from the film during use. These volatile components instead become integral parts of the adhesive through chemical reaction. At least 70 percent of the liquid components of the system, excluding water, react during the process.

Research or laboratory facility means a facility whose primary purpose is for research and development of new processes and products, that is conducted under the close supervision of technically trained personnel, and is not engaged in the manufacture of final or intermediate products for commercial purposes, except in a de minimis manner.

Responsible official means responsible official as defined in 40 CFR 70.2.

Rubber-to-metal coatings are coatings that contain heat-activated polymer systems in either solvent or water that, when applied to metal substrates, dry to a non-tacky surface and react chemically with the rubber and metal during a vulcanization process.

Startup, initial means the first time equipment is brought online in a facility.

Surface preparation means use of a cleaning material on a portion of or all of a substrate. This includes use of a cleaning material to remove dried coating, which is sometimes called depainting.

Temporary total enclosure means an enclosure constructed for the purpose of measuring the capture efficiency of pollutants emitted from a given source as defined in Method 204 of appendix M, 40 CFR part 51.

Thinner means an organic solvent that is added to a coating after the coating is received from the supplier.

Total volatile hydrocarbon (TVH) means the total amount of nonaqueous volatile organic matter determined according to Methods 204 and 204A through 204F of appendix M to 40 CFR part 51 and substituting the term TVH each place in the methods where the term VOC is used. The TVH includes both VOC and non-VOC.

Uncontrolled coating operation means a coating operation from which none of the organic HAP emissions are routed through an emission capture system and add-on control device.

Volatile organic compound (VOC) means any compound defined as VOC in 40 CFR 51.100(s).

Volume fraction of coating solids means the ratio of the volume of coating solids (also known as the volume of nonvolatiles) to the volume of a coating in which it is contained; liters (gal) of coating solids per liter (gal) of coating.

Wastewater means water that is generated in a coating operation and is collected, stored, or treated prior to being discarded or discharged.

**Table 1 to Subpart Mmmm of Part 63—Operating Limits if Using the Emission Rate With Add-On Controls Option**

If you are required to comply with operating limits by §63.3892(c), you must comply with the applicable operating limits in the following table:

<b>For the following device . . .</b>	<b>You must meet the following operating limit . . .</b>	<b>And you must demonstrate continuous compliance with the operating limit by . . .</b>
1. Thermal oxidizer	a. The average combustion temperature in any 3-hour period must not fall below the combustion temperature limit established according to §63.3967(a)	i. Collecting the combustion temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average combustion temperature at or above the temperature limit.
2. Catalytic oxidizer	a. The average temperature measured just before the catalyst bed	i. Collecting the temperature data according to §63.3968(c);

	in any 3-hour period must not fall below the limit established according to §63.3967(b) (for magnet wire coating machines, temperature can be monitored before or after the catalyst bed); and either	ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average temperature before (or for magnet wire coating machines after) the catalyst bed at or above the temperature limit.
	b. Ensure that the average temperature difference across the catalyst bed in any 3-hour period does not fall below the temperature difference limit established according to §63.3967(b) (2); or	i. Collecting the temperature data according to §63.3968(c); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average temperature difference at or above the temperature difference limit.
	c. Develop and implement an inspection and maintenance plan according to §63.3967(b)(4) or for magnet wire coating machines according to section 3.0 of appendix A to this subpart	i. Maintaining and up-to-date inspection and maintenance plan, records of annual catalyst activity checks, records of monthly inspections of the oxidizer system, and records of the annual internal inspections of the catalyst bed. If a problem is discovered during a monthly or annual inspection required by §63.3967(b)(4) or for magnet wire coating machines by section 3.0 of appendix A to this subpart, you must take corrective action as soon as practicable consistent with the manufacturer's recommendations.
3. Regenerative carbon adsorber	a. The total regeneration desorbing gas ( e.g., steam or nitrogen) mass flow for each carbon bed regeneration cycle must not fall below the total regeneration desorbing gas mass flow limit established according to §63.3967(c); and	i. Measuring the total regeneration desorbing gas ( e.g., steam or nitrogen) mass flow for each regeneration cycle according to §63.3968(d); and ii. Maintaining the total regeneration desorbing gas mass flow at or above the mass flow limit.
	b. The temperature of the carbon bed, after completing each regeneration and any cooling cycle, must not exceed the carbon bed temperature limit established according to §63.3967(c)	i. Measuring the temperature of the carbon bed after completing each regeneration and any cooling cycle according to §63.3968(d); and ii. Operating the carbon beds such that each carbon bed is not returned to service until completing each regeneration and any cooling cycle until the recorded temperature of the carbon bed is at or below the temperature limit.
4. Condenser	a. The average condenser outlet (product side) gas temperature in any 3-hour period must not exceed the temperature limit established according to §63.3967(d)	i. Collecting the condenser outlet (product side) gas temperature according to §63.3968(e); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average gas temperature at the outlet at or below the temperature limit.
5. Concentrators, including zeolite wheels and rotary	a. The average gas temperature of the desorption concentrate stream in any 3-hour period must not fall below	i. Collecting the temperature data according to §63.3968(f); ii. Reducing the data to 3-hour block averages;

carbon adsorbers	the limit established according to §63.3967(e); and	and iii. Maintaining the 3-hour average temperature at or above the temperature limit.
	b. The average pressure drop of the dilute stream across the concentrator in any 3-hour period must not fall below the limit established according to §63.3967(e)	i. Collecting the pressure drop data according to 63.3968(f); ii. Reducing the pressure drop data to 3-hour block averages; and iii. Maintaining the 3-hour average pressure drop at or above the pressure drop limit.
6. Emission capture system that is a PTE according to §63.3965(a)	a. The direction of the air flow at all times must be into the enclosure; and either	i. Collecting the direction of air flow, and either the facial velocity of air through all natural draft openings according to §63.3968(b)(1) or the pressure drop across the enclosure according to §63.3968(g)(2); and ii. Maintaining the facial velocity of air flow through all natural draft openings or the pressure drop at or above the facial velocity limit or pressure drop limit, and maintaining the direction of air flow into the enclosure at all times.
	b. The average facial velocity of air through all natural draft openings in the enclosure must be at least 200 feet per minutes; or	i. See items 6.a.i and 6.a.ii.
	c. The pressure drop across the enclosure must be at least 0.007 inch H <sub>2</sub> O, as established in Method 204 of appendix M to 40 CFR part 51	i. See items 6.a.i and 6.a.ii.
7. Emission capture system that is not a PTE according to §63.3965(a)	a. The average gas volumetric flow rate or duct static pressure in each duct between a capture device and add-on control device inlet in any 3-hour period must not fall below the average volumetric flow rate or duct static pressure limit established for that capture device according to §63.3967(f)	i. Collecting the gas volumetric flow rate or duct static pressure for each capture device according to §63.3968(g); ii. Reducing the data to 3-hour block averages; and iii. Maintaining the 3-hour average gas volumetric flow rate or duct static pressure for each capture device at or above the gas volumetric flow rate or duct static pressure limited.

**Table 2 to Subpart MMMM of Part 63—Applicability of General Provisions to Subpart MMMM of Part 63**

You must comply with the applicable General Provisions requirements according to the following table:

<b>Citation</b>	<b>Subject</b>	<b>Applicable to subpart MMMM</b>	<b>Explanation</b>
§63.1(a)(1)–(14)	General Applicability	Yes	

§63.1(b)(1)–(3)	Initial Applicability Determination	Yes	Applicability to subpart M MMM is also specified in §63.3881.
§63.1(c)(1)	Applicability After Standard Established	Yes	
§63.1(c)(2)–(3)	Applicability of Permit Program for Area Sources	No	Area sources are not subject to subpart M MMM.
§63.1(c)(4)–(5)	Extensions and Notifications	Yes	
§63.1(e)	Applicability of Permit Program Before Relevant Standard is Set	Yes	
§63.2	Definitions	Yes	Additional definitions are specified in §63.3981.
§63.1(a)–(c)	Units and Abbreviations	Yes	
§63.4(a)(1)–(5)	Prohibited Activities	Yes	
§63.4(b)–(c)	Circumvention/Severability	Yes	
§63.5(a)	Construction/Reconstruction	Yes	
§63.5(b)(1)–(6)	Requirements for Existing Newly Constructed, and Reconstructed Sources	Yes	
§63.5(d)	Application for Approval of Construction/Reconstruction	Yes	
§63.5(e)	Approval of Construction/Reconstruction	Yes	
§63.5(f)	Approval of Construction/Reconstruction Based on Prior State Review	Yes	
§63.6(a)	Compliance With Standards and Maintenance Requirements—Applicability	Yes	
§63.6(b)(1)–(7)	Compliance Dates for New and Reconstructed Sources	Yes	Section 63.3883 specifies the compliance dates.
§63.6(c)(1)–(5)	Compliance Dates for Existing Sources	Yes	Section 63.3883 specifies the compliance dates.
§63.6(e)(1)–(2)	Operation and Maintenance	Yes	
§63.6(e)(3)	Startup, Shutdown, and Malfunction Plan	Yes	Only sources using an add-on control device to comply with the standard must complete startup, shutdown, and malfunction plans.

§63.6(f)(1)	Compliance Except During Startup, Shutdown, and Malfunction	Yes	Applies only to sources using an add-on control device to comply with the standard.
§63.6(f)(2)–(3)	Methods for Determining Compliance.	Yes	
§63.6(g)(1)–(3)	Use of an Alternative Standard	Yes	
§63.6(h)	Compliance With Opacity/Visible Emission Standards	No	Subpart M MMM does not establish opacity standards and does not require continuous opacity monitoring systems (COMS).
§63.6(i)(1)–(16)	Extension of Compliance	Yes	
§63.6(j)	Presidential Compliance Exemption	Yes	
§63.7(a)(1)	Performance Test Requirements—Applicability	Yes	Applies to all affected sources. Additional requirements for performance testing are specified in §§63.3964, 63.3965, and 63.3966.
§63.7(a)(2)	Performance Test Requirements—Dates	Yes	Applies only to performance tests for capture system and control device efficiency at sources using these to comply with the standard. Section 63.3960 specifies the schedule for performance test requirements that are earlier than those specified in §63.7(a)(2).
§63.7(a)(3)	Performance Tests Required By the Administrator	Yes	
§63.7(b)–(e)	Performance Test Requirements—Notification, Quality Assurance, Facilities Necessary for Safe Testing, Conditions During Test	Yes	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§63.7(f)	Performance Test Requirements—Use of Alternative Test Method	Yes	Applies to all test methods except those used to determine capture system efficiency.
§63.7(g)–(h)	Performance Test Requirements—Data Analysis, Recordkeeping, Reporting, Waiver of Test	Yes	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§63.8(a)(1)–(3)	Monitoring Requirements—Applicability	Yes	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for monitoring are specified in §63.3968.

§63.8(a)(4)	Additional Monitoring Requirements	No	Subpart MMMM does not have monitoring requirements for flares.
§63.8(b)	Conduct of Monitoring	Yes	
§63.8(c)(1)–(3)	Continuous Monitoring Systems (CMS) Operation and Maintenance	Yes	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for CMS operations and maintenance are specified in §63.3968.
§63.8(c)(4)	CMS	No	§63.3968 specifies the requirements for the operation of CMS for capture systems and add-on control devices at sources using these to comply.
§63.8(c)(5)	COMS	No	Subpart MMMM does not have opacity or visible emission standards.
§63.8(c)(6)	CMS Requirements	No	Section 63.3968 specifies the requirements for monitoring systems for capture systems and add-on control devices at sources using these to comply.
§63.8(c)(7)	CMS Out-of-Control Periods	Yes	
§63.8(c)(8)	CMS Out-of-Control Periods and Reporting	No	§63.3920 requires reporting of CMS out-of-control periods.
§63.8(d)–(e)	Quality Control Program and CMS Performance Evaluation	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§63.8(f)(1)–(5)	Use of an Alternative Monitoring Method	Yes	
§63.8(f)(6)	Alternative to Relative Accuracy Test	No	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§63.8(g)(1)–(5)	Data Reduction	No	Sections 63.3967 and 63.3968 specify monitoring data reduction.
§63.9(a)–(d)	Notification Requirements	Yes	
§63.9(e)	Notification of Performance Test	Yes	Applies only to capture system and add-on control device performance tests at sources using these to comply with the standard.
§63.9(f)	Notification of Visible Emissions/Opacity Test	No	Subpart MMMM does not have opacity or visible emissions standards.
§63.9(g)(1)–(3)	Additional Notifications When Using CMS	No	Subpart MMMM does not require the use of continuous emissions

			monitoring systems.
§63.9(h)	Notification of Compliance Status	Yes	Section 63.3910 specifies the dates for submitting the notification of compliance status.
§63.9(i)	Adjustment of Submittal Deadlines	Yes	
§63.9(j)	Change in Previous Information	Yes	
§63.10(a)	Recordkeeping/Reporting— Applicability and General Information	Yes	
§63.10(b)(1)	General Recordkeeping Requirements	Yes	Additional requirements are specified in §§63.3930 and 63.3931.
§63.10(b)(2)(i)–(v)	Recordkeeping Relevant to Startup, Shutdown, and Malfunction Periods and CMS	Yes	Requirements for startup, shutdown, and malfunction records only apply to add-on control devices used to comply with the standard.
§63.10(b)(2)(vi)–(xi)		Yes	
§63.10(b)(2)(xii)	Records	Yes	
§63.10(b)(2)(xiii)		No	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§63.10(b)(2)(xiv)		Yes	
§63.10(b)(3)	Recordkeeping Requirements for Applicability Determinations	Yes	
§63.10(c)(1)–(6)	Additional Recordkeeping Requirements for Sources with CMS	Yes	
§63.10(c)(7)–(8)		No	The same records are required in §63.3920(a)(7).
§63.10(c)(9)–(15)		Yes	
§63.10(d)(1)	General Reporting Requirements	Yes	Additional requirements are specified in §63.3920.
§63.10(d)(2)	Report of Performance Test Results	Yes	Additional requirements are specified in §63.3920(b).
§63.10(d)(3)	Reporting Opacity or Visible Emissions Observations	No	Subpart M MMM does not require opacity or visible emissions observations.
§63.10(d)(4)	Progress Reports for Sources With Compliance Extensions	Yes	

§63.10(d)(5)	Startup, Shutdown, and Malfunction Reports	Yes	Applies only to add-on control devices at sources using these to comply with the standard.
§63.10(e) (1)–(2)	Additional CMS Reports	No	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§63.10(e) (3)	Excess Emissions/CMS Performance Reports	No	Section 63.3920 (b) specifies the contents of periodic compliance reports.
§63.10(e) (4)	COMS Data Reports	No	Subpart M MMMM does not specify requirements for opacity or COMS.
§63.10(f)	Recordkeeping/Reporting Waiver	Yes	
§63.11	Control Device Requirements/Flares	No	Subpart M MMM does not specify use of flares for compliance.
§63.12	State Authority and Delegations	Yes	
§63.13	Addresses	Yes	
§63.14	Incorporation by Reference	Yes	
§63.15	Availability of Information/Confidentiality	Yes	

**Table 3 to Subpart M MMM of Part 63—Default Organic HAP Mass Fraction for Solvents and Solvent Blends**

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data and which match either the solvent blend name or the chemical abstract series (CAS) number. If a solvent blend matches both the name and CAS number for an entry, that entry's organic HAP mass fraction must be used for that solvent blend. Otherwise, use the organic HAP mass fraction for the entry matching either the solvent blend name or CAS number, or use the organic HAP mass fraction from table 4 to this subpart if neither the name or CAS number match.

Solvent/solvent blend	CAS. No.	Average organic HAP mass fraction	Typical organic HAP, percent by mass
1. Toluene	108–88–3	1.0	Toluene.
2. Xylene(s)	1330–20–7	1.0	Xylenes, ethylbenzene.
3. Hexane	110–54–3	0.5	n-hexane.
4. n-Hexane	110–54–3	1.0	n-hexane.
5. Ethylbenzene	100–41–4	1.0	Ethylbenzene.
6. Aliphatic 140		0	None.
7. Aromatic 100		0.02	1% xylene, 1% cumene.
8. Aromatic 150		0.09	Naphthalene.
9. Aromatic naphtha	64742–95–	0.02	1% xylene, 1% cumene.

	6		
10. Aromatic solvent	64742-94-5	0.1	Naphthalene.
11. Exempt mineral spirits	8032-32-4	0	None.
12. Ligroines (VM & P)	8032-32-4	0	None.
13. Lactol spirits	64742-89-6	0.15	Toluene.
14. Low aromatic white spirit	64742-82-1	0	None.
15. Mineral spirits	64742-88-7	0.01	Xylenes.
16. Hydrotreated naphtha	64742-48-9	0	None.
17. Hydrotreated light distillate	64742-47-8	0.001	Toluene.
18. Stoddard solvent	8052-41-3	0.01	Xylenes.
19. Super high-flash naphtha	64742-95-6	0.05	Xylenes.
20. Varsol <sup>®</sup> solvent	8052-49-3	0.01	0.5% xylenes, 0.5% ethylbenzene.
21. VM & P naphtha	64742-89-8	0.06	3% toluene, 3% xylene.
22. Petroleum distillate mixture	68477-31-6	0.08	4% naphthalene, 4% biphenyl.

**Table 4 to Subpart MMMM of Part 63—Default Organic HAP Mass Fraction for Petroleum Solvent Groups<sup>a</sup>**

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data.

Solvent type	Average organic HAP mass fraction	Typical organic HAP, percent by mass
Aliphatic <sup>b</sup>	0.03	1% Xylene, 1% Toluene, and 1% Ethylbenzene.
Aromatic <sup>c</sup>	0.06	4% Xylene, 1% Toluene, and 1% Ethylbenzene.

<sup>a</sup>Use this table only if the solvent blend does not match any of the solvent blends in Table 3 to this subpart by either solvent blend name or CAS number and you only know whether the blend is aliphatic or aromatic.

<sup>b</sup>Mineral Spirits 135, Mineral Spirits 150 EC, Naphtha, Mixed Hydrocarbon, Aliphatic Hydrocarbon, Aliphatic Naphtha, Naphthol Spirits, Petroleum Spirits, Petroleum Oil, Petroleum Naphtha, Solvent Naphtha, Solvent Blend.

°Medium-flash Naphtha, High-flash Naphtha, Aromatic Naphtha, Light Aromatic Naphtha, Light Aromatic Hydrocarbons, Aromatic Hydrocarbons, Light Aromatic Solvent.

## **Appendix A to Subpart MMMM of Part 63—Alternative Capture Efficiency and Destruction Efficiency Measurement and Monitoring Procedures for Magnet Wire Coating Operations**

### 1.0 Introduction.

1.1 These alternative procedures for capture efficiency and destruction efficiency measurement and monitoring are intended principally for newer magnet wire coating machines where the control device is internal and integral to the oven so that it is difficult or infeasible to make gas measurements at the inlet to the control device.

1.2 In newer gas fired magnet wire ovens with thermal control (no catalyst), the burner tube serves as the control device (thermal oxidizer) for the process. The combustion of solvents in the burner tube is the principal source of heat for the oven.

1.3 In newer magnet wire ovens with a catalyst there is either a burner tube (gas fired ovens) or a tube filled with electric heating elements (electric heated oven) before the catalyst. A large portion of the solvent is often oxidized before reaching the catalyst. The combustion of solvents in the tube and across the catalyst is the principal source of heat for the oven. The internal catalyst in these ovens cannot be accessed without disassembly of the oven. This disassembly includes removal of the oven insulation. Oven reassembly often requires the installation of new oven insulation.

1.4 Some older magnet wire ovens have external afterburners. A significant portion of the solvent is oxidized within these ovens as well.

1.5 The alternative procedure for destruction efficiency determines the organic carbon content of the volatiles entering the control device based on the quantity of coating used, the carbon content of the volatile portion of the coating and the efficiency of the capture system. The organic carbon content of the control device outlet (oven exhaust for ovens without an external afterburner) is determined using Method 25 or 25A.

1.6 When it is difficult or infeasible to make gas measurements at the inlet to the control device, measuring capture efficiency with a gas-to-gas protocol (see §63.3965(d)) which relies on direct measurement of the captured gas stream will also be difficult or infeasible. In these situations, capture efficiency measurement is more appropriately done with a procedure which does not rely on direct measurement of the captured gas stream.

1.7 Magnet wire ovens are relatively small compared to many other coating ovens. The exhaust rate from an oven is low and varies as the coating use rate and solvent loading rate change from job to job. The air balance in magnet wire ovens is critical to product quality. Magnet wire ovens must be operated under negative pressure to avoid smoke and odor in the workplace, and the exhaust rate must be sufficient to prevent over heating within the oven.

1.8 The liquid and gas measurements needed to determine capture efficiency and control device efficiency using these alternative procedures may be made simultaneously.

1.9 Magnet wire facilities may have many ( e.g., 20 to 70 or more) individual coating lines each with its own capture and control system. With approval, representative capture efficiency and control device efficiency testing of one magnet wire coating machine out of a group of identical or very similar magnet

wire coating machines may be performed rather than testing every individual magnet wire coating machine. The operating parameters must be established for each tested magnet wire coating machine during each capture efficiency test and each control device efficiency test. The operating parameters established for each tested magnet wire coating machine also serve as the operating parameters for untested or very similar magnet wire coating machines represented by a tested magnet wire coating machine.

## 2.0 Capture Efficiency.

2.1 If the capture system is a permanent total enclosure as described in §63.3965(a), then its capture efficiency may be assumed to be 100 percent.

2.2 If the capture system is not a permanent total enclosure, then capture efficiency must be determined using the liquid-to-uncaptured-gas protocol using a temporary total enclosure or building enclosure in §63.3965(c), or an alternative capture efficiency protocol (see §63.3965(e)) which does not rely on direct measurement of the captured gas stream.

2.3 As an alternative to establishing and monitoring the capture efficiency operating parameters in §63.3967(f), the monitoring described in either section 2.4 or 2.5, and the monitoring described in sections 2.6 and 2.7 may be used for magnet wire coating machines.

2.4 Each magnet wire oven must be equipped with an interlock mechanism which will stop or prohibit the application of coating either when any exhaust fan for that oven is not operating or when the oven experiences an over limit temperature condition.

2.5 Each magnet wire oven must be equipped with an alarm which will be activated either when any oven exhaust fan is not operating or when the oven experiences an over limit temperature condition.

2.6 If the interlock in 2.4 or the alarm in 2.5 is monitoring for over limit temperature conditions, then the temperature(s) that will trigger the interlock or the alarm must be included in the start-up, shutdown and malfunction plan and the interlock or alarm must be set to be activated when the oven reaches that temperature.

2.7 Once every 6 months, each magnet wire oven must be checked using a smoke stick or equivalent approach to confirm that the oven is operating at negative pressure compared to the surrounding atmosphere.

## 3.0 Control Device Efficiency.

3.1 Determine the weight fraction carbon content of the volatile portion of each coating, thinner, additive, or cleaning material used during each test run using either the procedure in section 3.2 or 3.3.

3.2 Following the procedures in Method 204F, distill a sample of each coating, thinner, additive, or cleaning material used during each test run to separate the volatile portion. Determine the weight fraction carbon content of each distillate using ASTM Method D5291-02, "Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants" (incorporated by reference, see §63.14).

3.3 Analyze each coating, thinner, additive or cleaning material used during each test run using Method 311. For each volatile compound detected in the gas chromatographic analysis of each coating, thinner, additive, or cleaning material calculate the weight fraction of that whole compound in the coating, thinner, additive, or cleaning material. For each volatile compound detected in the gas chromatographic analysis of each coating, thinner, additive, or cleaning material calculate the weight fraction of the carbon in that

compound in the coating, thinner, additive, or cleaning material. Calculate the weight fraction carbon content of each coating, thinner, additive, or cleaning material as the ratio of the sum of the carbon weight fractions divided by the sum of the whole compound weight fractions.

3.4 Determine the mass fraction of total volatile hydrocarbon (TVH<sub>i</sub>) in each coating, thinner, additive, or cleaning material, i, used during each test run using Method 24. The mass fraction of total volatile hydrocarbon equals the weight fraction volatile matter (W<sub>v</sub> in Method 24) minus the weight fraction water (W<sub>w</sub> in Method 24), if any, present in the coating. The ASTM Method D6053–00, “Standard Test Method for Determination of Volatile Organic Compound (VOC) Content of Electrical Insulating Varnishes” (incorporated by reference, see §63.14), may be used as an alternative to Method 24 for magnet wire enamels. The specimen size for testing magnet wire enamels with ASTM Method D6053–00 must be 2.0 ±0.1 grams.

3.5 Determine the volume (VOL<sub>i</sub>) or mass (MASS<sub>i</sub>) of each coating, thinner, additive, or cleaning material, i, used during each test run.

3.6 Calculate the total volatile hydrocarbon input (TVHC<sub>inlet</sub>) to the control device during each test run, as carbon, using Equation 1:

$$TVHC_{inlet} = \sum_{i=1}^n (TVH_i \times VOL_i \times D_i \times CD_i) \quad (Eq. 1)$$

where:

TVH<sub>i</sub>= Mass fraction of TVH in coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run.

VOL<sub>i</sub>= Volume of coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run, liters.

D<sub>i</sub>= Density of coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run, kg per liter.

CD<sub>i</sub>= Weight fraction carbon content of the distillate from coating, thinner, additive, or cleaning material, i, used in the coating operation during the test run, percent.

n = Number of coating, thinner, additive, and cleaning materials used in the coating operation during the test run.

3.7 If the mass, MASS<sub>i</sub>, of each coating, solvent, additive, or cleaning material, i, used during the test run is measured directly then MASS<sub>i</sub> can be substituted for VOL<sub>i</sub> × D<sub>i</sub> in Equation 1 in section 3.6.

3.8 Determine the TVHC output (TVHC<sub>outlet</sub>) from the control device, as carbon, during each test run using the methods in §63.3966(a) and the procedure for determining M<sub>fo</sub> in §63.3966(d). TVHC<sub>outlet</sub> equals M<sub>fo</sub> times the length of the test run in hours.

3.9 Determine the control device efficiency (DRE) for each test run using Equation 2:

$$DRE = \frac{(TVHC_{inlet} - TVHC_{outlet})}{TVHC_{inlet}} \times 100 \quad (Eq. 2)$$

3.10 The efficiency of the control device is the average of the three individual test run values determined in section 3.9.

3.11 As an alternative to establishing and monitoring the destruction efficiency operating parameters for catalytic oxidizers in §63.3967(b), the monitoring described in sections 3.12 and 3.13 may be used for magnet wire coating machines equipped with catalytic oxidizers.

3.12 During the performance test, you must monitor and record the temperature either just before or just after the catalyst bed at least once every 15 minutes during each of the three test runs. Use the data collected during the performance test to calculate and record the average temperature either just before or just after the catalyst bed during the performance test. This is the minimum operating limit for your catalytic oxidizer and for the catalytic oxidizers in identical or very similar magnet wire coating machines represented by the tested magnet wire coating machine.

3.13 You must develop and implement an inspection and maintenance plan for your catalytic oxidizer(s). The plan must address, at a minimum, the elements specified in sections 3.14 and 3.15, and the elements specified in either (a) section 3.16 or (b) sections 3.17 and 3.18.

3.14 You must conduct a monthly external inspection of each catalytic oxidizer system, including the burner assembly and fuel supply lines for problems and, as necessary, adjust the equipment to assure proper air-to-fuel mixtures.

3.15 You must conduct an annual internal inspection of each accessible catalyst bed to check for channeling, abrasion, and settling. If problems are found, you must replace the catalyst bed or take corrective action consistent with the manufacturer's recommendations. This provision does not apply to internal catalysts which cannot be accessed without disassembling the magnet wire oven.

3.16 You must take a sample of each catalyst bed and perform an analysis of the catalyst activity ( *i.e.*, conversion efficiency) following the manufacturer's or catalyst supplier's recommended procedures. This sampling and analysis must be done within the time period shown in Table 1 below of the most recent of the last catalyst activity test or the last catalyst replacement. For example, if the warranty for the catalyst is 3 years and the catalyst was more recently replaced then the sampling and analysis must be done within the earlier of 26,280 operating hours or 5 calendar years of the last catalyst replacement. If the warranty for the catalyst is 3 years and the catalyst was more recently tested then the sampling and analysis must be done within the earlier of 13,140 operating hours or 3 calendar years of the last catalyst activity test. If problems are found during the catalyst activity test, you must replace the catalyst bed or take corrective action consistent with the manufacturer's recommendations.

**Table 1—Catalyst Monitoring Requirements**

<b>If the catalyst was last (more recently) replaced and the warranty period is . . .</b>	<b>Then the time between catalyst replacement and the next catalyst activity test cannot exceed the earlier of . . .</b>	<b>And the catalyst was more recently tested, then the time between catalyst activity tests cannot exceed the earlier of . . .</b>
1 year	8,760 operating hours or 5 calendar years	8,760 operating hours or 3 calendar years.
2 years	15,520 operating hours or 5 calendar years	8,760 operating hours or 3 calendar years.
3 years	26,280 operating hours or 5 calendar years	13,100 operating hours or 3 calendar years.
4 years	35,040 operating hours or 5 calendar	17,520 operating hours or 3 calendar

	years	years.
5 or more years	43,800 operating hours or 5 calendar years	21,900 operating hours or 3 calendar years.

3.17 During the performance test, you must determine the average concentration of organic compounds as carbon in the magnet wire oven exhaust stack gases ( $C_c$  in Equation 1 in §63.3966(d)) and the destruction efficiency of the catalytic oxidizer, and calculate the operating limit for oven exhaust stack gas concentration as follows. You must identify the highest organic HAP content coating used on this magnet wire coating machine or any identical or very similar magnet wire coating machines to which the same destruction efficiency test results will be applied. Calculate the percent emission reduction necessary to meet the magnet wire coating emission limit when using this coating. Calculate the average concentration of organic compounds as carbon in the magnet wire oven exhaust stack gases that would be equivalent to exactly meeting the magnet wire coating emissions limit when using the highest organic HAP content coating. The maximum operating limit for oven exhaust stack gas concentration equals 90 percent of this calculated concentration.

3.18 For each magnet wire coating machine equipped with a catalytic oxidizer you must perform an annual 10 minute test of the oven exhaust stack gases using EPA Method 25A. This test must be performed under steady state operating conditions similar to those at which the last destruction efficiency test for equipment of that type (either the specific magnet wire coating machine or an identical or very similar magnet wire coating machine) was conducted. If the average exhaust stack gas concentration during the annual test of a magnet wire coating machine equipped with a catalytic oxidizer is greater than the operating limit established in section 3.17 then that is a deviation from the operating limit for that catalytic oxidizer. If problems are found during the annual 10-minute test of the oven exhaust stack gases, you must replace the catalyst bed or take other corrective action consistent with the manufacturer's recommendations.

3.19 If a catalyst bed is replaced and the replacement catalyst is not of like or better kind and quality as the old catalyst, then you must conduct a new performance test to determine destruction efficiency according to §63.3966 and establish new operating limits for that catalytic oxidizer unless destruction efficiency test results and operating limits for an identical or very similar unit (including consideration of the replacement catalyst) are available and approved for use for the catalytic oxidizer with the replacement catalyst.

3.20 If a catalyst bed is replaced and the replacement catalyst is of like or better kind and quality as the old catalyst, then a new performance test to determine destruction efficiency is not required and you may continue to use the previously established operating limits for that catalytic oxidizer.

**Indiana Department of Environmental Management**  
Office of Air Quality

**Addendum to the Technical Support Document (ATSD) for a Part 70 Operating Permit (TITLE V)**

**Source Background and Description**

<b>Source Name:</b>	Batesville Manufacturing, Inc
<b>Source Location:</b>	(1) Assembly Plant 1000 East Pearl Street, Batesville, IN 47006
	(2) Options Plant 705 East Pearl Street, Batesville, IN 47006
	(3) Stamping Plant 100 Eastern Avenue, Batesville, IN 47006
<b>County:</b>	Ripley
<b>SIC Code:</b>	3995
<b>Permit Renewal No.:</b>	T137-24390-00016
<b>Permit Reviewer:</b>	Josiah Balogun

On October 3, 2008, the Office of Air Quality (OAQ) had a notice published in The Herald Tribune, Batesville, Indiana, stating that Batesville Manufacturing, Inc had applied for a Part 70 Operating Permit (TITLE V) to continue to operate a burial casket manufacturing operation. The notice also stated that OAQ proposed to issue a Title V for this operation and provided information on how the public could review the proposed Title V and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this Title V should be issued as proposed.

On November 3, 2008, Dustin L. Pflum of Batesville Manufacturing, Inc submitted comments on the proposed Title V Operating Permit. The comments are summarized in the subsequent pages, with IDEM's corresponding responses.

No changes have been made to the TSD because the OAQ prefers that the Technical Support Document reflects the permit that was on public notice. Changes that occur after the public notice are documented in this Addendum to the Technical Support Document. This accomplishes the desired result, ensuring that these types of concerns are documented and part of the record regarding this permit decision.

The summary of the comments and IDEM, OAQ responses, including changes to the permit (language deleted is shown in ~~strikeout~~ and language added is shown in **bold**) are as follows:

Comment 1: **Condition D.1.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-6] and the Technical Support Document**

The electrostatic metal casket spray booth, identified as B-14-40 is not subject to the requirements of 326 IAC 8-1-6, therefore please remove this reference in Condition D.1.2(a) as indicated below. In addition, please change the description of Booth 14-40 to "Brush Seal Coat"

The usage of VOC in the surface coating booths shall be limited as follows:

- (a) Pursuant to ~~326 IAC 8-1-6 and~~ MSM 137-14731-00016, issued on October 9, 2001, the VOC emissions from the electrostatic metal casket spray booth, identified as B-14-40 (~~Booth~~ **Brush Seal Coat**) shall be limited to less than 25 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with this limit will limit the VOC emissions to less than 25 tons per year and render the requirements of 326 IAC 8-1-6 not applicable to the electrostatic metal casket spray booth, identified as B-14-40 (~~Booth~~ **Brush Seal Coat**).

Response 1: The citation 326 IAC 8-1-6 has been removed from the permit and the description has been corrected as stated above.

Comment 2: **Condition D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-6] and the Technical Support Document**

The metal urn surface coating line is not subject to the requirements of 326 IAC 8-1-6; therefore please remove this reference in Condition D.2.2(a) as indicated below.

Pursuant to ~~326 IAC 8-1-6~~ and CP 137-10452-00016, issued on April 29, 1999, the metal urn surface coating line shall use less than 25 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve (12) consecutive month period, with compliance determined at the end of each month.

Compliance with the above limits will limit the VOC emissions from the metal urn surface coating line to less than 25 tons per year and render 326 IAC 8-1-6 not applicable to the metal urn surface coating line.

Response 2: The citation 326 IAC 8-1-6 has been removed from the permit as stated above.

Comment 3: Section E.1, Condition E.2 – The wood urn surface coating booths, P-W-1 and P-W-2, should be removed from this section of the permit because metal parts are not coated in these booths, therefore they are not affected units subject to the Miscellaneous Metal Coating NESHAP, 40 CFR 63 Subpart M. In addition, the number of booths should be corrected to reflect thirteen (13) booths.

Response 3: The wood urn surface coating booths, identified as P-W-1 and P-W-2 have been deleted from Section E.1 and Condition E.1.2

**SECTION E.1 EMISSIONS UNIT OPERATION CONDITIONS**

**Emissions Unit Description:**

.....  
Plant #2 (Options Plant):

(j) \*\*\*\*\*

~~(k) One (1) wood urn surface coating line capable of coating approximately 32 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-W-1 and P-W-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-W-1; and~~

.....  
Plant #3 (Stamping Plant, commenced operation in the early 1950s):

(~~k~~ k) Miscellaneous clean-up solvents usage throughout the plant.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

**National Emission Standards for Hazardous Air Pollutants Requirements [326 IAC 2-7-5(1)]**

.....

E.1.2 NESHAP Subpart M MMM Requirements [40 CFR 63, Subpart M]

Pursuant to 40 CFR 63, Subpart M, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart M (included as Attachment A), which was incorporated by reference as 326 IAC 20-1-1, for the entire affected source (consisting of all of the spray booths, identified as B-14-40 (Brush Seal Coat), B-21-5455 (Topcoat/Shade), B-21-57 (Topcoat 2), B-21-5652 (Prime), B-21-2324 (Color), B-61P-5 (Copper Line), B-61P-11 (Copper Line), B-60-33 (Ear), B-60-35 (Corner), B-60-20 (E-Room), B-60-21(E-Room), P-M-1, P-M-2, ~~P-W-1 and P-W-2~~, and associated solvent cleaning and coating mixing operations) beginning January 2, 2007, as follows:

.....

TSD.

Comment 4: **Several insignificant activities have been removed from the facility. Please revise the list of insignificant activities listed in the Technical Support Document as follows:**

**Insignificant Activities**

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):  
(a) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million British thermal units (mmBtu) per hour:

(1) Department 21

- (A) one (1) natural gas fired primer oven with a rated heat input of 3.5 mmBtu/hr;
- (B) one (1) natural gas fired topcoat oven with a rated heat input of 3.2 mmBtu/hr;
- ~~(C) one (1) natural gas fired rerun prime oven with a rated heat input of 0.8 mmBtu/hr;~~
- ~~(D) one (1) natural gas fired rerun topcoat oven with a rated heat input of 0.8 mmBtu/hr;~~
- (E) two (2) natural gas fired rerun air make-up units each with a rated heat input of 3.6 mmBtu/hr;

---

(2) Department C-14

- (A) four (4) natural gas fired washer heaters each with a rated heat input of 1.5 mmBtu/hr;
- ~~(B) one (1) natural gas fired washer heater with a rated heat input of 2.5 mmBtu/hr;~~
- (C) one (1) natural gas fired washer dry-off heater with a rated heat input of 1.65 mmBtu/hr;

---

(5) Departments C-60 and C-56

- (A) one (1) natural gas fired washer heater with a rated heat input of 1.5 mmBtu/hr;
- (B) one (1) natural gas fired dry-off heater with a rated heat input of 0.35 mmBtu/hr;
- ~~(C) one (1) natural gas fired caustic dip heater with a rated heat input of 1.5 mmBtu/hr;~~
- ~~(D) one (1) natural gas fired caustic rinse heater with a rated heat input of 3.8 mmBtu/hr;~~
- ~~(E) one (1) natural gas fired caustic dry-off heater with a rated heat input of 0.8 mmBtu/hr;~~
- (F) one (1) natural gas fired base coat oven with a rated heat input of 1.5 mmBtu/hr;
- (G) two (2) natural gas fired air make-up units each with a rated heat input of 3.15 mmBtu/hr;
- (H) one (1) natural gas fired air make-up unit with a rated heat input of 2.0 mmBtu/hr;
- (I) one (1) natural gas fired paint mix room air make-up unit with a rated heat input of 0.292 mmBtu/hr;
- (J) one (1) natural gas fired unit heater with a rated heat input of 0.3 mmBtu/hr;
- (K) five (5) natural gas fired holding furnaces each with a rated heat input of 0.25 mmBtu/hr;
- ~~(L) one (1) natural gas fired key machine furnace with a rated heat input of 0.25 mmBtu/hr;~~
- (M) one (1) natural gas fired premelt furnace with a rated heat input of 1.675 mmBtu/hr;
- (N) one (1) natural gas fired holding furnace with a rated heat input of 1.1 mmBtu/hr;
- (O) one (1) natural gas fired reclaim furnace with a rated heat input of 1.0 mmBtu/hr;

(P) one (1) natural gas fired heater with a rated heat input of 0.5 MMBtu/hr;

---

~~(d) A gasoline fuel transfer and dispensing operation handling less than or equal to 1,300 gallons per day, such as filling of tanks, locomotives, automobiles, having a storage capacity less than or equal to 10,500 gallons;~~

~~(e) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons;~~

---

(ee) A laboratory as defined in 326 IAC 2-7-1(21)~~(GD)~~;

---

(gg) The following operations emitting greater than 1 pound per day but less than 12.5 pounds per day of any combinations of HAPs:

~~(1) Aboveground storage tanks gasoline (300 gallons), wastewater blending (normally empty, 12,000 gallons), and miscellaneous chemicals (KOH with traces of phenol and glycol ether) (10,000 gallons);~~

~~(2) drums/totes containing miscellaneous chemicals including coatings and solvents, hydraulic oil/machine oils;~~

~~(3) two (2) bulk paint tanks (3,000 gallons each);~~

Response 4: The lists of insignificant activities, which have been removed from the source are not included in the list of insignificant activities and the existing insignificant activities are shown below:

### Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

(a) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million British thermal units (mmBtu) per hour:

(1) Department 21

(A) one (1) natural gas fired primer oven with a rated heat input of 3.5 mmBtu/hr;

(B) one (1) natural gas fired topcoat oven with a rated heat input of 3.2 mmBtu/hr;

(C) two (2) natural gas fired rerun air make-up units each with a rated heat input of 3.6 mmBtu/hr;

(D) one (1) natural gas fired prime air make-up unit with a rated heat input of 6.5 mmBtu/hr;

(E) one (1) natural gas fired topcoat air make-up unit with a rated heat input of 2.625 mmBtu/hr;

(F) two (2) natural gas fired air make-up units each with a rated heat input of 4.0 mmBtu/hr;

(G) one (1) natural gas fired unit heater with a rated heat input of 0.3 mmBtu/hr;

- (H) one (1) natural gas fired floor furnace with a rated heat input of 1.25 mmBtu/hr;
  - (I) one (1) natural gas fired color air make-up unit with a rated heat input of 3.5 mmBtu/hr;
  - (J) one (1) natural gas fired shade and topcoat air make-up unit with a rated heat input of 5.5 mmBtu/hr;
  - (K) one (1) natural gas fired paint mix room heater with a rated heat input of 2.0 mmBtu/hr;
- (2) Department C-14
- (A) four (4) natural gas fired washer heaters each with a rated heat input of 1.5 mmBtu/hr;
  - (B) one (1) natural gas fired washer dry-off heater with a rated heat input of 1.65 mmBtu/hr;
  - (C) one (1) natural gas fired air make-up unit with a rated heat input of 2.0 mmBtu/hr;
  - (D) one (1) natural gas fired air make-up unit with a rated heat input of 2.5 mmBtu/hr;
  - (E) one (1) natural gas fired air make-up unit with a rated heat input of 2.2 mmBtu/hr;
  - (F) one (1) natural gas fired sludge dryer with a rated heat input of 0.325 mmBtu/hr;
  - (G) ten (10) natural gas fired space heaters each with a rated heat input of 0.175 mmBtu/hr;
  - (H) four (4) natural gas fired HVAC units with a total rated heat input of 0.566 mmBtu/hr;
  - (I) two (2) natural gas fired unit heaters with a total rated heat input of 0.45 mmBtu/hr;
  - (J) one (1) natural gas fired air make-up unit with a rated heat input of 0.292 mmBtu/hr;
  - (K) two (2) natural gas fired door heaters each with a rated heat input of 1.0 mmBtu/hr;
  - (L) one (1) natural gas fired heater with a rated heat input of 0.5 MMBtu/hr;
- (3) Offices
- (A) twelve (12) natural gas fired heaters with a total rated heat input of 1.14 mmBtu/hr;

- (4) Departments C-9, C-10, C-13 and C-61P
  - (A) one (1) natural gas fired shipping air make-up unit with a rated heat input of 3.0 mmBtu/hr;
  - (B) one (1) natural gas fired air make-up unit with a rated heat input of 1.32 mmBtu/hr;
  - (C) one (1) natural gas fired unit heater with a rated heat input of 0.4 mmBtu/hr;
  - (D) four (4) natural gas fired door heaters each with a rated heat input of 1.0 mmBtu/hr;
  - (F) two (2) natural gas fired furnaces each with a rated heat input of 0.625 mmBtu/hr;
  - (G) one (1) natural gas fired floor furnace with a rated heat input of 1.25 mmBtu/hr;
  - (H) three (3) natural gas fired HVAC units with a total rated heat input of 0.46 mmBtu/hr;
  - (I) two (2) natural gas fired ovens each with a rated heat input of 0.5 mmBtu/hr;
  - (J) one (1) natural gas fired air make-up unit with a total rated heat input of 2.2 mmBtu/hr;
  - (K) three (3) natural gas fired HVAC units with a total rated heat input of less than 1.5 mmBtu/hr;
  
- (5) Departments C-60 and C-56
  - (A) one (1) natural gas fired washer heater with a rated heat input of 1.5 mmBtu/hr;
  - (B) one (1) natural gas fired dry-off heater with a rated heat input of 0.35 mmBtu/hr;
  - (C) one (1) natural gas fired base coat oven with a rated heat input of 1.5 mmBtu/hr;
  - (D) two (2) natural gas fired air make-up units each with a rated heat input of 3.15 mmBtu/hr;
  - (E) one (1) natural gas fired air make-up unit with a rated heat input of 2.0 mmBtu/hr;
  - (F) one (1) natural gas fired paint mix room air make-up unit with a rated heat input of 0.292 mmBtu/hr;
  - (G) one (1) natural gas fired unit heater with a rated heat input of 0.3 mmBtu/hr;
  - (H) five (5) natural gas fired holding furnaces each with a rated heat input of 0.25 mmBtu/hr;

- (I) one (1) natural gas fired premelt furnace with a rated heat input of 1.675 mmBtu/hr;
  - (J) one (1) natural gas fired holding furnace with a rated heat input of 1.1 mmBtu/hr;
  - (K) one (1) natural gas fired reclaim furnace with a rated heat input of 1.0 mmBtu/hr;
  - (L) one (1) natural gas fired heater with a rated heat input of 0.5 MMBtu/hr;
- (6) Stamping Plant:
- (A) two (2) natural gas fired phosphate washer heaters each with a rated heat input of 2.5 mmBtu/hr;
  - (B) one (1) natural gas fired cap washer heater with a rated heat input of 2.5 mmBtu/hr;
  - (C) six (6) natural gas fired space heaters each with a rated heat input of 0.175 mmBtu/hr;
  - (D) two (2) natural gas fired door heaters each with a rated heat input of 1.0 mmBtu/hr;
  - (E) one (1) natural gas fired air make-up unit with a rated heat input of 4.0 mmBtu/hr;
  - (F) one (1) natural gas fired air make-up unit with a rated heat input of 4.75 mmBtu/hr;
  - (G) one (1) natural gas fired air make-up unit with a rated heat input of 0.75 mmBtu/hr;
- (7) Options Plant:
- (A) two (2) natural gas fired air make-up units each with a rated heat input of 0.896 mmBtu/hr;
  - (B) various soldering irons with a total rated heat input of 1.6 mmBtu/hr;
- (b) Propane or liquefied petroleum gas, or butane-fired combustion sources with heat input equal to or less than 6.0 mmBtu/hr;
  - (c) Combustion source flame safety purging on startup;
  - (d) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids;
  - (e) Filling drums, pails or other packaging containers with lubricating oils, waxes, and greases;
  - (f) Application of oils, greases, lubricants or other nonvolatile materials applied as temporary protective coatings;
  - (g) Machining where an aqueous cutting coolant continuously floods the machining interface;
  - (h) Cleaners and solvents characterized as follows:

- (1) having a vapor pressure equal to or less than 2 kPa, 15 mmHg, or 0.3 psi measured at 38°C (100°F) or;
  - (2) having a vapor pressure equal to or less than 0.7 kPa, 5 mmHg, or 0.1 psi measured at 20°C (68°F);
- (i) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment;
  - (j) Closed loop heating and cooling systems;
  - (k) Infrared cure equipment;
  - (l) Activities associated with the treatment of wastewater streams with an oil and grease content less than or equal to 1% by volume;
  - (m) Any operation using aqueous solutions containing less than 1% by weight of VOCs excluding HAPs;
  - (n) Forced and induced draft cooling tower system not regulated under a NESHAP;
  - (o) Replacement or repair of electrostatic precipitators, bags in baghouses and filters in other air filtration equipment;
  - (p) Heat exchanger cleaning and repair;
  - (q) Process vessel degassing and cleaning to prepare for internal repairs;
  - (r) Paved and unpaved roads and parking lots with public access;
  - (s) Enclosed systems for conveying plastic raw materials and plastic finished goods;
  - (t) Asbestos abatement projects regulated by 326 IAC 14-10;
  - (u) Purging of gas lines and vessels that is related to routine maintenance and repair of buildings, structures, or vehicles at the source where air emissions from those activities would not be associated with any product process;
  - (v) Equipment used to collect any material that might be released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separators, tanks, and fluid handling equipment;
  - (w) Blowdown for any of the following: sight glass, boiler, compressors, pumps, and cooling tower;
  - (x) Diesel generators not exceeding 1600 horsepower;
  - (y) Stationary fire pumps;
  - (z) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 cubic feet per minute, including the following; deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations;
  - (aa) Filter or coalescer media changeout;

- (bb) Mold release agents using low volatile products (vapor pressure less than or equal to 2 kilopascals measured at 38°C;
- (cc) A laboratory as defined in 326 IAC 2-7-1 (21) (D);
- (dd) The following operations emitting greater than 1 pound per day but less than 5 pounds per day or 1 ton per year of a single HAP:
  - (1) welding operations in Department C-14;
  - (2) zinc melting operations in Department C-56;
  - (3) zinc casting operations in Department C-56;
  - (4) vacuum metalizing operations in Departments C-60 & C61;
  - (5) welding operations in Stamping Plant;
  - (6) welding operations in Optional Plant;
- (ff) The following operations emitting greater than 1 pound per day but less than 12.5 pounds per day of any combinations of HAPs:
  - (1) Aboveground storage tanks, wastewater blending (normally empty, 12,000 gallons), and miscellaneous chemicals;
  - (2) drums/totes containing miscellaneous chemicals including coatings and solvents, hydraulic oil/machine oils;
  - (3) two (2) bulk paint tanks (3,000 gallons each); and
- (gg) The following activities or categories not previously identified:
  - (1) plastic grinding operation;
  - (2) foot lining mattress, fabric interior and installation in Department C-13;
  - (3) process-related vehicular traffic on paved roads;
  - (4) process-related vehicular traffic on unpaved roads;
  - (5) wastewater treatment and sludge dryer;
  - (6) woodworking operations woodworking operations in Options Plant controlled by baghouse BW-1 and exhausting inside the building.

Comment 5: **Page 11 of the Technical Support Document – Potential to Emit After Issuance Table** – Please revise the Potential to Emit table to reflect the following changes, consistent with the limitations and descriptions in the permit:

Emission Unit	PM	PM10	SO2	VOC	CO	NOx	HAPs
Electrostatic metal casket spray booth B-21- <del>5455</del> <b>57</b>	3.84	3.84	0	less than <del>40</del> <b>88.3</b>	0	0	-----
Electrostatic metal casket spray booth B-21-5652	4.22	4.22	0	less than <del>40</del> <b>96</b>	0	0	-----
<del>Three (3)</del> <b>Two (2)</b> Air atomization/electrostatic metal casket spray booth B-60-33, <b>and</b> B-60-35 <del>and B-60-39</del> and B-60-39	4.71	4.71	0	215.9	0	0	-----

Response 5: This is the correct limited emission table. This ATSD becomes part of the TSD.

Comment 6: **Page 12 of the Technical Support Document** – Federal Rule Applicability, item (c), the number of booths should be corrected to reflect thirteen (13) booths.

- (c) The ~~fourteen (14)~~ **thirteen (13)** paint booths and the clean-up solvents are subject to the National Emission Standards for Hazardous Air Pollutants for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR Part 63, Subpart M MMM). The metal parts surface coating operations and associated operations are subject to 40 CFR Part 63, Subpart M MMM because they are located at a major source of HAPs and perform the surface coating of metal parts and products (defined by 40 CFR 63.3981(a)).

**Page 14 of the Technical Support Document** – Federal Rule Applicability, item (k), the wood urn surface coating booths, P-W-1 and P-W-2, should be removed from this list of affected units subject to the Miscellaneous Metal Coating NESHAP, 40 CFR 63 Subpart M MMM because metal parts are not coated in these booths, therefore they are not affected units subject to this rule.

The facilities subject to this rule include the following:

Plant #1 (Assembly Plant, commenced operation in late 1950's):

- (a) One (1) electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat), constructed in 1981, capable of processing approximately 50 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 14-EF-40;
- (b) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-5455 (Topcoat/Shade), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-54 and 21-EF-55;
- (c) One (1) electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 21-EF-57;
- (d) One (1) high volume low pressure (HVLP)/air atomization/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through three (3) stacks identified as 21-EF-5, 21-EF-6 and 21-EF-52;
- (e) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-2324 (Color), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-23 and 21-EF-24;
- (f) Two (2) air atomization spray booths, identified as B-60-33 (Ear) and B-60-35 (Corner) respectively, constructed in the 1960s, each using dry filters for overspray control, and each exhausting through one (1) stack identified as 60-EF-33 and 60-EF-35 respectively;
- (g) Two (2) air atomization/electrostatic disk spray booths, identified as B-60-20 (E-Room) and B-60-21 (E-Room), respectively, constructed in 1972, each using dry filters for overspray control, and each exhausting through four (4) stacks identified as 60-EF-20/60-EF-20A and 60-EF-21/60-EF-21A, respectively;
- (h) Two (2) air atomization/electrostatic spray booths, identified as B-61P-5 (Copper Line) and B-61P-11 (Copper Line), respectively, constructed in early 1972, each

using waterwash for overspray control, and each exhausting through one (1) stack identified as 61P-EF-5 and 61PEF-11, respectively;

- (i) One (1) brush sander, with a process weight rate of 2.66 tons per hour, equipped with a jet pulse baghouse, exhausting through one (1) stack inside the building, identified as S2;

Plant #2 (Options Plant):

- (j) One (1) metal urn surface coating line capable of coating approximately 36 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-M-1 and P-M-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-M-1; **and**

- ~~(k) One (1) wood urn surface coating line capable of coating approximately 32 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-W-1 and P-W-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-W-1; and~~

Plant #3 (Stamping Plant, commenced operation in the early 1950s):

- ~~(k)~~ Miscellaneous clean-up solvents usage throughout the plant.

Response 6: Since the wood urn surface coating is not subject to 40 CFR 63, Subpart M, the number of paint booths in this section is now thirteen (13) paint booths.

Comment 7: **Page 15 of the Technical Support Document** – The paragraph describing the 1993 modification should be revised to clarify the VOC limit for booth B-21-57 (Topcoat) was established to render the requirements of PSD not applicable to the modification.

#### 1993 Modification

The electrostatic metal casket spray booth, identified as B-21-57 (Topcoat), constructed in 1993 has uncontrolled VOC emissions of more than 40 tons per year. The VOC input to the spray booth identified as B-21-57 (Topcoat) shall be limited to less than 88.3 tons per twelve (12) consecutive month period with compliance determined at the end of each month. **This limit effectively restricts the net contemporaneous VOC emission increase from the booth to less than 40 tons per year. Compliance with the above limit will render 326 IAC 2-2 (PSD) not applicable to 1993 modification.**

~~Compliance with the above limit will limit the VOC emissions from the electrostatic metal casket spray booth, identified as B-21-57 (Topcoat) to less than 40 tons per year and render 326 IAC 2-2 (PSD) not applicable to 1993 modification.~~

Response 7: Condition D.1.1 - PSD Minor Limits has been revised in the permit.

Comment 8: **Page 15 of the Technical Support Document** – The paragraph describing the 1999 modification should be revised to clarify the 25 ton per year VOC limit for the metal urn surface coating line was established to render the requirements of 326 IAC 8-1-6 not applicable. In addition, the paragraph should be revised to clarify the wood urn surface coating line is limited to less than 40 tons per year to render PSD not applicable.

#### 1999 Modification

Pursuant to CP 137-10452-00016, issued on April 29, 1999, the wood urn surface coating line and metal urn surface coating line, constructed in 1999 have uncontrolled VOC emissions of more than 40 tons per year. The wood urn surface coating line and metal urn surface coating line shall use

less than 40 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve consecutive month period, with compliance determined at the end of each month period.

Pursuant to ~~326 IAC 8-1-6~~ and to CP 137-10452-00016, issued on April 29, 1999, the metal urn surface coating line shall use less than 25 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve (12) consecutive month period, with compliance determined at the end of each month.

Compliance with the above limits will limit the VOC emissions from the wood urn surface coating line **to less than 40 tons per year** and the metal urn surface coating line to less than 25 tons per year and render 326 IAC 8-1-6 and 326 IAC 2-2 (PSD) not applicable to 1999 modification.

Response 8: Condition D.2.2 - Volatile Organic Compounds (VOCs) has been revised in the permit accordingly.

Comment 9: **Page 16 of the Technical Support Document** – Please revise the Particulate Emission Limitations for Work Practices and Control Technologies for the surface coating operations in the TSD to be consistent with the condition in the permit.

#### State Rule Applicability – Individual Facilities

326 IAC 6-3-2 (Particulate Emission Limitations for Work Practices and Control Technologies)  
Pursuant to 326 IAC 6-3-2(d), the particulate matter (PM) from the ~~seven (7) spray booths, identified as B-60-33, B-60-35, B-60-39, B-60-20, B-60-21 P-M-1, P-M-2, P-W-1, and P-W-2~~ shall be controlled by dry filters and the ~~seven (7) spray booths, identified as B-14-40, B-21-5455, B-21-57, B-21-5652, B-21-2324, B-61P-5 and B-61P-11~~ shall be controlled by **dry filters or** water wash curtain and the Permittee shall operate the filters and water wash curtain in accordance with manufacturer's specifications.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)  
Pursuant to 326 IAC 6-3-2, the particulate emissions from the insignificant activities, wood working brazing equipment, cutting torches, soldering equipment and welding equipment and grinding and machining operation shall be limited by the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

Where:

E = rate of emission in pounds per hour and

P = process weight rate in tons per hour

The baghouse shall be in operation at all times ~~the grinding and machining and~~ the wood working operation are in operation, in order to comply with this limit.

Response 9: Condition D.1.3 has been revised accordingly.

Comment 10: **Page 18 of the Technical Support Document** - Please delete the following state rule applicability determination because there is no gasoline dispensing operation at the source.

#### ~~326 IAC 8-4 (Petroleum Sources)~~

~~Pursuant to 326 IAC 8-4-1, the gasoline dispensing operation at the source is not subject to the requirements of 326 IAC 8-4 (Petroleum Sources), because the source is not located in one of the county listed in 326 IAC 8-4-1(a). Therefore, the requirements of 326 IAC 8-4 do not apply.~~

Response 10: The above condition deleted by the source is correct. This ATSD becomes part of the TSD.

Comment 11: **Page 2 of Appendix A Calculations** – Please revise the calculations to reflect the following changes, consistent with the limitations in the permit:

Emission Unit	PM	PM10	SO2	VOC	CO	NOx	HAPs
Electrostatic metal casket spray booth B-21-57	3.84	3.84	0	less than 40 <b>88.3</b>	0	0	-----
Electrostatic metal casket spray booth B-21-5652	4.22	4.22	0	less than 40 <b>96</b>	0	0	-----
Two (2) Air atomization/electrostatic metal casket spray booth B-60-33 and B-60-35	4.71	4.71	0	215.9	0	0	-----

Response 11: The table is correct and becomes part of the TSD.

Comment 12: **Page 16 of the Technical Support Document**

326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP))

The operation of the ~~fourteen (14)~~ **thirteen (13)** paint booths and the clean-up solvents will emit greater than ten (10) tons per year for a single HAP and greater than twenty-five (25) tons per year for a combination of HAPs). Therefore, 326 IAC 2-4.1 would apply to the ~~fourteen (14)~~ **thirteen (13)** spray booths, and the clean-up solvent. However, pursuant to 326 IAC 2-4.1-1(b)(2), because this ~~fourteen (14)~~ **thirteen (13)** paint booths, are specifically regulated by NESHAP 40 CFR 63, Subpart M, which was issued pursuant to Section 112(d) of the CAA, this ~~fourteen (14)~~ **thirteen (13)** paint booths and the clean-up solvents are exempt from the requirements of 326 IAC 2-4.1. However, the limit established in CP 137-10452-00016 for the wood urn paint booth should remain in the Title V renewal permit

**Hazardous Air Pollutants (HAPs) [326 IAC 2-4.1-1]**

**Pursuant to CP137-10452-00016, issued on April 29, 1999, the wood urn surface coating line shall use less than 10 tons of any single HAP and less than 25 tons of total HAPs, per 12 consecutive month period, with compliance demonstrated at the end of each month. The usage limits are required to limit the potential to emit of single HAP and total HAPs from the wood urn coating operation to less than 10 and 25 tons per 12 consecutive month period, respectively. Compliance with this limit makes 326 IAC 2-4.1-1 not applicable.**

Response 12: The above condition was in the previous permit. The metal coating line is now covered by NESHAP and the wood coating line limits is still need in the permit. No new applicable limit is included in the permit. This ATSD becomes part of the TSD. The HAPs limit for the wood urn surface coating has been included in the permit. The Record Keeping, Reporting Requirements and reporting form have been revised in the permit and subsequent conditions have been renumbered.

**D.2.5 Hazardous Air Pollutants (HAPs) Limits [326 IAC 2-4.1-1]**

**Pursuant to CP137-10452-00016, issued on April 29, 1999, the wood urn surface coating line shall use less than 10 tons of any single HAP and less than 25 tons of total HAPs, per twelve (12) consecutive month period, with compliance determined at the end of each month.**

**Compliance with these limits will limit the single HAP and total HAPs of the wood urn surface coating line to less than 10 and 25 tons per year, respectively and will render the requirements of 326 IAC 2-4.1-1 not applicable to this emission unit.**

#### D.2.9 Record Keeping Requirement

- (a) To document compliance with Conditions D.2.1 ~~and~~ D.2.2 **and D.2.5**, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC **and HAPs** content and usage limits, and the VOC **and HAPs** emission limits established in Conditions D.2.1 and D.2.2.
- (1) The amount of VOC **and HAPs** in each coating material and solvent used.
  - (2) The amount of coating material and solvent less water used on a monthly basis.
    - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
    - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
  - (3) The cleanup solvent usage for each month; and
  - (4) The total VOC **and HAPs** usage for each month.

#### D.2.10 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.2.1, ~~and~~ D.2.2 **and D.2.5** shall be submitted to the address listed in Section C – General Reporting requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

### Other Changes

Upon further review IDEM, OAQ has made the following changes to the Title V permit T137-24390-00016. (deleted language appears as ~~strikeout~~ and the new language **bolded**):

Change 1: Condition D.1.1 - PSD Minor Limit has been revised.

#### D.1.1 PSD Minor Limits [326 IAC 2-2]

- (a) ~~\*\*\*\*\*~~
- (b) Pursuant to CP 137-2866-00004, issued on May 26, 1993, the VOC input to the spray booth, identified as B-21-57 (Topcoat 2) shall be limited to less than 88.3 tons per twelve (12) consecutive month period with compliance determined at the end of each month. **This limit effectively restricts the net contemporaneous VOC emission increase from the booth to less than 40 tons per year. Compliance with the above limit will render 326 IAC 2-2 (PSD) not applicable to the 1993 modification.**

~~Compliance with the above limit will limit the increase in VOC emissions from the electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2) to less than 40 tons per year and render 326 IAC 2-2 (PSD) not applicable to 1993 modification.~~

Change 2: Condition D.2.2 - Volatile Organic Compounds (VOCs) has been revised.

**D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]**

Pursuant to ~~326 IAC 8-1-6~~ and CP 137-10452-00016, issued on April 29, 1999, the metal urn surface coating line shall use less than 25 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve (12) consecutive month period, with compliance determined at the end of each month.

Compliance with the above limits will limit the VOC emissions from the metal urn surface coating line to less than 25 tons per year and render 326 IAC 8-1-6 not applicable to the metal urn surface coating line.

Change 3: The Potential to emit table has been adjusted to reflect the HAPs limits of the wood urn surface coating line. This ATSD becomes part of the TSD.

**Potential to Emit After Issuance**

\*\*\*\*\*

Emission Unit	Potential to Emit						
	PM (tons/yr)	PM10/PM2.5 (ton/yr)	SO2 (tons/yr)	VOC (tons/yr)	CO (tons/yr)	NOX (tons/yr)	HAPs (tons/yr)
Electrostatic metal casket spray booth B-14-40	2.26	2.26	0	less than 25	0	0	Single greater than 9 Total greater than 24
Air atomization/electrostatic metal casket spray booth B-21-5455	0.67	0.67	0	26.08	0	0	
Electrostatic metal casket spray booth <del>B-21-5455</del> 57	3.84	3.84	0	less than <del>40</del> 88.3	0	0	
HVLP/ air atomization/electrostatic metal casket spray booth B-21-5652	4.22	4.22	0	less than <del>40</del> 96.0	0	0	
Air atomization/electrostatic metal casket spray booth B-21-2324	4.09	4.09	0	205.7	0	0	
<del>Three</del> Two (3 2) Air atomization/electrostatic metal casket spray booth B-60-33, B-60-35 and B-60-39	4.71	4.71	0	215.9	0	0	
Two (2) Air atomization/electrostatic metal casket spray booth B-60-20 and B-60-21	0.09	0.09	0	41.01	0	0	

Emission Unit	Potential to Emit						
	PM (tons/yr)	PM10/ PM2.5 (ton/yr)	SO2 (tons/yr)	VOC (tons/yr)	CO (tons/yr)	NOX (tons/yr)	HAPs (tons/yr)
Two (2) Air atomization/electrostatic metal casket spray booth B-61P-5 and B-61P-11	0.4	0.4	0	18.6	0	0	
Mis Clean-up solvent	0	0	0	24.55	0	0	
One (1) metal Urn surface coating line P-M-1 and P-M-2	0.77	0.77	0	less than 40	0	0	
One (1) wood Urn surface coating line P-W-1 and P-W-2	0.81	0.81	0		0	0	<b>Single less than 10 Total less than 25</b>
Brush sander	7.9	7.9	0	0	0	0	0
Combustion Units	1.3	5	0.4	3.7	55.8	66.4	1.2
Insignificant Activities	0.65	0.65	0	0.1	0.9	5.5	0
<b>Total Emissions</b>	<b>31.7</b>	<b>35.4</b>	<b>0.4</b>	<b>&gt; 250</b>	<b>56.7</b>	<b>71.9</b>	<b>Single greater than 10 Total greater than 25</b>

**Indiana Department of Environmental Management**  
Office of Air Quality  
Technical Support Document (TSD) for a Part 70 Operating Permit Renewal

**Source Background and Description**

<b>Source Name:</b>	Batesville Manufacturing, Inc
<b>Source Location:</b>	(1) Assembly Plant 1000 East Pearl Street, Batesville, IN 47006
	(2) Options Plant 705 East Pearl Street, Batesville, IN 47006
	(3) Stamping Plant 100 Eastern Avenue, Batesville, IN 47006
<b>County:</b>	Ripley
<b>SIC Code:</b>	3995
<b>Permit Renewal No.:</b>	T137-24390-00016
<b>Permit Reviewer:</b>	Josiah Balogun

The Office of Air Quality (OAQ) has reviewed the operating permit renewal application from Batesville Manufacturing, Inc relating to the operation of a metal burial caskets manufacturing source.

**History**

On March 1, 2007, Batesville Manufacturing, Inc submitted an application to the OAQ requesting to renew its operating permit. Batesville Manufacturing, Inc was issued a Part 70 Operating Permit Renewal on December 3, 2002.

**Source Definition**

This metal caskets manufacturing source consists of three (3) plants:

- (1) Plant #1 (Assembly Plant) is located at 1000 East Pearl Street, Batesville, Indiana 47006.
- (2) Plant #2 (Options Plant) is located at 705 East Pearl Street, Batesville, Indiana 47006.
- (3) Plant #3 (Stamping Plant) is located at 100 Eastern Avenue, Batesville, Indiana 47006.

IDEM has determined that Plants #2 and #3 are located contiguous to each other and Plant #1 is located adjacent (nearby, within 0.5 miles distance). The three (3) plants are owned and operated by one (1) company, have the same SIC codes, and more than 50% of the products in Plant #2 are shipped to Plant #1. Therefore, the term "source" in the Part 70 documents refers to the three (3) plants as one (1) source.

**Permitted Emission Units and Pollution Control Equipment**

The source, which includes three (3) plants, consists of the following permitted emission units and pollution control devices:

Plant #1 (Assembly Plant, commenced operation in late 1950's):

- (a) One (1) electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat), constructed in 1981, capable of processing approximately 50 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 14-EF-40;

- (b) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-5455 (Topcoat/Shade), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-54 and 21-EF-55;
- (c) One (1) electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 21-EF-57;
- (d) One (1) high volume low pressure (HVLP)/air atomization/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through three (3) stacks identified as 21-EF-5, 21-EF-6 and 21-EF-52;
- (e) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-2324 (Color), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-23 and 21-EF-24;
- (f) Two (2) air atomization spray booths, identified as B-60-33 (Ear) and B-60-35 (Corner) respectively, constructed in the 1960s, each using dry filters for overspray control, and each exhausting through one (1) stack identified as 60-EF-33 and 60-EF-35 respectively;
- (g) Two (2) air atomization/electrostatic disk spray booths, identified as B-60-20 (E-Room) and B-60-21 (E-Room), respectively, constructed in 1972, each using dry filters for overspray control, and each exhausting through four (4) stacks identified as 60-EF-20/60-EF-20A and 60-EF-21/60-EF-21A, respectively;
- (h) Two (2) air atomization/electrostatic spray booths, identified as B-61P-5 (Copper Line) and B-61P-11 (Copper Line), respectively, constructed in early 1972, each using waterwash for overspray control, and each exhausting through one (1) stack identified as 61P-EF-5 and 61P-EF-11, respectively;
- (i) One (1) brush sander, with a process weight rate of 2.66 tons per hour, equipped with a jet pulse baghouse, exhausting through one (1) stack inside the building, identified as S2;

Plant #2 (Options Plant):

- (j) One (1) metal urn surface coating line capable of coating approximately 36 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-M-1 and P-M-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-M-1;
- (k) One (1) wood urn surface coating line capable of coating approximately 32 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-W-1 and P-W-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-W-1; and

Plant #3 (Stamping Plant, commenced operation in the early 1950s):

- (l) Miscellaneous clean-up solvents usage throughout the plant.

### **Emission Units and Pollution Control Equipment Constructed and/or Operated without a Permit**

There are no unpermitted emission units operating at this source during this review process.

### **Emission Units and Pollution Control Equipment Removed From the Source**

No emission units and control was removed from the source.

### **Insignificant Activities**

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million British thermal units (mmBtu) per hour:
  - (1) Department 21
    - (A) one (1) natural gas fired primer oven with a rated heat input of 3.5 mmBtu/hr;
    - (B) one (1) natural gas fired topcoat oven with a rated heat input of 3.2 mmBtu/hr;
    - (C) one (1) natural gas fired rerun prime oven with a rated heat input of 0.8 mmBtu/hr;
    - (D) one (1) natural gas fired rerun topcoat oven with a rated heat input of 0.8 mmBtu/hr;
    - (E) two (2) natural gas fired rerun air make-up units each with a rated heat input of 3.6 mmBtu/hr;
    - (F) one (1) natural gas fired prime air make-up unit with a rated heat input of 6.5 mmBtu/hr;
    - (G) one (1) natural gas fired topcoat air make-up unit with a rated heat input of 2.625 mmBtu/hr;
    - (H) two (2) natural gas fired air make-up units each with a rated heat input of 4.0 mmBtu/hr;
    - (I) one (1) natural gas fired unit heater with a rated heat input of 0.3 mmBtu/hr;
    - (J) one (1) natural gas fired floor furnace with a rated heat input of 1.25 mmBtu/hr;
    - (K) one (1) natural gas fired color air make-up unit with a rated heat input of 3.5 mmBtu/hr;
    - (L) one (1) natural gas fired shade and topcoat air make-up unit with a rated heat input of 5.5 mmBtu/hr;
    - (M) one (1) natural gas fired paint mix room heater with a rated heat input of 2.0 mmBtu/hr;

- (2) Department C-14
  - (A) four (4) natural gas fired washer heaters each with a rated heat input of 1.5 mmBtu/hr;
  - (B) one (1) natural gas fired washer heater with a rated heat input of 2.5 mmBtu/hr;
  - (C) one (1) natural gas fired washer dry-off heater with a rated heat input of 1.65 mmBtu/hr;
  - (D) one (1) natural gas fired air make-up unit with a rated heat input of 2.0 mmBtu/hr;
  - (E) one (1) natural gas fired air make-up unit with a rated heat input of 2.5 mmBtu/hr;
  - (F) one (1) natural gas fired air make-up unit with a rated heat input of 2.2 mmBtu/hr;
  - (G) one (1) natural gas fired sludge dryer with a rated heat input of 0.325 mmBtu/hr;
  - (H) ten (10) natural gas fired space heaters each with a rated heat input of 0.175 mmBtu/hr;
  - (I) four (4) natural gas fired HVAC units with a total rated heat input of 0.566 mmBtu/hr;
  - (J) two (2) natural gas fired unit heaters with a total rated heat input of 0.45 mmBtu/hr;
  - (K) one (1) natural gas fired air make-up unit with a rated heat input of 0.292 mmBtu/hr;
  - (L) two (2) natural gas fired door heaters each with a rated heat input of 1.0 mmBtu/hr;
  - (M) one (1) natural gas fired heater with a rated heat input of 0.5 MMBtu/hr;
- (3) Offices
  - (A) twelve (12) natural gas fired heaters with a total rated heat input of 1.14 mmBtu/hr;
- (4) Departments C-9, C-10, C-13 and C-61P
  - (A) one (1) natural gas fired shipping air make-up unit with a rated heat input of 3.0 mmBtu/hr;
  - (B) one (1) natural gas fired air make-up unit with a rated heat input of 1.32 mmBtu/hr;
  - (C) one (1) natural gas fired unit heater with a rated heat input of 0.4 mmBtu/hr;

- (D) four (4) natural gas fired door heaters each with a rated heat input of 1.0 mmBtu/hr;
  - (F) two (2) natural gas fired furnaces each with a rated heat input of 0.625 mmBtu/hr;
  - (G) one (1) natural gas fired floor furnace with a rated heat input of 1.25 mmBtu/hr;
  - (H) three (3) natural gas fired HVAC units with a total rated heat input of 0.46 mmBtu/hr;
  - (I) two (2) natural gas fired ovens each with a rated heat input of 0.5 mmBtu/hr;
  - (J) one (1) natural gas fired air make-up unit with a total rated heat input of 2.2 mmBtu/hr;
  - (K) three (3) natural gas fired HVAC units with a total rated heat input of less than 1.5 mmBtu/hr;
- (5) Departments C-60 and C-56
- (A) one (1) natural gas fired washer heater with a rated heat input of 1.5 mmBtu/hr;
  - (B) one (1) natural gas fired dry-off heater with a rated heat input of 0.35 mmBtu/hr;
  - (C) one (1) natural gas fired caustic dip heater with a rated heat input of 1.5 mmBtu/hr;
  - (D) one (1) natural gas fired caustic rinse heater with a rated heat input of 3.8 mmBtu/hr;
  - (E) one (1) natural gas fired caustic dry-off heater with a rated heat input of 0.8 mmBtu/hr;
  - (F) one (1) natural gas fired base coat oven with a rated heat input of 1.5 mmBtu/hr;
  - (G) two (2) natural gas fired air make-up units each with a rated heat input of 3.15 mmBtu/hr;
  - (H) one (1) natural gas fired air make-up unit with a rated heat input of 2.0 mmBtu/hr;
  - (I) one (1) natural gas fired paint mix room air make-up unit with a rated heat input of 0.292 mmBtu/hr;
  - (J) one (1) natural gas fired unit heater with a rated heat input of 0.3 mmBtu/hr;
  - (K) five (5) natural gas fired holding furnaces each with a rated heat input of 0.25 mmBtu/hr;
  - (L) one (1) natural gas fired key machine furnace with a rated heat input of 0.25 mmBtu/hr;

- (M) one (1) natural gas fired premelt furnace with a rated heat input of 1.675 mmBtu/hr;
- (N) one (1) natural gas fired holding furnace with a rated heat input of 1.1 mmBtu/hr;
- (O) one (1) natural gas fired reclaim furnace with a rated heat input of 1.0 mmBtu/hr;
- (P) one (1) natural gas fired heater with a rated heat input of 0.5 MMBtu/hr;
- (6) Stamping Plant:
  - (A) two (2) natural gas fired phosphate washer heaters each with a rated heat input of 2.5 mmBtu/hr;
  - (B) one (1) natural gas fired cap washer heater with a rated heat input of 2.5 mmBtu/hr;
  - (C) six (6) natural gas fired space heaters each with a rated heat input of 0.175 mmBtu/hr;
  - (D) two (2) natural gas fired door heaters each with a rated heat input of 1.0 mmBtu/hr;
  - (E) one (1) natural gas fired air make-up unit with a rated heat input of 4.0 mmBtu/hr;
  - (F) one (1) natural gas fired air make-up unit with a rated heat input of 4.75 mmBtu/hr;
  - (G) one (1) natural gas fired air make-up unit with a rated heat input of 0.75 mmBtu/hr;
- (7) Options Plant:
  - (A) two (2) natural gas fired air make-up units each with a rated heat input of 0.896 mmBtu/hr;
  - (B) various soldering irons with a total rated heat input of 1.6 mmBtu/hr;
- (b) Propane or liquefied petroleum gas, or butane-fired combustion sources with heat input equal to or less than 6.0 mmBtu/hr;
- (c) Combustion source flame safety purging on startup;
- (d) A gasoline fuel transfer and dispensing operation handling less than or equal to 1,300 gallons per day, such as filling of tanks, locomotives, automobiles, having a storage capacity less than or equal to 10,500 gallons;
- (e) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons;
- (f) Vessels storing lubricating oils, hydraulic oils, machining oils, and machining fluids;
- (g) Filling drums, pails or other packaging containers with lubricating oils, waxes, and greases;

- (h) Application of oils, greases, lubricants or other nonvolatile materials applied as temporary protective coatings;
- (i) Machining where an aqueous cutting coolant continuously floods the machining interface;
- (j) Cleaners and solvents characterized as follows:
  - (1) having a vapor pressure equal to or less than 2 kPa, 15 mmHg, or 0.3 psi measured at 38°C (100°F) or;
  - (2) having a vapor pressure equal to or less than 0.7 kPa, 5 mmHg, or 0.1 psi measured at 20°C (68°F);
- (k) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment;
- (l) Closed loop heating and cooling systems;
- (m) Infrared cure equipment;
- (n) Activities associated with the treatment of wastewater streams with an oil and grease content less than or equal to 1% by volume;
- (o) Any operation using aqueous solutions containing less than 1% by weight of VOCs excluding HAPs;
- (p) Forced and induced draft cooling tower system not regulated under a NESHAP;
- (q) Replacement or repair of electrostatic precipitators, bags in baghouses and filters in other air filtration equipment;
- (r) Heat exchanger cleaning and repair;
- (s) Process vessel degassing and cleaning to prepare for internal repairs;
- (t) Paved and unpaved roads and parking lots with public access;
- (u) Enclosed systems for conveying plastic raw materials and plastic finished goods;
- (v) Asbestos abatement projects regulated by 326 IAC 14-10;
- (w) Purging of gas lines and vessels that is related to routine maintenance and repair of buildings, structures, or vehicles at the source where air emissions from those activities would not be associated with any product process;
- (x) Equipment used to collect any material that might be released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separators, tanks, and fluid handling equipment;
- (y) Blowdown for any of the following: sight glass, boiler, compressors, pumps, and cooling tower;
- (z) Diesel generators not exceeding 1600 horsepower;
- (aa) Stationary fire pumps;
- (bb) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 cubic feet per

- minute, including the following; deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations;
- (cc) Filter or coalescer media changeout;
  - (dd) Mold release agents using low volatile products (vapor pressure less than or equal to 2 kilopascals measured at 38°C);
  - (ee) A laboratory as defined in 326 IAC 2-7-1 (21) (C);
  - (ff) The following operations emitting greater than 1 pound per day but less than 5 pounds per day or 1 ton per year of a single HAP:
    - (1) welding operations in Department C-14;
    - (2) zinc melting operations in Department C-56;
    - (3) zinc casting operations in Department C-56;
    - (4) vacuum metalizing operations in Departments C-60 & C61;
    - (5) welding operations in Stamping Plant;
    - (6) welding operations in Optional Plant;
  - (gg) The following operations emitting greater than 1 pound per day but less than 12.5 pounds per day of any combinations of HAPs:
    - (1) Aboveground storage tanks gasoline (300 gallons), wastewater blending (normally empty, 12,000 gallons), and miscellaneous chemicals (KOH with traces of phenol and glycol ether) (10,000 gallons);
    - (2) drums/totes containing miscellaneous chemicals including coatings and solvents, hydraulic oil/machine oils;
    - (3) two (2) bulk paint tanks (3,000 gallons each); and
  - (hh) The following activities or categories not previously identified:
    - (1) plastic grinding operation;
    - (2) foot lining mattress, fabric interior and installation in Department C-13;
    - (3) process-related vehicular traffic on paved roads;
    - (4) process-related vehicular traffic on unpaved roads;
    - (5) wastewater treatment and sludge dryer;
    - (6) woodworking operations woodworking operations in Options Plant controlled by baghouse BW-1 and exhausting inside the building.

### **Existing Approvals**

Since the issuance of the Part 70 Operating Permit T137-7280-00016 on December 3, 2002, the source has constructed or has been operating under the following approvals as well:

- (a) Review Request No. 137-16400-00016 issued on December 1, 2004.

All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

### **Enforcement Issue**

There are no enforcement actions pending.

**Emission Calculations**

See Appendix A of this document for detailed emission calculations.

**County Attainment Status**

The source is located in Ripley County

Pollutant	Designation
SO <sub>2</sub>	Better than national standards.
CO	Unclassifiable or attainment effective November 15, 1990.
O <sub>3</sub>	Unclassifiable or attainment effective June 15, 2004, for the 8-hour ozone standard. <sup>1</sup>
PM <sub>10</sub>	Unclassifiable effective November 15, 1990.
NO <sub>2</sub>	Cannot be classified or better than national standards.
Pb	Not designated.
<sup>1</sup> Unclassifiable or attainment effective October 18, 2000, for the 1-hour ozone standard which was revoked effective June 15, 2005. Unclassifiable or attainment effective April 5, 2005, for PM2.5.	

(a) Ozone Standards

- (1) On October 25, 2006, the Indiana Air Pollution Control Board finalized a rule revision to 326 IAC 1-4-1 revoking the one-hour ozone standard in Indiana.
- (2) On September 6, 2007, the Indiana Air Pollution Control Board finalized a temporary emergency rule to re-designate Allen, Clark, Elkhart, Floyd, LaPorte, St. Joseph as attainment for the 8-hour ozone standard.
- (3) On November 9, 2007, the Indiana Air Pollution Control Board finalized a temporary emergency rule to re-designate Boone, Clark, Elkhart, Floyd, LaPorte, Hamilton, Hancock, Hendricks, Johnson, Madison, Marion, Morgan, Shelby, and St. Joseph as attainment for the 8-hour ozone standard.
- (4) Volatile organic compounds (VOC) and Nitrogen Oxides (NOx) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NOx emissions are considered when evaluating the rule applicability relating to ozone. Ripley County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

(b) PM2.5

Ripley County has been classified as attainment for PM2.5. On May 8, 2008 U.S. EPA promulgated the requirements for Prevention of Significant Deterioration (PSD) for PM2.5 emissions, and the effective date of these rules was July 15<sup>th</sup>, 2008. Indiana has three years from the publication of these rules to revise its PSD rules, 326 IAC 2-2, to include those requirements. The May 8, 2008 rule revisions require IDEM to regulate PM10 emissions as a surrogate for PM2.5 emissions until 326 IAC 2-2 is revised.

(c) Other Criteria Pollutants

Ripley County has been classified as attainment or unclassifiable in Indiana for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

- (d) **Fugitive Emissions**  
Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 or 326 IAC 2-3, fugitive emissions are not counted toward the determination of PSD and Emission Offset applicability.

**Unrestricted Potential Emissions**

This table reflects the unrestricted potential emissions of the source.

<b>Pollutant</b>	<b>tons/year</b>
PM	> 250
PM <sub>10</sub>	> 250
SO <sub>2</sub>	< 250
VOC	> 250
CO	< 250
NO <sub>x</sub>	< 250

<b>HAPs</b>	<b>tons/year</b>
Single HAP	> 10
Total HAPs	> 25

- (a) The potential to emit (as defined in 326 IAC 2-7-1(29)) of PM10 and VOC are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) The potential to emit (as defined in 326 IAC 2-7-1(29)) of all other criteria pollutants are less than 100 tons per year.
- (c) The potential to emit (as defined in 326 IAC 2-7-1(29)) of any single HAP is equal to or greater than ten (10) tons per year and/or the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination of HAPs is equal to or greater than twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (d) Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-7, fugitive emissions are not counted toward the determination of Part 70 applicability.

**Part 70 Permit Conditions**

This source is subject to the requirements of 326 IAC 2-7, pursuant to which the source has to meet the following:

- (a) Emission limitations and standards, including those operational requirements and limitations that assure compliance with all applicable requirements at the time of issuance of Part 70 permits.
- (b) Monitoring and related record keeping requirements which assume that all reasonable information is provided to evaluate continuous compliance with the applicable requirements.

**Potential to Emit After Issuance**

The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered federally enforceable only after issuance of this Part 70 permit renewal, and only to the extent that the effect of the control equipment is made practically enforceable in the permit.

Emission Unit	Potential to Emit							
	PM (tons/yr)	PM10/PM2.5 (ton/yr)	SO2 (tons/yr)	VOC (tons/yr)	CO (tons/yr)	NOX (tons/yr)	HAPs (tons/yr)	
Electrostatic metal casket spray booth B-14-40	2.26	2.26	0	less than 25	0	0	Single greater than 9 Total greater than 24	
Air atomization/electrostatic metal casket spray booth B-21-5455	0.67	0.67	0	26.08	0	0		
Electrostatic metal casket spray booth B-21-5455	3.84	3.84	0	less than 40	0	0		
HVLP/ air atomization/electrostatic metal casket spray booth B-21-5652	4.22	4.22	0	less than 40	0	0		
Air atomization/electrostatic metal casket spray booth B-21-2324	4.09	4.09	0	205.7	0	0		
Three (3) Air atomization/electrostatic metal casket spray booth B-60-33, B-60-35 and B-60-39	4.71	4.71	0	215.9	0	0		
Two (2) Air atomization/electrostatic metal casket spray booth B-60-20 and B-60-21	0.09	0.09	0	41.01	0	0		
Two (2) Air atomization/electrostatic metal casket spray booth B-61P-5 and B-61P-11	0.4	0.4	0	18.6	0	0		
One (1) Wood Urn surface coating line P-W-1 and P-W-2	0.81	0.81	0	less than 40	0	0		
One (1) metal Urn surface coating line P-M-1 and P-M-2	0.77	0.77	0		0	0		
Mis Clean-up solvent	0	0	0	24.55	0	0		
Brush sander	7.9	7.9	0	0	0	0		0

Emission Unit	Potential to Emit						
	PM (tons/yr)	PM10/PM2.5 (ton/yr)	SO2 (tons/yr)	VOC (tons/yr)	CO (tons/yr)	NOX (tons/yr)	HAPs (tons/yr)
Combustion Units	1.3	5	0.4	3.7	55.8	66.4	1.2
Insignificant Activities	0.65	0.65	0	0.1	0.9	5.5	0
Total Emissions	31.7	35.4	0.4	> 250	56.7	71.9	Single greater than 10 Total greater than 25

- (a) This existing stationary source is major for PSD because the emissions of at least one regulated pollutant are greater than two hundred fifty (>250) tons per year, and is not one of the twenty-eight (28) listed source categories.
- (b) Fugitive Emissions  
 Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2, fugitive emissions are not counted toward the determination of PSD applicability.

**Federal Rule Applicability**

- (a) Pursuant to 40 CFR 64.2, Compliance Assurance Monitoring (CAM) is applicable to existing emission units that involve a pollutant-specific emission unit and meet the following criteria:
  - (1) has a potential to emit before controls equal to or greater than the major source threshold for the pollutant involved;
  - (2) is subject to an emission limitation or standard for that pollutant; and
  - (3) uses a control device, as defined in 40 CFR 64.1, to comply with that emission limitation or standard.

The emission units have the potential to emit of regulated pollutants (uncontrolled) less than the major source thresholds.

The VOC emissions from the spray booths are more than the major source threshold but the spray booths have no control devices.

Based on this evaluation, the requirements of 40 CFR Part 64, CAM are not applicable to any of the existing units as part of this Part 70 permit renewal.

- (b) All the storage tanks at the source have individual storage capacities of less than 10,500 gallons (40 cubic meter). Therefore, the requirements of New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60 Subpart Kb) are not included in the permit for this source.
- (c) The fourteen (14) paint booths and the clean-up solvents are subject to the National Emission Standards for Hazardous Air Pollutants for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR Part 63, Subpart Mmmm). The metal parts surface coating operations and associated operations are subject to 40 CFR Part

63, Subpart MMMM because they are located at a major source of HAPs and perform the surface coating of metal parts and products (defined by 40 CFR 63.3981(a)). Pursuant to 40 CFR 63.3982(b), the affected source is the collection of all of the items listed in (1) through (4) below that are used for surface coating of metal parts and products within each subcategory.

- (1) All coating operations as defined in 40 CFR 63.3981;
- (2) All storage containers and mixing vessels in which coatings, thinners and/or other additives, and cleaning materials are stored or mixed;
- (3) All manual and automated equipment and containers used for conveying coatings, thinners and/or other additives, and cleaning materials; and
- (4) All storage containers and all manual and automated equipment and containers used for conveying waste materials generated by a coating operation.

The facilities subject to this rule include the followings:

Plant #1 (Assembly Plant, commenced operation in late 1950's):

- (a) One (1) electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat), constructed in 1981, capable of processing approximately 50 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 14-EF-40;
- (b) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-5455 (Topcoat/Shade), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-54 and 21-EF-55;
- (c) One (1) electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through one (1) stack identified as 21-EF-57;
- (d) One (1) high volume low pressure (HVLP)/air atomization/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through three (3) stacks identified as 21-EF-5, 21-EF-6 and 21-EF-52;
- (e) One (1) air atomization/electrostatic metal casket spray booth, identified as B-21-2324 (Color), constructed in the 1960s, capable of processing approximately 90 caskets per hour, using waterwash for overspray control, and exhausting through two (2) stacks identified as 21-EF-23 and 21-EF-24;
- (f) Two (2) air atomization spray booths, identified as B-60-33 (Ear) and B-60-35 (Corner) respectively, constructed in the 1960s, each using dry filters for overspray control, and each exhausting through one (1) stack identified as 60-EF-33 and 60-EF-35 respectively;
- (g) Two (2) air atomization/electrostatic disk spray booths, identified as B-60-20 (E-Room) and B-60-21 (E-Room), respectively, constructed in 1972, each using dry filters for overspray control, and each exhausting through four (4) stacks identified as 60-EF-20/60-EF-20A and 60-EF-21/60-EF-21A, respectively;
- (h) Two (2) air atomization/electrostatic spray booths, identified as B-61P-5 (Copper Line) and B-61P-11 (Copper Line), respectively, constructed in early 1972, each using waterwash for

overspray control, and each exhausting through one (1) stack identified as 61P-EF-5 and 61P-EF-11, respectively;

- (i) One (1) brush sander, with a process weight rate of 2.66 tons per hour, equipped with a jet pulse baghouse, exhausting through one (1) stack inside the building, identified as S2;

Plant #2 (Options Plant):

- (j) One (1) metal urn surface coating line capable of coating approximately 36 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-M-1 and P-M-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-M-1;
- (k) One (1) wood urn surface coating line capable of coating approximately 32 urns per hour, constructed in 1999, consisting of two (2) spray booths, identified as P-W-1 and P-W-2, each utilizing high volume low pressure (HVLP) spray equipment and dry filters for particulate matter control, and exhausting through one (1) stack ID S-W-1; and

Plant #3 (Stamping Plant, commenced operation in the early 1950s):

- (l) Miscellaneous clean-up solvents usage throughout the plant.

Nonapplicable portions of the NESHAP will not be included in the permit. These emission units are subject to the following portions of Subpart M MMMM:

40 CFR 63.3880  
40 CFR 63.3881(a)(1-3), (b)  
40 CFR 63.3882  
40 CFR 63.3883, (b), (d)  
40 CFR 63.3890(b)(1-2), (c)  
40 CFR 63.3891, (a)(b)  
40 CFR 63.3892(a)  
40 CFR 63.3893(a)  
40 CFR 63.3900(a)(1), (b)  
40 CFR 63.3901  
40 CFR 63.3910(a), (b), (c)(1-7), (c)(8)(i), (c)(10-11)  
40 CFR 63.3920(a)(1-2), (a)(3)(i-iv, vi-vii), (a)(4-5)  
40 CFR 63.3930, (a-b), (c)(1-2), (d-g), (h-j)  
40 CFR 63.3931  
40 CFR 63.3940  
40 CFR 63.3941  
40 CFR 63.3942  
40 CFR 63.3950  
40 CFR 63.3951  
40 CFR 63.3952  
40 CFR 63.3980  
40 CFR 63.3981

Applicable portions of Tables 1, 2, 3, and 4 of 40 CFR 63, Subpart M MMMM

The provisions of 40 CFR 63 Subpart A – General Provisions, which are incorporated as 326 IAC 20-1-1, apply to the facilities described in this section except when otherwise specified in 40 CFR 63 Subpart M MMMM.

### **State Rule Applicability - Entire Source**

#### 326 IAC 2-2 (Prevention of Significant Deterioration)

This source was constructed before 1977 and at that time it has the potential to emit of at least one regulated pollutant greater than 250 tons per year. Therefore the source was a major source for PSD in 1977, and it is not one of the twenty-eight (28) listed sources.

#### 1981 Modification

Pursuant to 326 IAC 8-1-6 and MSM 137-14731-00016, issued on October 9, 2001, the VOC emissions from the electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat) shall be limited to less than 25 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with this limit will limit the VOC emissions to less than 25 tons per year and render the requirements of 326 IAC 8-1-6 and 326 IAC 2-2 (PSD) not applicable to 1981 modification.

#### 1992 Modification

The HVL/ air atomization/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992 has uncontrolled VOC emissions of more than 40 tons per year. The use of VOC solvents at the booth, identified as B-21-5652 (Prime) in Plant #1 shall not exceed 96 tons per twelve (12) consecutive month period with compliance determined at the end of each month. This limit effectively restricts the net contemporaneous VOC emission increase from the booth to less than 40 tons per year. Compliance with the above limit will render 326 IAC 2-2 (PSD) not applicable to 1992 modification.

#### 1993 Modification

The electrostatic metal casket spray booth, identified as B-21-57 (Topcoat), constructed in 1993 has uncontrolled VOC emissions of more than 40 tons per year. The VOC input to the spray booth identified as B-21-57(Topcoat) shall be limited to less than 88.3 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with the above limit will limit the VOC emissions from the electrostatic metal casket spray booth, identified as B-21-57 (Topcoat) to less than 40 tons per year and render 326 IAC 2-2 (PSD) not applicable to 1993 modification.

#### 1999 Modification

Pursuant to CP 137-10452-00016, issued on April 29, 1999, the wood urn surface coating line and metal urn surface coating line, constructed in 1999 have uncontrolled VOC emissions of more than 40 tons per year. The wood urn surface coating line and metal urn surface coating line shall use less than 40 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve consecutive month period, with compliance determined at the end of each month period.

Pursuant to 326 IAC 8-1-6 and CP 137-10452-00016, issued on April 29, 1999, the metal urn surface coating line shall use less than 25 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve (12) consecutive month period, with compliance determined at the end of each month.

Compliance with the above limits will limit the VOC emissions from the wood urn surface coating line and metal urn surface coating line to less than 25 tons per year and render 326 IAC 8-1-6 and 326 IAC 2-2 (PSD) not applicable to 1999 modification.

326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP))

The operation of the fourteen (14) paint booths and the clean-up solvents will emit greater than ten (10) tons per year for a single HAP and greater than twenty-five (25) tons per year for a combination of HAPs). Therefore, 326 IAC 2-4.1 would apply to the fourteen (14) spray booths, and the clean-up solvent. However, pursuant to 326 IAC 2-4.1-1(b)(2), because this fourteen (14) paint booths, are specifically regulated by NESHAP 40 CFR 63, Subpart M, which was issued pursuant to Section 112(d) of the CAA, this fourteen (14) paint booths and the clean-up solvents are exempt from the requirements of 326 IAC 2-4.1.

326 IAC 2-6 (Emission Reporting)

This source is subject to 326 IAC 2-6 (Emission Reporting) because it is required to have an operating permit under 326 IAC 2-7, Part 70 program. Pursuant to this rule, the Permittee shall submit an emission statement certified pursuant to the requirements of 326 IAC 2-6. In accordance with the compliance schedule specified in 326 IAC 2-6-3, an emission statement must be submitted triennially by July 1 beginning in 2006 and every 3 years after. Therefore, the next emission statement for this source must be submitted by July 1, 2009. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

**State Rule Applicability – Individual Facilities**

326 IAC 6-3-2 (Particulate Emission Limitations for Work Practices and Control Technologies)

Pursuant to 326 IAC 6-3-2(d), the particulate matter (PM) from the seven (7) spray booths, identified as B-60-33, B-60-35, B-60-39, B-60-20, B-60-21 P-M-1, P-M-2, P-W-1 and P-W-2 Shall be controlled by dry filters and the seven (7) spray booths, identified as B-14-40, B-21-5455, B-21-57, B-21-5652, B-21-2324, B-61P-5 and B-61P-11 shall be controlled by water wash curtain and the Permittee shall operate the filters and water wash curtain in accordance with manufacturer's specifications.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

Pursuant to 326 IAC 6-3-2, the particulate emissions from the insignificant activities, wood working brazing equipment, cutting torches, soldering equipment and welding equipment and grinding and machining operation shall be limited by the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

Where:

E = rate of emission in pounds per hour and  
P = process weight rate in tons per hour

The baghouse shall be in operation at all times the grinding and machining and the wood working operation are in operation, in order to comply with this limit.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)  
Pursuant to 326 IAC 6-3-2, (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate matter (PM) emission rate from the brush sander shall not exceed 7.90 pounds per hour when operating at a process weight rate of less than 2.66 tons per hour.

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The baghouse shall be in operation at all times the brush sander is in operation, in order to comply with this limit.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)  
Pursuant to 326 IAC 6-3-1(b)(5), the potential particulate emissions from the following emission units are less than 0.551 pounds per hour.

- (1) welding operations in Department C-14;
- (2) zinc melting operations in Department C-56;
- (3) zinc casting operations in Department C-56;
- (4) vacuum metalizing operations in Departments C-60 & C61;
- (5) welding operations in Stamping Plant;
- (6) welding operations in Optional Plant;

Therefore, they are exempt from the 326 IAC 6-3 rule.

326 IAC 8-1-6 (New Facilities; General Reduction Requirements)

This rule applies to facilities located anywhere in the state that were constructed on or after January 1, 1980, and which have potential volatile organic compound (VOC) emissions of 25 tons per year or more and are not otherwise regulated by other provisions of article 8.

- (a) The electrostatic metal casket spray booth, identified as B-14-40 (Brush Seal Coat), constructed in 1981, has uncontrolled VOC emissions greater than 25 tons per year. The VOC emissions from the electrostatic metal casket spray booth, identified as B-14-40 shall be limited to less than 25 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with this limit will limit the VOC emissions to less than 25 tons per year and render the requirements of 326 IAC 8-1-6 not applicable to the electrostatic metal casket spray booth.

- (b) Pursuant to CP137-2381-00004, issued on June 25, 1992, the HVLP/electrostatic metal casket spray booth, identified as B-21-5652 (Prime), constructed in 1992 shall be using coating materials with VOC contents, as applied to the casket, not exceeding 4.6 pounds per gallon less water, expressed as a daily volume-weighted average.

This daily volume weighted average shall be determined by the following equation:

$$A = \sum [(Dc \times Wo \times G) / (1 - Vw \times (Dc/Dw))] / \sum G$$

Where:

A is the daily volume weighted average in pounds VOC per gallon less water as applied;  
Wo is the VOC content of the coating in weight % organic;  
G is the gallon of material (gal/unit);  
Vw is the volume % of water in coating;  
Dc is the density of coating (lb/gal); and  
Dw is the density of water (lb/gal).

- (c) Pursuant to CP137-2866-00004, issued on May 26, 1993, the electrostatic metal casket spray booth, identified as B-21-57 (Topcoat 2), constructed in 1993 shall be:
- (1) using the coating materials with VOC content, as applied to the caskets not exceeding 4.7 pounds per gallon less water;
  - (2) Using electrostatic rotary atomizer spray equipments.

Compliance with this limit will render the requirements of 326 IAC 8-1-6 not applicable to this emission unit.

- (d) The metal urn surface coating line, identified as P-M-1 and P-M-2, constructed in 1999, has uncontrolled VOC emissions greater than 25 tons per year. The metal urn surface coating line shall use less than 25 tons of VOC, including coatings, dilution solvents and cleaning solvents per twelve (12) consecutive month period, with compliance determined at the end of each month.

Compliance with this limit will limit the VOC emissions to less than 25 tons per year and render the requirements of 326 IAC 8-1-6 not applicable to the metal urn surface coating line.

#### 326 IAC 8-2-12 (Wood Furniture and Cabinet Coating)

Pursuant to 326 IAC 8-2-12 (Wood Furniture and Cabinet Coating), the wood urn surface coating line, identified as P-W-1 and P-W-2 shall utilize one of the following application methods:

- (1) Airless Spray Application
- (2) Air Assisted Airless Spray Application
- (3) Electrostatic Spray Application
- (4) Electrostatic Bell or Disc Application
- (5) Heated Airless Spray Application
- (6) Roller Coating
- (7) Brush or Wipe Application
- (8) Dip-and-Drain Application

High Volume Low Pressure (HVLP) Spray Application is an accepted alternative method of application for Air Assisted Airless Spray Application. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

#### 326 IAC 8-4 (Petroleum Sources)

Pursuant to 326 IAC 8-4-1, the gasoline dispensing operation at the source is not subject to the requirements of 326 IAC 8-4 (Petroleum Sources), because the source is not located in one of the county listed in 326 IAC 8-4-1(a). Therefore, the requirements of 326 IAC 8-4 do not apply.

#### 326 IAC 8-6 (Organic Solvent Emission Limitations)

This rule applies to sources commencing operation after October 7, 1974 and prior to January 1, 1980, located anywhere in the state, with potential VOC emissions of 100 tons per year or more, and not

regulated by any other provision of Article 8. All spray booths and solvent usage operations at the source commenced either prior to October 7, 1974 or after January 1, 1980. Therefore, the source is not subject to the requirements of 326 IAC 8-6.

### **Compliance Determination and Monitoring Requirements**

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with all applicable state and federal rules on a continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a continuous demonstration. When this occurs, IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, Compliance Determination Requirements are included in the permit. The Compliance Determination Requirements in Section D of the permit are those conditions that are found directly within state and federal rules and the violation of which serves as grounds for enforcement action.

If the Compliance Determination Requirements are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

The source shall implement the following operator-training programs for the operations of all surface coating booths:

- (a) All operators that perform paint spray operations or booth maintenance shall be trained in the proper set-up and operation of the particulate control system. All existing operators shall be trained annually. All new operators shall be trained upon hiring or transfer.
- (b) Training shall include proper waterwash flow pattern and flow rate, filter alignment, filter inspection and maintenance, and trouble shooting practices. The training program shall be written and retained on site. The training program shall include a description of the methods to be used at the completion of initial and refresher training to demonstrate and document successful completion. Copies of the training program, the list of trained operators, and training records shall be maintained on site or available within one hour for inspection by IDEM.
- (c) All operators shall be given refresher training annually.

These monitoring conditions are necessary because the waterwash and dry filters must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-7 (Part 70).

### **Recommendation**

The staff recommends to the Commissioner that the Part 70 Operating Permit Renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on March 1, 2007.

## **Conclusion**

The operation of this metal burial caskets manufacturing source shall be subject to the conditions of the attached Part 70 Operating Permit Renewal No. T137-24390-00016.

Emission Summary

Source Name: Batesville Manufacturing, Inc  
 Source Location: 1000 East Pearl Street, IN 47006  
 Permit Number: T137-24390-00016  
 Permit Reviewer: Josiah Balogun  
 Date: 21-Aug-2008

Uncontrolled Potential Emissions

Emission Unit	Year of Construction	PM (tons/yr)	PM <sub>10</sub> (tons/yr)	SO <sub>2</sub> (tons/yr)	VOC (tons/yr)	CO (tons/yr)	NOx (tons/yr)	HAPs (tons/yr)
Electrostatic metal casket spray booth B-14-40	1981	45.26	45.26	0	88.9	0	0	Single HAP > 9 Combined HAPs > 24
Air atomization/electrostatic metal casket spray booth B-21-5455	1960	13.36	13.36	0	26.08	0	0	
Electrostatic metal casket spray booth B-21-57	1993	76.84	76.84	0	150.02	0	0	
HVLP/ air atomization/electrostatic metal casket spray booth B-21-5652	1992	84.31	84.31	0	120.47	0	0	
Air atomization/electrostatic metal casket spray booth B-21-2324	1960	81.73	81.73	0	205.7	0	0	
Three (3) Air atomization/electrostatic metal casket spray booth B-60-33, B-60-35 and B-60-39	1960	94.24	74.24	0	215.9	0	0	
Two (2) Air atomization/electrostatic disk casket spray booth B-60-20 and B-60-21	1972	1.73	1.73	0	41.01	0	0	
Two (2) Air atomization/electrostatic metal casket spray booth B-61P-5 and B-61P-11	1972	7.91	7.91	0	18.6	0	0	
One (1) wood Urn surface coating line P-W-1 and P-W-2	1999	16.24	16.24	0	150.88	0	0	
One (1) metal Urn surface coating line P-M-1 and P-M-2	1999	15.34	15.34	0	38.88	0	0	
Mis Clean-up solvent Brush sander		0	0	0	24.55	0	0	
		7.9	7.9	0	0	0	0	
Combustion Units		1.3	5	0.4	3.7	55.8	66.4	
Insignificant Activities		0.65	0.65	0	0.1	0.9	5.5	0
Total Emissions		446.8	430.5	0.4	1084.79	56.7	71.9	Single HAP > 10 Combined HAPs > 25

Appendix A: Emissions Calculations

Emission Summary

Source Name: Batesville Manufacturing, Inc  
 Source Location: 1000 East Pearl Street, IN 47006  
 Permit Number: T137-24390-00016  
 Permit Reviewer: Josiah Balogun  
 Date: 21-Aug-2008

Limited Potential Emissions

Emission Unit	Year of Construction	PM (tons/yr)	PM <sub>10</sub> (tons/yr)	SO <sub>2</sub> (tons/yr)	VOC (tons/yr)	CO (tons/yr)	NOx (tons/yr)	HAPs (tons/yr)
Electrostatic metal casket spray booth B-14-40	1981	2.26	2.26	0	less than 25	0	0	Single HAP > 9 Combined HAPs > 24
Air atomization/electrostatic metal casket spray booth B-21-5455	1960	0.67	0.67	0	26.08	0	0	
Electrostatic metal casket spray booth B-21-57	1993	3.84	3.84	0	less than 40	0	0	
HVLP/ air atomization/electrostatic metal casket spray booth B-21-5652	1992	4.22	4.22	0	less than 40	0	0	
Air atomization/electrostatic metal casket spray booth B-21-2324	1960	4.09	4.09	0	205.7	0	0	
Three (3) Air atomization/electrostatic metal casket spray booth B-60-33, B-60-35 and B-60-39	1960	4.71	4.71	0	215.9	0	0	
Two (2) Air atomization/electrostatic disk casket spray booth B-60-20 and B-60-21	1972	0.09	0.09	0	41.01	0	0	
Two (2) Air atomization/electrostatic metal casket spray booth B-61P-5 and B-61P-11	1972	0.4	0.4	0	18.6	0	0	
One (1) wood Urn surface coating line P-W-1 and P-W-2	1999	0.81	0.81	0	less than 40	0	0	
One (1) metal Urn surface coating line P-M-1 and P-M-2	1999	0.77	0.77	0		0	0	
Mis Clean-up solvent		0	0	0	24.55	0	0	
Brush sander		7.9	7.9	0	0	0	0	
Combustion Units		1.3	5	0.4	3.7	55.8	66.4	
Insignificant Activities		0.65	0.65	0	0.1	0.9	5.5	0
Total Emissions		31.7	35.4	0.4	greater than 250	56.7	71.9	Single HAP >10 Combined HAPs > 25

**Appendix A: Emission Calculations  
VOC and Particulate**

**Company Name:** Batesville Manufacturing, Inc  
**Address City IN Zip:** 1000 East Pearl Street, IN 47006  
**Permit Number:** T137-24390-00016  
**Reviewer:** Josiah Balogun  
**Date:** 21-Aug-2008

Emission Units	Material	Density (Lb/Gal)	Weight % Volatile (H2O& Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Vol (solids)	Gal of Mat (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC tons per year	Particulate Potential ton/yr	Control efficiency	Control Emission (tons/yr)	lb VOC /gal solids	Transfer Efficiency
<b>Assembly Plant</b>																	
B-14-40	Burgundy	8.83	32.93%	0.00%	32.93%	0.00%	61.32%	0.1745	40.00	2.9	2.91	88.90	45.26	95.00%	2.26	4.74	75.00%
B-21-5455	Top Coat	8.80	32.80%	0.00%	32.80%	0.00%	61.56%	0.0262	78.80	2.9	2.89	26.08	13.36	95.00%	0.67	4.69	75.00%
	Pearl Mica (Top Coat)	9.00	54.02%	0.00%	54.02%	0.00%	47.08%	0.0500	1.20	4.9	4.86	1.28	0.27	95.00%	0.01	10.33	75.00%
	Gold Sparkle	8.50	36.29%	0.00%	36.29%	0.00%	54.39%	0.0500	80.00	3.1	3.08	54.04	23.72	95.00%	1.19	5.67	75.00%
B-21-57	Top Coat	8.80	32.80%	0.00%	32.80%	0.00%	61.56%	0.1483	80.00	2.9	2.89	150.02	76.84	95.00%	3.84	4.69	75.00%
B-21-5652	Primer	12.30	26.32%	0.00%	26.32%	0.00%	56.21%	0.1062	80.00	3.2	3.24	120.47	84.31	95.00%	4.22	5.76	75.00%
	Top Coat	8.80	32.80%	0.00%	32.80%	0.00%	61.56%	0.0350	3.13	2.9	2.89	1.38	0.71	95.00%	0.04	4.69	75.00%
B-21-2324	Carnation	10.60	38.62%	0.00%	38.62%	0.00%	39.46%	0.14340	80.00	4.1	4.09	205.70	81.73	95.00%	4.09	10.37	75.00%
B-60-33	Catalyst #19	12.70	0.84%	0.00%	0.84%	0.00%	98.71%	0.10730	30.00	0.1	0.11	1.50	44.39	95.00%	2.22	0.11	75.00%
	Lord 406 Adhesive	9.40	0.00%	0.00%	0.00%	0.00%	100.00%	0.30520	30.00	0.0	0.00	0.00	94.24	95.00%	4.71	0.00	75.00%
B-60-33	Toluene	7.30	100.00%	0.00%	100.00%	0.00%	0.00%	0.00996	1.00	7.3	7.30	0.32	0.00	95.00%	0.00	#DIV/0!	75.00%
	Catalyst	9.80	25.00%	0.00%	25.00%	0.00%	63.74%	0.19400	1.00	2.5	2.45	2.08	1.56	95.00%	0.08	3.84	75.00%
B-60-33	SC-100	7.30	100.00%	0.00%	100.00%	0.00%	0.00%	6.72700	1.00	7.3	7.30	215.09	0.00	95.00%	0.00	#DIV/0!	75.00%
	BCA-Glycol Ether DB Acetate	8.20	100.00%	0.00%	100.00%	0.00%	0.00%	0.16440	1.00	8.2	8.20	5.90	0.00	95.00%	0.00	#DIV/0!	75.00%
<b>Hardware</b>	Plastic prep coat	9.60	70.00%	70.00%	0.00%	0.00%	30.00%	0.05430	1.00	0.0	0.00	0.00	0.17	95.00%	0.01	0.00	75.00%
	Plastic basecoat	7.60	71.05%	0.00%	71.05%	0.00%	25.00%	0.00020	1462.5	5.4	5.40	6.92	0.70	95.00%	0.04	21.60	75.00%
	Hi Solids sealcoat	7.60	85.55%	0.00%	85.55%	0.00%	7.00%	0.00040	1462.5	6.5	6.50	16.66	0.70	95.00%	0.04	92.88	75.00%
	Plastic basecoat	7.60	71.05%	0.00%	71.05%	0.00%	25.00%	0.00160	450.0	5.4	5.40	17.03	1.73	95.00%	0.09	21.60	75.00%
	Hi Solids sealcoat	7.60	85.55%	0.00%	85.55%	0.00%	7.00%	0.00320	450.0	6.5	6.50	41.01	1.73	95.00%	0.09	92.88	75.00%
	Plastic basecoat	7.60	71.05%	0.00%	71.05%	0.00%	25.00%	0.00060	1162.5	5.4	5.40	16.50	1.68	95.00%	0.08	21.60	75.00%
	Hi Solids sealcoat	7.60	85.55%	0.00%	85.55%	0.00%	7.00%	0.00120	1162.5	6.5	6.50	39.73	1.68	95.00%	0.08	92.88	75.00%
	Plastic basecoat	7.60	71.05%	0.00%	71.05%	0.00%	25.00%	0.00030	675.0	5.4	5.40	4.79	0.49	95.00%	0.02	21.60	75.00%
	Hi Solids sealcoat	7.60	85.55%	0.00%	85.55%	0.00%	7.00%	0.00050	675.0	6.5	6.50	9.61	0.41	95.00%	0.02	92.88	75.00%
B-61P-5/B-61P-11	Omega Spatter coat	11.80	22.91%	0.00%	22.91%	0.00%	61.88%	0.04810	7.00	2.7	2.70	3.99	3.35	95.00%	0.17	4.37	75.00%
	Omega Pink Primer	8.40	68.02%	0.00%	68.02%	0.00%	19.88%	0.10620	7.00	5.7	5.71	18.60	2.19	95.00%	0.11	28.74	75.00%
	Top Coat	8.80	32.80%	0.00%	32.80%	0.00%	61.56%	0.17450	7.00	2.9	2.89	15.44	7.91	95.00%	0.40	4.69	75.00%
<b>Options Plant - Metal and Wood Urn Coating Lines</b>																	
P-W-1/P-W-2	Pecan Stain	7.3	80.88%	0.0%	80.9%	0.0%	11.41%	0.05000	32.00	5.9	5.90	41.38	2.45	95.00%	0.12	51.75	75%
	30 Deg Lacquer	7.7	69.90%	0.0%	69.9%	0.0%	23.46%	0.20000	32.00	5.4	5.38	150.88	16.24	95.00%	0.81	22.94	75%
	Sanding Sealer	7.7	73.04%	0.0%	73.0%	0.0%	19.02%	0.05000	32.00	5.6	5.62	39.41	3.64	95.00%	0.18	29.57	75%
P-M-1/P-M-2	Bell Primer	12.2	27.09%	0.0%	27.1%	0.0%	44.84%	0.03000	36.00	3.3	3.30	15.63	10.52	95.00%	0.53	7.37	75%
	CCR	7.0	100.00%	0.0%	100.0%	0.0%	0.00%	0.16440	1.00	7.0	7.00	5.04	0.00	95.00%	0.00	#DIV/0!	75%
	SC-100	7.3	100.00%	0.0%	100.0%	0.0%	0.00%	0.00543	1.00	7.3	7.30	0.17	0.00	95.00%	0.00	#DIV/0!	75%
	Carnation	10.6	38.80%	0.0%	38.8%	0.0%	39.46%	0.06000	36.00	4.1	4.11	38.91	15.34	95.00%	0.77	10.42	75%
<b>Stamping Plant</b>																	
Solvent		7.30	100.00%	0.00%	100.00%	0.00%	0.00%	0.7677	1.00	7.3	7.30	24.55	0.00	95.00%	0.00	#DIV/0!	100.00%

Total Emissions **1379.01** **537.33**

Control Emissions **26.87**

Methodology:

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) \* Weight % Organics) / (1-Volume % water)  
Pounds of VOC per Gallon Coating = (Density (lb/gal) \* Weight % Organics)  
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) \* Gal of Material (gal/unit) \* Maximum (units/hr) \* (8760 hr/yr) \* (1 ton/2000 lbs)  
Particulate Potential Tons per Year = (units/hour) \* (gal/unit) \* (lbs/gal) \* (1- Weight % Volatiles) \* (1-Transfer efficiency) \*(8760 hrs/yr) \*(1 ton/2000 lbs)  
Pounds VOC per Gallon of Solids = (Density (lbs/gal) \* Weight % organics) / (Volume % solids) \* Transfer Efficiency  
Total = Sum of all coatings and solvents used  
Controlled emission rate = uncontrolled emission rate \* (1 - control efficiency)

**Appendix A: Emission Calculations  
HAP Emission Calculations**

**Company Name:** Batesville Manufacturing, Inc  
**Address City IN Zip:** 1000 East Pearl Street, IN 47006  
**Permit Number:** T137-24390-00016  
**Reviewer:** Josiah Balogun  
**Date:** 21-Aug-2008

Material	Density Lb/Gal	Maximum Usage (Gal/yr)	Weight % Xylene	Weight % Toluene	Weight % Ethylbenzene	Weight % Glycol Ethers	Xylene Emissions (ton/yr)	Toluene Emissions (ton/yr)	Ethylbenzene (ton/yr)	Glycol Ethers Emissions (ton/yr)	Total (ton/yr)
<b>Assembly Plant</b>											
High Solid Primer	12.18	121230	5.00%	0.00%	0.00%	5.00%	36.91	0.00	0.00	36.91	73.83
Omega Basecoat	9.10	121230	17.90%	16.48%	0.00%	0.00%	98.74	90.90	0.00	0.00	189.64
Carnation	10.65	188874	5.00%	20.00%	1.00%	0.00%	50.29	201.15	10.06	0.00	261.50
Plastic Topcoat	7.40	142438	1.50%	0.00%	0.00%	35.00%	7.91	0.00	0.00	184.46	192.36
Hi Build Clear	8.85	142438	20.00%	0.00%	5.00%	0.00%	126.06	0.00	31.51	0.00	157.57
Autumn Oak Spray	6.98	7231	50.00%	10.00%	15.00%	0.00%	12.62	2.52	3.79	0.00	18.93
<b>Metal Urn Coating Line</b>											
Primer	9.60	9461	2.50%	15.00%	0.00%	0.00%	1.14	6.81	0.00	0.00	7.95
Clear Topcoat	8.40	44150	21.00%	0.00%	4.00%	0.00%	38.94	0.00	7.42	0.00	46.36
Ivory Pearl	8.30	18922	40.00%	0.00%	8.00%	0.00%	31.41	0.00	6.28	0.00	37.69
<b>Wood Urn Coating Line</b>											
Sealer	7.90	14016	2.50%	37.50%	0.00%	0.00%	1.38	20.76	0.00	0.00	22.15
Autumn Oak Spray	7.00	14016	47.50%	7.50%	12.50%	0.00%	23.30	3.68	6.13	0.00	33.11
Clear Topcoat	7.70	56064	2.50%	0.00%	2.50%	0.00%	5.40	0.00	5.40	0.00	10.79
<b>Brush Unit of Assembly Plant</b>											
Brush Topcoat Mix	8.54	19316	12.02%	0.00%	2.00%	0.00%	9.91	0.00	1.65	0.00	11.56

<b>Total Potential Emissions</b>	<b>444.00</b>	<b>325.83</b>	<b>72.23</b>	<b>221.37</b>	<b>1063.44</b>
----------------------------------	---------------	---------------	--------------	---------------	----------------

**METHODOLOGY**

HAPS emission rate (tons/yr) = Density (lb/gal) \* Gal of Material (gal/unit) \* Maximum (unit/hr) \* Weight % HAP \* 1 ton/2000 lbs

**Appendix A: Emissions Calculations  
Natural Gas Combustion Only  
MM BTU/HR >100  
Combustion Units**

**Company Name:** Batesville Manufacturing, Inc  
**Address City IN Zip:** 1000 East Pearl Street, IN 47006  
**Permit Number:** T137-24390-00016  
**Reviewer:** Josiah Balogun  
**Date:** 21-Aug-2008

Heat Input Capacity  
MMBtu/hr

Potential Throughput  
MMCF/yr

151.6

1328.0

Emission Factor in lb/MMCF	Pollutant					
	PM*	PM10*	SO2	NOx	VOC	CO
Potential Emission in tons/yr	1.9	7.6	0.6	100.0 **see below	5.5	84.0
	1.3	5.0	0.4	66.4	3.7	55.8

\*PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

\*\*Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

**Methodology**

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

See page 6 for HAPs emissions calculations.

**Appendix A: Emissions Calculations  
 Natural Gas Combustion Only  
 MM BTU/HR >100  
 Combustion Units  
 HAPs Emissions**

**Company Name:** Batesville Manufacturing, Inc  
**Address City IN Zip:** 1000 East Pearl Street, IN 47006  
**Permit Number:** T137-24390-00016  
**Reviewer:** Josiah Balogun  
**Date:** 21-Aug-2008

HAPs - Organics					
	Benzene	Dichlorobenzene	Formaldehyde	Hexane	Toluene
Emission Factor in lb/MMcf	2.1E-03	1.2E-03	7.5E-02	1.8E+00	3.4E-03
Potential Emission in tons/yr	1.394E-03	7.968E-04	4.980E-02	1.195E+00	2.258E-03

HAPs - Metals					
	Lead	Cadmium	Chromium	Manganese	Nickel
Emission Factor in lb/MMcf	5.0E-04	1.1E-03	1.4E-03	3.8E-04	2.1E-03
Potential Emission in tons/yr	3.320E-04	7.304E-04	9.296E-04	2.523E-04	1.394E-03

Methodology is the same as page 5.

The five highest organic and metal HAPs emission factors are provided above.  
 Additional HAPs emission factors are available in AP-42, Chapter 1.4.

**Appendix A: Emission Calculations**  
**LPG-Propane - Industrial Ovens**  
**(Heat input capacity: < 10 MMBtu/hr)**

**Company Name:** Batesville Manufacturing, Inc  
**Address City IN Zip:** 1000 East Pearl Street, IN 47006  
**Permit Number:** T137-24390-00016  
**Reviewer:** Josiah Balogun  
**Date:** 21-Aug-2008

Heat Input Capacity  
MMBtu/hr

Potential Throughput  
kgals/year

SO2 Emission factor = 0.10 x S

S = Sulfur Content =  grains/100ft<sup>3</sup>

Emission Factor in lb/kgal	Pollutant					
	PM*	PM <sub>10</sub> *	SO <sub>2</sub>	NOx	VOC	CO
	0.6	0.6	0.1 (0.10S)	19.0	0.5 **TOC value	3.2
Potential Emission in tons/yr	0.2	0.2	0.0	5.5	0.1	0.9

\*PM emission factor is filterable PM only. PM10 emission factor is assumed to be the same as PM based on a footnote in Table 1.5-1, therefore PM10 is filterable only as well.

**Methodology**

1 gallon of LPG has a heating value of 94,000 Btu

1 gallon of propane has a heating value of 91,500 Btu (use this to convert emission factors to an energy basis for propane)

(Source - AP-42 (Supplement B 10/96) page 1.5-1)

Potential Throughput (kgals/year) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1kgal per 1000 gallon x 1 gal per 0.0915 MMBtu

Emission Factors are from AP42 (Supplement B 10/96), Table 1.5-1 (SCC #1-02-010-02)

Emission (tons/yr) = Throughput (kgals/yr) x Emission Factor (lb/kgal) / 2,000 lb/ton

**Appendix A: Emissions Calculations  
Insignificant Activities**

**Source Name:** Batesville Manufacturing, Inc  
**Source Location:** 1000 East Pearl Street, IN 47006  
**Permit Number:** T137-24390-00016  
**Permit Reviewer:** Josiah Balogun  
**Date:** 21-Aug-2008

<b>Particulate Emissions (PM/PM10) (tons/year)</b>				
<b>Emission Unit</b>	<b>Grain Loading (gr/dscf)</b>	<b>Air Flow Rate (scfm)</b>	<b>Uncontrolled Emissions (tons/yr)</b>	<b>Controlled Emissions (tons/yr) 90% Controlled Efficiency</b>
<b>Grinding and machining operation</b>	0.03	4000	4.5	0.45
<b>Total Emissions</b>			4.5	0.45

Methodology

Uncontrolled Emissions (tons/yr)= Grain Loading(gr/dscf) \*Air Flow rate(scfm) \*(60min/hr)\* (lb/7000)\*4.38 (tons hr/lb)  
 Contolled Emissions = Uncontrolled Emissions \*Controlled Efficiency