



*Mitchell E. Daniels, Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
(800) 451-6027  
www.IN.gov/idem

TO: Interested Parties / Applicant  
DATE: October 1, 2007  
RE: Jasper Desk Company, Incorporated / 037-25165-00007  
FROM: Nisha Sizemore  
Chief, Permits Branch  
Office of Air Quality

### Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days from the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures  
FNPER-AM.dot 03/23/06



**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT**  
*We make Indiana a cleaner, healthier place to live.*

---

Mitchell E. Daniels, Jr.  
 Governor

Thomas W. Easterly  
 Commissioner

100 North Senate Avenue  
 MC 61-53 IGCN 1003  
 Indianapolis, Indiana 46204-2251  
 (317) 232-8603  
 (800) 451-6027  
 www.IN.gov/idem

October 1, 2007

Mr. Gene Streicher  
 Jasper Desk Company, Incorporated  
 P.O. Box 111  
 Jasper, Indiana 47547

Re: 037-25165-00007  
 First Administrative Amendment to  
 Part 70 Operating Permit Renewal No.: 037-17545-00007

Dear Mr. Streicher:

On August 21, 2007, an application was received from Jasper Desk Company, Incorporated, located at 415 East 6<sup>th</sup> Street, Jasper, Indiana 47546. The purpose of the application was to notify IDEM Office of Air Quality (OAQ) of a change of equipment description. Additionally, IDEM, OAQ is revising certain sections or portions of the permit to accommodate regulatory and/or administrative changes. The **bold faced language** is new language that has been added and the ~~strikeout~~ is language that has been removed. Pursuant to the provisions of 326 IAC 2-7-11a(1) (4) and (7), the permit is hereby administratively changed as follows:

1. OAQ will delete the "responsible official" listing from Condition A.1 of the permit in order to minimize the administrative maintenance associated with this item.
2. The company mailing address was updated to reflect the post office box as was indicated in the application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary wood office furniture manufacturing plant.

|                                  |   |
|----------------------------------|---|
| <del>Responsible Official:</del> | <b>General Manager</b>  |
| Source Address:                  | 415 East 6 <sup>th</sup> Street, Jasper, Indiana 47546  |
| Mailing Address:                 | <b>415 East 6<sup>th</sup> Street P.O. Box 111, Jasper, Indiana 47547</b>   |
| General Source Phone Number:     | (812) 482-4132  |
| SIC Code:                        | 2521  |
| County Location:                 | Dubois  |
| Source Location Status:          | Nonattainment for the PM2.5 standard<br>Attainment for all other criteria pollutants  |
| Source Status:                   | Part 70 Permit Program<br>Minor Source, under PSD, and Nonattainment NSR<br>Minor Source, Section 112 of the Clean Air Act<br>Not 1 of 28 Source Categories |

3. An equipment description change was made to reflect the replacement of the booth water pans with dry filters. The replacement will not result in any emission increases associated with the replacement. Changes were made to Sections A.2, D.2 and Conditions D.2.3 and D.2.4, as indicated:

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]  
[326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

\*\*\*

- (e) One (1) surface coating booth, identified as SB-3, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stack 4.
- (f) One (1) surface coating booth, identified as SB-4, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stacks 6a and 6b.
- (g) One (1) surface coating booth, identified as SB-5, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stacks 7a and 7b.
- (h) One (1) surface coating booth, identified as SB-6, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stacks 8a and 8b.

\*\*\*

**SECTION D.2 FACILITY OPERATION CONDITIONS**

**Facility Description [326 IAC 2-7-5(15)]: Surface Coating Operations**

\*\*\*

- (e) One (1) surface coating booth, identified as SB-3, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stack 4.
- (f) One (1) surface coating booth, identified as SB-4, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stacks 6a and 6b.
- (g) One (1) surface coating booth, identified as SB-5, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stacks 7a and 7b.
- (h) One (1) surface coating booth, identified as SB-6, constructed prior to 1981, using ~~water pans~~ **dry filters** for control and exhausting to stacks 8a and 8b.

\*\*\*

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

D.2.3 Particulate Control

The baffles **and** dry filters ~~and water pans~~ for PM overspray control shall be in operation at all times when the seven (7) surface coating booths are in operation.

D.2.4 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the dry filters controlling emissions from spray booths SB-2, **SB-3, SB-4, SB-5, SB-6** and SB-7. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks 3a, 3b, **4, 6a, 6b, 7a, 7b, 8a, 8b** and 9 while the respective booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

- (b) ~~Daily inspections shall be performed to verify that the water level of the water pans controlling emissions from spray booths SB-3, SB-4, SB-5 and SB-6 meet the manufacturer's recommended level. To monitor the performance of the water pans, the water level of the pans shall be maintained weekly at a level where surface agitation indicates impact of the air flow. Water shall be kept free of solids and floating material that reduces the capture efficiency of the water pan.~~ To monitor the performance of the baffles controlling emissions from spray booth SB-1, weekly inspections of the baffle panels shall be conducted to verify placement and configuration meet recommendations of the manufacturer. In addition, weekly observations shall be made of the overspray from the surface coating booth stacks (1a, 1b, **3a, 3b, 4, 6a, 6b, 7a, 7b, 8a and 8b**) while the respective booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

\*\*\*

4. The IDEM, OAQ mailing addresses now include a new mail code. The mail code for the Permits Branch and Compliance Branch is MC 61-53 IGCN 1003. The Asbestos Section is MC 61-52 IGCN 1003 and Technical Support and Modeling Section is MC 61-50 IGCN 1003. The addresses were updated throughout the permit.

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
**MC61-53 IGCN 1003**  
Indianapolis, Indiana 46204-2251

5. This change was made to correct a grammatical error.

C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

\*\*\*

- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in ~~one hundred and twenty (120)~~ **one hundred twenty** (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.

\*\*\*

As a convenience, a revised copy of the entire permit is being provided.

Jasper Desk Company, Incorporated  
Jasper, Indiana  
Permit Reviewer: Gary Freeman

Page 4 of 4  
037-25165-00007  
First Administrative Amendment

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Gary Freeman, at (800) 451-6027, and ask for Gary Freeman or extension 3-5334, or dial (317) 233-5334.

Sincerely,

*Original document signed by*

Iryn Calilung, Section Chief  
Permits Branch  
Office of Air Quality

Attachments: Copy of the revised permit

IC/gkf

cc: File – Dubois County  
Dubois County Health Department  
Air Compliance Section Inspector – Southwest Regional Office  
Permit Review Section 4 - Gary Freeman  
Compliance Data Section  
U.S. EPA Region V



Mitchell E. Daniels, Jr.  
 Governor

Thomas W. Easterly  
 Commissioner

100 North Senate Avenue  
 MC 61-53 IGCN 1003  
 Indianapolis, Indiana 46204-2251  
 (317) 232-8603  
 (800) 451-6027  
 www.IN.gov/idem

## PART 70 OPERATING PERMIT RENEWAL OFFICE OF AIR QUALITY

**Jasper Desk Company, Incorporated  
 415 East 6<sup>th</sup> Street  
 Jasper, Indiana 47546**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

**The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.**

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

|   |  |
|---|--|
| Operation Permit No.: T037-17545-00007  |  |
| Issued by: Original Signed by<br>Nisha Sizemore, Chief<br>Permits Branch<br>Office of Air Quality | Issuance Date: June 15, 2006<br><br>Expiration Date: June 15, 2011 |

|   |  |
|---|--|
| First Administrative Amendment 037-25165-00007  |  |
| Issued by:<br><i>Original document<br/>signed by</i><br>Iryn Calilung, Section Chief<br>Permits Branch<br>Office of Air Quality | Issuance Date: October 1, 2007<br><br>Expiration Date: June 15, 2011 |

## TABLE OF CONTENTS

|                  |   |    |
|------------------|---|----|
| <b>SECTION A</b> | <b>SOURCE SUMMARY</b> .....   | 5  |
| A.1              | General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]  |    |
| A.2              | Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]<br>[326 IAC 2-7-5(15)]                                   |    |
| A.3              | Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]<br>[326 IAC 2-7-5(15)]                         |    |
| A.4              | Part 70 Permit Applicability [326 IAC 2-7-2]  |    |
| <b>SECTION B</b> | <b>GENERAL CONDITIONS</b> .....   | 7  |
| B.1              | Definitions [326 IAC 2-7-1]   |    |
| B.2              | Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)]<br>[IC 13-15-3-6(a)]                                      |    |
| B.3              | Term of Conditions [326 IAC 2-1.1-9.5]  |    |
| B.4              | Enforceability [326 IAC 2-7-7]  |    |
| B.5              | Severability [326 IAC 2-7-5(5)]   |    |
| B.6              | Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]  |    |
| B.7              | Duty to Provide Information [326 IAC 2-7-5(6)(E)]   |    |
| B.8              | Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]   |    |
| B.9              | Annual Compliance Certification [326 IAC 2-7-6(5)]  |    |
| B.10             | Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]<br>[326 IAC 1-6-3]                             |    |
| B.11             | Emergency Provisions [326 IAC 2-7-16]   |    |
| B.12             | Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]  |    |
| B.13             | Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]  |    |
| B.14             | Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]   |    |
| B.15             | Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]  |    |
| B.16             | Permit Modification, Reopening, Revocation and Reissuance, or Termination<br>[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9] |    |
| B.17             | Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]   |    |
| B.18             | Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]  |    |
| B.19             | Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]<br>[326 IAC 2-7-12 (b)(2)]                            |    |
| B.20             | Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]   |    |
| B.21             | Source Modification Requirement [326 IAC 2-7-10.5]  |    |
| B.22             | Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]   |    |
| B.23             | Transfer of Ownership or Operational Control [326 IAC 2-7-11]   |    |
| B.24             | Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]   |    |
| B.25             | Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]   |    |
| <b>SECTION C</b> | <b>SOURCE OPERATION CONDITIONS</b> .....  | 18 |
|                  | <b>Emission Limitations and Standards [326 IAC 2-7-5(1)]</b>  |    |
| C.1              | Opacity [326 IAC 5-1]   |    |
| C.2              | Open Burning [326 IAC 4-1] [IC 13-17-9]   |    |
| C.3              | Incineration [326 IAC 4-2] [326 IAC 9-1-2]  |    |
| C.4              | Fugitive Dust Emissions [326 IAC 6-4]   |    |
| C.5              | Stack Height [326 IAC 1-7]  |    |
| C.6              | Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]   |    |
|                  | <b>Testing Requirements [326 IAC 2-7-6(1)]</b>  |    |
| C.7              | Performance Testing [326 IAC 3-6]   |    |

## TABLE OF CONTENTS (Continued)

### **Compliance Requirements [326 IAC 2-1.1-11]**

C.8 Compliance Requirements [326 IAC 2-1.1-11]

### **Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

C.10 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

### **Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

C.11 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

C.12 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

C.13 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]

C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]  
[326 IAC 2-7-6]

### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)]  
[326 IAC 2-6]

C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

### **Stratospheric Ozone Protection**

C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

## **SECTION D.1 FACILITY OPERATION CONDITIONS - 25 MMBtu Wood-Fired Boiler .....25**

### **Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.1.1 Particulate Matter (PM) [326 IAC 6.5-4-16]

D.1.2 Particulate Matter (PM) [326 IAC 6.5-1-2]

D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

### **Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.1.4 Visible Emissions Notations

### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.1.5 Record Keeping Requirements

## **SECTION D.2 FACILITY OPERATION CONDITIONS - Surface Coating Operations .....27**

### **Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.2.1 Particulate Matter Limitations [326 IAC 6.5-1-2(a)]

D.2.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

### **Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.2.3 Particulate Control

D.2.4 Monitoring

### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.2.5 Record Keeping Requirements

### **National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

D.2.6 General Provisions Relating to National Emission Standards for Hazardous Air Pollutants for Wood Furniture Manufacturing Operations [326 IAC 20-1] [40 CFR Part 63, Subpart A]

D.2.7 National Emission Standards for Hazardous Air Pollutants for Wood Furniture Manufacturing Operations Requirements [40 CFR Part 63, Subpart JJ] [326 IAC 20-14]

**TABLE OF CONTENTS (Continued)**

**SECTION D.3 FACILITY OPERATION CONDITIONS - Woodworking Operations .....54**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.3.1 Particulate Matter Limitations: Dubois County [326 IAC 6.5-4-16]

D.3.2 PSD Minor Limit [326 IAC 2-2]

D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

D.3.4 Particulate Control [326 IAC 2-7-6(6)] [40 CFR 64]

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.3.5 Visible Emissions Notations [40 CFR 64]

D.3.6 Baghouse Inspections [40 CFR 64]

D.3.7 Broken or Failed Bag Detection

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.3.8 Record Keeping Requirements

**SECTION D.4 FACILITY OPERATION CONDITIONS - Insignificant Activities: Grinding and Machining Operations, Brazing, Soldering and Welding Equipment and Cutting Torches .....56**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.4.1 Particulate Emission Limitations [326 IAC 6.5-1-2]

D.4.2 Particulate Control

Certification .....57

Emergency Occurrence Report .....58

Part 70 Usage Report .....60

Quarterly Deviation and Compliance Monitoring Report .....61

## SECTION A

## SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

---

The Permittee owns and operates a stationary wood office furniture manufacturing plant.

|                              |   |
|------------------------------|---|
| Source Address:              | 415 East 6 <sup>th</sup> Street, Jasper, Indiana 47546  |
| Mailing Address:             | P.O. Box 111, Jasper, Indiana 47547   |
| General Source Phone Number: | (812) 482-4132  |
| SIC Code:                    | 2521  |
| County Location:             | Dubois  |
| Source Location Status:      | Nonattainment for the PM2.5 standard<br>Attainment for all other criteria pollutants  |
| Source Status:               | Part 70 Permit Program<br>Minor Source, under PSD, and Nonattainment NSR<br>Minor Source, Section 112 of the Clean Air Act<br>Not 1 of 28 Source Categories |

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) wood-fired firetube boiler, identified as UB-1, constructed in 1955, rated at 25 million British thermal units per hour and exhausting to stack 11.
- (b) One (1) natural gas-fired firetube boiler, identified as UB-2, constructed in 1970, rated at 10.5 million British thermal units per hour (250 horsepower) and exhausting to stack 14.
- (c) One (1) surface coating booth, identified as SB-1, constructed prior to 1950, using baffles for control and exhausting to stacks 1a and 1b.
- (d) One (1) surface coating booth, identified as SB-2, constructed prior to 1981, using dry filters for control and exhausting to stacks 3a and 3b.
- (e) One (1) surface coating booth, identified as SB-3, constructed prior to 1981, using dry filters for control and exhausting to stack 4.
- (f) One (1) surface coating booth, identified as SB-4, constructed prior to 1981, using dry filters for control and exhausting to stacks 6a and 6b.
- (g) One (1) surface coating booth, identified as SB-5, constructed prior to 1981, using dry filters for control and exhausting to stacks 7a and 7b.
- (h) One (1) surface coating booth, identified as SB-6, constructed prior to 1981, using dry filters for control and exhausting to stacks 8a and 8b.
- (i) One (1) surface coating booth, identified as SB-7, constructed prior to 1981, using dry filters for control and exhausting to stack 9.

Under the National Emission Standards for Hazardous Air Pollutants for Wood Furniture Manufacturing Operations (40 CFR 63, Subpart JJ), the seven surface coating booths (SB-1 through SB-7) are considered to be existing wood furniture surface coating operations.

- (j) Woodworking operations, identified as DC-1, constructed in 1993, with a maximum capacity of 1,797 pounds per hour, using a baghouse as control and exhausting to stacks 12a and 12b.
- (k) Woodworking operations, identified as DC-2, constructed in 1987, with a maximum capacity of 2,259 pounds per hour, using a baghouse as control, and exhausting to stacks 13a and 13b.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]  
[326 IAC 2-7-5(15)]

---

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs; brazing equipment, cutting torches, soldering equipment, welding equipment. [326 IAC 6.5-1-2]
- (b) Trimmers that do not produce fugitive emissions and that are equipped with a dust collection or trim material recovery device such as a bag filter or cyclone. [326 IAC 6.5-1-2]
- (c) Paved and unpaved roads and parking lots with public access. [326 IAC 6-4]
- (d) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations. [326 IAC 6.5-1-2]
- (e) Insignificant Surface Coating Operations, including:
  - (1) Aerosol lacquers and topcoats for touchup 0.532 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (2) Lacquer tint (spray gun) 0.017 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (3) Aerosol distressing lacquer 0.052 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (4) Aerosol blush eliminator 0.455 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (5) Two minute touch up (spray gun) 0.012 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (6) Boothcoat protectant 2 pounds VOC per hour (booths coated semi-annually). [326 IAC 6.5-1-2]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

---

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

## SECTION B

## GENERAL CONDITIONS

### B.1 Definitions [326 IAC 2-7-1]

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

### B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]

---

- (a) This permit, T037-17545-00007, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

### B.3 Term of Conditions [326 IAC 2-1.1-9.5]

---

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

### B.4 Enforceability [326 IAC 2-7-7]

---

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

### B.5 Severability [326 IAC 2-7-5(5)]

---

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

---

This permit does not convey any property rights of any sort or any exclusive privilege.

### B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

---

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
  - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]  
[326 IAC 1-6-3]

---

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) for the source as described in 326 IAC 4-6-2. At a minimum, the PMPs shall include:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and Southwest Regional Office within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

IDEM Main Office  
Telephone Number: 1-800-451-6027 (ask for Office of Air Quality,  
Compliance Section), or  
Telephone Number: 317-233-0178 (ask for Compliance Section)  
Facsimile Number: 317-233-6865  
Southwest Regional Office  
Telephone Number: (888) 672- 8323 or (812) 380-2305  
Facsimile Number: (812) 380-2304

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
  - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
  - (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
  - (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.

- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

**B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]**

---

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
  - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
  - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
  - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
  - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.

- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

**B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]**

---

- (a) All terms and conditions of permits established prior to T037-17545-00007 and issued pursuant to permitting programs approved into the state implementation plan have been either
  - (1) incorporated as originally stated,
  - (2) revised under 326 IAC 2-7-10.5, or
  - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit.

**B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]**

---

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

**B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]**

---

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination  
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

---

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
- (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]

---

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
- (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
  - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.

**B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]**

---

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

**B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]**

---

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.

- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

**B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]**

---

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

- (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b), (c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]  
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.21 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

## SECTION C

## SOURCE OPERATION CONDITIONS

Entire Source

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### C.1 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of thirty percent (30%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

#### C.2 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable

#### C.3 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

#### C.4 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

#### C.5 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted. The provisions of 326 IAC 1-7-1(3), 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4, and 326 IAC 1-7-5(a), (b), and (d) are not federally enforceable.

#### C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:

- (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
- (2) If there is a change in the following:
  - (A) Asbestos removal or demolition start date;
  - (B) Removal or demolition contractor; or
  - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-52 IGCN 1003  
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**  
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

### **Testing Requirements [326 IAC 2-7-6(1)]**

#### **C.7 Performance Testing [326 IAC 3-6]**

---

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ, not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

#### **Compliance Requirements [326 IAC 2-1.1-11]**

##### **C.8 Compliance Requirements [326 IAC 2-1.1-11]**

---

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

#### **Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

##### **C.9 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

---

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.10 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

C.11 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on March 29, 1999.
- (b) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level.  
[326 IAC 1-5-3]

C.12 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance as defined in 40 CFR 68 is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.13 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
  - (1) initial inspection and evaluation;
  - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
  - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
  - (1) monitoring results;
  - (2) review of operation and maintenance procedures and records;
  - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.

- (e) The Permittee shall maintain the following records:
  - (1) monitoring data;
  - (2) monitor performance data, if applicable; and
  - (3) corrective actions taken.

**C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]  
[326 IAC 2-7-6]**

---

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

**C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)] [326 IAC 2-6]**

---

- (a) Pursuant to 326 IAC 2-6-3(b)(3), starting in 2006 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:
  - (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
  - (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management  
Technical Support and Modeling Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-50 IGCN 1003  
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

**C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]**

---

- (a) Records of all required monitoring data, reports and support information required by this Permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

**C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]**

---

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

**Stratospheric Ozone Protection**

**C.18 Compliance with 40 CFR 82 and 326 IAC 22-1**

---

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

## SECTION D.1

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]: 25 MMBtu Wood-Fired Boiler

- (a) One (1) wood-fired firetube boiler, identified as UB-1, constructed in 1955, rated at 25 million British thermal units per hour and exhausting to stack 11.
- (b) One (1) natural gas fired firetube boiler, identified as UB-2, constructed in 1970, rated at 10.5 million British thermal units per hour (250 horsepower) and exhausting to stack 14.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.1.1 Particulate Matter (PM) [326 IAC 6.5-4-16]

Pursuant to 326 IAC 6.5-4-16, the particulate matter emissions from the 25.0 million British thermal units per hour wood-fired boiler shall not exceed 0.6 pounds per million British thermal units and 14.6 tons per year. The input of wood fuel to the wood-fired boiler shall not exceed 4,376 tons per twelve consecutive month period.

#### D.1.2 Particulate Matter (PM) [326 IAC 6.5-1-2]

Pursuant to 326 IAC 6.5-1-2(b)(3), the particulate matter emissions from the 10.5 MMBtu natural gas-fired boiler (UB-2) shall not exceed one-hundredth (0.01) grain per dry standard cubic feet.

#### D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for the wood fired boiler and its control device.

### Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

#### D.1.4 Visible Emissions Notations

- (a) Visible emission notations of the wood-fired boiler stack exhaust shall be performed once per day during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed at the boiler exhaust stack, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

## **Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

### **D.1.5 Record Keeping Requirements**

---

- (a) To document compliance with Condition D.1.1, monthly records shall be kept of the weight of wood wastes burned in the boiler.
- (b) To document compliance with Condition D.1.4, the Permittee shall maintain records of once per day visible emission notations of the wood-fired boiler stack exhaust.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

## SECTION D.2

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]: Surface Coating Operations

- (c) One (1) surface coating booth, identified as SB-1, constructed prior to 1950, using baffles for control and exhausting to stacks 1a and 1b.
- (d) One (1) surface coating booth, identified as SB-2, constructed prior to 1981, using dry filters for control and exhausting to stacks 3a and 3b.
- (e) One (1) surface coating booth, identified as SB-3, constructed prior to 1981, using dry filters for control and exhausting to stack 4.
- (f) One (1) surface coating booth, identified as SB-4, constructed prior to 1981, using dry filters for control and exhausting to stacks 6a and 6b.
- (g) One (1) surface coating booth, identified as SB-5, constructed prior to 1981, using dry filters for control and exhausting to stacks 7a and 7b.
- (h) One (1) surface coating booth, identified as SB-6, constructed prior to 1981, using dry filters for control and exhausting to stacks 8a and 8b.
- (i) One (1) surface coating booth, identified as SB-7, constructed prior to 1981, using dry filters for control and exhausting to stack 9.

Under the National Emission Standards for Hazardous Air Pollutants for Wood Furniture Manufacturing Operations (40 CFR 63, Subpart JJ), the seven surface coating booths (SB-1 through SB-7) are considered to be existing wood furniture surface coating operations.

#### Insignificant Activities:

- (d) Insignificant Surface Coating Operations, including:
  - (1) Aerosol lacquers and topcoats for touchup 0.532 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (2) Lacquer tint (spray gun) 0.017 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (3) Aerosol distressing lacquer 0.052 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (4) Aerosol blush eliminator 0.455 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (5) Two minute touch up (spray gun) 0.012 pounds VOC per hour. [326 IAC 6.5-1-2]
  - (6) Boothcoat protectant 2 pounds VOC per hour (booths coated semi-annually). [326 IAC 6.5-1-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.2.1 Particulate Matter Limitations [326 IAC 6.5-1-2(a)]

Pursuant to 326 IAC 6.5-1-2(a) (formerly 326 IAC 6-1-2), particulate matter emissions from the surface coating operations shall not exceed 0.03 grains per dry standard cubic foot.

**D.2.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]**

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

**D.2.3 Particulate Control**

The baffles and dry filters for PM overspray control shall be in operation at all times when the seven (7) surface coating booths are in operation.

**D.2.4 Monitoring**

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the dry filters controlling emissions from spray booths SB-2 SB-3, SB-4, SB-5, SB-6 and SB-7. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks 3a, 3b, 4, 6a, 6b, 7a, 7b, 8a, 8b and 9 while the respective booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.
- (b) To monitor the performance of the baffles controlling emissions from spray booth SB-1, weekly inspections of the baffle panels shall be conducted to verify placement and configuration meet recommendations of the manufacturer. In addition, weekly observations shall be made of the overspray from the surface coating booth stacks (1a, 1b, 3a, 3b, 4, 6a, 6b, 7a, 7b, 8a and 8b) while the respective booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.
- (c) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

**D.2.5 Record Keeping Requirements**

- (a) To document compliance with Condition D.2.4, the Permittee shall maintain a log of weekly overspray observations, weekly observations of the dry filters, and the daily and monthly inspections prescribed by Condition D.2.4.

- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

D.2.6 General Provisions Relating to National Emission Standards for Hazardous Air Pollutants under 40 CFR Part 63 [326 IAC 20-1] [40 CFR Part 63, Subpart A]

---

- (a) Pursuant to 40 CFR 63.800(d), the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1 for the wood furniture surface coating operations as specified in Appendix A of 40 CFR Part 63, Subpart JJ, in accordance with the schedule in 40 CFR 63, Subpart JJ.
- (b) Pursuant to 40 CFR 63.10, the Permittee shall submit all of the required notifications and reports to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

D.2.7 National Emission Standards for Hazardous Air Pollutants for Wood Furniture Manufacturing Operations Requirements [40 CFR Part 63, Subpart JJ] [326 IAC 20-14]

---

Pursuant to CFR Part 63, Subpart JJ, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart JJ, which are incorporated by reference as 326 IAC 20-14 for the wood furniture surface coating and spray adhesive operations as specified as follows.

**§ 63.800 Applicability.**

- (a) The affected source to which this subpart applies is each facility that is engaged, either in part or in whole, in the manufacture of wood furniture or wood furniture components and that is located at a plant site that is a major source as defined in 40 CFR part 63, subpart A, §63.2. The owner or operator of a source that meets the definition for an incidental wood furniture manufacturer shall maintain purchase or usage records demonstrating that the source meets the definition in §63.801 of this subpart, but the source shall not be subject to any other provisions of this subpart.
- (d) Owners or operators of affected sources shall also comply with the requirements of subpart A of this part (General Provisions), according to the applicability of subpart A to such sources, as identified in Table 1 of this subpart.

**§ 63.801 Definitions.**

- (a) All terms used in this subpart that are not defined below have the meaning given to them in the CAA and in subpart A (General Provisions) of this part.

*Adhesive* means any chemical substance that is applied for the purpose of bonding two surfaces together other than by mechanical means. Under this subpart, adhesives shall not be considered coatings or finishing materials. Products used on humans and animals, adhesive tape, contact paper, or any other product with an adhesive incorporated onto or in an inert substrate shall not be considered adhesives under this subpart.

*Administrator* means the Administrator of the United States Environmental Protection Agency or his or her authorized representative.

*Aerosol adhesive* means an adhesive that is dispensed from a pressurized container as a suspension of fine solid or liquid particles in gas.

*Affected source* means a wood furniture manufacturing facility that is engaged, either in part or in whole, in the manufacture of wood furniture or wood furniture components and that is located at a plant site that is a major source as defined in 40 CFR part 63.2, excluding sources that meet the criteria established in §63.800(a), (b) and (c) of this subpart.

*Alternative method* means any method of sampling and analyzing for an air pollutant that is not a reference or equivalent method but has been demonstrated to the Administrator's satisfaction to, in specific cases, produce results adequate for a determination of compliance.

*As applied* means the HAP and solids content of the coating or contact adhesive that is actually used for coating or gluing the substrate. It includes the contribution of materials used for in-house dilution of the coating or contact adhesive.

*Basecoat* means a coat of colored material, usually opaque, that is applied before graining inks, glazing coats, or other opaque finishing materials, and is usually topcoated for protection.

*Baseline conditions* means the conditions that exist prior to an affected source implementing controls, such as a control system.

*Building enclosure* means a building housing a process that meets the requirements of a temporary total enclosure. The EPA Method 204E is used to identify all emission points from the building enclosure and to determine which emission points must be tested. For additional information see *Guidelines for Determining Capture Efficiency*, January 1994. Docket No. A-93-10, Item No. IV-B-1.

*Capture device* means a hood, enclosed room, floor sweep, or other means of collecting solvent emissions or other pollutants into a duct so that the pollutant can be directed to a pollution control device such as an incinerator or carbon adsorber.

*Capture efficiency* means the fraction of all organic vapors generated by a process that are directed to a control device.

*Certified product data sheet (CPDS)* means documentation furnished by coating or adhesive suppliers or an outside laboratory that provides:

- (1) The VHAP content of a finishing material, contact adhesive, or solvent, by percent weight, measured using the EPA Method 311 (as promulgated in this subpart), or an equivalent or alternative method (or formulation data if the coating meets the criteria specified in §63.805(a));
- (2) The solids content of a finishing material or contact adhesive by percent weight, determined using data from the EPA Method 24, or an alternative or equivalent method (or formulation data if the coating meets the criteria specified in §63.805 (a)); and
- (3) The density, measured by EPA Method 24 or an alternative or equivalent method. Therefore, the reportable VHAP content shall represent the maximum aggregate emissions potential of the finishing material, adhesive, or solvent in concentrations greater than or equal to 1.0 percent by weight or 0.1 percent for VHAP that are carcinogens, as defined by the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR part 1910), as formulated. Only VHAP present in concentrations greater than or equal to 1.0 percent by weight, or 0.1 percent for VHAP that are carcinogens, must be reported on the CPDS. The purpose of the CPDS is to assist the affected source in demonstrating compliance with the emission limitations presented in §63.802.

Note: Because the optimum analytical conditions under EPA Method 311 vary by coating, the coating or adhesive supplier may also choose to include on the CPDS the optimum analytical conditions for analysis of the coating, adhesive, or solvent using EPA Method 311. Such information may include, but not be limited to, separation column, oven temperature, carrier gas, injection port temperature, extraction solvent, and internal standard.)

*Cleaning operations* means operations in which organic HAP solvent is used to remove coating materials or adhesives from equipment used in wood furniture manufacturing operations.

*Coating* means a protective, decorative, or functional film applied in a thin layer to a surface. Such materials include, but are not limited to, paints, topcoats, varnishes, sealers, stains, washcoats, basecoats, enamels, inks, and temporary protective coatings. Aerosol spray paints used for touch-up and repair are not considered coatings under this subpart.

*Coating application station* means the part of a coating operation where the coating is applied, e.g., a spray booth.

*Coating operation* means those activities in which a coating is applied to a substrate and is subsequently air-dried, cured in an oven, or cured by radiation.

*Coating solids (or solids)* means the part of the coating which remains after the coating is dried or cured; solids content is determined using data from the EPA Method 24, or an equivalent or alternative method.

*Compliant coating/contact adhesive* means a finishing material, contact adhesive, or strippable booth coating that meets the emission limits specified in Table 3 of this subpart.

*Contact adhesive* means an adhesive that is applied to two substrates, dried, and mated under only enough pressure to result in good contact. The bond is immediate and sufficiently strong to hold pieces together without further clamping, pressure, or airing.

*Continuous coater* means a finishing system that continuously applies finishing materials onto furniture parts moving along a conveyor. Finishing materials that are not transferred to the part are recycled to a reservoir. Several types of application methods can be used with a continuous coater including spraying, curtain coating, roll coating, dip coating, and flow coating.

*Continuous compliance* means that the affected source is meeting the emission limitations and other requirements of the rule at all times and is fulfilling all monitoring and recordkeeping provisions of the rule in order to demonstrate compliance.

*Control device* means any equipment that reduces the quantity of a pollutant that is emitted to the air. The device may destroy or secure the pollutant for subsequent recovery. Includes, but is not limited to, incinerators, carbon adsorbers, and condensers.

*Control device efficiency* means the ratio of the pollutant released by a control device and the pollutant introduced to the control device.

*Control system* means the combination of capture and control devices used to reduce emissions to the atmosphere.

*Conventional air spray* means a spray coating method in which the coating is atomized by mixing it with compressed air and applied at an air pressure greater than 10 pounds per square inch (gauge) at the point of atomization. Airless and air assisted airless spray technologies are not conventional air spray because the coating is not atomized by mixing it with compressed air. Electrostatic spray technology is also not considered conventional air spray because an electrostatic charge is employed to attract the coating to the workpiece.

*Data quality objective (DQO) approach* means a set of approval criteria that must be met so that data from an alternative test method can be used in determining the capture efficiency of a control system. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

*Day* means a period of 24 consecutive hours beginning at midnight local time, or beginning at a time consistent with a facility's operating schedule.

*Disposed offsite* means sending used organic HAP solvent or coatings outside of the facility boundaries for disposal.

*Emission* means the release or discharge, whether directly or indirectly, of HAP into the ambient air.

*Enamel* means a coat of colored material, usually opaque, that is applied as a protective topcoat over a basecoat, primer, or previously applied enamel coats. In some cases, another finishing material may be applied as a topcoat over the enamel.

*Equipment leak* means emissions of VHAP from pumps, valves, flanges, or other equipment used to transfer or apply coatings, adhesives, or organic HAP solvents.

*Equivalent method* means any method of sampling and analyzing for an air pollutant that has been demonstrated to the Administrator's satisfaction to have a consistent and quantitatively known relationship to the reference method, under specific conditions.

*Finishing material* means a coating used in the wood furniture industry. Such materials include, but are not limited to, stains, basecoats, washcoats, enamels, sealers, and topcoats.

*Finishing operation* means those operations in which a finishing material is applied to a substrate and is subsequently air-dried, cured in an oven, or cured by radiation.

*Foam adhesive* means a contact adhesive used for gluing foam to fabric, foam to foam, and fabric to wood.

*Gluing operation* means those operations in which adhesives are used to join components, for example, to apply a laminate to a wood substrate or foam to fabric.

*Incidental wood furniture manufacturer* means a major source that is primarily engaged in the manufacture of products other than wood furniture or wood furniture components and that uses no more than 100 gallons per month of finishing material or adhesives in the manufacture of wood furniture or wood furniture components.

*Incinerator* means, for the purposes of this industry, an enclosed combustion device that thermally oxidizes volatile organic compounds to CO and CO<sub>2</sub>. This term does not include devices that burn municipal or hazardous waste material.

*Janitorial maintenance* means the upkeep of equipment or building structures that is not directly related to the manufacturing process, for example, cleaning of restroom facilities.

*Lower confidence limit (LCL) approach* means a set of approval criteria that must be met so that data from an alternative test method can be used in determining the capture efficiency of a control system. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

*Material safety data sheet (MSDS)* means the documentation required for hazardous chemicals by the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR Part 1910) for a solvent, cleaning material, contact adhesive, coating, or other material that identifies select reportable hazardous ingredients of the material, safety and health considerations, and handling procedures.

*Noncompliant coating/contact adhesive* means a finishing material, contact adhesive, or strippable booth coating that has a VHAP content (VOC content for the strippable booth coating) greater than the emission limitation presented in Table 3 of this subpart.

*Nonporous substrate* means a surface that is impermeable to liquids. Examples include metal, rigid plastic, flexible vinyl, and rubber.

*Normally closed container* means a container that is closed unless an operator is actively engaged in activities such as emptying or filling the container.

*Operating parameter value* means a minimum or maximum value established for a control device or process parameter that, if achieved by itself or in combination with one or more other operating parameter values, determines that an owner or operator has complied with an applicable emission limit.

*Organic HAP solvent* means a HAP that is a volatile organic liquid used for dissolving or dispersing constituents in a coating or contact adhesive, adjusting the viscosity of a coating or contact adhesive, or cleaning equipment. When used in a coating or contact adhesive, the organic HAP solvent evaporates during drying and does not become a part of the dried film.

*Overall control efficiency* means the efficiency of a control system, calculated as the product of the capture and control device efficiencies, expressed as a percentage.

*Permanent total enclosure* means a permanently installed enclosure that completely surrounds a source of emissions such that all emissions are captured and contained for discharge through a control device. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

*Recycled onsite* means the reuse of an organic HAP solvent in a process other than cleaning or washoff.

*Reference method* means any method of sampling and analyzing for an air pollutant that is published in Appendix A of 40 CFR part 60.

*Research or laboratory facility* means any stationary source whose primary purpose is to conduct research and development to develop new processes and products where such source is operated under the close supervision of technically trained personnel and is not engaged in the manufacture of products for commercial sale in commerce, except in a de minimis manner.

*Responsible official* has the meaning given to it in 40 CFR part 70, State Operating Permit Programs (Title V permits).

*Sealer* means a finishing material used to seal the pores of a wood substrate before additional coats of finishing material are applied. Special purpose finishing materials that are used in some finishing systems to optimize aesthetics are not sealers.

*Solvent* means a liquid used in a coating or contact adhesive to dissolve or disperse constituents and/or to adjust viscosity. It evaporates during drying and does not become a part of the dried film.

*Stain* means any color coat having a solids content by weight of no more than 8.0 percent that is applied in single or multiple coats directly to the substrate. It includes, but is not limited to, nongrain raising stains, equalizer stains, prestains, sap stains, body stains, no-wipe stains, penetrating stains, and toners.

*Storage containers* means vessels or tanks, including mix equipment, used to hold finishing, gluing, cleaning, or washoff materials.

*Strippable spray booth material* means a coating that:

(1) Is applied to a spray booth wall to provide a protective film to receive over spray during finishing operations;

(2) That is subsequently peeled off and disposed; and

(3) By achieving (1) and (2) of this definition reduces or eliminates the need to use organic HAP solvents to clean spray booth walls.

*Substrate* means the surface onto which a coating or contact adhesive is applied (or into which a coating or contact adhesive is impregnated).

*Temporary total enclosure* means an enclosure that meets the requirements of §63.805(e)(1) (i) through (iv) and is not permanent, but constructed only to measure the capture efficiency of pollutants emitted from a given source. Additionally, any exhaust point from the enclosure shall be at least four equivalent duct or hood diameters from each natural draft opening. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

*Thinner* means a volatile liquid that is used to dilute coatings or contact adhesives (to reduce viscosity, color strength, and solids, or to modify drying conditions).

*Topcoat* means the last film-building finishing material that is applied in a finishing system.

*Touchup and repair* means the application of finishing materials to cover minor finishing imperfections.

*VHAP* means any volatile hazardous air pollutant listed in Table 2 to Subpart JJ.

*VHAP of potential concern* means any VHAP from the list in table 6 of this subpart.

*Volatile organic compound (VOC)* means any organic compound which participates in atmospheric photochemical reactions, that is, any organic compound other than those which the Administrator designates as having negligible photochemical reactivity. A VOC may be measured by a reference method, an equivalent method, an alternative method, or by procedures specified under any rule. A reference method, an equivalent method, or an alternative method, however, may also measure nonreactive organic compounds. In such cases, the owner or operator may exclude the nonreactive organic compounds when determining compliance with a standard. For a list of compounds that the Administrator has designated as having negligible photochemical reactivity, refer to 40 CFR part 51.10.

*Washcoat* means a transparent special purpose finishing material having a solids content by weight of 12.0 percent by weight or less. Washcoats are applied over initial stains to protect, to control color, and to stiffen the wood fibers in order to aid sanding.

*Washoff operations* means those operations in which organic HAP solvent is used to remove coating from wood furniture or a wood furniture component.

*Wood furniture* means any product made of wood, a wood product such as rattan or wicker, or an engineered wood product such as particleboard that is manufactured under any of the following standard industrial classification codes: 2434, 2511, 2512, 2517, 2519, 2521, 2531, 2541, 2599, or 5712.

*Wood furniture component* means any part that is used in the manufacture of wood furniture. Examples include, but are not limited to, drawer sides, cabinet doors, seat cushions, and laminated tops. However, foam seat cushions manufactured and fabricated at a facility that does not engage in any other wood furniture or wood furniture component manufacturing operation are excluded from this definition.

*Wood furniture manufacturing operations* means the finishing, gluing, cleaning, and washoff operations associated with the production of wood furniture or wood furniture components.

(b) The nomenclature used in this subpart has the following meaning:

(1)  $A_k$  = the area of each natural draft opening (k) in a total enclosure, in square meters.

(2)  $C_c$  = the VHAP content of a finishing material (c), in kilograms of volatile hazardous air pollutants per kilogram of coating solids (kg VHAP/kg solids), as supplied. Also given in pounds of volatile hazardous air pollutants per pound of coating solids (lb VHAP/lb solids).

(3)  $C_{aj}$  = the concentration of VHAP in gas stream (j) exiting the control device, in parts per million by volume.

- (4)  $C_{bi}$ =the concentration of VHAP in gas stream (i) entering the control device, in parts per million by volume.
- (5)  $C_{di}$ =the concentration of VHAP in gas stream (i) entering the control device from the affected source, in parts per million by volume.
- (6)  $C_{rk}$ =the concentration of VHAP in uncontrolled gas stream (k) emitted directly to the atmosphere from the affected source, in parts per million by volume.
- (7) E=the emission limit achieved by an emission point or a set of emission points, in kg VHAP/kg solids (lb VHAP/lb solids).
- (8) F=the control device efficiency, expressed as a fraction.
- (9) FV=the average inward face velocity across all natural draft openings in a total enclosure, in meters per hour.
- (10) G=the VHAP content of a contact adhesive, in kg VHAP/kg solids (lb VHAP/lb solids), as applied.
- (11) M=the mass of solids in finishing material used monthly, kg solids/month (lb solids/month).
- (12) N=the capture efficiency, expressed as a fraction.
- (13)  $Q_{aj}$ =the volumetric flow rate of gas stream (j) exiting the control device, in dry standard cubic meters per hour.
- (14)  $Q_{bi}$ =the volumetric flow rate of gas stream (i) entering the control device, in dry standard cubic meters per hour.
- (15)  $Q_{di}$ =the volumetric flow rate of gas stream (i) entering the control device from the emission point, in dry standard cubic meters per hour.
- (16)  $Q_{rk}$ =the volumetric flow rate of uncontrolled gas stream (k) emitted directly to the atmosphere from the emission point, in dry standard cubic meters per hour.
- (17)  $Q_{ini}$ =the volumetric flow rate of gas stream (i) entering the total enclosure through a forced makeup air duct, in standard cubic meters per hour (wet basis).
- (18)  $Q_{outj}$ =the volumetric flow rate of gas stream (j) exiting the total enclosure through an exhaust duct or hood, in standard cubic meters per hour (wet basis).
- (19) R=the overall efficiency of the control system, expressed as a percentage.
- (20) S=the VHAP content of a solvent, expressed as a weight fraction, added to finishing materials.
- (21) W=the amount of solvent, in kilograms (pounds), added to finishing materials during the monthly averaging period.
- (22) ac=after the control system is installed and operated.
- (23) bc=before control.

**§ 63.802 Emission limits.**

- (a) Each owner or operator of an existing affected source subject to this subpart shall:

(1) Limit VHAP emissions from finishing operations by meeting the emission limitations for existing sources presented in Table 3 of this subpart, using any of the compliance methods in §63.804(a). To determine VHAP emissions from a finishing material containing formaldehyde or styrene, the owner or operator of the affected source shall use the methods presented in §63.803(l)(2) for determining styrene and formaldehyde usage.

(2) Limit VHAP emissions from contact adhesives by achieving a VHAP limit for contact adhesives based on the following criteria:

(i) For foam adhesives (contact adhesives used for upholstery operations) used in products that meet the upholstered seating flammability requirements of California Technical Bulletin 116, 117, or 133, the Business and Institutional Furniture Manufacturers Association's (BIFMA's) X5.7, UFAC flammability testing, or any similar requirements from local, State, or Federal fire regulatory agencies, the VHAP content of the adhesive shall not exceed 1.8 kg VHAP/kg solids (1.8 lb VHAP/lb solids), as applied; or

(ii) For all other contact adhesives (including foam adhesives used in products that do not meet the standards presented in paragraph (a)(2)(i) of this section, but excluding aerosol adhesives and excluding contact adhesives applied to nonporous substrates, the VHAP content of the adhesive shall not exceed 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied.

(3) Limit HAP emissions from strippable spray booth coatings by using coatings that contain no more than 0.8 kg VOC/kg solids (0.8 lb VOC/lb solids), as applied.

### **§ 63.803 Work practice standards.**

(a) *Work practice implementation plan.* (1) Each owner or operator of an affected source subject to this subpart shall prepare and maintain a written work practice implementation plan that defines environmentally desirable work practices for each wood furniture operation manufacturing operation and addresses each of the work practice standards presented in paragraphs (b) through (l) of this section. The plan shall be developed no more than 60 days after the compliance date.

(2) The written work practice implementation plan shall be available for inspection by the Administrator (or delegated State, local, or Tribal authority) upon request. If the Administrator (or delegated State, local, or Tribal authority) determines that the work practice implementation plan does not include sufficient mechanisms for ensuring that the work practice standards are being implemented, the Administrator (or delegated State, local, or Tribal authority) may require the affected source to modify the plan. Revisions or modifications to the plan do not require a revision of the source's Title V permit.

(3) The inspection and maintenance plan required by paragraph (c) of this section and the formulation assessment plan for finishing operations required by paragraph (l) of this section are also reviewable by the Administrator (or delegated State, local, or Tribal authority).

(b) *Operator training course.* Each owner or operator of an affected source shall train all new and existing personnel, including contract personnel, who are involved in finishing, gluing, cleaning, and washoff operations, use of manufacturing equipment, or implementation of the requirements of this subpart. All new personnel, those hired after the compliance date of the standard, shall be trained upon hiring. All existing personnel, those hired before the compliance date of the standard, shall be trained within six months of the compliance date of the standard. All personnel shall be given refresher training annually. The affected source shall maintain a copy of the training program with the work practice implementation plan. The training program shall include, at a minimum, the following:

(1) A list of all current personnel by name and job description that are required to be trained;

(2) An outline of the subjects to be covered in the initial and refresher training for each position or group of personnel;

(3) Lesson plans for courses to be given at the initial and the annual refresher training that include, at a minimum, appropriate application techniques, appropriate cleaning and washoff procedures, appropriate equipment setup and adjustment to minimize finishing material usage and overspray, and appropriate management of cleanup wastes; and

(4) A description of the methods to be used at the completion of initial or refresher training to demonstrate and document successful completion.

(c) *Inspection and maintenance plan.* Each owner or operator of an affected source shall prepare and maintain with the work practice implementation plan a written leak inspection and maintenance plan that specifies:

(1) A minimum visual inspection frequency of once per month for all equipment used to transfer or apply coatings, adhesives, or organic HAP solvents;

(2) An inspection schedule;

(3) Methods for documenting the date and results of each inspection and any repairs that were made;

(4) The timeframe between identifying the leak and making the repair, which adheres, at a minimum, to the following schedule:

(i) A first attempt at repair (e.g., tightening of packing glands) shall be made no later than five calendar days after the leak is detected; and

(ii) Final repairs shall be made within 15 calendar days after the leak is detected, unless the leaking equipment is to be replaced by a new purchase, in which case repairs shall be completed within three months.

(d) *Cleaning and washoff solvent accounting system.* Each owner or operator of an affected source shall develop an organic HAP solvent accounting form to record:

(1) The quantity and type of organic HAP solvent used each month for washoff and cleaning, as defined in §63.801 of this subpart;

(2) The number of pieces washed off, and the reason for the washoff; and

(3) The quantity of spent organic HAP solvent generated from each washoff and cleaning operation each month, and whether it is recycled onsite or disposed offsite.

(e) *Chemical composition of cleaning and washoff solvents.* Each owner or operator of an affected source shall not use cleaning or washoff solvents that contain any of the pollutants listed in Table 4 to this subpart, in concentrations subject to MSDS reporting as required by OSHA.

(f) *Spray booth cleaning.* Each owner or operator of an affected source shall not use compounds containing more than 8.0 percent by weight of VOC for cleaning spray booth components other than conveyors, continuous coaters and their enclosures, or metal filters, or plastic filters unless the spray booth is being refurbished. If the spray booth is being refurbished, that is the spray booth coating or other protective material used to cover the booth is being replaced, the affected source shall use no more than 1.0 gallon of organic HAP solvent per booth to prepare the surface of the booth prior to applying the booth coating.

(g) *Storage requirements.* Each owner or operator of an affected source shall use normally closed containers for storing finishing, gluing, cleaning, and washoff materials.

(h) *Application equipment requirements.* Each owner or operator of an affected source shall use conventional air spray guns to apply finishing materials only under any of the following circumstances:

- (1) To apply finishing materials that have a VOC content no greater than 1.0 lb VOC/lb solids, as applied;
- (2) For touchup and repair under the following conditions:
  - (i) The touchup and repair occurs after completion of the finishing operation; or
  - (ii) The touchup and repair occurs after the application of stain and before the application of any other type of finishing material, and the materials used for touchup and repair are applied from a container that has a volume of no more than 2.0 gallons.
- (3) When spray is automated, that is, the spray gun is aimed and triggered automatically, not manually;
- (5) The conventional air gun is used to apply finishing materials and the cumulative total usage of that finishing material is no more than 5.0 percent of the total gallons of finishing material used during that semiannual period; or
- (6) The conventional air gun is used to apply stain on a part for which it is technically or economically infeasible to use any other spray application technology.

The affected source shall demonstrate technical or economic infeasibility by submitting to the Administrator a videotape, a technical report, or other documentation that supports the affected source's claim of technical or economic infeasibility. The following criteria shall be used, either independently or in combination, to support the affected source's claim of technical or economic infeasibility:

- (i) The production speed is too high or the part shape is too complex for one operator to coat the part and the application station is not large enough to accommodate an additional operator; or
  - (ii) The excessively large vertical spray area of the part makes it difficult to avoid sagging or runs in the stain.
- (i) *Line cleaning.* Each owner or operator of an affected source shall pump or drain all organic HAP solvent used for line cleaning into a normally closed container.
- (j) *Gun cleaning.* Each owner or operator of an affected source shall collect all organic HAP solvent used to clean spray guns into a normally closed container.
- (k) *Washoff operations.* Each owner or operator of an affected source shall control emissions from washoff operations by:
- (1) Using normally closed tanks for washoff; and
  - (2) Minimizing dripping by tilting or rotating the part to drain as much solvent as possible.
- (l) *Formulation assessment plan for finishing operations.* Each owner or operator of an affected source shall prepare and maintain with the work practice implementation plan a formulation assessment plan that:
- (1) Identifies VHAP from the list presented in Table 5 of this subpart that are being used in finishing operations by the affected source;
  - (2) Establishes a baseline level of usage by the affected source, for each VHAP identified in paragraph (l)(1) of this section. The baseline usage level shall be the highest annual usage from 1994, 1995, or 1996, for each VHAP identified in paragraph (l)(1) of this section. For formaldehyde, the baseline level of usage shall be based on the amount of free formaldehyde present in the finishing material when it is applied. For styrene, the baseline level of usage shall be an estimate of unreacted styrene, which shall be calculated by multiplying the amount of styrene monomer in the finishing material, when it is applied, by a factor of 0.16. Sources using a control device to reduce emissions may adjust their usage based on the overall control efficiency of the control system, which is determined using the equation in §63.805 (d) or (e).

(3) Tracks the annual usage of each VHAP identified in (l)(1) by the affected source that is present in amounts subject to MSDS reporting as required by OSHA.

(4) If, after November 1998, the annual usage of the VHAP identified in paragraph (l)(1) exceeds its baseline level, then the owner or operator of the affected source shall provide a written notification to the permitting authority that describes the amount of the increase and explains the reasons for exceedance of the baseline level. The following explanations would relieve the owner or operator from further action, unless the affected source is not in compliance with any State regulations or requirements for that VHAP:

(i) The exceedance is no more than 15.0 percent above the baseline level;

(ii) Usage of the VHAP is below the *de minimis* level presented in Table 5 of this subpart for that VHAP (sources using a control device to reduce emissions may adjust their usage based on the overall control efficiency of the control system, which is determined using the procedures in §63.805 (d) or (e);

(iii) The affected source is in compliance with its State's air toxic regulations or guidelines for the VHAP; or

(iv) The source of the pollutant is a finishing material with a VOC content of no more than 1.0 kg VOC/kg solids (1.0 lb VOC/lb solids), as applied.

(5) If none of the above explanations are the reason for the increase, the owner or operator shall confer with the permitting authority to discuss the reason for the increase and whether there are practical and reasonable technology-based solutions for reducing the usage. The evaluation of whether a technology is reasonable and practical shall be based on cost, quality, and marketability of the product, whether the technology is being used successfully by other wood furniture manufacturing operations, or other criteria mutually agreed upon by the permitting authority and owner or operator. If there are no practical and reasonable solutions, the facility need take no further action. If there are solutions, the owner or operator shall develop a plan to reduce usage of the pollutant to the extent feasible. The plan shall address the approach to be used to reduce emissions, a timetable for implementing the plan, and a schedule for submitting notification of progress.

(6) If, after November 1998, an affected source uses a VHAP of potential concern listed in Table 6 of this subpart for which a baseline level has not been previously established, then the baseline level shall be established as the *de minimis* level provided in that same table for that chemical. The affected source shall track the annual usage of each VHAP of potential concern identified in this paragraph that is present in amounts subject to MSDS reporting as required by OSHA. If usage of the VHAP of potential concern exceeds the *de minimis* level listed in table 6 of this subpart for that chemical, then the affected source shall provide an explanation to the permitting authority that documents the reason for the exceedance of the *de minimis* level. If the explanation is not one of those listed in paragraphs (l)(4)(i) through (l)(4)(iv) of this section, the affected source shall follow the procedures in paragraph (l)(5) of this section.

#### § 63.804 Compliance procedures and monitoring requirements.

(a) The owner or operator of an existing affected source subject to §63.802(a)(1) shall comply with those provisions using any of the methods presented in §63.804 (a)(1) through (a)(4).

(1) Calculate the average VHAP content for all finishing materials used at the facility using Equation 1, and maintain a value of E no greater than 1.0;

$$E = \frac{(M_{c1} C_{c1} + M_{c2} C_{c2} + \dots + M_{cn} C_{cn} + S_1 W_1 + S_2 W_2 + \dots + S_n W_n)}{(M_{c1} + M_{c2} + \dots + M_{cn})} \quad \text{Equation 1}$$

(2) Use compliant finishing materials according to the following criteria:

(i) Demonstrate that each stain, sealer, and topcoat has a VHAP content of no more than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied, and each thinner contains no more than 10.0 percent VHAP by weight by maintaining certified product data sheets for each coating and thinner;

(ii) Demonstrate that each washcoat, basecoat, and enamel that is purchased pre-made, that is, it is not formulated onsite by thinning another finishing material, has a VHAP content of no more than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied, and each thinner contains no more than 10.0 percent VHAP by weight by maintaining certified product data sheets for each coating and thinner; and

(iii) Demonstrate that each washcoat, basecoat, and enamel that is formulated at the affected source is formulated using a finishing material containing no more than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids) and a thinner containing no more than 3.0 percent VHAP by weight.

(4) Use any combination of an averaging approach, as described in paragraph (a)(1) of this section, compliant finishing materials, as described in paragraph (a)(2) of this section, and a control system, as described in paragraph (a)(3) of this section.

(b) The owner or operator of an affected source subject to §63.802(a)(2)(i) shall comply with the provisions by using compliant foam adhesives with a VHAP content no greater than 1.8 kg VHAP/kg solids (1.8 lb VHAP/lb solids), as applied.

(c) The owner or operator of an affected source subject to §63.802(a)(2)(ii) shall comply with those provisions by using either of the methods presented in §63.804 (c)(1) and (c)(2).

(1) Use compliant contact adhesives with a VHAP content no greater than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied; or

(g) *Continuous compliance demonstrations.* (1) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(1) or (d)(1) shall demonstrate continuous compliance by submitting the results of the averaging calculation (Equation 1) for each month within that semiannual period and submitting a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that the value of (E), as calculated by Equation 1, is no greater than 1.0 for existing sources or 0.8 for new sources. An affected source is in violation of the standard if E is greater than 1.0 for existing sources or 0.8 for new sources for any month. A violation of the monthly average is a separate violation of the standard for each day of operation during the month, unless the affected source can demonstrate through records that the violation of the monthly average can be attributed to a particular day or days during the period.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(2) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(2) or (d)(2) shall demonstrate continuous compliance by using compliant coatings and thinners, maintaining records that demonstrate the coatings and thinners are compliant, and submitting a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that compliant stains, washcoats, sealers, topcoats, basecoats, enamels, and thinners, as applicable, have been used each day in the semiannual reporting period or should otherwise identify the periods of noncompliance and the reasons for noncompliance. An affected source is in violation of the standard whenever a noncompliant coating, as demonstrated by records or by a sample of the coating, is used.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(3) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that are complying through the procedures established in §63.804 (a)(2) or (d)(2) and are applying coatings using continuous coaters shall demonstrate continuous compliance by following the procedures in paragraph (g)(3) (i) or (ii) of this section.

(i) Using compliant coatings, as determined by the VHAP content of the coating in the reservoir and the VHAP content as calculated from records, using compliant thinners, and submitting a compliance certification with the semiannual report required by §63.807(c).

(A) The compliance certification shall state that compliant coatings have been used each day in the semiannual reporting period, or should otherwise identify the days of noncompliance and the reasons for noncompliance. An affected source is in violation of the standard whenever a noncompliant coating, as determined by records or by a sample of the coating, is used. Use of a noncompliant coating is a separate violation for each day the noncompliant coating is used.

(B) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(ii) Using compliant coatings, as determined by the VHAP content of the coating in the reservoir, using compliant thinners, maintaining a viscosity of the coating in the reservoir that is no less than the viscosity of the initial coating by monitoring the viscosity with a viscosity meter or by testing the viscosity of the initial coating and retesting the coating in the reservoir each time solvent is added, maintaining records of solvent additions, and submitting a compliance certification with the semiannual report required by §63.807(c).

(A) The compliance certification shall state that compliant coatings, as determined by the VHAP content of the coating in the reservoir, have been used each day in the semiannual reporting period. Additionally, the certification shall state that the viscosity of the coating in the reservoir has not been less than the viscosity of the initial coating, that is, the coating that is initially mixed and placed in the reservoir, for any day in the semiannual reporting period.

(B) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(C) An affected source is in violation of the standard when a sample of the as-applied coating exceeds the applicable limit established in §63.804 (a)(2) or (d)(2), as determined using EPA Method 311, or the viscosity of the coating in the reservoir is less than the viscosity of the initial coating.

(5) Owners or operators of an affected source subject to the provisions of §63.802 (a)(2) (i) or (ii) or (b)(2) that comply through the procedures established in §63.804 (b), (c)(1), or (e)(1), shall submit a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that compliant contact and/or foam adhesives have been used each day in the semiannual reporting period, or should otherwise identify each day noncompliant contact and/or foam adhesives were used. Each day a noncompliant contact or foam adhesive is used is a single violation of the standard.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(7) Owners or operators of an affected source subject to the provisions of §63.802 (a)(3) or (b)(3) shall submit a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that compliant strippable spray booth coatings have been used each day in the semiannual reporting period, or should otherwise identify each day noncompliant materials were used. Each day a noncompliant strippable booth coating is used is a single violation of the standard.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(8) Owners or operators of an affected source subject to the work practice standards in §63.803 shall submit a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that the work practice implementation plan is being followed, or should otherwise identify the provisions of the plan that have not been implemented and each day the provisions were not implemented. During any period of time that an owner or operator is required to implement the provisions of the plan, each failure to implement an obligation under the plan during any particular day is a violation.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

#### **§ 63.805 Performance test methods.**

(a) The EPA Method 311 of appendix A of part 63 shall be used in conjunction with formulation data to determine the VHAP content of the liquid coating. Formulation data shall be used to identify VHAP present in the coating. The EPA Method 311 shall then be used to quantify those VHAP identified through formulation data. The EPA Method 311 shall not be used to quantify HAP such as styrene and formaldehyde that are emitted during the cure. The EPA Method 24 (40 CFR part 60, appendix A) shall be used to determine the solids content by weight and the density of coatings. If it is demonstrated to the satisfaction of the Administrator that a coating does not release VOC or HAP byproducts during the cure, for example, all VOC and HAP present in the coating is solvent, then batch formulation information shall be accepted. The owner or operator of an affected source may request approval from the Administrator to use an alternative method for determining the VHAP content of the coating. In the event of any inconsistency between the EPA Method 24 or Method 311 test data and a facility's formulation data, that is, if the EPA Method 24/311 value is higher, the EPA Method 24/311 test shall govern unless after consultation, a regulated source could demonstrate to the satisfaction of the enforcement agency that the formulation data were correct. Sampling procedures shall follow the guidelines presented in "Standard Procedures for Collection of Coating and Ink Samples for VOC Content Analysis by Reference Method 24 and Reference Method 24A," EPA-340/1-91-010. (Docket No. A-93-10, Item No. IV-A-1).

#### **§ 63.806 Recordkeeping requirements.**

(a) The owner or operator of an affected source subject to this subpart shall fulfill all recordkeeping requirements of §63.10 of subpart A, according to the applicability criteria in §63.800(d) of this subpart.

(b) The owner or operator of an affected source subject to the emission limits in §63.802 of this subpart shall maintain records of the following:

(1) A certified product data sheet for each finishing material, thinner, contact adhesive, and strippable spray booth coating subject to the emission limits in §63.802; and

(2) The VHAP content, in kg VHAP/kg solids (lb VHAP/lb solids), as applied, of each finishing material and contact adhesive subject to the emission limits in §63.802; and

(3) The VOC content, in kg VOC/kg solids (lb VOC/lb solids), as applied, of each strippable booth coating subject to the emission limits in §63.802 (a)(3) or (b)(3).

(c) The owner or operator of an affected source following the compliance method in §63.804 (a)(1) or (d)(1) shall maintain copies of the averaging calculation for each month following the compliance date, as well as the data on the quantity of coatings and thinners used that is necessary to support the calculation of E in Equation 1.

(d) The owner or operator of an affected source following the compliance procedures of §63.804 (f)(3)(ii) and (g)(3)(ii) shall maintain the records required by §63.806(b) as well as records of the following:

- (1) Solvent and coating additions to the continuous coater reservoir;
  - (2) Viscosity measurements; and
  - (3) Data demonstrating that viscosity is an appropriate parameter for demonstrating compliance.
- (e) The owner or operator of an affected source subject to the work practice standards in §63.803 of this subpart shall maintain onsite the work practice implementation plan and all records associated with fulfilling the requirements of that plan, including, but not limited to:
- (1) Records demonstrating that the operator training program required by §63.803(b) is in place;
  - (2) Records collected in accordance with the inspection and maintenance plan required by §63.803(c);
  - (3) Records associated with the cleaning solvent accounting system required by §63.803(d);
  - (4) Records associated with the limitation on the use of conventional air spray guns showing total finishing material usage and the percentage of finishing materials applied with conventional air spray guns for each semiannual period as required by §63.803(h)(5).
  - (5) Records associated with the formulation assessment plan required by §63.803(l); and
  - (6) Copies of documentation such as logs developed to demonstrate that the other provisions of the work practice implementation plan are followed.
- (h) The owner or operator of an affected source subject to the emission limits in §63.802 and following the compliance provisions of §63.804(f) (1), (2), (3), (5), (7) and (8) and §63.804(g) (1), (2), (3), (5), (7), and (8) shall maintain records of the compliance certifications submitted in accordance with §63.807(c) for each semiannual period following the compliance date.
- (i) The owner or operator of an affected source shall maintain records of all other information submitted with the compliance status report required by §63.9(h) and §63.807(b) and the semiannual reports required by §63.807(c).
- (j) The owner or operator of an affected source shall maintain all records in accordance with the requirements of §63.10(b)(1).

#### **§ 63.807 Reporting requirements.**

- (a) The owner or operator of an affected source subject to this subpart shall fulfill all reporting requirements of §63.7 through §63.10 of subpart A (General Provisions) according to the applicability criteria in §63.800(d) of this subpart.
- (c) The owner or operator of an affected source demonstrating compliance in accordance with §63.804(g) (1), (2), (3), (5), (7), and (8) shall submit a report covering the previous 6 months of wood furniture manufacturing operations:
- (1) The first report shall be submitted 30 calendar days after the end of the first 6-month period following the compliance date.
  - (2) Subsequent reports shall be submitted 30 calendar days after the end of each 6-month period following the first report.
  - (3) The semiannual reports shall include the information required by §63.804(g) (1), (2), (3), (5), (7), and (8), a statement of whether the affected source was in compliance or noncompliance, and, if the affected source was in noncompliance, the measures taken to bring the affected source into compliance.

(4) The frequency of the reports required by paragraph (c) of this section shall not be reduced from semiannually regardless of the history of the owner's or operator's compliance status.

(e) The owner or operator of an affected source required to provide a written notification under §63.803(1)(4) shall include in the notification one or more statements that explains the reasons for the usage increase. The notification shall be submitted no later than 30 calendar days after the end of the annual period in which the usage increase occurred.

**§ 63.808 Implementation and enforcement.**

(a) This subpart can be implemented and enforced by the U.S. EPA, or a delegated authority such as the applicable State, local, or Tribal agency. If the U.S. EPA Administrator has delegated authority to a State, local, or Tribal agency, then that agency, in addition to the U.S. EPA, has the authority to implement and enforce this subpart. Contact the applicable U.S. EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to a State, local, or Tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or Tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator of U.S. EPA and cannot be transferred to the State, local, or Tribal agency.

(c) The authorities that cannot be delegated to State, local, or Tribal agencies are as specified in paragraphs (c)(1) through (5) of this section.

(1) Approval of alternatives to the requirements in §§63.800, 63.802, and 63.803(a)(1), (b), (c) introductory text, and (d) through (l).

(2) Approval of alternatives to the monitoring and compliance requirements in §§63.804(f)(4)(iv)(D) and (E), 63.804(g)(4)(iii)(C), 63.804(g)(4)(vi), and 63.804(g)(6)(vi).

(3) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f), as defined in §63.90, and as required in this subpart, as well as approval of any alternatives to the specific test methods under §§63.805(a), 63.805(d)(2)(v), and 63.805(e)(1).

(4) Approval of major alternatives to monitoring under §63.8(f), as defined in §63.90, and as required in this subpart.

(5) Approval of major alternatives to recordkeeping and reporting under §63.10(f), as defined in §63.90, and as required in this subpart.

**Table 2 to Subpart JJ of Part 63—List of Volatile Hazardous Air Pollutants**

| Chemical name              | CAS No. |
|----------------------------|---------|
| Acetaldehyde.....          | 75070   |
| Acetamide.....             | 60355   |
| Acetonitrile.....          | 75058   |
| Acetophenone.....          | 98862   |
| 2-Acetylaminofluorine..... | 53963   |
| Acrolein.....              | 107028  |
| Acrylamide.....            | 79061   |
| Acrylic acid.....          | 79107   |
| Acrylonitrile.....         | 107131  |
| Allyl chloride.....        | 107051  |
| 4-Aminobiphenyl.....       | 92671   |
| Aniline.....               | 62533   |
| o-Anisidine.....           | 90040   |

|   |         |
|---|---------|
| Benzene.....  | 71432   |
| Benzidine.....  | 92875   |
| Benzotrichloride.....   | 98077   |
| Benzyl chloride.....  | 100447  |
| Biphenyl.....   | 92524   |
| Bis (2-ethylhexyl) phthalate (DEHP).....                                | 117817  |
| Bis (chloromethyl) ether.....   | 542881  |
| Bromoform.....  | 75252   |
| 1,3-Butadiene.....  | 106990  |
| Carbon disulfide.....   | 75150   |
| Carbon tetrachloride.....   | 56235   |
| Carbonyl sulfide.....   | 463581  |
| Catechol.....   | 120809  |
| Chloroacetic acid.....  | 79118   |
| 2-Chloroacetophenone.....   | 532274  |
| Chlorobenzene.....  | 108907  |
| Chloroform.....   | 67663   |
| Chloromethyl methyl ether.....  | 107302  |
| Chloroprene.....  | 126998  |
| Cresols (isomers and mixture).....                                      | 1319773 |
| o-Cresol.....   | 95487   |
| m-Cresol.....   | 108394  |
| p-Cresol.....   | 106445  |
| Cumene.....   | 98828   |
| 2,4-D (2,4-Dichlorophenoxyacetic acid, including salts and esters)..... | 94757   |
| DDE (1,1-Dichloro-2,2-bis(p-chlorophenyl)ethylene).....                 | 72559   |
| Diazomethane.....   | 334883  |
| Dibenzofuran.....   | 132649  |
| 1,2-Dibromo-3-chloropropane.....  | 96128   |
| Dibutylphthalate.....   | 84742   |
| 1,4-Dichlorobenzene.....  | 106467  |
| 3,3[prime]-Dichlorobenzidine.....                                       | 91941   |
| Dichloroethyl ether (Bis(2-chloroethyl)ether).....                      | 111444  |
| 1,3-Dichloropropene.....  | 542756  |
| Diethanolamine.....   | 111422  |
| N,N-Dimethylaniline.....  | 121697  |
| Diethyl sulfate.....  | 64675   |
| 3,3[prime]-Dimethoxybenzidine.....                                      | 119904  |
| 4-Dimethylaminoazobenzene.....  | 60117   |
| 3,3[prime]-Dimethylbenzidine.....                                       | 119937  |
| Dimethylcarbamoyl chloride.....   | 79447   |
| N,N-Dimethylformamide.....  | 68122   |
| 1,1-Dimethylhydrazine.....  | 57147   |
| Dimethyl phthalate.....   | 131113  |
| Dimethyl sulfate.....   | 77781   |
| 4,6-Dinitro-o-cresol, and salts.....                                    | 534521  |
| 2,4-Dinitrophenol.....  | 51285   |
| 2,4-Dinitrotoluene.....   | 121142  |
| 1,4-Dioxane (1,4-Diethyleneoxide).....                                  | 123911  |
| 1,2-Diphenylhydrazine.....  | 122667  |
| Epichlorohydrin (1-Chloro-2,3-epoxypropane).....                        | 106898  |
| 1,2-Epoxybutane.....  | 106887  |
| Ethyl acrylate.....   | 140885  |
| Ethylbenzene.....   | 100414  |
| Ethyl carbamate (Urethane).....   | 51796   |
| Ethyl chloride (Chloroethane).....                                      | 75003   |
| Ethylene dibromide (Dibromoethane).....                                 | 106934  |
| Ethylene dichloride (1,2-Dichloroethane).....                           | 107062  |
| Ethylene glycol.....  | 107211  |

|  |         |
|--|---------|
| Ethylene oxide.....                                  | 75218   |
| Ethylenethiourea.....                                | 96457   |
| Ethylidene dichloride (1,1-Dichloroethane).....      | 75343   |
| Formaldehyde.....                                    | 50000   |
| Glycoethers a.....                                   | .....   |
| Hexachlorobenzene.....                               | 118741  |
| Hexachloro-1,3-butadiene.....                        | 87683   |
| Hexachloroethane.....                                | 67721   |
| Hexamethylene-1,6-diisocyanate.....                  | 822060  |
| Hexamethylphosphoramide.....                         | 680319  |
| Hexane.....  | 110543  |
| Hydrazine.....                                       | 302012  |
| Hydroquinone.....                                    | 123319  |
| Isophorone.....                                      | 78591   |
| Maleic anhydride.....                                | 108316  |
| Methanol.....  | 67561   |
| Methyl bromide (Bromomethane).....                   | 74839   |
| Methyl chloride (Chloromethane).....                 | 74873   |
| Methyl chloroform (1,1,1-Trichloroethane).....       | 71556   |
| Methyl ethyl ketone (2-Butanone).....                | 78933   |
| Methylhydrazine.....                                 | 60344   |
| Methyl iodide (Iodomethane).....                     | 74884   |
| Methyl isobutyl ketone (Hexone).....                 | 108101  |
| Methyl isocyanate.....                               | 624839  |
| Methyl methacrylate.....                             | 80626   |
| Methyl tert-butyl ether.....                         | 1634044 |
| 4,4[prime]-Methylenebis (2-chloroaniline).....       | 101144  |
| Methylene chloride (Dichloromethane).....            | 75092   |
| 4,4[prime]-Methylenediphenyl diisocyanate (MDI)..... | 101688  |
| 4,4[prime]-Methylenedianiline.....                   | 101779  |
| Naphthalene.....                                     | 91203   |
| Nitrobenzene.....                                    | 98953   |
| 4-Nitrobiphenyl.....                                 | 92933   |
| 4-Nitrophenol.....                                   | 100027  |
| 2-Nitropropane.....                                  | 79469   |
| N-Nitroso-N-methylurea.....                          | 684935  |
| N-Nitrosodimethylamine.....                          | 62759   |
| N-Nitrosomorpholine.....                             | 59892   |
| Phenol.....  | 108952  |
| p-Phenylenediamine.....                              | 106503  |
| Phosgene.....  | 75445   |
| Phthalic anhydride.....                              | 85449   |
| Polychlorinated biphenyls (Aroclors).....            | 1336363 |
| Polycyclic Organic Matter b.....                     | .....   |
| 1,3-Propane sultone.....                             | 1120714 |
| beta-Propiolactone.....                              | 57578   |
| Propionaldehyde.....                                 | 123386  |
| Propoxur (Baygon).....                               | 114261  |
| Propylene dichloride (1,2-Dichloropropane).....      | 78875   |
| Propylene oxide.....                                 | 75569   |
| 1,2-Propylenimine (2-Methyl aziridine).....          | 75558   |
| Quinone.....   | 106514  |
| Styrene.....   | 100425  |
| Styrene oxide.....                                   | 96093   |
| 2,3,7,8-Tetrachlorodibenzo-p-dioxin.....             | 1746016 |
| 1,1,2,2-Tetrachloroethane.....                       | 79345   |
| Tetrachloroethylene (Perchloroethylene).....         | 127184  |
| Toluene.....   | 108883  |
| 2,4-Toluenediamine.....                              | 95807   |
| Toluene-2,4-diisocyanate.....                        | 584849  |

|   |         |
|---|---------|
| o-Toluidine.....                                | 95534   |
| 1,2,4-Trichlorobenzene.....                     | 120821  |
| 1,1,2-Trichloroethane.....                      | 79005   |
| Trichloroethylene.....                          | 79016   |
| 2,4,5-Trichlorophenol.....                      | 95954   |
| 2,4,6-Trichlorophenol.....                      | 88062   |
| Triethylamine.....                              | 121448  |
| Trifluralin.....                                | 1582098 |
| 2,2,4-Trimethylpentane.....                     | 540841  |
| Vinyl acetate.....                              | 108054  |
| Vinyl bromide.....                              | 593602  |
| Vinyl chloride.....                             | 75014   |
| Vinylidene chloride (1,1-Dichloroethylene)..... | 75354   |
| Xylenes (isomers and mixture).....              | 1330207 |
| o-Xylene.....                                   | 95476   |
| m-Xylene.....                                   | 108383  |
| p-Xylene.....                                   | 106423  |

- 
- a Includes mono- and di-ethers of ethylene glycol, diethylene glycols and triethylene glycol; R-(OCH2CH2) RR-OR where:  
 n = 1, 2, or 3,  
 R = alkyl or aryl groups  
 R[prime]= R, H, or groups which, when removed, yield glycol ethers with the structure: R-(OCH2CH2)n\_OH. Polymers are excluded from the glycol category.
- b Includes organic compounds with more than one benzene ring, and which have a boiling point greater than or equal to 100°C.

**Table 3 to Subpart JJ of Part 63—Summary of Emission Limits**

| Emission point   | Existing source | New source |
|--|-----------------|------------|
| -----  |                 |            |
| Finishing Operations:  |                 |            |
| (a) Achieve a weighted average VHAP content across all coatings (maximum kg VHAP/kg solids [lb VHAP/lb solids], as applied)..... | a 1.0           | a 0.8      |
| (b) Use compliant finishing materials (maximum kg VHAP/kg solids [lb VHAP/lb solids], as applied):                               |                 |            |
| _stains.....   | a 1.0           | a 1.0      |
| _washcoats.....  | a,b 1.0         | a,b 0.8    |
| _sealers.....  | a 1.0           | a 0.8      |
| _topcoats.....   | a 1.0           | a 0.8      |
| _basecoats.....  | a,b 1.0         | a,b 0.8    |
| _enamels.....  | a,b 1.0         | a,b 0.8    |
| _thinners (maximum percent VHAP allowable); or.....  | 10.0            | 10.0       |
| (d) Use any combination of (a), (b), and (c)   | 1.0             | 0.8        |
| Cleaning Operations:   |                 |            |
| Strippable spray booth material (maximum VOC content, kg VOC/kg solids [lb VOC/lb solids]).....                                  | 0.8             | 0.8        |
| Contact Adhesives:   |                 |            |
| (a) Use compliant contact adhesives (maximum kg VHAP/kg solids [lb VHAP/lb solids], as applied) based on following criteria:     |                 |            |
| i. For aerosol adhesives, and for  | d NA            | d NA       |

|  |     |     |
|--|-----|-----|
| contact adhesives applied to nonporous substrates.....   |     |     |
| ii. For foam adhesives used in products that meet flammability requirements....  | 1.8 | 0.2 |
| iii. For all other contact adhesives (including foam adhesives used in products that do not meet flammability requirements); or..... | 1.0 | 0.2 |

- a The limits refer to the VHAP content of the coating, as applied.
- b Washcoats, basecoats, and enamels must comply with the limits presented in this table if they are purchased premade, that is, if they are not formulated onsite by thinning other finishing materials. If they are formulated onsite, they must be formulated using compliant finishing materials, i.e., those that meet the limits specified in this table, and thinners containing no more than 3.0 percent VHAP by weight.
- d There is no limit on the VHAP content of these adhesives.

**Table 4 to Subpart JJ of Part 63—Pollutants Excluded From Use in Cleaning and Washoff Solvents**

| Chemical name                                | CAS No.  |
|--|----------|
| 4-Aminobiphenyl.....                         | 92671    |
| Styrene oxide.....                           | 96093    |
| Diethyl sulfate.....                         | 64675    |
| N-Nitrosomorpholine.....                     | 59892    |
| Dimethyl formamide.....                      | 68122    |
| Hexamethylphosphoramide.....                 | 680319   |
| Acetamide.....                               | 60355    |
| 4,4[prime]-Methylenedianiline.....           | 101779   |
| o-Anisidine.....                             | 90040    |
| 2,3,7,8-Tetrachlorodibenzo-p-dioxin.....     | 1746016  |
| Beryllium salts.....                         | .....    |
| Benzidine.....                               | 92875    |
| N-Nitroso-N-methylurea.....                  | 684935   |
| Bis (chloromethyl) ether.....                | 542881   |
| Dimethyl carbamoyl chloride.....             | 79447    |
| Chromium compounds (hexavalent).....         | .....    |
| 1,2-Propylenimine (2-Methyl aziridine).....  | 75558    |
| Arsenic and inorganic arsenic compounds..... | 99999904 |
| Hydrazine.....                               | 302012   |
| 1,1-Dimethyl hydrazine.....                  | 57147    |
| Beryllium compounds.....                     | 7440417  |
| 1,2-Dibromo-3-chloropropane.....             | 96128    |
| N-Nitrosodimethylamine.....                  | 62759    |
| Cadmium compounds.....                       | .....    |
| Benzo (a) pyrene.....                        | 50328    |
| Polychlorinated biphenyls (Aroclors).....    | 1336363  |
| Heptachlor.....                              | 76448    |
| 3,3[prime]-Dimethyl benzidine.....           | 119937   |
| Nickel subsulfide.....                       | 12035722 |
| Acrylamide.....                              | 79061    |
| Hexachlorobenzene.....                       | 118741   |
| Chlordane.....                               | 57749    |
| 1,3-Propane sultone.....                     | 1120714  |
| 1,3-Butadiene.....                           | 106990   |

|   |         |
|---|---------|
| Nickel refinery dust.....                           | .....   |
| 2-Acetylaminoflourine.....                          | 53963   |
| 3,3[prime]-Dichlorobenzidine.....                   | 53963   |
| Lindane (hexachlorcyclohexane, gamma).....          | 58899   |
| 2,4-Toluene diamine.....                            | 95807   |
| Dichloroethyl ether (Bis(2-chloroethyl) ether)..... | 111444  |
| 1,2-Diphenylhydrazine.....                          | 122667  |
| Toxaphene (chlorinated camphene).....               | 8001352 |
| 2,4-Dinitrotoluene.....                             | 121142  |
| 3,3[prime]-Dimethoxybenzidine.....                  | 119904  |
| Formaldehyde.....                                   | 50000   |
| 4,4[prime]-Methylene bis (2-chloroaniline).....     | 101144  |
| Acrylonitrile.....                                  | 107131  |
| Ethylene dibromide (1,2-Dibromoethane).....         | 106934  |
| DDE (1,1-p-chlorophenyl 1-2 dichloroethylene).....  | 72559   |
| Chlorobenzilate.....                                | 510156  |
| Dichlorvos.....                                     | 62737   |
| Vinyl chloride.....                                 | 75014   |
| Coke Oven Emissions.....                            | .....   |
| Ethylene oxide.....                                 | 75218   |
| Ethylene thiourea.....                              | 96457   |
| Vinyl bromide (bromoethene).....                    | 593602  |
| Selenium sulfide (mono and di).....                 | 7488564 |
| Chloroform.....                                     | 67663   |
| Pentachlorophenol.....                              | 87865   |
| Ethyl carbamate (Urethane).....                     | 51796   |
| Ethylene dichloride (1,2-Dichloroethane).....       | 107062  |
| Propylene dichloride (1,2-Dichloropropane).....     | 78875   |
| Carbon tetrachloride.....                           | 56235   |
| Benzene.....  | 71432   |
| Methyl hydrazine.....                               | 60344   |
| Ethyl acrylate.....                                 | 140885  |
| Propylene oxide.....                                | 75569   |
| Aniline.....  | 62533   |
| 1,4-Dichlorobenzene(p).....                         | 106467  |
| 2,4,6-Trichlorophenol.....                          | 88062   |
| Bis (2-ethylhexyl) phthalate (DEHP).....            | 117817  |
| o-Toluidine.....                                    | 95534   |
| Propoxur.....                                       | 114261  |
| 1,4-Dioxane (1,4-Diethyleneoxide).....              | 123911  |
| Acetaldehyde.....                                   | 75070   |
| Bromoform.....                                      | 75252   |
| Captan.....   | 133062  |
| Epichlorohydrin.....                                | 106898  |
| Methylene chloride (Dichloromethane).....           | 75092   |
| Dibenz (ah) anthracene.....                         | 53703   |
| Chrysene.....                                       | 218019  |
| Dimethyl aminoazobenzene.....                       | 60117   |
| Benzo (a) anthracene.....                           | 56553   |
| Benzo (b) fluoranthene.....                         | 205992  |
| Antimony trioxide.....                              | 1309644 |
| 2-Nitropropane.....                                 | 79469   |
| 1,3-Dichloropropene.....                            | 542756  |
| 7, 12-Dimethylbenz(a) anthracene.....               | 57976   |
| Benz(c) acridine.....                               | 225514  |
| Indeno(1,2,3-cd)pyrene.....                         | 193395  |
| 1,2:7,8-Dibenzopyrene.....                          | 189559  |

---

**Table 5 to Subpart JJ of Part 63—List of VHAP of Potential Concern Identified by Industry**

| CAS No.      | Chemical name         | EPA de minimis, tons/yr |
|--------------|-----------------------|-------------------------|
| 68122.....   | Dimethyl formamide    | 1.0                     |
| 50000.....   | Formaldehyde          | 0.2                     |
| 75092.....   | Methylene chloride    | 4.0                     |
| 79469.....   | 2-Nitropropane        | 1.0                     |
| 78591.....   | Isophorone            | 0.7                     |
| 1000425..... | Styrene monomer       | 1.0                     |
| 108952.....  | Phenol                | 0.1                     |
| 111422.....  | Dimethanolamine       | 5.0                     |
| 109864.....  | 2-Methoxyethanol      | 10.0                    |
| 111159.....  | 2-Ethoxyethyl acetate | 10.0                    |

**Table 6 to Subpart JJ of Part 63—VHAP of Potential Concern**

| CAS No.      | Chemical name                           | EPA de minimis, tons/yr* |
|--------------|---|--------------------------|
| 92671.....   | 4-Aminobiphenyl.....                    | 1.0                      |
| 96093.....   | Styrene oxide.....                      | 1.0                      |
| 64675.....   | Diethyl sulfate.....                    | 1.0                      |
| 59892.....   | N-Nitrosomorpholine.....                | 1.0                      |
| 68122.....   | Dimethyl formamide.....                 | 1.0                      |
| 680319.....  | Hexamethylphosphoramide.....            | 0.01                     |
| 60355.....   | Acetamide.....                          | 1.0                      |
| 101779.....  | 4,4[prime]-Methylenedianiline....       | 1.0                      |
| 90040.....   | o-Anisidine.....                        | 1.0                      |
| 1746016..... | 2,3,7,8-Tetrachlorodibenzo-p-dioxin.    | 0.00000006               |
| 92875.....   | Benzidine.....                          | 0.00003                  |
| 684935.....  | N-Nitroso-N-methylurea.....             | 0.00002                  |
| 542881.....  | Bis(chloromethyl) ether.....            | 0.00003                  |
| 79447.....   | Dimethyl carbamoyl chloride.....        | 0.002                    |
| 75558.....   | 1,2-Propylenimine (2-Methyl aziridine). | 0.0003                   |
| 57147.....   | 1,1-Dimethyl hydrazine.....             | 0.0008                   |
| 96128.....   | 1,2-Dibromo-3-chloropropane.....        | 0.001                    |
| 62759.....   | N-Nitrosodimethylamine.....             | 0.0001                   |
| 50328.....   | Benzo (a) pyrene.....                   | 0.001                    |
| 1336363..... | Polychlorinated biphenyls (Aroclors).   | 0.0009                   |
| 76448.....   | Heptachlor.....                         | 0.002                    |
| 119937.....  | 3,3[prime]-Dimethyl benzidine....       | 0.001                    |
| 79061.....   | Acrylamide.....                         | 0.002                    |
| 118741.....  | Hexachlorobenzene.....                  | 0.004                    |
| 57749.....   | Chlordane.....                          | 0.005                    |
| 1120714..... | 1,3-Propane sultone.....                | 0.003                    |
| 106990.....  | 1,3-Butadiene.....                      | 0.007                    |

|              |  |        |
|--------------|--|--------|
| 53963.....   | 2-Acetylaminoflourine.....                         | 0.0005 |
| 91941.....   | 3,3[prime]-Dichlorobenzidine.....                  | 0.02   |
| 58899.....   | Lindane (hexachlorocyclohexane,<br>gamma).         | 0.005  |
| 95807.....   | 2,4-Toluene diamine.....                           | 0.002  |
| 111444.....  | Dichloroethyl ether (Bis(2-<br>chloroethyl)ether). | 0.006  |
| 122667.....  | 1,2_Diphenylhydrazine.....                         | 0.009  |
| 8001352..... | Toxaphene (chlorinated camphene).                  | 0.006  |
| 121142.....  | 2,4-Dinitrotoluene.....                            | 0.002  |
| 119904.....  | 3,3[prime]-Dimethoxybenzidine.....                 | 0.01   |
| 50000.....   | Formaldehyde.....                                  | 0.2    |
| 101144.....  | 4,4[prime]-Methylene bis(2-<br>chloroaniline).     | 0.02   |
| 107131.....  | Acrylonitrile.....                                 | 0.03   |
| 106934.....  | Ethylene dibromide(1,2-<br>Dibromoethane).         | 0.01   |
| 72559.....   | DDE (1,1-p-chlorophenyl 1-2<br>dichloroethylene).  | 0.01   |
| 510156.....  | Chlorobenzilate.....                               | 0.04   |
| 62737.....   | Dichlorvos.....                                    | 0.02   |
| 75014.....   | Vinyl chloride.....                                | 0.02   |
| 75218.....   | Ethylene oxide.....                                | 0.09   |
| 96457.....   | Ethylene thiourea.....                             | 0.06   |
| 593602.....  | Vinyl bromide (bromoethene).....                   | 0.06   |
| 67663.....   | Chloroform.....                                    | 0.09   |
| 87865.....   | Pentachlorophenol.....                             | 0.07   |
| 51796.....   | Ethyl carbamate (Urethane).....                    | 0.08   |
| 107062.....  | Ethylene dichloride (1,2-<br>Dichloroethane).      | 0.08   |
| 78875.....   | Propylene dichloride (1,2-<br>Dichloropropane).    | 0.1    |
| 56235.....   | Carbon tetrachloride.....                          | 0.1    |
| 71432.....   | Benzene.....                                       | 0.2    |
| 140885.....  | Ethyl acrylate.....                                | 0.1    |
| 75569.....   | Propylene oxide.....                               | 0.5    |
| 62533.....   | Aniline.....                                       | 0.1    |
| 106467.....  | 1,4-Dichlorobenzene(p).....                        | 0.3    |
| 88062.....   | 2,4,6-Trichlorophenol.....                         | 0.6    |
| 117817.....  | Bis (2-ethylhexyl) phthalate<br>(DEHP).            | 0.5    |
| 95534.....   | o-Toluidine.....                                   | 0.4    |
| 114261.....  | Propoxur.....                                      | 2.0    |
| 79016.....   | Trichloroethylene.....                             | 1.0    |
| 123911.....  | 1,4-Dioxane (1,4-Diethyleneoxide)                  | 0.6    |
| 75070.....   | Acetaldehyde.....                                  | 0.9    |
| 75252.....   | Bromoform.....                                     | 2.0    |
| 133062.....  | Captan.....  | 2.0    |
| 106898.....  | Epichlorohydrin.....                               | 2.0    |
| 75092.....   | Methylene chloride<br>(Dichloromethane).           | 4.0    |
| 127184.....  | Tetrachloroethylene<br>(Perchloroethylene).        | 4.0    |
| 53703.....   | Dibenz (ah) anthracene.....                        | 0.01   |
| 218019.....  | Chrysene.....                                      | 0.01   |
| 60117.....   | Dimethyl aminoazobenzene.....                      | 1.0    |
| 56553.....   | Benzo (a) anthracene.....                          | 0.01   |
| 205992.....  | Benzo (b) fluoranthene.....                        | 0.01   |
| 79469.....   | 2-Nitropropane.....                                | 1.0    |
| 542756.....  | 1,3-Dichloropropene.....                           | 1.0    |

|               |  |        |
|---------------|--|--------|
| 57976.....    | 7,12-Dimethylbenz (a) anthracene.            | 0.01   |
| 225514.....   | Benz(c)acridine.....                         | 0.01   |
| 193395.....   | Indeno(1,2,3-cd)pyrene.....                  | 0.01   |
| 189559.....   | 1,2:7,8-Dibenzopyrene.....                   | 0.01   |
| 79345.....    | 1,1,2,2-Tetrachloroethane.....               | 0.03   |
| 91225.....    | Quinoline.....                               | 0.0006 |
| 75354.....    | Vinylidene chloride (1,1-Dichloroethylene).  | 0.04   |
| 87683.....    | Hexachlorobutadiene.....                     | 0.09   |
| 82688.....    | Pentachloronitrobenzene (Quintobenzene).     | 0.03   |
| 78591.....    | Isophorone.....                              | 0.7    |
| 79005.....    | 1,1,2-Trichloroethane.....                   | 0.1    |
| 74873.....    | Methyl chloride (Chloromethane)..            | 1.0    |
| 67721.....    | Hexachloroethane.....                        | 0.5    |
| 1582098.....  | Trifluralin.....                             | 0.9    |
| 1319773.....  | Cresols/Cresylic acid (isomers and mixture). | 1.0    |
| 108394.....   | m-Cresol.....                                | 1.0    |
| 75343.....    | Ethylidene dichloride (1,1-Dichloroethane).  | 1.0    |
| 95487.....    | o-Cresol.....                                | 1.0    |
| 106445.....   | p-Cresol.....                                | 1.0    |
| 74884.....    | Methyl iodide (Iodomethane).....             | 1.0    |
| 100425.....   | Styrene.....                                 | 1.0    |
| 107051.....   | Allyl chloride.....                          | 1.0    |
| 334883.....   | Diazomethane.....                            | 1.0    |
| 95954.....    | 2,4,5-Trichlorophenol.....                   | 1.0    |
| 133904.....   | Chloramben.....                              | 1.0    |
| 106887.....   | 1,2-Epoxybutane.....                         | 1.0    |
| 108054.....   | Vinyl acetate.....                           | 1.0    |
| 126998.....   | Chloroprene.....                             | 1.0    |
| 123319.....   | Hydroquinone.....                            | 1.0    |
| 92933.....    | 4-Nitrobiphenyl.....                         | 1.0    |
| 56382.....    | Parathion.....                               | 0.1    |
| 13463393..... | Nickel Carbonyl.....                         | 0.1    |
| 60344.....    | Methyl hydrazine.....                        | 0.006  |
| 151564.....   | Ethylene imine.....                          | 0.0003 |
| 77781.....    | Dimethyl sulfate.....                        | 0.1    |
| 107302.....   | Chloromethyl methyl ether.....               | 0.1    |
| 57578.....    | beta-Propiolactone.....                      | 0.1    |
| 100447.....   | Benzyl chloride.....                         | 0.04   |
| 98077.....    | Benzotrichloride.....                        | 0.0006 |
| 107028.....   | Acrolein.....                                | 0.04   |
| 584849.....   | 2,4-Toluene diisocyanate.....                | 0.1    |
| 75741.....    | Tetramethyl lead.....                        | 0.01   |
| 78002.....    | Tetraethyl lead.....                         | 0.01   |
| 12108133..... | Methylcyclopentadienyl manganese.            | 0.1    |
| 624839.....   | Methyl isocyanate.....                       | 0.1    |
| 77474.....    | Hexachlorocyclopentadiene.....               | 0.1    |
| 62207765..... | Fluomine.....                                | 0.1    |
| 10210681..... | Cobalt carbonyl.....                         | 0.1    |
| 79118.....    | Chloroacetic acid.....                       | 0.1    |
| 534521.....   | 4,6-Dinitro-o-cresol, and salts..            | 0.1    |
| 101688.....   | Methylene diphenyl diisocyanate..            | 0.1    |
| 108952.....   | Phenol.....                                  | 0.1    |
| 62384.....    | Mercury, (acetato-o) phenyl.....             | 0.01   |
| 98862.....    | Acetophenone.....                            | 1.0    |
| 108316.....   | Maleic anhydride.....                        | 1.0    |
| 532274.....   | 2-Chloroacetophenone.....                    | 0.06   |

|             |                                   |      |
|-------------|-----------------------------------|------|
| 51285.....  | 2,4-Dinitrophenol.....            | 1.0  |
| 109864..... | 2-Methoxy ethanol.....            | 10.0 |
| 98953.....  | Nitrobenzene.....                 | 1.0  |
| 74839.....  | Methyl bromide (Bromomethane).... | 10.0 |
| 75150.....  | Carbon disulfide.....             | 1.0  |
| 121697..... | N,N-Dimethylaniline.....          | 1.0  |
| 106514..... | Quinone.....                      | 5.0  |
| 123386..... | Propionaldehyde.....              | 5.0  |
| 120809..... | Catechol.....                     | 5.0  |
| 85449.....  | Phthalic anhydride.....           | 5.0  |
| 463581..... | Carbonyl sulfide.....             | 5.0  |
| 132649..... | Dibenzofurans.....                | 5.0  |
| 100027..... | 4-Nitrophenol.....                | 5.0  |
| 540841..... | 2,2,4-Trimethylpentane.....       | 5.0  |
| 111422..... | Diethanolamine.....               | 5.0  |
| 822060..... | Hexamethylene-1,6-diisocyanate... | 5.0  |
|             | Glycol ethersa.....               | 5.0  |
|             | Polycyclic organic matterb.....   | 0.01 |

-----  
\* These values are based on the de minimis levels provided in the proposed rulemaking pursuant to section 112(g) of the Act using a 70-year lifetime exposure duration for all VHAP. Default assumptions and the de minimis values based on inhalation reference doses (RfC) are not changed by this adjustment.

a Except for ethylene glycol butyl ether, ethylene glycol ethyl ether (2-ethoxy ethanol), ethylene glycol hexyl ether, ethylene glycol methyl ether (2-methoxyethanol), ethylene glycol phenyl ether, ethylene glycol propyl ether, ethylene glycol mono-2-ethylhexyl ether, diethylene glycol butyl ether, diethylene glycol ethyl ether, diethylene glycol methyl ether, diethylene glycol hexyl ether, diethylene glycol phenyl ether, diethylene glycol propyl ether, triethylene glycol butyl ether, triethylene glycol ethyl ether, triethylene glycol methyl ether, triethylene glycol propyl ether, ethylene glycol butyl ether acetate, ethylene glycol ethyl ether acetate, and diethylene glycol ethyl ether acetate.

b Except for benzo(b)fluoranthene, benzo(a)anthracene, benzo(a)pyrene, 7,12-dimethylbenz(a)anthracene, benz(c)acridine, chrysene, dibenz(ah)anthracene, 1,2:7,8-dibenzopyrene, indeno(1,2,3-cd)pyrene, but including dioxins and furans.

## SECTION D.3

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]: Woodworking Operations

- (j) Woodworking operations, identified as DC-1, constructed in 1993, with a maximum capacity of 1,797 pounds per hour, using a baghouse as control and exhausting to stacks 12a and 12b.
- (k) Woodworking operations, identified as DC-2, constructed in 1987, with a maximum capacity of 2,259 pounds per hour, using a baghouse as control and exhausting to stacks 13a and 13b.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.3.1 Particulate Matter Limitations: Dubois County [326 IAC 6.5-4-16]

Pursuant to 326 IAC 6.5-4-16 (Particulate Matter Limitations: Dubois County)(formerly 326 IAC 6-1-9), the particulate emissions from the woodworking operations shall be limited to 3.9 tons per year.

#### D.3.2 PSD Minor Limit [326 IAC 2-2]

The emissions of PM and PM10 from each of the woodworking operations (DC-1 and DC-2) shall not exceed 25 pounds per hour. Compliance with this limit makes the requirements of 326 IAC 2-2 (PSD) not applicable to the modifications performed in 1987 and 1993.

#### D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

### Compliance Determination Requirements

#### D.3.4 Particulate Control [326 IAC 2-7-6(6)] [40 CFR 64]

- (a) Except as otherwise provided by statute, rule, or this permit, the baghouses for particulate emissions control shall be in operation and control emissions at all times the associated woodworking operations are in operation.
- (b) In the event that bag failure is observed in a multi-compartment baghouse, if operations will continue for ten (10) days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.

### Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

#### D.3.5 Visible Emissions Notations [40 CFR 64]

- (a) Daily visible emission notations of the woodworking baghouse stack exhausts shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.

- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

#### D.3.6 Baghouse Inspections [40 CFR 64]

---

An inspection shall be performed each calendar quarter of all bags controlling the two (2) woodworking operations when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.

#### D.3.7 Broken or Failed Bag Detection

---

- (a) For a single compartment baghouses controlling emissions from a process operated continuously, a failed unit and the associated process shall be shut down immediately until the failed unit has been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit have been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in the emissions unit. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Bag failure can be indicated by a significant drop in the baghouse=s pressure reading with abnormal visible emissions, by an opacity violation, or by other means such as gas temperature, flow rate, air infiltration, leaks, dust traces or triboflows.

### **Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

#### D.3.8 Record Keeping Requirements

---

- (a) To document compliance with Condition D.3.5, the Permittee shall maintain records of daily visible emission notations of the woodworking baghouse stack exhausts.
- (b) To document compliance with Condition D.3.6, the Permittee shall maintain records of the results of the inspections required under Condition D.3.6 and the dates the vents are redirected.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

## SECTION D.4

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]: Insignificant Activities

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs; brazing equipment, cutting torches, soldering equipment, welding equipment. [326 IAC 6.5-1-2]
- (b) Trimmers that do not produce fugitive emissions and that are equipped with a dust collection or trim material recovery device such as a bag filter or cyclone. [326 IAC 6.5-1-2]
- (d) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations. [326 IAC 6.5-1-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.4.1 Particulate Emission Limitations [326 IAC 6.5-1-2]

Pursuant to 326 IAC 6.5-1-2, (formerly 326 IAC 6-1-2), particulate matter emissions from each of the insignificant trimmers, grinding and machining operations, the insignificant brazing, soldering and welding equipment and cutting torches shall not exceed 0.03 grains per dry standard cubic foot.

### Compliance Determination Requirements

#### D.4.2 Particulate Control

Pursuant to 326 IAC 6.5-1-2, and in order to comply with Condition D.4.1, the particulate control equipment shall be in operation and control emissions from the trimmers and grinding and machining operations at all times that these facilities are in operation.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

### PART 70 OPERATING PERMIT CERTIFICATION

Source Name: Jasper Desk Company, Incorporated  
Source Address: 415 East 6<sup>th</sup> Street, Jasper, Indiana 47546  
Mailing Address: P.O. Box 111, Jasper, Indiana 47547  
Part 70 Permit No.: T037-17545-00007

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.**

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify)
- 9 Report (specify)
- 9 Notification (specify)
- 9 Affidavit (specify)
- 9 Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE BRANCH  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251  
Phone: 317-233-0178  
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT  
EMERGENCY OCCURRENCE REPORT**

Source Name: Jasper Desk Company, Incorporated  
Source Address: 415 East 6<sup>th</sup> Street, Jasper, Indiana 47546  
Mailing Address: P.O. Box 111, Jasper, Indiana 47547  
Part 70 Permit No.: T037-17545-00007

**This form consists of 2 pages**

**Page 1 of 2**

|   |
|---|
| <p><input type="checkbox"/> This is an emergency as defined in 326 IAC 2-7-1(12)</p> <p><input type="checkbox"/> The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and</p> <p><input type="checkbox"/> The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.</p> |
|---|

If any of the following are not applicable, mark N/A

|   |
|---|
| Facility/Equipment/Operation:                       |
| Control Equipment:                                  |
| Permit Condition or Operation Limitation in Permit: |
| Description of the Emergency:                       |
| Describe the cause of the Emergency:                |

If any of the following are not applicable, mark N/A

**Page 2 of 2**

|   |
|---|
| Date/Time Emergency started:  |
| Date/Time Emergency was corrected:  |
| Was the facility being properly operated at the time of the emergency?    Y    N<br>Describe:   |
| Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:   |
| Estimated amount of pollutant(s) emitted during emergency:  |
| Describe the steps taken to mitigate the problem:   |
| Describe the corrective actions/response steps taken:   |
| Describe the measures taken to minimize emissions:  |
| If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value: |

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

A certification is not required for this report.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY Compliance Data Section

### Part 70 Usage Report Semi-Annual Report VOC and VHAP Usage - Wood Furniture NESHAP

Source Name: Jasper Desk Company, Incorporated  
 Source Address: 415 East 6<sup>th</sup> Street, Jasper, Indiana 47546  
 Mailing Address: P.O. Box 111, Jasper, Indiana 47547  
 Part 70 Permit No.: T037-17545-00007  
 Facility: Surface Coating Booths SB-1, SB-2, SB-3, SB-4, SB-5, SB-6 and SB-7.  
 Parameter: VOC and VHAPs - NESHAP  
 Limit: (1) Finishing operations -1.0 lb VHAP/lb Solids  
 (2) Thinners used for on-site formulation of washcoats, basecoats and enamels - 3% VHAP content by weight  
 (3) All other thinners - 10% VHAP content by weight  
 (4) Foam adhesives meeting the upholstered seating flammability requirements - 1.8 lb VHAP/lb Solids  
 (5) All other contact adhesives - 1.0 lb VHAP/lb Solids  
 (6) Strippable spray booth material - 0.8 pounds VOC per pound solids

Year \_\_\_\_\_

| Month | Finishing Operations<br>(lb VHAP /lb Solid) | Thinners Used for On-Site Formulation<br>(% by weight) | All Other Thinners<br>(% by weight) | Foam Adhesives (upholstered)<br>(lb VHAP / lb Solid) | Contact Adhesives<br>(lb VHAP / lb Solid) | Strippable Spray Booth Material (lb VOC / lb Solid) |
|-------|---|--|-------------------------------------|--|---|---|
| 1     |   |  |                                     |  |   |   |
| 2     |   |  |                                     |  |   |   |
| 3     |   |  |                                     |  |   |   |
| 4     |   |  |                                     |  |   |   |
| 5     |   |  |                                     |  |   |   |
| 6     |   |  |                                     |  |   |   |

- No deviation occurred in this month.
- Deviation/s occurred in this month.  
 Deviation has been reported on:

Submitted by: \_\_\_\_\_  
 Title/Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
Compliance Data Section**

**PART 70 OPERATING PERMIT  
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Jasper Desk Company, Incorporated  
Source Address: 415 East 6<sup>th</sup> Street, Jasper, Indiana 47546  
Mailing Address: P.O. Box 111, Jasper, Indiana 47547  
Part 70 Permit No.: T037-17545-00007

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

Page 1 of 2

|  |                               |
|--|-------------------------------|
| This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period". |                               |
| 9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.  |                               |
| 9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD  |                               |
| <b>Permit Requirement (specify permit condition #)</b>   |                               |
| <b>Date of Deviation:</b>  | <b>Duration of Deviation:</b> |
| <b>Number of Deviations:</b>   |                               |
| <b>Probable Cause of Deviation:</b>  |                               |
| <b>Response Steps Taken:</b>   |                               |
| <b>Permit Requirement (specify permit condition #)</b>   |                               |
| <b>Date of Deviation:</b>  | <b>Duration of Deviation:</b> |
| <b>Number of Deviations:</b>   |                               |
| <b>Probable Cause of Deviation:</b>  |                               |
| <b>Response Steps Taken:</b>   |                               |

|  |                               |
|--|-------------------------------|
| <b>Permit Requirement (specify permit condition #)</b> |                               |
| <b>Date of Deviation:</b>                              | <b>Duration of Deviation:</b> |
| <b>Number of Deviations:</b>                           |                               |
| <b>Probable Cause of Deviation:</b>                    |                               |
| <b>Response Steps Taken:</b>                           |                               |
| <b>Permit Requirement (specify permit condition #)</b> |                               |
| <b>Date of Deviation:</b>                              | <b>Duration of Deviation:</b> |
| <b>Number of Deviations:</b>                           |                               |
| <b>Probable Cause of Deviation:</b>                    |                               |
| <b>Response Steps Taken:</b>                           |                               |
| <b>Permit Requirement (specify permit condition #)</b> |                               |
| <b>Date of Deviation:</b>                              | <b>Duration of Deviation:</b> |
| <b>Number of Deviations:</b>                           |                               |
| <b>Probable Cause of Deviation:</b>                    |                               |
| <b>Response Steps Taken:</b>                           |                               |

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

A certification is not required for this report.