INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
We make Indiana a cleaner, healthier place to live.

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
MC 61-53
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

TO: Interested Parties / Applicant

DATE: January 18, 2008

RE: North American Bristol Corporation / 039-25698-00064

FROM: Matthew Stuckey, Deputy Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days from the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

(1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
(2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
(3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

(1) the name and address of the person making the request;
(2) the interest of the person making the request;
(3) identification of any persons represented by the person making the request;
(4) the reasons, with particularity, for the request;
(5) the issues, with particularity, proposed for considerations at any hearing; and
(6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER-AM.dot12/3/07

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
We make Indiana a cleaner, healthier place to live.

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

January 18, 2008

Mr. Ed Foy
North American Bristol Corporation
P.O. Box 609
Bristol, Indiana 46507

Re: 039-25698-00064
First Notice-Only Change to
M039-20061-00064

Dear Mr. Foy

North American Bristol Corporation was issued a Minor Source Operating Permit (MSOP) Renewal No. M039-20061-00064 on October 17, 2006 for a stationary PVC and ABS plastic pipe manufacturing plant located at 503 East Vistula Street, Bristol, Indiana 46507. On December 17, 2007, the Office of Air Quality (OAQ) received an application from the source requesting that the MSOP Renewal permit term be extended to ten (10) years. On December 16, 2007, rule revisions to 326 IAC 2-1.1-9 and 326 IAC 2-6.1-7 were finalized allowing for ten (10) year permit terms on MSOP renewals. This change to the permit is considered a notice-only change pursuant to 326 IAC 2-6.1-6(d)(6), since it incorporates newly applicable requirements as a result of a change in applicability. Pursuant to the provisions of 326 IAC 2-6.1-6, the permit is hereby revised as follows with the deleted language as ~~strikeouts~~ and new language **bolded**.

(a) The expiration date on the cover page has been extended by five (5) years as follows.

Issuance Date: October 17, 2006
Expiration Date: October 17, ~~2011~~ **2016**

(b) Condition B.2 has been revised to reflect the ten (10) year permit term.

B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5] [IC13-15-3-6(a)]

(a) This permit, 039-20061-00064, is issued for a fixed term of ~~five (5)~~ **ten (10)** years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.

(c) Section A.1 is revised to indicate that Elkhart County is now in attainment for the 8-hour ozone standard. Section A.1 is updated as follows:

Source Location Status: ~~Nonattainment area for 8-hour ozone~~
Attainment area for all ~~other~~ criteria pollutants

All other conditions of the permit shall remain unchanged and in effect. Attached please find the entire revised permit.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Pam K. Way of my staff, at 317-234-5373 or 1-800-451-6027, and ask for extension 4-5373.

Sincerely,

Original document signed by

Iryn Calilung, Section Chief
Permits Branch
Office of Air Quality

Attachments: Updated Permit
IC/pkw

cc: File -Elkhart County
Elkhart County Health Department
U.S. EPA, Region V
Air Compliance Section
IDEM Northern Regional Office
Compliance Data Section
Technical Support and Modeling
Permits Administrative and Development
Billing, Licensing and Training Section

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
We make Indiana a cleaner, healthier place to live.

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

MINOR SOURCE OPERATING PERMIT RENEWAL
OFFICE OF AIR QUALITY

North American Bristol Corporation
503 East Vistula Street
Bristol, Indiana 46507

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages. This permit to operate does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated there under, as well as other applicable local, state, and federal requirements.

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a MSOP under 326 IAC 2-6.1.

Operation Permit No.: M039-20061-00064	
Original signed by: Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: October 17, 2006 Expiration Date: October 17, 2016

First Significant Permit Revision No. 039-24476-00064, issued on August 1, 2007

First Notice-Only Change No. 039-25698-00064	
Issued by: *Original document signed by* Iryn Calilung Permits Branch Office of Air Quality	Issuance Date: January 18, 2008 Expiration Date: October 17, 2016

TABLE OF CONTENTS

A SOURCE SUMMARY 4
A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]
A.2 Emission Units and Pollution Control Equipment Summary

B GENERAL CONDITIONS 7
B.1 Definitions [326 IAC 2-1.1-1]
B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5] [IC13-15-3-6(a)]
B.3 Term of Conditions [326 IAC 2-1.1-9.5]
B.4 Enforceability
B.5 Severability
B.6 Property Right or Exclusive Privilege
B.7 Duty to Provide Information
B.8 Certification
B.9 Annual Notification [326 IAC 2-6.1-5(a)(5)]
B.10 Preventive Maintenance Plan [326 IAC 1-6-3]
B.11 Prior Permits Superseded [326 IAC 2-1.1-9.5]
B.12 Termination of Right to Operate [326 IAC 2-6.1-7(a)]
B.13 Deviations from Permit Requirements and Conditions
B.14 Permit Renewal [326 IAC 2-6.1-7]
B.15 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]
B.16 Source Modification Requirement
B.17 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2] [IC 13-17-3-2][IC 13-30-3-1]
B.18 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]
B.19 Annual Fee Payment [326 IAC 2-1.1-7]
B.20 Credible Evidence [326 IAC 1-1-6]

C SOURCE OPERATION CONDITIONS 12

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]
C.1 Particulate Emission Limitation For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]
C.2 Permit Revocation [326 IAC 2-1.1-9]
C.3 Opacity [326 IAC 5-1]
C.4 Fugitive Dust Emissions [326 IAC 6-4]
C.5 Asbestos Abatement Projects [326 IAC 14-10][326 IAC 18][40 CFR 61, Subpart M]

Testing Requirements
C.6 Performance Testing [326 IAC 3-6]

Compliance Requirements [326 IAC 2-1.1-11]
C.7 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements
C.8 Compliance Monitoring [326 IAC 2-1.1-11]
C.9 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]
C.10 Instrument Specifications [326 IAC 2-1.1-11]
C.11 Response to Excursions or Exceedances
C.12 Actions Related to Noncompliance Demonstrated by a Stack Test

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]
C.13 Malfunctions Report [326 IAC 1-6-2]
C.14 General Record Keeping Requirements [326 IAC 2-6.1-5]
C.15 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-5] [IC 13-14-1-13]

TABLE OF CONTENTS (Continued)

D.1 EMISSIONS UNIT OPERATION CONDITIONS 18

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]
D.1.1 Particulate [326 IAC 6-3-2]
D.1.2 Preventive Maintenance Plan [326 IAC 1-6-3]

Compliance Determination Requirements
D.1.3 Particulate Control

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)][326 IAC 2-6.1-5(a)(2)]
D.1.4 Visible Emissions Notations
D.1.5 Broken or Failed Bag Detection
D.1.6 Cyclone Failure Detection

Record Keeping and Reporting Requirement [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]
D.1.7 Record Keeping Requirements

D.2 EMISSIONS UNIT OPERATION CONDITIONS 22

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]
D.2.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]
D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]

Annual Notification 24
Malfunction Report 25

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 and A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)][326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary PVC and ABS plastic pipe manufacturing plant.

Source Address:	503 East Vistula Street, Bristol, Indiana 46507
Mailing Address:	P.O. Box 609, Bristol, Indiana 46507
General Source Phone Number:	(574) 848-4402
SIC Code:	3084
County Location:	Elkhart
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Minor Source Operating Permit Minor Source, under PSD and Emission Offset Rules; Minor Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary

This stationary source is approved to operate the following emission units and pollution control devices:

(a) One (1) railcar unloading operation, identified as RRUNLOAD, with a maximum capacity of 12,500 lbs of resin per hour, with particulate emissions controlled by a dust collector (RRDC), and exhausting through stack RRDC.

(b) One (1) PVC resin blender, identified as BL1, with a maximum blending capacity of 10,000 pounds of resin per hour, with particulate emissions controlled by a dust collector (DCBL1), and exhausting to stack DCBL1.

(c) Ten (10) extruder lines, using PVC resin, PVC compound, ABS pellets, and/or re-ground waste material as feedstock, with particulate emissions controlled by dust collectors, with no VOC emission controls, and exhausting inside the building, as follows:

Emission Unit ID	Maximum Throughput Rate (lbs/hour)	Control Unit ID
Extruder Line E1	1,000	DCE1
Extruder Line E2	800	DCE2
Extruder Line E3	1,100	DCE3
Extruder Line E4	250	DCE4
Extruder Line E5	2,400	DCE5
Extruder Line E6	1,300	DCE6
Extruder Line E7	1,200	DCE7
Extruder Line E8	1,000	DCE8
Extruder Line E9	900	DCE9
Extruder Line E10	1,200	DCE10

(d) One (1) regrinder/pulverizer, identified as R1, with a maximum regrinding capacity of 500 pounds of waste per hour, with re-ground material pneumatically conveyed to Silo 13, with

particulate emissions controlled by a bin vent dust collector (DCS13), and exhausting to stacks R01 and DCS13.

(e) Two (2) ABS dryers, identified as ABSDRY1 and ABSDRY2, each with a maximum drying capacity of 1,280 pounds of ABS resin per hour, with particulate emissions controlled by dust collectors (DCDRY1 and DCDRY2), and exhausting to stacks DCDRY1 and DCDRY2, respectively.

(f) Fifteen (15) silos for storing PVC compound, PVC resin, ABS pellets, re-ground plastic material, and limestone, using bin vent dust collectors to control particulate emissions, and exhausting to the atmosphere, as follows:

Emission Unit ID	Material Stored	Maximum Throughput (lbs/hour)	Maximum Storage Capacity (lbs)	Control Unit/Stack ID
Silo S1	PVC Compound	3652	122,600	DCS1
Silo S2	ABS Pellets	1800	122,600	DCS3
Silo S3	ABS Pellets	1800	122,600	
Silo S4	PVC Compound	3652	122,600	DCS5
Silo S5	PVC Compound	3652	122,600	
Silo S6	Limestone	1000	151,200	DCS6
Silo S7	PVC Compound	3652	122,600	DCS8
Silo S8	PVC Compound	3652	122,600	
Silo S9	PVC Compound	3652	122,600	DCS9
Silo S10	PVC Resin	8330	122,600	DCS11
Silo S11	PVC Resin	8330	211,000	
Silo S12	PVC Compound	3,652	122,600	DCS12
Silo S13	Re-ground Material	913	122,600	DCS13
Silo S14	Re-ground Material	913	122,600	DCS14
Silo S15	Re-ground Material	913	151,200	DCS15

(g) Ten (10) printers, identified as P1 constructed in 1985, with a maximum printing capacity of 9,580 pounds of PVC/ABS plastic tubes per hour, using no controls and venting inside the building.

(h) Propane or liquified petroleum gas or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) Btu per hour.

(i) The following VOC and HAP storage containers:

(1) Storage tanks with capacity less than or equal to one thousand (1,000) gallons and annual throughputs equal to or less than twelve thousand (12,000) gallons.

(2) Vessels storing lubricating oils, hydraulic oils, machining oils, or machining fluids.

(j) Machining where an aqueous cutting coolant continuously floods the machining interface.

(k) Degreasing operations that do not exceed one hundred forty-five (145) gallons per twelve (12) months, and not subject to 326 IAC 20-6.

(l) Cleaners and solvents characterized as:

(1) Having a vapor pressure equal to or less than two (2.0) kilo Pascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pound per square inch) measured at thirty-eight (38) degrees Centigrade (one hundred (100) degrees Fahrenheit); or

(2) Having a vapor pressure equal to or less than seven-tenths (0.7) kilo Pascal (five (5) millimeters of mercury or one-tenth (0.1) pound per square inch) measured at twenty (20) degrees Centigrade (sixty-eight (68) degrees Fahrenheit);

The use of which, for all cleaners and solvents combined, does not exceed one hundred forty-five (145) gallons per twelve (12) months.

(m) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment, including:

(n) Closed loop heating and cooling systems.

(o) Any operation using aqueous solutions containing less than or equal to one percent (1%) by weight of VOCs excluding HAPs.

(p) Replacement or repair of bags in baghouses, and filters in other air filtration equipment.

(q) Paved and unpaved roads and parking lots with public access.

(r) Conveyors, consisting of enclosed systems for conveying plastic raw material and plastic finished goods.

(s) Equipment used to collect any material that might be released during a malfunction, process upset, or spill cleanup, including catch tanks, temporary liquid separators, tanks, and/or fluid handling equipment.

(t) On-site fire training approved by the department.

(u) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors, and electrostatic precipitators with a design grain loading of less than or equal to three one-hundredths (0.03) grains per actual cubic foot and a gas flow rate less than or equal to four thousand (4,000) actual cubic feet per minute, including deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and/or woodworking operations.

SECTION B GENERAL CONDITIONS

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1.1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

B.1 Definitions [326 IAC 2-1.1-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations IC 13-11, 326 IAC 1-2, and 326 IAC 2-1.1-1 shall prevail.

B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5] [IC13-15-3-6(a)]

(a) This permit, 039-20061-00064, is issued for a fixed term of ten (10) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.

(b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

(a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or

(b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information

(a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by an “authorized individual” as defined by 326 IAC 2-1.1-1. Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.

(b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification

(a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an "authorized individual" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

(b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.

(c) An "authorized individual" is defined at 326 IAC 2-1.1-1(1).

B.9 Annual Notification [326 IAC 2-6.1-5(a)(5)]

(a) An annual notification shall be submitted by an authorized individual to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.

(b) The annual notice shall be submitted in the format attached no later than March 1 of each year to:

Compliance Branch, Office of Air Quality
Indiana Department of Environmental Management
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

(c) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

B.10 Preventive Maintenance Plan [326 IAC 1-6-3]

(a) The Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) for the source as described in 326 IAC 1-6-3. At a minimum, the PMPs shall include:

(1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;

(2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and

(3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

(b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Prior Permits Superseded [326 IAC 2-1.1-9.5]

(a) All terms and conditions of permits established prior to and issued pursuant to permitting programs approved into the state implementation plan have been either

(1) incorporated as originally stated,

(2) revised, or

(3) deleted.

(b) All previous registrations and permits are superseded by this permit.

B.12 Termination of Right to Operate [326 IAC 2-6.1-7(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-6.1-7.

B.13 Deviations from Permit Requirements and Conditions

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.14 Permit Renewal [326 IAC 2-6.1-7]

(a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-6.1-7. Such information shall be included in the application for each emission unit at this source. The renewal application does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

(b) A timely renewal application is one that is:

(1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and

(2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-6.1 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ,, any additional information identified as being needed to process the application.

B.15 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

(a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.

(b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(c) The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 2-6.1-6(d)]

B.16 Source Modification Requirement

A modification, construction, or reconstruction is governed by 326 IAC 2.

B.17 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)] [IC 13-14-2-2] [IC13-17-3-2][IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

(a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;

(b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under this title or the conditions of this permit or any operating permit revisions;

(c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any processes, emissions units (including monitoring and air

pollution control equipment), practices, or operations regulated or required under this permit or any operating permit revisions;

(d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

(e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.18 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]

(a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.

(b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-6.1-6(d)(3)]

B.19 Annual Fee Payment [326 IAC 2-1.1-7]

(a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing.

(b) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.20 Credible Evidence [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) and which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation of Permits), this permit to operate may be revoked for any of the following causes:

(a) Violation of any conditions of this permit.

(b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.

(c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.

(d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.

(e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

(a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.

(b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute non-overlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.5 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

(a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least

thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

(b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:

(1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or

(2) If there is a change in the following:

(A) Asbestos removal or demolition start date;

(B) Removal or demolition contractor; or

(C) Waste disposal site.

(c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).

(d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue
MC 61-52 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an “authorized individual” as defined by 326 IAC 2-7-1(34).

(e) Procedures for Asbestos Emission Control
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.

(f) Demolition and renovation
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).

(g) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to

thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements

C.6 Performance Testing [326 IAC 3-6]

(a) Compliance testing on new emissions units shall be conducted within 60 days after achieving maximum production rate, but no later than180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by an “authorized individual” as defined by 326 IAC 2-1.1-1(1).

(b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14 days) prior to the actual date. The notification submitted by the Permittee does not require certification by an “authorized individual” as defined by 326 IAC 2-1.1-1(1).

(c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ (and local agency) not later than forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAQ, (and local agency), if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.7 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.

Compliance Monitoring Requirements

C.8 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.9 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.10 Instrument Specifications [326 IAC 2-1.1-11]

(a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale.

(b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

C.11 Response to Excursions or Exceedances

(a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.

(b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:

(1) initial inspection and evaluation;

(2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or

(3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.

(c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:

(1) monitoring results;

(2) review of operation and maintenance procedures and records;

(3) inspection of the control device, associated capture system, and the process.

(d) Failure to take reasonable response steps shall be considered a deviation from the permit.

(e) The Permittee shall maintain the following records:

(1) monitoring data;

(2) monitor performance data, if applicable; and

(3) corrective actions taken.

C.12 Actions Related to Noncompliance Demonstrated by a Stack Test

(a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected emissions unit while the response actions are being implemented.

(b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that re-testing in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the re-testing deadline.

(c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to non-compliant stack tests.

The response action documents submitted pursuant to this condition do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

C.13 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

(a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.

(b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.

(c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).

(d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.14 General Record Keeping Requirements [326 IAC 2-6.1-5]

(a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

(b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented when operation begins.

C.15 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-5] [IC 13-14-1-13]

(a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

(b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(c) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit “calendar year” means the twelve (12) month period from January 1 to December 31 inclusive.

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description [326 IAC 2-6.1-5(a)(1)]:

(a) One (1) railcar unloading operation, identified as RRUNLOAD, with a maximum capacity of 12,500 lbs of resin per hour, with particulate emissions controlled by a dust collector (RRDC), and exhausting through stack RRDC.

(b) One (1) PVC resin blender, identified as BL1, with a maximum blending capacity of 10,000 pounds of resin per hour, with particulate emissions controlled by a dust collector (DCBL1), and exhausting to stack DCBL1.

(c) Ten (10) extruder lines, using PVC resin, PVC compound, ABS pellets, and/or re-ground waste material as feedstock, with particulate emissions controlled by dust collectors, with no VOC emission controls, and exhausting inside the building, as follows:

Emission Unit ID	Maximum Throughput Rate (lbs/hour)	Control Unit ID
Extruder Line E1	1,000	DCE1
Extruder Line E2	800	DCE2
Extruder Line E3	1,100	DCE3
Extruder Line E4	250	DCE4
Extruder Line E5	2,400	DCE5
Extruder Line E6	1,300	DCE6
Extruder Line E7	1,200	DCE7
Extruder Line E8	1,000	DCE8
Extruder Line E9	900	DCE9
Extruder Line E10	1,200	DCE10

(d) One (1) regrinder/pulverizer, identified as R1, with a maximum regrinding capacity of 500 pounds of waste per hour, with re-ground material pneumatically conveyed to Silo 13, with particulate emissions controlled by a bin vent dust collector (DCS13), and exhausting to stacks R01 and DCS13.

(e) Two (2) ABS dryers, identified as ABSDRY1 and ABSDRY2, each with a maximum drying capacity of 1,280 pounds of ABS resin per hour, with particulate emissions controlled by dust collectors (DCDRY1 and DCDRY2), and exhausting to stacks DCDRY1 and DCDRY2, respectively.

(f) Fifteen (15) silos for storing PVC compound, PVC resin, ABS pellets, re-ground plastic material, and limestone, using bin vent dust collectors to control particulate emissions, and exhausting to the atmosphere, as follows:

Emission Unit ID	Material Stored	Maximum Throughput (lbs/hour)	Maximum Storage Capacity (lbs)	Control Unit/Stack ID
Silo S1	PVC Compound	3652	122,600	DCS1
Silo S2	ABS Pellets	1800	122,600	DCS3
Silo S3	ABS Pellets	1800	122,600	
Silo S4	PVC Compound	3652	122,600	DCS5
Silo S5	PVC Compound	3652	122,600	
Silo S6	Limestone	1000	151,200	DCS6
Silo S7	PVC Compound	3652	122,600	DCS8
Silo S8	PVC Compound	3652	122,600	
Silo S9	PVC Compound	3652	122,600	DCS9
Silo S10	PVC Resin	8330	122,600	DCS11
Silo S11	PVC Resin	8330	211,000	

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description [326 IAC 2-6.1-5(a)(1)]:

Silo S12	PVC Compound	3652	122,600	DCS12
Silo S13	Re-ground Material	913	122,600	DCS13
Silo S14	Re-ground Material	913	122,600	DCS14
Silo S15	Re-ground Material	913	151,200	DCS15

(g) Ten (10) printers, identified as P1, with a maximum printing capacity of 9,580 pounds of PVC/ABS plastic tubes per hour, using no controls and venting inside the building.

(u) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors, and electrostatic precipitators with a design grain loading of less than or equal to three one-hundredths (0.03) grains per actual cubic foot and a gas flow rate less than or equal to four thousand (4,000) actual cubic feet per minute, including deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and/or woodworking operations.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

D.1.1 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the manufacturing facilities shall not exceed the pound per hour limits shown in the following table.

Emission Unit ID	Maximum Throughput (lbs/hour)	Allowable Emissions (lbs/hour)	Control Unit ID
Unloading (RRUNLOAD)	12,500	14.0	RRDC
PVC resin blender (BL1)	10,000	12.1	DCBL1
Extruder Line E1	1,000	2.58	DCE1
Extruder Line E2	800	2.22	DCE2
Extruder Line E3	1,100	2.75	DCE3
Extruder Line E4	250	1.02	DCE4
Extruder Line E5	2,400	4.63	DCE5
Extruder Line E6	1,300	3.07	DCE6
Extruder Line E7	1,200	2.91	DCE7
Extruder Line E8	1,000	2.58	DCE8
Extruder Line E9	900	2.40	DCE9
Extruder Line E10	1,200	2.91	DCE10
Regrinder/Pulverizer (R1)	500	1.62	DCS13
ABSDRYER1	1,280	3.04	DCDRY1
ABSDRYER2	1,280	3.04	DCDRY2
Silo S1	3652	6.14	DCS1
Silo S2	1800	3.82	DCS3
Silo S3	1800	3.82	
Silo S4	3652	6.14	DCS5
Silo S5	3652	6.14	
Silo S6	1000	2.58	DCS6
Silo S7	3652	6.14	DCS8
Silo S8	3652	6.14	
Silo S9	3652	6.14	DCS9
Silo S10	8330	10.7	DCS11
Silo S11	8330	10.7	
Silo S12	3652	6.14	DCS12
Silo S13	913	2.42	DCS13
Silo S14	913	2.42	DCS14
Silo S15	913	2.42	DCS15

Grinding & Machining	1,000	2.58	Fabric Filter

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$E = 4.10\ P^{0.67}$ where E = rate of emission in pounds per hour; and P = process weight rate in tons per hour

D.1.2 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for the railcar unloading operation (RRUNLOAD) and the PVC resin blender (BL1) and their control devices (RRDC and DCBL1, respectively).

Compliance Determination Requirements

D.1.3 Particulate Control

(a) Pursuant to 326 IAC 6-3-2, and in order to comply with Condition D.1.1, the dust collectors for particulate control shall be in operation and control emissions from the Railcar Unloading (RRUNLOAD), PVC resin blender (BL1), Extruder Line E1, Extruder Line E2, Extruder Line E3, Extruder Line E4, Extruder Line E5, Extruder Line E6, Extruder Line E7, Extruder Line E8, Extruder Line E9, Extruder Line E10, Regrinder/Pulverizer (R1), ABSDRYER1, ABSDRYER2, Silo S1, Silo S2, Silo S3, Silo S4, Silo S5, Silo S6, Silo S7, Silo S8, Silo S9, Silo S10, Silo S11, Silo S12, Silo S13, Silo S14, Silo S15, and the Grinding & Machining at all times that these facilities are in operation.

(b) In the event that bag failure is observed in a multi-compartment dust collector, if operations will continue for ten (10) days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)][326 IAC 2-6.1-5(a)(2)]

D.1.4 Visible Emissions Notations

(a) Daily visible emission notations of the railcar unloading operation (RRUNLOAD) and the PVC resin blender (BL1) stack exhausts (RRDC and DCBL1) shall be performed during normal daylight operations. A trained employee shall record whether emissions are normal or abnormal.

(b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.

(c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.

(d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.

(e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take

response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

D.1.5 Broken or Failed Bag Detection

(a) For a single compartment dust collector controlling emissions from a process operated continuously, failed units and the associated process shall be shut down immediately until the failed unit have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

(b) For a single compartment dust collector controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit have been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in the emissions unit. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

D.1.6 Cyclone Failure Detection

In the event that cyclone failure has been observed:

Failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

Record Keeping and Reporting Requirement [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.7 Record Keeping Requirements

(a) To document compliance with Condition D.1.5, the Permittee shall maintain a daily record of visible emission notations of the railcar unloading operation (RRUNLOAD) and the PVC resin blender (BL1) stack exhausts. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g., the process did not operate that day).

(b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

SECTION D.2 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description [326 IAC 2-6.1-5(a)(1)]:

(k) Degreasing operations that do not exceed one hundred forty-five (145) gallons per twelve (12) months, except if subject to 326 IAC 20-6.

(l) Cleaners and solvents characterized as:

(1) Having a vapor pressure equal to or less than two (2.0) kilo Pascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pound per square inch) measured at thirty-eight (38) degrees Centigrade (one hundred (100) degrees Fahrenheit); or

(2) Having a vapor pressure equal to or less than seven-tenths (0.7) kilo Pascal (five (5) millimeters of mercury or one-tenth (0.1) pound per square inch) measured at twenty (20) degrees Centigrade (sixty-eight (68) degrees Fahrenheit);

The use of which, for all cleaners and solvents combined, does not exceed one hundred forty-five (145) gallons per twelve (12) months.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

D.2.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations), for cold cleaning operations constructed after January 1, 1980, the Permittee shall:

(a) Equip the cleaner with a cover;

(b) Equip the cleaner with a facility for draining cleaned parts;

(c) Close the degreaser cover whenever parts are not being handled in the cleaner;

(d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;

(e) Provide a permanent, conspicuous label summarizing the operation requirements;

(f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]

(a) Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), for cold cleaner degreaser operations without remote solvent reservoirs existing as of July 1, 1990, located in Clark, Elkhart, Floyd, Lake, Marion, Porter or St. Joseph Counties, the Permittee shall ensure that the following requirements are met:

(1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:

(A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch)

measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F));

(B) The solvent is agitated; or

(C) The solvent is heated.

(2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.

(3) Provide a permanent, conspicuous label which lists the operating requirements outlined in subsection (b).

(4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure which does not cause excessive splashing.

(5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):

(A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.

(B) A water cover when solvent is used is insoluble in, and heavier than, water.

(C) Other systems of demonstrated equivalent control such as a refrigerated chiller of carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.

(b) Pursuant to 326 IAC 8-3-5(b) (Cold Cleaner Degreaser Operation and Control), the Permittee shall ensure that the following operating requirements are met:

(1) Close the cover whenever articles are not being handled in the degreaser.

(2) Drain cleaned articles for at least fifteen (15) seconds or until dripping ceases.

(3) Store waste solvent only in covered containers and prohibit the disposal or transfer of waste solvent in any manner in which greater than twenty percent (20%) of the waste solvent by weight could evaporate.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH

MINOR SOURCE OPERATING PERMIT
ANNUAL NOTIFICATION

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

Company Name:	North American Bristol Corporation
Address:	503 East Vistula Street
City:	Bristol, Indiana 46507
Phone #:	(574) 848-4402
MSOP #:	039-20061-00064

I hereby certify that North American Bristol Corporation is ☐ still in operation.
☐ no longer in operation.

I hereby certify that North American Bristol Corporation is ☐ in compliance with the requirements of MSOP 039-20061-00064.
☐ not in compliance with the requirements of MSOP 039-20061-00064.

Authorized Individual (typed):
Title:
Signature:
Date:

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

Noncompliance:

MALFUNCTION REPORT

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
FAX NUMBER - 317 233-6865

This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4.

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?_____, 25 TONS/YEAR SULFUR DIOXIDE ?_____, 25 TONS/YEAR NITROGEN OXIDES?_____, 25 TONS/YEAR VOC ?_____, 25 TONS/YEAR HYDROGEN SULFIDE ?_____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?_____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?_____, 25 TONS/YEAR FLUORIDES ?_____, 100TONS/YEAR CARBON MONOXIDE ?_____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?_____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?_____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?_____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?_____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMI LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF >MALFUNCTION= AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY:_____PHONE NO. ( )_____
LOCATION: (CITY AND COUNTY)_____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP:_____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON:_____
_____

DATE/TIME MALFUNCTION STARTED: _____/_____/ 20____ _____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION:
_____

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE_____/_____/ 20____ _____ AM/PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER:_____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____
_____

MEASURES TAKEN TO MINIMIZE EMISSIONS:_____
_____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES:_____
CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS:_____
CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT:_____
INTERIM CONTROL MEASURES: (IF APPLICABLE)_____
_____
_____

MALFUNCTION REPORTED BY:_____TITLE:_____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY:_____DATE:_____TIME:_____
*SEE PAGE 2

Please note - This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4.

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

***Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

_____

_____