



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
**Governor**

*Thomas W. Easterly*  
**Commissioner**

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

TO: Interested Parties / Applicant

DATE: May 22, 2009

RE: Supreme Corporation / 039-27944-00103

FROM: Matthew Stuckey, Branch Chief  
Permits Branch  
Office of Air Quality

## Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days from the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures  
FNPER-AM.dot12/3/07



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

Mr. Larry York  
Supreme Corporation  
2572 East Kercher Road  
Goshen, IN 46528

May 22, 2009

Re: 039-27944-00103  
First Administrative Amendment to  
Part 70 No.: T039-21505-00103

Dear Mr. York:

Supreme Corporation was issued a Part 70 Operating Permit on March 11, 2008 for a stationary truck and bus painting and parts manufacturing facility. A letter requesting the installation of filter banks in spray area A-2 was received on March 18, 2009. It has been determined there is no increase in the PTE of spray area A-2, and the necessary compliance determination and monitoring requirements are already specified in the permit. Pursuant to the provisions of 2-7-11, the permit is hereby administratively amended as follows (deletions are marked with a ~~strikeout~~ and the new information is in **bold**):

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary truck and bus painting and parts manufacturing facility.

Source Address:	2572 East Kercher Road, Goshen, IN 46528
Mailing Address:	<del>P. O. Box 463, Goshen, IN 46526</del> <b>2572 East Kercher Road, Goshen, IN 46528</b>
General Source Phone Number:	574-642-4888
SIC Code:	3713, 3089
County Location:	Elkhart
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Part 70 Operating Permit Program Minor Source, under PSD Rules Major Source, <b>under</b> Section 112 of the Clean Air Act Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

...

- (t) A spray undercoating area, identified as A-2, constructed in June 1991 **and approved in 2009 for modification**, with a maximum capacity of 12 metal units/day, ~~with no emission control, and exhausting within the building equipped with dry filter banks for PM control, and exhausting to stack SV-A-2;~~

...

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description [326 IAC 2-7-5(15)]:

- ...
- (t) A spray undercoating area, identified as A-2, constructed in June 1991 and approved in 2009 for modification, with a maximum capacity of 12 metal units/day, ~~with no emission control, and exhausting within the building~~ equipped with dry filter banks for PM control, and exhausting to stack SV-A-2;
- ...

Also, several of IDEM's branches and sections have been renamed. Therefore, IDEM has updated the addresses listed in the permit. References to "Permit Administration and Development Section" and the "Permits Branch" have been changed to "Permit Administration and Support Section". References to "Asbestos Section", "Compliance Data Section", "Air Compliance Section", and "Compliance Branch" have been changed to "Compliance and Enforcement Branch". The permit has been revised as follows:

Indiana Department of Environmental Management  
**Permit Administration and Support Section**, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

Indiana Department of Environmental Management  
**Compliance and Enforcement Branch**, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

Finally, all occurrences of the Compliance Data Branch telephone and facsimile numbers have been revised to 317-233-5674 **0178** and 317-233-5967 **6865**, respectively.

All other conditions of the permit shall remain unchanged and in effect. Please find attached the entire Part 70 Operating Permit as modified.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact John Haney, at (800) 451-6027, and ask for John Haney or extension 4-5328, or dial (317) 234-5328.

Sincerely,



Donald F. Robin, P.E., Section Chief  
Permits Branch  
Office of Air Quality

Attachments

DFR/jeh

cc: File - Elkhart County  
U.S. EPA, Region V  
Elkhart County Health Department  
Northern Regional Office  
Compliance and Enforcement Branch



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

## PART 70 OPERATING PERMIT RENEWAL OFFICE OF AIR QUALITY

**Supreme Corporation  
2572 East Kercher Road  
Goshen, IN 46528**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T039-21505-00103	
Issued by: Original Signed By:  Chrystal Wagner, Section Chief Permits Branch Office of Air Quality	Issuance Date: March 11, 2008  Expiration Date: March 11, 2013

First Administrative Amendment No.: 039-27944-00103	
Issued By:  Donald F. Robin, P.E., Section Chief Permits Branch Office of Air Quality	Issuance Date: May 22, 2009  Expiration Date: March 11, 2013

## TABLE OF CONTENTS

### A. SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]  
[326 IAC 2-7-5(15)]
- A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]  
[326 IAC 2-7-5(15)]
- A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

### B. GENERAL CONDITIONS

- B.1 Definitions [326 IAC 2-7-1]
- B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]
- B.3 Term of Conditions [326 IAC 2-1.1-9.5]
- B.4 Enforceability [326 IAC 2-7-7]
- B.5 Severability [326 IAC 2-7-5(5)]
- B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]
- B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]
- B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]  
[326 IAC 1-6-3]
- B.11 Emergency Provisions [326 IAC 2-7-16]
- B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]
- B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]
- B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
- B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
- B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination  
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]
- B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]
- B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12] [40 CFR 72]
- B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]  
[326 IAC 2-7-12(b)(2)]
- B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]
- B.21 Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2-2-2]
- B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]
- B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]
- B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)] [326 IAC 2-1.1-7]
- B.25 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 FR 8314] [326 IAC 1-1-6]

### C. SOURCE OPERATION CONDITIONS

#### Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates  
Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Stack Height [326 IAC 1-7]
- C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

#### Testing Requirements [326 IAC 2-7-6(1)]

- C.8 Performance Testing [326 IAC 3-6]

**Compliance Requirements [326 IAC 2-1.1-11]**

- C.9 Compliance Requirements [326 IAC 2-1.1-11]

**Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

- C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.12 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

- C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
- C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

**Stratospheric Ozone Protection**

- C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

**D.1. EMISSIONS UNIT OPERATION CONDITIONS - Surface Coating**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.1.1 PSD Minor Limit [326 IAC 2-2]
- D.1.2 Particulate Matter (PM) [326 IAC 6-3-2]
- D.1.3 Best Available Control Technology (BACT) [326 IAC 8-1-6]
- D.1.4 Miscellaneous Metal Coating [326 IAC 8-2-9]
- D.1.5 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]
- D.1.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.1.7 Volatile Organic Compounds (VOC)
- D.1.8 Particulate Matter (PM)

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

- D.1.9 Monitoring

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- D.1.10 Record Keeping Requirements
- D.1.11 Reporting Requirements

**D.2. EMISSIONS UNIT OPERATION CONDITIONS - FRP Units**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.2.1 PSD Minor Limit [326 IAC 2-2]
- D.2.2 Particulate Matter (PM) [326 IAC 6-3-2]
- D.2.3 Best Available Control Technology (BACT) [326 IAC 8-1-6]
- D.2.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]
- D.2.5 Operator Training [326 IAC 20-56-2]

**Compliance Determination Requirements**

- D.2.6 Volatile Organic Compounds (VOC)
- D.2.7 Particulate Matter (PM)
- D.2.8 Volatile Organic Compounds (VOC)

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.2.9 Monitoring

**Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.2.10 Record Keeping Requirements

D.2.11 Reporting Requirements

**D.3. EMISSIONS UNIT OPERATION CONDITIONS - Insignificant Activities**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.3.1 Particulate Matter (PM) [326 IAC 6-3-2]

D.3.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

D.3.3 Particulate Matter (PM)

**E.1. NESHAP Subpart M MMM Requirements**

**National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

E.1.1 General Provisions Relating to NESHAP M MMM [40 CFR Part 63, Subpart A] [326 IAC 20-1]

E.1.2 NESHAP Subpart M MMM Requirements [40 CFR Part 63, Subpart M MMM] [326 IAC 20-80]

E.1.3 One Time Deadlines Relating to NESHAP M MMM [40 CFR Part 63, Subpart M MMM] [326 IAC 20-80]

**E.2. NESHAP Subpart P PPP Requirements**

**National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

E.2.1 General Provisions Relating to NESHAP P PPP [40 CFR Part 63, Subpart A] [326 IAC 20-1]

E.2.2 NESHAP Subpart P PPP Requirements [40 CFR Part 63, Subpart P PPP] [326 IAC 20-81]

E.2.3 One Time Deadlines Relating to NESHAP P PPP [40 CFR Part 63, Subpart P PPP] [326 IAC 20-81]

**E.3. NESHAP Subpart W WWW Requirements**

**National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

E.3.1 General Provisions Relating to NESHAP W WWW [40 CFR Part 63, Subpart A] [326 IAC 20-1]

E.3.2 NESHAP Subpart W WWW Requirements [40 CFR Part 63, Subpart W WWW] [326 IAC 20-56]

E.3.3 One Time Deadlines Relating to NESHAP W WWW [40 CFR Part 63, Subpart W WWW] [326 IAC 20-56]

Certification

Emergency Occurrence Report

Part 70 Quarterly Report

Quarterly Deviation and Compliance Monitoring Report

## SECTION A

## SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in Conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

---

The Permittee owns and operates a stationary truck and bus painting and parts manufacturing facility.

Source Address:	2572 East Kercher Road, Goshen, IN 46528
Mailing Address:	2572 East Kercher Road, Goshen, IN 46528
General Source Phone Number:	574-642-4888
SIC Code:	3713, 3089
County Location:	Elkhart
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Part 70 Operating Permit Program Minor Source, under PSD Rules Major Source, under Section 112 of the Clean Air Act Not 1 of 28 Source Categories

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) A spray/bake booth, identified as H-1, constructed June 1991, which may coat metal or fiberglass reinforced plastic (FRP) surfaces, with a maximum production capacity of 1.66 units per hour, equipped with a dry filter for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stack SV-H-1;
- (b) A bake booth, identified as H-4, constructed November 4, 1999, which serves as an additional bake booth for sprayed parts from spray/bake booth H-1, with a rated heat input of 1.2 MMBtu per hour, with no controls, and exhausting to stack SV-H-4;
- (c) Two spray/bake booths, identified as H-2 and H-3, constructed May 28, 1997, which may coat metal or FRP surfaces, each with a maximum production capacity of 0.375 units per hour, each equipped with dry filters for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stacks SV-H-2 and SV-H-3;
- (d) An HVLP paint area, identified as A-1, constructed in June 1991, with a maximum production capacity of 3.1 metal truck rear-end parts per hour, equipped with dry filters for PM control, and exhausting to stack SV-A-1;
- (e) A base coat booth, identified as I-1, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units/hour, equipped with a dry filter for PM overspray control, and exhausting to stack SV-I-1;
- (f) A spray/bake booth, identified as I-2, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units per hour, and a maximum heat input capacity of 1.0 MMBtu per hour, equipped with a down draft dry filter system for PM overspray control, and exhausting through stack SV-I-2;

- (g) Two HVLP spray paint areas, identified as 1-1 and 1-2, constructed July 25, 1991, each with a maximum production capacity of 1.33 metal rear parts/hour, each equipped with a dry filter for PM control, and exhausting through stacks SV-1-1 and SV-1-2;
- (h) An undercoating air assisted spray booth, identified as 1-4, constructed July 25, 1991, with a maximum production capacity of 1.33 metal frames per hour, equipped with a dry filter for PM control, and exhausting through stack SV-1-4;
- (i) A spray paint booth, identified as P-6, constructed July 25, 1991, with a maximum capacity of 0.88 metal or FRP units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-6;
- (j) A spray paint area, identified as P-7, constructed July 25, 1991, with a maximum capacity of 16.66 metal parts/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-7;
- (k) A surface touch-up spray facility, identified as GM-2, constructed in 1987, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;
- (l) A spray booth identified as 1-3, constructed in January 1991, with a maximum production capacity of 14 metal units/day, equipped with a dry filter for PM control, and exhausting through stack SV-1-3;
- (m) A spray area, identified as 1-6, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, equipped with no controls, and exhausting within the building;
- (n) A spray area, identified as 1-7, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;
- (o) A portable undercoating station, identified as 1-8, constructed in January 1991, with a maximum production capacity of 14 metal units/day, with no controls, and exhausting within the building;
- (p) An undercoat air assisted spray booth, identified as 5-10, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with dry filters for PM control, and exhausting through stack SV-5-10;
- (q) An undercoat air assisted spray booth, identified as 5-12, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-5-12;
- (r) A spray booth, identified as 5-13, constructed in August 1985, with a maximum production capacity of 5 metal units/day, equipped with dry filter banks for PM control, and exhausting through stack SV-5-13;
- (s) A spray paint area, identified as N-2, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with dry filter banks for PM control, and exhausting to stack SV-N-2;
- (t) A spray undercoating area, identified as A-2, constructed in June 1991 and approved in 2009 for modification, with a maximum capacity of 12 metal units/day, equipped with dry filter banks for PM control, and exhausting to stack SV-A-2;

- (u) An air assisted undercoating booth, identified as N-1, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with a dry filter for PM control, and exhausting to stack SV-N-1;
- (v) A glue lamination air assisted spray facility, identified as 2-15, constructed July 25, 1991, with a maximum production capacity of 0.687 units per hour, equipped with no controls and exhausting within the building;
- (w) Four Safety Kleen gun cleaners, each equipped with remote solvent reservoirs, identified as SC-1, SC-2, SC-3, and SC-4, each using a maximum of 5 gallons of solvent per week, with no controls, and exhausting within the building;
- (x) Clean-up solvent processes for the source, with a maximum total usage of 6.5 gal of solvent per hour;
- (y) A plastic pultrusion machine, identified as M-1, constructed in February 1991, with a maximum capacity of 3.33 parts/hour, equipped with no controls, and exhausting within the building has been relocated to the P-Building;
- (z) A reciprocator, performing gel coating operation using FIT System and resin flow coating lamination, identified as M-2, constructed in February 1991, with a maximum production of 4.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M-2;
- (aa) A new portable MAS/FIT system for gel application, a reciprocator, performing resin lamination using a new automatic Chop FIT System, identified as M-4, constructed in February 1991, with a maximum production of 0.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M;
- (bb) A portable gelcoat FIT System, identified as M-3, constructed in February 1991, with a maximum production of 4.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M-3;
- (cc) One (1) small vehicle roof resin/gelcoat booth to be located in the old pultrusion area of the M-building to isolate the Flat Panel area from the Contoured Parts area, in order that fibers from the Flat Panel Area will not contaminate parts being made at the Contoured Parts area, utilizing existing gelcoat FIT System M-3 and existing Chop System M-6, with emissions from the booth exhausting through existing Stack SV-M-1;
- (dd) Two portable gelcoat operations, identified as M-5 and M-9 constructed in February 1991, both guns have been upgraded to a Portable FIT System, each with a maximum production of 0.67 parts/hour, each equipped with a dry filter bank for PM control, and exhausting through stacks SV-M-5 and SV-M-9. M-5 is now located in the Flat Panel area, and M-9 is located in the Tru-Green area;
- (ee) Three portable chop/resin guns, identified as M-6, M-7, and M-8. M-6 gun has been upgraded with a portable Chop FIT System, for the application of chop resin wet out, and an atomized gun for the application of spraycore reinforcement. M-7 and M-8 have been replaced with Chop FIT Wall Mount System. All have been constructed in February 1991, each with a maximum production of 0.67 parts/hour, each equipped with a dry filter bank for PM control, and exhausting through stack SV-M-6, SV-M-7, and SV-M-8;
- (ff) A FRP mold department, identified as B-1, constructed in August 1980, with a maximum capacity of 0.004 molds /hour, with no emission control, and exhausting to stack SV-B-1;

- (gg) A white resin air assisted spray gun, identified as B-2(a), constructed in August 1990, with a maximum capacity of 0.004 molds/hour, equipped with a dry filter for PM control, and exhausting to stack SV-B-2;
- (hh) A Tru-green mold repair spray gun, identified as B-2(b), constructed in August 1990, with a maximum capacity of 1.33 parts/hour, equipped with a dry filter for PM control, and exhausting to stack SV-B-2. Existing Venus portable airless/air-assisted spray system will be changed into a portable cup gun granite spray system;
- (ii) Two repair/touch-up FRP facilities, identified as N-3(a) and N-3(b), constructed in August 1987, each with a maximum capacity of 0.888 parts/hour, with no emission control, and exhausting within the building;
- (jj) Several fiberglass touch-up areas which operate as part of FRP production lines, using Binks 115 guns with no emission controls and exhausting within the buildings;
- (kk) Two bulk resin tanks, identified as M-13(a) and M-13(b), constructed prior to 1981, each with a maximum capacity of 40,000 gallons, with no emission control and exhausting through safety valves;
- (ll) A fiberglass reinforced plastic (FRP) cutting facility, identified as 7-1, constructed November 1990, with a maximum production of 0.65 lb. of grinding dust/hour, equipped with a cyclone for dust collection, and exhausting through stack SV-7-1;
- (mm) Grinder/buffer facilities, identified as M-10, constructed in February 1991, with a maximum capacity of 12 units/hour, equipped with dry filters for control and exhausting through stack SV-M-10;
- (nn) A woodworking facility, identified as N-4, constructed prior to 1987, with a maximum production capacity of 18.54 lb raw material/hour, equipped with a cyclone for dust collection, and exhausting through stack SV-N4;
- (oo) A woodworking facility, identified as 5-14, constructed July 25, 1991, with a maximum production capacity of 18.54 lb of raw product/hour equipped with a cyclone for sawdust collection, and exhausting through stack SV-5-14;
- (pp) A woodworking facility, identified as 1-9, constructed July 25, 1991, with a maximum capacity of 18.54 lb of raw product/hour, equipped with a cyclone for sawdust collection, and exhausting through stack SV-1-9;
- (qq) A woodworking facility, identified as Fleet Woodworking, consisting of a horizontal table saw, a cut-off saw, a radial arm saw, and a band saw, constructed July 1991, with a maximum production capacity of 504 boards per day, with a small drum cyclone/baghouse within the building for sawdust collecting, and exhausting within the building;
- (rr) Two waste wood furnaces, each with a wood storage silo, identified as 1-5 and M-12, constructed March 16, 1994, each of which have a maximum heat input capacity of 2.0 MMBtu per hour, and exhausting to stacks SV-1-5 and SV-M-12; and
- (ss) Two parts washers, each equipped with remote solvent reservoirs, identified as PW-1 and PW-2, each using a maximum of 5 gallons of solvent per week, with no controls, and exhausting within the building.

Under NESHAP MMMM H-1, H-4, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2 and N-1 are considered existing affected sources.

Under NESHAP PPPP H-1, H-4, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2 and N-1 are considered existing affected sources.

Under NESHAP WWWW M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115, M-13(a), M-13(b) are considered existing affected sources.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]  
[326 IAC 2-7-5(15)]

---

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, and welding equipment, including: [326 IAC 6-3-2]
  - (1) Three stick welding stations, identified as Stick Fleet Welding, with a maximum production capacity of 6 pounds of welding stick per hour, with no controls, and exhausting within the building;
  - (2) A four-torch oxyacetylene plasma cutting tool, identified as Fleet Torch, which has a cutting rate of 20 inches per minute, with no controls, and exhausting within the building; and
  - (3) Metal Inert Gas (MIG) welding stations, identified as MIG Welding, with a combined maximum production rate of 1080 pounds of welding wire per hour, with no controls and exhausting within the building.
- (b) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations. [326 IAC 6-3-2]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

---

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

## **SECTION B GENERAL CONDITIONS**

### **B.1 Definitions [326 IAC 2-7-1]**

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

### **B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]**

(a) This permit, T039-21505-00103, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.

(b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

### **B.3 Term of Conditions [326 IAC 2-1.1-9.5]**

---

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

(a) The condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or

(b) The emission unit to which the condition pertains permanently ceases operation.

### **B.4 Enforceability [326 IAC 2-7-7]**

---

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

### **B.5 Severability [326 IAC 2-7-5(5)]**

---

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### **B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]**

---

This permit does not convey any property rights of any sort or any exclusive privilege.

### **B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]**

---

(a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.

(b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by the "responsible official" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) The "responsible official" is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than April 15 of each year to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
  - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
  - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]  
[326 IAC 1-6-3]

---

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality,  
Compliance Section), or  
Telephone Number: 317-233-0178 (ask for Compliance Section)  
Facsimile Number: 317-233-6865

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
  - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
  - (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
  - (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
  - (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
  - (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
- (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
  - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
  - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
  - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

**B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]**

---

- (a) All terms and conditions of permits established prior to T169-23696-00001 and issued pursuant to permitting programs approved into the state implementation plan have been either:
- (1) incorporated as originally stated,
  - (2) revised under 326 IAC 2-7-10.5, or
  - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit.

**B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]**

---

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

**B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]**

---

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

**B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]**

---

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
- (1) That this permit contains a material mistake.

- (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
- (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permit Administration and Support Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
  - (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
  - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12] [40 CFR 72]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permit Administration and Support Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]  
[326 IAC 2-7-12(b)(2)]

---

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

---

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b),(c), or (e) without a prior permit revision, if each of the following conditions is met:
- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
  - (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
  - (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
  - (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permit Administration and Support Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b),(c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
  - (1) A brief description of the change within the source;
  - (2) The date on which the change will occur;
  - (3) Any change in emissions; and
  - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]  
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

**B.21 Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2-2-2]**

---

- (a) A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.
- (b) Any modification at an existing major source is governed by the requirements of 326 IAC 2-2-2.

B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permit Administration and Support Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)] [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.

- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

## SECTION C

## SOURCE OPERATION CONDITIONS

Entire Source

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.6 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:
    - (A) Asbestos removal or demolition start date;
    - (B) Removal or demolition contractor; or
    - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**  
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Accredited Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

## Testing Requirements [326 IAC 2-7-6(1)]

### C.8 Performance Testing [326 IAC 3-6]

---

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

## Compliance Requirements [326 IAC 2-1.1-11]

### C.9 Compliance Requirements [326 IAC 2-1.1-11]

---

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.

## Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

### C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

---

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

**C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

---

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

**C.12 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

---

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

**C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

---

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on January 8, 2003.
- (b) Upon direct notification by IDEM, OAQ that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level.  
[326 IAC 1-5-3]

**C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]**

---

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

**C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]**

---

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
  - (1) initial inspection and evaluation;

- (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
  - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
- (1) monitoring results;
  - (2) review of operation and maintenance procedures and records; and/or
  - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
- (1) monitoring data;
  - (2) monitor performance data, if applicable; and
  - (3) corrective actions taken.

**C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]**

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

**C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]**

- (a) In accordance with the compliance schedule specified in 326 IAC 2-6-3(b)(1), starting in 2007 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:

- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
- (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management  
Technical Support and Modeling Section, Office of Air Quality  
100 North Senate Avenue  
MC 61-50 IGCN 1003  
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]

---

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.
- (c) If there is a "project" (as defined in 326 IAC 2-2-1 (qq)) at an existing emissions unit or an emission unit at a source with Plantwide Applicability Limitation (PAL), which is not part of a "major modification" (as defined in 326 IAC 2-2-1 (ee)) and the Permittee elects to utilize the "projected actual emissions" (as defined in 326 IAC 2-2-1 (rr) and/or IAC 2-3-1 (mm)), the Permittee shall comply with following:
  - (1) Before beginning actual construction of the "project" (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1 (ll)) at an existing emissions unit, document and maintain the following records:
    - (A) A description of the project.
    - (B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.
    - (C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:
      - (i) Baseline actual emissions;
      - (ii) Projected actual emissions;

- (iii) Amount of emissions excluded under section 326 IAC 2-2-1(rr)(2)(A)(iii) and/or 326 IAC 2-3-1 (mm)(2)(A)(iii); and
  - (iv) An explanation for why the amount was excluded, and any netting calculations, if applicable.
- (2) Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and
  - (3) Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR pollutant at the emissions unit.

C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

---

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.
- (f) If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any "project" (as defined in 326 IAC 2-2-1 (qq)) at an existing emissions unit, and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:

- (1) The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as defined in 326 IAC 2-2-1 (xx), for that regulated NSR pollutant, and
  - (2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).
- (g) The report for project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:
- (1) The name, address, and telephone number of the major stationary source.
  - (2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.
  - (3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-2-2(d)(3).
  - (4) Any other information that the Permittee deems fit to include in this report,

Reports required in this part shall be submitted to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.

### **Stratospheric Ozone Protection**

#### **C.20 Compliance with 40 CFR 82 and 326 IAC 22-1**

---

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

**SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS**

**Emissions Unit Description**

- (a) A spray/bake booth, identified as H-1, constructed June 1991, which may coat metal or fiberglass reinforced plastic (FRP) surfaces, with a maximum production capacity of 1.66 units per hour, equipped with a dry filter for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stack SV-H-1;
- (b) A bake booth, identified as H-4, constructed November 4, 1999, which serves as an additional bake booth for sprayed parts from spray/bake booth H-1, with a rated heat input of 1.2 MMBtu per hour, with no controls, and exhausting to stack SV-H-4;
- (c) Two spray/bake booths, identified as H-2 and H-3, constructed May 28, 1997, which may coat metal or FRP surfaces, each with a maximum production capacity of 0.375 units per hour, each equipped with dry filters for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stacks SV-H-2 and SV-H-3;
- (d) An HVLP paint area, identified as A-1, constructed in June 1991, with a maximum production capacity of 3.1 metal truck rear-end parts per hour, equipped with dry filters for PM control, and exhausting to stack SV-A-1;
- (e) A base coat booth, identified as I-1, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units/hour, equipped with a dry filter for PM overspray control, and exhausting to stack SV-I-1;
- (f) A spray/bake booth, identified as I-2, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units per hour, and a maximum heat input capacity of 1.0 MMBtu per hour, equipped with a down draft dry filter system for PM overspray control, and exhausting through stack SV-I-2;
- (g) Two HVLP spray paint areas, identified as 1-1 and 1-2, constructed July 25, 1991, each with a maximum production capacity of 1.33 metal rear parts/hour, each equipped with a dry filter for PM control, and exhausting through stacks SV-1-1 and SV-1-2;
- (h) An undercoating air assisted spray booth, identified as 1-4, constructed July 25, 1991, with a maximum production capacity of 1.33 metal frames per hour, equipped with a dry filter for PM control, and exhausting through stack SV-1-4;
- (i) A spray paint booth, identified as P-6, constructed July 25, 1991, with a maximum capacity of 0.88 metal or FRP units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-6;
- (j) A spray paint area, identified as P-7, constructed July 25, 1991, with a maximum capacity of 16.66 metal parts/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-7;
- (k) A surface touch-up spray facility, identified as GM-2, constructed in 1987, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;
- (l) A spray booth identified as 1-3, constructed in January 1991, with a maximum production capacity of 14 metal units/day, equipped with a dry filter for PM control, and exhausting through stack SV-1-3;

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

**SECTION D.1**

**CONTINUED**

**Emissions Unit Description [326 IAC 2-7-5(15)]:**

- (m) A spray area, identified as 1-6, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, equipped with no controls, and exhausting within the building;
- (n) A spray area, identified as 1-7, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;
- (o) A portable undercoating station, identified as 1-8, constructed in January 1991, with a maximum production capacity of 14 metal units/day, with no controls, and exhausting within the building;
- (p) An undercoat air assisted spray booth, identified as 5-10, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with dry filters for PM control, and exhausting through stack SV-5-10;
- (q) An undercoat air assisted spray booth, identified as 5-12, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-5-12;
- (r) A spray booth, identified as 5-13, constructed in August 1985, with a maximum production capacity of 5 metal units/day, equipped with dry filter banks for PM control, and exhausting through stack SV-5-13;
- (s) A spray paint area, identified as N-2, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with dry filter banks for PM control, and exhausting to stack SV-N-2;
- (t) A spray undercoating area, identified as A-2, constructed in June 1991 and approved in 2009 for modification, with a maximum capacity of 12 metal units/day, equipped with dry filter banks for PM control, and exhausting to stack SV-A-2;
- (u) An air assisted undercoating booth, identified as N-1, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with a dry filter for PM control, and exhausting to stack SV-N-1;
- (v) A glue lamination air assisted spray facility, identified as 2-15, constructed July 25, 1991, with a maximum production capacity of 0.687 units per hour, equipped with no controls and exhausting within the building;
- (w) Four Safety Kleen gun cleaners, each equipped with remote solvent reservoirs, identified as SC-1, SC-2, SC-3, and SC-4, each using a maximum of 5 gallons of solvent per week, with no controls, and exhausting within the building;
- (x) Clean-up solvent processes for the source, with a maximum total usage of 6.5 gal of solvent per hour;
- (ss) Two parts washers, each equipped with remote solvent reservoirs, identified as PW-1 and PW-2, each using a maximum of 5 gallons of solvent per week, with no controls, and exhausting within the building.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

## Emission Limitations and Standards [326 IAC 2-7-5(1)]

### D.1.1 PSD Minor Limit [326 IAC 2-2]

---

- (a) VOC usage from surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, cleaners SC-1, SC-2, SC-3, SC-4, PW-1, PW-2, and clean-up solvents, combined with VOC emissions from units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b) as listed in Section D.2 shall be no more than 240 tons of VOC per twelve (12) consecutive month period, with compliance determined at the end of each month. This limit will limit the sourcewide potential to emit VOC to less than 250 tons per 12 consecutive month period. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.
- (b) PM emissions from surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, combined with PM emissions from units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b), shall be no more than 250 tons of PM per twelve (12) consecutive month period, with compliance determined at the end of each month. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.
- (c) PM10 emissions from surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, combined with PM10 emissions from units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b), shall be no more than 250 tons of PM10 per twelve (12) consecutive month period, with compliance determined at the end of each month. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.
- (d) The PM and PM10 transfer efficiency of the surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, cleaners SC-1, SC-2, SC-3, SC-4, PW-1, PW-2, and clean-up solvents shall not be less than 70%; and
- (e) The PM and PM10 control efficiency of the dry filters shall not be less than 85%.

### D.1.2 Particulate Matter (PM) [326 IAC 6-3-2(d)]

---

Pursuant to 326 IAC 6-3-2(d), particulate from the surface coating spray units shall be controlled by a dry particulate filter and the Permittee shall operate the control device in accordance with manufacturer's specifications.

### D.1.3 Best Available Control Technology (BACT) [326 IAC 8-1-6]

---

- (a) Pursuant to CP-039-7321-00103, issued May 28, 1997, BACT for spray/bake booths H-1, H-2, and H-3, when coating FRP substrates, shall be a combination of the use of high volume low pressure (HVLP) spray equipment and limits on the VOC content of 6.5 pounds of VOC per gallon of coating less water for basecoats and 5.1 pounds of VOC per gallon of coating less water for clearcoats. An exception to these VOC content limitations will be made for government work which requires the use of special coatings.
- (b) Pursuant to CP-039-3362-00103, issued January 6, 1995, BACT for booths I-1 and I-2, when coating FRP substrates, shall be a combination of the use of high volume low pressure (HVLP) spray equipment and limits on the VOC content of 6.5 pounds of VOC per gallon of coating less water for basecoats and 5.1 pounds of VOC per gallon of coating less water for clearcoats.
- (c) Input VOC to H-1, H-2, and H-3, when coating FRP substrates, shall be limited such that sourcewide PTE VOC is less than 240 tons of VOC per 12 consecutive month period.
- (d) Input VOC to I-1 and I-2, when coating FRP substrates, shall be limited such that PTE VOC is less than 80 tons of VOC per 12 consecutive month period.

- (e) Glue lamination spray unit 2-15, constructed after January 1, 1980, has PTE VOC greater than 25 tons/year. However, VOC usage for 2-15 shall be limited to less than 25 tons per 12 consecutive month period. Therefore 326 IAC 8-1-6 does not apply.

#### D.1.4 Miscellaneous Metal Coating [326 IAC 8-2-9]

---

- (a) Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coatings delivered to the applicators at spray booths/areas H-1, H-2, H-3, I-1, I-2, A-1, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, and N-1, when applied to metal surfaces, shall be limited to 4.3 pounds of VOC per gallon of coating less water for clear coatings, and 3.5 pounds of VOC per gallon of coating less water for air dried, forced warm air dried or extreme performance coatings. If more than one emission limitation applies to a specific coating, then the least stringent emission limitation shall be applied.
- (b) Solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

#### D.1.5 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]

---

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations), the owner or operator of Safety Kleen cleaners SC-1, SC-2, SC-3, and SC-4 and parts washers PW-1 and PW-2, shall:

- (a) Equip the cleaners with a cover, or with a closed solvent recycling system which prevents solvent evaporation in much the same way as a cover prevents evaporation;
- (b) Equip the cleaners with a facility for draining cleaned parts;
- (c) Close the degreaser covers, or keep solvent within the closed recycling system, whenever parts are not being handled in the cleaner;
- (d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;
- (e) Provide a permanent, conspicuous label summarizing the operation requirements;
- (f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

#### D.1.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

---

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these units and the associated control devices.

### **Compliance Determination Requirements**

#### D.1.7 Volatile Organic Compounds (VOC)

---

Compliance with the VOC content and usage limitations contained in Conditions D.1.1, D.1.3 and D.1.4 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

#### D.1.8 Particulate Matter (PM)

---

In order to comply with Condition D.1.2, dry filters shall be in operation on all vented units at all times the surface coating units are in operation.

## **Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

### **D.1.9 Monitoring**

---

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit
- (b) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

## **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

### **D.1.10 Record Keeping Requirements**

---

- (a) To document compliance with Conditions D.1.1(a), D.1.3, and D.1.4, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be taken daily or monthly, as indicated below, and shall be complete and sufficient to establish compliance with the VOC usage limits and the VOC emission limits established in Conditions D.1.1(a), D.1.3, and D.1.4.
  - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
  - (2) A log of the dates of use;
  - (3) The volume weighted VOC content of the coatings used for each month;
  - (4) The cleanup solvent usage for each month;
  - (5) The total VOC usage for each month; and
  - (6) The weight of VOCs emitted for each compliance period.
- (b) To document compliance with Condition D.1.9, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

### **D.1.11 Reporting Requirements**

---

A quarterly summary of the information to document compliance with Conditions D.1.1 and D.1.3 (c), (d), and (e), shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee requires the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**SECTION D.2**

**EMISSIONS UNIT OPERATION CONDITIONS**

**Emissions Unit Description [326 IAC 2-7-5(15)]:**

- (y) A plastic pultrusion machine, identified as M-1, constructed in February 1991, with a maximum capacity of 3.33 parts/hour, equipped with no controls, and exhausting within the building has been relocated to the P-Building;
- (z) A reciprocator, performing gel coating operation using FIT System and resin flow coating lamination, identified as M-2, constructed in February 1991, with a maximum production of 4.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M-2;
- (aa) A new portable MAS/FIT system for gel application, a reciprocator, performing resin lamination using a new automatic Chop FIT System, identified as M-4, constructed in February 1991, with a maximum production of 0.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M;
- (bb) A portable gelcoat FIT System, identified as M-3, constructed in February 1991, with a maximum production of 4.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M-3;
- (cc) One (1) small vehicle roof resin/gelcoat booth to be located in the old pultrusion area of the M-building to isolate the Flat Panel area from the Contoured Parts area, in order that fibers from the Flat Panel Area will not contaminate parts being made at the Contoured Parts area, utilizing existing gelcoat FIT System M-3 and existing Chop System M-6, with emissions from the booth exhausting through existing Stack SV-M-1;
- (dd) Two portable gelcoat operations, identified as M-5 and M-9 constructed in February 1991, both guns have been upgraded to a Portable FIT System, each with a maximum production of 0.67 parts/hour, each equipped with a dry filter bank for PM control, and exhausting through stacks SV-M-5 and SV-M-9. M-5 is now located in the Flat Panel area, and M-9 is located in the Tru-Green area;
- (ee) Three portable chop/resin guns, identified as M-6, M-7, and M-8. M-6 gun has been upgraded with a portable Chop FIT System, for the application of chop resin wet out, and an atomized gun for the application of spraycore reinforcement. M-7 and M-8 have been replaced with Chop FIT Wall Mount System. All have been constructed in February 1991, each with a maximum production of 0.67 parts/hour, each equipped with a dry filter bank for PM control, and exhausting through stack SV-M-6, SV-M-7, and SV-M-8;
- (ff) A FRP mold department, identified as B-1, constructed in August 1980, with a maximum capacity of 0.004 molds /hour, with no emission control, and exhausting to stack SV-B-1;
- (gg) A white resin air assisted spray gun, identified as B-2(a), constructed in August 1990, with a maximum capacity of 0.004 molds/hour, equipped with a dry filter for PM control, and exhausting to stack SV-B-2;
- (hh) A Tru-green mold repair spray gun, identified as B-2(b), constructed in August 1990, with a maximum capacity of 1.33 parts/hour, equipped with a dry filter for PM control, and exhausting to stack SV-B-2. Existing Venus portable airless/air-assisted spray system will be changed into a portable cup gun granite spray system;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

## SECTION D.2 CONTINUED

### Emissions Unit Description [326 IAC 2-7-5(15)]:

- (ii) Two repair/touch-up FRP facilities, identified as N-3(a) and N-3(b), constructed in August 1987, each with a maximum capacity of 0.888 parts/hour, with no emission control, and exhausting within the building;
- (jj) Several fiberglass touch-up areas which operate as part of FRP production lines, using Binks 115 guns with no emission controls and exhausting within the buildings;
- (kk) Two bulk resin tanks, identified as M-13(a) and M-13(b), constructed prior to 1981, each with a maximum capacity of 40,000 gallons, with no emission control and exhausting through safety valves;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.2.1 PSD Minor Limit [326 IAC 2-2]

- (a) VOC emissions from FRP units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b), combined with VOC usage from surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, cleaners SC-1, SC-2, SC-3, SC-4, and clean-up solvents as described in Section D.1 shall be no more than 240 tons of VOC per twelve (12) consecutive month period, with compliance determined at the end of each month. This limit will limit the sourcewide potential to emit VOC to less than 250 tons per 12 consecutive month period. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.
- (b) PM emissions from FRP units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b) combined with VOC usage from surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, shall be no more than 250 tons of PM per twelve (12) consecutive month period, with compliance determined at the end of each month. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.
- (c) PM10 emissions from FRP units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b) combined with PM10 usage from surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, shall be no more than 250 tons of PM10 per twelve (12) consecutive month period, with compliance determined at the end of each month. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.
- (d) The PM and PM10 transfer efficiency of the FRP units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b) shall not be less than 70%; and
- (e) The PM and PM10 control efficiency of the dry filters shall not be less than 85%.

#### D.2.2 Particulate Matter (PM) [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(d), particulate from the FRP production spray units shall be controlled by a dry particulate filter and the Permittee shall operate the control device in accordance with manufacturer's specifications.

**D.2.3 Best Available Control Technology (BACT) [326 IAC 8-1-6]**

Pursuant to Part 70 Permit 039-6046-00103, issued on April 19, 2001 and 326 IAC 8-1-6, BACT for FRP production units M-1, M-2, M-3, M-4, M-5, M-6, M-7, M-8, M-9, B-1, B-2(a), B-2(b) N-3(a), N-3(b) and Binks115 touch up areas, shall be the following:

- (a) The use of styrene-containing resins and gel coats shall be limited such that the potential to emit (PTE) VOC from the FRP units shall be less than 240 tons per twelve (12) consecutive month period.
- (b) The HAP monomer content of resins and gel coats used shall be limited to the following or their equivalent on an emissions mass basis:

Type of Gel Coat or Resin	HAP Monomer Content, % by weight
Production <sup>1</sup> Gel Coat	37
Tooling <sup>2</sup> Gel Coat	38
Production Resin	35
Tooling Resin	43

<sup>1</sup> Production refers to the manufacture of parts.

<sup>2</sup> Tooling refers to the manufacture of the molds from which parts are manufactured.

HAP monomer contents shall be calculated on a neat basis, which means excluding any filler. Compliance with these HAP monomer content limits shall be demonstrated on a monthly basis.

Gel coats or resins with HAP monomer contents lower than those specified in the table in this subsection or additional emission reduction techniques approved by IDEM, OAQ may be used to offset the use of gel coats or resins with HAP monomer contents higher than those specified in the table in this subsection. This is allowed to meet the HAP monomer content limits for resins and gel coats and shall be calculated on an equivalent emissions mass basis as shown below:

**$EmA < (MR * ERa) + (MG * EGa)$**

Where:

MR = Total monthly mass of resins within each resin category  
 MG = Total monthly mass of gel coats within each gel coats category  
 ERa = Emission factor for each resin based on allowable monomer content and allowable application method for each resin category.  
 EGa = Emission factor for each gel coat based on allowable monomer content for each gel coat category  
 EmA = Actual monthly emissions from all resins and gelcoats based on material specific emission factors, emission reduction techniques and emission controls

*Units: mass = tons  
 emission factor = lbs of monomer per ton of resin or gel coat  
 emissions = lbs of monomer*

- (c) Non-atomized spray application technology shall be used to mechanically apply unfilled production resins. Non-atomized spray application technology includes flow coaters, flow choppers, pressure-fed rollers, or other non-spray mechanical applications of a design and specifications approved by IDEM, OAQ.

If it is not possible to apply a portion of unfilled resins with non-atomized spray application technology, equivalent emissions reductions must be obtained via use of other emission reduction techniques. Examples of other emission reduction techniques include, but are not limited to, lower HAP monomer content resins and gel coats, closed molding, vapor suppression, vacuum bagging/bonding, or installing a control device.

- (d) Optimized spray techniques according to a manner approved by IDEM, OAQ shall be used for gel coats and filled resins (where fillers are required for corrosion or fire retardant purposes) at all times. Optimized spray techniques include, but are not limited to, the use of airless, air-assisted airless, high volume low pressure (HVLP), or other spray applicators demonstrated to the satisfaction of IDEM, OAQ, to be equivalent to the spray applicators listed above.

HVLP spray is defined as the technology used to apply material to substrate by means of application equipment that operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

- (e) A one (1) quart, air atomized spray gun may be used as needed for touch-up purposes only.
- (f) The following work practices shall be implemented:
- (1) To the extent possible, non-VOC, non-HAP solvents shall be used for cleanup.
  - (2) For VOC- and/or HAP-containing materials:
    - (A) Cleanup solvent containers shall be used to transport solvent from drums to work areas.
    - (B) Cleanup stations shall be designed as closed containers having soft gasketed spring-loaded closures and shall be completely closed when not in use.
    - (C) Solvent saturated cleanup rags shall be stored, transported, and discarded in containers that are tightly closed.
    - (D) Spray guns shall be designed to be cleaned without requiring the spraying of solvent into the air.
    - (E) All solvent sprayed during cleanup or resin changes shall be directed into containers. Such containers shall be closed as soon as solvent spraying is complete and the waste solvent shall be discarded in such a manner that evaporation is minimized.
  - (3) Storage containers shall be covered when not in use.

#### D.2.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control devices.

#### D.2.5 Operator Training [326 IAC 20-56-2]

- (a) Each owner or operator shall train all new and existing personnel, including contract personnel, who are involved in resin and gel coat spraying and spray-like applications (for example, those applications that could result in excess emissions if performed improperly) according to the following schedule:
- (1) All personnel hired after the effective date of this rule shall be trained within thirty (30) days of hiring.

- (2) All personnel hired before the effective date of this rule shall be trained or evaluated by a supervisor within thirty (30) days of the effective date of this rule.
  - (3) To ensure training goals listed in subsection (b) are maintained, all personnel shall be given refresher training annually.
  - (4) Personnel who have been trained by another owner or operator subject to this rule are exempt from subdivision (2) if written documentation that the employee's training is current is provided to the new employer.
  - (5) If the result of an evaluation shows that training is needed, such training shall occur within fifteen (15) days of the evaluation.
- (b) The lesson plans shall cover, for the initial and refresher training, at a minimum, all of the following topics:
- (1) Appropriate application techniques.
  - (2) Appropriate equipment cleaning procedures.
  - (3) Appropriate equipment setup and adjustment to minimize material usage and overspray.
- (c) The owner or operator shall maintain the following training records on site and available for inspection and review:
- (1) A copy of the current training program.
  - (2) A list of all current personnel, by name, that are required to be trained and the dates they were trained and the date of the most recent refresher training.
- (d) Records of prior training programs and former personnel are not required to be maintained.

### **Compliance Determination Requirements**

#### **D.2.6 Volatile Organic Compounds (VOC)**

---

Compliance with the VOC content and usage limitations contained in Conditions D.2.3(b) shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

#### **D.2.7 Particulate Matter (PM)**

---

In order to comply with Condition D.2.2, the dry filters shall be in operation at all times the FRP units are in operation.

#### **D.2.8 Volatile Organic Compound (VOC)**

---

Compliance with Condition D.2.3 shall be determined based upon the following criteria:

- (1) VOC emissions from the application of gel coat and resins shall be calculated as volatile organic HAP emissions. Monthly usage by weight, weight percent content of all monomers that are volatile organic HAP, method of application, and other emission reduction techniques for each gel coat and resin shall be recorded. Volatile organic HAP emissions shall be calculated by multiplying the usage of each gel coat and resin by the emission factor that is appropriate for the HAP monomer content, method of application, and other emission reduction techniques for each gel coat and resin, and summing the emissions for all gel coats and resins. Emission factors shall be obtained from the reference approved by IDEM, OAQ.

- (2) The emission factors approved for use by IDEM, OAQ shall be taken from the following reference: "Unified Emission Factors for Open Molding of Composites", Composites Fabricators Associations, July 23, 2001, with the exception of the emission factors for controlled spray application. This reference is included with this permit. For HAP-emitting operations not addressed by this reference, emission factors shall be taken from U.S. EPA's AP-42 document. For the purposes of these emission calculations, HAP monomer in resins and gel coats that is not styrene or methyl methacrylate shall be considered as styrene on an equivalent weight basis.

### **Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

#### **D.2.9 Monitoring [40 CFR 64]**

---

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit
- (b) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

#### **D.2.10 Record Keeping Requirements**

---

- (a) To document compliance with Conditions D.2.1 and D.2.3, the Permittee shall maintain records in accordance with (1) through (4) below for the fiberglass operations. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Conditions D.2.1 and D.2.3.
- (1) The usage by weight and volatile organic HAP monomer content of each resin and gel coat. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used;
- (2) A log of the dates of use;
- (3) Method of application and other emission reduction techniques for each resin and gel coat used;
- (4) The calculated total volatile organic HAP emissions from resin and gel coat use for each month.
- (b) To document compliance with Condition D.2.9, the Permittee shall maintain a log of daily and monthly inspections, and weekly observations.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.2.11 Reporting Requirements

---

A quarterly summary of the information to document compliance with Condition D.2.1 and D.2.3(a) shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee requires the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

### SECTION D.3 EMISSIONS UNIT OPERATION CONDITIONS

#### Emissions Unit Description

- (ll) A fiberglass reinforced plastic (FRP) cutting facility, identified as 7-1, constructed November 1990, with a maximum production of 0.65 lb. of grinding dust/hour, equipped with a cyclone for dust collection, and exhausting through stack SV-7-1;
- (mm) Grinder/buffer facilities, identified as M-10, constructed in February 1991, with a maximum capacity of 12 units/hour, equipped with dry filters for control and exhausting through stack SV-M-10;
- (nn) A woodworking facility, identified as N-4, constructed prior to 1987, with a maximum production capacity of 18.54 lb raw material/hour, equipped with a cyclone for dust collection, and exhausting through stack SV-N4;
- (oo) A woodworking facility, identified as 5-14, constructed July 25, 1991, with a maximum production capacity of 18.54 lb of raw product/hour equipped with a cyclone for sawdust collection, and exhausting through stack SV-5-14;
- (pp) A woodworking facility, identified as 1-9, constructed July 25, 1991, with a maximum capacity of 18.54 lb of raw product/hour, equipped with a cyclone for sawdust collection, and exhausting through stack SV-1-9;
- (qq) A woodworking facility, identified as Fleet Woodworking, consisting of a horizontal table saw, a cut-off saw, a radial arm saw, and a band saw, constructed July 1991, with a maximum production capacity of 504 boards per day, with a small drum cyclone/baghouse within the building for sawdust collecting, and exhausting within the building;

#### Insignificant Activities:

- (a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, and welding equipment, including: (326 IAC 6-3-2)
  - (1) Three stick welding stations, identified as Stick Fleet Welding, with a maximum production capacity of 6 pounds of welding stick per hour, with no controls, and exhausting within the building;
  - (2) A four-torch oxyacetylene plasma cutting tool, identified as Fleet Torch, which has a cutting rate of 20 inches per minute, with no controls, and exhausting within the building; and
  - (3) Metal Inert Gas (MIG) welding stations, identified as MIG Welding, with a combined maximum production rate of 1080 pounds of welding wire per hour, with no controls and exhausting within the building.
- (b) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations. (326 IAC 6-3-2)

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

## **Emission Limitations and Standards [326 IAC 2-7-5(1)]**

### **D.3.1 Particulate Matter (PM) [326 IAC 6-3-2]**

---

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes) the particulate emissions shall be limited by the following:

- (a) The allowable particulate matter emissions from the Fleet Woodworking operations shall each not exceed 0.58 pounds per hour when operating at a maximum production capacity of 110 pounds per hour.
- (b) The allowable particulate matter emissions from the welding operations shall each not exceed 2.72 pounds per hour when operating at a maximum production capacity of 1086 pounds per hour.
- (c) The allowable particulate matter emissions from the remaining FRP-working and woodworking facilities shall not exceed 2.5 pounds per hour when operating at a maximum process weight rate of 954 pounds per hour, or 0.48 tons per hour.

Interpolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

### **D.3.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]**

---

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for the following facilities and their control devices: FRP cutting facility, identified as 7-1, grinder/buffer facilities, identified as M-10, woodworking facilities identified as N-4, 5-14, SV-1-9, Fleet Woodworking, and grinding/machining operations.

## **Compliance Determination Requirements**

### **D.3.3 Particulate Matter (PM) [326 IAC 6-3-2]**

---

In order to comply with Condition D.3.1, the cyclones, filters, and other PM control devices shall be in operation at all times the FRP-working, woodworking, welding and cutting facilities are in operation.

**SECTION E.1**

**FACILITY OPERATION CONDITIONS**

**Emissions Unit Description [326 IAC 2-7-5(15)]:**

- (a) A spray/bake booth, identified as H-1, constructed June 1991, which may coat metal or fiberglass reinforced plastic (FRP) surfaces, with a maximum production capacity of 1.66 units per hour, equipped with a dry filter for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stack SV-H-1;
- (b) A bake booth, identified as H-4, constructed November 4, 1999, which serves as an additional bake booth for sprayed parts from spray/bake booth H-1, with a rated heat input of 1.2 MMBtu per hour, with no controls, and exhausting to stack SV-H-4;
- (c) Two spray/bake booths, identified as H-2 and H-3, constructed May 28, 1997, which may coat metal or FRP surfaces, each with a maximum production capacity of 0.375 units per hour, each equipped with dry filters for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stacks SV-H-2 and SV-H-3;
- (d) An HVLP paint area, identified as A-1, constructed in June 1991, with a maximum production capacity of 3.1 metal truck rear-end parts per hour, equipped with dry filters for PM control, and exhausting to stack SV-A-1;
- (e) A base coat booth, identified as I-1, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units/hour, equipped with a dry filter for PM overspray control, and exhausting to stack SV-I-1;
- (f) A spray/bake booth, identified as I-2, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units per hour, and a maximum heat input capacity of 1.0 MMBtu per hour, equipped with a down draft dry filter system for PM overspray control, and exhausting through stack SV-I-2;
- (g) Two HVLP spray paint areas, identified as 1-1 and 1-2, constructed July 25, 1991, each with a maximum production capacity of 1.33 metal rear parts/hour, each equipped with a dry filter for PM control, and exhausting through stacks SV-1-1 and SV-1-2;
- (h) An undercoating air assisted spray booth, identified as 1-4, constructed July 25, 1991, with a maximum production capacity of 1.33 metal frames per hour, equipped with a dry filter for PM control, and exhausting through stack SV-1-4;
- (i) A spray paint booth, identified as P-6, constructed July 25, 1991, with a maximum capacity of 0.88 metal or FRP units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-6;
- (j) A spray paint area, identified as P-7, constructed July 25, 1991, with a maximum capacity of 16.66 metal parts/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-7;
- (k) A surface touch-up spray facility, identified as GM-2, constructed in 1987, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**SECTION E.1**

**CONTINUED**

**Emissions Unit Description [326 IAC 2-7-5(15)]:**

- (l) A spray booth identified as 1-3, constructed in January 1991, with a maximum production capacity of 14 metal units/day, equipped with a dry filter for PM control, and exhausting through stack SV-1-3;
- (m) A spray area, identified as 1-6, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, equipped with no controls, and exhausting within the building;
- (n) A spray area, identified as 1-7, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;
- (o) A portable undercoating station, identified as 1-8, constructed in January 1991, with a maximum production capacity of 14 metal units/day, with no controls, and exhausting within the building;
- (p) An undercoat air assisted spray booth, identified as 5-10, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with dry filters for PM control, and exhausting through stack SV-5-10;
- (q) An undercoat air assisted spray booth, identified as 5-12, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-5-12;
- (r) A spray booth, identified as 5-13, constructed in August 1985, with a maximum production capacity of 5 metal units/day, equipped with dry filter banks for PM control, and exhausting through stack SV-5-13;
- (s) A spray paint area, identified as N-2, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with dry filter banks for PM control, and exhausting to stack SV-N-2;
- (t) A spray undercoating area, identified as A-2, constructed in June 1991, with a maximum capacity of 12 metal units/day, with no emission control, and exhausting within the building;
- (u) An air assisted undercoating booth, identified as N-1, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with a dry filter for PM control, and exhausting to stack SV-N-1;

Under NESHAP MMMM H-1, H-4, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2 and N-1 are considered existing affected sources.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

**E.1.1 General Provisions Relating to NESHAP MMMM [40 CFR Part 63, Subpart A] [326 IAC 20-1]**

Pursuant to 40 CFR 63.3901, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, as specified in Table 2 of 40 CFR Part 63, Subpart MMMM in accordance with schedule in 40 CFR 63 Subpart MMMM.

## E.1.2 NESHAP Subpart MMMM Requirements [40 CFR Part 63, Subpart MMMM] [326 IAC 20-80]

Pursuant to CFR Part 63, Subpart MMMM, the Permittee shall comply with the provisions of 40 CFR Part 63.3880, as specified as follows:

### What This Subpart Covers

#### § 63.3883 When do I have to comply with this subpart?

The date by which you must comply with this subpart is called the compliance date. The compliance date for each type of affected source is specified in paragraphs (a) through (c) of this section. The compliance date begins the initial compliance period during which you conduct the initial compliance demonstration described in §§63.3940, 63.3950, and 63.3960.

(b) For an existing affected source, the compliance date is the date 3 years after January 2, 2004.

### Emission Limitations

#### § 63.3890 What emission limits must I meet?

(b) For an existing affected source, you must limit organic HAP emissions to the atmosphere from the affected source to the applicable limit specified in paragraphs (b)(1) through (5) of this section, except as specified in paragraph (c) of this section, determined according to the requirements in §63.3941, §63.3951, or §63.3961.

(1) For each existing general use coating affected source, limit organic HAP emissions to no more than 0.31 kg (2.6 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

#### § 63.3891 What are my options for meeting the emission limits?

You must include all coatings (as defined in §63.3981), thinners and/or other additives, and cleaning materials used in the affected source when determining whether the organic HAP emission rate is equal to or less than the applicable emission limit in §63.3890. To make this determination, you must use at least one of the three compliance options listed in paragraphs (a) through (c) of this section. You may apply any of the compliance options to an individual coating operation, or to multiple coating operations as a group, or to the entire affected source. You may use different compliance options for different coating operations, or at different times on the same coating operation. You may employ different compliance options when different coatings are applied to the same part, or when the same coating is applied to different parts. However, you may not use different compliance options at the same time on the same coating operation. If you switch between compliance options for any coating operation or group of coating operations, you must document this switch as required by §63.3930(c), and you must report it in the next semiannual compliance report required in §63.3920.

(a) *Compliant material option.* Demonstrate that the organic HAP content of each coating used in the coating operation(s) is less than or equal to the applicable emission limit in §63.3890, and that each thinner and/or other additive, and cleaning material used contains no organic HAP. You must meet all the requirements of §§63.3940, 63.3941, and 63.3942 to demonstrate compliance with the applicable emission limit using this option.

(b) *Emission rate without add-on controls option.* Demonstrate that, based on the coatings, thinners and/or other additives, and cleaning materials used in the coating operation(s), the organic HAP emission rate for the coating operation(s) is less than or equal to the applicable emission limit in §63.3890, calculated as a rolling 12-month emission rate and determined on a monthly basis. You must meet all the requirements of §§63.3950, 63.3951, and 63.3952 to demonstrate compliance with the emission limit using this option.

**§ 63.3892 What operating limits must I meet?**

(a) For any coating operation(s) on which you use the compliant material option or the emission rate without add-on controls option, you are not required to meet any operating limits.

**§ 63.3893 What work practice standards must I meet?**

(a) For any coating operation(s) on which you use the compliant material option or the emission rate without add-on controls option, you are not required to meet any work practice standards.

**General Compliance Requirements**

**§ 63.3900 What are my general requirements for complying with this subpart?**

(a) You must be in compliance with the emission limitations in this subpart as specified in paragraphs (a)(1) of this section.

(1) Any coating operation(s) for which you use the compliant material option or the emission rate without add-on controls option, as specified in §63.3891(a) and (b), must be in compliance with the applicable emission limit in §63.3890 at all times.

(b) You must always operate and maintain your affected source, including all air pollution control and monitoring equipment you use for purposes of complying with this subpart, according to the provisions in §63.6(e)(1)(i).

**§ 63.3901 What parts of the General Provisions apply to me?**

Table 2 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you.

**Notifications, Reports, and Records**

**§ 63.3910 What notifications must I submit?**

(a) General. You must submit the notifications in §§63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) that apply to you by the dates specified in those sections, except as provided in paragraphs (b) and (c) of this section.

(b) Initial Notification. You must submit the initial notification required by §63.9(b) for a new or reconstructed affected source no later than 120 days after initial startup or 120 days after January 2, 2004, whichever is later. The Permittee submitted the initial notification to IDEM, OAQ on December 31, 2004. If you are using compliance with the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (subpart IIII of this part) as provided for under §63.3881(d) to constitute compliance with this subpart for any or all of your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations. If you are complying with another NESHAP that constitutes the predominant activity at your facility under §63.3881(e)(2) to constitute compliance with this subpart for your metal parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those metal parts coating operations.

(c) Notification of compliance status. You must submit the notification of compliance status required by §63.9(h) no later than 30 calendar days following the end of the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source. The notification of compliance status must contain the information specified in paragraphs (c)(1) through (11) of this section and in §63.9(h).

(1) Company name and address.

- (2) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.
- (3) Date of the report and beginning and ending dates of the reporting period. The reporting period is the initial compliance period described in §§63.3940, 63.3950, or 63.3960 that applies to your affected source.
- (4) Identification of the compliance option or options specified in §63.3891 that you used on each coating operation in the affected source during the initial compliance period.
- (5) Statement of whether or not the affected source achieved the emission limitations for the initial compliance period.
- (6) If you had a deviation, include the information in paragraphs (c)(6)(i) and (ii) of this section.
- (i) A description and statement of the cause of the deviation.
- (ii) If you failed to meet the applicable emission limit in §63.3890, include all the calculations you used to determine the kg (lb) of organic HAP emitted per liter (gal) coating solids used. You do not need to submit information provided by the materials' suppliers or manufacturers, or test reports.
- (7) For each of the data items listed in paragraphs (c)(7)(i) through (iv) of this section that is required by the compliance option(s) you used to demonstrate compliance with the emission limit, include an example of how you determined the value, including calculations and supporting data. Supporting data may include a copy of the information provided by the supplier or manufacturer of the example coating or material, or a summary of the results of testing conducted according to §63.3941(a), (b), or (c). You do not need to submit copies of any test reports.
- (i) Mass fraction of organic HAP for one coating, for one thinner and/or other additive, and for one cleaning material.
- (ii) Volume fraction of coating solids for one coating.
- (iii) Density for one coating, one thinner and/or other additive, and one leaning material, except that if you use the compliant material option, only the example coating density is required.
- (iv) The amount of waste materials and the mass of organic HAP contained in the waste materials for which you are claiming an allowance in Equation 1 of §63.3951.
- (8) The calculation of kg (lb) of organic HAP emitted per liter (gal) coating solids used for the compliance option(s) you used, as specified in paragraphs (c)(8)(i) through (iii) of this section.
- (i) For the compliant material option, provide an example calculation of the organic HAP content for one coating, using Equation 2 of §63.3941.
- (ii) For the emission rate without add-on controls option, provide the calculation of the total mass of organic HAP emissions for each month; the calculation of the total volume of coating solids used each month; and the calculation of the 12-month organic HAP emission rate using Equations 1 and 1A through 1C, 2, and 3, respectively, of §63.3951.

#### **§ 63.3920 What reports must I submit?**

- (a) Semiannual compliance reports. You must submit semiannual compliance reports for each affected source according to the requirements of paragraphs (a)(1) through (7) of this section. The semiannual compliance reporting requirements may be satisfied by reports required under other parts of the Clean Air Act (CAA), as specified in paragraph (a)(2) of this section.

(1) Dates. Unless the Administrator has approved or agreed to a different schedule for submission of reports under §63.10(a), you must prepare and submit each semiannual compliance report according to the dates specified in paragraphs (a)(1)(i) through (iv) of this section. Note that the information reported for each of the months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(i) The first semiannual compliance report must cover the first semiannual reporting period which begins the day after the end of the initial compliance period described in §63.3940, §63.3950, or §63.3960 that applies to your affected source and ends on June 30 or December 31, whichever date is the first date following the end of the initial compliance period.

(ii) Each subsequent semiannual compliance report must cover the subsequent semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(iii) Each semiannual compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(iv) For each affected source that is subject to permitting regulations pursuant to 40 CFR part 70 or 40 CFR part 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), you may submit the first and subsequent compliance reports according to the dates the permitting authority has established instead of according to the date specified in paragraph (a)(1)(iii) of this section.

(2) Inclusion with title V report. Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 40 CFR part 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a semiannual compliance report pursuant to this section along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the semiannual compliance report includes all required information concerning deviations from any emission limitation in this subpart, its submission will be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a semiannual compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permitting authority.

(3) General requirements. The semiannual compliance report must contain the information specified in paragraphs (a)(3)(i) through (vii) of this section, and the information specified in paragraphs (a)(4) through (7) and (c)(1) of this section that is applicable to your affected source.

(i) Company name and address.

(ii) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(iii) Date of report and beginning and ending dates of the reporting period. The reporting period is the 6-month period ending on June 30 or December 31. Note that the information reported for each of the 6 months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(iv) Identification of the compliance option or options specified in §63.3891 that you used on each coating operation during the reporting period. If you switched between compliance options during the reporting period, you must report the beginning and ending dates for each option you used.

(v) If you used the emission rate without add-on controls or the emission rate with add-on controls compliance option (§63.3891(b) or (c)), the calculation results for each rolling 12-month organic HAP emission rate during the 6-month reporting period.

- (vi) If you used the predominant activity alternative (§63.3890(c)(1)), include the annual determination of predominant activity if it was not included in the previous semi-annual compliance report.
- (vii) If you used the facility-specific emission limit alternative (§63.3890(c)(2)), include the calculation of the facility-specific emission limit for each 12-month compliance period during the 6-month reporting period.
- (4) No deviations. If there were no deviations from the emission limitations in §§63.3890, 63.3892, and 63.3893 that apply to you, the semiannual compliance report must include a statement that there were no deviations from the emission limitations during the reporting period. If you used the emission rate with add-on controls option and there were no periods during which the continuous parameter monitoring systems (CPMS) were out-of-control as specified in §63.8(c)(7), the semiannual compliance report must include a statement that there were no periods during which the CPMS were out-of-control during the reporting period.
- (5) Deviations: Compliant material option. If you used the compliant material option and there was a deviation from the applicable organic HAP content requirements in §63.3890, the semiannual compliance report must contain the information in paragraphs (a)(5)(i) through (iv) of this section.
- (i) Identification of each coating used that deviated from the applicable emission limit, and each thinner and/or other additive, and cleaning material used that contained organic HAP, and the dates and time periods each was used.
- (ii) The calculation of the organic HAP content (using Equation 2 of §63.3941) for each coating identified in paragraph (a)(5)(i) of this section. You do not need to submit background data supporting this calculation (e.g., information provided by coating suppliers or manufacturers, or test reports).
- (iii) The determination of mass fraction of organic HAP for each thinner and/or other additive, and cleaning material identified in paragraph (a)(5)(i) of this section. You do not need to submit background data supporting this calculation (e.g., information provided by material suppliers or manufacturers, or test reports).
- (iv) A statement of the cause of each deviation.
- (6) Deviations: Emission rate without add-on controls option. If you used the emission rate without add-on controls option and there was a deviation from the applicable emission limit in §63.3890, the semiannual compliance report must contain the information in paragraphs (a)(6)(i) through (iii) of this section.
- (i) The beginning and ending dates of each compliance period during which the 12-month organic HAP emission rate exceeded the applicable emission limit in §63.3890.
- (ii) The calculations used to determine the 12-month organic HAP emission rate for the compliance period in which the deviation occurred. You must submit the calculations for Equations 1, 1A through 1C, 2, and 3 of §63.3951; and if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4). You do not need to submit background data supporting these calculations (e.g., information provided by materials suppliers or manufacturers, or test reports).
- (iii) A statement of the cause of each deviation.

#### **§ 63.3930 What records must I keep?**

You must collect and keep records of the data and information specified in this section. Failure to collect and keep these records is a deviation from the applicable standard.

- (a) A copy of each notification and report that you submitted to comply with this subpart, and the documentation supporting each notification and report.

(b) A current copy of information provided by materials suppliers or manufacturers, such as manufacturer's formulation data, or test data used to determine the mass fraction of organic HAP and density for each coating, thinner and/or other additive, and cleaning material, and the volume fraction of coating solids for each coating. If you conducted testing to determine mass fraction of organic HAP, density, or volume fraction of coating solids, you must keep a copy of the complete test report. If you use information provided to you by the manufacturer or supplier of the material that was based on testing, you must keep the summary sheet of results provided to you by the manufacturer or supplier. You are not required to obtain the test report or other supporting documentation from the manufacturer or supplier.

(c) For each compliance period, the records specified in paragraphs (c)(1) through (4) of this section.

(1) A record of the coating operations on which you used each compliance option and the time periods (beginning and ending dates and times) for each option you used.

(2) For the compliant material option, a record of the calculation of the organic HAP content for each coating, using Equation 2 of §63.3941.

(3) For the emission rate without add-on controls option, a record of the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1, 1A through 1C, and 2 of §63.3951; and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.3951(e)(4); the calculation of the total volume of coating solids used each month using Equation 2 of §63.3951; and the calculation of each 12-month organic HAP emission rate using Equation 3 of §63.3951.

(d) A record of the name and volume of each coating, thinner and/or other additive, and cleaning material used during each compliance period. If you are using the compliant material option for all coatings at the source, you may maintain purchase records for each material used rather than a record of the volume used.

(e) A record of the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each compliance period unless the material is tracked by weight.

(f) A record of the volume fraction of coating solids for each coating used during each compliance period.

(g) If you use either the emission rate without add-on controls or the emission rate with add-on controls compliance option, the density for each coating, thinner and/or other additive, and cleaning material used during each compliance period.

(h) If you use an allowance in Equation 1 of §63.3951 for organic HAP contained in waste materials sent to or designated for shipment to a treatment, storage, and disposal facility (TSDF) according to §63.3951(e)(4), you must keep records of the information specified in paragraphs (h)(1) through (3) of this section.

(1) The name and address of each TSDF to which you sent waste materials for which you use an allowance in Equation 1 of §63.3951; a statement of which subparts under 40 CFR parts 262, 264, 265, and 266 apply to the facility; and the date of each shipment.

(2) Identification of the coating operations producing waste materials included in each shipment and the month or months in which you used the allowance for these materials in Equation 1 of §63.3951.

(3) The methodology used in accordance with §63.3951(e)(4) to determine the total amount of waste materials sent to or the amount collected, stored, and designated for transport to a TSDF each month; and the methodology to determine the mass of organic HAP contained in these waste materials. This must include the sources for all data used in the determination, methods used to generate the data, frequency of testing or monitoring, and supporting calculations and documentation, including the waste manifest for each shipment.

(i) [Reserved]

(j) You must keep records of the date, time, and duration of each deviation.

**§ 63.3931 In what form and for how long must I keep my records?**

(a) Your records must be in a form suitable and readily available for expeditious review, according to §63.10(b)(1). Where appropriate, the records may be maintained as electronic spreadsheets or as a database.

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record on-site for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record according to §63.10(b)(1). You may keep the records off-site for the remaining 3 years.

**Compliance Requirements for the Compliant Material Option**

**§ 63.3940 By what date must I conduct the initial compliance demonstration?**

You must complete the initial compliance demonstration for the initial compliance period according to the requirements in §63.3941. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through that month plus the next 12 months. The initial compliance demonstration includes the calculations according to §63.3941 and supporting documentation showing that during the initial compliance period, you used no coating with an organic HAP content that exceeded the applicable emission limit in §63.3890, and that you used no thinners and/or other additives, or cleaning materials that contained organic HAP as determined according to §63.3941(a).

**§ 63.3941 How do I demonstrate initial compliance with the emission limitations?**

You may use the compliant material option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected source. You must use either the emission rate without add-on controls option or the emission rate with add-on controls option for any coating operation in the affected source for which you do not use this option. To demonstrate initial compliance using the compliant material option, the coating operation or group of coating operations must use no coating with an organic HAP content that exceeds the applicable emission limits in §63.3890 and must use no thinner and/or other additive, or cleaning material that contains organic HAP as determined according to this section. Any coating operation for which you use the compliant material option is not required to meet the operating limits or work practice standards required in §§63.3892 and 63.3893, respectively. You must meet all the requirements of this section. Use the procedures in this section on each coating, thinner and/or other additive, and cleaning material in the condition it is in when it is received from its manufacturer or supplier and prior to any alteration. You do not need to redetermine the organic HAP content of coatings, thinners and/or other additives, and cleaning materials that are reclaimed on-site (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coating operation for which you use the compliant material option, provided these materials in their condition as received were demonstrated to comply with the compliant material option.

(a) Determine the mass fraction of organic HAP for each material used. You must determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during the compliance period by using one of the options in paragraphs (a)(1) through (5) of this section.

(1) *Method 311 (appendix A to 40 CFR part 63)*. You may use Method 311 for determining the mass fraction of organic HAP. Use the procedures specified in paragraphs (a)(1)(i) and (ii) of this section when performing a Method 311 test.

(i) Count each organic HAP that is measured to be present at 0.1 percent by mass or more for Occupational Safety and Health Administration (OSHA)-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is measured to be 0.5 percent of the material by mass, you do not have to count it. Express the mass fraction of each organic HAP you count as a value truncated to four places after the decimal point (e.g., 0.3791).

(ii) Calculate the total mass fraction of organic HAP in the test material by adding up the individual organic HAP mass fractions and truncating the result to three places after the decimal point (e.g., 0.763).

(2) *Method 24 (appendix A to 40 CFR part 60)*. For coatings, you may use Method 24 to determine the mass fraction of nonaqueous volatile matter and use that value as a substitute for mass fraction of organic HAP. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, you may use the alternative method contained in appendix A to subpart PPPP of this part, rather than Method 24. You may use the volatile fraction that is emitted, as measured by the alternative method in appendix A to subpart PPPP of this part, as a substitute for the mass fraction of organic HAP.

(3) *Alternative method*. You may use an alternative test method for determining the mass fraction of organic HAP once the Administrator has approved it. You must follow the procedure in §63.7(f) to submit an alternative test method for approval.

(4) *Information from the supplier or manufacturer of the material*. You may rely on information other than that generated by the test methods specified in paragraphs (a)(1) through (3) of this section, such as manufacturer's formulation data, if it represents each organic HAP that is present at 0.1 percent by mass or more for OSHA-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is 0.5 percent of the material by mass, you do not have to count it. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, you may rely on manufacturer's data that expressly states the organic HAP or volatile matter mass fraction emitted. If there is a disagreement between such information and results of a test conducted according to paragraphs (a)(1) through (3) of this section, then the test method results will take precedence unless, after consultation, you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(5) *Solvent blends*. Solvent blends may be listed as single components for some materials in data provided by manufacturers or suppliers. Solvent blends may contain organic HAP which must be counted toward the total organic HAP mass fraction of the materials. When test data and manufacturer's data for solvent blends are not available, you may use the default values for the mass fraction of organic HAP in these solvent blends listed in Table 3 or 4 to this subpart. If you use the tables, you must use the values in Table 3 for all solvent blends that match Table 3 entries according to the instructions for Table 3, and you may use Table 4 only if the solvent blends in the materials you use do not match any of the solvent blends in Table 3 and you know only whether the blend is aliphatic or aromatic. However, if the results of a Method 311 (appendix A to 40 CFR part 63) test indicate higher values than those listed on Table 3 or 4 to this subpart, the Method 311 results will take precedence unless, after consultation, you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(b) *Determine the volume fraction of coating solids for each coating*. You must determine the volume fraction of coating solids (liters (gal) of coating solids per liter (gal) of coating) for each coating used during the compliance period by a test, by information provided by the supplier or the manufacturer of the material, or by calculation, as specified in paragraphs (b)(1) through (4) of this section. If test results obtained according to paragraph (b)(1) of this section do not agree with the information obtained under

paragraph (b)(3) or (4) of this section, the test results will take precedence unless, after consultation, you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(1) *ASTM Method D2697–86 (Reapproved 1998) or ASTM Method D6093–97 (Reapproved 2003)*. You may use ASTM Method D2697–86 (Reapproved 1998), “Standard Test Method for Volume Nonvolatile Matter in Clear or Pigmented Coatings” (incorporated by reference, see §63.14), or ASTM Method D6093–97 (Reapproved 2003), “Standard Test Method for Percent Volume Nonvolatile Matter in Clear or Pigmented Coatings Using a Helium Gas Pycnometer” (incorporated by reference, see §63.14), to determine the volume fraction of coating solids for each coating. Divide the nonvolatile volume percent obtained with the methods by 100 to calculate volume fraction of coating solids.

(2) *Alternative method*. You may use an alternative test method for determining the solids content of each coating once the Administrator has approved it. You must follow the procedure in §63.7(f) to submit an alternative test method for approval.

(3) *Information from the supplier or manufacturer of the material*. You may obtain the volume fraction of coating solids for each coating from the supplier or manufacturer.

(4) *Calculation of volume fraction of coating solids*. You may determine the volume fraction of coating solids using Equation 1 of this section:

$$V_s = 1 - \frac{m_{\text{volatiles}}}{D_{\text{avg}}} \quad (\text{Eq. 1})$$

Where:

$V_s$  = Volume fraction of coating solids, liters (gal) coating solids per liter (gal) coating.

$m_{\text{volatiles}}$  = Total volatile matter content of the coating, including HAP, volatile organic compounds (VOC), water, and exempt compounds, determined according to Method 24 in appendix A of 40 CFR part 60, grams volatile matter per liter coating.

$D_{\text{avg}}$  = Average density of volatile matter in the coating, grams volatile matter per liter volatile matter, determined from test results using ASTM Method D1475–98, “Standard Test Method for Density of Liquid Coatings, Inks, and Related Products” (incorporated by reference, see §63.14), information from the supplier or manufacturer of the material, or reference sources providing density or specific gravity data for pure materials. If there is disagreement between ASTM Method D1475–98 test results and other information sources, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(c) *Determine the density of each coating*. Determine the density of each coating used during the compliance period from test results using ASTM Method D1475–98, “Standard Test Method for Density of Liquid Coatings, Inks, and Related Products” (incorporated by reference, see §63.14), information from the supplier or manufacturer of the material, or specific gravity data for pure chemicals. If there is disagreement between ASTM Method D1475–98 test results and the supplier's or manufacturer's information, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(d) *Determine the organic HAP content of each coating*. Calculate the organic HAP content, kg (lb) of organic HAP emitted per liter (gal) coating solids used, of each coating used during the compliance period using Equation 2 of this section:

$$H_c = \frac{(D_c)(W_c)}{V_s} \quad (\text{Eq. 2})$$

Where:

$H_c$  = Organic HAP content of the coating, kg organic HAP emitted per liter (gal) coating solids used.

$D_c$  = Density of coating, kg coating per liter (gal) coating, determined according to paragraph (c) of this section.

$W_c$  = Mass fraction of organic HAP in the coating, kg organic HAP per kg coating, determined according to paragraph (a) of this section.

$V_s$  = Volume fraction of coating solids, liter (gal) coating solids per liter (gal) coating, determined according to paragraph (b) of this section.

(e) *Compliance demonstration.* The calculated organic HAP content for each coating used during the initial compliance period must be less than or equal to the applicable emission limit in §63.3890; and each thinner and/or other additive, and cleaning material used during the initial compliance period must contain no organic HAP, determined according to paragraph (a) of this section. You must keep all records required by §§63.3930 and 63.3931. As part of the notification of compliance status required in §63.3910, you must identify the coating operation(s) for which you used the compliant material option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because you used no coatings for which the organic HAP content exceeded the applicable emission limit in §63.3890, and you used no thinners and/or other additives, or cleaning materials that contained organic HAP, determined according to the procedures in paragraph (a) of this section.

#### **§ 63.3942 How do I demonstrate continuous compliance with the emission limitations?**

(a) For each compliance period to demonstrate continuous compliance, you must use no coating for which the organic HAP content (determined using Equation 2 of §63.3941) exceeds the applicable emission limit in §63.3890, and use no thinner and/or other additive, or cleaning material that contains organic HAP, determined according to §63.3941(a). A compliance period consists of 12 months. Each month, after the end of the initial compliance period described in §63.3940, is the end of a compliance period consisting of that month and the preceding 11 months.

(b) If you choose to comply with the emission limitations by using the compliant material option, the use of any coating, thinner and/or other additive, or cleaning material that does not meet the criteria specified in paragraph (a) of this section is a deviation from the emission limitations that must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(5).

(c) As part of each semiannual compliance report required by §63.3920, you must identify the coating operation(s) for which you used the compliant material option. If there were no deviations from the applicable emission limit in §63.3890, submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because you used no coatings for which the organic HAP content exceeded the applicable emission limit in §63.3890, and you used no thinner and/or other additive, or cleaning material that contained organic HAP, determined according to §63.3941(a).

(d) You must maintain records as specified in §§63.3930 and 63.3931.

#### **Compliance Requirements for the Emission Rate Without Add-On Controls Option**

##### **§ 63.3950 By what date must I conduct the initial compliance demonstration?**

You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.3951. The initial compliance period begins on the applicable compliance date specified in §63.3883 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and volume of coating solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the calculations according to §63.3951 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.3890.

##### **§ 63.3951 How do I demonstrate initial compliance with the emission limitations?**

You may use the emission rate without add-on controls option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected

source. You must use either the compliant material option or the emission rate with add-on controls option for any coating operation in the affected source for which you do not use this option. To demonstrate initial compliance using the emission rate without add-on controls option, the coating operation or group of coating operations must meet the applicable emission limit in §63.3890, but is not required to meet the operating limits or work practice standards in §§63.3892 and 63.3893, respectively. You must conduct a separate initial compliance demonstration for each general use, magnet wire, rubber-to-metal, and extreme performance fluoropolymer coating operation unless you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c). If you are demonstrating compliance with a predominant activity or facility-specific emission limit as provided in §63.3890(c), you must demonstrate that all coating operations included in the predominant activity determination or calculation of the facility-specific emission limit comply with that limit. You must meet all the requirements of this section. When calculating the organic HAP emission rate according to this section, do not include any coatings, thinners and/or other additives, or cleaning materials used on coating operations for which you use the compliant material option or the emission rate with add-on controls option. You do not need to redetermine the mass of organic HAP in coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coating operation for which you use the emission rate without add-on controls option. If you use coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site, the amount of each used in a month may be reduced by the amount of each that is reclaimed. That is, the amount used may be calculated as the amount consumed to account for materials that are reclaimed.

- (a) Determine the mass fraction of organic HAP for each material. Determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each month according to the requirements in §63.3941(a).
- (b) Determine the volume fraction of coating solids. Determine the volume fraction of coating solids (liter (gal) of coating solids per liter (gal) of coating) for each coating used during each month according to the requirements in §63.3941(b).
- (c) Determine the density of each material. Determine the density of each liquid coating, thinner and/or other additive, and cleaning material used during each month from test results using ASTM Method D1475–98, “Standard Test Method for Density of Liquid Coatings, Inks, and Related Products” (incorporated by reference, see §63.14), information from the supplier or manufacturer of the material, or reference sources providing density or specific gravity data for pure materials. If you are including powder coatings in the compliance determination, determine the density of powder coatings, using ASTM Method D5965–02, “Standard Test Methods for Specific Gravity of Coating Powders” (incorporated by reference, see §63.14), or information from the supplier. If there is disagreement between ASTM Method D1475–98 or ASTM Method D5965–02 test results and other such information sources, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct. If you purchase materials or monitor consumption by weight instead of volume, you do not need to determine material density. Instead, you may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, 1C, and 2 of this section.
- (d) Determine the volume of each material used. Determine the volume (liters) of each coating, thinner and/or other additive, and cleaning material used during each month by measurement or usage records. If you purchase materials or monitor consumption by weight instead of volume, you do not need to determine the volume of each material used. Instead, you may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, and 1C of this section.
- (e) Calculate the mass of organic HAP emissions. The mass of organic HAP emissions is the combined mass of organic HAP contained in all coatings, thinners and/or other additives, and cleaning materials used during each month minus the organic HAP in certain waste materials. Calculate the mass of organic HAP emissions using Equation 1 of this section.

$$H_e = A + B + C - R_w \quad (\text{Eq. 1})$$

Where:

$H_e$  = Total mass of organic HAP emissions during the month, kg.

$A$  = Total mass of organic HAP in the coatings used during the month, kg, as calculated in Equation 1A of this section.

$B$  = Total mass of organic HAP in the thinners and/or other additives used during the month, kg, as calculated in Equation 1B of this section.

$C$  = Total mass of organic HAP in the cleaning materials used during the month, kg, as calculated in Equation 1C of this section.

$R_w$  = Total mass of organic HAP in waste materials sent or designated for shipment to a hazardous waste TSDF for treatment or disposal during the month, kg, determined according to paragraph (e)(4) of this section. (You may assign a value of zero to  $R_w$  if you do not wish to use this allowance.)

(1) Calculate the kg organic HAP in the coatings used during the month using Equation 1A of this section:

$$A = \sum_{i=1}^m (Vol_{c,i})(D_{c,i})(W_{c,i}) \quad (Eq. 1A)$$

Where:

$A$  = Total mass of organic HAP in the coatings used during the month, kg.

$Vol_{c,i}$  = Total volume of coating,  $i$ , used during the month, liters.

$D_{c,i}$  = Density of coating,  $i$ , kg coating per liter coating.

$W_{c,i}$  = Mass fraction of organic HAP in coating,  $i$ , kg organic HAP per kg coating. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

$m$  = Number of different coatings used during the month.

(2) Calculate the kg of organic HAP in the thinners and/or other additives used during the month using Equation 1B of this section:

$$B = \sum_{j=1}^n (Vol_{t,j})(D_{t,j})(W_{t,j}) \quad (Eq. 1B)$$

Where:

$B$  = Total mass of organic HAP in the thinners and/or other additives used during the month, kg.

$Vol_{t,j}$  = Total volume of thinner and/or other additive,  $j$ , used during the month, liters.

$D_{t,j}$  = Density of thinner and/or other additive,  $j$ , kg per liter.

$W_{t,j}$  = Mass fraction of organic HAP in thinner and/or other additive,  $j$ , kg organic HAP per kg thinner and/or other additive. For reactive adhesives as defined in §63.3981, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to subpart PPPP of this part.

$n$  = Number of different thinners and/or other additives used during the month.

(3) Calculate the kg organic HAP in the cleaning materials used during the month using Equation 1C of this section:

$$C = \sum_{k=1}^p (Vol_{s,k})(D_{s,k})(W_{s,k}) \quad (Eq. 1C)$$

Where:

$C$  = Total mass of organic HAP in the cleaning materials used during the month, kg.

$Vol_{s,k}$  = Total volume of cleaning material,  $k$ , used during the month, liters.

$D_{s,k}$  = Density of cleaning material,  $k$ , kg per liter.

$W_{s,k}$  = Mass fraction of organic HAP in cleaning material,  $k$ , kg organic HAP per kg material.

$p$  = Number of different cleaning materials used during the month.

(4) If you choose to account for the mass of organic HAP contained in waste materials sent or designated for shipment to a hazardous waste TSDF in Equation 1 of this section, then you must determine the mass according to paragraphs (e)(4)(i) through (iv) of this section.

(i) You may only include waste materials in the determination that are generated by coating operations in the affected source for which you use Equation 1 of this section and that will be treated or disposed

of by a facility that is regulated as a TSD under 40 CFR part 262, 264, 265, or 266. The TSD may be either off-site or on-site. You may not include organic HAP contained in wastewater.

(ii) You must determine either the amount of the waste materials sent to a TSD during the month or the amount collected and stored during the month and designated for future transport to a TSD. Do not include in your determination any waste materials sent to a TSD during a month if you have already included them in the amount collected and stored during that month or a previous month.

(iii) Determine the total mass of organic HAP contained in the waste materials specified in paragraph (e)(4)(ii) of this section.

(iv) You must document the methodology you use to determine the amount of waste materials and the total mass of organic HAP they contain, as required in §63.3930(h). If waste manifests include this information, they may be used as part of the documentation of the amount of waste materials and mass of organic HAP contained in them.

(f) Calculate the total volume of coating solids used. Determine the total volume of coating solids used, liters, which is the combined volume of coating solids for all the coatings used during each month, using Equation 2 of this section:

$$V_{st} = \sum_{i=1}^m (Vol_{c,i}) (V_{s,i}) \quad (Eq. 2)$$

Where:

$V_{st}$  = Total volume of coating solids used during the month, liters.

$Vol_{c,i}$  = Total volume of coating, i, used during the month, liters.

$V_{s,i}$  = Volume fraction of coating solids for coating, i, liter solids per liter coating, determined according to §63.3941(b).

m = Number of coatings used during the month.

(g) Calculate the organic HAP emission rate. Calculate the organic HAP emission rate for the compliance period, kg (lb) organic HAP emitted per liter (gal) coating solids used, using Equation 3 of this section:

$$H_{yr} = \frac{\sum_{y=1}^n H_e}{\sum_{y=1}^n V_{st}} \quad (Eq. 3)$$

Where:

$H_{yr}$  = Average organic HAP emission rate for the compliance period, kg organic HAP emitted per liter coating solids used.

$H_e$  = Total mass of organic HAP emissions from all materials used during month, y, kg, as calculated by Equation 1 of this section.

$V_{st}$  = Total volume of coating solids used during month, y, liters, as calculated by Equation 2 of this section.

y = Identifier for months.

n = Number of full or partial months in the compliance period (for the initial compliance period, n equals 12 if the compliance date falls on the first day of a month; otherwise n equals 13; for all following compliance periods, n equals 12).

(h) Compliance demonstration. The organic HAP emission rate for the initial compliance period calculated using Equation 3 of this section must be less than or equal to the applicable emission limit for each subcategory in §63.3890 or the predominant activity or facility-specific emission limit allowed in §63.3890(c). You must keep all records as required by §§63.3930 and 63.3931. As part of the notification of compliance status required by §63.3910, you must identify the coating operation(s) for which you used the emission rate without add-on controls option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance

period because the organic HAP emission rate was less than or equal to the applicable emission limit in §63.3890, determined according to the procedures in this section.

#### **§ 63.3952 How do I demonstrate continuous compliance with the emission limitations?**

(a) To demonstrate continuous compliance, the organic HAP emission rate for each compliance period, determined according to §63.3951(a) through (g), must be less than or equal to the applicable emission limit in §63.3890. A compliance period consists of 12 months. Each month after the end of the initial compliance period described in §63.3950 is the end of a compliance period consisting of that month and the preceding 11 months. You must perform the calculations in §63.3951(a) through (g) on a monthly basis using data from the previous 12 months of operation. If you are complying with a facility-specific emission limit under §63.3890(c), you must also perform the calculation using Equation 1 in §63.3890(c)(2) on a monthly basis using the data from the previous 12 months of operation.

(b) If the organic HAP emission rate for any 12-month compliance period exceeded the applicable emission limit in §63.3890, this is a deviation from the emission limitation for that compliance period and must be reported as specified in §§63.3910(c)(6) and 63.3920(a)(6).

(c) As part of each semiannual compliance report required by §63.3920, you must identify the coating operation(s) for which you used the emission rate without add-on controls option. If there were no deviations from the emission limitations, you must submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable emission limit in §63.3890, determined according to §63.3951(a) through (g).

(d) You must maintain records as specified in §§63.3930 and 63.3931.

#### **Other Requirements and Information**

#### **§ 63.3980 Who implements and enforces this subpart?**

(a) This subpart can be implemented and enforced by us, the U.S. Environmental Protection Agency (EPA), or a delegated authority such as your State, local, or tribal agency. If the Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the EPA) has the authority to implement and enforce this subpart. You should contact your EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are listed in paragraphs (c)(1) through (4) of this section:

- (1) Approval of alternatives to the requirements in §63.3881 through 3883 and §63.3890 through 3893.
- (2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.
- (3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.
- (4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

#### **§ 63.3981 What definitions apply to this subpart?**

Terms used in this subpart are defined in the CAA, in 40 CFR 63.2, and in this section as follows:

*Additive* means a material that is added to a coating after purchase from a supplier (e.g., catalysts, activators, accelerators).

*Add-on control* means an air pollution control device, such as a thermal oxidizer or carbon adsorber, that reduces pollution in an air stream by destruction or removal before discharge to the atmosphere.

*Adhesive, adhesive coating* means any chemical substance that is applied for the purpose of bonding two surfaces together. Products used on humans and animals, adhesive tape, contact paper, or any other product with an adhesive incorporated onto or in an inert substrate shall not be considered adhesives under this subpart.

*Assembled on-road vehicle coating* means any coating operation in which coating is applied to the surface of some component or surface of a fully assembled motor vehicle or trailer intended for on-road use including, but not limited to, components or surfaces on automobiles and light-duty trucks that have been repaired after a collision or otherwise repainted, fleet delivery trucks, and motor homes and other recreational vehicles (including camping trailers and fifth wheels). Assembled on-road vehicle coating includes the concurrent coating of parts of the assembled on-road vehicle that are painted off-vehicle to protect systems, equipment, or to allow full coverage. Assembled on-road vehicle coating does not include surface coating operations that meet the applicability criteria of the automobiles and light-duty trucks NESHAP. Assembled on-road vehicle coating also does not include the use of adhesives, sealants, and caulks used in assembling on-road vehicles.

*Capture device* means a hood, enclosure, room, floor sweep, or other means of containing or collecting emissions and directing those emissions into an add-on air pollution control device.

*Capture efficiency or capture system efficiency* means the portion (expressed as a percentage) of the pollutants from an emission source that is delivered to an add-on control device.

*Capture system* means one or more capture devices intended to collect emissions generated by a coating operation in the use of coatings or cleaning materials, both at the point of application and at subsequent points where emissions from the coatings and cleaning materials occur, such as flashoff, drying, or curing. As used in this subpart, multiple capture devices that collect emissions generated by a coating operation are considered a single capture system.

*Cleaning material* means a solvent used to remove contaminants and other materials, such as dirt, grease, oil, and dried or wet coating (e.g., depainting or paint stripping), from a substrate before or after coating application or from equipment associated with a coating operation, such as spray booths, spray guns, racks, tanks, and hangers. Thus, it includes any cleaning material used on substrates or equipment or both.

*Coating* means a material applied to a substrate for decorative, protective, or functional purposes. Such materials include, but are not limited to, paints, sealants, liquid plastic coatings, caulks, inks, adhesives, and maskants. Decorative, protective, or functional materials that consist only of protective oils for metal, acids, bases, or any combination of these substances, or paper film or plastic film which may be pre-coated with an adhesive by the film manufacturer, are not considered coatings for the purposes of this subpart. A liquid plastic coating means a coating made from fine particle-size polyvinyl chloride (PVC) in solution (also referred to as a plastisol).

*Coating operation* means equipment used to apply cleaning materials to a substrate to prepare it for coating application (surface preparation) or to remove dried coating; to apply coating to a substrate (coating application) and to dry or cure the coating after application; or to clean coating operation equipment (equipment cleaning). A single coating operation may include any combination of these types of equipment, but always includes at least the point at which a given quantity of coating or cleaning material is applied to a given part and all subsequent points in the affected source where organic HAP are emitted from the specific quantity of coating or cleaning material on the specific part. There may be multiple coating operations in an affected source. Coating application with handheld, non-refillable aerosol containers, touch-up markers, or marking pens is not a coating operation for the purposes of this subpart.

*Coatings solids* means the nonvolatile portion of the coating that makes up the dry film.

*Continuous parameter monitoring system (CPMS)* means the total equipment that may be required to meet the data acquisition and availability requirements of this subpart, used to sample, condition (if applicable), analyze, and provide a record of coating operation, or capture system, or add-on control device parameters.

*Controlled coating operation* means a coating operation from which some or all of the organic HAP emissions are routed through an emission capture system and add-on control device.

*Deviation* means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

- (1) Fails to meet any requirement or obligation established by this subpart including but not limited to, any emission limit or operating limit or work practice standard;
- (2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or
- (3) Fails to meet any emission limit, or operating limit, or work practice standard in this subpart during startup, shutdown, or malfunction, regardless of whether or not such failure is permitted by this subpart.

*Emission limitation* means the aggregate of all requirements associated with a compliance option including emission limit, operating limit, work practice standard, etc.

*Enclosure* means a structure that surrounds a source of emissions and captures and directs the emissions to an add-on control device.

*Exempt compound* means a specific compound that is not considered a VOC due to negligible photochemical reactivity. The exempt compounds are listed in 40 CFR 51.100(s).

*Extreme performance fluoropolymer coating* means coatings that are formulated systems based on fluoropolymer resins which often contain bonding matrix polymers dissolved in non-aqueous solvents as well as other ingredients. Extreme performance fluoropolymer coatings are typically used when one or more critical performance criteria are required including, but not limited to a nonstick low-energy surface, dry film lubrication, high resistance to chemical attack, extremely wide operating temperature, high electrical insulating properties, or that the surface comply with government (e.g., USDA, FDA) or third party specifications for health, safety, reliability, or performance. Once applied to a substrate, extreme performance fluoropolymer coatings undergo a curing process that typically requires high temperatures, a chemical reaction, or other specialized technology.

*Facility maintenance* means the routine repair or renovation (including the surface coating) of the tools, equipment, machinery, and structures that comprise the infrastructure of the affected facility and that are necessary for the facility to function in its intended capacity.

*General use coating* means any material that meets the definition of coating but does not meet the definition of high performance coating, rubber-to-metal coating, magnet wire coating, or extreme performance fluoropolymer coating as defined in this section.

*High performance architectural coating* means any coating applied to architectural subsections which is required to meet the specifications of Architectural Aluminum Manufacturer's Association's publication number AAMA 605.2-2000.

*High performance coating* means any coating that meets the definition of high performance architectural coating or high temperature coating in this section.

*High temperature coating* means any coating applied to a substrate which during normal use must withstand temperatures of at least 538 degrees Celsius (1000 degrees Fahrenheit).

*Hobby shop* means any surface coating operation, located at an affected source, that is used exclusively for personal, noncommercial purposes by the affected source's employees or assigned personnel.

*Magnet wire coatings*, commonly referred to as magnet wire enamels, are applied to a continuous strand of wire which will be used to make turns (windings) in electrical devices such as coils, transformers, or motors. Magnet wire coatings provide high dielectric strength and turn-to-turn conductor insulation. This allows the turns of an electrical device to be placed in close proximity to one another which leads to increased coil effectiveness and electrical efficiency.

*Magnet wire coating machine* means equipment which applies and cures magnet wire coatings.

*Manufacturer's formulation data* means data on a material (such as a coating) that are supplied by the material manufacturer based on knowledge of the ingredients used to manufacture that material, rather than based on testing of the material with the test methods specified in §63.3941. Manufacturer's formulation data may include, but are not limited to, information on density, organic HAP content, volatile organic matter content, and coating solids content.

*Mass fraction of organic HAP* means the ratio of the mass of organic HAP to the mass of a material in which it is contained, expressed as kg of organic HAP per kg of material.

*Month* means a calendar month or a pre-specified period of 28 days to 35 days to allow for flexibility in recordkeeping when data are based on a business accounting period.

*Non-HAP coating* means, for the purposes of this subpart, a coating that contains no more than 0.1 percent by mass of any individual organic HAP that is an OSHA-defined carcinogen as specified in 29 CFR 1910.1200(d)(4) and no more than 1.0 percent by mass for any other individual HAP.

*Organic HAP content* means the mass of organic HAP emitted per volume of coating solids used for a coating calculated using Equation 2 of §63.3941. The organic HAP content is determined for the coating in the condition it is in when received from its manufacturer or supplier and does not account for any alteration after receipt. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, organic HAP content is the mass of organic HAP that is emitted, rather than the organic HAP content of the coating as it is received.

*Permanent total enclosure (PTE)* means a permanently installed enclosure that meets the criteria of Method 204 of appendix M, 40 CFR part 51, for a PTE and that directs all the exhaust gases from the enclosure to an add-on control device.

*Personal watercraft* means a vessel (boat) which uses an inboard motor powering a water jet pump as its primary source of motive power and which is designed to be operated by a person or persons sitting, standing, or kneeling on the vessel, rather than in the conventional manner of sitting or standing inside the vessel.

*Protective oil* means an organic material that is applied to metal for the purpose of providing lubrication or protection from corrosion without forming a solid film. This definition of protective oil includes, but is not limited to, lubricating oils, evaporative oils (including those that evaporate completely), and extrusion oils. Protective oils used on miscellaneous metal parts and products include magnet wire lubricants and soft temporary protective coatings that are removed prior to installation or further assembly of a part or component.

*Reactive adhesive* means adhesive systems composed, in part, of volatile monomers that react during the adhesive curing reaction, and, as a result, do not evolve from the film during use. These volatile components instead become integral parts of the adhesive through chemical reaction. At least 70 percent of the liquid components of the system, excluding water, react during the process.

*Research or laboratory facility* means a facility whose primary purpose is for research and development of new processes and products, that is conducted under the close supervision of technically trained personnel, and is not engaged in the manufacture of final or intermediate products for commercial purposes, except in a de minimis manner.

*Responsible official* means responsible official as defined in 40 CFR 70.2.

*Rubber-to-metal coatings* are coatings that contain heat-activated polymer systems in either solvent or water that, when applied to metal substrates, dry to a non-tacky surface and react chemically with the rubber and metal during a vulcanization process.

*Startup, initial* means the first time equipment is brought online in a facility.

*Surface preparation* means use of a cleaning material on a portion of or all of a substrate. This includes use of a cleaning material to remove dried coating, which is sometimes called depainting.

*Temporary total enclosure* means an enclosure constructed for the purpose of measuring the capture efficiency of pollutants emitted from a given source as defined in Method 204 of appendix M, 40 CFR part 51.

*Thinner* means an organic solvent that is added to a coating after the coating is received from the supplier.

*Total volatile hydrocarbon (TVH)* means the total amount of nonaqueous volatile organic matter determined according to Methods 204 and 204A through 204F of appendix M to 40 CFR part 51 and substituting the term TVH each place in the methods where the term VOC is used. The TVH includes both VOC and non-VOC.

*Uncontrolled coating operation* means a coating operation from which none of the organic HAP emissions are routed through an emission capture system and add-on control device.

*Volatile organic compound (VOC)* means any compound defined as VOC in 40 CFR 51.100(s).

*Volume fraction of coating solids* means the ratio of the volume of coating solids (also known as the volume of nonvolatiles) to the volume of a coating in which it is contained; liters (gal) of coating solids per liter (gal) of coating.

*Wastewater* means water that is generated in a coating operation and is collected, stored, or treated prior to being discarded or discharged.

**Table 2 to Subpart MMMM of Part 63—Applicability of General Provisions to Subpart  
MMMM of Part 63**

You must comply with the applicable General Provisions requirements according to the following table:

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.1(a)(1)-(14) .....	General Applicability.	Yes.....	
§ 63.1(b)(1)-(3).....	Initial Applicability Determination.	Yes.....	Applicability to subpart MMMM is also specified in § 63.3881.
§ 63.1(c)(1).....	Applicability After Standard Established.	Yes.....	
§ 63.1(c)(2)-(3).....	Applicability of Permit Program for Area Sources.	No.....	Area sources are not subject to subpart MMMM.
§ 63.1(c)(4)-(5).....	Extensions and Notifications.	Yes.....	
§ 63.1(e).....	Applicability of Permit Program Before Relevant Standard is Set.	Yes.....	
§ 63.2.....	Definitions.....	Yes.....	Additional definitions are specified in § 63.3981.
§ 63.1(a)-(c).....	Units and Abbreviations.	Yes.....	
§ 63.4(a)(1)-(5).....	Prohibited Activities.	Yes.....	
§ 63.4(b)-(c).....	Circumvention/Severability.	Yes.....	
§ 63.5(a).....	Construction/Reconstruction.	Yes.....	
§ 63.5(b)(1)-(6).....	Requirements for Existing Newly Constructed, and Reconstructed Sources.	Yes.....	
§ 63.5(d).....	Application for Approval of Construction/Reconstruction.	Yes.....	
§ 63.5(e).....	Approval of Construction/Reconstruction.	Yes.....	
§ 63.5(f).....	Approval of Construction/Reconstruction Based on Prior State Review.	Yes.....	
§ 63.6(a).....	Compliance With Standards and Maintenance Requirements_Applicability.	Yes.....	
§ 63.6(b)(1)-(7).....	Compliance Dates for New and Reconstructed Sources.	Yes.....	Section § 63.3883 specifies the compliance dates.
§ 63.6(c)(1)-(5).....	Compliance Dates for Existing Sources.	Yes.....	Section § 63.3883 specifies the compliance dates.
§ 63.6(e)(1)-(2).....	Operation and Maintenance.	Yes.....	
§ 63.6(e)(3).....	Startup, Shutdown, and Malfunction Plan.	Yes.....	Only sources using an add-on control device to comply with the standard must complete startup, shutdown, and malfunction plans.

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.6(f)(1).....	Compliance Except During Startup, Shutdown, and Malfunction.	Yes.....	Applies only to sources using an add-on control device to comply with the standard.
§ 63.6(f)(2)-(3).....	Methods for Determining Compliance..	Yes.....	
§ 63.6(g)(1)-(3).....	Use of an Alternative Standard.	Yes.....	
§ 63.6(h).....	Compliance With Opacity/Visible Emission Standards.	No.....	Subpart MMMM does not establish opacity standards and does not require continuous opacity monitoring systems (COMS).
§ 63.6(i)(1)-(16).....	Extension of Compliance.	Yes.....	
§ 63.6(j).....	Presidential Compliance Exemption.	Yes.....	
§ 63.7(a)(1).....	Performance Test Requirements_Applicability.	Yes.....	Applies to all affected sources. Additional requirements for performance testing are specified in § 63.3964, § 63.3965, and § 63.3966.
§ 63.7(a)(2).....	Performance Test Requirements_Dates.	Yes.....	Applies only to performance tests for capture system and control device efficiency at sources using these to comply with the standard. Section § 63.3960 specifies the schedule for performance test requirements that are earlier than those specified in § 63.7(a)(2).
§ 63.7(a)(3).....	Performance Tests Required By the Administrator.	Yes.....	
§ 63.7(b)-(e).....	Performance Test Requirements_Notification, Quality Assurance, Facilities Necessary for Safe Testing, Conditions During Test.	Yes.....	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.7(f).....	Performance Test Requirements_Use of Alternative Test Method.	Yes.....	Applies to all test methods except those used to determine capture system efficiency.
§ 63.7(g)-(h).....	Performance Test Requirements_Data Analysis, Recordkeeping, Reporting, Waiver of Test.	Yes.....	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.

Citation	Subject	Applicable to subpart M MMM	Explanation
§ 63.8(a)(1)-(3).....	Monitoring Requirements_Applicability.	Yes.....	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for monitoring are specified in § 63.3968.
§ 63.8(a)(4).....	Additional Monitoring Requirements.	No.....	Subpart M MMM does not have monitoring requirements for flares.
§ 63.8(b).....	Conduct of Monitoring.	Yes.....	
§ 63.8(c)(1)-(3).....	Continuous Monitoring Systems (CMS) Operation and Maintenance.	Yes.....	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for monitoring are specified in § 63.3968.
§ 63.8(c)(4).....	CMS.....	No.....	§ 63.3968 specifies the requirements for the operation of CMS for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(5).....	COMS.....	No.....	Subpart M MMM does not have opacity or visible emission standards.
§ 63.8(c)(6).....	CMS Requirements.....	No.....	Section 63.3968 specifies the requirements for monitoring systems for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(7).....	CMS Out-of-Control Periods.	Yes.....	
§ 63.8(c)(8).....	CMS Out-of-Control Periods and Reporting.	No.....	§ 63.3920 requires reporting of CMS out-of-control periods.
§ 63.8(d)-(e).....	Quality Control Program and CMS Performance Evaluation.	No.....	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§ 63.8(f)(1)-(5).....	Use of an Alternative Monitoring Method	Yes.....	
§ 63.8(f)(6).....	Alternative to Relative Accuracy Test.	No.....	Subpart M MMM does not require the use of continuous emissions monitoring systems.

Citation	Subject	Applicable to subpart MMMM	Explanation
§ 63.8(g)(1)-(5).....	Data Reduction.....	No.....	Sections § 63.3967 and § 63.3968 specify monitoring data reduction.
§ 63.9(a)-(d).....	Notification Requirements.	Yes.....	
§ 63.9(e).....	Notification of Performance Test.	Yes.....	Applies only to capture system and add-on control device performance tests at sources using these to comply with the standard.
§ 63.9(f).....	Notification of Visible Emissions/Opacity Test.	No.....	Subpart MMMM does not have opacity or visible emissions standards.
§ 63.9(g)(1)-(3).....	Additional Notifications When Using CMS.	No.....	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§ 63.9(h).....	Notification of Compliance Status	Yes.....	Section § 63.3910 specifies the dates for submitting the notification of compliance status.
§ 63.9(i).....	Adjustment of Submittal Deadlines	Yes.....	
§ 63.9(j).....	Change in Previous Information.	Yes.....	
§ 63.10(a).....	Recordkeeping/Reporting Applicability and General Information.	Yes.....	
§ 63.10(b)(1).....	General Recordkeeping Requirements.	Yes.....	Additional requirements are specified in § 63.3930 and § 63.3931.
§ 63.10(b)(2) (i)-(v).....	Recordkeeping Relevant to Startup, Shutdown, and Malfunction Periods and CMS.	Yes.....	Requirements for startup, shutdown, and malfunction records only apply to add-on control devices used to comply with the standard.
§ 63.10(b)(2) (vi)-(xi).....	.....	Yes.....	
§ 63.10(b)(2) (xii).....	Records.....	Yes.....	
§ 63.10(b)(2) (xiii).....	.....	No.....	Subpart MMMM does not require the use of continuous emissions monitoring systems.
§ 63.10(b)(2) (xiv).....	.....	Yes.....	
§ 63.10(b)(3).....	Recordkeeping Requirements for Applicability Determinations.	Yes.....	
§ 63.10(c) (1)-(6).....	Additional Recordkeeping Requirements for Sources with CMS.	Yes.....	
§ 63.10(c) (7)-(8).....	.....	No.....	The same records are required in § 63.3920(a)(7).
§ 63.10(c) (9)-(15).....	.....	Yes.....	

Citation	Subject	Applicable to subpart M MMM	Explanation
§ 63.10(d)(1).....	General Reporting Requirements.	Yes.....	Additional requirements are specified in § 63.3920.
§ 63.10(d)(2).....	Report of Performance Test Results.	Yes.....	Additional requirements are specified in § 63.3920(b).
§ 63.10(d)(3).....	Reporting Opacity or Visible Emissions Observations.	No.....	Subpart M MMM does not require opacity or visible emissions observations.
§ 63.10(d)(4).....	Progress Reports for Sources With Compliance Extensions.	Yes.....	
§ 63.10(d)(5).....	Startup, Shutdown, and Malfunction Reports.	Yes.....	Applies only to add-on control devices at sources using these to comply with the standard.
§ 63.10(e) (1)-(2).....	Additional CMS Reports	No.....	Subpart M MMM does not require the use of continuous emissions monitoring systems.
§ 63.10(e) (3).....	Excess Emissions/CMS Performance Reports	No.....	Section § 63.3920 (b) specifies the contents of periodic compliance reports.
§ 63.10(e) (4).....	COMS Data Reports.....	No.....	Subpart M MMM does not specify requirements for opacity or COMS.
§ 63.10(f).....	Recordkeeping/Reporting Waiver.	Yes.....	
§ 63.11.....	Control Device Requirements/Flares.	No.....	Subpart M MMM does not specify use of flares for compliance.
§ 63.12.....	State Authority and Delegations.	Yes.....	
§ 63.13.....	Addresses.....	Yes.....	
§ 63.14.....	Incorporation by Reference.	Yes.....	
§ 63.15.....	Availability of Information/Confidentiality.	Yes.....	

**Table 3 to Subpart MMMM of Part 63—Default Organic HAP Mass Fraction for Solvents and Solvent Blends**

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data and which match either the solvent blend name or the chemical abstract series (CAS) number. If a solvent blend matches both the name and CAS number for an entry, that entry's organic HAP mass fraction must be used for that solvent blend. Otherwise, use the organic HAP mass fraction for the entry matching either the solvent blend name or CAS number, or use the organic HAP mass fraction from table 4 to this subpart if neither the name or CAS number match.

Solvent/solvent blend	CAS. No.	Average organic HAP mass fraction	Typical Organic HAP, percent by mass
1. Toluene.....	108-88-3	1.00	Toluene.
2. Xylene(s).....	1330-20-7	1.00	Xylenes, ethylbenzene.
3. Hexane.....	110-54-3	0.50	n-hexane.
4. n-Hexane.....	110-54-3	1.00	n-hexane.
5. Ethylbenzene.....	100-41-4	1.00	Ethylbenzene.
6. Aliphatic 140.....		0.00	None.
7. Aromatic 100.....		0.02	1% xylene, 1% cumene.
8. Aromatic 150.....		0.09	Naphthalene.
9. Aromatic naphtha.....	64742-95-6	0.02	1% xylene, 1% cumene.
10. Aromatic solvent.....	64742-94-5	0.10	Naphthalene.
11. Exempt mineral spirits..	8032-32-4	0.00	None.
12. Ligroines (VM & P).....	8032-32-4	0.00	None.
13. Lactol spirits.....	64742-89-6	0.15	Toluene.
14. Low aromatic white spirit.	64742-82-1	0.00	None.
15. Mineral spirits.....	64742-88-7	0.01	Xylenes.
16. Hydrotreated naphtha....	64742-48-9	0.00	None.
17. Hydrotreated light distillate.....	64742-47-8	0.00	Toluene.
18. Stoddard solvent.....	8052-41-3	0.01	Xylenes.
19. Super high-flash naphtha	64742-95-6	0.05	Xylenes.
20. Varsol solvent.....	8052-49-3	0.01	0.5% xylenes, 0.5% ethylbenzene.
21. VM & P naphtha.....	64742-89-8	0.06	3% toluene, 3% xylene.
22. Petroleum distillate mixture....	68477-31-6	0.08	4% naphthalene 4% biphenyl.

**Table 4 to Subpart MMMM of Part 63—Default Organic HAP Mass Fraction for Petroleum Solvent Groups<sup>a</sup>**

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data.

<b>Solvent type</b>	<b>Average organic HAP mass fraction</b>	<b>Typical organic HAP, percent by mass</b>
Aliphatic <sup>b</sup>	0.03	1% Xylene, 1% Toluene, and 1% Ethylbenzene.
Aromatic <sup>c</sup>	0.06	4% Xylene, 1% Toluene, and 1% Ethylbenzene.

<sup>a</sup> Use this table only if the solvent blend does not match any of the solvent blends in Table 3 to this subpart by either solvent blend name or CAS number and you only know whether the blend is aliphatic or aromatic.

<sup>b</sup> Mineral Spirits 135, Mineral Spirits 150 EC, Naphtha, Mixed Hydrocarbon, Aliphatic Hydrocarbon, Aliphatic Naphtha, Naphthol Spirits, Petroleum Spirits, Petroleum Oil, Petroleum Naphtha, Solvent Naphtha, Solvent Blend.

<sup>c</sup> Medium-flash Naphtha, High-flash Naphtha, Aromatic Naphtha, Light Aromatic Naphtha, Light Aromatic Hydrocarbons, Aromatic Hydrocarbons, Light Aromatic Solvent.

**E.1.3 One Time Deadlines Relating to NESHAP MMMM [40 CFR Part 63, Subpart MMMM] [326 IAC 20-80]**

- (a) The Permittee submitted Initial Notification on December 27, 2004 [40 CFR 63.3910(b)].
- (b) The Permittee shall conduct initial compliance demonstrations no later than January 31, 2008 [40 CFR 63.3940, 40 CFR 63.3950].
- (c) The Permittee shall submit notification of compliance status no later than March 1, 2008 [40 CFR 63.3910 (e)].
- (d) The Permittee shall submit first Semi-annual Compliance Report no later than July 31, 2008 [40 CFR 63.3920(a)(1)].

## SECTION E.2

## FACILITY OPERATION CONDITIONS

### Emissions Unit Description [326 IAC 2-7-5(15)]:

- (a) A spray/bake booth, identified as H-1, constructed June 1991, which may coat metal or fiberglass reinforced plastic (FRP) surfaces, with a maximum production capacity of 1.66 units per hour, equipped with a dry filter for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stack SV-H-1;
- (b) A bake booth, identified as H-4, constructed November 4, 1999, which serves as an additional bake booth for sprayed parts from spray/bake booth H-1, with a rated heat input of 1.2 MMBtu per hour, with no controls, and exhausting to stack SV-H-4;
- (c) Two spray/bake booths, identified as H-2 and H-3, constructed May 28, 1997, which may coat metal or FRP surfaces, each with a maximum production capacity of 0.375 units per hour, each equipped with dry filters for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stacks SV-H-2 and SV-H-3;
- (d) An HVLP paint area, identified as A-1, constructed in June 1991, with a maximum production capacity of 3.1 metal truck rear-end parts per hour, equipped with dry filters for PM control, and exhausting to stack SV-A-1;
- (e) A base coat booth, identified as I-1, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units/hour, equipped with a dry filter for PM overspray control, and exhausting to stack SV-I-1;
- (f) A spray/bake booth, identified as I-2, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units per hour, and a maximum heat input capacity of 1.0 MMBtu per hour, equipped with a down draft dry filter system for PM overspray control, and exhausting through stack SV-I-2;
- (g) Two HVLP spray paint areas, identified as 1-1 and 1-2, constructed July 25, 1991, each with a maximum production capacity of 1.33 metal rear parts/hour, each equipped with a dry filter for PM control, and exhausting through stacks SV-1-1 and SV-1-2;
- (h) An undercoating air assisted spray booth, identified as 1-4, constructed July 25, 1991, with a maximum production capacity of 1.33 metal frames per hour, equipped with a dry filter for PM control, and exhausting through stack SV-1-4;
- (i) A spray paint booth, identified as P-6, constructed July 25, 1991, with a maximum capacity of 0.88 metal or FRP units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-6;
- (j) A spray paint area, identified as P-7, constructed July 25, 1991, with a maximum capacity of 16.66 metal parts/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-7;
- (k) A surface touch-up spray facility, identified as GM-2, constructed in 1987, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**SECTION E.2**

**CONTINUED**

**Emissions Unit Description [326 IAC 2-7-5(15)]:**

- (l) A spray booth identified as 1-3, constructed in January 1991, with a maximum production capacity of 14 metal units/day, equipped with a dry filter for PM control, and exhausting through stack SV-1-3;
- (m) A spray area, identified as 1-6, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, equipped with no controls, and exhausting within the building;
- (n) A spray area, identified as 1-7, constructed in January 1991, with a maximum production capacity of 1.33 metal units/hour, with no controls, and exhausting within the building;
- (o) A portable undercoating station, identified as 1-8, constructed in January 1991, with a maximum production capacity of 14 metal units/day, with no controls, and exhausting within the building;
- (p) An undercoat air assisted spray booth, identified as 5-10, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with dry filters for PM control, and exhausting through stack SV-5-10;
- (q) An undercoat air assisted spray booth, identified as 5-12, constructed in August 1985, with a maximum production capacity of 0.55 metal units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-5-12;
- (r) A spray booth, identified as 5-13, constructed in August 1985, with a maximum production capacity of 5 metal units/day, equipped with dry filter banks for PM control, and exhausting through stack SV-5-13;
- (s) A spray paint area, identified as N-2, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with dry filter banks for PM control, and exhausting to stack SV-N-2;
- (t) A spray undercoating area, identified as A-2, constructed in June 1991, with a maximum capacity of 12 metal units/day, with no emission control, and exhausting within the building;
- (u) An air assisted undercoating booth, identified as N-1, constructed in June 1991, with a maximum capacity of 1.11 metal units/hour, equipped with a dry filter for PM control, and exhausting to stack SV-N-1;

Under NESHAP PPPP H-1, H-4, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2 and N-1 are considered existing affected sources.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

**E.2.1 General Provisions Relating to NESHAP PPPP [40 CFR Part 63, Subpart A] [326 IAC 20-1]**

Pursuant to 40 CFR 63.4501, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, as specified in Table 2 of 40 CFR Part 63, Subpart PPPP in accordance with schedule in 40 CFR 63 Subpart PPPP.

## E.2.2 NESHAP Subpart P PPP Requirements [40 CFR Part 63, Subpart P PPP] [326 IAC 20-81]

Pursuant to CFR Part 63, Subpart P PPP, the Permittee shall comply with the provisions of 40 CFR Part 63.4480, as specified as follows:

### **§ 63.4483 When do I have to comply with this subpart?**

The date by which you must comply with this subpart is called the compliance date. The compliance date for each type of affected source is specified in paragraphs (a) through (c) of this section. The compliance date begins the initial compliance period during which you conduct the initial compliance demonstration described in §§63.4540, 63.4550, and 63.4560.

(b) For an existing affected source, the compliance date is the date 3 years after April 19, 2004.

### **Emission Limitations**

#### **§ 63.4490 What emission limits must I meet?**

(b) For an existing affected source, you must limit organic HAP emissions to the atmosphere from the affected source to the applicable limit specified in paragraphs (b)(1) through (4) of this section, except as specified in paragraph (c) of this section, determined according to the requirements in §63.4541, §63.4551, or §63.4561.

(1) For each existing general use coating affected source, limit organic HAP emissions to no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.

#### **§ 63.4491 What are my options for meeting the emission limits?**

You must include all coatings (as defined in §63.4581), thinners and/or other additives, and cleaning materials used in the affected source when determining whether the organic HAP emission rate is equal to or less than the applicable emission limit in §63.4490. To make this determination, you must use at least one of the three compliance options listed in paragraphs (a) through (c) of this section. You may apply any of the compliance options to an individual coating operation, or to multiple coating operations as a group, or to the entire affected source. You may use different compliance options for different coating operations, or at different times on the same coating operation. You may employ different compliance options when different coatings are applied to the same part, or when the same coating is applied to different parts. However, you may not use different compliance options at the same time on the same coating operation. If you switch between compliance options for any coating operation or group of coating operations, you must document this switch as required by §63.4530(c), and you must report it in the next semiannual compliance report required in §63.4520.

(a) *Compliant material option.* Demonstrate that the organic HAP content of each coating used in the coating operation(s) is less than or equal to the applicable emission limit in §63.4490, and that each thinner and/or other additive, and cleaning material used contains no organic HAP. You must meet all the requirements of §§63.4540, 63.4541, and 63.4542 to demonstrate compliance with the applicable emission limit using this option.

(b) *Emission rate without add-on controls option.* Demonstrate that, based on the coatings, thinners and/or other additives, and cleaning materials used in the coating operation(s), the organic HAP emission rate for the coating operation(s) is less than or equal to the applicable emission limit in §63.4490, calculated as a rolling 12-month emission rate and determined on a monthly basis. You must meet all the requirements of §§63.4550, 63.4551, and 63.4552 to demonstrate compliance with the emission limit using this option.

#### **§ 63.4492 What operating limits must I meet?**

(a) For any coating operation(s) on which you use the compliant material option or the emission rate without add-on controls option, you are not required to meet any operating limits.

**§ 63.4493 What work practice standards must I meet?**

(a) For any coating operation(s) on which you use the compliant material option or the emission rate without add-on controls option, you are not required to meet any work practice standards.

**General Compliance Requirements**

**§ 63.4500 What are my general requirements for complying with this subpart?**

(a) You must be in compliance with the emission limitations in this subpart as specified in paragraphs (a)(1) and (2) of this section.

(1) Any coating operation(s) for which you use the compliant material option or the emission rate without add-on controls option, as specified in §63.4491(a) and (b), must be in compliance with the applicable emission limit in §63.4490 at all times.

(b) You must always operate and maintain your affected source, including all air pollution control and monitoring equipment you use for purposes of complying with this subpart, according to the provisions in §63.6(e)(1)(i).

**§ 63.4501 What parts of the General Provisions apply to me?**

Table 2 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you.

**Notifications, Reports, and Records**

**§ 63.4510 What notifications must I submit?**

(a) *General.* You must submit the notifications in §§63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) that apply to you by the dates specified in those sections, except as provided in paragraphs (b) and (c) of this section.

(b) *Initial notification.* You must submit the initial notification required by §63.9(b) for a new or reconstructed affected source no later than 120 days after initial startup or 120 days after April 19, 2004, whichever is later. The Permittee submitted the initial notification to IDEM, OAQ on April 19, 2005. If you are using compliance with the Surface Coating of Automobiles and Light-Duty Trucks NESHAP (subpart IIII of this part) as provided for under §63.4481(d) to constitute compliance with this subpart for any or all of your plastic parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those plastic parts coating operations. If you are complying with another NESHAP that constitutes the predominant activity at your facility under §63.4481(e)(2) to constitute compliance with this subpart for your plastic parts coating operations, then you must include a statement to this effect in your initial notification, and no other notifications are required under this subpart in regard to those plastic parts coating operations.

(c) *Notification of compliance status.* You must submit the notification of compliance status required by §63.9(h) no later than 30 calendar days following the end of the initial compliance period described in §63.4540, §63.4550, or §63.4560 that applies to your affected source. The notification of compliance status must contain the information specified in paragraphs (c)(1) through (11) of this section and in §63.9(h).

(1) Company name and address.

(2) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(3) Date of the report and beginning and ending dates of the reporting period. The reporting period is the initial compliance period described in §63.4540, §63.4550, or §63.4560 that applies to your affected source.

(4) Identification of the compliance option or options specified in §63.4491 that you used on each coating operation in the affected source during the initial compliance period.

(5) Statement of whether or not the affected source achieved the emission limitations for the initial compliance period.

(6) If you had a deviation, include the information in paragraphs (c)(6)(i) and (ii) of this section.

(i) A description and statement of the cause of the deviation.

(ii) If you failed to meet the applicable emission limit in §63.4490, include all the calculations you used to determine the kg (lb) organic HAP emitted per kg (lb) coating solids used. You do not need to submit information provided by the materials' suppliers or manufacturers, or test reports.

(7) For each of the data items listed in paragraphs (c)(7)(i) through (iv) of this section that is required by the compliance option(s) you used to demonstrate compliance with the emission limit, include an example of how you determined the value, including calculations and supporting data. Supporting data may include a copy of the information provided by the supplier or manufacturer of the example coating or material, or a summary of the results of testing conducted according to §63.4541(a), (b), or (c). You do not need to submit copies of any test reports.

(i) Mass fraction of organic HAP for one coating, for one thinner and/or other additive, and for one cleaning material.

(ii) Mass fraction of coating solids for one coating.

(iii) Density for one coating, one thinner and/or other additive, and one cleaning material, except that if you use the compliant material option, only the example coating density is required.

(iv) The amount of waste materials and the mass of organic HAP contained in the waste materials for which you are claiming an allowance in Equation 1 of §63.4551.

(8) The calculation of kg (lb) organic HAP emitted per kg (lb) coating solids used for the compliance option(s) you used, as specified in paragraphs (c)(8)(i) through (iii) of this section.

(i) For the compliant material option, provide an example calculation of the organic HAP content for one coating, using Equation 1 of §63.4541.

(ii) For the emission rate without add-on controls option, provide the calculation of the total mass of organic HAP emissions for each month; the calculation of the total mass of coating solids used each month; and the calculation of the 12-month organic HAP emission rate using Equations 1 and 1A through 1C, 2, and 3, respectively, of §63.4551.

### **§ 63.4520 What reports must I submit?**

(a) *Semiannual compliance reports.* You must submit semiannual compliance reports for each affected source according to the requirements of paragraphs (a)(1) through (7) of this section. The semiannual compliance reporting requirements may be satisfied by reports required under other parts of the Clean Air Act (CAA), as specified in paragraph (a)(2) of this section.

(1) *Dates.* Unless the Administrator has approved or agreed to a different schedule for submission of reports under §63.10(a), you must prepare and submit each semiannual compliance report according to the dates specified in paragraphs (a)(1)(i) through (iv) of this section. Note that the information reported

for each of the months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(i) The first semiannual compliance report must cover the first semiannual reporting period which begins the day after the end of the initial compliance period described in §63.4540, §63.4550, or §63.4560 that applies to your affected source and ends on June 30 or December 31, whichever date is the first date following the end of the initial compliance period.

(ii) Each subsequent semiannual compliance report must cover the subsequent semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(iii) Each semiannual compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(iv) For each affected source that is subject to permitting regulations pursuant to 40 CFR part 70 or 40 CFR part 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), you may submit the first and subsequent compliance reports according to the dates the permitting authority has established instead of according to the date specified in paragraph (a)(1)(iii) of this section.

(2) *Inclusion with title V report.* Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 40 CFR part 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a semiannual compliance report pursuant to this section along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the semiannual compliance report includes all required information concerning deviations from any emission limitation in this subpart, its submission will be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a semiannual compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permitting authority.

(3) *General requirements.* The semiannual compliance report must contain the information specified in paragraphs (a)(3)(i) through (vii) of this section, and the information specified in paragraphs (a)(4) through (7) and (c)(1) of this section that is applicable to your affected source.

(i) Company name and address.

(ii) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(iii) Date of report and beginning and ending dates of the reporting period. The reporting period is the 6-month period ending on June 30 or December 31. Note that the information reported for each of the 6 months in the reporting period will be based on the last 12 months of data prior to the date of each monthly calculation.

(iv) Identification of the compliance option or options specified in §63.4491 that you used on each coating operation during the reporting period. If you switched between compliance options during the reporting period, you must report the beginning and ending dates for each option you used.

(v) If you used the emission rate without add-on controls or the emission rate with add-on controls compliance option (§63.4491(b) or (c)), the calculation results for each rolling 12-month organic HAP emission rate during the 6-month reporting period.

(vi) If you used the predominant activity alternative (§63.4490(c)(1)), include the annual determination of predominant activity if it was not included in the previous semi-annual compliance report.

(vii) If you used the facility-specific emission limit alternative (§63.4490(c)(2)), include the calculation of the facility-specific emission limit for each 12-month compliance period during the 6-month reporting period.

(4) *No deviations.* If there were no deviations from the emission limitations in §§63.4490, 63.4492, and 63.4493 that apply to you, the semiannual compliance report must include a statement that there were no deviations from the emission limitations during the reporting period. If you used the emission rate with add-on controls option and there were no periods during which the continuous parameter monitoring systems (CPMS) were out-of-control as specified in §63.8(c)(7), the semiannual compliance report must include a statement that there were no periods during which the CPMS were out-of-control during the reporting period.

(5) *Deviations: Compliant material option.* If you used the compliant material option and there was a deviation from the applicable organic HAP content requirements in §63.4490, the semiannual compliance report must contain the information in paragraphs (a)(5)(i) through (iv) of this section.

(i) Identification of each coating used that deviated from the applicable emission limit, and each thinner and/or other additive, and cleaning material used that contained organic HAP, and the dates and time periods each was used.

(ii) The calculation of the organic HAP content (using Equation 1 of §63.4541) for each coating identified in paragraph (a)(5)(i) of this section. You do not need to submit background data supporting this calculation (e.g., information provided by coating suppliers or manufacturers, or test reports).

(iii) The determination of mass fraction of organic HAP for each thinner and/or other additive, and cleaning material identified in paragraph (a)(5)(i) of this section. You do not need to submit background data supporting this calculation (e.g., information provided by material suppliers or manufacturers, or test reports).

(iv) A statement of the cause of each deviation.

(6) *Deviations: Emission rate without add-on controls option.* If you used the emission rate without add-on controls option and there was a deviation from the applicable emission limit in §63.4490, the semiannual compliance report must contain the information in paragraphs (a)(6)(i) through (iii) of this section.

(i) The beginning and ending dates of each compliance period during which the 12-month organic HAP emission rate exceeded the applicable emission limit in §63.4490.

(ii) The calculations used to determine the 12-month organic HAP emission rate for the compliance period in which the deviation occurred. You must submit the calculations for Equations 1, 1A through 1C, 2, and 3 of §63.4551; and if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.4551(e)(4). You do not need to submit background data supporting these calculations (e.g., information provided by materials suppliers or manufacturers, or test reports).

(iii) A statement of the cause of each deviation.

### **§ 63.4530 What records must I keep?**

You must collect and keep records of the data and information specified in this section. Failure to collect and keep these records is a deviation from the applicable standard.

(a) A copy of each notification and report that you submitted to comply with this subpart, and the documentation supporting each notification and report.

(b) A current copy of information provided by materials suppliers or manufacturers, such as manufacturer's formulation data, or test data used to determine the mass fraction of organic HAP and density for each coating, thinner and/or other additive, and cleaning material, and the mass fraction of

coating solids for each coating. If you conducted testing to determine mass fraction of organic HAP, density, or mass fraction of coating solids, you must keep a copy of the complete test report. If you use information provided to you by the manufacturer or supplier of the material that was based on testing, you must keep the summary sheet of results provided to you by the manufacturer or supplier. You are not required to obtain the test report or other supporting documentation from the manufacturer or supplier.

(c) For each compliance period, the records specified in paragraphs (c)(1) through (4) of this section.

(1) A record of the coating operations on which you used each compliance option and the time periods (beginning and ending dates and times) for each option you used.

(2) For the compliant material option, a record of the calculation of the organic HAP content for each coating, using Equation 1 of §63.4541.

(3) For the emission rate without add-on controls option, a record of the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1, 1A through 1C, and 2 of §63.4551 and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to §63.4551(e)(4); the calculation of the total mass of coating solids used each month using Equation 2 of §63.4551; and the calculation of each 12-month organic HAP emission rate using Equation 3 of §63.4551.

(d) A record of the name and mass of each coating, thinner and/or other additive, and cleaning material used during each compliance period. If you are using the compliant material option for all coatings at the source, you may maintain purchase records for each material used rather than a record of the mass used.

(e) A record of the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each compliance period.

(f) A record of the mass fraction of coating solids for each coating used during each compliance period.

(g) If you use an allowance in Equation 1 of §63.4551 for organic HAP contained in waste materials sent to or designated for shipment to a treatment, storage, and disposal facility (TSDF) according to §63.4551(e)(4), you must keep records of the information specified in paragraphs (g)(1) through (3) of this section.

(1) The name and address of each TSDF to which you sent waste materials for which you use an allowance in Equation 1 of §63.4551, a statement of which subparts under 40 CFR parts 262, 264, 265, and 266 apply to the facility; and the date of each shipment.

(2) Identification of the coating operations producing waste materials included in each shipment and the month or months in which you used the allowance for these materials in Equation 1 of §63.4551.

(3) The methodology used in accordance with §63.4551(e)(4) to determine the total amount of waste materials sent to or the amount collected, stored, and designated for transport to a TSDF each month; and the methodology to determine the mass of organic HAP contained in these waste materials. This must include the sources for all data used in the determination, methods used to generate the data, frequency of testing or monitoring, and supporting calculations and documentation, including the waste manifest for each shipment.

(h) You must keep records of the date, time, and duration of each deviation.

#### **§ 63.4531 In what form and for how long must I keep my records?**

(a) Your records must be in a form suitable and readily available for expeditious review, according to §63.10(b)(1). Where appropriate, the records may be maintained as electronic spreadsheets or as a database.

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record on-site for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record according to §63.10(b)(1). You may keep the records off-site for the remaining 3 years.

### **Compliance Requirements for the Compliant Material Option**

#### **§ 63.4540 By what date must I conduct the initial compliance demonstration?**

You must complete the initial compliance demonstration for the initial compliance period according to the requirements in §63.4541. The initial compliance period begins on the applicable compliance date specified in §63.4483 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through that month plus the next 12 months. The initial compliance demonstration includes the calculations according to §63.4541 and supporting documentation showing that during the initial compliance period, you used no coating with an organic HAP content that exceeded the applicable emission limit in §63.4490, and that you used no thinners and/or other additives, or cleaning materials that contained organic HAP as determined according to §63.4541(a).

#### **§ 63.4541 How do I demonstrate initial compliance with the emission limitations?**

You may use the compliant material option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected source. You must use either the emission rate without add-on controls option or the emission rate with add-on controls option for any coating operation in the affected source for which you do not use this option. To demonstrate initial compliance using the compliant material option, the coating operation or group of coating operations must use no coating with an organic HAP content that exceeds the applicable emission limits in §63.4490 and must use no thinner and/or other additive, or cleaning material that contains organic HAP as determined according to this section. Any coating operation for which you use the compliant material option is not required to meet the operating limits or work practice standards required in §§63.4492 and 63.4493, respectively. You must meet all the requirements of this section. Use the procedures in this section on each coating, thinner and/or other additive, and cleaning material in the condition it is in when it is received from its manufacturer or supplier and prior to any alteration. You do not need to redetermine the organic HAP content of coatings, thinners and/or other additives, and cleaning materials that are reclaimed on-site (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coating operation for which you use the compliant material option, provided these materials in their condition as received were demonstrated to comply with the compliant material option.

(a) *Determine the mass fraction of organic HAP for each material used.* You must determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during the compliance period by using one of the options in paragraphs (a)(1) through (5) of this section.

(1) *Method 311 (appendix A to 40 CFR part 63).* You may use Method 311 for determining the mass fraction of organic HAP. Use the procedures specified in paragraphs (a)(1)(i) and (ii) of this section when performing a Method 311 test.

(i) Count each organic HAP that is measured to be present at 0.1 percent by mass or more for Occupational Safety and Health Administration (OSHA)-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is measured to be 0.5 percent of the material by mass, you do not have to count it. Express the mass fraction of each organic HAP you count as a value truncated to four places after the decimal point (e.g., 0.3791).

(ii) Calculate the total mass fraction of organic HAP in the test material by adding up the individual organic HAP mass fractions and truncating the result to three places after the decimal point (e.g., 0.763).

(2) *Method 24 (appendix A to 40 CFR part 60)*. For coatings, you may use Method 24 to determine the mass fraction of nonaqueous volatile matter and use that value as a substitute for mass fraction of organic HAP. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, you may use the alternative method contained in appendix A to this subpart, rather than Method 24. You may use the volatile fraction that is emitted, as measured by the alternative method in appendix A to this subpart, as a substitute for the mass fraction of organic HAP.

(3) *Alternative method*. You may use an alternative test method for determining the mass fraction of organic HAP once the Administrator has approved it. You must follow the procedure in §63.7(f) to submit an alternative test method for approval.

(4) *Information from the supplier or manufacturer of the material*. You may rely on information other than that generated by the test methods specified in paragraphs (a)(1) through (3) of this section, such as manufacturer's formulation data, if it represents each organic HAP that is present at 0.1 percent by mass or more for OSHA-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is 0.5 percent of the material by mass, you do not have to count it. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, you may rely on manufacturer's data that expressly states the organic HAP or volatile matter mass fraction emitted. If there is a disagreement between such information and results of a test conducted according to paragraphs (a)(1) through (3) of this section, then the test method results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(5) *Solvent blends*. Solvent blends may be listed as single components for some materials in data provided by manufacturers or suppliers. Solvent blends may contain organic HAP which must be counted toward the total organic HAP mass fraction of the materials. When test data and manufacturer's data for solvent blends are not available, you may use the default values for the mass fraction of organic HAP in these solvent blends listed in Table 3 or 4 to this subpart. If you use the tables, you must use the values in Table 3 for all solvent blends that match Table 3 entries according to the instructions for Table 3, and you may use Table 4 only if the solvent blends in the materials you use do not match any of the solvent blends in Table 3 and you know only whether the blend is aliphatic or aromatic. However, if the results of a Method 311 (appendix A to 40 CFR part 63) test indicate higher values than those listed on Table 3 or 4 to this subpart, the Method 311 results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(b) *Determine the mass fraction of coating solids for each coating*. You must determine the mass fraction of coating solids (kg (lb) of coating solids per kg (lb) of coating) for each coating used during the compliance period by a test, by information provided by the supplier or the manufacturer of the material, or by calculation, as specified in paragraphs (b)(1) through (3) of this section.

(1) *Method 24 (appendix A to 40 CFR part 60)*. Use Method 24 for determining the mass fraction of coating solids. For reactive adhesives in which some of the liquid fraction reacts to form solids, you may use the alternative method contained in appendix A to this subpart, rather than Method 24, to determine the mass fraction of coating solids.

(2) *Alternative method*. You may use an alternative test method for determining the solids content of each coating once the Administrator has approved it. You must follow the procedure in §63.7(f) to submit an alternative test method for approval.

(3) *Information from the supplier or manufacturer of the material*. You may obtain the mass fraction of coating solids for each coating from the supplier or manufacturer. If there is disagreement between such information and the test method results, then the test method results will take precedence unless,

after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct.

(c) *Calculate the organic HAP content of each coating.* Calculate the organic HAP content, kg (lb) organic HAP emitted per kg (lb) coating solids used, of each coating used during the compliance period using Equation 1 of this section:

$$H_c = \frac{W_c}{S_c} \quad (\text{Eq. 1})$$

Where:

$H_c$  = Organic HAP content of the coating, kg (lb) of organic HAP emitted per kg (lb) coating solids used.  
 $W_c$  = Mass fraction of organic HAP in the coating, kg organic HAP per kg coating, determined according to paragraph (a) of this section.

$S_c$  = Mass fraction of coating solids, kg coating solids per kg coating, determined according to paragraph (b) of this section.

(d) *Compliance demonstration.* The calculated organic HAP content for each coating used during the initial compliance period must be less than or equal to the applicable emission limit in §63.4490; and each thinner and/or other additive, and cleaning material used during the initial compliance period must contain no organic HAP, determined according to paragraph (a) of this section. You must keep all records required by §§63.4530 and 63.4531. As part of the notification of compliance status required in §63.4510, you must identify the coating operation(s) for which you used the compliant material option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because you used no coatings for which the organic HAP content exceeded the applicable emission limit in §63.4490, and you used no thinners and/or other additives, or cleaning materials that contained organic HAP, determined according to the procedures in paragraph (a) of this section.

#### **§ 63.4542 How do I demonstrate continuous compliance with the emission limitations?**

(a) For each compliance period to demonstrate continuous compliance, you must use no coating for which the organic HAP content (determined using Equation 1 of §63.4541) exceeds the applicable emission limit in §63.4490, and use no thinner and/or other additive, or cleaning material that contains organic HAP, determined according to §63.4541(a). A compliance period consists of 12 months. Each month, after the end of the initial compliance period described in §63.4540, is the end of a compliance period consisting of that month and the preceding 11 months.

(b) If you choose to comply with the emission limitations by using the compliant material option, the use of any coating, thinner and/or other additive, or cleaning material that does not meet the criteria specified in paragraph (a) of this section is a deviation from the emission limitations that must be reported as specified in §§63.4510(c)(6) and 63.4520(a)(5).

(c) As part of each semiannual compliance report required by §63.4520, you must identify the coating operation(s) for which you used the compliant material option. If there were no deviations from the applicable emission limit in §63.4490, submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because you used no coatings for which the organic HAP content exceeded the applicable emission limit in §63.4490, and you used no thinner and/or other additive, or cleaning material that contained organic HAP, determined according to §63.4541(a).

(d) You must maintain records as specified in §§63.4530 and 63.4531.

#### **Compliance Requirements for the Emission Rate Without Add-On Controls Option**

##### **§ 63.4550 By what date must I conduct the initial compliance demonstration?**

You must complete the initial compliance demonstration for the initial compliance period according to the requirements of §63.4551. The initial compliance period begins on the applicable compliance date

specified in §63.4483 and ends on the last day of the 12th month following the compliance date. If the compliance date occurs on any day other than the first day of a month, then the initial compliance period extends through the end of that month plus the next 12 months. You must determine the mass of organic HAP emissions and mass of coating solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The initial compliance demonstration includes the calculations according to §63.4551 and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in §63.4490.

#### **§ 63.4551 How do I demonstrate initial compliance with the emission limitations?**

You may use the emission rate without add-on controls option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected source. You must use either the compliant material option or the emission rate with add-on controls option for any coating operation in the affected source for which you do not use this option. To demonstrate initial compliance using the emission rate without add-on controls option, the coating operation or group of coating operations must meet the applicable emission limit in §63.4490, but is not required to meet the operating limits or work practice standards in §§63.4492 and 63.4493, respectively. You must meet all the requirements of this section. When calculating the organic HAP emission rate according to this section, do not include any coatings, thinners and/or other additives, or cleaning materials used on coating operations for which you use the compliant material option or the emission rate with add-on controls option. You do not need to redetermine the mass of organic HAP in coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site (or reclaimed off-site if you have documentation showing that you received back the exact same materials that were sent off-site) and reused in the coating operation for which you use the emission rate without add-on controls option. If you use coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site, the amount of each used in a month may be reduced by the amount of each that is reclaimed. That is, the amount used may be calculated as the amount consumed to account for materials that are reclaimed.

(a) *Determine the mass fraction of organic HAP for each material.* Determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each month according to the requirements in §63.4541(a).

(b) *Determine the mass fraction of coating solids.* Determine the mass fraction of coating solids (kg (lb) of coating solids per kg (lb) of coating) for each coating used during each month according to the requirements in §63.4541(b).

(c) *Determine the density of each material.* Determine the density of each liquid coating, thinner and/or other additive, and cleaning material used during each month from test results using ASTM Method D1475–98, “Standard Test Method for Density of Liquid Coatings, Inks, and Related Products” (incorporated by reference, see §63.14), information from the supplier or manufacturer of the material, or reference sources providing density or specific gravity data for pure materials. If there is disagreement between ASTM Method D1475–98 and other such information sources, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of the enforcement agency that the formulation data are correct. If you purchase materials or monitor consumption by weight instead of volume, you do not need to determine material density. Instead, you may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, 1C, and 2 of this section.

(d) *Determine the volume of each material used.* Determine the volume (liters) of each coating, thinner and/or other additive, and cleaning material used during each month by measurement or usage records. If you purchase materials or monitor consumption by weight instead of volume, you do not need to determine the volume of each material used. Instead, you may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, 1C, and 2 of this section.

(e) *Calculate the mass of organic HAP emissions.* The mass of organic HAP emissions is the combined mass of organic HAP contained in all coatings, thinners and/or other additives, and cleaning materials

used during each month minus the organic HAP in certain waste materials. Calculate the mass of organic HAP emissions using Equation 1 of this section.

$$H_e = A + B + C - R_w \quad (\text{Eq. 1})$$

Where:

$H_e$  = Total mass of organic HAP emissions during the month, kg.

$A$  = Total mass of organic HAP in the coatings used during the month, kg, as calculated in Equation 1A of this section.

$B$  = Total mass of organic HAP in the thinners and/or other additives used during the month, kg, as calculated in Equation 1B of this section.

$C$  = Total mass of organic HAP in the cleaning materials used during the month, kg, as calculated in Equation 1C of this section.

$R_w$  = Total mass of organic HAP in waste materials sent or designated for shipment to a hazardous waste TSDF for treatment or disposal during the month, kg, determined according to paragraph (e)(4) of this section. (You may assign a value of zero to  $R_w$  if you do not wish to use this allowance.)

(1) Calculate the kg organic HAP in the coatings used during the month using Equation 1A of this section:

$$A = \sum_{i=1}^m (Vol_{c,i}) (D_{c,i}) (W_{c,i}) \quad (\text{Eq. 1A})$$

Where:

$A$  = Total mass of organic HAP in the coatings used during the month, kg.

$Vol_{c,i}$  = Total volume of coating,  $i$ , used during the month, liters.

$D_{c,i}$  = Density of coating,  $i$ , kg coating per liter coating.

$W_{c,i}$  = Mass fraction of organic HAP in coating,  $i$ , kg organic HAP per kg coating. For reactive adhesives as defined in §63.4581, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to this subpart.

$m$  = Number of different coatings used during the month.

(2) Calculate the kg of organic HAP in the thinners and/or other additives used during the month using Equation 1B of this section:

$$B = \sum_{j=1}^n (Vol_{t,j}) (D_{t,j}) (W_{t,j}) \quad (\text{Eq. 1B})$$

Where:

$B$  = Total mass of organic HAP in the thinners and/or other additives used during the month, kg.

$Vol_{t,j}$  = Total volume of thinner and/or other additive,  $j$ , used during the month, liters.

$D_{t,j}$  = Density of thinner and/or other additive,  $j$ , kg per liter.

$W_{t,j}$  = Mass fraction of organic HAP in thinner and/or other additive,  $j$ , kg organic HAP per kg thinner and/or other additive. For reactive adhesives as defined in §63.4581, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to this subpart.

$n$  = Number of different thinners and/or other additives used during the month.

(3) Calculate the kg organic HAP in the cleaning materials used during the month using Equation 1C of this section:

$$C = \sum_{k=1}^p (Vol_{s,k}) (D_{s,k}) (W_{s,k}) \quad (\text{Eq. 1C})$$

Where:

$C$  = Total mass of organic HAP in the cleaning materials used during the month, kg.

$Vol_{s,k}$  = Total volume of cleaning material,  $k$ , used during the month, liters.

$D_{s,k}$  = Density of cleaning material,  $k$ , kg per liter.

$W_{s,k}$  = Mass fraction of organic HAP in cleaning material,  $k$ , kg organic HAP per kg material.

$p$  = Number of different cleaning materials used during the month.

(4) If you choose to account for the mass of organic HAP contained in waste materials sent or designated for shipment to a hazardous waste TSDF in Equation 1 of this section, then you must determine the mass according to paragraphs (e)(4)(i) through (iv) of this section.

(i) You may only include waste materials in the determination that are generated by coating operations in the affected source for which you use Equation 1 of this section and that will be treated or disposed of by a facility that is regulated as a TSDF under 40 CFR part 262, 264, 265, or 266. The TSDF may be either off-site or on-site. You may not include organic HAP contained in wastewater.

(ii) You must determine either the amount of the waste materials sent to a TSDF during the month or the amount collected and stored during the month and designated for future transport to a TSDF. Do not include in your determination any waste materials sent to a TSDF during a month if you have already included them in the amount collected and stored during that month or a previous month.

(iii) Determine the total mass of organic HAP contained in the waste materials specified in paragraph (e)(4)(ii) of this section.

(iv) You must document the methodology you use to determine the amount of waste materials and the total mass of organic HAP they contain, as required in §63.4530(g). If waste manifests include this information, they may be used as part of the documentation of the amount of waste materials and mass of organic HAP contained in them.

(f) *Calculate the total mass of coating solids used.* Determine the total mass of coating solids used, kg, which is the combined mass of coating solids for all the coatings used during each month, using Equation 2 of this section:

$$M_{st} = \sum_{i=1}^m (\text{Vol}_{c,i}) (D_{c,i}) (M_{s,i}) \quad (\text{Eq. 2})$$

Where:

$M_{st}$  = Total mass of coating solids used during the month, kg.

$\text{Vol}_{c,i}$  = Total volume of coating, i, used during the month, liters.

$D_{c,i}$  = Density of coating, i, kgs per liter coating, determined according to §63.4551(c).

$M_{s,i}$  = Mass fraction of coating solids for coating, i, kgs solids per kg coating, determined according to §63.4541(b).

m = Number of coatings used during the month.

(g) *Calculate the organic HAP emission rate.* Calculate the organic HAP emission rate for the compliance period, kg (lb) organic HAP emitted per kg (lb) coating solids used, using Equation 3 of this section:

$$H_{yr} = \frac{\sum_{y=1}^n H_e}{\sum_{y=1}^n M_{st}} \quad (\text{Eq. 3})$$

Where:

$H_{yr}$  = Average organic HAP emission rate for the compliance period, kg organic HAP emitted per kg coating solids used.

$H_e$  = Total mass of organic HAP emissions from all materials used during month, y, kg, as calculated by Equation 1 of this section.

$M_{st}$  = Total mass of coating solids used during month, y, kg, as calculated by Equation 2 of this section.

y = Identifier for months.

n = Number of full or partial months in the compliance period (for the initial compliance period, n equals 12 if the compliance date falls on the first day of a month; otherwise n equals 13; for all following compliance periods, n equals 12).

(h) *Compliance demonstration.* The organic HAP emission rate for the initial compliance period calculated using Equation 3 of this section must be less than or equal to the applicable emission limit

for each subcategory in §63.4490. You must keep all records as required by §§63.4530 and 63.4531. As part of the notification of compliance status required by §63.4510, you must identify the coating operation(s) for which you used the emission rate without add-on controls option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because the organic HAP emission rate was less than or equal to the applicable emission limit in §63.4490, determined according to the procedures in this section.

**§ 63.4552 How do I demonstrate continuous compliance with the emission limitations?**

(a) To demonstrate continuous compliance, the organic HAP emission rate for each compliance period, determined according to §63.4551(a) through (g), must be less than or equal to the applicable emission limit in §63.4490. A compliance period consists of 12 months. Each month after the end of the initial compliance period described in §63.4550 is the end of a compliance period consisting of that month and the preceding 11 months. You must perform the calculations in §63.4551(a) through (g) on a monthly basis using data from the previous 12 months of operation.

(b) If the organic HAP emission rate for any 12-month compliance period exceeded the applicable emission limit in §63.4490, this is a deviation from the emission limitation for that compliance period and must be reported as specified in §§63.4510(c)(6) and 63.4520(a)(6).

(c) As part of each semiannual compliance report required by §63.4520, you must identify the coating operation(s) for which you used the emission rate without add-on controls option. If there were no deviations from the emission limitations, you must submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable emission limit in §63.4490, determined according to §63.4551(a) through (g).

(d) You must maintain records as specified in §§63.4530 and 63.4531.

**Other Requirements and Information**

**§ 63.4580 Who implements and enforces this subpart?**

(a) This subpart can be implemented and enforced by us, the U.S. Environmental Protection Agency (EPA), or a delegated authority such as your State, local, or tribal agency. If the Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the EPA) has the authority to implement and enforce this subpart. You should contact your EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are listed in paragraphs (c)(1) through (4) of this section:

(1) Approval of alternatives to the requirements in §§63.4481 through 4483 and §§63.4490 through 4493.

(2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.

(3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.

(4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

### **§ 63.4581 What definitions apply to this subpart?**

Terms used in this subpart are defined in the CAA, in 40 CFR 63.2, and in this section as follows:

*Additive* means a material that is added to a coating after purchase from a supplier (e.g., catalysts, activators, accelerators).

*Add-on control* means an air pollution control device, such as a thermal oxidizer or carbon adsorber, that reduces pollution in an air stream by destruction or removal before discharge to the atmosphere.

*Adhesive, adhesive coating* means any chemical substance that is applied for the purpose of bonding two surfaces together. Products used on humans and animals, adhesive tape, contact paper, or any other product with an adhesive incorporated onto or in an inert substrate shall not be considered adhesives under this subpart.

*Assembled on-road vehicle coating* means any coating operation in which coating is applied to the surface of some component or surface of a fully assembled motor vehicle or trailer intended for on-road use including, but not limited to, components or surfaces on automobiles and light-duty trucks that have been repaired after a collision or otherwise repainted, fleet delivery trucks, and motor homes and other recreational vehicles (including camping trailers and fifth wheels). Assembled on-road vehicle coating includes the concurrent coating of parts of the assembled on-road vehicle that are painted off-vehicle to protect systems, equipment, or to allow full coverage. Assembled on-road vehicle coating does not include surface coating operations that meet the applicability criteria of the Automobiles and Light-Duty Trucks NESHAP. Assembled on-road vehicle coating also does not include the use of adhesives, sealants, and caulks used in assembling on-road vehicles.

*Automotive lamp coating* means any coating operation in which coating is applied to the surface of some component of the body of an exterior automotive lamp, including the application of reflective argent coatings and clear topcoats. Exterior automotive lamps include head lamps, tail lamps, turn signals, brake lights, and side marker lights. Automotive lamp coating does not include any coating operation performed on an assembled on-road vehicle.

*Capture device* means a hood, enclosure, room, floor sweep, or other means of containing or collecting emissions and directing those emissions into an add-on air pollution control device.

*Capture efficiency or capture system efficiency* means the portion (expressed as a percentage) of the pollutants from an emission source that is delivered to an add-on control device.

*Capture system* means one or more capture devices intended to collect emissions generated by a coating operation in the use of coatings or cleaning materials, both at the point of application and at subsequent points where emissions from the coatings and cleaning materials occur, such as flashoff, drying, or curing. As used in this subpart, multiple capture devices that collect emissions generated by a coating operation are considered a single capture system.

*Cleaning material* means a solvent used to remove contaminants and other materials, such as dirt, grease, oil, and dried or wet coating (e.g., depainting), from a substrate before or after coating application or from equipment associated with a coating operation, such as spray booths, spray guns, racks, tanks, and hangers. Thus, it includes any cleaning material used on substrates or equipment or both.

*Coating* means a material applied to a substrate for decorative, protective, or functional purposes. Such materials include, but are not limited to, paints, sealants, liquid plastic coatings, caulks, inks, adhesives, and maskants. Decorative, protective, or functional materials that consist only of protective oils for metal, acids, bases, or any combination of these substances, or paper film or plastic film which may be pre-coated with an adhesive by the film manufacturer, are not considered coatings for the purposes of this subpart. A liquid plastic coating means a coating made from fine particle-size polyvinyl chloride (PVC) in solution (also referred to as a plastisol).

*Coating operation* means equipment used to apply cleaning materials to a substrate to prepare it for coating application (surface preparation) or to remove dried coating; to apply coating to a substrate (coating application) and to dry or cure the coating after application; or to clean coating operation equipment (equipment cleaning). A single coating operation may include any combination of these types of equipment, but always includes at least the point at which a given quantity of coating or cleaning material is applied to a given part and all subsequent points in the affected source where organic HAP are emitted from the specific quantity of coating or cleaning material on the specific part. There may be multiple coating operations in an affected source. Coating application with handheld, non-refillable aerosol containers, touch-up markers, or marking pens is not a coating operation for the purposes of this subpart.

*Coatings solids* means the nonvolatile portion of the coating that makes up the dry film.

*Continuous parameter monitoring system (CPMS)* means the total equipment that may be required to meet the data acquisition and availability requirements of this subpart, used to sample, condition (if applicable), analyze, and provide a record of coating operation, or capture system, or add-on control device parameters.

*Controlled coating operation* means a coating operation from which some or all of the organic HAP emissions are routed through an emission capture system and add-on control device.

*Deviation* means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

- (1) Fails to meet any requirement or obligation established by this subpart including but not limited to, any emission limit or operating limit or work practice standard;
- (2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or
- (3) Fails to meet any emission limit, or operating limit, or work practice standard in this subpart during startup, shutdown, or malfunction, regardless of whether or not such failure is permitted by this subpart.

*Emission limitation* means the aggregate of all requirements associated with a compliance option including emission limit, operating limit, work practice standard, etc.

*Enclosure* means a structure that surrounds a source of emissions and captures and directs the emissions to an add-on control device.

*Exempt compound* means a specific compound that is not considered a VOC due to negligible photochemical reactivity. The exempt compounds are listed in 40 CFR 51.100(s).

*Facility maintenance* means the routine repair or renovation (including the surface coating) of the tools, equipment, machinery, and structures that comprise the infrastructure of the affected facility and that are necessary for the facility to function in its intended capacity.

*General use coating* means any coating operation that is not an automotive lamp, TPO, or assembled on-road vehicle coating operation.

*Hobby shop* means any surface coating operation, located at an affected source, that is used exclusively for personal, noncommercial purposes by the affected source's employees or assigned personnel.

*Manufacturer's formulation data* means data on a material (such as a coating) that are supplied by the material manufacturer based on knowledge of the ingredients used to manufacture that material, rather than based on testing of the material with the test methods specified in §63.4541. Manufacturer's formulation data may include, but are not limited to, information on density, organic HAP content, volatile organic matter content, and coating solids content.

*Mass fraction of coating solids* means the ratio of the mass of solids (also known as the mass of nonvolatiles) to the mass of a coating in which it is contained; kg of coating solids per kg of coating.

*Mass fraction of organic HAP* means the ratio of the mass of organic HAP to the mass of a material in which it is contained, expressed as kg of organic HAP per kg of material.

*Month* means a calendar month or a pre-specified period of 28 days to 35 days to allow for flexibility in recordkeeping when data are based on a business accounting period.

*Non-HAP coating* means, for the purposes of this subpart, a coating that contains no more than 0.1 percent by mass of any individual organic HAP that is an OSHA-defined carcinogen as specified in 29 CFR 1910.1200(d)(4) and no more than 1.0 percent by mass for any other individual HAP.

*Organic HAP content* means the mass of organic HAP emitted per mass of coating solids used for a coating calculated using Equation 1 of §63.4541. The organic HAP content is determined for the coating in the condition it is in when received from its manufacturer or supplier and does not account for any alteration after receipt. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, organic HAP content is the mass of organic HAP that is emitted, rather than the organic HAP content of the coating as it is received.

*Permanent total enclosure (PTE)* means a permanently installed enclosure that meets the criteria of Method 204 of appendix M, 40 CFR part 51, for a PTE and that directs all the exhaust gases from the enclosure to an add-on control device.

*Personal watercraft* means a vessel (boat) which uses an inboard motor powering a water jet pump as its primary source of motive power and which is designed to be operated by a person or persons sitting, standing, or kneeling on the vessel, rather than in the conventional manner of sitting or standing inside the vessel.

*Plastic part and product* means any piece or combination of pieces of which at least one has been formed from one or more resins. Such pieces may be solid, porous, flexible or rigid.

*Protective oil* means an organic material that is applied to metal for the purpose of providing lubrication or protection from corrosion without forming a solid film. This definition of protective oil includes, but is not limited to, lubricating oils, evaporative oils (including those that evaporate completely), and extrusion oils.

*Reactive adhesive* means adhesive systems composed, in part, of volatile monomers that react during the adhesive curing reaction, and, as a result, do not evolve from the film during use. These volatile components instead become integral parts of the adhesive through chemical reaction. At least 70 percent of the liquid components of the system, excluding water, react during the process.

*Research or laboratory facility* means a facility whose primary purpose is for research and development of new processes and products, that is conducted under the close supervision of technically trained personnel, and is not engaged in the manufacture of final or intermediate products for commercial purposes, except in a *de minimis* manner.

*Responsible official* means responsible official as defined in 40 CFR 70.2.

*Startup, initial* means the first time equipment is brought online in a facility.

*Surface preparation* means use of a cleaning material on a portion of or all of a substrate. This includes use of a cleaning material to remove dried coating, which is sometimes called depainting.

*Temporary total enclosure* means an enclosure constructed for the purpose of measuring the capture efficiency of pollutants emitted from a given source as defined in Method 204 of appendix M, 40 CFR part 51.

*Thermoplastic olefin (TPO)* means polyolefins (blends of polypropylene, polyethylene and its copolymers). This also includes blends of TPO with polypropylene and polypropylene alloys including,

but not limited to, thermoplastic elastomer (TPE), TPE polyurethane (TPU), TPE polyester (TPEE), TPE polyamide (TPAE), and thermoplastic elastomer polyvinyl chloride (TPVC).

*Thermoplastic olefin (TPO) coating* means any coating operation in which the coatings are components of a system of coatings applied to a TPO substrate, including adhesion promoters, primers, color coatings, clear coatings and topcoats. Thermoplastic olefin coating does not include the coating of TPO substrates on assembled on-road vehicles.

*Thinner* means an organic solvent that is added to a coating after the coating is received from the supplier.

*Total volatile hydrocarbon (TVH)* means the total amount of nonaqueous volatile organic matter determined according to Methods 204 and 204A through 204F of appendix M to 40 CFR part 51 and substituting the term TVH each place in the methods where the term VOC is used. The TVH includes both VOC and non-VOC.

*Uncontrolled coating operation* means a coating operation from which none of the organic HAP emissions are routed through an emission capture system and add-on control device.

*Volatile organic compound (VOC)* means any compound defined as VOC in 40 CFR 51.100(s).

*Wastewater* means water that is generated in a coating operation and is collected, stored, or treated prior to being discarded or discharged.

**Table 2 to Subpart PPPP of Part 63—Applicability of General Provisions to Subpart PPPP of Part 63**

You must comply with the applicable General Provisions requirements according to the following table:

Citation	Subject	Applicable to Subpart PPPP	Explanation
§ 63.1(a)(1)-(14)	General Applicability.	Yes.....	
§ 63.1(b)(1)-(3)..	Initial Applicability Determination	Yes.....	Applicability to subpart PPPP is also specified in §63.4481.
§ 63.1(c)(1).....	Applicability After Standard Established.	Yes.....	
§ 63.1(c)(2)-(3)..	Applicability of Permit Program for Area Sources.	No.....	Area sources are not subject to subpart PPPP.
§ 63.1(c)(4)-(5)..	Extensions and Notifications.	Yes.....	
§ 63.1(e).....	Applicability of Permit Program Before Relevant Standard is Set	Yes.....	
§ 63.2.....	Definitions.....	Yes.....	Additional Definitions are specified in § 63.3981
§ 63.1(a)-(c)...	Units and Abbreviations.	Yes.....	
§ 63.4(a)(1)-(5)..	Prohibited Activities.	Yes.....	
§ 63.4(b)-(c).....	Circumvention/Severability.	Yes.....	
§ 63.5(a).....	Construction/Reconstruction.	Yes.....	
§ 63.5(b)(1)-(6)..	Requirements for Existing Newly Constructed, and Reconstructed Sources.	Yes.....	
§ 63.5(d).....	Application for Approval of Construction/Reconstruction.	Yes.....	
§ 63.5(e).....	Approval of Construction/Reconstruction.	Yes.....	
§ 63.5(f).....	Approval of Construction/Reconstruction Based on Prior State Review.	Yes.....	
§ 63.6(a).....	Compliance With Standards and Maintenance Requirements-Applicability.	Yes.....	
§ 63.6(b)(1)-(7)..	Compliance Dates for New and Reconstructed Sources.	Yes.....	Section 63.4483 specifies the compliance dates.
§ 63.6(c)(1)-(5)..	Compliance Dates for Existing Sources.	Yes.....	Section 63.4483 specifies the compliance dates.
§ 63.6(e)(1)-(2)..	Operation and Maintenance.	Yes.....	
§ 63.6(e)(3).....	Startup, Shutdown, and Malfunction Plan.	Yes...	Only sources using an add-on control device to comply with the standard must complete startup, shutdown, and malfunction plans.
§ 63.6(f)(1).....	Compliance Except During Startup, Shutdown, and Malfunction.	Yes....	Applies only to sources using an add-on control device to comply with the standard.

Citation	Subject	Applicable to Subpart PPPP	Explanation
§ 63.6(f)(2)-(3)..	Methods for Determining Compliance.	Yes.....	
§ 63.6(g)(1)-(3)..	Use of an Alternative Standard.	Yes.....	
§ 63.6(h).....	Compliance With Opacity/Visible Emission Standards.	No.....	Subpart PPPP does not establish opacity standards and does not require continuous opacity monitoring systems (COMS).
§ 63.6(i)(1)-(16).	Extension of Compliance.	Yes.....	
§ 63.6(j).....	Presidential Compliance Exemption.	Yes.....	
§ 63.7(a)(1).....	Performance Test Requirements-Applicability.	Yes.....	Applies to all affected sources.Additional requirements for performance testing are specified in §§ 63.4564, 63.4565, and 63.4566.
§ 63.7(a)(2).....	Performance Test Requirements-Dates.	Yes.....	Applies only to performance tests for capture system and control device efficiency at sources using these to comply with the standard. Section 63.4560 specifies the schedule for performance test requirements that are earlier than those specified in §63.7(a)(2).
§ 63.7(a)(3).....	Performance Tests Required By the Administrator.	Yes.....	
§ 63.7(b)-(e).....	Performance Test Requirements-Notification, Quality Assurance, Facilities Necessary for Safe Testing, Conditions During Test.	Yes.....	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.7(f).....	Performance Test Requirements-Use of Alternative Test Method.	Yes....	Applies to all test methods except those used to determine capture system efficiency.
§ 63.7(g)-(h).....	Performance Test Requirements-Data Analysis, Recordkeeping, Reporting, Waiver of Test.	Yes.....	Applies only to performance tests for capture system and add-on control device efficiency at sources using these to comply with the standard.
§ 63.8(a)(1)-(3)..	Monitoring Requirements-Applicability.	Yes.....	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for monitoring are specified in §63.4568.
§ 63.8(a)(4).....	Additional Monitoring Requirements.	No.....	Subpart PPPP does not have monitoring requirements for flares.
§ 63.8(b).....	Conduct of Monitoring.	Yes....	
§ 63.8(c)(1)-(3)..	Continuous Monitoring Systems (CMS) Operation and Maintenance.	Yes....	Applies only to monitoring of capture system and add-on control device efficiency at sources using these to comply with the standard. Additional requirements for CMS operations and maintenance are specified in §63.4568.

Citation	Subject	Applicable to Subpart PPPP	Explanation
§ 63.8(c)(4).....	CMS.....	No....	§63.4568 specifies the requirements for the operation of CMS for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(5).....	COMS.....	No.....	Subpart PPPP does not have opacity or visible emission standards.
§ 63.8(c)(6).....	CMS Requirements.....	No.....	Section 63.4568 specifies the requirements for monitoring systems for capture systems and add-on control devices at sources using these to comply.
§ 63.8(c)(7).....	CMS Out-of-Control Periods.	Yes....	
§ 63.8(c)(8).....	CMS Out-of-Control Periods and Reporting.	No.....	§63.4520 requires reporting of CMS out-of-control periods.
§ 63.8(d)-(e).....	Quality Control Program and CMS Performance Evaluation.	No.....	Subpart PPPP does not require the use of continuous emissions monitoring systems.
§ 63.8(f)(1)-(5)..	Use of an Alternative Monitoring Method.	Yes....	
§ 63.8(f)(6).....	Alternative to Relative Accuracy Test.	No.....	Subpart PPPP does not require the use of continuous emissions monitoring systems.
§ 63.8(g)(1)-(5)..	Data Reduction.....	No.....	Sections 63.4567 and 63.4568 specify monitoring data reduction.
§ 63.9(a)-(d).....	Notification Requirements.	Yes....	
§ 63.9(e).....	Notification of Performance Test.	Yes.....	Applies only to capture system and add-on control device performance tests at sources using these to comply with the standard.
§ 63.9(f).....	Notification of Visible Emissions/Opacity Test.	No.....	Subpart PPPP does not have opacity or visible emission standards.
§ 63.9(g)(1)-(3)..	Additional Notifications When Using CMS.	No.....	Subpart PPPP does not require the use of continuous emissions monitoring systems.
§ 63.9(h).....	Notification of Compliance Status.	Yes.....	Section 63.4510 specifies the dates for submitting the notification of compliance status.
§ 63.9(i).....	Adjustment of Submittal Deadlines.	Yes.....	
§ 63.9(j).....	Change in Previous Information.	Yes.....	
§ 63.10(a).....	Recordkeeping/Reporting-Applicability and General Information	Yes.....	
§ 63.10(b)(1).....	General Recordkeeping Requirements.	Yes.....	Additional requirements are specified in §§ 63.4530 and 63.4531.
§ 63.10(b)(2) (i)-(v).....	Recordkeeping Relevant to Startup, Shutdown, and Malfunction Periods and CMS.	Yes.....	Requirements for startup, shutdown, and malfunction records only apply to add-on control devices used to comply with the standard.
§ 63.10(b)(2) (vi)-(xi).....	.....	Yes....	

Citation	Subject	Applicable to Subpart PPPP	Explanation
§ 63.10(b)(2) (xii)	Records.....	Yes....	
§ 63.10(b)(2)(xiii)	.....	No....	Subpart PPPP does not require the use of continuous emissions monitoring systems.
§ 63.10(b)(2)(xiv)	.....	Yes....	
§ 63.10(b)(3).....	Recordkeeping Requirements for Applicability Determinations.	Yes....	
§ 63.10(c)(1)-(6)..	Additional Recordkeeping Requirements for Sources with CMS.	Yes....	
§ 63.10(c) (7)-(8)	.....	No....	The same records are required in §63.3920(a)(7).
§ 63.10(c) (9)-(15)	.....	Yes...	
§ 63.10(d)(1).....	General Reporting Requirements.	Yes...	Additional Requirements are specified in §63.4520.
§ 63.10(d)(2).....	Report of Performance Test Results.	Yes.....	Additional requirements are specified in §63.4520(b).
§ 63.10(d)(3).....	Reporting Opacity or Visible Emissions Observations.	No.....	Subpart PPPP does not require opacity or visible emissions observations.
§ 63.10(d)(4).....	Progress Reports for Sources With Compliance Extensions.	Yes.....	
§ 63.10(d)(5).....	Startup, Shutdown, and Malfunction Reports.	Yes.....	Applies only to add-on control devices at sources using these to comply with the standard.
§ 63.10(e) (1)-(2).	Additional CMS Reports	No.....	Subpart PPPP does not require the use of continuous emissions monitoring systems.
§ 63.10(e) (3).....	Excess Emissions/CMS Performance Reports.	No.....	Section 63.4520 (b) specifies the contents of periodic compliance reports.
§ 63.10(e) (4)....	COMS Data Reports.....	No.....	Subpart PPPP does not specify requirements for opacity or COMS.
§ 63.10(f).....	Recordkeeping/Reporting Waiver.	Yes.....	
§ 63.11.....	Control Device Requirements/Flares.	No.....	Subpart PPPP does not specify use of flares for compliance.
§ 63.12.....	State Authority and Delegations.	Yes.....	
§ 63.13.....	Addresses.....	Yes.....	
§ 63.14.....	Incorporation by Reference	Yes.....	
§ 63.15.....	Availability of Information/Confidentiality.	Yes.....	

**Table 3 to Subpart PPPP of Part 63—Default Organic HAP Mass Fraction for Solvents and Solvent Blends**

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data and which match either the solvent blend name or the chemical abstract series (CAS) number. If a solvent blend matches both the name and CAS number for an entry, that entry's organic HAP mass fraction must be used for that solvent blend. Otherwise, use the organic HAP mass fraction for the entry matching either the solvent blend name or CAS number, or use the organic HAP mass fraction from table 4 to this subpart if neither the name or CAS number match.

Solvent/solvent blend	CAS. No.	Average organic HAP mass fraction	Typical Organic HAP, percent by mass
1. Toluene.....	108-88-3	1.00	Toluene.
2. Xylene(s).....	1330-20-7	1.00	Xylenes, ethylbenzene.
3. Hexane.....	110-54-3	0.50	n-hexane.
4. n-Hexane.....	110-54-3	1.00	n-hexane.
5. Ethylbenzene.....	100-41-4	1.00	Ethylbenzene.
6. Aliphatic 140.....		0.00	None.
7. Aromatic 100.....		0.02	1% xylene, 1% cumene.
8. Aromatic 150.....		0.09	Naphthalene.
9. Aromatic naphtha.....	64742-95-6	0.02	1% xylene, 1% cumene.
10. Aromatic solvent.....	64742-94-5	0.10	Naphthalene.
11. Exempt mineral spirits..	8032-32-4	0.00	None.
12. Ligroines (VM & P).....	8032-32-4	0.00	None.
13. Lactol spirits.....	64742-89-6	0.15	Toluene.
14. Low aromatic white spirit.	64742-82-1	0.00	None.
15. Mineral spirits.....	64742-88-7	0.01	Xylenes.
16. Hydrotreated naphtha....	64742-48-9	0.00	None.
17. Hydrotreated light distillate.....	64742-47-8	0.00	Toluene.
18. Stoddard solvent.....	8052-41-3	0.01	Xylenes.
19. Super high-flash naphtha	64742-95-6	0.05	Xylenes.
20. Varsol solvent.....	8052-49-3	0.01	0.5% xylenes, 0.5% ethylbenzene.
21. VM & P naphtha.....	64742-89-8	0.06	3% toluene, 3% xylene.
22. Petroleum distillate mixture....	68477-31-6	0.08	4% naphthalene 4% biphenyl.

**Table 4 to Subpart PPPP of Part 63—Default Organic HAP Mass Fraction for Petroleum Solvent Groups<sup>a</sup>**

You may use the mass fraction values in the following table for solvent blends for which you do not have test data or manufacturer's formulation data.

Solvent type	Average organic HAP mass fraction	Typical organic HAP, percent by mass
Aliphatic <sup>b</sup>	0.03	1% Xylene, 1% Toluene, and 1% Ethylbenzene.
Aromatic <sup>c</sup>	0.06	4% Xylene, 1% Toluene, and 1% Ethylbenzene.

<sup>a</sup> Use this table only if the solvent blend does not match any of the solvent blends in Table 3 to this subpart by either solvent blend name or CAS number and you only know whether the blend is aliphatic or aromatic.

<sup>b</sup> Mineral Spirits 135, Mineral Spirits 150 EC, Naphtha, Mixed Hydrocarbon, Aliphatic Hydrocarbon, Aliphatic Naphtha, Naphthol Spirits, Petroleum Spirits, Petroleum Oil, Petroleum Naphtha, Solvent Naphtha, Solvent Blend.

<sup>c</sup> Medium-flash Naphtha, High-flash Naphtha, Aromatic Naphtha, Light Aromatic Naphtha, Light Aromatic Hydrocarbons, Aromatic Hydrocarbons, Light Aromatic Solvent.

**E.2.3 One Time Deadlines Relating to NESHAP for Surface Coating of Plastic Parts and Products [40 CFR Part 63, Subpart PPPP] [326 IAC 20-81]**

- 
- (a) The Permittee submit Initial Notification on March 10, 2005 [40 CFR 63.4510(b)].
  - (b) The Permittee shall conduct initial compliance demonstrations no later than April 30, 2008 [40 CFR 63.4540, 40 CFR 63.4550 and 63.4560(b)(3)].
  - (c) The Permittee shall submit a notification of compliance status no later than May 30, 2008 [40 CFR 63.4510 (e)].
  - (d) The Permittee shall submit its first Semi-annual Compliance Report no later than July 31, 2008 [40 CFR 63.4520(a)(1)].

### SECTION E.3

### FACILITY OPERATION CONDITIONS

#### **Emissions Unit Description [326 IAC 2-7-5(15)]:**

- (a) A spray/bake booth, identified as H-1, constructed June 1991, which may coat metal or fiberglass reinforced plastic (FRP) surfaces, with a maximum production capacity of 1.66 units per hour, equipped with a dry filter for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stack SV-H-1;
- (b) A bake booth, identified as H-4, constructed November 4, 1999, which serves as an additional bake booth for sprayed parts from spray/bake booth H-1, with a rated heat input of 1.2 MMBtu per hour, with no controls, and exhausting to stack SV-H-4;
- (c) Two spray/bake booths, identified as H-2 and H-3, constructed May 28, 1997, which may coat metal or FRP surfaces, each with a maximum production capacity of 0.375 units per hour, each equipped with dry filters for particulate matter (PM) control with a 32,000 acfm exhaust fan, and exhausting to stacks SV-H-2 and SV-H-3;
- (e) A base coat booth, identified as I-1, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units/hour, equipped with a dry filter for PM overspray control, and exhausting to stack SV-I-1;
- (f) A spray/bake booth, identified as I-2, constructed January 6, 1995, which may coat metal or FRP surfaces, with a maximum production capacity of 0.60 units per hour, and a maximum heat input capacity of 1.0 MMBtu per hour, equipped with a down draft dry filter system for PM overspray control, and exhausting through stack SV-I-2;
- (i) A spray paint booth, identified as P-6, constructed July 25, 1991, with a maximum capacity of 0.88 metal or FRP units/hour, equipped with a dry filter for PM control, and exhausting through stack SV-P-6;
- (z) A reciprocator, performing gel coating operation using FIT System and resin flow coating lamination, identified as M-2, constructed in February 1991, with a maximum production of 4.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M-2;
- (aa) A new portable MAS/FIT system for gel application, a reciprocator, performing resin lamination using a new automatic Chop FIT System, identified as M-4, constructed in February 1991, with a maximum production of 0.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M;
- (bb) A portable gelcoat FIT System, identified as M-3, constructed in February 1991, with a maximum production of 4.67 parts/hour, equipped with a dry filter bank for PM control, and exhausting through stack SV-M-3;
- (cc) One (1) small vehicle roof resin/gelcoat booth to be located in the old pultrusion area of the M-building to isolate the Flat Panel area from the Contoured Parts area, in order that fibers from the Flat Panel Area will not contaminate parts being made at the Contoured Parts area, utilizing existing gelcoat FIT System M-3 and existing Chop System M-6, with emissions from the booth exhausting through existing Stack SV-M-1

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

**SECTION E.3**

**CONTINUED**

**Emissions Unit Description [326 IAC 2-7-5(15)]:**

- (dd) Two portable gelcoat operations, identified as M-5 and M-9 constructed in February 1991, both guns have been upgraded to a Portable FIT System, each with a maximum production of 0.67 parts/hour, each equipped with a dry filter bank for PM control, and exhausting through stacks SV-M-5 and SV-M-9. M-5 is now located in the Flat Panel area, and M-9 is located in the Tru-Green area;
- (ee) Three portable chop/resin guns, identified as M-6, M-7, and M-8. M-6 gun has been upgraded with a portable Chop FIT System, for the application of chop resin wet out, and an atomized gun for the application of spraycore reinforcement. M-7 and M-8 have been replaced with Chop FIT Wall Mount System. All have been constructed in February 1991, each with a maximum production of 0.67 parts/hour, each equipped with a dry filter bank for PM control, and exhausting through stack SV-M-6, SV-M-7, and SV-M-8;
- (ff) A FRP mold department, identified as B-1, constructed in August 1980, with a maximum capacity of 0.004 molds /hour, with no emission control, and exhausting to stack SV-B-1;
- (gg) A white resin air assisted spray gun, identified as B-2(a), constructed in August 1990, with a maximum capacity of 0.004 molds/hour, equipped with a dry filter for PM control, and exhausting to stack SV-B-2;
- (hh) A Tru-green mold repair spray gun, identified as B-2(b), constructed in August 1990, with a maximum capacity of 1.33 parts/hour, equipped with a dry filter for PM control, and exhausting to stack SV-B-2. Existing Venus portable airless/air-assisted spray system will be changed into a portable cup gun granite spray system;
- (ii) Two repair/touch-up FRP facilities, identified as N-3(a) and N-3(b), constructed in August 1987, each with a maximum capacity of 0.888 parts/hour, with no emission control, and exhausting within the building;
- (jj) Several fiberglass touch-up areas which operate as part of FRP production lines, using Binks 115 guns with no emission controls and exhausting within the buildings;
- (kk) Two bulk resin tanks, identified as M-13(a) and M-13(b), constructed prior to 1981, each with a maximum capacity of 40,000 gallons, with no emission control and exhausting through safety valves;
- (ll) A fiberglass reinforced plastic (FRP) cutting facility, identified as 7-1, constructed November 1990, with a maximum production of 0.65 lb. of grinding dust/hour, equipped with a cyclone for dust collection, and exhausting through stack SV-7-1;

Under NESHAP WWWW M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115, M-13(a), M-13(b) are considered existing affected sources.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

## **National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]**

### **E.3.1 General Provisions Relating to NESHAP WWWW [40 CFR Part 63, Subpart A] [326 IAC 20-1]**

Pursuant to 40 CFR 63.5925, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1, as specified in Table 15 of 40 CFR Part 63, Subpart WWWW in accordance with schedule in 40 CFR 63 Subpart WWWW.

### **E.3.2 NESHAP Subpart WWWW Requirements [40 CFR Part 63, Subpart WWWW] [326 IAC 20-56]**

Pursuant to CFR Part 63, Subpart WWWW, the Permittee shall comply with the provisions of 40 CFR Part 63.5780, as specified as follows:

#### **Compliance Dates and Standards**

##### **§ 63.5800 When do I have to comply with this subpart?**

You must comply with the standards in this subpart by the dates specified in Table 2 to this subpart. Facilities meeting a organic HAP emissions standard based on a 12-month rolling average must begin collecting data on the compliance date in order to demonstrate compliance.

##### **§ 63.5805 What standards must I meet to comply with this subpart?**

You must meet the requirements of paragraphs (a) through (h) of this section that apply to you. You may elect to comply using any options to meeting these standards described in §§63.5810 through 63.5830. Use the procedures in §63.5799 to determine if you meet or exceed the 100 tpy threshold.

(b) All operations at existing facilities not listed in paragraph (a) of this section must meet the organic HAP emissions limits in Table 3 to this subpart and the work practice standards in Table 4 to this subpart that apply, regardless of the quantity of HAP emitted.

#### **Options for Meeting Standards**

##### **§ 63.5810 What are my options for meeting the standards for open molding and centrifugal casting operations at new and existing sources?**

You must use one of the following methods in paragraphs (a) through (d) of this section to meet the standards for open molding or centrifugal casting operations in Table 3 or 5 to this subpart. You may use any control method that reduces organic HAP emissions, including reducing resin and gel coat organic HAP content, changing to nonatomized mechanical application, using covered curing techniques, and routing part or all of your emissions to an add-on control. You may use different compliance options for the different operations listed in Table 3 or 5 to this subpart. The necessary calculations must be completed within 30 days after the end of each month. You may switch between the compliance options in paragraphs (a) through (d) of this section. When you change to an option based on a 12-month rolling average, you must base the average on the previous 12 months of data calculated using the compliance option you are changing to, unless you were previously using an option that did not require you to maintain records of resin and gel coat use. In this case, you must immediately begin collecting resin and gel coat use data and demonstrate compliance 12 months after changing options.

(a) *Demonstrate that an individual resin or gel coat, as applied, meets the applicable emission limit in Table 3 or 5 to this subpart.* (1) Calculate your actual organic HAP emissions factor for each different process stream within each operation type. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 to this subpart for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. If you are using vapor

suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWW of 40 CFR part 63.

(2) If the calculated emission factor is less than or equal to the appropriate emission limit, you have demonstrated that this process stream complies with the emission limit in Table 3 to this subpart. It is not necessary that all your process streams, considered individually, demonstrate compliance to use this option for some process streams. However, for any individual resin or gel coat you use, if any of the process streams that include that resin or gel coat are to be used in any averaging calculations described in paragraphs (b) through (d) of this section, then all process streams using that individual resin or gel coat must be included in the averaging calculations.

(b) *Demonstrate that, on average, you meet the individual organic HAP emissions limits for each combination of operation type and resin application method or gel coat type.* Demonstrate that on average you meet the individual organic HAP emissions limits for each unique combination of operation type and resin application method or gel coat type shown in Table 3 to this subpart that applies to you.

(1)(i) Group the process streams described in paragraph (a) to this section by operation type and resin application method or gel coat type listed in Table 3 to this subpart and then calculate a weighted average emission factor based on the amounts of each individual resin or gel coat used for the last 12 months. To do this, sum the product of each individual organic HAP emissions factor calculated in paragraph (a)(1) of this section and the amount of neat resin plus and neat gel coat plus usage that corresponds to the individual factors and divide the numerator by the total amount of neat resin plus and neat gel coat plus used in that operation type as shown in Equation 2 of this section.

$$\text{Average organic HAP Emissions Factor} = \frac{\sum_{i=1}^n (\text{Actual Process Stream } EF_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 2})$$

Where:

Actual Process Stream  $EF_i$ =actual organic HAP emissions factor for process stream  $i$ , lbs/ton;  
Material $_i$ =neat resin plus or neat gel coat plus used during the last 12 calendar months for process stream  $i$ , tons;

$n$ =number of process streams where you calculated an organic HAP emissions factor.

(ii) You may, but are not required to, include process streams where you have demonstrated compliance as described in paragraph (a) of this section, subject to the limitations described in paragraph (a)(2) of this section, and you are not required to and should not include process streams for which you will demonstrate compliance using the procedures in paragraph (d) of this section.

(2) Compare each organic HAP emissions factor calculated in paragraph (b)(1) of this section with its corresponding organic HAP emissions limit in Table 3 or 5 to this subpart. If all emissions factors are equal to or less than their corresponding emission limits, then you are in compliance.

(c) *Demonstrate compliance with a weighted average emission limit.* Demonstrate each month that you meet each weighted average of the organic HAP emissions limits in Table 3 or 5 to this subpart that apply to you. When using this option, you must demonstrate compliance with the weighted average organic HAP emissions limit for all your open molding operations, and then separately demonstrate compliance with the weighted average organic HAP emissions limit for all your centrifugal casting operations. Open molding operations and centrifugal casting operations may not be averaged with each other.

(1) Each month calculate the weighted average organic HAP emissions limit for all open molding operations and the weighted average organic HAP emissions limit for all centrifugal casting operations for your facility for the last 12-month period to determine the organic HAP emissions limit you must meet. To do this, multiply the individual organic HAP emissions limits in Table 3 or 5 to this subpart for each open molding (centrifugal casting) operation type by the amount of neat resin plus or neat gel coat plus used in the last 12 months for each open molding (centrifugal casting) operation type, sum these

results, and then divide this sum by the total amount of neat resin plus and neat gel coat plus used in open molding (centrifugal casting) over the last 12 months as shown in Equation 3 of this section.

$$\text{Weighted Average Emission Limit} = \frac{\sum_{i=1}^n (EL_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 3})$$

Where:

EL<sub>i</sub>=organic HAP emissions limit for operation type i, lbs/ton from Tables 3 or 5 to this subpart;  
 Material<sub>i</sub>=neat resin plus or neat gel coat plus used during the last 12-month period for operation type i, tons;  
 n=number of operations.

(2) Each month calculate your weighted average organic HAP emissions factor for open molding and centrifugal casting. To do this, multiply your actual open molding (centrifugal casting) operation organic HAP emissions factors calculated in paragraph (b)(1) of this section and the amount of neat resin plus and neat gel coat plus used in each open molding (centrifugal casting) operation type, sum the results, and divide this sum by the total amount of neat resin plus and neat gel coat plus used in open molding (centrifugal casting) operations as shown in Equation 4 of this section.

$$\text{Actual Weighted Average organic HAP Emissions Factor} = \frac{\sum_{i=1}^n (\text{Actual Operation } EF_i * \text{Material}_i)}{\sum_{i=1}^n \text{Material}_i} \quad (\text{Eq. 4})$$

Where:

Actual Individual EF<sub>i</sub>=Actual organic HAP emissions factor for operation type i, lbs/ton;  
 Material<sub>i</sub>=neat resin plus or neat gel coat plus used during the last 12 calendar months for operation type i, tons;  
 n=number of operations.

(3) Compare the values calculated in paragraphs (c)(1) and (2) of this section. If each 12-month rolling average organic HAP emissions factor is less than or equal to the corresponding 12-month rolling average organic HAP emissions limit, then you are in compliance.

(d) *Meet the organic HAP emissions limit for one application method and use the same resin(s) for all application methods of that resin type.* This option is limited to resins of the same type. The resin types for which this option may be used are noncorrosion-resistant, corrosion-resistant and/or high strength, and tooling.

(1) For any combination of manual resin application, mechanical resin application, filament application, or centrifugal casting, you may elect to meet the organic HAP emissions limit for any one of these application methods and use the same resin in all of the resin application methods listed in this paragraph (d)(1). Table 7 to this subpart presents the possible combinations based on a facility selecting the application process that results in the highest allowable organic HAP content resin. If the resin organic HAP content is below the applicable value shown in Table 7 to this subpart, the resin is in compliance.

(2) You may also use a weighted average organic HAP content for each application method described in paragraph (d)(1) of this section. Calculate the weighted average organic HAP content monthly. Use Equation 2 in paragraph (b)(1) of this section except substitute organic HAP content for organic HAP emissions factor. You are in compliance if the weighted average organic HAP content based on the last 12 months of resin use is less than or equal to the applicable organic HAP contents in Table 7 to this subpart.

(3) You may simultaneously use the averaging provisions in paragraph (b) or (c) of this section to demonstrate compliance for any operations and/or resins you do not include in your compliance demonstrations in paragraphs (d)(1) and (2) of this section. However, any resins for which you claim

compliance under the option in paragraphs (d)(1) and (2) of this section may not be included in any of the averaging calculations described in paragraph (b) or (c) of this section.

(4) You do not have to keep records of resin use for any of the individual resins where you demonstrate compliance under the option in paragraph (d)(1) of this section unless you elect to include that resin in the averaging calculations described in paragraph (d)(2) of this section.

### **General Compliance Requirements**

#### **§ 63.5835 What are my general requirements for complying with this subpart?**

(a) You must be in compliance at all times with the work practice standards in Table 4 to this subpart, as well as the organic HAP emissions limits in Tables 3, or 5, or the organic HAP content limits in Table 7 to this subpart, as applicable, that you are meeting without the use of add-on controls.

(c) You must always operate and maintain your affected source, including air pollution control and monitoring equipment, according to the provisions in §63.6(e)(1)(i).

### **Testing and Initial Compliance Requirements**

#### **§ 63.5840 By what date must I conduct a performance test or other initial compliance demonstration?**

Open molding and centrifugal casting operations that elect to meet a organic HAP emissions limit on a 12-month rolling average must initiate collection of the required data on the compliance date, and demonstrate compliance 1 year after the compliance date.

#### **§ 63.5860 How do I demonstrate initial compliance with the standards?**

(a) You demonstrate initial compliance with each organic HAP emissions standard in paragraphs (a) through (h) of §63.5805 that applies to you by using the procedures shown in Tables 8 and 9 to this subpart.

### **Continuous Compliance Requirements**

#### **§ 63.5895 How do I monitor and collect data to demonstrate continuous compliance?**

(c) You must collect and keep records of resin and gel coat use, organic HAP content, and operation where the resin is used if you are meeting any organic HAP emissions limits based on an organic HAP emissions limit in Tables 3 or 5 to this subpart. You must collect and keep records of resin and gel coat use, organic HAP content, and operation where the resin is used if you are meeting any organic HAP content limits in Table 7 to this subpart if you are averaging organic HAP contents. Resin use records may be based on purchase records if you can reasonably estimate how the resin is applied. The organic HAP content records may be based on MSDS or on resin specifications supplied by the resin supplier.

(d) Resin and gel coat use records are not required for the individual resins and gel coats that are demonstrated, as applied, to meet their applicable emission as defined in §63.5810(a). However, you must retain the records of resin and gel coat organic HAP content, and you must include the list of these resins and gel coats and identify their application methods in your semiannual compliance reports. If after you have initially demonstrated that a specific combination of an individual resin or gel coat, application method, and controls meets its applicable emission limit, and the resin or gel coat changes or the organic HAP content increases, or you change the application method or controls, then you again must demonstrate that the individual resin or gel coat meets its emission limit as specified in paragraph (a) of §63.5810. If any of the previously mentioned changes results in a situation where an individual resin or gel coat now exceeds its applicable emission limit in Table 3 or 5 of this subpart, you must begin collecting resin and gel coat use records and calculate compliance using one of the averaging options on a 12-month rolling average.

**§ 63.5900 How do I demonstrate continuous compliance with the standards?**

(a) You must demonstrate continuous compliance with each standard in §63.5805 that applies to you according to the methods specified in paragraphs (a)(1) through (3) of this section.

(2) Compliance with organic HAP emissions limits is demonstrated by maintaining an organic HAP emissions factor value less than or equal to the appropriate organic HAP emissions limit listed in Tables 3, or 5 to this subpart, on a 12-month rolling average, and/or by including in each compliance report a statement that all resins and gel coats meet the appropriate organic HAP emissions limits, as discussed in §63.5895(d).

(3) Compliance with organic HAP content limits in Table 7 to this subpart is demonstrated by maintaining an average organic HAP content value less than or equal to the appropriate organic HAP contents listed in Table 7 to this subpart, on a 12-month rolling average, and/or by including in each compliance report a statement that all resins and gel coats individually meet the appropriate organic HAP content limits, as discussed in §63.5895(d).

(4) Compliance with the work practice standards in Table 4 to this subpart is demonstrated by performing the work practice required for your operation.

(b) You must report each deviation from each standard in §63.5805 that applies to you. The deviations must be reported according to the requirements in §63.5910.

(c) During periods of startup, shutdown or malfunction, you must meet the organic HAP emissions limits and work practice standards that apply to you.

**Notifications, Reports, and Records**

**§ 63.5905 What notifications must I submit and when?**

(a) You must submit all of the notifications in Table 13 to this subpart that apply to you by the dates specified in Table 13 to this subpart. The notifications are described more fully in 40 CFR part 63, subpart A, referenced in Table 13 to this subpart.

(b) If you change any information submitted in any notification, you must submit the changes in writing to the Administrator within 15 calendar days after the change.

**§ 63.5910 What reports must I submit and when?**

(a) You must submit each report in Table 14 to this subpart that applies to you.

(b) Unless the Administrator has approved a different schedule for submission of reports under §63.10(a), you must submit each report by the date specified in Table 14 to this subpart and according to paragraphs (b)(1) through (5) of this section.

(1) The first compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.5800 and ending on June 30 or December 31, whichever date is the first date following the end of the first calendar half after the compliance date that is specified for your source in §63.5800.

(2) The first compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date follows the end of the first calendar half after the compliance date that is specified for your affected source in §63.5800.

(3) Each subsequent compliance report must cover the semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(4) Each subsequent compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(5) For each affected source that is subject to permitting requirements pursuant to 40 CFR part 70 or 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to §70.6 (a)(3)(iii)(A) or §71.6(a)(3)(iii)(A), you may submit the first and subsequent compliance reports according to the dates the permitting authority has established instead of according to the dates in paragraphs (b)(1) through (4) of this section.

(c) The compliance report must contain the information in paragraphs (c)(1) through (6) of this section:

(1) Company name and address.

(2) Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.

(3) Date of the report and beginning and ending dates of the reporting period.

(4) If you had a startup, shutdown, or malfunction during the reporting period and you took actions consistent with your startup, shutdown, and malfunction plan, the compliance report must include the information in §63.10(d)(5)(i).

(5) If there are no deviations from any organic HAP emissions limitations (emissions limit and operating limit) that apply to you, and there are no deviations from the requirements for work practice standards in Table 4 to this subpart, a statement that there were no deviations from the organic HAP emissions limitations or work practice standards during the reporting period.

(6) If there were no periods during which the continuous monitoring system (CMS), including a continuous emissions monitoring system (CEMS) and an operating parameter monitoring system were out of control, as specified in §63.8(c)(7), a statement that there were no periods during which the CMS was out of control during the reporting period.

(d) For each deviation from a organic HAP emissions limitation (*i.e.*, emissions limit and operating limit) and for each deviation from the requirements for work practice standards that occurs at an affected source where you are not using a CMS to comply with the organic HAP emissions limitations or work practice standards in this subpart, the compliance report must contain the information in paragraphs (c)(1) through (4) of this section and in paragraphs (d)(1) and (2) of this section. This includes periods of startup, shutdown, and malfunction.

(1) The total operating time of each affected source during the reporting period.

(2) Information on the number, duration, and cause of deviations (including unknown cause, if applicable), as applicable, and the corrective action taken.

(g) Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by §70.6(a)(3)(iii)(A) or §71.6(a)(3)(iii)(A). If an affected source submits a compliance report pursuant to Table 14 to this subpart along with, or as part of, the semiannual monitoring report required by §70.6(a)(3)(iii)(A) or §71.6(a)(3)(iii)(A), and the compliance report includes all required information concerning deviations from any organic HAP emissions limitation (including any operating limit) or work practice requirement in this subpart, submission of the compliance report shall be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permitting authority.

(h) Submit compliance reports and startup, shutdown, and malfunction reports based on the requirements in Table 14 to this subpart, and not based on the requirements in §63.999.

### **§ 63.5915 What records must I keep?**

(a) You must keep the records listed in paragraphs (a)(1) through (3) of this section.

(1) A copy of each notification and report that you submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status that you submitted, according to the requirements in §63.10(b)(2)(xiv).

(2) The records in §63.6(e)(3)(iii) through (v) related to startup, shutdown, and malfunction.

(3) Records of performance tests, design, and performance evaluations as required in §63.10(b)(2).

(c) You must keep all data, assumptions, and calculations used to determine organic HAP emissions factors or average organic HAP contents for operations listed in Tables 3, 5, and 7 to this subpart.

(d) You must keep a certified statement that you are in compliance with the work practice requirements in Table 4 to this subpart, as applicable.

### **§ 63.5920 In what form and how long must I keep my records?**

(a) You must maintain all applicable records in such a manner that they can be readily accessed and are suitable for inspection according to §63.10(b)(1).

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record onsite for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1). You can keep the records offsite for the remaining 3 years.

(d) You may keep records in hard copy or computer readable form including, but not limited to, paper, microfilm, computer floppy disk, magnetic tape, or microfiche.

### **Other Requirements and Information**

#### **§ 63.5925 What parts of the General Provisions apply to me?**

Table 15 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you.

#### **§ 63.5930 Who implements and enforces this subpart?**

(a) This subpart can be administered by us, the EPA, or a delegated authority such as your State, local, or tribal agency. If the EPA Administrator has delegated authority to your State, local, or tribal agency, then that agency has the authority to administer and enforce this subpart. You should contact your EPA Regional Office to find out if this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under 40 CFR part 63, subpart E, the authorities contained in paragraph (c) of this section are not delegated.

(c) The authorities that will not be delegated to State, local, or tribal agencies are listed in paragraphs (c)(1) through (4) of this section:

(1) Approval of alternatives to the organic HAP emissions standards in §63.5805 under §63.6(g).

(2) Approval of major changes to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.

(3) Approval of major changes to monitoring under §63.8(f) and as defined in §63.90.

(4) Approval of major changes to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

### **§ 63.5935 What definitions apply to this subpart?**

Terms used in this subpart are defined in the CAA, in 40 CFR 63.2, and in this section as follows:

*Atomized mechanical application* means application of resin or gel coat with spray equipment that separates the liquid into a fine mist. This fine mist may be created by forcing the liquid under high pressure through an elliptical orifice, bombarding a liquid stream with directed air jets, or a combination of these techniques.

*Bulk molding compound (BMC)* means a putty-like molding compound containing resin(s) in a form that is ready to mold. In addition to resins, BMC may contain catalysts, fillers, and reinforcements. Bulk molding compound can be used in compression molding and injection molding operations to manufacture reinforced plastic composites products.

*BMC manufacturing* means a process that involves the preparation of BMC.

*Centrifugal casting* means a process for fabricating cylindrical composites, such as pipes, in which composite materials are positioned inside a rotating hollow mandrel and held in place by centrifugal forces until the part is sufficiently cured to maintain its physical shape.

*Charge* means the amount of SMC or BMC that is placed into a compression or injection mold necessary to complete one mold cycle.

*Cleaning* means removal of composite materials, such as cured and uncured resin from equipment, finished surfaces, floors, hands of employees, or any other surfaces.

*Clear production gel coat* means an unpigmented, quick-setting resin used to improve the surface appearance and/or performance of composites. It can be used to form the surface layer of any composites other than those used for molds in tooling operations.

*Closed molding* means a grouping of processes for fabricating composites in a way that HAP-containing materials are not exposed to the atmosphere except during the material loading stage (e.g., compression molding, injection molding, and resin transfer molding). Processes where the mold is covered with plastic (or equivalent material) prior to resin application, and the resin is injected into the covered mold are also considered closed molding.

*Composite* means a shaped and cured part produced by using composite materials.

*Composite materials* means the raw materials used to make composites. The raw materials include styrene containing resins. They may also include gel coat, monomer, catalyst, pigment, filler, and reinforcement.

*Compression molding* means a closed molding process for fabricating composites in which composite materials are placed inside matched dies that are used to cure the materials under heat and pressure without exposure to the atmosphere. The addition of mold paste or in-mold coating is considered part of the closed molding process. The composite materials used in this process are generally SMC or BMC.

*Compression/injection molding* means a grouping of processes that involves the use of compression molding and/or injection molding.

*Continuous casting* means a continuous process for fabricating composites in which composite materials are placed on an in-line conveyor belt to produce cast sheets that are cured in an oven.

*Continuous lamination* means a continuous process for fabricating composites in which composite materials are typically sandwiched between plastic films, pulled through compaction rollers, and cured

in an oven. This process is generally used to produce flat or corrugated products on an in-line conveyor.

*Continuous lamination/casting* means a grouping of processes that involves the use of continuous lamination and/or continuous casting.

*Controlled emissions* means those organic HAP emissions that are vented from a control device to the atmosphere.

*Corrosion-resistant gel coat* means a gel coat used on a product made with a corrosion-resistant resin that has a corrosion-resistant end-use application.

*Corrosion-resistant end-use applications* means applications where the product is manufactured specifically for an application that requires a level of chemical inertness or resistance to chemical attack above that required for typical reinforced plastic composites products. These applications include, but are not limited to, chemical processing and storage; pulp and paper production; sewer and wastewater treatment; power generation; potable water transfer and storage; food and drug processing; pollution or odor control; metals production and plating; semiconductor manufacturing; petroleum production, refining, and storage; mining; textile production; nuclear materials storage; swimming pools; and cosmetic production, as well as end-use applications that require high strength resins.

*Corrosion-resistant industry standard* includes the following standards: ASME RTP-1 or Sect. X; ASTM D5364, D3299, D4097, D2996, D2997, D3262, D3517, D3754, D3840, D4024, D4160, D4161, D4162, D4184, D3982, or D3839; ANSI/AWWA C950; UL 215, 1316 or 1746, IAPMO PS-199, or written customer requirements for resistance to specified chemical environments.

*Corrosion-resistant product* means a product made with a corrosion-resistant resin and is manufactured to a corrosion-resistant industry standard, or a food contact industry standard, or is manufactured for corrosion-resistant end-use applications involving continuous or temporary chemical exposures.

*Corrosion-resistant resin* means a resin that either:

- (1) Displays substantial retention of mechanical properties when undergoing ASTM C-581 coupon testing, where the resin is exposed for 6 months or more to one of the following materials: Material with a pH  $\geq$  12.0 or  $\leq$  3.0, oxidizing or reducing agents, organic solvents, or fuels or additives as defined in 40 CFR 79.2. In the coupon testing, the exposed resin needs to demonstrate a minimum of 50 percent retention of the relevant mechanical property compared to the same resin in unexposed condition. In addition, the exposed resin needs to demonstrate an increased retention of the relevant mechanical property of at least 20 percentage points when compared to a similarly exposed general-purpose resin. For example, if the general-purpose resin retains 45 percent of the relevant property when tested as specified above, then a corrosion-resistant resin needs to retain at least 65 percent (45 percent plus 20 percent) of its property. The general-purpose resin used in the test needs to have an average molecular weight of greater than 1,000, be formulated with a 1:2 ratio of maleic anhydride to phthalic anhydride and 100 percent diethylene glycol, and a styrene content between 43 to 48 percent; or
- (2) Complies with industry standards that require specific exposure testing to corrosive media, such as UL 1316, UL 1746, or ASTM F-1216.

*Doctor box* means the box or trough on an SMC machine into which the liquid resin paste is delivered before it is metered onto the carrier film.

*Filament application* means an open molding process for fabricating composites in which reinforcements are fed through a resin bath and wound onto a rotating mandrel. The materials on the mandrel may be rolled out or worked by using nonmechanical tools prior to curing. Resin application to the reinforcement on the mandrel by means other than the resin bath, such as spray guns, pressure-fed rollers, flow coaters, or brushes is not considered filament application.

*Filled Resin* means that fillers have been added to a resin such that the amount of inert substances is at least 10 percent by weight of the total resin plus filler mixture. Filler putty made from a resin is considered a filled resin.

*Fillers* means inert substances dispersed throughout a resin, such as calcium carbonate, alumina trihydrate, hydrous aluminum silicate, mica, feldspar, wollastonite, silica, and talc. Materials that are not considered to be fillers are glass fibers or any type of reinforcement and microspheres.

*Fire retardant gel coat* means a gel coat used for products for which low-flame spread/low-smoke resin is used.

*Fluid impingement technology* means a spray gun that produces an expanding non-misting curtain of liquid by the impingement of low-pressure uninterrupted liquid streams.

*Food contact industry standard* means a standard related to food contact application contained in Food and Drug Administration's regulations at 21 CFR 177.2420.

*Gel Coat* means a quick-setting resin used to improve surface appearance and/or performance of composites. It can be used to form the surface layer of any composites other than those used for molds in tooling operations.

*Gel coat application* means a process where either clear production, pigmented production, white/off-white or tooling gel coat is applied.

*HAP-containing materials storage* means an ancillary process which involves keeping HAP-containing materials, such as resins, gel coats, catalysts, monomers, and cleaners, in containers or bulk storage tanks for any length of time. Containers may include small tanks, totes, vessels, and buckets.

*High Performance gel coat* means a gel coat used on products for which National Sanitation Foundation, United States Department of Agriculture, ASTM, durability, or other property testing is required.

*High strength gel coat* means a gel coat applied to a product that requires high strength resin.

*High strength resins* means polyester resins which have a casting tensile strength of 10,000 pounds per square inch or more and which are used for manufacturing products that have high strength requirements such as structural members and utility poles.

*Injection molding* means a closed molding process for fabricating composites in which composite materials are injected under pressure into a heated mold cavity that represents the exact shape of the product. The composite materials are cured in the heated mold cavity.

*Low Flame Spread/Low Smoke Products* means products that meet the following requirements. The products must meet both the applicable flame spread requirements and the applicable smoke requirements. Interior or exterior building application products must meet an ASTM E-84 Flame Spread Index of less than or equal to 25, and Smoke Developed Index of less than or equal to 450, or pass National Fire Protection Association 286 Room Corner Burn Test with no flash over and total smoke released not exceeding 1000 meters square. Mass transit application products must meet an ASTM E-162 Flame Spread Index of less than or equal to 35 and ASTM E662 Smoke Density Ds @ 1.5 minutes less than or equal to 100 and Ds @ 4 minutes less than or equal to 200. Duct application products must meet ASTM E084 Flame Spread Index less than or equal to 25 and Smoke Developed Index less than or equal to 50 on the interior and/or exterior of the duct.

*Manual resin application* means an open molding process for fabricating composites in which composite materials are applied to the mold by pouring or by using hands and nonmechanical tools, such as brushes and rollers. Materials are rolled out or worked by using nonmechanical tools prior to curing. The use of pressure-fed rollers and flow coaters to apply resin is not considered manual resin application.

*Mechanical resin application* means an open molding process for fabricating composites in which composite materials (except gel coat) are applied to the mold by using mechanical tools such as spray

guns, pressure-fed rollers, and flow coaters. Materials are rolled out or worked by using nonmechanical tools prior to curing.

*Mixing* means the blending or agitation of any HAP-containing materials in vessels that are 5.00 gallons (18.9 liters) or larger, and includes the mixing of putties or polyputties. Mixing may involve the blending of resin, gel coat, filler, reinforcement, pigments, catalysts, monomers, and any other additives.

*Mold* means a cavity or matrix into or onto which the composite materials are placed and from which the product takes its form.

*Neat gel coat* means the resin as purchased for the supplier, but not including any inert fillers.

*Neat gel coat plus* means neat gel coat plus any organic HAP-containing materials that are added to the gel coat by the supplier or the facility, excluding catalysts and promoters. Neat gel coat plus does not include any additions of styrene or methyl methacrylate monomer in any form, including in catalysts and promoters.

*Neat resin* means the resin as purchased from the supplier, but not including any inert fillers. *Neat resin plus* means neat resin plus any organic HAP-containing materials that are added to the resin by the supplier or the facility. Neat resin plus does not include any added filler, reinforcements, catalysts, or promoters. Neat resin plus does include any additions of styrene or methyl methacrylate monomer in any form, including in catalysts and promoters.

*Nonatomized mechanical application* means the use of application tools other than brushes to apply resin and gel coat where the application tool has documentation provided by its manufacturer or user that this design of the application tool has been organic HAP emissions tested, and the test results showed that use of this application tool results in organic HAP emissions that are no greater than the organic HAP emissions predicted by the applicable nonatomized application equation(s) in Table 1 to this subpart. In addition, the device must be operated according to the manufacturer's directions, including instructions to prevent the operation of the device at excessive spray pressures. Examples of nonatomized application include flow coaters, pressure fed rollers, and fluid impingement spray guns.

*Noncorrosion-resistant resin* means any resin other than a corrosion-resistant resin or a tooling resin.

*Noncorrosion-resistant product* means any product other than a corrosion-resistant product or a mold.

*Non-routine manufacture* means that you manufacture parts to replace worn or damaged parts of a reinforced plastic composites product, or a product containing reinforced plastic composite parts, that was originally manufactured in another facility. For a part to qualify as non-routine manufacture, it must be used for repair or replacement, and the manufacturing schedule must be based on the current or anticipated repair needs of the reinforced plastic composites product, or a product containing reinforced plastic composite parts.

*Operation* means a specific process typically found at a reinforced plastic composites facility. Examples of operations are noncorrosion-resistant manual resin application, corrosion-resistant mechanical resin application, pigmented gel coat application, mixing and HAP-containing materials storage.

*Operation group* means a grouping of individual operations based primarily on mold type. Examples are open molding, closed molding, and centrifugal casting.

*Open molding* means a process for fabricating composites in a way that HAP-containing materials are exposed to the atmosphere. Open molding includes processes such as manual resin application, mechanical resin application, filament application, and gel coat application. Open molding also includes application of resins and gel coats to parts that have been removed from the open mold.

*Pigmented gel coat* means a gel coat that has a color, but does not contain 10 percent or more titanium dioxide by weight. It can be used to form the surface layer of any composites other than those used for molds in tooling operations.

*Polymer casting* means a process for fabricating composites in which composite materials are ejected from a casting machine or poured into an open, partially open, or closed mold and cured. After the composite materials are poured into the mold, they are not rolled out or worked while the mold is open, except for smoothing the material and/or vibrating the mold to remove bubbles. The composite materials may or may not include reinforcements. Products produced by the polymer casting process include cultured marble products and polymer concrete.

*Preform Injection* means a form of pultrusion where liquid resin is injected to saturate reinforcements in an enclosed system containing one or more chambers with openings only large enough to admit reinforcements. Resin, which drips out of the chamber(s) during the process, is collected in closed piping or covered troughs and then into a covered reservoir for recycle. Resin storage vessels, reservoirs, transfer systems, and collection systems are covered or shielded from the ambient air. Preform injection differs from direct die injection in that the injection chambers are not directly attached to the die.

*Prepreg materials* means reinforcing fabric received pre-coated with resin which is usually cured through the addition of heat.

*Pultrusion* means a continuous process for manufacturing composites that have a uniform cross-sectional shape. The process consists of pulling a fiber-reinforcing material through a resin impregnation chamber or bath and through a shaping die, where the resin is subsequently cured. There are several types of pultrusion equipment, such as open bath, resin injection, and direct die injection equipment.

*Repair* means application of resin or gel coat to a part to correct a defect, where the resin or gel coat application occurs after the part has gone through all the steps of its typical production process, or the application occurs outside the normal production area. For purposes of this subpart, rerouting a part back through the normal production line, or part of the normal production line, is not considered repair.

*Resin transfer molding* means a process for manufacturing composites whereby catalyzed resin is transferred or injected into a closed mold in which fiberglass reinforcement has been placed.

*Sheet molding compound (SMC)* means a ready-to-mold putty-like molding compound that contains resin(s) processed into sheet form. The molding compound is sandwiched between a top and a bottom film. In addition to resin(s), it may also contain catalysts, fillers, chemical thickeners, mold release agents, reinforcements, and other ingredients. Sheet molding compound can be used in compression molding to manufacture reinforced plastic composites products.

*Shrinkage controlled resin* means a resin that when promoted, catalyzed, and filled according to the resin manufacturer's recommendations demonstrates less than 0.3 percent linear shrinkage when tested according to ASTM D2566.

*SMC manufacturing* means a process which involves the preparation of SMC.

*Tooling gel coat* means a gel coat that is used to form the surface layer of molds. Tooling gel coats generally have high heat distortion temperatures, low shrinkage, high barcol hardness, and high dimensional stability.

*Tooling resin* means a resin that is used to produce molds. Tooling resins generally have high heat distortion temperatures, low shrinkage, high barcol hardness, and high dimensional stability.

*Uncontrolled oven organic HAP emissions* means those organic HAP emissions emitted from the oven through closed vent systems to the atmosphere and not to a control device. These organic HAP emissions do not include organic HAP emissions that may escape into the workplace through the opening of panels or doors on the ovens or other similar fugitive organic HAP emissions in the workplace.

*Uncontrolled wet-out area organic HAP emissions* means any or all of the following: Organic HAP emissions from wet-out areas that do not have any capture and control, organic HAP emissions that escape from wet-out area enclosures, and organic HAP emissions from wet-out areas that are captured by an enclosure but are vented to the atmosphere and not to an add-on control device.

*Unfilled* means that there has been no addition of fillers to a resin or that less than 10 percent of fillers by weight of the total resin plus filler mixture has been added.

*Vapor suppressant* means an additive, typically a wax, that migrates to the surface of the resin during curing and forms a barrier to seal in the styrene and reduce styrene emissions.

*Vapor-suppressed resin* means a resin containing a vapor suppressant added for the purpose of reducing styrene emissions during curing.

*White and off-white gel coat* means a gel coat that contains 10 percent of more titanium dioxide by weight.

**Table 1 to Subpart WWWW of Part 63—Equations to Calculate Organic HAP Emissions Factors for Specific Open Molding and Centrifugal Casting Process Streams<sup>1</sup>**

As specified in §63.5810, use the equations in the following table to calculate organic HAP emissions factors for specific open molding and centrifugal casting process streams:

If your operation type is a new or existing. . .	And you use. . .	With. . .	Use this organic HAP Emissions Factor (EF) Equation for materials with less than 33 percent organic HAP (19 percent organic HAP for nonatomized gel coat) <sup>2 3 4</sup>	Use this organic HAP emissions Factor (EF) Equation for materials with 33 percent or more organic HAP (19 percent for nonatomized gel coat) <sup>2 3 4</sup>
1. open molding operation	a. manual resin application	i. nonvapor-suppressed resin	EF = 0.126 x %HAP x 2000	EF = ((0.286 x %HAP) – 0.0529) x 2000
		ii. vapor-suppressed resin	EF = 0.126 x %HAP x 2000 x (1-(0.5 x VSE Factor))	EF = ((0.286 x %HAP)-0.0529) x 2000 x (1-(0.5 x VSE Factor))
		iii. vacuum bagging/closed-mold curing with roll out	EF = 0.126 x %HAP x 2000 x 0.5	EF = ((0.286 x %HAP)-0.0529) x 2000 x 0.8
		iv. vacuum bagging/closed-mold curing without roll out	EF = (0.126 x %HAP x 2000 x 0.5	EF = ((0.286 x %HAP) – 0.0529) x 2000 x 0.5
	c. nonatomized mechanical resin application	i. nonvapor-suppressed resin	EF = 0.107 x %HAP x 2000	EF = ((0.157 x %HAP) – 0.0165) x 2000
		ii. vapor-suppressed resin	EF = 0.107 x %HAP x 2000 x (1-(0.45 x VSE Factor))	EF = ((0.157 x %HAP) – 0.0165) x 2000 x (1-(0.45 x VSE Factor))
		iii. closed-mold curing with roll out	EF = 0.107 x %HAP x 2000 x 0.85	EF = ((0.157 x %HAP) - 0.0165) x 2000 x 0.85
		iv. vacuum bagging/closed-mold curing without roll out	EF = (0.107 x %HAP x 2000 x 0.55	EF = ((0.157 x %HAP) – 0.0165) x 2000 x 0.55
	e. filament application <sup>6</sup>	i. nonvapor-suppressed resin	EF = 0.184 x %HAP x 2000	EF = ((0.2746 x %HAP) – 0.0298) x 2000
		ii. vapor-suppressed resin	EF = 0.12 x %HAP x 2000	EF = ((0.2746 x %HAP) – 0.0298) x 2000 x 0.65
	g. nonatomized spray gel coat application	nonvapor-suppressed gel coat	EF = 0.185 x %HAP x 2000	EF = ((0.4506 x %HAP) – 0.0505) x 2000

**Footnotes to Table 1**

- <sup>1</sup> The equations in this table are intended for use in calculating emission factors to demonstrate compliance with the emission limits in subpart WWWW. These equations may not be the most appropriate method to calculate emission estimates for other purposes. However, this does not preclude a facility from using the equations in this table to calculate emission factors for purposes other than rule compliance if these equations are the most accurate available.
- <sup>2</sup> To obtain the organic HAP emissions factor value for an operation with an add-on control device multiply the EF above by the add-on control factor calculated using Equation 1 of §63.5810. The organic HAP emissions factors have units of lbs of organic HAP per ton of resin or gel coat applied.
- <sup>3</sup> Percent HAP means total weight percent of organic HAP (styrene, methyl methacrylate, and any other organic HAP) in the resin or gel coat prior to the addition of fillers, catalyst, and promoters. Input the percent HAP as a decimal, i.e., 33 percent HAP should be input as 0.33, not 33.
- <sup>4</sup> The VSE factor means the percent reduction in organic HAP emissions expressed as a decimal measured by the VSE test method of appendix A to this subpart.
- <sup>5</sup> This equation is based on a organic HAP emissions factor equation developed for mechanical atomized controlled spray. It may only be used for automated or robotic spray systems with automated spray. All spray operations using hand held spray guns must use the appropriate mechanical atomized or mechanical nonatomized organic HAP emissions factor equations. Automated or robotic spray systems using nonatomized spray should use the appropriate nonatomized mechanical resin application equation.
- <sup>6</sup> Applies only to filament application using an open resin bath. If resin is applied manually or with a spray gun, use the appropriate manual or mechanical application organic HAP emissions factor equation.

**Table 2 to Subpart WWWW of Part 63—Compliance Dates for New and Existing Reinforced Plastic Composites Facilities**

As required in §§63.5800 and 63.5840 you must demonstrate compliance with the standards by the dates in the following table:

If your facility is. . .	And. . . .	Then you must comply by this date. . .
1. An existing source. . .	a. Is a major source on or before the publication date of this subpart.	i. April 21, 2006, or ii. You must accept and meet an enforceable HAP emissions limit below the major source threshold prior to April 21, 2006.

**Table 3 to Subpart WWWW of Part 63—Organic HAP Emissions Limits for Existing Open Molding Sources, New Open Molding Sources Emitting Less Than 100 TPY of HAP, and New and Existing Centrifugal Casting and Continuous Lamination/Casting Sources that Emit Less Than 100 TPY of HAP**

As required in §§63.5796, 63.5805 (a) through (c) and (g), 63.5810(a), (b), and (d), 63.5820(c), 63.5830, 63.5835(a), 63.5895(c) and (d), 63.5900(a)(2), and 63.5915(c), you must meet the appropriate organic HAP emissions limits in the following table:

If your operation type is. . .	And you use. . .	<sup>1</sup> Your organic HAP emissions limit is. . .
1. open molding – corrosion-resistant and/or high strength (CR/HS).	a. mechanical resin application	113 lb/ton
	b. filament application	171 lb/ton
	c. manual resin application	123 lb/ton
2. open molding – non-CR/HS	a. mechanical resin application	88 lb/ton
	b. filament application	188 lb/ton
	c. manual resin application	87 lb/ton
3. open molding – tooling	a. mechanical resin application	254 lb/ton
	b. manual resin application	157 lb/ton
4. open molding – low-flame spread/low-smoke products	a. mechanical resin application	497 lb/ton
	b. filament application	270 lb/ton
	c. manual resin application	238 lb/ton
5. open molding – shrinkage controlled resins <sup>2</sup>	a. mechanical resin application	354 lb/ton
	b. filament application	215 lb/ton
	c. manual resin application	180 lb/ton
6. open molding – gel coat <sup>3</sup>	a. tooling gel coating	440 lb/ton
	b. white/off white pigmented gel coating	267 lb/ton
	c. all other pigmented gel coating	377 lb/ton
	d. CR/HS or high performance gel coat	605 lb/ton
	e. fire retardant gel coat	854 lb/ton
	f. clear production gel coat	522 lb/ton

<sup>1</sup> Organic HAP emissions limits for open molding and centrifugal casting are expressed as lb/ton. You must be at or below these values based on a 12-month rolling average.

<sup>2</sup> This emission limit applies regardless of whether the shrinkage controlled resin is used as a production resin or a tooling resin.

<sup>3</sup> If you only apply gel coat with manual application, for compliance purposes treat the gel coat as if it were applied using atomized spray guns to determine both emission limits and emission factors. If you use multiple application methods and any portion of a specific gel coat is applied using nonatomized spray, you may use the nonatomized spray gel coat equation to calculate any emission factor for the manually applied portion of that gel coat. Otherwise, use the atomized spray gel coat equation to calculate emission factors.

**Table 4 to Subpart WWWW of Part 63—Work Practice Standards**

[As required in §§63.5805 (a) through (d) and (g), 63.5835(a), 63.5900(a)(3), 63.5910(c)(5), and 63.5915(d), you must meet the appropriate work practice standards in the following table:]

For . . .	You must . . .
1. a new or existing closed molding operation using compression/injection molding.	Uncover, unwrap or expose only one charge per mold cycle per compression/injection molding machine. For machines with multiple molds, one charge means sufficient material to fill all molds for one cycle. For machines with robotic loaders, no more than one charge may be exposed prior to the loader. For machines fed by hoppers, sufficient material may be uncovered to fill the hopper. Hoppers must be closed when not adding materials. Materials may be uncovered to feed to slitting machines. Materials must be recovered after slitting.
2. a new or existing cleaning operation	Not use cleaning solvents that contain HAP, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.
3. a new or existing materials HAP-containing materials storage operation	Keep containers that store HAP-containing materials closed or covered except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

<sup>1</sup> containers of 5 gallons or less may be open when active mixing is taking place, or during periods when they are in process (i.e., they are actively being used to apply resin). For polymer casting mixing operations, containers with a surface area of 500 square inches or less may be open while active mixing is taking place.

**Table 5 to Subpart WWWW of Part 63 – Alternative Organic HAP Emissions limits for Open Molding, Centrifugal Casting, and SMC Manufacturing Operations where the standard is based on a 95 percent reduction requirement**

[As specified in §§63.5796, 63.5805(b) and (d), 6.5810(a) and (b), 63.5895(c), 63.5900(a)(2), and 63.5915(c), as an alternative to the 95 percent organic HAP emissions reductions requirement, you may meet the appropriate organic HAP emissions limits in the following table:]

If your operation type is . . .	And you use . . .	Your organic HAP emissions limit is <sup>1</sup>
1. Open molding – corrosion-resistant and/or high strength (CR/HS).	a. Mechanical resin application b. Filament application c. Manual resin application	6 lb/ton 9 lb/ton 7 lb/ton
2. Open molding – non-CR/HS	a. Mechanical resin application b. Filament application c. Manual resin application	13 lb/ton 10 lb/ton 5 lb/ton
3. Open molding - tooling	a. Mechanical resin application b. Filament application	13 lb/ton 8 lb/ton
4. Open molding – low flame spread/low smoke products	a. Mechanical resin application b. Filament application c. Manual resin application	25 lb/ton 14 lb/ton 12 lb/ton
5. Open molding – shrinkage controlled resins	a. Mechanical resin application b. Filament application c. Manual resin application	18 lb/ton 11 lb/ton 9 lb/ton

6. Open molding – gel coat <sup>2</sup>	a. Tooling gel coating	22 lb/ton
	b. White/off white pigmented gel coating	22 lb/ton
	c. All other pigmented gel coating	19 lb/ton
	d. CR/HS or high performance gel coat	31 lb/ton
	e. Fire retardant gel coat	43 lb/ton
	f. Clear production gel coat	27 lb/ton

<sup>1</sup> Organic HAP emissions limits for open molding and centrifugal casting expressed as lb/ton are calculated using the equations shown in Table 1 to this subpart. You must be at or below these values based on a 12-month rolling average.

<sup>2</sup> These limits are for spray application of gel coat. Manual gel coat application must be included as part of spray gel coat application for compliance purposes using the same organic HAP emissions factor equation and organic HAP emissions limit. If you only apply gel coat with manual application, treat the manually applied gel coat as if it were applied with atomized spray for compliance determinations.

**Table 7 to Subpart WWWW of Part 63—Options Allowing Use of the Same Resin Across Different Operations That Use the Same Resin Type**

As specified in § 63.5810(d), when electing to use the same resin(s) for multiple resin application methods, you may use any resin(s) with an organic HAP content less than or equal to the values shown in the following table, or any combination of resins whose weighted average organic HAP content based on a 12-month rolling average is less than or equal to the values shown the following table:

If your facility has the following resin type and application method . . .	The highest resin weight is* * * percent organic HAP content, or weighted average weight percent organic HAP content, you can use for . .	Is . . .
2. CR/HS resins, nonatomized mechanical	b. CR/HS filament application	46.4
	c. CR/HS manual	46.4
5. Non-CR/HS resins, nonatomized mechanical	a. Non-CR/HS manual	38.5
	b. non-CR/HS centrifugal casting <sup>1 2</sup>	38.5
7. Tooling resins, nonatomized mechanical	Tooling manual	91.4
8. Tooling resins, manual	Tooling atomized mechanical	45.9

**Table 8 to Subpart WWWW of Part 63—Initial Compliance with Organic HAP Emissions Limits**

As required in §63.5860(a), you must demonstrate initial compliance with organic HAP emissions limits as specified in the following table:

For . . .	That must meet the following organic HAP emissions limit. . .	You have demonstrated initial compliance if . . .
1. open molding and centrifugal casting operations.	a. an organic HAP emissions limit shown in Tables 3 and 5 to this subpart, or an organic HAP content limit shown in Table 7 to this subpart.	i. you have met the appropriate organic HAP emissions limits for these operations as calculated using the procedures in § 63.5810 on a 12-month rolling average 1 year after the appropriate compliance date, and/or ii. you demonstrate that any individual resins or get coats not included in (i) above, as applied, meet their applicable emission limits, or iii. you demonstrate using the appropriate values in Table 7 to this subpart that the weighted average of all resins and gel coats for each resin type and application method meet the appropriate organic HAP contents.

2. open molding centrifugal casting, continuous lamination/casting, SMC and BMC manufacturing, and mixing operations.	a. reduce total organic HAP emissions by at least 95 percent by weight.	Total organic HAP emissions, based on the results of the capture efficiency and destruction efficiency testing specified in Table 6 to this Subpart, are reduced by at least 95 percent by weight.
---	---	--

**Table 9 to Subpart WWWW of Part 63—Initial Compliance with Work Practice Standards**

As required in §63.5860(a), you must demonstrate initial compliance with work practice standards as specified in the following table:

For . . .	That must meet the following standards. . .	You have demonstrated initial compliance if . . .
1. a new or existing closed molding operation using compression/injection molding.	Uncover, unwrap or expose only one charge per mold cycle per compression/injection molding machine. For machines with multiple molds, one charge means sufficient material to fill all molds for one cycle. For machines with robotic loaders, no more than one charge may be exposed prior to the loader. For machines fed by hoppers, sufficient material may be uncovered to fill the hopper. Hoppers must be closed when not adding materials. Materials may be uncovered to feed to slitting machines. Materials must be recovered after slitting.	The owner or operator submits a certified statement in the notice of compliance status that only one charge is uncovered, unwrapped, or exposed per mold cycle per compression/injection molding machine, or prior to the loader, hoppers are closed except when adding materials, and materials are recovered after slitting.
2. a new or existing cleaning operation	Not use cleaning solvents that contain HAP, except that styrene may be used in closed systems, and organic HAP containing materials may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin between storage and applying resin to the mold or reinforcement.	The owner or operator submits a certified statement in the notice of compliance status that all cleaning materials, except styrene contained in closed systems, or materials used to clean cured resin from application equipment, contain no HAP.
3. a new or existing materials HAP-containing materials storage operation.	Keep containers that store HAP-containing materials closed or covered except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.	The owner or operator submits a certified statement in the notice of compliance status that all HAP-containing storage containers are kept closed or covered except when adding or removing material, and that any bulk storage tanks are vented only as necessary for safety.

**Table 13 to Subpart WWWW of Part 63—Applicability and Timing of Notifications**

As required in §63.5905(a), you must determine the applicable notifications and submit them by the dates shown in the following table:

If your facility . . .	You must submit . . .	By this date . . .
1. Is an existing source subject to this subpart	An Initial Notification containing the information specified in § 63.9(b)(2).	No later than the dates specified in § 63.9(b)(2).

2. Qualifies for a compliance extension as specified in § 63.9(c).	A request for a compliance extension as specified in § 63.9(c).	No later than the dates specified in § 63.6(i).
3. Is complying with organic HAP emissions limit averaging provisions.	A Notification of Compliance Status as specified in § 63.9(h).	No later than 1 year plus 30 days after your facility's compliance date.
4. Is complying with organic HAP content limits, application equipment requirements, or organic HAP emissions limit other than organic HAP emissions limit averaging.	A Notification of Compliance Status as specified in § 63.9(h).	No later than 30 calendar days after your facility's compliance date.

**Table 14 to Subpart WWWW of Part 63—Requirements for Reports**

As required in §63.5910(a), (b), (g), and (h), you must submit reports on the schedule shown in the following table:

<i>You must submit a(n)</i>	<i>The report must contain . . .</i>	<i>You must submit the report . . .</i>
1. Compliance report	<i>a. A statement that there were no deviations during that reporting period if there were no deviations from any emission limitations (emission limit, operating limit, opacity limit, and visible emission limit) that apply to you and there were no deviations from the requirements for work practice standards in Table 4 to this subpart that apply to you. If there were no periods during which the CMS, including CEMS, and operating parameter monitoring systems, was out of control as specified in § 63.8(c)(7), the report must also contain a statement that there were no periods during which the CMS was out of control during the reporting period.</i>	<i>Semiannually according to the requirements in § 63.5910(b).</i>
	<i>b. The information in § 63.5910(d) if you have a deviation from any emission limitation (emission limit, operating limit, or work practice standard) during the reporting period. If there were periods during which the CMS, including CEMS, and operating parameter monitoring systems, was out of control, as specified in § 63.8(c)(7), the report must contain the information in § 63.5910(e).</i>	<i>Semiannually according to the requirements in § 63.5910(b).</i>
	<i>c. The information in §63.10(d)(5)(i) if you had a startup, shutdown or malfunction during the reporting period, and you took actions consistent with your startup, shutdown, and malfunction plan.</i>	<i>Semiannually according to the requirements in § 63.5910(b).</i>
2. An immediate startup, shutdown, and malfunction report if you had a startup, shutdown, or malfunction during the reporting period that is not consistent with your startup, shutdown, and malfunction plan.	<i>a. Actions taken for the event</i>	<i>By fax or telephone within 2 working days after starting actions inconsistent with the plan.</i>

	<p><i>b. The information in § 63.10(d)(5)(ii)</i></p>	<p><i>By letter within 7 working days after the end of the event unless you have made alternative arrangements with the permitting authority. (§ 63.10(d)(5)(ii)).</i></p>
--	---	--

**E.3.3 One Time Deadlines Relating to NESHAP for Reinforced Plastic Composites Production [40 CFR Part 63, Subpart WWWW] [326 IAC 20-56]**

---

- (a) Pursuant to 40 CFR 63.5905, the Permittee must submit an Initial Notification by August 19, 2003.
  
- (b) The Permittee must submit a Notification of Compliance status report for source by May 21, 2007.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE AND ENFORCEMENT BRANCH**

**PART 70 OPERATING PERMIT  
CERTIFICATION**

Source Name: Supreme Corporation  
Source Address: 2572 East Kercher Road, Goshen, IN 46528  
Mailing Address: P.O. Box 463, Goshen, IN 46526  
Part 70 Permit No.: T039-21505-00103

**This certification shall be included when submitting monitoring, testing reports/results, or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE AND ENFORCEMENT BRANCH**

**100 North Senate Avenue  
MC 61-53 IGCN 1003  
Indianapolis, Indiana 46204  
Phone: 317-233-0178  
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT  
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: Supreme Corporation  
Source Address: 2572 East Kercher Road, Goshen, IN 46528  
Mailing Address: P.O. Box 463, Goshen, IN 46526  
Part 70 Permit No.: T039-21505-00103

**This form consists of 2 pages**

**Page 1 of 2**

<p>This is an emergency as defined in 326 IAC 2-7-1(12)</p> <ul style="list-style-type: none"><li><input type="checkbox"/> The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and</li><li><input type="checkbox"/> The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.</li></ul>
--

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

**Page 2 of 2**

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency?    Y    N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 COMPLIANCE AND ENFORCEMENT BRANCH**

**Part 70 Quarterly Report**

Source Name: Supreme Corporation  
 Source Address: 2572 East Kercher Road, Goshen, IN 46528  
 Mailing Address: P.O. Box 463, Goshen, IN 46526  
 Part 70 Permit No.: T039-21505-00103  
 Facilities: Surface coating and FRP production units, combined  
 Parameters: **VOC usage** for surface coating units H-1, H-2, H-3, A-1, I-1, I-2, 1-1, 1-2, 1-4, P-6, P-7, GM-2, 1-3, 1-6, 1-7, 1-8, 5-10, 5-12, 5-13, N-2, A-2, N-1, 2-15, SC-1, SC-2, SC-3, SC-4, PW-1, PW-2, and clean-up solvents  
 +  
**Actual VOC emissions** from all resins and gelcoats, based on input VOC and material specific emission factors, emission reduction techniques and emission controls from FRP production units M-1, M-2, M-4, M-3, M-5, M-9, M-6, M-7, M-8, B-1, B-2(a), B-2(b), N-3(a), N-3(b), Binks 115 areas, M-13(a) and M-13(b)  
 Limit: Two hundred and forty (240) tons of VOC per twelve (12) consecutive month period, with compliance to be determined at the end of each month.

YEAR: \_\_\_\_\_

Month	Total VOC Emissions This Month (tons)	Previous 11 Month VOC Emissions (tons)	12 Month Total VOC Emissions (tons)
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.  
 Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE AND ENFORCEMENT BRANCH**

**Part 70 Quarterly Report**

Source Name: Supreme Corporation  
Source Address: 2572 East Kercher Road, Goshen, IN 46528  
Mailing Address: P.O. Box 463, Goshen, IN 46526  
Part 70 Permit No.: T039-21505-00103  
Facilities: Spray booth I-1 and spray/bake booth I-2, combined, when coating FRP substrates  
Parameters: VOC usage  
Limit: Eighty (80) tons of VOC per twelve (12) consecutive month period, with compliance to be determined at the end of each month.

YEAR: \_\_\_\_\_

Month	Total VOC Emissions This Month (tons)	Previous 11 Month VOC Emissions (tons)	12 Month Total VOC Emissions (tons)
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.  
Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE AND ENFORCEMENT BRANCH**

**Part 70 Quarterly Report**

Source Name: Supreme Corporation  
Source Address: 2572 East Kercher Road, Goshen, IN 46528  
Mailing Address: P.O. Box 463, Goshen, IN 46526  
Part 70 Permit No.: T039-21505-00103  
Facility: Glue lamination spray unit 2-15  
Parameters: VOC usage  
Limit: Less than twenty-five (25) tons of VOC per twelve (12) consecutive month period, with compliance to be determined at the end of each month.

YEAR: \_\_\_\_\_

Month	Total VOC Emissions This Month (tons)	Previous 11 Month VOC Emissions (tons)	12 Month Total VOC Emissions (tons)
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.  
Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 COMPLIANCE AND ENFORCEMENT BRANCH**

**PART 70 OPERATING PERMIT  
 QUARTERLY DEVIATION and COMPLIANCE REPORT**

Source Name: Supreme Corporation  
 Source Address: 2572 East Kercher Road, Goshen, IN 46528  
 Mailing Address: P.O. Box 463, Goshen, IN 46526  
 Part 70 Permit No.: T039-21505-00103

**Months:** \_\_\_\_\_ **to** \_\_\_\_\_ **Year:** \_\_\_\_\_

<p>This report is an affirmation that the source has met all the requirements stated in this permit. This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

Form Completed by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
**Governor**

*Thomas W. Easterly*  
**Commissioner**

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

## **SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED**

**TO:** Larry York  
Supreme Corporation  
2572 E Kercher Road  
Goshen, Indiana 46528

**DATE:** May 22, 2009

**FROM:** Matt Stuckey, Branch Chief  
Permits Branch  
Office of Air Quality

**SUBJECT:** Final Decision  
Part 70  
039-27944-00103

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:  
Thomas Beard (Superior Corporation)  
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at [jbrush@idem.IN.gov](mailto:jbrush@idem.IN.gov).

Final Applicant Cover letter.dot 11/30/07

# Mail Code 61-53

IDEM Staff	CDENNY 5/22/2009 Supreme Corporation 039-27944-00103 (final)		Type of Mail:  <b>CERTIFICATE OF MAILING ONLY</b>	AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204		

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handing Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee	Remarks
1		Larry York Supreme Corporation 2572 E Kercher Rd Goshen IN 46528 (Source CAATS) <b>VIA CONFIRMED DELIVERY</b>										
2		Thomas A Beard VP - Ops Supreme Corporation 2572 E Kercher Rd Goshen IN 46528 (RO CAATS)										
3		Elkhart County Health Department 608 Oakland Avenue Elkhart IN 46516 (Health Department)										
4		Goshen City Council and Mayors Office 202 South 5th Street Suite 1 Goshen IN 46528 (Local Official)										
5		Laurence A. McHugh Barnes & Thornburg 100 North Michigan South Bend IN 46601-1632 (Affected Party)										
6		Mr. Kevin Parks D & B Environmental Services, Inc. 401 Lincoln Way West Oceola IN 46561 (Consultant)										
7		Elkhart County Board of Commissioners 117 North Second St. Goshen IN 46526 (Local Official)										
8												
9												
10												
11												
12												
13												
14												
15												

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See <b>Domestic Mail Manual R900, S913, and S921</b> for limitations of coverage on inured and COD mail. See <b>International Mail Manual</b> for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
<b>6</b>			