



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

TO: Interested Parties / Applicant

DATE: August 28, 2009

RE: Cummins Industrial Center / 071-27977-00015

FROM: Matthew Stuckey, Branch Chief  
Permits Branch  
Office of Air Quality

## Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-17-3-4 and 326 IAC 2, this approval is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-7-3 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures  
FNPER-MOD.dot 12/3/07



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels, Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

David Wehrkamp  
Cummins Industrial Center  
800 East Third Street,  
Seymour, Indiana 47274

August 28, 2009

Re: SPM 071-27977-00015  
Significant Permit Modification to  
Part 70 Renewal No.: T 071-21065-00015

Dear Wehrkamp:

Cummins Industrial Center was issued a Part 70 Operating Permit Renewal on December 28, 2006 for an internal combustion engine manufacturing plant, of which the testing and painting of the product is included. A letter requesting changes to this permit was received on March 27, 2009. Pursuant to the provisions of 326 IAC 2-7-12 a significant permit modification to this permit is hereby approved as described in the attached Technical Support Document.

All other conditions of the permit shall remain unchanged and in effect. For your convenience, the entire Part 70 Operating Permit as modified will be provided at issuance.

This decision is subject to the Indiana Administrative Orders and Procedures Act – IC 4-21.5-3-5. If you have any questions on this matter, please contact Josiah Balogun, OAQ, 100 North Senate Avenue, MC 61-53, Room 1003, Indianapolis, Indiana, 46204-2251, or call at (800) 451-6027, and ask for Josiah Balogun or extension (4-5257), or dial (317) 234-5257.

Sincerely,

Tripurari P. Sinha, Ph.D., Section Chief  
Permits Branch  
Office of Air Quality

Attachments:  
Updated Permit  
Technical Support Document  
PTE Calculations

JB

cc: File – Jackson County  
Jackson County Health Department  
U.S. EPA, Region V  
Compliance and Enforcement Branch



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
Governor

*Thomas W. Easterly*  
Commissioner

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

## PART 70 OPERATING PERMIT OFFICE OF AIR QUALITY


**Cummins Industrial Center  
800 East Third Street  
Seymour, Indiana 47274**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

**The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.**

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17. This permit addresses new source review requirements for existing equipment and is intended to fulfill the new source review procedures, pursuant to 326 IAC 2-7-10.5, applicable to those conditions.

Operation Permit No.: T071-21065-00015	
Issued by: Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: December 28, 2006  Expiration Date: December 28, 2011

First Significant Permit Modification No.: SPM 071-27977-00015	
Issued by:  Tripurari P. Sinha, Ph.D., Section Chief Permits Branch Office of Air Quality	Issuance Date: August 28, 2009  Expiration Date: December 28, 2011

## TABLE OF CONTENTS

### A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]
- A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
- A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

### B GENERAL CONDITIONS

- B.1 Definitions [326 IAC 2-7-1]
- B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]
- B.3 Term of Conditions [326 IAC 2-1.1-9.5]
- B.4 Enforceability [326 IAC 2-7-7]
- B.5 Severability [326 IAC 2-7-5(5)]
- B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]
- B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]
- B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3)and (13)][326 IAC 2-7-6(1)and(6)] [326 IAC 1-6-3]
- B.11 Emergency Provisions [326 IAC 2-7-16]
- B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]
- B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]
- B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
- B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
- B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]
- B.17 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4] [326 IAC 2-7-8(e)]
- B.18 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]
- B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]
- B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]
- B.21 Source Modification Requirement [326 IAC 2-7-10.5]
- B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]
- B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]
- B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]
- B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314][326 IAC 1-1-6]

### C SOURCE OPERATION CONDITIONS

#### Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Operation of Equipment [326 IAC 2-7-6(6)]
- C.7 Stack Height [326 IAC 1-7]
- C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

#### Testing Requirements [326 IAC 2-7-6(1)]

- C.9 Performance Testing [326 IAC 3-6]

#### Compliance Requirements [326 IAC 2-1.1-11]

- C.10 Compliance Requirements [326 IAC 2-1.1-11]

#### Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.12 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]
- C.13 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

- C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
- C.16 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]
- C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]
- C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

**Stratospheric Ozone Protection**

- C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

**D.1 FACILITY OPERATION CONDITIONS – Paint Spray Line EU-01**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.1.1 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3]
- D.1.2 Volatile Organic Compounds (VOC) [326 IAC 8-2-9]
- D.1.3 Volatile Organic Compounds (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9]
- D.1.4 Hazardous Air Pollutants
- D.1.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.1.6 Volatile Organic Compounds (VOC)[326 IAC 8-1-2]
- D.1.7 Volatile Organic Compounds (VOC)[326 IAC 8-1-2][326 IAC 8-1-4]

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

- D.1.8 Particulate Control
- D.1.9 Monitoring

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- D.1.10 Record Keeping Requirements
- D.1.11 Reporting Requirements

**D.2 FACILITY OPERATION CONDITIONS - Engine Test Cells EU-02**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.2.1 PSD Minor Limit [326 IAC 2-2]
- D.2.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

- D.2.3 Visible Emissions Notations

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

- D.2.4 Record Keeping Requirements
- D.2.5 Reporting Requirements

**D.3 FACILITY OPERATION CONDITIONS - Boilers EU-03**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- D.3.1 Particulate Matter Limitation (PM) [326 IAC 6-2-3]
- D.3.2 Sulfur Dioxide (SO<sub>2</sub>) [326 IAC 7-1.1-1] [326 IAC 7-2-1]
- D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

**Compliance Determination Requirements**

- D.3.4 Sulfur Dioxide Emissions and Sulfur Content

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

D.3.5 Visible Emissions Notations

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.3.6 Record Keeping Requirements

D.3.7 Reporting Requirements

**D.4 FACILITY OPERATION CONDITIONS - Insignificant Activities**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

D.4.1 Volatile Organic Compounds (VOC)

D.4.2 Volatile Organic Compounds (VOC)

D.4.3 Standards of Performance for Volatile Organic Liquid Storage Vessels [326 IAC 12]  
[40 CFR 60.116b, Subpart Kb]

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

D.4.4 Standards of Performance for Volatile Organic Liquid Storage Vessels [326 IAC 12]  
[40 CFR 60.116b, Subpart Kb]

**Certification**

**Emergency Occurrence Report**

**Part 70 Quarterly Reports**

**Quarterly Deviation and Compliance Monitoring Report**

## SECTION A

## SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

---

The Permittee owns and operates a stationary internal combustion engine manufacturing plant, of which the testing and painting of the product is included.

Source Address: 800 East Third Street, Seymour, Indiana 47274  
Mailing Address: Same  
General Source Phone Number: (812)524-6325  
SIC Code: 3519  
County Location: Jackson  
Source Location Status: Attainment for all criteria pollutants  
Source Status: Part 70 Permit Program  
Minor under PSD;  
Minor Source, Section 112 of the Clean Air Act

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) paint spray line, identified as EU-01, consisting of the following equipment:
- (1) One (1) primer spray booth, identified as EU-01A, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stacks S1 and S2.
  - (2) One (1) top coat spray booth, identified as EU-01B, constructed in 1995, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stacks S3 and S4.
  - (3) One (1) touch-up spray booth, identified as EU-01C, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stacks S5 and S6.
  - (4) One (1) offline spray booth, identified as EU-01D, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stack S7.
  - (5) One (1) small parts spray booth, identified as EU-01F, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stack S8.
- (b) Six (6) production engine test cells, identified as EU-02A, constructed in 1978, consisting of the following equipment:
- (1) Three (3) diesel-powered production engine test cells, identified as 801, 802, and 803, with maximum outputs of 1000, 1000 and 1650 hp respectively, with heat inputs of 6.41, 6.41 and 10.57 MMBtu/hr, respectively and exhausting to stacks 801.1 - 801.2, 802.1 - 802.2, and 803.1 and 803.2, respectively;
  - (2) Two (2) diesel-powered production engine test cells, identified as 804 and 805, with maximum outputs of 1650 hp, each, with heat input of 10.57 MMBtu/hr each and exhausting to stacks 804 and 805, respectively; and

- (3) One (1) diesel-powered or natural gas-fired production engine test cell, identified as 808, with maximum output of 1650 hp when combusting diesel fuel or 600hp when combusting natural gas, with heat input of 10.57 MMBtu/hr when combusting diesel fuel or 4.1 MMBtu/hr when combusting natural gas and exhausting to stack 808.
- (c) Ten (10) engineering engine test cells, identified as EU-02B, installed in 1978, consisting of the following equipment:
- (1) Two (2) diesel or biodiesel-powered engineering engine test cells, identified as 806 and 807, may be alternatively powered by liquid propane or natural gas with maximum outputs of 1800 hp, each, when combusting diesel or biodiesel, or 1800hp, each, when combusting liquid propane or natural gas and exhausting to stacks 806 and 807, respectively;
  - (2) One (1) diesel or biodiesel-powered engineering engine test cells, identified as HHP1, may be alternatively powered by liquid propane or natural gas, with maximum output of 4500 hp, when combusting diesel or biodiesel or 2200 hp when combusting liquid propane or natural gas, with heat input of 28.82 MMBtu/hr when combusting diesel or biodiesel or 14.40 MMBtu/hr when combusting liquid propane and natural gas and exhausting to stack HHP1;
  - (3) One (1) diesel or biodiesel-powered engineering engine test cells, identified as HHP2, with maximum output of 4500 hp when combusting diesel or biodiesel, with heat input of 28.82 MMBtu/hr and exhausting to stack HHP2;
  - (4) One (1) diesel or biodiesel-powered engineering engine test cell, identified as HHP3, may be alternatively powered by liquid propane or natural gas, with maximum output of 4500 hp when combusting diesel or biodiesel and 4500hp when combusting liquid propane or natural gas, with heat input of 28.82 MMBtu/hr when combusting diesel/biodiesel or liquid propane/natural gas and exhausting to stacks HHP3.1 and HHP3.2;
  - (5) One (1) diesel or biodiesel-powered engineering test cell, identified as HHP5, may be alternatively powered by liquid propane or natural gas, with output of 2200 hp when combusting diesel or biodiesel or 600 hp when combusting liquid propane or natural gas, with heat input of 14.09 MMBtu/hr when combusting diesel or biodiesel or 4.10 when combusting liquid propane or natural gas and exhausting to stack HHP5.1 - HHP5.2;
  - (6) One (1) diesel or biodiesel-powered engine test pad 8 (PI), identified as PI, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 3000 hp when combusting diesel or biodiesel or 2200 hp when combusting liquid propane or natural gas, with heat input of 19.22 MMBtu/hr when combusting diesel or biodiesel and 14.40 MMBtu/hr when combusting liquid propane or natural gas and exhausting to stacks PD8.1 and PD8.2;
  - (7) Two (2) diesel or biodiesel-powered engine test pad 10(PI) and 11(PI), identified as PI, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 1850, each, when combusting diesel, or biodiesel, or 1850 hp, each when combusting liquid propane or natural gas, with heat input of 11.85 MMBtu/hr, each, when combusting diesel, or biodiesel or 12.70 MMBtu/hr, each when combusting liquid propane or natural gas and exhausting to stacks PD10.1 and PD11.1; and
  - (8) One (1) diesel or biodiesel-powered engineering engine test cell, identified as HHP4, may be alternatively powered by liquid propane or natural gas, with a maximum output of 2200 hp when combusting diesel or biodiesel and 2200hp when combusting liquid propane or natural gas and a heat input of 14.09 MMBtu per hour when combusting diesel or biodiesel or 14.40 MMBtu/hr when combusting liquid propane or natural gas and exhausting to stacks HHP4.1 and HHP4.2.
- (d) One (1) diesel or biodiesel-powered engineering engine test cell Test Pad 9, identified as EU-02C, installed in 2005, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 4500 hp when combusting diesel or biodiese or 2200 hp when combusting liquid propane or natural gas, exhausting to stacks PD9.1 and PD9.2.

- (e) Two (2) natural gas-fired boilers with No.2 fuel oil backup, identified as EU-03A and EU-03B, installed in 1978, exhausting to stacks B1 and B2, respectively, each rated at 20.9 MMBtu per hour.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. [326 IAC 8-3];
- (b) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment. [326 IAC 6-3];
- (c) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations. [326 IAC 6-3]; and
- (d) One (1) 25,000 gallon No.2 diesel storage tank. [326 IAC 12] [40 CFR 60.116b, Subpart Kb]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

## SECTION B

## GENERAL CONDITIONS

### B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

### B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]

- (a) This permit, T071-21065-00015, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

### B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

### B.4 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

### B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

### B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

### B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U.S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

### B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.

- (c) A responsible official is defined at 326 IAC 2-7-1(34).

**B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]**

---

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
- (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was continuous or intermittent;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
  - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]**

---

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

- (b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

**B.11 Emergency Provisions [326 IAC 2-7-16]**

---

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
  - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or  
Telephone Number: 317-233-0178 (ask for Compliance Section)  
Facsimile Number: 317-233-6865

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification, which shall be submitted by the Permittee, does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
  - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
  - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
  - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and

- (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

**B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5] [326 IAC 2-7-10.5]**

---

- (a) All terms and conditions of permits established prior to T017-21065-00015 and issued pursuant to permitting programs approved into the state implementation plan have been:
  - (1) incorporated as originally stated,
  - (2) revised under 326 IAC 2-7-10.5, or
  - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this combined permit, all previous registrations and permits are superseded by this combined new source review and part 70 operating permit

**B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]**

---

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

**B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]**

---

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

**B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]**

---

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible

official” as defined by 326 IAC 2-7-1(34).

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
  - (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

**B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]**

---

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Administration and Support Section (PASS), Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
  - (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
  - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.

**B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]**

---

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Administration and Support Section (PASS), Office of Air Quality  
100 North Senate Avenue

MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Administration and Support Section (PASS), Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b), (c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;

- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]  
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

**B.21 Source Modification Requirement [326 IAC 2-7-10.5]**

---

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

**B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]**

---

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

**B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]**

---

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management  
Permits Administration and Support Section (PASS), Office of Air Quality

100 North Senate Avenue  
Indianapolis, Indiana 46204-2251

The application, which shall be submitted by the Permittee, does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. In the event that the source is a sub-contractor and is combined with a larger Part 70 source, the larger Part 70 source may pay the Permittees' annual fees as part of the larger source billing and subject to the fee cap of the larger source. If, however, the larger Part 70 does not pay its annual Part permit fee, IDEM, OAQ will assess a separate fee in accordance with 326 IAC 2-7-19(c) to be paid by the Permittee. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.

The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 1-1-6][326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

**SECTION C**

**SOURCE OPERATION CONDITIONS**

**Entire Source**

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]  
Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.
- C.2 Opacity [326 IAC 5-1]  
Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:
- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
  - (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]  
The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]  
The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.
- C.5 Fugitive Dust Emissions [326 IAC 6-4]  
The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.
- C.6 Operation of Equipment [326 IAC 2-7-6(6)]  
Except as provided by statute, rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission unit(s) vented to the control equipment are in operation.
- C.7 Stack Height [326 IAC 1-7]  
The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted. The provisions of 326 IAC 1-7-1(3), 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4, and 326 IAC 1-7-5(a), (b), and (d) are not federally enforceable.
- C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]  
The Permittee shall comply with the applicable requirements of 326 IAC 14-10, 326 IAC 18, and 40 CFR 61.140.

**Testing Requirements [326 IAC 2-7-6(1)]**

- C.9 Performance Testing [326 IAC 3-6]  
(a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ, of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ, not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

### **Compliance Requirements [326 IAC 2-1.1-11]**

#### **C.10 Compliance Requirements [326 IAC 2-1.1-11]**

---

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.

### **Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

#### **C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

---

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance and Enforcement Branch, Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

#### **C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

---

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

#### **C.13 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum

reading for the normal range shall be no less than twenty percent (20%) of full scale.

- (b) The Permittee may request that the IDEM, OAQ, approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

### **Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

#### **C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

---

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on December 13, 1996.
- (b) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

#### **C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]**

---

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

#### **C.16 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]**

---

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
  - (1) initial inspection and evaluation;
  - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
  - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
  - (1) monitoring results;
  - (2) review of operation and maintenance procedures and records;
  - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
  - (1) monitoring data;
  - (2) monitor performance data, if applicable; and
  - (3) corrective actions taken.

**C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]**

---

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ, that retesting in one hundred and twenty (120) days is not practicable, IDEM, OAQ, may extend the retesting deadline.
- (c) IDEM, OAQ, reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

**C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]**

---

Pursuant to 326 IAC 2-6-3(b)(3), starting in 2006 and every three (3) years thereafter, the Permittee shall submit by July 1 of each year an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:

- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
- (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management  
Technical Support and Modeling Section, Office of Air Quality  
100 North Senate Avenue  
MC61-50 IGCN 1003  
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

**C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]**

---

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

**C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]**

---

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the

deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue  
MC61-53 IGCN 1003  
Indianapolis, Indiana 46204-2251

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

### **Stratospheric Ozone Protection**

#### **C.21 Compliance with 40 CFR 82 and 326 IAC 22-1**

---

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

## SECTION D.1

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]:

- (a) One (1) paint spray line, identified as EU-01, consisting of the following equipment:
- (1) One (1) primer spray booth, identified as EU-01A, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stacks S1 and S2.
  - (2) One (1) top coat spray booth, identified as EU-01B, constructed in 1995, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stacks S3 and S4.
  - (3) One (1) touch-up spray booth, identified as EU-01C, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stacks S5 and S6.
  - (4) One (1) offline spray booth, identified as EU-01D, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stack S7.
  - (5) One (1) small parts spray booth, identified as EU-01F, constructed in 1986, with a maximum capacity of 3 engines per hour, equipped with dry filters for overspray control, exhausting to stack S8.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.1.1 Particulate Emission Limitations for Manufacturing Processes [326 IAC 6-3]

Pursuant to 326 IAC 6-3-2 (Particulate emission limitations, work practices, and control technologies), part (d), the particulate from EU-01A, EU-01B, EU-01C, EU-01D and EU-01F shall be controlled by a dry filter, and the Permittee shall operate the control device in accordance with the manufacturer's specifications.

#### D.1.2 Volatile Organic Compounds (VOC) [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the Permittee shall not cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of three and five-tenths (3.5) pounds of VOC per gallon of coating excluding water for extreme performance coatings, delivered to spray applicators in EU-01A, EU-01B, EU-01C, EU-01D and EU-01F, computed on a volume weighted average basis.

#### D.1.3 Volatile Organic Compound (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9(f), all solvents sprayed from the application equipment at spray booths EU-01A, EU-01B, EU-01C, EU-01D, and EU-01F during cleanup or color changes shall be directed into containers. Said containers shall be closed as soon as the solvent spraying is complete. In addition, all waste solvent shall be disposed of in such a manner that minimizes evaporation.

#### D.1.4 Hazardous Air Pollutants (HAPs)

- (a) The amount of any individual HAP delivered to the coating applicators (EU-01A through D and F) from coatings, and dilution and cleaning solvents, shall be limited to less than seven (7) tons per twelve (12) consecutive month period with compliance demonstrated at the end of each month. This usage limit, combined with the limits in conditions D.2.1 and D.2.2, is required to limit the potential to emit of each HAP to less than ten (10) tons per twelve (12) consecutive month period for the entire source.
- (b) The combination of HAPs delivered to the coating applicators (EU-01A through D and F) from coatings, and dilution and cleaning solvents, shall be limited to less than nineteen (19) tons per twelve (12) consecutive month period with compliance demonstrated at the end of each month. This usage limit, combined with the limits in conditions D.2.1 and D.2.2, is required to limit the potential to emit of a combination of HAPs to less than twenty-five (25) tons per twelve consecutive month period for the entire source.

Compliance with these limits will make this source a minor source for HAPs.

**D.1.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]**

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for EU-01A, EU-01B, EU-01C, EU-01D and EU-01F and any control devices.

**Compliance Determination Requirements**

**D.1.6 Volatile Organic Compounds (VOC) [326 IAC 8-1-2]**

Compliance with the VOC content limit in condition D.1.2 shall be determined pursuant to 326 IAC 8-1-2(a)(7), using a volume weighted average of coatings on a daily basis. This volume weighted average shall be determined by the following equation:

$$A = \frac{\sum (C \times U)}{\sum U}$$

Where: A is the volume weighted average in pounds VOC per gallon less water as applied;  
C is the VOC content of the coating in pounds VOC per gallon less water as applied;  
U is the usage rate of the coating in gallons per day.

**D.1.7 Volatile Organic Compounds (VOC) [326 IAC 8-1-2] [326 IAC 8-1-4]**

Compliance with the VOC content contained in condition D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ (and local agency if applicable) reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

**D.1.8 Particulate Control**

The dry filters for particulate control shall be in operation and controlling particulate, at all times when spray booths EU-01A, EU-01B, EU-01C, EU-01D and EU-01F are in operation.

**D.1.9 Monitoring**

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating stacks (S1, S2, S3, S4, S5, S6, S7 and S8) while one (1) or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or evidence of overspray emissions, the Permittee shall take reasonable steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

**D.1.10 Record Keeping Requirements**

- (a) To document compliance with condition D.1.2, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken daily and shall be complete and sufficient to establish compliance with the VOC usage limit established in condition D.1.2.
  - (1) The VOC content of each coating material and solvent used less water.
  - (2) The amount of coating material and solvent used on a daily basis.
    - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS)

necessary to verify the type and amount used.

- (B) Solvent usage records shall differentiate between those added to coatings (dilution) and those used as cleanup solvent.
  - (3) The volume weighted average VOC content of the coatings used for each day.
  - (4) The daily cleanup solvent usage; and
  - (5) The total VOC usage for each day.
- (b) To document compliance with condition D.1.4, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken monthly and shall be complete and sufficient to establish compliance with the HAP emission limits established in condition D.1.4.
  - (1) The amount and HAP content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
  - (2) The total coating usage for each month; and
  - (3) The cleanup or dilution solvent usage for each month.
- (c) To document compliance with conditions D.1.5 and D.1.9, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.1.11 Reporting Requirements

A quarterly summary of the information to document compliance with conditions D.1.2 and D.1.4 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

## SECTION D.2 EMISSIONS UNIT OPERATION CONDITIONS

### Emissions Unit Description:

- (b) Six (6) production engine test cells, identified as EU-02A, constructed in 1978, consisting of the following equipment:
  - (1) Three (3) diesel-powered production engine test cells, identified as 801, 802, and 803, with maximum outputs of 1000, 1000 and 1650 hp respectively, with heat inputs of 6.41, 6.41 and 10.57 MMBtu/hr, respectively and exhausting to stacks 801.1 - 801.2, 802.1 - 802.2, and 803.1 and 803.2, respectively;
  - (2) Two (2) diesel-powered production engine test cells, identified as 804 and 805, with maximum outputs of 1650 hp, each, with heat input of 10.57 MMBtu/hr each and exhausting to stacks 804 and 805, respectively; and
  - (3) One (1) diesel-powered or natural gas-fired production engine test cell, identified as 808, with maximum output of 1650 hp when combusting diesel fuel or 600hp when combusting natural gas, with heat input of 10.57 MMBtu/hr when combusting diesel fuel or 4.1 MMBtu/hr when combusting natural gas and exhausting to stack 808.
  
- (c) Ten (10) engineering engine test cells, identified as EU-02B, installed in 1978, consisting of the following equipment:
  - (1) Two (2) diesel or biodiesel-powered engineering engine test cells, identified as 806 and 807, may be alternatively powered by liquid propane or natural gas with maximum outputs of 1800 hp, each, when combusting diesel or biodiesel, or 1800hp, each, when combusting liquid propane or natural gas and exhausting to stacks 806 and 807, respectively;
  - (2) One (1) diesel or biodiesel-powered engineering engine test cells, identified as HHP1, may be alternatively powered by liquid propane or natural gas, with maximum output of 4500 hp, when combusting diesel or biodiesel or 2200 hp when combusting liquid propane or natural gas, with heat input of 28.82 MMBtu/hr when combusting diesel or biodiesel or 14.40 MMBtu/hr when combusting liquid propane and natural gas and exhausting to stack HHP1;
  - (3) One (1) diesel or biodiesel-powered engineering engine test cells, identified as HHP2, with maximum output of 4500 hp when combusting diesel or biodiesel, with heat input of 28.82 MMBtu/hr and exhausting to stack HHP2;
  - (4) One (1) diesel or biodiesel-powered engineering engine test cell, identified as HHP3, may be alternatively powered by liquid propane or natural gas, with maximum output of 4500 hp when combusting diesel or biodiesel and 4500hp when combusting liquid propane or natural gas, with heat input of 28.82 MMBtu/hr when combusting diesel/biodiesel or liquid propane/natural gas and exhausting to stacks HHP3.1 and HHP3.2;
  - (5) One (1) diesel or biodiesel-powered engineering test cell, identified as HHP5, may be alternatively powered by liquid propane or natural gas, with output of 2200 hp when combusting diesel or biodiesel or 600 hp when combusting liquid propane or natural gas, with heat input of 14.09 MMBtu/hr when combusting diesel or biodiesel or 4.10 when combusting liquid propane or natural gas and exhausting to stack HHP5.1 - HHP5.2;
  - (6) One (1) diesel or biodiesel-powered engine test pad 8 (PI), identified as PI, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 3000 hp when combusting diesel or biodiesel or 2200 hp when combusting liquid propane or natural gas, with heat input of 19.22 MMBtu/hr when combusting diesel or biodiesel and 14.40 MMBtu/hr when combusting liquid propane or natural gas and exhausting to stacks PD8.1 and PD8.2;

- (7) Two (2) diesel or biodiesel-powered engine test pad 10(PI) and 11(PI), identified as PI, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 1850, each, when combusting diesel, or biodiesel, or 1850 hp, each when combusting liquid propane or natural gas, with heat input of 11.85 MMBtu/hr, each, when combusting diesel, or biodiesel or 12.70 MMBtu/hr, each when combusting liquid propane or natural gas and exhausting to stacks PD10.1 and PD11.1; and
- (8) One (1) diesel or biodiesel-powered engineering engine test cell, identified as HHP4, may be alternatively powered by liquid propane or natural gas, with a maximum output of 2200 hp when combusting diesel or biodiesel and 2200hp when combusting liquid propane or natural gas and a heat input of 14.09 MMBtu per hour when combusting diesel or biodiesel or 14.40 MMBtu/hr when combusting liquid propane or natural gas and exhausting to stacks HHP4.1 and HHP4.2.
- (d) One (1) diesel or biodiesel-powered engineering engine test cell Test Pad 9, identified as EU-02C, installed in 2005, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 4500 hp when combusting diesel or biodiese or 2200 hp when combusting liquid propane or natural gas, exhausting to stacks PD9.1 and PD9.2.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

**Emission Limitations and Standards [326 IAC 2-7-5(1)]**

**D.2.1 PSD Minor Limit [326 IAC 2-2]**

- (a) The total NOx emissions from the seventeen (17) engine test cells, known as EU-02A, EU-02B, and EU-02C shall not exceed 217.9 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

The NOx emissions shall be calculated by the following equation:

$$\begin{aligned} \text{NOx emissions} = & \text{(Diesel fuel burned by 801, 802, 803, 804, 805 and 808) x (Ef1 of NOx/gal of} \\ & \text{diesel fuel )} + \text{(Diesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5,} \\ & \text{8(PI), 10(PI), 11(PI), HHP4 and EU-02C) x (Ef2, of NOx/gal of diesel fuel)} \\ & + \\ & \text{(Natural gas burned by 806, 807, 808, HHP1, HHP3 HHP4, HHP5 and PI) x (Ef3} \\ & \text{of NOx/ft}^3 \text{ of natural gas)} \\ & + \\ & \text{(Biodiesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI) (PI),} \\ & \text{11(PI), HHP4 and EU-02C) x (Ef4 of NOx/gal of biodiesel fuel)} \\ & + \\ & \text{(Propane fuel burned by 806, 807, HHP1, HHP3, HHP5, 8(PI) 10(PI), 11(PI),} \\ & \text{HHP4 and EU-02C) x (Ef5 of NOx/gal of Propane fuel)} \end{aligned}$$

- (b) The NOx emissions shall not exceed:
  - (1) Ef1 = Emission Limit in pounds of NOx per gallon of diesel fuel for 801, 802, 803, 804, 805 and 808;
  - (2) Ef2 = Emission Limit in pounds of NOx per gallon of diesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C;
  - (3) Ef3 = Emission Limits in pounds of NOx per cubic foot of natural gas for 806, 807, 808, HHP1, HHP3 HHP4, HHP5 and PI;
  - (4) Ef4 = Emission Limit in pounds of NOx per gallon of biodiesel fuel for 806, 807, HHP1, HHP2,

HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C; and

- (5) Ef5 = Emission Limit in pounds of NOx per kilogallon of propane for 806, 807, HHP1, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C.

Compliance with these limits shall limit the NOx emissions from the engine test cells and other emission units to less than two hundred and fifty (250) tons per year and render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable to this source.

- (c) The total VOC emissions from the eleven (11) engine test cells, known as EU-02B, and EU-02C shall not exceed the 163.56 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

The VOC emissions shall be calculated by the following equation:

$$\begin{aligned} \text{VOC emissions} = & \text{(Diesel fuel burned by 801, 802, 803, 804, 805 and 808) x (Ef1 of VOC/gal of} \\ & \text{diesel fuel) + (Diesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5,} \\ & \text{8(PI), 10(PI), 11(PI), HHP4 and EU-02C) x Ef2, of NOx/gal of diesel fuel} \\ & + \\ & \text{(Biodiesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI) (PI),} \\ & \text{11(PI), HHP4 and EU-02C) x (Ef4 of VOC/gal of biodiesel fuel)} \\ & + \\ & \text{(Natural gas burned by 806, 807, 808, HHP4, HHP5 and PI) x (Ef3 of VOC /ft}^3 \text{ of} \\ & \text{natural gas) at a natural gas heat content of 1,020 MMBtu/ft}^3 \\ & + \\ & \text{(Propane fuel burned by 806, 807, HHP1, HHP3, HHP5, 8(PI) 10(PI), 11(PI),} \\ & \text{HHP4 and EU-02C) x (Ef5 of VOC/gal of Propane fuel)} \end{aligned}$$

- (d) The VOC emissions shall not exceed:

- (1) Ef1 = Emission Limit in pounds of VOC per gallon of diesel fuel for 801, 802, 803, 804, 805 and 808;
- (2) Ef2 = Emission Limit in pounds of VOC per gallon of diesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C;
- (3) Ef3 = Emission Limits in pounds of VOC per cubic foot of natural gas for 806, 807, 808, HHP1, HHP3 HHP4, HHP5 and PI;
- (4) Ef4 = Emission Limit in pounds of VOC per gallon of biodiesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C; and
- (5) Ef5 = Emission Limit in pounds of VOC per kilogallon of propane for 806, 807, HHP1, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C.

Compliance with these limits shall limit the VOC emissions from the Engine test cells and other emission units to less than two hundred and fifty (250) tons per year and render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable to this source.

- (e) The total CO emissions from the eleven (11) engine test cells, known as EU-02B, and EU-02C shall not exceed 183.62 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

The CO emissions shall be calculated by the following equation:

$$\text{CO emissions} = \text{(Diesel fuel burned by 801, 802, 803, 804, 805 and 808) x (Ef1 of CO/gal of diesel fuel) + (Diesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C) x Ef2, of NOx/gal of diesel fuel}$$

+

(Biodiesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI) (PI), 11(PI), HHP4 and EU-02C) x (Ef4 of CO/gal of biodiesel fuel)

+

(Natural gas burned by 806, 807, 808, HHP4, HHP5 and PI) x (Ef3 of CO/ft<sup>3</sup> of natural gas)

+

(Propane fuel burned by 806, 807, HHP1, HHP3, HHP5, 8(PI) 10(PI), 11(PI), HHP4 and EU-02C) x (Ef5 of CO/gal of Propane fuel)

(f) The CO emissions shall not exceed:

- (1) Ef1 = Emission Limit in pounds of CO per gallon of diesel fuel for 801, 802, 803, 804, 805 and 808;
- (2) Ef2 = Emission Limit in pounds of CO per gallon of diesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C;
- (3) Ef3 = Emission Limits in pounds of CO per cubic foot of natural gas for 806, 807, 808, HHP1, HHP3 HHP4, HHP5 and PI;
- (4) Ef4 = Emission Limit in pounds of CO per gallon of biodiesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C; and
- (5) Ef5 = Emission Limit in pounds of CO per kilogallon of propane for 806, 807, HHP1, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C.

Compliance with these limits shall limit the CO emissions from the engine test cells and other emission units to less than two hundred and fifty (250) tons per year and render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable to this source.

#### D.2.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for EU-02A, EU-02B, and EU-02C and their control devices.

#### Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

#### D.2.3 Visible Emissions Notations

- (a) Visible emissions notations of the engine test cell stack exhausts (801.1 -801.2, 802.1 -802.2, 803.1-803.2, 804 through 808, HHP1, HHP2, HHP3.1 -HHP3.2, HHP4.1-HHP4.2, HHP5.1-HHP5.2, PD8.1-PD8.2, PD9.1 and PD9.2, PD10.1 and PD11.1) shall be performed once per day during normal daylight operations when combusting diesel fuel or biodiesel. A trained employee will record whether emissions are normal or abnormal.
- (b) For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

#### Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

#### D.2.4 Record Keeping Requirements

---

- (a) To document compliance with condition D.2.1, the Permittee shall maintain records in accordance with (1) and (3) below:
  - (1) Calendar dates covered in the compliance determination period; and
  - (2) Actual diesel, biodiesel fuel oil or propane usage for EU-02A, EU-02B, and EU-02C since last compliance determination period and equivalent NOx emissions.
  - (3) Actual natural gas usage for EU-02A and EU-02B since last compliance determination period and equivalent NOx emissions.
- (b) To document compliance with condition D.2.3 - Visible Emission Notation, the Permittee shall maintain records of daily visible emission notations of the stack exhausts listed, when combusting diesel fuel or biodiesel. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation, (e.g. the process did not operate that day).
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### D.2.5 Reporting Requirements

---

A quarterly summary of the information to document compliance with condition D.2.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

## SECTION D.3

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]:

- (e) Two (2) natural gas-fired boilers with No.2 fuel oil backup, identified as EU-03A and EU-03B, installed in 1978, exhausting to stacks B1 and B2, respectively, each rated at 20.9 MMBtu per hour.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.3.1 Particulate Matter (PM) Limitation [326 IAC 6-2-3]

Pursuant to 326 IAC 6-2-3(e), the PM emissions from boilers, EU-03A and EU-03B, shall each be limited to 0.6 pounds per million British thermal units heat input.

#### D.3.2 Sulfur Dioxide (SO<sub>2</sub>) [326 IAC 7-1.1-1] [326 IAC 7-2-1]

Pursuant to 326 IAC 7-1.1 (SO<sub>2</sub> Emissions Limitations) the SO<sub>2</sub> emissions from each boiler (EU-03A and EU-03B) shall not exceed five tenths (0.5) pounds per million British thermal units heat input while combusting fuel oil. Pursuant to 326 IAC 7-2-1, compliance shall be demonstrated on a thirty (30) day rolling weighted average. 326 IAC 7-1.1 and 326 IAC 7-2-1 are not federally enforceable.

#### D.3.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

### Compliance Determination Requirements

#### D.3.4 Sulfur Dioxide Emissions and Sulfur Content

Compliance shall be determined utilizing one of the following options for each boiler (EU-03A and EU-03B).

- (a) Pursuant to 326 IAC 3-7-4, the Permittee shall demonstrate that the sulfur dioxide emissions do not exceed five-tenths (0.5) pounds per million British thermal units heat input by:
- (1) Providing vendor analysis of fuel delivered, if accompanied by a vendor certification, or;
  - (2) Analyzing the oil sample to determine the sulfur content of the oil via the procedures in 40 CFR 60, Appendix A, Method 19.
    - (A) Oil samples may be collected from the fuel tank immediately after the fuel tank is filled and before any oil is combusted; and
    - (B) If a partially empty fuel tank is refilled, a new sample and analysis would be required upon filling.
- (b) Compliance may also be determined by conducting a stack test for sulfur dioxide emissions from the boiler using 40 CFR 60, Appendix A, Method 6 in accordance with the procedures in 326 IAC 3-6.

A determination of noncompliance pursuant to any of the methods specified in (a) or (b) above shall not be refuted by evidence of compliance pursuant to the other method.

### Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

#### D.3.5 Visible Emissions Notations

- (a) Visible emission notations of the boiler stack exhausts (B1 and B2) shall be performed once per day during normal daylight operations while combusting fuel oil. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail,

eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.

- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

### **Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

#### **D.3.6 Record Keeping Requirements**

---

- (a) To document compliance with condition D.3.2, the Permittee shall maintain records in accordance with (1) through (6) below.
  - (1) Calendar dates covered in the compliance determination period;
  - (2) Actual fuel oil usage since last compliance determination period and equivalent sulfur dioxide emissions;
  - (3) A certification, signed by the owner or operator, that the records of the fuel supplier certifications represent all of the fuel combusted during the period, the natural gas fired boiler certification does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34); and

If the fuel supplier certification is used to demonstrate compliance the following, as a minimum, shall be maintained:

- (4) Fuel supplier certifications;
- (5) The name of the fuel supplier; and
- (6) A statement from the fuel supplier that certifies the sulfur content of the fuel oil.

The Permittee shall retain records of all recording/monitoring data and support information for a period of five (5) years, or longer if specified elsewhere in this permit, from the date of the monitoring sample, measurement, or report. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit.

- (b) To document compliance with condition D.3.5, the Permittee shall maintain records of visible emission notations of the boiler stack exhausts once per shift.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### **D.3.7 Reporting Requirements**

---

The Permittee shall certify, on the form provided, that natural gas was fired in each of the boilers at all times during each quarter on a semi-annual basis. Alternatively, the Permittee shall report the number of days during which an alternate fuel was burned during each quarter.

## SECTION D.4

## FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]:

- (a) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. [326 IAC 8-3]
- (b) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment. [326 IAC 6-3]
- (c) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4,000 actual cubic feet per minute, including the following: deburring; buffing; polishing; abrasive blasting; pneumatic conveying; and woodworking operations. [326 IAC 6-3]
- (d) One (1) 25,000 gallon No.2 diesel storage tank, constructed in 1998. [326 IAC 12] [40 CFR 60.116b, Subpart Kb]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.4.1 Volatile Organic Compounds (VOC)

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations) for cold cleaning operations constructed after January 1, 1980, the owner or operator shall:

- (a) Equip the cleaner with a cover;
- (b) Equip the cleaner with a facility for draining cleaned parts;
- (c) Close the degreaser cover whenever parts are not being handled in the cleaner;
- (d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;
- (e) Provide a permanent, conspicuous label summarizing the operation requirements;
- (f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

#### D.4.2 Volatile Organic Compounds (VOC)

(a) Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaner degreaser facility construction of which commenced after July 1, 1990 shall ensure that the following control equipment requirements are met:

- (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:
  - (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F));
  - (B) The solvent is agitated; or
  - (C) The solvent is heated.
- (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.

- (3) Provide a permanent, conspicuous label which lists the operating requirements outlined in subsection (b).
  - (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure which does not cause excessive splashing.
  - (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):
    - (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
    - (B) A water cover when solvent is used is insoluble in, and heavier than, water.
    - (C) Other systems of demonstrated equivalent control such as a refrigerated chiller or carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.
- (b) Pursuant to 326 IAC 8-3-5(b) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaning facility construction of which commenced after July 1, 1990 shall ensure that the following operating requirements are met:
- (1) Close the cover whenever articles are not being handled in the degreaser.
  - (2) Drain cleaned articles for at least fifteen (15) seconds or until dripping ceases.
  - (3) Store waste solvent only in covered containers and prohibit the disposal or transfer of waste solvent in any manner in which greater than twenty percent (20%) of the waste solvent by weight could evaporate.

**D.4.3 Standards of Performance for Volatile Organic Liquid Storage Vessels [326 IAC 12] [40 CFR 60.116b, Subpart Kb]**

The one (1) 25,000 gallon No.2 diesel storage tank shall comply with the New Source Performance Standards (NSPS), 326 IAC 12 (40 CFR Part 60.116b, Subpart Kb). 40 CFR Part 60.116b paragraphs (a) and (b) require the Permittee to maintain accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. Records shall be kept for the life of the storage tanks.

**Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

**D.4.4 Standards of Performance for Volatile Organic Liquid Storage Vessels [326 IAC 12] [40 CFR 60.116b, Subpart Kb]**

The Permittee shall maintain accessible records showing the dimension of the No.2 diesel storage tank and an analysis showing the capacity of the storage vessel. Records shall be kept for the life of the storage tank.

## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

### PART 70 OPERATING PERMIT CERTIFICATION

Source Name: Cummins Industrial Center  
Source Address: 800 East Third Street, Seymour, Indiana 47274  
Mailing Address: 800 East Third Street, Seymour, Indiana 47274  
Part 70 Permit Renewal No.: T071-21065-00015

**This certification shall be included when submitting monitoring, testing reports/results,  
or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Affidavit (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE BRANCH  
100 North Senate Avenue  
Indianapolis, Indiana 46204  
Phone: 317-233-0178  
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT  
EMERGENCY OCCURRENCE REPORT**

Source Name: Cummins Industrial Center  
Source Address: 800 East Third Street, Seymour, Indiana 47274  
Mailing Address: 800 East Third Street, Seymour, Indiana 47274  
Part 70 Permit Renewal No.: T071-21065-00015

**This form consists of 2 pages**

**Page 1 of 2**

<input type="checkbox"/> This is an emergency as defined in 326 IAC 2-7-1(12)  <input type="checkbox"/> The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and  <input type="checkbox"/> The Permittee must submit notice by mail or facsimile within two (2) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.
--

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency?    Y    N
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by:

Title / Position:

Date:

Phone:

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**Quarterly Report for HAPs Usage**

Source Name: Cummins Industrial Center  
Source Address: 800 East Third Street, Seymour, Indiana 47274  
Mailing Address: 800 East Third Street, Seymour, Indiana 47274  
Part 70 Permit Renewal No.: T071-21065-00015  
Facility: EU-01  
Parameters: Combination of HAPs and Single HAP Usage  
Limits: Combination of HAPs less than nineteen (19) tons per twelve (12) consecutive month period with compliance determined at the end of each month, and/or single HAP less than seven (7) tons per twelve (12) consecutive month period with compliance determined at the end of each month.

QUARTER/YEAR: \_\_\_\_\_

Column 1	Column 2	Column 1 + Column 2
This Month	Previous 11 Months	12 Month Total

**COMBINATION HAPS**

Month 1			
Month 2			
Month 3			

**SINGLE HAP**

Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.  
Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 COMPLIANCE BRANCH**

**Part 70 Quarterly Report for Fuel Usage Limit**

Source Name: Cummins Industrial Center  
 Source Address: 800 East Third Street, Seymour, Indiana 47274  
 Mailing Address: 800 East Third Street, Seymour, Indiana 47274  
 Part 70 Renewal Permit No.: T071-21065-00015  
 Facilities: Seventeen (17) engine test cells, known as EU-02A, EU-02B and EU-02C  
 Parameter: NOx Emissions  
 Limit: NOx emissions shall not exceed 217.9 tons of NOx per twelve (12) consecutive month period

**YEAR:** \_\_\_\_\_

Month	This Month		EU-02 Equivalent NO <sub>x</sub> (tons) A + (B + C)	Previous 11 Months		EU-02 Equivalent NO <sub>x</sub> (tons) A + (B + C)	12 Month Total		EU-02 Equivalent NO <sub>x</sub> (tons) A + (B + C)
	EU-02 Diesel Fuel, biodiesel or propane (gallons) A	B + C		EU-02 Diesel Fuel, biodiesel or propane (gallons) A	B + C		EU-02 Diesel Fuel, biodiesel or propane (gallons) A	B + C	
	Natural Gas (cubic feet)			Natural Gas (cubic feet)			Natural Gas (cubic feet)		
	A	B		A	B		A	B	

<b>Total NOx Emissions from Diesel Fuel, Natural Gas, biodiesel or propane</b>	<b>Month</b>	<b>Month</b>	<b>Month</b>
<b>12 Month Total (tons)</b>			

- No deviation occurred in this quarter.
- Deviation(s) occurred in this quarter.  
 Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_

Title / Position: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**Part 70 Quarterly Report**

Source Name: Cummins Industrial Center  
Source Address: 800 East Third Street, Seymour Indiana 47274  
Mailing Address: 800 East Third Street, Seymour Indiana 47274  
Part 70 Permit No.: T071-21065-00015  
Facility: EU-02B and EU-02C  
Parameter: VOC  
Limit: Less than 163.56 tons per twelve (12) consecutive month period.

QUARTER :

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
Deviation has been reported on:

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**Part 70 Quarterly Report**

Source Name: Cummins Industrial Center  
Source Address: 800 East Third Street, Seymour Indiana 47274  
Mailing Address: 800 East Third Street, Seymour Indiana 47274  
Part 70 Permit No.: T071-21065-00015  
Facility: EU-02B and EU-02C  
Parameter: CO  
Limit: Less than 183.62 tons per twelve (12) consecutive month period.

QUARTER :

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
Deviation has been reported on:

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT  
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Cummins Industrial Center  
Source Address: 800 East Third Street, Seymour, Indiana 47274  
Mailing Address: 800 East Third Street, Seymour, Indiana 47274  
Part 70 Permit Renewal No.: T071-21065-00015

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	
<b>Permit Requirement</b> (specify permit condition #)	
<b>Date of Deviation:</b>	<b>Duration of Deviation:</b>
<b>Number of Deviations:</b>	
<b>Probable Cause of Deviation:</b>	
<b>Response Steps Taken:</b>	

Form Completed By:

Title/Position:

Date:

Phone:

Attach a signed certification to complete this report.

**Indiana Department of Environmental Management  
Office of Air Quality**

**Technical Support Document (TSD) for a Part 70 Significant Source and Permit Modification.**

**Source Description and Location**

Source Name:	Cummins Industrial Center
Source Location:	800 East Third Street, Seymour, IN 47274
County:	Jackson
SIC Code:	3519
Operation Permit No.:	T 071-21065-00015
Operation Permit Issuance Date:	December 28, 2006
Significant Source Modification No.:	071-27821-00015
Significant Permit Modification No.:	071-27977-00015
Permit Reviewer:	Josiah Balogun

**Existing Approvals**

The source was issued Part 70 Operating Permit No. 071-21065-00015 on December 28, 2006. The source has since received the following approvals:

- (a) Minor Source Modification No. 071-27683-00015, issued on April 30, 2009.
- (b) Minor Permit Modification No. 071-27806-00015, issued on June 24, 2009.

**County Attainment Status**

The source is located in Jackson County.

Pollutant	Designation
SO <sub>2</sub>	Better than national standards.
CO	Unclassifiable or attainment effective November 15, 1990.
O <sub>3</sub>	Attainment effective December 29, 2005, for the 8-hour ozone standard. <sup>1</sup>
PM <sub>10</sub>	Unclassifiable effective November 15, 1990.
NO <sub>2</sub>	Cannot be classified or better than national standards.
Pb	Not designated.
<sup>1</sup> Unclassifiable or attainment effective October 18, 2000, for the 1-hour ozone standard which was revoked effective June 15, 2005. Unclassifiable or attainment effective April 5, 2005, for PM2.5.	

- (a) **Ozone Standards**  
Volatile organic compounds (VOC) and Nitrogen Oxides (NOx) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NOx emissions are considered when evaluating the rule applicability relating to ozone. Jackson County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (b) **PM2.5**  
Jackson County has been classified as attainment for PM2.5. On May 8, 2008 U.S. EPA promulgated the requirements for Prevention of Significant Deterioration (PSD) for PM2.5 emissions, and the effective date of these rules was July 15<sup>th</sup>, 2008. Indiana has three

years from the publication of these rules to revise its PSD rules, 326 IAC 2-2, to include those requirements. The May 8, 2008 rule revisions require IDEM to regulate PM10 emissions as a surrogate for PM2.5 emissions until 326 IAC 2-2 is revised.

- (c) **Other Criteria Pollutants**  
Jackson County has been classified as attainment or unclassifiable in Indiana for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (d) **Fugitive Emissions**  
Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2, fugitive emissions are not counted toward the determination of PSD.

### Source Status

The table below summarizes the potential to emit of the entire source, prior to the proposed modification, after consideration of all enforceable limits established in the effective permits:

Pollutant	Emissions (ton/yr)
PM	28.97
PM <sub>10</sub>	28.97
SO <sub>2</sub>	62.89
VOC	86.34
CO	66.28
NO <sub>x</sub>	< 250

- (a) This existing source is not a major stationary source, under PSD (326 IAC 2-2), because no regulated pollutant is emitted at a rate of 250 tons per year or more, and it is not one of the twenty-eight (28) listed source categories, as specified in 326 IAC 2-2-1(gg)(1).
- (b) These emissions are based upon T 071-21065-00015, issued on December 28, 2006.

The table below summarizes the potential to emit HAPs for the entire source, prior to the proposed modification, after consideration of all enforceable limits established in the effective permits:

HAPs	Potential To Emit (ton/yr)
Single HAP	< 10
Total HAPs	< 25

This existing source is not a major source of HAPs, as defined in 40 CFR 63.2, because HAPs emissions are less than ten (10) tons per year for any single HAP and less than twenty-five (25) tons per year of a combination of HAPs. Therefore, this source is an area source under Section 112 of the Clean Air Act (CAA).

### Description of Proposed Modification

The Office of Air Quality (OAQ) has reviewed a modification application, submitted by Cummins Industrial Center on March 27, 2009 and on April 21 2009, requesting the flexibility to power their test cells with different fuels and also to increase the capacity of these test cells. The following are the list of the modified emission unit(s):

- (a) Ten (10) engineering engine test cells, identified as EU-02B, installed in 1978, consisting of the following equipment:

- (1) Two (2) diesel or biodiesel-powered engineering engine test cells, identified as 806 and 807, may be alternatively powered by liquid propane or natural gas with maximum outputs of 1800 hp, each, when combusting diesel or biodiesel, or 1800hp, each, when combusting liquid propane or natural gas and exhausting to stacks 806 and 807, respectively;
  - (2) One (1) diesel or biodiesel-powered engineering engine test cells, identified as HHP1, may be alternatively powered by liquid propane or natural gas, with maximum output of 4500 hp, when combusting diesel or biodiesel or 2200 hp when combusting liquid propane or natural gas, with heat input of 28.82 MMBtu/hr when combusting diesel or biodiesel or 14.40 MMBtu/hr when combusting liquid propane and natural gas and exhausting to stack HHP1;
  - (3) One (1) diesel or biodiesel-powered engineering engine test cells, identified as HHP2, with maximum output of 4500 hp when combusting diesel or biodiesel, with heat input of 28.82 MMBtu/hr and exhausting to stack HHP2;
  - (4) One (1) diesel or biodiesel-powered engineering engine test cell, identified as HHP3, may be alternatively powered by liquid propane or natural gas, with maximum output of 4500 hp when combusting diesel or biodiesel and 4500hp when combusting liquid propane or natural gas, with heat input of 28.82 MMBtu/hr when combusting diesel/biodiesel or liquid propane/natural gas and exhausting to stacks HHP3.1 and HHP3.2;
  - (5) One (1) diesel or biodiesel-powered engineering test cell, identified as HHP5, may be alternatively powered by liquid propane or natural gas, with output of 2200 hp when combusting diesel or biodiesel or 600 hp when combusting liquid propane or natural gas, with heat input of 14.09 MMBtu/hr when combusting diesel or biodiesel or 4.10 when combusting liquid propane or natural gas and exhausting to stack HHP5.1 - HHP5.2;
  - (6) One (1) diesel or biodiesel-powered engine test pad 8 (PI), identified as PI, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 3000 hp when combusting diesel or biodiesel or 2200 hp when combusting liquid propane or natural gas, with heat input of 19.22 MMBtu/hr when combusting diesel or biodiesel and 14.40 MMBtu/hr when combusting liquid propane or natural gas and exhausting to stacks PD8.1 and PD8.2;
  - (7) Two (2) diesel or biodiesel-powered engine test pad 10(PI) and 11(PI), identified as PI, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 1850, each, when combusting diesel, or biodiesel, or 1850 hp, each when combusting liquid propane or natural gas, with heat input of 11.85 MMBtu/hr, each, when combusting diesel, or biodiesel or 12.70 MMBtu/hr, each when combusting liquid propane or natural gas and exhausting to stacks PD10.1 and PD11.1; and
  - (8) One (1) diesel or biodiesel-powered engineering engine test cell, identified as HHP4, may be alternatively powered by liquid propane or natural gas, with a maximum output of 2200 hp when combusting diesel or biodiesel and 2200hp when combusting liquid propane or natural gas and a heat input of 14.09 MMBtu per hour when combusting diesel or biodiesel or 14.40 MMBtu/hr when combusting liquid propane or natural gas and exhausting to stacks HHP4.1 and HHP4.2.
- (b) One (1) diesel or biodiesel-powered engineering engine test cell Test Pad 9, identified as EU-02C, installed in 2005, may be alternatively powered by liquid propane or natural gas, with maximum outputs of 4500 hp when combusting diesel or biodiese or 2200 hp when combusting liquid propane or natural gas, exhausting to stacks PD9.1 and PD9.2.

**Enforcement Issues**

There are no pending enforcement actions related to this modification.

**Emission Calculations**

See Appendix A of this document for detailed emission calculations.

**Permit Level Determination – Part 70**

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emission unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, IDEM, or the appropriate local air pollution control agency.”

The following table is used to determine the appropriate permit level under 326 IAC 2-7-10.5. This table reflects the change in PTE of the modification before controls due to change in use of different fuels. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

<b>Pollutant</b>	<b>Potential To Emit Worst case (tons/year)</b>
PM	99.1
PM10	99.1
SO <sub>2</sub>	92.57
VOC	505.43
CO	785.54
NO <sub>x</sub>	1003.1

This source modification is subject to 326 IAC 2-7-10.5(f). Additionally, the modification will be incorporated into the Part 70 Operation Permit through a significant permit modification issued pursuant to 326 IAC 2-7-12(d) because this permit modification requires a case-by-case determination of emission limits.

**Permit Level Determination – PSD**

The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered federally enforceable only after issuance of this Part 70 permit modification, and only to the extent that the effect of the control equipment is made practically enforceable in the permit.

Process/Emission Unit	PM (tons/yr)	PM10 (tons/yr)	SO <sub>2</sub> (tons/yr)	VOC (tons/yr)	CO (tons/yr)	NO <sub>x</sub> (tons/yr)
Total emission before Modification	28.97	28.97	62.89	86.34	66.28	< 250
Total for Modification	99.10	99.10	92.57	< 250	< 250	< 250
Total After Modification	128.07	128.07	155.46	< 250	< 250	< 250
Major source Threshold	250	250	250	250	250	250

This modification to an existing minor stationary source is not major because the source wide emissions of all pollutants will still be less than the PSD major source threshold. Therefore, the requirements of 326 IAC 2-2 (PSD) do not apply.

**Federal Rule Applicability Determination**

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this proposed modification.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs) (326 IAC 14, 326 IAC 20 and 40 CFR Part 63) applicable to this proposed modification.

**State Rule Applicability Determination**

**326 IAC 2-2 (PSD)**

PSD applicability is discussed under the Permit Level Determination - PSD section.

**Compliance Determination and Monitoring Requirements**

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with all applicable state and federal rules on a continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, Compliance Determination Requirements are included in the permit. The Compliance Determination Requirements in Section D of the permit are those conditions that are found directly within state and federal rules and the violation of which serves as grounds for enforcement action.

If the Compliance Determination Requirements are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

There are no Compliance Determination and monitoring Requirements applicable to this modification at this time:

**Proposed Changes**

The changes listed below have been made to Part 70 Operating Permit No.T071-21065-00015. Deleted language appears as ~~strike throughs~~ and new language appears in **bold**:

Change 1: The emission units descriptions have been revised in Condition A.2 and Section D.2 of the permit accordingly. The Visible Emission Notation and the record Keeping requirements have been updated in the permit.

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

.....  
(c) Ten (10) engineering engine test cells, identified as EU-02B, installed in 1978, consisting of the following equipment:

- (1) Two (2) diesel **or biodiesel**-powered engineering engine test cells, identified as 806 and 807, **may be alternatively powered by liquid propane or natural gas** with maximum outputs of 1800 hp, each, **when combusting diesel or biodiesel, or 1800hp, each, when combusting liquid propane or natural gas** and exhausting to stacks 806 and 807, respectively;
- (2) One (1) diesel **or biodiesel**-powered engineering engine test cells, identified as HHP1, **may be alternatively powered by liquid propane or natural gas**, with maximum output of 4500 hp, when combusting diesel **or biodiesel** or 2200 hp when combusting **liquid propane or natural gas**, with heat input of 28.82 MMBtu/hr when combusting diesel **or biodiesel** or 14.40 MMBtu/hr when combusting **liquid propane and natural gas** and exhausting to stack HHP1;
- (3) One (1) diesel **or biodiesel**-powered engineering engine test cells, identified as HHP2, with maximum output of 4500 hp when combusting diesel **or biodiesel**, with heat input of 28.82 MMBtu/hr and exhausting to stack HHP2;
- (4) One (1) diesel **or biodiesel**-powered engineering engine test cell, identified as HHP3, **may be alternatively powered by liquid propane or natural gas**, with maximum output of 4500 hp when combusting **diesel or biodiesel and 4500hp when combusting liquid propane or natural gas**, with heat input of 28.82 MMBtu/hr when combusting diesel/**biodiesel or liquid propane/natural gas** and exhausting to stacks HHP3.1 and HHP3.2;
- (5) One (1) diesel **or biodiesel**-powered engineering test cell, identified as HHP5, **may be alternatively powered by liquid propane or natural gas**, with output of 2200 hp when combusting diesel **or biodiesel** or 600 hp when combusting **liquid propane or natural gas**, with heat input of 14.09 MMBtu/hr when combusting diesel **or biodiesel** or 4.10 when combusting **liquid propane or natural gas** and exhausting to stack HHP5.1 - HHP5.2;
- (6) One (1) diesel **or biodiesel**-powered ~~or natural gas-fired outside~~ engine test pad 8 (PI), identified as PI, **may be alternatively powered by liquid propane or natural gas**, with maximum outputs of 3000 hp when combusting diesel **or biodiesel** or 2200 hp when combusting **liquid propane or natural gas**, with heat input of 19.22 MMBtu/hr when combusting diesel **or biodiesel** and 14.40 MMBtu/hr when combusting **liquid propane or natural gas** and exhausting to stacks PD8.1 and PD8.2;
- (7) Two (2) diesel **or biodiesel**-powered ~~or natural gas-fired outside~~ engine test pad

- 10(PI) and 11(PI), identified as PI, **may be alternatively powered by liquid propane or natural gas**, with maximum outputs of 1850, each, when combusting diesel, **or biodiesel, or 1850 hp, each when combusting liquid propane or natural gas**, with heat input of 11.85 MMBtu/hr, each, when combusting diesel, **or biodiesel** or 12.70 MMBtu/hr, each when combusting **liquid propane or natural gas** and exhausting to stacks PD10.1 and PD11.1; and
- (8) One (1) diesel **or biodiesel**-powered ~~or natural gas-fired~~ engineering engine test cell, identified as HHP4, **may be alternatively powered by liquid propane or natural gas**, with a maximum output of 2200 hp when combusting diesel **or biodiesel and 2200hp when combusting liquid propane or natural gas** and a heat input of 14.09 MMBtu per hour when combusting diesel **or biodiesel** or 14.40 MMBtu/hr when combusting **liquid propane or natural gas** and exhausting to stacks HHP4.1 and HHP4.2.
- (d) One (1) diesel **or biodiesel**-powered engineering engine test cell Test Pad 9, identified as EU-02C, installed in 2005, **may be alternatively powered by liquid propane or natural gas**, with maximum outputs of ~~3540~~ **4500** hp when combusting diesel **or biodiesel** or 2200 hp when combusting **liquid propane or natural gas**, exhausting to stacks PD9.1 and PD9.2.
- .....

## SECTION D.2 EMISSIONS UNIT OPERATION CONDITIONS

### Emissions Unit Description:

- .....
- (c) Ten (10) engineering engine test cells, identified as EU-02B, installed in 1978, consisting of the following equipment:
- (1) Two (2) diesel **or biodiesel**-powered engineering engine test cells, identified as 806 and 807, **may be alternatively powered by liquid propane or natural gas** with maximum outputs of 1800 hp, each, **when combusting diesel or biodiesel, or 1800hp, each, when combusting liquid propane or natural gas and** exhausting to stacks 806 and 807, respectively;
- (2) One (1) diesel **or biodiesel**-powered engineering engine test cells, identified as HHP1, **may be alternatively powered by liquid propane or natural gas**, with maximum output of 4500 hp, when combusting diesel **or biodiesel** or 2200 hp when combusting **liquid propane or natural gas**, with heat input of 28.82 MMBtu/hr when combusting diesel **or biodiesel** or 14.40 MMBtu/hr when combusting **liquid propane and natural gas** and exhausting to stack HHP1;
- (3) One (1) diesel **or biodiesel**-powered engineering engine test cells, identified as HHP2, with maximum output of 4500 hp when combusting diesel **or biodiesel**, with heat input of 28.82 MMBtu/hr and exhausting to stack HHP2;
- (4) One (1) diesel **or biodiesel**-powered engineering engine test cell, identified as HHP3, **may be alternatively powered by liquid propane or natural gas**, with maximum output of 4500 hp when combusting **diesel or biodiesel and 4500hp when combusting liquid propane or natural gas**, with heat input of 28.82 MMBtu/hr when combusting diesel/**biodiesel or liquid propane/natural gas** and exhausting to stacks HHP3.1 and HHP3.2;
- (5) One (1) diesel **or biodiesel**-powered engineering test cell, identified as HHP5, **may be alternatively powered by liquid propane or natural gas**, with output of 2200 hp when combusting diesel **or biodiesel** or 600 hp when combusting **liquid propane or natural gas**, with heat input of 14.09 MMBtu/hr when combusting

diesel **or biodiesel** or 4.10 when combusting **liquid propane or natural gas** and exhausting to stack HHP5.1 - HHP5.2;

(6) One (1) diesel **or biodiesel**-powered ~~or natural gas-fired outside~~ engine test pad 8 (PI), identified as PI, **may be alternatively powered by liquid propane or natural gas**, with maximum outputs of 3000 hp when combusting diesel **or biodiesel** or 2200 hp when combusting **liquid propane or natural gas**, with heat input of 19.22 MMBtu/hr when combusting diesel **or biodiesel** and 14.40 MMBtu/hr when combusting **liquid propane or natural gas** and exhausting to stacks PD8.1 and PD8.2;

(7) Two (2) diesel **or biodiesel**-powered ~~or natural gas-fired outside~~ engine test pad 10(PI) and 11(PI), identified as PI, **may be alternatively powered by liquid propane or natural gas**, with maximum outputs of 1850, each, when combusting diesel, **or biodiesel, or 1850 hp, each when combusting liquid propane or natural gas**, with heat input of 11.85 MMBtu/hr, each, when combusting diesel, **or biodiesel** or 12.70 MMBtu/hr, each when combusting **liquid propane or natural gas** and exhausting to stacks PD10.1 and PD11.1; and

(8) One (1) diesel **or biodiesel**-powered ~~or natural gas-fired~~ engineering engine test cell, identified as HHP4, **may be alternatively powered by liquid propane or natural gas**, with a maximum output of 2200 hp when combusting diesel **or biodiesel and 2200hp when combusting liquid propane or natural gas** and a heat input of 14.09 MMBtu per hour when combusting diesel **or biodiesel** or 14.40 MMBtu/hr when combusting **liquid propane or natural gas** and exhausting to stacks HHP4.1 and HHP4.2.

(d) One (1) diesel **or biodiesel**-powered engineering engine test cell Test Pad 9, identified as EU-02C, installed in 2005, **may be alternatively powered by liquid propane or natural gas**, with maximum outputs of ~~3540~~ **4500** hp when combusting diesel **or biodiesel** or 2200 hp when combusting **liquid propane or natural gas**, exhausting to stacks PD9.1 and PD9.2.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.2.1 PSD Minor Limit [326 IAC 2-2]

- (a) The total **NOx emissions from diesel fuel, combusted by the seventeen (17) engine test cells, known as EU-02A, EU-02B, and EU-02C shall not exceed the amount calculated by the following equation, equivalent to NOx emissions of 217.9 tons per twelve (12) consecutive month period with compliance determined at the end of each month.**

**The NOx emissions shall be calculated by the following equation:**

$$\begin{aligned} \text{NOx emissions} = & \text{(Diesel fuel burned by EU-02A 801, 802, 803, 804, 805 and 808) x} \\ & \text{(0.427 lbs Ef1 of NOx/gal of diesel fuel) } \div \text{(2000 lbs/ton)} + \text{(Diesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI),} \\ & \text{11(PI), HHP4 EU-02B and EU-02C) x (0.455 lbs Ef2, of NOx/gal of} \\ & \text{diesel fuel) } \div \text{(2000 lbs/ton)} \\ & + \\ & \text{(Natural gas burned by 806, 807, 808, HHP1, HHP3 HHP4, HHP5} \\ & \text{and PI) x (0.00416 lbs Ef3 of NOx/ft}^3 \text{ of natural gas) } \div \text{(2000 lbs/ton)} \\ & \text{at a natural gas heat content of 1,020 MMBtu/ft}^3 \\ & + \end{aligned}$$

(Biodiesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI) (PI), 11(PI), HHP4 and EU-02C) x (Ef4 of NOx/gal of biodiesel fuel)

+

(Propane fuel burned by 806, 807, HHP1, HHP3, HHP5, 8(PI) 10(PI), 11(PI), HHP4 and EU-02C) x (Ef5 of NOx/gal of Propane fuel)

(b) The NOx emissions shall not exceed:

(1) 0.427 pounds of NOx per gallon of diesel fuel for EU-02A;

(2) 0.155 pounds of NOx per gallon of diesel fuel for EU-02B and EU-02C; and

(3) 0.00416 pounds of NOx per cubic foot of natural gas for 808, HHP4, HHP5 and PI.

(1) Ef1 = Emission Limit in pounds of NOx per gallon of diesel fuel for 801, 802, 803, 804, 805 and 808;

(2) Ef2 = Emission Limit in pounds of NOx per gallon of diesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C;

(3) Ef3 = Emission Limits in pounds of NOx per cubic foot of natural gas for 806, 807, 808, HHP1, HHP3 HHP4, HHP5 and PI;

(4) Ef4 = Emission Limit in pounds of NOx per gallon of biodiesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C; and

(5) Ef5 = Emission Limit in pounds of NOx per kilogallon of propane for 806, 807, HHP1, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C.

(e) Compliance with ~~these~~ ~~this~~ ~~limits~~ ~~in~~ ~~Condition~~ ~~D.2.1(a)~~ ~~and~~ ~~(b)~~ ~~will~~ ~~shall~~ limit the NOx emissions from the engine test cells and other emission units ~~to less than~~ ~~not to exceed~~ two hundred and fifty (250) tons per year and render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable to this source.

(c) The total VOC emissions from the eleven (11) engine test cells, known as EU-02B, and EU-02C shall not exceed the 163.56 tons per twelve (12) consecutive month period with compliance determined at the end of each month.

The VOC emissions shall be calculated by the following equation:

VOC emissions = (Diesel fuel burned by 801, 802, 803, 804, 805 and 808) x (Ef1 of VOC/gal of diesel fuel ) + (Diesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C) x Ef2, of NOx/gal of diesel fuel)

+

(Biodiesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI) (PI), 11(PI), HHP4 and EU-02C) x (Ef4 of VOC/gal of biodiesel fuel)

+

(Natural gas burned by 806, 807, 808, HHP4, HHP5 and PI) x (Ef3 of VOC /ft<sup>3</sup> of natural gas) at a natural gas heat content of 1,020 MMBtu/ft<sup>3</sup>

+  
(Propane fuel burned by 806, 807, HHP1, HHP3, HHP5, 8(PI)  
10(PI), 11(PI), HHP4 and EU-02C) x (Ef5 of VOC/gal of Propane  
fuel)

**(d) The VOC emissions shall not exceed:**

- (1) Ef1 = Emission Limit in pounds of VOC per gallon of diesel fuel for 801, 802, 803, 804, 805 and 808;
- (2) Ef2 = Emission Limit in pounds of VOC per gallon of diesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C;
- (3) Ef3 = Emission Limits in pounds of VOC per cubic foot of natural gas for 806, 807, 808, HHP1, HHP3 HHP4, HHP5 and PI;
- (4) Ef4 = Emission Limit in pounds of VOC per gallon of biodiesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C; and
- (5) Ef5 = Emission Limit in pounds of VOC per kilogallon of propane for 806, 807, HHP1, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C.

Compliance with these limits shall limit the VOC emissions from the Engine test cells and other emission units to less than two hundred and fifty (250) tons per year and render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable to this source.

**(e) The total CO emissions from the eleven (11) engine test cells, known as EU-02B, and EU-02C shall not exceed 183.62 tons per twelve (12) consecutive month period with compliance determined at the end of each month.**

The CO emissions shall be calculated by the following equation:

CO emissions = (Diesel fuel burned by 801, 802, 803, 804, 805 and 808) x (Ef1 of CO/gal of diesel fuel) + (Diesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C) x Ef2, of NOx/gal of diesel fuel)  
+  
(Biodiesel fuel burned by 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI) (PI), 11(PI), HHP4 and EU-02C) x (Ef4 of CO/gal of biodiesel fuel)  
+  
(Natural gas burned by 806, 807, 808, HHP4, HHP5 and PI) x (Ef3 of CO/ft<sup>3</sup> of natural gas)  
+  
(Propane fuel burned by 806, 807, HHP1, HHP3, HHP5, 8(PI) 10(PI), 11(PI), HHP4 and EU-02C) x (Ef5 of CO/gal of Propane fuel)

**(f) The CO emissions shall not exceed:**

- (1) Ef1 = Emission Limit in pounds of CO per gallon of diesel fuel for 801, 802, 803, 804, 805 and 808;
- (2) Ef2 = Emission Limit in pounds of CO per gallon of diesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C;

- (3) **Ef3 = Emission Limits in pounds of CO per cubic foot of natural gas for 806, 807, 808, HHP1, HHP3 HHP4, HHP5 and PI;**
- (4) **Ef4 = Emission Limit in pounds of CO per gallon of biodiesel fuel for 806, 807, HHP1, HHP2, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C; and**
- (5) **Ef5 = Emission Limit in pounds of CO per kilogallon of propane for 806, 807, HHP1, HHP3, HHP5, 8(PI), 10(PI), 11(PI), HHP4 and EU-02C.**

**Compliance with these limits shall limit the CO emissions from the engine test cells and other emission units to less than two hundred and fifty (250) tons per year and render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable to this source.**

**Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

**D.2.3 Visible Emissions Notations**

- (a) Visible emissions notations of the engine test cell stack exhausts (801.1 -801.2, 802.1 -802.2, 803.1-803.2, 804 through 808, HHP1, HHP2, HHP3.1 -HHP3.2, HHP4.1-HHP4.2, HHP5.1-HHP5.2, PD8.1-PD8.2, PD9.1 and PD9.2, PD10.1 and PD11.1) shall be performed once per day during normal daylight operations when combusting diesel fuel **or biodiesel**. A trained employee will record whether emissions are normal or abnormal.
- .....

**D.2.4 Record Keeping Requirements**

- (a) To document compliance with condition D.2.1, the Permittee shall maintain records in accordance with (1) and (3) below:
    - (1) Calendar dates covered in the compliance determination period; and
    - (2) Actual diesel, **biodiesel** fuel oil **or propane** usage for EU-02A, EU-02B, and EU-02C since last compliance determination period and equivalent NOx emissions.
    - (3) Actual natural gas usage for EU-02A and EU-02B since last compliance determination period and equivalent NOx emissions.
  - (b) To document compliance with condition D.2.3 - Visible Emission Notation, the Permittee shall maintain records of daily visible emission notations of the stack exhausts listed, when combusting diesel fuel **or biodiesel**. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation, (e.g. the process did not operate that day).
- .....

Facilities: seventeen (17) engine test cells, known as EU-02A, EU-02B and EU-02C  
Parameter: NOx Emissions  
Limit: less than 217.9 tons of NOx per twelve (12) consecutive month period.

**YEAR:** \_\_\_\_\_

Month	This Month		EU-02 Equivalent NO <sub>x</sub> (tons) A + (B + C)	Previous 11 Months		EU-02 Equivalent NO <sub>x</sub> (tons) A + (B + C)	12 Month Total		EU-02 Equivalent NO <sub>x</sub> (tons) A + (B + C)
	EU-02 Diesel, biodiesel or propane Fuel (gallons)			A	B + C		A	B + C	
	Natural Gas (cubic feet)			Natural Gas (cubic feet)			Natural Gas (cubic feet)		
	A	B		A	B		A	B	

<b>Total NOx Emissions from Diesel Fuel, &amp; Natural Gas, biodiesel or propane</b>	<b>Month</b>	<b>Month</b>	<b>Month</b>
<b>12 Month Total (tons)</b>			

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR QUALITY  
 COMPLIANCE DATA SECTION**

**Part 70 Quarterly Report**

**Source Name:** Cummins Industrial Center  
**Source Address:** 800 East Third Street, Seymour Indiana 47274  
**Mailing Address:** 800 East Third Street, Seymour Indiana 47274  
**Part 70 Permit No.:** T071-21065-00015  
**Facility:** EU-02B and EU-02C  
**Parameter:** VOC  
**Limit:** Less than 163.56 tons per twelve (12) consecutive month period.

**QUARTER :**

**YEAR:**

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
 Deviation has been reported on:

Submitted by: \_\_\_\_\_  
 Title / Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

**Attach a signed certification to complete this report.**

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**Part 70 Quarterly Report**

**Source Name:** Cummins Industrial Center  
**Source Address:** 800 East Third Street, Seymour Indiana 47274  
**Mailing Address:** 800 East Third Street, Seymour Indiana 47274  
**Part 70 Permit No.:** T071-21065-00015  
**Facility:** EU-02B and EU-02C  
**Parameter:** CO  
**Limit:** Less than 183.62 tons per twelve (12) consecutive month period.

**QUARTER :**

**YEAR:**

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.  
Deviation has been reported on:

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

**Attach a signed certification to complete this report.**

**Other Changes**

Upon further review IDEM, OAQ has made the following changes to the Title V permit T071-21065-00015. (deleted language appears as ~~strikout~~ and the new language **bolded**):

Change 1: Condition B.21 - Source Modification Requirement has been updated in the permit.

B.21 Source Modification Requirement [326 IAC 2-7-10.5]

- (a) A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and ~~326 IAC 2-7-10.5.~~
- (b) ~~Any modification at an existing major source is governed by the requirements of 326 IAC 2-2-2 and/or 326 IAC 2-3-2.~~

Change 2: The source is not a major source under PSD, therefore, the following conditions have been deleted from the permit.

C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [326 IAC 2-2] [326 IAC 2-3]

- ~~(c) If there is a reasonable possibility that a "project" (as defined in 326 IAC 2-2-1 (qq) and/or 326 IAC 2-3-1(II)) at an existing emissions unit, other than projects at a Clean Unit, which is not part of a "major modification" (as defined in 326 IAC 2-2-1(ee) and/or 326 IAC 2-3-1(z)) may result in significant emissions increase and the Permittee elects to utilize the "projected actual emissions" (as defined in 326 IAC 2-2-1(rr) and/or 326 IAC 2-3-1(mm)), the Permittee shall comply with following:~~
- ~~(1) Prior to commencing the construction of the "project" (as defined in 326 IAC 2-2-1(qq) and/or 326 IAC 2-3-1(II)) at an existing emissions unit, document and maintain the following records:~~
- ~~(A) A description of the project.~~
- ~~(B) Identification of any emissions unit whose emissions of a regulated new source review pollutant could be affected by the project.~~
- ~~(C) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including:~~
- ~~(i) Baseline actual emissions;~~
- ~~(ii) Projected actual emissions;~~
- ~~(iii) Amount of emissions excluded under section 326 IAC 2-2-1(rr)(2)(A)(iii) and/or 326 IAC 2-3-1(mm)(2)(A)(iii); and~~
- ~~(iv) An explanation for why the amount was excluded, and any netting calculations, if applicable.~~
- ~~(2) Monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any existing emissions unit identified in (1)(B) above; and~~
- ~~(3) Calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of five (5) years following resumption of regular operations after the change, or for a period of ten (10) years following resumption of regular operations after the change if the project increases the design capacity of or the potential to emit that regulated NSR pollutant at the emissions unit.~~

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11] [326 IAC 2-2] [326 IAC 2-3]

- ~~(e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.~~

~~(f) If the Permittee is required to comply with the recordkeeping provisions of (c) in Section C- General Record Keeping Requirements for any "project" (as defined in 326 IAC 2-2-1(qq) and/or 326 IAC 2-3-1(II)) at an existing emissions unit, and the project meets the following criteria, then the Permittee shall submit a report to IDEM, OAQ:~~

~~(1) The annual emissions, in tons per year, from the project identified in (c)(1) in Section C- General Record Keeping Requirements exceed the baseline actual emissions, as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(i), by a significant amount, as defined in 326 IAC 2-2-1(xx) and/or 326 IAC 2-3-1(qq), for that regulated NSR pollutant, and~~

~~(2) The emissions differ from the preconstruction projection as documented and maintained under Section C- General Record Keeping Requirements (c)(1)(C)(ii).~~

~~(g) The report for project at an existing emissions unit shall be submitted within sixty (60) days after the end of the year and contain the following:~~

~~(1) The name, address, and telephone number of the major stationary source.~~

~~(2) The annual emissions calculated in accordance with (c)(2) and (3) in Section C- General Record Keeping Requirements.~~

~~(3) The emissions calculated under the actual-to-projected actual test stated in 326 IAC 2-2-2(d)(3) and/or 326 IAC 2-3-2(e)(3).~~

~~(4) Any other information that the Permittee deems fit to include in this report.~~

Reports required in this part shall be submitted to:

Indiana Department of Environmental Management  
Air Compliance Section, Office of Air Quality  
100 North Senate Avenue  
MC61-53-IGCN 1003  
Indianapolis, Indiana 46204-2254

~~(h) The Permittee shall make the information required to be documented and maintained in accordance with (c) in Section C- General Record Keeping Requirements available for review upon a request for inspection by IDEM, OAQ. The general public may request this information from the IDEM, OAQ under 326 IAC 17.1.~~

Change 3: The source requested for a minor change in the descriptive information for one of the production test cell in EU-02A. The diesel oil has been changed to diesel fuel in the permit.

(b) Six (6) production engine test cells, identified as EU-02A, constructed in 1978, consisting of the following equipment:

.....  
(3) One (1) diesel-powered or natural gas-fired production engine test cell, identified as 808, with maximum output of 1650 hp when combusting diesel oil fuel or 600hp when combusting natural gas, with heat input of 10.57 MMBtu/hr when combusting diesel oil fuel or 4.1 MMBtu/hr when combusting natural gas and exhausting to stack 808.

Change 4: The Semi - Annual Natural Gas - Fired Boiler Certification has been removed from the permit because this is not a required compliance form.

**~~INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION  
PART 70 OPERATING PERMIT~~**

**~~SEMI-ANNUAL NATURAL GAS FIRED BOILER CERTIFICATION~~**

*[Applicable for boilers greater than or equal to 10 MMBtu/hr that can burn both natural gas and other fuels. The natural gas fired boiler certification is not required for boilers that can physically only burn natural gas.]*

Source Name: Cummins Industrial Center

Source Address: 800 East Third Street, Seymour, Indiana 47274

Mailing Address: 800 East Third Street, Seymour, Indiana 47274

Part 70 Permit Renewal No.: T071-21065-00015

Natural Gas Only  
 Alternate Fuel burned  
From: \_\_\_\_\_ To: \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

A certification by the responsible official as defined by 326 IAC 2-7-1(34) is required for this report.

**Conclusion and Recommendation**

The construction of this proposed modification shall be subject to the conditions of the attached proposed Part 70 Significant Source Modification No. 071-27821-00015 and Significant Permit Modification No. 071-27977-00015. The staff recommends to the Commissioner that this Part 70 Significant Source and Significant Permit Modification be approved.

**Appendix A: Emissions Calculations**

**Emission Summary**

**Source Name:** Cummins Industrial Center  
**Source Location:** 800 East Third Street, Seymour, IN 47274  
**Permit Number:** SPM 071-27977-00015  
**Permit Reviewer:** Josiah Balogun  
**Date:** 2-Jun-2009

**Uncontrolled Potential Emissions**

	<b>PM (tons/yr)</b>	<b>PM<sub>10</sub> (tons/yr)</b>	<b>SO<sub>2</sub> (tons/yr)</b>	<b>VOC (tons/yr)</b>	<b>CO (tons/yr)</b>	<b>NOx (tons/yr)</b>	<b>HAPs (tons/yr)</b>
<b>Emission Unit</b>							
EU-02B	95.9	95.9	89.6	476.4	740.42	954.49	neg
EU-02C	3.18	3.18	2.97	29.03	45.12	48.62	neg
Total Emissions	99.1	99.1	92.57	505.43	785.54	1003.1	Single HAP <10 Combined HAPs < 25

**Limited Potential Emissions**

	<b>PM (tons/yr)</b>	<b>PM<sub>10</sub> (tons/yr)</b>	<b>SO<sub>2</sub> (tons/yr)</b>	<b>VOC (tons/yr)</b>	<b>CO (tons/yr)</b>	<b>NOx (tons/yr)</b>	<b>HAPs (tons/yr)</b>
<b>Emission Unit</b>							
EU-02B	95.9	95.9	89.6	< 250	< 250	< 250	neg
EU-02C	3.18	3.18	2.97				neg
Total Emissions	99.1	99.1	92.57	< 250	< 250	< 250	Single HAP <10 Combined HAPs < 25





# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
**Governor**

*Thomas W. Easterly*  
**Commissioner**

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

## **SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED**

**TO:** David Wehrkamp  
Cummins Industrial Center  
800 E 3rd Street, MC 30125  
Seymore, IN 47274

**DATE:** August 28, 2009

**FROM:** Matt Stuckey, Branch Chief  
Permits Branch  
Office of Air Quality

**SUBJECT:** Final Decision  
Significant Permit Modification  
071-27977-00015

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:  
Darren Wildman - CIC Plant Manager  
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at [jbrush@idem.IN.gov](mailto:jbrush@idem.IN.gov).

Final Applicant Cover letter.dot 11/30/07



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We Protect Hoosiers and Our Environment.*

*Mitchell E. Daniels Jr.*  
**Governor**

*Thomas W. Easterly*  
**Commissioner**

100 North Senate Avenue  
Indianapolis, Indiana 46204  
(317) 232-8603  
Toll Free (800) 451-6027  
[www.idem.IN.gov](http://www.idem.IN.gov)

August 28, 2009

TO: Jackson County Public Library

From: Matthew Stuckey, Branch Chief  
Permits Branch  
Office of Air Quality

Subject: **Important Information for Display Regarding a Final Determination**

**Applicant Name: Cummins Industrial Center**  
**Permit Number: 071-27977-00015**

You previously received information to make available to the public during the public comment period of a draft permit. Enclosed is a copy of the final decision and supporting materials for the same project. Please place the enclosed information along with the information you previously received. To ensure that your patrons have ample opportunity to review the enclosed permit, **we ask that you retain this document for at least 60 days.**

The applicant is responsible for placing a copy of the application in your library. If the permit application is not on file, or if you have any questions concerning this public review process, please contact Joanne Smiddie-Brush, OAQ Permits Administration Section at 1-800-451-6027, extension 3-0185.

Enclosures  
Final Library.dot 11/30/07

# Mail Code 61-53

IDEM Staff	GHOTOPP 8/28/2009 Cummins Industrial Ctr 071-27977-00015 Final		Type of Mail:  <b>CERTIFICATE OF MAILING ONLY</b>	AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204		

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handing Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee	Remarks
1		David Wehrkamp Cummins Industrial Ctr 800 E 3rd St, MC 30125 Seymour 47274 (Source CAATS) via confirmed delivery										
2		Darren Wildman CIC Plant Mgr Cummins Industrial Ctr 800 E 3rd St, MC 30125 Seymour 47274 (RO CAATS)										
3		Jackson County Commissioner Jackson County Courthouse Brownstown IN 47220 (Local Official)										
4		Mr. Randy Brown Plumbers & Steam Fitters Union, Local 136 2300 St. Joe Industrial Park Dr Evansville IN 47720 (Affected Party)										
5		Mr. Tome Earnhart 3960 N. CR 300 W. North Vernon IN 47265 (Affected Party)										
6		Seymour City Council and Mayors Office 301 North Chestnut Street Seymour IN 47274 (Local Official)										
7		Jackson County Health Department 801 West 2nd Street Seymour IN 47274-2711 (Health Department)										
8		Jackson Co Public Library 303 W 2nd Street Seymour IN 47274-2184 (Library)										
9												
10												
11												
12												
13												
14												
15												

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See <b>Domestic Mail Manual R900, S913, and S921</b> for limitations of coverage on inured and COD mail. See <b>International Mail Manual</b> for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
<b>7</b>			