



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: July 14, 2009

RE: Heritage Asphalt LLC / 085-28153-00066

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days from the mailing of this notice.** The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER-AM.dot12/3/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Mr. Joe Muncy
Heritage Asphalt, L.L.C.
2820 East Durbin Street
Warsaw, IN 46580

July 14, 2009

Re: 085-28153-00066
Registration Notice-Only Change to
Registration No. R085-16440-00066

Dear Mr. Muncy:

SemMaterials Energy Partners, L.L.C. was issued a Registration No. R085-16440-00066 on December 10, 2002, for a stationary asphalt emulsion manufacturing and asphalt storage source located at 2820 East Durbin Street Warsaw, IN 46580. On June 26, 2009, the Office of Air Quality (OAQ) received an application from the source requesting that the registration be updated to indicate the operation name change to Heritage Asphalt, L.L.C. SemMaterials Energy Partners, L.L.C. will continue to own the facilities but all operations will be managed by Heritage Asphalt, L.L.C. The change of the operator does not affect the physical operations, equipment or emission units.

This change to the registration is considered a notice-only change pursuant to 326 IAC 2-5.5-6(d)(3). Pursuant to 326 IAC 2-5.5-6, the registration is hereby revised as follows, with deleted language as ~~strikeouts~~ and new language **bolded**:

The company name and mailing address have been updated in the permit as follows:

Company Name: ~~SemMaterials Energy Partners, LLC~~
Heritage Asphalt, L.L.C.

Mailing Address: ~~2820 East Durbin Street, Warsaw, Indiana 46580~~
5400 West 86th Street, Indianapolis, Indiana 46268

The source shall continue to operate according to 326 IAC 2-5.5. Please find enclosed the revised registration. A copy of the registration is available on the Internet at: <http://www.in.gov/ai/appfiles/idem-caats/>. For additional information about air permits and how the public and interested parties can participate, refer to the IDEM's Guide for Citizen Participation and Permit Guide on the Internet at: www.idem.in.gov

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5.
If you have any questions on this matter, please contact Ms. Renee Traivaranon at (800) 451-6027, press 0 and ask for extension 4-5615 or dial (317) 234-5615.

Sincerely,



Iryn Calilung, Section Chief
Permits Branch
Office of Air Quality

IC/rt

Attachments: Revised Registration
Notice of Decision
CC: File - Kosciusko County
Kosciusko County Health Department
Compliance and Enforcement Branch
Billing, Licensing and Training Section



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor


Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

REGISTRATION OFFICE OF AIR QUALITY

Heritage Asphalt, L.L.C.
2820 East Durbin Street
Warsaw, Indiana 46580

Pursuant to 326 IAC 2-5.1 (Construction of New Sources: Registrations) and 326 IAC 2-5.5 (Registrations), (herein known as the Registrant) is hereby authorized to construct and operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this registration.

Registration No. 085-16440-00066	
Original signed by: Paul Dubenetzky Permits Branch Office of Air Quality	Issuance Date: December 10, 2002
First Registration Revision No. 085-16930-00066, issued on April 7, 2003	
First Registration Notice-Only Change No. 085-18338-00066, issued on April 15, 2004	
Second Registration Notice-Only Change No. 085-21276-00066, issued on July 7, 2005	
Second Registration Revision No. 085-26171-00066, issued on March 17, 2008	
Third Registration Revision No. 085-27367-00066, issued on February 10, 2009	
Fourth Registration Revision No. 085-27549-00066, issued on March 25, 2009	
Third Registration Notice - Only Change No. 085-27859-00066, issued on May 5, 2009	
Fourth Registration Notice - Only Change No. 085-28153-00066	
Issued by:  Iryn Caillung, Section Chief Permits Branch Office of Air Quality	Issuance Date: July 14, 2009

SECTION A

SOURCE SUMMARY

This registration is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 and A.2 is descriptive information and does not constitute enforceable conditions. However, the Registrant should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Registrant to obtain additional permits pursuant to 326 IAC 2.

A.1 General Information

The Registrant owns and operates a stationary asphalt emulsion manufacturing and asphalt storage source.

Source Address:	2820 East Durbin Street, Warsaw, Indiana 46580
Mailing Address:	5400 West 86 th Street, Indianapolis, Indiana 46268
General Source Phone Number:	(563) 584-1893
SIC Code:	2951
County Location:	Kosciusko County
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Registration

A.2 Emission Units and Pollution Control Equipment Summary

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) boiler, fueled by natural gas only, identified as B-1, heat capacity is 5.02 mmBtu per hour. Stack height is 15 feet with a diameter of 24 inches.
- (b) One (1) hot water heater, fueled by natural gas only, identified as WH-1, heat capacity is 3.0 mmBtu per hour. Two (2) stacks, each has a height of 13 feet and a diameter of 16 inches.
- (c) One (1) hot oil heater, fueled by natural gas only, identified as HO-1, heat capacity is 8.4 mmBtu per hour. Stack height is 15 feet with a diameter of 24 inches.
- (d) One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-1, heat capacity is 1.25 mmBtu per hour. Stack height is 22 feet with a diameter of 10.75 inches.
- (e) One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-2, heat capacity is 1.72 mmBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.
- (f) One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-3, heat capacity is 1.72 mmBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.
- (g) One (1) loading rack, product name is asphalt, truck rack throughput is 18,000 gallons per hour.
- (h) One (1) loading rack, product name is asphalt and polymer modified asphalt, truck rack annual throughput is 18,000 gallons per hour.
- (i) Three (3) emulsion and cutback emulsion loading racks, identified as 1, 2, 3, each having a throughput of 18,000 gallons per hour.
- (j) One (1) emulsion and cutback emulsion loading rack, identified as 4, having a throughput of 12,000 gallons per hour.

(k) Storage Tanks:

- (1) Tank 101: storing asphalt cement, constructed in 1976, with a storage capacity of 20,080 gallons and annual throughput of 1,547,800 gallons per year, with a diameter of 10.5 feet and height of 31.0 feet, and a true vapor pressure less than 0.5 psi.
- (2) Tank 102: storing polymer modified asphalt cement, constructed in 1976, with a storage capacity of 82,751 gallons and annual throughput of 7,717,000 gallons per year, with a diameter of 29.67 feet and height of 16.0 feet, and a true vapor pressure less than 1.0 psi.
- (3) Tank 103: storing polymer modified asphalt cement, constructed in 1976, with a storage capacity of 82,751 gallons and annual throughput of 7,717,000 gallons per year, with a diameter of 29.67 feet and height of 16.0 feet, and a true vapor pressure less than 1.0 psi.
- (4) Tank 104: storing asphalt cement, constructed in 1992, with a storage capacity of 168,000 gallons and annual throughput of 13,343,000 gallons per year, with a diameter of 29.89 feet and height of 32.0 feet, and a true vapor pressure less than 0.5 psi.
- (5) Tank 105: storing asphalt cement, constructed in 1978, with a storage capacity of 489,002 gallons and annual throughput of 38,847,000 gallons per year, with a diameter of 51.0 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (6) Tank 106: storing asphalt cement, constructed in 1980, with a storage capacity of 489,002 gallons and annual throughput of 38,847,000 gallons per year, with a diameter of 51.0 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (7) Tank 107: storing asphalt cement, constructed in 1975, with a storage capacity of 24,614 gallons and annual throughput of 1,955,000 gallons per year, with a diameter of 10.5 feet and height of 38.0 feet, and a true vapor pressure less than 0.5 psi.
- (8) Tank 108: storing asphalt cement, constructed in 2001, with a storage capacity of 4,219,783 gallons, with a diameter of 134 feet and height of 40 feet, and a true vapor pressure less than 0.5 psi.
- (9) Tank 120: storing polymer modified asphalt cement, constructed in 1982, with a storage capacity of 24,614 gallons and annual throughput of 15,434,300 gallons per year, with a diameter of 10.5 feet and height of 38.0 feet, and a true vapor pressure less than 0.5 psi.
- (10) Tank 300: storing molten sulfur tank, constructed in 2004, with storage capacity of 5,264 gallons.
- (11) Tank 150: storing asphalt cement batch, constructed in 1982, with a storage capacity of 24,065 gallons and annual throughput of 15,434,300 gallons per year, with a diameter of 16.0 feet and height of 16.0 feet, and a true vapor pressure less than 0.5 psi.

- (12) Tank 201: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 44,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (13) Tank 202: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 44,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (14) Tank 203: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 42,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (15) Tank 204: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 44,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (16) Tank 205: storing asphalt emulsion and cutback emulsion, constructed in 2003, with a storage capacity of 40,304 gallons and annual throughput of 9,460,000 gallons per year, with a diameter of 14.0 feet and height of 35.0 feet, and a true vapor pressure less than 0.5 psi.
- (17) Tank 206: storing asphalt emulsion and cutback emulsion, constructed in 2003, with a storage capacity of 40,304 gallons and annual throughput of 9,460,000 gallons per year, with a diameter of 14.0 feet and height of 35.0 feet, and a true vapor pressure less than 0.5 psi.
- (18) Tank 207: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 65,179 gallons and annual throughput of 15,298,700 gallons per year, with a diameter of 21.5 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (19) Tank 208: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 65,179 gallons and annual throughput of 15,298,700 gallons per year, with a diameter of 21.5 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (20) Tank 209: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 124,127 gallons and annual throughput of 29,134,800 gallons per year, with a diameter of 29.67 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (21) Tank 210: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 124,127 gallons and annual throughput of 29,134,800 gallons per year, with a diameter of 29.67 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (22) Tank 211: storing asphalt emulsion and cutback emulsion, constructed in 2008, with a storage capacity of 42,300 gallons and annual throughput of 9,928,800 gallons per year, with a diameter of 15.0 feet and height of 32 feet, and a true vapor pressure less than 0.5 psi.

- (23) Tank 212: storing asphalt emulsion and cutback emulsion, constructed in 1986, with a storage capacity of 48,129 gallons and annual throughput of 11,296,800 gallons per year, with a diameter of 16.0 feet and height of 32.0 feet, and a true vapor pressure less than 0.5 psi.
- (24) Tank 400: storing fuel oil, constructed in 1975, with a storage capacity of 20,080 gallons and annual throughput of 29,039,400 gallons per year, with a diameter of 10.5 feet and height of 31.0 feet, and a true vapor pressure less than 0.5 psi.
- (25) Tank 401: storing LD-95, constructed in 1975, with a storage capacity of 10,364 gallons, with a diameter of 10.5 feet and height of 16.0 feet.

SECTION B

GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-1.1-1]

Terms in this registration shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-1.1-1) shall prevail.

B.2 Effective Date of Registration [IC 13-15-5-3]

Pursuant to IC 13-15-5-3, this registration is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

B.3 Registration Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation), this registration to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this registration.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this registration.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this registration shall not require revocation of this registration.
- (d) For any cause which establishes in the judgment of IDEM, the fact that continuance of this registration is not consistent with purposes of this article.

B.4 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of permits established prior to Registration No. 085-16440-00066 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted.
- (b) All previous registrations and permits are superseded by this registration.

B.5 Annual Notification [326 IAC 2-5.1-2(f)(3)] [326 IAC 2-5.5-4(a)(3)]

Pursuant to 326 IAC 2-5.1-2(f)(3) and 326 IAC 2-5.5-4(a)(3):

- (a) An annual notification shall be submitted by an authorized individual to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this registration.
- (b) The annual notice shall be submitted in the format attached no later than March 1 of each year to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, IN 46204-2251

- (c) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

B.6 Source Modification Requirement [326 IAC 2-5.5-6(a)]

Pursuant to 326 IAC 2-5.5-6(a), an application or notification shall be submitted in accordance with 326 IAC 2 to the Office of Air Quality (OAQ) if the source proposes to construct new emission units, modify existing emission units, or otherwise modify the source.

B.7 Registrations [326 IAC 2-5.1-2(i)]

Pursuant to 326 IAC 2-5.1-2(i), this registration does not limit the source's potential to emit.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-5.1-2(g)] [326 IAC 2-5.5-4(b)]

C.1 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this registration:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.2 Fugitive Dust Emissions [326 IAC 6-4]

The Registrant shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

SECTION D.1

OPERATION CONDITIONS

Facility Description [326 IAC 2-5.1-2(f)(2)] [326 IAC 2-5.5-4(a)(2)]:

- (a) One (1) boiler, fueled by natural gas only, identified as B-1, heat capacity is 5.02 mmBtu per hour. Stack height is 15 feet with a diameter of 24 inches.
- (b) One (1) hot water heater, fueled by natural gas only, identified as WH-1, heat capacity is 3.0 mmBtu per hour. Two (2) stacks, each has a height of 13 feet and a diameter of 16 inches.
- (c) One (1) hot oil heater, fueled by natural gas only, identified as HO-1, heat capacity is 8.4 mmBtu per hour. Stack height is 15 feet with a diameter of 24 inches.
- (d) One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-1, heat capacity is 1.25 mmBtu per hour. Stack height is 22 feet with a diameter of 10.75 inches.
- (e) One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-2, heat capacity is 1.72 mmBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.
- (f) One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-3, heat capacity is 1.72 mmBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.
- (g) One (1) loading rack, product name is asphalt, truck rack throughput is 18,000 gallons per hour.
- (h) One (1) loading rack, product name is asphalt and polymer modified asphalt, truck rack annual throughput is 18,000 gallons per hour.
- (i) Three (3) emulsion and cutback emulsion loading racks, identified as 1, 2, 3, each having a throughput of 18,000 gallons per hour.
- (j) One (1) emulsion and cutback emulsion loading rack, identified as 4, having a throughput of 12,000 gallons per hour.
- (k) Storage Tanks:
 - (1) Tank 101: storing asphalt cement, constructed in 1976, with a storage capacity of 20,080 gallons and annual throughput of 1,547,800 gallons per year, with a diameter of 10.5 feet and height of 31.0 feet, and a true vapor pressure less than 0.5 psi.
 - (2) Tank 102: storing polymer modified asphalt cement, constructed in 1976, with a storage capacity of 82,751 gallons and annual throughput of 7,717,000 gallons per year, with a diameter of 29.67 feet and height of 16.0 feet, and a true vapor pressure less than 1.0 psi.
 - (3) Tank 103: storing polymer modified asphalt cement, constructed in 1976, with a storage capacity of 82,751 gallons and annual throughput of 7,717,000 gallons per year, with a diameter of 29.67 feet and height of 16.0 feet, and a true vapor pressure less than 1.0 psi.
 - (4) Tank 104: storing asphalt cement, constructed in 1992, with a storage capacity of 168,000 gallons and annual throughput of 13,343,000 gallons per year, with a diameter of 29.89 feet and height of 32.0 feet, and a true vapor pressure less than 0.5 psi.

- (5) Tank 105: storing asphalt cement, constructed in 1978, with a storage capacity of 489,002 gallons and annual throughput of 38,847,000 gallons per year, with a diameter of 51.0 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (6) Tank 106: storing asphalt cement, constructed in 1980, with a storage capacity of 489,002 gallons and annual throughput of 38,847,000 gallons per year, with a diameter of 51.0 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (7) Tank 107: storing asphalt cement, constructed in 1975, with a storage capacity of 24,614 gallons and annual throughput of 1,955,000 gallons per year, with a diameter of 10.5 feet and height of 38.0 feet, and a true vapor pressure less than 0.5 psi.
- (8) Tank 108: storing asphalt cement, constructed in 2001, with a storage capacity of 4,219,783 gallons, with a diameter of 134 feet and height of 40 feet, and a true vapor pressure less than 0.5 psi.
- (9) Tank 120: storing polymer modified asphalt cement, constructed in 1982, with a storage capacity of 24,614 gallons and annual throughput of 15,434,300 gallons per year, with a diameter of 10.5 feet and height of 38.0 feet, and a true vapor pressure less than 0.5 psi.
- (10) Tank 300: storing molten sulfur tank, constructed in 2004, with storage capacity of 5,264 gallons.
- (11) Tank 150: storing asphalt cement batch, constructed in 1982, with a storage capacity of 24,065 gallons and annual throughput of 15,434,300 gallons per year, with a diameter of 16.0 feet and height of 16.0 feet, and a true vapor pressure less than 0.5 psi.
- (12) Tank 201: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 44,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (13) Tank 202: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 44,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (14) Tank 203: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 42,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.
- (15) Tank 204: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 44,529 gallons and annual throughput of 10,451,850 gallons per year, with a diameter of 15.39 feet and height of 32.0 feet, and a true vapor pressure less than 1.0 psi.

- (16) Tank 205: storing asphalt emulsion and cutback emulsion, constructed in 2003, with a storage capacity of 40,304 gallons and annual throughput of 9,460,000 gallons per year, with a diameter of 14.0 feet and height of 35.0 feet, and a true vapor pressure less than 0.5 psi.
- (17) Tank 206: storing asphalt emulsion and cutback emulsion, constructed in 2003, with a storage capacity of 40,304 gallons and annual throughput of 9,460,000 gallons per year, with a diameter of 14.0 feet and height of 35.0 feet, and a true vapor pressure less than 0.5 psi.
- (18) Tank 207: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 65,179 gallons and annual throughput of 15,298,700 gallons per year, with a diameter of 21.5 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (19) Tank 208: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 65,179 gallons and annual throughput of 15,298,700 gallons per year, with a diameter of 21.5 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (20) Tank 209: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 124,127 gallons and annual throughput of 29,134,800 gallons per year, with a diameter of 29.67 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (21) Tank 210: storing asphalt emulsion and cutback emulsion, constructed in 1975, with a storage capacity of 124,127 gallons and annual throughput of 29,134,800 gallons per year, with a diameter of 29.67 feet and height of 24.0 feet, and a true vapor pressure less than 1.0 psi.
- (22) Tank 211: storing asphalt emulsion and cutback emulsion, constructed in 2008, with a storage capacity of 42,300 gallons and annual throughput of 9,928,800 gallons per year, with a diameter of 15.0 feet and height of 32 feet, and a true vapor pressure less than 0.5 psi.
- (23) Tank 212: storing asphalt emulsion and cutback emulsion, constructed in 1986, with a storage capacity of 48,129 gallons and annual throughput of 11,296,800 gallons per year, with a diameter of 16.0 feet and height of 32.0 feet, and a true vapor pressure less than 0.5 psi.
- (24) Tank 400: storing fuel oil, constructed in 1975, with a storage capacity of 20,080 gallons and annual throughput of 29,039,400 gallons per year, with a diameter of 10.5 feet and height of 31.0 feet, and a true vapor pressure less than 0.5 psi.
- (25) Tank 401: storing LD-95, constructed in 1975, with a storage capacity of 10,364 gallons, with a diameter of 10.5 feet and height of 16.0 feet.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-5.1-2(f)(1)] [326 IAC 2-5.5-4(a)(1)]

There are no Federal or State rules are applicable to these facilities.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH**

**REGISTRATION
ANNUAL NOTIFICATION**

This form should be used to comply with the notification requirements under 326 IAC 2-5.1-2(f)(3) and 326 IAC 2-5.5-4(a)(3).

Company Name:	Heritage Asphalt, L.L.C.
Address:	2820 East Durbin Street
City:	Warsaw, Indiana 46580
Phone Number:	(563) 584-1893
Registration No.:	No. 085-16440-00066

I hereby certify that Heritage Asphalt, L.L.C. is :	<input type="checkbox"/> still in operation.
	<input type="checkbox"/> no longer in operation.
I hereby certify that Heritage Asphalt, L.L.C. is :	<input type="checkbox"/> in compliance with the requirements of Registration No. 085-16440-00066.
	<input type="checkbox"/> not in compliance with the requirements of Registration No. 085-16440-00066.

Authorized Individual (typed):
Title:
Signature:
Phone Number:
Date:

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

Noncompliance:



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED

TO: Joe Muncy
Heritage Asphalt Company
2820 East Durbin Street
Waraw, Indiana 46580

DATE: July 14, 2009

FROM: Matt Stuckey, Branch Chief
Permits Branch
Office of Air Quality

SUBJECT: Final Decision
Registration - Notice Only Change
085-28153-00066

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:
Thomas Mattix (Heritage Group)
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at jbrush@idem.IN.gov.

Final Applicant Cover letter.dot 11/30/07

Mail Code 61-53

IDEM Staff	CDENNY 7/14/2009 Heritage Asphalt, LLC 085-28153-00066 (final)		Type of Mail: CERTIFICATE OF MAILING ONLY	AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204		

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handing Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee	Remarks
1		Joe Muncy Heritage Asphalt, LLC 2820 E Durbin St Warsaw IN 46580 (Source CAATS) VIA CONFIRMED DELIVERY										
2		David Blackburn President Heritage Asphalt, LLC 5400 W 86th St Indianapolis IN 46268 (RO CAATS)										
3		United Water Indiana 350 S. Buffalo Warsaw IN 46580 (Affected Party)										
4		Mr. Charles L. Berger Berger & Berger, Attorneys at Law 313 Main Street Evansville IN 47700 (Affected Party)										
5		Warsaw City Council and Mayors Office P.O. Box 817 Warsaw IN 46581 (Local Official)										
6		Kosciusko County Board of Commissioners 100 W. Center St, Room 220 Warsaw IN 46580 (Local Official)										
7		Thomas Mattix Heritage Group 5400 West 86th Street Indianapolis IN 46268 (Consultant)										
8		Mr. Tim Thomas c/o Boilermakers Local 374 6333 Kennedy Ave. Hammond IN 46333 (Affected Party)										
9		Kosciusko County Health Department 100 W. Center Street, 3rd Floor Warsaw IN 46580-2877 (Health Department)										
10												
11												
12												
13												
14												
15												

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See Domestic Mail Manual R900, S913, and S921 for limitations of coverage on inured and COD mail. See International Mail Manual for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
8			