INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: September 23, 2009

RE: ELSA, LLC / 095-28469-00048

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days from the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

(1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
(2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
(3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

(1) the name and address of the person making the request;
(2) the interest of the person making the request;
(3) identification of any persons represented by the person making the request;
(4) the reasons, with particularity, for the request;
(5) the issues, with particularity, proposed for considerations at any hearing; and
(6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER-AM.dot12/3/07

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
We Protect Hoosiers and Our Environment.

Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Mr. Jeffery Russell
ELSA, LLC
1240 South State Road 37
Elwood, IN 46036

September 23, 2009

Re: 095-28469-00048
Fourth Administrative Amendment to
Part 70 Operating Permit Renewal No.
T095-16479-00048

Dear Mr. Russell:

ELSA, LLC was issued a Part 70 Operating Permit Renewal on December 6, 2006 for a fuel tank and exhaust systems manufacturing plant located at 1240 South State Road 37, Elwood, Indiana. A letter requesting changes to this permit was received on September 16, 2009. The source indicated that the Administrative Amendment (AA) No.: 095-27789-00048 issued on July 31, 2009 for the new Filler Paint Line permit had typographical errors that incorrectly included outdated NESHAP language for a degreaser still identified in permit conditions D.1.6 and D.1.7. Since the facility quit using Trichloroethylene (they switched to n-Propyl Bromide) and previously submitted a modification request that has already been approved by IDEM, OAQ in Significant Source Modification No.: T095-27662-00048 issued May 29, 2009 and the Minor Permit Modification No.: T095-27297-00048 issued June 17 2009, this AA will remove the NESHAP language for 40 CFR Part 63 Subpart T.

The changes listed below have been made to Part 70 Operating Permit Renewal No.T095-16479- 00048. Deleted language appears as ~~strikethroughs~~ and new language appears in **bold**:

(1) Condition A.2 and Description Box D.1 have been revised to add the new solvent, remove the references to trichloroethylene and 40 CFR Part 63 Subpart T.

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)][326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

(a) One (1) open top vapor degreaser utilizing ~~trichloroethylene~~ **N-propyl bromide (NPB) based solvent**, identified as AN-01, constructed in 1989, with a maximum capacity of 2.3 gallons per hour, and exhausting to stack S3. ~~Under 40 CFR Part 63, Subpart T, this is considered a batch vapor cold solvent cleaning machine.~~

* * * *

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

(a) One (1) open top vapor degreaser utilizing ~~trichloroethylene~~ **N-propyl bromide (NPB) based solvent**, identified as AN-01, constructed in 1989, with a maximum capacity of 2.3 gallons per hour, and exhausting to stack S3. ~~Under 40 CFR Part 63, Subpart T, this is considered a batch vapor cold solvent cleaning machine.~~

* * * *

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

(2) Conditions D.1.6 and D.1.7 have been removed because 40 CFR Part 63, Subpart T no longer applies to the source. The source has stopped the use of trichloroethylene in the degreasers and does not use any of the other listed Halogenated solvents. In addition, these conditions have been removed from the Table of Contents.

~~National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]~~

~~D.1.6 General Provisions Relating to National Emission Standards for Hazardous Air Pollutants for Halogenated Solvent Cleaning [40 CFR 63.460] [326 IAC 20-1] [40 CFR Part 63, Subpart A]~~

~~(a) Pursuant to 40 CFR 63.460, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1 for the open top vapor degreaser (AN-01) as specified in Appendix A of 40 CFR Part 63, Subpart T in accordance with the schedule in 40 CFR 63 Subpart T.~~

~~(b) Pursuant to 40 CFR 63.10, the Permittee shall submit all required notifications and reports to:~~

~~Indiana Department of Environmental Management~~
~~Compliance and Enforcement Branch, Office of Air Quality~~
~~100 North Senate Avenue~~
~~MC 61-53 IGCN 1003~~
~~Indianapolis, Indiana 46204-2251~~

~~D.1.7 National Emission Standards for Hazardous Air Pollutants for Halogenated Solvent Cleaning [40 CFR Part 63, Subpart T] [326 IAC 20-6]~~

~~Pursuant to 40 CFR Part 63, Subpart T, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart T for the open top vapor degreaser (AN-01), as follows:~~

~~§ 63.460 Applicability and designation of source.~~

~~(a) The provisions of this subpart apply to each individual batch vapor, in-line vapor, in-line cold, and batch cold solvent cleaning machine that uses any solvent containing methylene chloride (CAS No. 75-09-2), perchloroethylene (CAS No. 127-18-4), trichloroethylene (CAS No. 79-01-6), 1,1,1-trichloroethane (CAS No. 71-55-6), carbon tetrachloride (CAS No. 56-23-5) or chloroform (CAS No. 67-66-3), or any combination of these halogenated HAP solvents, in a total concentration greater than 5 percent by weight, as a cleaning and/or drying agent. The concentration of these solvents may be determined using EPA test method 18, material safety data sheets, or engineering calculations. Wipe cleaning activities, such as using a rag containing halogenated solvent or a spray cleaner containing halogenated solvent are not covered under the provisions of this subpart.~~

~~(b) Except as noted in appendix C (General Provisions Applicability to Subpart T) of this subpart, the provisions of subpart A of this part (General Provisions) apply to owners or operators of any solvent cleaning machine meeting the applicability criteria of paragraph (a) of this section.~~

~~(d) Except as provided in paragraph (g) of this section, each solvent cleaning machine subject to this subpart that commenced construction or reconstruction on or before November 29, 1993 shall achieve compliance with the provisions of this subpart no later than December 2, 1997.~~

~~§ 63.463 Batch vapor and in-line cleaning machine standards.~~

~~(a) Except as provided in §63.464 for all cleaning machines, each owner or operator of a solvent cleaning machine subject to the provisions of this subpart shall ensure that each existing or new batch vapor or in-line solvent cleaning machine subject to the provisions of this subpart conforms to the design requirements specified in paragraphs (a)(1) through (7) of this section. The owner or operator of a continuous web cleaning machine shall comply with the requirements of paragraph (g) or (h) of this section, as appropriate, in lieu of complying with this paragraph.~~

~~(1) Each cleaning machine shall be designed or operated to meet the control equipment or technique parts through removal of cleaned parts.~~

~~(ii) A reduced room draft as described in §63.463(e)(2)(ii).~~

~~(2) Each cleaning machine shall have freeboard ratio of 0.75 or greater.~~

~~(3) Each cleaning machine shall have an automated parts handling system capable of moving parts or parts baskets at a speed of 3.4 meters per minute (11 feet per minute) or less from the initial loading of parts through removal of cleaned parts.~~

~~(4) Each vapor cleaning machine shall be equipped with a device that shuts off the sump heat if the sump liquid solvent level drops to the sump heater coils. This requirement does not apply to a vapor cleaning machine that uses steam to heat the solvent.~~

~~(5) Each vapor cleaning machine shall be equipped with a vapor level control device that shuts off sump heat if the vapor level in the vapor cleaning machine rises above the height of the primary condenser.~~

~~(6) Each vapor cleaning machine shall have a primary condenser.~~

~~(7) Each cleaning machine that uses a lip exhaust shall be designed and operated to route all collected solvent vapors through a properly operated and maintained carbon adsorber that meets the requirements of paragraph (e)(2)(vii) of this section.~~

~~(b) Except as provided in §63.464, each owner or operator of an existing or new batch vapor cleaning machine shall comply with either paragraph (b)(1) or (b)(2) of this section.~~

~~(2) Each owner or operator of a batch vapor cleaning machine with a solvent/air interface area greater than 1.21 square meters (13 square feet) shall comply with the requirements specified in either paragraph (b)(2)(i) or (b)(2)(ii) of this section.~~

~~(i) Employ one of the control combinations listed in table 2 of this subpart or other equivalent methods of control as determined using the procedure in §63.469, equivalent methods of control.~~

~~**Table 2_Control Combinations for Batch Vapor Solvent Cleaning MachinesWith a Solvent/Air Interface Area Greater than 1.21 Square Meters (13Square Feet)**~~

Option	Control combinations
6	Freeboard refrigeration device, reduced room draft, freeboard ratio of 1.0.

~~(d) Except as provided in §63.464 for all cleaning machines, each owner or operator of an existing or new batch vapor or in-line solvent cleaning machine shall meet all of the following required work and operational practices specified in paragraphs (d)(1) through (12) of this section as applicable. The owner~~

~~or operator of a continuous web cleaning machine shall comply with the requirements of paragraph (g) or (h) of this section, as appropriate, in lieu of complying with this paragraph.~~

~~(1) Control air disturbances across the cleaning machine opening(s) by incorporating the control equipment or techniques in paragraph (d)(1)(i) or (d)(1)(ii) of this section.~~

~~(ii) A reduced room draft as described in §63.463(e)(2)(ii).~~

~~(2) The parts baskets or the parts being cleaned in an open-top batch vapor cleaning machine shall not occupy more than 50 percent of the solvent/air interface area unless the parts baskets or parts are introduced at a speed of 0.9 meters per minute (3 feet per minute) or less.~~

~~(3) Any spraying operations shall be done within the vapor zone or within a section of the solvent cleaning machine that is not directly exposed to the ambient air (i.e., a baffled or enclosed area of the solvent cleaning machine).~~

~~(4) Parts shall be oriented so that the solvent drains from them freely. Parts having cavities or blind holes shall be tipped or rotated before being removed from any solvent cleaning machine unless an equally effective approach has been approved by the Administrator.~~

~~(5) Parts baskets or parts shall not be removed from any solvent cleaning machine until dripping has stopped.~~

~~(6) During startup of each vapor cleaning machine, the primary condenser shall be turned on before the sump heater.~~

~~(7) During shutdown of each vapor cleaning machine, the sump heater shall be turned off and the solvent vapor layer allowed to collapse before the primary condenser is turned off.~~

~~(8) When solvent is added or drained from any solvent cleaning machine, the solvent shall be transferred using threaded or other leakproof couplings and the end of the pipe in the solvent sump shall be located beneath the liquid solvent surface.~~

~~(9) Each solvent cleaning machine and associated controls shall be maintained as recommended by the manufacturers of the equipment or using alternative maintenance practices that have been demonstrated to the Administrator's satisfaction to achieve the same or better results as those recommended by the manufacturer.~~

~~(10) Each operator of a solvent cleaning machine shall complete and pass the applicable sections of the test of solvent cleaning procedures in appendix A to this part if requested during an inspection by the Administrator.~~

~~(11) Waste solvent, still bottoms, and sump bottoms shall be collected and stored in closed containers. The closed containers may contain a device that would allow pressure relief, but would not allow liquid solvent to drain from the container.~~

~~(12) Sponges, fabric, wood, and paper products shall not be cleaned.~~

~~(e) Each owner or operator of a solvent cleaning machine complying with paragraph (b), (c), (g), or (h) of this section shall comply with the requirements specified in paragraphs (e)(1) through (4) of this section.~~

~~(1) Conduct monitoring of each control device used to comply with §63.463 of this subpart as provided in §63.466.~~

~~(2) Determine during each monitoring period whether each control device used to comply with these standards meets the requirements specified in paragraphs (e)(2)(i) through (xi) of this section.~~

~~(i) If a freeboard refrigeration device is used to comply with these standards, the owner or operator shall ensure that the chilled air blanket temperature (in °F), measured at the center of the air blanket, is no greater than 30 percent of the solvent's boiling point.~~

~~(ii) If a reduced room draft is used to comply with these standards, the owner or operator shall comply with the requirements specified in paragraphs (e)(2)(ii)(A) and (e)(2)(ii)(B) of this section.~~

~~(A) Ensure that the flow or movement of air across the top of the freeboard area of the solvent cleaning machine or within the solvent cleaning machine enclosure does not exceed 15.2 meters per minute (50 feet per minute) at any time as measured using the procedures in §63.466(d).~~

~~(B) Establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less as described in §63.466(d).~~

~~(3) If any of the requirements of paragraph (e)(2) of this section are not met, determine whether an exceedance has occurred using the criteria in paragraphs (e)(3)(i) and (e)(3)(ii) of this section.~~

~~(i) An exceedance has occurred if the requirements of paragraphs (e)(2)(ii)(B), (e)(2)(iii)(A), (e)(2)(iv)(A), (e)(2)(v), (e)(2)(vi)(B), (e)(2)(vi)(C), (e)(2)(vii)(B), or (e)(2)(vii)(C) of this section have not been met.~~

~~(ii) An exceedance has occurred if the requirements of paragraphs (e)(2)(i), (e)(2)(ii)(A), (e)(2)(iii)(B),(e)(2)(iv)(B),(e)(2)(vi)(A) or (e)(2)(vii)(A) of this section have not been met and are not corrected within 15 days of detection. Adjustments of repairs shall be made to the solvent cleaning system or control device to reestablish required levels. The parameter must be remeasured immediately upon adjustment or repair and demonstrated to be within required limits.~~

~~(4) The owner or operator shall report all exceedances and all corrections and adjustments made to avoid an exceedance as specified in §63.468(h).~~

~~§ 63.465 Test Methods~~

~~(e) An owner or operator of a source shall determine their potential to emit from all solvent cleaning operations, using the procedures described in paragraphs (e)(1) through (e)(3) of this section. A facility's total potential to emit is the sum of the HAP emissions from all solvent cleaning operations, plus all HAP emissions from other sources within the facility.~~

~~(1) Determine the potential to emit for each individual solvent cleaning using equation 6.~~

~~PTEi=Hi×Wi×SAIi (6)~~

~~Where:~~

~~PTEi=the potential to emit for solvent cleaning machine i (kilograms of solvent per year).~~

~~Hi=hours of operation for solvent cleaning machine i (hours per year).~~

~~=8760 hours per year, unless otherwise restricted by a Federally enforceable requirement.~~

~~Wi=the working mode uncontrolled emission rate (kilograms per square meter per hour).~~

~~=1.95 kilograms per square meter per hour for batch vapor and cold cleaning machines.~~

~~=1.12 kilograms per square meter per hour for in-line cleaning machines.~~

~~SAIi = solvent/air interface area of solvent cleaning machine i (square meters). Section 63.461 defines the solvent/air interface area for those machines that have a solvent/air interface. Cleaning machines that do not have a solvent/air interface shall calculate a solvent/air interface area using the procedure in paragraph (e)(2) of this section.~~

~~(2) Cleaning machines that do not have a solvent/air interface shall calculate a solvent/air interface area using equation 7.~~

~~SAI=2.20 * (Vol)0.6 (7)~~

~~Where:~~

~~SAI=the solvent/air interface area (square meters).~~

~~Vol=the cleaning capacity of the solvent cleaning machine (cubic meters).~~

~~(3) Sum the PTEi for all solvent cleaning operations to obtain the total potential to emit for solvent cleaning operations at the facility.~~

~~§ 63.466 Monitoring procedures.~~

~~(a) Except as provided in paragraph (g) of this section, each owner or operator of a batch vapor or in-line solvent cleaning machine complying with the equipment standards in §63.463(b)(1)(i), (b)(2)(i), (c)(1)(i), (c)(2)(i), (g)(1), or (g)(2) shall conduct monitoring and record the results on a weekly basis for the control devices, as appropriate, specified in paragraphs (a)(1) through (5) of this section.~~

~~(1) If a freeboard refrigeration device is used to comply with these standards, the owner or operator shall use a thermometer or thermocouple to measure the temperature at the center of the air blanket during the idling mode.~~

~~(c) Except as provided in paragraph (g) of this section, each owner or operator of a batch vapor or in-line solvent cleaning machine complying with the equipment or idling standards in §63.463 shall monitor the hoist speed as described in paragraphs (c)(1) through (c)(4) of this section.~~

~~(1) The owner or operator shall determine the hoist speed by measuring the time it takes for the hoist to travel a measured distance. The speed is equal to the distance in meters divided by the time in minutes (meters per minute).~~

~~(2) The monitoring shall be conducted monthly. If after the first year, no exceedances of the hoist speed are measured, the owner or operator may begin monitoring the hoist speed quarterly.~~

~~(3) If an exceedance of the hoist speed occurs during quarterly monitoring, the monitoring frequency returns to monthly until another year of compliance without an exceedance is demonstrated.~~

~~(4) If an owner or operator can demonstrate to the Administrator's satisfaction in the initial compliance report that the hoist cannot exceed a speed of 3.4 meters per minute (11 feet per minute), the required monitoring frequency is quarterly, including during the first year of compliance.~~

~~(d) Except as provided in paragraph (g) of this section, each owner or operator of a batch vapor or in-line solvent cleaning machine complying with the equipment standards in §63.463 (b)(1)(i), (b)(2)(i), (c)(1)(i), or (c)(2)(i) using a reduced room draft shall conduct monitoring and record the results as specified in paragraph(d)(1) or (d)(2) of this section.~~

~~(1) If the reduced room draft is maintained by controlling room parameters (i.e., redirecting fans, closing doors and windows, etc.), the owner or operator shall conduct an initial monitoring test of the windspeed and of room parameters, quarterly monitoring of windspeed, and weekly monitoring of room parameters as specified in paragraphs (d)(1)(i) and (d)(1)(ii) of this section.~~

~~(i) Measure the windspeed within 6 inches above the top of the freeboard area of the solvent cleaning machine using the procedure specified in paragraphs (d)(1)(i)(A) through (d)(1)(i)(D) of this section.~~

~~(A) Determine the direction of the wind current by slowly rotating a velometer or similar device until the maximum speed is located.~~

~~(B) Orient a velometer in the direction of the wind current at each of the four corners of the machine.~~

~~(C) Record the reading for each corner.~~

~~(D) Average the values obtained at each corner and record the average wind speed.~~

~~(ii) Monitor on a weekly basis the room parameters established during the initial compliance test that are used to achieve the reduced room draft.~~

~~(g) Each owner or operator using a control device listed in paragraphs (a) through (e) of this section can use alternative monitoring procedures approved by the Administrator.~~

~~§ 63.467 Recordkeeping requirements~~

~~(a) Each owner or operator of a batch vapor or in-line solvent cleaning machine complying with the provisions of §63.463 shall maintain records in written or electronic form specified in paragraphs (a)(1) through (7) of this section for the lifetime of the machine.~~

~~(1) Owner's manuals, or if not available, written maintenance and operating procedures, for the solvent cleaning machine and control equipment.~~

~~(2) The date of installation for the solvent cleaning machine and all of its control devices. If the exact date for installation is not known, a letter certifying that the cleaning machine and its control devices were installed prior to, or on, November 29, 1993, or after November 29, 1993, may be substituted.~~

~~(5) Records of the halogenated HAP solvent content for each solvent used in a solvent cleaning machine subject to the provisions of this subpart.~~

~~(b) Each owner or operator of a batch vapor or in-line solvent cleaning machine complying with §63.463 shall maintain records specified in paragraphs (b)(1) through (b)(4) of this section either in electronic or written form for a period of 5 years.~~

~~(1) The results of control device monitoring required under §63.466.~~

~~(2) Information on the actions taken to comply with §63.463(e) and (f). This information shall include records of written or verbal orders for replacement parts, a description of the repairs made, and additional monitoring conducted to demonstrate that monitored parameters have returned to accepted levels.~~

~~(3) Estimates of annual solvent consumption for each solvent cleaning machine.~~

~~§ 63.468 Reporting requirements.~~

~~(a) Each owner or operator of an existing solvent cleaning machine subject to the provisions of this subpart shall submit an initial notification report to the Administrator no later than August 29, 1995. This report shall include the information specified in paragraphs (a)(1) through (a)(6) of this section.~~

~~(1) The name and address of the owner or operator.~~

~~(2) The address (i.e., physical location) of the solvent cleaning machine(s).~~

~~(3) A brief description of each solvent cleaning machine including machine type (batch vapor, batch cold, vapor in-line or cold in-line), solvent/air interface area, and existing controls.~~

~~(4) The date of installation for each solvent cleaning machine or a letter certifying that the solvent cleaning machine was installed prior to, or after, November 29, 1993.~~

~~(5) The anticipated compliance approach for each solvent cleaning machine.~~

~~(6) An estimate of annual halogenated HAP solvent consumption for each solvent cleaning machine.~~

~~(d) Each owner or operator of a batch vapor or in-line solvent cleaning machine complying with the provisions of §63.463 shall submit to the Administrator an initial statement of compliance for each solvent cleaning machine. For existing sources, this report shall be submitted to the Administrator no later than 150 days after the compliance date specified in §63.460(d). For new sources, this report shall be submitted to the Administrator no later than 150 days after startup or May 1, 1995, whichever is later. This statement shall include the requirements specified in paragraphs (d)(1) through (d)(6) of this section.~~

~~(1) The name and address of the owner or operator.~~

~~(2) The address (i.e., physical location) of the solvent cleaning machine(s).~~

~~(3) A list of the control equipment used to achieve compliance for each solvent cleaning machine.~~

~~(4) For each piece of control equipment required to be monitored, a list of the parameters that are monitored and the values of these parameters measured on or during the first month after the compliance date.~~

~~(5) Conditions to maintain the wind speed requirements of §63.463(e)(2)(ii), if applicable.~~

~~(f) Each owner or operator of a batch vapor or in-line solvent cleaning machine complying with the provisions of §63.463 shall submit an annual report by February 1 of the year following the one for which the reporting is being made. This report shall include the requirements specified in paragraphs (f)(1) through (f)(3) of this section.~~

~~(1) A signed statement from the facility owner or his designee stating that, "All operators of solvent cleaning machines have received training on the proper operation of solvent cleaning machines and their control devices sufficient to pass the test required in §63.463(d)(10)."~~

~~(2) An estimate of solvent consumption for each solvent cleaning machine during the reporting period.~~

~~(3) The reports required under paragraphs (f) and (g) of this section can be combined into a single report for each facility.~~

~~(h) Each owner or operator of a batch vapor or in-line solvent cleaning machine shall submit an exceedance report to the Administrator semiannually except when, the Administrator determines on a case-by-case basis that more frequent reporting is necessary to accurately assess the compliance status of the source or, an exceedance occurs. Once an exceedance has occurred the owner or operator shall follow a quarterly reporting format until a request to reduce reporting frequency under paragraph (i) of this section is approved. Exceedance reports shall be delivered or postmarked by the 30th day following the end of each calendar half or quarter, as appropriate. The exceedance report shall include the applicable information in paragraphs (h) (1) through (3) of this section.~~

~~(1) Information on the actions taken to comply with §63.463 (e) and (f). This information shall include records of written or verbal orders for replacement parts, a description of the repairs made, and additional monitoring conducted to demonstrate that monitored parameters have returned to accepted levels.~~

~~(2) If an exceedance has occurred, the reason for the exceedance and a description of the actions taken.~~

~~(3) If no exceedances of a parameter have occurred, or a piece of equipment has not been inoperative, out of control, repaired, or adjusted, such information shall be stated in the report.~~

~~(i) An owner or operator who is required to submit an exceedance report on a quarterly (or more frequent) basis may reduce the frequency of reporting to semiannual if the conditions in paragraphs (i)(1) through (i)(3) of this section are met.~~

~~(1) The source has demonstrated a full year of compliance without an exceedance.~~

~~(2) The owner or operator continues to comply with all relevant recordkeeping and monitoring requirements specified subpart A (General Provisions) and in this subpart.~~

~~(3) The Administrator does not object to a reduced frequency of reporting for the affected source as provided in paragraph (e)(3)(iii) of subpart A (General Provisions).~~

~~(k) Each owner or operator of a solvent cleaning machine requesting an equivalency determination, as described in §63.469 shall submit an equivalency request report to the Administrator. For existing sources, this report must be submitted to the Administrator no later than June 3, 1996. For new sources, this report must be submitted and approved by the Administrator prior to startup.~~

~~§ 63.469 Equivalent methods of control.~~

~~Upon written application, the Administrator may approve the use of equipment or procedures after they have been satisfactorily demonstrated to be equivalent, in terms of reducing emissions of methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride or chloroform to the atmosphere, to those prescribed for compliance within a specified paragraph of this subpart. The application must contain a complete description of the equipment or procedure and the proposed equivalency testing procedure and the date, time, and location scheduled for the equivalency demonstration.~~

~~§ 63.470 Implementation and enforcement.~~

~~(a) This subpart can be implemented and enforced by the U.S. EPA, or a delegated authority such as the applicable State, local, or Tribal agency. If the U.S. EPA Administrator has delegated authority to a State, local, or Tribal agency, then that agency, in addition to the U.S. EPA, has the authority to implement and enforce this subpart. Contact the applicable U.S. EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to a State, local, or Tribal agency.~~

~~(b) In delegating implementation and enforcement authority of this subpart to a State, local, or Tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator of U.S. EPA and cannot be transferred to the State, local, or Tribal agency.~~

~~(c) The authorities that cannot be delegated to State, local, or Tribal agencies are as specified in paragraphs (c)(1) through (4) of this section.~~

~~(1) Approval of alternatives to the requirements in §§63.460, 63.462(a) through (d), and 63.463 through 63.464 (except for the authorities in §63.463(d)(9)). Use the procedures in §63.469 to request the use of alternative equipment or procedures.~~

~~(2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f), as defined in §63.90, and as required in this subpart.~~

~~(3) Approval of major alternatives to monitoring under §63.8(f), as defined in §63.90, and as required in this subpart.~~

~~(4) Approval of major alternatives to recordkeeping and reporting under §63.10(f), as defined in §63.90, and as required in this subpart.~~

All other conditions of the permit shall remain unchanged and in effect. Please find attached the entire Part 70 Operating Permit Renewal as revised.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Charles Sullivan, of my staff, at (317) 232-8422, or 1-800-451-6027, and ask for extension 2-8422.

Sincerely,

Donald F. Robin

Donald F. Robin, P.E., Section Chief
Permits Branch
Office of Air Quality

DFR/cs
cc: File - Madison County
U.S. EPA, Region V
Madison County Health Department
Air Compliance Section Inspector
Compliance and Enforcement Branch
Permit Administration and Support Section

IDEM

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

PART 70 OPERATING PERMIT RENEWAL
OFFICE OF AIR QUALITY

ELSA, LLC.
1240 South State Road 37
Elwood, Indiana 46036

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T095-16479-00048	
Issued by: Original signed by: Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: December 6, 2006 Expiration Date: December 6, 2011

First Administrative Amendment No.: 095-24841-00048, issued on November 1, 2007.
Second Administrative Amendment No.: 095-27543-00048, issued on March 9, 2009.
First Minor Permit Modification No.: 095-27297-00048, issued on June 17, 2009.
Third Administrative Amendment No.: 095-27789-00048, issued on July 31, 2009.

Fourth Administrative Amendment No.: 095-28469-00048	
Issued by: Donald F. Robin Donald F. Robin, P.E., Section Chief Permits Branch Office of Air Quality	Issuance Date: September 23, 2009 Expiration Date: December 6, 2011

TABLE OF CONTENTS

SECTION A SOURCE SUMMARY
A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]
A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]
A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

SECTION B GENERAL CONDITIONS
B.1 Definitions [326 IAC 2-7-1]
B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)][IC 13-15-3-6(a)]
B.3 Term of Conditions [326 IAC 2-1.1-9.5]
B.4 Enforceability [326 IAC 2-7-7]
B.5 Severability [326 IAC 2-7-5(5)]
B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]
B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]
B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]
B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]
B.11 Emergency Provisions [326 IAC 2-7-16]
B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]
B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]
B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]
B.17 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4] [326 IAC 2-7-8(e)]
B.18 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]
B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]
B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]
B.21 Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2]
B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]
B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]
B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]
B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314][326 IAC 1-1-6]

SECTION C SOURCE OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]
C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]
C.2 Opacity [326 IAC 5-1]
C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
C.5 Fugitive Dust Emissions [326 IAC 6-4]
C.6 Stack Height [326 IAC 1-7]
C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

Testing Requirements [326 IAC 2-7-6(1)]
C.8 Performance Testing [326 IAC 3-6]

Compliance Requirements [326 IAC 2-1.1-11]
C.9 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]
C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
C.11 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]
C.12 Instrument Specifications [326 IAC 2-1.1-11][326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]
C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]
C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]
C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection
C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-3]
D.1.2 HAP Minor Limit [40 CFR 63 Subpart MMMM]]

Compliance Determination Requirements
D.1.3 Hazardous Air Pollutants (HAP)

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]
D.1.4 Recordkeeping Requirements
D.1.5 Reporting Requirements

SECTION D.2 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.2.1 Volatile Organic Compounds (VOC) Limitations [326 IAC 8-2-9]
D.2.2 Volatile Organic Compound (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9]
D.2.3 PSD Minor Limit [326 IAC 2-2]
D.2.4 HAP Minor Limit [40 CFR 63, Subpart MMMM]
D.2.5 Emission Offset Minor Limitation [326 IAC 2-3]
D.2.6 Incinerators [326 IAC 4-2-2]
D.2.7 Particulate [326 IAC 6-3-2(d)]
D.2.8 Carbon Monoxide
D.2.9 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements
D.2.10 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants [326 IAC 8-1-2] [326 IAC 8-1-4]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]
D.2.11 Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]
D.2.12 Record Keeping Requirements
D.2.13 Reporting Requirements

SECTION D.3 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.3.1 Particulate [326 IAC 6-3-2]

Certification
VOC Usage and HAP Usage Quarterly Reports
Emergency Occurrence Report
Quarterly Deviation and Compliance Monitoring Report

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary fuel tank and exhaust systems manufacturing plant.

Source Address:	1240 South State Road 37, Elwood, Indiana 46036
Mailing Address:	1240 South State Road 37, Elwood, Indiana 46036
General Source Phone Number:	(765) 557-2009
SIC Code:	3714
County Location:	Madison
Source Location Status:	Nonattainment for 8-hour ozone standard Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Minor Source under PSD and Emission Offset Rules; Minor Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)][326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

(a) One (1) open top vapor degreaser utilizing N-propyl bromide (NPB) based solvent, identified as AN-01, constructed in 1989, with a maximum capacity of 2.3 gallons per hour, and exhausting to stack S3.

(b) One (1) paint booth coating metal parts, identified as AM-08 Robotic (formerly Subaru) Paint Booth, constructed in 1989, with a maximum capacity of 28 units per hour, using dry filters to control particulate emissions, and exhausting to stack S14.

(c) One (1) paint booth coating metal parts, identified as AM-09 Robotic (formerly Top Coat) Booth, constructed in 1989, with a maximum capacity of 25 fuel tanks/hr, using a robotic spray arm, using dry filters to control particulate emissions, and exhausting to stack S15.

(d) One (1) paint booth coating metal parts, identified as AM-10 Paint (formerly Touch-up) Booth, constructed in 1989, with a maximum capacity of 25 fuel tanks/hr, using dry filters to control particulate emissions, and exhausting to stack S16.

(e) One (1) ring paint operation, approved for construction in 2007, identified as AN-33, with a maximum capacity of 1.625 gal/hr. This operation uses a mechanically applied drop of paint (for control quality) that is then brushed on the part at three different areas.

(f) One (1) paint booth coating metal parts, identified as BE-04 Robotic (formerly PSU Tank Robot) Paint Booth, constructed in 1993, with a maximum capacity of 36 fuel tanks per hour, using dry filters to control particulate emissions, and exhausting to stack S34.

(g) One (1) paint booth coating metal parts, identified as BE-05 Paint (formerly PSU Touch-up) Booth, constructed in 1993, with a maximum capacity of 36 fuel tanks per hour, using dry filters to control particulate emissions, and exhausting to stack S35.

(h) One (1) paint booth coating metal parts, identified as BE-06 Robotic (formerly PSU Tank Final) Paint Booth, constructed in 2005, with a maximum capacity of 25 fuel tanks/hour, using dry filters to control particulate emissions and exhausting to stack S42.

(i) One (1) paint booth coating metal parts, identified as Exhaust Robotic (formerly PSU Exhaust Robot) Paint Booth, constructed in 1997 and modified in 2006, with a maximum capacity of 23 mufflers per hour, using dry filters to control particulate emissions, and exhausting to stack S44.

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

(a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment cutting torches, soldering equipment, welding equipment [326 IAC 6-3-2].

(1) Eight (8) metal inert gas (MIG) welders, identified as AC31, AC36-1, AJ29, AJ28-1, AP12, AP19, AP23, and AP40, constructed in 2000, 2000, 1992, 1992, 1989, 1990, 1990, and 1990, respectively, each with a maximum wire consumption of 0.94 pounds per hour, all exhausting to stack 4.

(2) One (1) metal inert gas (MIG) welder, identified as AP32, constructed in 1990, with a maximum wire consumption of 0.94 pounds per hour, exhausting to stack SE-01.

(3) Six (6) metal inert gas (MIG) welders, identified as AE12, AE30-11, AE31, AE32, AE33, and AE34, all constructed in 1998, each with a maximum wire consumption of 0.80 pounds per hour, all exhausting to stack 5.

(4) Nine (9) metal inert gas (MIG) welders, identified as AA08-2, AA13, AF24, AF30, AF31, AF32-2, AF35, AF36, and AF37, constructed in 1998, 1993, 1998, 1992, 1992, 1998, 1995, 1993, and 1998, respectively, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack 7.

(5) Five (5) metal inert gas (MIG) welders, identified as AB313, AB31-A, AB38, AB39, and AB40, constructed in 2000, 2000, 2000, 2000, and 1992 respectively, each with a maximum wire consumption of 0.75 pounds per hour, all exhausting to stacks 6 and 8.

(6) One (1) metal inert gas (MIG) welder, identified as kaizen, constructed in 1994, with a maximum wire consumption of 0.74 pounds per hour, exhausting to stack 17.

(7) Ten (10) metal inert gas (MIG) welders, identified as AW03, AW04, AY07, AY12, AY13, AZ02, AZ03, AZ05, AZ06, and AZ08, constructed in 1994, 1994, 1995, 1994, 1994, 1994, 1995, 1992, 1994, and 1994, respectively, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack 28.

(8) Five (5) metal inert gas (MIG) welders, identified as AW01, AW02, AY02, AY03, and AY05, constructed in 1990, 1995, 1995, 1989, and 1993, respectively, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack SE-01.

(9) Fourteen (14) metal inert gas (MIG) welders, identified as AI31-2, AI33-1, AI33-2, AI33-3, AI34-1, AS24, AS26, AS30, AS31, AS33-1, AS38, AS39, AS47, and AS50, constructed in 1995, 1995, 1995, 1997, 1997, 1997, 1989, 1995, 1995, 1997, 1997, 1997, 1995, and 1997, respectively, each with a maximum wire consumption of 0.74 pounds per hour, and two (2) tungsten inert gas (TIG) welders, identified as

AS55, and AS59, both constructed in 1997, both with a maximum metal consumption of 0.03 pounds per hour, and all exhausting to stack 29.

(10) Nineteen (19) metal inert gas (MIG) welders, identified as BK01, BK05, BK14, BK18, BL10, BL11, BL16, BL29-1, BL29-2, BQ22, BQ23, BS10, BS11, BS12-1, BS13, BS14, BS15, BS16-1, and BS17-1, constructed in 1996, 1996, 1996, 1996, 1996, 1992, 1996, 1992, 1992, 1999, 1999, 1999, 1999, 1995, 1996, 1996, 1996, 1996, and 1996, respectively each with a maximum wire consumption of 0.74 pounds per hour, and three (3) tungsten inert gas (TIG) welders, identified as BS17-2, BV10, and BV11, constructed in 1996, 1995, and 1993, respectively, each with a maximum metal consumption of 0.03 pounds per hour, and all exhausting to stack 33.

(11) Twenty-one (21) metal inert gas (MIG) welders, identified as AG02, AE24, AG01, AG09, AG10, AQ00, AS01, AS04-1, AY10-1, AM00, AM01, AP01, AV08, AV09, AV01, AV02, AV04, AV05, AV06, AV07, and AV07-1, constructed in 1990, 1990, 1990, 1990, 1990, 1993, 1991, 1991, 1991, 1990, 1992, 1992, 1990, 1990, 1990, 1990, 1990, 1995, 1995, 1990, and 1990, respectively, each with a maximum wire consumption of 0.75 pounds per hour, all exhausting to stack 37.

(12) One (1) metal inert gas (MIG) welder, identified as AK01, constructed in 1989, with a maximum wire consumption of 0.75 pounds per hour, exhausting to stack SE-01.

(13) Seventeen (17) metal inert gas (MIG) welders, identified as BH02, BH05, BH06, BH07, BH07-1, BH08, BH08-1, BH10, BH11, BH11-1, BH13, BH14, BH17, BH3-1, BH3-2, BU32, and BH34-1, constructed in 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1993, and 1993, respectively, each with a maximum wire consumption of 0.74 pounds per hour, and two (2) tungsten inert gas (TIG) welders, identified as BU43-1 and BU45-1, constructed in 1992 and 1995, respectively, both with a maximum metal consumption of 0.03 pounds per hour, and all exhausting to stack 38.

(14) One (1) metal inert gas (MIG) welder, identified as eng, constructed in 1995, with a maximum wire consumption of 0.74 pounds per hour, exhausting to stack 43.

(15) Seven (7) metal inert gas (MIG) welders, identified as DC1, DC2, DC3, DC4, DC5, DC6, and AG1, all constructed in 2002, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack 99.

(16) Twenty-one (21) metal inert gas (MIG) welders, identified as BG28A, BG28B, BG32A, BG32B, BG33A, BG33B, BG35A, BG35B, BG47A, BG47B, 2300, BG20, BG21, BG22-2, BG23, BG24, BG25, BG25-1, BG27A, BG27B, and BG27C, constructed in 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 1993, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, and 2001, respectively, each with a maximum wire consumption of 0.75 pounds per hour, all exhausting to stack 100.

(17) Four (4) Metal Inert Gas welding units, approved for construction in 2007, identified as AR-02, AR-03, AR-05, and BR-01, each with a maximum wire consumption rate of 0.045 pound per hour, and exhausting to stack SE-01.

(18) Seven (7) electrical resistance welding stations, approved for construction in 2007, and identified as AN-20, AN-21, AN-22, AN-23, AN-25, AN-27, and AN-29.

(b) Activities with emissions equal to or less than the following thresholds: 5 tons per year PM or PM10, 10 tons per year SO_2, NOx, or VOC, 0.2 tons per year Pb, 1.0 tons per year of a single HAP, or 2.5 tons per year of any combination of HAPs:

(1) One (1) paint burn-off oven, constructed in 2002. [326 IAC 4-2-2]

(c) One (1) tank washing machine, approved for construction in 2007, identified as AN-24.

(d) Hydrostatic testing equipment, approved for construction in 2007, identified as AN-31.

(e) One (1) printing operation that puts an ink label on plastic airboxes, approved for construction in 2007, with a maximum ink consumption rate of 3.75 pounds per year.

(f) Two (2) natural gas fired heating units, identified as Building E Heaters, approved for construction in 2007, each rated at 0.5 MMBtu/hr, exhausting to stack SHE-01 and SHE-02.

(g) One (1) airbox injection molding process, approved for construction in 2007, molding polypropylene at a maximum rate of 90.4 pounds per hour.

(h) One (1) filler pipe paint line, approved for construction in 2009, with a stand-alone paint booth located inside the paint room. Line consists of multiple stations to bend, flare, trim and wash (using caustic and water-based cleaning solutions) straight pieces of pipe. A minor amount of brazing and welding also occurs to the pipe in this line**.**

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

(a) It is a major source, as defined in 326 IAC 2-7-1(22);

(b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5] [326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]

(a) This permit, T095-16479-00048, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.

(b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

(a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or

(b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability [326 IAC 2-7-7]

Less otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

(a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.

(b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

(a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

(b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.

(c) A responsible official is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

(a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

(b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(c) The annual compliance certification report shall include the following:

(1) The appropriate identification of each term or condition of this permit that is the basis of the certification;

(2) The compliance status;

(3) Whether compliance was continuous or intermittent;

(4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and

(5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

(a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare, maintain, and implement Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each facility:

(1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;

(2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and

(3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

(b) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

(a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.

(b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

(1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;

(2) The permitted facility was at the time being properly operated;

(3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;

(4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

IDEM Main Office
Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance and Enforcement Branch), or
Telephone Number: 317-233-0178 (ask for Compliance and Enforcement Branch)
Facsimile Number: 317-233-6865

(5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

(A) A description of the emergency;

(B) Any steps taken to mitigate the emissions; and

(C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(6) The Permittee immediately took all reasonable steps to correct the emergency.

(c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.

(d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.

(e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.

(f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.

(g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

(h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

(a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

(b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.

(c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.

(d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:

(1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;

(2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;

(3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and

(4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.

(e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).

(f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]

(g) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(c)(7)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]

(a) All terms and conditions of permits established prior to T095-16479-00048 and issued pursuant to permitting programs approved into the state implementation plan have been either:

(1) incorporated as originally stated,

(2) revised under 326 IAC 2-7-10.5, or

(3) deleted under 326 IAC 2-7-10.5.

(b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit.

B.14 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

(a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:

(1) That this permit contains a material mistake.

(2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.

(3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]

(c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]

(d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-3] [326 IAC 2-7-4] [326 IAC 2-7-8(e)]

(a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

(b) A timely renewal application is one that is:

(1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and

(2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.

B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12][40 CFR 72]

(a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

(b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]

(a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.

(b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

(a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

(1) The changes are not modifications under any provision of Title I of the Clean Air Act;

(2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;

(3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

(4) The Permittee notifies the:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

(5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emissions trades that are subject to 326 IAC 2-7-20(b), (c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

(b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

(1) A brief description of the change within the source;

(2) The date on which the change will occur;

(3) Any change in emissions; and

(4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).

(d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

(e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.21 Source Modification Requirement [326 IAC 2-7-10.5] [326 IAC 2]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2] [IC 13-30-3-1] [IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

(a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;

(b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;

(c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;

(d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

(e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

(a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.

(b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

(a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.

(b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.

(c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314][326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

(a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.

(b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4(4) are not federally enforceable.

C.6 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted. The provisions of 326 IAC 1-7-1(3), 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4, and 326 IAC 1-7-5(a), (b), and (d) are not federally enforceable.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

(a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

(b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:

(1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or

(2) If there is a change in the following:

(A) Asbestos removal or demolition start date;

(B) Removal or demolition contractor; or

(C) Waste disposal site.

(c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).

(d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(e) Procedures for Asbestos Emission Control
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.

(f) Demolition and renovation
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).

(g) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.8 Performance Testing [326 IAC 3-6]

(a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.12 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

(a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale.

(b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

(a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.

(b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

within ninety (90) days after the date of issuance of this permit.

The ERP does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) If the ERP is disapproved by IDEM, OAQ, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.

(d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.

(e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.

(f) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level.
[326 IAC 1-5-3]

C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.15 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]

(a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.

(b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:

(1) initial inspection and evaluation;

(2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or

(3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.

(c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:

(1) monitoring results;

(2) review of operation and maintenance procedures and records;

(3) inspection of the control device, associated capture system, and the process.

(d) Failure to take reasonable response steps shall be considered a deviation from the permit.

(e) The Permittee shall maintain the following records:

(1) monitoring data;

(2) monitor performance data, if applicable; and

(3) corrective actions taken.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

(a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.

(b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.

(c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

(a) Pursuant to 326 IAC 2-6-3(b)(2), starting in 2005 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:

(1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);

(2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1 (32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
MC 61-50 IGCN 1003
Indianapolis, Indiana 46204-2251

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

(a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

(b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

(a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

(c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(e) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

Stratospheric Ozone Protection

C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

(a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.

(b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.

(c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

(a) One (1) open top vapor degreaser utilizing N-propyl bromide (NPB) based solvent, identified as AN-01, constructed in 1989, with a maximum capacity of 2.3 gallons per hour, and exhausting to stack S3.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-3]

Pursuant to 326 IAC 8-3-3 (Open Top Vapor Degreasing Operations) for open top vapor degreasing operations (AN-01) constructed after January 1, 1980, the Permittee shall:

(a) Equip the open top vapor degreaser with a cover that can be opened and closed easily without disturbing the vapor zone;

(b) Keep the cover closed at all times except when processing workloads through the degreaser;

(c) Minimize solvent carry-out by:

(1) Racking parts to allow complete drainage;

(2) Moving parts in and out of the degreaser at less than eleven (11) feet per minute;

(3) Degreasing the workload in the vapor zone at least thirty (30) seconds or until condensation ceases;

(4) Tipping out any pools of solvent on the cleaned parts before removal;

(5) Allowing parts to dry within the degreaser for at least fifteen (15) seconds or until visually dry;

(d) Not degrease porous or absorbent materials, such as cloth, leather, wood or rope;

(e) Not occupy more than half of the degreaser's open top area with the workload;

(f) Not load the degreaser such that the vapor level drops more than fifty percent (50%) of the vapor depth when the workload is removed;

(g) Never spray above the vapor level;

(h) Repair solvent leaks immediately, or shut down the degreaser;

(i) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, such that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere;

(j) Not use workplace fans near the degreaser opening;

(k) Not allow visually detectable water in the solvent exiting the water separator; and

(l) Provide a permanent, conspicuous label summarizing the operating requirements.

D.1.2 HAP Minor Limitations [40 CFR 63, Subpart MMMM] [326 IAC 2-4.1]

The amount of HAP used in the open top vapor degreaser (AN-01) (listed in this Section), combined with the amount of HAP used in the surface coating operations shall be limited to less than nine and nine-tenths (9.9) tons per twelve (12) consecutive month period for any single HAP and less than 24.4 tons per twelve (12) consecutive month period for any combination of HAPs.

This limit, combined with the HAP usage limits in Condition D.2.4 and the HAP emissions from the other emission units at this source, will limit the source-wide emissions of HAPs to less than ten (10) tons of a single HAP and less than twenty-five (25) tons of a combination of HAPs per twelve (12) consecutive month period. Compliance with these limits makes the requirements of 40 CFR 63, Subpart MMMM and 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) not applicable to this source.

Compliance Determination Requirements

D.1.3 Hazardous Air Pollutants (HAP)

Compliance with the HAP usage limitations in Condition D.1.2 shall be determined by one of the following:

(a) The manufacturer's certified product data sheet.

(b) The manufacturer's material safety data sheet.

(c) Sampling and analysis, using methods outlined in 40 CFR 63.3941, Subpart MMMM.

(d) An alternate method approved by IDEM, OAQ.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.4 Record Keeping Requirements

(a) To document compliance with Condition D.1.2, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken monthly and shall be complete and sufficient to establish compliance with the HAP usage limits established in Condition D.1.2. Records necessary to demonstrate compliance shall be available within 30 days of the end of each compliance period.

(1) The amount and HAP content of each solvent used on a monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.

(2) The total HAP usage for each month; and

(3) The weight of HAPs emitted for each compliance period.

(b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.5 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.2 FACILITY OPERATION CONDITIONS

(b) One (1) paint booth coating metal parts, identified as AM-08 Robotic (formerly Subaru) Paint Booth, constructed in 1989, with a maximum capacity of 28 units per hour, using dry filters to control particulate emissions, and exhausting to stack S14.

(c) One (1) paint booth coating metal parts, identified as AM-09 Robotic (formerly Top Coat) Booth, constructed in 1989, with a maximum capacity of 25 fuel tanks/hr, using a robotic spray arm, using dry filters to control particulate emissions, and exhausting to stack S15.

(d) One (1) paint booth coating metal parts, identified as AM-10 Paint (formerly Touch-up) Booth, constructed in 1989, with a maximum capacity of 25 fuel tanks/hr, using dry filters to control particulate emissions, and exhausting to stack S16.

(e) One (1) ring paint operation, approved for construction in 2007, identified as AN-33, with a maximum capacity of 1.625 gal/hr. This operation uses a mechanically applied drop of paint (for control quality) that is then brushed on the part at three different areas.

(f) One (1) paint booth coating metal parts, identified as BE-04 Robotic (formerly PSU Tank Robot) Paint Booth, constructed in 1993, with a maximum capacity of 36 fuel tanks per hour, using dry filters to control particulate emissions, and exhausting to stack S34.

(g) One (1) paint booth coating metal parts, identified as BE-05 Paint (formerly PSU Touch-up) Booth, constructed in 1993, with a maximum capacity of 36 fuel tanks per hour, using dry filters to control particulate emissions, and exhausting to stack S35.

(h) One (1) paint booth coating metal parts, identified as BE-06 Robotic (formerly PSU Tank Final) Paint Booth, constructed in 2005, with a maximum capacity of 25 fuel tanks/hour, using dry filters to control particulate emissions and exhausting to stack S42.

(i) One (1) paint booth coating metal parts, identified as Exhaust Robotic (formerly PSU Exhaust Robot) Paint Booth, constructed in 1997 and modified in 2006, with a maximum capacity of 23 mufflers per hour, using dry filters to control particulate emissions, and exhausting to stack S44.

Insignificant Activities

(b) Activities with emissions equal to or less than the following thresholds: 5 tons per year PM or PM10, 10 tons per year SO_2, NO_x, or VOC, 0.2 tons per year Pb, 1.0 tons per year of a single HAP, or 2.5 tons per year of any combination of HAPs:

(1) One (1) paint burn-off oven, constructed in 2002. [326 IAC 4-2-2]

(e) One (1) printing operation that puts an ink label on plastic airboxes, approved for construction in 2007, with a maximum ink consumption rate of 3.75 pounds per year.

(f) Two (2) natural gas fired heating units, identified as Building E Heaters, approved for construction in 2007, each rated at 0.5 MMBtu/hr, exhausting to stack SHE-01 and SHE-02.

(g) One (1) airbox injection molding process, approved for construction in 2007, molding polypropylene at a maximum rate of 90.4 pounds per hour.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Volatile Organic Compounds (VOC) Limitations [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9, for the surface coating booths identified as BE-04 Robotic Paint Booth (S34), BE-05 Paint Booth (S35), BE-06 Robotic Paint Booth (S42), and the Exhaust Robotic Paint Booth (S44), the Permittee shall not allow the discharge into the atmosphere VOC in excess of three and five-tenths (3.5) pounds of VOC per gallon of coating, excluding water, as delivered to the applicator.

D.2.2 Volatile Organic Compound (VOC) Limitations, Clean-up Requirements [326 IAC 8-2-9]

Pursuant to 326 IAC 8-2-9(f), all solvents sprayed from the application equipment of the surface coating booths identified as BE-04 Robotic Paint Booth (S34), BE-05 Paint Booth (S35), BE-06 Robotic Paint Booth (S42), and the Exhaust Robotic Paint Booth (S44) during cleanup or color changes shall be directed into containers. Said containers shall be closed as soon as the solvent spraying is complete. In addition, all waste solvent shall be disposed of in such a manner that minimizes evaporation.

D.2.3 PSD Minor Modification Limit [326 IAC 2-2]

(a) Pursuant to CP 095-7134-00048, issued on June 9, 1997, the PM emissions from the Exhaust Robotic Paint Booth (S44) shall be less than 5.70 pounds per hour. The PM-10 emissions from the Exhaust Robotic Paint Booth (S44) shall be less than 3.42 pounds per hour. These limitations are equivalent to PM emissions of less than 25 tons per year and PM-10 emissions of less than 15 tons per year for the modifications performed in 1997. Compliance with these limitations ensures that the requirements of 326 IAC 2-2 do not apply to the modification made in 1997.

(b) Pursuant to SSM 095-19454-00048, issued February 3, 2005, the PM emissions from the BE-06 Robotic Paint Booth (S42) shall be less than 5.70 pounds per hour. The PM-10 emissions from the BE-06 Robotic Paint Booth (S42) shall be less than 3.42 pounds per hour. These limitations are equivalent to PM emissions of less than 25 tons per year and PM-10 emissions of less than 15 tons per year for the modifications performed in 2005. Compliance with these limitations ensures that the requirements of 326 IAC 2-2 do not apply to the modification made in 2005.

Compliance with these limits makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable for PM and PM10 to the modifications performed in 1997 and 2005.

D.2.4 HAP Minor Limitations [40 CFR 63, Subpart MMMM] [326 IAC 2-4.1]

The amount of HAP used in the surface coating operations (AM-08 Robotic Paint Booth (S14), AM-09 Robotic Paint Booth (S15), AM-10 Paint Booth (S16), BE-04 Robotic Paint Booth (S34), BE-05 Paint Booth (S35), BE-06 Robotic Paint Booth (S42), and the Exhaust Robotic Paint Booth (S44), combined with the amount of HAP used in the open top vapor degreaser (AN-01) shall be limited to less than nine and nine-tenths (9.9) tons per twelve (12) consecutive month period for any single HAP and less than 24.4 tons per twelve (12) consecutive month period for any combination of HAPs with compliance determined at the end of each month.

These limits, combined with the HAP usage limits in Condition D.1.2 and the HAP emissions from the other emission units at this source, will limit the source-wide emissions of HAPs to less than ten (10) tons of a single HAP and less than twenty-five (25) tons of a combination of HAPs per twelve (12) consecutive month period. Compliance with these limits makes the requirements of 40 CFR 63, Subpart MMMM and 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) not applicable to this source.

D.2.5 Emission Offset Minor Limitation [326 IAC 2-3]

The amount of VOC used in the Exhaust Robotic Paint Booth (S44) shall be limited to less than forty (40.0) tons per twelve (12) consecutive month period, with compliance determined at the end of each month. Compliance with this limit makes the modifications to the Exhaust Robotic Paint Booth (S44) done in 2006 minor under Emission Offset (326 IAC 2-3).

D.2.6 Incinerators [326 IAC 4-2-2]

Pursuant to 326 IAC 4-2-2 (Incinerators), the insignificant paint burn-off oven shall comply with the following:

(a) All incinerators shall comply with the following requirements:

(1) Consist of primary and secondary chambers or the equivalent.

(2) Be equipped with a primary burner unless burning only wood products.

(3) Comply with 326 IAC 5-1 and 326 IAC 2.

(4) Be maintained, operated, and burn waste in accordance with the manufacturer's specifications or an operation and maintenance plan as specified in paragraph (c).

(5) Not emit particulate matter in excess of one (1) of the following:

(A) Three-tenths (0.3) pound of particulate matter per one thousand (1,000) pounds of dry exhaust gas under standard conditions corrected to fifty percent (50%) excess air for incinerators with a maximum solid waste capacity of greater than or equal to two hundred (200) pounds per hour.

(B) Five-tenths (0.5) pound of particulate matter per one thousand (1,000) pounds of dry exhaust gas under standard conditions corrected to fifty percent (50%) excess air for incinerators with solid waste capacity less than two hundred (200) pounds per hour.

(6) If any of the requirements of subparagraph (1) through (5) are not met, then the owner or operator shall stop charging the incinerator until adjustments are made that address the underlying cause of the deviation.

(b) An incinerator is exempt from paragraph (a)(5) if subject to a more stringent particulate matter emission limit in 40 CFR 52 Subpart P, State Implementation Plan for Indiana.

(c) An owner or operator developing an operation and maintenance plan pursuant to paragraph (a)(4) must comply with the following:

(1) The operation and maintenance plan must be designed to meet the particulate matter emission limitation specified in subsection (a)(5) and include the following:

(A) Procedures for receiving, handling, and charging waste.

(B) Procedures for incinerator startup and shutdown.

(C) Procedures for responding to a malfunction.

(D) Procedures for maintaining proper combustion air supply levels.

(E) Procedures for operating the incinerator and associated air pollution control systems.

(F) Procedures for handling ash.

(G) A list of wastes that can be burned in the incinerator.

(2) Each incinerator operator shall review the plan before initial implementation of the operation and maintenance plan and annually thereafter.

(3) The operation and maintenance plan must be readily accessible to incinerator operators.

(4) The owner or operator of the incinerator shall notify the department, in writing, thirty (30) days after the operation and maintenance plan is initially developed pursuant to this section.

(d) The owner or operator of the incinerator must make the manufacturer's specifications or the operation and maintenance plan available to the department upon request.

D.2.7 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), CP 095-7134-00048, issued June 9, 1997, and in order to comply with Condition D.2.3, particulate from the surface coating operations identified as AM-08 Robotic Paint Booth (S14), AM-09 Robotic Paint Booth (S15), AM-10 Paint Booth (S16), BE-04 Robotic Paint Booth (S34), BE-05 Paint Booth (S35), BE-06 Robotic Paint Booth (S42), and Exhaust Robotic Paint Booth (S44) shall be controlled by a dry particulate filter, and the Permittee shall operate the control devices in accordance with manufacturer's specifications.

D.2.8 Carbon Monoxide [326 IAC 9-1-2]

Pursuant to 326 IAC 9-1-2(a)(2), for the paint burn-off oven, the Permittee shall burn the waste gas stream in a direct flame afterburner or a secondary chamber.

D.2.9 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.2.10 Volatile Organic Compounds (VOC) and Hazardous Air Pollutants (HAP) [326 IAC 8-1-2] [326 IAC 8-1-4]

(a) Compliance with the VOC content limits contained in Conditions D.2.1 and D.2.5 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

(b) Compliance with the HAP usage limitations in Condition D.2.4 shall be determined by one of the following:

(1) The manufacturer's certified product data sheet.

(2) The manufacturer's material safety data sheet.

(3) Sampling and analysis, using methods outlined in 40 CFR 63.3941, Subpart MMMM.

(4) An alternate method approved by IDEM, OAQ.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.11 Monitoring

(a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks (S14, S15, S16, S34, S35, S42, and S44) while one or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

(b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emissions, or when evidence of overspray emissions is observed, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.12 Record Keeping Requirements

(a) To document compliance with Condition D.2.4, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken monthly and shall be complete and sufficient to establish compliance with the HAP usage limits established in Condition D.2.4. Records necessary to demonstrate compliance shall be available within 30 days of the end of each compliance period.

(1) The amount and HAP content of each coating material and solvent used on a monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.

(2) The total HAP usage for each month; and

(3) The weight of HAPs emitted for each compliance period.

(b) To document compliance with Conditions D.2.1 and D.2.5, the Permittee shall maintain records in accordance with (1) through (3) below for the surface coating booths identified as BE-04 Robotic Paint Booth (S34), BE-05 Paint Booth (S35), BE-06 Robotic Paint Booth (S42), and the Exhaust Robotic Paint Booth (S44). Records maintained for (1) through (3) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC content limit established in Condition D.2.1 and D.2.5.

(1) The VOC content and amount of each coating material and solvent used less water. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents; and

(2) The volume weighted VOC content of the coatings used for each month.

(3) The weight of VOC emitted for each compliance period.

(c) To document compliance with Condition D.2.11, the Permittee shall maintain a log of weekly overspray observations, and daily and monthly inspections.

(d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2.13 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.2.4 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Insignificant Activities

(a) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment cutting torches, soldering equipment, welding equipment [326 IAC 6-3-2].

(1) Eight (8) metal inert gas (MIG) welders, identified as AC31, AC36-1, AJ29, AJ28-1, AP12, AP19, AP23, and AP40, constructed in 2000, 2000, 1992, 1992, 1989, 1990, 1990, and 1990, respectively, each with a maximum wire consumption of 0.94 pounds per hour, all exhausting to stack 4.

(2) One (1) metal inert gas (MIG) welder, identified as AP32, constructed in 1990, with a maximum wire consumption of 0.94 pounds per hour, exhausting to stack SE-01.

(3) Six (6) metal inert gas (MIG) welders, identified as AE12, AE30-11, AE31, AE32, AE33, and AE34, all constructed in 1998, each with a maximum wire consumption of 0.80 pounds per hour, all exhausting to stack 5.

(4) Nine (9) metal inert gas (MIG) welders, identified as AA08-2, AA13, AF24, AF30, AF31, AF32-2, AF35, AF36, and AF37, constructed in 1998, 1993, 1998, 1992, 1992, 1998, 1995, 1993, and 1998, respectively, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack 7.

(5) Five (5) metal inert gas (MIG) welders, identified as AB313, AB31-A, AB38, AB39, and AB40, constructed in 2000, 2000, 2000, 2000, and 1992 respectively, each with a maximum wire consumption of 0.75 pounds per hour, all exhausting to stacks 6 and 8.

(6) One (1) metal inert gas (MIG) welder, identified as kaizen, constructed in 1994, with a maximum wire consumption of 0.74 pounds per hour, exhausting to stack 17.

(7) Ten (10) metal inert gas (MIG) welders, identified as AW03, AW04, AY07, AY12, AY13, AZ02, AZ03, AZ05, AZ06, and AZ08, constructed in 1994, 1994, 1995, 1994, 1994, 1994, 1995, 1992, 1994, and 1994, respectively, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack 28.

(8) Five (5) metal inert gas (MIG) welders, identified as AW01, AW02, AY02, AY03, and AY05, constructed in 1990, 1995, 1995, 1989, and 1993, respectively, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack SE-01.

(9) Fourteen (14) metal inert gas (MIG) welders, identified as AI31-2, AI33-1, AI33-2, AI33-3, AI34-1, AS24, AS26, AS30, AS31, AS33-1, AS38, AS39, AS47, and AS50, constructed in 1995, 1995, 1995, 1997, 1997, 1997, 1989, 1995, 1995, 1997, 1997, 1997, 1995, and 1997, respectively, each with a maximum wire consumption of 0.74 pounds per hour, and two (2) tungsten inert gas (TIG) welders, identified as AS55, and AS59, both constructed in 1997, both with a maximum metal consumption of 0.03 pounds per hour, and all exhausting to stack 29.

(10) Nineteen (19) metal inert gas (MIG) welders, identified as BK01, BK05, BK14, BK18, BL10, BL11, BL16, BL29-1, BL29-2, BQ22, BQ23, BS10, BS11, BS12-1, BS13, BS14, BS15, BS16-1, and BS17-1, constructed in 1996, 1996, 1996, 1996, 1996, 1992, 1996, 1992, 1992, 1999, 1999, 1999, 1999, 1995, 1996, 1996, 1996, 1996, and 1996, respectively each with a maximum wire consumption of 0.74 pounds per hour, and three (3) tungsten inert gas (TIG) welders, identified as BS17-2, BV10, and BV11, constructed in 1996, 1995, and 1993, respectively, each with a maximum metal consumption of 0.03 pounds per hour, and all exhausting to stack 33.

(11) Twenty-one (21) metal inert gas (MIG) welders, identified as AG02, AE24, AG01, AG09, AG10, AQ00, AS01, AS04-1, AY10-1, AM00, AM01, AP01, AV08, AV09, AV01, AV02, AV04, AV05, AV06, AV07, and AV07-1, constructed in 1990, 1990, 1990, 1990, 1990, 1993, 1991, 1991, 1991, 1990, 1992, 1992, 1990, 1990, 1990, 1990, 1990, 1995, 1995, 1990, and 1990, respectively, each with a maximum wire consumption of 0.75 pounds per hour, all exhausting to stack 37.

(12) One (1) metal inert gas (MIG) welder, identified as AK01, constructed in 1989, with a maximum wire consumption of 0.75 pounds per hour, exhausting to stack SE-01.

(13) Seventeen (17) metal inert gas (MIG) welders, identified as BH02, BH05, BH06, BH07, BH07-1, BH08, BH08-1, BH10, BH11, BH11-1, BH13, BH14, BH17, BH3-1, BH3-2, BU32, and BH34-1, constructed in 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1999, 1993, and 1993, respectively, each with a maximum wire consumption of 0.74 pounds per hour, and two (2) tungsten inert gas (TIG) welders, identified as BU43-1 and BU45-1, constructed in 1992 and 1995, respectively, both with a maximum metal consumption of 0.03 pounds per hour, and all exhausting to stack 38.

(14) One (1) metal inert gas (MIG) welder, identified as eng, constructed in 1995, with a maximum wire consumption of 0.74 pounds per hour, exhausting to stack 43.

(15) Seven (7) metal inert gas (MIG) welders, identified as DC1, DC2, DC3, DC4, DC5, DC6, and AG1, all constructed in 2002, each with a maximum wire consumption of 0.74 pounds per hour, all exhausting to stack 99.

(16) Twenty-one (21) metal inert gas (MIG) welders, identified as BG28A, BG28B, BG32A, BG32B, BG33A, BG33B, BG35A, BG35B, BG47A, BG47B, 2300, BG20, BG21, BG22-2, BG23, BG24, BG25, BG25-1, BG27A, BG27B, and BG27C, constructed in 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 1993, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, 2001, and 2001, respectively, each with a maximum wire consumption of 0.75 pounds per hour, all exhausting to stack 100.

(17) Four (4) Metal Inert Gas welding units, approved for construction in 2007, identified as AR-02, AR-03, AR-05, and BR-01, each with a maximum wire consumption rate of 0.045 pound per hour, and exhausting to stack SE-01.

(18) Seven (7) electrical resistance welding stations, approved for construction in 2007, and identified as AN-20, AN-21, AN-22, AN-23, AN-25, AN-27, and AN-29.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the welding operations shall not exceed 9.03 pounds per hour when operating at a process weight rate of 6,500 pounds per hour.

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$E = 4.10\ P^{0.67}$ where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY

PART 70 OPERATING PERMIT
CERTIFICATION

Source Name: ELSA, LLC.
Source Address: 1240 South State Road 37, Elwood, Indiana 46036
Mailing Address: 1240 South State Road 37, Elwood, Indiana 46036
Part 70 Permit No.: T095-16479-00048

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

☐ Annual Compliance Certification Letter

☐ Test Result (specify)

☐ Report (specify)

☐ Notification (specify)

☐ Affidavit (specify)

☐ Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
Signature:
Printed Name:
Title/Position:
Phone:
Date:

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

VOC Usage Quarterly Report

Source Name: ELSA, LLC.
Source Address: 1240 South State Road 37, Elwood, Indiana 46036
Mailing Address: 1240 South State Road 37, Elwood, Indiana 46036
Part 70 Permit No.: T095-16479-00048
Parameter: VOC Usage
Facility: Exhaust Robotic Paint Booth (S44)
Limit: Less than forty (40.0) tons per twelve (12) month consecutive period, with compliance determined at the end of each month.

QUARTER: YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

☐ No deviation occurred in this quarter.

☐ Deviation/s occurred in this quarter.
Deviation has been reported on:

Submitted by:_____
Title / Position: _____
Signature:_____
Date:_____
Phone: _____

Attach a signed certification to complete this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

HAP Usage Quarterly Report

Source Name: ELSA, LLC.
Source Address: 1240 South State Road 37, Elwood, Indiana 46036
Mailing Address: 1240 South State Road 37, Elwood, Indiana 46036
Part 70 Permit No.: T095-16479-00048
Parameter: Single HAP, Combination HAPs
Facility: Open Top Vapor Degreaser (AN-01), AM-08 Robotic Paint Booth (S14), AM-09 Robotic Paint (S15), AM-10 Paint Booth (S16), BE-04 Robotic Paint Booth (S34), BE-05 Paint Booth (S35), BE-06 Robotic Paint Booth (S42), and Exhaust Robotic Paint Booth (S44).
Limit: Less than 9.9 tons for a single HAP and less than 24.4 tons for a combination of HAPs per twelve (12) month consecutive period.

QUARTER: YEAR:

Month	Column 1		Column 2		Column 1 + Column 2	
	This Month		Previous 11 Months		12 Month Total	
	Single HAP	Comb. HAPs	Single HAP	Comb. HAPs	Single HAP	Comb. HAPs
Month 1						
Month 2						
Month 3						

☐ No deviation occurred in this quarter.

☐ Deviation/s occurred in this quarter.
Deviation has been reported on:

Submitted by:_____
Title / Position: _____
Signature:_____
Date:_____
Phone: _____

Attach a signed certification to complete this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY

COMPLIANCE AND ENFORCEMENT BRANCH
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
Phone: 317-233-0178
Fax: 317-233-6865

PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT

Source Name:	ELSA, LLC.
Source Address:	1240 South State Road 37, Elwood, Indiana 46036
Mailing Address:	1240 South State Road 37, Elwood, Indiana 46036
Part 70 Permit No.:	T095-16479-00048

This form consists of 2 pages **Page 1 of 2**

☐ This is an emergency as defined in 326 IAC 2-7-1(12)
- ☐ The Permittee must notify the Office of Air Quality (OAQ), within four (**4**) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and
- ☐ The Permittee must submit notice in writing or by facsimile within two (**2**) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A **Page 2 of 2**

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N
Type of Pollutants Emitted: TSP, PM-10, SO_2, VOC, NO_X, CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by:_____

Title / Position: _____

Date:_____

Phone: _____

A certification is not required for this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

PART 70 OPERATING PERMIT
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT

Source Name: ELSA, LLC.
Source Address: 1240 South State Road 37, Elwood, Indiana 46036
Mailing Address: 1240 South State Road 37, Elwood, Indiana 46036
Part 70 Permit No.: T095-16479-00048

Months: _____ to _____ Year: _____

This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

☐ NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

☐ THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD

Permit Requirement (specify permit condition #)	
Date of Deviation:	**Duration of Deviation:**
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	**Duration of Deviation:**
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	**Duration of Deviation:**
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	**Duration of Deviation:**
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	**Duration of Deviation:**
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed by:_____

Title / Position: _____

Date:_____

Phone: _____

Attach a signed certification to complete this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED

TO: Jeff Russell
ELSA, LLC
1240 S SR 37
Elwood, IN 46036

DATE: September 23, 2009

FROM: Matt Stuckey, Branch Chief
Permits Branch
Office of Air Quality

SUBJECT: Final Decision
Administrative Amendment
095-28469-00048

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at jbrush@idem.IN.gov.

Final Applicant Cover letter.dot 11/30/07

Mail Code 61-53

IDEM Staff	GHOTOPP 9/23/2009 ELSA, LLC. 095-28469-00048 Final			AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING
Name and address of Sender	▶	Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204	Type of Mail: **CERTIFICATE OF MAILING ONLY**	

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handing Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee Remarks
1		Jeff Russell ELSA, LLC. 1240 S SR 37 Elwood IN 46036 (Source CAATS) via confirmed delivery									
2		Madison County Commissioners 16 E. 9th Suite 104 Anderson IN 46016 *(Local Official)*									
3		Elwood City Council and Mayors Office 1505 South "B" Street Elwood IN 46036 *(Local Official)*									
4		Mr. Charles L. Berger Berger & Berger, Attorneys at Law 313 Main Street Evansville IN 47700 *(Affected Party)*									
5		Madison County Health Department 206 E 9th St Anderson IN 46016-1512 *(Health Department)*									
6		Alexandria Town Council 125 N. Wayne St. Alexandria IN 46001 *(Local Official)*									
7		Mr. Gary McKinney Anderson Brownfields Coordinator 120 E. 8th St. Anderson IN 46016 *(Local Official)*									
8											
9											
10											
11											
12											
13											
14											
15											

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is $50,000 per piece subject to a limit of $50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is $500. The maximum indemnity payable is $25,000 for registered mail, sent with optional postal insurance. See ***Domestic Mail Manual*** **R900, S913**, and **S921** for limitations of coverage on inured and COD mail. See ***International Mail Manual*** for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
6			

FACSIMILIE OF PS Form 3877