



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: June 8, 2010

RE: Cimbar Performance Minerals MV, LLC / 129 - 29181 - 00023

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision – Approval

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to 326 IAC 2, this approval was effective immediately upon submittal of the application.

If you wish to challenge this decision, IC 4-21.5-3-7 requires that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days from the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER-AM.dot12/3/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Brett Cline
Cimbar Performance Minerals MV, LLC
2700 Bluff Rd.
Mt. Vernon, IN 47620

June 8, 2010

Re: 129-29181-00023
Fourth Notice-Only Change to
M129-22660-00023

Dear Mr. Cline:

Cimbar Performance Minerals MV, LLC, formerly Barrett's Minerals, Inc., was issued a Minor Source Operating Permit (MSOP) Renewal No. M129-22660-00023 on November 28, 2007, for a stationary talc, barite and calcium carbonate processing plant located at 2700 Bluff Rd., Mt. Vernon, IN 47620. On April 19, 2010, the Office of Air Quality (OAQ) received an application from the source relating to the construction and operation of a new air jet milling system, consisting of mills # 5 & 6. The potential emissions of regulated criteria pollutants and hazardous air pollutants from the new air jet milling system (AU), consisting of mills # 5 & 6, illustrated in Appendix A, are less than the ranges specified 326 IAC 2-6.1-6(g)(4) and 326 IAC 2-6.1-6(d)(10), respectively, and the new air jet milling system is of the same type and will comply with the same applicable requirements and permit terms and conditions as existing air mills AP, AU and AX. The addition of this/these unit(s) will not cause the source's potential to emit to be greater than the threshold levels specified in 326 IAC 2-2 or 326 IAC 2-3, and the uncontrolled/unlimited potential to emit of the entire source will continue to be less than the threshold levels specified in 326 IAC 2-7. Therefore, the addition of the new air jet milling system, consisting of mills # 5 & 6, to the permit is considered a notice-only change pursuant to 326 IAC 2-6.1-6(d)(13).

"Integral Part of the Process" Determination

With this application, the Permittee has submitted the following information to justify why the baghouse (BJ) should be considered an integral part of the new air jet milling system's talc processing operations:

The control equipment serves a primary purpose other than pollution control.

The primary purpose of baghouse (BJ) is not to control air pollution. Baghouse (BJ) is used to pneumatically collect and separate resized talc material from the new air jet milling system's talc processing operations. This equipment would have been installed even if the air quality regulation were not in place, because it is used as an air separator, specifically to collect product (i.e., the talc). The product being manufactured could not be produced without the operation of the baghouse.

IDEM, OAQ has evaluated the information submitted by the Permittee, and agrees that baghouse (BJ) should be considered an integral part of the new air jet milling system, identified as BJ. This determination is based on the fact that the unit is specifically used to collect and separate the product, talc, from the air stream, for packaging and sale. Therefore, the permitting level will be determined using the potential to emit after the baghouse (BJ). Operating conditions in the proposed permit will specify that this baghouse (BJ) shall operate at all times when the new air jet milling system is in operation.

This determination is similar to the initial determination made for the twin air mill (AU) baghouse, under MSOP SPR 129-17710-00023, issued on March 23, 2004, and re-evaluated under MSOP Renewal 129-22660-00023, issued November 28, 2007.

Pursuant to the provisions of 326 IAC 2-6.1-6, the permit is hereby revised as follows with the deleted language as ~~strikeouts~~ and new language **bolded**.

A.2 Emission Units and Pollution Control Equipment Summary

This stationary source consists of the following emission units and pollution control devices:

- (t) **One (1) twin air jet milling system, identified as BJ, consisting of mills # 5 & 6, approved for construction in 2010, for dry material size reduction of talc products, with a maximum throughput capacity of two (2.0) tons of talc per hour, connected pneumatically to one (1) integral baghouse, identified as BJ, for product reclamation, and exhausting outside the building through Stack BJ. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.**

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description: (continued)

- (t) **One (1) twin air jet milling system, identified as BJ, consisting of mills # 5 & 6, approved for construction in 2010, for dry material size reduction of talc products, with a maximum throughput capacity of two (2.0) tons of talc per hour, connected pneumatically to one (1) integral baghouse, identified as BJ, for product reclamation, and exhausting outside the building through Stack BJ. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.**

D.1.1 PSD PM Minor Limits [326 IAC 2-2]

Particulate matter (PM) from facilities listed in the following table shall not exceed the pound per hour emission rates:

Facility Description	Baghouse Identification	Limited PM Emission Rate (lbs/hr)
Twin air jet milling system	BJ	0.439

D.1.4 Particulate Control

- (a) In order to comply with Conditions D.1.1 and D.1.2, the baghouses, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through ~~BI~~**BJ** for particulate control shall be in operation and control emissions from the talc, barite and calcium carbonate processing facilities at all times that these facilities are in operation.

D.1.6 Visible Emissions Notations

- (a) Visible emission notations of the talc, barite and calcium carbonate processing stack exhausts, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through ~~BI~~**BJ**, shall be performed once per day during normal daylight operations. A trained employee shall record whether emissions are normal or abnormal.

D.1.7 Baghouse Parametric Monitoring

- (a) The Permittee shall record the pressure drop across the baghouses, identified as B through Z, AA through AC, AG through AM, AY, BA through BD and BF through ~~B~~**BJ**, used in conjunction with the talc, barite and calcium carbonate processing facilities at least once per day when these facilities are in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 3.0 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances, shall be considered a deviation from this permit.

D.1.9 Record Keeping Requirements

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain a daily record of visible emission notations of the talc, barite and calcium carbonate processing baghouse stack exhausts, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through ~~B~~**BJ**. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g., the roller miller exhausted to Stack D did not operate that day).
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain a daily record of the pressure drop across the baghouses, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through ~~B~~**BJ**, controlling talc, barite and calcium carbonate processing facilities. The Permittee shall include in its daily record when a pressure drop reading is not taken and the reason for the lack of a pressure drop reading, (e.g., the roller miller did not operate that day).

SECTION E.1

EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description: (continued)

- (t) **One (1) twin air jet milling system, identified as BJ, consisting of mills # 5 & 6, approved for construction in 2010, for dry material size reduction of talc products, with a maximum throughput capacity of two (2.0) tons of talc per hour, connected pneumatically to one (1) integral baghouse, identified as BJ, for product reclamation, and exhausting outside the building through Stack BJ. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.**

Furthermore, IDEM, OAQ has decided to make additional revisions to the permit as described below. The permit has been revised with deleted language as ~~strikeouts~~ and new language **bolded**, as follows:

1. IDEM, OAQ has decided to remove all references to the source mailing address. IDEM, OAQ will continue to maintain records of the mailing address.
2. For clarity, IDEM, OAQ has changed references to the general conditions: "in accordance with Section B", "in accordance with Section C", or other similar language, to "Section C ... contains the Permittee's obligations with regard to the records required by this condition."
3. IDEM, OAQ has decided that the phrases "no later than" and "not later than" are clearer than "within" in relation to the end of a timeline. Therefore all timelines have been switched to "no later than" or "not later than".

4. IDEM, OAQ has determined that rather than having a Certification condition and various references throughout the permit as to whether a particular report, notice, or correspondence needs to include a certification, the specific conditions that require an affirmation of truth and completeness shall state so. The certification condition has been removed. All statements to whether a certification, pursuant to the former Section B - Certification, is needed or not, have been removed. Section B - Credible Evidence and Section C - Asbestos Abatement Projects still require certification as the underlying rules also require certifications.
5. IDEM, OAQ has added a new paragraph (b) to Section B - Preventive Maintenance Plan, to handle a future situation where the Permittee adds units that need preventive maintenance plans developed. IDEM, OAQ has decided to clarify other aspects of Section B - Preventive Maintenance Plan.
6. Paragraph (d) of Section C - General Reporting Requirements has been removed because IDEM already states the timeline and certification needs of each report in the condition requiring the report.
7. The Air Board adopted LSA Document #07-202, effective June 6, 2008, that changed a MSOP renewal application due date to one hundred twenty (120) prior to expiration of the current permit.
8. IDEM, OAQ has decided to state which rule establishes the authority to set a deadline for the Permittee to submit additional information. Therefore, Section B - Permit Renewal has been revised.
9. IDEM has decided to reference 326 IAC 2 in Section B-Source Modification Requirements, rather than the specific construction rule.
10. IDEM, OAQ has added 326 IAC 5-1-1 to the exception clause of Section C - Opacity, since 326 IAC 5-1-1 does list exceptions.
11. IDEM, OAQ has revised Section C - Incineration to more closely reflect the two underlying rules.
12. IDEM has decided not to list the submission date of the Fugitive Dust Plan required by Section C - Fugitive Particulate Matter Emission Limitations, because the plan has been included with the permit and requires permit action to change the plan.
13. IDEM, OAQ has removed the first paragraph of Section C - Performance Testing due to the fact that specific testing conditions elsewhere in the permit will specify the timeline and procedures.
14. IDEM, OAQ has removed Section C - Monitoring Methods. The conditions that require the monitoring or testing, if required state what methods shall be used.
15. IDEM has decided to include a general condition titled Response to Excursions and Exceedances. The Permittee will be required to take reasonable response steps when a compliance monitoring parameter is determined to be out of range or abnormal.
16. IDEM, OAQ has revised Section C - Response to Excursions or Exceedances. The introduction sentence has been added to clarify that it is only when an excursion or exceedance is detected that the requirements of this condition need to be followed. The word "excess" was added to the last sentence of paragraph (a) because the Permittee only has to minimize excess emissions. The middle of paragraph (b) has been deleted as it was duplicative of paragraph (a). The phrase "or are returning" was added to subparagraph (b)(2) as this is an acceptable response assuming the operation or emission unit does return to

normal or its usual manner of operation. The phrase "within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable" was replaced with "normal or usual manner of operation" because the first phrase is just a limited list of the second phrase. The recordkeeping required by paragraph (e) was changed to require only records of the response because the previously listed items are required to be recorded elsewhere in the permit.

17. IDEM, OAQ has revised Section C - Actions Related to Noncompliance Demonstrated by a Stack Test. The requirements to take response steps and minimize excess emissions have been removed because Section C - Response to Excursions or Exceedances already requires response steps related to exceedances and excess emissions minimization. The start of the timelines was switched from "the receipt of the test results" to "the date of the test". There was confusion if the "receipt" was by IDEM, OAQ, the Permittee, or someone else. Since the start of the timelines has been moved up, the length of the timelines was increased. The new timelines require action within a comparable timeline; and the new timelines still ensure that the Permittee will return to compliance within a reasonable timeframe.
18. Paragraph (b) of Section C - Emission Statement has been removed. It was duplicative of the requirement in Section C - General Reporting Requirements.
19. The voice of paragraph (b) of Section C - General Record Keeping Requirements has been changed to clearly indicate that it is the Permittee that must follow the requirements of the paragraph.
20. IDEM, OAQ has decided to clarify Section D - Testing Requirements.
21. IDEM has decided not to list the due date of the next performance test. IDEM will just list the frequency of the testing since the last valid test. This is not a change to the nature or frequency of the requirement since the date listed was based on the frequency listed.
22. The word "status" has been added to Section D - Record Keeping Requirements and Section D - Reporting Requirements. The Permittee has the obligation to document the compliance status. The wording has been revised to properly reflect this.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary talc, barite and calcium carbonate processing source.

Mailing Address: _____ 2700 Bluff Road, Mt. Vernon, Indiana 47620

SECTION B _____ GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-1.1-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-1.1-1) shall prevail.

B.2 Permit Term [326 IAC 2-6.1-7(a)] [326 IAC 2-1.1-9.5] [IC 13-15-3-6(a)]

(a) This permit, MSOP 129-22660-00023, is issued for a fixed term of ten (10) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.

- (b) ~~If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, until the renewal permit has been issued or denied.~~

B.3 ~~Term of Conditions [326 IAC 2-1.1-9.5]~~

~~Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:~~

- (a) ~~the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or~~
- (b) ~~the emission unit to which the condition pertains permanently ceases operation.~~

B.4 ~~Enforceability~~

~~Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.~~

B.5 ~~Severability~~

~~The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.~~

B.6 ~~Property Rights or Exclusive Privilege~~

~~This permit does not convey any property rights of any sort or any exclusive privilege.~~

B.7 ~~Duty to Provide Information~~

- (a) ~~The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.~~
- (b) ~~For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U.S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.~~

B.8 ~~Certification~~

- (a) ~~Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an "authorized individual" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.~~
- (b) ~~One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.~~
- (c) ~~An "authorized individual" is defined at 326 IAC 2-1.1-1(1).~~

B.9 ~~Annual Notification [326 IAC 2-6.1-5(a)(5)]~~

- (a) ~~An annual notification shall be submitted by an authorized individual to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.~~

- ~~(b) The annual notice shall be submitted in the format attached no later than March 1 of each year to:~~

~~Compliance and Enforcement Branch, Office of Air Quality
Indiana Department of Environmental Management
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251~~

- ~~(c) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.~~

~~B.10 Preventive Maintenance Plan [326 IAC 1-6-3]~~

- ~~(a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:~~

- ~~(1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;~~
~~(2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and~~
~~(3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.~~

- ~~(b) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMPs do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).~~

- ~~(c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.~~

~~B.11 Prior Permits Superseded [326 IAC 2-1.1-9.5]~~

- ~~(a) All terms and conditions of permits established prior to MSOP 129-22660-00023 and issued pursuant to permitting programs approved into the state implementation plan have been either:~~

- ~~(1) incorporated as originally stated,~~
~~(2) revised, or~~
~~(3) deleted.~~

- ~~(b) All previous registrations and permits are superseded by this permit.~~

~~B.12 Termination of Right to Operate [326 IAC 2-6.1-7(a)]~~

~~The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least ninety (90) days prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-6.1-7.~~

B.13 — Permit Renewal [326 IAC 2-6.1-7]

- (a) ~~The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-6.1-7. Such information shall be included in the application for each emission unit at this source. The renewal application does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).~~

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) ~~A timely renewal application is one that is:~~
- (1) ~~Submitted at least ninety (90) days prior to the date of the expiration of this permit; and~~
- (2) ~~If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.~~
- (c) ~~If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-6.1 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.~~

B.14 — Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

- (a) ~~Permit amendments and revisions are governed by the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.~~

- (b) ~~Any application requesting an amendment or modification of this permit shall be submitted to:~~

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

~~Any such application shall be certified by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).~~

- (c) ~~The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]~~

B.15 — Source Modification Requirement

~~A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.~~

B.16 — Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)] [IC 13-14-2-2] [IC 13-17-3-2] [IC 13-30-3-1]

~~Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert~~

~~that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:~~

- ~~(a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;~~
- ~~(b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;~~
- ~~(c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;~~
- ~~(d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and~~
- ~~(e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.~~

~~B.17 Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]~~

- ~~(a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.~~
- ~~(b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:~~

~~Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53-IGCN 1003
Indianapolis, Indiana 46204-2251~~

~~The application which shall be submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).~~

- ~~(c) The Permittee may implement notice only changes addressed in the request for a notice only change immediately upon submittal of the request. [326 IAC 2-6.1-6(d)(3)]~~

~~B.18 Annual Fee Payment [326 IAC 2-1.1-7]~~

- ~~(a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.~~
- ~~(b) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.~~

~~B.19 Credible Evidence [326 IAC 1-1-6]~~

~~For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the~~

~~use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.~~

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-1.1-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-1.1-1) shall prevail.

B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]

- (a) This permit, M129-22660-00023, is issued for a fixed term of ten (10) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.

- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) An annual notification shall be submitted by an authorized individual to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) The annual notice shall be submitted in the format attached no later than March 1 of each year to:
- Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (c) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

B.9 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) A Preventive Maintenance Plan meets the requirements of 326 IAC 1-6-3 if it includes, at a minimum:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

The Permittee shall implement the PMPs.

- (b) If required by specific condition(s) in Section D of this permit where no PMP was previously required, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) no later than ninety (90) days after issuance of this permit or ninety (90) days after initial start-up, whichever is later, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The Permittee shall implement the PMPs.

- (c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions.
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.10 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of permits established prior to M129-22660-00023 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted.
- (b) All previous registrations and permits are superseded by this permit.

B.11 Termination of Right to Operate [326 IAC 2-6.1-7(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least one hundred twenty (120) days prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-6.1-7.

B.12 Permit Renewal [326 IAC 2-6.1-7]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-6.1-7. Such information shall be included in the application for each emission unit at this source. The renewal application does require an affirmation that the statements in the application are true and complete by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

**Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251**

- (b) A timely renewal application is one that is:
- (1) Submitted at least one hundred twenty (120) days prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-6.1 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified, pursuant to 326 IAC 2-6.1-4(b), in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.13 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

**Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251**

- (c) The Permittee shall notify the OAQ no later than thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

B.14 Source Modification Requirement

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

B.15 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2][IC 13-17-3-2][IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;

- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.16 Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]

- (a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require an affirmation that the statements in the application are true and complete by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement notice-only changes addressed in the request for a notice-only change immediately upon submittal of the request. [326 IAC 2-6.1-6(d)(3)]

B.17 Annual Fee Payment [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees due no later than thirty (30) calendar days of receipt of a bill from IDEM, OAQ.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.18 Credible Evidence [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-6-1-5(a)(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than one hundred (100) pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed five hundred fifty-one thousandths (0.551) pounds per hour.

C.2 Permit Revocation [326 IAC 2-1-1-9]

Pursuant to 326 IAC 2-1-1-9 (Revocation of Permits), this permit to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

~~C.6 Fugitive Dust Emissions [326 IAC 6-4]~~

~~The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).~~

~~C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]~~

~~Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the plan submitted on September 24, 2007. The plan requires that all dump trucks shall be tarped when transporting raw ore material into the source and that water shall be applied to outside storage piles on an as-needed basis.~~

~~C.8 Stack Height [326 IAC 1-7]~~

~~The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.~~

~~C.9 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]~~

~~(a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos-containing material (RACM) to be stripped, removed or disturbed is at least two hundred sixty (260) linear feet on pipes or one hundred sixty (160) square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.~~

~~(b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:~~

~~(1) When the amount of affected asbestos-containing material increases or decreases by at least twenty percent (20%); or~~

~~(2) If there is a change in the following:~~

~~(A) Asbestos removal or demolition start date;~~

~~(B) Removal or demolition contractor; or~~

~~(C) Waste disposal site.~~

~~(c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).~~

~~(d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).~~

All required notifications shall be submitted to:
Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) ~~Procedures for Asbestos Emission Control~~
~~The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(e). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least seventy-five hundredths (0.75) cubic feet on all facility components.~~
- (f) ~~Demolition and Renovation~~
~~The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).~~
- (g) ~~Indiana Accredited Asbestos Inspector~~
~~The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.~~

~~Testing Requirements [326 IAC 2-6.1-5(a)(2)]~~

~~C.10 Performance Testing [326 IAC 3-6]~~

- (a) ~~All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.~~

~~A test protocol, except as provided elsewhere in this permit, shall be submitted to:~~

~~Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251~~

~~no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).~~

- (b) ~~The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).~~
- (c) ~~Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.~~

~~Compliance Requirements [326 IAC 2-1.1-11]~~

~~C.11 Compliance Requirements [326 IAC 2-1.1-11]~~

~~The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.~~

Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]

C.12 Compliance Monitoring [326 IAC 2-1.1-11]

~~Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.~~

C.13 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

~~Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.~~

C.14 Instrument Specifications [326 IAC 2-1.1-11]

- ~~(a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.~~
- ~~(b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.~~

Corrective Actions and Response Steps

C.15 Response to Excursions or Exceedances

- ~~(a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.~~
- ~~(b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
 - ~~(1) initial inspection and evaluation~~
 - ~~(2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or~~
 - ~~(3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.~~~~
- ~~(c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - ~~(1) monitoring results;~~
 - ~~(2) review of operation and maintenance procedures and records;~~
 - ~~(3) inspection of the control device, associated capture system, and the process.~~~~

- (d) ~~Failure to take reasonable response steps shall be considered a deviation from the permit.~~
- (e) ~~The Permittee shall maintain the following records:~~
 - (1) ~~monitoring data;~~
 - (2) ~~monitor performance data, if applicable; and~~
 - (3) ~~corrective actions taken.~~

C.16 ~~Actions Related to Noncompliance Demonstrated by a Stack Test~~

- (a) ~~When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.~~
- (b) ~~A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.~~
- (c) ~~IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.~~

~~The response action documents submitted pursuant to this condition do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).~~

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

C.17 ~~Malfunctions Report [326 IAC 1-6-2]~~

~~Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):~~

- (a) ~~A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.~~
- (b) ~~When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.~~
- (c) ~~Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).~~
- (d) ~~Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]~~

C.18 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.19 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53-IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation of Permits), this permit to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.

- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-1 (Applicability) and 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator except as provided in 326 IAC 4-2 or in this permit. The Permittee shall not operate a refuse incinerator or refuse burning equipment except as provided in 326 IAC 9-1-2 or in this permit.

C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]

Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the attached plan as in Attachment A.

C.8 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

C.9 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed

is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project.

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).

- (g) **Indiana Licensed Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Licensed Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-6.1-5(a)(2)]

C.10 Performance Testing [326 IAC 3-6]

- (a) For performance testing required by this permit, a test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date.

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date.
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.11 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]

C.12 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.13 Instrument Specifications [326 IAC 2-1.1-11]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that

an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps

C.14 Response to Excursions or Exceedances

Upon detecting an excursion where a response step is required by the D Section or an exceedance of a limitation in this permit:

- (a) The Permittee shall take reasonable response steps to restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing excess emissions.**
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction. The response may include, but is not limited to, the following:**
 - (1) initial inspection and evaluation;**
 - (2) recording that operations returned or are returning to normal without operator action (such as through response by a computerized distribution control system); or**
 - (3) any necessary follow-up actions to return operation to normal or usual manner of operation.**
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:**
 - (1) monitoring results;**
 - (2) review of operation and maintenance procedures and records; and/or**
 - (3) inspection of the control device, associated capture system, and the process.**
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.**
- (e) The Permittee shall record the reasonable response steps taken.**

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall submit a description of its response actions to IDEM, OAQ, no later than seventy-five (75) days after the date of the test.**
- (b) A retest to demonstrate compliance shall be performed no later than one hundred eighty (180) days after the date of the test. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred eighty (180) days is not practicable, IDEM, OAQ may extend the retesting deadline**
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.**

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

C.16 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.17 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, for all record keeping requirements not already legally required, the Permittee shall be allowed up to ninety (90) days from the date of permit issuance or the date of initial start-up, whichever is later, to begin such record keeping.

C.18 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping

receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

- (c) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

D.1.3 Preventive Maintenance Plan [326 IAC 1-6-3]

~~A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for all facilities, except the crusher system, and their baghouse control devices.~~
Section B - Preventive Maintenance Plan contains the Permittee's obligation with regard to the preventive maintenance plan required by this condition.

D.1.5 Testing Requirements [326 IAC 2-1.1-11]

- (a) ~~Within~~**Not later than** one hundred eighty (180) days of issuance of this MSOP Renewal, 129-22660-00023, in order to demonstrate compliance with Condition E.1.2, the Permittee shall perform PM testing of the following facilities:

utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the **most recent** last valid compliance demonstration. Testing shall be conducted in accordance with **the provisions of 326 IAC 3-6 (Source Sampling Procedures)**. Section C - Performance Testing contains the **Permittee's obligation with regard to the performance testing required by this condition.**

- (b) ~~By April 23, 2008~~ In order to demonstrate compliance with Condition E.1.2, **no later than five (5) years from the most recent valid compliance demonstration**, the Permittee shall perform PM and opacity testing of one (1) of the two (2) silos, identified as North and South, connected pneumatically to baghouses, identified as B and C, exhausted to Stacks B and C, ~~the~~ utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the **most recent** last valid compliance demonstration. Testing shall be conducted in accordance with **the provisions of 326 IAC 3-6 (Source Sampling Procedures)**. Section C - Performance Testing contains the **Permittee's obligation with regard to the performance testing required by this condition.**
- (c) ~~By April 23, 2008~~ In order to demonstrate compliance with Condition E.1.2, **no later than five (5) years from the most recent valid compliance demonstration**, the Permittee shall perform PM and opacity testing of one (1) of the eleven (11) silos, identified as Silos #1 through #11, connected pneumatically to baghouses, identified as N through X, exhausted to Stacks N through X, respectively, ~~the~~ utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the **most recent** last valid compliance demonstration. Testing shall be conducted in accordance with **the provisions of 326 IAC 3-6 (Source Sampling Procedures)**. Section C - Performance Testing contains the **Permittee's obligation with regard to the performance testing required by this condition.**
- (d) ~~By April 23, 2008~~ In order to demonstrate compliance with Conditions E.1.2 and E.2.2, **no later than five (5) years from the most recent valid compliance demonstration**, the Permittee shall perform PM and opacity testing of the pellet mill and natural gas-fired dryer, identified as Pellet Mill, connected pneumatically to a baghouse, identified as AY, exhausted to Stack AY, ~~the~~ utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the **most recent** last valid

compliance demonstration. Testing shall be conducted in accordance with **the provisions of 326 IAC 3-6 (Source Sampling Procedures)**. Section C - Performance Testing **contains the Permittee's obligation with regard to the performance testing required by this condition.**

- (e) ~~By May 15, 2010~~ In order to demonstrate compliance with Condition E.1.2, **no later than five (5) years from the most recent valid compliance demonstration**, the Permittee shall perform PM and opacity testing of the classifier #3, connected pneumatically to a baghouse, identified as AC, exhausted to Stack AC, ~~the~~ utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the last **most recent** last compliance demonstration. Testing shall be conducted in accordance with **the provisions of 326 IAC 3-6 (Source Sampling Procedures)**. Section C - Performance Testing **contains the Permittee's obligation with regard to the performance testing required by this condition.**
- (f) ~~By March 2, 2011~~ In order to demonstrate compliance with Condition E.1.2, **no later than five (5) years from the most recent valid compliance demonstration**, the Permittee shall perform PM and opacity testing of either the single air mill (powder), connected pneumatically to a baghouse, identified as AP, exhausted to Stack AP, or the #3 air mill, connected pneumatically to a baghouse, identified as AX, exhausted to Stack AX, ~~the~~ utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the **most recent** last valid compliance demonstration. Testing shall be conducted in accordance with **the provisions of 326 IAC 3-6 (Source Sampling Procedures)**. Section C - Performance Testing **contains the Permittee's obligation with regard to the performance testing required by this condition.**

D.1.6 Visible Emissions Notations

- (e) If abnormal emissions are observed, the Permittee shall take reasonable response. ~~steps in accordance with Section C- Response to Excursions or Exceedances~~ **contains the Permittee's obligation with regard to the reasonable response steps required by this condition.** Failure to take response steps ~~in accordance with Section C- Response to Excursions or Exceedances~~ shall be considered a deviation from this permit.

D.1.7 Baghouse Parametric Monitoring

- (a) The Permittee shall record the pressure drop across the baghouses, identified as B through Z, AA through AC, AG through AM, AY, BA through BD and BF through BJ, used in conjunction with the talc, barite and calcium carbonate processing facilities at least once per day when these facilities are in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 3.0 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response. ~~in accordance with Section C- Response to Excursions or Exceedances~~ **contains the Permittee's obligation with regard to the reasonable response steps required by this condition.** A pressure reading that is outside the above-mentioned range is not a deviation from this permit. Failure to take response steps ~~in accordance with Section C- Response to Excursions or Exceedances,~~ shall be considered a deviation from this permit.
- (b) The Permittee shall record the pressure drop across the baghouses, identified as AO, AP and AS through AX, used in conjunction with the talc, barite and calcium carbonate processing facilities at least once per day when these facilities are in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 3.0 and 5.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response. ~~in accordance with Section C- Response to Excursions or Exceedances~~ **contains the Permittee's obligation with regard to the reasonable**

response steps required by this condition. A pressure reading that is outside the above-mentioned range is not a deviation from this permit. Failure to take response steps in accordance with ~~Section C - Response to Excursions or Exceedances~~, shall be considered a deviation from this permit.

D.1.9 Record Keeping Requirements

- (a) To document **the compliance status** with Condition D.1.6, the Permittee shall maintain a daily record of visible emission notations of the talc, barite and calcium carbonate processing baghouse stack exhausts, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through BJ. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g., the roller miller exhausted to Stack D did not operate that day).
- (b) To document **the compliance status** with Condition D.1.7, the Permittee shall maintain a daily record of the pressure drop across the baghouses, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through BJ, controlling talc, barite and calcium carbonate processing facilities. The Permittee shall include in its daily record when a pressure drop reading is not taken and the reason for the lack of a pressure drop reading, (e.g., the roller miller did not operate that day).
- (c) ~~All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit~~ **contains the Permittee's obligations with regard to the records required by this condition.**

Intentionally left blank..... continued on next page.....

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY**

**MINOR SOURCE OPERATING PERMIT
CERTIFICATION**

Source Name: Cimbar Performance Minerals MV, LLC
Source Address: 2700 Bluff Road, Mt. Vernon, Indiana 47620
Mailing Address: 2700 Bluff Road, Mt. Vernon, Indiana 47620
Permit No.: MSOP 129-22660-00023

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

_____ Please check what document is being certified:

Annual Compliance Certification Letter

Test Result (specify) _____

Report (specify) _____

Notification (specify) _____

Affidavit (specify) _____

Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature: _____

Printed Name: _____

Title/Position: _____

Phone: _____

Date: _____

Intentionally left blank..... continued on next page.....

All other conditions of the permit shall remain unchanged and in effect. Attached please find the entire revised permit. A copy of the permit is available on the Internet at: <http://www.in.gov/ai/appfiles/idem-caats/>. For additional information about air permits and how the public and interested parties can participate, refer to the IDEM's Guide for Citizen Participation and Permit Guide on the Internet at: www.idem.in.gov

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Ms. Hannah Desrosiers, of my staff, at 317-234-5374 or 1-800-451-6027, and ask for extension 4-5374.

Sincerely,



Iryn Callung, Section Chief
Permits Branch
Office of Air Quality

Attachments: Appendix A - Emissions Calculations, Updated Permit, Attachment A - Fugitive Dust Plan.

IC/hld

cc: File - Posey County
Posey County Health Department
U.S. EPA, Region V
Compliance and Enforcement Branch
Billing, Licensing and Training Section

Appendix A: Emissions Calculations
Summary of Emissions from the Entire Source after the Revision

Company Name: Cimbar Performance Minerals MV, LLC
 Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
 MSOP Renewal: 129-22660-00023
 Revision No: 129-29181-00023
 Reviewer: Hannah L. Desrosiers
 Date Received: April 19, 2010

Integral and Uncontrolled Potential Emissions									
	PM (tons/yr)	PM-10 (tons/yr)	PM-2.5 (tons/yr)	SO2 (tons/yr)	NOx (tons/yr)	VOC (tons/yr)	CO (tons/yr)	Lead (tons/yr)	HAPs (tons/yr)
<i>Existing Units (from Permit No.: 129-28690-00023)</i>									
All Integral Control Units From Page 2	67.2	67.2	67.2	0	0	0	0	0	0
Nat. Gas Comb.	0.050	0.200	0.150	0.016	2.63	0.145	2.21	0.04960	0.050
Crusher System	0.153	0.153	0.153	0	0	0	0	0	0
Paved Roads	10.4	2.02	2.02	0	0	0	0	0	0
Loading & Unload	0.354	0.354	0.354	0	0	0	0	0	0
Subtotal	78.1	69.9	69.9	0.016	2.63	0.145	2.21	0.0496	0.050
<i>NEW Units</i>									
Twin Air Jet Mills #5 & #6 (BJ)	1.925	1.925	1.925	0	0	0	0	0	0
Total	80.0	71.8	71.8	0.016	2.63	0.145	2.21	0.0496	0.050

Limited and Controlled Potential Emissions									
	PM (tons/yr)	PM-10 (tons/yr)	PM-2.5 (tons/yr)	SO2 (tons/yr)	NOx (tons/yr)	VOC (tons/yr)	CO (tons/yr)	Lead (tons/yr)	HAPs (tons/yr)
<i>Existing Units (from Permit No.: 129-28690-00023)</i>									
All Integral Control Units subject to NSPS OOO/UUU	55.6	55.6	55.6	0	0	0	0	0	0
Roller Mill	4.05	4.05	4.05	0	0	0	0	0	0
Impact Mill	4.05	4.05	4.05	0	0	0	0	0	0
#1 Bepex	0.912	0.912	0.912	0	0	0	0	0	0
Ball Mill	2.61	2.61	2.61	0	0	0	0	0	0
Nat. Gas Comb.	0.050	0.200	0.150	0.016	2.628	0.145	2.208	0.0496	0.050
Crusher System	0.153	0.153	0.153	0	0	0	0	0	0
Paved Roads	10.4	2.02	2.02	0	0	0	0	0	0
Loading & Unload	0.354	0.354	0.354	0	0	0	0	0	0
Subtotal	78.1	69.9	69.9	0.016	2.63	0.145	2.21	0.0496	0.050
<i>NEW Units</i>									
Twin Air Jet Mills #5 & #6 (BJ)	1.925	1.925	1.925	0	0	0	0	0	0
Total	80.0	71.8	71.8	0.016	2.63	0.145	2.21	0.0496	0.050

Appendix A: Emission Calculations
Particulate Emissions from the New Talc Processing Unit

Company Name: Cimbar Performance Minerals MV, LLC
Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
MSOP Renewal: 129-22660-00023
Revision No: 129-29181-00023
Reviewer: Hannah L. Desrosiers
Date: April 19, 2010

Limited/Controlled Emissions								
Facility Description	Baghouse ID	Control Efficiency (%)	Allowable Loading per Dry Cubic meter of Outlet Air (grams/cubic meter)	Gas or Air Flow Rate (acfm.)	Exhaust Temp. (F)	Average Moisture Content	PM* Emission Rate after Controls (lbs/hr)	PM* Emission Rate after Controls (tons/yr)
Twin Air Jet Mills #5 & #6 (BJ)	BJ	99.9%	0.05	3,600.0	350.0	0.5%	0.439	1.925
Total							0.439	1.925

Methodology

Emission Rate in lbs/hr (after controls) = (grams x (1pound/453.5924 grams)/cubic meter x (1 cubic ft/0.02832 cubic meters) x (acfm) x 528/(460 + Temp (°F)) x (100 - Moisture %)/100 x (60 mi
Emission Rate in tons/yr = (lbs/hr) (8760 hr/yr) (ton/2000 lb)

NOTES

Potential emissions for particulate matter (PTE) were calculated after consideration of the controls. (See page 1 and 2 of 30, of the letter for further clarification)

*PM-10 and PM-2.5 emissions have been assumed equal to PM emissions

Appendix A: Emissions Calculations
Summary of Emissions from the Existing Emission Units

Company Name: Cimbar Performance Minerals MV, LLC
Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
MSOP Renewal: 129-22660-00023
Revision No: 129-29181-00023
Reviewer: Hannah L. Desrosiers
Date: April 19, 2010

Integral and Uncontrolled Potential Emissions									
	PM (tons/yr)	PM-10 (tons/yr)	PM-2.5 (tons/yr)	SO₂ (tons/yr)	NO_x (tons/yr)	VOC (tons/yr)	CO (tons/yr)	Lead (tons/yr)	HAPs (tons/yr)
All Integral Control Units From Page 2	67.2	67.2	67.2	0	0	0	0	0	0
Nat. Gas Comb.	0.050	0.200	0.150	0.016	2.63	0.145	2.21	0.0496	0.050
Crusher System	0.153	0.153	0.153	0	0	0	0	0	0
Paved Roads	10.4	2.02	2.02	0	0	0	0	0	0
Loading & Unload	0.354	0.354	0.354	0	0	0	0	0	0
Total	78.1	69.9	69.9	0.016	2.63	0.145	2.21	0.050	0.050

Limited and Controlled Potential Emissions									
	PM (tons/yr)	PM-10 (tons/yr)	PM-2.5 (tons/yr)	SO₂ (tons/yr)	NO_x (tons/yr)	VOC (tons/yr)	CO (tons/yr)	Lead (tons/yr)	HAPs (tons/yr)
All Integral Control Units subject to NSPS OOO/UUU	55.6	55.6	55.6	0	0	0	0	0	0
Roller Mill	4.05	4.05	4.05	0	0	0	0	0	0
Impact Mill	4.05	4.05	4.05	0	0	0	0	0	0
#1 Bepex	0.912	0.912	0.912	0	0	0	0	0	0
Ball Mill	2.61	2.61	2.61	0	0	0	0	0	0
Nat. Gas Comb.	0.050	0.200	0.150	0.016	2.628	0.145	2.208	0.0496	0.050
Crusher System	0.153	0.153	0.153	0	0	0	0	0	0
Paved Roads	10.4	2.02	2.02	0	0	0	0	0	0
Loading & Unload	0.354	0.354	0.354	0	0	0	0	0	0
Total	78.1	69.9	69.9	0.016	2.63	0.145	2.21	0.0496	0.050

Appendix A: Emission Calculations
Baghouse Operations for Existing Emission Units

Company Name: Cimbar Performance Minerals MV, LLC
Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
MSOP Renewal: 129-22660-00023
Revision No: 129-29181-00023
Reviewer: Hannah L. Desrosiers
Date: April 19, 2010

Facilities Subject to Requirements of NSPS Subparts OOO and UUU

Facility Description	Baghouse ID	Control Efficiency (%)	Allowable Loading per Dry Cubic meter of Outlet Air (grams/cubic meter)	Gas or Air Flow Rate (acfm.)	Exhaust Temp. (F)	Average Moisture Content	PM/PM-10/PM-2.5 Emission Rate after Controls (lbs/hr)	PM/PM-10/PM-2.5 Emission Rate after Controls (tons/yr)
Grinding Plant								
North Silo	B	99.9%	0.05	1,500.0	70.0	6.5%	0.262	1.15
South Silo	C	99.9%	0.05	1,500.0	70.0	6.5%	0.262	1.15
Classifier #1	E	99.9%	0.05	1,550.0	150.0	6.5%	0.235	1.029
Red Silo	F	99.9%	0.05	1,500.0	150.0	6.5%	0.227	1.00
Green Silo	G	99.9%	0.05	1,500.0	150.0	6.5%	0.227	1.00
Blue Silo	H	99.9%	0.05	1,500.0	150.0	6.5%	0.227	1.00
Yellow Silo	I	99.9%	0.05	2,000.0	150.0	6.5%	0.303	1.33
Pink Silo	J	99.9%	0.05	2,000.0	150.0	6.5%	0.303	1.33
Orange Silo	K	99.9%	0.05	2,000.0	70.0	6.5%	0.349	1.53
#1 Silo	N	99.9%	0.05	900.0	150.0	6.5%	0.136	0.597
#2 Silo	O	99.9%	0.05	900.0	150.0	6.5%	0.136	0.597
#3 Silo	P	99.9%	0.05	900.0	150.0	6.5%	0.136	0.597
#4 Silo	Q	99.9%	0.05	900.0	150.0	6.5%	0.136	0.597
#5 Silo	R	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
#6 Silo	S	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
#7 Silo	T	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
#8 Silo	U	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
#9 Silo	V	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
#10 Silo	W	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
#11 Silo	X	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
#12 Silo	AA	99.0%	0.05	960.0	150.0	6.5%	0.146	0.637
#13 Silo	AB	99.0%	0.05	960.0	150.0	6.5%	0.146	0.637
Classifier #3	AC	99.0%	0.05	1,550.0	180.0	6.5%	0.224	0.981
Silo A	AG	99.9%	0.05	680.0	150.0	6.5%	0.103	0.451
Silo B	AH	99.9%	0.05	1,550.0	150.0	6.5%	0.235	1.029
Silo C	AI	99.9%	0.05	680.0	150.0	6.5%	0.103	0.451
Silo D	AJ	99.9%	0.05	680.0	150.0	6.5%	0.103	0.451
Silo #14	AK	99.9%	0.05	1,500.0	150.0	6.5%	0.227	0.996
Common Baghouse	AM	99.9%	0.05	680.0	150.0	6.5%	0.103	0.451
Bepex Air Mill Room							14.2	62.2
Silo #15	AO	99.9%	0.05	1,500.0	70.0	6.5%	0.262	1.146
Single Air Mill (powder)	AP	99.9%	0.05	4,000.0	200.0	6.5%	0.560	2.454
Silo #16	AS	99.9%	0.05	1,000.0	70.0	6.5%	0.174	0.764
Silo #17	AT	99.9%	0.05	1,000.0	70.0	6.5%	0.174	0.764
Twin Air Mill	AU	99.9%	0.05	5,500.0	195.0	6.5%	0.776	3.400
Silo #18	AV	99.9%	0.05	1,500.0	195.0	6.5%	0.212	0.927
Silo #19	AW	99.9%	0.05	1,500.0	195.0	6.5%	0.212	0.927
#3 Air Mill	AX	99.9%	0.05	2,650.0	200.0	6.5%	0.371	1.626
Pellet Mill & Nat. Gas Dryer	AY	99.9%	0.05	19,040.0	120.0	6.5%	3.035	13.294
Classifier #2	BA	99.9%	0.05	1,550.0	70.0	6.5%	0.270	1.184
Pellet Mill Transfer	BB	99.9%	0.05	680.0	70.0	6.5%	0.119	0.520
Product Recycling Bin	BC	99.9%	0.05	3,000.0	70.0	6.5%	0.523	2.292
R1 Bin	BD	99.9%	0.05	1,550.0	70.0	6.5%	0.270	1.184
Auto Packaging Machine Op.	BF	99.9%	0.05	3,000.0	70.0	6.5%	0.523	2.292
Cosmetic Circuit Receiver	BG	99.9%	0.05	1,570.0	70.0	6.5%	0.274	1.200
Bulk Truck Loadout	BH	99.9%	0.05	1,500.0	70.0	6.5%	0.262	1.146
Bulk Railcar Loadout	BI	99.9%	0.05	1,500.0	70.0	6.5%	0.262	1.146
Subtotal of Emissions Based on OOO							14.2	62.2
Nat. Gas Dryer (Subpart UUU)	AY	99.9%	0.025	19,040.0	120.0	6.5%	1.52	6.65
Subtotal Worst Case Emissions from (OOO/UUU)							12.7	55.6

Facilities NOT Subject to Either NSPS OOO or UUU

Facility Description	Baghouse ID	Control Efficiency (%)	Grain Loading per Actual Cubic foot of Outlet Air (grains/cu.ft.)	Gas or Air Flow Rate (acfm.)	Exhaust Temp. (F)	Average Moisture Content	PM/PM-10 Emission Rate after Controls (lbs/hr)	PM/PM-10 Emission Rate after Controls (tons/yr)
Roller Mill	D	99.9%	0.01	14,000.0	180.0	6.5%	0.926	4.054
Impact Mill	M	99.9%	0.01	14,000.0	180.0	6.5%	0.926	4.054
#1 Bepex	Y	99.9%	0.01	3,000.0	150.0	6.5%	0.208	0.912
Ball Mill	Z	99.9%	0.01	9,000.0	180.0	6.5%	0.595	2.606
Subtotal of Emissions for Facilities NOT Subject to Either NSPS OOO or UUU							2.654	11.627
Total Including Worst Case Emissions from Above (OOO/UUU)							15.34	67.2

Methodology

PM-10 and PM-2.5 emissions have been assumed equal to PM emissions
Emission Rate in lbs/hr (after controls) = (grams x (1pound/453.5924 grams)/cubic meter x (1 cubic ft/0.02832 cubic meters) x (acfm) x 528/(460 + T) x (100 - Moisture %)/100 x (60 min/hr)
Emission Rate in tons/yr = (lbs/hr) (8760 hr/yr) (ton/2000 lb)

Moisture content ranges between 3 - 10%

**Appendix A: Emission Calculations
Baghouse Operations for Existing Emission Units
326 IAC 6-3-2 Allowable Rate of Emissions**

**Company Name: Cimbar Performance Minerals MV, LLC
Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
MSOP Renewal: 129-22660-00023
Revision No: 129-29181-00023
Reviewer: Hannah L. Desrosiers
Date: April 19, 2010**

Facility Description	Baghouse ID	Process Rate (lbs/hr)	Process Weight Rate (tons/hr)	Allowable PM Emissions (lbs/hr)	Potential PM Emissions (lbs/hr)	Equivalent	Is the NSPS Subpart OOO
						NSPS Subpart OOO PM Emissions (lbs/hr)	More Stringent than the Limit Pursuant to 326 IAC 6-3-2 or Not Applicable?
Grinding Plant							
Crusher System		100,000	50.0	44.58	0.035	Not Applicable	Not Applicable
North Silo	B	70,000	35.0	41.32	0.262	0.262	Yes
South Silo	C	70,000	35.0	41.32	0.262	0.262	Yes
Roller Mill	D	28,000	14.0	24.03	0.926	Not Applicable	Not Applicable
Classifier #1	E	20,000	10.0	19.18	0.235	0.235	Yes
Red Silo	F	28,000	14.0	24.03	0.227	0.227	Yes
Green Silo	G	28,000	14.0	24.03	0.227	0.227	Yes
Blue Silo	H	28,000	14.0	24.03	0.227	0.227	Yes
Yellow Silo	I	28,000	14.0	24.03	0.303	0.303	Yes
Pink Silo	J	28,000	14.0	24.03	0.303	0.303	Yes
Orange Silo	K	28,000	14.0	24.03	0.349	0.349	Yes
Impact Mill	M	18,000	9.0	17.87	0.926	Not Applicable	Not Applicable
#1 Silo	N	28,000	14.0	24.03	0.136	0.136	Yes
#2 Silo	O	28,000	14.0	24.03	0.136	0.136	Yes
#3 Silo	P	28,000	14.0	24.03	0.136	0.136	Yes
#4 Silo	Q	28,000	14.0	24.03	0.136	0.136	Yes
#5 Silo	R	28,000	14.0	24.03	0.227	0.227	Yes
#6 Silo	S	28,000	14.0	24.03	0.227	0.227	Yes
#7 Silo	T	28,000	14.0	24.03	0.227	0.227	Yes
#8 Silo	U	28,000	14.0	24.03	0.227	0.227	Yes
#9 Silo	V	28,000	14.0	24.03	0.227	0.227	Yes
#10 Silo	W	28,000	14.0	24.03	0.227	0.227	Yes
#11 Silo	X	28,000	14.0	24.03	0.227	0.227	Yes
#1 Bepex	Y	2,000	1.0	4.10	0.208	Not Applicable	Not Applicable
Ball Mill	Z	15,000	7.5	15.82	0.595	Not Applicable	Not Applicable
#12 Silo	AA	28,000	14.0	24.03	0.146	0.146	Yes
#13 Silo	AB	70,000	35.0	41.32	0.146	0.146	Yes
Classifier #3	AC	20,000	10.0	19.18	0.224	0.224	Yes
Silo A	AG	28,000	14.0	24.03	0.103	0.103	Yes
Silo B	AH	28,000	14.0	24.03	0.235	0.235	Yes
Silo C	AI	28,000	14.0	24.03	0.103	0.103	Yes
Silo D	AJ	28,000	14.0	24.03	0.103	0.103	Yes
Silo #14	AK	28,000	14.0	24.03	0.227	0.227	Yes
Common Baghouse	AM	28,000	14.0	24.03	0.103	0.103	Yes
Bepex Air Mill Room							
Silo #15	AO	28,000	14.0	24.03	0.262	0.262	Yes
Single Air Mill (powder)	AP	8,000	4.0	10.38	0.560	0.560	Yes
Silo #16	AS	28,000	14.0	24.03	0.174	0.174	Yes
Silo #17	AT	28,000	14.0	24.03	0.174	0.174	Yes
Twin Air Mill	AU	4,000	2.0	6.52	0.776	0.776	Yes
Silo #18	AV	28,000	14.0	24.03	0.212	0.212	Yes
Silo #19	AW	28,000	14.0	24.03	0.212	0.212	Yes
#3 Air Mill	AX	8,000	4.0	10.38	0.371	0.371	Yes
Pellet Mill & Nat. Gas Dryer	AY	16,000	8.0	16.51	3.035	3.035	Yes
Classifier #2	BA	20,000	10.0	19.18	0.270	0.270	Yes
Pellet Mill Transfer	BB	8,000	4.0	10.38	0.119	0.119	Yes
Product Recycling Bin	BC	10,000	5.0	12.05	0.523	0.523	Yes
R1 Bin	BD	50,000	25.0	35.43	0.270	0.270	Yes
Auto Packaging Machine Op.	BF	16,000	8.0	16.51	0.523	0.523	Yes
Cosmetic Circuit Receiver	BG	14,000	7.0	15.10	0.274	0.274	Yes
Bulk Truck Loadout	BH	32,000	16.0	26.28	0.262	0.262	Yes
Bulk Railcar Loadout	BI	16,000	8.0	16.51	0.262	0.262	Yes

Methodology

Allowable Emissions = 4.10(Process Weight Rate)^{0.67} for process weight rates less than or = to 60,000 pounds per hour
 Allowable Emissions = 55(Process Weight Rate)^{0.11} - 40 for process weight rates greater than 60,000 pounds per hour

Appendix A: Emission Calculations
Baghouse Operations for Existing Emission Units
Demonstration of PM limits to keep source minor with respect to 326 IAC 2-2 (PSD)

Company Name: Cimbar Performance Minerals MV, LLC
Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
MSOP Renewal: 129-22660-00023
Revision No: 129-29181-00023
Reviewer: Hannah L. Desrosiers
Date: April 19, 2010

Facility Description	Baghouse ID	Prior PM Limits From 129-23559-00023 (lbs/hr)	Limited PM Emission Rate after Controls (lbs/hr)	Potential PM Emission Rate (lbs/hr)
Grinding Plant				
Crusher System		2.53	2.53	0.035
North Silo	B	0.262	0.262	0.262
South Silo	C	0.262	0.262	0.262
Roller Mill	D	7.350	7.350	0.926
Classifier #1	E	0.189	0.235	0.235
Red Silo	F	0.227	0.227	0.227
Green Silo	G	0.227	0.227	0.227
Blue Silo	H	0.227	0.227	0.227
Yellow Silo	I	0.265	0.303	0.303
Pink Silo	J	0.265	0.303	0.303
Orange Silo	K	0.262	0.349	0.349
Impact Mill	M	7.350	7.350	0.926
#1 Silo	N	0.136	0.136	0.136
#2 Silo	O	0.136	0.136	0.136
#3 Silo	P	0.136	0.136	0.136
#4 Silo	Q	0.136	0.136	0.136
#5 Silo	R	0.227	0.227	0.227
#6 Silo	S	0.227	0.227	0.227
#7 Silo	T	0.227	0.227	0.227
#8 Silo	U	0.227	0.227	0.227
#9 Silo	V	0.227	0.227	0.227
#10 Silo	W	0.227	0.227	0.227
#11 Silo	X	0.227	0.227	0.227
#1 Bepex	Y	3.30	3.30	0.208
Ball Mill	Z	9.43	9.43	0.595
#12 Silo	AA	0.146	0.146	0.146
#13 Silo	AB	0.146	0.146	0.146
Classifier #3	AC		0.224	0.224
Silo A	AG	0.103	0.103	0.103
Silo B	AH	0.235	0.235	0.235
Silo C	AI	0.103	0.103	0.103
Silo D	AJ	0.103	0.103	0.103
Silo #14	AK	0.103	0.227	0.227
Common Baghouse	AM	0.103	0.103	0.103
Bepex Air Mill Room				
Silo #15	AO	0.174	0.262	0.262
Single Air Mill (powder)	AP	0.371	0.560	0.560
Silo #16	AS	0.174	0.174	0.174
Silo #17	AT	0.174	0.174	0.174
Twin Air Mill	AU	0.471	0.776	0.776
Silo #18	AV	0.130	0.212	0.212
Silo #19	AW	0.130	0.212	0.212
#3 Air Mill	AX	0.230	0.371	0.371
Pellet Mill & Nat. Gas Dryer	AY	1.375	3.035	3.035
Classifier #2	BA		0.270	0.270
Pellet Mill Transfer	BB		0.119	0.119
Product Recycling Bin	BC		0.523	0.523
R1 Bin	BD		0.270	0.270
Auto Packaging Machine Op.	BF		0.523	0.523
Cosmetic Circuit Receiver	BG		0.274	0.274
Bulk Truck Loadout	BH		0.262	0.262
Bulk Railcar Loadout	BI		0.262	0.262
Total (lbs/hr)		38.6	44.2	16.89
Total (tons/yr)		168.8	193.4	74.0

Limits in Italics have been revised in the renewal

Appendix A: Emissions Calculations
Emissions from Existing Emission Units

Company Name: Cimbar Performance Minerals MV, LLC
Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
MSOP Renewal: 129-22660-00023
Revision No: 129-29181-00023
Reviewer: Hannah L. Desrosiers
Date: April 19, 2010

Natural Gas Combustion

Small Industrial Boiler with MM BTU/HR <100

Heat Input Capacity* MMBtu/hr	Potential Throughput MMCF/yr
6.00	52.56

Emission Factor in lb/MMCF	Regulated Pollutant						
	PM*	PM10**	PM2.5	SO2	NOx	VOC	CO
	1.90	7.60	5.70	0.600	100 ***see below	5.50	84.0
Potential Emission in tons/yr	0.050	0.200	0.150	0.016	2.63	0.145	2.21

* Natural Gas Fired Dryer part of Pellet Mill @ 6 mmBtu/hr

** PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable fractions combined. PM2.5 emission factor is condensable fraction only.

*** Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Emission Factor in lb/MMcf	HAPs - Organics				
	Benzene	Dichlorobenzene	Formaldehyde	Hexane	Toluene
	2.10E-03	1.20E-03	7.50E-02	1.80	3.40E-03
Potential Emission in tons/yr	5.52E-05	3.15E-05	1.97E-03	0.0473	8.94E-05

Emission Factor in lb/MMcf	HAPs - Metals				
	Lead	Cadmium	Chromium	Manganese	Nickel
	5.00E-04	1.10E-03	1.40E-03	3.80E-04	2.10E-03
Potential Emission in tons/yr	1.31E-05	2.89E-05	3.68E-05	9.99E-06	5.52E-05

The five highest organic and metal HAPs emission factors are provided above.

Additional HAPs emission factors are available in AP-42, Chapter 1.4.

Total Combined HAPs	0.050	tons/yr
"Worst" Single HAP	0.0473	tons/yr (hexane)

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

Crushing (primary)

The following calculations determine the amount of emissions created by the crushing of aggregate, based on 8760 hours of use and AP-42 emissions factors, [Ch 11.19.2 (Fifth edition, 1/95)].

PM, PM10, and PM 2.5 emissions are assumed equal.

$$\text{PTE PM/PM10/PM2.5} = 50 \text{ ton/hr x } 0.0007 \text{ lb/ton} / 2000 \text{ lb/ton x } 8760 \text{ hr/yr} = \boxed{0.153 \text{ tons/yr}}$$

Loading & Unloading

The following calculations determine the amount of emissions created by truck loading and unloading of aggregate, based on 8760 hours of use and AP-42 emission factors, Ch 13.2.4 (Fifth edition, 1/95).

PM, PM10, and PM 2.5 emissions are assumed equal.

$$E_f = k \cdot (0.0032)^M \cdot (U/5)^{1.3} / (M/2)^{1.4}$$

$$= 0.0016 \text{ lb/ton}$$

where k = 0.74 (particle size multiplier)

U = 10 mile/hr mean wind speed

M = 5 % material moisture content

$$\text{PTE PM/PM10/PM2.5} = 50 \text{ ton/hr x } 0.0016 \text{ lb/ton} / 2000 \text{ lb/ton x } 8760 \text{ hr/yr} = \boxed{0.354 \text{ tons/yr}}$$

Appendix A: Emissions Calculations
Particulate Emissions

Company Name: Cimbar Performance Minerals MV, LLC
Address City IN Zip: 2700 Bluff Road, Mt. Vernon, Indiana 47620
MSOP Renewal: 129-22660-00023
Revision No: 129-29181-00023
Reviewer: Hannah L. Desrosiers
Date: April 19, 2010

Paved Roads

The following calculations determine the amount of emissions created by paved roads, based on 8,760 hours of use and AP-42, Ch 13.2.1 (11/2006).

Dump Trucks

0.7 total trip/hr x Road = 195 yards each way, truck carries 20 tons of ore
0.222 average miles/round trip x
8760 hr/yr = 2717.6 miles per year

PM Emissions

$$E_f = k \left[\frac{s}{2} \right]^{0.65} \left[\frac{W}{3} \right]^{1.5} - C$$

$$= 3.36 \text{ lb/mile}$$

where k = 0.082 (particle size multiplier for PM30 or TSP) (k=0.082 for PM-30 or TSP)
s = 5.5 mean % silt content of concrete batching paved roads

W = 23.00 tons average vehicle weight
C = 0.00047 lbs/mile for exhaust, break and tire wear
E = $\frac{3.36 \text{ lb/mi} \times 2717.6 \text{ mi/yr}}{2000 \text{ lb/ton}}$ = 4.56 tons/yr

Taking natural mitigation due to precipitation into consideration:

$$E_{ext} = E \cdot [1 - p/4]^{365} = 4.17 \text{ tons/yr}$$

where: p = 125 days of rain greater than or equal to 0.01 inches (see Fig. 13.2.2-1)

PM-10 Emissions

$$E_f = k \left[\frac{s}{2} \right]^{0.65} \left[\frac{W}{3} \right]^{1.5} - C$$

$$= 0.66 \text{ lb/mile}$$

where k = 0.016 (particle size multiplier for PM10) (k=0.016 for PM-10)
s = 5.5 mean % silt content of concrete batching paved roads

W = 23.00 tons average vehicle weight
C = 0.00047 lbs/mile for exhaust, break and tire wear
E = $\frac{0.665 \text{ lb/mi} \times 2717.590909 \text{ mi/yr}}{2000 \text{ lb/ton}}$ = 0.890 tons/yr

Taking natural mitigation due to precipitation into consideration:

$$E_{ext} = E \cdot [1 - p/4]^{365} = 0.814 \text{ tons/yr}$$

where: p = 125 days of rain greater than or equal to 0.01 inches (see Fig. 13.2.2-1)

Front-end Loader

2.8 total trip/hr x Road = 135 yards each way, loader carries 5 tons of ore
0.153 average miles/round trip x
8760 hr/yr = 7525.6 miles per year

PM Emissions

$$E_f = k \left[\frac{s}{2} \right]^{0.65} \left[\frac{W}{3} \right]^{1.5} - C$$

$$= 1.80 \text{ lb/mile}$$

where k = 0.082 (particle size multiplier for PM30 or TSP) (k=0.082 for PM-30 or TSP)
s = 5.5 mean % silt content of concrete batching paved roads

W = 15.15 tons average vehicle weight
C = 0.00047 lbs/mile for exhaust, break and tire wear
E = $\frac{1.80 \text{ lb/mi} \times 7525.6 \text{ mi/yr}}{2000 \text{ lb/ton}}$ = 6.76 tons/yr

Taking natural mitigation due to precipitation into consideration:

$$E_{ext} = E \cdot [1 - p/4]^{365} = 6.18 \text{ tons/yr}$$

where: p = 125 days of rain greater than or equal to 0.01 inches (see Fig. 13.2.2-1)

PM-10 Emissions

$$E_f = k \left[\frac{s}{2} \right]^{0.65} \left[\frac{W}{3} \right]^{1.5} - C$$

$$= 0.35 \text{ lb/mile}$$

where k = 0.016 (particle size multiplier for PM10) (k=0.016 for PM-10)
s = 5.5 mean % silt content of concrete batching paved roads

W = 15.15 tons average vehicle weight
C = 0.00047 lbs/mile for exhaust, break and tire wear
E = $\frac{0.350 \text{ lb/mi} \times 7525.636364 \text{ mi/yr}}{2000 \text{ lb/ton}}$ = 1.32 tons/yr

Taking natural mitigation due to precipitation into consideration:

$$E_{ext} = E \cdot [1 - p/4]^{365} = 1.20 \text{ tons/yr}$$

where: p = 125 days of rain greater than or equal to 0.01 inches (see Fig. 13.2.2-1)

Total PM	10.4	tons/yr
Total PM-10	2.02	tons/yr

PM 2.5 emissions are assumed equal to PM10 emissions.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

**Minor Source Operating Permit Renewal
OFFICE OF AIR QUALITY**

**Cimbar Performance Minerals MV, LLC
2700 Bluff Road
Mt. Vernon, Indiana 47620**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain an MSOP under 326 IAC 2-6.1.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages.

Operation Permit No.: MSOP 129-22660-00023	
Original Signed By: Nisha Sizemore, Chief Permits Branch Office of Air Quality	Issuance Date: November 28, 2007 Expiration Date: November 28, 2017
First Notice-Only Change No.: MSOP 129-25722-00003, issued January 17, 2008	
Second Notice-Only Change No.: 129-28690-00023, issued December 03, 2009	
Third Notice-Only Change No.: MSOP 129-29181-00023	
Issued By:  Iryn Calilung, Section Chief Permits Branch Office of Air Quality	Issuance Date: June 8, 2010 Expiration Date: November 28, 2017

TABLE OF CONTENTS

SECTION A	SOURCE SUMMARY	4
A.1	General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]	
A.2	Emission Units and Pollution Control Equipment Summary	
SECTION B	GENERAL CONDITIONS	8
B.1	Definitions [326 IAC 2-1.1-1]	
B.2	Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]	
B.3	Term of Conditions [326 IAC 2-1.1-9.5]	
B.4	Enforceability	
B.5	Severability	
B.6	Property Rights or Exclusive Privilege	
B.7	Duty to Provide Information	
B.8	Annual Notification [326 IAC 2-6.1-5(a)(5)]	
B.9	Preventive Maintenance Plan [326 IAC 1-6-3]	
B.10	Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.11	Termination of Right to Operate [326 IAC 2-6.1-7(a)]	
B.12	Permit Renewal [326 IAC 2-6.1-7]	
B.13	Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]	
B.14	Source Modification Requirement	
B.15	Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2] [IC 13-17-3-2][IC 13-30-3-1]	
B.16	Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]	
B.17	Annual Fee Payment [326 IAC 2-1.1-7]	
B.18	Credible Evidence [326 IAC 1-1-6]	
SECTION C	SOURCE OPERATION CONDITIONS	13
	Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]	
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2	Permit Revocation [326 IAC 2-1.1-9]	
C.3	Opacity [326 IAC 5-1]	
C.4	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.5	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.6	Fugitive Dust Emissions [326 IAC 6-4]	
C.7	Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]	
C.8	Stack Height [326 IAC 1-7]	
C.9	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	Testing Requirements [326 IAC 2-6.1-5(a)(2)]	
C.10	Performance Testing [326 IAC 3-6]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.11	Compliance Requirements [326 IAC 2-1.1-11]	
	Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]	
C.12	Compliance Monitoring [326 IAC 2-1.1-11]	
C.13	Instrument Specifications [326 IAC 2-1.1-11]	
	Corrective Actions and Response Steps	
C.14	Response to Excursions or Exceedances	
C.15	Actions Related to Noncompliance Demonstrated by a Stack Test	

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

- C.16 Malfunctions Report [326 IAC 1-6-2]
- C.17 General Record Keeping Requirements [326 IAC 2-6.1-5]
- C.18 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2]
[IC 13-14-1-13]

D.1 EMISSIONS UNIT OPERATION CONDITIONS: Entire Source..... 19

Emission Limitations and Standards

- D.1.1 PSD Minor Limit [326 IAC 2-2]
- D.1.2 Particulate [326 IAC 6-3-2]
- D.1.3 Preventive Maintenance Plan [326 IAC 1-6-3]

Compliance Determination Requirements

- D.1.4 Particulate Control
- D.1.5 Testing Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

- D.1.6 Visible Emissions Notations
- D.1.7 Baghouse Parametric Monitoring
- D.1.8 Broken or Failed Bag Detection

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

- D.1.9 Record Keeping Requirements

E.1 EMISSIONS UNIT OPERATION CONDITIONS - NSPS Subpart OOO..... 28

New Source Performance Standards (NSPS) Requirements [326 IAC 2-6]

- E.1.1 General Provisions Relating to NSPS Subpart OOO [326 IAC 12] [40 CFR Part 60, Subpart A]
- E.1.2 NSPS Subpart OOO Requirements [40 CFR Part 60, Subpart OOO] [326 IAC 12]

E.2 EMISSIONS UNIT OPERATION CONDITIONS - NSPS Subpart UUU 39

New Source Performance Standards (NSPS) Requirements [326 IAC 2-6]

- E.2.1 General Provisions Relating to NSPS Subpart OOO [326 IAC 12] [40 CFR Part 60, Subpart A]
- E.2.2 NSPS Subpart UUU Requirements [40 CFR Part 60, Subpart UUU] [326 IAC 12]

Annual Notification 42

Malfunction Report..... 43

Attachment A: Fugitive Dust Plan

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in Conditions A.1 and A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary talc, barite and calcium carbonate processing source.

Source Address:	2700 Bluff Road, Mt. Vernon, Indiana 47620
General Source Phone Number:	812- 838-8330
SIC Code:	3295
County Location:	Posey
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Minor Source Operating Permit Program Minor Source, under PSD Rules Minor Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) grinding plant, installed in 1991, exhausted to Stacks A through K and M controlled by twelve (12) baghouses, identified as A through K and M, capacity: 14.0 tons of talc, barite or calcium carbonate per hour, consisting of the following:
- (1) One (1) electric crusher system, manufactured on September 14, 1960, capacity 50.0 tons of ore per hour.
 - (2) Two (2) silos, identified as North and South, connected pneumatically to baghouses, identified as B and C, exhausted to Stacks B and C, throughput capacity: 35.0 tons of ore per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (3) One (1) roller mill, manufactured in November 1928, connected pneumatically to a baghouse, identified as D, exhausted to Stack D, throughput capacity: 14.0 tons of nonmetallic minerals per hour.
 - (4) One (1) classifier #1, connected pneumatically to a baghouse, identified as E, exhausted to Stack E, throughput capacity: 10.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a screening operation and is an affected facility.
 - (5) Six (6) silos, identified as Red, Green, Blue, Yellow, Pink and Orange, connected pneumatically to baghouses, identified as F, G, H, I, J and K, exhausted to Stacks F, G, H, I, J and K, respectively, throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (6) One (1) impact mill, manufactured on September 10, 1962, connected pneumatically to a baghouse, identified as M, exhausted to Stack M, throughput capacity: 9.0 tons of nonmetallic minerals per hour.

- (b) Four (4) silos, identified as Silo #1, Silo #2, Silo #3 and Silo #4, installed in 1994, connected pneumatically to baghouses, identified as N, O, P and Q, exhausted to Stacks N, O, P and Q, respectively, capacity: 8,313 cubic feet, each, and throughput capacity: 14.0 tons of minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (c) Two (2) silos, identified as Silo #5 and Silo #6, installed in 1994, connected pneumatically to baghouses, identified as R and S, exhausted to Stacks R and S, capacity: 6,107 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (d) Five (5) silos, identified as Silo #7, Silo #8, Silo #9, Silo #10 and Silo #11, installed in 1994, connected pneumatically to baghouses, identified as T, U, V, W and X, exhausted to Stacks T, U, V, W and X, respectively, capacity: 11,083 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (e) One (1) hammer mill micronizer, identified as #1 Bepex, manufactured on December 10, 1974, installed in 1994, connected pneumatically to a baghouse, identified as Y, exhausted to Stack Y, capacity: 1.00 ton of nonmetallic minerals per hour.
- (f) One (1) ball mill micronizer, identified as Ball Mill, manufactured on January 25, 1950, connected pneumatically to a baghouse, identified as Z, exhausted to Stack Z, capacity: 7.5 tons of non metallic minerals per hour, two (2) silos, identified as Silo #12 connected pneumatically to a baghouse, identified as AA, throughput capacity: 14.0 tons of nonmetallic minerals per hour, and Silo #13, connected pneumatically to a baghouse, identified as AB, throughput capacity: 35.0 tons of ore per hour, exhausted to Stacks AA and AB, capacity: 6,688 cubic feet, each and one (1) classifier #3, installed in 1994, connected pneumatically to a baghouse, identified as AC, exhausted to Stack AC, capacity: 10.0 tons of minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, Silo #12 and #13 are storage bins and are affected facilities and the classifier #3 is a screening operation and is an affected facility.
- (g) One (1) pellet mill and natural gas-fired dryer, identified as Pellet Mill, installed in 1996, connected pneumatically to a baghouse, identified as AY, installed in 2006, exhausted to Stack AY, capacity: 8.0 tons of nonmetallic minerals per hour and rated at 6.0 million British thermal units per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility. Under NSPS, 40 CFR Part 60.730, Subpart UUU, the dryer is an affected facility.
- (h) Five (5) material storage silos, identified as Silo A, Silo B, Silo C, Silo D and Silo #14, exhausted to Stacks AG, AH, AI, AJ and AK, respectively, connected pneumatically to baghouses, identified as AG, AH, AI, AJ and AK, respectively, installed in 1997, capacity: 12,038 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Silos A, B, C and D are also connected pneumatically to a common baghouse, identified as AM for unloading/transfer purposes, throughput capacity: 14.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (i) One (1) Bepex/Air Mill Room, capacity: 2.0 tons of nonmetallic minerals per hour, consisting of:
 - (1) Three (3) silos, identified as Silo #15, Silo #16 and Silo #17, connected pneumatically to baghouses, identified as AO, AS and AT, exhausted to Stacks AO, AS and AT, throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.

- (2) One (1) single air mill (powder), connected pneumatically to a baghouse, identified as AP, exhausted to Stack AP, throughput capacity: 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (j) One (1) twin air mill, connected pneumatically to a baghouse, identified as AU, exhausted to Stack AU, installed in 2004, capacity: 2.0 tons of talc per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (k) One (1) air jet milling system, installed in 2005, capacity of 2.5 tons of nonmetallic minerals per hour, consisting of:
 - (1) Two (2) silos, identified as Silo #18 and Silo #19, connected pneumatically to baghouses, identified as AV, and AW, exhausted to Stacks AV and AW, capacity; 3,950 cubic feet, each and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (2) One (1) #3 air mill, connected pneumatically to a baghouse, identified as AX, exhausted to Stack AX, capacity 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (l) One (1) classifier #2, connected pneumatically to a baghouse, identified as BA installed in 1995, exhausted to Stack BA, capacity: 10.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a screening operation and is an affected facility.
- (m) One (1) Pellet Mill Transfer, connected pneumatically to a baghouse, identified as BB, installed in 1999, exhausted to Stack BB, capacity: 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a pneumatic system and is an affected facility.
- (n) One (1) product recycling bin, connected pneumatically to a baghouse, identified as BC, installed in 2001, exhausted to Stack BC, capacity: 5.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a storage bin and is an affected facility.
- (o) One (1) R1 bin, connected pneumatically to a baghouse, identified as BD, installed in 1994, exhausted to Stack BD, capacity: 25.0 tons of ore per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a storage bin and is an affected facility.
- (p) One (1) auto packaging machine operation, connected pneumatically to a baghouse, identified as BF, installed in 2002, exhausted to Stack BF, capacity: 8.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a bagging operation and is an affected facility.
- (q) One (1) cosmetic circuit receiver, connected pneumatically to a baghouse, identified as BG, installed in 1992, exhausted to Stack BG, capacity: 7.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a pneumatic system and is an affected facility.
- (r) One (1) bulk truck loadout operation, connected pneumatically to a baghouse, identified as BH, installed in 1996, exhausted to Stack BH, capacity: 16.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a loading station and is an

affected facility.

- (s) One (1) bulk railcar loadout operation, connected pneumatically to a baghouse, identified as BI, installed in 1997, exhausted to Stack BI, capacity: 8.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a loading station and is an affected facility.

- (t) One (1) twin air jet milling system, identified as BJ, consisting of mills # 5 & 6, approved for construction in 2010, for dry material size reduction of talc products, with a maximum throughput capacity of two (2.0) tons of talc per hour, connected pneumatically to one (1) integral baghouse, identified as BJ, for product reclamation, and exhausting outside the building through Stack BJ. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-1.1-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-1.1-1) shall prevail.

B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]

- (a) This permit, M129-22660-00023, is issued for a fixed term of ten (10) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) An annual notification shall be submitted by an authorized individual to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) The annual notice shall be submitted in the format attached no later than March 1 of each year to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (c) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

B.9 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) A Preventive Maintenance Plan meets the requirements of 326 IAC 1-6-3 if it includes, at a minimum:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

The Permittee shall implement the PMPs.

- (b) If required by specific condition(s) in Section D of this permit where no PMP was previously required, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) no later than ninety (90) days after issuance of this permit or ninety (90) days after initial start-up, whichever is later, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The Permittee shall implement the PMPs.

- (c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions.
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.10 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of permits established prior to M129-22660-00023 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted.
- (b) All previous registrations and permits are superseded by this permit.

B.11 Termination of Right to Operate [326 IAC 2-6.1-7(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least one hundred twenty (120) days prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-6.1-7.

B.12 Permit Renewal [326 IAC 2-6.1-7]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-6.1-7. Such information shall be included in the application for each emission unit at this source. The renewal application does require an affirmation that the statements in the application are true and complete by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
 - (1) Submitted at least one hundred twenty (120) days prior to the date of the expiration of this permit; and

- (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-6.1 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified, pursuant to 326 IAC 2-6.1-4(b), in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.13 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (c) The Permittee shall notify the OAQ no later than thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

B.14 Source Modification Requirement

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

B.15 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2][IC 13-17-3-2][IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.16 Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]

- (a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.

- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require an affirmation that the statements in the application are true and complete by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement notice-only changes addressed in the request for a notice-only change immediately upon submittal of the request. [326 IAC 2-6.1-6(d)(3)]

B.17 Annual Fee Payment [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees due no later than thirty (30) calendar days of receipt of a bill from IDEM, OAQ.

- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.18 Credible Evidence [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than one hundred (100) pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed five hundred fifty-one thousandths (0.551) pounds per hour.

C.2 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation of Permits), this permit to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-1 (Applicability) and 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator except as provided in 326 IAC 4-2 or in this permit. The Permittee shall not operate a refuse incinerator or refuse burning equipment except as provided in 326 IAC 9-1-2 or in this permit.

C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]

Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the attached plan as in Attachment A.

C.8 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

C.9 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
- (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project.

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Licensed Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Licensed Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-6.1-5(a)(2)]

C.10 Performance Testing [326 IAC 3-6]

- (a) For performance testing required by this permit, a test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date.
- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date.
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.11 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]

C.12 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.13 Instrument Specifications [326 IAC 2-1.1-11]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps

C.14 Response to Excursions or Exceedances

Upon detecting an excursion where a response step is required by the D Section or an exceedance of a limitation in this permit:

- (a) The Permittee shall take reasonable response steps to restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing excess emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction. The response may include, but is not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned or are returning to normal without operator action (such as through response by a computerized distribution control system); or
 - (3) any necessary follow-up actions to return operation to normal or usual manner of operation.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records; and/or
 - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall record the reasonable response steps taken.

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall submit a description of its response actions to IDEM, OAQ, no later than seventy-five (75) days after the date of the test.

- (b) A retest to demonstrate compliance shall be performed no later than one hundred eighty (180) days after the date of the test. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred eighty (180) days is not practicable, IDEM, OAQ may extend the retesting deadline
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

C.16 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.17 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, for all record keeping requirements not already legally required, the Permittee shall be allowed up to ninety (90) days from the date of permit issuance or the date of initial start-up, whichever is later, to begin such record keeping.

C.18 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

- (c) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

SECTION D.1

EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description: Entire Source

- (a) One (1) grinding plant, installed in 1991, exhausted to Stacks A through K and M controlled by twelve (12) baghouses, identified as A through K and M, capacity: 14.0 tons of talc, barite or calcium carbonate per hour, consisting of the following:
 - (1) One (1) electric crusher system, manufactured on September 14, 1960, capacity 50.0 tons of ore per hour.
 - (2) Two (2) silos, identified as North and South, connected pneumatically to baghouses, identified as B and C, exhausted to Stacks B and C, throughput capacity: 35.0 tons of ore per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (3) One (1) roller mill, manufactured in November 1928, connected pneumatically to a baghouse, identified as D, exhausted to Stack D, throughput capacity: 14.0 tons of nonmetallic minerals per hour.
 - (4) One (1) classifier #1, connected pneumatically to a baghouse, identified as E, exhausted to Stack E, throughput capacity: 10.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a screening operation and is an affected facility.
 - (5) Six (6) silos, identified as Red, Green, Blue, Yellow, Pink and Orange, connected pneumatically to baghouses, identified as F, G, H, I, J and K, exhausted to Stacks F, G, H, I, J and K, respectively, throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (6) One (1) impact mill, manufactured on September 10, 1962, connected pneumatically to a baghouse, identified as M, exhausted to Stack M, throughput capacity: 9.0 tons of non-metallic minerals per hour.
- (b) Four (4) silos, identified as Silo #1, Silo #2, Silo #3 and Silo #4, installed in 1994, connected pneumatically to baghouses, identified as N, O, P and Q, exhausted to Stacks N, O, P and Q, respectively, capacity: 8,313 cubic feet, each, and throughput capacity: 14.0 tons of minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (c) Two (2) silos, identified as Silo #5 and Silo #6, installed in 1994, connected pneumatically to baghouses, identified as R and S, exhausted to Stacks R and S, capacity: 6,107 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (d) Five (5) silos, identified as Silo #7, Silo #8, Silo #9, Silo #10 and Silo #11, installed in 1994, connected pneumatically to baghouses, identified as T, U, V, W and X, exhausted to Stacks T, U, V, W and X, respectively, capacity: 11,083 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (e) One (1) hammer mill micronizer, identified as #1 Bepex, manufactured on December 10, 1974, installed in 1994, connected pneumatically to a baghouse, identified as Y, exhausted to Stack Y, capacity: 1.00 ton of nonmetallic minerals per hour.

Emissions Unit Description: (continued)

- (f) One (1) ball mill micronizer, identified as Ball Mill, manufactured on January 25, 1950, connected pneumatically to a baghouse, identified as Z, exhausted to Stack Z, capacity: 7.5 tons of non metallic minerals per hour, two (2) silos, identified as Silo #12 connected pneumatically to a baghouse, identified as AA, throughput capacity: 14.0 tons of nonmetallic minerals per hour, and Silo #13, connected pneumatically to a baghouse, identified as AB, throughput capacity: 35.0 tons of ore per hour, exhausted to Stacks AA and AB, capacity: 6,688 cubic feet, each and one (1) classifier #3, installed in 1994, connected pneumatically to a baghouse, identified as AC, exhausted to Stack AC, capacity: 10.0 tons of minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, Silo #12 and #13 are storage bins and are affected facilities and the classifier #3 is a screening operation and is an affected facility.
- (g) One (1) pellet mill and natural gas-fired dryer, identified as Pellet Mill, installed in 1996, connected pneumatically to a baghouse, identified as AY, installed in 2006, exhausted to Stack AY, capacity: 8.0 tons of nonmetallic minerals per hour and rated at 6.0 million British thermal units per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility. Under NSPS, 40 CFR Part 60.730, Subpart UUU, the dryer is an affected facility.
- (h) Five (5) material storage silos, identified as Silo A, Silo B, Silo C, Silo D and Silo #14, exhausted to Stacks AG, AH, AI, AJ and AK, respectively, connected pneumatically to baghouses, identified as AG, AH, AI, AJ and AK, respectively, installed in 1997, capacity: 12,038 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Silos A, B, C and D are also connected pneumatically to a common baghouse, identified as AM for unloading/transfer purposes, throughput capacity: 14.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (i) One (1) Bepex/Air Mill Room, capacity: 2.0 tons of nonmetallic minerals per hour, consisting of:
 - (1) Three (3) silos, identified as Silo #15, Silo #16 and Silo #17, connected pneumatically to baghouses, identified as AO, AS and AT, exhausted to Stacks AO, AS and AT, throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (2) One (1) single air mill (powder), connected pneumatically to a baghouse, identified as AP, exhausted to Stack AP, throughput capacity: 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (j) One (1) twin air mill, connected pneumatically to a baghouse, identified as AU, exhausted to Stack AU, installed in 2004, capacity: 2.0 tons of talc per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (k) One (1) air jet milling system, installed in 2005, capacity of 2.5 tons of nonmetallic minerals per hour, consisting of:
 - (1) Two (2) silos, identified as Silo #18 and Silo #19, connected pneumatically to baghouses, identified as AV, and AW, exhausted to Stacks AV and AW, capacity; 3,950 cubic feet, each and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (2) One (1) #3 air mill, connected pneumatically to a baghouse, identified as AX, exhausted to Stack AX, capacity 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.

Emissions Unit Description: (continued)

- (l) One (1) classifier #2, connected pneumatically to a baghouse, identified as BA installed in 1995, exhausted to Stack BA, capacity: 10.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a screening operation and is an affected facility.
- (m) One (1) Pellet Mill Transfer, connected pneumatically to a baghouse, identified as BB, installed in 1999, exhausted to Stack BB, capacity: 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a pneumatic system and is an affected facility.
- (n) One (1) product recycling bin, connected pneumatically to a baghouse, identified as BC, installed in 2001, exhausted to Stack BC, capacity: 5.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a storage bin and is an affected facility.
- (o) One (1) R1 bin, connected pneumatically to a baghouse, identified as BD, installed in 1994, exhausted to Stack BD, capacity: 25.0 tons of ore per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a storage bin and is an affected facility.
- (p) One (1) auto packaging machine operation, connected pneumatically to a baghouse, identified as BF, installed in 2002, exhausted to Stack BF, capacity: 8.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a bagging operation and is an affected facility.
- (q) One (1) cosmetic circuit receiver, connected pneumatically to a baghouse, identified as BG, installed in 1992, exhausted to Stack BG, capacity: 7.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a pneumatic system and is an affected facility.
- (r) One (1) bulk truck loadout operation, connected pneumatically to a baghouse, identified as BH, installed in 1996, exhausted to Stack BH, capacity: 16.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a loading station and is an affected facility.
- (s) One (1) bulk railcar loadout operation, connected pneumatically to a baghouse, identified as BI, installed in 1997, exhausted to Stack BI, capacity: 8.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a loading station and is an affected facility.
- (t) One (1) twin air jet milling system, identified as BJ, consisting of mills # 5 & 6, approved for construction in 2010, for dry material size reduction of talc products, with a maximum throughput capacity of two (2.0) tons of talc per hour, connected pneumatically to one (1) integral baghouse, identified as BJ, for product reclamation, and exhausting outside the building through Stack BJ. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards

D.1.1 PSD PM Minor Limits [326 IAC 2-2]

Particulate matter (PM) from facilities listed in the following table shall not exceed the pound per hour emission rates:

Facility Description	Baghouse Identification	Limited PM Emission Rate (lbs/hr)
Crusher System		2.53
North Silo	B	0.262
South Silo	C	0.262
Roller Mill	D	7.35
Classifier #1	E	0.235
Red Silo	F	0.227
Green Silo	G	0.227
Blue Silo	H	0.227
Yellow Silo	I	0.303
Pink Silo	J	0.303
Orange Silo	K	0.349
Impact Mill	M	7.35
#1 Silo	N	0.136
#2 Silo	O	0.136
#3 Silo	P	0.136
#4 Silo	Q	0.136
#5 Silo	R	0.227
#6 Silo	S	0.227
#7 Silo	T	0.227
#8 Silo	U	0.227
#9 Silo	V	0.227
#10 Silo	W	0.227
#11 Silo	X	0.227
#1 Bepex	Y	3.30
Ball Mill	Z	9.43
#12 Silo	AA	0.146
#13 Silo	AB	0.146
Classifier #3	AC	0.224
Silo A	AG	0.103
Silo B	AH	0.235
Silo C	AI	0.103
Silo D	AJ	0.103
Silo #14	AK	0.227
Common Baghouse	AM	0.103
Silo #15	AO	0.262
Single Air Mill (powder)	AP	0.560
Silo #16	AS	0.174
Silo #17	AT	0.174
Twin Air Mill	AU	0.776
Silo #18	AV	0.212
Silo #19	AW	0.212
#3 Air Mill	AX	0.371
Pellet Mill & Nat. Gas Dryer	AY	3.04
Classifier #2	BA	0.270
Pellet Mill Transfer	BB	0.119
Product Recycling Bin	BC	0.523
R1 Bin	BD	0.270
Auto Packaging Machine Op.	BF	0.523
Cosmetic Circuit Receiver	BG	0.274
Bulk Truck Loadout	BH	0.262
Bulk Railcar Loadout	BI	0.262
Twin Air Jet Mill	BJ	0.439

Compliance with these PM limits and potential PM emissions from other emission units at this source shall limit PM emissions to less than two hundred fifty (250) tons per year and renders the entire source minor with respect to 326 IAC 2-2 (PSD).

D.1.2 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the particulate emission rate from the:

- (a) crusher system shall not exceed 44.5 pounds per hour when operating at a process weight rate of 50.0 tons per hour,
- (b) roller mill shall not exceed 24.0 pounds per hour when operating at a process weight rate of 14.0 tons per hour,
- (c) impact mill shall not exceed 17.8 pounds per hour when operating at a process weight rate of 9.0 tons per hour,
- (d) #1 Bepex shall not exceed 4.1 pounds per hour when operating at a process weight rate of 1.0 ton per hour, and
- (e) ball mill shall not exceed 15.8 pounds per hour when operating at a process weight rate of 7.5 tons per hour.

The pounds per hour limitations were calculated with the following equations:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

and

Interpolation and extrapolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P_{0.11} - 40 \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour.}$$

D.1.3 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan is required for all facilities, except the crusher system, and their baghouse control devices. Section B - Preventive Maintenance Plan contains the Permittee's obligation with regard to the preventive maintenance plan required by this condition.

Compliance Determination Requirements

D.1.4 Particulate Control

- (a) In order to comply with Conditions D.1.1 and D.1.2, the baghouses, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through BJ for particulate control shall be in operation and control emissions from the talc, barite and calcium carbonate processing facilities at all times that these facilities are in operation.
- (b) In the event that bag failure is observed in a multi-compartment baghouse, if operations will continue for ten (10) days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date

the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.

D.1.5 Testing Requirements [326 IAC 2-1.1-11]

(a) Not later than one hundred eighty (180) days of issuance of this MSOP Renewal, 129-22660-00023, in order to demonstrate compliance with Condition E.1.2, the Permittee shall perform PM testing of the following facilities:

- (1) classifier #1, connected pneumatically to a baghouse, identified as E, exhausted to Stack E,
- (2) one (1) of the six (6) silos, identified as Red, Green, Blue, Yellow, Pink and Orange, connected pneumatically to baghouses, identified as F, G, H, I, J and K, exhausted to Stacks F, G, H, I, J and K, respectively,
- (3) one (1) of the three (3) silos, identified as Silo #15, Silo #16 and Silo #17, connected pneumatically to baghouses, identified as AO, AS and AT, exhausted to Stacks AO, AS and AT,
- (4) classifier #2, connected pneumatically to a baghouse, identified as BA installed in 1995, exhausted to Stack BA,
- (5) Pellet Mill Transfer, connected pneumatically to a baghouse, identified as BB, exhausted to Stack BB,
- (6) product recycling bin, connected pneumatically to a baghouse, identified as BC, exhausted to Stack BC,
- (7) R1 bin, connected pneumatically to a baghouse, identified as BD, exhausted to Stack BD,
- (8) auto packaging machine operation, connected pneumatically to a baghouse, identified as BF, exhausted to Stack BF,
- (9) cosmetic circuit receiver, connected pneumatically to a baghouse, identified as BG, exhausted to Stack BG,
- (10) bulk truck loadout operation, connected pneumatically to a baghouse, identified as BH, exhausted to Stack BH,
- (11) bulk railcar loadout operation, connected pneumatically to a baghouse, identified as BI, exhausted to Stack BI,

utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with the provisions of 326 IAC 3-6 (Source Sampling Procedures). Section C - Performance Testing contains the Permittee's obligation with regard to the performance testing required by this condition.

(b) In order to demonstrate compliance with Condition E.1.2, no later than five (5) years from the most recent valid compliance demonstration, the Permittee shall perform PM and opacity testing of one (1) of the two (2) silos, identified as North and South, connected pneumatically to baghouses, identified as B and C, exhausted to Stacks B and C, utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with the provisions of 326 IAC 3-6 (Source Sampling Procedures). Section C -

Performance Testing contains the Permittee's obligation with regard to the performance testing required by this condition.

- (c) In order to demonstrate compliance with Condition E.1.2, no later than five (5) years from the most recent valid compliance demonstration, the Permittee shall perform PM and opacity testing of one (1) of the eleven (11) silos, identified as Silos #1 through #11, connected pneumatically to baghouses, identified as N through X, exhausted to Stacks N through X, respectively, utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with the provisions of 326 IAC 3-6 (Source Sampling Procedures). Section C - Performance Testing contains the Permittee's obligation with regard to the performance testing required by this condition.
- (d) In order to demonstrate compliance with Conditions E.1.2 and E.2.2, no later than five (5) years from the most recent valid compliance demonstration, the Permittee shall perform PM and opacity testing of the pellet mill and natural gas-fired dryer, identified as Pellet Mill, connected pneumatically to a baghouse, identified as AY, exhausted to Stack AY, utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with the provisions of 326 IAC 3-6 (Source Sampling Procedures). Section C - Performance Testing contains the Permittee's obligation with regard to the performance testing required by this condition.
- (e) In order to demonstrate compliance with Condition E.1.2, no later than five (5) years from the most recent valid compliance demonstration, the Permittee shall perform PM and opacity testing of the classifier #3, connected pneumatically to a baghouse, identified as AC, exhausted to Stack AC, utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the last most recent compliance demonstration. Testing shall be conducted in accordance with the provisions of 326 IAC 3-6 (Source Sampling Procedures). Section C - Performance Testing contains the Permittee's obligation with regard to the performance testing required by this condition.
- (f) In order to demonstrate compliance with Condition E.1.2, no later than five (5) years from the most recent valid compliance demonstration, the Permittee shall perform PM and opacity testing of either the single air mill (powder), connected pneumatically to a baghouse, identified as AP, exhausted to Stack AP, or the #3 air mill, connected pneumatically to a baghouse, identified as AX, exhausted to Stack AX, utilizing methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with the provisions of 326 IAC 3-6 (Source Sampling Procedures). Section C - Performance Testing contains the Permittee's obligation with regard to the performance testing required by this condition.

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.6 Visible Emissions Notations

- (a) Visible emission notations of the talc, barite and calcium carbonate processing stack exhausts, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through BJ, shall be performed once per day during normal day-light operations. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.

- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed, the Permittee shall take reasonable response. Section C- Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.

D.1.7 Baghouse Parametric Monitoring

- (a) The Permittee shall record the pressure drop across the baghouses, identified as B through Z, AA through AC, AG through AM, AY, BA through BD and BF through BJ, used in conjunction with the talc, barite and calcium carbonate processing facilities at least once per day when these facilities are in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 3.0 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response. Section C- Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. A pressure reading that is outside the above-mentioned range is not a deviation from this permit. Failure to take response steps shall be considered a deviation from this permit.
- (b) The Permittee shall record the pressure drop across the baghouses, identified as AO, AP and AS through AX, used in conjunction with the talc, barite and calcium carbonate processing facilities at least once per day when these facilities are in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 3.0 and 5.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response. Section C- Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. A pressure reading that is outside the above-mentioned range is not a deviation from this permit. Failure to take response steps shall be considered a deviation from this permit.
- (c) The instrument used for determining the pressure shall comply with Section C - Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated at least once every six (6) months.

D.1.8 Broken or Failed Bag Detection

- (a) For a single compartment baghouse controlling emissions from a process operated continuously, a failed unit and the associated process shall be shut down immediately until the failed unit has been repaired or replaced.
- (b) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit has been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in the emissions unit.

Bag failure can be indicated by a significant drop in the baghouse's pressure reading with abnormal visible emissions, by an opacity violation, or by other means such as gas temperature, flow rate, air infiltration, or leaks.

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.9 Record Keeping Requirements

- (a) To document the compliance status with Condition D.1.6, the Permittee shall maintain a daily record of visible emission notations of the talc, barite and calcium carbonate processing baghouse stack exhausts, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through BJ. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g., the roller miller exhausted to Stack D did not operate that day).
- (b) To document the compliance status with Condition D.1.7, the Permittee shall maintain a daily record of the pressure drop across the baghouses, identified as B through Z, AA through AC, AG through AM, AO and AP, AS through AY, BA through BD and BF through BJ, controlling talc, barite and calcium carbonate processing facilities. The Permittee shall include in its daily record when a pressure drop reading is not taken and the reason for the lack of a pressure drop reading, (e.g., the roller miller did not operate that day).
- (c) Section C - General Record Keeping Requirements contains the Permittee's obligations with regard to the records required by this condition.

SECTION E.1

EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description: NSPS Subpart OOO for:

- (a) One (1) grinding plant, installed in 1991, exhausted to Stacks A through K and M controlled by twelve (12) baghouses, identified as A through K and M, capacity: 14.0 tons of talc, barite or calcium carbonate per hour, consisting of the following:
 - (2) Two (2) silos, identified as North and South, connected pneumatically to baghouses, identified as B and C, exhausted to Stacks B and C, throughput capacity: 35.0 tons of ore per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (4) One (1) classifier #1, connected pneumatically to a baghouse, identified as E, exhausted to Stack E, throughput capacity: 10.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a screening operation and is an affected facility.
 - (5) Six (6) silos, identified as Red, Green, Blue, Yellow, Pink and Orange, connected pneumatically to baghouses, identified as F, G, H, I, J and K, exhausted to Stacks F, G, H, I, J and K, respectively, throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (b) Four (4) silos, identified as Silo #1, Silo #2, Silo #3 and Silo #4, installed in 1994, connected pneumatically to baghouses, identified as N, O, P and Q, exhausted to Stacks N, O, P and Q, respectively, capacity: 8,313 cubic feet, each, and throughput capacity: 14.0 tons of minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (c) Two (2) silos, identified as Silo #5 and Silo #6, installed in 1994, connected pneumatically to baghouses, identified as R and S, exhausted to Stacks R and S, capacity: 6,107 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (d) Five (5) silos, identified as Silo #7, Silo #8, Silo #9, Silo #10 and Silo #11, installed in 1994, connected pneumatically to baghouses, identified as T, U, V, W and X, exhausted to Stacks T, U, V, W and X, respectively, capacity: 11,083 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (e) One (1) hammer mill micronizer, identified as #1 Bepex, manufactured on December 10, 1974, installed in 1994, connected pneumatically to a baghouse, identified as Y, exhausted to Stack Y, capacity: 1.00 ton of nonmetallic minerals per hour.
- (f) One (1) ball mill micronizer, identified as Ball Mill, manufactured on January 25, 1950, connected pneumatically to a baghouse, identified as Z, exhausted to Stack Z, capacity: 7.5 tons of nonmetallic minerals per hour, two (2) silos, identified as Silo #12 connected pneumatically to a baghouse, identified as AA, throughput capacity: 14.0 tons of nonmetallic minerals per hour, and Silo #13, connected pneumatically to a baghouse, identified as AB, throughput capacity: 35.0 tons of ore per hour, exhausted to Stacks AA and AB, capacity: 6,688 cubic feet, each and one (1) classifier #3, installed in 1994, connected pneumatically to a baghouse, identified as AC, exhausted to Stack AC, capacity: 10.0 tons of minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, Silo #12 and #13 are storage bins and are affected facilities and the classifier #3 is a screening operation and is an affected facility.

Emissions Unit Description: NSPS Subpart OOO for: (continued)

- (g) One (1) pellet mill and natural gas-fired dryer, identified as Pellet Mill, installed in 1996, connected pneumatically to a baghouse, identified as AY, installed in 2006, exhausted to Stack AY, capacity: 8.0 tons of nonmetallic minerals per hour and rated at 6.0 million British thermal units per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility. Under NSPS, 40 CFR Part 60.730, Subpart UUU, the dryer is an affected facility.
- (h) Five (5) material storage silos, identified as Silo A, Silo B, Silo C, Silo D and Silo #14, exhausted to Stacks AG, AH, AI, AJ and AK, respectively, connected pneumatically to baghouses, identified as AG, AH, AI, AJ and AK, respectively, installed in 1997, capacity: 12,038 cubic feet, each, and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Silos A, B, C and D are also connected pneumatically to a common baghouse, identified as AM for unloading/transfer purposes, throughput capacity: 14.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
- (i) One (1) Bepex/Air Mill Room, capacity: 2.0 tons of nonmetallic minerals per hour, consisting of:
 - (1) Three (3) silos, identified as Silo #15, Silo #16 and Silo #17, connected pneumatically to baghouses, identified as AO, AS and AT, exhausted to Stacks AO, AS and AT, throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (2) One (1) single air mill (powder), connected pneumatically to a baghouse, identified as AP, exhausted to Stack AP, throughput capacity: 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (j) One (1) twin air mill, connected pneumatically to a baghouse, identified as AU, exhausted to Stack AU, installed in 2004, capacity: 2.0 tons of talc per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (k) One (1) air jet milling system, installed in 2005, capacity of 2.5 tons of nonmetallic minerals per hour, consisting of:
 - (1) Two (2) silos, identified as Silo #18 and Silo #19, connected pneumatically to baghouses, identified as AV, and AW, exhausted to Stacks AV and AW, capacity; 3,950 cubic feet, each and throughput capacity: 14.0 tons of nonmetallic minerals per hour, each. Under NSPS, 40 CFR Part 60.670, Subpart OOO, these are storage bins and are affected facilities.
 - (2) One (1) #3 air mill, connected pneumatically to a baghouse, identified as AX, exhausted to Stack AX, capacity 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.
- (l) One (1) classifier #2, connected pneumatically to a baghouse, identified as BA installed in 1995, exhausted to Stack BA, capacity: 10.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a screening operation and is an affected facility.
- (m) One (1) Pellet Mill Transfer, pneumatically connected to a baghouse, identified as BB, installed in 1999, exhausted to Stack BB, capacity: 4.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a pneumatic system and is an affected facility.

Emissions Unit Description: NSPS Subpart OOO for: (continued)

- (n) One (1) product recycling bin, connected pneumatically to a baghouse, identified as BC, installed in 2001, exhausted to Stack BC, capacity: 5.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a storage bin and is an affected facility.
- (o) One (1) R1 bin, connected pneumatically to a baghouse, identified as BD, installed in 1994, exhausted to Stack BD, capacity: 25.0 tons of ore per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a storage bin and is an affected facility.
- (p) One (1) auto packaging machine operation, connected pneumatically to a baghouse, identified as BF, installed in 2002, exhausted to Stack BF, capacity: 8.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a bagging operation and is an affected facility.
- (q) One (1) cosmetic circuit receiver, connected pneumatically to a baghouse, identified as BG, installed in 1992, exhausted to Stack BG, capacity: 7.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a pneumatic system and is an affected facility.
- (r) One (1) bulk truck loadout operation, connected pneumatically to a baghouse, identified as BH, installed in 1996, exhausted to Stack BH, capacity: 16.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a loading station and is an affected facility.
- (s) One (1) bulk railcar loadout operation, connected pneumatically to a baghouse, identified as BI, installed in 1997, exhausted to Stack BI, capacity: 8.0 tons of nonmetallic minerals per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a loading station and is an affected facility.
- (t) One (1) twin air jet milling system, identified as BJ, consisting of mills # 5 & 6, approved for construction in 2010, for dry material size reduction of talc products, with a maximum throughput capacity of two (2.0) tons of talc per hour, connected pneumatically to one (1) integral baghouse, identified as BJ, for product reclamation, and exhausting outside the building through Stack BJ. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

New Source Performance Standards (NSPS) Requirements [326 IAC 2-6]

E.1.1 General Provisions Relating to NSPS Subpart OOO [326 IAC 12] [40 CFR Part 60, Subpart A]

Pursuant to 40 CFR 60.670, the Permittee shall comply with the provisions of 40 CFR Part 60, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 12 for the talc, barite and calcium carbonate processing source, as specified in Table 1 of 40 CFR Part 60, Subpart OOO in accordance with schedule in 40 CFR 60 Subpart OOO.

E.1.2 NSPS Subpart OOO Requirements [40 CFR Part 60, Subpart OOO] [326 IAC 12]

Pursuant to CFR Part 60, Subpart OOO, the Permittee shall comply with the provisions of 40 CFR Part 60, Subpart OOO, which are incorporated by reference as 326 IAC 12 for the facilities listed in Section E.1 as specified as follows.

Subpart 000—Standards of Performance for Nonmetallic Mineral Processing Plants

Source: 51 FR 31337, Aug. 1, 1985, unless otherwise noted.

§ 60.670 Applicability and designation of affected facility.

(a)(1) Except as provided in paragraphs (a)(2), (b), (c), and (d) of this section, the provisions of this subpart are applicable to the following affected facilities in fixed or portable nonmetallic mineral processing plants: each crusher, grinding mill, screening operation, bucket elevator, belt conveyor, bagging operation, storage bin, enclosed truck or railcar loading station. Also, crushers and grinding mills at hot mix asphalt facilities that reduce the size of nonmetallic minerals embedded in recycled asphalt pavement and subsequent affected facilities up to, but not including, the first storage silo or bin are subject to the provisions of this subpart.

(2) The provisions of this subpart do not apply to the following operations: All facilities located in underground mines; and stand-alone screening operations at plants without crushers or grinding mills.

(b) An affected facility that is subject to the provisions of subpart F or I or that follows in the plant process any facility subject to the provisions of subparts F or I of this part is not subject to the provisions of this subpart.

(c) Facilities at the following plants are not subject to the provisions of this subpart:

(1) Fixed sand and gravel plants and crushed stone plants with capacities, as defined in §60.671, of 23 megagrams per hour (25 tons per hour) or less;

(2) Portable sand and gravel plants and crushed stone plants with capacities, as defined in §60.671, of 136 megagrams per hour (150 tons per hour) or less; and

(3) Common clay plants and pumice plants with capacities, as defined in §60.671, of 9 megagrams per hour (10 tons per hour) or less.

(d)(1) When an existing facility is replaced by a piece of equipment of equal or smaller size, as defined in §60.671, having the same function as the existing facility, the new facility is exempt from the provisions of §§60.672, 60.674, and 60.675 except as provided for in paragraph (d)(3) of this section.

(2) An owner or operator complying with paragraph (d)(1) of this section shall submit the information required in §60.676(a).

(3) An owner or operator replacing all existing facilities in a production line with new facilities does not qualify for the exemption described in paragraph (d)(1) of this section and must comply with the provisions of §§60.672, 60.674 and 60.675.

(e) An affected facility under paragraph (a) of this section that commences construction, reconstruction, or modification after August 31, 1983 is subject to the requirements of this part.

(f) Table 1 of this subpart specifies the provisions of subpart A of this part 60 that apply and those that do not apply to owners and operators of affected facilities subject to this subpart.

Table 1_Applicability of Subpart A to Subpart 000

Subpart A reference	Applies to Subpart 000	Comment
60.1, Applicability.....	Yes.....	

60.2, Definitions.....	Yes.....	
60.3, Units and abbreviations.....	Yes.....	
60.4, Address:		
(a).....	Yes.....	
(b).....	Yes.....	
60.5, Determination of construction or modification.	Yes.....	
60.6, Review of plans.....	Yes.....	
60.7, Notification and recordkeeping..	Yes.....	Except in (a)(2) report of anticipated date of initial startup is not required (§ 60.676(h)).
60.8, Performance tests.....	Yes.....	Except in (d), after 30 days notice for an initially scheduled performance test, any rescheduled performance test requires 7 days notice, not 30 days (§ 60.675(g)).
60.9, Availability of information.....	Yes.....	
60.10, State authority.....	Yes.....	
60.11, Compliance with standards and	Yes.....	Except in (b) under certain conditions maintenance requirements. (§§ 60.675 (c)(3) and (c)(4)), Method 9 observation may be reduced from 3 hours to 1 hour. Some affected facilities exempted from Method 9 tests (§ 60.675(h)).
60.12, Circumvention.....	Yes.....	
60.13, Monitoring requirements.....	Yes.....	
60.14, Modification.....	Yes.....	
60.15, Reconstruction.....	Yes.....	
60.16, Priority list.....	Yes.....	
60.17, Incorporations by reference....	Yes.....	
60.18, General control device.....	No.....	Flares will not be used to comply with the emission limits.
60.19, General notification and reporting requirements.	Yes.....	

[51 FR 31337, Aug. 1, 1985, as amended at 62 FR 31359, June 9, 1997]

§ 60.671 Definitions.

All terms used in this subpart, but not specifically defined in this section, shall have the meaning given them in the Act and in subpart A of this part.

Bagging operation means the mechanical process by which bags are filled with nonmetallic minerals.

Belt conveyor means a conveying device that transports material from one location to another by means of an endless belt that is carried on a series of idlers and routed around a pulley at each end.

Bucket elevator means a conveying device of nonmetallic minerals consisting of a head and foot assembly which supports and drives an endless single or double strand chain or belt to which buckets are attached.

Building means any frame structure with a roof.

Capacity means the cumulative rated capacity of all initial crushers that are part of the plant.

Capture system means the equipment (including enclosures, hoods, ducts, fans, dampers, etc.) used to capture and transport particulate matter generated by one or more process operations to a control device.

Control device means the air pollution control equipment used to reduce particulate matter emissions released to the atmosphere from one or more process operations at a nonmetallic mineral processing plant.

Conveying system means a device for transporting materials from one piece of equipment or location to another location within a plant. Conveying systems include but are not limited to the following: Feeders, belt conveyors, bucket elevators and pneumatic systems.

Crusher means a machine used to crush any nonmetallic minerals, and includes, but is not limited to, the following types: jaw, gyratory, cone, roll, rod mill, hammermill, and impactor.

Enclosed truck or railcar loading station means that portion of a nonmetallic mineral processing plant where nonmetallic minerals are loaded by an enclosed conveying system into enclosed trucks or railcars.

Fixed plant means any nonmetallic mineral processing plant at which the processing equipment specified in §60.670(a) is attached by a cable, chain, turnbuckle, bolt or other means (except electrical connections) to any anchor, slab, or structure including bedrock.

Fugitive emission means particulate matter that is not collected by a capture system and is released to the atmosphere at the point of generation.

Grinding mill means a machine used for the wet or dry fine crushing of any nonmetallic mineral. Grinding mills include, but are not limited to, the following types: hammer, roller, rod, pebble and ball, and fluid energy. The grinding mill includes the air conveying system, air separator, or air classifier, where such systems are used.

Initial crusher means any crusher into which nonmetallic minerals can be fed without prior crushing in the plant.

Nonmetallic mineral means any of the following minerals or any mixture of which the majority is any of the following minerals:

(a) Crushed and Broken Stone, including Limestone, Dolomite, Granite, Traprock, Sandstone, Quartz, Quartzite, Marl, Marble, Slate, Shale, Oil Shale, and Shell.

(b) Sand and Gravel.

(c) Clay including Kaolin, Fireclay, Bentonite, Fuller's Earth, Ball Clay, and Common Clay.

(d) Rock Salt.

(e) Gypsum.

(f) Sodium Compounds, including Sodium Carbonate, Sodium Chloride, and Sodium Sulfate.

(g) Pumice.

(h) Gilsonite.

(i) Talc and Pyrophyllite.

- (j) Boron, including Borax, Kernite, and Colemanite.
- (k) Barite.
- (l) Fluorospar.
- (m) Feldspar.
- (n) Diatomite.
- (o) Perlite.
- (p) Vermiculite.
- (q) Mica.
- (r) Kyanite, including Andalusite, Sillimanite, Topaz, and Dumortierite.

Nonmetallic mineral processing plant means any combination of equipment that is used to crush or grind any nonmetallic mineral wherever located, including lime plants, power plants, steel mills, asphalt concrete plants, portland cement plants, or any other facility processing nonmetallic minerals except as provided in §60.670 (b) and (c).

Portable plant means any nonmetallic mineral processing plant that is mounted on any chassis or skids and may be moved by the application of a lifting or pulling force. In addition, there shall be no cable, chain, turnbuckle, bolt or other means (except electrical connections) by which any piece of equipment is attached or clamped to any anchor, slab, or structure, including bedrock that must be removed prior to the application of a lifting or pulling force for the purpose of transporting the unit.

Production line means all affected facilities (crushers, grinding mills, screening operations, bucket elevators, belt conveyors, bagging operations, storage bins, and enclosed truck and railcar loading stations) which are directly connected or are connected together by a conveying system.

Screening operation means a device for separating material according to size by passing undersize material through one or more mesh surfaces (screens) in series, and retaining oversize material on the mesh surfaces (screens).

Size means the rated capacity in tons per hour of a crusher, grinding mill, bucket elevator, bagging operation, or enclosed truck or railcar loading station; the total surface area of the top screen of a screening operation; the width of a conveyor belt; and the rated capacity in tons of a storage bin.

Stack emission means the particulate matter that is released to the atmosphere from a capture system.

Storage bin means a facility for storage (including surge bins) or nonmetallic minerals prior to further processing or loading.

Transfer point means a point in a conveying operation where the nonmetallic mineral is transferred to or from a belt conveyor except where the nonmetallic mineral is being transferred to a stockpile.

Truck dumping means the unloading of nonmetallic minerals from movable vehicles designed to transport nonmetallic minerals from one location to another. Movable vehicles include but are not limited to: trucks, front end loaders, skip hoists, and railcars.

Vent means an opening through which there is mechanically induced air flow for the purpose of exhausting from a building air carrying particulate matter emissions from one or more affected facilities.

Wet mining operation means a mining or dredging operation designed and operated to extract any nonmetallic mineral regulated under this subpart from deposits existing at or below the water table, where the nonmetallic mineral is saturated with water.

Wet screening operation means a screening operation at a nonmetallic mineral processing plant which removes unwanted material or which separates marketable fines from the product by a washing process which is designed and operated at all times such that the product is saturated with water.

[51 FR 31337, Aug. 1, 1985, as amended at 62 FR 31359, June 9, 1997]

§ 60.672 Standard for particulate matter.

(a) On and after the date on which the performance test required to be conducted by §60.8 is completed, no owner or operator subject to the provisions of this subpart shall cause to be discharged into the atmosphere from any transfer point on belt conveyors or from any other affected facility any stack emissions which:

(1) Contain particulate matter in excess of 0.05 g/dscm (0.022 gr/dscf); and

(2) Exhibit greater than 7 percent opacity, unless the stack emissions are discharged from an affected facility using a wet scrubbing control device. Facilities using a wet scrubber must comply with the reporting provisions of §60.676 (c), (d), and (e).

(b) On and after the sixtieth day after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under §60.11 of this part, no owner or operator subject to the provisions of this subpart shall cause to be discharged into the atmosphere from any transfer point on belt conveyors or from any other affected facility any fugitive emissions which exhibit greater than 10 percent opacity, except as provided in paragraphs (c), (d), and (e) of this section.

(c) On and after the sixtieth day after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under §60.11 of this part, no owner or operator shall cause to be discharged into the atmosphere from any crusher, at which a capture system is not used, fugitive emissions which exhibit greater than 15 percent opacity.

(d) Truck dumping of nonmetallic minerals into any screening operation, feed hopper, or crusher is exempt from the requirements of this section.

(e) If any transfer point on a conveyor belt or any other affected facility is enclosed in a building, then each enclosed affected facility must comply with the emission limits in paragraphs (a), (b) and (c) of this section, or the building enclosing the affected facility or facilities must comply with the following emission limits:

(1) No owner or operator shall cause to be discharged into the atmosphere from any building enclosing any transfer point on a conveyor belt or any other affected facility any visible fugitive emissions except emissions from a vent as defined in §60.671.

(2) No owner or operator shall cause to be discharged into the atmosphere from any vent of any building enclosing any transfer point on a conveyor belt or any other affected facility emissions which exceed the stack emissions limits in paragraph (a) of this section.

(f) On and after the sixtieth day after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under §60.11 of this part, no owner or operator shall cause to be discharged into the atmosphere from any baghouse that controls emissions from only an individual, enclosed storage bin, stack emissions which exhibit greater than 7 percent opacity.

[51 FR 31337, Aug. 1, 1985, as amended at 62 FR 31359, June 9, 1997; 65 FR 61778, Oct. 17, 2000]

§ 60.673 Reconstruction.

(a) The cost of replacement of ore-contact surfaces on processing equipment shall not be considered in calculating either the “fixed capital cost of the new components” or the “fixed capital cost that would be required to construct a comparable new facility” under §60.15. Ore-contact surfaces are crushing surfaces; screen meshes, bars, and plates; conveyor belts; and elevator buckets.

(b) Under §60.15, the “fixed capital cost of the new components” includes the fixed capital cost of all depreciable components (except components specified in paragraph (a) of this section) which are or will be replaced pursuant to all continuous programs of component replacement commenced within any 2-year period following August 31, 1983.

§ 60.675 Test methods and procedures.

(a) In conducting the performance tests required in §60.8, the owner or operator shall use as reference methods and procedures the test methods in appendix A of this part or other methods and procedures as specified in this section, except as provided in §60.8(b). Acceptable alternative methods and procedures are given in paragraph (e) of this section.

(b) The owner or operator shall determine compliance with the particulate matter standards in §60.672(a) as follows:

(1) Method 5 or Method 17 shall be used to determine the particulate matter concentration. The sample volume shall be at least 1.70 dscm (60 dscf). For Method 5, if the gas stream being sampled is at ambient temperature, the sampling probe and filter may be operated without heaters. If the gas stream is above ambient temperature, the sampling probe and filter may be operated at a temperature high enough, but no higher than 121 °C (250 °F), to prevent water condensation on the filter.

(2) Method 9 and the procedures in §60.11 shall be used to determine opacity.

(c)(1) In determining compliance with the particulate matter standards in §60.672 (b) and (c), the owner or operator shall use Method 9 and the procedures in §60.11, with the following additions:

(i) The minimum distance between the observer and the emission source shall be 4.57 meters (15 feet).

(ii) The observer shall, when possible, select a position that minimizes interference from other fugitive emission sources (e.g., road dust). The required observer position relative to the sun (Method 9, Section 2.1) must be followed.

(2) In determining compliance with the opacity of stack emissions from any baghouse that controls emissions only from an individual enclosed storage bin under §60.672(f) of this subpart, using Method 9, the duration of the Method 9 observations shall be 1 hour (ten 6-minute averages).

(3) When determining compliance with the fugitive emissions standard for any affected facility described under §60.672(b) of this subpart, the duration of the Method 9 observations may be reduced from 3 hours (thirty 6-minute averages) to 1 hour (ten 6-minute averages) only if the following conditions apply:

(i) There are no individual readings greater than 10 percent opacity; and

(ii) There are no more than 3 readings of 10 percent for the 1-hour period.

(4) When determining compliance with the fugitive emissions standard for any crusher at which a capture

system is not used as described under §60.672(c) of this subpart, the duration of the Method 9 observations may be reduced from 3 hours (thirty 6-minute averages) to 1 hour (ten 6-minute averages) only if the following conditions apply:

(i) There are no individual readings greater than 15 percent opacity; and

(ii) There are no more than 3 readings of 15 percent for the 1-hour period.

(d) In determining compliance with §60.672(e), the owner or operator shall use Method 22 to determine fugitive emissions. The performance test shall be conducted while all affected facilities inside the building are operating. The performance test for each building shall be at least 75 minutes in duration, with each side of the building and the roof being observed for at least 15 minutes.

(e) The owner or operator may use the following as alternatives to the reference methods and procedures specified in this section:

(1) For the method and procedure of paragraph (c) of this section, if emissions from two or more facilities continuously interfere so that the opacity of fugitive emissions from an individual affected facility cannot be read, either of the following procedures may be used:

(i) Use for the combined emission stream the highest fugitive opacity standard applicable to any of the individual affected facilities contributing to the emissions stream.

(ii) Separate the emissions so that the opacity of emissions from each affected facility can be read.

(g) If, after 30 days notice for an initially scheduled performance test, there is a delay (due to operational problems, etc.) in conducting any rescheduled performance test required in this section, the owner or operator of an affected facility shall submit a notice to the Administrator at least 7 days prior to any rescheduled performance test.

[54 FR 6680, Feb. 14, 1989, as amended at 62 FR 31360, June 9, 1997]

§ 60.676 Reporting and recordkeeping.

(a) Each owner or operator seeking to comply with §60.670(d) shall submit to the Administrator the following information about the existing facility being replaced and the replacement piece of equipment.

(1) For a crusher, grinding mill, bucket elevator, bagging operation, or enclosed truck or railcar loading station:

(i) The rated capacity in megagrams or tons per hour of the existing facility being replaced and

(ii) The rated capacity in tons per hour of the replacement equipment.

(2) For a screening operation:

(i) The total surface area of the top screen of the existing screening operation being replaced and

(ii) The total surface area of the top screen of the replacement screening operation.

(3) For a conveyor belt:

(i) The width of the existing belt being replaced and

(ii) The width of the replacement conveyor belt.

(4) For a storage bin:

(i) The rated capacity in megagrams or tons of the existing storage bin being replaced and

(ii) The rated capacity in megagrams or tons of replacement storage bins.

(f) The owner or operator of any affected facility shall submit written reports of the results of all performance tests conducted to demonstrate compliance with the standards set forth in §60.672 of this subpart, including reports of opacity observations made using Method 9 to demonstrate compliance with §60.672(b), (c), and (f), and reports of observations using Method 22 to demonstrate compliance with §60.672(e).

(h) The subpart A requirement under §60.7(a)(2) for notification of the anticipated date of initial startup of an affected facility shall be waived for owners or operators of affected facilities regulated under this subpart.

(i) A notification of the actual date of initial startup of each affected facility shall be submitted to the Administrator.

(1) For a combination of affected facilities in a production line that begin actual initial startup on the same day, a single notification of startup may be submitted by the owner or operator to the Administrator. The notification shall be postmarked within 15 days after such date and shall include a description of each affected facility, equipment manufacturer, and serial number of the equipment, if available.

(j) The requirements of this section remain in force until and unless the Agency, in delegating enforcement authority to a State under section 111(c) of the Act, approves reporting requirements or an alternative means of compliance surveillance adopted by such States. In that event, affected facilities within the State will be relieved of the obligation to comply with the reporting requirements of this section, provided that they comply with requirements established by the State.

[51 FR 31337, Aug. 1, 1985, as amended at 54 FR 6680, Feb. 14, 1989; 62 FR 31360, June 9, 1997; 65 FR 61778, Oct. 17, 2000]

SECTION E.2

EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description: NSPS Subpart UUU for:

- (g) One (1) pellet mill and natural gas-fired dryer, identified as Pellet Mill, installed in 1996, pneumatically connected to a baghouse, identified as AY, installed in 2006, exhausted to Stack AY, capacity: 8.0 tons of nonmetallic minerals per hour and rated at 6.0 million British thermal units per hour. Under NSPS, 40 CFR Part 60.670, Subpart OOO, this is a grinding mill and is an affected facility. Under NSPS, 40 CFR Part 60.730, Subpart UUU, the dryer is an affected facility.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

New Source Performance Standards (NSPS) Requirements [326 IAC 2-6]

E.2.1 General Provisions Relating to NSPS Subpart OOO [326 IAC 12] [40 CFR Part 60, Subpart A]

Pursuant to 40 CFR 60.736, the Permittee shall comply with the provisions of 40 CFR Part 60, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 12 for the natural gas-fired dryer, as specified in 40 CFR Part 60, Subpart UUU in accordance with schedule in 40 CFR 60 Subpart UUU.

E.2.2 NSPS Subpart UUU Requirements [40 CFR Part 60, Subpart UUU] [326 IAC 12]

Pursuant to CFR Part 60, Subpart UUU, the Permittee shall comply with the provisions of 40 CFR Part 60, Subpart UUU, which are incorporated by reference as 326 IAC 12 for the natural gas-fired dryer, identified as part of the Pellet Mill as specified as follows.

Subpart UUU—Standards of Performance for Calciners and Dryers in Mineral Industries

Source: 57 FR 44503, Sept. 28, 1992, unless otherwise noted.

§ 60.730 Applicability and designation of affected facility.

(a) The affected facility to which the provisions of this subpart apply is each calciner and dryer at a mineral processing plant. Feed and product conveyors are not considered part of the affected facility. For the brick and related clay products industry, only the calcining and drying of raw materials prior to firing of the brick are covered.

(b) An affected facility that is subject to the provisions of subpart LL, Metallic Mineral Processing Plants, is not subject to the provisions of this subpart. Also, the following processes and process units used at mineral processing plants are not subject to the provisions of this subpart: vertical shaft kilns in the magnesium compounds industry; the chlorination-oxidation process in the titanium dioxide industry; coating kilns, mixers, and aerators in the roofing granules industry; and tunnel kilns, tunnel dryers, apron dryers, and grinding equipment that also dries the process material used in any of the 17 mineral industries (as defined in §60.731, "Mineral processing plant").

(c) The owner or operator of any facility under paragraph (a) of this section that commences construction, modification, or reconstruction after April 23, 1986, is subject to the requirements of this subpart.

§ 60.731 Definitions.

As used in this subpart, all terms not defined herein shall have the meaning given them in the Clean Air Act and in subpart A of this part.

Calciner means the equipment used to remove combined (chemically bound) water and/or gases from mineral material through direct or indirect heating. This definition includes expansion furnaces and multiple hearth furnaces.

Control device means the air pollution control equipment used to reduce particulate matter emissions released to the atmosphere from one or more affected facilities.

Dryer means the equipment used to remove uncombined (free) water from mineral material through direct or indirect heating.

Installed in series means a calciner and dryer installed such that the exhaust gases from one flow through the other and then the combined exhaust gases are discharged to the atmosphere.

Mineral processing plant means any facility that processes or produces any of the following minerals, their concentrates or any mixture of which the majority (>50 percent) is any of the following minerals or a combination of these minerals: alumina, ball clay, bentonite, diatomite, feldspar, fire clay, fuller's earth, gypsum, industrial sand, kaolin, lightweight aggregate, magnesium compounds, perlite, roofing granules, talc, titanium dioxide, and vermiculite.

§ 60.732 Standards for particulate matter.

Each owner or operator of any affected facility that is subject to the requirements of this subpart shall comply with the emission limitations set forth in this section on and after the date on which the initial performance test required by §60.8 is completed, but not later than 180 days after the initial startup, whichever date comes first. No emissions shall be discharged into the atmosphere from any affected facility that:

(a) Contains particulate matter in excess of 0.092 gram per dry standard cubic meter (g/dscm) [0.040 grain per dry standard cubic foot (gr/dscf)] for calciners and for calciners and dryers installed in series and in excess of 0.057 g/dscm (0.025 gr/dscf) for dryers; and

(b) Exhibits greater than 10 percent opacity, unless the emissions are discharged from an affected facility using a wet scrubbing control device.

[57 FR 44503, Sept. 28, 1992, as amended at 65 FR 61778, Oct. 17, 2000]

§ 60.733 Reconstruction.

The cost of replacement of equipment subject to high temperatures and abrasion on processing equipment shall not be considered in calculating either the "fixed capital cost of the new components" or the "fixed capital cost that would be required to construct a comparable new facility" under §60.15. Calciner and dryer equipment subject to high temperatures and abrasion are: end seals, flights, and refractory lining.

§ 60.734 Monitoring of emissions and operations.

(a) With the exception of the process units described in paragraphs (b), (c), and (d) of this section, the owner or operator of an affected facility subject to the provisions of this subpart who uses a dry control device to comply with the mass emission standard shall install, calibrate, maintain, and operate a continuous monitoring system to measure and record the opacity of emissions discharged into the atmosphere from the control device.

(c) The owner or operator of a ball clay rotary dryer, a diatomite rotary dryer, a feldspar fluid bed dryer, a fuller's earth rotary dryer, a gypsum rotary dryer, a gypsum flash calciner, gypsum kettle calciner, an industrial sand rotary dryer, a kaolin rotary dryer, a kaolin multiple hearth furnace, a perlite expansion furnace, a talc flash dryer, a talc rotary dryer, a titanium dioxide direct or indirect rotary dryer or a vermiculite expansion furnace who uses a dry control device is exempt from the monitoring requirements of this section.

§ 60.735 Recordkeeping and reporting requirements.

(a) Records of the measurements required in §60.734 of this subpart shall be retained for at least 2 years.

(c) Each owner or operator shall submit written reports semiannually of exceedances of control device operating parameters required to be monitored by §60.734 of this subpart. For the purpose of these reports, exceedances are defined as follows:

(1) All 6-minute periods during which the average opacity from dry control devices is greater than 10 percent; or

(d) The requirements of this section remain in force until and unless the Agency, in delegating enforcement authority to a State under section 111(c) of the Clean Air Act, approves reporting requirements or an alternative means of compliance surveillance adopted by such State. In that event, affected facilities within the State will be relieved of the obligation to comply with this section provided that they comply with the requirements established by the State.

[57 FR 44503, Sept. 28, 1992, as amended at 58 FR 40591, July 29, 1993]

§ 60.736 Test methods and procedures.

(a) In conducting the performance tests required in §60.8, the owner or operator shall use the test methods in appendix A of this part or other methods and procedures as specified in this section, except as provided in §60.8(b).

(b) The owner or operator shall determine compliance with the particulate matter standards in §60.732 as follows:

(1) Method 5 shall be used to determine the particulate matter concentration. The sampling time and volume for each test run shall be at least 2 hours and 1.70 dscm.

(2) Method 9 and the procedures in §60.11 shall be used to determine opacity from stack emissions.

§ 60.737 Delegation of authority.

(a) In delegating implementation and enforcement authority to a State under section 111(c) of the Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.

(b) Authorities which will not be delegated to States: No restrictions.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH**

**MINOR SOURCE OPERATING PERMIT
ANNUAL NOTIFICATION**

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

Source Name:	Cimbar Performance Minerals MV, LLC
Address:	2700 Bluff Road
City:	Mt. Vernon, Indiana 47620
Phone #:	812- 838-8330
MSOP #:	129-22660-00023

I hereby certify that Cimbar Performance Minerals MV. LLC is

- still in operation.
- no longer in operation.

I hereby certify that Cimbar Performance Minerals MV. LLC is

- in compliance with the requirements of MSOP 129-22660-00023.
- not in compliance with the requirements of MSOP 129-22660-00023.

Authorized Individual (typed):
Title:
Signature:
Date:

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

Noncompliance:

MALFUNCTION REPORT

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
FAX NUMBER - 317 233-6865**

**This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6
and to qualify for the exemption under 326 IAC 1-6-4.**

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?_____, 25 TONS/YEAR SULFUR DIOXIDE ?_____, 25 TONS/YEAR NITROGEN OXIDES?_____, 25 TONS/YEAR VOC ?_____, 25 TONS/YEAR HYDROGEN SULFIDE ?_____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?_____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?_____, 25 TONS/YEAR FLUORIDES ?_____, 100 TONS/YEAR CARBON MONOXIDE ?_____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?_____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?_____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?_____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?_____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF "MALFUNCTION" AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: _____ PHONE NO. () _____
LOCATION: (CITY AND COUNTY) _____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP: _____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/20____ _____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: _____
DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/20____ _____ AM/PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____

CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____

CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____

INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

*SEE PAGE 2

**Please note - This form should only be used to report malfunctions
applicable to Rule 326 IAC 1-6 and to qualify for
the exemption under 326 IAC 1-6-4.**

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

***Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

**Minor Source Operating Permit
(MSOP) Renewal
OFFICE OF AIR QUALITY**

**Cimbar Performance Minerals MV, LLC
2700 Bluff Road
Mt. Vernon, Indiana 47620**

Attachment A

**MINERAL ORE PROCESSING FACILITY
FUGITIVE DUST CONTROL PLAN**

129-28690-00023

MINERAL ORE PROCESSING FACILITY FUGITIVE DUST CONTROL PLAN

Background

Fugitive dust sources from this site can be categorized into four groups: roadways, stockpiles, ore transportation, and process bin loading (interior). Ore stockpiles are located in three areas: inside, outside, and outside-under-shed. All stockpiles are contained within 8' high concrete bunkers. All roadways are paved. Transportation is by haul truck and front-end loader. Bin loading is by front-end loader. The three mineral ores processed are Talc, Barite, and Calcium Carbonate. Total site area is seven (7.0) acres.

Plan of Control

A. Person responsible for plan implementation:

Plant Manager
2700 Bluff Rd.
Mt. Vernon, IN 47620
(812) 838-8330 ext. 235

B. Roadway Control Measures

Fugitive particulate matter emissions from paved roads shall be controlled by one or more of the following:

- (1) watering (on an as needed basis).
- (2) vehicle speed shall not exceed 10 mph.

C. Stockpiles

Fugitive particulate matter emissions from ore stockpiles shall be controlled by one or more of the following:

- (1) watering of the stockpiles (on an as needed basis).
- (2) watering around the stockpile areas (on an as needed basis).

D. Transporting

Fugitive particulate matter emissions from the transportation of ore by truck, front-end loader, etc. shall be controlled by one or more of the following methods:

- (1) tarping of all trucks used to haul incoming ore shipments to the plantsite.
- (2) minimizing the vehicular distance required for ore transfers.
- (3) maintaining ten (10) mph speed limit.
- (4) watering stockpiles (on an as needed basis).

Note: "An as-needed basis" means the frequency or quantity of application necessary to minimize visible particulate matter emissions.

E. Bin loading

Fugitive particulate matter emissions from the loading of the process bin (inside) by the front-end loader shall be controlled by one or more of the following methods:

- (1) watering of the stockpiles (on an as needed basis).
- (2) minimizing the free-fall distance into the process bin.
- (3) decreasing the rate of discharge into the process bin.
- (4) minimizing the angle of discharge into the process bin.

Records shall be kept and maintained which document all control measures and activities to be implemented in accordance with the control plan. Said records shall be available upon the request of the commissioner, and shall be retained for three (3) years.

Last Updated: May 10, 2010
Initial Submission: September 24, 2007

Reference

The Indiana Administrative Code, Title 326 Air Pollution Control Board, Article 6: Particulate Rules, weblink:
<http://www.in.gov/legislative/iac/T03260/A00060.PDF?> . See page 12 for Rule 5: Fugitive Particulate Matter Emission Limitations.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED

TO: Brett Cline
Cimbar Performance Minerals MV, LLC
2700 Bluff Rd
Mt Vernon, IN 47620

DATE: June 8, 2010

FROM: Matt Stuckey, Branch Chief
Permits Branch
Office of Air Quality

SUBJECT: Final Decision
MSOP - Notice-Only Change
129 - 29181 - 00023

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:
Paul Householder, Plant Mgr
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at jbrush@idem.IN.gov.

Final Applicant Cover letter.dot 11/30/07

Mail Code 61-53

IDEM Staff	LPOGOST 6/8/2010 Cimbar Performance Minerals MV, LLC 129 - 29181 - 00023 final)		AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING	
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204	Type of Mail: CERTIFICATE OF MAILING ONLY	

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handing Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee
											Remarks
1		Brett Cline Cimbar Performance Minerals MV, LLC 2700 Bluff Rd Mt Vernon IN 47620 (Source CAATS) Via confirmed delivery									
2		Paul Householder Plant Mgr Cimbar Performance Minerals MV, LLC 2700 Bluff Rd Mt Vernon IN 47620 (RO CAATS)									
3		Mr. Charles L. Berger Berger & Berger, Attorneys at Law 313 Main Street Evansville IN 47700 (Affected Party)									
4		Mr. Randy Brown Plumbers & Steam Fitters Union, Local 136 2300 St. Joe Industrial Park Dr Evansville IN 47720 (Affected Party)									
5		Posey County Commissioners County Courthouse, 126 E. 3rd Street Mount Vernon IN 47620 (Local Official)									
6		Mr. Bob Deig 7130 Carson School Rd Mount Vernon IN 47620 (Affected Party)									
7		Posey County Health Department 126 E. 3rd St, Coliseum Bldg Mount Vernon IN 47620-1811 (Health Department)									
8		Mount Vernon City Council and Mayors Office 520 Main Street Mount Vernon IN 47620 (Local Official)									
9		Dr. Jeff Seyler Univ. of So Ind., 8600 Univ. Blvd. Evansville IN 47712 (Affected Party)									
10		Mr. Don Mottley Save Our Rivers 6222 Yankeetown Hwy Boonville IN 47601 (Affected Party)									
11		Mrs. Connie Parkinson 510 Western Hills Dr. Mt. Vernon IN 47620 (Affected Party)									
12		Robert Hess c/o Mellon Corporation 830 Post Road East, Suite 105 Westport CT 06880 (Affected Party)									
13		Juanita Burton 7911 W. Franklin Road Evansville IN 47712 (Affected Party)									
14		Mr. John Blair 800 Adams Ave Evansville IN 47713 (Affected Party)									
15											

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See Domestic Mail Manual R900, S913, and S921 for limitations of coverage on inured and COD mail. See International Mail Manual for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
---	--	--	--