



Mitchell E. Daniels, Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
(800) 451-6027
www.IN.gov/idem

TO: Interested Parties / Applicant
DATE: Dec. 8, 2010
RE: Patrick Industries, Inc. / 039-29242-00324
FROM: Matthew Stuckey, Deputy Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision: Approval – Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-6-1(b) or IC 13-15-6-1(a) require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204.

For an **initial Title V Operating Permit**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **thirty (30)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(b).

For a **Title V Operating Permit renewal**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **fifteen (15)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(a).

The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

Pursuant to 326 IAC 2-7-18(d), any person may petition the U.S. EPA to object to the issuance of an initial Title V operating permit, permit renewal, or modification within sixty (60) days of the end of the forty-five (45) day EPA review period. Such an objection must be based only on issues that were raised with reasonable specificity during the public comment period, unless the petitioner demonstrates that it was impracticable to raise such issues, or if the grounds for such objection arose after the comment period.

To petition the U.S. EPA to object to the issuance of a Title V operating permit, contact:

U.S. Environmental Protection Agency
401 M Street
Washington, D.C. 20406

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Part 70 Operating Permit Renewal OFFICE OF AIR QUALITY

Patrick Industries, Inc.
Plant 130: 1808 West Hively Avenue, Elkhart, Indiana 46517
Plant 140: 57420 Nagy Drive, Elkhart, Indiana 46517

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T039-29242-00324	
Issued by:  Chrystal A. Wagner, Section Chief Permits Branch Office of Air Quality	Issuance Date: Dec. 8, 2010 Expiration Date: Dec. 8, 2015

TABLE OF CONTENTS

A. SOURCE SUMMARY	5
A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]	
A.2 Part 70 Source Definition [326 IAC 2-7-1(22)]	
A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]	
A.4 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.5 Part 70 Permit Applicability [326 IAC 2-7-2]	
B. GENERAL CONDITIONS	9
B.1 Definitions [326 IAC 2-7-1]	
B.2 Permit Term [326 IAC 2-7-5(2)][326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)] [IC 13-15-3-6(a)]	
B.3 Term of Conditions [326 IAC 2-1.1-9.5]	
B.4 Enforceability [326 IAC 2-7-7] [IC 13-17-12]	
B.5 Severability [326 IAC 2-7-5(5)]	
B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	
B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]	
B.8 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]	
B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]	
B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]	
B.11 Emergency Provisions [326 IAC 2-7-16]	
B.12 Permit Shield [326 IAC 2-7-15][326 IAC 2-7-20][326 IAC 2-7-12]	
B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]	
B.14 Termination of Right to Operate [326 IAC 2-7-10][326 IAC 2-7-4(a)]	
B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)][326 IAC 2-7-8(a)][326 IAC 2-7-9]	
B.16 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4][326 IAC 2-7-8(e)]	
B.17 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12] [40 CFR 72]	
B.18 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12(b)(2)]	
B.19 Operational Flexibility [326 IAC 2-7-20][326 IAC 2-7-10.5]	
B.20 Source Modification Requirement [326 IAC 2-7-10.5]	
B.21 Inspection and Entry [326 IAC 2-7-6][IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]	
B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]	
B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]	
B.24 Advanced Source Modification Approval [326 IAC 2-7-5(16)] [326 IAC 2-7-10.5]	
B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]	
C. SOURCE OPERATION CONDITIONS	20
Emission Limitations and Standards [326 IAC 2-7-5(1)]	
C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2 Opacity [326 IAC 5-1]	
C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.5 Fugitive Dust Emissions [326 IAC 6-4]	
C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
Testing Requirements [326 IAC 2-7-6(1)]	
C.7 Performance Testing [326 IAC 3-6]	
Compliance Requirements [326 IAC 2-1.1-11]	
C.8 Compliance Requirements [326 IAC 2-1.1-11]	

Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]

- C.9 Compliance Monitoring [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]
- C.10 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)]
[326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]

- C.11 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.12 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
- C.13 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)]
[326 IAC 2-6]
- C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection

- C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS - Woodworking Operations 26

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Prevention of Significant Deterioration (PSD) [326 IAC 2-2]
- D.1.2 Particulate Emissions Limitations for Manufacturing Processes [326 IAC 6-3-2]
- D.1.3 Baghouse Limitations [326 IAC 2-7-1(21)(G)(xxx)]
- D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.5 Particulate Control [40 CFR 64]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.6 Visible Emissions Notations [40 CFR 64]
- D.1.7 Baghouse Inspections [40 CFR 64]
- D.1.8 Broken or Failed Bag Detection [40 CFR 64]
- D.1.9 Storage Silo Inspections [40 CFR 64]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.10 Record Keeping Requirements

SECTION D.2 FACILITY OPERATION CONDITIONS - Surface Coating Operations..... 31

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.2.1 PSD Minor Limit [326 IAC 2-2]
- D.2.2 Particulate [326 IAC 6-3-2(d)]
- D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]
- D.2.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.2.5 Volatile Organic Compounds (VOC) [326 IAC 8-1-4] [326 IAC 8-1-2(a)]
- D.2.6 Particulate Control [326 IAC 6-3-2][326 IAC 2-2]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.2.7 Monitoring
- D.2.8 Scrubber Inspections
- D.2.9 Scrubber Malfunction

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.10 Record Keeping Requirements

D.2.11 Reporting Requirements

SECTION D.3 FACILITY OPERATION CONDITIONS - Insignificant Activities 36

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Particulate [326 IAC 6-2-4(a)]

E.1 FACILITY OPERATION CONDITION: NESHAP JJ 37

**National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements
[326 IAC 2-7-5(1)]**

E.1.1 General Provisions Relating to NESHAP Subpart JJ [326 IAC 20-1][40 CFR Part 63,
Subpart A]

E.1.2 NESHAP Subpart JJ Requirements [40 CFR Part 63, Subpart JJ]

Certification 40
Emergency Occurrence Report 41
Quarterly Report..... 43
Semi-Annual Report..... 44
Quarterly Deviation and Compliance Monitoring Report 45

Attachment A - National Emission Standards for Wood Furniture Manufacturing Operations —Subpart JJ

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1, A.3, and A.4 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary wood product manufacturing plant.

Source Address: Plant 130: 1808 West Hively Avenue, Elkhart, Indiana 46517
Plant 140: 57420 Nagy Drive, Elkhart, Indiana 46517
General Source Phone Number: 574-206-7745
SIC Code: 2434, 2421, 2431, 2541
County Location: Elkhart
Source Location Status: Attainment for all criteria pollutants
Source Status: Part 70 Operating Permit Program
Minor Source, under PSD
Major Source, Section 112 of the Clean Air Act
Not 1 of 28 Source Categories

A.2 Part 70 Source Definition [326 IAC 2-7-1(22)]

This stationary wood product manufacturing company consists of two (2) plants:

- (a) Plant 130 is located at 1808 West Hively Avenue, Elkhart, Indiana 46517; and
- (b) Plant 140 is located at 57420 Nagy Drive, Elkhart, Indiana 46517.

Since the two (2) plants are located in contiguous properties, have the same SIC codes and are owned by one (1) company, they will be considered one (1) source, effective from the date of issuance of Part 70 permit T039-7650-00324, issued on October 6, 1998.

A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

Plant 130 (1808 West Hively Avenue)

- (a) One (1) sawdust storage silo, identified as S-1, constructed in 1997, with a capacity of 690 cubic yards, collecting sawdust from the woodworking equipment through a cyclonic baghouse system, and exhausting to stack C1-1.
- (b) Woodworking equipment, identified as WW1a, constructed in 1995, with a maximum throughput of 25,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to three (3) stacks, identified as C1-2, C1-3 and C1-4
- (c) Woodworking equipment, identified as WW1b, constructed in 1995, with a maximum throughput of 25,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to two (2) stacks, identified as C1-5 and C1-6.
- (d) Woodworking equipment, identified as WW1c, constructed in 2003, having a maximum throughput capacity of 5,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to stack C1-7.

- (e) Two (2) denibbers for D1, identified as DN1a and DN1b, constructed in 2000, each with maximum capacities of 3,900 board feet per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to stack C1-4.
- (f) One (1) denibber for D4, identified as DN4, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to stack C1-4.
- (g) One (1) adhesive spray booth and one (1) wood wrapping press, identified as SA1 and WWP1, respectively, constructed in 1995, with a maximum capacity of laminating 39.143 linear feet per hour, utilizing a high volume low pressure (HVLP) application system, with particulate emissions controlled by dry filters, and exhausting to stack E1-10. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (h) One (1) dualtech automated back sealing machine, identified as D1, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D2, exhausting to stack E1-2, and a hot air drying tunnel exhausting to stack E1-3. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (i) One (1) rototech automated front staining machine, identified as D3, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) airless/air assist spray guns, with particulate emissions controlled by dry filters, exhausting to stack E1-4, and a forced air drying tunnel exhausting to stack E1-5. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (j) One (1) dualtech automated sealing machine, identified as D4, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D5, exhausting to stack E1-6, and a hot air/infrared drying tunnel exhausting to stack E1-7. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (k) One (1) dualtech automated topcoat machine, identified as D6, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D7, exhausting to stack E1-8, a hot air drying tunnel exhausting to stack E1-9, and a non-heated cooling hood exhausting inside the building. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (l) One (1) manual touch up booth, identified as TU1, constructed in 2000, with a maximum capacity of one (1) gallon of stain, two (2) gallons of sealer, and two (2) gallons of topcoat per day, consisting of one (1) airless/air assist gun, with particulate emissions controlled by dry filters, exhausting to stack TU-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (m) One (1) rototech automated back staining machine, identified as D8, constructed in 2002, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) HVLP spray guns used for coating cabinet doors and an infrared drying oven, with particulate emissions controlled by dry filters, and exhausting to stack E1-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

- (n) One (1) vacuum coater, identified as VC-1, constructed in 1995, with a maximum capacity of 5,000 linear feet of wood per hour, applying coatings containing no VOC or HAP to wood trim, utilizing an ultraviolet (UV) curing process, with particulate emissions controlled by dry filters, and exhausting to stack E1-11. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (o) One (1) manual coating booth with two (2) HVLP spray guns, identified as D-9, approved for construction in 2009, with a maximum capacity of 1000 doors per day, with particulate emissions controlled by dry filters, exhausting to stack E1-12. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (p) One (1) spray coating line, identified as SCL-1, consisting of coating equipment and electric dryer, with a throughput capacity of 250 units per hour, using manual air assisted airless spray application method, venting to stack SCLS1, and using dry filters as control. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Plant 140 (57420 Nagy Drive)

- (q) Woodworking equipment, identified as WW2a, constructed in 1995, with a maximum throughput of 3,000 pounds of wood per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-1.
- (r) Woodworking equipment, identified as WW2b, constructed in 1995, with a maximum throughput of 5,000 pounds of wood per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2.
- (s) Six (6) wood wrapping machines, identified as WR2a, WR2b, WR2c, WR2d, WR2e, and WR2f, constructed in 1995, each with a maximum capacity of 280 pounds of wood styles per hour, using water-based and hot melt adhesives, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, exhausting to stack C2-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (t) Four (4) wood panel laminating machines, identified as WPL2, constructed in 1995, each with a maximum capacity of 1,500 pounds of wood panels per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

A.4 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour:
 - (1) One (1) natural gas-fired boiler, identified as B1, constructed in 1995, rated at 0.4 MMBtu/hr, and exhausting to stack B1. [326 IAC 6-2-4]
 - (2) Four (4) natural gas-fired hot water boilers, identified as AB1, AB2, AB3, and AB4, constructed in 2000, with each rated at 1 MMBtu per hour, exhausting to stacks AB1, AB2, AB3, and AB4, respectively. [326 IAC 6-2-4]

- (b) Insignificant woodworking equipment, meeting the definition of "insignificant woodworking operation" as specified in 326 IAC 2-7-1(21)(G)(xxx), identified as WW1c, constructed in 2005, having a maximum process weight rate of 5,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, with a maximum air flow rate of 35,000 standard cubic feet of air per minute (scfm) and a maximum outlet grain loading of less than 0.003 grains per dry standard cubic foot of exhaust air, and exhausting to stack C1-7. [326 IAC 2-7-1(21)(G)(xxx)] [326 IAC 6-3-2]

A.5 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)][326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)][IC 13-15-3-6(a)]

- (a) This permit, T039-29242-00324, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit or of permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control).
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability [326 IAC 2-7-7] [IC 13-17-12]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]

- (a) A certification required by this permit meets the requirements of 326 IAC 2-7-6(1) if:
 - (i) it contains a certification by a "responsible official" as defined by 326 IAC 2-7-1(34), and
 - (ii) the certification states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) The Permittee may use the attached Certification Form, or its equivalent, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) A "responsible official" is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than April 15 of each year to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)][326 IAC 1-6-3]

(a) A Preventive Maintenance Plan meets the requirements of 326 IAC 1-6-3 if it includes, at a minimum:

- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
- (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

The Permittee shall implement the PMPs.

(b) If required by specific condition(s) in Section D of this permit where no PMP was previously required, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) no later than ninety (90) days after issuance of this permit or ninety (90) days after initial start-up, whichever is later, including the following information on each facility:

- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
- (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The PMP extension notification does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

The Permittee shall implement the PMPs.

(c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions. The PMPs and their submittal do not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, or Northern Regional Office within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance and Enforcement Branch), or
Telephone Number: 317-233-0178 (ask for Office of Air Quality, Compliance and Enforcement Branch)
Facsimile Number: 317-233-6865
Northern Regional Office phone: (574) 245-4870; fax: (574) 245-4877.

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

B.12 Permit Shield [326 IAC 2-7-15][326 IAC 2-7-20][326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to

be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.

- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]

- (a) All terms and conditions of permits established prior to T039-29242-00324 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised under 326 IAC 2-7-10.5, or
 - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit, except for permits issued pursuant to Title IV of the Clean Air Act and 326 IAC 21 (Acid Deposition Control)

B.14 Termination of Right to Operate [326 IAC 2-7-10][326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)][326 IAC 2-7-8(a)][326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require a certification that

meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.16 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4][326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
 - (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the

deadline specified, pursuant to 326 IAC 2-7-4(a)(2)(D), in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.17 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12] [40 CFR 72]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Pursuant to 326 IAC 2-7-11(b) and 326 IAC 2-7-12(a), administrative Part 70 operating permit amendments and permit modifications for purposes of the acid rain portion of a Part 70 permit shall be governed by regulations promulgated under Title IV of the Clean Air Act. [40 CFR 72]
- (c) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.18 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)][326 IAC 2-7-12(b)(2)]

- (a) No Part 70 permit revision or notice shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.19 Operational Flexibility [326 IAC 2-7-20][326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b),(c), or (e) without a prior permit revision, if each of the following conditions is met:
 - (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
 - (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b),(c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.
- (f) This condition does not apply to emission trades of SO₂ or NO_x under 326 IAC 21 or 326 IAC 10-4.

B.20 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

B.21 Inspection and Entry [326 IAC 2-7-6][IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.24 Advanced Source Modification Approval [326 IAC 2-7-5(16)] [326 IAC 2-7-10.5]

- (a) The requirements to obtain a source modification approval under 326 IAC 2-7-10.5 or a permit modification under 326 IAC 2-7-12 are satisfied by this permit for the proposed emission units, control equipment or insignificant activities in Sections A.2 and A.3.
- (b) Pursuant to 326 IAC 2-1.1-9 any permit authorizing construction may be revoked if construction of the emission unit has not commenced within eighteen (18) months from the date of issuance of the permit, or if during the construction, work is suspended for a continuous period of one (1) year or more.

B.25 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-1 (Applicability) and 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator except as provided in 326 IAC 4-2 or in this permit. The Permittee shall not operate a refuse incinerator or refuse burning equipment except as provided in 326 IAC 9-1-2 or in this permit.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:

- (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
- (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Licensed Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Licensed Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.7 Performance Testing [326 IAC 3-6]

-
- (a) For performance testing required by this permit, a test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.8 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]

C.9 Compliance Monitoring [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, for all monitoring requirements not already legally required, the Permittee shall be allowed up to ninety (90) days from the date of permit issuance or of initial start-up, whichever is later, to begin such monitoring. If due to circumstances beyond the Permittee's control, any monitoring equipment required by this permit cannot be installed and operated no later than ninety (90) days after permit issuance or the date of initial startup, whichever is later, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.10 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]

C.11 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall maintain the most recently submitted written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) Upon direct notification by IDEM, OAQ that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.12 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.13 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]

Upon detecting an excursion where a response step is required by the D Section or an exceedance of a limitation in this permit:

- (a) The Permittee shall take reasonable response steps to restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing excess emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction. The response may include, but is not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned or are returning to normal without operator action (such as through response by a computerized distribution control system);
or
 - (3) any necessary follow-up actions to return operation to normal or usual manner of operation.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records; and/or

- (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall record the reasonable response steps taken.

C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5][326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall submit a description of its response actions to IDEM, OAQ, no later than seventy-five (75) days after the date of the test.
- (b) A retest to demonstrate compliance shall be performed no later than one hundred eighty (180) days after the date of the test. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred eighty (180) days is not practicable, IDEM, OAQ may extend the retesting deadline
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.15 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

In accordance with the compliance schedule specified in 326 IAC 2-6-3(b)(1), starting in 2004 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:

- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
- (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1(32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
MC 61-50 IGCN 1003
Indianapolis, Indiana 46204-2251

The emission statement does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

C.16 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are

available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

- (b) Unless otherwise specified in this permit, for all record keeping requirements not already legally required, the Permittee shall be allowed up to ninety (90) days from the date of permit issuance or the date of initial start-up, whichever is later, to begin such record keeping.

C.17 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported except that a deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. This report shall be submitted not later than thirty (30) days after the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34). A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.
- (b) The address for report submittal is:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

Stratospheric Ozone Protection

C.18 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with applicable standards for recycling and emissions reduction.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Woodworking Operations

Plant 130 (1808 West Hively Avenue)

- (a) One (1) sawdust storage silo, identified as S-1, constructed in 1997, with a capacity of 690 cubic yards, collecting sawdust from the woodworking equipment through a cyclonic baghouse system, and exhausting to stack C1-1.
- (b) Woodworking equipment, identified as WW1a, constructed in 1995, with a maximum throughput of 25,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to three (3) stacks, identified as C1-2, C1-3 and C1-4.
- (c) Woodworking equipment, identified as WW1b, constructed in 1995, with a maximum throughput of 25,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to two (2) stacks, identified as C1-5 and C1-6.
- (d) Two (2) denibbers for D1, identified as DN1a and DN1b, constructed in 2000, each with maximum capacities of 3,900 board feet per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to stack C1-4.
- (e) One (1) denibber for D4, identified as DN4, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to stack C1-4.

Plant 140 (57420 Nagy Drive)

- (p) Woodworking equipment, identified as WW2a, constructed in 1995, with a maximum throughput of 3,000 pounds of wood per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-1.
- (q) Woodworking equipment, identified as WW2b, constructed in 1995, with a maximum throughput of 5,000 pounds of wood per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2.
- (r) Six (6) wood wrapping machines, identified as WR2a, WR2b, WR2c, WR2d, WR2e, and WR2f, constructed in 1995, each with a maximum capacity of 280 pounds of wood styles per hour, using water-based and hot melt adhesives, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, exhausting to stack C2-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (s) Four (4) wood panel laminating machines, identified as WPL2, constructed in 1995, each with a maximum capacity of 1,500 pounds of wood panels per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Insignificant Activities: Insignificant Woodworking Plant 130 (1808 West Hively Avenue)

- (b) Insignificant woodworking equipment, meeting the definition of "insignificant woodworking operation" as specified in 326 IAC 2-7-1(21)(G)(xxx), identified as WW1c, constructed in 2005, having a maximum process weight rate of 5,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, with a maximum air flow rate of 35,000

Facility Description [326 IAC 2-7-5(15)]: Woodworking (Continued)

standard cubic feet of air per minute (scfm) and a maximum outlet grain loading of less than 0.003 grains per dry standard cubic foot of exhaust air, and exhausting to stack C1-7. [326 IAC 2-7-1(21)(G)(xxx)] [326 IAC 6-3-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Prevention of Significant Deterioration (PSD) [326 IAC 2-2]

Pursuant to 326 IAC 2-2 (PSD), the particulate emissions from the significant and insignificant woodworking operations, denibbers, wood wrapping operations, laminating operations and sawdust storage silo are subject to PM/PM₁₀ emission limits as shown in the following table:

Stack ID	PM/PM ₁₀ limit (lb/hr)
C1-1	3.6
C1-2	4.2
C1-3	2.9
C1-4	9.3
C1-5	3.0
C1-6	5.3
C1-7	2.9
C2-1	4.2
C2-2	1.4

These limits, combined with the total potential to emit PM/PM₁₀ from the other emission units at this source, will ensure that the potential to emit PM/PM₁₀ remains less than 250 tons per twelve (12) consecutive month period. Compliance with these limits will render the requirements of 326 IAC 2-2 (PSD) not applicable.

D.1.2 Particulate Emissions Limitations for Manufacturing Processes [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the exhaust stacks of the baghouses and cyclones controlling the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo shall not exceed the pounds per hour limits as shown in the following table:

Particulate Emission Rate		
Exhaust Stack ID	Process Weight Rate (lbs)	Particulate Emission Rate (lb/hr)
C1-1	55,000	37.8
C1-2	11,000	12.8
C1-3	7,500	9.9
C1-4	6,500	9.0
C1-5	12,000	13.6
C1-6	13,000	14.4
C1-7	5,000	7.6
C2-1	4,680	7.2
C2-2	9,500	11.6

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

D.1.3 Baghouse Limitations [326 IAC 2-7-1(21)(G)(xxx)]

The insignificant woodworking operation (WW1c) controlled by a cyclonic baghouse shall be considered an insignificant activity for Title V permitting purposes provided that the baghouse operations meet the requirements of 326 IAC 2-7-1(21)(G)(xxx), including the following:

- (a) Each woodworking baghouse shall not exhaust to the atmosphere greater than forty thousand (40,000) cubic feet of air per minute and shall not emit particulate matter with a diameter less than ten (10) microns in excess of one hundredth (0.01) grain per dry standard cubic foot of outlet air.
- (b) The opacity from each baghouse shall not exceed ten percent (10%).
- (c) Visible emissions from the baghouse shall be observed daily using procedures in accordance with Method 22 and normal or abnormal emissions are recorded. In the event abnormal emissions are observed for greater than six (6) minutes in duration, the following shall occur:
 - (1) The baghouse shall be inspected.
 - (2) Corrective actions, such as replacing or reseating bags, are initiated, when necessary.

D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan is required for these facilities and their control devices. Section B - Preventive Maintenance Plan, of this permit, contains the Permittee's obligations with regard to the records required by this condition.

Compliance Determination Requirements

D.1.5 Particulate Control [326 IAC 6-3-2][326 IAC 2-2][326 IAC 2-7-1(21)(G)(xxx)]

In order to comply with Conditions D.1.1, D.1.2 and D.1.3, the baghouses and cyclones for particulate control shall be in operation and control emissions from the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo at all times that the woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo are in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)][326 IAC 2-7-5(1)]

D.1.6 Visible Emissions Notations [326 IAC 6-3-2][326 IAC 2-2][326 IAC 2-7-1(21)(G)(xxx)][40 CFR 64]

- (a) Daily visible emission notations of the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo stack exhausts (C1-1, C1-2, C1-3, C1-4, C1-5, C1-6, C1-7, C2-1, and C2-2), shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.

- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed at the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo stack exhausts, the Permittee shall take reasonable response. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.

D.1.7 Baghouse Inspections [40 CFR 64]

An inspection shall be performed each calendar quarter of all bags controlling the woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. All defective bags shall be replaced.

D.1.8 Broken or Failed Bag Detection

- (a) For a single compartment baghouse controlling emissions from a process operated continuously a failed unit and the associated process shall be shut down immediately until the failed unit has been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit has been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in the emissions unit. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Bag failure can be indicated by a significant drop in the baghouses pressure reading with abnormal visible emissions, by an opacity violation, or by other means such as gas temperature, flow rate, air infiltration, leaks, dust traces or triboflows.

D.1.9 Storage Silo Inspections [40 CFR 64]

An inspection of the sawdust outloading operation and storage silo shall be performed at least once every two weeks. If abnormal emissions are observed, the Permittee shall take reasonable response. Section C - Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.

Abnormal emissions can be indicated by evidence of sawdust in the area surrounding the storage silo.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-19]

D.1.10 Record Keeping Requirements

- (a) To document the compliance status with Conditions D.1.3(c) and D.1.6, the Permittee shall maintain records of daily visible emission notations of the exhaust from stacks C1-1, C1-2, C1-3, C1-4, C1-5, C1-6, C1-7, C2-1, and C2-2.

- (b) To document the compliance status with Conditions D.1.3(c), D.1.7, and D.1.9, the Permittee shall maintain records of the results of the inspections required under Conditions D.1.3(c), D.1.7, and D.1.9.
- (c) The Permittee shall maintain records of corrective actions to document the compliance status with Condition D.1.3 and 326 IAC 2-7-21(1)(G)(xxx)(GG)(dd).
- (d) Section C - General Record Keeping Requirements contains the Permittee's obligations with regard to the records required by this condition.

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: Surface Coating Operations

Plant 130 (1808 West Hively Avenue)

- (g) One (1) adhesive spray booth and one (1) wood wrapping press, identified as SA1 and WWP1, respectively, constructed in 1995, with a maximum capacity of laminating 39.143 linear feet per hour, utilizing a high volume low pressure (HVLP) application system, with particulate emissions controlled by dry filters, and exhausting to stack E1-10. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (h) One (1) dualtech automated back sealing machine, identified as D1, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D2, exhausting to stack E1-2, and a hot air drying tunnel exhausting to stack E1-3. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (i) One (1) rototech automated front staining machine, identified as D3, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) airless/air assist spray guns, with particulate emissions controlled by dry filters, exhausting to stack E1-4, and a forced air drying tunnel exhausting to stack E1-5. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (j) One (1) dualtech automated sealing machine, identified as D4, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D5, exhausting to stack E1-6, and a hot air/infrared drying tunnel exhausting to stack E1-7. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (k) One (1) dualtech automated topcoat machine, identified as D6, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D7, exhausting to stack E1-8, a hot air drying tunnel exhausting to stack E1-9, and a non-heated cooling hood exhausting inside the building. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (l) One (1) manual touch up booth, identified as TU1, constructed in 2000, with a maximum capacity of one (1) gallon of stain, two (2) gallons of sealer, and two (2) gallons of topcoat per day, consisting of one (1) airless/air assist gun, with particulate emissions controlled by dry filters, exhausting to stack TU-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (m) One (1) rototech automated back staining machine, identified as D8, constructed in 2002, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) HVLP spray guns used for coating cabinet doors and an infrared drying oven, with particulate emissions controlled by dry filters, and exhausting to stack E1-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Facility Description [326 IAC 2-7-5(15)]: (Continued)

- (n) One (1) vacuum coater, identified as VC-1, constructed in 1995, with a maximum capacity of 5,000 linear feet of wood per hour, applying coatings containing no VOC or HAP to wood trim, utilizing an ultraviolet (UV) curing process, with particulate emissions controlled by dry filters, and exhausting to stack E1-11. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (o) One (1) manual coating booth with two (2) HVLP spray guns, identified as D-9, approved for construction in 2009, with a maximum capacity of 1000 doors per day, with particulate emissions controlled by dry filters, exhausting to stack E1-12. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (p) One (1) spray coating line, identified as SCL-1, approved for construction in 2010, consisting of coating equipment and electric dryer, with a throughput capacity of 250 units per hour, using robotic air assisted airless spray application method, venting to stack SCLS1, and using dry filters as control. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Plant 140 (57420 Nagy Drive)

- (r) Six (6) wood wrapping machines, identified as WR2a, WR2b, WR2c, WR2d, WR2e, and WR2f, constructed in 1995, each with a maximum capacity of 280 pounds of wood styles per hour, using water-based and hot melt adhesives, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, exhausting to stack C2-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (s) Three (3) wood panel laminating machines, identified as WPL2, constructed in 1995, each with a maximum capacity of 1,500 pounds of wood panels per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 PSD Minor Limit [326 IAC 2-2]

- (a) The total VOC input to all the surface coating operations and laminating operations (D1, D3, D4, D6, D8, D9, TU1, SCL-1, SA1, WWP1, VC1, WR2 (a, b, c, d, e), and WPL2 (3 machines)) combined shall not exceed 249 tons per twelve (12) consecutive month period, with compliance determined on a monthly basis.

This limit, in conjunction with the uncontrolled potential to emit of the boilers, heaters and insignificant laminating operations, is equivalent to VOC emissions of less than 250 tons per year for the entire source. Compliance with this VOC usage limit makes the requirements of 326 IAC 2-2 (PSD) not applicable.

- (b) Pursuant to 326 IAC 2-2 (PSD), the particulate emissions from the surface coating operations are subject to PM/PM₁₀ emission limits as shown in the following table:

PSD Minor Limit for PM / PM10, By Stack ID	
Stack ID	PM/PM10 limit (lb/hr)
E1-1	1.1
E1-2	1.9
E1-3	1.1
E1-4	1.1
E1-5	1.1
E1-6	2.0
E1-7	1.1
E1-8	2.0
E1-9	1.1
E1-10	1.4
E1-11	1.1
TU1	1.1
E1-12	1.6
SCLS1	1.1

These limits, in combination with other PM/PM₁₀ emissions from this source, will ensure that the source-wide potential to emit PM/PM₁₀ remains less than 250 tons per twelve (12) consecutive month period.

D.2.2 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate emissions from the surface coating facilities shall be controlled by a dry particulate filter and/or water wall and water scrubber system, and the Permittee shall operate the control devices in accordance with manufacturer's specifications.

D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]

Pursuant to 326 IAC 8-2-12 (Wood Furniture and Cabinet Coating), the emission units identified as D1, D3, D4, D6, D8, D9, TU1, and SCL-1 applying surface coatings to wood furniture and cabinets shall utilize one of the following application methods:

- Airless Spray Application
- Air Assisted Airless Spray Application
- Electrostatic Spray Application
- Electrostatic Bell or Disc Application
- Heated Airless Spray Application
- Roller Coating
- Brush or Wipe Application
- Dip-and-Drain Application

High Volume Low Pressure (HVLV) Spray Application is an accepted alternative method of application for Air Assisted Airless Spray Application. HVLV spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

D.2.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan is required for these facilities and their control devices. Section B - Preventive Maintenance Plan, of this permit, contains the Permittee's obligations with regard to the records required by this condition.

Compliance Determination Requirements

D.2.5 Volatile Organic Compounds (VOC) [326 IAC 8-1-4] [326 IAC 8-1-2(a)]

Compliance with the VOC content and usage limitations contained in Conditions D.2.1(a) and D.2.3 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.2.6 Particulate Control [326 IAC 6-3-2][326 IAC 2-2]

In order to comply with Conditions D.2.1 and D.2.2, the dry particulate filters and/or water wall and water scrubber systems for particulate control shall be in operation and control emissions from the surface coating operations all times that they are in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.7 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the dry filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating facilities stacks while one (1) or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps. Section C - Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.
- (b) Daily inspections shall be performed to verify that the water level of the water wall/baffles meets the manufacturer's recommended level. To monitor the performance of the water wall/baffles, the water level shall be maintained weekly at a level where surface agitation indicates impact of the air flow. Water shall be kept free of solids and floating material that reduces the capture efficiency of the water pan. To monitor the performance of the baffles, weekly inspections of the baffle panels shall be conducted to verify placement and configuration meet recommendations of the manufacturer. In addition, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. If a noticeable change in overspray emission, or evidence of overspray emission is observed at any stack exhaust, the Permittee shall take reasonable response. Section C - Response to Excursions or Exceedances, contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.
- (c) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emission, or when evidence of overspray emissions is observed at any stack exhaust, the Permittee shall take reasonable response. Section C - Response to Excursions or Exceedances, contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.

D.2.8 Scrubber Inspections

An inspection of the scrubbers controlling emissions from the surface coating facilities shall be performed semi-annually. Inspections required by this condition shall not be performed in consecutive months. Section B - Preventive Maintenance Plan, of this permit, contains the Permittee's obligations with regard to repairs or replacement of defective components.

D.2.9 Scrubber Malfunction

In the event that a scrubber malfunction has been observed:

- (a) The affected unit will be shut down immediately in accordance with safe operating procedures until the failed unit has been repaired or the appropriate components replaced”.
- (b) Based upon the findings of the inspection, any additional corrective actions will be devised within eight (8) hours of discovery and will include a timetable for completion.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.10 Record Keeping Requirements

- (a) To document the compliance status with Condition D.2.1(a), the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits established in Condition D.2.1(a). Records necessary to demonstrate compliance shall be available not later than thirty (30) days of the end of each compliance period.
 - (1) The amount and VOC content of each coating material, dilution solvent and cleaning solvent used on a monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used;
 - (2) The total VOC usage for each month; and
 - (3) The weight of VOCs emitted for each compliance period.
- (b) To document the compliance status with Condition D.2.6, the Permittee shall maintain a log of weekly overspray observations, and daily and monthly inspections.
- (c) To document the compliance status with Condition D.2.7, the Permittee shall maintain records of the results of the inspections required under Condition D.2.7. The Permittee shall include in its records when an inspection is not completed, i.e. the unit did not operate that day.
- (d) Section C - General Record Keeping Requirements contains the Permittee's obligations with regard to the records required by this condition.

D.2.11 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.2.1(a) shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, not later than thirty (30) days after the end of the quarter being reported.

SECTION D.3

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

Insignificant Activities

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour:
 - (1) One (1) natural gas-fired boiler, identified as B1, constructed in 1995, rated at 0.4 MMBtu/hr, and exhausting to stack B1. [326 IAC 6-2-4]
 - (2) Four (4) natural gas-fired hot water boilers, identified as AB1, AB2, AB3, and AB4, constructed in 2000, with each rated at 1 MMBtu per hour, exhausting to stacks AB1, AB2, AB3, and AB4, respectively. [326 IAC 6-2-4]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Particulate [326 IAC 6-2-4(a)]

Pursuant to 326 IAC 6-2-4(a), the PM emission limit for each boiler B1, AB1, AB2, AB3, and AB4 is 0.6 lb/MMBtu.

SECTION E.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]: NESHAP JJ

Plant 130 (1808 West Hively Avenue)

- (g) One (1) adhesive spray booth and one (1) wood wrapping press, identified as SA1 and WWP1, respectively, constructed in 1995, with a maximum capacity of laminating 39,143 linear feet per hour, utilizing a high volume low pressure (HVLP) application system, with particulate emissions controlled by dry filters, and exhausting to stack E1-10. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (h) One (1) dualtech automated back sealing machine, identified as D1, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D2, exhausting to stack E1-2, and a hot air drying tunnel exhausting to stack E1-3. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (i) One (1) rototech automated front staining machine, identified as D3, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) airless/air assist spray guns, with particulate emissions controlled by dry filters, exhausting to stack E1-4, and a forced air drying tunnel exhausting to stack E1-5. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (j) One (1) dualtech automated sealing machine, identified as D4, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D5, exhausting to stack E1-6, and a hot air/infrared drying tunnel exhausting to stack E1-7. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (k) One (1) dualtech automated topcoat machine, identified as D6, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D7, exhausting to stack E1-8, a hot air drying tunnel exhausting to stack E1-9, and a non-heated cooling hood exhausting inside the building. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (l) One (1) manual touch up booth, identified as TU1, constructed in 2000, with a maximum capacity of one (1) gallon of stain, two (2) gallons of sealer, and two (2) gallons of topcoat per day, consisting of one (1) airless/air assist gun, with particulate emissions controlled by dry filters, exhausting to stack TU-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Facility Description [326 IAC 2-7-5(15)]: (Continued)

- (m) One (1) rototech automated back staining machine, identified as D8, constructed in 2002, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) HVLP spray guns used for coating cabinet doors and an infrared drying oven, with particulate emissions controlled by dry filters, and exhausting to stack E1-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (n) One (1) vacuum coater, identified as VC-1, constructed in 1995, with a maximum capacity of 5,000 linear feet of wood per hour, applying coatings containing no VOC or HAP to wood trim, utilizing an ultraviolet (UV) curing process, with particulate emissions controlled by dry filters, and exhausting to stack E1-11. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (o) One (1) manual coating booth with two (2) HVLP spray guns, identified as D9, approved for construction in 2009, with a maximum capacity of 1000 doors per day, with particulate emissions controlled by dry filters, exhausting to stack E1-12. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (p) One (1) spray coating line, identified as SCL-1, approved for construction in 2010, consisting of coating equipment and electric dryer, with a throughput capacity of 250 units per hour, using robotic air assisted airless spray application method, venting to stack SCLS1, and using dry filters as control. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Plant 140 (57420 Nagy Drive)

- (r) Six (6) wood wrapping machines, identified as WR2a, WR2b, WR2c, WR2d, WR2e, and WR2f, constructed in 1995, each with a maximum capacity of 280 pounds of wood styles per hour, using water-based and hot melt adhesives, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, exhausting to stack C2-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (s) Four (4) wood panel laminating machines, identified as WPL2, constructed in 1995, each with a maximum capacity of 1,500 pounds of wood panels per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

National Emission Standards for Hazardous Air Pollutants (NESHAP) Requirements [326 IAC 2-7-5(1)]

E.1.1 General Provisions Relating to NESHAP JJ [326 IAC 20-1] [40 CFR Part 63, Subpart A]

Pursuant to 40 CFR 63.800, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1, for the surface coating operations identified as SA1, WWP1, D1, D3, D4, D6, TU1, D8, VC-1, D9, SCL-1,

WR2a-f, and WPL2, as specified in Table 1 of 40 CFR Part 63, Subpart JJ, in accordance with schedule in 40 CFR 63, Subpart JJ.

E.1.2 NESHAP Subpart JJ Requirements [40 CFR Part 63, Subpart JJ] [326 IAC 20-14-1]

The Permittee shall comply with the provisions of 40 CFR Part 63, Subpart JJ, which are incorporated by reference as 326 IAC 20-14-1, for the surface coating operations identified as SA1, WWP1, D1, D3, D4, D6, TU1, D8, VC-1, D9, SCL-1, WR2a-f, and WPL2. A copy of the rule is included as Attachment A. This source is subject to the following portions of NESHAP Subpart JJ:

- (1) 40 CFR 63.800 (except (f) and (g))
- (2) 40 CFR 63.801
- (3) 40 CFR 63.802 (except (b))
- (4) 40 CFR 63.803
- (5) 40 CFR 63.804 (except (d) and (e))
- (6) 40 CFR 63.805 (except (d)(7), (d)(9), (e)(4), and (e)(6))
- (7) 40 CFR 63.806
- (8) 40 CFR 63.807
- (9) 40 CFR 63.808
- (10) Table 1
- (11) Table 2
- (12) Table 3
- (13) Table 4
- (14) Table 5
- (15) Table 6

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

**PART 70 OPERATING PERMIT
CERTIFICATION**

Source Name: Patrick Industries, Inc.
Source Address: 1808 West Hively Avenue, Elkhart, Indiana 46517 and 57420 Nagy Drive,
Elkhart, Indiana 46517.
Part 70 Permit No.: T039-29242-00324

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Affidavit (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
Phone: 317-233-0178
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT**

Source Name: Patrick Industries, Inc.
Source Address: 1808 West Hively Avenue, Elkhart, Indiana 46517 and 57420 Nagy Drive,
Elkhart, Indiana 46517
Part 70 Permit No.: T039-29242-00324

This form consists of 2 pages

Page 1 of 2

<input type="checkbox"/> This is an emergency as defined in 326 IAC 2-7-1(12)
X The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and
X The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH
Part 70 Quarterly Report

Source Name: Patrick Industries, Inc.
Source Address: 1808 West Hively Avenue, Elkhart, Indiana 46517; and 57420 Nagy Drive, Elkhart, Indiana 46517.
Part 70 Permit No.: T039-29242-00324
Facility: All Laminating/Surface Coating Facilities
Parameter: VOC
Limit: Less than 249 tons per twelve consecutive month period, with compliance determined at the end of each month.

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

No deviation occurred in this quarter.

Deviation/s occurred in this quarter.
Deviation has been reported on:

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR MANAGEMENT
 COMPLIANCE AND ENFORCEMENT BRANCH**

**PART 70 OPERATING PERMIT
 Semi-Annual Report
 VOC and VHAP usage - Wood Furniture NESHAP**

Source Name: Patrick Industries, Inc.
 Source Address: 1808 West Hively Avenue, Elkhart, Indiana 46517 and 57420 Nagy Drive, Elkhart, Indiana 46517.
 Part 70 Permit No.: T039-29242-00324
 Facility: All Laminating/Surface Coating Facilities
 Parameter: VOC and VHAPs - NESHAP
 Limit: (1) Finishing operations - 1.0 lb VHAP/lb Solids
 (2) Thinners used for on-site formulation of washcoats, basecoats and enamels - 3% VHAP content by weight
 (3) All other thinner mixtures - 10% VHAP content by weight
 (4) Foam adhesives meeting the upholstered seating flammability requirements - 1.8 lb VHAP/lb Solids
 (5) All other contact adhesives - 1.0 lb VHAP/lb Solids
 (6) Strippable spray booth material - 0.8 pounds VOC per pound solids

YEAR: _____

Month	Finishing Operations (1lb VHAP/lb Solid)	Thinners (3% by weight)	All Other Thinner Mixtures (10% by weight)	Foam Adhesives (upholstered) (1.8lb VHAP/lb Solid)	Contact Adhesives (1.0 lb VHAP/lb Solid)	Strippable Spray Booth Material (0.8 lb VOC/ lb Solid)
1						
2						
3						
4						
5						
6						

- No deviation occurred in this month.
- Deviation/s occurred in this month.
 Deviation has been reported on:

Submitted by: _____
 Title/Position: _____
 Signature: _____
 Date: _____
 Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH**

**PART 70 OPERATING PERMIT
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Patrick Industries, Inc.
Source Address: 1808 West Hively Avenue, Elkhart, Indiana 46517; and 57420 Nagy Drive, Elkhart, Indiana 46517.
Part 70 Permit No.: T039-29242-00324

Months: _____ **to** _____ **Year:** _____

Page 1 of 2

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements of this permit, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed By: _____

Title/Position: _____

Date: _____

Phone: _____

**Indiana Department of Environmental Management
Office of Air Quality
Attachment A
to a
Part 70 Operating Permit Renewal**

Source Background and Description

Source Name:	Patrick Industries, Inc.
Source Location:	Plant 130: 1808 West Hively Avenue, Elkhart, Indiana 46517 Plant 140: 57420 Nagy Drive, Elkhart, Indiana 46517
County:	Elkhart
SIC Code:	2434, 2421, 2431, 2541
Operation Permit No.:	T039-29242-00324
Permit Reviewer:	APT

40 CFR 63, Subpart JJ—National Emission Standards for Hazardous Air Pollutants from Wood Furniture Manufacturing Operations

Source: 60 FR 62936, Dec. 7, 1995, unless otherwise noted.

§ 63.800 Applicability.

(a) The affected source to which this subpart applies is each facility that is engaged, either in part or in whole, in the manufacture of wood furniture or wood furniture components and that is located at a plant site that is a major source as defined in 40 CFR part 63, subpart A, §63.2. The owner or operator of a source that meets the definition for an incidental wood furniture manufacturer shall maintain purchase or usage records demonstrating that the source meets the definition in §63.801 of this subpart, but the source shall not be subject to any other provisions of this subpart.

(b) A source that complies with the limits and criteria specified in paragraphs (b)(1), (b)(2), or (b)(3) of this section is an area source for the purposes of this subpart and is not subject to any other provision of this rule, provided that: In the case of paragraphs (b)(1) and (b)(2), finishing materials, adhesives, cleaning solvents and washoff solvents used for wood furniture or wood furniture component manufacturing operations account for at least 90 percent of annual HAP emissions at the plant site, and if the plant site has HAP emissions that do not originate from the listed materials, the owner or operator shall keep any records necessary to demonstrate that the 90 percent criterion is being met. A source that initially relies on the limits and criteria specified in paragraphs (b)(1), (b)(2), and (b)(3) to become an area source, but subsequently exceeds the relevant limit (without first obtaining and complying with other limits that keep its potential to emit hazardous air pollutants below major source levels), becomes a major source and must comply thereafter with all applicable provisions of this subpart starting on the applicable compliance date in §63.800. Nothing in this paragraph (b) is intended to preclude a source from limiting its potential to emit through other appropriate mechanisms that may be available through the permitting authority.

(1) The owner or operator of the source uses no more than 250 gallons per month, for every month, of coating, gluing, cleaning, and washoff materials at the source, including materials used for source categories other than wood furniture (surface coating), but excluding materials used in routine janitorial or facility grounds maintenance, personal uses by employees or other persons, the use of products for the purpose of maintaining motor vehicles operated by the facility, or the use of toxic chemicals contained in intake water (used for processing or noncontact cooling) or intake air (used either as compressed air or for combustion). The owner or operator shall maintain records of the total gallons of coating, gluing, cleaning, and washoff materials used each month, and upon request submit such records to the Administrator. These records shall be maintained for five years.

(2) The owner or operator of the source uses no more than 3,000 gallons per rolling 12-month period, for every 12-month period, of coating, gluing, cleaning, and washoff materials at the source, including materials used for source categories other than wood furniture (surface coating), but excluding materials used in routine janitorial or facility grounds maintenance, personal uses by employees or other persons, the use of products for the purpose of maintaining motor vehicles operated by the facility, or the use of toxic chemicals contained in intake water (used for processing or noncontact cooling) or intake air (used either as compressed air or for combustion). A rolling 12-month period includes the previous 12 months of operation. The owner or operator of the source shall maintain records of the total gallons of coating, gluing, cleaning, and washoff materials used each

month and the total gallons used each previous month, and upon request submit such records to the Administrator. Because records are needed over the previous set of 12 months, the owner or operator shall keep monthly records beginning no less than one year before the compliance date specified in §63.800(e). Records shall be maintained for five years.

(3) The source emits no more than 4.5 Mg (5 tons) of any one HAP per rolling 12-month period and no more than 11.4 Mg (12.5 tons) of any combination of HAP per rolling 12-month period, and at least 90 percent of the plantwide emissions per rolling 12-month period are associated with the manufacture of wood furniture or wood furniture components.

(c) This subpart does not apply to research or laboratory facilities as defined in §63.801.

(d) Owners or operators of affected sources shall also comply with the requirements of subpart A of this part (General Provisions), according to the applicability of subpart A to such sources, as identified in Table 1 of this subpart.

(e) The compliance date for existing affected sources that emit less than 50 tons per year of HAP in 1996 is December 7, 1998. The compliance date for existing affected sources that emit 50 tons or more of hazardous air pollutants in 1996 is November 21, 1997. The owner or operator of an existing area source that increases its emissions of (or its potential to emit) HAP such that the source becomes a major source that is subject to this subpart shall comply with this subpart one year after becoming a major source.

(f) New affected sources must comply with the provisions of this standard immediately upon startup or by December 7, 1995, whichever is later. New area sources that become major sources shall comply with the provisions of this standard immediately upon becoming a major source.

(g) Reconstructed affected sources are subject to the requirements for new affected sources. The costs associated with the purchase and installation of air pollution control equipment (e.g., incinerators, carbon adsorbers, etc.) are not considered in determining whether the facility has been reconstructed, unless the control equipment is required as part of the process (e.g., product recovery). Additionally, the costs of retrofitting and replacement of equipment that is installed specifically to comply with this subpart are not considered reconstruction costs. For example, an affected source may convert to waterborne coatings to meet the requirements of this subpart. At most facilities, this conversion will require the replacement of existing storage tanks, mix equipment, and transfer lines. The cost of replacing the equipment is not considered in determining whether the facility has been reconstructed.

[60 FR 62936, Dec. 7, 1995, as amended at 62 FR 30259, June 3, 1997]

§ 63.801 Definitions.

(a) All terms used in this subpart that are not defined below have the meaning given to them in the CAA and in subpart A (General Provisions) of this part.

Adhesive means any chemical substance that is applied for the purpose of bonding two surfaces together other than by mechanical means. Under this subpart, adhesives shall not be considered coatings or finishing materials. Products used on humans and animals, adhesive tape, contact paper, or any other product with an adhesive incorporated onto or in an inert substrate shall not be considered adhesives under this subpart.

Administrator means the Administrator of the United States Environmental Protection Agency or his or her authorized representative.

Aerosol adhesive means an adhesive that is dispensed from a pressurized container as a suspension of fine solid or liquid particles in gas.

Affected source means a wood furniture manufacturing facility that is engaged, either in part or in whole, in the manufacture of wood furniture or wood furniture components and that is located at a plant site that is a major source as defined in 40 CFR part 63.2, excluding sources that meet the criteria established in §63.800(a), (b) and (c) of this subpart.

Alternative method means any method of sampling and analyzing for an air pollutant that is not a reference or equivalent method but has been demonstrated to the Administrator's satisfaction to, in specific cases, produce results adequate for a determination of compliance.

As applied means the HAP and solids content of the coating or contact adhesive that is actually used for coating or gluing the substrate. It includes the contribution of materials used for in-house dilution of the coating or contact adhesive.

Basecoat means a coat of colored material, usually opaque, that is applied before graining inks, glazing coats, or other opaque finishing materials, and is usually topcoated for protection.

Baseline conditions means the conditions that exist prior to an affected source implementing controls, such as a control system.

Building enclosure means a building housing a process that meets the requirements of a temporary total enclosure. The EPA Method 204E is used to identify all emission points from the building enclosure and to determine which emission points must be tested. For additional information see *Guidelines for Determining Capture Efficiency*, January 1994. Docket No. A-93-10, Item No. IV-B-1.

Capture device means a hood, enclosed room, floor sweep, or other means of collecting solvent emissions or other pollutants into a duct so that the pollutant can be directed to a pollution control device such as an incinerator or carbon adsorber.

Capture efficiency means the fraction of all organic vapors generated by a process that are directed to a control device.

Certified product data sheet (CPDS) means documentation furnished by coating or adhesive suppliers or an outside laboratory that provides:

(1) The VHAP content of a finishing material, contact adhesive, or solvent, by percent weight, measured using the EPA Method 311 (as promulgated in this subpart), or an equivalent or alternative method (or formulation data if the coating meets the criteria specified in §63.805(a));

(2) The solids content of a finishing material or contact adhesive by percent weight, determined using data from the EPA Method 24, or an alternative or equivalent method (or formulation data if the coating meets the criteria specified in §63.805 (a)); and

(3) The density, measured by EPA Method 24 or an alternative or equivalent method. Therefore, the reportable VHAP content shall represent the maximum aggregate emissions potential of the finishing material, adhesive, or solvent in concentrations greater than or equal to 1.0 percent by weight or 0.1 percent for VHAP that are carcinogens, as defined by the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR part 1910), as formulated. Only VHAP present in concentrations greater than or equal to 1.0 percent by weight, or 0.1 percent for VHAP that are carcinogens, must be reported on the CPDS. The purpose of the CPDS is to assist the affected source in demonstrating compliance with the emission limitations presented in §63.802.

Note: Because the optimum analytical conditions under EPA Method 311 vary by coating, the coating or adhesive supplier may also choose to include on the CPDS the optimum analytical conditions for analysis of the coating, adhesive, or solvent using EPA Method 311. Such information may include, but not be limited to, separation column, oven temperature, carrier gas, injection port temperature, extraction solvent, and internal standard.)

Cleaning operations means operations in which organic HAP solvent is used to remove coating materials or adhesives from equipment used in wood furniture manufacturing operations.

Coating means a protective, decorative, or functional film applied in a thin layer to a surface. Such materials include, but are not limited to, paints, topcoats, varnishes, sealers, stains, washcoats, basecoats, enamels, inks, and temporary protective coatings. Aerosol spray paints used for touch-up and repair are not considered coatings under this subpart.

Coating application station means the part of a coating operation where the coating is applied, e.g., a spray booth.

Coating operation means those activities in which a coating is applied to a substrate and is subsequently air-dried, cured in an oven, or cured by radiation.

Coating solids (or solids) means the part of the coating which remains after the coating is dried or cured; solids content is determined using data from the EPA Method 24, or an equivalent or alternative method.

Compliant coating/contact adhesive means a finishing material, contact adhesive, or strippable booth coating that meets the emission limits specified in Table 3 of this subpart.

Contact adhesive means an adhesive that is applied to two substrates, dried, and mated under only enough pressure to result in good contact. The bond is immediate and sufficiently strong to hold pieces together without further clamping, pressure, or airing.

Continuous coater means a finishing system that continuously applies finishing materials onto furniture parts moving along a conveyor. Finishing materials that are not transferred to the part are recycled to a reservoir. Several types of application methods can be used with a continuous coater including spraying, curtain coating, roll coating, dip coating, and flow coating.

Continuous compliance means that the affected source is meeting the emission limitations and other requirements of the rule at all times and is fulfilling all monitoring and recordkeeping provisions of the rule in order to demonstrate compliance.

Control device means any equipment that reduces the quantity of a pollutant that is emitted to the air. The device may destroy or secure the pollutant for subsequent recovery. Includes, but is not limited to, incinerators, carbon adsorbers, and condensers.

Control device efficiency means the ratio of the pollutant released by a control device and the pollutant introduced to the control device.

Control system means the combination of capture and control devices used to reduce emissions to the atmosphere.

Conventional air spray means a spray coating method in which the coating is atomized by mixing it with compressed air and applied at an air pressure greater than 10 pounds per square inch (gauge) at the point of atomization. Airless and air assisted airless spray technologies are not conventional air spray because the coating is not atomized by mixing it with compressed air. Electrostatic spray technology is also not considered conventional air spray because an electrostatic charge is employed to attract the coating to the workpiece.

Data quality objective (DQO) approach means a set of approval criteria that must be met so that data from an alternative test method can be used in determining the capture efficiency of a control system. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

Day means a period of 24 consecutive hours beginning at midnight local time, or beginning at a time consistent with a facility's operating schedule.

Disposed offsite means sending used organic HAP solvent or coatings outside of the facility boundaries for disposal.

Emission means the release or discharge, whether directly or indirectly, of HAP into the ambient air.

Enamel means a coat of colored material, usually opaque, that is applied as a protective topcoat over a basecoat, primer, or previously applied enamel coats. In some cases, another finishing material may be applied as a topcoat over the enamel.

Equipment leak means emissions of VHAP from pumps, valves, flanges, or other equipment used to transfer or apply coatings, adhesives, or organic HAP solvents.

Equivalent method means any method of sampling and analyzing for an air pollutant that has been demonstrated to the Administrator's satisfaction to have a consistent and quantitatively known relationship to the reference method, under specific conditions.

Finishing material means a coating used in the wood furniture industry. Such materials include, but are not limited to, stains, basecoats, washcoats, enamels, sealers, and topcoats.

Finishing operation means those operations in which a finishing material is applied to a substrate and is subsequently air-dried, cured in an oven, or cured by radiation.

Foam adhesive means a contact adhesive used for gluing foam to fabric, foam to foam, and fabric to wood.

Gluing operation means those operations in which adhesives are used to join components, for example, to apply a laminate to a wood substrate or foam to fabric.

Incidental wood furniture manufacturer means a major source that is primarily engaged in the manufacture of products other than wood furniture or wood furniture components and that uses no more than 100 gallons per month of finishing material or adhesives in the manufacture of wood furniture or wood furniture components.

Incinerator means, for the purposes of this industry, an enclosed combustion device that thermally oxidizes volatile organic compounds to CO and CO₂. This term does not include devices that burn municipal or hazardous waste material.

Janitorial maintenance means the upkeep of equipment or building structures that is not directly related to the manufacturing process, for example, cleaning of restroom facilities.

Lower confidence limit (LCL) approach means a set of approval criteria that must be met so that data from an alternative test method can be used in determining the capture efficiency of a control system. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

Material safety data sheet (MSDS) means the documentation required for hazardous chemicals by the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR Part 1910) for a solvent, cleaning material, contact adhesive, coating, or other material that identifies select reportable hazardous ingredients of the material, safety and health considerations, and handling procedures.

Noncompliant coating/contact adhesive means a finishing material, contact adhesive, or strippable booth coating that has a VHAP content (VOC content for the strippable booth coating) greater than the emission limitation presented in Table 3 of this subpart.

Nonporous substrate means a surface that is impermeable to liquids. Examples include metal, rigid plastic, flexible vinyl, and rubber.

Normally closed container means a container that is closed unless an operator is actively engaged in activities such as emptying or filling the container.

Operating parameter value means a minimum or maximum value established for a control device or process parameter that, if achieved by itself or in combination with one or more other operating parameter values, determines that an owner or operator has complied with an applicable emission limit.

Organic HAP solvent means a HAP that is a volatile organic liquid used for dissolving or dispersing constituents in a coating or contact adhesive, adjusting the viscosity of a coating or contact adhesive, or cleaning equipment. When used in a coating or contact adhesive, the organic HAP solvent evaporates during drying and does not become a part of the dried film.

Overall control efficiency means the efficiency of a control system, calculated as the product of the capture and control device efficiencies, expressed as a percentage.

Permanent total enclosure means a permanently installed enclosure that completely surrounds a source of emissions such that all emissions are captured and contained for discharge through a control device. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

Recycled onsite means the reuse of an organic HAP solvent in a process other than cleaning or washoff.

Reference method means any method of sampling and analyzing for an air pollutant that is published in Appendix A of 40 CFR part 60.

Research or laboratory facility means any stationary source whose primary purpose is to conduct research and development to develop new processes and products where such source is operated under the close supervision of technically trained personnel and is not engaged in the manufacture of products for commercial sale in commerce, except in a de minimis manner.

Responsible official has the meaning given to it in 40 CFR part 70, State Operating Permit Programs (Title V permits).

Sealer means a finishing material used to seal the pores of a wood substrate before additional coats of finishing material are applied. Special purpose finishing materials that are used in some finishing systems to optimize aesthetics are not sealers.

Solvent means a liquid used in a coating or contact adhesive to dissolve or disperse constituents and/or to adjust viscosity. It evaporates during drying and does not become a part of the dried film.

Stain means any color coat having a solids content by weight of no more than 8.0 percent that is applied in single or multiple coats directly to the substrate. It includes, but is not limited to, nongrain raising stains, equalizer stains, prestains, sap stains, body stains, no-wipe stains, penetrating stains, and toners.

Storage containers means vessels or tanks, including mix equipment, used to hold finishing, gluing, cleaning, or washoff materials.

Strippable spray booth material means a coating that:

- (1) Is applied to a spray booth wall to provide a protective film to receive over spray during finishing operations;
- (2) That is subsequently peeled off and disposed; and
- (3) By achieving (1) and (2) of this definition reduces or eliminates the need to use organic HAP solvents to clean spray booth walls.

Substrate means the surface onto which a coating or contact adhesive is applied (or into which a coating or contact adhesive is impregnated).

Temporary total enclosure means an enclosure that meets the requirements of §63.805(e)(1) (i) through (iv) and is not permanent, but constructed only to measure the capture efficiency of pollutants emitted from a given source. Additionally, any exhaust point from the enclosure shall be at least four equivalent duct or hood diameters from each natural draft opening. For additional information, see *Guidelines for Determining Capture Efficiency*, January 1994. (Docket No. A-93-10, Item No. IV-B-1).

Thinner means a volatile liquid that is used to dilute coatings or contact adhesives (to reduce viscosity, color strength, and solids, or to modify drying conditions).

Topcoat means the last film-building finishing material that is applied in a finishing system.

Touchup and repair means the application of finishing materials to cover minor finishing imperfections.

VHAP means any volatile hazardous air pollutant listed in Table 2 to Subpart JJ.

VHAP of potential concern means any VHAP from the list in table 6 of this subpart.

Volatile organic compound (VOC) means any organic compound which participates in atmospheric photochemical reactions, that is, any organic compound other than those which the Administrator designates as having negligible photochemical reactivity. A VOC may be measured by a reference method, an equivalent method, an alternative method, or by procedures specified under any rule. A reference method, an equivalent method, or an alternative method, however, may also measure nonreactive organic compounds. In such cases, the owner or operator may exclude the nonreactive organic compounds when determining compliance with a standard. For a list of compounds that the Administrator has designated as having negligible photochemical reactivity, refer to 40 CFR part 51.10.

Washcoat means a transparent special purpose finishing material having a solids content by weight of 12.0 percent by weight or less. Washcoats are applied over initial stains to protect, to control color, and to stiffen the wood fibers in order to aid sanding.

Washoff operations means those operations in which organic HAP solvent is used to remove coating from wood furniture or a wood furniture component.

Wood furniture means any product made of wood, a wood product such as rattan or wicker, or an engineered wood product such as particleboard that is manufactured under any of the following standard industrial classification codes: 2434, 2511, 2512, 2517, 2519, 2521, 2531, 2541, 2599, or 5712.

Wood furniture component means any part that is used in the manufacture of wood furniture. Examples include, but are not limited to, drawer sides, cabinet doors, seat cushions, and laminated tops. However, foam seat cushions manufactured and fabricated at a facility that does not engage in any other wood furniture or wood furniture component manufacturing operation are excluded from this definition.

Wood furniture manufacturing operations means the finishing, gluing, cleaning, and washoff operations associated with the production of wood furniture or wood furniture components.

(b) The nomenclature used in this subpart has the following meaning:

(1) A_k = the area of each natural draft opening (k) in a total enclosure, in square meters.

(2) C_c = the VHAP content of a finishing material (c), in kilograms of volatile hazardous air pollutants per kilogram of coating solids (kg VHAP/kg solids), as supplied. Also given in pounds of volatile hazardous air pollutants per pound of coating solids (lb VHAP/lb solids).

(3) C_{aj} = the concentration of VHAP in gas stream (j) exiting the control device, in parts per million by volume.

(4) C_{bi} = the concentration of VHAP in gas stream (i) entering the control device, in parts per million by volume.

(5) C_{di} = the concentration of VHAP in gas stream (i) entering the control device from the affected source, in parts per million by volume.

(6) C_{fk} = the concentration of VHAP in uncontrolled gas stream (k) emitted directly to the atmosphere from the affected source, in parts per million by volume.

(7) E = the emission limit achieved by an emission point or a set of emission points, in kg VHAP/kg solids (lb VHAP/lb solids).

(8) F = the control device efficiency, expressed as a fraction.

(9) FV = the average inward face velocity across all natural draft openings in a total enclosure, in meters per hour.

(10) G = the VHAP content of a contact adhesive, in kg VHAP/kg solids (lb VHAP/lb solids), as applied.

(11) M = the mass of solids in finishing material used monthly, kg solids/month (lb solids/month).

(12) N = the capture efficiency, expressed as a fraction.

(13) Q_{aj} = the volumetric flow rate of gas stream (j) exiting the control device, in dry standard cubic meters per hour.

(14) Q_{bi} = the volumetric flow rate of gas stream (i) entering the control device, in dry standard cubic meters per hour.

(15) Q_{di} = the volumetric flow rate of gas stream (i) entering the control device from the emission point, in dry standard cubic meters per hour.

(16) Q_{fk} = the volumetric flow rate of uncontrolled gas stream (k) emitted directly to the atmosphere from the emission point, in dry standard cubic meters per hour.

(17) Q_{ini} =the volumetric flow rate of gas stream (i) entering the total enclosure through a forced makeup air duct, in standard cubic meters per hour (wet basis).

(18) Q_{outj} =the volumetric flow rate of gas stream (j) exiting the total enclosure through an exhaust duct or hood, in standard cubic meters per hour (wet basis).

(19) R=the overall efficiency of the control system, expressed as a percentage.

(20) S=the VHAP content of a solvent, expressed as a weight fraction, added to finishing materials.

(21) W=the amount of solvent, in kilograms (pounds), added to finishing materials during the monthly averaging period.

(22) ac=after the control system is installed and operated.

(23) bc=before control.

[60 FR 62936, Dec. 7, 1995, as amended at 62 FR 30260, June 3, 1997; 62 FR 31363, June 9, 1997; 63 FR 71380, Dec. 28, 1998]

§ 63.802 Emission limits.

(a) Each owner or operator of an existing affected source subject to this subpart shall:

(1) Limit VHAP emissions from finishing operations by meeting the emission limitations for existing sources presented in Table 3 of this subpart, using any of the compliance methods in §63.804(a). To determine VHAP emissions from a finishing material containing formaldehyde or styrene, the owner or operator of the affected source shall use the methods presented in §63.803(l)(2) for determining styrene and formaldehyde usage.

(2) Limit VHAP emissions from contact adhesives by achieving a VHAP limit for contact adhesives based on the following criteria:

(i) For foam adhesives (contact adhesives used for upholstery operations) used in products that meet the upholstered seating flammability requirements of California Technical Bulletin 116, 117, or 133, the Business and Institutional Furniture Manufacturers Association's (BIFMA's) X5.7, UFAC flammability testing, or any similar requirements from local, State, or Federal fire regulatory agencies, the VHAP content of the adhesive shall not exceed 1.8 kg VHAP/kg solids (1.8 lb VHAP/lb solids), as applied; or

(ii) For all other contact adhesives (including foam adhesives used in products that do not meet the standards presented in paragraph (a)(2)(i) of this section, but excluding aerosol adhesives and excluding contact adhesives applied to nonporous substrates, the VHAP content of the adhesive shall not exceed 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied.

(3) Limit HAP emissions from strippable spray booth coatings by using coatings that contain no more than 0.8 kg VOC/kg solids (0.8 lb VOC/lb solids), as applied.

(b) Each owner or operator of a new affected source subject to this subpart shall:

(1) Limit VHAP emissions from finishing operations by meeting the emission limitations for new sources presented in Table 3 of this subpart using any of the compliance methods in §63.804(d). To determine VHAP emissions from a finishing material containing formaldehyde or styrene, the owner or operator of the affected source shall use the methods presented in §63.803(l)(2) for determining styrene and formaldehyde usage.

(2) Limit VHAP emissions from contact adhesives by achieving a VHAP limit for contact adhesives, excluding aerosol adhesives and excluding contact adhesives applied to nonporous substrates, of no greater than 0.2 kg VHAP/kg solids (0.2 lb VHAP/lb solids), as applied, using either of the compliance methods in §63.804(e).

(3) Limit HAP emissions from strippable spray booth coatings by using coatings that contain no more than 0.8 kg VOC/kg solids (0.8 lb VOC/lb solids), as applied.

§ 63.803 Work practice standards.

(a) *Work practice implementation plan.* (1) Each owner or operator of an affected source subject to this subpart shall prepare and maintain a written work practice implementation plan that defines environmentally desirable work practices for each wood furniture operation manufacturing operation and addresses each of the work practice standards presented in paragraphs (b) through (l) of this section. The plan shall be developed no more than 60 days after the compliance date.

(2) The written work practice implementation plan shall be available for inspection by the Administrator (or delegated State, local, or Tribal authority) upon request. If the Administrator (or delegated State, local, or Tribal authority) determines that the work practice implementation plan does not include sufficient mechanisms for ensuring that the work practice standards are being implemented, the Administrator (or delegated State, local, or Tribal authority) may require the affected source to modify the plan. Revisions or modifications to the plan do not require a revision of the source's Title V permit.

(3) The inspection and maintenance plan required by paragraph (c) of this section and the formulation assessment plan for finishing operations required by paragraph (l) of this section are also reviewable by the Administrator (or delegated State, local, or Tribal authority).

(b) *Operator training course.* Each owner or operator of an affected source shall train all new and existing personnel, including contract personnel, who are involved in finishing, gluing, cleaning, and washoff operations, use of manufacturing equipment, or implementation of the requirements of this subpart. All new personnel, those hired after the compliance date of the standard, shall be trained upon hiring. All existing personnel, those hired before the compliance date of the standard, shall be trained within six months of the compliance date of the standard. All personnel shall be given refresher training annually. The affected source shall maintain a copy of the training program with the work practice implementation plan. The training program shall include, at a minimum, the following:

(1) A list of all current personnel by name and job description that are required to be trained;

(2) An outline of the subjects to be covered in the initial and refresher training for each position or group of personnel;

(3) Lesson plans for courses to be given at the initial and the annual refresher training that include, at a minimum, appropriate application techniques, appropriate cleaning and washoff procedures, appropriate equipment setup and adjustment to minimize finishing material usage and overspray, and appropriate management of cleanup wastes; and

(4) A description of the methods to be used at the completion of initial or refresher training to demonstrate and document successful completion.

(c) *Inspection and maintenance plan.* Each owner or operator of an affected source shall prepare and maintain with the work practice implementation plan a written leak inspection and maintenance plan that specifies:

(1) A minimum visual inspection frequency of once per month for all equipment used to transfer or apply coatings, adhesives, or organic HAP solvents;

(2) An inspection schedule;

(3) Methods for documenting the date and results of each inspection and any repairs that were made;

(4) The timeframe between identifying the leak and making the repair, which adheres, at a minimum, to the following schedule:

(i) A first attempt at repair (e.g., tightening of packing glands) shall be made no later than five calendar days after the leak is detected; and

(ii) Final repairs shall be made within 15 calendar days after the leak is detected, unless the leaking equipment is to be replaced by a new purchase, in which case repairs shall be completed within three months.

(d) *Cleaning and washoff solvent accounting system.* Each owner or operator of an affected source shall develop an organic HAP solvent accounting form to record:

(1) The quantity and type of organic HAP solvent used each month for washoff and cleaning, as defined in §63.801 of this subpart;

(2) The number of pieces washed off, and the reason for the washoff; and

(3) The quantity of spent organic HAP solvent generated from each washoff and cleaning operation each month, and whether it is recycled onsite or disposed offsite.

(e) *Chemical composition of cleaning and washoff solvents.* Each owner or operator of an affected source shall not use cleaning or washoff solvents that contain any of the pollutants listed in Table 4 to this subpart, in concentrations subject to MSDS reporting as required by OSHA.

(f) *Spray booth cleaning.* Each owner or operator of an affected source shall not use compounds containing more than 8.0 percent by weight of VOC for cleaning spray booth components other than conveyors, continuous coaters and their enclosures, or metal filters, or plastic filters unless the spray booth is being refurbished. If the spray booth is being refurbished, that is the spray booth coating or other protective material used to cover the booth is being replaced, the affected source shall use no more than 1.0 gallon of organic HAP solvent per booth to prepare the surface of the booth prior to applying the booth coating.

(g) *Storage requirements.* Each owner or operator of an affected source shall use normally closed containers for storing finishing, gluing, cleaning, and washoff materials.

(h) *Application equipment requirements.* Each owner or operator of an affected source shall use conventional air spray guns to apply finishing materials only under any of the following circumstances:

(1) To apply finishing materials that have a VOC content no greater than 1.0 lb VOC/lb solids, as applied;

(2) For touchup and repair under the following conditions:

(i) The touchup and repair occurs after completion of the finishing operation; or

(ii) The touchup and repair occurs after the application of stain and before the application of any other type of finishing material, and the materials used for touchup and repair are applied from a container that has a volume of no more than 2.0 gallons.

(3) When spray is automated, that is, the spray gun is aimed and triggered automatically, not manually;

(4) When emissions from the finishing application station are directed to a control device;

(5) The conventional air gun is used to apply finishing materials and the cumulative total usage of that finishing material is no more than 5.0 percent of the total gallons of finishing material used during that semiannual period; or

(6) The conventional air gun is used to apply stain on a part for which it is technically or economically infeasible to use any other spray application technology.

The affected source shall demonstrate technical or economic infeasibility by submitting to the Administrator a videotape, a technical report, or other documentation that supports the affected source's claim of technical or economic infeasibility. The following criteria shall be used, either independently or in combination, to support the affected source's claim of technical or economic infeasibility:

(i) The production speed is too high or the part shape is too complex for one operator to coat the part and the application station is not large enough to accommodate an additional operator; or

(ii) The excessively large vertical spray area of the part makes it difficult to avoid sagging or runs in the stain.

(i) *Line cleaning*. Each owner or operator of an affected source shall pump or drain all organic HAP solvent used for line cleaning into a normally closed container.

(j) *Gun cleaning*. Each owner or operator of an affected source shall collect all organic HAP solvent used to clean spray guns into a normally closed container.

(k) *Washoff operations*. Each owner or operator of an affected source shall control emissions from washoff operations by:

(1) Using normally closed tanks for washoff; and

(2) Minimizing dripping by tilting or rotating the part to drain as much solvent as possible.

(l) *Formulation assessment plan for finishing operations*. Each owner or operator of an affected source shall prepare and maintain with the work practice implementation plan a formulation assessment plan that:

(1) Identifies VHAP from the list presented in Table 5 of this subpart that are being used in finishing operations by the affected source;

(2) Establishes a baseline level of usage by the affected source, for each VHAP identified in paragraph (l)(1) of this section. The baseline usage level shall be the highest annual usage from 1994, 1995, or 1996, for each VHAP identified in paragraph (l)(1) of this section. For formaldehyde, the baseline level of usage shall be based on the amount of free formaldehyde present in the finishing material when it is applied. For styrene, the baseline level of usage shall be an estimate of unreacted styrene, which shall be calculated by multiplying the amount of styrene monomer in the finishing material, when it is applied, by a factor of 0.16. Sources using a control device to reduce emissions may adjust their usage based on the overall control efficiency of the control system, which is determined using the equation in §63.805 (d) or (e).

(3) Tracks the annual usage of each VHAP identified in (l)(1) by the affected source that is present in amounts subject to MSDS reporting as required by OSHA.

(4) If, after November 1998, the annual usage of the VHAP identified in paragraph (l)(1) exceeds its baseline level, then the owner or operator of the affected source shall provide a written notification to the permitting authority that describes the amount of the increase and explains the reasons for exceedance of the baseline level. The following explanations would relieve the owner or operator from further action, unless the affected source is not in compliance with any State regulations or requirements for that VHAP:

(i) The exceedance is no more than 15.0 percent above the baseline level;

(ii) Usage of the VHAP is below the *de minimis* level presented in Table 5 of this subpart for that VHAP (sources using a control device to reduce emissions may adjust their usage based on the overall control efficiency of the control system, which is determined using the procedures in §63.805 (d) or (e));

(iii) The affected source is in compliance with its State's air toxic regulations or guidelines for the VHAP; or

(iv) The source of the pollutant is a finishing material with a VOC content of no more than 1.0 kg VOC/kg solids (1.0 lb VOC/lb solids), as applied.

(5) If none of the above explanations are the reason for the increase, the owner or operator shall confer with the permitting authority to discuss the reason for the increase and whether there are practical and reasonable technology-based solutions for reducing the usage. The evaluation of whether a technology is reasonable and practical shall be based on cost, quality, and marketability of the product, whether the technology is being used successfully by other wood furniture manufacturing operations, or other criteria mutually agreed upon by the permitting authority and owner or operator. If there are no practical and reasonable solutions, the facility need take no further action. If there are solutions, the owner or operator shall develop a plan to reduce usage of the pollutant to the extent feasible. The plan shall address the approach to be used to reduce emissions, a timetable for implementing the plan, and a schedule for submitting notification of progress.

(6) If, after November 1998, an affected source uses a VHAP of potential concern listed in table 6 of this subpart for which a baseline level has not been previously established, then the baseline level shall be established as the *de minimis* level provided

in that same table for that chemical. The affected source shall track the annual usage of each VHAP of potential concern identified in this paragraph that is present in amounts subject to MSDS reporting as required by OSHA. If usage of the VHAP of potential concern exceeds the *de minimis* level listed in table 6 of this subpart for that chemical, then the affected source shall provide an explanation to the permitting authority that documents the reason for the exceedance of the *de minimis* level. If the explanation is not one of those listed in paragraphs (l)(4)(i) through (l)(4)(iv) of this section, the affected source shall follow the procedures in paragraph (l)(5) of this section.

[60 FR 62936, Dec. 7, 1995, as amended at 63 FR 71380, Dec. 28, 1998; 68 FR 37353, June 23, 2003]

§ 63.804 Compliance procedures and monitoring requirements.

(a) The owner or operator of an existing affected source subject to §63.802(a)(1) shall comply with those provisions using any of the methods presented in §63.804 (a)(1) through (a)(4).

(1) Calculate the average VHAP content for all finishing materials used at the facility using Equation 1, and maintain a value of E no greater than 1.0;

$$E = (M_{c1}C_{c1} + M_{c2}C_{c2} + \dots + M_{cn}C_{cn} + S_1W_1 + S_2W_2 + \dots + S_nW_n) / (M_{c1} + M_{c2} + \dots + M_{cn}) \quad \text{Equation 1}$$

(2) Use compliant finishing materials according to the following criteria:

(i) Demonstrate that each stain, sealer, and topcoat has a VHAP content of no more than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied, and each thinner contains no more than 10.0 percent VHAP by weight by maintaining certified product data sheets for each coating and thinner;

(ii) Demonstrate that each washcoat, basecoat, and enamel that is purchased pre-made, that is, it is not formulated onsite by thinning another finishing material, has a VHAP content of no more than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied, and each thinner contains no more than 10.0 percent VHAP by weight by maintaining certified product data sheets for each coating and thinner; and

(iii) Demonstrate that each washcoat, basecoat, and enamel that is formulated at the affected source is formulated using a finishing material containing no more than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids) and a thinner containing no more than 3.0 percent VHAP by weight.

(3) Use a control system with an overall control efficiency (R) such that the value of E_{ac} in Equation 2 is no greater than 1.0.

$$R = [(E_{bc} - E_{ac}) / E_{bc}] (100) \quad \text{Equation 2}$$

The value of E_{bc} in Equation 2 shall be calculated using Equation 1; or

(4) Use any combination of an averaging approach, as described in paragraph (a)(1) of this section, compliant finishing materials, as described in paragraph (a)(2) of this section, and a control system, as described in paragraph (a)(3) of this section.

(b) The owner or operator of an affected source subject to §63.802(a)(2)(i) shall comply with the provisions by using compliant foam adhesives with a VHAP content no greater than 1.8 kg VHAP/kg solids (1.8 lb VHAP/lb solids), as applied.

(c) The owner or operator of an affected source subject to §63.802(a)(2)(ii) shall comply with those provisions by using either of the methods presented in §63.804 (c)(1) and (c)(2).

(1) Use compliant contact adhesives with a VHAP content no greater than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied; or

(2) Use a control system with an overall control efficiency (R) such that the value of G_{ac} is no greater than 1.0.

$$R = [(G_{bc} - G_{ac}) / G_{bc}] (100) \quad \text{Equation 3}$$

(d) The owner or operator of a new affected source subject to §63.802(b)(1) may comply with those provisions by using any of the following methods:

(1) Calculate the average VHAP content across all finishing materials used at the facility using Equation 1, and maintain a value of E no greater than 0.8;

(2) Use compliant finishing materials according to the following criteria:

(i) Demonstrate that each sealer and topcoat has a VHAP content of no more than 0.8 kg VHAP/kg solids (0.8 lb VHAP/lb solids), as applied, each stain has a VHAP content of no more than 1.0 kg VHAP/kg solids (1.0 lb VHAP/lb solids), as applied, and each thinner contains no more than 10.0 percent VHAP by weight;

(ii) Demonstrate that each washcoat, basecoat, and enamel that is purchased pre-made, that is, it is not formulated onsite by thinning another finishing material, has a VHAP content of no more than 0.8 kg VHAP/kg solids (0.8 lb VHAP/lb solids), as applied, and each thinner contains no more than 10.0 percent VHAP by weight; and

(iii) Demonstrate that each washcoat, basecoat, and enamel that is formulated onsite is formulated using a finishing material containing no more than 0.8 kg VHAP/kg solids (0.8 lb VHAP/lb solids) and a thinner containing no more than 3.0 percent HAP by weight.

(3) Use a control system with an overall control efficiency (R) such that the value of E_{ac} in Equation 4 is no greater than 0.8.

$$R = [(E_{bc} - E_{ac}) / E_{bc}] (100) \quad \text{Equation 4}$$

The value of E_{bc} in Equation 4 shall be calculated using Equation 1; or

(4) Use any combination of an averaging approach, as described in (d)(1), compliant finishing materials, as described in (d)(2), and a control system, as described in (d)(3).

(e) The owner or operator of a new affected source subject to §63.802(b)(2) shall comply with the provisions using either of the following methods:

(1) Use compliant contact adhesives with a VHAP content no greater than 0.2 kg VHAP/kg solids (0.2 lb VHAP/lb solids), as applied; or

(2) Use a control system with an overall control efficiency (R) such that the value of G_{ac} in Equation 3 is no greater than 0.2.

(f) *Initial compliance.* (1) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(1) or (d)(1) shall submit the results of the averaging calculation (Equation 1) for the first month with the initial compliance status report required by §63.807(b). The first month's calculation shall include data for the entire month in which the compliance date falls. For example, if the source's compliance date is November 21, 1997, the averaging calculation shall include data from November 1, 1997 to November 30, 1997.

(2) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(2) or (d)(2) shall submit an initial compliance status report, as required by §63.807(b), stating that compliant stains, washcoats, sealers, topcoats, basecoats, enamels, and thinners, as applicable, are being used by the affected source.

(3) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that are complying through the procedures established in §63.804 (a)(2) or (d)(2) and are applying coatings using continuous coaters shall demonstrate initial compliance by:

(i) Submitting an initial compliance status report, as required by §63.807(b), stating that compliant coatings, as determined by the VHAP content of the coating in the reservoir and the VHAP content as calculated from records, and compliant thinners are being used; or

(ii) Submitting an initial compliance status report, as required by §63.807(b), stating that compliant coatings, as determined by the VHAP content of the coating in the reservoir, are being used; the viscosity of the coating in the reservoir is being monitored; and compliant thinners are being used. The affected source shall also submit data that demonstrate that viscosity is an appropriate parameter for demonstrating compliance.

(4) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(3) or (d)(3) shall demonstrate initial compliance by:

(i) Submitting a monitoring plan that identifies each operating parameter to be monitored for the capture device and discusses why each parameter is appropriate for demonstrating continuous compliance;

(ii) Conducting an initial performance test as required under §63.7 using the procedures and test methods listed in §63.7 and §63.805 (c) and (d) or (e);

(iii) Calculating the overall control efficiency (R) following the procedures in §63.805 (d) or (e); and

(iv) Determining those operating conditions critical to determining compliance and establishing one or more operating parameters that will ensure compliance with the standard.

(A) For compliance with a thermal incinerator, minimum combustion temperature shall be the operating parameter.

(B) For compliance with a catalytic incinerator equipped with a fixed catalyst bed, the minimum gas temperature both upstream and downstream of the catalyst bed shall be the operating parameter.

(C) For compliance with a catalytic incinerator equipped with a fluidized catalyst bed, the minimum gas temperature upstream of the catalyst bed and the pressure drop across the catalyst bed shall be the operating parameters.

(D) For compliance with a carbon adsorber, the operating parameters shall be the total regeneration mass stream flow for each regeneration cycle and the carbon bed temperature after each regeneration, or the concentration level of organic compounds exiting the adsorber, unless the owner or operator requests and receives approval from the Administrator to establish other operating parameters.

(E) For compliance with a control device not listed in this section, one or more operating parameter values shall be established using the procedures identified in §63.804(g)(4)(vi).

(v) Owners or operators complying with §63.804(f)(4) shall calculate each site-specific operating parameter value as the arithmetic average of the maximum or minimum operating parameter values, as appropriate, that demonstrate compliance with the standards, during the three test runs required by §63.805(c)(1).

(5) Owners or operators of an affected source subject to the provisions of §63.802 (a)(2) or (b)(2) that comply through the procedures established in §63.804 (b), (c)(1), or (e)(1), shall submit an initial compliance status report, as required by §63.807(b), stating that compliant contact adhesives are being used by the affected source.

(6) Owners or operators of an affected source subject to the provisions of §63.802 (a)(2)(ii) or (b)(2) that comply through the procedures established in §63.804 (c)(2) or (e)(2), shall demonstrate initial compliance by:

(i) Submitting a monitoring plan that identifies each operating parameter to be monitored for the capture device and discusses why each parameter is appropriate for demonstrating continuous compliance;

(ii) Conducting an initial performance test as required under §63.7 using the procedures and test methods listed in §63.7 and §63.805 (c) and (d) or (e);

(iii) Calculating the overall control efficiency (R) following the procedures in §63.805 (d) or (e); and

(iv) Determining those operating conditions critical to determining compliance and establishing one or more operating parameters that will ensure compliance with the standard.

- (A) For compliance with a thermal incinerator, minimum combustion temperature shall be the operating parameter.
- (B) For compliance with a catalytic incinerator equipped with a fixed catalyst bed, the minimum gas temperature both upstream and downstream of the catalyst shall be the operating parameter.
- (C) For compliance with a catalytic incinerator equipped with a fluidized catalyst bed, the minimum gas temperature upstream of the catalyst bed and the pressure drop across the catalyst bed shall be the operating parameters.
- (v) Owners or operators complying with §63.804(f)(6) shall calculate each site-specific operating parameter value as the arithmetic average of the maximum or minimum operating values as appropriate, that demonstrate compliance with the standards, during the three test runs required by §63.805(c)(1).
- (7) Owners or operators of an affected source subject to the provisions of §63.802 (a)(3) or (b)(3) shall submit an initial compliance status report, as required by §63.807(b), stating that compliant strippable spray booth coatings are being used by the affected source.
- (8) Owners or operators of an affected source subject to the work practice standards in §63.803 shall submit an initial compliance status report, as required by §63.807(b), stating that the work practice implementation plan has been developed and procedures have been established for implementing the provisions of the plan.
- (g) *Continuous compliance demonstrations.* (1) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(1) or (d)(1) shall demonstrate continuous compliance by submitting the results of the averaging calculation (Equation 1) for each month within that semiannual period and submitting a compliance certification with the semiannual report required by §63.807(c).
- (i) The compliance certification shall state that the value of (E), as calculated by Equation 1, is no greater than 1.0 for existing sources or 0.8 for new sources. An affected source is in violation of the standard if E is greater than 1.0 for existing sources or 0.8 for new sources for any month. A violation of the monthly average is a separate violation of the standard for each day of operation during the month, unless the affected source can demonstrate through records that the violation of the monthly average can be attributed to a particular day or days during the period.
- (ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.
- (2) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(2) or (d)(2) shall demonstrate continuous compliance by using compliant coatings and thinners, maintaining records that demonstrate the coatings and thinners are compliant, and submitting a compliance certification with the semiannual report required by §63.807(c).
- (i) The compliance certification shall state that compliant stains, washcoats, sealers, topcoats, basecoats, enamels, and thinners, as applicable, have been used each day in the semiannual reporting period or should otherwise identify the periods of noncompliance and the reasons for noncompliance. An affected source is in violation of the standard whenever a noncompliant coating, as demonstrated by records or by a sample of the coating, is used.
- (ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.
- (3) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that are complying through the procedures established in §63.804 (a)(2) or (d)(2) and are applying coatings using continuous coaters shall demonstrate continuous compliance by following the procedures in paragraph (g)(3) (i) or (ii) of this section.
- (i) Using compliant coatings, as determined by the VHAP content of the coating in the reservoir and the VHAP content as calculated from records, using compliant thinners, and submitting a compliance certification with the semiannual report required by §63.807(c).
- (A) The compliance certification shall state that compliant coatings have been used each day in the semiannual reporting period, or should otherwise identify the days of noncompliance and the reasons for noncompliance. An affected source is in violation of

the standard whenever a noncompliant coating, as determined by records or by a sample of the coating, is used. Use of a noncompliant coating is a separate violation for each day the noncompliant coating is used.

(B) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(ii) Using compliant coatings, as determined by the VHAP content of the coating in the reservoir, using compliant thinners, maintaining a viscosity of the coating in the reservoir that is no less than the viscosity of the initial coating by monitoring the viscosity with a viscosity meter or by testing the viscosity of the initial coating and retesting the coating in the reservoir each time solvent is added, maintaining records of solvent additions, and submitting a compliance certification with the semiannual report required by §63.807(c).

(A) The compliance certification shall state that compliant coatings, as determined by the VHAP content of the coating in the reservoir, have been used each day in the semiannual reporting period. Additionally, the certification shall state that the viscosity of the coating in the reservoir has not been less than the viscosity of the initial coating, that is, the coating that is initially mixed and placed in the reservoir, for any day in the semiannual reporting period.

(B) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(C) An affected source is in violation of the standard when a sample of the as-applied coating exceeds the applicable limit established in §63.804 (a)(2) or (d)(2), as determined using EPA Method 311, or the viscosity of the coating in the reservoir is less than the viscosity of the initial coating.

(4) Owners or operators of an affected source subject to the provisions of §63.802 (a)(1) or (b)(1) that comply through the procedures established in §63.804 (a)(3) or (d)(3) shall demonstrate continuous compliance by installing, calibrating, maintaining, and operating the appropriate monitoring equipment according to manufacturer's specifications. The owner or operator shall also submit the excess emissions and continuous monitoring system performance report and summary report required by §63.807(d) and §63.10(e) of subpart A.

(i) Where a capture/control device is used, a device to monitor each site-specific operating parameter established in accordance with §63.804(f)(6)(i) is required.

(ii) Where an incinerator is used, a temperature monitoring device equipped with a continuous recorder is required.

(A) Where a thermal incinerator is used, a temperature monitoring device shall be installed in the firebox or in the ductwork immediately downstream of the firebox in a position before any substantial heat exchange occurs.

(B) Where a catalytic incinerator equipped with a fixed catalyst bed is used, temperature monitoring devices shall be installed in the gas stream immediately before and after the catalyst bed.

(C) Where a catalytic incinerator equipped with a fluidized catalyst bed is used, a temperature monitoring device shall be installed in the gas stream immediately before the bed. In addition, a pressure monitoring device shall be installed to determine the pressure drop across the catalyst bed. The pressure drop shall be measured monthly at a constant flow rate.

(iii) Where a carbon adsorber is used one of the following is required:

(A) An integrating stream flow monitoring device having an accuracy of ± 10 percent, capable of recording the total regeneration stream mass flow for each regeneration cycle; and a carbon bed temperature monitoring device, having an accuracy of ± 1 percent of the temperature being monitored or ± 0.5 °C, whichever is greater, and capable of recording the carbon bed temperature after each regeneration and within 15 minutes of completing any cooling cycle;

(B) An organic monitoring device, equipped with a continuous recorder, to indicate the concentration level of organic compounds exiting the carbon adsorber; or

(C) Any other monitoring device that has been approved by the Administrator in accordance with §63.804(f)(4)(iv)(D).

(iv) Owners or operators of an affected source shall not operate the capture or control device at a daily average value greater than or less than (as appropriate) the operating parameter values. The daily average value shall be calculated as the average of all values for a monitored parameter recorded during the operating day.

(v) Owners or operators of an affected source that are complying through the use of a catalytic incinerator equipped with a fluidized catalyst bed shall maintain a constant pressure drop, measured monthly, across the catalyst bed.

(vi) An owner or operator who uses a control device not listed in §63.804(f)(4) shall submit, for the Administrator's approval, a description of the device, test data verifying performance, and appropriate site-specific operating parameters that will be monitored to demonstrate continuous compliance with the standard.

(5) Owners or operators of an affected source subject to the provisions of §63.802 (a)(2) (i) or (ii) or (b)(2) that comply through the procedures established in §63.804 (b), (c)(1), or (e)(1), shall submit a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that compliant contact and/or foam adhesives have been used each day in the semiannual reporting period, or should otherwise identify each day noncompliant contact and/or foam adhesives were used. Each day a noncompliant contact or foam adhesive is used is a single violation of the standard.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(6) Owners or operators of an affected source subject to the provisions of §63.802 (a)(2)(ii) or (b)(2) that comply through the procedures established in §63.804 (c)(2) or (e)(2), shall demonstrate continuous compliance by installing, calibrating, maintaining, and operating the appropriate monitoring equipment according to the manufacturer's specifications. The owner or operator shall also submit the excess emissions and continuous monitoring system performance report and summary report required by §63.807(d) and §63.10(e) of subpart A of this part.

(i) Where a capture/control device is used, a device to monitor each site-specific operating parameter established in accordance with §63.804(f)(6)(i) is required.

(ii) Where an incinerator is used, a temperature monitoring device equipped with a continuous recorder is required.

(A) Where a thermal incinerator is used, a temperature monitoring device shall be installed in the firebox or in the ductwork immediately downstream of the firebox in a position before any substantial heat exchange occurs.

(B) Where a catalytic incinerator equipped with a fixed catalyst bed is used, temperature monitoring devices shall be installed in the gas stream immediately before and after the catalyst bed.

(C) Where a catalytic incinerator equipped with a fluidized catalyst bed is used, a temperature monitoring device shall be installed in the gas stream immediately before the bed. In addition, a pressure monitoring device shall be installed to measure the pressure drop across the catalyst bed. The pressure drop shall be measured monthly at a constant flow rate.

(iii) Where a carbon adsorber is used one of the following is required:

(A) An integrating stream flow monitoring device having an accuracy of ± 10 percent, capable of recording the total regeneration stream mass flow for each regeneration cycle; and a carbon bed temperature monitoring device, having an accuracy of ± 1 percent of the temperature being monitored or ± 0.5 °C, whichever is greater, and capable of recording the carbon bed temperature after each regeneration and within 15 minutes of completing any cooling cycle;

(B) An organic monitoring device, equipped with a continuous recorder, to indicate the concentration level of organic compounds exiting the carbon adsorber; or

(C) Any other monitoring device that has been approved by the Administrator in accordance with §63.804(f)(4)(iv)(D).

(iv) Owners or operators of an affected source shall not operate the capture or control device at a daily average value greater than or less than (as appropriate) the operating parameter values. The daily average value shall be calculated as the average of all values for a monitored parameter recorded during the operating day.

(v) Owners or operators of an affected source that are complying through the use of a catalytic incinerator equipped with a fluidized catalyst bed shall maintain a constant pressure drop, measured monthly, across the catalyst bed.

(vi) An owner or operator using a control device not listed in this section shall submit to the Administrator a description of the device, test data verifying the performance of the device, and appropriate operating parameter values that will be monitored to demonstrate continuous compliance with the standard. Compliance using this device is subject to the Administrator's approval.

(7) Owners or operators of an affected source subject to the provisions of §63.802 (a)(3) or (b)(3) shall submit a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that compliant strippable spray booth coatings have been used each day in the semiannual reporting period, or should otherwise identify each day noncompliant materials were used. Each day a noncompliant strippable booth coating is used is a single violation of the standard.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

(8) Owners or operators of an affected source subject to the work practice standards in §63.803 shall submit a compliance certification with the semiannual report required by §63.807(c).

(i) The compliance certification shall state that the work practice implementation plan is being followed, or should otherwise identify the provisions of the plan that have not been implemented and each day the provisions were not implemented. During any period of time that an owner or operator is required to implement the provisions of the plan, each failure to implement an obligation under the plan during any particular day is a violation.

(ii) The compliance certification shall be signed by a responsible official of the company that owns or operates the affected source.

§ 63.805 Performance test methods.

(a) The EPA Method 311 of appendix A of part 63 shall be used in conjunction with formulation data to determine the VHAP content of the liquid coating. Formulation data shall be used to identify VHAP present in the coating. The EPA Method 311 shall then be used to quantify those VHAP identified through formulation data. The EPA Method 311 shall not be used to quantify HAP such as styrene and formaldehyde that are emitted during the cure. The EPA Method 24 (40 CFR part 60, appendix A) shall be used to determine the solids content by weight and the density of coatings. If it is demonstrated to the satisfaction of the Administrator that a coating does not release VOC or HAP byproducts during the cure, for example, all VOC and HAP present in the coating is solvent, then batch formulation information shall be accepted. The owner or operator of an affected source may request approval from the Administrator to use an alternative method for determining the VHAP content of the coating. In the event of any inconsistency between the EPA Method 24 or Method 311 test data and a facility's formulation data, that is, if the EPA Method 24/311 value is higher, the EPA Method 24/311 test shall govern unless after consultation, a regulated source could demonstrate to the satisfaction of the enforcement agency that the formulation data were correct. Sampling procedures shall follow the guidelines presented in "Standard Procedures for Collection of Coating and Ink Samples for VOC Content Analysis by Reference Method 24 and Reference Method 24A," EPA-340/1-91-010. (Docket No. A-93-10, Item No. IV-A-1).

(b) Owners or operators demonstrating compliance in accordance with §63.804 (f)(4) or (f)(6) and §63.804 (g)(4) or (g)(6), or complying with any of the other emission limits of §63.802 by operating a capture or control device shall determine the overall control efficiency of the control system (R) as the product of the capture and control device efficiency, using the test methods cited in §63.805(c) and the procedures in §63.805 (d) or (e).

(c) When an initial compliance demonstration is required by §63.804 (f)(4) or (f)(6) of this subpart, the procedures in paragraphs (c)(1) through (c)(6) of this section shall be used in determining initial compliance with the provisions of this subpart.

(1) The EPA Method 18 (40 CFR part 60, appendix A) shall be used to determine the HAP concentration of gaseous air streams. The test shall consist of three separate runs, each lasting a minimum of 30 minutes.

(2) The EPA Method 1 or 1A (40 CFR part 60, appendix A) shall be used for sample and velocity traverses.

(3) The EPA Method 2, 2A, 2C, or 2D (40 CFR part 60, appendix A) shall be used to measure velocity and volumetric flow rates.

(4) The EPA Method 3 (40 CFR part 60, appendix A) shall be used to analyze the exhaust gases.

(5) The EPA Method 4 (40 CFR part 60, appendix A) shall be used to measure the moisture in the stack gas.

(6) The EPA Methods 2, 2A, 2C, 2D, 3, and 4 shall be performed, as applicable, at least twice during each test period.

(d) Each owner or operator of an affected source demonstrating compliance in accordance with §63.804 (f)(4) or (f)(6) shall perform a gaseous emission test using the following procedures:

(1) Construct the overall HAP emission reduction system so that all volumetric flow rates and total HAP emissions can be accurately determined by the applicable test methods specified in §63.805(c) (1) through (6);

(2) Determine capture efficiency from the affected emission point(s) by capturing, venting, and measuring all HAP emissions from the affected emission point(s). During a performance test, the owner or operator shall isolate affected emission point(s) located in an area with other nonaffected gaseous emission sources from all other gaseous emission point(s) by any of the following methods:

(i) Build a temporary total enclosure (see §63.801) around the affected emission point(s); or

(ii) Use the building that houses the process as the enclosure (see §63.801);

(iii) Use any alternative protocol and test method provided they meet either the requirements of the data quality objective (DQO) approach or the lower confidence level (LCL) approach (see §63.801);

(iv) Shut down all nonaffected HAP emission point(s) and continue to exhaust fugitive emissions from the affected emission point(s) through any building ventilation system and other room exhausts such as drying ovens. All exhaust air must be vented through stacks suitable for testing; or

(v) Use another methodology approved by the Administrator provided it complies with the EPA criteria for acceptance under part 63, appendix A, Method 301.

(3) Operate the control device with all affected emission points that will subsequently be delivered to the control device connected and operating at maximum production rate;

(4) Determine the efficiency (F) of the control device using the following equation:

$$F = \frac{\sum_{i=1}^n Q_{di} C_{di} - \sum_{j=1}^p Q_{aj} C_{aj}}{\sum_{i=1}^n Q_{di} C_{di}} \quad (\text{Equation 5})$$

(5) Determine the efficiency (N) of the capture system using the following equation:

$$N = \frac{\sum_{i=1}^n Q_{di} C_{di}}{\sum_{i=1}^n Q_{di} C_{di} + \sum_{k=1}^p Q_{fk} C_{fk}} \quad (\text{Equation 6})$$

(6) For each affected source complying with §63.802(a)(1) in accordance with §63.804(a)(3), compliance is demonstrated if the product of (F×N)(100) yields a value (R) such that the value of E_{ac} in Equation 2 is no greater than 1.0.

(7) For each new affected source complying with §63.802(b)(1) in accordance with §63.804(d)(3), compliance is demonstrated if the product of (F×N)(100) yields a value (R) such that the value of E_{ac} in Equation 4 is no greater than 0.8.

(8) For each affected source complying with §63.802(a)(2)(ii) in accordance with §63.804(c)(2), compliance is demonstrated if the product of (F×N)(100) yields a value (R) such that the value of G_{ac} in Equation 3 is no greater than 1.0.

(9) For each new affected source complying with §63.802(b)(2) in accordance with §63.804(e)(2), compliance is demonstrated if the product of (F×N)(100) yields a value (R) such that the value of G_{ac} in Equation 3 is no greater than 0.2.

(e) An alternative method to the compliance method in §63.805(d) is the installation of a permanent total enclosure around the affected emission point(s). A permanent total enclosure presents prima facie evidence that all HAP emissions from the affected emission point(s) are directed to the control device. Each affected source that complies using a permanent total enclosure shall:

(1) Demonstrate that the total enclosure meets the requirements in paragraphs (e)(1) (i) through (iv). The owner or operator of an enclosure that does not meet these requirements may apply to the Administrator for approval of the enclosure as a total enclosure on a case-by-case basis. The enclosure shall be considered a total enclosure if it is demonstrated to the satisfaction of the Administrator that all HAP emissions from the affected emission point(s) are contained and vented to the control device. The requirements for automatic approval are as follows:

(i) The total area of all natural draft openings shall not exceed 5 percent of the total surface area of the total enclosure's walls, floor, and ceiling;

(ii) All sources of emissions within the enclosure shall be a minimum of four equivalent diameters away from each natural draft opening;

(iii) The average inward face velocity (FV) across all natural draft openings shall be a minimum of 3,600 meters per hour as determined by the following procedures:

(A) All forced makeup air ducts and all exhaust ducts are constructed so that the volumetric flow rate in each can be accurately determined by the test methods specified in §63.805 (c)(2) and (3). Volumetric flow rates shall be calculated without the adjustment normally made for moisture content; and

(B) Determine FV by the following equation:

$$FV = \frac{\sum_{j=1}^n Q_{out j} - \sum_{i=1}^p Q_{in i}}{\sum_{k=1}^q A_k} \quad (\text{Equation 7})$$

(iv) All access doors and windows whose areas are not included as natural draft openings and are not included in the calculation of FV shall be closed during routine operation of the process.

(2) Determine the control device efficiency using Equation (5), and the test methods and procedures specified in §63.805 (c)(1) through (6).

(3) For each affected source complying with §63.802(a)(1) in accordance with §63.804(a)(3), compliance is demonstrated if:

- (i) The installation of a permanent total enclosure is demonstrated ($N=1$);
- (ii) The value of F is determined from Equation (5); and
- (iii) The product of $(F \times N)(100)$ yields a value (R) such that the value of E_{ac} in Equation 2 is no greater than 1.0.

(4) For each new affected source complying with §63.802(b)(1) in accordance with §63.804(d)(3), compliance is demonstrated if:

- (i) The installation of a permanent total enclosure is demonstrated ($N = 1$);
- (ii) The value of F is determined from Equation (5); and
- (iii) The product of $(F \times N)(100)$ yields a value (R) such that the value of E_{ac} in Equation 4 is no greater than 0.8.

(5) For each affected source complying with §63.802(a)(2)(ii) in accordance with §63.804(c)(2), compliance is demonstrated if:

- (i) The installation of a permanent total enclosure is demonstrated ($N=1$);
- (ii) The value of F is determined from Equation (5); and
- (iii) The product of $(F \times N)(100)$ yields a value (R) such that the value of G_{ac} in Equation 3 is no greater than 1.0.

(6) For each new affected source complying with §63.802(b)(2) in accordance with §63.804(e)(2), compliance is demonstrated if:

- (i) The installation of a permanent total enclosure is demonstrated ($N=1$);
- (ii) The value of F is determined from Equation (5); and
- (iii) The product of $(F \times N)(100)$ yields a value (R) such that the value of G_{ac} in Equation 3 is no greater than 0.2.

§ 63.806 Recordkeeping requirements.

(a) The owner or operator of an affected source subject to this subpart shall fulfill all recordkeeping requirements of §63.10 of subpart A, according to the applicability criteria in §63.800(d) of this subpart.

(b) The owner or operator of an affected source subject to the emission limits in §63.802 of this subpart shall maintain records of the following:

(1) A certified product data sheet for each finishing material, thinner, contact adhesive, and strippable spray booth coating subject to the emission limits in §63.802; and

(2) The VHAP content, in kg VHAP/kg solids (lb VHAP/lb solids), as applied, of each finishing material and contact adhesive subject to the emission limits in §63.802; and

(3) The VOC content, in kg VOC/kg solids (lb VOC/lb solids), as applied, of each strippable booth coating subject to the emission limits in §63.802 (a)(3) or (b)(3).

(c) The owner or operator of an affected source following the compliance method in §63.804 (a)(1) or (d)(1) shall maintain copies of the averaging calculation for each month following the compliance date, as well as the data on the quantity of coatings and thinners used that is necessary to support the calculation of E in Equation 1.

(d) The owner or operator of an affected source following the compliance procedures of §63.804 (f)(3)(ii) and (g)(3)(ii) shall maintain the records required by §63.806(b) as well as records of the following:

- (1) Solvent and coating additions to the continuous coater reservoir;
- (2) Viscosity measurements; and
- (3) Data demonstrating that viscosity is an appropriate parameter for demonstrating compliance.

(e) The owner or operator of an affected source subject to the work practice standards in §63.803 of this subpart shall maintain onsite the work practice implementation plan and all records associated with fulfilling the requirements of that plan, including, but not limited to:

- (1) Records demonstrating that the operator training program required by §63.803(b) is in place;
- (2) Records collected in accordance with the inspection and maintenance plan required by §63.803(c);
- (3) Records associated with the cleaning solvent accounting system required by §63.803(d);
- (4) Records associated with the limitation on the use of conventional air spray guns showing total finishing material usage and the percentage of finishing materials applied with conventional air spray guns for each semiannual period as required by §63.803(h)(5).
- (5) Records associated with the formulation assessment plan required by §63.803(l); and
- (6) Copies of documentation such as logs developed to demonstrate that the other provisions of the work practice implementation plan are followed.

(f) The owner or operator of an affected source following the compliance method of §63.804 (f)(4) or (g)(4) shall maintain copies of the calculations demonstrating that the overall control efficiency (R) of the control system results in the value of E_{ac} required by Equations 2 or 4, records of the operating parameter values, and copies of the semiannual compliance reports required by §63.807(d).

(g) The owner or operator of an affected source following the compliance method of §63.804 (f)(6) or (g)(6), shall maintain copies of the calculations demonstrating that the overall control efficiency (R) of the control system results in the applicable value of G_{ac} calculated using Equation 3, records of the operating parameter values, and copies of the semiannual compliance reports required by §63.807(d).

(h) The owner or operator of an affected source subject to the emission limits in §63.802 and following the compliance provisions of §63.804(f) (1), (2), (3), (5), (7) and (8) and §63.804(g) (1), (2), (3), (5), (7), and (8) shall maintain records of the compliance certifications submitted in accordance with §63.807(c) for each semiannual period following the compliance date.

(i) The owner or operator of an affected source shall maintain records of all other information submitted with the compliance status report required by §63.9(h) and §63.807(b) and the semiannual reports required by §63.807(c).

(j) The owner or operator of an affected source shall maintain all records in accordance with the requirements of §63.10(b)(1).

§ 63.807 Reporting requirements.

(a) The owner or operator of an affected source subject to this subpart shall fulfill all reporting requirements of §63.7 through §63.10 of subpart A (General Provisions) according to the applicability criteria in §63.800(d) of this subpart.

(b) The owner or operator of an affected source demonstrating compliance in accordance with §63.804(f) (1), (2), (3), (5), (7) and (8) shall submit the compliance status report required by §63.9(h) of subpart A (General Provisions) no later than 60 days after the compliance date. The report shall include the information required by §63.804(f) (1), (2), (3), (5), (7), and (8) of this subpart.

(c) The owner or operator of an affected source demonstrating compliance in accordance with §63.804(g) (1), (2), (3), (5), (7), and (8) shall submit a report covering the previous 6 months of wood furniture manufacturing operations:

(1) The first report shall be submitted 30 calendar days after the end of the first 6-month period following the compliance date.

(2) Subsequent reports shall be submitted 30 calendar days after the end of each 6-month period following the first report.

(3) The semiannual reports shall include the information required by §63.804(g) (1), (2), (3), (5), (7), and (8), a statement of whether the affected source was in compliance or noncompliance, and, if the affected source was in noncompliance, the measures taken to bring the affected source into compliance.

(4) The frequency of the reports required by paragraph (c) of this section shall not be reduced from semiannually regardless of the history of the owner's or operator's compliance status.

(d) The owner or operator of an affected source demonstrating compliance in accordance with §63.804(g) (4) and (6) of this subpart shall submit the excess emissions and continuous monitoring system performance report and summary report required by §63.10(e) of subpart A. The report shall include the monitored operating parameter values required by §63.804(g) (4) and (6). If the source experiences excess emissions, the report shall be submitted quarterly for at least 1 year after the excess emissions occur and until a request to reduce reporting frequency is approved, as indicated in §63.10(e)(3)(C). If no excess emissions occur, the report shall be submitted semiannually.

(e) The owner or operator of an affected source required to provide a written notification under §63.803(1)(4) shall include in the notification one or more statements that explains the reasons for the usage increase. The notification shall be submitted no later than 30 calendar days after the end of the annual period in which the usage increase occurred.

§ 63.808 Implementation and enforcement.

(a) This subpart can be implemented and enforced by the U.S. EPA, or a delegated authority such as the applicable State, local, or Tribal agency. If the U.S. EPA Administrator has delegated authority to a State, local, or Tribal agency, then that agency, in addition to the U.S. EPA, has the authority to implement and enforce this subpart. Contact the applicable U.S. EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to a State, local, or Tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or Tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator of U.S. EPA and cannot be transferred to the State, local, or Tribal agency.

(c) The authorities that cannot be delegated to State, local, or Tribal agencies are as specified in paragraphs (c)(1) through (5) of this section.

(1) Approval of alternatives to the requirements in §§63.800, 63.802, and 63.803(a)(1), (b), (c) introductory text, and (d) through (l).

(2) Approval of alternatives to the monitoring and compliance requirements in §§63.804(f)(4)(iv)(D) and (E), 63.804(g)(4)(iii)(C), 63.804(g)(4)(vi), and 63.804(g)(6)(vi).

(3) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f), as defined in §63.90, and as required in this subpart, as well as approval of any alternatives to the specific test methods under §§63.805(a), 63.805(d)(2)(v), and 63.805(e)(1).

(4) Approval of major alternatives to monitoring under §63.8(f), as defined in §63.90, and as required in this subpart.

(5) Approval of major alternatives to recordkeeping and reporting under §63.10(f), as defined in §63.90, and as required in this subpart.

§§ 63.809-63.819 [Reserved]

Table 1 to Subpart JJ of Part 63—General Provisions Applicability to Subpart JJ

Reference	Applies to subpart JJ	Comment
63.1(a)	Yes	
63.1(b)(1)	No	Subpart JJ specifies applicability.
63.1(b)(2)	Yes	
63.1(b)(3)	Yes	
63.1(c)(1)	No	Subpart JJ specifies applicability.
63.1(c)(2)	No	Area sources are not subject to subpart JJ.
63.1(c)(4)	Yes	
63.1(c)(5)	Yes	
63.1(e)	Yes	
63.2	Yes	Additional terms are defined in 63.801(a) of subpart JJ. When overlap between subparts A and JJ occurs, subpart JJ takes precedence.
63.3	Yes	Other units used in subpart JJ are defined in 63.801(b).
63.4	Yes	
63.5	Yes	
63.6(a)	Yes	
63.6(b)(1)	Yes	
63.6(b)(2)	Yes	
63.6(b)(3)	Yes	
63.6(b)(4)	No	May apply when standards are proposed under Section 112(f) of the CAA.
63.6(b)(5)	Yes	
63.6(b)(7)	Yes	
63.6(c)(1)	Yes	
63.6(c)(2)	No	
63.6(c)(5)	Yes	
63.6(e)(1)	Yes	
63.6(e)(2)	Yes	

63.6(e)(3)	Yes	Applies only to affected sources using a control device to comply with the rule.
63.6(f)(1)	No	Affected sources complying through the procedures specified in 63.804 (a)(1), (a)(2), (b), (c)(1), (d)(1), (d)(2), (e)(1), and (e)(2) are subject to the emission standards at all times, including periods of startup, shutdown, and malfunction.
63.6(f)(2)	Yes	
63.6(f)(3)	Yes	
63.6(g)	Yes	
63.6(h)	No	
63.6 (i)(1)– (i)(3)	Yes	
63.6(i)(4)(i)	Yes	
63.6(i)(4)(ii)	No	
63.6 (i)(5)– (i)(14)	Yes	
63.6(i)(16)	Yes	
63.6(j)	Yes	
63.7	Yes	Applies only to affected sources using a control device to comply with the rule.
63.8	Yes	Applies only to affected sources using a control device to comply with the rule.
63.9(a)	Yes	
63.9(b)	Yes	Existing sources are required to submit initial notification report within 270 days of the effective date.
63.9(c)	Yes	
63.9(d)	Yes	
63.9(e)	Yes	Applies only to affected sources using a control device to comply with the rule.
63.9(f)	No	
63.9(g)	Yes	Applies only to affected sources using a control device to comply with the rule.
63.9(h)	Yes	63.9(h)(2)(ii) applies only to affected sources using a control device to comply with the rule.
63.9(i)	Yes	

63.9(j)	Yes	
63.10(a)	Yes	
63.10(b)(1)	Yes	
63.10(b)(2)	Yes	Applies only to affected sources using a control device to comply with the rule.
63.10(b)(3)	Yes	
63.10(c)	Yes	
63.10(d)(1)	Yes	
63.10(d)(2)	Yes	Applies only to affected sources using a control device to comply with the rule.
63.10(d)(3)	No	
63.10(d)(4)	Yes	
63.10(d)(5)	Yes	Applies only to affected sources using a control device to comply with the rule.
63.10(e)	Yes	Applies only to affected sources using a control device to comply with the rule.
63.10(f)	Yes	
63.11	No	
63.12–63.15	Yes	

Table 2 to Subpart JJ of Part 63—List of Volatile Hazardous Air Pollutants

Chemical name	CAS No.
Acetaldehyde	75070
Acetamide	60355
Acetonitrile	75058
Acetophenone	98862
2-Acetylaminofluorine	53963
Acrolein	107028
Acrylamide	79061
Acrylic acid	79107
Acrylonitrile	107131

Allyl chloride	107051
4-Aminobiphenyl	92671
Aniline	62533
o-Anisidine	90040
Benzene	71432
Benzidine	92875
Benzotrichloride	98077
Benzyl chloride	100447
Biphenyl	92524
Bis (2-ethylhexyl) phthalate (DEHP)	117817
Bis (chloromethyl) ether	542881
Bromoform	75252
1,3-Butadiene	106990
Carbon disulfide	75150
Carbon tetrachloride	56235
Carbonyl sulfide	463581
Catechol	120809
Chloroacetic acid	79118
2-Chloroacetophenone	532274
Chlorobenzene	108907
Chloroform	67663
Chloromethyl methyl ether	107302
Chloroprene	126998
Cresols (isomers and mixture)	1319773
o-Cresol	95487
m-Cresol	108394
p-Cresol	106445
Cumene	98828

2,4-D (2,4-Dichlorophenoxyacetic acid, including salts and esters)	94757
DDE (1,1-Dichloro-2,2-bis(p-chlorophenyl)ethylene)	72559
Diazomethane	334883
Dibenzofuran	132649
1,2-Dibromo-3-chloropropane	96128
Dibutylphthalate	84742
1,4-Dichlorobenzene	106467
3,3'-Dichlorobenzidine	91941
Dichloroethyl ether (Bis(2-chloroethyl)ether)	111444
1,3-Dichloropropene	542756
Diethanolamine	111422
N,N-Dimethylaniline	121697
Diethyl sulfate	64675
3,3'-Dimethoxybenzidine	119904
4-Dimethylaminoazobenzene	60117
3,3'-Dimethylbenzidine	119937
Dimethylcarbamoyl chloride	79447
N,N-Dimethylformamide	68122
1,1-Dimethylhydrazine	57147
Dimethyl phthalate	131113
Dimethyl sulfate	77781
4,6-Dinitro-o-cresol, and salts	534521
2,4-Dinitrophenol	51285
2,4-Dinitrotoluene	121142
1,4-Dioxane (1,4-Diethyleneoxide)	123911
1,2-Diphenylhydrazine	122667
Epichlorohydrin (1-Chloro-2,3-epoxypropane)	106898
1,2-Epoxybutane	106887

Ethyl acrylate	140885
Ethylbenzene	100414
Ethyl carbamate (Urethane)	51796
Ethyl chloride (Chloroethane)	75003
Ethylene dibromide (Dibromoethane)	106934
Ethylene dichloride (1,2-Dichloroethane)	107062
Ethylene glycol	107211
Ethylene oxide	75218
Ethylenethiourea	96457
Ethylidene dichloride (1,1-Dichloroethane)	75343
Formaldehyde	50000
Glycolethers ^a	
Hexachlorobenzene	118741
Hexachloro-1,3-butadiene	87683
Hexachloroethane	67721
Hexamethylene-1,6-diisocyanate	822060
Hexamethylphosphoramide	680319
Hexane	110543
Hydrazine	302012
Hydroquinone	123319
Isophorone	78591
Maleic anhydride	108316
Methanol	67561
Methyl bromide (Bromomethane)	74839
Methyl chloride (Chloromethane)	74873
Methyl chloroform (1,1,1-Trichloroethane)	71556
Methyl ethyl ketone (2-Butanone)	78933
Methylhydrazine	60344

Methyl iodide (Iodomethane)	74884
Methyl isobutyl ketone (Hexone)	108101
Methyl isocyanate	624839
Methyl methacrylate	80626
Methyl tert-butyl ether	1634044
4,4'-Methylenebis (2-chloroaniline)	101144
Methylene chloride (Dichloromethane)	75092
4,4'-Methylenediphenyl diisocyanate (MDI)	101688
4,4'-Methylenedianiline	101779
Naphthalene	91203
Nitrobenzene	98953
4-Nitrobiphenyl	92933
4-Nitrophenol	100027
2-Nitropropane	79469
N-Nitroso-N-methylurea	684935
N-Nitrosodimethylamine	62759
N-Nitrosomorpholine	59892
Phenol	108952
p-Phenylenediamine	106503
Phosgene	75445
Phthalic anhydride	85449
Polychlorinated biphenyls (Aroclors)	1336363
Polycyclic Organic Matter ^b	
1,3-Propane sultone	1120714
beta-Propiolactone	57578
Propionaldehyde	123386
Propoxur (Baygon)	114261
Propylene dichloride (1,2-Dichloropropane)	78875

Propylene oxide	75569
1,2-Propylenimine (2-Methyl aziridine)	75558
Quinone	106514
Styrene	100425
Styrene oxide	96093
2,3,7,8-Tetrachlorodibenzo-p-dioxin	1746016
1,1,2,2-Tetrachloroethane	79345
Tetrachloroethylene (Perchloroethylene)	127184
Toluene	108883
2,4-Toluediamine	95807
Toluene-2,4-diisocyanate	584849
o-Toluidine	95534
1,2,4-Trichlorobenzene	120821
1,1,2-Trichloroethane	79005
Trichloroethylene	79016
2,4,5-Trichlorophenol	95954
2,4,6-Trichlorophenol	88062
Triethylamine	121448
Trifluralin	1582098
2,2,4-Trimethylpentane	540841
Vinyl acetate	108054
Vinyl bromide	593602
Vinyl chloride	75014
Vinylidene chloride (1,1-Dichloroethylene)	75354
Xylenes (isomers and mixture)	1330207
o-Xylene	95476
m-Xylene	108383
p-Xylene	106423

^aIncludes mono- and di-ethers of ethylene glycol, diethylene glycols and triethylene glycol; R-(OCH₂CH₂)_n RR-OR where:

n = 1, 2, or 3,

R = alkyl or aryl groups

R' = R, H, or groups which, when removed, yield glycol ethers with the structure: R-(OCH₂CH₂)_n-OH. Polymers are excluded from the glycol category.

^bIncludes organic compounds with more than one benzene ring, and which have a boiling point greater than or equal to 100°C.

[63 FR 71381, Dec. 28, 1998]

Table 3 to Subpart JJ of Part 63—Summary of Emission Limits

Emission point	Existing source	New source
Finishing Operations:		
(a) Achieve a weighted average VHAP content across all coatings (maximum kg VHAP/kg solids [lb VHAP/lb solids], as applied)	^a 1.0	^a 0.8
(b) Use compliant finishing materials (maximum kg VHAP/kg solids [lb VHAP/lb solids], as applied):		
—stains	^a 1.0	^a 1.0
—washcoats	^{a,b} 1.0	^{a,b} 0.8
—sealers	^a 1.0	^a 0.8
—topcoats	^a 1.0	^a 0.8
—basecoats	^{a,b} 1.0	^{a,b} 0.8
—enamels	^{a,b} 1.0	^{a,b} 0.8
—thinners (maximum percent VHAP allowable); or	10.0	10.0
(c) As an alternative, use control device; or	^c 1.0	^c 0.8
(d) Use any combination of (a), (b), and (c)	1.0	0.8
Cleaning Operations:		
Strippable spray booth material (maximum VOC content, kg VOC/kg solids [lb VOC/lb solids])	0.8	0.8
Contact Adhesives:		
(a) Use compliant contact adhesives (maximum kg VHAP/kg solids [lb VHAP/lb solids], as applied) based on following criteria:		
i. For aerosol adhesives, and for contact adhesives applied to	^d NA	^d NA

nonporous substrates		
ii. For foam adhesives used in products that meet flammability requirements	1.8	0.2
iii. For all other contact adhesives (including foam adhesives used in products that do not meet flammability requirements); or	1.0	0.2
(b) Use a control device	^e 1.0	^e 0.2

^aThe limits refer to the VHAP content of the coating, as applied.

^bWashcoats, basecoats, and enamels must comply with the limits presented in this table if they are purchased premade, that is, if they are not formulated onsite by thinning other finishing materials. If they are formulated onsite, they must be formulated using compliant finishing materials, i.e., those that meet the limits specified in this table, and thinners containing no more than 3.0 percent VHAP by weight.

^cThe control device must operate at an efficiency that is equivalent to no greater than 1.0 kilogram (or 0.8 kilogram) of VHAP being emitted from the affected emission source per kilogram of solids used.

^dThere is no limit on the VHAP content of these adhesives.

^eThe control device must operate at an efficiency that is equivalent to no greater than 1.0 kilogram (or 0.2 kilogram) of VHAP being emitted from the affected emission source per kilogram of solids used.

[60 FR 62936, Dec. 7, 1995, as amended at 62 FR 30260, June 3, 1997]

Table 4 to Subpart JJ of Part 63—Pollutants Excluded From Use in Cleaning and Washoff Solvents

Chemical name	CAS No.
4-Aminobiphenyl	92671
Styrene oxide	96093
Diethyl sulfate	64675
N-Nitrosomorpholine	59892
Dimethyl formamide	68122
Hexamethylphosphoramide	680319
Acetamide	60355
4,4'-Methylenedianiline	101779
o-Anisidine	90040
2,3,7,8-Tetrachlorodibenzo-p-dioxin	1746016
Beryllium salts	

Benzidine	92875
N-Nitroso-N-methylurea	684935
Bis (chloromethyl) ether	542881
Dimethyl carbamoyl chloride	79447
Chromium compounds (hexavalent)	
1,2-Propylenimine (2-Methyl aziridine)	75558
Arsenic and inorganic arsenic compounds	99999904
Hydrazine	302012
1,1-Dimethyl hydrazine	57147
Beryllium compounds	7440417
1,2-Dibromo-3-chloropropane	96128
N-Nitrosodimethylamine	62759
Cadmium compounds	
Benzo (a) pyrene	50328
Polychlorinated biphenyls (Aroclors)	1336363
Heptachlor	76448
3,3'-Dimethyl benzidine	119937
Nickel subsulfide	12035722
Acrylamide	79061
Hexachlorobenzene	118741
Chlordane	57749
1,3-Propane sultone	1120714
1,3-Butadiene	106990
Nickel refinery dust	
2-Acetylaminoflourine	53963
3,3'-Dichlorobenzidine	53963
Lindane (hexachlorcyclohexane, gamma)	58899
2,4-Toluene diamine	95807

Dichloroethyl ether (Bis(2-chloroethyl) ether)	111444
1,2-Diphenylhydrazine	122667
Toxaphene (chlorinated camphene)	8001352
2,4-Dinitrotoluene	121142
3,3'-Dimethoxybenzidine	119904
Formaldehyde	50000
4,4'-Methylene bis (2-chloroaniline)	101144
Acrylonitrile	107131
Ethylene dibromide (1,2-Dibromoethane)	106934
DDE (1,1-p-chlorophenyl 1-2 dichloroethylene)	72559
Chlorobenzilate	510156
Dichlorvos	62737
Vinyl chloride	75014
Coke Oven Emissions	
Ethylene oxide	75218
Ethylene thiourea	96457
Vinyl bromide (bromoethene)	593602
Selenium sulfide (mono and di)	7488564
Chloroform	67663
Pentachlorophenol	87865
Ethyl carbamate (Urethane)	51796
Ethylene dichloride (1,2-Dichloroethane)	107062
Propylene dichloride (1,2-Dichloropropane)	78875
Carbon tetrachloride	56235
Benzene	71432
Methyl hydrazine	60344
Ethyl acrylate	140885
Propylene oxide	75569

Aniline	62533
1,4-Dichlorobenzene(p)	106467
2,4,6-Trichlorophenol	88062
Bis (2-ethylhexyl) phthalate (DEHP)	117817
o-Toluidine	95534
Propoxur	114261
1,4-Dioxane (1,4-Diethyleneoxide)	123911
Acetaldehyde	75070
Bromoform	75252
Captan	133062
Epichlorohydrin	106898
Methylene chloride (Dichloromethane)	75092
Dibenz (ah) anthracene	53703
Chrysene	218019
Dimethyl aminoazobenzene	60117
Benzo (a) anthracene	56553
Benzo (b) fluoranthene	205992
Antimony trioxide	1309644
2-Nitropropane	79469
1,3-Dichloropropene	542756
7, 12-Dimethylbenz(a) anthracene	57976
Benz(c) acridine	225514
Indeno(1,2,3-cd)pyrene	193395
1,2:7,8-Dibenzopyrene	189559

Table 5 to Subpart JJ of Part 63—List of VHAP of Potential Concern Identified by Industry

CAS No.	Chemical name	EPA de minimis, tons/yr
68122	Dimethyl formamide	1.0
50000	Formaldehyde	0.2
75092	Methylene chloride	4.0
79469	2-Nitropropane	1.0
78591	Isophorone	0.7
1000425	Styrene monomer	1.0
108952	Phenol	0.1
111422	Dimethanolamine	5.0
109864	2-Methoxyethanol	10.0
111159	2-Ethoxyethyl acetate	10.0

[63 FR 71382, Dec. 28, 1998]

Table 6 to Subpart JJ of Part 63—VHAP of Potential Concern

CAS No.	Chemical name	EPA de minimis, tons/yr*
92671	4-Aminobiphenyl	1.0
96093	Styrene oxide	1.0
64675	Diethyl sulfate	1.0
59892	N-Nitrosomorpholine	1.0
68122	Dimethyl formamide	1.0
680319	Hexamethylphosphoramide	0.01
60355	Acetamide	1.0
101779	4,4'-Methylenedianiline	1.0
90040	o-Anisidine	1.0
1746016	2,3,7,8-Tetrachlorodibenzo-p-dioxin	0.00000006
92875	Benzidine	0.00003
684935	N-Nitroso-N-methylurea	0.00002
542881	Bis(chloromethyl) ether	0.00003

79447	Dimethyl carbamoyl chloride	0.002
75558	1,2-Propylenimine (2-Methyl aziridine)	0.0003
57147	1,1-Dimethyl hydrazine	0.0008
96128	1,2-Dibromo-3-chloropropane	0.001
62759	N-Nitrosodimethylamine	0.0001
50328	Benzo (a) pyrene	0.001
1336363	Polychlorinated biphenyls (Aroclors)	0.0009
76448	Heptachlor	0.002
119937	3,3'-Dimethyl benzidine	0.001
79061	Acrylamide	0.002
118741	Hexachlorobenzene	0.004
57749	Chlordane	0.005
1120714	1,3-Propane sultone	0.003
106990	1,3-Butadiene	0.007
53963	2-Acetylaminoflourine	0.0005
91941	3,3'-Dichlorobenzidine	0.02
58899	Lindane (hexachlorocyclohexane, gamma)	0.005
95807	2,4-Toluene diamine	0.002
111444	Dichloroethyl ether (Bis(2-chloroethyl)ether)	0.006
122667	1,2—Diphenylhydrazine	0.009
8001352	Toxaphene (chlorinated camphene)	0.006
121142	2,4-Dinitrotoluene	0.002
119904	3,3'-Dimethoxybenzidine	0.01
50000	Formaldehyde	0.2
101144	4,4'-Methylene bis(2-chloroaniline)	0.02
107131	Acrylonitrile	0.03
106934	Ethylene dibromide(1,2-Dibromoethane)	0.01
72559	DDE (1,1-p-chlorophenyl 1-2 dichloroethylene)	0.01

510156	Chlorobenzilate	0.04
62737	Dichlorvos	0.02
75014	Vinyl chloride	0.02
75218	Ethylene oxide	0.09
96457	Ethylene thiourea	0.06
593602	Vinyl bromide (bromoethene)	0.06
67663	Chloroform	0.09
87865	Pentachlorophenol	0.07
51796	Ethyl carbamate (Urethane)	0.08
107062	Ethylene dichloride (1,2-Dichloroethane)	0.08
78875	Propylene dichloride (1,2-Dichloropropane)	0.1
56235	Carbon tetrachloride	0.1
71432	Benzene	0.2
140885	Ethyl acrylate	0.1
75569	Propylene oxide	0.5
62533	Aniline	0.1
106467	1,4-Dichlorobenzene(p)	0.3
88062	2,4,6-Trichlorophenol	0.6
117817	Bis (2-ethylhexyl) phthalate (DEHP)	0.5
95534	o-Toluidine	0.4
114261	Propoxur	2.0
79016	Trichloroethylene	1.0
123911	1,4-Dioxane (1,4-Diethyleneoxide)	0.6
75070	Acetaldehyde	0.9
75252	Bromoform	2.0
133062	Captan	2.0
106898	Epichlorohydrin	2.0
75092	Methylene chloride (Dichloromethane)	4.0

127184	Tetrachloroethylene (Perchloroethylene)	4.0
53703	Dibenz (ah) anthracene	0.01
218019	Chrysene	0.01
60117	Dimethyl aminoazobenzene	1.0
56553	Benzo (a) anthracene	0.01
205992	Benzo (b) fluoranthene	0.01
79469	2-Nitropropane	1.0
542756	1,3-Dichloropropene	1.0
57976	7,12-Dimethylbenz (a) anthracene	0.01
225514	Benz(c)acridine	0.01
193395	Indeno(1,2,3-cd)pyrene	0.01
189559	1,2:7,8-Dibenzopyrene	0.01
79345	1,1,2,2-Tetrachloroethane	0.03
91225	Quinoline	0.0006
75354	Vinylidene chloride (1,1-Dichloroethylene)	0.04
87683	Hexachlorobutadiene	0.09
82688	Pentachloronitrobenzene (Quintobenzene)	0.03
78591	Isophorone	0.7
79005	1,1,2-Trichloroethane	0.1
74873	Methyl chloride (Chloromethane)	1.0
67721	Hexachloroethane	0.5
1582098	Trifluralin	0.9
1319773	Cresols/Cresylic acid (isomers and mixture)	1.0
108394	m-Cresol	1.0
75343	Ethylidene dichloride (1,1-Dichloroethane)	1.0
95487	o-Cresol	1.0
106445	p-Cresol	1.0
74884	Methyl iodide (Iodomethane)	1.0

100425	Styrene	1.0
107051	Allyl chloride	1.0
334883	Diazomethane	1.0
95954	2,4,5—Trichlorophenol	1.0
133904	Chloramben	1.0
106887	1,2—Epoxybutane	1.0
108054	Vinyl acetate	1.0
126998	Chloroprene	1.0
123319	Hydroquinone	1.0
92933	4-Nitrobiphenyl	1.0
56382	Parathion	0.1
13463393	Nickel Carbonyl	0.1
60344	Methyl hydrazine	0.006
151564	Ethylene imine	0.0003
77781	Dimethyl sulfate	0.1
107302	Chloromethyl methyl ether	0.1
57578	beta-Propiolactone	0.1
100447	Benzyl chloride	0.04
98077	Benzotrichloride	0.0006
107028	Acrolein	0.04
584849	2,4—Toluene diisocyanate	0.1
75741	Tetramethyl lead	0.01
78002	Tetraethyl lead	0.01
12108133	Methylcyclopentadienyl manganese	0.1
624839	Methyl isocyanate	0.1
77474	Hexachlorocyclopentadiene	0.1
62207765	Fluomine	0.1
10210681	Cobalt carbonyl	0.1

79118	Chloroacetic acid	0.1
534521	4,6-Dinitro-o-cresol, and salts	0.1
101688	Methylene diphenyl diisocyanate	0.1
108952	Phenol	0.1
62384	Mercury, (acetato-o) phenyl	0.01
98862	Acetophenone	1.0
108316	Maleic anhydride	1.0
532274	2-Chloroacetophenone	0.06
51285	2,4-Dinitrophenol	1.0
109864	2-Methoxy ethanol	10.0
98953	Nitrobenzene	1.0
74839	Methyl bromide (Bromomethane)	10.0
75150	Carbon disulfide	1.0
121697	N,N-Dimethylaniline	1.0
106514	Quinone	5.0
123386	Propionaldehyde	5.0
120809	Catechol	5.0
85449	Phthalic anhydride	5.0
463581	Carbonyl sulfide	5.0
132649	Dibenzofurans	5.0
100027	4-Nitrophenol	5.0
540841	2,2,4-Trimethylpentane	5.0
111422	Diethanolamine	5.0
822060	Hexamethylene-1,6-diisocyanate	5.0
	Glycol ethers ^a	5.0
	Polycyclic organic matter ^b	0.01

*These values are based on the de minimis levels provided in the proposed rulemaking pursuant to section 112(g) of the Act using a 70-year lifetime exposure duration for all VHAP. Default assumptions and the de minimis values based on inhalation reference doses (RfC) are not changed by this adjustment.

^aExcept for ethylene glycol butyl ether, ethylene glycol ethyl ether (2-ethoxy ethanol), ethylene glycol hexyl ether, ethylene glycol methyl ether (2-methoxyethanol), ethylene glycol phenyl ether, ethylene glycol propyl ether, ethylene glycol mono-2-ethylhexyl ether, diethylene glycol butyl ether, diethylene glycol ethyl ether, diethylene glycol methyl ether, diethylene glycol hexyl ether, diethylene glycol phenyl ether, diethylene glycol propyl ether, triethylene glycol butyl ether, triethylene glycol ethyl ether, triethylene glycol methyl ether, triethylene glycol propyl ether, ethylene glycol butyl ether acetate, ethylene glycol ethyl ether acetate, and diethylene glycol ethyl ether acetate.

^bExcept for benzo(b)fluoranthene, benzo(a)anthracene, benzo(a)pyrene, 7,12-dimethylbenz(a)anthracene, benz(c)acridine, chrysene, dibenz(ah)anthracene, 1,2:7,8-dibenzopyrene, indeno(1,2,3-cd)pyrene, but including dioxins and furans.

[63 FR 71383, Dec. 28, 1998]

Indiana Department of Environmental Management
Office of Air Quality
Technical Support Document (TSD) for a
Part 70 Operating Permit Renewal

Source Background and Description

Source Name:	Patrick Industries, Inc.
Source Location:	Plant 130: 1808 West Hively Avenue, Elkhart, Indiana 46517 Plant 140: 57420 Nagy Drive, Elkhart, Indiana 46517
County:	Elkhart
SIC Code:	2434, 2421, 2431, 2541
Permit Renewal No.:	T039-29242-00324
Permit Reviewer:	APT

The Office of Air Quality (OAQ) has reviewed the operating permit renewal application from Patrick Industries, Inc., relating to the operation of a stationary wood product manufacturing plant. On May 10, 2010, Patrick Industries, Inc. submitted an application to the OAQ requesting to renew its operating permit. Patrick Industries, Inc. was issued its first Part 70 Operating Permit Renewal (T039-17506-00324) on February 7, 2006.

Source Definition

This stationary wood product manufacturing source consists of two (2) plants:

- (a) Plant 130 is located at 1808 West Hively Avenue, Elkhart, Indiana 46517; and
- (b) Plant 140 is located at 57420 Nagy Drive, Elkhart, Indiana 46517.

These two (2) plants are located on one (1) or more contiguous properties, have the same two-digit SIC codes and are under common ownership; therefore they are considered one (1) major source as defined by 326 IAC 2-7-1(22). This determination was made during the issuance of Part 70 permit T039-7650-00324, issued on October 6, 1998.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units:

Plant 130 (1808 West Hively Avenue)

- (a) One (1) sawdust storage silo, identified as S-1, constructed in 1997, with a capacity of 690 cubic yards, collecting sawdust from the woodworking equipment through a cyclonic baghouse system, and exhausting to stack C1-1.
- (b) Woodworking equipment, identified as WW1a, constructed in 1995, with a maximum throughput of 25,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to three (3) stacks, identified as C1-2, C1-3 and C1-4.
- (c) Woodworking equipment, identified as WW1b, constructed in 1995, with a maximum throughput of 25,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to two (2) stacks, identified as C1-5 and C1-6.

- (d) Two (2) denibbers for D1, identified as DN1a and DN1b, constructed in 2000, each with maximum capacities of 3,900 board feet per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to stack C1-4.
- (e) One (1) denibber for D4, identified as DN4, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, using a cyclonic baghouse system to control particulate emissions, and exhausting to stack C1-4.
- (f) One (1) adhesive spray booth and one (1) wood wrapping press, identified as SA1 and WWP1, respectively, constructed in 1995, with a maximum capacity of laminating 39.143 linear feet per hour, utilizing a high volume low pressure (HVLP) application system, with particulate emissions controlled by dry filters, and exhausting to stack E1-10. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (g) One (1) dualtech automated back sealing machine, identified as D1, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D2, exhausting to stack E1-2, and a hot air drying tunnel exhausting to stack E1-3. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (h) One (1) rototech automated front staining machine, identified as D3, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) airless/air assist spray guns, with particulate emissions controlled by dry filters, exhausting to stack E1-4, and a forced air drying tunnel exhausting to stack E1-5. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (i) One (1) dualtech automated sealing machine, identified as D4, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D5, exhausting to stack E1-6, and a hot air/infrared drying tunnel exhausting to stack E1-7. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (j) One (1) dualtech automated topcoat machine, identified as D6, constructed in 2000, with a maximum capacity of 3,900 board feet per hour, equipped with eight (8) airless/air assist spray guns, with particulate emissions controlled by a water wall and water scrubber system, identified as D7, exhausting to stack E1-8, a hot air drying tunnel exhausting to stack E1-9, and a non-heated cooling hood exhausting inside the building. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (k) One (1) manual touch up booth, identified as TU1, constructed in 2000, with a maximum capacity of one (1) gallon of stain, two (2) gallons of sealer, and two (2) gallons of topcoat per day, consisting of one (1) airless/air assist gun, with particulate emissions controlled by dry filters, exhausting to stack TU-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (l) One (1) rototech automated back staining machine, identified as D8, constructed in 2002, with a maximum capacity of 3,900 board feet per hour, equipped with twenty (20) HVLP spray guns used for coating cabinet doors and an infrared drying oven, with particulate emissions controlled by dry filters, and exhausting to stack E1-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

- (m) One (1) vacuum coater, identified as VC-1, constructed in 1995, with a maximum capacity of 5,000 linear feet of wood per hour, applying coatings containing no VOC or HAP to wood trim, utilizing an ultraviolet (UV) curing process, with particulate emissions controlled by dry filters, and exhausting to stack E1-11. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (n) One (1) manual coating booth with two (2) HVLP spray guns, identified as D-9, approved for construction in 2009, with a maximum capacity of 1000 doors per day, with particulate emissions controlled by dry filters, exhausting to stack E1-12. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (o) One (1) spray coating line, identified as SCL-1, approved for construction in 2010, consisting of coating equipment and electric dryer, with a throughput capacity of 250 units per hour, using manual air assisted airless spray application method, venting to stack SCLS1, and using dry filters as control. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Plant 140 (57420 Nagy Drive)

- (p) Woodworking equipment, identified as WW2a, constructed in 1995, with a maximum throughput of 3,000 pounds of wood per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-1.
- (q) Woodworking equipment, identified as WW2b, constructed in 1995, with a maximum throughput of 5,000 pounds of wood per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2.
- (r) Six (6) wood wrapping machines, identified as WR2a, WR2b, WR2c, WR2d, WR2e, and WR2f, constructed in 1995, each with a maximum capacity of 280 pounds of wood styles per hour, using water-based and hot melt adhesives, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, exhausting to stack C2-1. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.
- (s) Four (4) wood panel laminating machines, identified as WPL2, constructed in 1995, each with a maximum capacity of 1,500 pounds of wood panels per hour, using a cyclonic baghouse system, replaced in 2008, to control particulate emissions, and exhausting to stack C2-2. Under 40 CFR 63, Subpart JJ, this is an affected facility that is engaged in the manufacture of wood furniture or wood furniture components.

Emission Units and Pollution Control Equipment Constructed and/or Operated without a Permit

There are no unpermitted emission units operating at this source during this review process.

Insignificant Activities

The source also consists of the following insignificant activities:

- (a) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour:

- (1) One (1) natural gas-fired boiler, identified as B1, constructed in 1995, rated at 0.4 MMBtu/hr, and exhausting to stack B1. [326 IAC 6-2-4]
- (2) Four (4) natural gas-fired hot water boilers, identified as AB1, AB2, AB3, and AB4, constructed in 2000, with each rated at 1.0 MMBtu per hour, exhausting to stacks AB1, AB2, AB3, and AB4, respectively. [326 IAC 6-2-4]
- (3) Fifteen (15) natural gas-fired forced air and radiant heaters, identified as H1 through H15, constructed after September 21, 1983, with nine (9) units rated at 0.2 MMBtu/hr and six (6) units rated at 0.1 MMBtu/hr, and exhausting to stacks H1 – H15, respectively.
- (b) Woodworking equipment, identified as WW1c, constructed in 2003, having a maximum throughput capacity of 5,000 pounds of wood per hour, using a cyclonic baghouse system to control particulate emissions, with a maximum air flow rate of 35,000 standard cubic feet of air per minute (scfm) and a maximum outlet grain loading of less than 0.003 grains per dry standard cubic foot of exhaust air, and exhausting to stack C1-7.
- (c) Closed loop heating and cooling systems.
- (d) Infrared cure equipment.
- (e) Exposure chambers (“towers, “columns”), for curing of ultraviolet inks and ultraviolet coatings where heat is the intended discharge.
- (f) Solvent recycling systems with batch capacity less than or equal to 100 gallons.
- (g) Any operation using aqueous solutions containing less than 1% by weight VOCs excluding HAPs.
- (h) Trimmers that do not produce fugitive emissions and that are equipped with a dust collection or trim material recovery device such as a bag filter or cyclone.
- (i) Water based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs.
- (j) Blowdown for any of the following: sight glass; boiler; compressors; pumps; and cooling tower.

Existing Approvals

Since the issuance of Part 70 Operating Permit Renewal No. T039-17506-00324, on February 7, 2006, the source has constructed or has been operating under the following approvals as well:

- (1) Administrative Amendment No. 039-24904-00324, issued on August 8, 2007;
- (2) Administrative Amendment, 039-26481-00324, issued on May 28, 2008;
- (3) Administrative Amendment, 039-26709-00324, issued on August 22, 2008;
- (4) Minor Source Modification, 039-27770-00324, issued on November 17, 2009;
- (5) Significant Permit Modification, 039-27902-00324, issued on January 8, 2010;
- (6) Significant Source Modification, 039-28997-00324, issued on June 28, 2010; and
- (7) Significant Permit Modification, 039-29039-00324, issued on July 16, 2010.

Enforcement Issues

There are no enforcement actions pending.

Emission Calculations

In October 1993 a Final Order Granting Summary Judgment was signed by Administrative Law Judge (“ALJ”) Garrettson resolving an appeal filed by Kimball Hospitality Furniture Inc. (Cause Nos. 92-A-J-730 and 92-A-J-833) related to the method by which IDEM calculated potential emissions from woodworking operations. In his findings, the ALJ determined that particulate controls are necessary for the facility to produce its normal product and are integral to the normal operation of the facility, and therefore, potential emissions should be calculated after controls. Based on this ruling, potential emissions for particulate matter were calculated after consideration of the controls.

See Appendix A of this document for detailed emissions calculations.

County Attainment Status

The source is located in Elkhart County.

Pollutant	Designation
SO ₂	Better than national standards.
CO	Unclassifiable or attainment effective November 15, 1990.
O ₃	Attainment effective July 19, 2007, for the 8-hour ozone standard. ¹
PM ₁₀	Unclassifiable effective November 15, 1990.
NO ₂	Cannot be classified or better than national standards.
Pb	Not designated.
¹ Attainment effective October 18, 2000, for the 1-hour ozone standard for the South Bend-Elkhart area, including Elkhart County, and is a maintenance area for the 1-hour National Ambient Air Quality Standards (NAAQS) for purposes of 40 CFR 51, Subpart X*. The 1-hour standard was revoked effective June 15, 2005. On October 25, 2006, the Indiana Air Pollution Control Board finalized a rule revision to 326 IAC 1-4-1 revoking the one-hour ozone standard in Indiana. Unclassifiable or attainment effective April 5, 2005, for PM _{2.5} .	

- (a) **Ozone Standards**
 Volatile organic compounds (VOC) and Nitrogen Oxides (NO_x) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to ozone. Elkhart County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

- (b) **PM_{2.5}**
 Elkhart County has been classified as attainment for PM_{2.5}. On May 8, 2008, U.S. EPA promulgated the requirements for Prevention of Significant Deterioration (PSD) for PM_{2.5} emissions. These rules became effective on July 15, 2008. Indiana has three (3) years from the publication of these rules to revise its PSD rules, 326 IAC 2-2, to include those requirements. The May 8, 2008 rule revisions require IDEM to regulate PM₁₀ emissions as a surrogate for PM_{2.5} emissions until 326 IAC 2-2 is revised.

- (c) **Other Criteria Pollutants**
 Elkhart County has been classified as attainment or unclassifiable in Indiana for PM₁₀, SO₂, NO₂, CO and lead. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2. See the State Rule Applicability section.

Fugitive Emissions

Since this type of operation is not one (1) of the twenty-eight (28) listed source categories under 326 IAC 2-2 or 326 IAC 2-7, and there is no applicable New Source Performance Standard that was in effect on August 7, 1980, fugitive emissions are not counted toward the determination of PSD and Part 70 Permit applicability.

Unrestricted Potential Emissions

This table reflects the unrestricted potential emissions of the source.

Unrestricted Potential Emissions	
Pollutant	Tons/year
PM	> 250
PM ₁₀	> 250
SO ₂	< 100
VOC	> 250
CO	< 100
NO _x	< 100
Single HAP (Xylene)	> 10
Total HAP	> 25

- (a) The potential to emit (as defined in 326 IAC 2-7-1(29)) of VOC, PM, and PM₁₀ is greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7 and will be issued a Part 70 Operating Permit Renewal.
- (b) The potential to emit (as defined in 326 IAC 2-7-1(29)) of any single HAP is greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination of HAPs is greater than twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the 2006 OAQ pollutant emission data.

Pollutant	Actual Emissions (ton/yr)
PM	48
PM ₁₀	48
SO ₂	0
VOC	115
CO	1
NO _x	1
Worst case HAP Xylene	(not reported)
Total HAPs	(not reported)

Part 70 Permit Conditions

This source is subject to the requirements of 326 IAC 2-7, because the source met the following:

- (a) Emission limitations and standards, including those operational requirements and limitations that assure compliance with all applicable requirements at the time of issuance of Part 70 permits.
- (b) Monitoring and related record keeping requirements which assume that all reasonable information is provided to evaluate continuous compliance with the applicable requirements.

Potential to Emit After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered federally enforceable only after issuance of this Part 70 permit renewal, and only to the extent that the effect of the control equipment is made practically enforceable in the permit.

Process/facility	Potential to Emit (tons/year)						
	PM	PM ₁₀ *	SO ₂	VOC	CO	NO _x	HAPs
Existing Units: All Surface Coating facilities and All Woodworking facilities	< 250	< 250	---	< 250	---	---	82.69
Other Existing Units: Natural Gas Fired Heaters and Boilers (B1, AB1-AB4, H1-H15), Insignificant Laminating Activities			<1		<3	<3	
Total for Source	<250	<250	<1	<250	<3	<3	>10/25
Title V Major Source Thresholds	NA	100	100	100	100	100	10 single / 25 combined
PSD Major Source Thresholds	250	250	250	250	250	250	NA
*Under the Part 70 Permit program (40 CFR 70), particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers (PM10), not particulate matter (PM), is considered as a "regulated air pollutant".							

- (a) This existing stationary source is not major for PSD because the emissions of each regulated pollutant are less than two hundred fifty (<250) tons per year, and it is not in one (1) of the twenty-eight (28) listed source categories.

Federal Rule Applicability

- (a) Pursuant to 40 CFR 64.2, Compliance Assurance Monitoring (CAM) is applicable to each existing pollutant-specific emission unit that meets the following criteria:
- (1) has a potential to emit before controls equal to or greater than the major source threshold for the pollutant involved;
 - (2) is subject to an emission limitation or standard for that pollutant; and
 - (3) uses a control device, as defined in 40 CFR 64.1, to comply with that emission limitation or standard.

The following table is used to identify the applicability of each of the criteria, under 40 CFR 64.1, to each existing emission unit and specified pollutant subject to CAM:

Emission Unit/ Pollutant	Control Device Used	Emission Limitation (Y/N)	Uncontrolled PTE of (tons/year)	Controlled PTE of (tons/year)	Major Source Threshold (tons/year)	CAM Applicable (Y/N)	Large Unit (Y/N)
VOC							
SCL-1	N	Y	114.56	114.56	100	N	N
D1	N	Y	149.9	149.9	100	N	N
D3, D8	N	Y	329.44	329.44	100	N	N

Emission Unit/ Pollutant	Control Device Used	Emission Limitation (Y/N)	Uncontrolled PTE of (tons/year)	Controlled PTE of (tons/year)	Major Source Threshold (tons/year)	CAM Applicable (Y/N)	Large Unit (Y/N)
D4	N	Y	124.92	124.92	100	N	N
D6	N	Y	82.4	82.4	100	N	N
SA1, WWP1	N	Y	0	0	100	N	N
VC-1	N	Y	0	0	100	N	N
D9	N	Y	32	32	100	N	N
WR2, WPL2	N	Y	0	0	100	N	N
<i>PM/PM10</i>							
SCL-1	Y	Y	60	2.94	100	N	N
D1	Y	Y	15.62	3.07	100	N	N
D3, D8	Y	Y	6.28	1.24	100	N	N
D4	Y	Y	14.48	2.84	100	N	N
D6	Y	Y	12.91	2.53	100	N	N
SA1, WWP1	Y	Y	3.6	0.7	100	N	N
VC-1	Y	Y	2.17	0.43	100	N	N
D9	Y	Y	2.43	0.24	100	N	N
WR2, WPL2	Y	Y	0	0	100	N	N
232RF8 Storage Silo (S-1)	Y	Y	260	2.60	100	Y	N
276RF8 Mill Room (WW1a)	Y	Y	309	3.09	100	Y	N
72RF8 Mill Room (WW1a)	Y	Y	214	2.14	100	Y	N
484RF10 HWD (DN1a, DN1b, & DN4)	Y	Y	678	6.78	100	Y	N
156RF10 KC (WW1b)	Y	Y	218	2.18	100	Y	N
276RF10 Grinder (WW1b)	Y	Y	387	3.87	100	Y	N
Woodworking 1c (WW1c)	Y	Y	405	4.05	100	Y	N

Emission Unit/ Pollutant	Control Device Used	Emission Limitation (Y/N)	Uncontrolled PTE of (tons/year)	Controlled PTE of (tons/year)	Major Source Threshold (tons/year)	CAM Applicable (Y/N)	Large Unit (Y/N)
276RF8 Mill Room (WW2a)	Y	Y	676	6.76	100	Y	N
wood wrapping (WR2a - WR2f)	Y	Y			100	Y	N
276RF8 Mill Room (WW2b)	Y	Y	327	3.27	100	Y	N
81PJD10 Laminators (WPL2)	Y	Y			100	Y	N

Based on this evaluation, the requirements of 40 CFR Part 64, CAM are applicable to the woodworking, laminating, denibbing and sawdust storage silo operations, identified as: WW1a, WW1b, WW1c, WW2a, WR2a - WR2f, WW2b, WPL2, S-1, DN1a, DN1b, and DN4 exhausting to stacks C1-1, C1-2, C1-3, C1-4, C1-5, C1-6, C1-7, C2-1, and C2-2 for particulate matter (PM). A CAM plan has been submitted and the Compliance Determination and Monitoring Requirements section includes a detailed description of the CAM compliance requirements. The CAM plan for these emission units is as follows:

The Permittee shall use cyclones and/or baghouses to control particulate emissions from the woodworking, laminating, denibbing and sawdust storage operations. The cyclones and baghouses shall be in operation at all times that the woodworking, laminating, denibbing and sawdust storage operations are in operation. Visible emissions from the cyclones and baghouses shall be observed daily using procedures in accordance with Method 22 and normal and abnormal emissions shall be recorded. Baghouse and cyclone inspections shall be performed quarterly when venting to the atmosphere. In the event that bag/cyclone failure has been observed, the affected units and their associated processes shall be shut down immediately until the failed units have been repaired or replaced.

- (b) The requirements of the New Source Performance Standards for Small Industrial-Commercial-Institutional Steam Generating Units (326 IAC 12, 40 CFR 60, Subpart Dc) are not applicable to the four (4) natural gas-fired boilers because these boilers each have a maximum design heat input capacity less than 10 MMBtu/hr.
- (c) New Source Performance Standards (NSPS) 40 CFR Part 60
There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) applicable to this source at this time.
- (d) This source is subject to the National Emission Standards for Hazardous Air Pollutants for Wood Furniture Manufacturing Operations (NESHAP) (40 CFR 63, Subpart JJ), which is incorporated by reference as 326 IAC 20-14. The wood furniture coating operations and adhesive application operations at the source are subject to the National Emission Standards for Hazardous Air Pollutants, 40 CFR 63, Subpart JJ, because the source is engaged, either in part or in whole, in the manufacture of wood furniture or wood furniture components, and the source is a major source of HAPs as defined in 40 CFR 63.2.

Under the National Emissions Standards for Hazardous Air Pollutants for Wood Furniture Manufacturing Operations (NESHAP) (40 CFR 63, Subpart JJ), the emission units identified as SA1, WWP1, D1, D3, D4, D6, TU1, D8, VC-1, D9, SCL-1, WR2a-f, and WPL2 are existing affected units at an existing affected source. These units are subject to the following portions of 40 CFR 63, Subpart JJ (nonapplicable portions of the NESHAP will not be included in the permit):

- (1) 40 CFR 63.800 (except (f) and (g))
- (2) 40 CFR 63.801

- (3) 40 CFR 63.802 (except (b))
- (4) 40 CFR 63.803
- (5) 40 CFR 63.804 (except (d) and (e))
- (6) 40 CFR 63.805 (except (d)(7), (d)(9), (e)(4), and (e)(6))
- (7) 40 CFR 63.806
- (8) 40 CFR 63.807
- (9) 40 CFR 63.808
- (10) Table 1
- (11) Table 2
- (12) Table 3
- (13) Table 4
- (14) Table 5
- (15) Table 6

The provisions of 40 CFR 63 Subpart A – General Provisions, which are incorporated as 326 IAC 20-1-1, apply to the facilities described in this section except when otherwise specified in 40 CFR Part 63, Subpart JJ.

- (e) The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Surface Coating of Wood Building Products, Subpart QQQQ (40 CFR Part 63), are not included in the permit for the surface coating facilities. Pursuant to 63.4681(c)(2), surface coating of wood furniture subject to Subpart JJ, including finishing, gluing, cleaning, and washoff operations associated with the production of wood furniture or wood furniture components, and surface coating of millwork and trim associated with cabinet manufacturing is not to subject to Subpart QQQQ. All of the surface coating and adhesive application facilities at this source are subject to the requirements of 40 CFR 63, Subpart JJ, and therefore, are not subject to the requirements of 40 CFR 63, Subpart QQQQ.
- (f) The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Plywood and Composite Wood Products, Subpart DDDD (40 CFR Part 63), are not included in the permit for the six (6) wood wrapping machines, identified as WR2a, WR2b, WR2c, WR2d, WR2e, and WR2f, and the three (3) wood panel laminating machines, identified as WPL2. These units apply laminated material to gypsum and wood products; however, no heated resin is utilized to bond these materials. A non-HAP containing, room temperature adhesive is applied directly to the substrate. Pursuant to 63.2231(a), this source does not meet the definition of a Plywood and Composite Wood Products manufacturing facility.
- (g) There are no new National Emission Standards for Hazardous Air Pollutants (NESHAP) (326 IAC 14, 326 IAC 20 and 40 CFR Part 63) included in this permit renewal.

State Rule Applicability - Entire Source

326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

- (a) Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration), the particulate emissions from the significant and insignificant woodworking operations, denibbers, wood wrapping operations, laminating operations and sawdust storage silo are subject to PM/PM₁₀ emission limits as shown in the following table:

Stack ID	PM/PM ₁₀ limit (lb/hr)
C1-1	3.6
C1-2	4.2
C1-3	2.9
C1-4	9.3
C1-5	3.0
C1-6	5.3
C1-7	2.9
C2-1	4.2
C2-2	1.4

- (b) Pursuant to 326 IAC 2-2 (PSD), the particulate emissions from the surface coating operations are subject to PM/PM₁₀ emission limits as shown in the following table:

PSD Minor Limit for PM / PM ₁₀ , By Stack ID	
Stack ID	PM/PM ₁₀ limit (lb/hr)
E1-1	1.1
E1-2	1.9
E1-3	1.1
E1-4	1.1
E1-5	1.1
E1-6	2.0
E1-7	1.1
E1-8	2.0
E1-9	1.1
E1-10	1.4
E1-11	1.1
TU1	1.1
E1-12	1.6
SCM1S1	1.1

These limits, combined with the total potential to emit PM/PM₁₀ from the other emission units at this source, will ensure that the potential to emit PM/PM₁₀ remains less than 250 tons per twelve (12) consecutive month period. Compliance with these limits will render the requirements of 326 IAC 2-2 (PSD) not applicable and make this source minor for PM and PM₁₀ under 326 IAC 2-2 (PSD).

- (c) The total VOC input to all the surface coating operations and laminating operations (D1, D3, D4, D6, D8, D9, TU1, SCL-1, SA1, WWP1, VC1, WR2 (a, b, c, d, e, and f), and WPL2 (3 machines)) combined shall not exceed 249 tons per twelve (12) consecutive month period, with compliance determined on a monthly basis.

This limit, in conjunction with the uncontrolled potential to emit of the boilers, heaters and insignificant laminating operations is equivalent to VOC emissions of less than 250 tons per year for the entire source. Compliance with this VOC usage limit makes the requirements of 326 IAC 2-2 (PSD) not applicable.

326 IAC 2-4.1 (New Source Toxic Control)

The potential to emit HAP from this source is greater than ten (10) tons per year for a single HAP and greater than twenty-five (25) tons per year for a combination of HAPs. However, the source is specifically regulated by NESHAP 40 CFR 63, Subpart JJ, which was issued pursuant to Section 112(d) of the CAA. Therefore, pursuant to 326 IAC 2-4.1-1(b)(2), the source is exempt from the requirements of 326 IAC 2-4.1.

326 IAC 2-6 (Emission Reporting)

This source, not located in Lake, Porter, or LaPorte County, is subject to 326 IAC 2-6 (Emission Reporting) because it is required to have an operating permit pursuant to 326 IAC 2-7 (Part 70). The potential to emit of VOC and PM₁₀ is less than 250 tons per year; and the potential to emit of CO, NO_x, and SO₂ is less than 2,500 tons per year. Therefore, pursuant to 326 IAC 2-6-3(a)(2),

triennial reporting is required. An emission statement shall be submitted in accordance with the compliance schedule in 326 IAC 2-6-3 by July 1, 2010, and every three (3) years thereafter. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 6-4 (Fugitive Dust Emissions)

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

State Rule Applicability – Individual Facilities

State Rule Applicability – Woodworking Equipment, Denibbers, Wood Wrapping Machines, Wood Laminating Machines and Sawdust Storage Silo

326 IAC 2-7-1(21)(G)(xxx)

The insignificant woodworking operation (WW1c) controlled by a cyclonic baghouse shall be considered an insignificant activity for Title V permitting purposes provided that the baghouse operations meet the requirements of 326 IAC 2-7-1(21)(G)(xxx), including the following:

- (a) Each woodworking baghouse shall not exhaust to the atmosphere greater than forty thousand (40,000) cubic feet of air per minute and shall not emit particulate matter with a diameter less than ten (10) microns in excess of one hundredth (0.01) grain per dry standard cubic foot of outlet air.
- (b) The opacity from each baghouse shall not exceed ten percent (10%).
- (c) Visible emissions from the baghouse shall be observed daily using procedures in accordance with Method 22 and normal or abnormal emissions are recorded. In the event abnormal emissions are observed for greater than six (6) minutes in duration, the following shall occur:
 - (1) The baghouse shall be inspected.
 - (2) Corrective actions, such as replacing or reseating bags, are initiated, when necessary.

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the exhaust stacks of the baghouses and cyclones controlling the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo shall not exceed the pounds per hour limits as shown in the following table:

Particulate Emission Rate		
Exhaust Stack ID	Process Weight Rate (lbs)	Particulate Emission Rate (lb/hr)
C1-1	55,000	37.8
C1-2	11,000	12.8
C1-3	7,500	9.9
C1-4	6,500	9.0
C1-5	12,000	13.6
C1-6	13,000	14.4
C1-7	5,000	7.6
C2-1	4,680	7.2
C2-2	9,500	11.6

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
P = process weight rate in tons per hour

State Rule Applicability – Surface Coating

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

Pursuant to 326 IAC 6-3-2(d), particulate emissions from the surface coating facilities shall be controlled by a dry particulate filter and/or water wall and water scrubber system, and the Permittee shall operate the control devices in accordance with manufacturer's specifications.

326 IAC 8-1-6 (Volatile Organic Compounds Limitations - BACT)

- (a) The emission units identified as D1, D3, D4, D6, D8, D9, TU1, and SCL-1 are not subject to the requirements of 326 IAC 8-1-6 (Volatile Organic Compounds Limitations - BACT) because they are each subject to the requirements of 326 IAC 8-2-12.
- (b) The emission units identified as SA1, WWP1, VC-1, WR2a through WR2f, and WPL2 are not subject to the requirements of 326 IAC 8-1-6 (Volatile Organic Compounds Limitations - BACT) because they do not have the potential to emit VOC. Any change or modification which may increase the potential to emit VOC from these facilities to greater than twenty-five (25) tons per year or more shall require prior approval by the IDEM, OAQ before such changes may take place.

326 IAC 8-2-12 (Volatile Organic Compounds (VOC))

- (a) The emission units identified as SA1, WWP1, VC-1, WR2a through WR2f, and WPL2 are not subject to the requirements of 326 IAC 8-2-12 because they do not have the potential to emit VOC.
- (b) The surface coating operations identified as D1, D3, D4, D6, D8, D9, TU1, and SCL-1 are subject to the requirements of 326 IAC 8-2-12 because they have actual VOC emissions greater than fifteen (15) pounds per day.
 - (1) Pursuant to 326 IAC 8-2-12 (Wood Furniture and Cabinet Coating), the emission units identified as D1, D3, D4, D6, D8, D9, TU1, and SCL-1 applying surface coatings to wood furniture and cabinets shall utilize one of the following application methods:

- Airless Spray Application
- Air Assisted Airless Spray Application
- Electrostatic Spray Application
- Electrostatic Bell or Disc Application
- Heated Airless Spray Application
- Roller Coating
- Brush or Wipe Application

Dip-and-Drain Application

High Volume Low Pressure (HVLP) Spray Application is an accepted alternative method of application for Air Assisted Airless Spray Application. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

State Rule Applicability – Natural Gas-Fired Boilers and Natural Gas-Fired Radiant Heaters

326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations)

The natural gas fired boilers and space heaters are not subject to the requirements of 326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations) because they have the potential to emit less than twenty-five (25) tons per year of SO₂.

326 IAC 6-2-4 (Particulate Matter- Sources of Indirect Heating)

- (a) The natural gas-fired radiant heaters at this source are not subject to the requirements of 326 IAC 6-2-4 (Particulate Matter- Sources of Indirect Heating) because they are not sources of indirect heating.
- (b) The one (1) 0.4 MMBtu natural gas-fired boiler (B1) and the four (4) 1.0 MMBtu natural gas-fired hot water boilers (AB1-AB4) are subject to the requirements of 326 IAC 6-2-4 (Particulate Emission Limitations for Sources of Indirect Heating) because each boiler was constructed after September 21, 1983. Pursuant to this rule, the particulate matter (PM) emissions from the boilers shall not exceed the pound per million Btu limit calculated using the following equation:

$$Pt = \frac{1.09}{Q^{0.26}}$$

Where Pt = pounds of particulate matter emitted per million Btu heat input (lb/MMBtu)
Q = total source maximum operating capacity rating (Q = 4.4 MMBtu/hr)

Pt for the boiler B1 is as follows: $Pt = 1.09 / 0.4^{0.26} = 1.38$ lb PM/MMBtu

Pt for the boilers AB1, AB2, AB3, and AB4 is as follows: $Pt = 1.09 / (1+1+1+1+0.4)^{0.26} = 0.74$ lb PM/MMBtu

However, pursuant to 326 IAC 6-2-4(a), for any facility with Q less than 10 MMBtu/hr, Pt shall not exceed 0.6 pounds per MMBtu heat input. Therefore, the PM emission limit for boilers B1, AB1, AB2, AB3, and AB4 shall be 0.6 lb/MMBtu, each.

Compliance Determination and Monitoring Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section

D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance determination and monitoring requirements applicable to this source are as follows:

The woodworking operations, wood wrapping machines, wood laminating machines, denibbers and sawdust storage silo have applicable compliance monitoring conditions as specified below:

(a) Particulate Control

In order to comply with 326 IAC 6-3-2, 326 IAC 2-2, 326 IAC 2-7-1(21)(G)(xxx), and 40 CFR 64, the baghouses and cyclones for particulate control shall be in operation and control emissions from the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo at all times that the woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo are in operation.

(b) Visible Emissions Notations

- (1) Daily visible emission notations of the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo stack exhausts (C1-1, C1-2, C1-3, C1-4, C1-5, C1-6, C1-7, C2-1, and C2-2), shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (2) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (3) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (4) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (5) If abnormal emissions are observed at the significant and insignificant woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo stack exhausts, the Permittee shall take reasonable response steps. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.

(c) Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the woodworking operations, wood wrapping operations, wood laminating operations, denibbers and sawdust storage silo when venting to the atmosphere. A baghouse inspection shall be performed within three (3) months of redirecting vents to the atmosphere and every three (3) months thereafter. Inspections are optional when venting to the indoors. All defective bags shall be replaced.

(d) Broken or Failed Bag Detection

- (1) For a single compartment baghouse controlling emissions from a process operated

continuously a failed unit and the associated process shall be shut down immediately until the failed unit has been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

- (2) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit has been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in the emissions unit. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Bag failure can be indicated by a significant drop in the baghouses pressure reading with abnormal visible emissions, by an opacity violation, or by other means such as gas temperature, flow rate, air infiltration, leaks, dust traces or triboflows.

(e) Storage Silo Inspections

An inspection of the sawdust outloading operation and storage silo shall be performed at least once every two (2) weeks. Section B - Preventive Maintenance Plan, of this permit, contains the Permittee's obligations with regard to repairs or replacement of defective components for the sawdust outloading operation when abnormal emissions are observed or there is evidence of sawdust in the area surrounding the storage silo.

These monitoring conditions are necessary because the baghouses and cyclones for the woodworking operations, denibbers, wood wrapping and laminating machines and sawdust storage silo must operate properly to ensure compliance with 326 IAC 2-2 (PSD), 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), 40 CFR Part 64, CAM, and 326 IAC 2-7 (Part 70).

The surface coating facilities have applicable compliance monitoring and record keeping requirements as specified below:

(a) Monitoring

- (1) Daily inspections shall be performed to verify the placement, integrity and particle loading of the dry filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating facilities stacks while one (1) or more of the booths are in operation. If a condition exists which should result in a response step, the Permittee shall take reasonable response steps. Section C - Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.
- (2) Daily inspections shall be performed to verify that the water level of the water wall/baffles meets the manufacturer's recommended level. To monitor the performance of the water wall/baffles, the water level shall be maintained weekly at a level where surface agitation indicates impact of the air flow. Water shall be kept free of solids and floating material that reduces the capture efficiency of the water pan. To monitor the performance of the baffles, weekly inspections of the baffle panels shall be conducted to verify placement and configuration meet recommendations of the manufacturer. In addition, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. If a noticeable change in overspray emission, or evidence of overspray emission is observed at any stack exhaust, the Permittee shall take reasonable response. Section C - Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.

- (3) Monthly inspections shall be performed of the coating emissions from the stacks and the presence of overspray on the rooftops and the nearby ground. When there is a noticeable change in overspray emission, or when evidence of overspray emissions is observed at any stack exhaust, the Permittee shall take reasonable response. Section C - Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take response steps shall be considered a deviation from this permit.

(b) Scrubber Inspections

An inspection of the scrubbers controlling emissions from the surface coating facilities shall be performed semi-annually. Inspections required by this condition shall not be performed in consecutive months. Section B - Preventive Maintenance Plan, of this permit, contains the Permittee's obligations with regard to repairs or replacement of defective components.

(c) Scrubber Malfunction

In the event that a scrubber malfunction has been observed:

- (1) The affected unit will be shut down immediately in accordance with safe operating procedures until the failed unit has been repaired or the appropriate components replaced".
- (2) Based upon the findings of the inspection, any additional corrective actions will be devised within eight (8) hours of discovery and will include a timetable for completion.

(d) Volatile Organic Compounds (VOC) [326 IAC 8-1-4] [326 IAC 8-1-2(a)]

Compliance with the VOC content and usage limitations shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

(e) Record Keeping Requirements

The Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken monthly and shall be complete and sufficient to establish compliance with the 326 IAC 2-2 (PSD) VOC usage limits and/or the VOC emission limits. Records necessary to demonstrate compliance shall be available within 30 days of the end of each compliance period.

- (1) The amount and VOC content of each coating material, dilution solvent and cleaning solvent used on a monthly basis. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
- (2) The total VOC usage for each month; and
- (3) The weight of VOCs emitted for each compliance period.

These monitoring and record keeping conditions are necessary because the dry filters, water wall and water scrubber system for the surface coating operations must operate properly to ensure compliance with 326 IAC 2-2 (PSD), 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes) and 326 IAC 2-7 (Part 70).

(e) Testing Requirements

(1) Woodworking Operations

The woodworking operations, laminating operations, wrapping operations, and denibbers at this source do not have a testing requirement. The woodworking operations, laminating operations, wrapping operations, and denibbers are required by Conditions in the Permit to use baghouses and cyclones to control PM and PM₁₀ emissions. Visible emission notations, quarterly inspection, and bag failure and cyclone failure requirements have been added consistent with current compliance monitoring requirements for Title V woodworking sources. These monitoring requirements should be sufficient to ensure compliance with the particulate matter emission limitations specified in the Permit.

(2) Surface Coating Operations

The surface coating operations do not have a testing requirement for PM, PM₁₀, VOC, or HAP. The surface coating operations and laminating operations at this source do not have a testing requirement for PM or PM₁₀ because each of these emissions units accounts for a small portion of the total potential to emit for PM or PM₁₀ from the source before controls. The Permittee is not required to perform compliance stack tests on the surface coating facilities and laminating operations for VOC and HAP emissions because there are no VOC/HAP control devices in operation and records must be kept of all VOCs and HAPs used at the source.

Recommendation

The staff recommends to the Commissioner that this Part 70 Operating Permit Renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on May 10, 2010.

Conclusion

The operation of this stationary wood product manufacturing plant shall be subject to the conditions of the attached Part 70 Operating Permit Renewal No. 039-29242-00324.

IDEM Contact

- (a) Questions regarding this proposed permit can be directed to Angela Taylor at the Indiana Department Environmental Management, Office of Air Quality, Permits Branch, 100 North Senate Avenue, MC 61-53 IGCN 1003, Indianapolis, Indiana 46204-2251 or by telephone at (317) 234-6543 or toll free at 1-800-451-6027 extension 6543.
- (b) A copy of the findings is available on the Internet at: <http://www.in.gov/ai/appfiles/idem-caats/>
- (c) For additional information about air permits and how the public and interested parties can participate, refer to the IDEM's Guide for Citizen Participation and Permit Guide on the Internet at: www.idem.in.gov

**Appendix A: Emissions Calculations
Emissions Summary**

Source Name: Patrick Industries, Inc.
Source Address: **Plant 1:** 1808 West Hively Avenue, Elkhart, Indiana 46517
Plant 2: 57420 Nagy Drive, Elkhart, Indiana 46517
County: Elkhart
SIC Code: 2434, 2421, 2431, 2541
Operation Permit No.: T039-29242-00324
Permit Reviewer: APT

<u>Pollutant</u>	<u>Emissions Generating Activity</u>			<u>TOTAL</u>
	<u>Surface Coating</u>	<u>Combustion</u>	<u>Woodworking</u>	
PM	120.59	0.23	3474.37	3595.19
PM10	120.59	0.23	3474.37	3595.19
SO2	-----	0.02	-----	0.02
NOx	-----	2.98	-----	2.98
VOC	945.07	0.16	-----	945.24
CO	-----	2.50	-----	2.50
total HAPs	101.57	0.06	-----	101.63
worst case single HAP - Xylene	44.51	0.03	-----	44.54

<u>Pollutant</u>	<u>Emissions Generating Activity</u>			<u>TOTAL</u>
	<u>Surface Coating</u>	<u>Combustion</u>	<u>Woodworking</u>	
PM	16.45	0.23	34.74	51.42
PM10	16.45	0.23	34.74	51.42
SO2	-----	0.02	-----	0.02
NOx	-----	2.98	-----	2.98
VOC	limited < 249.0	0.16	-----	< 250
CO	-----	2.50	-----	2.50
total HAPs	101.52	0.06	-----	101.57
worst case single HAP - Xylene	53.81	0.03	-----	53.84

Appendix A: Emissions Calculations

VOC and Particulate

From Surface Coating Operations

Source Name: Patrick Industries, Inc.
 Source Address: Plant 1: 1808 West Hively Avenue, Elkhart, Indiana 46517
 Plant 2: 57420 Nagy Drive, Elkhart, Indiana 46517

County: Elkhart
 SIC Code: 2434, 2421, 2431, 2541

Operation Permit No.: T039-29242-00324
 Permit Reviewer: APT

Material	Unit ID	Stack ID	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water and Exempt Solvents	Weight % Organics	Volume % Non-Volatiles (solids)	Gal of Mat. - gal/unit	Maximum unit/hour	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	lb VOC/gal solids	Transfer Efficiency	Uncontrolled Particulate Potential (lb/hr)	PM Control Efficiency	Controlled Particulate Potential (lb/hr)	Uncontrolled Particulate Potential (ton/yr)	Controlled Particulate Potential (tons/yr)			
Plant 130																								
Helmbond 859 adhesive	SA1	E1-10	8.92	54.0%	54.0%	0.00%	45.0%	0.005	100	0.00	0.00	0.00	0.00	0.00	0.00	80%	0.41	80%	0.08	1.80	0.35			
Helmbond 859 adhesive	WWP1	E1-10	8.92	54.0%	54.0%	0.00%	45.0%	0.005	100	0.00	0.00	0.00	0.00	0.00	0.00	80%	0.41	80%	0.08	1.80	0.35			
970-40LSV-435A-437-6446 MULTICURE	D1	E1-2	7.40	79.1%	39.2%	39.9%	20.8%	0.0081	1424	4.86	2.96	34.13	819.11	149.49	0.00	80%	3.57	80%	0.71	15.62	3.07			
Adom Stain Base 4	D3	E1-4	6.72	98.0%	77.0%	21.0%	2.0%	0.0187	1424	6.14	1.41	37.61	902.57	164.72	70.49	80%	0.72	80%	0.14	3.14	0.62			
970-10LSV-434-437-6411)10 SHEEN MULTICURE	D4	E1-6	7.44	77.5%	38.8%	38.7%	21.8%	0.007	1424	4.71	2.88	28.52	684.48	124.92	0.00	80%	3.31	80%	0.66	14.48	2.84			
370-72CSV-1975-CHEMIVINYLS(46-6161)	D6	E1-8	7.41	79.9%	54.2%	25.7%	20.0%	0.007	1424	4.16	1.90	18.81	451.63	82.40	0.00	80%	2.95	80%	0.59	12.91	2.53			
970-40LSV-435A-437-6446 MULTICURE	TU1	TU-1	7.40	79.1%	39.2%	39.9%	20.8%	0.0081	1424	4.86	2.96	34.13	819.11	149.49	0.00	80%	3.57	80%	0.71	15.62	3.07			
Adom Stain Base 4	D8	E1-1	6.72	98.0%	77.0%	21.0%	2.0%	0.0187	1424	6.14	1.41	37.61	902.57	164.72	70.49	80%	0.72	80%	0.14	3.14	0.62			
Akzo 973-FSW-863	VC-1	E1-11	10.00	1.1%	0.0%	1.10%	98.5%	0.001	500	0.11	0.11	0.03	0.66	0.12	0.00	80%	0.49	80%	0.10	2.17	0.43			
431-7050SPB Chemiguard II	D-9	E1-12	7.52	77.3%	17.6%	59.70%	22.6%	0.013	125	5.45	4.49	7.30	175.09	31.95	0.00	80%	0.55	90%	0.06	2.43	0.24			
PRIMER - WHITE NDS2002 - worst case VOC	SCL-1	SCLS1	8.79	59.49%	9.32%	50.17%	40.51%	0.0160	250	4.86	4.41	17.64	423.35	77.26	10.89	80%	2.85	95%	0.14	12.48	0.61			
PAINT - WHITE EGS570-90015 - Worst Case PM	SCL-1	SCLS1	9.87	54.23%	47.04%	7.19%	45.77%	0.0480	250	1.34	0.71	8.52	204.38	37.70	1.55	80%	10.84	95%	0.54	47.49	2.33			
Plant 140																								
40-003A adhesive	WR2a-WR2f	C2-1	8.80	43.0%	43.0%	0.00%	55.0%	0.050	1000	0.00	0.00	0.00	0.00	0.00	0.00	100%	0.00	100%	0.00	0.00	0.00			
40-003A adhesive	WPL2	C2-2	8.80	43.0%	43.0%	0.00%	55.0%	0.050	1000	0.00	0.00	0.00	0.00	0.00	0.00	100%	0.00	100%	0.00	0.00	0.00			
Acetone and n-Butyl acetate are the cleaning materials used.													PTE		945.07						120.59		16.45	

Appendix A: Emissions Calculations
HAP Emissions from Surface Coating Operations

Source Name: Patrick Industries, Inc.
 Source Address: Plant 1: 1808 West Hively Avenue, Elkhart, Indiana 46517
 Plant 2: 57420 Nagy Drive, Elkhart, Indiana 46517
 County: Elkhart
 SIC Code: 2434, 2421, 2431, 2541
 Operation Permit No.: T039-29242-00324
 Permit Reviewer: APT

Material	Unit ID	Stack ID	Density (lb/gal)	Gal of Mat. - gal/unit	Maximum unit/hour	Weight % Toluene	Weight % Cumene	Weight % Formaldehyde	Weight % Ethylbenzene	Weight % Xylenes	Weight % Methyl Alcohol	Weight % Naphthalene	Toluene Emissions (ton/yr)	Cumene Emissions (ton/yr)	Formaldehyde Emissions (ton/yr)	Ethylbenzene Emissions (ton/yr)	Xylenes Emissions (ton/yr)	Methanol Emissions (ton/yr)	Naphthalene Emissions (ton/yr)
Plant 130																			
Helmbond 899 adhesive	SA1	E1-10	8.92	0.086	100	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Helmbond 899 adhesive	WWP1	E1-10	8.92	0.056	100	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
970-40LV-435A-437-6446 MULTICURE	D1	E1-2	7.40	0.0081	1424	1.96%	0.004%	0.007%	0.582%	2.484%	0.000%	0.049%	7.35	0.01	0.03	2.18	9.30	0.00	0.18
Span Base #3	D3	E1-4	6.66	0.0187	1424	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
970-10LV-434-437-6411100 SHEEN MULTICURE	D4	E1-6	7.40	0.007	1424	1.96%	0.004%	0.007%	0.582%	2.472%	0.00%	0.049%	6.32	0.01	0.02	1.87	7.97	0.00	0.16
970-72CV-1975-CHEM/INYL(546-5161)	D6	E1-8	7.41	0.007	1424	0.013%	0.007%	0.000%	0.503%	2.161%	0.00%	0.00%	0.04	0.02	0.00	1.62	6.94	0.00	0.00
970-40LV-435A-437-6446 MULTICURE	TU1	TU-1	7.40	0.0081	1424	1.96%	0.004%	0.007%	0.582%	2.484%	0.000%	0.049%	7.35	0.01	0.03	2.18	9.30	0.00	0.18
Span Base #3	D8	E1-1	6.66	0.0187	1424	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
UV Coating	VC-1	E1-11	9.89	0.001	900	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
431-7050SP8 Champard II	D-9	E1-12	7.52	0.013	125	0.11%	0.009%	0.041%	2.14%	9.19%	17.20%	0.00%	0.06	0.00	0.02	1.15	4.90	9.21	0.00
PRIMER - WHITE NDS2002 - worst case VOC	SCL-1	SCL51	8.79	0.0160	250	0.00%	0.00%	0.00%	5.00%	10.00%	0.00%	0.00%	0.00	0.00	0.00	7.70	15.40	0.00	0.00
PAINT - WHITE EG5570-80015 - Worst Case PM	SCL-1	SCL51	9.87	0.0489	250	0.00%	0.00%	0.00%	9.00%	9.00%	0.00%	0.00%	0.08	0.00	0.00	0.00%	0.00%	0.00%	0.00%
Plant 140																			
40-003A adhesive	WR2a-WR2f	C2-1	8.80	0.050	1000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
40-003A adhesive	WPL2	C2-2	8.80	0.050	1000	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Single HAP Totals													21.13	0.07	0.10	16.68	53.81	9.21	0.52

METHODOLOGY

PTE HAPs (tons/yr) = Density (lb/gal) x Max. Usage (gal/unit) x Maximum Throughput (unit/hr) x Weight % HAP x 8760 hrs/yr x 1 ton/2000 lbs

Combined HAPs Total = **101.52**

**Appendix A: Emissions Calculations
Emissions from Combustion Operations**

Source Name: Patrick Industries, Inc.
Source Address: Plant 1: 1808 West Hively Avenue, Elkhart, Indiana 46517
Plant 2: 57420 Nagy Drive, Elkhart, Indiana 46517
County: Elkhart
SIC Code: 2434, 2421, 2431, 2541
Operation Permit No.: T039-29242-00324
Permit Reviewer: APT

# of Emission Units	Emission Unit ID	Total Heat Input Capacity (MMBtu/hr)	Total Maximum Potential Throughput (MMCF/yr)
1	B1	0.40	3.50
4	AB1 - AB4	4.00	35.0
15	H1 - H15	2.40	21.0

Emission Factors (lbs/MMCF)					
PM*	PM10*	SO ₂	NO _x **	CO	VOC
7.6	7.6	0.6	100	84.0	5.5

Potential To Emit (tons/yr)							
Emission Unit ID	PM	PM10	SO ₂	NO _x	CO	VOC	HAPs
B1	0.01	0.01	0.00	0.18	0.15	0.01	3.3E-03
AB1 - AB4	0.13	0.13	0.01	1.75	1.47	0.10	3.3E-02
H1 - H15	0.08	0.08	0.01	1.05	0.88	0.06	2.0E-02
TOTALS	0.23	0.23	0.02	2.98	2.50	0.16	0.056

* PM and PM10 emission factor are for condensible and filterable PM and PM10 combined.

**Emission factors for NO_x: Uncontrolled = 100 lb/MMCF

Emission factors are from AP-42, Chapter 1.4 - Natural Gas Combustion, Tables 1.4-1, 1.4-2, 1.4-3 and 1.4-4. SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03. (AP-42 Supplement D 7/98)

1 MMBtu = 1,000,000 Btu

1 MMCF = 1,000,000 cubic feet of gas

All Emission factors are based on normal firing.

Methodology

Max. Potential Throughput (MMCF/yr) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

PTE (tons/yr) = Max. Potential Throughput (MMCF/yr) x Emission Factor (lb/MMCF) x 1 ton/2,000 lbs

Appendix A: Emissions Calculations

Appendix A: Emission Calculations
Particulate Emissions From Woodworking Operations

TSD Appendix A: Page 5 of 5

Source Name: Patrick Industries, Inc.
Source Address: **Plant 1:** 1808 West Hively Avenue, Elkhart, Indiana 46517
Plant 2: 57420 Nagy Drive, Elkhart, Indiana 46517
County: Elkhart
SIC Code: 2434, 2421, 2431, 2541
Operation Permit No.: T039-29242-00324
Permit Reviewer: APT

Plant #	Emissions Unit/Baghouse ID	Stack ID	Air Flow Rate (acfm)	Outlet Grain Loading (grain/dscf)	Control Efficiency (%)	PTE of PM/PM10 (ton/yr) (Uncontrolled ¹)	PTE of PM/PM10 (ton/yr) (Controlled ²)	Maximum Throughput Capacity (lbs/hr)	326 IAC 6-3-2 Allowable PM Emission Rate (lbs/hr)	Actual PM Emissions (lbs/hr)
Plant 1	232RF8 Storage Silo (S-1)	C1-1	23,090	0.003	99.0%	260	2.60	55,000	37.8	0.59
	276RF8 Mill Room (WW1a)	C1-2	27,470	0.003	99.0%	309	3.09	11,000	12.8	0.71
	72RF8 Mill Room (WW1a)	C1-3	19,000	0.003	99.0%	214	2.14	7,500	9.9	0.49
	484RF10 HWD (DN1a, DN1b, & DN4)	C1-4	60,190	0.003	99.0%	678	6.78	6,500	9.0	1.55
	156RF10 KC (WW1b)	C1-5	19,400	0.003	99.0%	218	2.18	12,000	13.6	0.50
	276RF10 Grinder (WW1b)	C1-6	34,330	0.003	99.0%	387	3.87	13,000	14.4	0.88
	Woodworking 1c (WW1c)	C1-7	36,000	0.003	99.0%	405	4.05	5,000	7.6	0.93
Plant 2	276RF8 Mill Room (WW2a)	C2-1	60,000	0.003	99.0%	676	6.76	3,000	7.2	1.54
	Wood Wrapping (WR2a - WR2f)							1,680		
	276RF8 Mill Room (WW2b)	C2-2	29,000	0.003	99.0%	327	3.27	4,500	11.6	0.75
	81PJD10 Laminators (WPL2)							5,000		
TOTAL						3,474	34.7			

Assume all PM is equal to PM10.

Methodology

PTE of PM/PM10 Controlled (tons/yr) = Flow Rate (acfm) x Outlet Grain Loading (gr/ascf) x 60 (min/hr) x 8760 (hr/yr) x 1/7000 (lb/gr) x 1 ton/2000 lbs

PTE of PM/PM10 Uncontrolled (tons/yr) = Flow Rate (acfm) x Outlet Grain Loading (gr/ascf) x 60 (min/hr) x 8760 (hr/yr) x 1/7000 (lb/gr) x 1 ton/2000 lbs x 1/(1-Control Eff. (%))

Allowable PM Emission Rate (lb/hr) = 4.1 x (Throughput (lbs/hr)/2000)^{0.67}

Actual PM Emission Rate (lb/hr) = Flow Rate (acfm) x Outlet Grain Loading (gr/ascf) x 60 (min/hr) x 1/7000 (lb/gr)

Uncontrolled¹ = The uncontrolled particulate emissions are calculated without consideration of the integral control devices for the purpose of determining 326 IAC 2-2 (PSD) applicability only.

Controlled² = The controlled particulate emissions are calculated with the consideration that the woodworking controls are integral to the processes and are used for Part 70 applicability.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED

TO: Doyle Stump
VP of Mfg
Patrick Industries, Inc.
107 W. Franklin St.
Elkhart IN 46515

DATE: Dec. 8, 2010

FROM: Matt Stuckey, Branch Chief
Permits Branch
Office of Air Quality

SUBJECT: Final Decision
Title V Renewal
039-29242-00324

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:
Chris Heaton Industrial Safety & Environmental Services, Inc.
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at jbrush@idem.IN.gov.

Final Applicant Cover letter.dot 11/30/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Dec. 8, 2010

TO: Elkhart Public Library

From: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Subject: **Important Information for Display Regarding a Final Determination**

Applicant Name: Patrick Industries, Inc.
Permit Number: 039-29343-00324

You previously received information to make available to the public during the public comment period of a draft permit. Enclosed is a copy of the final decision and supporting materials for the same project. Please place the enclosed information along with the information you previously received. To ensure that your patrons have ample opportunity to review the enclosed permit, **we ask that you retain this document for at least 60 days.**

The applicant is responsible for placing a copy of the application in your library. If the permit application is not on file, or if you have any questions concerning this public review process, please contact Joanne Smiddie-Brush, OAQ Permits Administration Section at 1-800-451-6027, extension 3-0185.

Enclosures
Final Library.dot 11/30/07

Mail Code 61-53

IDEM Staff	BMILLER 12/8/2010 Patrick Industries, Inc. 039-29242-00324 (final)		Type of Mail: CERTIFICATE OF MAILING ONLY	AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204		

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handling Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee
											Remarks
1		Doyle Stump VP of Mfg Patrick Industries, Inc. 107 West Franklin St Elkhart IN 46515 (Source CAATS) <i>Via Confirm Delivery</i>									
2		Elkhart City Council and Mayors Office 229 South Second Street Elkhart IN 46516 (Local Official)									
3		Elkhart Public Library 300 S 2nd St Elkhart IN 46516-3184 (Library)									
4		Elkhart County Health Department 608 Oakland Avenue Elkhart IN 46516 (Health Department)									
5		Laurence A. McHugh Barnes & Thornburg 100 North Michigan South Bend IN 46601-1632 (Affected Party)									
6		Elkhart County Board of Commissioners 117 North Second St. Goshen IN 46526 (Local Official)									
7		Mr. Chris Heaton Industrial Safety and Environmental Services, Inc. 30723 Old US 20 Elkhart IN 46514 (Consultant)									
8		Mark Zeltwanger 26545 CR 52 Nappanee IN 46550 (Affected Party)									
9											
10											
11											
12											
13											
14											
15											

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See Domestic Mail Manual R900, S913, and S921 for limitations of coverage on inured and COD mail. See International Mail Manual for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
-----------------------------------------	------------------------------------------------	----------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------