



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: November 17, 2010

RE: Federal Mogul Corporation, Inc. / 017-29348-00029

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER.dot12/03/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Minor Source Operating Permit Renewal OFFICE OF AIR QUALITY

Federal Mogul Corporation, Inc.
101 Industrial Blvd.
Logansport, Indiana 46947

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages.

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation, or standard, except for the requirement to obtain a MSOP under 326 IAC 2-6.1.


Operation Permit No.: M017-29348-00029	
Issued by:  Iryn Calilung, Section Chief Permits Branch Office of Air Quality	Issuance Date November 17, 2010 Expiration Date: November 17, 2020

TABLE OF CONTENTS

A. SOURCE SUMMARY	4
A.1 General Information [326 IAC 2-5.1-3(c)][326 IAC 2-6.1-4(a)]	
A.2 Emission Units and Pollution Control Equipment Summary	
B. GENERAL CONDITIONS	7
B.1 Definitions [326 IAC 2-1.1-1]	
B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]	
B.3 Term of Conditions [326 IAC 2-1.1-9.5]	
B.4 Enforceability	
B.5 Severability	
B.6 Property Rights or Exclusive Privilege	
B.7 Duty to Provide Information	
B.8 Annual Notification [326 IAC 2-6.1-5(a)(5)]	
B.9 Preventive Maintenance Plan [326 IAC 1-6-3]	
B.10 Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.11 Termination of Right to Operate [326 IAC 2-6.1-7(a)]	
B.12 Permit Renewal [326 IAC 2-6.1-7]	
B.13 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]	
B.14 Source Modification Requirement	
B.15 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2] [IC 13-17-3-2][IC 13-30-3-1]	
B.16 Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]	
B.17 Annual Fee Payment [326 IAC 2-1.1-7]	
B.18 Credible Evidence [326 IAC 1-1-6]	
C. SOURCE OPERATION CONDITIONS	12
Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]	
C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2 Permit Revocation [326 IAC 2-1.1-9]	
C.3 Opacity [326 IAC 5-1]	
C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.6 Fugitive Dust Emissions [326 IAC 6-4]	
C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
Testing Requirements [326 IAC 2-6.1-5(a)(2)]	
C.8 Performance Testing [326 IAC 3-6]	
Compliance Requirements [326 IAC 2-1.1-11]	
C.9 Compliance Requirements [326 IAC 2-1.1-11]	
Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]	
C.10 Compliance Monitoring [326 IAC 2-1.1-11]	
C.11 Instrument Specifications [326 IAC 2-1.1-11]	
Corrective Actions and Response Steps	
C.12 Response to Excursions or Exceedances	
C.13 Actions Related to Noncompliance Demonstrated by a Stack Test	

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

- C.14 Malfunctions Report [326 IAC 1-6-2]
- C.15 General Record Keeping Requirements [326 IAC 2-6.1-5]
- C.16 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2]
[IC 13-14-1-13]

D.1. EMISSIONS UNIT OPERATION CONDITIONS..... 18

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

- D.1.1 VOC Limit [326 IAC 8-2-9]
- D.1.2 VOC Limit [326 IAC 8-1-6]

Compliance Determination Requirements

- D.1.3 Volatile Organic Compounds (VOC)[326 IAC 8-1-2] [326 IAC 8-1-4]

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

- D.1.4 Record Keeping Requirements
- D.1.5 Reporting Requirements

SECTION D.2. EMISSIONS UNIT OPERATION CONDITIONS..... 20

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

- D.2.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]
- D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]

SECTION D.3. EMISSION UNIT OPERATION CONDITIONS 22

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

- D.3.1 Particulate [326 IAC 6-3-2]
- D.3.2 Preventive Maintenance Plan [326 IAC 1-6-3]

Compliance Determination Requirements

- D.3.3 Particulate Control

Annual Notification 23
MSOP Quarterly Reports 24
Malfunction Report 26

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 and A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)][326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary automotive fuel pump manufacturing operation.

Source Address:	101 Industrial Blvd., Logansport, Indiana 46947
General Source Phone Number:	(574) 722-6141
SIC Code:	3647, 3714, and 8713
County Location:	Cass
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Minor Source Operating Permit Program Minor Source, under PSD and Emission Offset Rules Minor Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary

This stationary source consists of the following emission units and pollution control devices:

- (a) Impregnation Line, identified as EU-02, installed in 1996, consisting of the following equipment:
 - (1) Four (4) dip coating tanks, identified as TANK 1 through TANK 4, with a maximum coating rate of two hundred eighty-eight (288) pieces of metal automotive fuel pump parts per hour, each. TANK 1 and TANK 3 exhaust to one (1) stack, ID #S-2, and TANK 2 and TANK 4 exhaust to one (1) stack, ID #GV;

Note: TANK 1, TANK 2, and TANK 3 contain aqueous based solutions, and TANK 4 contains only water for the final rinse.
- (b) Electric Fuel Pump Test Line, identified as EU-04, installed in 1997, consisting of the following equipment:
 - (1) One (1) Cummins electric fuel pump tester, identified as CUMEFP, with a maximum test rate of eight-eighths and seventy-five hundredths (88.75) pumps per hour, uncontrolled and exhausting through one (1) stack ID #S-22;
- (c) Technical Center Research and Development, identified as EU-05, installed in 1996, consisting of the following equipment:
 - (1) Four (4) spent fuel outdoor storage tanks, identified as T-1 through T-4, each containing unleaded gasoline, #2 diesel fuel, and GP-1140 fuel, respectively, each with a maximum tank capacity of 2000, 2000, 2000, and 1000 gallons, respectively, uncontrolled and exhausting to the outside atmosphere;
 - (2) Three (3) fuel stands for testing pumps, with a maximum capacity of testing 4000 pumps per year, combined, exhausting through stacks ST-1, ST-2, and ST-3, respectively;

- (3) Flow testers for testing pump flows for sink, rotary vane #1 and rotary vane #2, with a maximum capacity of testing 119,600 pumps per year, combined, exhausting through stacks ST-1, ST-2, and ST-3, respectively;
- (4) Four (4) Stoddard Solvent drums for temporary storage of testing media for the flow test sink, rotary vane #1, and rotary vane #2 lines, with a maximum capacity of fifty-five (55) gallons, each;
- (d) Two (2) pump test stands, consisting of one (1) Roller Vane Diesel Tester designated as ROTVANTST and one (1) Oil Pump Audit Stand designated as OILAUDIT, installed in 2000, uncontrolled and exhausting inside the building;
- (e) One (1) roller vane oil pump test stand identified as ROLVANOILTST, installed in 2000, uncontrolled and exhausting inside the building;
- (f) Nine (9) production line fuel pump testing units, identified as GEROTST, CHRYTST1, CHRYTST2, TURBTST, MARINTST, ROTVANTST, SOLENTST, DAUTTST and GERMIDTST, respectively, with total maximum VOC emission rate equal to three and two hundredths (3.02) tons per year, uncontrolled and exhausting inside the building;
- (g) One (1) electrical and mechanical fuel pumps testing unit, identified as DURABTST, with a maximum VOC emission rate equal to eighteen hundred-thousandths (0.00018) tons per year, uncontrolled and exhausting inside the building;
- (h) One (1) pump flow static pressure testing unit, identified as GERAUDTST, with a maximum VOC emission rate equal to twelve hundred-thousandths (0.00012) tons per year, uncontrolled and exhausting inside the building, ;
- (i) Two (2) cold cleaners with self closing lids, identified as DEGRDIE and DEGRTOOL, using a maximum of ninety-eight (98) gallons per year, and fifty-six (56) gallons per year of solvent, respectively, uncontrolled and exhausting inside the building ;
- (j) Two (2) cold cleaners with drum reservoirs, identified as DEGRPLAT and DEGRMOLD, using a maximum of one hundred thirty-three (133) gallons per year and fifty-six (56) gallons per year of solvent, respectively, uncontrolled and exhausting inside the building;
- (k) One (1) industrial parts washer utilizing a soap-based, non-VOC/non-HAP containing cleaner, installed in 2000, uncontrolled and exhausting inside the building;
- (l) Twenty (20) plastic injection molding lines with no solvent in the resin, collectively identified as INJMOLD, with a maximum throughput of four hundred (400) pounds of plastic parts per hour, uncontrolled and exhausting inside the building;
- (m) Machining of aluminum where an aqueous cutting coolant continuously floods the machining interface.
- (n) Plastic machining operations, for the manufacture of fixtures needed in the production of the automotive fuel pumps, installed in 1996, uncontrolled and exhausting inside the building. The plastic machined is Delrin, and contains negligible amounts of HAPs and VOCs;
- (o) Ten (10) natural gas fired forced air heaters, identified as HTR1 through HTR10, with a maximum heat input capacity of three hundredths (0.03), twenty hundredths (0.20), fifteen hundredths (0.15), seven hundredths (0.07), thirteen hundredths (0.13), seven hundredths (0.07), nine hundredths (0.09), fourteen (0.14), twelve hundredths (0.12), and

eleven hundredths (0.11) mmBtu per hour, respectively, uncontrolled and exhausting inside the building;

- (p) One (1) small shotblast cabinet located in the satellite tool room, having a maximum process weight rate of eighty (80) pounds per hour, serviced by one (1) fifty-five (55) cubic feet per minute (cfm) dust collector for particulate control, and exhausting inside the building; and
- (q) One (1) small shotblast booth located in the technical center research and development, having a maximum process weight rate of eighty (80) pounds per hour, serviced by one (1) fifty-five (55) cubic feet per minute (cfm) dust collector for particulate control, and exhausting inside the building.
- (r) One (1) Samsco wastewater evaporator, identified as WWEVAP, with a maximum oil and grease content of less than or equal to one percent (1%) by volume, uncontrolled and exhausting inside the building;

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-1.1-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-1.1-1) shall prevail.

B.2 Permit Term [326 IAC 2-6.1-7(a)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]

- (a) This permit, M017-29348-00029, is issued for a fixed term of ten (10) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) An annual notification shall be submitted by an authorized individual to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) The annual notice shall be submitted in the format attached no later than March 1 of each year to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (c) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

B.9 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) A Preventive Maintenance Plan meets the requirements of 326 IAC 1-6-3 if it includes, at a minimum:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

The Permittee shall implement the PMPs.

- (b) If required by specific condition(s) in Section D of this permit where no PMP was previously required, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) no later than ninety (90) days after issuance of this permit or ninety (90) days after initial start-up, whichever is later, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The Permittee shall implement the PMPs.

- (c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions.
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.10 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of permits established prior to M017-29348-00029 and issued pursuant to permitting programs approved into the state implementation plan have been either:
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted.
- (b) All previous registrations and permits are superseded by this permit.

B.11 Termination of Right to Operate [326 IAC 2-6.1-7(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least one hundred twenty (120) days prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-6.1-7.

B.12 Permit Renewal [326 IAC 2-6.1-7]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-6.1-7. Such information shall be included in the application for each emission unit at this source. The renewal application does require an affirmation that the statements in the application are true and complete by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
 - (1) Submitted at least one hundred twenty (120) days prior to the date of the expiration of this permit; and

- (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-6.1 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified, pursuant to 326 IAC 2-6.1-4(b), in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.13 Permit Amendment or Revision [326 IAC 2-5.1-3(e)(3)][326 IAC 2-6.1-6]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (c) The Permittee shall notify the OAQ no later than thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

B.14 Source Modification Requirement

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

B.15 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)][326 IAC 2-6.1-5(a)(4)][IC 13-14-2-2][IC 13-17-3-2][IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.16 Transfer of Ownership or Operational Control [326 IAC 2-6.1-6]

- (a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage, and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require an affirmation that the statements in the application are true and complete by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement notice-only changes addressed in the request for a notice-only change immediately upon submittal of the request. [326 IAC 2-6.1-6(d)(3)]

B.17 Annual Fee Payment [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees due no later than thirty (30) calendar days of receipt of a bill from IDEM, OAQ.
- (b) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.18 Credible Evidence [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than one hundred (100) pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed five hundred fifty-one thousandths (0.551) pounds per hour.

C.2 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation of Permits), this permit to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-1 (Applicability) and 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute non-overlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4, or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator except as provided in 326 IAC 4-2 or in this permit. The Permittee shall not operate a refuse incinerator or refuse burning equipment except as provided in 326 IAC 9-1-2 or in this permit.

C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolitions start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project.

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.

- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Licensed Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Licensed Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-6.1-5(a)(2)]

C.8 Performance Testing [326 IAC 3-6]

- (a) For performance testing required by this permit, a test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date.
- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date.
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]

C.10 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.11 Instrument Specifications [326 IAC 2-1.1-11]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.

- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps

C.12 Response to Excursions or Exceedances

Upon detecting an excursion where a response step is required by the D Section or an exceedance of a limitation in this permit:

- (a) The Permittee shall take reasonable response steps to restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing excess emissions.
- (b) The response shall include minimizing the period of any startup, shutdown, or malfunction. The response may include, but is not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned or are returning to normal without operator action (such as through response by a computerized distribution control system); or
 - (3) any necessary follow-up actions to return operation to normal or usual manner of operation.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records; and/or
 - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall record the reasonable response steps taken.

C.13 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall submit a description of its response actions to IDEM, OAQ, no later than seventy-five (75) days after the date of the test.
- (b) A retest to demonstrate compliance shall be performed no later than one hundred eighty (180) days after the date of the test. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred eighty (180) days is not practicable, IDEM, OAQ may extend the retesting deadline

- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

C.14 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.15 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required monitoring data, reports, and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, for all record keeping requirements not already legally required, the Permittee shall be allowed up to ninety (90) days from the date of permit issuance or the date of initial start-up, whichever is later, to begin such record keeping.

C.16 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or

certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

- (c) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit, "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emission Unit Description [326 IAC 2-6.1-5(a)(1)]: Surface Coating and Pump Testing Operations

- (a) Impregnation Line, identified as EU-02, installed in 1996, consisting of the following equipment:
- (1) Four (4) dip coating tanks, identified as TANK 1 through TANK 4, with a maximum coating rate of two hundred eighty-eight (288) pieces of metal automotive fuel pump parts per hour, each. TANK 1 and TANK 3 exhaust to one (1) stack, ID #S-2, and TANK 2 and TANK 4 exhaust to one (1) stack, ID #GV;
- Note: TANK 1, TANK 2, and TANK 3 contain aqueous based solutions, and TANK 4 contains only water for the final rinse.
- (b) Electric Fuel Pump Test Line, identified as EU-04, installed in 1997, consisting of the following equipment:
- (1) One (1) Cummins electric fuel pump tester, identified as CUMEFP, with a maximum test rate of eight-eight and seventy-five hundredths (88.75) pumps per hour, uncontrolled and exhausting through one (1) stack ID #S-22;
- (c) Technical Center Research and Development, identified as EU-05, installed in 1996, consisting of the following equipment:
- (1) Four (4) spent fuel outdoor storage tanks, identified as T-1 through T-4, each containing unleaded gasoline, #2 diesel fuel, and GP-1140 fuel, respectively, each with a maximum tank capacity of 2000, 2000, 2000, and 1000 gallons, respectively, uncontrolled and exhausting to the outside atmosphere;
 - (2) Three (3) fuel stands for testing pumps, with a maximum capacity of testing 4000 pumps per year, combined, exhausting through stacks ST-1, ST-2, and ST-3, respectively;
 - (3) Flow testers for testing pump flows for sink, rotary vane #1 and rotary vane #2, with a maximum capacity of testing 119,600 pumps per year, combined, exhausting through stacks ST-1, ST-2, and ST-3, respectively;
 - (4) Four (4) Stoddard Solvent drums for temporary storage of testing media for the flow test sink, rotary vane #1, and rotary vane #2 lines, with a maximum capacity of fifty-five (55) gallons, each;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

D.1.1 VOC Limit [326 IAC 8-2-9]

The Impregnation Line (EU-02), consisting of four (4) dip coating tanks, identified as TANK 1 through TANK 4, combined, shall use less than fifteen (15) pounds per day of VOC, including coatings, dilution solvents, and cleaning solvents. Compliance with this limit makes 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations) not applicable.

D.1.2 VOC Limit [326 IAC 8-1-6]

The Technical Center Research and Development, identified as EU-05, shall use less than twenty-five (25) tons of VOC per twelve (12) consecutive month period, with compliance determined at the end of each month, including coatings, dilution solvents, and cleaning solvents.

Compliance with this limit renders the provisions of 326 IAC 8-1-6 (New Facilities; VOC Reduction Requirements) not applicable.

Compliance Determination Requirements

D.1.3 Volatile Organic Compounds (VOC)[326 IAC 8-1-2] [326 IAC 8-1-4]

Compliance with the VOC usage limit contained in Conditions D.1.1 and D.1.2, shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) by preparing or obtaining from the manufacturer the copies of the "as supplied" and "as applied" VOC data sheets. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Record Keeping Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.4 Record Keeping Requirements

(a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (3) below. Records maintained for (1) through (3) shall be taken as stated below and shall be complete and sufficient to establish compliance with the VOC usage limits established in Conditions D.1.1 and D.1.2.

- (1) The VOC content of each coating material and solvent used less water.
- (2) The amount of each coating material and solvent used on a daily and monthly basis.
 - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
- (3) The total VOC usage for each day and month.

(b) Section C - General Record Keeping Requirements contains the Permittee's obligations with regard to the records required by this condition.

D.1.5 Reporting Requirements

A quarterly summary of the information to document the compliance status with conditions D.1.1 and D.1.2 shall be submitted using the reporting forms located at the end of this permit, or their equivalent, not later than thirty (30) days after the end of the quarter being reported. Section C - General Reporting Requirements contains the Permittee's obligation with regard to the reporting required by this condition.

SECTION D.2 EMISSIONS UNIT OPERATION CONDITIONS

Emission Unit Description [326 IAC 2-6.1-5(a)(1)]: Degreasing Operations

- (i) Two (2) cold cleaners with self closing lids, identified as DEGRDIE and DEGRTOOL, using a maximum of ninety-eight (98) gallons per year, and fifty-six (56) gallons per year of solvent, respectively, uncontrolled and exhausting inside the building ;
- (j) Two (2) cold cleaners with drum reservoirs, identified as DEGRPLAT and DEGRMOLD, using a maximum of one hundred thirty-three (133) gallons per year and fifty-six (56) gallons per year of solvent, respectively, uncontrolled and exhausting inside the building;

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

D.2.1 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations), for cold cleaning operations constructed after January 1, 1980, identified as DEGRDIE, DEGRTOOL, DEGRPLAT and DEGRMOLD, the Permittee shall:

- (a) Equip the cleaner with a cover;
- (b) Equip the cleaner with a facility for draining cleaned parts;
- (c) Close the degreaser cover whenever parts are not being handled in the cleaner;
- (d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;
- (e) Provide a permanent, conspicuous label summarizing the operation requirements;
- (f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

D.2.2 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]

(a) Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), for cold cleaner degreaser operations without remote solvent reservoirs constructed after July 1, 1990, identified as DEGRDIE and DEGRTOOL, the Permittee shall ensure that the following control equipment requirements are met:

- (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:
 - (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F));
 - (B) The solvent is agitated; or
 - (C) The solvent is heated.

- (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury, or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.
 - (3) Provide a permanent, conspicuous label, which lists the operating requirements outlined in subsection (b).
 - (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure, which does not cause excessive splashing.
 - (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):
 - (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
 - (B) A water cover when solvent is used is insoluble in, and heavier than, water.
 - (C) Other systems of demonstrated equivalent control such as a refrigerated chiller or carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.
- (b) Pursuant to 326 IAC 8-3-5(b) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaning facility construction of which commenced after July 1, 1990, shall ensure that the following operating requirements are met:
- (1) Close the cover whenever articles are not being handled in the degreaser.
 - (2) Drain cleaned articles for at least fifteen (15) seconds or until dripping ceases.
 - (3) Store waste solvent only in covered containers and prohibit the disposal or transfer of waste solvent in any manner in which greater than twenty percent (20%) of the waste solvent by weight could evaporate.

SECTION D.3 EMISSION UNIT OPERATION CONDITIONS

Emission Unit Description [326 IAC 2-6.1-5(a)(1)]: Shotblasting Operations

- (o) One (1) small shotblast cabinet located in satellite tool room serviced by one (1) fifty-five (55) cubic feet per minute (cfm) dust collector, using the dust collector as a control, and exhausting inside the building; and
- (p) One (1) small shotblast booth located in the technical center research and development serviced by one (1) fifty-five (55) cubic feet per minute (cfm) dust collector, using the dust collector as a control, and exhausting inside the building.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(a)(1)]

D.3.1 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2) (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the small blast cabinet located in satellite tool room and the small blast booth located in technical center research and development, each, shall continue to not exceed five hundred fifty-one thousandths (0.551) pound per hour when operating at a process weight rate of eighty (80) pounds per hour, each.

D.3.2 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan is required for this facility and its control device. Section B - Preventive Maintenance Plan contains the Permittee's obligation with regard to the preventive maintenance plan required by this condition.

Compliance Determination Requirements

D.3.3 Particulate Control

- (a) In order to comply with Condition D.3.1, the dust collectors for particulate control shall be in operation and control emissions from the small blast cabinet located in satellite tool room, and the small blast booth located in technical center research and development, at all times that the corresponding shotblast unit is in operation.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH**

**MINOR SOURCE OPERATING PERMIT
ANNUAL NOTIFICATION**

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

Company Name:	Federal Mogul Corporation, Inc.
Address:	101 Industrial Blvd.
City:	Logansport, Indiana 46947
Phone #:	(574) 722-5297
MSOP #:	M017-29348-00029

I hereby certify that Federal Mogul Corporation, Inc. is : still in operation.
 no longer in operation.
I hereby certify that Federal Mogul Corporation, Inc. is : in compliance with the requirements of MSOP M017-29348-00029.
 not in compliance with the requirements of MSOP M017-29348-00029.

Authorized Individual (typed):
Title:
Signature:
Date:

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

Noncompliance:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

MSOP Quarterly Report

Source Name: Federal Mogul Corporation, Inc.
Source Address: 101 Industrial Blvd., Logansport, Indiana, 46947
FESOP No.: M017-29348-00029
Facility: Four (4) dip tanks, identified as TANK 1-4
Parameter: **VOC Input/Usage**
Limit: Less than fifteen (15) pounds per day, combined.

Month: _____ Quarter: _____ Year: _____

Day	VOC Input (pounds/day)	Day	VOC Input (pounds/day)
1		17	
2		18	
3		19	
4		20	
5		21	
6		22	
7		23	
8		24	
9		25	
10		26	
11		27	
12		28	
13		29	
14		30	
15		31	
16		TOTAL	

- No deviation occurred in this month.
- Deviation/s occurred in this month.
Deviation has been reported on _____

Submitted by: _____
Title/Position: _____
Signature: _____
Date: _____
Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

MSOP Quarterly Report

Source Name: Federal Mogul Corporation, Inc.
Source Address: 101 Industrial Blvd., Logansport, Indiana, 46947
FESOP No.: M017-29348-00029
Facility: Technical Center Research and Development (EU-05)
Parameter: **VOC Input/Usage**
Limit: Less than twenty-five (25) tons per twelve (12) consecutive month period.

Quarter: _____ Year: _____

Month	Column 1 This Month	Column 2 Previous 11 Months	Column 1 + Column 2 12 Month Total
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

MALFUNCTION REPORT
INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH
FAX NUMBER: (317) 233-6865

**This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6
and to qualify for the exemption under 326 IAC 1-6-4.**

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?____, 25 TONS/YEAR SULFUR DIOXIDE ?____, 25 TONS/YEAR NITROGEN OXIDES?____, 25 TONS/YEAR VOC ?____, 25 TONS/YEAR HYDROGEN SULFIDE ?____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?____, 25 TONS/YEAR FLUORIDES ?____, 100 TONS/YEAR CARBON MONOXIDE ?____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF "MALFUNCTION" AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: _____ PHONE NO. () _____
LOCATION: (CITY AND COUNTY) _____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP: _____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/20____ _____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: _____

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/20____ _____ AM/PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____

CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____

CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____

INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

*SEE PAGE 2

Please note - This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6 and to qualify for the exemption under 326 IAC 1-6-4.

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

***Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

Indiana Department of Environmental Management
Office of Air Quality

Technical Support Document (TSD) for a
Minor Source Operating Permit Renewal

Source Background and Description
--

Source Name:	Federal Mogul Corporation, Inc.
Source Location:	101 Industrial Blvd., Logansport, Indiana, 46947
County:	Cass
SIC Code:	3647, 3714, and 8713
Permit Renewal No.:	M017-29348-00029
Permit Reviewer:	Hannah L. Desrosiers

The Office of Air Quality (OAQ) has reviewed the operating permit renewal application from Federal Mogul Corporation, Inc. relating to the continued operation of a stationary automotive fuel pump manufacturing operation.

On June 10, 2010, Federal Mogul Corporation, Inc. submitted an application to the OAQ requesting to renew its operating permit. Federal Mogul Corporation, Inc. was issued a MSOP (M017-18763-00029) on October 7, 2005.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units:

- (a) Impregnation Line, identified as EU-02, installed in 1996, consisting of the following equipment:
 - (1) Four (4) dip coating tanks, identified as TANK 1 through TANK 4, with a maximum coating rate of two hundred eighty-eight (288) pieces of metal automotive fuel pump parts per hour, each. TANK 1 and TANK 3 exhaust to one (1) stack, ID #S-2, and TANK 2 and TANK 4 exhaust to one (1) stack, ID #GV;

Note: TANK 1, TANK 2, and TANK 3 contain aqueous based solutions, and TANK 4 contains only water for the final rinse.
- (b) Electric Fuel Pump Test Line, identified as EU-04, installed in 1997, consisting of the following equipment:
 - (1) One (1) Cummins electric fuel pump tester, identified as CUMEFP, with a maximum test rate of eight-eight and seventy-five hundredths (88.75) pumps per hour, uncontrolled and exhausting through one (1) stack ID #S-22;
- (c) Technical Center Research and Development, identified as EU-05, installed in 1996, consisting of the following equipment:
 - (1) Four (4) spent fuel outdoor storage tanks, identified as T-1 through T-4, each containing unleaded gasoline, #2 diesel fuel, and GP-1140 fuel, respectively, each with a maximum tank capacity of 2000, 2000, 2000, and 1000 gallons, respectively, uncontrolled and exhausting to the outside atmosphere;

- (2) Three (3) fuel stands for testing pumps, with a maximum capacity of testing 4000 pumps per year, combined, exhausting through stacks ST-1, ST-2, and ST-3, respectively;
- (3) Flow testers for testing pump flows for sink, rotary vane #1 and rotary vane #2, with a maximum capacity of testing 119,600 pumps per year, combined, exhausting through stacks ST-1, ST-2, and ST-3, respectively;
- (4) Four (4) Stoddard Solvent drums for temporary storage of testing media for the flow test sink, rotary vane #1, and rotary vane #2 lines, with a maximum capacity of fifty-five (55) gallons, each;
- (d) Two (2) pump test stands, consisting of one (1) Roller Vane Diesel Tester designated as ROTVANTST and one (1) Oil Pump Audit Stand designated as OILAUDIT, installed in 2000, uncontrolled and exhausting inside the building;
- (e) One (1) roller vane oil pump test stand identified as ROLVANOILTST, installed in 2000, uncontrolled and exhausting inside the building;
- (f) Nine (9) production line fuel pump testing units, identified as GEROTST, CHRYTST1, CHRYTST2, TURBTST, MARINTST, ROTVANTST, SOLENTST, DAUTTST and GERMIDTST, respectively, with total maximum VOC emission rate equal to three and two hundredths (3.02) tons per year, uncontrolled and exhausting inside the building;
- (g) One (1) electrical and mechanical fuel pumps testing unit, identified as DURABTST, with a maximum VOC emission rate equal to eighteen hundred-thousandths (0.00018) tons per year, uncontrolled and exhausting inside the building;
- (h) One (1) pump flow static pressure testing unit, identified as GERAUDTST, with a maximum VOC emission rate equal to twelve hundred-thousandths (0.00012) tons per year, uncontrolled and exhausting inside the building, ;
- (i) Two (2) cold cleaners with self closing lids, identified as DEGRDIE and DEGRTOOL, using a maximum of ninety-eight (98) gallons per year, and fifty-six (56) gallons per year of solvent, respectively, uncontrolled and exhausting inside the building ;
- (j) Two (2) cold cleaners with drum reservoirs, identified as DEGRPLAT and DEGRMOLD, using a maximum of one hundred thirty-three (133) gallons per year and fifty-six (56) gallons per year of solvent, respectively, uncontrolled and exhausting inside the building;
- (k) One (1) industrial parts washer utilizing a soap-based, non-VOC/non-HAP containing cleaner, installed in 2000, uncontrolled and exhausting inside the building;
- (l) Twenty (20) plastic injection molding lines with no solvent in the resin, collectively identified as INJMOLD, with a maximum throughput of four hundred (400) pounds of plastic parts per hour, uncontrolled and exhausting inside the building;
- (m) Machining of aluminum where an aqueous cutting coolant continuously floods the machining interface.
- (n) Plastic machining operations, for the manufacture of fixtures needed in the production of the automotive fuel pumps, installed in 1996, uncontrolled and exhausting inside the building. The plastic machined is Delrin, and contains negligible amounts of HAPs and VOCs.

- (o) Ten (10) natural gas fired forced air heaters, identified as HTR1 through HTR10, with a maximum heat input capacity of three hundredths (0.03), twenty hundredths (0.20), fifteen hundredths (0.15), seven hundredths (0.07), thirteen hundredths (0.13), seven hundredths (0.07), nine hundredths (0.09), fourteen (0.14), twelve hundredths (0.12), and eleven hundredths (0.11) mmBtu per hour, respectively, uncontrolled and exhausting inside the building;
- (p) One (1) small shotblast cabinet located in the satellite tool room, having a maximum process weight rate of eighty (80) pounds per hour, serviced by one (1) fifty-five (55) cubic feet per minute (cfm) dust collector for particulate control, and exhausting inside the building; and
- (q) One (1) small shotblast booth located in the technical center research and development, having a maximum process weight rate of eighty (80) pounds per hour, serviced by one (1) fifty-five (55) cubic feet per minute (cfm) dust collector for particulate control, and exhausting inside the building.
- (r) One (1) Samsco wastewater evaporator, identified as WWEVAP, with a maximum oil and grease content of less than or equal to one percent (1%) by volume, uncontrolled and exhausting inside the building;

Emission Units and Pollution Control Equipment Constructed and/or Operated without a Permit

There are no unpermitted emission units operating at this source during this review process.

Emission Units and Pollution Control Equipment Removed From the Source

There have been no emission units or pollution control equipment removed from the source during this review process.

Existing Approvals

The source has been operating under MSOP No. M017-18763-00029, issued on October 7, 2005.

All terms and conditions of previous permits issued pursuant to permitting programs approved into the State Implementation Plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

Enforcement Issue

There are no pending enforcement actions related to this source.

Emission Calculations

See Appendix A of this document for detailed emission calculations.

- (a) During this review, the emissions calculations were updated to reflect the source's most current "worst-case" operating conditions for all units, and includes emissions not previously counted. Additionally, since OAQ relies on the most up-to-date emission factors recommended by U.S. EPA, facility emissions have been characterized using the most recent version of U.S. EPA's AP-42 emission factors, where applicable.

- (b) PM2.5 emissions have been calculated for all applicable units in preparation for compliance with the May 8, 2008 promulgation of Prevention of Significant Deterioration (PSD) requirements for PM2.5 emissions.
- (c) Updated MSDSs were submitted by the source for all coatings and materials used, therefore the following applies:
 - (1) The coatings used in the Impregnation Line (EU-02) are applied using dip processes, and based on MSDSs submitted by the source;
 - (A) The materials currently being used in TANK 1 and TANK 3 contain trace levels of HAPs. Therefore, negligible emissions of HAPS are anticipated from this unit.
 - (B) The emissions calculations for TANK 2 have been revised. The material used in TANK 2 is diluted with water to form an "as-applied" formulation of three (3) quarts of material to ninety-seven (97.0) gallons of water. The resultant solution is used for an entire 8-hour shift, and is equivalent to a maximum usage rate of ten hundredths (0.10) gallons per hour.
 - (C) TANK 4 contains only water, and consequently contains no VOCs or HAPs. Therefore, negligible emissions of criteria pollutants and HAPs are anticipated from this unit.
 - (D) Since the materials used in TANK 1, TANK 2, TANK 3, and TANK 4 are applied using dip coating methods, particulate emissions are determined to be negligible.
 - (2) PM emissions from the Electric Fuel Pump Test Line (EU-04) and the Research and Development Technical Center (EU-05) shotblast units, not previously accounted for in MSOP #017-18763-00029, have been calculated.
 - (3) During this review, a calculation error was discovered in the emissions calculations. As a result, the HAP Emissions calculations from the Technical Center Research and Development (EU-05) have been revised.
 - (4) The one (1) industrial parts washer, installed in 2000, uses aqueous soap-based cleaner solutions that, based on an MSDS submitted by the source, contain no VOCs or HAPs. Therefore, negligible emissions of criteria pollutants and HAPS are anticipated from this unit.
 - (5) Potential emissions from the injection molding operation identified as INJMOLD, have been evaluated. Based on MSDSs and other information submitted by the source, particulate, VOC, and HAP emissions have been determined negligible; and
 - (6) Potential emissions from the plastic machining operations have been evaluated. Based on MSDSs and other information submitted by the source, particulate, VOC, and HAP emissions have been determined negligible.

County Attainment Status

The source is located in Cass County. The following attainment status designations are applicable to Cass County:

Pollutant	Designation
SO2	Better than national standards.
CO	Unclassifiable or attainment effective November 15, 1990.
O3	Unclassifiable or attainment effective June 15, 2004, for the 8-hour ozone standard. ¹
PM10	Unclassifiable effective November 15, 1990.
PM2.5	Unclassifiable or attainment effective April 5, 2005
NO2	Cannot be classified or better than national standards.
Pb	Not designated.
¹ Unclassifiable or attainment effective October 18, 2000, for the 1-hour ozone standard which was revoked effective June 15, 2005.	

- (a) Ozone Standards
 Volatile organic compounds (VOC) and Nitrogen Oxides (NOx) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NOx emissions are considered when evaluating the rule applicability relating to ozone. Cass County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NOx emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (b) PM2.5
 Cass County has been classified as attainment for PM2.5. On May 8, 2008, U.S. EPA promulgated the requirements for Prevention of Significant Deterioration (PSD) for PM2.5 emissions. These rules became effective on July 15, 2008. Indiana has three years from the publication of these rules to revise its PSD rules, 326 IAC 2-2, to include those requirements. The May 8, 2008 rule revisions require IDEM to regulate PM10 emissions as a surrogate for PM2.5 emissions until 326 IAC 2-2 is revised.
- (c) Other Criteria Pollutants
 Cass County has been classified as attainment or unclassifiable in Indiana for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2, 326 IAC 2-3, or 326 IAC 2-7, and there is no applicable New Source Performance Standard that was in effect on August 7, 1980, fugitive emissions are not counted toward the determination of PSD, Emission Offset, and Part 70 Permit applicability.

Unrestricted Potential Emissions

The following table reflects the unrestricted potential emissions of the source.

Intentionally left blank..... continued on next page.....

Pollutant	tons/year
PM	8.27
PM10 ^α	8.30
PM2.5 ^β	8.29
SO2	2.92E-03
NOx	0.49
VOC	37.65
CO	0.41
Total HAPs	7.82
"worst" Single HAP	2.52 (MTBE)

HAPs	tons/year
MTBE	2.52
Toluene	2.29
Xylenes	2.06
Benzene	0.84
Ethyl Benzene	0.34
Glycol Ethers	0.05
Miscellaneous ^γ	0.03
Cumene	0.02
remaining HAPs	9.15E-03
Total	8.15

Note: Appendix A of this TSD reflects the unrestricted potential emissions of the source.

- α Under the Part 70 Permit program (40 CFR 70), particulate matter with an aerodynamic diameter less than or equal to a nominal ten (10) micrometers (PM10), not particulate matter (PM), is considered as a "regulated air pollutant".
 - β US EPA has directed states to regulate PM10 emissions as surrogate for PM2.5 emissions.
 - γ As noted in Appendix A to the TSD for MSOP 017-18763-00029, issued October 7, 2005, the "miscellaneous" category includes negligible emissions from the roller vane diesel tester, oil pump audit stand, roller vane oil pump test stand, two (2) cold cleaners with self closing lids, two (2) cold cleaners with drum reservoirs, the Samsco wastewater evaporator (oil & grease content less than 1%), blast cabinet located in satellite tool room, and the blast booth located in technical R & D center.
- (a) The potential to emit (as defined in 326 IAC 2-7-1(29)) of all regulated pollutants is less than one hundred (100) tons per year. However, the potential to emit VOC is equal to or greater than twenty-five (25) tons per year. The source is not subject to the provisions of 326 IAC 2-7. Therefore, the source will be issued an MSOP Renewal.
 - (b) The potential to emit (as defined in 326 IAC 2-7-1(29)) of any single HAP is less than ten (10) tons per year and/or the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination of HAPs is less than twenty-five (25) tons per year. Therefore, the source will be issued an MSOP Renewal.

Federal Rule Applicability

New Source Performance Standards (NSPS)

- (a) 40 CFR 60, Subpart Kb - Standards for Volatile Organic Liquid Storage Vessels
 The requirements of the New Source Performance Standard for Volatile Organic Liquid Storage Vessels, 40 CFR 60, Subpart Kb (326 IAC 12), are still not included in this renewal for the four (4) spent fuel outdoor storage tanks, identified as T-1 through T-4, and the four (4) Stoddard Solvent drums for temporary storage of testing media, because although each tank was constructed/installed after the rule applicability date of July 23, 1984, each tank still has a maximum capacity of less than 75 m³ (19,813 gallons), and the liquid stored in each tank still has a maximum true vapor pressure of less than fifteen kiloPascals (15.0 kPa).
- (b) 40 CFR 60, Subpart MM - Standards for Automobile and Light Duty Truck Surface Coating Operations
 The requirements of the New Source Performance Standard for Automobile and Light Duty Truck Surface Coating Operations, 40 CFR 60, Subpart MM (326 IAC 12), are not included in this renewal, since this source is still not an automobile assembly plant.

(c) 40 CFR 60, Subpart IIII - Standards for Stationary Compression Ignition Internal Combustion Engines

The requirements of the New Source Performance Standard for Stationary Compression Ignition Internal Combustion Engines, 40 CFR 60, Subpart IIII (4I) (326 IAC 12), are not included in this renewal, since the one (1) Cummins electric fuel pump tester, identified as CUMEFP, previously described as combusting diesel fuel is not a combustion unit but a passive fuel pump testing unit that instead uses the diesel fuel as a testing media.

(d) There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) included in this renewal for this source.

National Emission Standards for Hazardous Air Pollutants (NESHAP)

(a) 40 CFR 63, Subpart T - NESHAPs for Halogenated Solvent Cleaning

The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Halogenated Solvent Cleaning, 40 CFR 63, Subpart T (326 IAC 20-6), are still not included in this renewal, since this source still does not use a cold solvent cleaner/degreasing solvent that contains any of the halogenated compounds, listed in 40 CFR 63.460(a).

(b) 40 CFR 63, Subpart JJJ - NESHAPs: Group IV Polymers and Resins

The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs): Group IV Polymers and Resins, 40 CFR 63, Subpart JJJ (3J) (326 IAC 20-21), are not included in this renewal, since this source is still not a major source of HAPs, and does not manufacture thermoplastic products, as defined in §63.1312.

(c) 40 CFR 63, Subpart OOO - NESHAPs: Manufacture of Amino/Phenolic Resins

The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs): Manufacture of Amino/Phenolic Resins, 40 CFR 63, Subpart OOO (3O) (326 IAC 20-58), are not included in this renewal, since this source is still not a major source of HAPs, and does not produce amino/phenolic resins, as defined in §63.1402.

(d) 40 CFR 63 Subpart IIII - NESHAPs for Surface Coating of Automobiles and Light Duty Trucks

The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs): Surface Coating of Automobiles and Light-Duty Trucks, 40 CFR 63, Subpart IIII (4I) (326 IAC 20-85), are still not included in this renewal, since this source is still not a major source of HAP emissions, and does not topcoat all of the body parts for any single new automobile or new light-duty truck at this facility.

(e) 40 CFR 63 Subpart MMMM - NESHAPs for Miscellaneous Metal Parts and Products Surface Coating

The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63, Subpart MMMM (4M) (326 IAC 20-80), are still not included in this renewal, since this source is not a major source of HAPs, as defined in 40 CFR 63.2.

(f) 40 CFR 63 Subpart PPPP - NESHAPs for Surface Coating of Plastic Parts and Products

The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Surface Coating of Plastic Parts and Products, 40 CFR 63, Subpart PPPP (4P) (326 IAC 20-81), are not included in this renewal, because although this source applies surface coatings to plastic automotive parts, this source is not a major source of HAPs.

- (g) 40 CFR 63, Subpart WWWW - NESHAPs: Reinforced Plastic Composites Production
The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs): Reinforced Plastic Composites Production, 40 CFR 63, Subpart WWWW (4W) (326 IAC 20-56), are not included in this renewal, since this source is not a major source of HAPs, and does not manufacture reinforced and/or non-reinforced plastic composites or plastic molding compounds using thermoset resins and/or gel coats that contain styrene, to produce plastic composites.
- (h) 40 CFR 63, Subpart ZZZZ - NESHAPs for Stationary Reciprocating Internal Combustion Engines
The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Stationary Reciprocating Internal Combustion Engines, 40 CFR 63, Subpart ZZZZ (4Z) (326 IAC 20-82), are not included in this renewal, since the one (1) Cummins electric fuel pump tester, identified as CUMAFP, previously described as combusting diesel fuel is not a combustion unit but a passive fuel pump testing unit that instead uses the diesel fuel as a testing media.
- (i) 40 CFR 63, Subpart DDDDD - NESHAPs for Industrial, Commercial, and Institutional Boilers and Process Heaters
The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Industrial, Commercial, and Institutional Boilers and Process Heaters, 40 CFR 63, Subpart DDDDD (5D) (326 IAC 20), are not included in this renewal, as follows:

On June 8, 2007, the United States Court of Appeals for the District of Columbia Circuit (in *National Resource Defense Council, Sierra Club, Environmental Integrity Project vs. EPA*, No. 04-1385), vacated 40 CFR 63, Subpart DDDDD in its entirety. Additionally, since State Rule 326 IAC 20-95 incorporated the requirements of the NESHAP 40 CFR 63, Subpart DDDDD by reference, the requirements of 326 IAC 20-95 are no longer effective. However, since NESHAP 40 CFR Part 63, Subpart DDDDD has been vacated, Section 112(j) of the Clean Air Act, major sources of Hazardous Air Pollutants (HAPs), in specified source categories, requires a case-by-case MACT determination when EPA fails to promulgate a scheduled MACT Standard by the regulatory deadline. Federal Mogul Corporation, Inc. is still considered an area source under Section 112 of the Clean Air Act, MACT Standards. Therefore, the source is not subject to a case-by-case MACT determination.
- (j) 40 CFR 63, Subpart HHHHHH - NESHAPs for Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources
The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs): Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH (6H) (326 IAC 20), are not included in this renewal, because although this source this source meets the definition of an area source, as defined in 40 CFR § 63.2, and apply coatings to plastic automotive parts, they use dip not spray application methods, and the coatings used do not contain compounds of cadmium (Cd), chromium (Cr), lead (Pb), manganese (Mn), or nickel (Ni). Additionally, this source does not perform paint stripping using MeCl, and does not conduct any autobody refinishing operations.
- (k) 40 CFR 63, Subpart VVVVVV - NESHAPs for Chemical Manufacturing Area Sources
The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Chemical Manufacturing Area Sources, 40 CFR 63, Subpart VVVVVV (6V) (326 IAC 20), are not included in this renewal, since pursuant to 40 CFR 63.11494(c)(2)(iii), fabricating operations that convert an already produced solid polymer into a different shape by melting or mixing the polymer and then forcing it or pulling it through an orifice to create an extruded product are exempt from the rule.

- (l) 40 CFR 63, Subpart WWWWWW - NESHAPs for Plating and Polishing Operations
The requirements of 40 CFR 63, Subpart WWWWWW (6W), the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Plating and Polishing Operations, which are incorporated by reference as 326 IAC 20, are not included in this renewal, because this source does not meet the definition of a plating and polishing facility, as defined in § 63.11511, and the coatings used do not contain or have the potential to emit any of the specifically listed plating or polishing metal HAPs, (i.e., compounds of cadmium (Cd), chromium (Cr), lead (Pb), manganese (Mn), or nickel (Ni), or any of these metals in the elemental form).
- (m) 40 CFR 63, Subpart XXXXXX - NESHAPs for Nine Metal Fabrication and Finishing Source Categories
The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Nine Metal Fabrication and Finishing Source Categories, 40 CFR 63, Subpart XXXXXX (6X) (326 IAC 20), are not included in this renewal, because although this existing source manufactures metal automobile parts, it is not primarily engaged in the operations in one of the nine metal fabrication and finishing source categories, as defined in 40 CFR 63.11514 and 63.11522.
- (n) There are no National Emission Standards for Hazardous Air Pollutants (NESHAP) (326 IAC 14, 326 IAC 20, and 40 CFR Part 63) included in this permit renewal.

Compliance Assurance Monitoring (CAM)

Pursuant to 40 CFR 64.2, Compliance Assurance Monitoring (CAM) is not included in this renewal, because the potential to emit of the source is limited to less than the Title V major source thresholds and the source is not required to obtain a Part 70 or Part 71 permit.

State Rule Applicability - Entire Source

- (a) 326 IAC 1-6-3 (Preventive Maintenance Plan)
The source is still subject to 326 IAC 1-6-3.
- (b) 326 IAC 2-2 (Prevention of Significant Deterioration (PSD))
While this existing source is located in an Attainment/Unclassifiable Area for all criteria pollutants, it still does not meet the definition of a major stationary source under PSD (326 IAC 2-2), because no regulated pollutant is emitted at a rate of two hundred fifty (250) tons per year or more, and it is not one of the twenty-eight (28) listed source categories, as specified in 326 IAC 2-2-1(gg)(1). Therefore, the requirements of 326 IAC 2-2 (PSD) still do not apply to this source, and are not included in this renewal.
- (c) 326 IAC 2-3 (Emission Offset)
Cass County has been classified as attainment or unclassifiable in Indiana for all criteria pollutants. Therefore, the requirements of 326 IAC 2-3 (Emission Offset) still do not apply to this source, and are not included in this renewal.
- (d) 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP))
The unrestricted potential HAP emissions from this existing source continues to be less than the Title V Major Source thresholds of ten (10) tons per year for any single HAP and less than twenty-five (25) tons per year of a combination of HAPs, see "Unrestricted Potential Emissions" section above. Therefore, the requirements of 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) still do not apply to this source, and the requirements are not included in this renewal.

- (e) 326 IAC 2-6 (Emission Reporting)
This source is still not subject to 326 IAC 2-6 (Emission Reporting) because it is not required to have an operating permit pursuant to 326 IAC 2-7 (Part 70); it is not located in Lake, Porter, or LaPorte County, and its potential to emit lead is less than five (5) tons per year. Therefore, pursuant to 326 IAC 2-6-1(b), the source is still only subject to additional information requests as provided in 326 IAC 2-6-5.
- (f) 326 IAC 2-6.1 (Minor Source Operating Permits (MSOP))
MSOP applicability is discussed under the "Unrestricted Potential Emissions" section above.
- (g) 326 IAC 5-1 (Opacity Limitations)
This source is still subject to the opacity limitations specified in 326 IAC 5-1-2(1).
- (h) 326 IAC 6-4 (Fugitive Dust Emissions Limitations)
Pursuant to 326 IAC 6-4 (Fugitive Dust Emissions Limitations), the source shall continue to not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4.
- (i) 326 IAC 6.5 PM Limitations Except Lake County
This source is still not subject to 326 IAC 6.5 (PM Limitations Except Lake County) because it is not located in one of the following counties: Clark, Dearborn, Dubois, Howard, Marion, St. Joseph, Vanderburgh, Vigo or Wayne.
- (j) 326 IAC 12 (New Source Performance Standards)
See Federal Rule Applicability Section of this TSD.
- (k) 326 IAC 20 (Hazardous Air Pollutants)
See Federal Rule Applicability Section of this TSD.

State Rule Applicability – Individual Facilities

Surface Coating Operations

- (a) 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)
Pursuant to 326 IAC 6-3-1(b)(5), surface coating operations using dip coating are specifically exempted from the rule. This source continues to perform dip coating of metal automotive fuel pump parts. Therefore, the requirements of 326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes) still do not apply to the surface coating operations at this source, and are not included in this renewal.
- (b) 326 IAC 8-1-6 (New facilities: general reduction requirements)
The existing surface coating operation, Impregnation Line (EU-02), consisting of TANK 1 through TANK 4, continues to be subject to 326 IAC 8-2-9 (Miscellaneous Metal Coating). Therefore, the requirements of 326 IAC 8-1-6 General Reduction Requirements still do not apply and are not included in this renewal.
- (c) 326 IAC 8-2-2 (Automobile and light duty truck coating operations)
The existing surface coating operation, Impregnation Line (EU-02), consisting of TANK 1 through TANK 4, continues to apply surface coatings to metal automotive fuel pump parts not automobile or light-duty truck bodies or body parts for automobiles or light-duty trucks, as defined in 40 CFR 63.3176. Therefore, the requirements of 326 IAC 8-2-2 Automobile and light duty truck coating operations still do not apply and are not included in this renewal.

- (d) 326 IAC 8-2-9 (Miscellaneous Metal Coating)
The existing surface coating operation, Impregnation Line (EU-02), consisting of TANK 1 through TANK 4, constructed after July 1, 1990, continues to coat metal automotive fuel pump parts under Standard Industrial Classification Code major group #37, and continues to have potential and actual VOC emissions of greater than fifteen (15) pounds per day. Therefore, the Impregnation Line (EU-02) continues to be subject to the requirements of 326 IAC 8-2-9 Miscellaneous Metal Coating. However, the source previously requested the option of accepting a limit of less than fifteen (15) pounds per day total VOC input to Impregnation Line EU-02. Therefore, the owner or operator of this source shall continue to comply with the following:
- (1) The VOC input to the Impregnation Line (EU-02), consisting of TANK 1 through TANK 4, combined, shall continue to not exceed fifteen (15.0) pounds per day. Compliance with this limit renders the requirements of 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations) not applicable.
 - (2) Pursuant to 326 IAC 8-2-9(f), solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.
- (e) There are no other 326 IAC 8 Rules that are applicable to the existing surface coating operation, Impregnation Line (EU-02), consisting of TANK 1 through TANK 4.

Fuel Pump Testing Operations

- (a) 326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes)
The activities performed in the Electric Fuel Pump Test Line (EU-04) and the Research and Development Technical Center (EU-05), each, do not meet the definition of a "manufacturing process", as defined in 326 IAC 6-3-1.5(2), because they pertain specifically to the quality assurance and quality control of a manufactured item. Therefore, the activities performed in the Electric Fuel Pump Test Line (EU-04) and the Research and Development Technical Center (EU-05), each, are exempt from the requirements of 326 IAC 6-3, and the requirements are not included in the permit.
- (b) 326 IAC 8-1-6 (New facilities; general reduction requirements)
 - (1) The potential to emit VOCs from Technical Center Research and Development, identified as EU-05, are still twenty-six and five tenths (26.5) tons per year. Therefore, the Technical Center Research and Development continues to be subject to the requirements of 326 IAC 8-1-6. However, the source previously requested the option of accepting a limit of less than twenty-five (25) tons per year total VOC input to the Technical Center Research and Development. Therefore, the requirements of 326 IAC 8-1-6 (New Facilities; General Reduction Requirements) still do not apply and are not included in this renewal.

See Appendix A for detailed calculations.
 - (2) The potential to emit VOCs from the Electric Fuel Pump Test Line, identified as EU-04, continue to be less than twenty-five (25) tons per year. Therefore, the requirements of 326 IAC 8-1-6 (New Facilities; General Reduction) still do not apply and are not included in this renewal.

See Appendix A for detailed calculations.

- (c) 326 IAC 8-4-3 (Petroleum Liquid Storage Facilities)
The four (4) spent fuel outdoor storage tanks, identified as T-1 through T-4, and the four (4) Stoddard Solvent drums for temporary storage of testing media, each, still have maximum capacities less than 39,000 gallons. Therefore, the requirements of 326 IAC 8-4-3 (Petroleum Liquid Storage Facilities) still do not apply and are not included in this permit.
- (d) 326 IAC 8-9 (Volatile Organic Liquid Storage Vessels)
This stationary automotive fuel pump and auto light lens manufacturing operation is still located in Cass County, not Clark, Floyd, Lake, or Porter Counties. Therefore, the four (4) spent fuel outdoor storage tanks, identified as T-1 through T-4, and the four (4) Stoddard Solvent drums for temporary storage of testing media, are each still not subject to this rule and the requirements are not included in this renewal.
- (e) There are no other 326 IAC 8 Rules that are applicable to the Fuel Pump Testing Operations.

Degreasing Operations

- (a) 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)
The existing degreasing operations, including the two (2) cold cleaners equipped with drum reservoirs, identified as DEGRPLAT and DEGRMOLD, and the two (2) cold cleaners equipped with self closing lids, identified as DEGRDIE and DEGRTOOL, each continue to have potential particulate emissions less than five hundred fifty-one thousandths (0.551) pound per hour. Therefore, the requirements of 326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes) still do not apply to the degreasing operations at this source, and are not included in this renewal.
- (b) 326 IAC 8-3 (Organic Solvent Degreasing Operations)
- (1) The two (2) cold cleaners equipped with drum reservoirs, identified as DEGRPLAT and DEGRMOLD, constructed in 2000, each, still meet the definition of a cold cleaner degreaser under 326 IAC 1-2-18.5, utilizing an organic solvent containing volatile organic compounds (VOCs) (as defined by 326 IAC 1-2-90), were constructed after the rule applicability date of July 1, 1990, and are each still equipped with a remote solvent reservoir. Therefore, pursuant to 326 IAC 8-3-1(a)(2), DEGRPLAT and DEGRMOLD, each, are still subject to 326 IAC 8-3-2 (Cold Cleaner Operations) and the requirements are included in this renewal.
- (2) The two (2) cold cleaners equipped with self closing lids, identified as DEGRDIE and DEGRTOOL, constructed in 2000, each, still meet the definition of a cold cleaner degreaser under 326 IAC 1-2-18.5, utilizing an organic solvent containing volatile organic compounds (VOCs) (as defined by 326 IAC 1-2-90), were constructed after the rule applicability date of July 1, 1990, and are each still not equipped with a remote solvent reservoir. Therefore, pursuant to 326 IAC 8-3-1(b)(2), DEGRDIE and DEGRTOOL are each still subject to 326 IAC 8-3-2 (Cold Cleaner Operations) and 326 IAC 8-3-5 (Cold Cleaner Degreaser Operation and Control) and the requirements are included in this renewal.
- (3) The one (1) industrial parts washer, installed in 2000, still uses aqueous soap-based cleaning solutions containing less than or equal to one percent (1%) by weight of VOCs, excluding HAPs. Therefore, pursuant to 326 IAC 2-1.1-3(13)(D)(Exemptions), the requirements of 326 IAC 8-3 still do not apply to this facility and are not included in this renewal.

- (c) 326 IAC 8-6-1 (Organic Solvent Emission Limitations)
This existing stationary automotive fuel pump and auto light lens manufacturing operation is located in Cass County, and was constructed after January 1, 1980. Moreover, the source-wide VOC emissions are still less than one hundred (100) tons per year. Therefore, the requirements of 326 IAC 8-6-1 still do not apply and are not included in this renewal.
- (d) There are no other 326 IAC 8 Rules that are applicable to the degreasing operations.

Shotblasting Operations

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

The small blast cabinet located in the satellite tool room and the small blast booth located in technical center research and development, continue to operate at a maximum process weight rate of eighty (80) pounds per hour, each. Therefore pursuant to 326 IAC 6-3-2 (e)(2), particulate emissions from the small blast cabinet located in satellite tool room and the small blast booth located in technical center research and development, each, shall continue to not exceed five hundred fifty-one thousandths (0.551) pound per hour.

Based on the calculations in Appendix A, the uncontrolled potential PM emission rate, for each unit is:

$$4.13 \text{ tons/yr} \times (2000 \text{ lbs/ton} / 8760 \text{ hrs/yr}) = 0.94 \text{ lbs/hr, each.}$$

The uncontrolled potential particulate emission rate from the small blast cabinet located in the satellite tool room and the small blast booth located in technical center research and development, each is ninety-four hundredths (0.94) pounds per hour, which is greater than the allowable rate of five hundred fifty one thousandths (0.551) pounds per hour. Therefore, the dust collectors for particulate control shall continue to be in operation at all times that the corresponding shot blast unit is in operation, in order to comply with this limit.

See Appendix A, for the detailed calculations.

Plastic Injection Molding Operations

- (a) 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)
The potential particulate emissions from the twenty (20) plastic injection molding lines, collectively identified as INJMOLD, combined are less than five hundred fifty-one thousandths (0.551) pound per hour. Therefore, pursuant to 326 IAC 6-3-1(b)(14), the injection molding operations are exempt from 326 IAC 6-3, and the requirements are not included in the permit.
- (b) 326 IAC 8-1-6 (VOC Rules: General Reduction Requirements for New Facilities)
The unlimited potential VOC emissions from the twenty (20) plastic injection molding lines, collectively identified as INJMOLD, combined, are less than twenty-five (25) tons per year. Therefore, pursuant to 326 IAC 8-1-6(1), the injection molding operations are exempt from 326 IAC 8-1-6, and the requirements are not included in the permit.
- (c) There are no other 326 IAC 8 Rules that are applicable to the plastic injection molding operations.

Natural Gas Combustion

- (a) 326 IAC 4-2-2 (Incinerators)
The ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, are each still not an incinerator, as defined by 326 IAC 1-2-34, since they do not burn waste substances. Therefore, 326 IAC 4-2-2 still does not apply to any of the ten (10) natural

gas-fired forced air heaters, identified as HTR1 through HTR10, and the requirements are not included in this renewal.

- (b) 326 IAC 6-2 (Particulate Emissions from Indirect Heating Units)
 The ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, each, still do not meet the definition of an indirect heating unit, as defined in 236 IAC 1-2-19. Therefore, 326 IAC 6-2 still does not apply to any of the ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, and the requirements are not included in this renewal.
- (c) 326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes)
 The ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, each, still do not meet the definition of a "manufacturing process", as defined in 326 IAC 6-3-1.5(2). Therefore, the ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, each, are still exempt from the requirements of 326 IAC 6-3, and the requirements are not included in this renewal.
- (d) 326 IAC 7-1.1 (Sulfur Dioxide Emissions Limitations)
 The potential SO₂ emissions from the ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, each, are still less than twenty-five (25) tons per year and ten (10) pounds per hour respectively. Therefore, 326 IAC 7-1.1-2 still does not apply to any of the ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, and the requirements are not included in this renewal.

Compliance Determination, Monitoring, Testing, Record Keeping, and Reporting Requirements
--

Compliance Determination

- (a) The Surface Coating Operation, Impregnation Line (EU-02), consisting of TANK 1 through TANK 4, has applicable compliance determination requirements, as specified below:

Emission Unit/Control	Operating Parameters	Method
Impregnation Line (EU-02), consisting of TANK 1 through TANK 4	VOC content	Preparing or obtaining the "as supplied" and "as applied" VOC data sheets <hr/> Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4

Confirmation of the VOC content of the coatings used in TANK 1 through TANK 4 is still required to render the provisions of 326 IAC 8-1-6 (BACT) not applicable.

- (b) The dust collectors used to control particulate in the small blast cabinet located in the satellite tool room, and the small blast booth located in the technical center research and development, shall be in operation and control emissions at all times that the corresponding shotblast unit is in operation.
- (c) There are still no specific compliance determination requirements for the Electric Fuel Pump Test Line (EU-04) and the Research and Development Technical Center (EU-05), the two (2) cold cleaners equipped with drum reservoirs, identified as DEGRPLAT and DEGRMOLD, and the two (2) cold cleaners equipped with self closing lids, identified as DEGRDIE and DEGRTOOL, the one (1) industrial parts washer, installed in 2000, the small blast cabinet located in the satellite tool room, the small blast booth located in

technical center research and development, the twenty (20) plastic injection molding lines, collectively identified as INJMOLD, and the ten (10) natural gas-fired forced air heaters, identified as HTR1 through HTR10, at this existing source.

Testing requirements

There continue to be no specific testing requirements associated with any of the emission units located at this existing source.

Compliance Monitoring Requirements

There continue to be no specific compliance monitoring requirements for any of the emission units located at this existing source.

Recordkeeping and Reporting Requirements

- (a) The source shall continue to maintain records of material and solvent usage, clean-up solvent usage, and VOC content, usage and emissions in order demonstrate compliance with the VOC limits established for the existing surface coating operation, Impregnation Line (EU-02), consisting of TANK 1 through TANK 4; and
- (b) The source shall continue to submit a quarterly summary of the VOC input into the existing surface coating operation, Impregnation Line (EU-02), consisting of TANK 1 through TANK 4.

Recommendation and Conclusion

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant. An application for the purposes of this review was received on June 10, 2010.

The operation of this stationary automotive fuel pump and auto light lenses manufacturing operation shall be subject to the conditions of the attached MSOP Renewal No.: M017-29348-00029. The staff recommends to the Commissioner that this MSOP Renewal be approved.

IDEM Contact

- (a) Questions regarding this proposed permit can be directed to Ms. Hannah Desrosiers at the Indiana Department Environmental Management, Office of Air Quality, Permits Branch, 100 North Senate Avenue, MC 61-53 IGCN 1003, Indianapolis, Indiana 46204-2251 or by telephone at (317) 234-5374 or toll free at 1-800-451-6027 extension 4-5374.
- (b) A copy of the findings is available on the Internet at: <http://www.in.gov/ai/appfiles/idem-caats/>
- (c) For additional information about air permits and how the public and interested parties can participate, refer to the IDEM's Guide for Citizen Participation and Permit Guide on the Internet at: www.idem.in.gov

Appendix A: Emissions Calculations Emission Summary

Company Name: Federal Mogul Corporation
Address City IN Zip: 101 Industrial Boulevard, Logansport, IN 46947
MSOP Renewal No.: 017-29348-00029
Reviewer: Hannah L. Desrosiers
Date Submitted: 11/17/10

Uncontrolled Potential Emissions (tons/year)						
Category	Pollutant	Emissions Generating Activity				TOTAL
		Impregnation Line (EU-02)	Electric Fuel Pump Test Line ⁽¹⁾ (EU-04)	Technical Center R&D (EU-05)	Natural Gas-Fired Heaters	
Criteria Pollutants	PM	0.00	4.13	4.13	0.01	8.27
	PM10	0.00	4.13	4.13	0.04	8.30
	PM2.5	0.00	4.13	4.13	0.03	8.29
	SO2	0	0	0	2.92E-03	2.92E-03
	NOx	0	0	0	0.49	0.49
	VOC	3.78	7.35	26.50	0.03	37.65
Hazardous Air Pollutants	CO	0	0	0	0.41	0.41
	Benzene	0	0	0.84	1.02E-05	0.84
	Dichlorobenzene	0	0	0	5.83E-06	5.83E-06
	Ethyl Benzene	0	0	0.34	0	0.34
	Formaldehyde	0	0	0	3.65E-04	3.65E-04
	Glycol Ethers	0.05	0	0	0	0.05
	Hexane	0	0	0	8.75E-03	8.75E-03
	MTBE	0	0	2.52	0	2.52
	Napthalene	0	0	0.02	0	0.02
	Toluene	0	0	2.29	1.65E-05	2.29
	Xylenes	0	0	2.06	0	2.06
	Cadmium	0	0	0	5.35E-06	5.35E-06
	Chromium	0	0	0	6.81E-06	6.81E-06
	Lead	0	0	0	2.43E-06	2.43E-06
	Manganese	0	0	0	1.85E-06	1.85E-06
	Nickel	0	0	0	1.02E-05	1.02E-05
Miscellaneous ⁽⁴⁾	0	0	0.03	0	0.03	
Totals	0.05	0	8.09	0.01	8.15	
						2.52

Total emissions based on rated capacity at 8,760 hours/year

Controlled and Limited Potential Emissions (tons/year)						
Category	Pollutant	Emissions Generating Activity				TOTAL
		Impregnation Line EU-02	Cummins Fuel Pump Tester ^{(1)(a)} EU-04	Technical Center R&D ^(a) EU-05	Natural Gas-Fired Heaters	
Criteria Pollutants	PM	0.00	0.21	0.21	0.01	0.42
	PM10	0.00	0.21	0.21	0.04	0.45
	PM2.5	0.00	0.21	0.21	0.03	0.44
	SO2	0	0	0	2.92E-03	2.92E-03
	NOx	0	0	0	0.49	0.49
	VOC	2.74 ⁽²⁾	7.35	<25 ⁽³⁾	0.03	35.12
Hazardous Air Pollutants	CO	0	0	0	0.41	0.41
	Benzene	0	0	0.84	1.02E-05	0.84
	Dichlorobenzene	0	0	0	5.83E-06	5.83E-06
	Ethyl Benzene	0	0	0.34	0	0.34
	Formaldehyde	0	0	0	3.65E-04	3.65E-04
	Glycol Ethers	0.05	0	0	0	0.05
	Hexane	0	0	0	8.75E-03	8.75E-03
	MTBE	0	0	2.52	0	2.52
	Napthalene	0	0	0.02	0	0.02
	Toluene	0	0	2.29	1.65E-05	2.29
	Xylenes	0	0	2.06	0	2.06
	Cadmium	0	0	0	5.35E-06	5.35E-06
	Chromium	0	0	0	6.81E-06	6.81E-06
	Lead	0	0	0	2.43E-06	2.43E-06
	Manganese	0	0	0	1.85E-06	1.85E-06
	Nickel	0	0	0	1.02E-05	1.02E-05
Miscellaneous ⁽⁴⁾	0	0	0.03	0	0.03	
Totals	0.05	0	8.09	0.01	8.15	
						2.52

Total emissions based on rated capacity at 8,760 hours/year.

Notes

(1) The emissions also include emissions from the production line fuel pump testing units, electrical and mechanical fuel pumps testing unit and pump flow static pressure testing unit. The emissions from these units are based on MSOP no. 017-18763-00029, issued on October 07, 2005.

(a) A control device is required for compliance with 326 IAC 6-3-2, therefore controlled emissions are shown.

(2) In order to render the requirements of 326 IAC 8-2-9 not applicable, the actual VOC input/usage to EU-02 shall be limited to less than 15 pounds per day.

(3) In order to render the requirements of 326 IAC 8-1-6 not applicable, the combined VOC input/usage to EU-05 shall be limited to less than 25 tons per year.

(4) There are negligible emissions from roller vane diesel tester, oil pump audit stand, roller vane oil pump test stand, two (2) cold cleaners with self closing lid, two (2) cold cleaners with drum reservoir, samsco wastewater evaporator (oil & grease content less than 1%), blast cabinet located in satellite tool room and blast booth located in technical R & D center. All degreasing operations have an annual solvent usage less than 145 gallons per 12 months. The blast cabinets are serviced by 55 cfm dust collectors. The industrial parts washer uses a soap based, non-VOC cleaner and plastic injection molding lines do not contain any solvent in resin; therefore, there are no emissions from these units.

**Appendix A: Emissions Calculations
VOC and Particulate
from Impregnation Line (EU-02)**

Company Name: Federal Mogul Corporation
Address City IN Zip: 101 Industrial Boulevard, Logansport, IN 46947
MSOP Renewal No.: 017-29348-00029
Reviewer: Hannah L. Desrosiers
Date Submitted: 11/17/10

Dip Tanks #1, #3 and #4

Unit ID	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
Dip Tank 1	8.3454	100.00%	98.7%	1.3%	0.0%	0.00%	0.00110	288	0.11	0.11	0.04	0.86	0.16	0.0	NA	100%
Dip Tank 3	8.3454	100.00%	95.0%	5.0%	90.0%	10.00%	0.00640	288	0.04	0.42	0.77	18.46	3.37	0.0	NA	100%
Dip Tank 4	8.3454	100.00%	100.0%	0.0%	100.0%	0.00%	0.01000	288	NA	0.00	0.00	0.00	0.00	0.0	NA	100%

Total State Potential Emissions (tons/yr)

3.52 0.00

Methodology

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)
Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)
Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)
Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)
Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)
Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Notes

Total emissions based on rated capacity at 8,760 hours/year.
Based on MSDSs submitted by the source, the following applies:
The materials currently being used in Tanks #1 and #3, each, do not contain any HAPs.
Dip tank #4 contains only water, and therefore contains no VOCs or HAPs.
Constant: the density of water is 8.3454, and the specific gravity is 1.0.
The materials used in Dip Tanks #1, #3, and #4 are applied using dip coating methods, therefore particulate emissions are determined negligible.
NA = not applicable

Dip Tank #2

Material	Maximum Capacity (gal/hr)	VOC * (lbs/gal)	Potential VOC (lbs/hr)	Potential VOC (lbs/yr)	Potential VOC (tons/yr)	Potential PM ** (lbs/hr)
T DET N 9.5 Soap	0.094	0.62	0.0581	508.54	0.25	0.0000
Water	12.238	0.00	0.000	0.00	0.00	0.0000

Total State Potential Emissions (tons/yr)

0.06 508.54 0.25 0.00

Methodology

Total emissions based on rated capacity at 8,760 hours/year.
Maximum Capacity (gal/hr) T DET N 9.5 Soap = (3 quarts/shift) * (1 gallon/4 quarts) * (Shift/8 hr) = 0.094 gal/hr
VOC (lbs/gal) = (Density (lb/gal) * Weight % Organics)
Potential VOC (lbs/hr) = Maximum Capacity (gal/hr)*VOC(lbs/gal)
Potential VOC (lbs/yr) = Potential VOC (lbs/hr)*(8760 hr/year)
Potential VOC (ton/yr) = Potential VOC (lbs/yr)*(1 ton/2000 lbs)

Notes

The source mixes 3 Quarts of T DET Soap with 97.9 gallons of water for each 8 hour shift.
% of T DET N 9.5 in Final Mix = 0.79 %
Density of T DET N 9.5 Soap (lb/gal) = Density of water (8.3454 lb/gal) * specific gravity of T DET N 9.5 Soap taken from MSDS (1.06) = 8.8461
T DET N 9.5 weight % organics content (0.7%) based on Appendix A: Calculations from FESOP no. 017-10438-00029, issued on February 23, 2000.
** The material used in Dip Tank #2 is applied using dip coating methods, therefore particulate emissions are determined negligible.

**Appendix A: Emission Calculations
Electric Fuel Pump Test Line (EU-04) and
Technical Center Research and Development (EU-05)
Particulate Emissions from the Shotblast Operations**

Company Name: Federal Mogul Corporation
Address City IN Zip: 101 Industrial Boulevard, Logansport, IN 46947
MSOP Renewal No.: 017-29348-00029
Reviewer: Hannah L. Desrosiers
Date Submitted: 11/17/10

Unit ID	Control Efficiency (%)	Grain Loading per Actual Cubic foot of Outlet Air* (grains/acfm)	Gas or Air Flow Rate (acfm.)	Emission Rate after Controls (lb/hr)	Emission Rate after Controls (tons/yr)	Emission Rate before Controls (lb/hr)	Emission Rate before Controls (tons/yr)
Satellite Tool Room dust collector	95.0%	0.100	55.0	0.047	0.21	0.94	4.13
Technical Center Research and Development dust collector	95.0%	0.100	55.0	0.047	0.21	0.94	4.13
Totals:				0.09	0.41	1.89	8.26

Methodology

Emission Rate in lbs/hr (after controls) = (grains/cub. ft.) (sq. ft.) ((cub. ft./min.)/sq. ft.) (60 min/hr) (lb/7000 grains)

Emission Rate in lbs/hr (before controls) = (Controlled emission rate lb/hr) / (1- control efficiency)

Emission Rate in tons/yr = (lbs/hr) (8760 hr/yr) (ton/2000 lb)

NOTES

*The dust collectors used to control particulate emissions from the shot blast units have not been rated for outlet grain loading. Therefore, a value of one hundred thousandths (0.100) grains/actual cubic feet/min has been used to form a conservative estimate.

PM10 and PM 2.5 emissions are assumed equal to PM emissions.

Based on a MSDS submitted by the source, the shotblast material currently in use by the source does not contain any HAPs.

**Appendix A: Emissions Calculations
Electric Fuel Pump Test Line (EU-04) and
Technical Center Research and Development (EU-05)
VOC and HAP Emissions**

Company Name: Federal Mogul Corporation
Address City IN Zip: 101 Industrial Boulevard, Logansport, IN 46947
MSOP Renewal No.: 017-29348-00029
Reviewer: Hannah L. Desrosiers
Date Submitted: 11/17/10

Electric Fuel Pump Test Line (EU-04) ¹

VOC carry out losses = 5.05 g/pump
 VOC emissions (TPY) = gm/pump * pump/hr * hr/yr * lb/gm * ton/lb

4.33	tons per year
------	---------------

Technical Center Research and Development (EU-05)

VOC Emissions (TPY)

Testing Media	Gallons Purchased	Gallons used or sold	Gallons unaccounted	Density (lb/gal)	Lbs unaccounted/yr	VOC Emissions (TPY)
Gasoline	29,425.71	24,388.57	5,037.14	6.66	33,547.35	16.77
#2 Diesel	2,879.63	2,378.58	501.05	7.08	3,547.43	1.77
GP1140	4,006.66	3,173.48	833.18	6.16	5,132.39	2.57
Stoddard Solvent	3,523.93	2,114.36	1,409.57	6.41	9,035.34	4.52
Total						25.63

HAPs Emissions (TPY)

<u>Gasoline</u>	<u>Tons per year</u>				
MTBE = 15% (by weight) * 16.77 (tons per year) =	2.52				
Xylene = 12% (by weight) * 16.77 (tons per year) =	2.01				
Toluene = 10% (by weight) * 16.77 (tons per year) =	1.68				
Benzene = 5% (by weight) * 16.77 (tons per year) =	0.84				
Ethyl Bz = 2% (by weight) * 16.77 (tons per year) =	0.34				
	7.38				
 <u>#2 Diesel</u>					
Naphthalene = 1% (by weight) * 1.77 (tons per year) =	0.02				
 <u>GP1140</u>					
Toluene = 22% (by weight) + (3% of 67% (by weight)) * 2.57(tons per year) =	0.62				
Xylene = (3% of 67% (by weight)) * 2.57 (tons per year) =	0.05				
 <u>Stoddard Solvent</u>					
Xylene = 1% (by weight) * 4.52 (tons per year) =	0.05				
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">* Total VOC from Technical Center R & D =</td> <td style="text-align: right;">26.50</td> </tr> <tr> <td style="text-align: right;">* Total HAPs from Technical Center R & D =</td> <td style="text-align: right;">8.09</td> </tr> </table>		* Total VOC from Technical Center R & D =	26.50	* Total HAPs from Technical Center R & D =	8.09
* Total VOC from Technical Center R & D =	26.50				
* Total HAPs from Technical Center R & D =	8.09				

* Note

Negligible emissions are expected from the roller vane diesel tester, oil pump audit stand, roller vane oil pump test stand, two (2) cold cleaners with self closing lid, two (2) cold cleaners with drum reservoir, samsco wastewater evaporator (oil & grease content less than 1%), blast cabinet located in satellite tool room and blast booth located in technical R & D center. All degreasing operations have an annual solvent usage less than 145 gallons per 12 months and the blast cabinets are serviced by 55 cfm dust collectors. Additionally, the industrial parts washer uses a soap based, non-VOC/non-HAP cleaner and the plastic injection molding lines do not contain any solvent in resin; therefore, there no emissions are expected from these units.

The emissions from these units are based on MSOP no. 017-18763-00029, issued on October 07, 2005.

Appendix A: Emissions Calculations**Natural Gas Combustion Only****MM BTU/HR <100****Ten (10) Forced-Air Heaters**

Company Name: Federal Mogul Corporation
Address City IN Zip: 101 Industrial Boulevard, Logansport, IN 46947
MSOP Renewal No.: 017-29348-00029
Reviewer: Hannah L. Desrosiers
Date Submitted: 11/17/10

Combined Heat Input Capacity MMBtu/hr	Potential Throughput MMCF/yr
1.11	9.72

Emission Factor in lb/MMCF	Criteria Pollutant						
	PM	PM10	PM2.5	SO2	NOx	VOC	CO
	1.9	7.6	5.7	0.6	100.0	5.5	84.0
					*see below		
Potential Emission in tons/yr	0.01	0.04	0.03	2.92E-03	0.49	0.03	0.41

PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable fractions combined. PM2.5 emission factor is condensable fraction only.

Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Emission Factor in lb/MMcf	HAPs - Organics				
	Benzene	Dichlorobenzene	Formaldehyde	Hexane	Toluene
	2.1E-03	1.2E-03	7.5E-02	1.8E+00	3.4E-03
Potential Emission in tons/yr	1.02E-05	5.83E-06	3.65E-04	8.75E-03	1.65E-05

Emission Factor in lb/MMcf	HAPs - Metals				
	Lead	Cadmium	Chromium	Manganese	Nickel
	5.0E-04	1.1E-03	1.4E-03	3.8E-04	2.1E-03
Potential Emission in tons/yr	2.43E-06	5.35E-06	6.81E-06	1.85E-06	1.02E-05

The five highest organic and metal HAPs emission factors are provided above.

Additional HAPs emission factors are available in AP-42, Chapter 1.4.

Total Combined HAPs:	9.18E-03	tons/yr
----------------------	----------	---------

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED

TO: Ryan Slavens
Federal Mogul Corp.
101 Industrial Blvd
Logansport, IN 46947

DATE: November 17, 2010

FROM: Matt Stuckey, Branch Chief
Permits Branch
Office of Air Quality

SUBJECT: Final Decision
MSOP Renewal
017-29348-00029

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:
Bradley Angie – Plant Manager
Mike Ahonen – Bruce Carter Associates
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at jbrush@idem.IN.gov.

Final Applicant Cover letter.dot 11/30/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

November 17, 2010

TO: Logansport Cass County Public Library

From: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Subject: **Important Information for Display Regarding a Final Determination**

Applicant Name: Federal mogul Corporation
Permit Number: 017-29348-00029

You previously received information to make available to the public during the public comment period of a draft permit. Enclosed is a copy of the final decision and supporting materials for the same project. Please place the enclosed information along with the information you previously received. To ensure that your patrons have ample opportunity to review the enclosed permit, **we ask that you retain this document for at least 60 days.**

The applicant is responsible for placing a copy of the application in your library. If the permit application is not on file, or if you have any questions concerning this public review process, please contact Joanne Smiddie-Brush, OAQ Permits Administration Section at 1-800-451-6027, extension 3-0185.

Enclosures
Final Library.dot 11/30/07

Mail Code 61-53

IDEM Staff	GHOTOPP 11/17/2010 Federal Mogul Corp 017-29348-00029 Final		Type of Mail: CERTIFICATE OF MAILING ONLY	AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204		

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handing Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee	Remarks
1		Ryan Slavens Federal Mogul Corp 101 Industrial Blvd Logansport IN 46947 (Source CAATS) via confirmed delivery										
2		Bradley Angle Plant Mgr Federal Mogul Corp 101 Industrial Blvd Logansport IN 46947 (RO CAATS)										
3		Mr. Charles L. Berger Berger & Berger, Attorneys at Law 313 Main Street Evansville IN 47700 (Affected Party)										
4		Mr. Harry D. DuVall P.O. Box 147 Idaville IN 47950 (Affected Party)										
5		Cass County Board of Commissioner 200 Court Park Logansport IN 46947 (Local Official)										
6		Cass County Health Department 1201 Michigan Ave Stre 230 Logansport IN 46947-1530 (Health Department)										
7		Logansport Cass Co Public Library 616 E Broadway Logansport IN 46947-3187 (Library)										
8		Logansport City Council and Mayors Office 601 Broadway Logansport IN 46947 (Local Official)										
9		Mr. Robert Kelley 2555 S 30th Street Lafayette IN 44909 (Affected Party)										
10		Mr. Tim Thomas c/o Boilermakers Local 374 6333 Kennedy Ave. Hammond IN 46333 (Affected Party)										
11		Kurt Brandstatter Central Paving, Inc. P.O. Box 357 Logansport IN 46947 (Affected Party)										
12		Mike Ahonen Bruce Carter Associates 616 South 4th Street Elkhart IN 46516 (Consultant)										
13		Mark Zeltwanger 26545 CR 52 Nappanee IN 46550 (Affected Party)										
14												
15												

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See Domestic Mail Manual R900, S913, and S921 for limitations of coverage on inured and COD mail. See International Mail Manual for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
12			