



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: August 25, 2011

RE: Nishikawa Cooper LLC / 087-29472-00031

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision: Approval – Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-6-1(b) or IC 13-15-6-1(a) require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204.

For an **initial Title V Operating Permit**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **thirty (30)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(b).

For a **Title V Operating Permit renewal**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **fifteen (15)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(a).

The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

Pursuant to 326 IAC 2-7-18(d), any person may petition the U.S. EPA to object to the issuance of an initial Title V operating permit, permit renewal, or modification within sixty (60) days of the end of the forty-five (45) day EPA review period. Such an objection must be based only on issues that were raised with reasonable specificity during the public comment period, unless the petitioner demonstrates that it was impracticable to raise such issues, or if the grounds for such objection arose after the comment period.

To petition the U.S. EPA to object to the issuance of a Title V operating permit, contact:

U.S. Environmental Protection Agency
401 M Street
Washington, D.C. 20406

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

PART 70 OPERATING PERMIT RENEWAL OFFICE OF AIR QUALITY

**Nishikawa Cooper, LLC
324 Morrow Street
Topeka, Indiana 46571**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 USC 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17. This permit also addresses certain new source review requirements for existing equipment and is intended to fulfill the new source review procedures pursuant to 326 IAC 2-2 and 326 IAC 2-7-10.5, applicable to those conditions.

Part 70 Permit No.: T087-29472-00031	
Issued by:  Chrystal A. Wagner, Section Chief Permits Branch Office of Air Quality	Issuance Date: August 25, 2011 Expiration Date: August 25, 2016

TABLE OF CONTENTS

A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
[326 IAC 2-7-5(15)]
- A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]
- A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

B. GENERAL CONDITIONS

- B.1 Definitions [326 IAC 2-7-1]
- B.2 Permit Term [326 IAC 2-7-5(2)][326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)]
[IC 13-15-3-6(a)]
- B.3 Term of Conditions [326 IAC 2-1.1-9.5]
- B.4 Enforceability [326 IAC 2-7-7] [IC 13-17-12]
- B.5 Severability [326 IAC 2-7-5(5)]
- B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]
- B.8 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]
- B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]
- B.11 Emergency Provisions [326 IAC 2-7-16]
- B.12 Permit Shield [326 IAC 2-7-15][326 IAC 2-7-20][326 IAC 2-7-12]
- B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]
- B.14 Termination of Right to Operate [326 IAC 2-7-10][326 IAC 2-7-4(a)]
- B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)][326 IAC 2-7-8(a)][326 IAC 2-7-9]
- B.16 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4][326 IAC 2-7-8(e)]
- B.17 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]
- B.18 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
[326 IAC 2-7-12(b)(2)]
- B.19 Operational Flexibility [326 IAC 2-7-20][326 IAC 2-7-10.5]
- B.20 Source Modification Requirement [326 IAC 2-7-10.5]
- B.21 Inspection and Entry [326 IAC 2-7-6][IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]
- B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]
- B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]
- B.24 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]

C. SOURCE OPERATION CONDITIONS

- Emission Limitations and Standards [326 IAC 2-7-5(1)]
- C.1 Particulate Emission Limitations For Processes with Process Weight Rates
Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Stack Height [326 IAC 1-7]
- C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]
- Testing Requirements [326 IAC 2-7-6(1)]
- C.8 Performance Testing [326 IAC 3-6]
- C.9 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]
C.10 Compliance Monitoring [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]
C.11 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)]
[326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]
C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
C.14 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]
C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]
C.16 Emission Statement [326 IAC 2 7 5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)]
[326 IAC 2-6]
C.17 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
C.18 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection
C.19 Compliance with 40 CFR 82 and 326 IAC 22-1

D.1 FACILITY OPERATION CONDITIONS: Spray booths and application lines

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-1-6][326 IAC 2-2]
D.1.2 Volatile Organic Compound Limitation [326 IAC 2-2]
D.1.3 Particulate [326 IAC 6-3-2(d)]
D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements
D.1.5 Volatile Organic Compounds (VOC)
D.1.6 VOC Emissions

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]
D.1.7 Particulate Matter

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]
D.1.8 Record Keeping Requirements
D.1.9 Reporting Requirements

D.2 FACILITY OPERATION CONDITIONS: Extrusion lines

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.2.1 Particulate Matter (PM) [326 IAC 6-3-2]

D.3 FACILITY OPERATION CONDITIONS - Mixing Departments

Emission Limitations and Standards [326 IAC 2-7-5(1)]
D.3.1 Particulate [326 IAC 6-3-2]

Compliance Determination Requirements
D.3.2 Particulate Matter

D.4 FACILITY OPERATION CONDITIONS - Insignificant Activities

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.1 Particulate [326 IAC 6-3-2]

E.1 FACILITY OPERATION CONDITIONS - Emergency Generator

E.1.1 General Provisions Relating to NESHAP Subpart AAAAA [326 IAC 20-1] [40 CFR Part 63, Subpart A]

E.1.2 Reciprocating Internal Combustion Engines NESHAP [40 CFR Part 63, Subpart ZZZZ]

Certification

Emergency Occurrence Report

Quarterly Reports

Quarterly Deviation and Compliance Monitoring Report

Attachment A - National Emission Standards for Hazardous Air Pollutants for Reciprocating Internal Combustion Engines (NESHAP), 40 CFR 63, Subpart ZZZZ

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]

The Permittee owns and operates an extruded rubber seals manufacturing source.

Source Address: 324 Morrow Street, Topeka, Indiana 46571
General Source Phone Number: (260) 593 2156
SIC Code: 3061
County Location: LaGrange
Source Location Status: Attainment for all criteria pollutants
Source Status: Part 70 Operating Permit Program
Minor Source, under PSD Rules
Major Source, Section 112 of the Clean Air Act
Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)][326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

- (a) CV Line 5, identified as CV-5, consisting of the following equipment:
- (1) Two (2) extruders, identified as CV-5Ex, constructed in 1989, with a combined capacity of 400 pounds of rubber per hour, equipped with strip feeders, and two (2) dusters controlled by one (1) dust collector (DC-2) vented internally, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber and coating curing oven, identified as CV-5C, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-5, S-1.
 - (3) Two (2) exhaust hoods, identified as CV-5EH1 and CV-5EH2, exhausting to stacks CV-5, S-2, and CV-5, S-3, respectively.
 - (4) One (1) Line 5 spray booth coating extruded rubber parts, identified as emission unit CV-5SB, constructed in 2000, equipped with six (6) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, using dry filters as control, and exhausting to one (1) stack identified as CV-5, S-4, maximum capacity: 7.93 pounds of waterborne urethane coating per hour.
- (b) CV Line 6, identified as CV-6, consisting of the following equipment:
- (1) One (1) extruder, identified as CV-6Ex, constructed in 1989, with a capacity of 400 pounds of rubber per hour, equipped with strip feeders, and two (2) dusters controlled by one (1) dust collector (DC-2) vented internally, and exhausting to general ventilation.
 - (2) One (1) microwave curing oven, identified as CV-6C2, and exhausting to CV-6, S-2.

- (3) One (1) natural gas-fired rubber and coating curing oven, identified as CV-6C1, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-6, S-1.
 - (4) Two (2) exhaust hoods, identified as CV-6EH1 and CV-6EH2, CV-6EH1 exhausting to stack CV-5, S-2, and CV-6EH2, exhausting to stacks CV-6, S-2, and CV-5, S-3.
 - (5) One (1) Line 6 spray booth, identified as CV-6SB, constructed in 2000, equipped with six (6) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, using dry filters as control, and exhausting to one (1) stack identified as CV-6, S-3, maximum capacity: 7.93 pounds of waterborne urethane coating per hour.
- (c) CV Line 7, identified as CV-7, consisting of the following equipment:
- (1) Three (3) extruders, identified as CV-7Ex, constructed in 1991, with a combined capacity of 600 of rubber pounds per hour, equipped with one (1) duster, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber and coating curing oven, identified as CV-C, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-7, S-1.
 - (3) One (1) exhaust hood, identified as CV-7EH, exhausting to stack CV-6, S-2.
 - (4) One (1) Line 7 waterborne urethane coating booth coating extruded rubber parts, identified as CV-7SB, constructed in 2001, with a capacity of 1.36 gallons of waterborne coating per hour, equipped with spray guns and dry filters, and exhausting to stack CV-7, S-2.
- (d) CV Line 8, identified as CV-8, consisting of the following equipment:
- (1) Four (4) extruders, identified as CV-8Ex, constructed in 1995, with a combined capacity of 400 pounds of rubber per hour, equipped with four (4) strip feeders, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber vulcanizing oven, identified as CV-8C1, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stacks CV-8, S-1, CV-8, S-2, CV-8, S-3.
 - (3) Two (2) exhaust hoods, identified as CV-8EH1 and CV-8EH2, both exhausting to stack CV-8, S-4.
 - (4) One (1) natural gas fired coating curing oven, identified as CV-8C2, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stack CV-8, S-4.
 - (5) One (1) urethane application spray booth, identified as CV-8SB, constructed in 1997, equipped with six (6) spray guns coating extruded rubber parts and one (1) blown air dryer, with a capacity of 10 grams of coating per minute per gun, and exhausting to stack CV-8, S-5.
- (e) CV Line 9, identified as CV-9, consisting of the following equipment:
- (1) Two (2) extruders, identified as CV-9Ex, constructed in 1995, with a combined capacity of 400 pounds of rubber per hour, equipped with, two (2) feed hoppers,

- and one (1) duster controlled by one (1) dust collector (DC-3) vented internally, and exhausting to general ventilation.
- (2) One (1) natural gas fired rubber curing oven, identified as CV-9C1, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stack CV-9, S-1.
 - (3) One (1) urethane application line, identified as CV-9Ex, constructed in 1996, equipped with six (6) spray guns coating extruded rubber parts and one (1) blown air dryer, with a capacity of 10 grams of coating per minute per gun, and exhausting to stack CV-9, S-5.
 - (4) One (1) natural gas fired coating curing oven with two (2) heat exchangers, identified as CV-9C2, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stacks CV-9, S-2 and CV-9, S-3.
 - (5) One (1) exhaust hood, identified as CV-9EH, and exhausting to stack CV-9, S-4.
- (f) CV Line 10, identified as CV-10, consisting of the following equipment:
- (1) Three (3) extruders, identified as CV-10Ex, with a combined capacity of 750 pounds of rubber per hour, constructed in 2004, and exhausting to general ventilation.
 - (2) Two (2) natural gas-fired microwave curing ovens, identified as CV-10C1, with a heat input capacity of 0.15 MMBtu/hr each, and exhausting to stack CV-10, S-1.
 - (3) One (1) natural gas-fired rubber curing oven, identified as CV-10C2, consisting of four (4) burners each with a heat input capacity of 0.102 MMBtu/hr, and exhausting to stack CV-10, S-2.
 - (4) Six (6) electric heaters, with a capacity of 3 kilowatt hours, each.
 - (5) One (1) exhaust hood, identified as CV-10EH, and exhausting to stack CV-10, S-3.
 - (6) One (1) spray booth, identified as CV-10SB1, constructed in 2004, equipped with four (4) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-10, S-5.
 - (7) One (1) spray booth, identified as CV-10SB2, constructed in 2004, equipped with four (4) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-10, S-6.
 - (8) Three (3) infrared coating curing ovens, identified as CV-10C3, CV-10C4, and CV-10C5, the first two exhausting to general ventilation, the third exhausting to stack CV-10, S-4.
 - (9) One (1) plasma arc generator, consisting of one (1) electric generator, with a capacity of 1.2 kilowatt hours, exhausting to stack CV-10, S-1.

- (g) CV Line 11, identified as CV-11, consisting of the following equipment:
- (1) Four (4) extruders, identified as CV-11Ex, constructed in 1987 and modified in 2008, with a combined capacity of 200 pounds of rubber per hour, equipped with four (4) strip feeders, and exhausting to general ventilation.
 - (2) One (1) electric microwave rubber curing oven, identified as CV-11C1, and exhausting to stack CV-11, S-1.
 - (3) One (1) natural gas rubber curing oven, identified as CV-11C2, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
 - (4) Two (2) exhaust hoods, identified as CV-11EH1 and CV-11EH2, and exhausting to stacks CV-11, S-2 and CV-11, S-1, respectively.
 - (5) One (1) spray booth, identified as CV-11SB, constructed in 2000 and modified in 2008, equipped with four (4) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-11 S-3.
 - (6) One (1) natural gas coating curing oven, identified as CV-11C3, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
- (h) SDM Line 1 (EA), identified as SDM-1, consisting of the following equipment:
- (1) One (1) core metal heater, identified as SDM-1MH, with two (2) natural gas-fired burners with a maximum heat input rate of 0.375 MMBtu/hr.
 - (2) Four (4) extruders, identified as SDM-1Ex, constructed in 2004, with a combined capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave curing ovens, identified as SDM-1C1 and SDM-1C2, with a maximum heat input rate 0.143 MMBtu/hr each, exhausting to stack SDM-1, S-1.
 - (4) One (1) natural gas-fired rubber curing oven, identified as SDM-C3, with two (2) burners with a maximum heat input rate of 0.850 MMBtu/hr each, exhausting to stack SDM-1, S-2.
 - (5) One (1) electric plasma arc generator, identified as SDM-1PI, exhausting to stack SDM-1, S-3.
 - (6) One (1) spray booth, identified as SDM-1SB, constructed in 2004, equipped with six (6) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters to control PM overspray emissions, and exhausting to stack SDM-1, S-5.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-1, C4, with two burners rated at 0.340 MMBtu/hr each, and exhausting to stack SDM-1, S-4.
- (i) SDM Line 3 (EC), identified as SDM-3, consisting of the following equipment:
- (1) One (1) natural gas-fired core metal heater, identified as SDM-3MH, with a heat input capacity of 1.19 MMBtu/hr, and exhausting to general ventilation.

- (2) Three (3) extruders, identified as SDM-3Ex, constructed in 1994, with a combined capacity of 400 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) One (1) natural gas-fired bead type rubber curing over and deodorizing furnace, identified as SDM-3C1, with a heat input capacity of 1.99 MMBtu/hr, and exhausting to stacks SDM, S-2, SDM-3, S-3 and SDM-3, S-4.
 - (4) One (1) bead recovery/dryer system, identified as SDM-3, exhausting to stack SDM-3, S-5.
 - (5) One (1) SDM EC urethane application spray booth, identified as SDM-3SB, constructed in 1996, equipped with three (3) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, exhausting to stack SDM-3, S-7.
 - (6) One (1) natural gas-fired curing oven, identified as SDM-3C2, with a heat input capacity of 1.0 MMBtu/hr, and exhausting to stack SDM-3, S-6.
- (j) SDM Line 4 (ED), identified as SDM-4, consisting of the following equipment:
- (1) One (1) core metal heater, identified as SDM-4MH, with two (2) natural gas-fired burners, each has a heat input capacity of 0.375 million British thermal unit per hour, and exhausting to stack SDM-4, S-1.
 - (2) Four (4) extruders, identified as SDM-4Ex, constructed in 2002, with a maximum capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave rubber curing ovens, identified as SDM-4C1, each with a heat input capacity of 0.143 MMBtu/hr, and both exhausting to stack SDM-4, S-2.
 - (4) One (1) natural gas-fired curing oven, identified as SDM-4C2, with two (2) burners, each with a heat input capacity of 0.850 MMBtu/hr, and exhausting to stack SDM-4, S-3.
 - (5) One (1) electric plasma arc unit, identified as SDM-4PI, exhausting to stack SDM-4, S-4.
 - (6) One (1) spray booth, identified as SDM-4SB, constructed in 2002, equipped with six (6) High-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters to control PM overspray emissions, exhausting to stack SDM-4, S-6.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-4C3, with two burners each having a heat input capacity of 0.34 MMBtu/hr, and exhausting to stack SDM-4, S-5.
- (k) SDM Line 5 (EE), identified as SDM-5, consisting of the following equipment:
- (1) One (1) core metal heater, identified as SDM-5MH, with (2) natural gas-fired burners with heat input capacity of 0.375 MMBtu/hr each.
 - (2) Four (4) extruders, identified as SDM-5Ex, constructed in 2002, with a combined capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.

- (3) Two (2) natural gas-fired microwave curing ovens, identified as SDM-5C1, with a heat input capacity of 0.143 MMBtu/hr each, exhausting to stack SDM-5, S-1.
 - (4) One (1) natural gas-fired rubber curing ovens, identified as SDM-5C2, with two (2) burners, each having a heat input capacity of 0.850 MMBtu/hr, exhausting to stack SDM-5, S-2.
 - (5) One (1) electric plasma arc unit, identified as SDM-5PI, and exhausting to stack SDM-5, S-3.
 - (6) One (1) spray line, identified as SDM-5SB, constructed in 2002, equipped with six (6) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters as controls, with a capacity of 10 grams per minute of coating per gun, and exhausting to stack SDM-5, S-5.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-5C3, with two (2) 0.340 MMBtu/hr burners, exhausting to stacks SDM-5, S-4.
- (I) L-Coat Extrusion Line, identified as LC-1, consisting of the following equipment:
- (1) Four (4) plastic extruders identified as LC-1Ex, constructed in 2006, with a capacity of 19.0 pounds per hour each, and exhausting to general ventilation.
 - (2) Three (3) rubber extruders, identified as LC-1Ex, constructed in 2006, with a capacity of 447.0 pounds per hour each, and exhausting to general ventilation.
 - (3) One (1) natural gas curing oven, identified as LC-1C1, exhausting to stacks LC, S-1, LC, S-2, and LC, S-3, consisting of the following burners:
 - (A) Four (4) natural gas-fired burners, constructed in 2006, with a heat input capacity of 0.782 MMBtu/hr each.
 - (B) Five (5) natural gas-fired burners, constructed in 2007, with a heat input capacity of 0.782 MMBtu/hr each.
 - (4) Three (3) exhaust hoods, identified as LC-1EH1, LC-1EH2, and LC-1EH3, and exhausting to LC, S-4, LC, S-5, and LC, S-6, respectively.
 - (5) One (1) plasma arc unit, identified as LC-1PI, exhausting to stack LC, S-7.
 - (6) One (1) L-Coat Glassline Spray Booth, identified as LC-1SB1, constructed in 2006, utilizing seven (7) high-volume low-pressure (HVLP) spray guns with a maximum capacity of 1.0 unit per hour and particulate emissions controlled by dry filters, and exhausting to stack LC, S-9.
 - (7) One (1) L-Coat Glassline Spray Booth, identified as LC-1SB2, constructed in 2007, utilizing seven (7) high-volume low-pressure (HVLP) spray guns with a maximum capacity of 1.0 unit per hour and particulate emissions controlled by dry filters, and exhausting to one (1) stack LC, S-10.
 - (8) One (1) natural gas coating curing oven, identified as LC-1C2, consisting of six (6) natural gas-fired burners with a maximum heat input capacity of 0.086 MMBtu/hr each, and exhausting to stack LC, S-8.

- (m) One (1) mixing department, identified as Mix-1, constructed in 1987, equipped with one (1) carbon black weigh station and one (1) raw chemical weigh station, both exhausting to a small baghouse identified as Mix-1, S-1, with a capacity of 416.7 pounds of rubber per hour, 3.2 pounds of talc per hour, and 83.3 pounds of carbon black per hour.
- (n) One (1) spray coating booth coating extruded rubber parts, identified as emission unit L42C Nissan, constructed in 2008, equipped with one (1) spray gun, using dry filters as particulate control, with a capacity of ten (10) grams per hour, and exhausting to stack LC-42C, S-1.
- (o) One (1) VN surface coating line, identified as VN-1SB, constructed in 2004, including:
 - (1) One (1) surface coating booth, equipped with one (1) high-volume low-pressure (HVLP) spray gun coating extruded rubber parts, applying surface coatings to rubber parts at a maximum design rate of 0.15 gallons per hour, with particulate emissions controlled by a dry filter system, with emissions exhausted through Stack VN-1, S-1.
 - (2) One (1) electric curing oven, identified as VN-1C.
- (p) One (1) off line finishing spray booth, identified as F-1, constructed in 2007 and modified in 2009, with a capacity of 10 grams of coating per minute, exhausting at stack F-1, S-1 with an associated primer station where primer is applied by hand.
- (q) One (1) off line finishing spray booth, identified as F-2, constructed in 2007, with a capacity of 10 grams of coating per minute, exhausting at stack F-2, S-1.
- (r) One (1) off line finishing spray booth, identified as F-3, constructed in 2007, with a capacity of 10 grams of coating per minute, exhausting at stack F-3, S-1.
- (s) One (1) off line finishing spray booth, identified as F-4, approved for construction in 2009, with a capacity of 10 grams of coating per minute, exhausting to stack F-4, S-1.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)][326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21), that are specifically regulated:

- (a) Dango Mixing Mills B and F, each with a dispersion system, using particulate filters as control [326 IAC 6-3]
- (b) Color Mixing Mill [326 IAC 6-3]
- (c) Mold Tech Repair Sandblast Unit [326 IAC 6-3]
- (d) Mold Tech Repair Weld and Metalworking Equipment [326 IAC 6-3]
- (e) Dango Barwell Extruders [326 IAC 6-3]
- (f) Polymer Block Cutting Station [326 IAC 6-3]
- (g) Scrap Cardboard Bailing Unit [326 IAC 6-3]
- (h) Weld Shop Equipment [326 IAC 6-3]
- (i) Silicone Coating Mixing Station [326 IAC 6-3]

- (j) Die Room Metalworking Equipment [326 IAC 6-3]
- (k) SDM Mezzanine Units [326 IAC 6-3]
- (l) Barwell Warm-Up Mill [326 IAC 6-3]
- (m) One (1) emergency generator rated at 54 HP, burning natural gas, installed in December 2008 and manufactured in 2008. This emergency generator is a new affected source under 40 CFR 63, Subpart ZZZZ. [40 CFR 63, Subpart ZZZZ]

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because it is a major source, as defined in 326 IAC 2-7-1(22).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)][326 IAC 2-1.1-9.5][326 IAC 2-7-4(a)(1)(D)][IC 13-15-3-6(a)]

- (a) This permit, T087-29472-00031, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
- (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

B.3 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.4 Enforceability [326 IAC 2-7-7] [IC 13-17-12]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]

- (a) A certification required by this permit meets the requirements of 326 IAC 2-7-6(1) if:

- (1) it contains a certification by a "responsible official" as defined by 326 IAC 2-7-1(34), and
 - (2) the certification states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) The Permittee may use the attached Certification Form, or its equivalent with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) A "responsible official" is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
- (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)][326 IAC 2-7-6(1) and (6)][326 IAC 1-6-3]

- (a) A Preventive Maintenance Plan meets the requirements of 326 IAC 1-6-3 if it includes, at a minimum:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

The Permittee shall implement the PMPs.

- (b) If required by specific condition(s) in Section D of this permit where no PMP was previously required, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) no later than ninety (90) days after issuance of this permit or ninety (90) days after initial start-up, whichever is later, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The PMP extension notification does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

The Permittee shall implement the PMPs.

- (c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions. The PMPs and their submittal do not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance and Enforcement Branch), or
Telephone Number: 317-233-0178 (ask for Office of Air Quality, Compliance and Enforcement Branch)
Facsimile Number: 317-233-6865

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

B.12 Permit Shield [326 IAC 2-7-15][326 IAC 2-7-20][326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the

permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.

- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
- (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5][326 IAC 2-7-10.5]

- (a) All terms and conditions of permits established prior to T087-29472-00031 and issued pursuant to permitting programs approved into the state implementation plan have been either:
- (1) incorporated as originally stated,
 - (2) revised under 326 IAC 2-7-10.5, or
 - (3) deleted under 326 IAC 2-7-10.5.
- (b) Provided that all terms and conditions are accurately reflected in this permit, all previous registrations and permits are superseded by this Part 70 operating permit.

B.14 Termination of Right to Operate [326 IAC 2-7-10][326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination

[326 IAC 2-7-5(6)(C)][326 IAC 2-7-8(a)][326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.16 Permit Renewal [326 IAC 2-7-3][326 IAC 2-7-4][326 IAC 2-7-8(e)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
 - (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified, pursuant to 326 IAC 2-7-4(a)(2)(D), in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.17 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]

(a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

(b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.18 Permit Revision Under Economic Incentives and Other Programs
[326 IAC 2-7-5(8)][326 IAC 2-7-12(b)(2)]

(a) No Part 70 permit revision or notice shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.

(b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.19 Operational Flexibility [326 IAC 2-7-20][326 IAC 2-7-10.5]

(a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b),(c), or (e) without a prior permit revision, if each of the following conditions is met:

(1) The changes are not modifications under any provision of Title I of the Clean Air Act;

(2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;

(3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

(4) The Permittee notifies the:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-7-20(b),(c), or (e). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.20 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

B.21 Inspection and Entry [326 IAC 2-7-6][IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.

- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.24 Credible Evidence [326 IAC 2-7-5(3)][326 IAC 2-7-6][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-1 (Applicability) and 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator except as provided in 326 IAC 4-2 or in this permit. The Permittee shall not operate a refuse incinerator or refuse burning equipment except as provided in 326 IAC 9-1-2 or in this permit.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted by using ambient air quality modeling pursuant to 326 IAC 1-7-4. The provisions of 326 IAC 1-7-1(3), 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4, and 326 IAC 1-7-5(a), (b), and (d) are not federally enforceable.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least

thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Licensed Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to

thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Licensed Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.8 Performance Testing [326 IAC 3-6]

- (a) For performance testing required by this permit, a test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)][326 IAC 2-7-6(1)]

C.10 Compliance Monitoring [326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, for all monitoring requirements not already legally required, the Permittee shall be allowed up to ninety (90) days from the date of permit issuance or of initial start-up, whichever is later, to begin such monitoring. If due to circumstances beyond the Permittee's control, any monitoring equipment required by this permit cannot be installed and operated no later than ninety (90) days after permit issuance or the date of initial startup, whichever is later, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.11 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5][326 IAC 2-7-6]

C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall maintain the most recently submitted written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) Upon direct notification by IDEM, OAQ that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.14 Response to Excursions or Exceedances [326 IAC 2-7-5] [326 IAC 2-7-6]

Upon detecting an excursion where a response step is required by the D Section or an exceedance of a limitation in this permit:

- (a) The Permittee shall take reasonable response steps to restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing excess emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction. The response may include, but is not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned or are returning to normal without operator action (such as through response by a computerized distribution control system);
or
 - (3) any necessary follow-up actions to return operation to normal or usual manner of operation.

- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records; and/or
 - (3) inspection of the control device, associated capture system, and the process.
- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall record the reasonable response steps taken.

C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5][326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall submit a description of its response actions to IDEM, OAQ, no later than seventy-five (75) days after the date of the test.
- (b) A retest to demonstrate compliance shall be performed no later than one hundred eighty (180) days after the date of the test. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred eighty (180) days is not practicable, IDEM, OAQ may extend the retesting deadline
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.16 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

In accordance with the compliance schedule specified in 326 IAC 2-6-3(b)(1), starting in 2004 and every three (3) years thereafter, the Permittee shall submit by July 1 an emission statement covering the previous calendar year. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4(c) and shall meet the following requirements:

- (1) Indicate estimated actual emissions of all pollutants listed in 326 IAC 2-6-4(a);
- (2) Indicate estimated actual emissions of regulated pollutants as defined by 326 IAC 2-7-1(32) ("Regulated pollutant, which is used only for purposes of Section 19 of this rule") from the source, for purpose of fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue
MC 61-50 IGCN 1003
Indianapolis, Indiana 46204-2251

The emission statement does require a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34).

C.17 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, for all record keeping requirements not already legally required, the Permittee shall be allowed up to ninety (90) days from the date of permit issuance or the date of initial start-up, whichever is later, to begin such record keeping.

C.18 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported except that a deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. This report shall be submitted not later than thirty (30) days after the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include a certification that meets the requirements of 326 IAC 2-7-6(1) by a "responsible official" as defined by 326 IAC 2-7-1(34). A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.
- (b) The address for report submittal is:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

Stratospheric Ozone Protection

C.19 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with applicable standards for recycling and emissions reduction.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) CV Line 5, identified as CV-5:
 - (4) One (1) Line 5 spray booth coating extruded rubber parts, identified as emission unit CV-5SB, constructed in 2000, equipped with six (6) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, using dry filters as control, and exhausting to one (1) stack identified as CV-5, S-4, maximum capacity: 7.93 pounds of waterborne urethane coating per hour.
- (b) CV Line 6, identified as CV-6:
 - (5) One (1) Line 6 spray booth, identified as CV-6SB, constructed in 2000, equipped with six (6) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, using dry filters as control, and exhausting to one (1) stack identified as CV-6, S-3, maximum capacity: 7.93 pounds of waterborne urethane coating per hour.
- (c) CV Line 7, identified as CV-7:
 - (4) One (1) Line 7 waterborne urethane coating booth coating extruded rubber parts, identified as CV-7SB, constructed in 2001, with a capacity of 1.36 gallons of waterborne coating per hour, equipped with spray guns and dry filters, and exhausting to stack CV-7, S-2.
- (d) CV Line 8, identified as CV-8:
 - (4) One (1) natural gas fired coating curing oven, identified as CV-8C2, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stack CV-8, S-4.
 - (5) One (1) urethane application spray booth, identified as CV-8SB, constructed in 1997, equipped with six (6) spray guns coating extruded rubber parts and one (1) blown air dryer, with a capacity of 10 grams of coating per minute per gun, and exhausting to stack CV-8, S-5.
- (e) CV Line 9, identified as CV-9:
 - (3) One (1) urethane application line, identified as CV-9Ex, constructed in 1996, equipped with six (6) spray guns coating extruded rubber parts and one (1) blown air dryer, with a capacity of 10 grams of coating per minute per gun, and exhausting to stack CV-9, S-5.
 - (4) One (1) natural gas fired coating curing oven with two (2) heat exchangers, identified as CV-9C2, with a maximum capacity of 1.59 MMBt/hr, and exhausting to stacks CV-9, S-2 and CV-9, S-3.
- (f) CV Line 10, identified as CV-10:
 - (6) One (1) spray booth, identified as CV-10SB1, constructed in 2004, equipped with four (4) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-10, S-5.

- (7) One (1) spray booth, identified as CV-10SB2, constructed in 2004, equipped with four (4) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-10, S-6.
- (8) Three (3) infrared coating curing ovens, identified as CV-10C3, CV-10C4, and CV-10C5, the first two exhausting to general ventilation, the third exhausting to stack CV-10, S-4.
- (g) CV Line 11, identified as CV-11:
 - (5) One (1) spray booth, identified as CV-11SB, constructed in 2000 and modified in 2008, equipped with four (4) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-11 S-3.
 - (6) One (1) natural gas coating curing oven, identified as CV-11C3, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
- (i) SDM Line 1 (EA), identified as SDM-1:
 - (6) One (1) spray booth, identified as SDM-1SB, constructed in 2004, equipped with six (6) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters to control PM overspray emissions, and exhausting to stack SDM-1, S-5.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-1, C4, with two burners rated at 0.340 MMBtu/hr each, and exhausting to stack SDM-1, S-4.
- (j) SDM Line 3 (EC), identified as SDM-3:
 - (5) One (1) SDM EC urethane application spray booth, identified as SDM-3SB, constructed in 1996, equipped with three (3) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, exhausting to stack SDM-3, S-7.
 - (6) One (1) natural gas-fired curing oven, identified as SDM-3C2, with a heat input capacity of 1.0 MMBtu/hr, and exhausting to stack SDM-3, S-6.
- (k) SDM Line 4 (ED), identified as SDM-4:
 - (6) One (1) spray booth, identified as SDM-4SB, constructed in 2002, equipped with six (6) High-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters to control PM overspray emissions, exhausting to stack SDM-4, S-6.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-4C3, with two burners each having a heat input capacity of 0.34 MMBtu/hr, and exhausting to stack SDM-4, S-5.
- (l) SDM Line 5 (EE), identified as SDM-5:
 - (6) One (1) spray line, identified as SDM-5SB, constructed in 2002, equipped with six (6) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters as controls, with a capacity of 10 grams per minute of coating per gun, and exhausting to stack SDM-5, S-5.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-5C3, with two (2) 0.340 MMBtu/hr burners, exhausting to stacks SDM-5, S-4.

- (m) L-Coat Extrusion Line, identified as LC-1:
- (1) Four (4) plastic extruders identified as LC-1Ex, constructed in 2006, with a capacity of 19.0 pounds per hour each, and exhausting to general ventilation.
 - (2) Three (3) rubber extruders, identified as LC-1Ex, constructed in 2006, with a capacity of 447.0 pounds per hour each, and exhausting to general ventilation.
 - (3) One (1) natural gas curing oven, identified as LC-1C1, exhausting to stacks LC, S-1, LC, S-2, and LC, S-3, consisting of the following burners:
 - (A) Four (4) natural gas-fired burners, constructed in 2006, with a heat input capacity of 0.782 MMBtu/hr each.
 - (B) Five (5) natural gas-fired burners, constructed in 2007, with a heat input capacity of 0.782 MMBtu/hr each.
 - (4) Three (3) exhaust hoods, identified as LC-1EH1, LC-1EH2, and LC-1EH3, and exhausting to LC, S-4, LC, S-5, and LC, S-6, respectively.
 - (5) One (1) plasma arc unit, identified as LC-1PI, exhausting to stack LC, S-7.
 - (6) One (1) L-Coat Glassline Spray Booth, identified as LC-1SB1, constructed in 2006, utilizing seven (7) high-volume low-pressure (HVLP) spray guns with a maximum capacity of 1.0 unit per hour and particulate emissions controlled by dry filters, and exhausting to stack LC, S-9.
 - (7) One (1) L-Coat Glassline Spray Booth, identified as LC-1SB2, constructed in 2007, utilizing seven (7) high-volume low-pressure (HVLP) spray guns with a maximum capacity of 1.0 unit per hour and particulate emissions controlled by dry filters, and exhausting to one (1) stack LC, S-10.
 - (8) One (1) natural gas coating curing oven, identified as LC-1C2, consisting of six (6) natural gas-fired burners with a maximum heat input capacity of 0.086 MMBtu/hr each, and exhausting to stack LC, S-8.
- (n) One (1) spray coating booth coating extruded rubber parts, identified as emission unit L42C Nissan, constructed in 2008, equipped with one (1) spray gun, using dry filters as particulate control, with a capacity of ten (10) grams per hour, and exhausting to stack LC-42C, S-1.
- (o) One (1) VN surface coating line, identified as VN-1SB, constructed in 2004:
- (1) One (1) surface coating booth, equipped with one (1) high-volume low-pressure (HVLP) spray gun coating extruded rubber parts, applying surface coatings to rubber parts at a maximum design rate of 0.15 gallons per hour, with particulate emissions controlled by a dry filter system, with emissions exhausted through Stack VN-1, S-1.
 - (2) One (1) electric curing oven, identified as VN-1C.
- (p) One (1) off line finishing spray booth, identified as F-1, constructed in 2007 and modified in 2009, with a capacity of 10 grams of coating per minute, exhausting at stack F-1, S-1 with an associated primer station where primer is applied by hand.
- (q) One (1) off line finishing spray booth, identified as F-2, constructed in 2007, with a capacity of 10 grams of coating per minute, exhausting at stack F-2, S-1.

- (r) One (1) off line finishing spray booth, identified as F-3, constructed in 2007, with a capacity of 10 grams of coating per minute, exhausting at stack F-3, S-1.
- (s) One (1) off line finishing spray booth, identified as F-4, approved for construction in 2009, with a capacity of 10 grams of coating per minute, exhausting to stack F-4, S-1.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Volatile Organic Compounds (VOCs) [326 IAC 8-1-6]

Pursuant to Part 70 No. 087-7182-00031 issued on April 12, 2001, Significant Permit Modification No. 087-19170-00031 issued on September 9, 2004, and 326 IAC 8-1-6, New facilities; General reduction requirements, the best available control technology (BACT) for the one (1) silicone application line (X019) shall be as follows:

- (a) The total VOC usage at the three (3) spray booths (CV-11SB, CV-5SB, and CV-6SB), three (3) urethane application lines (CV-9SB, SDM-3SB, and CV-8SB), two (2) waterborne urethane coating booths (L42C Nissan and CV-7SB), surface coating lines VN-1SB, SDM-1SB, CV-10SB, SDM-4SB, and SDM-5SB shall be limited to no more than 148 tons per consecutive twelve (12) month period, with compliance determined at the end of each month.
- (b) All coating, urethane and silicone application devices at these facilities shall be drip; high volume, low pressure (HVLP) spray guns; or a coating application device at least as efficient. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.
- (c) All VOC containing containers shall be kept covered when not in use.

D.1.2 Volatile Organic Compound Limitation [326 IAC 2-2]

The total VOC usage at the three (3) spray booths (CV Line 11, CV Line 5, and CV Line 6), three (3) urethane application lines (CV Line 9, SDM Line 3 (EC), and CV Line 8), two (2) waterborne urethane coating booths (CV Line 7, and L42C Nissan), one (1) surface coating line (VN surface coating line), two (2) spray lines (SDM Line 4 (ED) and SDM Line 5 (EE)), one (1) spray line (SDM Line 1 (EA)), one (1) spray line (CV Line 10), the two (2) L-Coat Glassline spray booths (LC-1SB1 and LC-1SB2), and three (3) plastic extruders and three (3) rubber extruders (L-Coat Extrusion Line), shall be limited to no more than 148 tons per consecutive twelve (12) month period, with compliance determined at the end of each month. Emissions from these surface coating operations in combination with uncontrolled potential VOC emissions of 97.63 tons per year from extruding and curing operations (except the L-Coat Extrusion Line), 1.90 tons per year from mixing and milling, 0.892 tons per year from insignificant activities that include three (3) off line finishing spray booths (F-1, F-2, and F-3), and 1.30 tons per year from combustion, shall limit the total VOC emitted at this source to less than 250 tons per year.

Compliance with this limit shall render the requirements of 326 IAC 2-2 (PSD) not applicable.

D.1.3 Particulate [326 IAC 6-3-2(d)]

Particulate from the surface coating manufacturing processes CV-5SB, CV-6SB and CV-7SB shall be controlled by a dry particulate filter, waterwash, or an equivalent control device, and the Permittee shall operate the control device in accordance with manufacturer's specifications.

D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these surface coating facilities and all control devices. Section B - Preventive Maintenance Plan contains the Permittee's obligation with regard to the preventive maintenance plan required by this condition.

Compliance Determination Requirements

D.1.5 Volatile Organic Compounds (VOCs)

Compliance with the VOC usage limitations contained in Conditions D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer. IDEM, OAQ reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.6 VOC Emissions

Compliance with Conditions D.1.1 and D.1.2 shall be demonstrated within 30 days of the end of each month based on the total volatile organic compound for the most recent twelve (12) month period.

Compliance Monitoring Requirements

D.1.7 Particulate Matter

- (a) Weekly inspections shall be performed to verify the placement, integrity and particle loading of the filters controlling the surface coating operations CV-5SB, CV-6SB and CV-7SB at this source. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks, while the associated booths are in operation. If a condition exists which should result in a response step the Permittee shall take reasonable response. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take reasonable response steps shall be considered a deviation from this permit.

- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the nearby ground for surface coating operations CV-5SB, CV-6SB and CV-7SB. The Response to Excursions or Exceedances for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. If a condition exists which should result in a response step the Permittee shall take reasonable response. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take reasonable response steps shall be considered a deviation from this permit.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-19]

D.1.8 Record Keeping Requirements

- (a) To document the compliance status with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and the VOC emission limits established in Conditions D.1.1 and D.1.2.
 - (1) The amount and VOC content of each coating material and solvent used associated with the units identified in the limits in Condition D.1.1 and D.1.2. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used;

- (2) The total VOC usage for each month; and
 - (3) The weight of VOCs emitted for each compliance period.
- (b) To document the compliance status with Condition D.1.7, the Permittee shall maintain a record of weekly filter inspections and overspray observations.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.9 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.1.1 and D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

SECTION D.2 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) CV Line 5, identified as CV-5:
 - (1) Two (2) extruders, identified as CV-5Ex, constructed in 1989, with a combined capacity of 400 pounds of rubber per hour, equipped with strip feeders, and two (2) dusters controlled by one (1) dust collector (DC-2) vented internally, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber and coating curing oven, identified as CV-5C, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-5, S-1.
 - (3) Two (2) exhaust hoods, identified as CV-5EH1 and CV-5EH2, exhausting to stacks CV-5, S-2, and CV-5, S-3, respectively.
- (b) CV Line 6, identified as CV-6:
 - (1) One (1) extruder, identified as CV-6Ex, constructed in 1989, with a capacity of 400 pounds of rubber per hour, equipped with strip feeders, and two (2) dusters controlled by one (1) dust collector (DC-2) vented internally, and exhausting to general ventilation.
 - (2) One (1) microwave curing oven, identified as CV-6C2, and exhausting to CV-6, S-2.
 - (3) One (1) natural gas-fired rubber and coating curing oven, identified as CV-6C1, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-6, S-1.
 - (4) Two (2) exhaust hoods, identified as CV-6EH1 and CV-6EH2, CV-6EH1 exhausting to stack CV-5, S-2, and CV-6EH2, exhausting to stacks CV-6, S-2, and CV-5, S-3.
- (c) CV Line 7, identified as CV-7:
 - (1) Three (3) extruders, identified as CV-7Ex, constructed in 1991, with a combined capacity of 600 of rubber pounds per hour, equipped with one (1) duster, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber and coating curing oven, identified as CV-C, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-7, S-1.
 - (3) One (1) exhaust hood, identified as CV-7EH, exhausting to stack CV-6, S-2.
- (d) CV Line 8, identified as CV-8:
 - (1) Four (4) extruders, identified as CV-8Ex, constructed in 1995, with a combined capacity of 400 pounds of rubber per hour, equipped with four (4) strip feeders, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber vulcanizing oven, identified as CV-8C1, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stacks CV-8, S-1, CV-8, S-2, CV-8, S-3.
 - (3) Two (2) exhaust hoods, identified as CV-8EH1 and CV-86EH2, both exhausting to stack CV-8, S-4.

- (e) CV Line 9, identified as CV-9:
- (1) Two (2) extruders, identified as CV-9Ex, constructed in 1995, with a combined capacity of 400 pounds of rubber per hour, equipped with, two (2) feed hoppers, and one (1) duster controlled by one (1) dust collector (DC-3) vented internally, and exhausting to general ventilation.
 - (2) One (1) natural gas fired rubber curing oven, identified as CV-9C1, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stack CV-9, S-1.
 - (5) One (1) exhaust hood, identified as CV-9EH, and exhausting to stack CV-9, S-4.
- (f) CV Line 10, identified as CV-10:
- (1) Three (3) extruders, identified as CV-10Ex, with a combined capacity of 750 pounds of rubber per hour, constructed in 2004, and exhausting to general ventilation.
 - (2) Two (2) natural gas-fired microwave curing ovens, identified as CV-10C1, with a heat input capacity of 0.15 MMBtu/hr each, and exhausting to stack CV-10, S-1.
 - (3) One (1) natural gas-fired rubber curing oven, identified as CV-10C2, consisting of four (4) burners each with a heat input capacity of 0.102 MMBtu/hr, and exhausting to stack CV-10, S-2.
 - (4) Six (6) electric heaters, with a capacity of 3 kilowatt hours, each.
 - (5) One (1) exhaust hood, identified as CV-10EH, and exhausting to stack CV-10, S-3.
 - (9) One (1) plasma arc generator, consisting of one (1) electric generator, with a capacity of 1.2 kilowatt hours, exhausting to stack CV-10, S-1.
- (g) CV Line 11, identified as CV-11:
- (1) Four (4) extruders, identified as CV-11Ex, constructed in 1987 and modified in 2008, with a combined capacity of 200 pounds of rubber per hour, equipped with, four (4) strip feeders, and exhausting to general ventilation.
 - (2) One (1) electric microwave rubber curing oven, identified as CV-11C1, and exhausting to stack CV-11, S-1.
 - (3) One (1) natural gas rubber curing oven, identified as CV-11C2, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
 - (4) Two (2) exhaust hoods, identified as CV-11EH1 and CV-11EH2, and exhausting to stacks CV-11, S-2 and CV-11, S-1, respectively.
- (h) SDM Line 1 (EA), identified as SDM-1:
- (1) One (1) core metal heater, identified as SDM-1MH, with two (2) natural gas-fired burners with a maximum heat input rate of 0.375 MMBtu/hr.
 - (2) Four (4) extruders, identified as SDM-1Ex, constructed in 2004, with a combined capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave curing ovens, identified as SDM-1C1 and SDM-1C2, with a maximum heat input rate 0.143 MMBtu/hr each, exhausting to stack SDM-1, S-1.

- (4) One (1) natural gas-fired rubber curing oven, identified as SDM-C3, with two (2) burners with a maximum heat input rate of 0.850 MMBtu/hr each, exhausting to stack SDM-1, S-2.
 - (5) One (1) electric plasma arc generator, identified as SDM-1PI, exhausting to stack SDM-1, S-3.
- (i) SDM Line 3 (EC), identified as SDM-3:
- (1) One (1) natural gas-fired core metal heater, identified as SDM-3MH, with a heat input capacity of 1.19 MMBtu/hr, and exhausting to general ventilation.
 - (2) Three (3) extruders, identified as SDM-3Ex, constructed in 1994, with a combined capacity of 400 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) One (1) natural gas-fired bead type rubber curing over and deodorizing furnace, identified as SDM-3C1, with a heat input capacity of 1.99 MMBtu/hr, and exhausting to stacks SDM, S-2, SDM-3, S-3 and SDM-3, S-4.
 - (4) One (1) bead recovery/dryer system, identified as SDM-3, exhausting to stack SDM-3, S-5.
- (j) SDM Line 4 (ED), identified as SDM-4:
- (1) One (1) core metal heater, identified as SDM-4MH, with two (2) natural gas-fired burners, each has a heat input capacity of 0.375 million British thermal unit per hour, and exhausting to stack SDM-4, S-1.
 - (2) Four (4) extruders, identified as SDM-4Ex, constructed in 2002, with a maximum capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave rubber curing ovens, identified as SDM-4C1, each with a heat input capacity of 0.143 MMBtu/hr, and both exhausting to stack SDM-4, S-2.
 - (4) One (1) natural gas-fired curing oven, identified as SDM-4C2, with two (2) burners, each with a heat input capacity of 0.850 MMBtu/hr, and exhausting to stack SDM-4, S-3.
 - (5) One (1) electric plasma arc unit, identified as SDM-4PI, exhausting to stack SDM-4, S-4.
- (k) SDM Line 5 (EE), identified as SDM-5:
- (1) One (1) core metal heater, identified as SDM-5MH, with (2) natural gas-fired burners with heat input capacity of 0.375 MMBtu/hr each.
 - (2) Four (4) extruders, identified as SDM-5Ex, constructed in 2002, with a combined capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave curing ovens, identified as SDM-5C1, with a heat input capacity of 0.143 MMBtu/hr each, exhausting to stack SDM-5, S-1.

- (4) One (1) natural gas-fired rubber curing ovens, identified as SDM-5C2, with two (2) burners, each having a heat input capacity of 0.850 MMBtu/hr, exhausting to stack SDM-5, S-2.
 - (5) One (1) electric plasma arc unit, identified as SDM-5PI, and exhausting to stack SDM-5, S-3.
- (The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), particulate emitted from the facilities listed below shall be limited as stated, based on the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
 P = process weight rate in tons per hour

The particulate from the facilities at this source shall be limited as specified in the following table:

Emission Unit	Process Weight Rate (tons per hour)	Allowable PM Emission Rate [326 IAC 6-3-2] (pounds per hour)
CV-11Ex	0.1	0.877
CV-5Ex	0.2	1.39
CV-6Ex	0.2	1.39
CV-7Ex	0.3	1.83
CV-8Ex	0.2	1.39
CV-9Ex	0.2	1.39
SDM-1Ex	0.65	3.07
SDM-2Ex	0.2	1.39
SDM-3Ex	0.2	1.39
SDM-4Ex	0.65	3.07
SDM-5Ex	0.65	3.07
CV-10Ex	0.375	2.13

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (o) One (1) mixing department, identified as Mix-1, constructed in 1987, equipped with one (1) carbon black weigh station and one (1) raw chemical weigh station, both exhausting to a small baghouse identified as Mix-1, S-1, with a capacity of 416.7 pounds of rubber per hour, 3.2 pounds of talc per hour, and 83.3 pounds of carbon black per hour.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Particulate Matter (PM) [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), particulate emitted from the facilities listed below shall be limited as stated, based on the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
P = process weight rate in tons per hour

Emission Unit	Process Weight Rate (tons per hour)	Allowable PM Emission Rate [326 IAC 6-3-2] (pounds per hour)
Mix-1	0.25	1.63

Compliance Determination Requirements

D.3.2 Particulate Matter (PM)

In order to comply with Condition D.3.1, the baghouse (Mix-1, S-1) for PM control shall be in operation and control emissions from the mixing department at all times that the mixing department is in operation.

SECTION D.4 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) Dango Mixing Mills B and F, each with a dispersion system, using particulate filters as control [326 IAC 6-3]
- (b) Color Mixing Mill [326 IAC 6-3]
- (c) Mold Tech Repair Sandblast Unit [326 IAC 6-3]
- (d) Mold Tech Repair Weld and Metalworking Equipment [326 IAC 6-3]
- (e) Dango Barwell Extruders [326 IAC 6-3]
- (f) Polymer Block Cutting Station [326 IAC 6-3]
- (g) Scrap Cardboard Bailing Unit [326 IAC 6-3]
- (h) Weld Shop Equipment [326 IAC 6-3]
- (i) Silicone Coating Mixing Station [326 IAC 6-3]
- (j) Die Room Metalworking Equipment [326 IAC 6-3]
- (k) SDM Mezzanine Units [326 IAC 6-3]
- (l) Barwell Warm-Up Mill [326 IAC 6-3]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.1 Particulate Matter (PM) [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), particulate emitted from each of the insignificant activities shall not exceed the allowable PM emission rate based on the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

SECTION E.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) One (1) emergency generator rated at 54 HP, burning natural gas, installed in December 2008 and manufactured in 2008.

This emergency generator is a new affected source under 40 CFR 63, Subpart ZZZZ.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

E.1.1 General Provisions Relating to NESHAP Subpart ZZZZ [326 IAC 20-1] [40 CFR Part 63, Subpart A]

Pursuant to 40 CFR 63.7140, the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-1-1, in accordance with schedule in 40 CFR 63 Subpart ZZZZ.

E.1.2 Reciprocating Internal Combustion Engines NESHAP [40 CFR Part 63, Subpart ZZZZ]

The Permittee, which uses the emergency generator, is subject to the following provisions of 40 CFR Part 63, Subpart ZZZZ (included as Attachment A of this permit):

- (1) 40 CFR 63.6580
- (2) 40 CFR 63.6585
- (3) 40 CFR 63.6590(c)

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

PART 70 OPERATING PERMIT CERTIFICATION

Source Name: Nishikawa Cooper, LLC
Source Address: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Permit No.: T087-29472-00031

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify)
- Report (specify)
- Notification (specify)
- Affidavit (specify)
- Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY**

**Compliance and Enforcement Branch
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
Phone: 317-233-0178
Fax: 317-233-6865**

**PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT**

Source Name: Nishikawa Cooper, LLC
Source Address: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Permit No.: T087-29472-00031

This form consists of 2 pages

Page 1 of 2

- This is an emergency as defined in 326 IAC 2-7-1(12)
- The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance and Enforcement Branch); and
 - The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 Compliance and Enforcement Branch**

Part 70 Quarterly Report

Source Name: Nishikawa Cooper, LLC
 Source Address: 324 Morrow Street, Topeka, Indiana 46571
 Part 70 Permit No.: T087-29472-00031
 Facilities: Four (4) spray booths (CV Line 11, CV Line 5, and CV Line 6), three (3) urethane application lines (CV Line 9, SDM Line 3 (EC), and CV Line 8), three (3) waterborne urethane coating booths (CV Line 7, and L42C Nissan), one (1) surface coating line (VN surface coating line), two (2) spray lines (SDM Line 4 (ED) and SDM Line 5 (EE), one (1) spray line (SDM Line 1 (EA)), two (2) spray lines (CV Line 10), the two (2) L-Coat Glassline spray booths (LC-1SB1 and LC-1SB2), and four (4) plastic extruders and three (3) rubber extruders (L-Coat Extrusion Line), described in permit Section D.1.
 Parameter: Total Volatile Organic Compounds (VOC) Usage
 Limit: Less than 148 tons per twelve (12) consecutive month period, with compliance determined at the end of each month.

YEAR: _____

Month	Column 1	Column 2	Column 1 + Column 2
	Total VOC Usage This Month (tons)	Total VOC Usage Previous 11 Months (tons)	12 Month Total VOC Usage (tons)
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
 Deviation has been reported on: _____

Submitted by: _____
 Title / Position: _____
 Signature: _____
 Date: _____
 Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
Compliance and Enforcement Branch**

**PART 70 OPERATING PERMIT
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Nishikawa Cooper, LLC
Source Address: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Permit No.: T087-29472-00031

Months: _____ to _____ Year: _____

Page 1 of 2

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Page 2 of 2

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

A certification is not required for this report.

**Indiana Department of Environmental Management
Office of Air Quality**

Source Name:	Nishikawa Cooper, LLC
Source Location:	324 Morrow Street, Topeka, Indiana 46571
County:	LaGrange
SIC Code:	3061
Operation Permit No.:	T087-29472-00031

Title 40: Protection of Environment

Part 63 - National Emission Standards for Hazardous Air Pollutants

Subpart ZZZZ—National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Source: 69 FR 33506, June 15, 2004, unless otherwise noted.

What This Subpart Covers

§ 63.6580 What is the purpose of subpart ZZZZ?

Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations.

[73 FR 3603, Jan. 18, 2008]

§ 63.6585 Am I subject to this subpart?

You are subject to this subpart if you own or operate a stationary RICE at a major or area source of HAP emissions, except if the stationary RICE is being tested at a stationary RICE test cell/stand.

(a) A stationary RICE is any internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work and which is not mobile. Stationary RICE differ from mobile RICE in that a stationary RICE is not a non-road engine as defined at 40 CFR 1068.30, and is not used to propel a motor vehicle or a vehicle used solely for competition.

(b) A major source of HAP emissions is a plant site that emits or has the potential to emit any single HAP at a rate of 10 tons (9.07 megagrams) or more per year or any combination of HAP at a rate of 25 tons (22.68 megagrams) or more per year, except that for oil and gas production facilities, a major source of HAP emissions is determined for each surface site.

(c) An area source of HAP emissions is a source that is not a major source.

(d) If you are an owner or operator of an area source subject to this subpart, your status as an entity subject to a standard or other requirements under this subpart does not subject you to the obligation to obtain a permit under 40 CFR part 70 or 71, provided you are not required to obtain a permit under 40 CFR 70.3(a) or 40 CFR 71.3(a) for a reason other than your status as an area source under this subpart.

Notwithstanding the previous sentence, you must continue to comply with the provisions of this subpart as applicable.

(e) If you are an owner or operator of a stationary RICE used for national security purposes, you may be eligible to request an exemption from the requirements of this subpart as described in 40 CFR part 1068, subpart C.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3603, Jan. 18, 2008]

§ 63.6590 What parts of my plant does this subpart cover?

This subpart applies to each affected source.

(a) *Affected source.* An affected source is any existing, new, or reconstructed stationary RICE located at a major or area source of HAP emissions, excluding stationary RICE being tested at a stationary RICE test cell/stand.

(1) *Existing stationary RICE.*

(i) For stationary RICE with a site rating of more than 500 brake horsepower (HP) located at a major source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before December 19, 2002.

(ii) For stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.

(iii) For stationary RICE located at an area source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.

(iv) A change in ownership of an existing stationary RICE does not make that stationary RICE a new or reconstructed stationary RICE.

(2) *New stationary RICE.* (i) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after December 19, 2002.

(ii) A stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

(iii) A stationary RICE located at an area source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

(3) *Reconstructed stationary RICE.* (i) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after December 19, 2002.

(ii) A stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after June 12, 2006.

(iii) A stationary RICE located at an area source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after June 12, 2006.

(b) *Stationary RICE subject to limited requirements.* (1) An affected source which meets either of the criteria in paragraphs (b)(1)(i) through (ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).

(i) The stationary RICE is a new or reconstructed emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.

(ii) The stationary RICE is a new or reconstructed limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.

(2) A new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis must meet the initial notification requirements of §63.6645(f) and the requirements of §§63.6625(c), 63.6650(g), and 63.6655(c). These stationary RICE do not have to meet the emission limitations and operating limitations of this subpart.

(3) The following stationary RICE do not have to meet the requirements of this subpart and of subpart A of this part, including initial notification requirements:

(i) Existing spark ignition 2 stroke lean burn (2SLB) stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(ii) Existing spark ignition 4 stroke lean burn (4SLB) stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(iii) Existing emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(iv) Existing limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(v) Existing stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis;

(vi) Existing residential emergency stationary RICE located at an area source of HAP emissions;

(vii) Existing commercial emergency stationary RICE located at an area source of HAP emissions; or

(viii) Existing institutional emergency stationary RICE located at an area source of HAP emissions.

(c) *Stationary RICE subject to Regulations under 40 CFR Part 60.* An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines. No further requirements apply for such engines under this part.

(1) A new or reconstructed stationary RICE located at an area source;

(2) A new or reconstructed 2SLB stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;

(3) A new or reconstructed 4SLB stationary RICE with a site rating of less than 250 brake HP located at a major source of HAP emissions;

(4) A new or reconstructed spark ignition 4 stroke rich burn (4SRB) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;

(5) A new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis;

(6) A new or reconstructed emergency or limited use stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;

(7) A new or reconstructed compression ignition (CI) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9674, Mar. 3, 2010; 75 FR 37733, June 30, 2010; 75 FR 51588, Aug. 20, 2010]

§ 63.6595 When do I have to comply with this subpart?

(a) *Affected sources.* (1) If you have an existing stationary RICE, excluding existing non-emergency CI stationary RICE, with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than June 15, 2007. If you have an existing non-emergency CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, an existing stationary CI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary CI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than May 3, 2013. If you have an existing stationary SI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary SI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than October 19, 2013.

(2) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions before August 16, 2004, you must comply with the applicable emission limitations and operating limitations in this subpart no later than August 16, 2004.

(3) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions after August 16, 2004, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(4) If you start up your new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions before January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart no later than January 18, 2008.

(5) If you start up your new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions after January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(6) If you start up your new or reconstructed stationary RICE located at an area source of HAP emissions before January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart no later than January 18, 2008.

(7) If you start up your new or reconstructed stationary RICE located at an area source of HAP emissions after January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(b) *Area sources that become major sources.* If you have an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP, the compliance dates in paragraphs (b)(1) and (2) of this section apply to you.

(1) Any stationary RICE for which construction or reconstruction is commenced after the date when your area source becomes a major source of HAP must be in compliance with this subpart upon startup of your affected source.

(2) Any stationary RICE for which construction or reconstruction is commenced before your area source becomes a major source of HAP must be in compliance with the provisions of this subpart that are applicable to RICE located at major sources within 3 years after your area source becomes a major source of HAP.

(c) If you own or operate an affected source, you must meet the applicable notification requirements in §63.6645 and in 40 CFR part 63, subpart A.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9675, Mar. 3, 2010; 75 FR 51589, Aug. 20, 2010]

Emission and Operating Limitations

§ 63.6600 What emission limitations and operating limitations must I meet if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

(a) If you own or operate an existing, new, or reconstructed spark ignition 4SRB stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 1a to this subpart and the operating limitations in Table 1b to this subpart which apply to you.

(b) If you own or operate a new or reconstructed 2SLB stationary RICE with a site rating of more than 500 brake HP located at major source of HAP emissions, a new or reconstructed 4SLB stationary RICE with a site rating of more than 500 brake HP located at major source of HAP emissions, or a new or reconstructed CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2a to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

(c) If you own or operate any of the following stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the emission limitations in Tables 1a, 2a, 2c, and 2d to this subpart or operating limitations in Tables 1b and 2b to this subpart: an existing 2SLB stationary RICE; an existing 4SLB stationary RICE; a stationary RICE that combusts landfill

gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis; an emergency stationary RICE; or a limited use stationary RICE.

(d) If you own or operate an existing non-emergency stationary CI RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2c to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 9675, Mar. 3, 2010]

§ 63.6601 What emission limitations must I meet if I own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 brake HP and less than or equal to 500 brake HP located at a major source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart. If you own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at major source of HAP emissions manufactured on or after January 1, 2008, you must comply with the emission limitations in Table 2a to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 9675, Mar. 3, 2010; 75 FR 51589, Aug. 20, 2010]

§ 63.6602 What emission limitations must I meet if I own or operate an existing stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions?

If you own or operate an existing stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2c to this subpart which apply to you. Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

[75 FR 51589, Aug. 20, 2010]

§ 63.6603 What emission limitations and operating limitations must I meet if I own or operate an existing stationary RICE located at an area source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

(a) If you own or operate an existing stationary RICE located at an area source of HAP emissions, you must comply with the requirements in Table 2d to this subpart and the operating limitations in Table 1b and Table 2b to this subpart that apply to you.

(b) If you own or operate an existing stationary non-emergency CI RICE greater than 300 HP located at area sources in areas of Alaska not accessible by the Federal Aid Highway System (FAHS) you do not have to meet the numerical CO emission limitations specified in Table 2d to this subpart. Existing stationary non-emergency CI RICE greater than 300 HP located at area sources in areas of Alaska not accessible by the FAHS must meet the management practices that are shown for stationary non-emergency CI RICE less than or equal to 300 HP in Table 2d to this subpart.

[75 FR 9675, Mar. 3, 2010, as amended at 75 FR 51589, Aug. 20, 2010; 76 FR 12866, Mar. 9, 2011]

§ 63.6604 What fuel requirements must I meet if I own or operate an existing stationary CI RICE?

If you own or operate an existing non-emergency, non-black start CI stationary RICE with a site rating of more than 300 brake HP with a displacement of less than 30 liters per cylinder that uses diesel fuel, you must use diesel fuel that meets the requirements in 40 CFR 80.510(b) for nonroad diesel fuel. Existing non-emergency CI stationary RICE located in Guam, American Samoa, the Commonwealth of the Northern Mariana Islands, or at area sources in areas of Alaska not accessible by the FAHS are exempt from the requirements of this section.

[75 FR 51589, Aug. 20, 2010]

General Compliance Requirements

§ 63.6605 What are my general requirements for complying with this subpart?

(a) You must be in compliance with the emission limitations and operating limitations in this subpart that apply to you at all times.

(b) At all times you must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require you to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

[75 FR 9675, Mar. 3, 2010]

Testing and Initial Compliance Requirements

§ 63.6610 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?

If you own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions you are subject to the requirements of this section.

(a) You must conduct the initial performance test or other initial compliance demonstrations in Table 4 to this subpart that apply to you within 180 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions in §63.7(a)(2).

(b) If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004 and own or operate stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must demonstrate initial compliance with either the proposed emission limitations or the promulgated emission limitations no later than February 10, 2005 or no later than 180 days after startup of the source, whichever is later, according to §63.7(a)(2)(ix).

(c) If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004 and own or operate stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, and you chose to comply with the proposed emission limitations when demonstrating initial compliance, you must conduct a second performance test to demonstrate compliance with the

promulgated emission limitations by December 13, 2007 or after startup of the source, whichever is later, according to §63.7(a)(2)(ix).

(d) An owner or operator is not required to conduct an initial performance test on units for which a performance test has been previously conducted, but the test must meet all of the conditions described in paragraphs (d)(1) through (5) of this section.

(1) The test must have been conducted using the same methods specified in this subpart, and these methods must have been followed correctly.

(2) The test must not be older than 2 years.

(3) The test must be reviewed and accepted by the Administrator.

(4) Either no process or equipment changes must have been made since the test was performed, or the owner or operator must be able to demonstrate that the results of the performance test, with or without adjustments, reliably demonstrate compliance despite process or equipment changes.

(5) The test must be conducted at any load condition within plus or minus 10 percent of 100 percent load.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3605, Jan. 18, 2008]

§ 63.6611 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a new or reconstructed 4SLB SI stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions?

If you own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions, you must conduct an initial performance test within 240 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions specified in Table 4 to this subpart, as appropriate.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 51589, Aug. 20, 2010]

§ 63.6612 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate an existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing stationary RICE located at an area source of HAP emissions?

If you own or operate an existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing stationary RICE located at an area source of HAP emissions you are subject to the requirements of this section.

(a) You must conduct any initial performance test or other initial compliance demonstration according to Tables 4 and 5 to this subpart that apply to you within 180 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions in §63.7(a)(2).

(b) An owner or operator is not required to conduct an initial performance test on a unit for which a performance test has been previously conducted, but the test must meet all of the conditions described in paragraphs (b)(1) through (4) of this section.

- (1) The test must have been conducted using the same methods specified in this subpart, and these methods must have been followed correctly.
- (2) The test must not be older than 2 years.
- (3) The test must be reviewed and accepted by the Administrator.
- (4) Either no process or equipment changes must have been made since the test was performed, or the owner or operator must be able to demonstrate that the results of the performance test, with or without adjustments, reliably demonstrate compliance despite process or equipment changes.

[75 FR 9676, Mar. 3, 2010, as amended at 75 FR 51589, Aug. 20, 2010]

§ 63.6615 When must I conduct subsequent performance tests?

If you must comply with the emission limitations and operating limitations, you must conduct subsequent performance tests as specified in Table 3 of this subpart.

§ 63.6620 What performance tests and other procedures must I use?

- (a) You must conduct each performance test in Tables 3 and 4 of this subpart that applies to you.
- (b) Each performance test must be conducted according to the requirements that this subpart specifies in Table 4 to this subpart. If you own or operate a non-operational stationary RICE that is subject to performance testing, you do not need to start up the engine solely to conduct the performance test. Owners and operators of a non-operational engine can conduct the performance test when the engine is started up again.
- (c) [Reserved]
- (d) You must conduct three separate test runs for each performance test required in this section, as specified in §63.7(e)(3). Each test run must last at least 1 hour.
- (e)(1) You must use Equation 1 of this section to determine compliance with the percent reduction requirement:

$$\frac{C_i - C_o}{C_i} \times 100 = R \quad (\text{Eq. 1})$$

Where:

C_i = concentration of CO or formaldehyde at the control device inlet,

C_o = concentration of CO or formaldehyde at the control device outlet, and

R = percent reduction of CO or formaldehyde emissions.

- (2) You must normalize the carbon monoxide (CO) or formaldehyde concentrations at the inlet and outlet of the control device to a dry basis and to 15 percent oxygen, or an equivalent percent carbon dioxide (CO₂). If pollutant concentrations are to be corrected to 15 percent oxygen and CO₂ concentration is

measured in lieu of oxygen concentration measurement, a CO₂ correction factor is needed. Calculate the CO₂ correction factor as described in paragraphs (e)(2)(i) through (iii) of this section.

(i) Calculate the fuel-specific F_o value for the fuel burned during the test using values obtained from Method 19, section 5.2, and the following equation:

$$F_o = \frac{0.209 F_d}{F_c} \quad (\text{Eq. 2})$$

Where:

F_o = Fuel factor based on the ratio of oxygen volume to the ultimate CO₂ volume produced by the fuel at zero percent excess air.

0.209 = Fraction of air that is oxygen, percent/100.

F_d = Ratio of the volume of dry effluent gas to the gross calorific value of the fuel from Method 19, dsm³ / J (dscf/10⁶ Btu).

F_c = Ratio of the volume of CO₂ produced to the gross calorific value of the fuel from Method 19, dsm³ / J (dscf/10⁶ Btu).

(ii) Calculate the CO₂ correction factor for correcting measurement data to 15 percent oxygen, as follows:

$$X_{co_2} = \frac{5.9}{F_o} \quad (\text{Eq. 3})$$

Where:

X_{co2} = CO₂ correction factor, percent.

5.9 = 20.9 percent O₂ - 15 percent O₂, the defined O₂ correction value, percent.

(iii) Calculate the NO_x and SO₂ gas concentrations adjusted to 15 percent O₂ using CO₂ as follows:

$$C_{adj} = C_d \frac{X_{co_2}}{\%CO_2} \quad (\text{Eq. 4})$$

Where:

%CO₂ = Measured CO₂ concentration measured, dry basis, percent.

(f) If you comply with the emission limitation to reduce CO and you are not using an oxidation catalyst, if you comply with the emission limitation to reduce formaldehyde and you are not using NSCR, or if you comply with the emission limitation to limit the concentration of formaldehyde in the stationary RICE exhaust and you are not using an oxidation catalyst or NSCR, you must petition the Administrator for operating limitations to be established during the initial performance test and continuously monitored thereafter; or for approval of no operating limitations. You must not conduct the initial performance test until after the petition has been approved by the Administrator.

(g) If you petition the Administrator for approval of operating limitations, your petition must include the information described in paragraphs (g)(1) through (5) of this section.

(1) Identification of the specific parameters you propose to use as operating limitations;

(2) A discussion of the relationship between these parameters and HAP emissions, identifying how HAP emissions change with changes in these parameters, and how limitations on these parameters will serve to limit HAP emissions;

(3) A discussion of how you will establish the upper and/or lower values for these parameters which will establish the limits on these parameters in the operating limitations;

(4) A discussion identifying the methods you will use to measure and the instruments you will use to monitor these parameters, as well as the relative accuracy and precision of these methods and instruments; and

(5) A discussion identifying the frequency and methods for recalibrating the instruments you will use for monitoring these parameters.

(h) If you petition the Administrator for approval of no operating limitations, your petition must include the information described in paragraphs (h)(1) through (7) of this section.

(1) Identification of the parameters associated with operation of the stationary RICE and any emission control device which could change intentionally (e.g., operator adjustment, automatic controller adjustment, etc.) or unintentionally (e.g., wear and tear, error, etc.) on a routine basis or over time;

(2) A discussion of the relationship, if any, between changes in the parameters and changes in HAP emissions;

(3) For the parameters which could change in such a way as to increase HAP emissions, a discussion of whether establishing limitations on the parameters would serve to limit HAP emissions;

(4) For the parameters which could change in such a way as to increase HAP emissions, a discussion of how you could establish upper and/or lower values for the parameters which would establish limits on the parameters in operating limitations;

(5) For the parameters, a discussion identifying the methods you could use to measure them and the instruments you could use to monitor them, as well as the relative accuracy and precision of the methods and instruments;

(6) For the parameters, a discussion identifying the frequency and methods for recalibrating the instruments you could use to monitor them; and

(7) A discussion of why, from your point of view, it is infeasible or unreasonable to adopt the parameters as operating limitations.

(i) The engine percent load during a performance test must be determined by documenting the calculations, assumptions, and measurement devices used to measure or estimate the percent load in a specific application. A written report of the average percent load determination must be included in the notification of compliance status. The following information must be included in the written report: the engine model number, the engine manufacturer, the year of purchase, the manufacturer's site-rated brake horsepower, the ambient temperature, pressure, and humidity during the performance test, and all assumptions that were made to estimate or calculate percent load during the performance test must be

clearly explained. If measurement devices such as flow meters, kilowatt meters, beta analyzers, stain gauges, etc. are used, the model number of the measurement device, and an estimate of its accurate in percentage of true value must be provided.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9676, Mar. 3, 2010]

§ 63.6625 What are my monitoring, installation, collection, operation, and maintenance requirements?

(a) If you elect to install a CEMS as specified in Table 5 of this subpart, you must install, operate, and maintain a CEMS to monitor CO and either oxygen or CO₂ at both the inlet and the outlet of the control device according to the requirements in paragraphs (a)(1) through (4) of this section.

(1) Each CEMS must be installed, operated, and maintained according to the applicable performance specifications of 40 CFR part 60, appendix B.

(2) You must conduct an initial performance evaluation and an annual relative accuracy test audit (RATA) of each CEMS according to the requirements in §63.8 and according to the applicable performance specifications of 40 CFR part 60, appendix B as well as daily and periodic data quality checks in accordance with 40 CFR part 60, appendix F, procedure 1.

(3) As specified in §63.8(c)(4)(ii), each CEMS must complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each successive 15-minute period. You must have at least two data points, with each representing a different 15-minute period, to have a valid hour of data.

(4) The CEMS data must be reduced as specified in §63.8(g)(2) and recorded in parts per million or parts per billion (as appropriate for the applicable limitation) at 15 percent oxygen or the equivalent CO₂ concentration.

(b) If you are required to install a continuous parameter monitoring system (CPMS) as specified in Table 5 of this subpart, you must install, operate, and maintain each CPMS according to the requirements in paragraphs (b)(1) through (5) of this section. For an affected source that is complying with the emission limitations and operating limitations on March 9, 2011, the requirements in paragraph (b) of this section are applicable September 6, 2011.

(1) You must prepare a site-specific monitoring plan that addresses the monitoring system design, data collection, and the quality assurance and quality control elements outlined in paragraphs (b)(1)(i) through (v) of this section and in §63.8(d). As specified in §63.8(f)(4), you may request approval of monitoring system quality assurance and quality control procedures alternative to those specified in paragraphs (b)(1) through (5) of this section in your site-specific monitoring plan.

(i) The performance criteria and design specifications for the monitoring system equipment, including the sample interface, detector signal analyzer, and data acquisition and calculations;

(ii) Sampling interface (e.g., thermocouple) location such that the monitoring system will provide representative measurements;

(iii) Equipment performance evaluations, system accuracy audits, or other audit procedures;

(iv) Ongoing operation and maintenance procedures in accordance with provisions in §63.8(c)(1) and (c)(3); and

(v) Ongoing reporting and recordkeeping procedures in accordance with provisions in §63.10(c), (e)(1), and (e)(2)(i).

(2) You must install, operate, and maintain each CPMS in continuous operation according to the procedures in your site-specific monitoring plan.

(3) The CPMS must collect data at least once every 15 minutes (see also §63.6635).

(4) For a CPMS for measuring temperature range, the temperature sensor must have a minimum tolerance of 2.8 degrees Celsius (5 degrees Fahrenheit) or 1 percent of the measurement range, whichever is larger.

(5) You must conduct the CPMS equipment performance evaluation, system accuracy audits, or other audit procedures specified in your site-specific monitoring plan at least annually.

(6) You must conduct a performance evaluation of each CPMS in accordance with your site-specific monitoring plan.

(c) If you are operating a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must monitor and record your fuel usage daily with separate fuel meters to measure the volumetric flow rate of each fuel. In addition, you must operate your stationary RICE in a manner which reasonably minimizes HAP emissions.

(d) If you are operating a new or reconstructed emergency 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions, you must install a non-resettable hour meter prior to the startup of the engine.

(e) If you own or operate any of the following stationary RICE, you must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions:

(1) An existing stationary RICE with a site rating of less than 100 HP located at a major source of HAP emissions;

(2) An existing emergency or black start stationary RICE with a site rating of less than or equal to 500 HP located at a major source of HAP emissions;

(3) An existing emergency or black start stationary RICE located at an area source of HAP emissions;

(4) An existing non-emergency, non-black start stationary CI RICE with a site rating less than or equal to 300 HP located at an area source of HAP emissions;

(5) An existing non-emergency, non-black start 2SLB stationary RICE located at an area source of HAP emissions;

(6) An existing non-emergency, non-black start landfill or digester gas stationary RICE located at an area source of HAP emissions;

(7) An existing non-emergency, non-black start 4SLB stationary RICE with a site rating less than or equal to 500 HP located at an area source of HAP emissions;

(8) An existing non-emergency, non-black start 4SRB stationary RICE with a site rating less than or equal to 500 HP located at an area source of HAP emissions;

(9) An existing, non-emergency, non-black start 4SLB stationary RICE with a site rating greater than 500 HP located at an area source of HAP emissions that is operated 24 hours or less per calendar year; and

(10) An existing, non-emergency, non-black start 4SRB stationary RICE with a site rating greater than 500 HP located at an area source of HAP emissions that is operated 24 hours or less per calendar year.

(f) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing emergency stationary RICE located at an area source of HAP emissions, you must install a non-resettable hour meter if one is not already installed.

(g) If you own or operate an existing non-emergency, non-black start CI engine greater than or equal to 300 HP that is not equipped with a closed crankcase ventilation system, you must comply with either paragraph (g)(1) or paragraph (g)(2) of this section. Owners and operators must follow the manufacturer's specified maintenance requirements for operating and maintaining the open or closed crankcase ventilation systems and replacing the crankcase filters, or can request the Administrator to approve different maintenance requirements that are as protective as manufacturer requirements. Existing CI engines located at area sources in areas of Alaska not accessible by the FAHS do not have to meet the requirements of paragraph (g) of this section.

(1) Install a closed crankcase ventilation system that prevents crankcase emissions from being emitted to the atmosphere, or

(2) Install an open crankcase filtration emission control system that reduces emissions from the crankcase by filtering the exhaust stream to remove oil mist, particulates, and metals.

(h) If you operate a new, reconstructed, or existing stationary engine, you must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Tables 1a, 2a, 2c, and 2d to this subpart apply.

(i) If you own or operate a stationary CI engine that is subject to the work, operation or management practices in items 1 or 2 of Table 2c to this subpart or in items 1 or 4 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

(j) If you own or operate a stationary SI engine that is subject to the work, operation or management practices in items 6, 7, or 8 of Table 2c to this subpart or in items 5, 6, 7, 9, or 11 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change

requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Acid Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from Total Acid Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010; 75 FR 51589, Aug. 20, 2010; 76 FR 12866, Mar. 9, 2011]

§ 63.6630 How do I demonstrate initial compliance with the emission limitations and operating limitations?

- (a) You must demonstrate initial compliance with each emission and operating limitation that applies to you according to Table 5 of this subpart.
- (b) During the initial performance test, you must establish each operating limitation in Tables 1b and 2b of this subpart that applies to you.
- (c) You must submit the Notification of Compliance Status containing the results of the initial compliance demonstration according to the requirements in §63.6645.

Continuous Compliance Requirements

§ 63.6635 How do I monitor and collect data to demonstrate continuous compliance?

- (a) If you must comply with emission and operating limitations, you must monitor and collect data according to this section.
- (b) Except for monitor malfunctions, associated repairs, required performance evaluations, and required quality assurance or control activities, you must monitor continuously at all times that the stationary RICE is operating. A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions.
- (c) You may not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities in data averages and calculations used to report emission or operating levels. You must, however, use all the valid data collected during all other periods.

[69 FR 33506, June 15, 2004, as amended at 76 FR 12867, Mar. 9, 2011]

§ 63.6640 How do I demonstrate continuous compliance with the emission limitations and operating limitations?

(a) You must demonstrate continuous compliance with each emission limitation and operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you according to methods specified in Table 6 to this subpart.

(b) You must report each instance in which you did not meet each emission limitation or operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you. These instances are deviations from the emission and operating limitations in this subpart. These deviations must be reported according to the requirements in §63.6650. If you change your catalyst, you must reestablish the values of the operating parameters measured during the initial performance test. When you reestablish the values of your operating parameters, you must also conduct a performance test to demonstrate that you are meeting the required emission limitation applicable to your stationary RICE.

(c) [Reserved]

(d) For new, reconstructed, and rebuilt stationary RICE, deviations from the emission or operating limitations that occur during the first 200 hours of operation from engine startup (engine burn-in period) are not violations. Rebuilt stationary RICE means a stationary RICE that has been rebuilt as that term is defined in 40 CFR 94.11(a).

(e) You must also report each instance in which you did not meet the requirements in Table 8 to this subpart that apply to you. If you own or operate a new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing emergency stationary RICE, an existing limited use stationary RICE, or an existing stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart, except for the initial notification requirements: a new or reconstructed stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new or reconstructed emergency stationary RICE, or a new or reconstructed limited use stationary RICE.

(f) *Requirements for emergency stationary RICE.* (1) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, a new or reconstructed emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that was installed on or after June 12, 2006, or an existing emergency stationary RICE located at an area source of HAP emissions, you must operate the emergency stationary RICE according to the requirements in paragraphs (f)(1)(i) through (iii) of this section. Any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (f)(1)(i) through (iii) of this section, is prohibited. If you do not operate the engine according to the requirements in paragraphs (f)(1)(i) through (iii) of this section, the engine will not be considered an emergency engine under this subpart and will need to meet all requirements for non-emergency engines.

(i) There is no time limit on the use of emergency stationary RICE in emergency situations.

(ii) You may operate your emergency stationary RICE for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Maintenance checks and readiness testing of such units is limited to 100 hours per year. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness

testing, but a petition is not required if the owner or operator maintains records indicating that Federal, State, or local standards require maintenance and testing of emergency RICE beyond 100 hours per year.

(iii) You may operate your emergency stationary RICE up to 50 hours per year in non-emergency situations, but those 50 hours are counted towards the 100 hours per year provided for maintenance and testing. The 50 hours per year for non-emergency situations cannot be used for peak shaving or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity; except that owners and operators may operate the emergency engine for a maximum of 15 hours per year as part of a demand response program if the regional transmission organization or equivalent balancing authority and transmission operator has determined there are emergency conditions that could lead to a potential electrical blackout, such as unusually low frequency, equipment overload, capacity or energy deficiency, or unacceptable voltage level. The engine may not be operated for more than 30 minutes prior to the time when the emergency condition is expected to occur, and the engine operation must be terminated immediately after the facility is notified that the emergency condition is no longer imminent. The 15 hours per year of demand response operation are counted as part of the 50 hours of operation per year provided for non-emergency situations. The supply of emergency power to another entity or entities pursuant to financial arrangement is not limited by this paragraph (f)(1)(iii), as long as the power provided by the financial arrangement is limited to emergency power.

(2) If you own or operate an emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that was installed prior to June 12, 2006, you must operate the engine according to the conditions described in paragraphs (f)(2)(i) through (iii) of this section. If you do not operate the engine according to the requirements in paragraphs (f)(2)(i) through (iii) of this section, the engine will not be considered an emergency engine under this subpart and will need to meet all requirements for non-emergency engines.

(i) There is no time limit on the use of emergency stationary RICE in emergency situations.

(ii) You may operate your emergency stationary RICE for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by the manufacturer, the vendor, or the insurance company associated with the engine. Required testing of such units should be minimized, but there is no time limit on the use of emergency stationary RICE in emergency situations and for routine testing and maintenance.

(iii) You may operate your emergency stationary RICE for an additional 50 hours per year in non-emergency situations. The 50 hours per year for non-emergency situations cannot be used for peak shaving or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

[69 FR 33506, June 15, 2004, as amended at 71 FR 20467, Apr. 20, 2006; 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010; 75 FR 51591, Aug. 20, 2010]

Notifications, Reports, and Records

§ 63.6645 What notifications must I submit and when?

(a) You must submit all of the notifications in §§63.7(b) and (c), 63.8(e), (f)(4) and (f)(6), 63.9(b) through (e), and (g) and (h) that apply to you by the dates specified if you own or operate any of the following;

(1) An existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions.

- (2) An existing stationary RICE located at an area source of HAP emissions.
- (3) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.
- (4) A new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 HP located at a major source of HAP emissions.
- (5) This requirement does not apply if you own or operate an existing stationary RICE less than 100 HP, an existing stationary emergency RICE, or an existing stationary RICE that is not subject to any numerical emission standards.
- (b) As specified in §63.9(b)(2), if you start up your stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions before the effective date of this subpart, you must submit an Initial Notification not later than December 13, 2004.
- (c) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions on or after August 16, 2004, you must submit an Initial Notification not later than 120 days after you become subject to this subpart.
- (d) As specified in §63.9(b)(2), if you start up your stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions before the effective date of this subpart and you are required to submit an initial notification, you must submit an Initial Notification not later than July 16, 2008.
- (e) If you start up your new or reconstructed stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions on or after March 18, 2008 and you are required to submit an initial notification, you must submit an Initial Notification not later than 120 days after you become subject to this subpart.
- (f) If you are required to submit an Initial Notification but are otherwise not affected by the requirements of this subpart, in accordance with §63.6590(b), your notification should include the information in §63.9(b)(2)(i) through (v), and a statement that your stationary RICE has no additional requirements and explain the basis of the exclusion (for example, that it operates exclusively as an emergency stationary RICE if it has a site rating of more than 500 brake HP located at a major source of HAP emissions).
- (g) If you are required to conduct a performance test, you must submit a Notification of Intent to conduct a performance test at least 60 days before the performance test is scheduled to begin as required in §63.7(b)(1).
- (h) If you are required to conduct a performance test or other initial compliance demonstration as specified in Tables 4 and 5 to this subpart, you must submit a Notification of Compliance Status according to §63.9(h)(2)(ii).
- (1) For each initial compliance demonstration required in Table 5 to this subpart that does not include a performance test, you must submit the Notification of Compliance Status before the close of business on the 30th day following the completion of the initial compliance demonstration.
- (2) For each initial compliance demonstration required in Table 5 to this subpart that includes a performance test conducted according to the requirements in Table 3 to this subpart, you must submit the Notification of Compliance Status, including the performance test results, before the close of business on the 60th day following the completion of the performance test according to §63.10(d)(2).

[73 FR 3606, Jan. 18, 2008, as amended at 75 FR 9677, Mar. 3, 2010; 75 FR 51591, Aug. 20, 2010]

§ 63.6650 What reports must I submit and when?

(a) You must submit each report in Table 7 of this subpart that applies to you.

(b) Unless the Administrator has approved a different schedule for submission of reports under §63.10(a), you must submit each report by the date in Table 7 of this subpart and according to the requirements in paragraphs (b)(1) through (b)(9) of this section.

(1) For semiannual Compliance reports, the first Compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.6595 and ending on June 30 or December 31, whichever date is the first date following the end of the first calendar half after the compliance date that is specified for your source in §63.6595.

(2) For semiannual Compliance reports, the first Compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date follows the end of the first calendar half after the compliance date that is specified for your affected source in §63.6595.

(3) For semiannual Compliance reports, each subsequent Compliance report must cover the semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(4) For semiannual Compliance reports, each subsequent Compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(5) For each stationary RICE that is subject to permitting regulations pursuant to 40 CFR part 70 or 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6 (a)(3)(iii)(A), you may submit the first and subsequent Compliance reports according to the dates the permitting authority has established instead of according to the dates in paragraphs (b)(1) through (b)(4) of this section.

(6) For annual Compliance reports, the first Compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.6595 and ending on December 31.

(7) For annual Compliance reports, the first Compliance report must be postmarked or delivered no later than January 31 following the end of the first calendar year after the compliance date that is specified for your affected source in §63.6595.

(8) For annual Compliance reports, each subsequent Compliance report must cover the annual reporting period from January 1 through December 31.

(9) For annual Compliance reports, each subsequent Compliance report must be postmarked or delivered no later than January 31.

(c) The Compliance report must contain the information in paragraphs (c)(1) through (6) of this section.

(1) Company name and address.

(2) Statement by a responsible official, with that official's name, title, and signature, certifying the accuracy of the content of the report.

(3) Date of report and beginning and ending dates of the reporting period.

(4) If you had a malfunction during the reporting period, the compliance report must include the number, duration, and a brief description for each type of malfunction which occurred during the reporting period and which caused or may have caused any applicable emission limitation to be exceeded. The report must also include a description of actions taken by an owner or operator during a malfunction of an affected source to minimize emissions in accordance with §63.6605(b), including actions taken to correct a malfunction.

(5) If there are no deviations from any emission or operating limitations that apply to you, a statement that there were no deviations from the emission or operating limitations during the reporting period.

(6) If there were no periods during which the continuous monitoring system (CMS), including CEMS and CPMS, was out-of-control, as specified in §63.8(c)(7), a statement that there were no periods during which the CMS was out-of-control during the reporting period.

(d) For each deviation from an emission or operating limitation that occurs for a stationary RICE where you are not using a CMS to comply with the emission or operating limitations in this subpart, the Compliance report must contain the information in paragraphs (c)(1) through (4) of this section and the information in paragraphs (d)(1) and (2) of this section.

(1) The total operating time of the stationary RICE at which the deviation occurred during the reporting period.

(2) Information on the number, duration, and cause of deviations (including unknown cause, if applicable), as applicable, and the corrective action taken.

(e) For each deviation from an emission or operating limitation occurring for a stationary RICE where you are using a CMS to comply with the emission and operating limitations in this subpart, you must include information in paragraphs (c)(1) through (4) and (e)(1) through (12) of this section.

(1) The date and time that each malfunction started and stopped.

(2) The date, time, and duration that each CMS was inoperative, except for zero (low-level) and high-level checks.

(3) The date, time, and duration that each CMS was out-of-control, including the information in §63.8(c)(8).

(4) The date and time that each deviation started and stopped, and whether each deviation occurred during a period of malfunction or during another period.

(5) A summary of the total duration of the deviation during the reporting period, and the total duration as a percent of the total source operating time during that reporting period.

(6) A breakdown of the total duration of the deviations during the reporting period into those that are due to control equipment problems, process problems, other known causes, and other unknown causes.

(7) A summary of the total duration of CMS downtime during the reporting period, and the total duration of CMS downtime as a percent of the total operating time of the stationary RICE at which the CMS downtime occurred during that reporting period.

(8) An identification of each parameter and pollutant (CO or formaldehyde) that was monitored at the stationary RICE.

(9) A brief description of the stationary RICE.

(10) A brief description of the CMS.

(11) The date of the latest CMS certification or audit.

(12) A description of any changes in CMS, processes, or controls since the last reporting period.

(f) Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6 (a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a Compliance report pursuant to Table 7 of this subpart along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the Compliance report includes all required information concerning deviations from any emission or operating limitation in this subpart, submission of the Compliance report shall be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a Compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permit authority.

(g) If you are operating as a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must submit an annual report according to Table 7 of this subpart by the date specified unless the Administrator has approved a different schedule, according to the information described in paragraphs (b)(1) through (b)(5) of this section. You must report the data specified in (g)(1) through (g)(3) of this section.

(1) Fuel flow rate of each fuel and the heating values that were used in your calculations. You must also demonstrate that the percentage of heat input provided by landfill gas or digester gas is equivalent to 10 percent or more of the total fuel consumption on an annual basis.

(2) The operating limits provided in your federally enforceable permit, and any deviations from these limits.

(3) Any problems or errors suspected with the meters.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9677, Mar. 3, 2010]

§ 63.6655 What records must I keep?

(a) If you must comply with the emission and operating limitations, you must keep the records described in paragraphs (a)(1) through (a)(5), (b)(1) through (b)(3) and (c) of this section.

(1) A copy of each notification and report that you submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status that you submitted, according to the requirement in §63.10(b)(2)(xiv).

(2) Records of the occurrence and duration of each malfunction of operation (*i.e.*, process equipment) or the air pollution control and monitoring equipment.

(3) Records of performance tests and performance evaluations as required in §63.10(b)(2)(viii).

(4) Records of all required maintenance performed on the air pollution control and monitoring equipment.

(5) Records of actions taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

(b) For each CEMS or CPMS, you must keep the records listed in paragraphs (b)(1) through (3) of this section.

(1) Records described in §63.10(b)(2)(vi) through (xi).

(2) Previous (*i.e.*, superseded) versions of the performance evaluation plan as required in §63.8(d)(3).

(3) Requests for alternatives to the relative accuracy test for CEMS or CPMS as required in §63.8(f)(6)(i), if applicable.

(c) If you are operating a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must keep the records of your daily fuel usage monitors.

(d) You must keep the records required in Table 6 of this subpart to show continuous compliance with each emission or operating limitation that applies to you.

(e) You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate any of the following stationary RICE;

(1) An existing stationary RICE with a site rating of less than 100 brake HP located at a major source of HAP emissions.

(2) An existing stationary emergency RICE.

(3) An existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart.

(f) If you own or operate any of the stationary RICE in paragraphs (f)(1) or (2) of this section, you must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. If the engines are used for demand response operation, the owner or operator must keep records of the notification of the emergency situation, and the time the engine was operated as part of demand response.

(1) An existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions that does not meet the standards applicable to non-emergency engines.

(2) An existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010; 75 FR 51592, Aug. 20, 2010]

§ 63.6660 In what form and how long must I keep my records?

(a) Your records must be in a form suitable and readily available for expeditious review according to §63.10(b)(1).

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1).

[69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010]

Other Requirements and Information

§ 63.6665 What parts of the General Provisions apply to me?

Table 8 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you. If you own or operate a new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with any of the requirements of the General Provisions specified in Table 8: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing stationary RICE that combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, an existing emergency stationary RICE, or an existing limited use stationary RICE. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in the General Provisions specified in Table 8 except for the initial notification requirements: A new stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new emergency stationary RICE, or a new limited use stationary RICE.

[75 FR 9678, Mar. 3, 2010]

§ 63.6670 Who implements and enforces this subpart?

(a) This subpart is implemented and enforced by the U.S. EPA, or a delegated authority such as your State, local, or tribal agency. If the U.S. EPA Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the U.S. EPA) has the authority to implement and enforce this subpart. You should contact your U.S. EPA Regional Office to find out whether this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under 40 CFR part 63, subpart E, the authorities contained in paragraph (c) of this section are retained by the Administrator of the U.S. EPA and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are:

(1) Approval of alternatives to the non-opacity emission limitations and operating limitations in §63.6600 under §63.6(g).

(2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.

(3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.

(4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.

(5) Approval of a performance test which was conducted prior to the effective date of the rule, as specified in §63.6610(b).

§ 63.6675 What definitions apply to this subpart?

Terms used in this subpart are defined in the Clean Air Act (CAA); in 40 CFR 63.2, the General Provisions of this part; and in this section as follows:

Area source means any stationary source of HAP that is not a major source as defined in part 63.

Associated equipment as used in this subpart and as referred to in section 112(n)(4) of the CAA, means equipment associated with an oil or natural gas exploration or production well, and includes all equipment from the well bore to the point of custody transfer, except glycol dehydration units, storage vessels with potential for flash emissions, combustion turbines, and stationary RICE.

Black start engine means an engine whose only purpose is to start up a combustion turbine.

CAA means the Clean Air Act (42 U.S.C. 7401 *et seq.*, as amended by Public Law 101-549, 104 Stat. 2399).

Commercial emergency stationary RICE means an emergency stationary RICE used in commercial establishments such as office buildings, hotels, stores, telecommunications facilities, restaurants, financial institutions such as banks, doctor's offices, and sports and performing arts facilities.

Compression ignition means relating to a type of stationary internal combustion engine that is not a spark ignition engine.

Custody transfer means the transfer of hydrocarbon liquids or natural gas: After processing and/or treatment in the producing operations, or from storage vessels or automatic transfer facilities or other such equipment, including product loading racks, to pipelines or any other forms of transportation. For the purposes of this subpart, the point at which such liquids or natural gas enters a natural gas processing plant is a point of custody transfer.

Deviation means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

(1) Fails to meet any requirement or obligation established by this subpart, including but not limited to any emission limitation or operating limitation;

(2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or

(3) Fails to meet any emission limitation or operating limitation in this subpart during malfunction, regardless of whether or not such failure is permitted by this subpart.

(4) Fails to satisfy the general duty to minimize emissions established by §63.6(e)(1)(i).

Diesel engine means any stationary RICE in which a high boiling point liquid fuel injected into the combustion chamber ignites when the air charge has been compressed to a temperature sufficiently high for auto-ignition. This process is also known as compression ignition.

Diesel fuel means any liquid obtained from the distillation of petroleum with a boiling point of approximately 150 to 360 degrees Celsius. One commonly used form is fuel oil number 2. Diesel fuel also includes any non-distillate fuel with comparable physical and chemical properties (e.g. biodiesel) that is suitable for use in compression ignition engines.

Digester gas means any gaseous by-product of wastewater treatment typically formed through the anaerobic decomposition of organic waste materials and composed principally of methane and CO₂.

Dual-fuel engine means any stationary RICE in which a liquid fuel (typically diesel fuel) is used for compression ignition and gaseous fuel (typically natural gas) is used as the primary fuel.

Emergency stationary RICE means any stationary internal combustion engine whose operation is limited to emergency situations and required testing and maintenance. Examples include stationary RICE used to produce power for critical networks or equipment (including power supplied to portions of a facility) when electric power from the local utility (or the normal power source, if the facility runs on its own power production) is interrupted, or stationary RICE used to pump water in the case of fire or flood, etc. Stationary RICE used for peak shaving are not considered emergency stationary RICE. Stationary RICE used to supply power to an electric grid or that supply non-emergency power as part of a financial arrangement with another entity are not considered to be emergency engines, except as permitted under §63.6640(f). All emergency stationary RICE must comply with the requirements specified in §63.6640(f) in order to be considered emergency stationary RICE. If the engine does not comply with the requirements specified in §63.6640(f), then it is not considered to be an emergency stationary RICE under this subpart.

Engine startup means the time from initial start until applied load and engine and associated equipment reaches steady state or normal operation. For stationary engine with catalytic controls, engine startup means the time from initial start until applied load and engine and associated equipment, including the catalyst, reaches steady state or normal operation.

Four-stroke engine means any type of engine which completes the power cycle in two crankshaft revolutions, with intake and compression strokes in the first revolution and power and exhaust strokes in the second revolution.

Gaseous fuel means a material used for combustion which is in the gaseous state at standard atmospheric temperature and pressure conditions.

Gasoline means any fuel sold in any State for use in motor vehicles and motor vehicle engines, or nonroad or stationary engines, and commonly or commercially known or sold as gasoline.

Glycol dehydration unit means a device in which a liquid glycol (including, but not limited to, ethylene glycol, diethylene glycol, or triethylene glycol) absorbent directly contacts a natural gas stream and absorbs water in a contact tower or absorption column (absorber). The glycol contacts and absorbs water vapor and other gas stream constituents from the natural gas and becomes "rich" glycol. This glycol is then regenerated in the glycol dehydration unit reboiler. The "lean" glycol is then recycled.

Hazardous air pollutants (HAP) means any air pollutants listed in or pursuant to section 112(b) of the CAA.

Institutional emergency stationary RICE means an emergency stationary RICE used in institutional establishments such as medical centers, nursing homes, research centers, institutions of higher education, correctional facilities, elementary and secondary schools, libraries, religious establishments, police stations, and fire stations.

ISO standard day conditions means 288 degrees Kelvin (15 degrees Celsius), 60 percent relative humidity and 101.3 kilopascals pressure.

Landfill gas means a gaseous by-product of the land application of municipal refuse typically formed through the anaerobic decomposition of waste materials and composed principally of methane and CO₂.

Lean burn engine means any two-stroke or four-stroke spark ignited engine that does not meet the definition of a rich burn engine.

Limited use stationary RICE means any stationary RICE that operates less than 100 hours per year.

Liquefied petroleum gas means any liquefied hydrocarbon gas obtained as a by-product in petroleum refining of natural gas production.

Liquid fuel means any fuel in liquid form at standard temperature and pressure, including but not limited to diesel, residual/crude oil, kerosene/naphtha (jet fuel), and gasoline.

Major Source, as used in this subpart, shall have the same meaning as in §63.2, except that:

(1) Emissions from any oil or gas exploration or production well (with its associated equipment (as defined in this section)) and emissions from any pipeline compressor station or pump station shall not be aggregated with emissions from other similar units, to determine whether such emission points or stations are major sources, even when emission points are in a contiguous area or under common control;

(2) For oil and gas production facilities, emissions from processes, operations, or equipment that are not part of the same oil and gas production facility, as defined in §63.1271 of subpart HHH of this part, shall not be aggregated;

(3) For production field facilities, only HAP emissions from glycol dehydration units, storage vessel with the potential for flash emissions, combustion turbines and reciprocating internal combustion engines shall be aggregated for a major source determination; and

(4) Emissions from processes, operations, and equipment that are not part of the same natural gas transmission and storage facility, as defined in §63.1271 of subpart HHH of this part, shall not be aggregated.

Malfunction means any sudden, infrequent, and not reasonably preventable failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner which causes, or has the potential to cause, the emission limitations in an applicable standard to be exceeded. Failures that are caused in part by poor maintenance or careless operation are not malfunctions.

Natural gas means a naturally occurring mixture of hydrocarbon and non-hydrocarbon gases found in geologic formations beneath the Earth's surface, of which the principal constituent is methane. Natural gas may be field or pipeline quality.

Non-selective catalytic reduction (NSCR) means an add-on catalytic nitrogen oxides (NO_x) control device for rich burn engines that, in a two-step reaction, promotes the conversion of excess oxygen, NO_x, CO, and volatile organic compounds (VOC) into CO₂, nitrogen, and water.

Oil and gas production facility as used in this subpart means any grouping of equipment where hydrocarbon liquids are processed, upgraded (*i.e.*, remove impurities or other constituents to meet contract specifications), or stored prior to the point of custody transfer; or where natural gas is processed, upgraded, or stored prior to entering the natural gas transmission and storage source category. For purposes of a major source determination, facility (including a building, structure, or installation) means oil and natural gas production and processing equipment that is located within the boundaries of an individual surface site as defined in this section. Equipment that is part of a facility will typically be located within close proximity to other equipment located at the same facility. Pieces of production equipment or groupings of equipment located on different oil and gas leases, mineral fee tracts, lease tracts, subsurface or surface unit areas, surface fee tracts, surface lease tracts, or separate surface sites, whether or not connected by a road, waterway, power line or pipeline, shall not be considered part of the same facility. Examples of facilities in the oil and natural gas production source category include, but are not limited to, well sites, satellite tank batteries, central tank batteries, a compressor station that transports natural gas to a natural gas processing plant, and natural gas processing plants.

Oxidation catalyst means an add-on catalytic control device that controls CO and VOC by oxidation.

Peaking unit or engine means any standby engine intended for use during periods of high demand that are not emergencies.

Percent load means the fractional power of an engine compared to its maximum manufacturer's design capacity at engine site conditions. Percent load may range between 0 percent to above 100 percent.

Potential to emit means the maximum capacity of a stationary source to emit a pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the stationary source to emit a pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is federally enforceable. For oil and natural gas production facilities subject to subpart HH of this part, the potential to emit provisions in §63.760(a) may be used. For natural gas transmission and storage facilities subject to subpart HHH of this part, the maximum annual facility gas throughput for storage facilities may be determined according to §63.1270(a)(1) and the maximum annual throughput for transmission facilities may be determined according to §63.1270(a)(2).

Production field facility means those oil and gas production facilities located prior to the point of custody transfer.

Production well means any hole drilled in the earth from which crude oil, condensate, or field natural gas is extracted.

Propane means a colorless gas derived from petroleum and natural gas, with the molecular structure C_3H_8 .

Residential emergency stationary RICE means an emergency stationary RICE used in residential establishments such as homes or apartment buildings.

Responsible official means responsible official as defined in 40 CFR 70.2.

Rich burn engine means any four-stroke spark ignited engine where the manufacturer's recommended operating air/fuel ratio divided by the stoichiometric air/fuel ratio at full load conditions is less than or equal to 1.1. Engines originally manufactured as rich burn engines, but modified prior to December 19, 2002 with passive emission control technology for NO_x (such as pre-combustion chambers) will be considered lean burn engines. Also, existing engines where there are no manufacturer's

recommendations regarding air/fuel ratio will be considered a rich burn engine if the excess oxygen content of the exhaust at full load conditions is less than or equal to 2 percent.

Site-rated HP means the maximum manufacturer's design capacity at engine site conditions.

Spark ignition means relating to either: A gasoline-fueled engine; or any other type of engine with a spark plug (or other sparking device) and with operating characteristics significantly similar to the theoretical Otto combustion cycle. Spark ignition engines usually use a throttle to regulate intake air flow to control power during normal operation. Dual-fuel engines in which a liquid fuel (typically diesel fuel) is used for CI and gaseous fuel (typically natural gas) is used as the primary fuel at an annual average ratio of less than 2 parts diesel fuel to 100 parts total fuel on an energy equivalent basis are spark ignition engines.

Stationary reciprocating internal combustion engine (RICE) means any reciprocating internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work and which is not mobile. Stationary RICE differ from mobile RICE in that a stationary RICE is not a non-road engine as defined at 40 CFR 1068.30, and is not used to propel a motor vehicle or a vehicle used solely for competition.

Stationary RICE test cell/stand means an engine test cell/stand, as defined in subpart P of this part, that tests stationary RICE.

Stoichiometric means the theoretical air-to-fuel ratio required for complete combustion.

Storage vessel with the potential for flash emissions means any storage vessel that contains a hydrocarbon liquid with a stock tank gas-to-oil ratio equal to or greater than 0.31 cubic meters per liter and an American Petroleum Institute gravity equal to or greater than 40 degrees and an actual annual average hydrocarbon liquid throughput equal to or greater than 79,500 liters per day. Flash emissions occur when dissolved hydrocarbons in the fluid evolve from solution when the fluid pressure is reduced.

Subpart means 40 CFR part 63, subpart ZZZZ.

Surface site means any combination of one or more graded pad sites, gravel pad sites, foundations, platforms, or the immediate physical location upon which equipment is physically affixed.

Two-stroke engine means a type of engine which completes the power cycle in single crankshaft revolution by combining the intake and compression operations into one stroke and the power and exhaust operations into a second stroke. This system requires auxiliary scavenging and inherently runs lean of stoichiometric.

[69 FR 33506, June 15, 2004, as amended at 71 FR 20467, Apr. 20, 2006; 73 FR 3607, Jan. 18, 2008; 75 FR 9679, Mar. 3, 2010; 75 FR 51592, Aug. 20, 2010; 76 FR 12867, Mar. 9, 2011]

Table 1 to Subpart ZZZZ of Part 63— Emission Limitations for Existing, New, and Reconstructed Spark Ignition, 4SRB Stationary RICE >500 HP Located at a Major Source of HAP Emissions

As stated in §§63.6600 and 63.6640, you must comply with the following emission limitations at 100 percent load plus or minus 10 percent for existing, new and reconstructed 4SRB stationary RICE >500 HP located at a major source of HAP emissions:

For each . . .	You must meet the following emission limitation, except during periods of startup . . .	During periods of startup you must . . .
1. 4SRB stationary RICE	a. Reduce formaldehyde emissions by 76 percent or more. If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004, you may reduce formaldehyde emissions by 75 percent or more until June 15, 2007 or	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply. ¹
	b. Limit the concentration of formaldehyde in the stationary RICE exhaust to 350 ppbvd or less at 15 percent O ₂	

¹Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.6(g) for alternative work practices.

[75 FR 9679, Mar. 3, 2010, as amended at 75 FR 51592, Aug. 20, 2010]

Table 1bto Subpart ZZZZ of Part 63—Operating Limitations for Existing, New, and Reconstructed Spark Ignition 4SRB Stationary RICE >500 HP Located at a Major Source of HAP Emissions and Existing Spark Ignition 4SRB Stationary RICE >500 HP Located at an Area Source of HAP Emissions

As stated in §§63.6600, 63.6603, 63.6630 and 63.6640, you must comply with the following operating limitations for existing, new and reconstructed 4SRB stationary RICE >500 HP located at a major source of HAP emissions and existing 4SRB stationary RICE >500 HP located at an area source of HAP emissions that operate more than 24 hours per calendar year:

For each . . .	You must meet the following operating limitation . . .
1. 4SRB stationary RICE complying with the requirement to reduce formaldehyde emissions by 76 percent or more (or by 75 percent or more, if applicable) and using NSCR; or 4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 350 ppbvd or less at 15 percent O ₂ and using NSCR; or 4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 2.7 ppmvd or less at 15 percent O ₂ and using NSCR.	a. Maintain your catalyst so that the pressure drop across the catalyst does not change by more than 2 inches of water at 100 percent load plus or minus 10 percent from the pressure drop across the catalyst measured during the initial performance test; and b. Maintain the temperature of your stationary RICE exhaust so that the catalyst inlet temperature is greater than or equal to 750 °F and less than or equal to 1250 °F.
2. 4SRB stationary RICE complying with the requirement to reduce formaldehyde emissions by 76 percent or more (or by 75 percent or more, if applicable) and not using NSCR; or	Comply with any operating limitations approved by the Administrator.

<p>4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 350 ppbvd or less at 15 percent O₂ and not using NSCR; or 4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 2.7 ppmvd or less at 15 percent O₂ and not using NSCR.</p>	
---	--

[76 FR 12867, Mar. 9, 2011]

Table 2ato Subpart ZZZZ of Part 63—Emission Limitations for New and Reconstructed 2SLB and Compression Ignition Stationary RICE >500 HP and New and Reconstructed 4SLB Stationary RICE ≥250 HP Located at a Major Source of HAP Emissions

As stated in §§63.6600 and 63.6640, you must comply with the following emission limitations for new and reconstructed lean burn and new and reconstructed compression ignition stationary RICE at 100 percent load plus or minus 10 percent:

For each . . .	You must meet the following emission limitation, except during periods of startup . . .	During periods of startup you must . . .
1. 2SLB stationary RICE	a. Reduce CO emissions by 58 percent or more; or b. Limit concentration of formaldehyde in the stationary RICE exhaust to 12 ppmvd or less at 15 percent O ₂ . If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004, you may limit concentration of formaldehyde to 17 ppmvd or less at 15 percent O ₂ until June 15, 2007	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply. ¹
2. 4SLB stationary RICE	a. Reduce CO emissions by 93 percent or more; or	
	b. Limit concentration of formaldehyde in the stationary RICE exhaust to 14 ppmvd or less at 15 percent O ₂	
3. CI stationary RICE	a. Reduce CO emissions by 70 percent or more; or	
	b. Limit concentration of formaldehyde in the stationary RICE exhaust to 580 ppbvd or less at 15 percent O ₂	

¹Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.6(g) for alternative work practices.

[75 FR 9680, Mar. 3, 2010]

Table 2bto Subpart ZZZZ of Part 63— Operating Limitations for New and Reconstructed 2SLB and Compression Ignition Stationary RICE >500 HP Located at a Major Source of HAP Emissions, New and Reconstructed 4SLB Stationary RICE ≥250 HP Located at a Major Source of HAP Emissions, Existing Compression Ignition Stationary RICE >500 HP, and Existing 4SLB Stationary RICE >500 HP Located at an Area Source of HAP Emissions

As stated in §§63.6600, 63.6601, 63.6603, 63.6630, and 63.6640, you must comply with the following operating limitations for new and reconstructed 2SLB and compression ignition stationary RICE located at a major source of HAP emissions; new and reconstructed 4SLB stationary RICE ≥250 HP located at a major source of HAP emissions; existing compression ignition stationary RICE >500 HP; and existing 4SLB stationary RICE >500 HP located at an area source of HAP emissions that operate more than 24 hours per calendar year:

For each . . .	You must meet the following operating limitation . . .
1. 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to reduce CO emissions and using an oxidation catalyst; or 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust and using an oxidation catalyst; or 4SLB stationary RICE and CI stationary RICE complying with the requirement to limit the concentration of CO in the stationary RICE exhaust and using an oxidation catalyst	a. maintain your catalyst so that the pressure drop across the catalyst does not change by more than 2 inches of water at 100 percent load plus or minus 10 percent from the pressure drop across the catalyst that was measured during the initial performance test; and b. maintain the temperature of your stationary RICE exhaust so that the catalyst inlet temperature is greater than or equal to 450 °F and less than or equal to 1350 °F. ¹
2. 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to reduce CO emissions and not using an oxidation catalyst; or 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust and not using an oxidation catalyst; or 4SLB stationary RICE and CI stationary RICE complying with the requirement to limit the concentration of CO in the stationary RICE exhaust and not using an oxidation catalyst	Comply with any operating limitations approved by the Administrator.

¹Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.8(g) for a different temperature range.

[75 FR 51593, Aug. 20, 2010, as amended at 76 FR 12867, Mar. 9, 2011]

Table 2cto Subpart ZZZZ of Part 63—Requirements for Existing Compression Ignition Stationary RICE Located at a Major Source of HAP Emissions and Existing Spark Ignition Stationary RICE ≤500 HP Located at a Major Source of HAP Emissions

As stated in §§63.6600, 63.6602, and 63.6640, you must comply with the following requirements for existing compression ignition stationary RICE located at a major source of HAP emissions and existing spark ignition stationary RICE ≤500 HP located at a major source of HAP emissions:

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
1. Emergency stationary CI RICE and black start stationary CI RICE. ¹	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ² b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary. ³	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply. ³
2. Non-Emergency, non-black start stationary CI RICE <100 HP	a. Change oil and filter every 1,000 hours of operation or annually, whichever comes first; ²	
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary. ³	
3. Non-Emergency, non-black start CI stationary RICE 100≤HP≤300 HP	Limit concentration of CO in the stationary RICE exhaust to 230 ppmvd or less at 15 percent O ₂	
4. Non-Emergency, non-black start CI stationary RICE 300<HP≤500	a. Limit concentration of CO in the stationary RICE exhaust to 49 ppmvd or less at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
5. Non-Emergency, non-black start stationary CI RICE >500 HP	a. Limit concentration of CO in the stationary RICE exhaust to 23 ppmvd or less at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
6. Emergency stationary SI RICE and black start stationary SI RICE. ¹	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ²	

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
	b. Inspect spark plugs every 1,000 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary. ³	
7. Non-Emergency, non-black start stationary SI RICE <100 HP that are not 2SLB stationary RICE	a. Change oil and filter every 1,440 hours of operation or annually, whichever comes first; ²	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 1,440 hours of operation or annually, whichever comes first, and replace as necessary. ³	
8. Non-Emergency, non-black start 2SLB stationary SI RICE <100 HP	a. Change oil and filter every 4,320 hours of operation or annually, whichever comes first; ²	
	b. Inspect spark plugs every 4,320 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 4,320 hours of operation or annually, whichever comes first, and replace as necessary. ³	
9. Non-emergency, non-black start 2SLB stationary RICE 100≤HP≤500	Limit concentration of CO in the stationary RICE exhaust to 225 ppmvd or less at 15 percent O ₂	
10. Non-emergency, non-black start 4SLB stationary RICE 100≤HP≤500	Limit concentration of CO in the stationary RICE exhaust to 47 ppmvd or less at 15 percent O ₂	
11. Non-emergency, non-black start 4SRB	Limit concentration of formaldehyde in the stationary	

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
stationary RICE 100≤HP≤500	RICE exhaust to 10.3 ppmvd or less at 15 percent O ₂	
12. Non-emergency, non-black start landfill or digester gas-fired stationary RICE 100≤HP≤500	Limit concentration of CO in the stationary RICE exhaust to 177 ppmvd or less at 15 percent O ₂	

¹If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the work practice requirements on the schedule required in Table 2c of this subpart, or if performing the work practice on the required schedule would otherwise pose an unacceptable risk under Federal, State, or local law, the work practice can be delayed until the emergency is over or the unacceptable risk under Federal, State, or local law has abated. The work practice should be performed as soon as practicable after the emergency has ended or the unacceptable risk under Federal, State, or local law has abated. Sources must report any failure to perform the work practice on the schedule required and the Federal, State or local law under which the risk was deemed unacceptable.

²Sources have the option to utilize an oil analysis program as described in §63.6625(i) in order to extend the specified oil change requirement in Table 2c of this subpart.

³Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.6(g) for alternative work practices.

[75 FR 51593, Aug. 20, 2010]

Table 2dto Subpart ZZZZ of Part 63— Requirements for Existing Stationary RICE Located at Area Sources of HAP Emissions

As stated in §§63.6603 and 63.6640, you must comply with the following requirements for existing stationary RICE located at area sources of HAP emissions:

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
1. Non-Emergency, non-black start CI stationary RICE ≤300 HP	a. Change oil and filter every 1,000 hours of operation or annually, whichever comes first; ¹	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply.
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first;	

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	
2. Non-Emergency, non-black start CI stationary RICE 300<HP≤500	a. Limit concentration of CO in the stationary RICE exhaust to 49 ppmvd at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
3. Non-Emergency, non-black start CI stationary RICE >500 HP	a. Limit concentration of CO in the stationary RICE exhaust to 23 ppmvd at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
4. Emergency stationary CI RICE and black start stationary CI RICE. ²	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ¹	
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	
5. Emergency stationary SI RICE; black start stationary SI RICE; non-emergency, non-black start 4SLB stationary RICE >500 HP that operate 24 hours or less per calendar year; non-emergency, non-black start 4SRB stationary RICE >500 HP that operate 24 hours or less per calendar year. ²	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ¹ b. Inspect spark plugs every 1,000 hours of operation or annually, whichever comes first; and c. Inspect all hoses and	

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
	belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	
6. Non-emergency, non-black start 2SLB stationary RICE	a. Change oil and filter every 4,320 hours of operation or annually, whichever comes first; ¹	
	b. Inspect spark plugs every 4,320 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 4,320 hours of operation or annually, whichever comes first, and replace as necessary.	
7. Non-emergency, non-black start 4SLB stationary RICE ≤500 HP	a. Change oil and filter every 1,440 hours of operation or annually, whichever comes first; ¹	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 1,440 hours of operation or annually, whichever comes first, and replace as necessary.	
8. Non-emergency, non-black start 4SLB stationary RICE >500 HP	a. Limit concentration of CO in the stationary RICE exhaust to 47 ppmvd at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 93 percent or more.	
9. Non-emergency, non-black start 4SRB stationary RICE ≤500 HP	a. Change oil and filter every 1,440 hours of operation or annually,	

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
	whichever comes first; ¹	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 1,440 hours of operation or annually, whichever comes first, and replace as necessary.	
10. Non-emergency, non-black start 4SRB stationary RICE >500 HP	a. Limit concentration of formaldehyde in the stationary RICE exhaust to 2.7 ppmvd at 15 percent O ₂ ; or	
	b. Reduce formaldehyde emissions by 76 percent or more.	
11. Non-emergency, non-black start landfill or digester gas-fired stationary RICE	a. Change oil and filter every 1,440 hours of operation or annually, whichever comes first; ¹	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 1,440 hours of operation or annually, whichever comes first, and replace as necessary.	

¹Sources have the option to utilize an oil analysis program as described in §63.6625(i) in order to extend the specified oil change requirement in Table 2d of this subpart.

²If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the management practice requirements on the schedule required in Table 2d of this subpart, or if performing the management practice on the required schedule would otherwise pose an unacceptable risk under Federal, State, or local law, the management practice can be delayed until the emergency is over or the unacceptable risk under Federal, State, or local law has abated. The management practice should be performed as soon as practicable after the emergency has ended or the

unacceptable risk under Federal, State, or local law has abated. Sources must report any failure to perform the management practice on the schedule required and the Federal, State or local law under which the risk was deemed unacceptable.

[75 FR 51595, Aug. 20, 2010]

Table 3 to Subpart ZZZZ of Part 63—Subsequent Performance Tests

As stated in §§63.6615 and 63.6620, you must comply with the following subsequent performance test requirements:

For each . . .	Complying with the requirement to . . .	You must . . .
1. New or reconstructed 2SLB stationary RICE with a brake horsepower >500 located at major sources; new or reconstructed 4SLB stationary RICE with a brake horsepower ≥250 located at major sources; and new or reconstructed CI stationary RICE with a brake horsepower >500 located at major sources	Reduce CO emissions and not using a CEMS	Conduct subsequent performance tests semiannually. ¹
2. 4SRB stationary RICE with a brake horsepower ≥5,000 located at major sources	Reduce formaldehyde emissions	Conduct subsequent performance tests semiannually. ¹
3. Stationary RICE with a brake horsepower >500 located at major sources and new or reconstructed 4SLB stationary RICE with a brake horsepower 250≤HP≤500 located at major sources	Limit the concentration of formaldehyde in the stationary RICE exhaust	Conduct subsequent performance tests semiannually. ¹
4. Existing non-emergency, non-black start CI stationary RICE with a brake horsepower >500 that are not limited use stationary RICE; existing non-emergency, non-black start 4SLB and 4SRB stationary RICE located at an area source of HAP emissions with a brake horsepower >500 that are operated more than 24 hours per calendar year that are not limited use stationary RICE	Limit or reduce CO or formaldehyde emissions	Conduct subsequent performance tests every 8,760 hrs. or 3 years, whichever comes first.
5. Existing non-emergency, non-black start CI stationary RICE with a brake horsepower >500 that are limited use stationary RICE; existing non-emergency, non-black start 4SLB and 4SRB stationary RICE located at an area source of HAP emissions with a brake horsepower >500 that are operated more than 24 hours per calendar year and are limited use stationary RICE	Limit or reduce CO or formaldehyde emissions	Conduct subsequent performance tests every 8,760 hrs. or 5 years, whichever comes first.

¹After you have demonstrated compliance for two consecutive tests, you may reduce the frequency of subsequent performance tests to annually. If the results of any subsequent annual performance test indicate the stationary RICE is not in compliance with the CO or formaldehyde emission limitation, or you deviate from any of your operating limitations, you must resume semiannual performance tests.

[75 FR 51596, Aug. 20, 2010]

Table 4 to Subpart ZZZZ of Part 63—Requirements for Performance Tests

As stated in §§63.6610, 63.6611, 63.6612, 63.6620, and 63.6640, you must comply with the following requirements for performance tests for stationary RICE:

For each . ..	Complying with the requirement to ...	You must ...	Using ...	According to the following requirements ...
1. 2SLB, 4SLB, and CI stationary RICE	a. Reduce CO emissions	i. Measure the O ₂ at the inlet and outlet of the control device; and	(1) Portable CO and O ₂ analyzer	(a) Using ASTM D6522–00 (2005) ^a (incorporated by reference, see §63.14). Measurements to determine O ₂ must be made at the same time as the measurements for CO concentration.
		ii. Measure the CO at the inlet and the outlet of the control device	(1) Portable CO and O ₂ analyzer	(a) Using ASTM D6522–00 (2005) ^{ab} (incorporated by reference, see §63.14) or Method 10 of 40 CFR appendix A. The CO concentration must be at 15 percent O ₂ , dry basis.
2. 4SRB stationary RICE	a. Reduce formaldehyde emissions	i. Select the sampling port location and the number of traverse points; and	(1) Method 1 or 1A of 40 CFR part 60, appendix A §63.7(d)(1)(i)	(a) Sampling sites must be located at the inlet and outlet of the control device.
		ii. Measure O ₂ at the inlet and outlet of the control device; and	(1) Method 3 or 3A or 3B of 40 CFR part 60, appendix A, or ASTM Method D6522–00m (2005)	(a) Measurements to determine O ₂ concentration must be made at the same time as the measurements for formaldehyde concentration.
		iii. Measure moisture content at the inlet and outlet of the control device; and	(1) Method 4 of 40 CFR part 60, appendix A, or Test Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348–03	(a) Measurements to determine moisture content must be made at the same time and location as the measurements for formaldehyde concentration.
		iv. Measure formaldehyde at the inlet and the outlet of the control device	(1) Method 320 or 323 of 40 CFR part 63, appendix A; or ASTM D6348–03, ^c provided in ASTM D6348–03 Annex A5 (Analyte Spiking Technique), the percent R must be greater than or	(a) Formaldehyde concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.

For each . . .	Complying with the requirement to . . .	You must . . .	Using . . .	According to the following requirements . . .
			equal to 70 and less than or equal to 130	
3. Stationary RICE	a. Limit the concentration of formaldehyde or CO in the stationary RICE exhaust	i. Select the sampling port location and the number of traverse points; and	(1) Method 1 or 1A of 40 CFR part 60, appendix A §63.7(d)(1)(i)	(a) If using a control device, the sampling site must be located at the outlet of the control device.
		ii. Determine the O ₂ concentration of the stationary RICE exhaust at the sampling port location; and	(1) Method 3 or 3A or 3B of 40 CFR part 60, appendix A, or ASTM Method D6522-00 (2005)	(a) Measurements to determine O ₂ concentration must be made at the same time and location as the measurements for formaldehyde concentration.
		iii. Measure moisture content of the stationary RICE exhaust at the sampling port location; and	(1) Method 4 of 40 CFR part 60, appendix A, or Test Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348-03	(a) Measurements to determine moisture content must be made at the same time and location as the measurements for formaldehyde concentration.
		iv. Measure formaldehyde at the exhaust of the stationary RICE; or	(1) Method 320 or 323 of 40 CFR part 63, appendix A; or ASTM D6348-03, ^c provided in ASTM D6348-03 Annex A5 (Analyte Spiking Technique), the percent R must be greater than or equal to 70 and less than or equal to 130	(a) Formaldehyde concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.
		v. Measure CO at the exhaust of the stationary RICE	(1) Method 10 of 40 CFR part 60, appendix A, ASTM Method D6522-00 (2005), ^a Method 320 of 40 CFR part 63, appendix A, or ASTM D6348-03	(a) CO Concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour longer runs.

^aYou may also use Methods 3A and 10 as options to ASTM-D6522-00 (2005). You may obtain a copy of ASTM-D6522-00 (2005) from at least one of the following addresses: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, or University Microfilms International, 300 North Zeeb Road, Ann Arbor, MI 48106. ASTM-D6522-00 (2005) may be used to test both CI and SI stationary RICE.

^bYou may also use Method 320 of 40 CFR part 63, appendix A, or ASTM D6348-03.

°You may obtain a copy of ASTM–D6348–03 from at least one of the following addresses: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428–2959, or University Microfilms International, 300 North Zeeb Road, Ann Arbor, MI 48106.

[75 FR 51597, Aug. 20, 2010]

Table 5 to Subpart ZZZZ of Part 63—Initial Compliance With Emission Limitations and Operating Limitations

As stated in §§63.6612, 63.6625 and 63.6630, you must initially comply with the emission and operating limitations as required by the following:

For each . . .	Complying with the requirement to . . .	You have demonstrated initial compliance if . . .
<p>1. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year</p>	<p>a. Reduce CO emissions and using oxidation catalyst, and using a CPMS</p>	<p>i. The average reduction of emissions of CO determined from the initial performance test achieves the required CO percent reduction; and ii. You have installed a CPMS to continuously monitor catalyst inlet temperature according to the requirements in §63.6625(b); and iii. You have recorded the catalyst pressure drop and catalyst inlet temperature during the initial performance test.</p>
<p>2. Non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year</p>	<p>a. Limit the concentration of CO, using oxidation catalyst, and using a CPMS</p>	<p>i. The average CO concentration determined from the initial performance test is less than or equal to the CO emission limitation; and ii. You have installed a CPMS to continuously monitor catalyst inlet temperature according to the requirements in §63.6625(b); and iii. You have recorded the catalyst pressure drop and catalyst inlet temperature during the initial performance test.</p>
<p>3. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of</p>	<p>a. Reduce CO emissions and not using oxidation catalyst</p>	<p>i. The average reduction of emissions of CO determined from the initial performance test achieves the required CO percent reduction; and ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and iii. You have recorded the approved operating parameters (if any) during the initial performance test.</p>

For each . . .	Complying with the requirement to . . .	You have demonstrated initial compliance if . . .
HAP that are operated more than 24 hours per calendar year		
4. Non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Limit the concentration of CO, and not using oxidation catalyst	i. The average CO concentration determined from the initial performance test is less than or equal to the CO emission limitation; and ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and iii. You have recorded the approved operating parameters (if any) during the initial performance test.
5. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Reduce CO emissions, and using a CEMS	i. You have installed a CEMS to continuously monitor CO and either O ₂ or CO ₂ at both the inlet and outlet of the oxidation catalyst according to the requirements in §63.6625(a); and ii. You have conducted a performance evaluation of your CEMS using PS 3 and 4A of 40 CFR part 60, appendix B; and iii. The average reduction of CO calculated using §63.6620 equals or exceeds the required percent reduction. The initial test comprises the first 4-hour period after successful validation of the CEMS. Compliance is based on the average percent reduction achieved during the 4-hour period.
6. Non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Limit the concentration of CO, and using a CEMS	i. You have installed a CEMS to continuously monitor CO and either O ₂ or CO ₂ at the outlet of the oxidation catalyst according to the requirements in §63.6625(a); and ii. You have conducted a performance evaluation of your CEMS using PS 3 and 4A of 40 CFR part 60, appendix B; and
		iii. The average concentration of CO calculated using §63.6620 is less than or equal to the CO emission limitation. The initial test comprises the first 4-hour period after successful validation of the CEMS. Compliance is based on the average concentration measured during the 4-hour period.

For each . . .	Complying with the requirement to . . .	You have demonstrated initial compliance if . . .
7. Non-emergency 4SRB stationary RICE >500 HP located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Reduce formaldehyde emissions and using NSCR	i. The average reduction of emissions of formaldehyde determined from the initial performance test is equal to or greater than the required formaldehyde percent reduction; and ii. You have installed a CPMS to continuously monitor catalyst inlet temperature according to the requirements in §63.6625(b); and
		iii. You have recorded the catalyst pressure drop and catalyst inlet temperature during the initial performance test.
8. Non-emergency 4SRB stationary RICE >500 HP located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Reduce formaldehyde emissions and not using NSCR	i. The average reduction of emissions of formaldehyde determined from the initial performance test is equal to or greater than the required formaldehyde percent reduction; and ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and
		iii. You have recorded the approved operating parameters (if any) during the initial performance test.
9. Existing non-emergency 4SRB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Limit the concentration of formaldehyde and not using NSCR	i. The average formaldehyde concentration determined from the initial performance test is less than or equal to the formaldehyde emission limitation; and
		ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and
		iii. You have recorded the approved operating parameters (if any) during the initial performance test.
10. New or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE 250≤HP≤500 located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP	a. Limit the concentration of formaldehyde in the stationary RICE exhaust and using oxidation catalyst or NSCR	i. The average formaldehyde concentration, corrected to 15 percent O ₂ , dry basis, from the three test runs is less than or equal to the formaldehyde emission limitation; and ii. You have installed a CPMS to continuously monitor catalyst inlet temperature according to the requirements in §63.6625(b); and

For each . . .	Complying with the requirement to . . .	You have demonstrated initial compliance if . . .
		iii. You have recorded the catalyst pressure drop and catalyst inlet temperature during the initial performance test.
11. New or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE 250≤HP≤500 located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP	a. Limit the concentration of formaldehyde in the stationary RICE exhaust and not using oxidation catalyst or NSCR	i. The average formaldehyde concentration, corrected to 15 percent O ₂ , dry basis, from the three test runs is less than or equal to the formaldehyde emission limitation; and ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and
		iii. You have recorded the approved operating parameters (if any) during the initial performance test.
12. Existing non-emergency stationary RICE 100≤HP≤500 located at a major source of HAP, and existing non-emergency stationary CI RICE 300<HP≤500 located at an area source of HAP	a. Reduce CO or formaldehyde emissions	i. The average reduction of emissions of CO or formaldehyde, as applicable determined from the initial performance test is equal to or greater than the required CO or formaldehyde, as applicable, percent reduction.
13. Existing non-emergency stationary RICE 100≤HP≤500 located at a major source of HAP, and existing non-emergency stationary CI RICE 300<HP≤500 located at an area source of HAP	a. Limit the concentration of formaldehyde or CO in the stationary RICE exhaust	i. The average formaldehyde or CO concentration, as applicable, corrected to 15 percent O ₂ , dry basis, from the three test runs is less than or equal to the formaldehyde or CO emission limitation, as applicable.

[76 FR 12867, Mar. 9, 2011]

Table 6 to Subpart ZZZZ of Part 63—Continuous Compliance With Emission Limitations, Operating Limitations, Work Practices, and Management Practices

As stated in §63.6640, you must continuously comply with the emissions and operating limitations and work or management practices as required by the following:

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
1. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, and new or reconstructed non-emergency CI stationary RICE >500 HP located at a	a. Reduce CO emissions and using an oxidation catalyst, and using a CPMS	i. Conducting semiannual performance tests for CO to demonstrate that the required CO percent reduction is achieved; ^a and ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and iii. Reducing these data to 4-hour

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
major source of HAP		rolling averages; and iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and
		v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.
2. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, and new or reconstructed non-emergency CI stationary RICE >500 HP located at a major source of HAP	a. Reduce CO emissions and not using an oxidation catalyst, and using a CPMS	i. Conducting semiannual performance tests for CO to demonstrate that the required CO percent reduction is achieved; ^a and ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.
3. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, new or reconstructed non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP, existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Reduce CO emissions or limit the concentration of CO in the stationary RICE exhaust, and using a CEMS	i. Collecting the monitoring data according to §63.6625(a), reducing the measurements to 1-hour averages, calculating the percent reduction or concentration of CO emissions according to §63.6620; and ii. Demonstrating that the catalyst achieves the required percent reduction of CO emissions over the 4-hour averaging period, or that the emission remain at or below the CO concentration limit; and iii. Conducting an annual RATA of your CEMS using PS 3 and 4A of 40 CFR part 60, appendix B, as well as daily and periodic data quality checks in accordance with 40 CFR part 60, appendix F, procedure 1.
4. Non-emergency 4SRB stationary RICE >500 HP located at a major source of HAP	a. Reduce formaldehyde emissions and using NSCR	i. Collecting the catalyst inlet temperature data according to §63.6625(b); and
		ii. Reducing these data to 4-hour rolling averages; and

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
		iii. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and
		iv. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.
5. Non-emergency 4SRB stationary RICE >500 HP located at a major source of HAP	a. Reduce formaldehyde emissions and not using NSCR	i. Collecting the approved operating parameter (if any) data according to §63.6625(b); and ii. Reducing these data to 4-hour rolling averages; and
		iii. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.
6. Non-emergency 4SRB stationary RICE with a brake HP ≥5,000 located at a major source of HAP	a. Reduce formaldehyde emissions	Conducting semiannual performance tests for formaldehyde to demonstrate that the required formaldehyde percent reduction is achieved. ^a
7. New or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP and new or reconstructed non-emergency 4SLB stationary RICE 250 ≤HP≤500 located at a major source of HAP	a. Limit the concentration of formaldehyde in the stationary RICE exhaust and using oxidation catalyst or NSCR	i. Conducting semiannual performance tests for formaldehyde to demonstrate that your emissions remain at or below the formaldehyde concentration limit; ^a and ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and
		v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.
8. New or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP and new or	a. Limit the concentration of formaldehyde in the stationary RICE exhaust	i. Conducting semiannual performance tests for formaldehyde to demonstrate that your emissions

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
reconstructed non-emergency 4SLB stationary RICE 250 ≤HP≤500 located at a major source of HAP	and not using oxidation catalyst or NSCR	remain at or below the formaldehyde concentration limit; ^a and ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.
9. Existing emergency and black start stationary RICE ≤500 HP located at a major source of HAP, existing non-emergency stationary RICE <100 HP located at a major source of HAP, existing emergency and black start stationary RICE located at an area source of HAP, existing non-emergency stationary CI RICE ≤300 HP located at an area source of HAP, existing non-emergency 2SLB stationary RICE located at an area source of HAP, existing non-emergency landfill or digester gas stationary SI RICE located at an area source of HAP, existing non-emergency 4SLB and 4SRB stationary RICE ≤500 HP located at an area source of HAP, existing non-emergency 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate 24 hours or less per calendar year	a. Work or Management practices	i. Operating and maintaining the stationary RICE according to the manufacturer's emission-related operation and maintenance instructions; or ii. Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.
10. Existing stationary CI RICE >500 HP that are not limited use stationary RICE, and existing 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year and are not limited use stationary RICE	a. Reduce CO or formaldehyde emissions, or limit the concentration of formaldehyde or CO in the stationary RICE exhaust, and using oxidation catalyst or NSCR	i. Conducting performance tests every 8,760 hours or 3 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and
		ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and
		v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.
11. Existing stationary CI RICE >500 HP that are not limited use stationary RICE, and existing 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year and are not limited use stationary RICE	a. Reduce CO or formaldehyde emissions, or limit the concentration of formaldehyde or CO in the stationary RICE exhaust, and not using oxidation catalyst or NSCR	i. Conducting performance tests every 8,760 hours or 3 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and
		ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.
12. Existing limited use CI stationary RICE >500 HP and existing limited use 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year	a. Reduce CO or formaldehyde emissions or limit the concentration of formaldehyde or CO in the stationary RICE exhaust, and using an oxidation catalyst or NSCR	i. Conducting performance tests every 8,760 hours or 5 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and
		ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
		v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.
13. Existing limited use CI stationary RICE >500 HP and existing limited use 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year	a. Reduce CO or formaldehyde emissions or limit the concentration of formaldehyde or CO in the stationary RICE exhaust, and not using an oxidation catalyst or NSCR	i. Conducting performance tests every 8,760 hours or 5 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and
		ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.

^aAfter you have demonstrated compliance for two consecutive tests, you may reduce the frequency of subsequent performance tests to annually. If the results of any subsequent annual performance test indicate the stationary RICE is not in compliance with the CO or formaldehyde emission limitation, or you deviate from any of your operating limitations, you must resume semiannual performance tests.

[76 FR 12870, Mar. 9, 2011]

Table 7 to Subpart ZZZZ of Part 63—Requirements for Reports

As stated in §63.6650, you must comply with the following requirements for reports:

For each ...	You must submit a ...	The report must contain ...	You must submit the report ...
1. Existing non-emergency, non-black start stationary RICE 100≤HP≤500 located at a major source of HAP; existing non-emergency, non-black start stationary CI RICE >500 HP located at a major source of HAP; existing non-emergency	Compliance report	a. If there are no deviations from any emission limitations or operating limitations that apply to you, a statement that there were no deviations from the emission limitations or operating limitations during the reporting period. If there were no periods during	i. Semiannually according to the requirements in §63.6650(b)(1)–(5) for engines that are not limited use stationary RICE subject to numerical emission

<p>4SRB stationary RICE >500 HP located at a major source of HAP; existing non-emergency, non-black start stationary CI RICE >300 HP located at an area source of HAP; existing non-emergency, non-black start 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP and operated more than 24 hours per calendar year; new or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP; and new or reconstructed non-emergency 4SLB stationary RICE $250 \leq HP \leq 500$ located at a major source of HAP</p>		<p>which the CMS, including CEMS and CPMS, was out-of-control, as specified in §63.8(c)(7), a statement that there were not periods during which the CMS was out-of-control during the reporting period; or b. If you had a deviation from any emission limitation or operating limitation during the reporting period, the information in §63.6650(d). If there were periods during which the CMS, including CEMS and CPMS, was out-of-control, as specified in §63.8(c)(7), the information in §63.6650(e); or c. If you had a malfunction during the reporting period, the information in §63.6650(c)(4)</p>	<p>limitations; and ii. Annually according to the requirements in §63.6650(b)(6)–(9) for engines that are limited use stationary RICE subject to numerical emission limitations. i. Semiannually according to the requirements in §63.6650(b). i. Semiannually according to the requirements in §63.6650(b).</p>
<p>2. New or reconstructed non-emergency stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis</p>	<p>Report</p>	<p>a. The fuel flow rate of each fuel and the heating values that were used in your calculations, and you must demonstrate that the percentage of heat input provided by landfill gas or digester gas, is equivalent to 10 percent or more of the gross heat input on an annual basis; and</p>	<p>i. Annually, according to the requirements in §63.6650.</p>
		<p>b. The operating limits provided in your federally enforceable permit, and any deviations from these limits; and</p>	<p>i. See item 2.a.i.</p>
		<p>c. Any problems or errors suspected with the meters.</p>	<p>i. See item 2.a.i.</p>

[75 FR 51603, Aug. 20, 2010]

Table 8 to Subpart ZZZZ of Part 63—Applicability of General Provisions to Subpart ZZZZ.

As stated in §63.6665, you must comply with the following applicable general provisions.

<p>General provisions citation</p>	<p>Subject of citation</p>	<p>Applies to subpart</p>	<p>Explanation</p>
<p>§63.1</p>	<p>General applicability of the General Provisions</p>	<p>Yes.</p>	
<p>§63.2</p>	<p>Definitions</p>	<p>Yes</p>	<p>Additional terms defined in §63.6675.</p>
<p>§63.3</p>	<p>Units and abbreviations</p>	<p>Yes.</p>	

General provisions citation	Subject of citation	Applies to subpart	Explanation
§63.4	Prohibited activities and circumvention	Yes.	
§63.5	Construction and reconstruction	Yes.	
§63.6(a)	Applicability	Yes.	
§63.6(b)(1)–(4)	Compliance dates for new and reconstructed sources	Yes.	
§63.6(b)(5)	Notification	Yes.	
§63.6(b)(6)	[Reserved]		
§63.6(b)(7)	Compliance dates for new and reconstructed area sources that become major sources	Yes.	
§63.6(c)(1)–(2)	Compliance dates for existing sources	Yes.	
§63.6(c)(3)–(4)	[Reserved]		
§63.6(c)(5)	Compliance dates for existing area sources that become major sources	Yes.	
§63.6(d)	[Reserved]		
§63.6(e)	Operation and maintenance	No.	
§63.6(f)(1)	Applicability of standards	No.	
§63.6(f)(2)	Methods for determining compliance	Yes.	
§63.6(f)(3)	Finding of compliance	Yes.	
§63.6(g)(1)–(3)	Use of alternate standard	Yes.	
§63.6(h)	Opacity and visible emission standards	No	Subpart ZZZZ does not contain opacity or visible emission standards.
§63.6(i)	Compliance extension procedures and criteria	Yes.	
§63.6(j)	Presidential compliance exemption	Yes.	
§63.7(a)(1)–(2)	Performance test dates	Yes	Subpart ZZZZ contains performance test dates at §§63.6610, 63.6611, and 63.6612.
§63.7(a)(3)	CAA section 114 authority	Yes.	
§63.7(b)(1)	Notification of performance test	Yes	Except that §63.7(b)(1) only applies as specified in §63.6645.

General provisions citation	Subject of citation	Applies to subpart	Explanation
§63.7(b)(2)	Notification of rescheduling	Yes	Except that §63.7(b)(2) only applies as specified in §63.6645.
§63.7(c)	Quality assurance/test plan	Yes	Except that §63.7(c) only applies as specified in §63.6645.
§63.7(d)	Testing facilities	Yes.	
§63.7(e)(1)	Conditions for conducting performance tests	No.	Subpart ZZZZ specifies conditions for conducting performance tests at §63.6620.
§63.7(e)(2)	Conduct of performance tests and reduction of data	Yes	Subpart ZZZZ specifies test methods at §63.6620.
§63.7(e)(3)	Test run duration	Yes.	
§63.7(e)(4)	Administrator may require other testing under section 114 of the CAA	Yes.	
§63.7(f)	Alternative test method provisions	Yes.	
§63.7(g)	Performance test data analysis, recordkeeping, and reporting	Yes.	
§63.7(h)	Waiver of tests	Yes.	
§63.8(a)(1)	Applicability of monitoring requirements	Yes	Subpart ZZZZ contains specific requirements for monitoring at §63.6625.
§63.8(a)(2)	Performance specifications	Yes.	
§63.8(a)(3)	[Reserved]		
§63.8(a)(4)	Monitoring for control devices	No.	
§63.8(b)(1)	Monitoring	Yes.	
§63.8(b)(2)–(3)	Multiple effluents and multiple monitoring systems	Yes.	
§63.8(c)(1)	Monitoring system operation and maintenance	Yes.	
§63.8(c)(1)(i)	Routine and predictable SSM	Yes.	
§63.8(c)(1)(ii)	SSM not in Startup Shutdown Malfunction Plan	Yes.	
§63.8(c)(1)(iii)	Compliance with operation and maintenance requirements	Yes.	
§63.8(c)(2)–(3)	Monitoring system installation	Yes.	
§63.8(c)(4)	Continuous monitoring system (CMS) requirements	Yes	Except that subpart ZZZZ does not require Continuous Opacity

General provisions citation	Subject of citation	Applies to subpart	Explanation
			Monitoring System (COMS).
§63.8(c)(5)	COMS minimum procedures	No	Subpart ZZZZ does not require COMS.
§63.8(c)(6)–(8)	CMS requirements	Yes	Except that subpart ZZZZ does not require COMS.
§63.8(d)	CMS quality control	Yes.	
§63.8(e)	CMS performance evaluation	Yes	Except for §63.8(e)(5)(ii), which applies to COMS.
		Except that §63.8(e) only applies as specified in §63.6645.	
§63.8(f)(1)–(5)	Alternative monitoring method	Yes	Except that §63.8(f)(4) only applies as specified in §63.6645.
§63.8(f)(6)	Alternative to relative accuracy test	Yes	Except that §63.8(f)(6) only applies as specified in §63.6645.
§63.8(g)	Data reduction	Yes	Except that provisions for COMS are not applicable. Averaging periods for demonstrating compliance are specified at §§63.6635 and 63.6640.
§63.9(a)	Applicability and State delegation of notification requirements	Yes.	
§63.9(b)(1)–(5)	Initial notifications	Yes	Except that §63.9(b)(3) is reserved.
		Except that §63.9(b) only applies as specified in §63.6645.	
§63.9(c)	Request for compliance extension	Yes	Except that §63.9(c) only applies as specified in §63.6645.
§63.9(d)	Notification of special compliance requirements for new sources	Yes	Except that §63.9(d) only applies as specified in §63.6645.
§63.9(e)	Notification of performance test	Yes	Except that §63.9(e) only applies as specified in §63.6645.
§63.9(f)	Notification of visible emission (VE)/opacity test	No	Subpart ZZZZ does not contain opacity or VE standards.
§63.9(g)(1)	Notification of performance evaluation	Yes	Except that §63.9(g) only applies as specified in §63.6645.

General provisions citation	Subject of citation	Applies to subpart	Explanation
§63.9(g)(2)	Notification of use of COMS data	No	Subpart ZZZZ does not contain opacity or VE standards.
§63.9(g)(3)	Notification that criterion for alternative to RATA is exceeded	Yes	If alternative is in use.
		Except that §63.9(g) only applies as specified in §63.6645.	
§63.9(h)(1)–(6)	Notification of compliance status	Yes	Except that notifications for sources using a CEMS are due 30 days after completion of performance evaluations. §63.9(h)(4) is reserved.
			Except that §63.9(h) only applies as specified in §63.6645.
§63.9(i)	Adjustment of submittal deadlines	Yes.	
§63.9(j)	Change in previous information	Yes.	
§63.10(a)	Administrative provisions for recordkeeping/reporting	Yes.	
§63.10(b)(1)	Record retention	Yes.	
§63.10(b)(2)(i)–(v)	Records related to SSM	No.	
§63.10(b)(2)(vi)–(xi)	Records	Yes.	
§63.10(b)(2)(xii)	Record when under waiver	Yes.	
§63.10(b)(2)(xiii)	Records when using alternative to RATA	Yes	For CO standard if using RATA alternative.
§63.10(b)(2)(xiv)	Records of supporting documentation	Yes.	
§63.10(b)(3)	Records of applicability determination	Yes.	
§63.10(c)	Additional records for sources using CEMS	Yes	Except that §63.10(c)(2)–(4) and (9) are reserved.
§63.10(d)(1)	General reporting requirements	Yes.	
§63.10(d)(2)	Report of performance test results	Yes.	
§63.10(d)(3)	Reporting opacity or VE observations	No	Subpart ZZZZ does not contain opacity or VE standards.

General provisions citation	Subject of citation	Applies to subpart	Explanation
§63.10(d)(4)	Progress reports	Yes.	
§63.10(d)(5)	Startup, shutdown, and malfunction reports	No.	
§63.10(e)(1) and (2)(i)	Additional CMS Reports	Yes.	
§63.10(e)(2)(ii)	COMS-related report	No	Subpart ZZZZ does not require COMS.
§63.10(e)(3)	Excess emission and parameter exceedances reports	Yes.	Except that §63.10(e)(3)(i) (C) is reserved.
§63.10(e)(4)	Reporting COMS data	No	Subpart ZZZZ does not require COMS.
§63.10(f)	Waiver for recordkeeping/reporting	Yes.	
§63.11	Flares	No.	
§63.12	State authority and delegations	Yes.	
§63.13	Addresses	Yes.	
§63.14	Incorporation by reference	Yes.	
§63.15	Availability of information	Yes.	

[75 FR 9688, Mar. 3, 2010]

**Indiana Department of Environmental Management
Office of Air Quality**

**Addendum to the Technical Support Document (TSD) for
a Part 70 Operating Permit Renewal**

Source Description and Location

Source Name:	Nishikawa Cooper, LLC
Source Location:	324 Morrow Street, Topeka, Indiana 46571
County:	LaGrange
SIC Code:	3061
Operation Permit (Renewal) No.:	T 087-29472-00031
Permit Reviewer:	Madhurima D. Moulik

Public Notice Information

On June 24, 2011, the Office of Air Quality (OAQ) had a notice published in the LaGrange Standard, LaGrange, Indiana, stating that Nishikawa Cooper, LLC had applied for a Part 70 renewal No. T087-29472-00031. The notice also stated that OAQ proposed to issue a Part 70 Permit renewal and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

Public Comments

The following comments were submitted by the Permittee:

Comment 1

IDEM updated the company name in the TSD. Please update the company name in the permit and calculations as well.

Response 1

IDEM has updated the company name to Nishikawa Cooper, LLC in the permit and related documents.

Comment 2

Nishikawa Cooper, LLC strives to provide a safe working environment for its employees. Roof access at the plant is only available via ladders on the side of the building. There are no side rails on the roof. Roof access to view overspray is particularly unsafe during the winter months. The company has a good history of monitoring and replacing our dry filters. Therefore, overspray is not likely to occur at the plant.

The Permittee requests the removal of the monthly rooftop inspections to reduce the risk of injury to its employees. Since there is no corresponding record keeping requirement, it appears that IDEM may have intended to remove this requirement. If removal is not acceptable to IDEM, the Permittee would at a minimum request the removal of this requirement during the winter months of December, January and February when snow, ice and other winter hazards are present in addition to the inherent danger of accessing the roof at this site. In addition all compliance monitoring should be limited to booths CV-5SB, CV-6SB, and CV-7SB.

Response 2

D.1.7(b) has been modified to delete the requirement for rooftop inspections and to clarify that the monthly inspections for presence of overspray on the nearby ground is required only for operations CV-5SB, CV-6SB, and CV-7SB.

D.1.7 Particulate Matter

- (a) Weekly inspections shall be performed to verify the placement, integrity and particle loading of the filters controlling the surface coating operations CV-5SB, CV-6SB and CV-7SB at this source. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks, while the associated booths are in operation. If a condition exists which should result in a response step the Permittee shall take reasonable response. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take reasonable response steps shall be considered a deviation from this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the ~~rooftops and the~~ nearby ground **for surface coating operations CV-5SB, CV-6SB and CV-7SB**. The Response to Excursions or Exceedances for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. If a condition exists which should result in a response step the Permittee shall take reasonable response. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take reasonable response steps shall be considered a deviation from this permit.

Comment 3

We request that the emission unit descriptions in Condition D.1.1 be revised to reflect the current nomenclature. Please revise the descriptions as follows:

D.1.1 (a) The total VOC usage at the ~~three (3) four (4)~~ spray booths (~~CV Line 11, CV Line 5, and CV Line 6~~ **CV-11SB, CV-5SB, CV-6SB**), three (3) urethane application lines (~~CV Line 9, SDM Line 3 (EC), and CV Line 8~~ **CV-9SB, SDM-3SB, and CV-8SB**), ~~three (3) two~~ waterborne urethane coating booths (~~CV Line 7, and L42C Nissan and CV-7SB~~), ~~one (1) surface coating lines (VN surface coating line), two (2) spray lines (SDM Line 4 (ED) and SDM Line 5 (EE))~~ **SDM-1SB, CV-10SB, SDM-4SB, and SDM-5SB**), ~~one (1) spray line (SDM Line 1 (EA)), and two (2) spray lines (CV Line 10)~~ shall be limited to no more than 148 tons per consecutive twelve (12) month period, with compliance determined at the end of each month.

Response 3

The descriptions of emissions units in Condition D.1.1 have been revised as follows:

D.1.1 Volatile Organic Compounds (VOCs) [326 IAC 8-1-6]

Pursuant to Part 70 No. 087-7182-00031 issued on April 12, 2001, Significant Permit Modification No. 087-19170-00031 issued on September 9, 2004, and 326 IAC 8-1-6, New facilities; General reduction requirements, the best available control technology (BACT) for the one (1) silicone application line (X019) shall be as follows:

- (a) The total VOC usage at the ~~three (3) four (4)~~ spray booths (~~CV Line 11, CV Line 5, and CV Line 6~~ **CV-11SB, CV-5SB, and CV-6SB**), three (3) urethane application lines (~~CV Line 9, SDM Line 3 (EC), and CV Line 8~~ **CV-9SB, SDM-3SB, and CV-8SB**), ~~two (2) three (3)~~ waterborne urethane coating booths (~~CV Line 7, and L42C Nissan and CV-7SB~~), ~~one (1) surface coating lines (VN surface coating line), two (2) spray lines (SDM Line 4 (ED) and SDM Line 5 (EE))~~ **SDM-1SB, CV-10SB, SDM-4SB, and SDM-**

5SB), ~~one (1) spray line (SDM Line 1 (EA)), and two (2) spray lines (CV Line 10)~~ shall be limited to no more than 148 tons per consecutive twelve (12) month period, with compliance determined at the end of each month.

- (b) All coating, urethane and silicone application devices at these facilities shall be drip; high volume, low pressure (HVLP) spray guns; or a coating application device at least as efficient. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.
- (c) All VOC containing containers shall be kept covered when not in use.

Comment 4

The Permittee requested the following emission unit description correction for the surface coating booth for Line CV-11 in Sections A.2 and D.1:

- (g)(5) One (1) spray booth, identified as CV-11Ex~~SB~~, constructed in 2000 and modified in 2008, equipped with four (4) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-11 S-3.

Response 4

The following corrections have been made to Sections A.2 and D.1 facility descriptions:

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)][326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

...

- (g) CV Line 11, identified as CV-11, consisting of the following equipment:
 - (1) Four (4) extruders, identified as CV-11Ex, constructed in 1987 and modified in 2008, with a combined capacity of 200 pounds of rubber per hour, equipped with four (4) strip feeders, and exhausting to general ventilation.
 - (2) One (1) electric microwave rubber curing oven, identified as CV-11C1, and exhausting to stack CV-11, S-1.
 - (3) One (1) natural gas rubber curing oven, identified as CV-11C2, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
 - (4) Two (2) exhaust hoods, identified as CV-11EH1 and CV-11EH2, and exhausting to stacks CV-11, S-2 and CV-11, S-1, respectively.
 - (5) One (1) spray booth, identified as CV-11~~SB~~Ex, constructed in 2000 and modified in 2008, equipped with four (4) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-11 S-3.
 - (6) One (1) natural gas coating curing oven, identified as CV-11C3, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

- (a) CV Line 5, identified as CV-5:
- (4) One (1) Line 5 spray booth coating extruded rubber parts, identified as emission unit CV-5SB, constructed in 2000, equipped with six (6) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, using dry filters as control, and exhausting to one (1) stack identified as CV-5, S-4, maximum capacity: 7.93 pounds of waterborne urethane coating per hour.
....
- (g) CV Line 11, identified as CV-11:
- (5) One (1) spray booth, identified as CV-11SBE~~x~~, constructed in 2000 and modified in 2008, equipped with four (4) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-11 S-3.
- (6) One (1) natural gas coating curing oven, identified as CV-11C3, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
....

IDEM Analysis - Greenhouse Gases

IDEM has estimated the emissions of greenhouse gases (CO₂e) for the emissions units at this facility (included as Appendix A to this Addendum).

This source remains a minor source under Prevention of Significant Deterioration (PSD) rules since the PTE of CO₂e is less than 100,000 tons per year. Therefore, pursuant to 326 IAC 2-2, the PSD requirements do not apply.

**TSD Addendum - Appendix A: Emissions Calculations
Natural Gas Combustion Only
MM BTU/HR <100**

Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Plt ID: 087-00031
Date: 8/2/2011

Heat Input Capacity MMBtu/hr	HHV mmBtu mmscf	Potential Throughput MMCF/yr
45.0	1000	394.1

Emission Factor in lb/MMCF	Pollutant						
	PM*	PM10*	direct PM2.5*	SO2	NOx	VOC	CO
	1.9	7.6	7.6	0.6	100 **see below	5.5	84
Potential Emission in tons/yr	0.4	1.5	1.5	0.1	19.7	1.1	16.6

*PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

PM2.5 emission factor is filterable and condensable PM2.5 combined.

**Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

See page 2 for HAPs emissions calculations.

**TSD Addendum - Appendix A: Emissions Calculations
Natural Gas Combustion Only
MM BTU/HR <100**

**Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Plt ID: 087-00031
Date: 8/2/2011**

HAPs - Organics					
Emission Factor in lb/MMcf	Benzene 2.1E-03	Dichlorobenzene 1.2E-03	Formaldehyde 7.5E-02	Hexane 1.8E+00	Toluene 3.4E-03
Potential Emission in tons/yr	4.138E-04	2.365E-04	1.478E-02	3.547E-01	6.700E-04

HAPs - Metals					
Emission Factor in lb/MMcf	Lead 5.0E-04	Cadmium 1.1E-03	Chromium 1.4E-03	Manganese 3.8E-04	Nickel 2.1E-03
Potential Emission in tons/yr	9.853E-05	2.168E-04	2.759E-04	7.488E-05	4.138E-04

Methodology is the same as page 1.

The five highest organic and metal HAPs emission factors are provided above.
Additional HAPs emission factors are available in AP-42, Chapter 1.4.
See Page 3 for Greenhouse Gas calculations.

**TSD Addendum - Appendix A: Emissions Calculations
Natural Gas Combustion Only
MM BTU/HR <100**

Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Plt ID: 087-00031
Date: 8/2/2011

	Greenhouse Gas		
	CO2	CH4	N2O
Emission Factor in lb/MMcf	120,000	2.3	2.2
Potential Emission in tons/yr	23,647	0.5	0.4
Summed Potential Emissions in tons/yr	23,648		
CO2e Total in tons/yr	23,791		

Methodology

The N2O Emission Factor for uncontrolled is 2.2. The N2O Emission Factor for low Nox burner is 0.64.
Emission Factors are from AP 42, Table 1.4-2 SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03.
Greenhouse Warming Potentials (GWP) from Table A-1 of 40 CFR Part 98 Subpart A.
Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton
CO2e (tons/yr) = CO2 Potential Emission ton/yr x CO2 GWP (1) + CH4 Potential Emission ton/yr x CH4 GWP (21) + N2O Potential Emission ton/yr x N2O GWP (310).

Indiana Department of Environmental Management
Office of Air Quality

Technical Support Document (TSD) for a Part 70 Operating Permit Renewal

Source Background and Description

Source Name:	Nishikawa Cooper, LLC
Source Location:	324 Morrow Street, Topeka, Indiana 46571
County:	LaGrange
SIC Code:	3061
Operation Permit (Renewal) No.:	T 087-29472-00031
Permit Reviewer:	Madhurima D. Moulik

The Office of Air Quality (OAQ) has reviewed a Part 70 Operating Permit Renewal application from Nishikawa Cooper, LLC relating to the operation of an extruded rubber seals manufacturing source. On July 16, 2010, Nishikawa Cooper, LLC submitted an application to the OAQ requesting to renew its operating permit. Nishikawa Cooper, LLC was issued its first Part 70 Operating Permit Renewal No. 087-21424-00031 on April 17, 2006.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units:

- (a) CV Line 5, identified as CV-5, consisting of the following equipment:
 - (1) Two (2) extruders, identified as CV-5Ex, constructed in 1989, with a combined capacity of 400 pounds of rubber per hour, equipped with strip feeders, and two (2) dusters controlled by one (1) dust collector (DC-2) vented internally, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber and coating curing oven, identified as CV-5C, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-5, S-1.
 - (3) Two (2) exhaust hoods, identified as CV-5EH1 and CV-5EH2, exhausting to stacks CV-5, S-2, and CV-5, S-3, respectively.
 - (4) One (1) Line 5 spray booth coating extruded rubber parts, identified as emission unit CV-5SB, constructed in 2000, equipped with six (6) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, using dry filters as control, and exhausting to one (1) stack identified as CV-5, S-4, maximum capacity: 7.93 pounds of waterborne urethane coating per hour.

- (b) CV Line 6, identified as CV-6, consisting of the following equipment:
 - (1) One (1) extruder, identified as CV-6Ex, constructed in 1989, with a capacity of 400 pounds of rubber per hour, equipped with strip feeders, and two (2) dusters controlled by one (1) dust collector (DC-2) vented internally, and exhausting to general ventilation.
 - (2) One (1) microwave curing oven, identified as CV-6C2, and exhausting to CV-6, S-2.
 - (3) One (1) natural gas-fired rubber and coating curing oven, identified as CV-6C1, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-6, S-1.
 - (4) Two (2) exhaust hoods, identified as CV-6EH1 and CV-6EH2, CV-6EH1 exhausting to stack CV-5, S-2, and CV-6EH2, exhausting to stacks CV-6, S-2, and CV-5, S-3.

- (5) One (1) Line 6 spray booth, identified as CV-6SB, constructed in 2000, equipped with six (6) airless high-volume low-pressure (HVLP) guns coating extruded rubber parts, using dry filters as control, and exhausting to one (1) stack identified as CV-6, S-3, maximum capacity: 7.93 pounds of waterborne urethane coating per hour.
- (c) CV Line 7, identified as CV-7, consisting of the following equipment:
- (1) Three (3) extruders, identified as CV-7Ex, constructed in 1991, with a combined capacity of 600 of rubber pounds per hour, equipped with one (1) duster, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber and coating curing oven, identified as CV-C, with a heat input capacity of 1.59 MMBtu/hr, exhausting to stack CV-7, S-1.
 - (3) One (1) exhaust hood, identified as CV-7EH, exhausting to stack CV-6, S-2.
 - (4) One (1) Line 7 waterborne urethane coating booth coating extruded rubber parts, identified as CV-7SB, constructed in 2001, with a capacity of 1.36 gallons of waterborne coating per hour, equipped with spray guns and dry filters, and exhausting to stack CV-7, S-2.
- (d) CV Line 8, identified as CV-8, consisting of the following equipment:
- (1) Four (4) extruders, identified as CV-8Ex, constructed in 1995, with a combined capacity of 400 pounds of rubber per hour, equipped with four (4) strip feeders, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber vulcanizing oven, identified as CV-8C1, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stacks CV-8, S-1, CV-8, S-2, CV-8, S-3.
 - (3) Two (2) exhaust hoods, identified as CV-8EH1 and CV-8EH2, both exhausting to stack CV-8, S-4.
 - (4) One (1) natural gas fired coating curing oven, identified as CV-8C2, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stack CV-8, S-4.
 - (5) One (1) urethane application spray booth, identified as CV-8SB, constructed in 1997, equipped with six (6) spray guns coating extruded rubber parts and one (1) blown air dryer, with a capacity of 10 grams of coating per minute per gun, and exhausting to stack CV-8, S-5.
- (e) CV Line 9, identified as CV-9, consisting of the following equipment:
- (1) Two (2) extruders, identified as CV-9Ex, constructed in 1995, with a combined capacity of 400 pounds of rubber per hour, equipped with, two (2) feed hoppers, and one (1) duster controlled by one (1) dust collector (DC-3) vented internally, and exhausting to general ventilation.
 - (2) One (1) natural gas fired rubber curing oven, identified as CV-9C1, with a maximum capacity of 1.59 MMBtu/hr, and exhausting to stack CV-9, S-1.
 - (3) One (1) urethane application line, identified as CV-9Ex, constructed in 1996, equipped with six (6) spray guns coating extruded rubber parts and one (1) blown air dryer, with a capacity of 10 grams of coating per minute per gun, and exhausting to stack CV-9, S-5.

- (4) One (1) natural gas fired coating curing oven with two (2) heat exchangers, identified as CV-9C2, with a maximum capacity of 1.59 MMBt/hr, and exhausting to stacks CV-9, S-2 and CV-9, S-3.
- (5) One (1) exhaust hood, identified as CV-9EH, and exhausting to stack CV-9, S-4.
- (f) CV Line 10, identified as CV-10, consisting of the following equipment:
 - (1) Three (3) extruders, identified as CV-10Ex, with a combined capacity of 750 pounds of rubber per hour, constructed in 2004, and exhausting to general ventilation.
 - (2) Two (2) natural gas-fired microwave curing ovens, identified as CV-10C1, with a heat input capacity of 0.15 MMBtu/hr each, and exhausting to stack CV-10, S-1.
 - (3) One (1) natural gas-fired rubber curing oven, identified as CV-10C2, consisting of four (4) burners each with a heat input capacity of 0.102 MMBtu/hr, and exhausting to stack CV-10, S-2.
 - (4) Six (6) electric heaters, with a capacity of 3 kilowatt hours, each.
 - (5) One (1) exhaust hood, identified as CV-10EH, and exhausting to stack CV-10, S-3.
 - (6) One (1) spray booth, identified as CV-10SB1, constructed in 2004, equipped with four (4) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-10, S-5.
 - (7) One (1) spray booth, identified as CV-10SB2, constructed in 2004, equipped with four (4) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-10, S-6.
 - (8) Three (3) infrared coating curing ovens, identified as CV-10C3, CV-10C4, and CV-10C5, the first two exhausting to general ventilation, the third exhausting to stack CV-10, S-4.
 - (9) One (1) plasma arc generator, consisting of one (1) electric generator, with a capacity of 1.2 kilowatt hours, exhausting to stack CV-10, S-1.
- (g) CV Line 11, identified as CV-11, consisting of the following equipment:
 - (1) Four (4) extruders, identified as CV-11Ex, constructed in 1987 and modified in 2008, with a combined capacity of 200 pounds of rubber per hour, equipped with four (4) strip feeders, and exhausting to general ventilation.
 - (2) One (1) electric microwave rubber curing oven, identified as CV-11C1, and exhausting to stack CV-11, S-1.
 - (3) One (1) natural gas rubber curing oven, identified as CV-11C2, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
 - (4) Two (2) exhaust hoods, identified as CV-11EH1 and CV-11EH2, and exhausting to stacks CV-11, S-2 and CV-11, S-1, respectively.
 - (5) One (1) spray booth, identified as CV-11Ex, constructed in 2000 and modified in 2008, equipped with four (4) airless high-volume low-pressure (HVLP) guns

coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, with dry filters for particulate control, exhausting to stack CV-11 S-3.

- (6) One (1) natural gas coating curing oven, identified as CV-11C3, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stacks CV-11, S-1 and CV-11, S-2.
- (i) SDM Line 1 (EA), identified as SDM-1, consisting of the following equipment:
- (1) One (1) core metal heater, identified as SDM-1MH, with two (2) natural gas-fired burners with a maximum heat input rate of 0.375 MMBtu/hr.
 - (2) Four (4) extruders, identified as SDM-1Ex, constructed in 2004, with a combined capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave curing ovens, identified as SDM-1C1 and SDM-1C2, with a maximum heat input rate 0.143 MMBtu/hr each, exhausting to stack SDM-1, S-1.
 - (4) One (1) natural gas-fired rubber curing oven, identified as SDM-C3, with two (2) burners with a maximum heat input rate of 0.850 MMBtu/hr each, exhausting to stack SDM-1, S-2.
 - (5) One (1) electric plasma arc generator, identified as SDM-1PI, exhausting to stack SDM-1, S-3.
 - (6) One (1) spray booth, identified as SDM-1SB, constructed in 2004, equipped with six (6) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters to control PM overspray emissions, and exhausting to stack SDM-1, S-5.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-1, C4, with two burners rated at 0.340 MMBtu/hr each, and exhausting to stack SDM-1, S-4.
- (k) SDM Line 3 (EC), identified as SDM-3, consisting of the following equipment:
- (1) One (1) natural gas-fired core metal heater, identified as SDM-3MH, with a heat input capacity of 1.19 MMBtu/hr, and exhausting to general ventilation.
 - (2) Three (3) extruders, identified as SDM-3Ex, constructed in 1994, with a combined capacity of 400 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) One (1) natural gas-fired bead type rubber curing over and deodorizing furnace, identified as SDM-3C1, with a heat input capacity of 1.99 MMBtu/hr, and exhausting to stacks SDM, S-2, SDM-3, S-3 and SDM-3, S-4.
 - (4) One (1) bead recovery/dryer system, identified as SDM-3, exhausting to stack SDM-3, S-5.
 - (5) One (1) SDM EC urethane application spray booth, identified as SDM-3SB, constructed in 1996, equipped with three (3) spray guns coating extruded rubber parts, with a capacity of 10 grams of coating per minute per gun, exhausting to stack SDM-3, S-7.
 - (6) One (1) natural gas-fired curing oven, identified as SDM-3C2, with a heat input capacity of 1.0 MMBtu/hr, and exhausting to stack SDM-3, S-6.

- (l) SDM Line 4 (ED), identified as SDM-4, consisting of the following equipment:
- (1) One (1) core metal heater, identified as SDM-4MH, with two (2) natural gas-fired burners, each has a heat input capacity of 0.375 million British thermal unit per hour, and exhausting to stack SDM-4, S-1.
 - (2) Four (4) extruders, identified as SDM-4Ex, constructed in 2002, with a maximum capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave rubber curing ovens, identified as SDM-4C1, each with a heat input capacity of 0.143 MMBtu/hr, and both exhausting to stack SDM-4, S-2.
 - (4) One (1) natural gas-fired curing oven, identified as SDM-4C2, with two (2) burners, each with a heat input capacity of 0.850 MMBtu/hr, and exhausting to stack SDM-4, S-3.
 - (5) One (1) electric plasma arc unit, identified as SDM-4PI, exhausting to stack SDM-4, S-4.
 - (6) One (1) spray booth, identified as SDM-4SB, constructed in 2002, equipped with six (6) High-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters to control PM overspray emissions, exhausting to stack SDM-4, S-6.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-4C3, with two burners each having a heat input capacity of 0.34 MMBtu/hr, and exhausting to stack SDM-4, S-5.
- (m) SDM Line 5 (EE), identified as SDM-5, consisting of the following equipment:
- (1) One (1) core metal heater, identified as SDM-5MH, with (2) natural gas-fired burners with heat input capacity of 0.375 MMBtu/hr each.
 - (2) Four (4) extruders, identified as SDM-5Ex, constructed in 2002, with a combined capacity of 1289 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) Two (2) natural gas-fired microwave curing ovens, identified as SDM-5C1, with a heat input capacity of 0.143 MMBtu/hr each, exhausting to stack SDM-5, S-1.
 - (4) One (1) natural gas-fired rubber curing ovens, identified as SDM-5C2, with two (2) burners, each having a heat input capacity of 0.850 MMBtu/hr, exhausting to stack SDM-5, S-2.
 - (5) One (1) electric plasma arc unit, identified as SDM-5PI, and exhausting to stack SDM-5, S-3.
 - (6) One (1) spray line, identified as SDM-5SB, constructed in 2002, equipped with six (6) high-volume low-pressure (HVLP) spray guns coating extruded rubber parts, using dry filters as controls, with a capacity of 10 grams per minute of coating per gun, and exhausting to stack SDM-5, S-5.
 - (7) One (1) natural gas-fired coating cure oven, identified as SDM-5C3, with two (2) 0.340 MMBtu/hr burners, exhausting to stacks SDM-5, S-4.

- (n) L-Coat Extrusion Line, identified as LC-1, consisting of the following equipment:
 - (1) Four (4) plastic extruders identified as LC-1Ex, constructed in 2006, with a capacity of 19.0 pounds per hour each, and exhausting to general ventilation.
 - (2) Three (3) rubber extruders, identified as LC-1Ex, constructed in 2006, with a capacity of 447.0 pounds per hour each, and exhausting to general ventilation.
 - (3) One (1) natural gas curing oven, identified as LC-1C1, exhausting to stacks LC, S-1, LC, S-2, and LC, S-3, consisting of the following burners:
 - (A) Four (4) natural gas-fired burners, constructed in 2006, with a heat input capacity of 0.782 MMBtu/hr each.
 - (B) Five (5) natural gas-fired burners, constructed in 2007, with a heat input capacity of 0.782 MMBtu/hr each.
 - (4) Three (3) exhaust hoods, identified as LC-1EH1, LC-1EH2, and LC-1EH3, and exhausting to LC, S-4, LC, S-5, and LC, S-6, respectively.
 - (5) One (1) plasma arc unit, identified as LC-1PI, exhausting to stack LC, S-7.
 - (6) One (1) L-Coat Glassline Spray Booth, identified as LC-1SB1, constructed in 2006, utilizing seven (7) high-volume low-pressure (HVLP) spray guns with a maximum capacity of 1.0 unit per hour and particulate emissions controlled by dry filters, and exhausting to stack LC, S-9.
 - (7) One (1) L-Coat Glassline Spray Booth, identified as LC-1SB2, constructed in 2007, utilizing seven (7) high-volume low-pressure (HVLP) spray guns with a maximum capacity of 1.0 unit per hour and particulate emissions controlled by dry filters, and exhausting to one (1) stack LC, S-10.
 - (8) One (1) natural gas coating curing oven, identified as LC-1C2, consisting of six (6) natural gas-fired burners with a maximum heat input capacity of 0.086 MMBtu/hr each, and exhausting to stack LC, S-8.
- (o) One (1) mixing department, identified as Mix-1, constructed in 1987, equipped with one (1) carbon black weigh station and one (1) raw chemical weigh station, both exhausting to a small baghouse identified as Mix-1, S-1, with a capacity of 416.7 pounds of rubber per hour, 3.2 pounds of talc per hour, and 83.3 pounds of carbon black per hour.
- (p) One (1) spray coating booth coating extruded rubber parts, identified as emission unit L42C Nissan, constructed in 2008, equipped with one (1) spray gun, using dry filters as particulate control, with a capacity of ten (10) grams per hour, and exhausting to stack LC-42C, S-1.
- (q) One (1) VN surface coating line, identified as VN-1SB, constructed in 2004, including:
 - (1) One (1) surface coating booth, equipped with one (1) high-volume low-pressure (HVLP) spray gun coating extruded rubber parts, applying surface coatings to rubber parts at a maximum design rate of 0.15 gallons per hour, with particulate emissions controlled by a dry filter system, with emissions exhausted through Stack VN-1, S-1.
 - (2) One (1) electric curing oven, identified as VN-1C.
- (r) One (1) off line finishing spray booth, identified as F-1, constructed in 2007 and modified in 2009, with a capacity of 10 grams of coating per minute, exhausting at stack F-1, S-1 with an associated primer station where primer is applied by hand.

- (s) One (1) off line finishing spray booth, identified as F-2, constructed in 2007, with a capacity of 10 grams of coating per minute, exhausting at stack F-2, S-1.
- (t) One (1) off line finishing spray booth, identified as F-3, constructed in 2007, with a capacity of 10 grams of coating per minute, exhausting at stack F-3, S-1.
- (u) One (1) off line finishing spray booth, identified as F-4, approved for construction in 2009, with a capacity of 10 grams of coating per minute, exhausting to stack F-4, S-1.

Emission Units and Pollution Control Equipment Constructed and/or Operated without a Permit
--

There are no unpermitted emission units operating at this source during this review process.

Emission Units and Pollution Control Equipment Removed From the Source

The following emission units have been removed from the source:

- (a) SDM Line 2 (EB), identified as SDM-2, consisting of the following equipment:
 - (1) One (1) natural gas-fired core metal heater, identified as SDM-2MH, with a heat input capacity of 1.19 MMBtu/hr, and exhausting to stack SDM-2, S-1.
 - (2) Two (2) extruders (one (1) sponge and one (1) dense), identified as SDM-2Ex, constructed in 1989, with a combined capacity of 400 pounds of rubber per hour, and exhausting to general ventilation.
 - (3) One (1) natural gas-fired bead type rubber curing oven and deodorizing furnace, identified as SDM-2C1, with a heat input capacity of 1.99 MMBtu/hr, and exhausting to stacks SDM-2, S-2 and SDM-2, S-3.
 - (4) One (1) bead recovery/dryer system, identified as SDM-2RD, exhausting to stack SDM-2, S-4.
 - (5) One (1) spray booth, identified as SDM-2SB, constructed in 1994, equipped with five (5) spray guns and drip applicators coating extruded rubber parts, with a maximum capacity of 0.00086 gallons per minute and 4080 meters per hour for the drip and wipe and 10 grams of coating per minute per gun for the spray application, and exhausting to stack SDM-2, S-7.
 - (6) One (1) natural gas-fired drying oven (2 sections) rated at 2.0 million British thermal units per hour, and exhausting at stacks SDM-2, S-5 and SDM-2, S-6.
- (b) CV Line 1, identified as CV-1, consisting of the following equipment:
 - (1) One (1) extruder, identified as CV-1Ex, constructed in 1987, with a capacity of 200 pounds of rubber per hour, equipped with extruders, strip feeders, and one (1) duster controlled by one (1) dust collector (DC-1) vented internally, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired rubber and coating curing oven, identified as CV-1C, with a heat input capacity of 1.59 MMBtu/hr, and exhausting to stack CV-1, S-1.
 - (3) One (1) natural gas-fired pre-heater, identified as CV-1Pr, with a heat input capacity of 0.298 MMBtu/hr, and exhausting to stack CV-1, S-2.
 - (4) One (1) exhaust hood, exhausting to stack CV-1, S-2.

- (5) One (1) spray booth, identified as CV-1SB, constructed in 2000, equipped with three (3) airless high-volume low-pressure (HVL) guns coating extruded rubber parts, using dry filters as particulate control, and exhausting to stack identified as CV-1 S-3, maximum capacity: 3.97 pounds of waterborne urethane coating per hour.
- (c) CV Line 4, identified as CV-4, consisting of the following equipment:
- (1) Two (2) extruders, identified as CV-4Ex, constructed in 1988, with a combined capacity of 200 pounds of rubber per hour, equipped with strip feeders, and one (1) duster controlled by one (1) dust collector (DC-1) vented internally, curing ovens, and exhausting to general ventilation.
 - (2) One (1) natural gas-fired pre-heater, identified as CV-4Pr, with a heat input capacity of 0.298 MMBtu/hr, and exhausting to stack CV-1, S-2.
 - (3) One (1) exhaust hood, exhausting to stack CV-1, S-2.
 - (4) One (1) natural gas-fired rubber and coating curing oven, identified as CV-4C, with a heat input capacity of 1.59 MMBtu/hr, and exhausting to stack CV-4, S-1.
 - (5) One (1) Line 4 waterborne urethane coating booth coating extruded rubber parts, identified as CV-4SB, constructed in 2001, with a capacity of 0.45 gallons per hour, equipped with dry filters and exhausting to stack CV-4, S-2.

The source did not install the following permitted emission units:

- (a) CV Line 12, identified as CV-12, consisting of the following equipment:
- (1) One (1) extrusion, identified as CV-12Ex, approved for construction in 2008, with a capacity of 200 pounds of rubber per hour, and exhausting to general ventilation.
 - (2) One (1) electric microwave oven, identified as CV-12C1.
 - (3) One (1) natural gas rubber curing oven, identified as CV-12C2, approved for construction in 2008, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stack CV-12, S-1.
 - (4) One (1) natural gas coating curing oven, identified as CV-12C3, approved for construction in 2008, with a heat input capacity of 0.5 MMBtu/hr, and exhausting to stack CV-12, S-2.

Insignificant Activities

The source also consists of the following insignificant activities:

- (a) Dango Mixing Mills B and F, each with a dispersion system, using particulate filters as control [326 IAC 6-3]
- (b) Color Mixing Mill [326 IAC 6-3]
- (c) Mold Tech Repair Sandblast Unit [326 IAC 6-3]
- (d) Mold Tech Repair Weld and Metalworking Equipment [326 IAC 6-3]
- (e) Dango Barwell Extruders [326 IAC 6-3]
- (f) Polymer Block Cutting Station [326 IAC 6-3]

- (g) Scrap Cardboard Bailing Unit [326 IAC 6-3]
- (h) Weld Shop Equipment [326 IAC 6-3]
- (i) Silicone Coating Mixing Station [326 IAC 6-3]
- (j) Die Room Metalworking Equipment [326 IAC 6-3]
- (k) SDM Mezzanine Units [326 IAC 6-3]
- (l) Barwell Warm-Up Mill [326 IAC 6-3]
- (m) One (1) emergency generator rated at 54 HP, burning natural gas, installed in December 2008 and manufactured in 2008. This emergency generator is a new affected source under 40 CFR 63, Subpart ZZZZ. [40 CFR 63, Subpart ZZZZ]

Existing Approvals

Since the issuance of the Part 70 Operating Permit (1st Renewal) T087-21424-00031 on April 17, 2006, the source has constructed or has been operating under the following additional approvals:

- (a) Significant Permit Modification No.: 087-23608-00031 issued on December 22, 2006.
- (b) Administrative Amendment No.: 087-25082-00031 issued on September 10, 2007.
- (c) Administrative Amendment No.: 087-26801-00031 issued on September 29, 2008.
- (d) Administrative Amendment No.: 087-27406-00031 issued on April 16, 2009.
- (e) Administrative Amendment No.: 087-27812-00031 issued on May 4, 2009.
- (f) Administrative Amendment No.: 087-28586-00031 issued on October 26, 2009.

All terms and conditions of previous permits issued pursuant to permitting programs approved into the State Implementation Plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

Enforcement Issue

There are no enforcement actions pending.

Emission Calculations

See Appendix A of this document for detailed emission calculations.

County Attainment Status

The source is located in LaGrange County.

Pollutant	Designation
SO ₂	Better than national standards.
CO	Unclassifiable or attainment effective November 15, 1990.
O ₃	Unclassifiable or attainment effective June 15, 2004, for the 8-hour ozone standard. ¹

Pollutant	Designation
PM ₁₀	Unclassifiable effective November 15, 1990.
NO ₂	Cannot be classified or better than national standards.
Pb	Not designated.

¹Unclassifiable or attainment effective October 18, 2000, for the 1-hour ozone standard which was revoked effective June 15, 2005.
 Unclassifiable or attainment effective April 5, 2005, for PM_{2.5}.

(Air Pollution Control Board; 326 IAC 1-4-45; filed Dec 26, 2007, 1:43 p.m.: 20080123-IR-326070308FRA)

- (a) **Ozone Standards**
 Volatile organic compounds (VOC) and Nitrogen Oxides (NO_x) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to ozone. LaGrange County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (b) **PM_{2.5}**
 LaGrange County has been classified as attainment for PM_{2.5}. On May 8, 2008, U.S. EPA promulgated the requirements for Prevention of Significant Deterioration (PSD) for PM_{2.5} emissions. These rules became effective on July 15, 2008. Indiana has three years from the publication of these rules to revise its PSD rules, 326 IAC 2-2, to include those requirements. The May 8, 2008 rule revisions require IDEM to regulate PM₁₀ emissions as a surrogate for PM_{2.5} emissions until 326 IAC 2-2 is revised.
- (c) **Other Criteria Pollutants**
 LaGrange County has been classified as attainment or unclassifiable in Indiana for all other criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2, 326 IAC 2-3, or 326 IAC 2-7, and there is no applicable New Source Performance Standard that was in effect on August 7, 1980, fugitive emissions are not counted toward the determination of PSD, Emission Offset, and Part 70 Permit applicability.

Unrestricted Potential Emissions

This table reflects the unrestricted potential emissions of the source.

Pollutant	Potential To Emit (tons/year)
PM	60.45
PM10	61.58
SO ₂	0.12
VOC	319.3
CO	16.55
NO _x	19.71

Notes:

- (1) Includes one (1) spray coating line (X025), four (4) spray booths (Lines 2, 3, 5 and 6), one (1) silicone application line (X019), two (2) CV finishing touchup stations (X004), three (3) urethane application lines (X020, X021, X023), four (4) waterborne urethane coating booths (Lines 4 and 7, Small Robot #1 and Small Robot #2), one (1) surface coating line (X003), two (2) spray lines (X034 and X036), one (1) spray line (X037), and two (2) spray lines (X039 and X040).
 - (2) In order to render the requirements of 326 IAC 8-1-6 (New Facilities: General Reduction Requirements) not applicable, the VOC delivered to one (1) spray coating line (X025) is limited to less than 25 tons per 12 consecutive months. In order to render the requirements of 326 IAC 2-4.1-1 (New Source Toxics Control) not applicable, the individual HAP and combined HAPs delivered to one (1) spray coating line (X025) is limited to less than 10 and 25 tons per 12 consecutive months, respectively.
 - (3) Includes CV extrusion lines (X005 through X016, X033, X035 and X038), hot air curing lines (X005 through X011, X014 through X016, X035 and X038) and autoclave curing lines (X012 and X013).
 - (4) Includes seven (7) deodorizing furnaces (1.59 MMBtu/hr each), two (2) vulcanizing ovens (1.59 MMBtu/hr each), six (6) curing ovens (0.143 MMBtu/hr each), four (4) hot air rubber curing ovens (0.85 MMBtu/hr each), four (4) wire metal system burners (0.375 MMBtu/hr each), two (2) deodorizing furnaces (1.99 MMBtu/hr each), two (2) core metal heaters (1.19 MMBtu/hr each), one (1) drying oven (2 MMBtu/hr), one (1) curing oven (1.0 MMBtu/hr), one (1) preheat oven (1.5 MMBtu/hr), one (1) curing oven (2.0 MMBtu/hr), one (1) make-up air heater (1.5 MMBtu/hr), five (5) coating cure ovens (0.34 MMBtu/hr each), two (2) coating cure ovens (0.25 MMBtu/hr each) and four (4) hot air rubber curing ovens (0.4 MMBtu/hr each). All combustion devices fire natural gas.
 - (5) In order to render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable, the VOC delivered to spray coating lines, extruding and curing, mixing and milling, combustion devices and insignificant devices is limited to less than 148 tons per year, 96.47 tons per year, 1.90 tons per year, 1.12 tons per year and 2.0 tons per year, respectively.
- (a) This existing stationary source is not major for PSD because the emissions of each regulated pollutant are less than two hundred fifty (<250) tons per year, and it is not in one of the twenty-eight (28) listed source categories.

Federal Rule Applicability

- (a) This source does not involve a pollutant-specific emissions unit as defined in 40 CFR 64.1 for VOC, PM or HAPs:
- (1) with the potential to emit before controls equal to or greater than the major source threshold for VOC or HAPs,
 - (2) that is subject to an emission limitation or standard for VOC or HAPs, and
 - (3) uses a control device as defined in 40 CFR 64.1 to comply with that emission limitation or standard.

Therefore, the requirements of 40 CFR Part 64, Compliance Assurance Monitoring, are not applicable to this modification.

- (b) Pursuant to 40 CFR 60.451, large appliance surface coating line means that a portion of a large appliance assembly plant is engaged in the application and curing of organic surface coatings on large appliance parts or products. Large appliance part means any organic surface-coated metal lid, door, casing, panel, or other interior or exterior metal part or accessory that is assembled to form any large appliance product like organic surface-coated metal range, oven, microwave oven, refrigerator, freezer, washer, dryer, dishwasher, water heater, or trash compactor manufactured for household, commercial, or recreational use. The requirements of the New Source Performance Standard, 326 IAC 12 (40 CFR 60.450), Subpart SS, *Standards of Performance for Industrial Surface Coating: Large Appliances* apply to each surface coating operation in a large appliance surface coating line that commenced construction, modification, or reconstruction after December 24, 1980. The source does not have any large appliance surface coating line and hence the requirements of 40 CFR 60.450, Subpart SS are not included in the permit.
- (c) The requirements of the New Source Performance Standard, 326 IAC 12 (40 CFR 60.720, Subpart TTT), *Standards of Performance for Industrial Surface Coating: Surface Coating of Plastic Parts for Business Machines*, are not included in the permit for the surface coating operations because the Permittee does not apply prime coats, color

coats, texture coats, or touch-up coats to plastic parts for use in the manufacture of business machines.

- (d) The requirements of New Source Performance Standard, (40 CFR 60.740, Subpart VVV) *Standards of Performance for Polymeric Coating of Supporting Substrates* are not included in the permit since the source does not have on-site any coating operation and coating mix preparation equipment used to prepare coatings for the polymeric coating of supporting substrates.
- (e) The emergency generator (insignificant activity), installed in 2008, located at a major source for HAPs, is subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP), 326 IAC 20 (40 CFR 63, Subpart ZZZZ) for Stationary Reciprocating Internal Combustion Engines. Pursuant to 40 CFR 63.6590(c), the 54 HP unit must meet the requirements of 40 CFR 60, Subpart JJJJ, for spark ignition engines, and no other requirements under the NESHAP, Subpart ZZZZ, apply.

However, the emergency generator, installed after June 12, 2006, and manufactured before January 1, 2009, and rated at greater than 25 HP, is not subject to any requirements under 40 CFR 60, Subpart JJJJ. Therefore, the requirements of 40 CFR 60, Subpart JJJJ, are not included in this permit.

The emergency generator is subject to the following requirements under 40 CFR 63, Subpart ZZZZ:

- (1) 40 CFR 63.6580
 - (2) 40 CFR 63.6585
 - (3) 40 CFR 63.6590(c)
- (f) The requirements of the National Emission Standards for Hazardous Air Pollutants, 326 IAC 20 (40 CFR Part 63.4480, Subpart PPPP) are not included in the permit because this source applies surface coating to extruded rubber pieces and does not apply surface coating to plastic parts and products as defined in 40 CFR 63.4581.
 - (g) The requirements of the National Emission Standards for Hazardous Air Pollutants, 326 IAC 20 (40 CFR, Subpart MMMM) for miscellaneous metal parts coating operations is not included in this permit because this source does not apply surface coating to any metal parts or products.

State Rule Applicability - Entire Source

326 IAC 1-5-2 (Emergency Reduction Plans)

The source submitted an Emergency Reduction Plan (ERP) on November 15, 1996. The ERP has been verified to fulfill the requirements of 326 IAC 1-5-2 (Emergency Reduction Plans).

326 IAC 2-2 (Prevention of Significant Deterioration)

This source, which is not one of the 28 listed source categories, is an existing minor stationary source because the potential to emit VOC from the source has always been restricted to less than 250 tons per year. All surface coating lines and extrusion lines constructed after August 7, 1980 have potential to emit of each attainment criteria pollutant less than major source thresholds. Therefore, the PSD requirements will continue to not apply to this source.

326 IAC 2-6 (Emission Reporting)

Since this source is required to have an operating permit under 326 IAC 2-7, Part 70 Permit Program, this source is subject to 326 IAC 2-6 (Emission Reporting). This source is not permitted to emit more than 2,500 tons per year of CO, NOx, or SO2, or more than 250 tons per year of PM-10 or VOC. Therefore, in accordance with the compliance schedule in 326 IAC 2-6-3, an emission statement must be submitted triennially by July 1 beginning in 2007 and every 3 years after. The emission statement shall contain, at a minimum, the information specified in 326 IAC 2-6-4.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in the permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP))

Pursuant to 326 IAC 2-4.1-1 (New Source Toxics Control), any new process or production unit, which in and of itself emits or has the potential to emit (PTE) 10 tons per year of any HAP or 25 tons per year of the combination of HAPs, and is constructed or reconstructed after July 27, 1997, must be controlled using technologies consistent with Maximum Achievable Control Technology (MACT).

SDM EB silicone application line, identified as emission unit X019, has Xylene emissions greater than ten (10) tons per year. However, this line was constructed before the July 27, 1997 applicability date.

The potential to emit individual HAP and combination of HAPs from the following extrusion lines, which are constructed or reconstructed after July 27, 1997, is less than 10 tons per year and 25 tons per year, respectively:

1. SDM EA Extrusion Line, identified as X014;
2. SDM ED Extrusion Line, identified as X033;
3. SDM EE Extrusion Line, identified as X035; and
4. CV Line 10 Extrusion Line, identified as X038.

No other process or production unit, which is constructed or reconstructed after July 27, 1997, has the potential to emit (PTE) 10 tons per year of any HAP or 25 tons per year of the combination of HAPs. Therefore, 326 IAC 2-4.1 does not apply.

State Rule Applicability – Individual Facilities

326 IAC 4-2-1 (Incinerators)

The requirements of 326 IAC 4-2-1 apply to all incinerators that emit regulated pollutants. Pursuant to 326 IAC 1-2-34, an incinerator is defined as an engineered apparatus that burns waste substances with controls on combustion factors including, but not limited to, temperature, retention time, and air. No combustion device at the source burns waste substances with controls on combustion factors. Therefore, 326 IAC 4-2-1 does not apply.

326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes) for surface coating
Pursuant to 326 IAC 6-3-2(d)(1), particulate from the surface coating operations at the following surface coating lines shall be controlled by a dry particulate filter, and the Permittee shall operate the control device in accordance with manufacturer's specifications:

- (a) One (1) spray coating line (X025);
- (b) One (1) Line 2 spray booth (X029);
- (c) One (1) Line 3 spray booth (X030);
- (d) One (1) Line 5 spray booth (X031);

- (e) One (1) Line 6 spray booth (X032);
- (f) Two (2) CV finishing touchup stations (X004);
- (g) One (1) SDM EB silicone application line (X019);
- (h) One (1) urethane application line (CV Line 9, X020);
- (i) One (1) SDM EC urethane application line (X021);
- (j) One (1) urethane application line (X023);
- (k) One (1) Line 4 waterborne urethane coating booth (X026);
- (l) One (1) Line 7 waterborne urethane coating booth (X027)
- (m) One (1) waterborne urethane coating booth (Small Robot #1);
- (n) One (1) spray line (X034);
- (o) One (1) surface coating line (X003);
- (p) One (1) spray line (X036);
- (q) One (1) spray line (X037);
- (r) One (1) spray line (X039); and
- (s) One (1) spray line (X040).

326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)

The particulate from the facilities at this source shall be limited as specified in the following table:

Emission Unit	Process Weight Rate (tons per hour)	Allowable PM Emission Rate [326 IAC 6-3-2] (pounds per hour)
CV-11Ex	0.1	0.877
CV-5Ex	0.2	1.39
CV-6Ex	0.2	1.39
CV-7Ex	0.3	1.83
CV-8Ex	0.2	1.39
CV-9Ex	0.2	1.39
SDM-1Ex	0.65	3.07
SDM-2Ex	0.2	1.39
SDM-3Ex	0.2	1.39
SDM-4Ex	0.65	3.07
SDM-5Ex	0.65	3.07

Emission Unit	Process Weight Rate (tons per hour)	Allowable PM Emission Rate [326 IAC 6-3-2] (pounds per hour)
CV-10Ex	0.375	2.13

The allowable particulate matter (PM) emission rates from the above facilities were calculated by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

All particulate control equipment shall be in operation at all times when the operations are performed to comply with this limit.

The particulate emissions from the following insignificant activities are also restricted by the above formula:

- (a) Pellet Lines Mixing Mills A, C, D and E [326 IAC 6-3]
- (b) Pelletizers [326 IAC 6-3]
- (c) Dango Mixing Mills B and F, each with a dispersion system, using particulate filters as control [326 IAC 6-3]
- (d) Color Mixing Mill [326 IAC 6-3]
- (f) Mold Tech Repair Sandblast Unit [326 IAC 6-3]
- (g) Mold Tech Repair Weld and Metalworking Equipment [326 IAC 6-3]
- (h) Dango Barwell Extruders [326 IAC 6-3]
- (i) Polymer Block Cutting Station [326 IAC 6-3]
- (j) Scrap Cardboard Bailing Unit [326 IAC 6-3]
- (k) Weld Shop Equipment [326 IAC 6-3]
- (l) Silicone Coating Mixing Station [326 IAC 6-3]
- (m) Die Room Metalworking Equipment [326 IAC 6-3]
- (n) SDM Mezzanine Units [326 IAC 6-3]
- (o) Barwell Warm-Up Mill [326 IAC 6-3]

The potential to emit before controls from all insignificant activities is below the significant unit emission thresholds.

326 IAC 8-1-6 (General Reduction Requirements)

This rule applies to facilities located anywhere in the state that were constructed on or after January 1, 1980, which have potential volatile organic compounds (VOC) emissions of 25 tons per year or more, and which are not otherwise regulated by another provision of Article 8.

The total VOC usage at the sourcewide surface coating operations is limited to no more than 148 tons per consecutive twelve (12) month period with compliance determined at the end of each month. Pursuant to Part 70 No. 087-7182-00031, issued on April 12, 2001 and Part 70 SPM No. 087-19170-00031, issued on September 9, 2004, this sourcewide surface coating VOC usage limit with the following conditions is determined to be the best available control technology (BACT) for the silicone application line (X019):

- (1) All coating, urethane and silicone application devices at these facilities or shall be drip; high volume, low pressure (HVLP) spray guns; or a coating application device at least as efficient. HVLP spray is the technology used to apply coating to substrate by means of

coating application equipment which operates between one-tenth (0.1) and ten (10) pounds per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

- (2) All VOC containing containers shall be kept covered when not in use.

The potential to emit VOC from all of the following extrusion lines, which are constructed or reconstructed on or after January 1, 1980, is less than 25 tons per year:

1. CV Line 2 Extrusion Line, identified as X006;
2. CV Line 3 Extrusion Line, identified as X007;
3. CV Line 5 Extrusion Line, identified as X009;
4. CV Line 6 Extrusion Line, identified as X010;
5. CV Line 7 Extrusion Line, identified as X011;
6. CV Line 8 Extrusion Line, identified as X012;
7. CV Line 9 Extrusion Line, identified as X013;
8. SDM EA Extrusion Line, identified as X014; ;
9. SDM EC Extrusion Line, identified as X016;
10. SDM ED Extrusion Line, identified as X033;
11. SDM EE Extrusion Line, identified as X035; and
12. CV Line 10 Extrusion Line, identified as X038.

No other process or production unit constructed on or after January 1, 1980 has potential volatile organic compounds (VOC) emissions of 25 tons per year or more. Therefore, 326 IAC 8-1-6 (New Facilities: General Reduction Requirements) does not apply.

326 IAC 8-2-1 (Surface Coating Emission Limitations)

This source does not perform any operations of the types described in 326 IAC 8-2-2 through 8-2-13. Therefore, 326 IAC 8-2 does not apply.

Compliance Determination and Monitoring Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with all applicable state and federal rules on a continuous basis. All state and federal rules contain compliance provisions; however, these provisions do not always fulfill the requirement for a continuous demonstration. When this occurs, IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, Compliance Determination Requirements are included in the permit. The Compliance Determination Requirements in Section D of the permit are those conditions that are found directly within state and federal rules and the violation of which serves as grounds for enforcement action.

If the Compliance Determination Requirements are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance determination requirements applicable to this source are as follows:

- (a) IDEM may require compliance testing at any specific time to determine if the source is in compliance with an applicable limit or standard. The Permittee has demonstrated compliance through emission rate calculations with emission limits applicable to the facilities at this source. Therefore, no emissions testing is required in this Part 70 permit.

- (b) In order to comply with Condition D.3.1, the baghouse (Mix-1, S-1) for PM control shall be in operation and control emissions from the mixing department at all times that the mixing department is in operation.

The compliance monitoring requirements applicable to this source are as follows:

- (a) Weekly inspections shall be performed to verify the placement, integrity and particle loading of the filters controlling the surface coating operations CV-5SB, CV-6SB and CV-7SB at this source. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks, while the associated booths are in operation. If a condition exists which should result in a response step the Permittee shall take reasonable response. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take reasonable response steps shall be considered a deviation from this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Response to Excursions or Exceedances for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. If a condition exists which should result in a response step the Permittee shall take reasonable response. Section C – Response to Excursions or Exceedances contains the Permittee's obligation with regard to the reasonable response steps required by this condition. Failure to take reasonable response steps shall be considered a deviation from this permit.

Recommendation

The staff recommends to the Commissioner that the Part 70 Operating Permit Renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on July 16, 2010. Additional information was received on May 13, 2011.

Conclusion

The operation of this extruded rubber seals manufacturing source shall be subject to the conditions of the attached Part 70 Operating Permit Second Renewal No. 087-29472-00031.

IDEM Contact

- (a) Questions regarding this proposed permit can be directed to Madhurima D. Moulik at the Indiana Department Environmental Management, Office of Air Quality, Permits Branch, 100 North Senate Avenue, MC 61-53 IGCN 1003, Indianapolis, Indiana 46204-2251 or by telephone at (317) 233-0868 or toll free at 1-800-451-6027 extension 3-0868.
- (b) A copy of the findings is available on the Internet at: <http://www.in.gov/ai/appfiles/idem-caats/>
- (c) For additional information about air permits and how the public and interested parties can participate, refer to the IDEM's Guide for Citizen Participation and Permit Guide on the Internet at: www.idem.in.gov

Appendix A: Emission Calculations

Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Plt ID: 087-00031
Date: 8/25/2011

Uncontrolled Potential Emissions (tons/year)				
Emissions Generating Activity				
Pollutant	Surface Coating	Combustion	Rubber Parts Manufacturing (including extrusion lines)	TOTAL
PM	40.87	0.37	19.21	60.45
PM10	40.87	1.50	19.21	61.58
SO ₂	0.00	0.12	0.00	0.12
NO _x	0.00	19.71	0.00	19.71
VOC	211.01	1.08	107.20	319.30
CO	0.00	16.55	0.00	16.55
total HAPs	59.17	0.37	97.76	157.31
worst case single HAP	24.67 (Xylene)	0.32 (Hexane)	27.85 (Hexane)	28.17 (Hexane)
Total emissions based on rated capacity at 8,760 hours/year.				
Controlled Potential Emissions (tons/year)				
Emissions Generating Activity				
Pollutant	Surface Coating	Combustion	Rubber Parts Manufacturing (including extrusion lines)	TOTAL
PM	2.04	0.37	2.38	4.80
PM10	2.04	1.50	2.38	5.92
SO ₂	0.00	0.12	0.00	0.12
NO _x	0.00	19.71	0.00	19.71
VOC	148.00	1.08	98.37	247.45
CO	0.00	16.55	0.00	16.55
total HAPs	59.17	0.37	97.76	157.31
worst case single HAP	24.67 (Xylene)	0.32 (Hexane)	27.85 (Hexane)	28.17 (Hexane)
Total emissions based on rated capacity at 8,760 hours/year, after control.				
VOC emissions from extruding and curing and mixing and milling operations are limited to less than 96.47 TPY and 1.9 TPY, respectively.				

Appendix A: Emissions Calculations

Natural Gas Combustion Only
MM BTU/HR <100

Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Per ID: 087-00031
Date: 8/25/2011

Heat Input Capacity ⁽¹⁾ MMBtu/hr	Potential Throughput MMCF/yr
44.99	394.14

Emission Factor in lb/MMCF	Pollutant					
	PM*	PM10*	SO2	NOx	VOC	CO
	1.9	7.6	0.6	100.0	5.5	84.0
				**see below		
Potential Emission in tons/yr	0.374	1.498	0.118	19.71	1.084	16.55

*PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

**Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Note: (1) Combined heat input capacity for the following combustion devices:

Line	Unit Description (ID)	MMBtu/hr
CV Line 5 (CV-5)	Rubber/Coating Curing Oven (CV-5C)	1.590
CV Line 6 (CV-6)	Rubber/Coating Curing Oven (CV-6C1)	1.590
CV Line 7 (CV-7)	Rubber/Coating Curing Oven (CV-C)	1.590
CV Line 8 (CV-8)	Rubber Curing Oven (CV-8C1)	1.590
	Coating Curing Oven (CV-8C2)	1.590
CV Line 9 (CV-9)	Rubber Curing Oven (CV-9C1)	1.590
	Coating Curing Oven (CV-9C2)	1.590
CV Line 10 (CV-10)	Microwave Curing Ovens (CV-10C1)	0.500
	Rubber Curing Oven (CV-10C2)	0.400
	Coating Curing Oven (CV-10C6)	0.400
	Rubber Curing Oven (CV-11C2)	0.500
	Coating Curing Oven (CV-11C3)	0.500
CV Line 12 (CV-12)	Rubber Curing Oven (CV-12C2)	0.500
	Coating Curing Oven (CV-12C3)	0.500
SDM Line 1 (EA) (SDM-1)	Core Metal Heater (SMD-1MH)	0.375
	Microwave Curing Oven (SMD-1C1)	0.143
	Microwave Curing Oven (SMD-1C2)	0.143
	Rubber Curing Oven (SMD-1C3)	1.700
	Coating Curing Oven (SMD-1, C4)	0.680
SDM Line 2 (EB) (SDM-2)	Core Metal Heater (SMD-2MH)	1.190
	Bead Type Rubber Curing Oven & Deodorizing Oven (SDM-2C1)	1.990
	Drying Oven	2.000
SDM Line 3 (EC) (SDM-3)	Core Metal Heater (SMD-3MH)	1.190
	Bead Type Rubber Curing Oven & Deodorizing Oven (SDM-3C1)	1.990
	Coating Curing Oven (SMD-3C2)	1.000
SDM Line 4 (ED) (SDM-4)	Core Metal Heater (SMD-4MH)	0.750
	Microwave Rubber Curing Ovens (SMD-4C1)	0.286
	Curing Oven (SDM-4C2)	1.700
	Coating Cure Oven (SDM-4C3)	0.680
SDM Line 5 (EE) (SDM-5)	Core Metal Heater (SMD-5MH)	0.750
	Microwave Curing Ovens (SMD-5C1)	0.286
	Rubber Curing Oven (SDM-5C2)	1.700
	Coating Curing Oven (SDM-5C3)	0.680
L-Coat Extrusion Line (LC-1)	Curing Oven (LC-1C1)	7.038
	Curing Oven (LC-1C2)	0.516
CV Line 1 (CV-1)	Rubber and Coating Curing Oven (CV-1C)	1.590
	Pre-Heater (CV-1Pr)	0.298
CV Line 4 (CV-4)	Pre-Heater (CV-4Pr)	0.298
	Rubber and Coating Curing Oven (CV-4C)	1.590

Methodology 44.993

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

See page 3 for HAPs emissions calculations.

Appendix A: Emissions Calculations
 Natural Gas Combustion Only
 MM BTU/HR <100
 HAPs Emissions

Company Name: Nishikawa Cooper LLC
 Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
 Part 70 Renewal No.: T087-21424-00031
 PR ID: 087-00031
 Date: 8/25/2011

HAPs - Organics

Emission Factor in lb/MMcf	Benzene 2.1E-03	e 1.2E-03	Formaldehyde 7.5E-02	Hexane 1.8E+00	Toluene 3.4E-03
Potential Emission in tons/yr	4.14E-04	2.36E-04	1.48E-02	3.55E-01	6.70E-04

HAPs - Metals

Emission Factor in lb/MMcf	Lead 5.0E-04	Cadmium 1.1E-03	Chromium 1.4E-03	Manganese 3.8E-04	Nickel 2.1E-03
Potential Emission in tons/yr	9.85E-05	2.17E-04	2.76E-04	7.49E-05	4.14E-04

Methodology is the same as page 2.

The five highest organic and metal HAPs emission factors are provided above.
 Additional HAPs emission factors are available in AP-42, Chapter 1.4.

**Appendix A: Emissions Calculations
VOC and Particulate**

Company Name: Nishikawa Cooper LLC
 Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
 Part 70 Renewal No.: T087-29472-00031
 Pit ID: 087-00031
 Date: 8/25/2011

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency*
VN Surface Coating Line (VN-1SB)																
FKJF Recipe	6.58	88.00%	0.0%	88.0%	0.0%	12.00%	0.15000	1.000	5.79	5.79	0.87	20.85	3.80	0.00	48.25	75%
Spray Booth (SDM-2SB)																
FKJF Recipe	6.58	88.00%	0.0%	88.0%	0.0%	12.00%	0.00086	4080.000	5.79	5.79	20.32	487.62	88.99	0.00	48.25	100%
FKJF Recipe	6.58	88.00%	0.0%	88.0%	0.0%	12.00%	6.61000	1.000	5.79	5.79	5.82	139.60	25.48	0.10	48.25	75%
Urethane Application Line (CV-9Ex)							lbs/hr									
BB 35062	8.51	80.00%	43.0%	37.0%	43.0%	19.00%	6.61000	1.000	5.52	3.15	2.45	58.70	10.71	0.91	16.57	75%
SDM EC Urethane Application Spray Booth (SDM-3SB)							lbs/hr									
BB 35062	8.51	80.00%	43.0%	37.0%	43.0%	19.00%	3.30500	1.000	5.52	3.15	1.22	29.35	5.36	0.46	16.57	75%
Urethane Application Spray Booth (CV-8SB)							lbs/hr									
BB 35062	8.51	80.00%	43.0%	37.0%	43.0%	19.00%	6.61000	1.000	5.52	3.15	2.45	58.70	10.71	0.91	16.57	75%
Spray Booth-Line 2 (X029)							lbs/hr									
SP-217	8.51	60.20%	49.8%	10.4%	52.2%	34.70%	3.97000	1.000	1.85	0.89	0.41	9.91	1.81	1.55	2.55	75%
Spray Booth-Line 1 (CV-1SB)							lbs/hr									
SP-217	8.51	60.20%	49.8%	10.4%	52.2%	34.70%	3.97000	1.000	1.85	0.89	0.41	9.91	1.81	1.55	2.55	75%
Line 5 Spray Booth (CV-SSB)							lbs/hr									
SP-217	8.51	60.20%	49.8%	10.4%	52.2%	34.70%	7.93000	1.000	1.85	0.89	0.82	19.79	3.61	3.10	2.55	75%
Line 6 Spray Booth (CV-6SB)							lbs/hr									
SP-217	8.51	60.20%	49.8%	10.4%	52.2%	34.70%	7.93000	1.000	1.85	0.89	0.82	19.79	3.61	3.10	2.55	75%
Line 4 Waterborne Urethane Coating Booth (CV-4SB)							lbs/hr									
SP-217	8.51	60.20%	49.8%	10.4%	52.2%	34.70%	3.97000	1.000	1.85	0.89	0.41	9.91	1.81	1.55	2.55	75%
Line 7 Waterborne Urethane Coating Booth (CV-7SB)							lbs/hr									
SP-217	8.51	60.20%	49.8%	10.4%	52.2%	34.70%	11.90000	1.000	1.85	0.89	1.24	29.70	5.42	4.65	2.55	75%
Small Robot#1 (X028)							lbs/hr									
SP-217	8.51	60.20%	49.8%	10.4%	52.2%	34.70%	1.32000	1.000	1.85	0.89	0.14	3.29	0.60	0.52	2.55	75%

**Appendix A: Emissions Calculations
VOC and Particulate - continued**

**Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Pit ID: 087-00031
Date: 8/25/2011**

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency*
Spray Coating Line (X025)																
H792C	7.20	100.00%	0.0%	100.0%	0.0%	0.00%	0.00120	195.000	7.20	7.20	1.68	40.3	7.36	0.00	n/a	75%
UNISTOLE P 401	7.34	95.00%	0.0%	95.0%	0.0%	0.00%	0.00071	195.000	6.97	6.97	0.97	23.3	4.25	0.06	n/a	75%
Oflex Hardener EH-47	8.59	54.50%	0.0%	54.5%	0.0%	1.00%	0.00019	195.000	4.68	4.68	0.17	4.1	0.76	0.16	468	75%
FUM Primer Blend	7.37	93.53%	0.00%	93.5%	0.0%	0.09%	0.00210	195.000	6.89	6.89	2.82	67.7	12.4	0.21	7659	75%
ST 97 PA	7.51	50.00%	0.0%	50.0%	0.0%	50.00%	0.00009	195.000	3.75	3.75	0.06	1.5	0.28	0.07	7.51	75%
H792C	7.20	100.00%	0.0%	100.0%	0.0%	0.00%	0.00141	195.000	7.20	7.20	1.98	47.4	8.65	0.00	n/a	75%
Oflex Hardener EH-47	8.59	54.50%	0.0%	54.5%	0.0%	1.00%	0.00026	195.000	4.68	4.68	0.24	5.8	1.06	0.22	468	75%
Oflex No. 100 H-5	8.01	74.00%	0.0%	74.0%	0.0%	25.00%	0.00264	195.000	5.93	5.93	3.05	73.2	13.37	1.17	23.7	75%
FUM Coating Blend	7.77	79.94%	0.00%	79.9%	0.0%	16.1%	0.00440	195.000	6.21	6.21	5.33	128.0	23.4	1.46	39	75%
Line 10 Spray Booth (CV-10SB1)							grams/min/gun	number of guns								
F-KWD	8.35	70.83%	69.8%	1.0%	0.0%	0.00%	10.00000	4.000	0.09	0.09	0.05	1.3	0.24	2.36	n/a	65%
Line 10 Spray Booth (CV-10SB2)							grams/min/gun	number of guns								
F-KWD	8.35	70.83%	69.8%	1.0%	0.0%	0.00%	10.00000	2.000	0.09	0.09	0.03	0.7	0.12	1.18	n/a	65%
Cleaning Agent							grams/min/gun	number of guns								
Mean Green	8.51	4.10%	0.0%	4.1%	0.0%	0.00%	10.00000	6.000	0.35	0.35	0.33	7.8	1.42	11.66	n/a	65%
SDM EE Spray Booth (SDM-5SB)							pounds/hr/gun	number of guns								
TW-017B	8.51	78.50%	69.1%	9.4%	71.0%	19.80%	1.32000	6.000	2.76	0.80	0.74	17.87	3.26	1.86	4.04	75%
Spray Booth (SDM-4SB)							pounds/hr/gun	number of guns								
TW-017B	8.51	78.50%	69.1%	9.4%	71.0%	19.80%	1.32000	6.000	2.76	0.80	0.74	17.87	3.26	1.86	4.04	75%
SDM EA Spray Booth (SDM-1SB)							grams/min/gun	number of guns								
TW-017B	8.51	78.50%	69.1%	9.4%	71.0%	19.80%	10.00000	6.000	2.76	0.80	0.75	17.89	3.26	1.87	4.04	75%
Limited Potential Emissions										48.18	1156.23	211.01	40.87			

		Control Efficiency:		Limited VOC lbs per Hour	Limited VOC lbs per Day	Limited VOC tons per Year	Controlled PM tons/yr
		VOC	PM				
L-Coat Glassline		0.00%	95.00%	33.79	810.96	148.00	2.04
Total Limited Potential Emissions:	Total Controlled Potential Emissions:						
Total Emissions	VOC	Total Emissions	PM/PM10				
Unlimited (tons/yr)	211.01	Uncontrolled (tons/yr)	40.87				
Limited (tons/yr)	148.00	Controlled (tons/yr)	2.04				

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)
Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)
Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)
Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hrs/yr) * (1 ton/2000 lbs)
Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1-Weight % Volatiles) * (1-Transfer efficiency) * (8760 hrs/yr) * (1 ton/2000 lbs)
Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)
Potential VOC Pounds per Hour = Throughput (grams/min/gun) * Number of Guns * Weight % Organics * 60 min/hr * 1 lb/454 grams
Potential VOC Pounds per Hour for cleaning agent = Throughput (grams/min/gun) * Number of Guns * Weight % Organics * 3 min/hr * 1 lb/454 grams (cleaning agent will not be used more than 3 minutes per hour)
Particulate Potential Tons per Year = (grams/min/gun) * Number of guns * 60 min/hr * 1 lb/454 grams * (1-Weight % Volatiles) * (1-Transfer efficiency) * (8760 hrs/yr) * (1 ton/2000 lbs)

* Transfer Efficiency for HVLP and flat coated surface is 65-75%.
Transfer Efficiency for drip applicators and finishing touchup operations is 100%.

**Appendix A: Emission Calculations
HAP Emission Calculations**

Company Name: Nishikawa Standard Company
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-21424-00031
Plt ID: 087-00031
Reviewer: GS/EVP
Date: 8/25/2011

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Emission Factor	Weight % Glycol Ethers	Weight % Toluene	Weight % MIBK	Weight % Ethylene Glycol	Weight % Xylene	Glycol Ethers Emissions (ton/yr)	Toluene Emissions (ton/yr)	MIBK Emissions (ton/yr)	Ethylene Glycol Emissions (ton/yr)	Xylene Emissions (ton/yr)
Small Robot #2 (X003)														
FKJF Recipe	6.58	0.15000	1.00	N/A	0.00%	0.00%	0.00%	0.00%	13.15%	0.00	0.00	0.00	0.00	0.57
CV Finishing Touchup Stations (X004)														
FKJF Recipe	6.58	0.60800	1.00	N/A	0.00%	0.00%	0.00%	0.00%	13.15%	0.00	0.00	0.00	0.00	2.30
Silicone application line SDM-EB (X019)														
FKJF Recipe	6.58	0.00086	4080.00	N/A	0.00%	0.00%	0.00%	0.00%	13.15%	0.00	0.00	0.00	0.00	13.30
lbs/hr														
FKJF Recipe	6.58	6.61000	1.00	N/A	0.00%	0.00%	0.00%	0.00%	13.15%	0.00	0.00	0.00	0.00	3.81
Urethane Application Line-CV Line 9 (X020)														
BB 35062	8.51	6.61000	1.00	N/A	2.00%	0.00%	0.00%	0.00%	0.00%	0.58	0.00	0.00	0.00	0.00
Urethane Application Line-SDM EC (X021)														
BB 35062	8.51	3.30500	1.00	N/A	2.00%	0.00%	0.00%	0.00%	0.00%	0.29	0.00	0.00	0.00	0.00
Urethane Application Line-CV Line 8 (X023)														
BB 35062	8.51	6.61000	1.00	N/A	2.00%	0.00%	0.00%	0.00%	0.00%	0.58	0.00	0.00	0.00	0.00
Spray Booth-Line 2 (X029)														
SP-217	8.51	3.97000	1.00	N/A	4.60%	0.00%	0.00%	0.00%	0.40%	0.80	0.00	0.00	0.00	0.07
Spray Booth-Line 3 (X030)														
SP-217	8.51	3.97000	1.00	N/A	4.60%	0.00%	0.00%	0.00%	0.40%	0.80	0.00	0.00	0.00	0.07
Spray Booth-Line 5 (X031)														
SP-217	8.51	7.93000	1.00	N/A	4.60%	0.00%	0.00%	0.00%	0.40%	1.60	0.00	0.00	0.00	0.14
Spray Booth-Line 6 (X032)														
SP-217	8.51	7.93000	1.00	N/A	4.60%	0.00%	0.00%	0.00%	0.40%	1.60	0.00	0.00	0.00	0.14
Waterborne Urethane Coating Booth-Line 4 (X026)														
SP-217	8.51	3.97000	1.00	N/A	4.60%	0.00%	0.00%	0.00%	0.40%	0.80	0.00	0.00	0.00	0.07
Waterborne Urethane Coating Booth-Line 7 (X027)														
SP-217	8.51	11.90000	1.00	N/A	4.60%	0.00%	0.00%	0.00%	0.40%	2.40	0.00	0.00	0.00	0.21
Waterborne Urethane Coating Booth-Small Robot#1 (X028)														
SP-217	8.51	1.32000	1.00	N/A	4.60%	0.00%	0.00%	0.00%	0.40%	0.27	0.00	0.00	0.00	0.02

Appendix A: Emission Calculations
HAP Emission Calculations

Company Name: Nishikawa Cooper LLC
 Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
 Part 70 Renewal No.: T087-29472-00031
 Plt ID: 087-00031
 Date: 8/25/2011

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Emission Factor	Weight % Glycol Ethers	Weight % Toluene	Weight % MIBK	Weight % Ethylene Glycol	Weight % Xylene	Glycol Ethers Emissions (ton/yr)	Toluene Emissions (ton/yr)	MIBK Emissions (ton/yr)	Ethylene Glycol Emissions (ton/yr)	Xylene Emissions (ton/yr)
Spray Coating Line (X025)														
H792C	7.20	1.20E-03	195.00	N/A	0.00%	90.00%	9.00%	0.00%	0.00%	0.00	6.64	0.66	0.00	0.00
UNISTOLE P 401	7.34	7.10E-04	195.00	N/A	0.00%	95.00%	0.00%	0.00%	0.00%	0.00	4.23	0.00	0.00	0.00
Oflex Hardener EH-47	8.59	1.90E-04	195.00	N/A	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00
ST 97 PA	7.51	0.00009	195.00	N/A	0.00%	50.00%	0.00%	0.00%	0.00%	0.00	0.29	0.00	0.00	0.00
H792C	7.2	0.00141	195.00	N/A	0.00%	90.00%	9.00%	0.00%	0.00%	0.00	7.80	0.78	0.00	0.00
Oflex Hardener EH-47	8.59	0.00026	195.00	N/A	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00
Oflex No. 100 H-5	8.01	0.00264	195.00	N/A	0.00%	0.00%	22.00%	0.00%	22.00%	0.00	0.00	3.97	0.00	3.97
SDM EE Spray Line (X036)		lbs/hr/gun	no. of guns											
TW-017B	8.56	1.32000	6.00	N/A	0.00%	0.00%	0.00%	0.60%	0.00%	0.00	0.00	0.00	0.21	0.00
SDM EA Spray Line (X037)		grams/min/gun	n	no. of guns										
TW-017B	8.56	10.00000	6.00	N/A	0.00%	0.00%	0.00%	0.60%	0.00%	0.00	0.00	0.00	0.21	0.00

Total Potential Emissions **9.71 18.96 5.42 0.42 24.67**

Total HAPs (tons per year) 59.17

METHODOLOGY

HAPS emission rate (tons/yr) = Density (lb/gal) * Gal of Material (gal/unit) * Maximum (unit/hr) * Weight % HAP * 8760 hrs/yr * 1 ton/2000 lbs * Material usage limitation.

**Appendix A: Emission Calculations
Extrusion Lines**

Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Pit ID: 087-00031
Date: 8/25/2011

Emission Unit	Potential Talc Throughput (lbs/hr)	Talc Transfer Efficiency	Control Efficiency	Uncontrolled		Controlled	
				Potential PM/PM10 Emissions (lbs/hr)	Potential PM/PM10 Emissions (tons/yr)	Potential PM/PM10 Emissions (lbs/hr)	Potential PM/PM10 Emissions (tons/yr)
CV Line 1 Duster	2	75%	99%	0.01	2.2	0.01	0.02
CV Line 4 Duster	2	75%	99%	0.50	2.2	0.01	0.02
CV Line 5 Dusters	4	75%	99%	1.00	4.4	0.01	0.04
CV Line 6 Dusters	4	75%	99%	1.00	4.4	0.01	0.04
CV Line 7 Duster	2	75%	0%	0.50	2.2	0.50	2.19
CV Line 9 Duster	2	75%	99%	0.50	2.2	0.01	0.02
Total				4.00	17.52	0.54	2.34

Note:
Talc is applied to extruded rubber in the dusters by dragging the hot, tacky rubber through a trough of talc. The talc adheres to the rubber and there are minimal emissions generated during the transfer of the talc to the rubber.
CV Line 9 uses sodium bicarbonate instead of talc but emission calculations are the same.

Potential Uncontrolled Emissions (lbs/hr) = Talc Throughput (lbs/hr) x (1 - Transfer Efficiency)
Potential Uncontrolled Emissions (tons/yr) = Potential Uncontrolled Emissions (lbs/hr) x 8,760 hrs/yr x 1 ton/2,000 lbs
Potential Controlled Emissions (lbs/hr) = Talc Throughput (lbs/hr) x (1 - Transfer Efficiency) x Control Efficiency
Potential Controlled Emissions (tons/yr) = Potential Controlled Emissions (lbs/hr) x 8,760 hrs/yr x 1 ton/2,000 lbs

Emission Unit	Dust Collector Unit ID	Process Weight Rate (tons/hr)	326 IAC 6-3-2 allowable emission rate (lb/hr)	Able to Comply?	Control Device Required to Comply?
CV Line 1 Duster	DC-1	0.101	0.88	Yes	No
CV Line 4 Duster	DC-1	0.101	0.88	Yes	No
CV Line 5 Dusters	DC-1	0.202	1.40	Yes	No
CV Line 6 Dusters	DC-1	0.202	1.40	Yes	No
CV Line 7 Duster	DC-2	0.201	1.83	Yes	No
CV Line 9 Duster	DC-2	0.201	1.40	Yes	No

The allowable PM emission rate pursuant to 326 IAC 6-3-2(c), Process Operations, for weight rates up to 60,000 lb/hr is determined using the following formula:
E = 4.1 * P^{0.67}
where: E = allowable PM emission rate (lb/hr)
P = process weight rate (tons/hr)

Other Emissions from Rubber Parts Manufacturing

	Rubber Throughput (lbs/hr)	VOC Emission Factor (lbs/lb rubber)	VOC (lbs/hr)	VOC (tons/yr)	Total HAPs Emission Factor (lbs/lb rubber)	HAPs (lbs/hr)	HAPs (tons/yr)	PM/PM10 Emission Factor (lbs/lb rubber)	PM/PM10 (lbs/hr)	PM/PM10 (tons/yr)	PM/PM10 Control Efficiency	PM/PM10 after controls (lbs/hr)	PM/PM10 after controls (tons/yr)
Extruding (CV-1Ex)	200	5.00E-04	0.1	0.438	7.52E-05	0.015	0.066	1.12E-07	2.24E-05	9.81E-05	0.00%	2.24E-05	9.81E-05
Extruding (CV-4Ex)	200	5.00E-04	0.1	0.438	7.52E-05	0.015	0.066	1.12E-07	2.24E-05	9.81E-05	0.00%	2.24E-05	9.81E-05
Extruding (CV-8Ex)	400	5.00E-04	0.2	0.876	7.52E-05	0.030	0.132	1.12E-07	4.48E-05	1.96E-04	0.00%	4.48E-05	1.96E-04
Extruding (CV-8Ex)	400	5.00E-04	0.2	0.876	7.52E-05	0.030	0.132	1.12E-07	4.48E-05	1.96E-04	0.00%	4.48E-05	1.96E-04
Extruding (CV-7Ex)	600	5.00E-04	0.3	1.314	7.52E-05	0.045	0.198	1.12E-07	6.72E-05	2.94E-04	0.00%	6.72E-05	2.94E-04
Extruding (CV-8Ex)	400	5.00E-04	0.2	0.876	7.52E-05	0.030	0.132	1.12E-07	4.48E-05	1.96E-04	0.00%	4.48E-05	1.96E-04
Extruding (CV-9Ex)	400	5.00E-04	0.2	0.876	7.52E-05	0.030	0.132	1.12E-07	4.48E-05	1.96E-04	0.00%	4.48E-05	1.96E-04
Extruding (CV-10Ex)	750	5.00E-04	0.3750	1.643	7.52E-05	0.022	0.098	1.12E-07	2.24E-05	9.81E-05	0.00%	2.24E-05	9.81E-05
Extruding (CV-11Ex)	200	5.00E-04	0.1	0.438	7.52E-05	0.015	0.066	1.12E-07	2.24E-05	9.81E-05	0.00%	2.24E-05	9.81E-05
Extruding (SDM-1Ex)	1289	5.00E-04	0.6445	2.823	7.52E-05	0.097	0.425	1.12E-07	1.44E-04	6.32E-04	0.00%	1.44E-04	6.32E-04
Extruding (SDM-2Ex)	400	5.00E-04	0.2	0.876	7.52E-05	0.030	0.132	1.12E-07	4.48E-05	1.96E-04	0.00%	4.48E-05	1.96E-04
Extruding (SDM-3Ex)	400	5.00E-04	0.2	0.876	7.52E-05	0.030	0.132	1.12E-07	4.48E-05	1.96E-04	0.00%	4.48E-05	1.96E-04
Extruding (SDM-4Ex)	1289	5.00E-04	0.6445	2.823	3.99E-05	0.051	0.225	3.67E-08	4.73E-05	2.07E-04	0.00%	4.73E-05	2.07E-04
Extruding (SDM-5Ex)	1289	5.00E-04	0.6445	2.823	3.99E-05	0.051	0.225	3.67E-08	4.73E-05	2.07E-04	0.00%	4.73E-05	2.07E-04
Extruding (LC-1Ex)	1417	5.00E-04	0.7085	3.103	7.52E-05	0.107	0.467	1.12E-07	1.59E-04	6.95E-04	0.00%	1.59E-04	6.95E-04
Hot Air Curing (CV-1C)	200	2.49E-03	0.498	2.18	3.46E-03	0.692	3.03	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (X006)	200	2.49E-03	0.498	2.18	3.46E-03	0.692	3.03	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (X007)	200	2.49E-03	0.498	2.18	3.46E-03	0.692	3.03	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (CV-4C)	200	2.49E-03	0.498	2.18	3.46E-03	0.692	3.03	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (CV-5C)	400	2.49E-03	0.996	4.36	3.46E-03	1.38	6.06	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (CV-6C1 and CV-6C2)	400	2.49E-03	0.996	4.36	3.46E-03	1.38	6.06	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (CV-7C)	600	2.49E-03	1.494	6.54	3.46E-03	2.08	9.09	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (SDM-5C1 and SDM-5C2)	1289	1.90E-03	2.449	10.73	9.76E-04	1.26	5.51	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (CV-10C1 and CV-10C2)	750	1.90E-03	1.425	6.24	9.76E-04	0.73	3.21	N/A	N/A	N/A	N/A	N/A	N/A
Autoclave Curing (CV-8C1 and CV-8C2)	400	6.15E-03	2.460	10.8	6.04E-03	2.42	10.6	N/A	N/A	N/A	N/A	N/A	N/A
Autoclave Curing (CV-9C1)	400	6.15E-03	2.460	10.8	6.04E-03	2.42	10.6	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (SDM-1C1, SDM-1C2 and SDM-1C3)	1289	2.49E-03	3.210	14.06	3.46E-03	4.46	19.53	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (SDM-2C1)	400	2.49E-03	0.996	4.36	3.46E-03	1.38	6.06	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (SDM-3C1)	400	2.49E-03	0.996	4.36	3.46E-03	1.38	6.06	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (CV-11C1 and CV-11C2)	200	2.49E-03	0.498	2.18	3.46E-03	0.692	3.03	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (CV-12C1 and CV-12C2)	200	2.49E-03	0.498	2.18	3.46E-03	0.692	3.03	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (SDM-4C1 and SDM-4C2)	1289	2.49E-03	3.210	14.06	3.46E-03	4.46	19.53	N/A	N/A	N/A	N/A	N/A	N/A
Hot Air Curing (LC-1C1)	1417	2.49E-03	3.540	15.48	3.46E-03	4.46	19.53	N/A	N/A	N/A	N/A	N/A	N/A
Mixing and Milling (Mx-1)	417	4.44E-04	0.185	0.810	1.40E-04	0.058	0.256	9.25E-04	0.385	1.69	98.00%	0.008	0.034
10234 Totals:			24.5	107.2		22.3	97.8		0.386	1.69		0.008	0.037

Emission Factors from Tables 4.12-6, 4.12-8 and 4.12-4 of AP-42 draft Section 4.12, 06/99.
VOC emission factor is derived from stack test results obtained by Wisconsin DNR for polyethylene plastic processing facilities.
Emission factors are for the worst case compound for each pollutant.

Appendix A: Emission Calculations
HAP Emission Calculations
Individual HAP emissions when using worst case total HAP materials

Company Name: Nishikawa Cooper LLC
Address City IN Zip: 324 Morrow Street, Topeka, Indiana 46571
Part 70 Renewal No.: T087-29472-00031
Plt ID: 087-00031
Date: 8/25/2011

Hot Air Curing

HAP	Worst Case Emission Factor	Potential Rubber Throughput	Potential Emissions	Potential Emissions
	(lb/lb rubber)	(lbs/hr)	(lbs/hr)	(tons/yr)
1,1,1 Trichloroethane	1.48E-06	2089	0.003	0.014
Acetophenone	3.58E-07	2089	0.001	0.003
Aniline	1.26E-05	2089	0.026	0.115
bis(2-Ethylhexyl)phthalate	5.92E-08	2089	0.000	0.001
Chloroethane	4.95E-06	2089	0.010	0.045
Chloromethane	2.18E-05	2089	0.046	0.199
Cumene	2.32E-07	2089	0.000	0.002
Ethyl Acrylate	1.16E-04	2089	0.242	1.06
Hexane	2.78E-03	2089	5.807	25.4
Xylenes	2.42E-05	2089	0.051	0.221
Methylene Chloride	4.08E-04	2089	0.852	3.73
Naphthalene	9.87E-07	2089	0.002	0.009
Phenol	3.13E-05	2089	0.065	0.286
Toluene	2.55E-05	2089	0.053	0.233

Autoclave Curing

HAP	Worst Case Emission Factor	Potential Rubber Throughput	Potential Emissions	Potential Emissions
	(lb/lb rubber)	(lbs/hr)	(lbs/hr)	(tons/yr)
1,4 Dichlorobenzene	2.53E-08	800	0.00002	0.0001
2-Methylphenol	6.93E-09	800	0.00001	0.00002
Acetaldehyde	3.22E-07	800	0.000	0.001
Acetophenone	9.76E-08	800	0.0001	0.0003
Benzene	2.07E-05	800	0.017	0.073
Biphenyl	3.14E-08	800	0.00003	0.0001
bis(2-Ethylhexyl)phthalate	2.73E-07	800	0.0002	0.001
Carbon Disulfide	5.93E-03	800	4.74	20.8
Carbonyl Sulfide	4.17E-05	800	0.033	0.146
Cumene	1.46E-06	800	0.001	0.005
Dibenzofuran	2.81E-09	800	0.000002	0.00001
Dimethylphthalate	3.02E-09	800	0.000002	0.00001
Epichlorohydrin	1.85E-06	800	0.001	0.006
Ethylbenzene	2.55E-06	800	0.002	0.009
Hexane	3.22E-06	800	0.003	0.011
Isocetane	5.23E-07	800	0.000	0.002
Xylenes	1.68E-05	800	0.013	0.059
Naphthalene	1.64E-07	800	0.0001	0.001
Phenol	4.75E-08	800	0.00004	0.0002
Styrene	1.86E-07	800	0.0001	0.001
t-Butyl Methyl Ether	7.31E-09	800	0.00001	0.00003
Toluene	1.59E-05	800	0.013	0.056

Mixing and Milling

HAP	Worst Case Emission Factor	Potential Rubber Throughput	Potential Emissions	Potential Emissions
	(lb/lb rubber)	(lbs/hr)	(lbs/hr)	(tons/yr)
1,1,1 Trichloroethane	6.03E-08	417	0.00003	0.00011
Acetophenone	1.45E-08	417	0.00001	0.00003
Aniline	5.13E-07	417	0.00021	0.00094
Benzene	4.62E-08	417	0.00002	0.00008
bis(2-Ethylhexyl)phthalate	2.40E-09	417	0.000001	0.00000
Cadmium Compounds	2.65E-09	417	0.000001	0.00000
Chloroethane	2.01E-07	417	0.00008	0.00037
Chloromethane	8.86E-07	417	0.00037	0.00162
Chromium Compounds	4.20E-08	417	0.00002	0.00008
Cumene	9.43E-09	417	0.00000	0.00002
Ethyl Acrylate	1.45E-07	417	0.00006	0.00026
Hexane	1.13E-04	417	0.04712	0.20639
Xylenes	1.06E-06	417	0.00044	0.00194
Methylene Chloride	1.65E-05	417	0.00688	0.03014
Naphthalene	4.01E-08	417	0.00002	0.00007
Nickel Compounds	3.21E-08	417	0.00001	0.00006
Phenol	1.27E-06	417	0.00053	0.00232
Tetrachloroethene	4.10E-06	417	0.00171	0.00749
Toluene	1.04E-06	417	0.00043	0.00190

Extruding

HAP	Worst Case Emission Factor	Potential Rubber Throughput	Potential Emissions	Potential Emissions
	(lb/lb rubber)	(lbs/hr)	(lbs/hr)	(tons/yr)
1,1,1 Trichloroethane	3.23E-08	8417	0.0003	0.001
Acetophenone	7.79E-09	8417	0.0001	0.0003
Aniline	2.75E-07	8417	0.002	0.010
bis(2-Ethylhexyl)phthalate	1.29E-09	8417	0.00001	0.00005
Chloroethane	1.08E-07	8417	0.001	0.004
Chloromethane	4.75E-07	8417	0.004	0.018
Chromium	2.59E-09	8417	0.00002	0.00010
Cumene	5.05E-09	8417	0.00004	0.0002
Ethylacrylate	2.53E-06	8417	0.021	0.093
Hexane	6.05E-05	8417	0.509	2.23
Xylenes	5.28E-07	8417	0.004	0.019
Methylene Chloride	8.87E-06	8417	0.075	0.327
Naphthalene	2.15E-08	8417	0.00018	0.0008
Nickel	1.98E-09	8417	0.00002	0.00007
Phenol	6.80E-07	8417	0.006	0.025
Toluene	5.55E-07	8417	0.005	0.020

Emission Factors from Tables 4.12-6, 4.12-9, 4.12-10 and 4.12-4 of AP-42 draft Section 4.12, 06/99. These calculations are for the maximum potential emissions of each individual HAP considering the compounds used at this source.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED

TO: Michael Hough
Nishikawa Standard Company
324 Morrow St
Topeka, IN 46571

DATE: August 25, 2011

FROM: Matt Stuckey, Branch Chief
Permits Branch
Office of Air Quality

SUBJECT: Final Decision
Title V
087-29472-00031

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at jbrush@idem.IN.gov.

Final Applicant Cover letter.dot 11/30/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

August 25, 2011

TO: LaGrange Public Library

From: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Subject: **Important Information for Display Regarding a Final Determination**

Applicant Name: Nishikawa Cooper, LLC
Permit Number: 087-29472-00031

You previously received information to make available to the public during the public comment period of a draft permit. Enclosed is a copy of the final decision and supporting materials for the same project. Please place the enclosed information along with the information you previously received. To ensure that your patrons have ample opportunity to review the enclosed permit, **we ask that you retain this document for at least 60 days.**

The applicant is responsible for placing a copy of the application in your library. If the permit application is not on file, or if you have any questions concerning this public review process, please contact Joanne Smiddie-Brush, OAQ Permits Administration Section at 1-800-451-6027, extension 3-0185.

Enclosures
Final Library.dot 11/30/07

Mail Code 61-53

IDEM Staff	CDENNY 8/25/2011 Nishikawa Standard Company 087-29472-00031 (final)		Type of Mail: CERTIFICATE OF MAILING ONLY	AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204		

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handling Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee
											Remarks
1		Michael Hough Nishikawa Standard Company 324 Morrow St Topeka IN 46571 (Source CAATS)									
2		Tony Baker Plant Mgr Nishikawa Standard Company 324 Morrow St Topeka IN 46571 (RO CAATS)									
3		LaGrange County Public Library (Topeka Branch) 105 South Main Street Topeka IN 46571 (Library)									
4		Mr. Steve Christman NISWMD 2320 W 800 S, P.O. Box 370 Ashley IN 46705 (Affected Party)									
5		Topeka Town Council P.O. Box 127 Topeka IN 46571 (Local Official)									
6		LaGrange County Health Dept. 304 B Townline Road Lagrange IN 46761 (Health Department)									
7		LaGrange County Commissioners 114 W. Michigan St. LaGrange IN 46761 (Local Official)									
8		Ms. Amanda Hennessy Keramida Environmental, Inc. 401 N College Ave Indianapolis IN 46202 (Consultant)									
9		Mark Zeltwanger 26545 CR 52 Nappanee IN 46550 (Affected Party)									
10											
11											
12											
13											
14											
15											

Total number of pieces Listed by Sender	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50, 000 per occurrence. The maximum indemnity payable on Express mil merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See Domestic Mail Manual R900, S913, and S921 for limitations of coverage on inured and COD mail. See International Mail Manual for limitations o coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
---	--	--	--