



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: November 5, 2010

RE: POET Biorefining – Cloverdale, LLC / 133-29592-00003

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Suite N 501E, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER.dot12/03/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

Mr. Dave Brooks
POET Biorefining - Cloverdale, LLC
2265 East County Road 800 South
Cloverdale, IN 46120

November 5, 2010

Re: 133-29592-00003
First Significant Revision to
F133-28725-00003

Dear Mr. Brooks:

Putnam County Ethanol, LLC was issued a Federally Enforceable State Operating Permit (FESOP) No. F133-28725-00003 on March 26, 2010 for a stationary ethanol production facility located at 2265 East County Road 800 South. On August 23, 2010, the Office of Air Quality (OAQ) received an application from the source requesting to:

- 1) Change the name of the source from Putnam County Ethanol, LLC to POET Biorefining - Cloverdale, LLC. POET Biorefining recently purchased the fuel ethanol facility.
- 2) Increase the maximum throughput rates of EU001 - EU003 from 30,000 bushels of corn per hour to 50,000 bushels of corn per hour. This is due to the fact that corn can be received by three (3) dump puts as opposed to only the (2), which are identified in the existing permit.
- 3) Add a mash preparation scrubber (CE011) to control emissions generated by the slurry tank and yeast propagation tank emission units (EU017 & EU018).
- 4) Remove the secondary control device from the fermentation scrubber. The fermentation scrubber CE-12 will control emissions generated by the six (6) fermentation vessels (EU019 - EU024) and the two (2) beer wells (EU025 and EU026).
- 5) Replace the permitted seven (7) chamber regenerative thermal oxidizer (RTO) with two (2) five (5) chamber RTOs to be identified as CE015 and CE016, which will exhaust to a common stack SV014.
- 6) Remove previously permitted DDGS storage silo (EU039) and DDGS storage silo bypass (EU040) and associated baghouses CE015 and CE016.

The attached Technical Support Document (TSD) provides additional explanation of the changes to the source/permit. Pursuant to the provisions of 326 IAC 2-8-11.1, these changes to the permit are required to be reviewed in accordance with the Significant Permit Revision (SPR) procedures of 326 IAC 2-8-11.1(f). Pursuant to the provisions of 326 IAC 2-8-11.1, a significant permit revision to this permit is hereby approved as described in the attached Technical Support Document (TSD).

The following construction conditions are applicable to the proposed project:

1. General Construction Conditions
The data and information supplied with the application shall be considered part of this source modification approval. Prior to any proposed change in construction which may affect the potential to emit (PTE) of the proposed project, the change must be approved

by the Office of Air Quality (OAQ).

2. This approval to construct does not relieve the permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.
3. Effective Date of the Permit
Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.
4. Pursuant to 326 IAC 2-1.1-9 (Revocation), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.
5. All requirements and conditions of this construction approval shall remain in effect unless modified in a manner consistent with procedures established pursuant to 326 IAC 2.

Pursuant to 326 IAC 2-8-11.1, this permit shall be revised by incorporating the significant permit revision into the permit. All other conditions of the permit shall remain unchanged and in effect. Attached please find the entire revised permit.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact Jason R. Krawczyk, of my staff, at 317-232-8427 or 1-800-451-6027, and ask for extension 2-8427.

Sincerely,



Iryn Calilung Section Chief
Permits Branch
Office of Air Quality

Attachments: Technical Support Document and revised permit

IC/JRK

cc: File - Putnam County
Putnam County Health Department
U.S. EPA, Region V
Compliance and Enforcement Branch
Billing, Licensing and Training Section



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

New Source Construction and Federally Enforceable State Operating Permit OFFICE OF AIR QUALITY

**POET Biorefining - Cloverdale, LLC
2265 East County Road 800 South
Cloverdale, Indiana 46120**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

Operation Permit No.: F133-28725-00003	
Issued by: <i>Original Signed by:</i> Iryn Calilung, Section Chief Permits Branch Office of Air Quality	Issuance Date: March 26, 2010 Expiration Date: March 26, 2015

First Significant Permit Revision No.: F133-29592-00003	
Issued by:  Iryn Calilung, Section Chief Permits Branch Office of Air Quality	Issuance Date: November 5, 2010 Expiration Date: March 26, 2015

TABLE OF CONTENTS

A. SOURCE SUMMARY.....	7
A.1 General Information [326 IAC 2-8-3(b)]	
A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]	
A.3 Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-8-3(c)(3)(I)]	
A.4 FESOP Applicability [326 IAC 2-8-2]	
B. GENERAL CONDITIONS	12
B.1 Definitions [326 IAC 2-8-1]	
B.2 Revocation of Permits [326 IAC 2-1.1-9(5)]	
B.3 Affidavit of Construction [326 IAC 2-5.1-3(h)] [326 IAC 2-5.1-4][326 IAC 2-8]	
B.4 Permit Term [326 IAC 2-8-4(2)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]	
B.5 Term of Conditions [326 IAC 2-1.1-9.5]	
B.6 Enforceability [326 IAC 2-8-6] [IC 13-17-12]	
B.7 Severability [326 IAC 2-8-4(4)]	
B.8 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]	
B.9 Duty to Provide Information [326 IAC 2-8-4(5)(E)]	
B.10 Certification [326 IAC 2-8-3(d)][326 IAC 2-8-4(3)(C)(i)][326 IAC 2-8-5(1)]	
B.11 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]	
B.12 Compliance Order Issuance [326 IAC 2-8-5(b)]	
B.13 Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]	
B.14 Emergency Provisions [326 IAC 2-8-12]	
B.15 Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.16 Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3(h)]	
B.17 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]	
B.18 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)][326 IAC 2-8-7(a)][326 IAC 2-8-8]	
B.19 Permit Renewal [326 IAC 2-8-3(h)]	
B.20 Permit Amendment or Revision [326 IAC 2-8-10][326 IAC 2-8-11.1]	
B.21 Operational Flexibility [326 IAC 2-8-15][326 IAC 2-8-11.1]	
B.22 Source Modification Requirement [326 IAC 2-8-11.1]	
B.23 Inspection and Entry [326 IAC 2-8-5(a)(2)][IC 13-14-2-2][IC 13-17-3-2] [IC 13-30-3-1]	
B.24 Transfer of Ownership or Operational Control [326 IAC 2-8-10]	
B.25 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16] [326 IAC 2-1.1-7]	
B.26 Advanced Source Modification Approval [326 IAC 2-8-4(11)] [326 IAC 2-1.1-9]	
B.27 Credible Evidence [326 IAC 2-8-4(3)][326 IAC 2-8-5][62 FR 8314] [326 IAC 1-1-6]	
C. SOURCE OPERATION CONDITIONS	22
Emission Limitations and Standards [326 IAC 2-8-4(1)]	
C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]	
C.2 Overall Source Limit [326 IAC 2-8]	
C.3 Opacity [326 IAC 5-1]	
C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.6 Fugitive Dust Emissions [326 IAC 6-4]	
C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]	
C.8 Stack Height [326 IAC 1-7]	
C.9 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	

Testing Requirements [326 IAC 2-8-4(3)]

- C.10 Performance Testing [326 IAC 3-6]

Compliance Requirements [326 IAC 2-1.1-11]

- C.11 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-8-4][326 IAC 2-8-5(a)(1)]

- C.12 Compliance Monitoring [326 IAC 2-8-4(3)][326 IAC 2-8-5(a)(1)]
- C.13 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.14 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-8-4(3)]
[326 IAC 2-8-5(1)]

Corrective Actions and Response Steps [326 IAC 2-8-4][326 IAC 2-8-5(a)(1)]

- C.15 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]
- C.16 Response to Excursions or Exceedances [326 IAC 2-8-4] [326 IAC 2-8-5]
- C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]
[326 IAC 2-8-5]

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

- C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]
- C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection

- C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

D.1 EMISSIONS UNIT OPERATION CONDITIONS - Grain Receiving and Handling

Processes..... 29

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.1.1 FESOP and PSD Emissions [326 IAC 2-8-4] [326 IAC 2-2]
- D.1.2 Particulate Emission Limitations [326 IAC 6-3-2]
- D.1.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.1.4 Particulate Control
- D.1.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11]

Compliance Monitoring Requirements

- D.1.6 Visible Emissions Notations
- D.1.7 Baghouse Parametric Monitoring
- D.1.8 Broken or Failed Bag Detection [326 IAC 2-8-5(1)] [326 IAC 2-8-4(1)]

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

- D.1.9 Record Keeping Requirements

D.2 EMISSIONS UNIT OPERATION CONDITIONS - Mash Preparation, Fermentation, Distillation, and Dehydration Process 35

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.2.1 FESOP VOC and HAP Emissions [326 IAC 2-2] [326 IAC 2-8-4] [326 IAC 2-4.1]
- D.2.2 VOC Emissions [326 IAC 8-5-6]
- D.2.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.2.4 VOC and HAP Control
- D.2.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]]

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- D.2.6 Parametric Monitoring [326 IAC 8-5-6]
- D.2.7 Scrubber Detection

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

- D.2.8 Record Keeping Requirements

D.3 EMISSIONS UNIT OPERATION CONDITIONS - DDGS Dryer and Cooling Process..... 39

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.3.1 PSD Minor Limits [326 IAC 2-2]
- D.3.2 FESOP Limits [326 IAC 2-8-4]
- D.3.3 VOC Emissions [326 IAC 8-5-6]
- D.3.4 Particulate Emission Limitations [326 IAC 6-3-2]
- D.3.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.3.6 VOC and HAP Control
- D.3.7 Particulate Control
- D.3.8 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- D.3.9 Visible Emissions Notations
- D.3.10 Baghouse Parametric Monitoring
- D.3.11 Broken or Failed Bag Detection [326 IAC 2-8-5(1)] [326 IAC 2-8-4(1)]
- D.3.12 Thermal Oxidation Temperature [326 IAC 8-5-6]
- D.3.13 Parametric Monitoring [326 IAC 8-5-6]

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

- D.3.14 Record Keeping Requirements

D.4 EMISSIONS UNIT OPERATION CONDITIONS - Ethanol Loading Rack..... 45

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.4.1 FESOP Limits [326 IAC 2-2] [326 IAC 2-8-4]
- D.4.2 VOC Emissions [326 IAC 8-5-6]
- D.4.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.4.4 VOC Control
- D.4.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

Compliance Monitoring Requirements [326 IAC 2-8-4][326 IAC 2-8-5(a)(1)]

- D.4.6 Visible Emissions Notations
- D.4.7 Flare Pilot Flame [326 IAC 8-5-6]

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)][326 IAC 28-16]

- D.4.8 Record Keeping Requirements
- D.4.9 Reporting Requirements

D.5 EMISSIONS UNIT OPERATION CONDITIONS - Natural Gas Fired Combustion Units 48

Emission Limitation and Standards [326 IAC 2-8-4(1)]

- D.5.1 FESOP Nitrogen Oxides (NOx) and Carbon Monoxide (CO) Limits [326 IAC 2-8-4] [326 IAC 2-2]
- D.5.2 Particulate Emissions [326 IAC 6-2-4] [326 IAC 2-8-4] [326 IAC 2-2]
- D.5.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.5.4 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11]

Record Keeping and Reporting Requirements

- D.5.5 Record Keeping Requirements
- D.5.6 Reporting Requirements

D.6 EMISSIONS UNIT OPERATION CONDITIONS - Diesel Fired Combustion Units 50

Emission Limitation and Standards [326 IAC 2-8-4(1)]

- D.6.1 FESOP Limits [326 IAC 2-8-4][326 IAC 2-2]

Record Keeping and Reporting Requirements

- D.6.2 Record Keeping Requirements
- D.6.3 Reporting Requirements

E.1 SOURCE OPERATION CONDITIONS - 40 CFR 60, Subpart Db - Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units 52

- E.1.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]
- E.1.2 Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units [40 CFR 60, Subpart Db] [326 IAC 12]

E.2 SOURCE OPERATION CONDITIONS - 40 CFR 60, Subpart Kb - Standards of Performance for Volatile Organic Liquid Storage Vessels for which Construction, Reconstruction, or Modification Commenced after July 23, 1984..... 53

- E.2.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]
- E.2.2 Standards of Performance for Volatile Organic Liquid Storage Vessels for which Construction, Reconstruction, or Modification Commenced after July 23, 1984 [40 CFR 60, Subpart Kb] [326 IAC 12]

E.3 SOURCE OPERATION CONDITIONS - 40 CFR 60, Subpart VVa - Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006 ... 55

- E.3.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]
- E.3.2 Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry [40 CFR 60, Subpart VV] [326 IAC 12]

E.4 SOURCE OPERATION CONDITIONS 40 CFR 60, Subpart IIII - Standards of Performance for Stationary Compression Ignition Internal Combustion Engines..... 58

- E.4.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]

E.4.2 Standards of Performance for Stationary Compression Ignition Internal Combustion Engines
[40 CFR 60, Subpart IIII]

**E.5 SOURCE OPERATION CONDITIONS 40 CFR 63, Subpart ZZZZ - National Emissions Standards
for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines 60**

E.5.1 General Provisions Relating to National Emissions Standards for Hazardous Air Pollutants
[326 IAC 20-1] [40 CFR 63, Subpart A]

E.5.2 National Emissions Standards for Hazardous Air Pollutants for Stationary Compression
Ignition Internal Combustion Engines [40 CFR 63, Subpart ZZZZ]

Certification Form 62
Emergency Occurrence Form 63
Quarterly Report Forms 65-69
Quarterly Deviation and Compliance Monitoring Report Form 70
Affidavit of Construction 72

- Attachment A: Fugitive Dust Plan
- Attachment B: NSPS Subpart Db
- Attachment C: NSPS Subpart Kb
- Attachment D: NSPS Subpart VVa
- Attachment E: NSPS Subpart IIII
- Attachment F: NESHAP Subpart ZZZZ

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary ethanol production facility.

Source Address:	2265 East County Road 800 South, Ste. #1 Cloverdale, Indiana 46120
General Source Phone Number:	(765) 795-3235
SIC Code:	2869
County Location:	Putnam
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Federally Enforceable State Operating Permit Program Minor Source, under PSD and Emission Offset Rules Minor Source, Section 112 of the Clean Air Act Not 1 of 28 Source Categories

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

This stationary source consists of the following emission units and pollution control devices:

Grain Handling Process:

- (a) Three (3) truck dump pits, collectively identified as EU001, originally constructed in March 2008, obtaining new operation approval in 2010, with a combined maximum throughput rate of 50,000 bushels of corn per hour, controlled by baghouse CE001, and exhausting through stack SV001.
- (b) One (1) grain handling operation, originally constructed in March 2008, obtaining new operation approval in 2010, controlled by baghouse CE001, exhausting through stack SV001, and consisting of the following:
 - (1) One (1) grain conveyor, identified as EU002, with a maximum throughput rate of 50,000 bushels of grain per hour.
 - (2) One (1) grain elevator, identified as EU003, with a maximum throughput rate of 50,000 bushels of grain per hour.
- (c) Four (4) grain storage silos, with two (2) originally constructed in March 2008 and obtaining new operation approval in 2010, and two (2) approved for construction in 2010, identified as EU004 through EU007, with a total maximum combined capacity of 2,200,000 bushels, controlled by baghouse CE002, and exhausting through stack SV002.
- (d) One (1) scalper, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU008, with a maximum throughput rate of 6,000 bushels of grain per hour, controlled by the baghouse identified as CE003 and exhausting through stack SV003.
- (e) One (1) conveyor transfer and surge bin, originally constructed in March 2008, obtaining

new operation approval in 2010, identified as EU009, with a maximum throughput rate of 6,000 bushels of grain per hour, controlled by the baghouse identified as CE003 and exhausting through stack SV003.

- (f) Seven (7) hammermills, approved for construction in 2010, identified as EU010 through EU016, each with a maximum throughput rate of 23 tons per hour, controlled by baghouses CE004 through CE010, respectively, and exhausting through stacks SV004 through SV010, respectively.
- (g) One (1) DDGS truck loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU041, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.
- (h) One (1) DDGS rail loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU042, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.

Mash Preparation, Fermentation, Distillation, and Dehydration Process:

- (i) One (1) mash preparation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 for VOC/HAP controls, exhausting through stack SV011. This process consists of the following:

- (1) One (1) slurry tank, identified as EU017.
- (2) One (1) yeast propagation tank, identified as EU018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

- (j) One (1) fermentation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE012 for VOC/HAP controls, exhausting through stack SV012. This process consists of the following:

- (1) Six (6) fermenters, identified as EU019 through EU024.
- (2) Two (2) beer wells, identified as EU025 and EU026.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

- (k) One (1) distillation and dehydration process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum ethanol production of 72,000 gallons per hour, using wet scrubber CE013 for VOC control, exhausting through stack SV013. This process consists of the following:

- (1) One degas column, identified as EU027.
- (2) One (1) beer stripper, identified as EU028.

- (3) One (1) rectifier column, identified as EU029.
- (4) One (1) side stripper, identified as EU030.
- (5) One (1) set of three (3) molecular sieve, identified as EU031.
- (6) One (1) set of three (3) evaporators, identified as EU032.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

Evaporation Process, DDGS Dryer, & Cooling Process:

- (l) One (1) stillage process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum DDGS production of 567,648,0000 gallons per year; using two (2) 30 MMBtu/hr regenerative thermal oxidizers (CE015 & CE016) for VOC control, approved for construction in 2010, exhausting through stack SV014. This process consists of the following:
 - (1) One (1) set of four (4) centrifuges, identified as EU033, originally constructed in March 2008.
 - (2) Two (2) natural gas fired DDGS dryers, identified as EU034 and EU035, originally constructed in March 2008, each with a maximum heat input rate of 83 MMBtu/hr, and each with a total maximum throughput rate of 25 tons of DDGS per hour.
- (m) One (1) DDGS fluid bed cooler, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU038, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE014) for particulate control, with emissions vented to and controlled by RTOs CE015 & CE016, and exhausting to stack SV014.

Note: The RTO must occasionally be temporarily shut down for maintenance or other operational reasons. In this event, the DDGS dryers and fluid bed cooler will be shut down.
- (n) One (1) DDGS storage building/flat storage, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU039, using a baghouse (CE017) for particulate control, and exhausting to stack SV017.

Denatured Ethanol Storage and Loadout Racks:

- (o) One (1) ethanol loadout rack (two rail loadouts utilizing top loading only and one truck loadout utilizing submerged loading only), originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU043, with a maximum throughput rate of 118.25 million gallons per year. The loadout process is controlled by enclosed flare CE018, which is fueled by natural gas and has a maximum heat input capacity of 6.8 MMBtu per hour, and exhausting through stack SV018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

Natural Gas Fired Combustion Units:

- (p) Two (2) natural gas fired boilers, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU036 and EU037, each with a rated heat capacity of 145.3 MMBtu/hr, exhausting to stacks SV015 and SV016.

Under NSPS, 40 CFR 60, Subpart Db, these units are considered affected facilities.

Diesel Fired Combustion Unit:

- (q) One (1) diesel generator, approved for construction in 2010, identified as EU044, with a rated capacity of 2,000 KW, exhausting to SV019.

Under NSPS, Subpart IIII, this unit is considered an affected source.
Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

A.3 Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities:

- (a) Space heaters, process heaters, or boilers using the following fuels:
- (1) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour, including space heaters with a combined heat input capacity not to exceed 2.5 million (2,500,000) Btu per hour.
- (b) Other emission units, not regulated by a NESHAP, with PM₁₀, NO_x, and SO₂ emissions less than five (5) pounds per hour or twenty-five (25) pounds per day, CO emissions less than twenty-five (25) pounds per day, VOC emissions less than three (3) pounds per hour or fifteen (15) pounds per day, lead emissions less than six-tenths (0.6) tons per year or three and twenty-nine hundredths (3.29) pounds per day, and emitting greater than one (1) pound per day but less than five (5) pounds per day or one (1) ton per year of a single HAP, or emitting greater than one (1) pound per day but less than twelve and five tenths (12.5) pounds per day or two and five tenths (2.5) ton per year of any combination of HAPs:
- (1) One (1) denaturant storage tank, identified as T001, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum capacity of 180,000 gallons of 200-proof ethanol.
- Under NSPS, Subpart Kb, this unit is considered an affected facility.
- (2) One (1) 200 proof ethanol shift tank, identified as T002, originally constructed in March 2008, obtaining new operation approval in 2010, with a capacity of 180,000 gallons.
- Under NSPS, Subpart Kb, this unit is considered an affected facility.
- (3) Two (2) 200 proof ethanol storage tanks, identified as T003 and T004, originally constructed in March 2008, obtaining new operation approval in 2010, each with a maximum capacity of 1,000,000 gallons of denatured ethanol.
- Under NSPS, Subpart Kb, these units are considered affected facilities.
- (4) One (1) denaturant storage tank, identified as T005, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum capacity

of 60,000 gallons of denatured gasoline.

Under NSPS, Subpart Kb, this unit is considered an affected facility.

- (c) Solvent recycling systems with batch capacity less than or equal to 100 gallons.
- (d) Forced and induced draft cooling tower system not regulated under a NESHAP.
- (e) Replacement or repair of bags in baghouses and filters in other air filtration equipment.
- (f) Underground conveyors, including underground grain and product transfer conveyors.
- (g) Blowdown for any of the following: sight glass; boiler; compressors; pumps; and cooling tower.
- (h) Stationary fire pumps, including one (1) diesel fire pump, identified as EU045, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack SV020.

Under NSPS, Subpart IIII, this unit is considered an affected source.

Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

- (i) Grinding and machining operations controlled with fabric filters, scrubbers, mist collectors, wet collectors and electrostatic precipitators with a design grain loading of less than or equal to 0.03 grains per actual cubic foot and a gas flow rate less than or equal to 4000 actual cubic feet per minute, including the following: deburring, buffing, polishing, abrasive blasting, pneumatic conveying, and woodworking operations.
- (j) Paved roads and parking lots with public access. [326 IAC 6-4]

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) for a Federally Enforceable State Operating Permit (FESOP).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-8-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Revocation of Permits [326 IAC 2-1.1-9(5)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this permit if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

B.3 Affidavit of Construction [326 IAC 2-5.1-3(h)] [326 IAC 2-5.1-4][326 IAC 2-8]

This document shall also become the approval to operate pursuant to 326 IAC 2-5.1-4 and 326 IAC 2-8 when prior to the start of operation, the following requirements are met:

- (a) The attached Affidavit of Construction shall be submitted to the Office of Air Quality (OAQ), verifying that the emission units were constructed as proposed in the application or the permit. The emission units covered in this permit may begin operating on the date the Affidavit of Construction is postmarked or hand delivered to IDEM if constructed as proposed.
- (b) If actual construction of the emission units differs from the construction proposed in the application, the source may not begin operation until the permit has been revised pursuant to 326 IAC 2 and an Operation Permit Validation Letter is issued.
- (c) The Permittee shall attach the Operation Permit Validation Letter received from the Office of Air Quality (OAQ) to this permit.

B.4 Permit Term [326 IAC 2-8-4(2)][326 IAC 2-1.1-9.5][IC 13-15-3-6(a)]

-
- (a) This permit, F133-28725-00003, is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date of this permit.
 - (b) If IDEM, OAQ, upon receiving a timely and complete renewal permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, until the renewal permit has been issued or denied.

B.5 Term of Conditions [326 IAC 2-1.1-9.5]

Notwithstanding the permit term of a permit to construct, a permit to operate, or a permit modification, any condition established in a permit issued pursuant to a permitting program approved in the state implementation plan shall remain in effect until:

- (a) the condition is modified in a subsequent permit action pursuant to Title I of the Clean Air Act; or
- (b) the emission unit to which the condition pertains permanently ceases operation.

B.6 Enforceability [326 IAC 2-8-6] [IC 13-17-12]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.7 Severability [326 IAC 2-8-4(4)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.8 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.9 Duty to Provide Information [326 IAC 2-8-4(5)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.10 Certification [326 IAC 2-8-3(d)][326 IAC 2-8-4(3)(C)(i)][326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an "authorized individual" of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification. One (1) certification may cover multiple forms in one (1) submittal.
- (c) An "authorized individual" is defined at 326 IAC 2-1.1-1(1).

B.11 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

- (c) The annual compliance certification report shall include the following:
- (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.12 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.13 Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit or ninety (90) days after initial start-up, whichever is later, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The PMP extension notification does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or

potential to emit. The PMPs do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.14 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance and Enforcement Branch), or
Telephone Number: 317-233-0178 (ask for Compliance and Enforcement Branch)
Facsimile Number: 317-233-6865

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
 - (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
 - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
 - (e) The Permittee seeking to establish the occurrence of an emergency shall make records available upon request to ensure that failure to implement a PMP did not cause or contribute to an exceedance of any limitations on emissions. However, IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
 - (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
 - (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.
- Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.
- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report. Any emergencies that have been previously reported pursuant to paragraph (b)(5) of this condition and certified by an "authorized individual" need only be referenced by the date of the original report.

B.15 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of permits established prior to F133-28725-00003 and issued pursuant to permitting programs approved into the state implementation plan have been either:
- (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted.
- (b) All previous registrations and permits are superseded by this permit.

B.16 Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3(h)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

B.17 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.18 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)][326 IAC 2-8-7(a)][326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Federally Enforceable State Operating Permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
- (1) That this permit contains a material mistake.

- (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
- (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

B.19 Permit Renewal [326 IAC 2-8-3(h)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (b) A timely renewal application is one that is:
 - (1) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (2) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (c) If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.

B.20 Permit Amendment or Revision [326 IAC 2-8-10][326 IAC 2-8-11.1]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

Any such application shall be certified by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.21 Operational Flexibility [326 IAC 2-8-15][326 IAC 2-8-11.1]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-8-15(b) through (d) without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
- (3) The changes do not result in emissions which exceed the limitations provided in this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site, on a rolling five (5) year basis, which document all such changes and emission trades that are subject to 326 IAC 2-8-15(b) through (d). The Permittee shall make such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-8-15(b)(2), (c)(1), and (d).

- (b) Emission Trades [326 IAC 2-8-15(c)]
The Permittee may trade emissions increases and decreases at the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).
- (c) Alternative Operating Scenarios [326 IAC 2-8-15(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ, or U.S. EPA is required.
- (d) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.22 Source Modification Requirement [326 IAC 2-8-11.1]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2.

B.23 Inspection and Entry [326 IAC 2-8-5(a)(2)][IC 13-14-2-2][IC 13-17-3-2][IC 13-30-3-1]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.24 Transfer of Ownership or Operational Control [326 IAC 2-8-10]

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permit Administration and Support Section, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The application which shall be submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.25 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, Billing, Licensing, and Training Section), to determine the appropriate permit fee.

B.26 Advanced Source Modification Approval [326 IAC 2-8-4(11)] [326 IAC 2-1.1-9]

- (a) The requirements to obtain a permit modification under 326 IAC 2-8-11.1 are satisfied by this permit for the proposed emission units, control equipment or insignificant activities in Sections A.2 and A.3.
- (b) Pursuant to 326 IAC 2-1.1-9 any permit authorizing construction may be revoked if construction of the emission unit has not commenced within eighteen (18) months from the date of issuance of the permit, or if during the construction, work is suspended for a continuous period of one (1) year or more.

B.27 Credible Evidence [326 IAC 2-8-4(3)][326 IAC 2-8-5][62 FR 8314] [326 IAC 1-1-6]

For the purpose of submitting compliance certifications or establishing whether or not the Permittee has violated or is in violation of any condition of this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information relevant to whether the Permittee would have been in compliance with the condition of this permit if the appropriate performance or compliance test or procedure had been performed.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-8-4(1)]

C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) Pounds per Hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

(a) Pursuant to 326 IAC 2-8:

- (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one hundred (100) tons per twelve (12) consecutive month period.
- (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
- (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.

(b) Pursuant to 326 IAC 2-2 (PSD), potential to emit particulate matter (PM) from the entire source shall be limited to less than two hundred fifty (250) tons per twelve (12) consecutive month period.

(c) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.

(d) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A,

Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.5 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.6 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.7 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]

Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the attached plan as in Attachment A.

C.8 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

C.9 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).

- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and Renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).
- (g) **Indiana Licensed Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Licensed Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos.

Testing Requirements [326 IAC 2-8-4(3)]

C.10 Performance Testing [326 IAC 3-6]

- (a) Compliance testing on new emissions units shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the Permittee submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.11 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-8-4][326 IAC 2-8-5(a)(1)]

C.12 Compliance Monitoring [326 IAC 2-8-4(3)][326 IAC 2-8-5(a)(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance or ninety (90) days of initial start-up, whichever is later. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

C.13 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.14 Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-8-4(3)][326 IAC 2-8-5(1)]

- (a) When required by any condition of this permit, an analog instrument used to measure a parameter related to the operation of an air pollution control device shall have a scale such that the expected maximum reading for the normal range shall be no less than twenty percent (20%) of full scale.
- (b) The Permittee may request that the IDEM, OAQ approve the use of an instrument that does not meet the above specifications provided the Permittee can demonstrate that an alternative instrument specification will adequately ensure compliance with permit conditions requiring the measurement of the parameters.

Corrective Actions and Response Steps [326 IAC 2-8-4][326 IAC 2-8-5(a)(1)]

C.15 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.16 Response to Excursions or Exceedances [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) Upon detecting an excursion or exceedance, the Permittee shall restore operation of the emissions unit (including any control device and associated capture system) to its normal or usual manner of operation as expeditiously as practicable in accordance with good air pollution control practices for minimizing emissions.
- (b) The response shall include minimizing the period of any startup, shutdown or malfunction and taking any necessary corrective actions to restore normal operation and prevent the likely recurrence of the cause of an excursion or exceedance (other than those caused by excused startup or shutdown conditions). Corrective actions may include, but are not limited to, the following:
 - (1) initial inspection and evaluation;
 - (2) recording that operations returned to normal without operator action (such as through response by a computerized distribution control system); or
 - (3) any necessary follow-up actions to return operation to within the indicator range, designated condition, or below the applicable emission limitation or standard, as applicable.
- (c) A determination of whether the Permittee has used acceptable procedures in response to an excursion or exceedance will be based on information available, which may include, but is not limited to, the following:
 - (1) monitoring results;
 - (2) review of operation and maintenance procedures and records; and/or
 - (3) inspection of the control device, associated capture system, and the process.

- (d) Failure to take reasonable response steps shall be considered a deviation from the permit.
- (e) The Permittee shall maintain the following records:
 - (1) monitoring data;
 - (2) monitor performance data, if applicable; and
 - (3) corrective actions taken.

C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4][326 IAC 2-8-5]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance or ninety (90) days of initial start-up, whichever is later.

C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) The first report shall cover the period commencing on the date of issuance of this permit or the date of initial start-up, whichever is later, and ending on the last day of the reporting period. Reporting periods are based on calendar years, unless otherwise specified in this permit. For the purpose of this permit, "calendar year" means the twelve (12) month period from January 1 to December 31 inclusive.

Stratospheric Ozone Protection

C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description:

Grain and Handling Process:

- (a) Three (3) truck dump pits, collectively identified as EU001, originally constructed in March 2008, obtaining new operation approval in 2010, with a combined maximum throughput rate of 50,000 bushels of corn per hour, controlled by baghouse CE001, and exhausting through stack SV001.
- (b) One (1) grain handling operation, originally constructed in March 2008, obtaining new operation approval in 2010, controlled by baghouse CE001, exhausting through stack SV001, and consisting of the following:
 - (1) One (1) grain conveyor, identified as EU002, with a maximum throughput rate of 50,000 bushels of grain per hour.
 - (2) One (1) grain elevator, identified as EU003, with a maximum throughput rate of 50,000 bushels of grain per hour.
- (c) Four (4) grain storage silos, with two (2) originally constructed in March 2008 and obtaining new operation approval in 2010, and two (2) approved for construction in 2010, identified as EU004 through EU007, with a total maximum combined capacity of 2,200,000 bushels, controlled by baghouse CE002, and exhausting through stack SV002.
- (d) One (1) scalper, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU008, with a maximum throughput rate of 6,000 bushels of grain per hour, controlled by the baghouse identified as CE003 and exhausting through stack SV003.
- (e) One (1) conveyor transfer and surge bin, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU009, with a maximum throughput rate of 6,000 bushels of grain per hour, controlled by the baghouse identified as CE003 and exhausting through stack SV003.
- (f) Seven (7) hammermills, approved for construction in 2010, identified as EU010 through EU016, each with a maximum throughput rate of 23 tons per hour, controlled by baghouses CE004 through CE010, respectively, and exhausting through stacks SV004 through SV010, respectively.
- (g) One (1) DDGS truck loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU041, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.
- (h) One (1) DDGS rail loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU042, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

D.1.1 FESOP and PSD Limits [326 IAC 2-8-4] [326 IAC 2-2]

- (a) In order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM emissions from the following units shall not exceed the emission limits listed in the table below:

Unit ID	Stack ID	Unit Description	Baghouse ID	PM Emission Limit (lbs/hr)
EU001, EU002, EU003, EU041, EU042	SV001	Grain Receiving, Handling & DDGS Loading	CE001	1.14 (Combined)
EU004, EU005 EU006, EU007	SV002	Grain Storage Silos	CE002	0.69 (Combined)
EU008, EU009	SV003	Scalper and Conveyor Transfer / Surge Bin	CE003	0.24 (Combined)
EU010	SV004	Hammermill #1	CE004	0.41
EU011	SV005	Hammermill #2	CE005	0.41
EU012	SV006	Hammermill #3	CE006	0.41
EU013	SV007	Hammermill #4	CE007	0.41
EU014	SV008	Hammermill #5	CE008	0.41
EU015	SV009	Hammermill #6	CE009	0.41
EU016	SV010	Hammermill #7	CE010	0.41

- (b) Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM10 and PM2.5 emissions from the following units shall not exceed the emission limits listed in the table below:

Unit ID	Stack ID	Unit Description	Baghouse ID	PM10 Emission Limit (lbs/hr)	PM2.5 Emission Limit (lbs/hr)
EU001, EU002, EU003, EU041, EU042	SV001	Grain Receiving, Handling & DDGS Loading	CE001	1.14 (Combined)	1.14 (Combined)
EU004, EU005 EU006, EU007	SV002	Grain Storage Silos	CE002	0.69 (Combined)	0.69 (Combined)
EU008, EU009	SV003	Scalper and Conveyor Transfer / Surge Bin	CE003	0.24 (Combined)	0.24 (Combined)
EU010	SV004	Hammermill #1	CE004	0.41	0.41
EU011	SV005	Hammermill #2	CE005	0.41	0.41
EU012	SV006	Hammermill #3	CE006	0.41	0.41
EU013	SV007	Hammermill #4	CE007	0.41	0.41
EU014	SV008	Hammermill #5	CE008	0.41	0.41
EU015	SV009	Hammermill #6	CE009	0.41	0.41
EU016	SV010	Hammermill #7	CE010	0.41	0.41

Compliance with these PM limits in conjunction with the PM PTE from all other emission units shall limit the PM emissions from the entire source to less than 250 tons per year and therefore, render the requirements of 326 IAC 2-2 (PSD) not applicable.

Compliance with these PM10 and PM2.5 limits in conjunction with the PM10 and PM2.5 PTE emissions from all other emissions units shall limit the PM10 and PM2.5 emissions from the entire source to less than 100 tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not applicable.

D.1.2 Particulate Emission Limitations [326 IAC 6-3-2]

- (a) Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), particulate emissions from each of following operations shall not exceed the pound per hour limit listed in the table below:

Unit ID	Stack ID	Unit Description	Max. Throughput Rate (tons/hr)	Particulate Emission Limit (lbs/hr)
EU001	SV001	Three (3) Truck Dump Pits	1,400	82.02
EU002		Grain Conveyor	1,400	82.02
EU003		Grain Elevator	1,400	82.02
EU043		DDGS Truck Loading	400	66.31
EU044		DDGS Rail Loading	400	66.31
EU004	SV002	Grain Storage Silo	1,400	82.02
EU005		Grain Storage Silo	1,400	82.02
EU006		Grain Storage Silo	1,400	82.02
EU007		Grain Storage Silo	1,400	82.02
EU008	SV003	Scalper	168	56.64
EU009		Conveyor Transfer / Surge Bin	168	56.64
EU010	SV004	Hammermill #1	23	33.51
EU011	SV005	Hammermill #2	23	33.51
EU012	SV006	Hammermill #3	23	33.51
EU013	SV007	Hammermill #4	23	33.51
EU014	SV008	Hammermill #5	23	33.51
EU015	SV009	Hammermill #6	23	33.51
EU016	SV010	Hammermill #7	23	33.51

The pounds per hour limitations were calculated using the following equations:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

Interpolation and extrapolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P^{0.11} - 40 \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

- (b) Pursuant to 326 IAC 6-3-2(e)(3), when the process weight exceeds 200 tons per hour, the maximum allowable emission may exceed the emission limits shown in the table above, provided the concentration of particulate matter in the gas discharged to the atmosphere is less than 0.10 pounds per 1,000 pounds of gases.

D.1.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.1.4 Particulate Control

- (a) In order to comply with Conditions D.1.1(a) and (b), and D.1.2, the baghouses for particulate control shall be in operation and control emissions from the emission units at all times that the emission units are in operation as listed in the table below, when these units are in operation:

Unit ID	Unit Description	Baghouse ID
EU001, EU002, EU003, EU041, EU042	Grain Receiving, Handling & DDGS Loading	CE001
EU004, EU005 EU006, EU007	Grain Storage Silos	CE002
EU008, EU009	Scalper and Conveyor Transfer / Surge Bin	CE003
EU010	Hammermill #1	CE004
EU011	Hammermill #2	CE005
EU012	Hammermill #3	CE006
EU013	Hammermill #4	CE007
EU014	Hammermill #5	CE008
EU015	Hammermill #6	CE009
EU016	Hammermill #7	CE010

- (b) In the event that bag failure is observed in a multi-compartment baghouse, if operations will continue for ten (10) days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification.

D.1.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Conditions D.1.1(a) and D.1.2, the Permittee shall perform testing within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up according to what is listed below, and utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.
- (1) PM testing for baghouse CE001, which shall be controlling emissions from the grain receiving and handling, (EU001 through EU003) and DDGS loading (EU041 and EU042).
 - (2) PM testing for baghouse CE002, which shall be controlling emissions from the grain storage silos (EU004 through EU007).
 - (3) PM testing for baghouse CE003, which shall be controlling emissions from the scalper and conveyor transfer (EU008) and surge bin (EU009).
 - (4) PM testing for one of the baghouses (CE004 through CE010), which shall be controlling emissions from the respective hammermills (EU010 through EU016).
- (b) In order to demonstrate compliance with Conditions D.1.1(b), the Permittee shall perform testing within one hundred eighty (180) days of publication of the new or revised condensible PM test method(s) referenced in the U.S. EPA's Final Rule for Implementation of the New Source Review (NSR) Program for Particulate Matter Less Than 2.5 Micrometers (PM_{2.5}), signed on May 8th, 2008 or within 180 days after initial start-up, whichever is later. This testing shall be conducted utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing. PM₁₀ and PM_{2.5} includes filterable and condensible PM.

- (1) PM10 and PM2.5 testing for baghouse CE001, which shall be controlling emissions from the grain receiving and handling, (EU001 through EU003) and DDGS loading (EU041 and EU042).
- (2) PM10 and PM2.5 testing for baghouse CE002, which shall be controlling emissions from the grain storage silos (EU004 through EU007).
- (3) PM10 and PM2.5 testing for baghouse CE003, which shall be controlling emissions from the scalper and conveyor transfer (EU008) and surge bin (EU009).
- (4) PM10 and PM2.5 testing for one of the baghouses (CE004 through CE010), which shall be controlling emissions from the respective hammermills (EU010 through EU016).

Note: A different representative stack shall be tested during each compliance testing demonstration until such a time that all baghouse exhausts have been tested. The testing cycle will then begin again with the first baghouse tested.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.1.6 Visible Emissions Notations

- (a) Visible emission notations of the baghouse stack exhausts (stacks SV001 through SV010) shall be performed once per day during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed, the Permittee shall take reasonable steps in accordance with Section C – Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

D.1.7 Baghouse Parametric Monitoring

The Permittee shall record the pressure drop across the baghouses (CE001 through CE010) used in conjunction with the grain receiving, handling, DDGS loading operations (EU001 through EU003, EU041, and EU042), the grain storage silos (EU004 through EU007), scalper and conveyor transfer / surge bin (EU008 and EU009), and hammermills (EU010 through EU016), at least once per day when these units are in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 0.5 to 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Response to Excursions or Exceedances. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

The instrument used for determining the pressure shall comply with Section C - Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ and shall be calibrated or replaced at least once every six (6) months.

D.1.8 Broken or Failed Bag Detection [326 IAC 2-8-5(1)] [326 IAC 2-8-4(1)]

- (a) For a single compartment baghouse controlling emissions from a process operated continuously, a failed unit and the associated process shall be shut down immediately until the failed units has been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit has been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in emissions unit. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Bag failure can be indicated by a significant drop in the baghouse's pressure reading with abnormal visible emissions, by an opacity violation, or by other means such as gas temperature, flow rate, air infiltration, leaks, dust traces or triboflows.

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.1.9 Record Keeping Requirements

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain records of once per day visible emission notations of the baghouse stack exhausts. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g. the process did not operate that day).
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain once per day records of the pressure drop across the baghouses. The Permittee shall include in its daily record when a pressure drop reading is not taken and the reason for the lack of the pressure drop reading (e.g. the process did not operate that day).
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

SECTION D.2 EMISSIONS UNIT OPERATION CONDITIONS - Mash Preparation, Fermentation, Distillation, and Dehydration Process

Facility Description [326 IAC 2-8-4(10)]:

Mash Preparation, Fermentation, Distillation, and Dehydration Process:

- (i) One (1) mash preparation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 for VOC/HAP controls, exhausting through stack SV011. This process consists of the following:

- (1) One (1) slurry tank, identified as EU017.
- (2) One (1) yeast propagation tank, identified as EU018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

- (j) One (1) fermentation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE012 for VOC/HAP controls, exhausting through stack SV012. This process consists of the following:

- (1) Six (6) fermenters, identified as EU019 through EU024.
- (2) Two (2) beer wells, identified as EU025 and EU026.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

- (k) One (1) distillation and dehydration process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum ethanol production of 72,000 gallons per hour, using wet scrubber CE013 for VOC control, exhausting through stack SV013. This process consists of the following:

- (1) One degas column, identified as EU027.
- (2) One (1) beer stripper, identified as EU028.
- (3) One (1) rectifier column, identified as EU029.
- (4) One (1) side stripper, identified as EU030.
- (5) One (1) set of three (3) molecular sieve, identified as EU031.
- (6) One (1) set of three (3) evaporators, identified as EU032.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(The information describing the process contained in this facility description box is descriptive information

and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.2.1 FESOP VOC and HAP Emissions [326 IAC 2-2] [326 IAC 2-8-4] [326 IAC 2-4.1]

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) and 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) not applicable:

- (a) Mash Preparation Process:
 - (1) VOC emissions from scrubber CE011 shall not exceed 1.31 lb/hr.
 - (2) Combined HAP emissions from scrubber CE011 shall not exceed 0.15 lb/hr.
 - (3) Acetaldehyde emissions from scrubber CE011 shall not exceed 0.13 lb/hr.
- (b) Fermentation Process:
 - (1) VOC emissions from scrubber CE012 shall not exceed 8.69 lb/hr.
 - (2) Combined HAP emissions from scrubber CE012 shall not exceed 0.99 lb/hr.
 - (3) Acetaldehyde emissions from scrubber CE012 shall not exceed 0.87 lb/hr.
- (b) Distillation and Dehydration Process:
 - (1) VOC emissions from scrubber CE013 shall not exceed 0.81 lb/hr.
 - (2) Combined HAP emissions from scrubber CE013 shall not exceed 0.75 lb/hr.
 - (3) Acetaldehyde emissions from scrubber CE013 shall not exceed 0.62 lb/hr.

Compliance with these limits, combined with the VOC and HAP PTE from other units, shall limit the VOC emissions from the entire source to less than one hundred (100) tons per year, and shall limit the total HAP emissions from the entire source to less than ten (10) tons per year for a single HAP and less than twenty-five (25) tons per year for any combination of HAPs. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program), 326 IAC 2-2 (PSD), and 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) are not applicable.

D.2.2 VOC Emissions [326 IAC 8-5-6]

Pursuant to 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills), the Permittee shall comply with the following:

- (a) The VOC emissions from the mash preparation process shall be controlled at all times by wet scrubber CE011.
- (b) The overall control efficiency for the mash preparation wet scrubber (CE011) (including the capture efficiency and adsorption efficiency) shall be at least 98%, or the VOC outlet concentration shall not exceed 20 ppmv.
- (c) The VOC emissions from the fermentation process shall be controlled at all times by wet scrubber CE012.
- (d) The overall control efficiency for the fermentation wet scrubber (CE012) (including the capture efficiency and adsorption efficiency) shall be at least 98%, or the VOC outlet

concentration shall not exceed 20 ppmv.

- (e) The VOC emissions from the distillation and dehydration process shall be controlled by wet scrubber CE013.
- (f) The overall control efficiency for the distillation and dehydration wet scrubber (CE013) (including the capture efficiency and adsorption efficiency) shall be at least 98%, or the VOC outlet concentration shall not exceed 20 ppmv.

D.2.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.2.4 VOC and HAP Control

In order to comply with Conditions D.2.1 and D.2.2, the following shall apply:

- (a) The wet scrubber CE011 shall be in operation and control emissions from the mash preparation process at all times that this process is in operation.
- (b) The wet scrubber CE012 shall be in operation and control emissions from the fermentation process at all times that this process is in operation.
- (c) The wet scrubber CE013 shall be in operation and control emissions from the distillation and dehydration process at all times that this process is in operation.

D.2.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

In order to demonstrate compliance with Conditions D.2.1 and D.2.2, the Permittee shall perform VOC (including emission rate, destruction efficiency, and capture efficiency) and acetaldehyde testing for scrubbers CE011, CE012, and CE013 within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.2.6 Parametric Monitoring [326 IAC 8-5-6]

- (a) The Permittee shall monitor and record the flow rate of scrubbers CE011 and CE013 at least once per day when the associated processes are in operation. When for any one reading, the flow rate of any scrubber is less than the normal minimum stated in the table below, or a minimum established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. A flow rate that is below the above mentioned minimum is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

Scrubber ID	Associated Process	Minimum Flow Rate
CE011	Mash Preparation	3 gallons per minute
CE012	Fermentation	100 gallons per minute
CE013	Distillation & Dehydration	30 gallons per minute

- (b) The Permittee shall monitor and record the pressure drop across the scrubbers CE011,

CE012, and CE013 at least once per day when the associated processes are in operation. When for any one reading, the pressure drop across a scrubber is outside the normal range of 1.0 and 12.0 inches of water, or a minimum established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

The instruments used for determining the flow rate and pressure drop shall comply with Section C - Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated or replaced at least once every six (6) months.

D.2.7 Scrubber Detection

In the event that a scrubber malfunction has been observed:

Failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions). Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.2.8 Record Keeping Requirements

- (a) To document compliance with Condition D.2.6, the Permittee shall maintain once per day records of the flow rate and pressure drop for scrubbers CE011 and CE013 during normal operation. The Permittee shall include in its daily record when a flow rate reading or pressure drop reading is not taken and the reason for the lack of flow rate reading or pressure drop reading (e.g. the process did not operate that day).
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

SECTION D.3 EMISSIONS UNIT OPERATION CONDITIONS - Evaporation Process, DDGS Dryer and Cooling Process

Facility Description [326 IAC 2-8-4(10)]:

Evaporation Process, DDGS Dryer, & Cooling Process:

- (l) One (1) stillage process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum DDGS production of 567,648,0000 gallons per year; using two (2) 30 MMBtu/hr regenerative thermal oxidizers (CE015 & CE016) for VOC control, approved for construction in 2010, exhausting through stack SV014. This process consists of the following:
 - (1) One (1) set of four (4) centrifuges, identified as EU033, originally constructed in March 2008.
 - (2) Two (2) natural gas fired DDGS dryers, identified as EU034 and EU035, originally constructed in March 2008, each with a maximum heat input rate of 83 MMBtu/hr, and each with a total maximum throughput rate of 25 tons of DDGS per hour.
- (m) One (1) DDGS fluid bed cooler, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU038, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE014) for particulate control, with emissions vented to and controlled by RTOs CE015 & CE016, and exhausting to stack SV014.

Note: The RTO must occasionally be temporarily shut down for maintenance or other operational reasons. In this event, the DDGS dryers and fluid bed cooler will be shut down.
- (n) One (1) DDGS storage building/flat storage, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU039, using a baghouse (CE017) for particulate control, and exhausting to stack SV017.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

D.3.1 PSD Minor Limits [326 IAC 2-2]

- (a) In order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits for the RTOs (CE015 and CE016) which are used to control emissions from the DDGS dryers (EU034 and EU035), the DDGS fluid bed cooler (EU038), and the set of centrifuges (EU033):
 - (1) PM emissions shall not exceed 10.80 lbs/hr for stack SV014.
- (b) In order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM emissions from the following units shall not exceed the emission limits listed in the table below:

Unit	Stack ID	Unit Description	Control ID	PM Emission Limit (lbs/hr)
EU039	SV017	DDGS Storage Bldg. / Flat Storage	CE017	0.14

Compliance with these PM limits in conjunction with the limited PM PTE from other emission units shall limit the PM emissions from the entire source to less than 250 tons per year and therefore, render the requirements of 326 IAC 2-2 (PSD) not applicable.

D.3.2 FESOP Limits [326 IAC 2-8-4]

- (a) Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC

2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits for the RTOs (CE015 and CE016) which are used to control emissions from the DDGS dryers (EU034 and EU035), the DDGS fluid bed cooler (EU038), and the set of centrifuges (EU033):

- (1) PM10 emissions shall not exceed 10.80 lbs/hr for stack SV014.
 - (2) PM2.5 emissions shall not exceed 10.80 lb/hrs for stack SV014.
 - (3) VOC emissions shall not exceed 4.83 lbs/hr for stack SV014.
 - (4) CO emissions shall not exceed 15.10 lbs/hr for stack SV014.
 - (5) SO2 emissions shall not exceed 13.63 lbs/hr for stack SV014.
 - (6) NOx emissions shall not exceed 12.03 lbs/hr for stack SV014.
 - (7) Acetaldehyde emissions shall not exceed 0.53 lbs/hr for stack SV014.
 - (9) Total HAP emissions shall not exceed 1.10 lbs/hr for stack SV014.
- (b) Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM10 and PM2.5 emissions from the following units shall not exceed the emission limits listed in the table below:

Unit ID	Stack ID	Unit Description	Control ID	PM10 Emission Limit (lbs/hr)	PM2.5 Emission Limit (lbs/hr)
EU039	SV017	DDGS Storage Bldg. / Flat Storage	CE017	0.14	0.14

Compliance with these limits, combined with the limited PM10, PM2.5, VOC, SO2, CO, NOx, and HAP PTE from other units, the PM10, PM2.5, VOC, SO2, CO, and NOx emissions from the entire source shall be limited to less than one hundred (100) tons per year, and the total HAP emissions from the entire source are limited to less than ten (10) tons per year for a single HAP and less than twenty-five (25) tons per year for any combination of HAPs. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) and are not applicable.

D.3.3 VOC Emissions [326 IAC 8-5-6]

Pursuant to 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills), the Permittee shall comply with the following:

- (a) The VOC emissions from the DDGS Dryers (EU034 and EU035), shall be controlled by the RTOs identified as CE015 and CE016 at all times.
- (b) The overall control efficiency, including the capture efficiency and destruction efficiency, of RTOs CE015 and CE016 shall each be at least 98%, or the VOC outlet concentration shall not exceed 10 ppmv.

D.3.4 Particulate Emission Limitations [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), particulate emissions from each of following operations shall not exceed the pound per hour limit listed in the table below:

Unit ID	Unit Description	Max. Throughput Rate (tons/hr)	Particulate Emission Limit (lbs/hr)
EU034	DDGS Dryer	25	35.43
EU035	DDGS Dryer	25	35.43
EU038	DDGS Cooler	40	42.53
EU039	DDGS Storage Bldg. / Flat Storage	40	42.53

The pounds per hour limitations were calculated using the following equations:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

Interpolation and extrapolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P^{0.11} - 40 \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.3.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.3.6 VOC and HAP Control

In order to comply with Conditions D.3.24 and D.3.3, the thermal oxidizers CE015 and CE016 shall be in operation and control emissions from the DDGS dryers (EU034 and EU035) and the DDGS fluid bed cooler (EU038), at all times that these units are in operation.

D.3.7 Particulate Control

- (a) In order to comply with Conditions D.3.1(a), D.3.2(a), and D.3.4, the baghouse (CE014) for particulate control shall be in operation and control emissions from the DDGS cooler (EU038) at all times that the DDGS cooler (EU038) is in operation.
- (b) In order to comply with the Conditions in D.3.1(b), D.3.2(b), and D.3.4, the baghouse (CE017) for particulate control shall be in operation and control emissions from DDGS Storage Building / Flat Storage (EU039) at all times this unit is in operation.
- (c) In the event that bag failure is observed in a multi-compartment baghouse, if operations will continue for ten (10) days or more after the failure is observed before the failed units will be repaired or replaced, the Permittee shall promptly notify the IDEM, OAQ of the expected date the failed units will be repaired or replaced. The notification shall also include the status of the applicable compliance monitoring parameters with respect to normal, and the results of any response actions taken up to the time of notification

D.3.8 Testing Requirements [326 IAC 2-8-5(a)(1),(4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

In order to demonstrate compliance with Conditions D.3.1, D.3.2, D.3.3, and D.3.4, the Permittee shall perform:

- (a) PM testing for the RTO common stack (SV014) within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up,

utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

- (b) PM10 and PM2.5 testing for the RTO common stack (SV014), within one hundred eighty (180) days of publication of the new or revised condensible PM test method(s) referenced in the U.S. EPA's Final Rule for Implementation of the New Source Review (NSR) Program for Particulate Matter Less Than 2.5 Micrometers (PM2.5), signed on May 8th, 2008 or within 180 days after initial start-up, whichever is later. This testing shall be conducted utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing. PM10 and PM2.5 includes filterable and condensible PM.
- (c) PM testing for the DDGS Storage Building / Flat Storage (EU039) within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.
- (d) PM10 and PM2.5 testing for the DDGS Storage Building / Flat Storage (EU039), within one hundred eighty (180) days of publication of the new or revised condensible PM test method(s) referenced in the U.S. EPA's Final Rule for Implementation of the New Source Review (NSR) Program for Particulate Matter Less Than 2.5 Micrometers (PM2.5), signed on May 8th, 2008 or within 180 days of start-up, whichever is later. This testing shall be conducted utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing. PM10 and PM2.5 includes filterable and condensible PM.
- (e) VOC (including emission rate, destruction efficiency, and capture efficiency), NOx, CO, and Acetaldehyde testing for the RTO common stack (SV014) within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.3.9 Visible Emissions Notations

-
- (a) Visible emission notations of the stack exhausts from SV014 and SV017, shall be performed once per day during normal daylight operations. A trained employee or a trained contractor shall record whether emissions are normal or abnormal.
 - (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
 - (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
 - (d) A trained employee or contractor is a person who has worked or trained at the plant at least one (1) month and has been trained in the appearance and characteristics of

normal visible emissions for that specific process.

- (e) If abnormal emissions are observed, the Permittee shall take reasonable response steps in accordance with Section C- Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

D.3.10 Baghouse Parametric Monitoring

The Permittee shall record the pressure drop across the baghouses CE014 and CE017 used in conjunction with the DDGS cooling operation (EU038) and DDGS Storage Building / Flat Storage (EU039) at least once per day when the emissions units are in operation. When for any one reading, the pressure drops across the baghouses are outside the normal range of 0.5 to 6.0 inches of water or a range established during the most recent stack tests, the Permittee shall take reasonable response steps in accordance with Section C- Response to Excursions or Exceedances. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

The instrument used for determining the pressure shall comply with Section C - Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ and shall be calibrated or replaced at least once every six (6) months.

D.3.11 Broken or Failed Bag Detection [326 IAC 2-8-5(1)] [326 IAC 2-8-4(1)]

- (a) For a single compartment baghouse controlling emissions from a process operated continuously, a failed unit and the associated process shall be shut down immediately until the failed units has been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For a single compartment baghouse controlling emissions from a batch process, the feed to the process shall be shut down immediately until the failed unit has been repaired or replaced. The emissions unit shall be shut down no later than the completion of the processing of the material in emissions unit. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Bag failure can be indicated by a significant drop in the baghouse's pressure reading with abnormal visible emissions, by an opacity violation, or by other means such as gas temperature, flow rate, air infiltration, leaks, dust traces or triboflows.

D.3.12 Thermal Oxidation Temperature [326 IAC 8-5-6]

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on both RTOs (CE015 and CE016) for measuring operating temperature. For the purpose of this condition, continuous means no less than once per minute. The output of this system shall be recorded as 3-hour average. From the date of issuance of this permit until the approved stack test results are available, the Permittee shall operate both RTOs (CE015 and CE016) at or above the 3-hour average temperature of 1,400°F.
- (b) The Permittee shall determine the 3-hour average temperatures from the most recent valid stack test that demonstrates compliance with limits in Conditions D.3.2 and D.3.3 as approved by IDEM.
- (c) On and after the date the approved stack test results are available, the Permittee shall operate both RTOs (CE015 and CE016) at or above the 3-hour average temperature as observed during the compliant stack test.

D.3.13 Parametric Monitoring [326 IAC 8-5-6]

- (a) The Permittee shall determine the appropriate duct pressure or fan amperage from the most recent valid stack test that demonstrates compliance with limits in Conditions D.3.2 and D.3.3.
- (b) The duct pressure or fan amperage shall be observed at least once per day when the RTOs are in operation. On and after the date the approved stack test results are available, the duct pressure or fan amperage shall be maintained within the normal range as established in most recent compliant stack test.

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.3.14 Record Keeping Requirements

- (a) To document compliance with Condition D.3.9, the Permittee shall maintain records of once per day visible emission notations of stacks SV014 and SV017. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g. the process did not operate that day).
- (b) To document compliance with Condition D.3.10, the Permittee shall maintain once per day records of the pressure drop across the baghouses CE014 and CE017. The Permittee shall include in its daily record when a pressure drop reading is not taken and the reason for the lack of the pressure drop reading (e.g. the process did not operate that day).
- (c) To document compliance with Condition D.3.12, the Permittee shall maintain continuous temperature records for the RTOs (CE015 and CE016) and the 3-hour average temperature used to demonstrate compliance during the most recent compliant stack test.
- (d) To document compliance with Condition D.3.13, the Permittee shall maintain daily records of the duct pressure or fan amperage for the RTOs (CE015 and CE016). The Permittee shall include in its daily record when a duct pressure reading or fan amperage reading is not taken and the reason for the lack of a duct pressure reading or fan amperage reading (e.g. the process did not operate that day).
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

SECTION D.4 EMISSIONS UNIT OPERATION CONDITIONS - Denatured Ethanol Loading Racks

Facility Description [326 IAC 2-8-4(10)]:

Denatured Ethanol Storage and Loadout Racks:

- (p) One (1) ethanol loadout rack (two rail loadouts utilizing top loading only and one truck loadout utilizing submerged loading only), originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU043, with a maximum throughput rate of 118.25 million gallons per year. The loadout process is controlled by enclosed flare CE018, which is fueled by natural gas and has a maximum heat input capacity of 6.8 MMBtu per hour, and exhausting through stack SV018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.4.1 FESOP Limits [326 IAC 2-8-4] [326 IAC 2-2]

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits for the ethanol loading rack (EU045):

- (a) The total combined load-out rate of denatured ethanol and E-85 associated with the ethanol loading rack (EU043) shall not exceed 118,250,000 gallons per twelve consecutive month period, with compliance determined at the end of each month.
- (b) The E-85 load-out rate associated with the ethanol loading rack (EU043) shall not exceed 14,300,000 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- (c) VOC emissions associated with the loading rack (EU043) shall not exceed 0.131 pounds per thousand gallons.
- (d) The NOx emissions associated with the ethanol loading rack (EU043) shall not exceed 0.0334 pounds per thousand gallons.
- (e) The CO emissions associated with the ethanol loading rack (EU043) shall not exceed 0.084 pounds per thousand gallons.

Compliance with these limits, combined with the limited VOC, CO, NOx, and HAP PTE from other units, the VOC, CO, and NOx, emissions from the entire source shall be limited to less than one hundred (100) tons per year, and the total HAP emissions from the entire source shall be limited to less than ten (10) tons per year for a single HAP and less than twenty-five (25) tons per year for any combination of HAPs. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) 326 IAC 2-2 (PSD) are not applicable.

D.4.2 VOC Emissions [326 IAC 8-5-6]

Pursuant to 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills), the Permittee shall comply with the following:

- (a) The Permittee shall use flare CE018 to control the emissions from the ethanol loading rack (EU043) when loading denatured ethanol and/or E-85 to trucks.
- (b) The Permittee shall use flare CE018 to control emissions from the ethanol loading rack (EU043) when loading denatured ethanol and/or E-85 to railcars.
- (c) The overall control efficiency, including the capture efficiency and destruction efficiency, for the enclosed flare (CE018) shall be at least 98%.

D.4.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.4.4 VOC Control

In order to comply with Conditions D.4.1 and D.4.2, the enclosed flare CE018 shall be in operation and control emissions from the ethanol loading rack (EU043) at all times when denatured ethanol and/or E-85 is being loaded to trucks or railcars.

D.4.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

In order to demonstrate compliance with Conditions D.4.1(e), (f), and (g), and D.4.2(c) associated with the ethanol loading rack (EU043), the Permittee shall perform VOC (including emission rate, destruction efficiency, and capture efficiency), CO, and NO_x testing for enclosed flare CE018 within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the last valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.4.6 Visible Emissions Notations

- (a) Visible emission notations of the flare (CE018) stack exhaust (SV018) shall be performed once per day during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) If abnormal emissions are observed, the Permittee shall take reasonable steps in accordance with Section C – Response to Excursions or Exceedances. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

D.4.7 Flare Pilot Flame [326 IAC 8-5-6]

In order to comply with Conditions D.4.1 and D.4.2, the Permittee shall monitor the presence of a flare pilot flame using a thermocouple or any other equivalent device to detect the presence of a flame when the ethanol loading rack (EU043) is in operation and loading denatured ethanol and/or E-85 to trucks or railcars.

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.4.8 Record Keeping Requirements

- (a) To document compliance with Condition D.4.1(a), the Permittee shall maintain monthly records of the amount of denatured ethanol and E-85 loaded out by truck and rail at the ethanol loading rack (EU043).
- (b) To document compliance with Condition D.4.1(b), the Permittee shall maintain monthly records of the amount of E-85 loaded out by truck and rail at the ethanol loading rack (EU043).
- (c) To document compliance with Condition D.4.6, the Permittee shall maintain records of once per day visible emission notations of stack SV018. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g. the process did not operate that day).
- (d) To document compliance with Condition D.4.7, the Permittee shall maintain records of temperature or other parameters sufficient to demonstrate the presence of a pilot flame when the ethanol loading rack is in operation.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.4.9 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.4.1(a) and (b) shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

SECTION D.5 - EMISSIONS UNIT OPERATION CONDITIONS - Natural Gas Fired Combustion Units

Facility Description [326 IAC 2-8-4(10)]:

Natural Gas Fired Combustion Units:

- (p) Two (2) natural gas fired boilers, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU036 and EU037, each with a rated heat capacity of 145.3 MMBtu/hr, exhausting to stacks SV015 and SV016.

Under NSPS, 40 CFR 60, Subpart Db, these units are considered affected facilities.

Insignificant Activity:

- (a) Space heaters, process heaters, or boilers using the following fuels:
- (1) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour, including space heaters with a combined heat input capacity not to exceed 2.5 million (2,500,000) Btu per hour.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.5.1 FESOP Nitrogen Oxides (NO_x) and Carbon Monoxide (CO) Limits [326 IAC 2-8-4] [326 IAC 2-2]

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the following conditions shall apply:

- (a) The boilers (EU036 and EU037) shall only burn natural gas.
- (b) The total input of the natural gas to the boilers (EU036 and EU037) shall not exceed 2545.7 MMCF per twelve (12) consecutive month period, with compliance determined at the end of each month.
- (c) NO_x emissions from fuel combustion shall not exceed 30 pounds per MMCF.
- (d) CO emissions from fuel combustion shall not exceed 20 pounds per MMCF.

Compliance with these limits combined with the NO_x and CO PTE from all other units, the NO_x and CO emissions from the entire source shall be limited to less than one hundred (100) tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not applicable.

D.5.2 Particulate Emissions [326 IAC 6-2-4] [326 IAC 2-8-4] [326 IAC 2-2]

Pursuant to 326 IAC 6-2-4 (Particulate Emission Limitations for Sources of Indirect Heating: Emission Limitations for facilities specified in 326 IAC 6-2-1(d)), the PM emissions from the boilers EU036 and EU037 shall not exceed 0.249 pounds per million Btu heat input (lb/MMBtu). This limitation was calculated using the following equation:

$$Pt = \frac{1.09}{Q^{0.26}}$$

where Q = total source heat input capacity (MMBtu/hr)

For these units, $Q = 290.6$ MMBtu/hr.

D.5.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and their control devices.

Compliance Determination Requirements

D.5.4 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11]

In order to demonstrate compliance with Conditions D.5.1(c) and D.5.1(d), the Permittee shall perform CO testing for the boilers (EU036 and EU037) within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.5.5 Record Keeping Requirements

- (a) In order to demonstrate compliance with Condition D.5.1(b) the Permittee shall record the quantity of natural gas combusted at the boilers.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.5.6 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.5.1(b) shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

SECTION D.6 - EMISSIONS UNIT OPERATION CONDITIONS - Diesel Fired Combustion Units

Facility Description [326 IAC 2-8-4(10)]:

- (q) One (1) diesel generator, approved for construction in 2010, identified as EU044, with a rated capacity of 2,000 KW, exhausting to SV019.

Under NSPS, Subpart IIII, this unit is considered an affected source.

Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

Insignificant Activities:

- (h) Stationary fire pumps, including one (1) diesel fire pump, identified as EU045, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack SV020.

Under NSPS, Subpart IIII, this unit is considered an affected source.

Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.6.1 FESOP Limits [326 IAC 2-8-4] [326 IAC 2-2]

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits:

- (a) The diesel generator (EU044) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.
- (b) The diesel fire pump (EU045) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with these limits, combined with the NO_x, CO, and SO₂ PTE from all other units, the NO_x, CO, and SO₂ emissions from the entire source shall be limited to less than one hundred (100) tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not applicable.

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.6.2 Record Keeping Requirements

- (a) To document compliance with Condition D.6.1(a), the Permittee shall maintain records of the number of hours that the diesel generator (EU044) operates each month.
- (b) To document compliance with Condition D.6.1(b), the Permittee shall maintain records of the number of hours that the diesel fire pump (EU045) operates each month.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.6.3 Reporting Requirements

The monthly hours of operation of the diesel generator (EU044) and diesel fire pump (EU045) shall be submitted quarterly to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or its equivalent, within

thirty (30) days after the end of the six (6) month period being reported. The report submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1.

SECTION E.1 FACILITY OPERATION CONDITIONS - 40 CFR 60, Subpart Db - Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units

Facility Description [326 IAC 2-8-4(10)]:

- (p) Two (2) natural gas fired boilers, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU036 and EU037, each with a rated heat capacity of 145.3 MMBtu/hr, exhausting to stacks SV015 and SV016.

Under NSPS, 40 CFR 60, Subpart Db, these units are considered affected facilities.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

E.1.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]

- (a) The Permittee shall comply with the provisions of 40 CFR Part 60, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 12, for the Industrial-Commercial-Institutional Steam Generating Units, as specified in 40 CFR 60, Subpart Db in accordance with the schedule in 40 CFR 60, Subpart Db.

- (b) Pursuant to 40 CFR 60.19, the Permittee shall submit all required notifications and reports to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Ave.
MC61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

E.1.2 Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units [40 CFR 60, Subpart Db] [326 IAC 12]

The Permittee shall comply with the following provisions of 40 CFR Part 60, Subpart Db (included as Attachment B) which are incorporated by reference as 326 IAC 12 for the Industrial-Commercial-Institutional Steam Generating Units:

- (1) 40 CFR 60.40b (a), (g), and (j)
- (2) 40 CFR 60.41b
- (3) 40 CFR 60.44b (a), (h), and (i)
- (4) 40 CFR 60.46b (a), (c), and (e) (1)
- (5) 40 CFR 60.48b (b)(1), (c), (d), (e)(2), (f), and (g)
- (6) 40 CFR 60.49b (a) (1), and (3), (b), (c), (d), (g), (i), (v) and (w)

SECTION E.2 FACILITY OPERATION CONDITIONS - 40 CFR 60, Subpart Kb - Standards of Performance for Volatile Organic Liquid Storage Vessels for which Construction, Reconstruction, or Modification Commenced after July 23, 1984

Facility Description [326 IAC 2-8-4(10)]:

Insignificant Activities:

(b) Other emission units, not regulated by a NESHAP, with PM₁₀, NO_x, and SO₂ emissions less than five (5) pounds per hour or twenty-five (25) pounds per day, CO emissions less than twenty-five (25) pounds per day, VOC emissions less than three (3) pounds per hour or fifteen (15) pounds per day, lead emissions less than six-tenths (0.6) tons per year or three and twenty-nine hundredths (3.29) pounds per day, and emitting greater than one (1) pound per day but less than five (5) pounds per day or one (1) ton per year of a single HAP, or emitting greater than one (1) pound per day but less than twelve and five tenths (12.5) pounds per day or two and five tenths (2.5) ton per year of any combination of HAPs:

(1) One (1) denaturant storage tank, identified as T001, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum capacity of 180,000 gallons of 200-proof ethanol.

Under NSPS, Subpart Kb, this unit is considered an affected facility.

(2) One (1) 200 proof ethanol shift tank, identified as T002, originally constructed in March 2008, obtaining new operation approval in 2010, with a capacity of 180,000 gallons.

Under NSPS, Subpart Kb, this unit is considered an affected facility.

(3) Two (2) 200 proof ethanol storage tanks, identified as T003 and T004, originally constructed in March 2008, obtaining new operation approval in 2010, each with a maximum capacity of 1,000,000 gallons of denatured ethanol.

Under NSPS, Subpart Kb, these units are considered affected facilities.

(4) One (1) denaturant storage tank, identified as T005, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum capacity of 60,000 gallons of denatured gasoline.

Under NSPS, Subpart Kb, this unit is considered an affected facility.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

E.2.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]

(a) The Permittee shall comply with the provisions of 40 CFR Part 60, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 12, for the Volatile Organic Liquid Storage Vessels for which Construction, Reconstruction, or Modification Commenced after July 23, 1984, as specified in 40 CFR 60, Subpart Kb in accordance with the schedule in 40 CFR 60, Subpart Kb.

(b) Pursuant to 40 CFR 60.19, the Permittee shall submit all required notifications and reports to:

Indiana Department of Environmental Management

Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Ave.
MC61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

E.2.2 Standards of Performance for Volatile Organic Liquid Storage Vessels for which Construction, Reconstruction, or Modification Commenced after July 23, 1984 [40 CFR 60, Subpart Kb] [326 IAC 12]

The Permittee shall comply with the following provisions of 40 CFR Part 60, Subpart Kb (included as Attachment C) which are incorporated by reference as 326 IAC 12 for the Volatile Organic Liquid Storage Vessels for which Construction, Reconstruction, or Modification Commenced after July 23, 1984:

- (1) 40 CFR 60.110b (a), (b), (d) (2), (3), (7) and (8), (e)(1)(i), (2) and (3)
- (2) 40 CFR 60.111b
- (3) 40 CFR 60.112b(a)(1)
- (4) 40 CFR 60.113b(a)
- (5) 40 CFR 60.115b(a)
- (6) 40 CFR 60.116b(a) through (c), and (e)
- (7) 40 CFR 60.117b

SECTION E.3 FACILITY OPERATION CONDITIONS - 40 CFR 60, Subpart VVa - Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006

Facility Description [326 IAC 2-8-4(10)]:

(i) One (1) mash preparation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 for VOC/HAP controls, exhausting through stack SV011. This process consists of the following:

- (1) One (1) slurry tank, identified as EU017.
- (2) One (1) yeast propagation tank, identified as EU018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(j) One (1) fermentation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE012 for VOC/HAP controls, exhausting through stack SV012. This process consists of the following:

- (1) Six (6) fermenters, identified as EU019 through EU024.
- (2) Two (2) beer wells, identified as EU025 and EU026.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(k) One (1) distillation and dehydration process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum ethanol production of 72,000 gallons per hour, using wet scrubber CE013 for VOC control, exhausting through stack SV013. This process consists of the following:

- (1) One degas column, identified as EU027.
- (2) One (1) beer stripper, identified as EU028.
- (3) One (1) rectifier column, identified as EU029.
- (4) One (1) side stripper, identified as EU030.
- (5) One (1) set of three (3) molecular sieve, identified as EU031.
- (6) One (1) set of three (3) evaporators, identified as EU032.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(o) One (1) ethanol loadout rack (two rail loadouts utilizing top loading only and one truck loadout utilizing submerged loading only), originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU043, with a maximum throughput rate of 118.25 million gallons per year. The loadout process is controlled by enclosed flare CE018, which is fueled by natural gas and has a maximum heat input capacity of 6.8 MMBtu per hour, and exhausting through stack SV018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

E.3.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]

(a) The Permittee shall comply with the provisions of 40 CFR Part 60, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 12, for the sources of equipment leaks of VOC, as specified in 40 CFR 60, Subpart VVa in accordance with the schedule in 40 CFR 60, Subpart VVa.

(b) Pursuant to 40 CFR 60.19, the Permittee shall submit all required notifications and reports to :

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Ave.
MC61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

E.3.2 Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry [40 CFR 60, Subpart VV] [326 IAC 12]

The Permittee shall comply with the following provisions of 40 CFR Part 60, Subpart VVa (included as Attachment D) which are incorporated by reference as 326 IAC 12 for the sources of equipment leaks of VOC:

- (1) 40 CFR 60.480a
- (2) 40 CFR 60.481a
- (3) 40 CFR 60.482-1a
- (4) 40 CFR 60.482-2a
- (5) 40 CFR 60.482-3a
- (6) 40 CFR 60.482-4a
- (7) 40 CFR 60.482-5a
- (8) 40 CFR 60.482-6a
- (9) 40 CFR 60.482-7a
- (10) 40 CFR 60.482-8a
- (11) 40 CFR 60.482-9a
- (12) 40 CFR 60.482-10a
- (13) 40 CFR 60.482-11a
- (14) 40 CFR 60.483-1a
- (15) 40 CFR 60.483-2a
- (16) 40 CFR 60.484a
- (17) 40 CFR 60.485a
- (18) 40 CFR 60.486a
- (19) 40 CFR 60.487a

- (20) 40 CFR 60.488a
- (21) 40 CFR 60.489a

SECTION E.4 FACILITY OPERATION CONDITIONS - 40 CFR 60, Subpart IIII - Standards of Performance for Stationary Compression Ignition (CI) Internal Combustion Engines (ICE)

Facility Description [326 IAC 2-8-4(10)]:

Emission Units:

- (g) One (1) diesel generator, approved for construction in 2010, identified as EU044, with a rated capacity of 2,000 KW, exhausting to SV019.

Under NSPS, Subpart IIII, this unit is considered an affected source.
Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

Insignificant Activities:

- (h) Stationary fire pumps, including one (1) diesel fire pump, identified as EU045, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack SV020.

Under NSPS, Subpart IIII, this unit is considered an affected source.
Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

E.4.1 General Provisions Relating to New Source Performance Standards [326 IAC 12-1] [40 CFR 60, Subpart A]

- (a) The Permittee shall comply with the provisions of 40 CFR Part 60, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 12, for the stationary compression ignition internal combustion engines, as specified in 40 CFR 60, Subpart IIII in accordance with the schedule in 40 CFR 60, Subpart IIII.
- (b) Pursuant to 40 CFR 60.19, the Permittee shall submit all required notifications and reports to:
- Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

E.4.2 Standards of Performance for Stationary Compression Ignition Internal Combustion Engines [40 CFR 60, Subpart IIII]

The Permittee shall comply with the following provisions of 40 CFR Part 60, Subpart IIII (included as Attachment E) which are incorporated by reference as 326 IAC 12 for the stationary compression ignition (CI) internal combustion engines (ICE):

EU044 is subject to the following portions of 40 CFR 60, Subpart IIII:

- (1) 40 CFR 60.4200 (a)(1)(i) and (c)
- (2) 40 CFR 60.4205 (b)
- (3) 40 CFR 60.4206
- (4) 40 CFR 60.4207 (a),(b),(c)
- (5) 40 CFR 60.4208

- (6) 40 CFR 60.4209
- (7) 40 CFR 60.4211 (a),(c),(e)
- (8) 40 CFR 60.4212
- (9) 40 CFR 60.4214 (b),(c)
- (10) 40 CFR 60.4218
- (11) 40 CFR 60.4219
- (12) Table 2
- (13) Table 6
- (14) Table 8

EU045 is subject to the following portions of 40 CFR 60, Subpart IIII.

- (1) 40 CFR 4200 (a) (2) and (3), (b), and (c)
- (2) 40 CFR 4205 (c)
- (3) 40 CFR 4206
- (4) 40 CFR 4207 (a), (b), and (c)
- (5) 40 CFR 4209
- (6) 40 CFR 4211 (a), (b) (1) through (4), and (e)
- (7) 40 CFR 4214 (b) and (c)
- (8) 40 CFR 4218
- (9) 40 CFR 4219
- (10) Table 4
- (11) Table 8

SECTION E.5 FACILITY OPERATION CONDITIONS - 40 CFR 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE)

Facility Description [326 IAC 2-8-4(10)]:

Emission Units:

- (r) One (1) diesel generator, approved for construction in 2010, identified as EU044, with a rated capacity of 2,000 KW, exhausting to SV019.

Under NSPS, Subpart IIII, this unit is considered an affected source.

Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

Insignificant Activities:

- (h) Stationary fire pumps, including one (1) diesel fire pump, identified as EU045, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack SV020.

Under NSPS, Subpart IIII, this unit is considered an affected source.

Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

National Emissions Standards for Hazardous Air Pollutants (NESHAP) Requirements: Stationary Reciprocating Internal Combustion Engines

E.5.1 General Provisions Relating to National Emissions Standards for Hazardous Air Pollutants under 40 CFR Part 63 [326 IAC 20-1] [40 CFR Part 63, Subpart A]

- (a) Pursuant to 40 CFR 63.340(b), the Permittee shall comply with the provisions of 40 CFR Part 63, Subpart A – General Provisions, which are incorporated by reference as 326 IAC 20-82, for the reciprocating internal combustion engines as specified in Table 8 of 40 CFR Part 63, Subpart ZZZZ in accordance with the schedule in 40 CFR 63, Subpart ZZZZ.

- (b) Pursuant to 40 CFR 63.10, the Permittee shall submit all required notifications and reports to:

Indiana Department of Environmental Management
Compliance and Enforcement Branch, Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

E.5.2 National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines [40 CFR Part 63, Subpart ZZZZ]

The Permittee shall comply with the following provisions of 40 CFR Part 63, Subpart ZZZZ (included as Attachment F) which are incorporated by reference as 326 IAC 20-82 for the reciprocating internal combustion engine:

EU044 is subject to the following portions of 40 CFR 63, Subpart ZZZZ:

- (1) 40 CFR 63.6580
- (2) 40 CFR 63.6585(a),(c),(d)
- (3) 40 CFR 63.6590(a)(2)(iii),(c)(1)
- (4) 40 CFR 63.6595(a)(7),(b),(c)
- (5) 40 CFR 63.6605
- (6) 40 CFR 63.6665
- (7) 40 CFR 63.6670
- (8) 40 CFR 63.6675

EU045 is subject to the following portions of 40 CFR 63, Subpart ZZZZ.

- (1) 40 CFR 63.6580
- (2) 40 CFR 63.6585(a),(c),(d)
- (3) 40 CFR 63.6590(a)(2)(iii),(c)(1)
- (4) 40 CFR 65.95(a)(7),(b),(c)
- (5) 40 CFR 63.6605
- (6) 40 CFR 63.6665
- (7) 40 CFR 63.6670
- (8) 40 CFR 63.6675

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) CERTIFICATION

Source Name: POET Biorefining - Cloverdale, LLC
Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, Indiana 46120
FESOP Permit No.: F133-28725-00003

**This certification shall be included when submitting monitoring, testing reports/results
or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify) _____
- Report (specify) _____
- Notification (specify) _____
- Affidavit (specify) _____
- Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251
Phone: (317) 233-0178
Fax: (317) 233-6865**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
EMERGENCY OCCURRENCE REPORT**

Source Name: POET Biorefining - Cloverdale, LLC
Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, Indiana 46120
FESOP Permit No.: F133-28725-00003

This form consists of 2 pages

Page 1 of 2

- | |
|--|
| <p><input type="checkbox"/> This is an emergency as defined in 326 IAC 2-7-1(12)</p> <ul style="list-style-type: none">• The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-0178, ask for Compliance Section); and• The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-6865), and follow the other requirements of 326 IAC 2-7-16 |
|--|

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 COMPLIANCE AND ENFORCEMENT BRANCH**

FESOP Quarterly Report

Source Name: POET Biorefining - Cloverdale, LLC
 Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
 FESOP No.: 133-28725-00003
 Facility: Ethanol Loadout Rack (EU043)
 Parameter: Total Denatured Ethanol and E-85 Loaded
 Limit: The total combined load-out rate of denatured ethanol and E-85 associated with the ethanol loading rack (EU043) shall not exceed 118,250,000 gallons per twelve consecutive month period, with compliance determined at the end of each month.

QUARTER: _____ YEAR: _____

Month	Column 1 This Month	Column 2 Previous 11 Months	Column 1 + Column 2 12 Month Total
	Denatured Ethanol & E-85 (gallons)	Denatured Ethanol & E-85 (gallons)	Denatured Ethanol & E-85 (gallons)
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
 Deviation has been reported on: _____

Submitted by: _____
 Title / Position: _____
 Signature: _____
 Date: _____
 Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 COMPLIANCE AND ENFORCEMENT BRANCH**

FESOP Quarterly Report

Source Name: POET Biorefining - Cloverdale, LLC
 Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
 Mailing Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
 FESOP No.: 133-28725-00003
 Facility: Ethanol Loadout Rack (EU043)
 Parameter: Total E-85 Loaded
 Limit: The E-85 load-out rate associated with the ethanol loading rack (EU043) shall not exceed 14,300,000 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.

QUARTER: _____ YEAR: _____

Month	Column 1 This Month	Column 2 Previous 11 Months	Column 1 + Column 2 12 Month Total
	E-85 (gallons)	E-85 (gallons)	E-85 (gallons)
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
 Deviation has been reported on: _____

Submitted by: _____
 Title / Position: _____
 Signature: _____
 Date: _____
 Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 COMPLIANCE AND ENFORCEMENT BRANCH**

FESOP Quarterly Report

Source Name: POET Biorefining - Cloverdale, LLC
 Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
 FESOP No.: 133-28725-00003
 Facility: Boilers EU036 and EU037
 Parameter: Natural Gas Usage
 Limit: Shall not exceed 2545.7 MMCF natural gas usage combined per twelve (12) consecutive month period with compliance determined at the end of each month.

QUARTER: _____ YEAR: _____

Month	Column 1 This Month	Column 2 Previous 11 Months	Column 1 + Column 2 12 Month Total
	Natural gas Usage (MMCF)	Natural gas Usage (MMCF)	Natural gas Usage (MMCF)
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
 Deviation has been reported on: _____

Submitted by: _____
 Title / Position: _____
 Signature: _____
 Date: _____
 Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 COMPLIANCE AND ENFORCEMENT BRANCH**

FESOP Quarterly Report

Source Name: POET Biorefining - Cloverdale, LLC
 Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
 FESOP No.: 133-28725-00003
 Facility: Diesel Generator (EU044)
 Parameter: Hours of Operation
 Limit: Shall not exceed 250 hours per twelve (12) consecutive month period with compliance determined at the end of each month.

QUARTER: _____ YEAR: _____

Month	Column 1 This Month	Column 2 Previous 11 Months	Column 1 + Column 2 12 Month Total
	Hours of Operation	Hours of Operation	Hours of Operation
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
 Deviation has been reported on: _____

Submitted by: _____
 Title / Position: _____
 Signature: _____
 Date: _____
 Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 COMPLIANCE AND ENFORCEMENT BRANCH**

FESOP Quarterly Report

Source Name: POET Biorefining - Cloverdale, LLC
 Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
 FESOP No.: 133-28725-00003
 Facility: Diesel Fire Pump (EU045)
 Parameter: Hours of Operation
 Limit: Shall not exceed 250 hours per twelve (12) consecutive month period with compliance determined at the end of each month.

QUARTER: _____ YEAR: _____

Month	Column 1 This Month	Column 2 Previous 11 Months	Column 1 + Column 2 12 Month Total
	Hours of Operation	Hours of Operation	Hours of Operation
Month 1			
Month 2			
Month 3			

- No deviation occurred in this quarter.
- Deviation/s occurred in this quarter.
 Deviation has been reported on: _____

Submitted by: _____
 Title / Position: _____
 Signature: _____
 Date: _____
 Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 COMPLIANCE AND ENFORCEMENT BRANCH
 FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
 QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: POET Biorefining - Cloverdale, LLC
 Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, Indiana 46120
 FESOP Permit No.: F133-28725-00003

Months: _____ **to** _____ **Year:** _____

This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. A deviation required to be reported pursuant to an applicable requirement that exists independent of the permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked ANo deviations occurred this reporting period@.	
<input type="checkbox"/> NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.	
<input type="checkbox"/> THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

Mail to: Permit Administration & Support Section
Office of Air Quality
100 North Senate Avenue
MC 61-53 IGCN 1003
Indianapolis, Indiana 46204-2251

POET Biorefining - Cloverdale, LLC
2265 East County Road 800 South, Ste. #1
Cloverdale, Indiana 46120

Affidavit of Construction

I, _____, being duly sworn upon my oath, depose and say:
(Name of the Authorized Representative)

1. I live in _____ County, Indiana and being of sound mind and over twenty-one (21) years of age, I am competent to give this affidavit.
2. I hold the position of _____ for _____
(Title) (Company Name)
3. By virtue of my position with _____, I have personal
(Company Name)
knowledge of the representations contained in this affidavit and am authorized to make these representations on behalf of _____
(Company Name)
4. I hereby certify that POET Biorefining - Cloverdale, LLC located at 2265 East County Road 800 South, Ste. #1, Cloverdale, Indiana 46120, completed construction of the stationary ethanol production facility. on in conformity with the requirements and intent of the construction permit application received by the Office of Air Quality on December 8, 2009 and as permitted pursuant to New Source Construction Permit and Federally Enforceable State Operating Permit No. F133-28725-00003, Plant ID No. 133-00003 issued on _____.
5. **Permittee, please cross out the following statement if it does not apply:** Additional (operations/facilities) were constructed/substituted as described in the attachment to this document and were not made in accordance with the construction permit.

Further Affiant said not.

I affirm under penalties of perjury that the representations contained in this affidavit are true, to the best of my information and belief.

Signature _____
Date _____

STATE OF INDIANA)
)SS

COUNTY OF _____)

Subscribed and sworn to me, a notary public in and for _____ County and State of Indiana
on this _____ day of _____, 20____. My Commission expires: _____.

Signature _____
Name _____ (typed or printed)

**Indiana Department of Environmental Management
Office of Air Quality**

Attachment A

Fugitive Particulate Matter Emission Control Plan

This plan addresses the fugitive particulate matter (dust) generated by the operation of the POET Biorefining - Cloverdale, LLC facility located in Cloverdale, Indiana.

The facility receives corn by truck for storage and processing into fuel ethanol. POET Biorefining - Cloverdale, LLC also receives denaturant (gasoline or natural gas liquids), bulk chemicals, equipment and miscellaneous maintenance products by truck. POET Biorefining - Cloverdale, LLC ships dried distillers grains with solubles (DDGS) and denatured ethanol off-site by truck and rail.

- 1) Company Address:**
POET Biorefining - Cloverdale, LLC
2265 East County 800 South
Cloverdale, Indiana 46120

- 2) Person Responsible for Plan Implementation:**
Facility Manager
2265 East County 800 South
Cloverdale, Indiana 46120

- 3) Processes, Operations, and Areas which have the Potential to Emit Fugitive Dust:**
 - a. Grain Receiving
 - b. DDGS Loading
 - c. Vehicle Travel on Paved Roads
 - d. Vehicle Travel on Unpaved Roads and Parking Area

- 4) Measures to be Implemented to Control Fugitive Dust**

For the purposes of this fugitive dust control plan, abnormal fugitive dust emissions are defined as fugitive dust emissions heavier than normal or fugitive dust emissions reaching the facility's property boundary.

** Note: The trucking receiving, rail shipping/receiving, and grain handling operations are applicable to 40 CFR Subpart DD (Standards of Performance for Grain Elevators). This regulation limits the fugitive emissions from truck receiving rail operations to less than or equal to 5 percent opacity; and the fugitive emissions from grain handling operations to 0 percent opacity, as measured using US EPA Method 9.**

a. Truck Receiving

- i) Description: The facility operates three truck receiving areas. Each truck receiving area is located within a building enclosure that is open at each end and vented to fabric filter dust collection systems.

- ii) Fugitive Dust Control Measures: Specific fugitive dust control measures that will be implemented include:
 - Maintaining a speed limit of 10 miles per hour on all plant roads;
 - Operating and maintaining the particulate matter aspiration system in the grain receiving building; and
 - Cleaning up spilled grain as soon as possible.

Facility personnel will be trained to identify abnormal fugitive dust emissions. If abnormal fugitive dust emissions are observed, additional corrective actions will be taken by facility personnel. These may include closing the doors on the truck receiving building and/or stopping grain receiving operations until the source of the abnormal fugitive emissions is identified and corrected.

b. Truck DDGS Shipping

- i) Description: The facility operates one truck DDGS shipping. The truck DDGS shipping area is located within a building enclosure that is open at each end.
- ii) Fugitive Dust Control Measures: Specific fugitive dust control measures that will be implemented include:
 - Reducing loading drop height in to the trucks with a flexible load system or adjustable arm;
 - Maintaining a speed limit of 10 miles per hour on all plant roads; and
 - Cleaning up spilled DDGS as soon as possible.

Facility personnel will be trained to identify abnormal fugitive dust emissions. If abnormal fugitive dust emissions are observed, additional corrective actions will be taken by facility personnel. These may include stopping DDGS shipping operations until the source of the abnormal fugitive emissions is identified and corrected.

c. Rail DDGS Shipping

- i) Description: The facility operates rail shipping for DDGS that is located within a building enclosure that is open at each end and vented to a fabric filter dust collection system.
- ii) Fugitive Dust Control Measures: Specific fugitive dust control measures that will be implemented include:
 - Operating and maintaining the particulate matter aspiration system in the DDGS shipping building; and
 - Cleaning up spilled DDGS as soon as possible.

Facility personnel will be trained to identify abnormal fugitive dust emissions. If abnormal fugitive dust emissions are observed, additional corrective actions will be taken by facility personnel. These may include stopping DDGS shipping operations until the source of the abnormal fugitive emissions is identified and corrected.

d. Paved Roads and Parking Areas

- i) Description: The roads on the facility that are traveled by grain trucks, DDGS trucks, employee vehicles, and other support vehicles are paved. Parking areas are also paved. Trucks delivering grain to the facility are primarily staged on the facility access road. Trucks in the staging process do not travel at sufficient speed to normally generate fugitive dust.
- ii) Fugitive Dust Control Measures: Specific fugitive dust control measures that will be implemented include:
 - Maintaining a speed limit of 10 miles per hour on all plant roads.

Facility personnel will be trained to identify abnormal fugitive dust emissions. If abnormal fugitive dust emissions are observed, additional corrective actions will be

taken by facility personnel. Corrective measures may include either sweeping the roads using a wet sweeper or the application of water.

e. Unpaved Roads

- i) Description: Maintenance activities may require occasional truck traffic on unpaved surfaces. No routine operations will require travel on unpaved surfaces.
- ii) Fugitive Dust Control Measures: Facility personnel will be trained to identify abnormal fugitive dust emissions. If abnormal fugitive dust emissions are observed, additional corrective actions will be taken by facility personnel. Corrective measures may include the application of water or other dust suppressant.

5) Plan implementation:

This plan will be implemented upon facility start up.

**Indiana Department of Environmental Management
Office of Air Quality**

Attachment B

Subpart Db—Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units

Source: 72 FR 32742, June 13, 2007, unless otherwise noted.

§ 60.40b Applicability and delegation of authority.

(a) The affected facility to which this subpart applies is each steam generating unit that commences construction, modification, or reconstruction after June 19, 1984, and that has a heat input capacity from fuels combusted in the steam generating unit of greater than 29 megawatts (MW) (100 million British thermal units per hour (MMBtu/hr)).

(b) Any affected facility meeting the applicability requirements under paragraph (a) of this section and commencing construction, modification, or reconstruction after June 19, 1984, but on or before June 19, 1986, is subject to the following standards:

(1) Coal-fired affected facilities having a heat input capacity between 29 and 73 MW (100 and 250 MMBtu/hr), inclusive, are subject to the particulate matter (PM) and nitrogen oxides (NO_x) standards under this subpart.

(2) Coal-fired affected facilities having a heat input capacity greater than 73 MW (250 MMBtu/hr) and meeting the applicability requirements under subpart D (Standards of performance for fossil-fuel-fired steam generators; §60.40) are subject to the PM and NO_x standards under this subpart and to the sulfur dioxide (SO₂) standards under subpart D (§60.43).

(3) Oil-fired affected facilities having a heat input capacity between 29 and 73 MW (100 and 250 MMBtu/hr), inclusive, are subject to the NO_x standards under this subpart.

(4) Oil-fired affected facilities having a heat input capacity greater than 73 MW (250 MMBtu/hr) and meeting the applicability requirements under subpart D (Standards of performance for fossil-fuel-fired steam generators; §60.40) are also subject to the NO_x standards under this subpart and the PM and SO₂ standards under subpart D (§60.42 and §60.43).

(c) Affected facilities that also meet the applicability requirements under subpart J (Standards of performance for petroleum refineries; §60.104) are subject to the PM and NO_x standards under this subpart and the SO₂ standards under subpart J (§60.104).

(d) Affected facilities that also meet the applicability requirements under subpart E (Standards of performance for incinerators; §60.50) are subject to the NO_x and PM standards under this subpart.

(e) Steam generating units meeting the applicability requirements under subpart Da (Standards of performance for electric utility steam generating units; §60.40Da) are not subject to this subpart.

(f) Any change to an existing steam generating unit for the sole purpose of combusting gases containing total reduced sulfur (TRS) as defined under §60.281 is not considered a modification under §60.14 and the steam generating unit is not subject to this subpart.

(g) In delegating implementation and enforcement authority to a State under section 111(c) of the Clean Air Act, the following authorities shall be retained by the Administrator and not transferred to a State.

(1) Section 60.44b(f).

(2) Section 60.44b(g).

(3) Section 60.49b(a)(4).

(h) Any affected facility that meets the applicability requirements and is subject to subpart Ea, subpart Eb, or subpart AAAA of this part is not covered by this subpart.

(i)

(i) Heat recovery steam generators that are associated with combined cycle gas turbines and that meet the applicability requirements of subpart KKKK of this part are not subject to this subpart. This subpart will continue to apply to all other heat recovery steam generators that are capable of combusting more than 29 MW (100 MMBtu/hr) heat input of fossil fuel. If the heat recovery steam generator is subject to this subpart, only emissions resulting from combustion of fuels in the steam generating unit are subject to this subpart. (The gas turbine emissions are subject to subpart GG or KKKK, as applicable, of this part.)

(j) Any affected facility meeting the applicability requirements under paragraph (a) of this section and commencing construction, modification, or reconstruction after June 19, 1986 is not subject to subpart D (Standards of Performance for Fossil-Fuel-Fired Steam Generators, §60.40).

(k) Any affected facility that meets the applicability requirements and is subject to an EPA approved State or Federal section 111(d)/129 plan implementing subpart Cb or subpart BBBB of this part is not covered by this subpart.

[72 FR 32742, June 13, 2007, as amended at 74 FR 5084, Jan. 28, 2009]

§ 60.41b Definitions.

As used in this subpart, all terms not defined herein shall have the meaning given them in the Clean Air Act and in subpart A of this part.

Annual capacity factor means the ratio between the actual heat input to a steam generating unit from the fuels listed in §60.42b(a), §60.43b(a), or §60.44b(a), as applicable, during a calendar year and the potential heat input to the steam generating unit had it been operated for 8,760 hours during a calendar year at the maximum steady state design heat input capacity. In the case of steam generating units that are rented or leased, the actual heat input shall be determined based on the combined heat input from all operations of the affected facility in a calendar year.

Byproduct/waste means any liquid or gaseous substance produced at chemical manufacturing plants, petroleum refineries, or pulp and paper mills (except natural gas, distillate oil, or residual oil) and combusted in a steam generating unit for heat recovery or for disposal. Gaseous substances with carbon dioxide (CO₂) levels greater than 50 percent or carbon monoxide levels greater than 10 percent are not byproduct/waste for the purpose of this subpart.

Chemical manufacturing plants mean industrial plants that are classified by the Department of Commerce under Standard Industrial Classification (SIC) Code 28.

Coal means all solid fuels classified as anthracite, bituminous, subbituminous, or lignite by the American Society of Testing and Materials in ASTM D388 (incorporated by reference, see §60.17), coal refuse, and petroleum coke. Coal-derived synthetic fuels, including but not limited to solvent refined coal, gasified coal not meeting the definition of natural gas, coal-oil mixtures, coke oven gas, and coal-water mixtures, are also included in this definition for the purposes of this subpart.

Coal refuse means any byproduct of coal mining or coal cleaning operations with an ash content greater than 50 percent, by weight, and a heating value less than 13,900 kJ/kg (6,000 Btu/lb) on a dry basis.

Cogeneration, also known as combined heat and power, means a facility that simultaneously produces both electric (or mechanical) and useful thermal energy from the same primary energy source.

Coke oven gas means the volatile constituents generated in the gaseous exhaust during the carbonization of bituminous coal to form coke.

Combined cycle system means a system in which a separate source, such as a gas turbine, internal combustion engine, kiln, etc., provides exhaust gas to a steam generating unit.

Conventional technology means wet flue gas desulfurization (FGD) technology, dry FGD technology, atmospheric fluidized bed combustion technology, and oil hydrodesulfurization technology.

Distillate oil means fuel oils that contain 0.05 weight percent nitrogen or less and comply with the specifications for fuel oil numbers 1 and 2, as defined by the American Society of Testing and Materials in ASTM D396 (incorporated by reference, see §60.17) or diesel fuel oil numbers 1 and 2, as defined by the American Society for Testing and Materials in ASTM D975 (incorporated by reference, see §60.17).

Dry flue gas desulfurization technology means a SO₂ control system that is located downstream of the steam generating unit and removes sulfur oxides from the combustion gases of the steam generating unit by contacting the combustion gases with an alkaline reagent and water, whether introduced separately or as a premixed slurry or solution and forming a dry powder material. This definition includes devices where the dry powder material is subsequently converted to another form. Alkaline slurries or solutions used in dry flue gas desulfurization technology include but are not limited to lime and sodium.

Duct burner means a device that combusts fuel and that is placed in the exhaust duct from another source, such as a stationary gas turbine, internal combustion engine, kiln, etc., to allow the firing of additional fuel to heat the exhaust gases before the exhaust gases enter a steam generating unit.

Emerging technology means any SO₂ control system that is not defined as a conventional technology under this section, and for which the owner or operator of the facility has applied to the Administrator and received approval to operate as an emerging technology under §60.49b(a)(4).

Federally enforceable means all limitations and conditions that are enforceable by the Administrator, including the requirements of 40 CFR parts 60 and 61, requirements within any applicable State Implementation Plan, and any permit requirements established under 40 CFR 52.21 or under 40 CFR 51.18 and 51.24.

Fluidized bed combustion technology means combustion of fuel in a bed or series of beds (including but not limited to bubbling bed units and circulating bed units) of limestone aggregate (or other sorbent materials) in which these materials are forced upward by the flow of combustion air and the gaseous products of combustion.

Fuel pretreatment means a process that removes a portion of the sulfur in a fuel before combustion of the fuel in a steam generating unit.

Full capacity means operation of the steam generating unit at 90 percent or more of the maximum steady-state design heat input capacity.

Gaseous fuel means any fuel that is a gas at ISO conditions. This includes, but is not limited to, natural gas and gasified coal (including coke oven gas).

Gross output means the gross useful work performed by the steam generated. For units generating only electricity, the gross useful work performed is the gross electrical output from the turbine/generator set. For cogeneration units, the gross useful work performed is the gross electrical or mechanical output plus 75 percent of the useful thermal output measured relative to ISO conditions that is not used to generate additional electrical or mechanical output or to enhance the performance of the unit (*i.e.*, steam delivered to an industrial process).

Heat input means heat derived from combustion of fuel in a steam generating unit and does not include the heat derived from preheated combustion air, recirculated flue gases, or exhaust gases from other sources, such as gas turbines, internal combustion engines, kilns, etc.

Heat release rate means the steam generating unit design heat input capacity (in MW or Btu/hr) divided by the furnace volume (in cubic meters or cubic feet); the furnace volume is that volume bounded by the front furnace wall where the burner is located, the furnace side waterwall, and extending to the level just below or in front of the first row of convection pass tubes.

Heat transfer medium means any material that is used to transfer heat from one point to another point.

High heat release rate means a heat release rate greater than 730,000 J/sec-m³ (70,000 Btu/hr-ft³).

ISO Conditions means a temperature of 288 Kelvin, a relative humidity of 60 percent, and a pressure of 101.3 kilopascals.

Lignite means a type of coal classified as lignite A or lignite B by the American Society of Testing and Materials in ASTM D388 (incorporated by reference, see §60.17).

Low heat release rate means a heat release rate of 730,000 J/sec-m³ (70,000 Btu/hr-ft³) or less.

Mass-feed stoker steam generating unit means a steam generating unit where solid fuel is introduced directly into a retort or is fed directly onto a grate where it is combusted.

Maximum heat input capacity means the ability of a steam generating unit to combust a stated maximum amount of fuel on a steady state basis, as determined by the physical design and characteristics of the steam generating unit.

Municipal-type solid waste means refuse, more than 50 percent of which is waste consisting of a mixture of paper, wood, yard wastes, food wastes, plastics, leather, rubber, and other combustible materials, and noncombustible materials such as glass and rock.

Natural gas means:

(1) A naturally occurring mixture of hydrocarbon and nonhydrocarbon gases found in geologic formations beneath the earth's surface, of which the principal constituent is methane; or

(2) Liquefied petroleum gas, as defined by the American Society for Testing and Materials in ASTM D1835 (incorporated by reference, see §60.17); or

(3) A mixture of hydrocarbons that maintains a gaseous state at ISO conditions. Additionally, natural gas must either be composed of at least 70 percent methane by volume or have a gross calorific value between 34 and 43 megajoules (MJ) per dry standard cubic meter (910 and 1,150 Btu per dry standard cubic foot).

Noncontinental area means the State of Hawaii, the Virgin Islands, Guam, American Samoa, the Commonwealth of Puerto Rico, or the Northern Mariana Islands.

Oil means crude oil or petroleum or a liquid fuel derived from crude oil or petroleum, including distillate and residual oil.

Petroleum refinery means industrial plants as classified by the Department of Commerce under Standard Industrial Classification (SIC) Code 29.

Potential sulfur dioxide emission rate means the theoretical SO₂ emissions (nanograms per joule (ng/J) or lb/MMBtu heat input) that would result from combusting fuel in an uncleaned state and without using emission control systems. For gasified coal or oil that is desulfurized prior to combustion, the *Potential sulfur*

dioxide emission rate is the theoretical SO₂emissions (ng/J or lb/MMBtu heat input) that would result from combusting fuel in a cleaned state without using any post combustion emission control systems.

Process heater means a device that is primarily used to heat a material to initiate or promote a chemical reaction in which the material participates as a reactant or catalyst.

Pulp and paper mills means industrial plants that are classified by the Department of Commerce under North American Industry Classification System (NAICS) Code 322 or Standard Industrial Classification (SIC) Code 26.

Pulverized coal-fired steam generating unit means a steam generating unit in which pulverized coal is introduced into an air stream that carries the coal to the combustion chamber of the steam generating unit where it is fired in suspension. This includes both conventional pulverized coal-fired and micropulverized coal-fired steam generating units. Residual oil means crude oil, fuel oil numbers 1 and 2 that have a nitrogen content greater than 0.05 weight percent, and all fuel oil numbers 4, 5 and 6, as defined by the American Society of Testing and Materials in ASTM D396 (incorporated by reference, see §60.17).

Spreader stoker steam generating unit means a steam generating unit in which solid fuel is introduced to the combustion zone by a mechanism that throws the fuel onto a grate from above. Combustion takes place both in suspension and on the grate.

Steam generating unit means a device that combusts any fuel or byproduct/waste and produces steam or heats water or heats any heat transfer medium. This term includes any municipal-type solid waste incinerator with a heat recovery steam generating unit or any steam generating unit that combusts fuel and is part of a cogeneration system or a combined cycle system. This term does not include process heaters as they are defined in this subpart.

Steam generating unit operating day means a 24-hour period between 12:00 midnight and the following midnight during which any fuel is combusted at any time in the steam generating unit. It is not necessary for fuel to be combusted continuously for the entire 24-hour period.

Very low sulfur oil means for units constructed, reconstructed, or modified on or before February 28, 2005, oil that contains no more than 0.5 weight percent sulfur or that, when combusted without SO₂emission control, has a SO₂emission rate equal to or less than 215 ng/J (0.5 lb/MMBtu) heat input. For units constructed, reconstructed, or modified after February 28, 2005 and not located in a noncontinental area, *very low sulfur oil* means oil that contains no more than 0.30 weight percent sulfur or that, when combusted without SO₂emission control, has a SO₂emission rate equal to or less than 140 ng/J (0.32 lb/MMBtu) heat input. For units constructed, reconstructed, or modified after February 28, 2005 and located in a noncontinental area, *very low sulfur oil* means oil that contains no more than 0.5 weight percent sulfur or that, when combusted without SO₂emission control, has a SO₂emission rate equal to or less than 215 ng/J (0.50 lb/MMBtu) heat input.

Wet flue gas desulfurization technology means a SO₂control system that is located downstream of the steam generating unit and removes sulfur oxides from the combustion gases of the steam generating unit by contacting the combustion gas with an alkaline slurry or solution and forming a liquid material. This definition applies to devices where the aqueous liquid material product of this contact is subsequently converted to other forms. Alkaline reagents used in wet flue gas desulfurization technology include, but are not limited to, lime, limestone, and sodium.

Wet scrubber system means any emission control device that mixes an aqueous stream or slurry with the exhaust gases from a steam generating unit to control emissions of PM or SO₂.

Wood means wood, wood residue, bark, or any derivative fuel or residue thereof, in any form, including, but not limited to, sawdust, sanderdust, wood chips, scraps, slabs, millings, shavings, and processed pellets made from wood or other forest residues.

[72 FR 32742, June 13, 2007, as amended at 74 FR 5084, Jan. 28, 2009]

§ 60.42b Standard for sulfur dioxide (SO₂).

(a) Except as provided in paragraphs (b), (c), (d), or (j) of this section, on and after the date on which the performance test is completed or required to be completed under §60.8, whichever comes first, no owner or operator of an affected facility that commenced construction, reconstruction, or modification on or before February 28, 2005, that combusts coal or oil shall cause to be discharged into the atmosphere any gases that contain SO₂ in excess of 87 ng/J (0.20 lb/MMBtu) or 10 percent (0.10) of the potential SO₂ emission rate (90 percent reduction) and the emission limit determined according to the following formula:

$$E_s = \frac{(K_a H_a + K_b H_b)}{(H_a + H_b)}$$

Where:

E_s= SO₂ emission limit, in ng/J or lb/MMBtu heat input;

K_a= 520 ng/J (or 1.2 lb/MMBtu);

K_b= 340 ng/J (or 0.80 lb/MMBtu);

H_a= Heat input from the combustion of coal, in J (MMBtu); and

H_b= Heat input from the combustion of oil, in J (MMBtu).

For facilities complying with the percent reduction standard, only the heat input supplied to the affected facility from the combustion of coal and oil is counted in this paragraph. No credit is provided for the heat input to the affected facility from the combustion of natural gas, wood, municipal-type solid waste, or other fuels or heat derived from exhaust gases from other sources, such as gas turbines, internal combustion engines, kilns, etc.

(b) On and after the date on which the performance test is completed or required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that commenced construction, reconstruction, or modification on or before February 28, 2005, that combusts coal refuse alone in a fluidized bed combustion steam generating unit shall cause to be discharged into the atmosphere any gases that contain SO₂ in excess of 87 ng/J (0.20 lb/MMBtu) or 20 percent (0.20) of the potential SO₂ emission rate (80 percent reduction) and 520 ng/J (1.2 lb/MMBtu) heat input. If coal or oil is fired with coal refuse, the affected facility is subject to paragraph (a) or (d) of this section, as applicable. For facilities complying with the percent reduction standard, only the heat input supplied to the affected facility from the combustion of coal and oil is counted in this paragraph. No credit is provided for the heat input to the affected facility from the combustion of natural gas, wood, municipal-type solid waste, or other fuels or heat derived from exhaust gases from other sources, such as gas turbines, internal combustion engines, kilns, etc.

(c) On and after the date on which the performance test is completed or is required to be completed under §60.8, whichever comes first, no owner or operator of an affected facility that combusts coal or oil, either alone or in combination with any other fuel, and that uses an emerging technology for the control of SO₂ emissions, shall cause to be discharged into the atmosphere any gases that contain SO₂ in excess of 50 percent of the potential SO₂ emission rate (50 percent reduction) and that contain SO₂ in excess of the emission limit determined according to the following formula:

$$E_s = \frac{(K_c H_c + K_d H_d)}{(H_c + H_d)}$$

Where:

E_s = SO₂ emission limit, in ng/J or lb/MM Btu heat input;

K_c = 260 ng/J (or 0.60 lb/MMBtu);

K_d = 170 ng/J (or 0.40 lb/MMBtu);

H_c = Heat input from the combustion of coal, in J (MMBtu); and

H_d = Heat input from the combustion of oil, in J (MMBtu).

For facilities complying with the percent reduction standard, only the heat input supplied to the affected facility from the combustion of coal and oil is counted in this paragraph. No credit is provided for the heat input to the affected facility from the combustion of natural gas, wood, municipal-type solid waste, or other fuels, or from the heat input derived from exhaust gases from other sources, such as gas turbines, internal combustion engines, kilns, etc.

(d) On and after the date on which the performance test is completed or required to be completed under §60.8, whichever comes first, no owner or operator of an affected facility that commenced construction, reconstruction, or modification on or before February 28, 2005 and listed in paragraphs (d)(1), (2), (3), or (4) of this section shall cause to be discharged into the atmosphere any gases that contain SO₂ in excess of 520 ng/J (1.2 lb/MMBtu) heat input if the affected facility combusts coal, or 215 ng/J (0.5 lb/MMBtu) heat input if the affected facility combusts oil other than very low sulfur oil. Percent reduction requirements are not applicable to affected facilities under paragraphs (d)(1), (2), (3) or (4) of this section. For facilities complying with paragraphs (d)(1), (2), or (3) of this section, only the heat input supplied to the affected facility from the combustion of coal and oil is counted in this paragraph. No credit is provided for the heat input to the affected facility from the combustion of natural gas, wood, municipal-type solid waste, or other fuels or heat derived from exhaust gases from other sources, such as gas turbines, internal combustion engines, kilns, etc.

(1) Affected facilities that have an annual capacity factor for coal and oil of 30 percent (0.30) or less and are subject to a federally enforceable permit limiting the operation of the affected facility to an annual capacity factor for coal and oil of 30 percent (0.30) or less;

(2) Affected facilities located in a noncontinental area; or

(3) Affected facilities combusting coal or oil, alone or in combination with any fuel, in a duct burner as part of a combined cycle system where 30 percent (0.30) or less of the heat entering the steam generating unit is from combustion of coal and oil in the duct burner and 70 percent (0.70) or more of the heat entering the steam generating unit is from the exhaust gases entering the duct burner; or

(4) The affected facility burns coke oven gas alone or in combination with natural gas or very low sulfur distillate oil.

(e) Except as provided in paragraph (f) of this section, compliance with the emission limits, fuel oil sulfur limits, and/or percent reduction requirements under this section are determined on a 30-day rolling average basis.

(f) Except as provided in paragraph (j)(2) of this section, compliance with the emission limits or fuel oil sulfur limits under this section is determined on a 24-hour average basis for affected facilities that (1) have a

federally enforceable permit limiting the annual capacity factor for oil to 10 percent or less, (2) combust only very low sulfur oil, and (3) do not combust any other fuel.

(g) Except as provided in paragraph (i) of this section and §60.45b(a), the SO₂emission limits and percent reduction requirements under this section apply at all times, including periods of startup, shutdown, and malfunction.

(h) Reductions in the potential SO₂emission rate through fuel pretreatment are not credited toward the percent reduction requirement under paragraph (c) of this section unless:

(1) Fuel pretreatment results in a 50 percent or greater reduction in potential SO₂emissions and

(2) Emissions from the pretreated fuel (without combustion or post-combustion SO₂control) are equal to or less than the emission limits specified in paragraph (c) of this section.

(i) An affected facility subject to paragraph (a), (b), or (c) of this section may combust very low sulfur oil or natural gas when the SO₂control system is not being operated because of malfunction or maintenance of the SO₂control system.

(j) Percent reduction requirements are not applicable to affected facilities combusting only very low sulfur oil. The owner or operator of an affected facility combusting very low sulfur oil shall demonstrate that the oil meets the definition of very low sulfur oil by: (1) Following the performance testing procedures as described in §60.45b(c) or §60.45b(d), and following the monitoring procedures as described in §60.47b(a) or §60.47b(b) to determine SO₂emission rate or fuel oil sulfur content; or (2) maintaining fuel records as described in §60.49b(r).

(k)(1) Except as provided in paragraphs (k)(2), (k)(3), and (k)(4) of this section, on and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that commences construction, reconstruction, or modification after February 28, 2005, and that combusts coal, oil, natural gas, a mixture of these fuels, or a mixture of these fuels with any other fuels shall cause to be discharged into the atmosphere any gases that contain SO₂in excess of 87 ng/J (0.20 lb/MMBtu) heat input or 8 percent (0.08) of the potential SO₂emission rate (92 percent reduction) and 520 ng/J (1.2 lb/MMBtu) heat input. For facilities complying with the percent reduction standard and paragraph (k)(3) of this section, only the heat input supplied to the affected facility from the combustion of coal and oil is counted in paragraph (k) of this section. No credit is provided for the heat input to the affected facility from the combustion of natural gas, wood, municipal-type solid waste, or other fuels or heat derived from exhaust gases from other sources, such as gas turbines, internal combustion engines, kilns, etc.

(2) Units firing only very low sulfur oil, gaseous fuel, a mixture of these fuels, or a mixture of these fuels with any other fuels with a potential SO₂emission rate of 140 ng/J (0.32 lb/MMBtu) heat input or less are exempt from the SO₂emissions limit in paragraph (k)(1) of this section.

(3) Units that are located in a noncontinental area and that combust coal, oil, or natural gas shall not discharge any gases that contain SO₂in excess of 520 ng/J (1.2 lb/MMBtu) heat input if the affected facility combusts coal, or 215 ng/J (0.50 lb/MMBtu) heat input if the affected facility combusts oil or natural gas.

[72 FR 32742, June 13, 2007, as amended at 74 FR 5084, Jan. 28, 2009]

§ 60.43b Standard for particulate matter (PM).

(a) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever comes first, no owner or operator of an affected facility that commenced construction, reconstruction, or modification on or before February 28, 2005 that combusts coal or combusts mixtures of coal with other fuels, shall cause to be discharged into the atmosphere from that affected facility any gases that contain PM in excess of the following emission limits:

(1) 22 ng/J (0.051 lb/MMBtu) heat input, (i) If the affected facility combusts only coal, or

(ii) If the affected facility combusts coal and other fuels and has an annual capacity factor for the other fuels of 10 percent (0.10) or less.

(2) 43 ng/J (0.10 lb/MMBtu) heat input if the affected facility combusts coal and other fuels and has an annual capacity factor for the other fuels greater than 10 percent (0.10) and is subject to a federally enforceable requirement limiting operation of the affected facility to an annual capacity factor greater than 10 percent (0.10) for fuels other than coal.

(3) 86 ng/J (0.20 lb/MMBtu) heat input if the affected facility combusts coal or coal and other fuels and

(i) Has an annual capacity factor for coal or coal and other fuels of 30 percent (0.30) or less,

(ii) Has a maximum heat input capacity of 73 MW (250 MMBtu/hr) or less,

(iii) Has a federally enforceable requirement limiting operation of the affected facility to an annual capacity factor of 30 percent (0.30) or less for coal or coal and other solid fuels, and

(iv) Construction of the affected facility commenced after June 19, 1984, and before November 25, 1986.

(4) An affected facility burning coke oven gas alone or in combination with other fuels not subject to a PM standard under §60.43b and not using a post-combustion technology (except a wet scrubber) for reducing PM or SO₂ emissions is not subject to the PM limits under §60.43b(a).

(b) On and after the date on which the performance test is completed or required to be completed under §60.8, whichever comes first, no owner or operator of an affected facility that commenced construction, reconstruction, or modification on or before February 28, 2005, and that combusts oil (or mixtures of oil with other fuels) and uses a conventional or emerging technology to reduce SO₂ emissions shall cause to be discharged into the atmosphere from that affected facility any gases that contain PM in excess of 43 ng/J (0.10 lb/MMBtu) heat input.

(c) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever comes first, no owner or operator of an affected facility that commenced construction, reconstruction, or modification on or before February 28, 2005, and that combusts wood, or wood with other fuels, except coal, shall cause to be discharged from that affected facility any gases that contain PM in excess of the following emission limits:

(1) 43 ng/J (0.10 lb/MMBtu) heat input if the affected facility has an annual capacity factor greater than 30 percent (0.30) for wood.

(2) 86 ng/J (0.20 lb/MMBtu) heat input if (i) The affected facility has an annual capacity factor of 30 percent (0.30) or less for wood;

(ii) Is subject to a federally enforceable requirement limiting operation of the affected facility to an annual capacity factor of 30 percent (0.30) or less for wood; and

(iii) Has a maximum heat input capacity of 73 MW (250 MMBtu/hr) or less.

(d) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that combusts municipal-type solid waste or mixtures of municipal-type solid waste with other fuels, shall cause to be discharged into the atmosphere from that affected facility any gases that contain PM in excess of the following emission limits:

(1) 43 ng/J (0.10 lb/MMBtu) heat input;

- (i) If the affected facility combusts only municipal-type solid waste; or
 - (ii) If the affected facility combusts municipal-type solid waste and other fuels and has an annual capacity factor for the other fuels of 10 percent (0.10) or less.
- (2) 86 ng/J (0.20 lb/MMBtu) heat input if the affected facility combusts municipal-type solid waste or municipal-type solid waste and other fuels; and
- (i) Has an annual capacity factor for municipal-type solid waste and other fuels of 30 percent (0.30) or less;
 - (ii) Has a maximum heat input capacity of 73 MW (250 MMBtu/hr) or less;
 - (iii) Has a federally enforceable requirement limiting operation of the affected facility to an annual capacity factor of 30 percent (0.30) or less for municipal-type solid waste, or municipal-type solid waste and other fuels; and
 - (iv) Construction of the affected facility commenced after June 19, 1984, but on or before November 25, 1986.
- (e) For the purposes of this section, the annual capacity factor is determined by dividing the actual heat input to the steam generating unit during the calendar year from the combustion of coal, wood, or municipal-type solid waste, and other fuels, as applicable, by the potential heat input to the steam generating unit if the steam generating unit had been operated for 8,760 hours at the maximum heat input capacity.
- (f) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that can combust coal, oil, wood, or mixtures of these fuels with any other fuels shall cause to be discharged into the atmosphere any gases that exhibit greater than 20 percent opacity (6-minute average), except for one 6-minute period per hour of not more than 27 percent opacity. Owners and operators of an affected facility that elect to install, calibrate, maintain, and operate a continuous emissions monitoring system (CEMS) for measuring PM emissions according to the requirements of this subpart and are subject to a federally enforceable PM limit of 0.030 lb/MMBtu or less are exempt from the opacity standard specified in this paragraph.
- (g) The PM and opacity standards apply at all times, except during periods of startup, shutdown, or malfunction.
- (h)(1) Except as provided in paragraphs (h)(2), (h)(3), (h)(4), (h)(5), and (h)(6) of this section, on and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that commenced construction, reconstruction, or modification after February 28, 2005, and that combusts coal, oil, wood, a mixture of these fuels, or a mixture of these fuels with any other fuels shall cause to be discharged into the atmosphere from that affected facility any gases that contain PM in excess of 13 ng/J (0.030 lb/MMBtu) heat input,
- (2) As an alternative to meeting the requirements of paragraph (h)(1) of this section, the owner or operator of an affected facility for which modification commenced after February 28, 2005, may elect to meet the requirements of this paragraph. On and after the date on which the initial performance test is completed or required to be completed under §60.8, no owner or operator of an affected facility that commences modification after February 28, 2005 shall cause to be discharged into the atmosphere from that affected facility any gases that contain PM in excess of both:
- (i) 22 ng/J (0.051 lb/MMBtu) heat input derived from the combustion of coal, oil, wood, a mixture of these fuels, or a mixture of these fuels with any other fuels; and
 - (ii) 0.2 percent of the combustion concentration (99.8 percent reduction) when combusting coal, oil, wood, a mixture of these fuels, or a mixture of these fuels with any other fuels.

(3) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that commences modification after February 28, 2005, and that combusts over 30 percent wood (by heat input) on an annual basis and has a maximum heat input capacity of 73 MW (250 MMBtu/h) or less shall cause to be discharged into the atmosphere from that affected facility any gases that contain PM in excess of 43 ng/J (0.10 lb/MMBtu) heat input.

(4) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that commences modification after February 28, 2005, and that combusts over 30 percent wood (by heat input) on an annual basis and has a maximum heat input capacity greater than 73 MW (250 MMBtu/h) shall cause to be discharged into the atmosphere from that affected facility any gases that contain PM in excess of 37 ng/J (0.085 lb/MMBtu) heat input.

(5) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, an owner or operator of an affected facility not located in a noncontinental area that commences construction, reconstruction, or modification after February 28, 2005, and that combusts only oil that contains no more than 0.30 weight percent sulfur, coke oven gas, a mixture of these fuels, or either fuel (or a mixture of these fuels) in combination with other fuels not subject to a PM standard in §60.43b and not using a post-combustion technology (except a wet scrubber) to reduce SO₂ or PM emissions is not subject to the PM limits in (h)(1) of this section.

(6) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, an owner or operator of an affected facility located in a noncontinental area that commences construction, reconstruction, or modification after February 28, 2005, and that combusts only oil that contains no more than 0.5 weight percent sulfur, coke oven gas, a mixture of these fuels, or either fuel (or a mixture of these fuels) in combination with other fuels not subject to a PM standard in §60.43b and not using a post-combustion technology (except a wet scrubber) to reduce SO₂ or PM emissions is not subject to the PM limits in (h)(1) of this section.

[72 FR 32742, June 13, 2007, as amended at 74 FR 5084, Jan. 28, 2009]

§ 60.44b Standard for nitrogen oxides (NOX).

(a) Except as provided under paragraphs (k) and (l) of this section, on and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that is subject to the provisions of this section and that combusts only coal, oil, or natural gas shall cause to be discharged into the atmosphere from that affected facility any gases that contain NO_x(expressed as NO₂) in excess of the following emission limits:

Fuel/steam generating unit type	Nitrogen oxide emission limits (expressed as NO ₂) heat input	
	ng/J	lb/MMBTu
(1) Natural gas and distillate oil, except (4):		
(i) Low heat release rate	43	0.10
(ii) High heat release rate	86	0.20
(2) Residual oil:		
(i) Low heat release rate	130	0.30
(ii) High heat release rate	170	0.40
(3) Coal:		
(i) Mass-feed stoker	210	0.50

(ii) Spreader stoker and fluidized bed combustion	260	0.60
(iii) Pulverized coal	300	0.70
(iv) Lignite, except (v)	260	0.60
(v) Lignite mined in North Dakota, South Dakota, or Montana and combusted in a slag tap furnace	340	0.80
(vi) Coal-derived synthetic fuels	210	0.50
(4) Duct burner used in a combined cycle system:		
(i) Natural gas and distillate oil	86	0.20
(ii) Residual oil	170	0.40

(b) Except as provided under paragraphs (k) and (l) of this section, on and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that simultaneously combusts mixtures of coal, oil, or natural gas shall cause to be discharged into the atmosphere from that affected facility any gases that contain NO_x in excess of a limit determined by the use of the following formula:

$$E_n = \frac{(EL_g H_g) + (EL_o H_o) + (EL_c H_c)}{(H_g + H_o + H_c)}$$

Where:

E_n= NO_xemission limit (expressed as NO₂), ng/J (lb/MMBtu);

EL_{go}= Appropriate emission limit from paragraph (a)(1) for combustion of natural gas or distillate oil, ng/J (lb/MMBtu);

H_{go}= Heat input from combustion of natural gas or distillate oil, J (MMBtu);

EL_{ro}= Appropriate emission limit from paragraph (a)(2) for combustion of residual oil, ng/J (lb/MMBtu);

H_{ro}= Heat input from combustion of residual oil, J (MMBtu);

EL_c= Appropriate emission limit from paragraph (a)(3) for combustion of coal, ng/J (lb/MMBtu);
 and

H_c= Heat input from combustion of coal, J (MMBtu).

(c) Except as provided under paragraph (l) of this section, on and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that simultaneously combusts coal or oil, or a mixture of these fuels with natural gas, and wood, municipal-type solid waste, or any other fuel shall cause to be discharged into the atmosphere any gases that contain NO_x in excess of the emission limit for the coal or oil, or mixtures of these fuels with natural gas combusted in the affected facility, as determined pursuant to paragraph (a) or (b) of this section, unless the affected facility has an annual capacity factor for coal or oil, or mixture of these fuels with natural gas of 10 percent (0.10) or less and is subject to a federally enforceable requirement that limits operation of the affected facility to an annual capacity factor of 10 percent (0.10) or less for coal, oil, or a mixture of these fuels with natural gas.

(d) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that simultaneously combusts natural gas with wood, municipal-type solid waste, or other solid fuel, except coal, shall cause to be discharged into the atmosphere from that affected facility any gases that contain NO_x in excess of 130 ng/J (0.30 lb/MMBtu) heat input unless the affected facility has an annual capacity factor for natural gas of 10 percent (0.10) or less and is subject to a federally enforceable requirement that limits operation of the affected facility to an annual capacity factor of 10 percent (0.10) or less for natural gas.

(e) Except as provided under paragraph (l) of this section, on and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that simultaneously combusts coal, oil, or natural gas with byproduct/waste shall cause to be discharged into the atmosphere any gases that contain NO_x in excess of the emission limit determined by the following formula unless the affected facility has an annual capacity factor for coal, oil, and natural gas of 10 percent (0.10) or less and is subject to a federally enforceable requirement that limits operation of the affected facility to an annual capacity factor of 10 percent (0.10) or less:

$$E_n = \frac{(EL_g H_g) + (EL_o H_o) + (EL_c H_c)}{(H_g + H_o + H_c)}$$

Where:

E_n = NO_x emission limit (expressed as NO₂), ng/J (lb/MMBtu);

EL_{g_o} = Appropriate emission limit from paragraph (a)(1) for combustion of natural gas or distillate oil, ng/J (lb/MMBtu);

H_{g_o} = Heat input from combustion of natural gas, distillate oil and gaseous byproduct/waste, J (MMBtu);

EL_{r_o} = Appropriate emission limit from paragraph (a)(2) for combustion of residual oil and/or byproduct/waste, ng/J (lb/MMBtu);

H_{r_o} = Heat input from combustion of residual oil, J (MMBtu);

EL_c = Appropriate emission limit from paragraph (a)(3) for combustion of coal, ng/J (lb/MMBtu);
and

H_c = Heat input from combustion of coal, J (MMBtu).

(f) Any owner or operator of an affected facility that combusts byproduct/waste with either natural gas or oil may petition the Administrator within 180 days of the initial startup of the affected facility to establish a NO_x emission limit that shall apply specifically to that affected facility when the byproduct/waste is combusted. The petition shall include sufficient and appropriate data, as determined by the Administrator, such as NO_x emissions from the affected facility, waste composition (including nitrogen content), and combustion conditions to allow the Administrator to confirm that the affected facility is unable to comply with the emission limits in paragraph (e) of this section and to determine the appropriate emission limit for the affected facility.

(1) Any owner or operator of an affected facility petitioning for a facility-specific NO_x emission limit under this section shall:

(i) Demonstrate compliance with the emission limits for natural gas and distillate oil in paragraph (a)(1) of this section or for residual oil in paragraph (a)(2) or (l)(1) of this section, as appropriate, by conducting a 30-

day performance test as provided in §60.46b(e). During the performance test only natural gas, distillate oil, or residual oil shall be combusted in the affected facility; and

(ii) Demonstrate that the affected facility is unable to comply with the emission limits for natural gas and distillate oil in paragraph (a)(1) of this section or for residual oil in paragraph (a)(2) or (l)(1) of this section, as appropriate, when gaseous or liquid byproduct/waste is combusted in the affected facility under the same conditions and using the same technological system of emission reduction applied when demonstrating compliance under paragraph (f)(1)(i) of this section.

(2) The NO_x emission limits for natural gas or distillate oil in paragraph (a)(1) of this section or for residual oil in paragraph (a)(2) or (l)(1) of this section, as appropriate, shall be applicable to the affected facility until and unless the petition is approved by the Administrator. If the petition is approved by the Administrator, a facility-specific NO_x emission limit will be established at the NO_x emission level achievable when the affected facility is combusting oil or natural gas and byproduct/waste in a manner that the Administrator determines to be consistent with minimizing NO_x emissions. In lieu of amending this subpart, a letter will be sent to the facility describing the facility-specific NO_x limit. The facility shall use the compliance procedures detailed in the letter and make the letter available to the public. If the Administrator determines it is appropriate, the conditions and requirements of the letter can be reviewed and changed at any point.

(g) Any owner or operator of an affected facility that combusts hazardous waste (as defined by 40 CFR part 261 or 40 CFR part 761) with natural gas or oil may petition the Administrator within 180 days of the initial startup of the affected facility for a waiver from compliance with the NO_x emission limit that applies specifically to that affected facility. The petition must include sufficient and appropriate data, as determined by the Administrator, on NO_x emissions from the affected facility, waste destruction efficiencies, waste composition (including nitrogen content), the quantity of specific wastes to be combusted and combustion conditions to allow the Administrator to determine if the affected facility is able to comply with the NO_x emission limits required by this section. The owner or operator of the affected facility shall demonstrate that when hazardous waste is combusted in the affected facility, thermal destruction efficiency requirements for hazardous waste specified in an applicable federally enforceable requirement preclude compliance with the NO_x emission limits of this section. The NO_x emission limits for natural gas or distillate oil in paragraph (a)(1) of this section or for residual oil in paragraph (a)(2) or (l)(1) of this section, as appropriate, are applicable to the affected facility until and unless the petition is approved by the Administrator. (See 40 CFR 761.70 for regulations applicable to the incineration of materials containing polychlorinated biphenyls (PCB's).) In lieu of amending this subpart, a letter will be sent to the facility describing the facility-specific NO_x limit. The facility shall use the compliance procedures detailed in the letter and make the letter available to the public. If the Administrator determines it is appropriate, the conditions and requirements of the letter can be reviewed and changed at any point.

(h) For purposes of paragraph (i) of this section, the NO_x standards under this section apply at all times including periods of startup, shutdown, or malfunction.

(i) Except as provided under paragraph (j) of this section, compliance with the emission limits under this section is determined on a 30-day rolling average basis.

(j) Compliance with the emission limits under this section is determined on a 24-hour average basis for the initial performance test and on a 3-hour average basis for subsequent performance tests for any affected facilities that:

(1) Combust, alone or in combination, only natural gas, distillate oil, or residual oil with a nitrogen content of 0.30 weight percent or less;

(2) Have a combined annual capacity factor of 10 percent or less for natural gas, distillate oil, and residual oil with a nitrogen content of 0.30 weight percent or less; and

(3) Are subject to a federally enforceable requirement limiting operation of the affected facility to the firing of natural gas, distillate oil, and/or residual oil with a nitrogen content of 0.30 weight percent or less and limiting operation of the affected facility to a combined annual capacity factor of 10 percent or less for natural gas, distillate oil, and residual oil with a nitrogen content of 0.30 weight percent or less.

(k) Affected facilities that meet the criteria described in paragraphs (j)(1), (2), and (3) of this section, and that have a heat input capacity of 73 MW (250 MMBtu/hr) or less, are not subject to the NO_x emission limits under this section.

(l) On and after the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, no owner or operator of an affected facility that commenced construction or reconstruction after July 9, 1997 shall cause to be discharged into the atmosphere from that affected facility any gases that contain NO_x(expressed as NO₂) in excess of the following limits:

(1) If the affected facility combusts coal, oil, natural gas, a mixture of these fuels, or a mixture of these fuels with any other fuels: A limit of 86 ng/J (0.20 lb/MMBtu) heat input unless the affected facility has an annual capacity factor for coal, oil, and natural gas of 10 percent (0.10) or less and is subject to a federally enforceable requirement that limits operation of the facility to an annual capacity factor of 10 percent (0.10) or less for coal, oil, and natural gas; or

(2) If the affected facility has a low heat release rate and combusts natural gas or distillate oil in excess of 30 percent of the heat input on a 30-day rolling average from the combustion of all fuels, a limit determined by use of the following formula:

$$E_n = \frac{(0.10 \times H_{go}) + (0.20 \times H_r)}{(H_{go} + H_r)}$$

Where:

E_n= NO_x emission limit, (lb/MMBtu);

H_{go}= 30-day heat input from combustion of natural gas or distillate oil; and

H_r= 30-day heat input from combustion of any other fuel.

(3) After February 27, 2006, units where more than 10 percent of total annual output is electrical or mechanical may comply with an optional limit of 270 ng/J (2.1 lb/MWh) gross energy output, based on a 30-day rolling average. Units complying with this output-based limit must demonstrate compliance according to the procedures of §60.48Da(i) of subpart Da of this part, and must monitor emissions according to §60.49Da(c), (k), through (n) of subpart Da of this part.

[72 FR 32742, June 13, 2007, as amended at 74 FR 5086, Jan. 28, 2009]

§ 60.45b Compliance and performance test methods and procedures for sulfur dioxide.

(a) The SO₂emission standards in §60.42b apply at all times. Facilities burning coke oven gas alone or in combination with any other gaseous fuels or distillate oil are allowed to exceed the limit 30 operating days per calendar year for SO₂control system maintenance.

(b) In conducting the performance tests required under §60.8, the owner or operator shall use the methods and procedures in appendix A (including fuel certification and sampling) of this part or the methods and procedures as specified in this section, except as provided in §60.8(b). Section 60.8(f) does not apply to this section. The 30-day notice required in §60.8(d) applies only to the initial performance test unless otherwise specified by the Administrator.

(c) The owner or operator of an affected facility shall conduct performance tests to determine compliance with the percent of potential SO₂emission rate (% P_s) and the SO₂emission rate (E_s) pursuant to §60.42b following the procedures listed below, except as provided under paragraph (d) and (k) of this section.

(1) The initial performance test shall be conducted over 30 consecutive operating days of the steam generating unit. Compliance with the SO₂ standards shall be determined using a 30-day average. The first operating day included in the initial performance test shall be scheduled within 30 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup of the facility.

(2) If only coal, only oil, or a mixture of coal and oil is combusted, the following procedures are used:

(i) The procedures in Method 19 of appendix A–7 of this part are used to determine the hourly SO₂ emission rate (E_{ho}) and the 30-day average emission rate (E_{ao}). The hourly averages used to compute the 30-day averages are obtained from the CEMS of §60.47b(a) or (b).

(ii) The percent of potential SO₂ emission rate (%P_s) emitted to the atmosphere is computed using the following formula:

$$\%P_s = 100 \left(1 - \frac{\%R_g}{100} \right) \left(1 - \frac{\%R_f}{100} \right)$$

Where:

%P_s = Potential SO₂ emission rate, percent;

%R_g = SO₂ removal efficiency of the control device as determined by Method 19 of appendix A of this part, in percent; and

%R_f = SO₂ removal efficiency of fuel pretreatment as determined by Method 19 of appendix A of this part, in percent.

(3) If coal or oil is combusted with other fuels, the same procedures required in paragraph (c)(2) of this section are used, except as provided in the following:

(i) An adjusted hourly SO₂ emission rate (E_{ho}^o) is used in Equation 19–19 of Method 19 of appendix A of this part to compute an adjusted 30-day average emission rate (E_{ao}^o). The E_{ho}^o is computed using the following formula:

$$E_{ho}^o = \frac{E_{ho} - E_w(1 - X_k)}{X_k}$$

Where:

E_{ho}^o = Adjusted hourly SO₂ emission rate, ng/J (lb/MMBtu);

E_{ho} = Hourly SO₂ emission rate, ng/J (lb/MMBtu);

E_w = SO₂ concentration in fuels other than coal and oil combusted in the affected facility, as determined by the fuel sampling and analysis procedures in Method 19 of appendix A of this part, ng/J (lb/MMBtu). The value E_w for each fuel lot is used for each hourly average during the time that the lot is being combusted; and

X_k = Fraction of total heat input from fuel combustion derived from coal, oil, or coal and oil, as determined by applicable procedures in Method 19 of appendix A of this part.

(ii) To compute the percent of potential SO₂ emission rate (%P_s), an adjusted %R_g(%R_g^o) is computed from the adjusted E_{ao}^o from paragraph (b)(3)(i) of this section and an adjusted average SO₂ inlet rate (E_{ai}^o) using the following formula:

$$\%R_g^o = 100 \left(1.0 - \frac{E_{ao}^o}{E_{ai}^o} \right)$$

To compute E_{ai}^o, an adjusted hourly SO₂ inlet rate (E_{hi}^o) is used. The E_{hi}^o is computed using the following formula:

$$E_{hi}^o = \frac{E_{hi} - E_w(1 - X_k)}{X_k}$$

Where:

E_{hi}^o = Adjusted hourly SO₂ inlet rate, ng/J (lb/MMBtu); and

E_{hi} = Hourly SO₂ inlet rate, ng/J (lb/MMBtu).

(4) The owner or operator of an affected facility subject to paragraph (c)(3) of this section does not have to measure parameters E_w or X_k if the owner or operator elects to assume that X_k = 1.0. Owners or operators of affected facilities who assume X_k = 1.0 shall:

(i) Determine %P_s following the procedures in paragraph (c)(2) of this section; and

(ii) Sulfur dioxide emissions (E_s) are considered to be in compliance with SO₂ emission limits under §60.42b.

(5) The owner or operator of an affected facility that qualifies under the provisions of §60.42b(d) does not have to measure parameters E_w or X_k in paragraph (c)(3) of this section if the owner or operator of the affected facility elects to measure SO₂ emission rates of the coal or oil following the fuel sampling and analysis procedures in Method 19 of appendix A–7 of this part.

(d) Except as provided in paragraph (j) of this section, the owner or operator of an affected facility that combusts only very low sulfur oil, natural gas, or a mixture of these fuels, has an annual capacity factor for oil of 10 percent (0.10) or less, and is subject to a federally enforceable requirement limiting operation of the affected facility to an annual capacity factor for oil of 10 percent (0.10) or less shall:

(1) Conduct the initial performance test over 24 consecutive steam generating unit operating hours at full load;

(2) Determine compliance with the standards after the initial performance test based on the arithmetic average of the hourly emissions data during each steam generating unit operating day if a CEMS is used, or based on a daily average if Method 6B of appendix A of this part or fuel sampling and analysis procedures under Method 19 of appendix A of this part are used.

(e) The owner or operator of an affected facility subject to §60.42b(d)(1) shall demonstrate the maximum design capacity of the steam generating unit by operating the facility at maximum capacity for 24 hours. This demonstration will be made during the initial performance test and a subsequent demonstration may be requested at any other time. If the 24-hour average firing rate for the affected facility is less than the maximum design capacity provided by the manufacturer of the affected facility, the 24-hour average firing rate shall be used to determine the capacity utilization rate for the affected facility, otherwise the maximum design capacity provided by the manufacturer is used.

(f) For the initial performance test required under §60.8, compliance with the SO₂ emission limits and percent reduction requirements under §60.42b is based on the average emission rates and the average percent reduction for SO₂ for the first 30 consecutive steam generating unit operating days, except as provided under paragraph (d) of this section. The initial performance test is the only test for which at least 30 days prior notice is required unless otherwise specified by the Administrator. The initial performance test is to be scheduled so that the first steam generating unit operating day of the 30 successive steam generating unit operating days is completed within 30 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup of the facility. The boiler load during the 30-day period does not have to be the maximum design load, but must be representative of future operating conditions and include at least one 24-hour period at full load.

(g) After the initial performance test required under §60.8, compliance with the SO₂ emission limits and percent reduction requirements under §60.42b is based on the average emission rates and the average percent reduction for SO₂ for 30 successive steam generating unit operating days, except as provided under paragraph (d). A separate performance test is completed at the end of each steam generating unit operating day after the initial performance test, and a new 30-day average emission rate and percent reduction for SO₂ are calculated to show compliance with the standard.

(h) Except as provided under paragraph (i) of this section, the owner or operator of an affected facility shall use all valid SO₂ emissions data in calculating %P_s and E_{h_o} under paragraph (c), of this section whether or not the minimum emissions data requirements under §60.46b are achieved. All valid emissions data, including valid SO₂ emission data collected during periods of startup, shutdown and malfunction, shall be used in calculating %P_s and E_{h_o} pursuant to paragraph (c) of this section.

(i) During periods of malfunction or maintenance of the SO₂ control systems when oil is combusted as provided under §60.42b(i), emission data are not used to calculate %P_s or E_s under §60.42b(a), (b) or (c), however, the emissions data are used to determine compliance with the emission limit under §60.42b(i).

(j) The owner or operator of an affected facility that only combusts very low sulfur oil, natural gas, or a mixture of these fuels with any other fuels not subject to an SO₂ standard is not subject to the compliance and performance testing requirements of this section if the owner or operator obtains fuel receipts as described in §60.49b(r).

(k) The owner or operator of an affected facility seeking to demonstrate compliance in §§60.42b(d)(4), 60.42b(j), 60.42b(k)(2), and 60.42b(k)(3) (when not burning coal) shall follow the applicable procedures in §60.49b(r).

[72 FR 32742, June 13, 2007, as amended at 74 FR 5086, Jan. 28, 2009]

§ 60.46b Compliance and performance test methods and procedures for particulate matter and nitrogen oxides.

(a) The PM emission standards and opacity limits under §60.43b apply at all times except during periods of startup, shutdown, or malfunction. The NO_x emission standards under §60.44b apply at all times.

(b) Compliance with the PM emission standards under §60.43b shall be determined through performance testing as described in paragraph (d) of this section, except as provided in paragraph (i) of this section.

(c) Compliance with the NO_x emission standards under §60.44b shall be determined through performance testing under paragraph (e) or (f), or under paragraphs (g) and (h) of this section, as applicable.

(d) To determine compliance with the PM emission limits and opacity limits under §60.43b, the owner or operator of an affected facility shall conduct an initial performance test as required under §60.8, and shall conduct subsequent performance tests as requested by the Administrator, using the following procedures and reference methods:

(1) Method 3A or 3B of appendix A–2 of this part is used for gas analysis when applying Method 5 of appendix A–3 of this part or Method 17 of appendix A–6 of this part.

(2) Method 5, 5B, or 17 of appendix A of this part shall be used to measure the concentration of PM as follows:

(i) Method 5 of appendix A of this part shall be used at affected facilities without wet flue gas desulfurization (FGD) systems; and

(ii) Method 17 of appendix A–6 of this part may be used at facilities with or without wet scrubber systems provided the stack gas temperature does not exceed a temperature of 160 °C (320 °F). The procedures of sections 8.1 and 11.1 of Method 5B of appendix A–3 of this part may be used in Method 17 of appendix A–6 of this part only if it is used after a wet FGD system. Do not use Method 17 of appendix A–6 of this part after wet FGD systems if the effluent is saturated or laden with water droplets.

(iii) Method 5B of appendix A of this part is to be used only after wet FGD systems.

(3) Method 1 of appendix A of this part is used to select the sampling site and the number of traverse sampling points. The sampling time for each run is at least 120 minutes and the minimum sampling volume is 1.7 dscm (60 dscf) except that smaller sampling times or volumes may be approved by the Administrator when necessitated by process variables or other factors.

(4) For Method 5 of appendix A of this part, the temperature of the sample gas in the probe and filter holder is monitored and is maintained at 160 ± 14 °C (320 ± 25 °F).

(5) For determination of PM emissions, the oxygen (O₂) or CO₂ sample is obtained simultaneously with each run of Method 5, 5B, or 17 of appendix A of this part by traversing the duct at the same sampling location.

(6) For each run using Method 5, 5B, or 17 of appendix A of this part, the emission rate expressed in ng/J heat input is determined using:

(i) The O₂ or CO₂ measurements and PM measurements obtained under this section;

(ii) The dry basis F factor; and

(iii) The dry basis emission rate calculation procedure contained in Method 19 of appendix A of this part.

(7) Method 9 of appendix A of this part is used for determining the opacity of stack emissions.

(e) To determine compliance with the emission limits for NO_x required under §60.44b, the owner or operator of an affected facility shall conduct the performance test as required under §60.8 using the continuous system for monitoring NO_x under §60.48(b).

(1) For the initial compliance test, NO_x from the steam generating unit are monitored for 30 successive steam generating unit operating days and the 30-day average emission rate is used to determine compliance with the NO_x emission standards under §60.44b. The 30-day average emission rate is calculated as the average of all hourly emissions data recorded by the monitoring system during the 30-day test period.

(2) Following the date on which the initial performance test is completed or is required to be completed in §60.8, whichever date comes first, the owner or operator of an affected facility which combusts coal (except as specified under §60.46b(e)(4)) or which combusts residual oil having a nitrogen content greater than 0.30 weight percent shall determine compliance with the NO_x emission standards in §60.44b on a continuous basis through the use of a 30-day rolling average emission rate. A new 30-day rolling average emission rate is calculated for each steam generating unit operating day as the average of all of the hourly NO_x emission data for the preceding 30 steam generating unit operating days.

(3) Following the date on which the initial performance test is completed or is required to be completed under §60.8, whichever date comes first, the owner or operator of an affected facility that has a heat input capacity greater than 73 MW (250 MMBtu/hr) and that combusts natural gas, distillate oil, or residual oil having a nitrogen content of 0.30 weight percent or less shall determine compliance with the NO_x standards under §60.44b on a continuous basis through the use of a 30-day rolling average emission rate. A new 30-day rolling average emission rate is calculated each steam generating unit operating day as the average of all of the hourly NO_x emission data for the preceding 30 steam generating unit operating days.

(4) Following the date on which the initial performance test is completed or required to be completed under §60.8, whichever date comes first, the owner or operator of an affected facility that has a heat input capacity of 73 MW (250 MMBtu/hr) or less and that combusts natural gas, distillate oil, gasified coal, or residual oil having a nitrogen content of 0.30 weight percent or less shall upon request determine compliance with the NO_x standards in §60.44b through the use of a 30-day performance test. During periods when performance tests are not requested, NO_x emissions data collected pursuant to §60.48b(g)(1) or §60.48b(g)(2) are used to calculate a 30-day rolling average emission rate on a daily basis and used to prepare excess emission reports, but will not be used to determine compliance with the NO_x emission standards. A new 30-day rolling average emission rate is calculated each steam generating unit operating day as the average of all of the hourly NO_x emission data for the preceding 30 steam generating unit operating days.

(5) If the owner or operator of an affected facility that combusts residual oil does not sample and analyze the residual oil for nitrogen content, as specified in §60.49b(e), the requirements of §60.48b(g)(1) apply and the provisions of §60.48b(g)(2) are inapplicable.

(f) To determine compliance with the emissions limits for NO_x required by §60.44b(a)(4) or §60.44b(l) for duct burners used in combined cycle systems, either of the procedures described in paragraph (f)(1) or (2) of this section may be used:

(1) The owner or operator of an affected facility shall conduct the performance test required under §60.8 as follows:

(i) The emissions rate (E) of NO_x shall be computed using Equation 1 in this section:

$$E = E_{sg} + \left(\frac{H_g}{H_b} \right) (E_{tg} - E_{tg}) \quad (\text{Eq.1})$$

Where:

E = Emissions rate of NO_x from the duct burner, ng/J (lb/MMBtu) heat input;

E_{sg} = Combined effluent emissions rate, in ng/J (lb/MMBtu) heat input using appropriate F factor as described in Method 19 of appendix A of this part;

H_g = Heat input rate to the combustion turbine, in J/hr (MMBtu/hr);

H_b = Heat input rate to the duct burner, in J/hr (MMBtu/hr); and

E_g = Emissions rate from the combustion turbine, in ng/J (lb/MMBtu) heat input calculated using appropriate F factor as described in Method 19 of appendix A of this part.

(ii) Method 7E of appendix A of this part shall be used to determine the NO_x concentrations. Method 3A or 3B of appendix A of this part shall be used to determine O₂ concentration.

(iii) The owner or operator shall identify and demonstrate to the Administrator's satisfaction suitable methods to determine the average hourly heat input rate to the combustion turbine and the average hourly heat input rate to the affected duct burner.

(iv) Compliance with the emissions limits under §60.44b(a)(4) or §60.44b(l) is determined by the three-run average (nominal 1-hour runs) for the initial and subsequent performance tests; or

(2) The owner or operator of an affected facility may elect to determine compliance on a 30-day rolling average basis by using the CEMS specified under §60.48b for measuring NO_x and O₂ and meet the requirements of §60.48b. The sampling site shall be located at the outlet from the steam generating unit. The NO_x emissions rate at the outlet from the steam generating unit shall constitute the NO_x emissions rate from the duct burner of the combined cycle system.

(g) The owner or operator of an affected facility described in §60.44b(j) or §60.44b(k) shall demonstrate the maximum heat input capacity of the steam generating unit by operating the facility at maximum capacity for 24 hours. The owner or operator of an affected facility shall determine the maximum heat input capacity using the heat loss method or the heat input method described in sections 5 and 7.3 of the ASME *Power Test Codes* 4.1 (incorporated by reference, see §60.17). This demonstration of maximum heat input capacity shall be made during the initial performance test for affected facilities that meet the criteria of §60.44b(j). It shall be made within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial start-up of each facility, for affected facilities meeting the criteria of §60.44b(k). Subsequent demonstrations may be required by the Administrator at any other time. If this demonstration indicates that the maximum heat input capacity of the affected facility is less than that stated by the manufacturer of the affected facility, the maximum heat input capacity determined during this demonstration shall be used to determine the capacity utilization rate for the affected facility. Otherwise, the maximum heat input capacity provided by the manufacturer is used.

(h) The owner or operator of an affected facility described in §60.44b(j) that has a heat input capacity greater than 73 MW (250 MMBtu/hr) shall:

(1) Conduct an initial performance test as required under §60.8 over a minimum of 24 consecutive steam generating unit operating hours at maximum heat input capacity to demonstrate compliance with the NO_x emission standards under §60.44b using Method 7, 7A, 7E of appendix A of this part, or other approved reference methods; and

(2) Conduct subsequent performance tests once per calendar year or every 400 hours of operation (whichever comes first) to demonstrate compliance with the NO_x emission standards under §60.44b over a minimum of 3 consecutive steam generating unit operating hours at maximum heat input capacity using Method 7, 7A, 7E of appendix A of this part, or other approved reference methods.

(i) The owner or operator of an affected facility seeking to demonstrate compliance with the PM limit in paragraphs §60.43b(a)(4) or §60.43b(h)(5) shall follow the applicable procedures in §60.49b(r).

(j) In place of PM testing with Method 5 or 5B of appendix A–3 of this part, or Method 17 of appendix A–6 of this part, an owner or operator may elect to install, calibrate, maintain, and operate a CEMS for monitoring PM emissions discharged to the atmosphere and record the output of the system. The owner or operator of an affected facility who elects to continuously monitor PM emissions instead of conducting performance testing using Method 5 or 5B of appendix A–3 of this part or Method 17 of appendix A–6 of this part shall comply with the requirements specified in paragraphs (j)(1) through (j)(14) of this section.

(1) Notify the Administrator one month before starting use of the system.

(2) Notify the Administrator one month before stopping use of the system.

(3) The monitor shall be installed, evaluated, and operated in accordance with §60.13 of subpart A of this part.

(4) The initial performance evaluation shall be completed no later than 180 days after the date of initial startup of the affected facility, as specified under §60.8 of subpart A of this part or within 180 days of notification to the Administrator of use of the CEMS if the owner or operator was previously determining compliance by Method 5, 5B, or 17 of appendix A of this part performance tests, whichever is later.

(5) The owner or operator of an affected facility shall conduct an initial performance test for PM emissions as required under §60.8 of subpart A of this part. Compliance with the PM emission limit shall be determined by using the CEMS specified in paragraph (j) of this section to measure PM and calculating a 24-hour block arithmetic average emission concentration using EPA Reference Method 19 of appendix A of this part, section 4.1.

(6) Compliance with the PM emission limit shall be determined based on the 24-hour daily (block) average of the hourly arithmetic average emission concentrations using CEMS outlet data.

(7) At a minimum, valid CEMS hourly averages shall be obtained as specified in paragraphs (j)(7)(i) of this section for 75 percent of the total operating hours per 30-day rolling average.

(i) At least two data points per hour shall be used to calculate each 1-hour arithmetic average.

(ii) [Reserved]

(8) The 1-hour arithmetic averages required under paragraph (j)(7) of this section shall be expressed in ng/J or lb/MMBtu heat input and shall be used to calculate the boiler operating day daily arithmetic average emission concentrations. The 1-hour arithmetic averages shall be calculated using the data points required under §60.13(e)(2) of subpart A of this part.

(9) All valid CEMS data shall be used in calculating average emission concentrations even if the minimum CEMS data requirements of paragraph (j)(7) of this section are not met.

(10) The CEMS shall be operated according to Performance Specification 11 in appendix B of this part.

(11) During the correlation testing runs of the CEMS required by Performance Specification 11 in appendix B of this part, PM and O₂(or CO₂) data shall be collected concurrently (or within a 30-to 60-minute period) by both the continuous emission monitors and performance tests conducted using the following test methods.

(i) For PM, Method 5 or 5B of appendix A–3 of this part or Method 17 of appendix A–6 of this part shall be used; and

(ii) After July 1, 2010 or after Method 202 of appendix M of part 51 has been revised to minimize artifact measurement and notice of that change has been published in the Federal Register, whichever is later, for condensable PM emissions, Method 202 of appendix M of part 51 shall be used; and

(iii) For O₂(or CO₂), Method 3A or 3B of appendix A–2 of this part, as applicable shall be used.

(12) Quarterly accuracy determinations and daily calibration drift tests shall be performed in accordance with procedure 2 in appendix F of this part. Relative Response Audit's must be performed annually and Response Correlation Audits must be performed every 3 years.

(13) When PM emissions data are not obtained because of CEMS breakdowns, repairs, calibration checks, and zero and span adjustments, emissions data shall be obtained by using other monitoring systems as approved by the Administrator or EPA Reference Method 19 of appendix A of this part to provide, as necessary, valid emissions data for a minimum of 75 percent of total operating hours per 30-day rolling average.

(14) After July 1, 2011, within 90 days after completing a correlation testing run, the owner or operator of an affected facility shall either successfully enter the test data into EPA's WebFIRE data base located at <http://cfpub.epa.gov/oarweb/index.cfm?action=fire.main> or mail a copy to: United States Environmental Protection Agency; Energy Strategies Group; 109 TW Alexander DR; Mail Code: D243–01; RTP, NC 27711.

§ 60.47b Emission monitoring for sulfur dioxide.

(a) Except as provided in paragraphs (b) and (f) of this section, the owner or operator of an affected facility subject to the SO₂standards in §60.42b shall install, calibrate, maintain, and operate CEMS for measuring SO₂concentrations and either O₂or CO₂concentrations and shall record the output of the systems. For units complying with the percent reduction standard, the SO₂and either O₂or CO₂concentrations shall both be monitored at the inlet and outlet of the SO₂control device. If the owner or operator has installed and certified SO₂and O₂or CO₂CEMS according to the requirements of §75.20(c)(1) of this chapter and appendix A to part 75 of this chapter, and is continuing to meet the ongoing quality assurance requirements of §75.21 of this chapter and appendix B to part 75 of this chapter, those CEMS may be used to meet the requirements of this section, provided that:

(1) When relative accuracy testing is conducted, SO₂concentration data and CO₂(or O₂) data are collected simultaneously; and

(2) In addition to meeting the applicable SO₂and CO₂(or O₂) relative accuracy specifications in Figure 2 of appendix B to part 75 of this chapter, the relative accuracy (RA) standard in section 13.2 of Performance Specification 2 in appendix B to this part is met when the RA is calculated on a lb/MMBtu basis; and

(3) The reporting requirements of §60.49b are met. SO₂and CO₂(or O₂) data used to meet the requirements of §60.49b shall not include substitute data values derived from the missing data procedures in subpart D of part 75 of this chapter, nor shall the SO₂data have been bias adjusted according to the procedures of part 75 of this chapter.

(b) As an alternative to operating CEMS as required under paragraph (a) of this section, an owner or operator may elect to determine the average SO₂emissions and percent reduction by:

(1) Collecting coal or oil samples in an as-fired condition at the inlet to the steam generating unit and analyzing them for sulfur and heat content according to Method 19 of appendix A of this part. Method 19 of appendix A of this part provides procedures for converting these measurements into the format to be used in calculating the average SO₂input rate, or

(2) Measuring SO₂according to Method 6B of appendix A of this part at the inlet or outlet to the SO₂control system. An initial stratification test is required to verify the adequacy of the Method 6B of appendix A of this part sampling location. The stratification test shall consist of three paired runs of a suitable SO₂and CO₂measurement train operated at the candidate location and a second similar train operated according to the procedures in section 3.2 and the applicable procedures in section 7 of Performance Specification 2. Method 6B of appendix A of this part, Method 6A of appendix A of this part, or a combination of Methods 6 and 3 or 3B of appendix A of this part or Methods 6C and 3A of appendix A of this part are suitable measurement techniques. If Method 6B of appendix A of this part is used for the second train, sampling time and timer operation may be adjusted for the stratification test as long as an adequate sample volume is collected; however, both sampling trains are to be operated similarly. For the location to be adequate for Method 6B of appendix A of this part 24-hour tests, the mean of the absolute difference between the three paired runs must be less than 10 percent.

(3) A daily SO₂emission rate, E_D, shall be determined using the procedure described in Method 6A of appendix A of this part, section 7.6.2 (Equation 6A–8) and stated in ng/J (lb/MMBtu) heat input.

(4) The mean 30-day emission rate is calculated using the daily measured values in ng/J (lb/MMBtu) for 30 successive steam generating unit operating days using equation 19–20 of Method 19 of appendix A of this part.

(c) The owner or operator of an affected facility shall obtain emission data for at least 75 percent of the operating hours in at least 22 out of 30 successive boiler operating days. If this minimum data requirement is not met with a single monitoring system, the owner or operator of the affected facility shall supplement the emission data with data collected with other monitoring systems as approved by the Administrator or the reference methods and procedures as described in paragraph (b) of this section.

(d) The 1-hour average SO₂ emission rates measured by the CEMS required by paragraph (a) of this section and required under §60.13(h) is expressed in ng/J or lb/MMBtu heat input and is used to calculate the average emission rates under §60.42(b). Each 1-hour average SO₂ emission rate must be based on 30 or more minutes of steam generating unit operation. The hourly averages shall be calculated according to §60.13(h)(2). Hourly SO₂ emission rates are not calculated if the affected facility is operated less than 30 minutes in a given clock hour and are not counted toward determination of a steam generating unit operating day.

(e) The procedures under §60.13 shall be followed for installation, evaluation, and operation of the CEMS.

(1) Except as provided for in paragraph (e)(4) of this section, all CEMS shall be operated in accordance with the applicable procedures under Performance Specifications 1, 2, and 3 of appendix B of this part.

(2) Except as provided for in paragraph (e)(4) of this section, quarterly accuracy determinations and daily calibration drift tests shall be performed in accordance with Procedure 1 of appendix F of this part.

(3) For affected facilities combusting coal or oil, alone or in combination with other fuels, the span value of the SO₂ CEMS at the inlet to the SO₂ control device is 125 percent of the maximum estimated hourly potential SO₂ emissions of the fuel combusted, and the span value of the CEMS at the outlet to the SO₂ control device is 50 percent of the maximum estimated hourly potential SO₂ emissions of the fuel combusted. Alternatively, SO₂ span values determined according to section 2.1.1 in appendix A to part 75 of this chapter may be used.

(4) As an alternative to meeting the requirements of paragraphs (e)(1) and (e)(2) of this section, the owner or operator may elect to implement the following alternative data accuracy assessment procedures:

(i) For all required CO₂ and O₂ monitors and for SO₂ and NO_x monitors with span values greater than or equal to 100 ppm, the daily calibration error test and calibration adjustment procedures described in sections 2.1.1 and 2.1.3 of appendix B to part 75 of this chapter may be followed instead of the CD assessment procedures in Procedure 1, section 4.1 of appendix F to this part.

(ii) For all required CO₂ and O₂ monitors and for SO₂ and NO_x monitors with span values greater than 30 ppm, quarterly linearity checks may be performed in accordance with section 2.2.1 of appendix B to part 75 of this chapter, instead of performing the cylinder gas audits (CGAs) described in Procedure 1, section 5.1.2 of appendix F to this part. If this option is selected: The frequency of the linearity checks shall be as specified in section 2.2.1 of appendix B to part 75 of this chapter; the applicable linearity specifications in section 3.2 of appendix A to part 75 of this chapter shall be met; the data validation and out-of-control criteria in section 2.2.3 of appendix B to part 75 of this chapter shall be followed instead of the excessive audit inaccuracy and out-of-control criteria in Procedure 1, section 5.2 of appendix F to this part; and the grace period provisions in section 2.2.4 of appendix B to part 75 of this chapter shall apply. For the purposes of data validation under this subpart, the cylinder gas audits described in Procedure 1, section 5.1.2 of appendix F to this part shall be performed for SO₂ and NO_x span values less than or equal to 30 ppm; and

(iii) For SO₂, CO₂, and O₂ monitoring systems and for NO_x emission rate monitoring systems, RATAs may be performed in accordance with section 2.3 of appendix B to part 75 of this chapter instead of following the procedures described in Procedure 1, section 5.1.1 of appendix F to this part. If this option is selected: The frequency of each RATA shall be as specified in section 2.3.1 of appendix B to part 75 of this chapter; the applicable relative accuracy specifications shown in Figure 2 in appendix B to part 75 of this chapter shall be met; the data validation and out-of-control criteria in section 2.3.2 of appendix B to part 75 of this chapter shall be followed instead of the excessive audit inaccuracy and out-of-control criteria in Procedure 1, section 5.2 of appendix F to this part; and the grace period provisions in section 2.3.3 of appendix B to part 75 of this chapter shall apply. For the purposes of data validation under this subpart, the relative accuracy specification in section 13.2 of Performance Specification 2 in appendix B to this part shall be met on a lb/MMBtu basis for SO₂ (regardless of the SO₂ emission level during the RATA), and for NO_x when the average NO_x emission rate measured by the reference method during the RATA is less than 0.100 lb/MMBtu.

(f) The owner or operator of an affected facility that combusts very low sulfur oil or is demonstrating compliance under §60.45b(k) is not subject to the emission monitoring requirements under paragraph (a) of this section if the owner or operator maintains fuel records as described in §60.49b(r).

[72 FR 32742, June 13, 2007, as amended at 74 FR 5087, Jan. 28, 2009]

§ 60.48b Emission monitoring for particulate matter and nitrogen oxides.

(a) Except as provided in paragraph (j) of this section, the owner or operator of an affected facility subject to the opacity standard under §60.43b shall install, calibrate, maintain, and operate a continuous opacity monitoring systems (COMS) for measuring the opacity of emissions discharged to the atmosphere and record the output of the system. The owner or operator of an affected facility subject to an opacity standard under §60.43b and meeting the conditions under paragraphs (j)(1), (2), (3), (4), or (5) of this section who elects not to install a COMS shall conduct a performance test using Method 9 of appendix A-4 of this part and the procedures in §60.11 to demonstrate compliance with the applicable limit in §60.43b and shall comply with either paragraphs (a)(1), (a)(2), or (a)(3) of this section. If during the initial 60 minutes of observation all 6-minute averages are less than 10 percent and all individual 15-second observations are less than or equal to 20 percent, the observation period may be reduced from 3 hours to 60 minutes.

(1) Except as provided in paragraph (a)(2) and (a)(3) of this section, the owner or operator shall conduct subsequent Method 9 of appendix A-4 of this part performance tests using the procedures in paragraph (a) of this section according to the applicable schedule in paragraphs (a)(1)(i) through (a)(1)(iv) of this section, as determined by the most recent Method 9 of appendix A-4 of this part performance test results.

(i) If no visible emissions are observed, a subsequent Method 9 of appendix A-4 of this part performance test must be completed within 12 calendar months from the date that the most recent performance test was conducted;

(ii) If visible emissions are observed but the maximum 6-minute average opacity is less than or equal to 5 percent, a subsequent Method 9 of appendix A-4 of this part performance test must be completed within 6 calendar months from the date that the most recent performance test was conducted;

(iii) If the maximum 6-minute average opacity is greater than 5 percent but less than or equal to 10 percent, a subsequent Method 9 of appendix A-4 of this part performance test must be completed within 3 calendar months from the date that the most recent performance test was conducted; or

(iv) If the maximum 6-minute average opacity is greater than 10 percent, a subsequent Method 9 of appendix A-4 of this part performance test must be completed within 30 calendar days from the date that the most recent performance test was conducted.

(2) If the maximum 6-minute opacity is less than 10 percent during the most recent Method 9 of appendix A-4 of this part performance test, the owner or operator may, as an alternative to performing subsequent Method 9 of appendix A-4 of this part performance tests, elect to perform subsequent monitoring using Method 22 of appendix A-7 of this part according to the procedures specified in paragraphs (a)(2)(i) and (ii) of this section.

(i) The owner or operator shall conduct 10 minute observations (during normal operation) each operating day the affected facility fires fuel for which an opacity standard is applicable using Method 22 of appendix A-7 of this part and demonstrate that the sum of the occurrences of any visible emissions is not in excess of 5 percent of the observation period (*i.e.* , 30 seconds per 10 minute period). If the sum of the occurrence of any visible emissions is greater than 30 seconds during the initial 10 minute observation, immediately conduct a 30 minute observation. If the sum of the occurrence of visible emissions is greater than 5 percent of the observation period (*i.e.* , 90 seconds per 30 minute period) the owner or operator shall either document and adjust the operation of the facility and demonstrate within 24 hours that the sum of the occurrence of visible emissions is equal to or less than 5 percent during a 30 minute observation (*i.e.* , 90 seconds) or conduct a new Method 9 of appendix A-4 of this part performance test using the procedures in paragraph (a) of this section within 30 calendar days according to the requirements in §60.46d(d)(7).

(ii) If no visible emissions are observed for 30 operating days during which an opacity standard is applicable, observations can be reduced to once every 7 operating days during which an opacity standard is applicable. If any visible emissions are observed, daily observations shall be resumed.

(3) If the maximum 6-minute opacity is less than 10 percent during the most recent Method 9 of appendix A-4 of this part performance test, the owner or operator may, as an alternative to performing subsequent Method 9 of appendix A-4 performance tests, elect to perform subsequent monitoring using a digital opacity compliance system according to a site-specific monitoring plan approved by the Administrator. The observations shall be similar, but not necessarily identical, to the requirements in paragraph (a)(2) of this section. For reference purposes in preparing the monitoring plan, see OAQPS "Determination of Visible Emission Opacity from Stationary Sources Using Computer-Based Photographic Analysis Systems." This document is available from the U.S. Environmental Protection Agency (U.S. EPA); Office of Air Quality and Planning Standards; Sector Policies and Programs Division; Measurement Policy Group (D243-02), Research Triangle Park, NC 27711. This document is also available on the Technology Transfer Network (TTN) under Emission Measurement Center Preliminary Methods.

(b) Except as provided under paragraphs (g), (h), and (i) of this section, the owner or operator of an affected facility subject to a NO_x standard under §60.44b shall comply with either paragraphs (b)(1) or (b)(2) of this section.

(1) Install, calibrate, maintain, and operate CEMS for measuring NO_x and O₂(or CO₂) emissions discharged to the atmosphere, and shall record the output of the system; or

(2) If the owner or operator has installed a NO_x emission rate CEMS to meet the requirements of part 75 of this chapter and is continuing to meet the ongoing requirements of part 75 of this chapter, that CEMS may be used to meet the requirements of this section, except that the owner or operator shall also meet the requirements of §60.49b. Data reported to meet the requirements of §60.49b shall not include data substituted using the missing data procedures in subpart D of part 75 of this chapter, nor shall the data have been bias adjusted according to the procedures of part 75 of this chapter.

(c) The CEMS required under paragraph (b) of this section shall be operated and data recorded during all periods of operation of the affected facility except for CEMS breakdowns and repairs. Data is recorded during calibration checks, and zero and span adjustments.

(d) The 1-hour average NO_x emission rates measured by the continuous NO_x monitor required by paragraph (b) of this section and required under §60.13(h) shall be expressed in ng/J or lb/MMBtu heat input and shall be used to calculate the average emission rates under §60.44b. The 1-hour averages shall be calculated using the data points required under §60.13(h)(2).

(e) The procedures under §60.13 shall be followed for installation, evaluation, and operation of the continuous monitoring systems.

(1) For affected facilities combusting coal, wood or municipal-type solid waste, the span value for a COMS shall be between 60 and 80 percent.

(2) For affected facilities combusting coal, oil, or natural gas, the span value for NO_x is determined using one of the following procedures:

(i) Except as provided under paragraph (e)(2)(ii) of this section, NO_x span values shall be determined as follows:

Fuel	Span values for NO_x (ppm)
Natural gas	500.

Oil	500.
Coal	1,000.
Mixtures	$500(x + y) + 1,000z.$

Where:

x = Fraction of total heat input derived from natural gas;

y = Fraction of total heat input derived from oil; and

z = Fraction of total heat input derived from coal.

(ii) As an alternative to meeting the requirements of paragraph (e)(2)(i) of this section, the owner or operator of an affected facility may elect to use the NO_x span values determined according to section 2.1.2 in appendix A to part 75 of this chapter.

(3) All span values computed under paragraph (e)(2)(i) of this section for combusting mixtures of regulated fuels are rounded to the nearest 500 ppm. Span values computed under paragraph (e)(2)(ii) of this section shall be rounded off according to section 2.1.2 in appendix A to part 75 of this chapter.

(f) When NO_x emission data are not obtained because of CEMS breakdowns, repairs, calibration checks and zero and span adjustments, emission data will be obtained by using standby monitoring systems, Method 7 of appendix A of this part, Method 7A of appendix A of this part, or other approved reference methods to provide emission data for a minimum of 75 percent of the operating hours in each steam generating unit operating day, in at least 22 out of 30 successive steam generating unit operating days.

(g) The owner or operator of an affected facility that has a heat input capacity of 73 MW (250 MMBtu/hr) or less, and that has an annual capacity factor for residual oil having a nitrogen content of 0.30 weight percent or less, natural gas, distillate oil, gasified coal, or any mixture of these fuels, greater than 10 percent (0.10) shall:

(1) Comply with the provisions of paragraphs (b), (c), (d), (e)(2), (e)(3), and (f) of this section; or

(2) Monitor steam generating unit operating conditions and predict NO_x emission rates as specified in a plan submitted pursuant to §60.49b(c).

(h) The owner or operator of a duct burner, as described in §60.41b, that is subject to the NO_x standards in §60.44b(a)(4), §60.44b(e), or §60.44b(l) is not required to install or operate a continuous emissions monitoring system to measure NO_x emissions.

(i) The owner or operator of an affected facility described in §60.44b(j) or §60.44b(k) is not required to install or operate a CEMS for measuring NO_x emissions.

(j) The owner or operator of an affected facility that meets the conditions in either paragraph (j)(1), (2), (3), (4), (5), or (6) of this section is not required to install or operate a COMS if:

(1) The affected facility uses a PM CEMS to monitor PM emissions; or

(2) The affected facility burns only liquid (excluding residual oil) or gaseous fuels with potential SO₂ emissions rates of 26 ng/J (0.060 lb/MMBtu) or less and does not use a post-combustion technology to reduce SO₂ or PM emissions. The owner or operator must maintain fuel records of the sulfur content of the fuels burned, as described under §60.49b(r); or

(3) The affected facility burns coke oven gas alone or in combination with fuels meeting the criteria in paragraph (j)(2) of this section and does not use a post-combustion technology to reduce SO₂ or PM emissions; or

(4) The affected facility does not use post-combustion technology (except a wet scrubber) for reducing PM, SO₂, or carbon monoxide (CO) emissions, burns only gaseous fuels or fuel oils that contain less than or equal to 0.30 weight percent sulfur, and is operated such that emissions of CO to the atmosphere from the affected facility are maintained at levels less than or equal to 0.15 lb/MMBtu on a steam generating unit operating day average basis. Owners and operators of affected facilities electing to comply with this paragraph must demonstrate compliance according to the procedures specified in paragraphs (j)(4)(i) through (iv) of this section; or

(i) You must monitor CO emissions using a CEMS according to the procedures specified in paragraphs (j)(4)(i)(A) through (D) of this section.

(A) The CO CEMS must be installed, certified, maintained, and operated according to the provisions in §60.58b(i)(3) of subpart Eb of this part.

(B) Each 1-hour CO emissions average is calculated using the data points generated by the CO CEMS expressed in parts per million by volume corrected to 3 percent oxygen (dry basis).

(C) At a minimum, valid 1-hour CO emissions averages must be obtained for at least 90 percent of the operating hours on a 30-day rolling average basis. The 1-hour averages are calculated using the data points required in §60.13(h)(2).

(D) Quarterly accuracy determinations and daily calibration drift tests for the CO CEMS must be performed in accordance with procedure 1 in appendix F of this part.

(ii) You must calculate the 1-hour average CO emissions levels for each steam generating unit operating day by multiplying the average hourly CO output concentration measured by the CO CEMS times the corresponding average hourly flue gas flow rate and divided by the corresponding average hourly heat input to the affected source. The 24-hour average CO emission level is determined by calculating the arithmetic average of the hourly CO emission levels computed for each steam generating unit operating day.

(iii) You must evaluate the preceding 24-hour average CO emission level each steam generating unit operating day excluding periods of affected source startup, shutdown, or malfunction. If the 24-hour average CO emission level is greater than 0.15 lb/MMBtu, you must initiate investigation of the relevant equipment and control systems within 24 hours of the first discovery of the high emission incident and, take the appropriate corrective action as soon as practicable to adjust control settings or repair equipment to reduce the 24-hour average CO emission level to 0.15 lb/MMBtu or less.

(iv) You must record the CO measurements and calculations performed according to paragraph (j)(4) of this section and any corrective actions taken. The record of corrective action taken must include the date and time during which the 24-hour average CO emission level was greater than 0.15 lb/MMBtu, and the date, time, and description of the corrective action.

(5) The affected facility uses a bag leak detection system to monitor the performance of a fabric filter (baghouse) according to the most recent requirements in section §60.48Da of this part; or

(6) The affected facility burns only gaseous fuels or fuel oils that contain less than or equal to 0.30 weight percent sulfur and operates according to a written site-specific monitoring plan approved by the permitting authority. This monitoring plan must include procedures and criteria for establishing and monitoring specific parameters for the affected facility indicative of compliance with the opacity standard.

(k) Owners or operators complying with the PM emission limit by using a PM CEMS must calibrate, maintain, operate, and record the output of the system for PM emissions discharged to the atmosphere as specified in §60.46b(j). The CEMS specified in paragraph §60.46b(j) shall be operated and data recorded

during all periods of operation of the affected facility except for CEMS breakdowns and repairs. Data is recorded during calibration checks, and zero and span adjustments.

[72 FR 32742, June 13, 2007, as amended at 74 FR 5087, Jan. 28, 2009]

§ 60.49b Reporting and recordkeeping requirements.

(a) The owner or operator of each affected facility shall submit notification of the date of initial startup, as provided by §60.7. This notification shall include:

(1) The design heat input capacity of the affected facility and identification of the fuels to be combusted in the affected facility;

(2) If applicable, a copy of any federally enforceable requirement that limits the annual capacity factor for any fuel or mixture of fuels under §§60.42b(d)(1), 60.43b(a)(2), (a)(3)(iii), (c)(2)(ii), (d)(2)(iii), 60.44b(c), (d), (e), (i), (j), (k), 60.45b(d), (g), 60.46b(h), or 60.48b(i);

(3) The annual capacity factor at which the owner or operator anticipates operating the facility based on all fuels fired and based on each individual fuel fired; and

(4) Notification that an emerging technology will be used for controlling emissions of SO₂. The Administrator will examine the description of the emerging technology and will determine whether the technology qualifies as an emerging technology. In making this determination, the Administrator may require the owner or operator of the affected facility to submit additional information concerning the control device. The affected facility is subject to the provisions of §60.42b(a) unless and until this determination is made by the Administrator.

(b) The owner or operator of each affected facility subject to the SO₂, PM, and/or NO_x emission limits under §§60.42b, 60.43b, and 60.44b shall submit to the Administrator the performance test data from the initial performance test and the performance evaluation of the CEMS using the applicable performance specifications in appendix B of this part. The owner or operator of each affected facility described in §60.44b(j) or §60.44b(k) shall submit to the Administrator the maximum heat input capacity data from the demonstration of the maximum heat input capacity of the affected facility.

(c) The owner or operator of each affected facility subject to the NO_x standard in §60.44b who seeks to demonstrate compliance with those standards through the monitoring of steam generating unit operating conditions in the provisions of §60.48b(g)(2) shall submit to the Administrator for approval a plan that identifies the operating conditions to be monitored in §60.48b(g)(2) and the records to be maintained in §60.49b(g). This plan shall be submitted to the Administrator for approval within 360 days of the initial startup of the affected facility. An affected facility burning coke oven gas alone or in combination with other gaseous fuels or distillate oil shall submit this plan to the Administrator for approval within 360 days of the initial startup of the affected facility or by November 30, 2009, whichever date comes later. If the plan is approved, the owner or operator shall maintain records of predicted nitrogen oxide emission rates and the monitored operating conditions, including steam generating unit load, identified in the plan. The plan shall:

(1) Identify the specific operating conditions to be monitored and the relationship between these operating conditions and NO_x emission rates (*i.e.* , ng/J or lbs/MMBtu heat input). Steam generating unit operating conditions include, but are not limited to, the degree of staged combustion (*i.e.* , the ratio of primary air to secondary and/or tertiary air) and the level of excess air (*i.e.* , flue gas O₂level);

(2) Include the data and information that the owner or operator used to identify the relationship between NO_x emission rates and these operating conditions; and

(3) Identify how these operating conditions, including steam generating unit load, will be monitored under §60.48b(g) on an hourly basis by the owner or operator during the period of operation of the affected facility; the quality assurance procedures or practices that will be employed to ensure that the data generated by monitoring these operating conditions will be representative and accurate; and the type and format of the

records of these operating conditions, including steam generating unit load, that will be maintained by the owner or operator under §60.49b(g).

(d) Except as provided in paragraph (d)(2) of this section, the owner or operator of an affected facility shall record and maintain records as specified in paragraph (d)(1) of this section.

(1) The owner or operator of an affected facility shall record and maintain records of the amounts of each fuel combusted during each day and calculate the annual capacity factor individually for coal, distillate oil, residual oil, natural gas, wood, and municipal-type solid waste for the reporting period. The annual capacity factor is determined on a 12-month rolling average basis with a new annual capacity factor calculated at the end of each calendar month.

(2) As an alternative to meeting the requirements of paragraph (d)(1) of this section, the owner or operator of an affected facility that is subject to a federally enforceable permit restricting fuel use to a single fuel such that the facility is not required to continuously monitor any emissions (excluding opacity) or parameters indicative of emissions may elect to record and maintain records of the amount of each fuel combusted during each calendar month.

(e) For an affected facility that combusts residual oil and meets the criteria under §§60.46b(e)(4), 60.44b(j), or (k), the owner or operator shall maintain records of the nitrogen content of the residual oil combusted in the affected facility and calculate the average fuel nitrogen content for the reporting period. The nitrogen content shall be determined using ASTM Method D4629 (incorporated by reference, see §60.17), or fuel suppliers. If residual oil blends are being combusted, fuel nitrogen specifications may be prorated based on the ratio of residual oils of different nitrogen content in the fuel blend.

(f) For an affected facility subject to the opacity standard in §60.43b, the owner or operator shall maintain records of opacity. In addition, an owner or operator that elects to monitor emissions according to the requirements in §60.48b(a) shall maintain records according to the requirements specified in paragraphs (f)(1) through (3) of this section, as applicable to the visible emissions monitoring method used.

(1) For each performance test conducted using Method 9 of appendix A–4 of this part, the owner or operator shall keep the records including the information specified in paragraphs (f)(1)(i) through (iii) of this section.

(i) Dates and time intervals of all opacity observation periods;

(ii) Name, affiliation, and copy of current visible emission reading certification for each visible emission observer participating in the performance test; and

(iii) Copies of all visible emission observer opacity field data sheets;

(2) For each performance test conducted using Method 22 of appendix A–4 of this part, the owner or operator shall keep the records including the information specified in paragraphs (f)(2)(i) through (iv) of this section.

(i) Dates and time intervals of all visible emissions observation periods;

(ii) Name and affiliation for each visible emission observer participating in the performance test;

(iii) Copies of all visible emission observer opacity field data sheets; and

(iv) Documentation of any adjustments made and the time the adjustments were completed to the affected facility operation by the owner or operator to demonstrate compliance with the applicable monitoring requirements.

(3) For each digital opacity compliance system, the owner or operator shall maintain records and submit reports according to the requirements specified in the site-specific monitoring plan approved by the Administrator.

(g) Except as provided under paragraph (p) of this section, the owner or operator of an affected facility subject to the NO_x standards under §60.44b shall maintain records of the following information for each steam generating unit operating day:

(1) Calendar date;

(2) The average hourly NO_x emission rates (expressed as NO₂) (ng/J or lb/MMBtu heat input) measured or predicted;

(3) The 30-day average NO_x emission rates (ng/J or lb/MMBtu heat input) calculated at the end of each steam generating unit operating day from the measured or predicted hourly nitrogen oxide emission rates for the preceding 30 steam generating unit operating days;

(4) Identification of the steam generating unit operating days when the calculated 30-day average NO_x emission rates are in excess of the NO_x emissions standards under §60.44b, with the reasons for such excess emissions as well as a description of corrective actions taken;

(5) Identification of the steam generating unit operating days for which pollutant data have not been obtained, including reasons for not obtaining sufficient data and a description of corrective actions taken;

(6) Identification of the times when emission data have been excluded from the calculation of average emission rates and the reasons for excluding data;

(7) Identification of "F" factor used for calculations, method of determination, and type of fuel combusted;

(8) Identification of the times when the pollutant concentration exceeded full span of the CEMS;

(9) Description of any modifications to the CEMS that could affect the ability of the CEMS to comply with Performance Specification 2 or 3; and

(10) Results of daily CEMS drift tests and quarterly accuracy assessments as required under appendix F, Procedure 1 of this part.

(h) The owner or operator of any affected facility in any category listed in paragraphs (h)(1) or (2) of this section is required to submit excess emission reports for any excess emissions that occurred during the reporting period.

(1) Any affected facility subject to the opacity standards in §60.43b(f) or to the operating parameter monitoring requirements in §60.13(i)(1).

(2) Any affected facility that is subject to the NO_x standard of §60.44b, and that:

(i) Combusts natural gas, distillate oil, gasified coal, or residual oil with a nitrogen content of 0.3 weight percent or less; or

(ii) Has a heat input capacity of 73 MW (250 MMBtu/hr) or less and is required to monitor NO_x emissions on a continuous basis under §60.48b(g)(1) or steam generating unit operating conditions under §60.48b(g)(2).

(3) For the purpose of §60.43b, excess emissions are defined as all 6-minute periods during which the average opacity exceeds the opacity standards under §60.43b(f).

(4) For purposes of §60.48b(g)(1), excess emissions are defined as any calculated 30-day rolling average NO_x emission rate, as determined under §60.46b(e), that exceeds the applicable emission limits in §60.44b.

(i) The owner or operator of any affected facility subject to the continuous monitoring requirements for NO_x under §60.48(b) shall submit reports containing the information recorded under paragraph (g) of this section.

(j) The owner or operator of any affected facility subject to the SO₂ standards under §60.42b shall submit reports.

(k) For each affected facility subject to the compliance and performance testing requirements of §60.45b and the reporting requirement in paragraph (j) of this section, the following information shall be reported to the Administrator:

(1) Calendar dates covered in the reporting period;

(2) Each 30-day average SO₂ emission rate (ng/J or lb/MMBtu heat input) measured during the reporting period, ending with the last 30-day period; reasons for noncompliance with the emission standards; and a description of corrective actions taken; For an exceedance due to maintenance of the SO₂ control system covered in paragraph 60.45b(a), the report shall identify the days on which the maintenance was performed and a description of the maintenance;

(3) Each 30-day average percent reduction in SO₂ emissions calculated during the reporting period, ending with the last 30-day period; reasons for noncompliance with the emission standards; and a description of corrective actions taken;

(4) Identification of the steam generating unit operating days that coal or oil was combusted and for which SO₂ or diluent (O₂ or CO₂) data have not been obtained by an approved method for at least 75 percent of the operating hours in the steam generating unit operating day; justification for not obtaining sufficient data; and description of corrective action taken;

(5) Identification of the times when emissions data have been excluded from the calculation of average emission rates; justification for excluding data; and description of corrective action taken if data have been excluded for periods other than those during which coal or oil were not combusted in the steam generating unit;

(6) Identification of "F" factor used for calculations, method of determination, and type of fuel combusted;

(7) Identification of times when hourly averages have been obtained based on manual sampling methods;

(8) Identification of the times when the pollutant concentration exceeded full span of the CEMS;

(9) Description of any modifications to the CEMS that could affect the ability of the CEMS to comply with Performance Specification 2 or 3;

(10) Results of daily CEMS drift tests and quarterly accuracy assessments as required under appendix F, Procedure 1 of this part; and

(11) The annual capacity factor of each fired as provided under paragraph (d) of this section.

(l) For each affected facility subject to the compliance and performance testing requirements of §60.45b(d) and the reporting requirements of paragraph (j) of this section, the following information shall be reported to the Administrator:

(1) Calendar dates when the facility was in operation during the reporting period;

(2) The 24-hour average SO₂ emission rate measured for each steam generating unit operating day during the reporting period that coal or oil was combusted, ending in the last 24-hour period in the quarter; reasons for noncompliance with the emission standards; and a description of corrective actions taken;

(3) Identification of the steam generating unit operating days that coal or oil was combusted for which SO₂ or diluent (O₂ or CO₂) data have not been obtained by an approved method for at least 75 percent of the operating hours; justification for not obtaining sufficient data; and description of corrective action taken;

(4) Identification of the times when emissions data have been excluded from the calculation of average emission rates; justification for excluding data; and description of corrective action taken if data have been excluded for periods other than those during which coal or oil were not combusted in the steam generating unit;

(5) Identification of "F" factor used for calculations, method of determination, and type of fuel combusted;

(6) Identification of times when hourly averages have been obtained based on manual sampling methods;

(7) Identification of the times when the pollutant concentration exceeded full span of the CEMS;

(8) Description of any modifications to the CEMS that could affect the ability of the CEMS to comply with Performance Specification 2 or 3; and

(9) Results of daily CEMS drift tests and quarterly accuracy assessments as required under Procedure 1 of appendix F 1 of this part. If the owner or operator elects to implement the alternative data assessment procedures described in §§60.47b(e)(4)(i) through (e)(4)(iii), each data assessment report shall include a summary of the results of all of the RATAs, linearity checks, CGAs, and calibration error or drift assessments required by §§60.47b(e)(4)(i) through (e)(4)(iii).

(m) For each affected facility subject to the SO₂ standards in §60.42(b) for which the minimum amount of data required in §60.47b(c) were not obtained during the reporting period, the following information is reported to the Administrator in addition to that required under paragraph (k) of this section:

(1) The number of hourly averages available for outlet emission rates and inlet emission rates;

(2) The standard deviation of hourly averages for outlet emission rates and inlet emission rates, as determined in Method 19 of appendix A of this part, section 7;

(3) The lower confidence limit for the mean outlet emission rate and the upper confidence limit for the mean inlet emission rate, as calculated in Method 19 of appendix A of this part, section 7; and

(4) The ratio of the lower confidence limit for the mean outlet emission rate and the allowable emission rate, as determined in Method 19 of appendix A of this part, section 7.

(n) If a percent removal efficiency by fuel pretreatment (*i.e.* , %R_f) is used to determine the overall percent reduction (*i.e.* , %R_o) under §60.45b, the owner or operator of the affected facility shall submit a signed statement with the report.

(1) Indicating what removal efficiency by fuel pretreatment (*i.e.* , %R_f) was credited during the reporting period;

(2) Listing the quantity, heat content, and date each pre-treated fuel shipment was received during the reporting period, the name and location of the fuel pretreatment facility; and the total quantity and total heat content of all fuels received at the affected facility during the reporting period;

(3) Documenting the transport of the fuel from the fuel pretreatment facility to the steam generating unit; and

(4) Including a signed statement from the owner or operator of the fuel pretreatment facility certifying that the percent removal efficiency achieved by fuel pretreatment was determined in accordance with the provisions of Method 19 of appendix A of this part and listing the heat content and sulfur content of each fuel before and after fuel pretreatment.

(o) All records required under this section shall be maintained by the owner or operator of the affected facility for a period of 2 years following the date of such record.

(p) The owner or operator of an affected facility described in §60.44b(j) or (k) shall maintain records of the following information for each steam generating unit operating day:

(1) Calendar date;

(2) The number of hours of operation; and

(3) A record of the hourly steam load.

(q) The owner or operator of an affected facility described in §60.44b(j) or §60.44b(k) shall submit to the Administrator a report containing:

(1) The annual capacity factor over the previous 12 months;

(2) The average fuel nitrogen content during the reporting period, if residual oil was fired; and

(3) If the affected facility meets the criteria described in §60.44b(j), the results of any NO_x emission tests required during the reporting period, the hours of operation during the reporting period, and the hours of operation since the last NO_x emission test.

(r) The owner or operator of an affected facility who elects to use the fuel based compliance alternatives in §60.42b or §60.43b shall either:

(1) The owner or operator of an affected facility who elects to demonstrate that the affected facility combusts only very low sulfur oil, natural gas, wood, a mixture of these fuels, or any of these fuels (or a mixture of these fuels) in combination with other fuels that are known to contain an insignificant amount of sulfur in §60.42b(j) or §60.42b(k) shall obtain and maintain at the affected facility fuel receipts from the fuel supplier that certify that the oil meets the definition of distillate oil and gaseous fuel meets the definition of natural gas as defined in §60.41b and the applicable sulfur limit. For the purposes of this section, the distillate oil need not meet the fuel nitrogen content specification in the definition of distillate oil. Reports shall be submitted to the Administrator certifying that only very low sulfur oil meeting this definition, natural gas, wood, and/or other fuels that are known to contain insignificant amounts of sulfur were combusted in the affected facility during the reporting period; or

(2) The owner or operator of an affected facility who elects to demonstrate compliance based on fuel analysis in §60.42b or §60.43b shall develop and submit a site-specific fuel analysis plan to the Administrator for review and approval no later than 60 days before the date you intend to demonstrate compliance. Each fuel analysis plan shall include a minimum initial requirement of weekly testing and each analysis report shall contain, at a minimum, the following information:

(i) The potential sulfur emissions rate of the representative fuel mixture in ng/J heat input;

(ii) The method used to determine the potential sulfur emissions rate of each constituent of the mixture. For distillate oil and natural gas a fuel receipt or tariff sheet is acceptable;

(iii) The ratio of different fuels in the mixture; and

(iv) The owner or operator can petition the Administrator to approve monthly or quarterly sampling in place of weekly sampling.

(s) Facility specific NO_x standard for Cytec Industries Fortier Plant's C.AOG incinerator located in Westwego, Louisiana:

(1) *Definitions* .

Oxidation zone is defined as the portion of the C.AOG incinerator that extends from the inlet of the oxidizing zone combustion air to the outlet gas stack.

Reducing zone is defined as the portion of the C.AOG incinerator that extends from the burner section to the inlet of the oxidizing zone combustion air.

Total inlet air is defined as the total amount of air introduced into the C.AOG incinerator for combustion of natural gas and chemical by-product waste and is equal to the sum of the air flow into the reducing zone and the air flow into the oxidation zone.

(2) *Standard for nitrogen oxides* . (i) When fossil fuel alone is combusted, the NO_x emission limit for fossil fuel in §60.44b(a) applies.

(ii) When natural gas and chemical by-product waste are simultaneously combusted, the NO_x emission limit is 289 ng/J (0.67 lb/MMBtu) and a maximum of 81 percent of the total inlet air provided for combustion shall be provided to the reducing zone of the C.AOG incinerator.

(3) *Emission monitoring* . (i) The percent of total inlet air provided to the reducing zone shall be determined at least every 15 minutes by measuring the air flow of all the air entering the reducing zone and the air flow of all the air entering the oxidation zone, and compliance with the percentage of total inlet air that is provided to the reducing zone shall be determined on a 3-hour average basis.

(ii) The NO_x emission limit shall be determined by the compliance and performance test methods and procedures for NO_x in §60.46b(i).

(iii) The monitoring of the NO_x emission limit shall be performed in accordance with §60.48b.

(4) *Reporting and recordkeeping requirements* . (i) The owner or operator of the C.AOG incinerator shall submit a report on any excursions from the limits required by paragraph (a)(2) of this section to the Administrator with the quarterly report required by paragraph (i) of this section.

(ii) The owner or operator of the C.AOG incinerator shall keep records of the monitoring required by paragraph (a)(3) of this section for a period of 2 years following the date of such record.

(iii) The owner or operator of the C.AOG incinerator shall perform all the applicable reporting and recordkeeping requirements of this section.

(t) Facility-specific NO_x standard for Rohm and Haas Kentucky Incorporated's Boiler No. 100 located in Louisville, Kentucky:

(1) *Definitions* .

Air ratio control damper is defined as the part of the low NO_x burner that is adjusted to control the split of total combustion air delivered to the reducing and oxidation portions of the combustion flame.

Flue gas recirculation line is defined as the part of Boiler No. 100 that recirculates a portion of the boiler flue gas back into the combustion air.

(2) *Standard for nitrogen oxides* . (i) When fossil fuel alone is combusted, the NO_x emission limit for fossil fuel in §60.44b(a) applies.

(ii) When fossil fuel and chemical by-product waste are simultaneously combusted, the NO_x emission limit is 473 ng/J (1.1 lb/MMBtu), and the air ratio control damper tee handle shall be at a minimum of 5 inches (12.7 centimeters) out of the boiler, and the flue gas recirculation line shall be operated at a minimum of 10 percent open as indicated by its valve opening position indicator.

(3) *Emission monitoring for nitrogen oxides* . (i) The air ratio control damper tee handle setting and the flue gas recirculation line valve opening position indicator setting shall be recorded during each 8-hour operating shift.

(ii) The NO_x emission limit shall be determined by the compliance and performance test methods and procedures for NO_x in §60.46b.

(iii) The monitoring of the NO_x emission limit shall be performed in accordance with §60.48b.

(4) *Reporting and recordkeeping requirements* . (i) The owner or operator of Boiler No. 100 shall submit a report on any excursions from the limits required by paragraph (b)(2) of this section to the Administrator with the quarterly report required by §60.49b(i).

(ii) The owner or operator of Boiler No. 100 shall keep records of the monitoring required by paragraph (b)(3) of this section for a period of 2 years following the date of such record.

(iii) The owner or operator of Boiler No. 100 shall perform all the applicable reporting and recordkeeping requirements of §60.49b.

(u) *Site-specific standard for Merck & Co., Inc.'s Stonewall Plant in Elkton, Virginia* . (1) This paragraph (u) applies only to the pharmaceutical manufacturing facility, commonly referred to as the Stonewall Plant, located at Route 340 South, in Elkton, Virginia ("site") and only to the natural gas-fired boilers installed as part of the powerhouse conversion required pursuant to 40 CFR 52.2454(g). The requirements of this paragraph shall apply, and the requirements of §§60.40b through 60.49b(t) shall not apply, to the natural gas-fired boilers installed pursuant to 40 CFR 52.2454(g).

(i) The site shall equip the natural gas-fired boilers with low NO_x technology.

(ii) The site shall install, calibrate, maintain, and operate a continuous monitoring and recording system for measuring NO_x emissions discharged to the atmosphere and opacity using a continuous emissions monitoring system or a predictive emissions monitoring system.

(iii) Within 180 days of the completion of the powerhouse conversion, as required by 40 CFR 52.2454, the site shall perform a performance test to quantify criteria pollutant emissions.

(2) [Reserved]

(v) The owner or operator of an affected facility may submit electronic quarterly reports for SO₂ and/or NO_x and/or opacity in lieu of submitting the written reports required under paragraphs (h), (i), (j), (k) or (l) of this section. The format of each quarterly electronic report shall be coordinated with the permitting authority. The electronic report(s) shall be submitted no later than 30 days after the end of the calendar quarter and shall be accompanied by a certification statement from the owner or operator, indicating whether compliance with the applicable emission standards and minimum data requirements of this subpart was achieved during the reporting period. Before submitting reports in the electronic format, the owner or operator shall coordinate with the permitting authority to obtain their agreement to submit reports in this alternative format.

(w) The reporting period for the reports required under this subpart is each 6 month period. All reports shall be submitted to the Administrator and shall be postmarked by the 30th day following the end of the reporting period.

(x) Facility-specific NO_x standard for Weyerhaeuser Company's No. 2 Power Boiler located in New Bern, North Carolina:

(1) *Standard for nitrogen oxides*. (i) When fossil fuel alone is combusted, the NO_x emission limit for fossil fuel in §60.44b(a) applies.

(ii) When fossil fuel and chemical by-product waste are simultaneously combusted, the NO_x emission limit is 215 ng/J (0.5 lb/MMBtu).

(2) *Emission monitoring for nitrogen oxides*. (i) The NO_x emissions shall be determined by the compliance and performance test methods and procedures for NO_x in §60.46b.

(ii) The monitoring of the NO_x emissions shall be performed in accordance with §60.48b.

(3) *Reporting and recordkeeping requirements*. (i) The owner or operator of the No. 2 Power Boiler shall submit a report on any excursions from the limits required by paragraph (x)(2) of this section to the Administrator with the quarterly report required by §60.49b(i).

(ii) The owner or operator of the No. 2 Power Boiler shall keep records of the monitoring required by paragraph (x)(3) of this section for a period of 2 years following the date of such record.

(iii) The owner or operator of the No. 2 Power Boiler shall perform all the applicable reporting and recordkeeping requirements of §60.49b.

(y) Facility-specific NO_x standard for INEOS USA's AOGI located in Lima, Ohio:

(1) *Standard for NO_x*. (i) When fossil fuel alone is combusted, the NO_x emission limit for fossil fuel in §60.44b(a) applies.

(ii) When fossil fuel and chemical byproduct/waste are simultaneously combusted, the NO_x emission limit is 645 ng/J (1.5 lb/MMBtu).

(2) *Emission monitoring for NO_x*. (i) The NO_x emissions shall be determined by the compliance and performance test methods and procedures for NO_x in §60.46b.

(ii) The monitoring of the NO_x emissions shall be performed in accordance with §60.48b.

(3) *Reporting and recordkeeping requirements*. (i) The owner or operator of the AOGI shall submit a report on any excursions from the limits required by paragraph (y)(2) of this section to the Administrator with the quarterly report required by paragraph (i) of this section.

(ii) The owner or operator of the AOGI shall keep records of the monitoring required by paragraph (y)(3) of this section for a period of 2 years following the date of such record.

(iii) The owner or operator of the AOGI shall perform all the applicable reporting and recordkeeping requirements of this section.

**Indiana Department of Environmental Management
Office of Air Quality**

Attachment C

**Subpart Kb—Standards of Performance for Volatile Organic Liquid Storage Vessels
(Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or
Modification Commenced After July 23, 1984**

Source: 52 FR 11429, Apr. 8, 1987, unless otherwise noted.

§ 60.110b Applicability and designation of affected facility.

(a) Except as provided in paragraph (b) of this section, the affected facility to which this subpart applies is each storage vessel with a capacity greater than or equal to 75 cubic meters (m^3) that is used to store volatile organic liquids (VOL) for which construction, reconstruction, or modification is commenced after July 23, 1984.

(b) This subpart does not apply to storage vessels with a capacity greater than or equal to 151 m^3 storing a liquid with a maximum true vapor pressure less than 3.5 kilopascals (kPa) or with a capacity greater than or equal to 75 m^3 but less than 151 m^3 storing a liquid with a maximum true vapor pressure less than 15.0 kPa.

(c) [Reserved]

(d) This subpart does not apply to the following:

- (1) Vessels at coke oven by-product plants.
- (2) Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
- (3) Vessels permanently attached to mobile vehicles such as trucks, railcars, barges, or ships.
- (4) Vessels with a design capacity less than or equal to 1,589.874 m^3 used for petroleum or condensate stored, processed, or treated prior to custody transfer.
- (5) Vessels located at bulk gasoline plants.
- (6) Storage vessels located at gasoline service stations.
- (7) Vessels used to store beverage alcohol.
- (8) Vessels subject to subpart GGGG of 40 CFR part 63.

(e) *Alternative means of compliance* —(1) *Option to comply with part 65.* Owners or operators may choose to comply with 40 CFR part 65, subpart C, to satisfy the requirements of §§60.112b through 60.117b for storage vessels that are subject to this subpart that meet the specifications in paragraphs (e)(1)(i) and (ii) of this section. When choosing to comply with 40 CFR part 65, subpart C, the monitoring requirements of §60.116b(c), (e), (f)(1), and (g) still apply. Other provisions applying to owners or operators who choose to comply with 40 CFR part 65 are provided in 40 CFR 65.1.

(i) A storage vessel with a design capacity greater than or equal to 151 m^3 containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 5.2 kPa; or

(ii) A storage vessel with a design capacity greater than 75 m^3 but less than 151 m^3 containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 27.6 kPa.

(2) *Part 60, subpart A.* Owners or operators who choose to comply with 40 CFR part 65, subpart C, must also comply with §§60.1, 60.2, 60.5, 60.6, 60.7(a)(1) and (4), 60.14, 60.15, and 60.16 for those storage vessels. All sections and paragraphs of subpart A of this part that are not mentioned in this paragraph (e)(2) do not apply to owners or operators of storage vessels complying with 40 CFR part 65, subpart C, except that provisions required to be met prior to implementing 40 CFR part 65 still apply. Owners and operators who choose to comply with 40 CFR part 65, subpart C, must comply with 40 CFR part 65, subpart A.

(3) *Internal floating roof report.* If an owner or operator installs an internal floating roof and, at initial startup, chooses to comply with 40 CFR part 65, subpart C, a report shall be furnished to the Administrator stating that the control equipment meets the specifications of 40 CFR 65.43. This report shall be an attachment to the notification required by 40 CFR 65.5(b).

(4) *External floating roof report.* If an owner or operator installs an external floating roof and, at initial startup, chooses to comply with 40 CFR part 65, subpart C, a report shall be furnished to the Administrator stating that the control equipment meets the specifications of 40 CFR 65.44. This report shall be an attachment to the notification required by 40 CFR 65.5(b).

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989; 65 FR 78275, Dec. 14, 2000; 68 FR 59332, Oct. 15, 2003]

§ 60.111b Definitions.

Terms used in this subpart are defined in the Act, in subpart A of this part, or in this subpart as follows:

Bulk gasoline plant means any gasoline distribution facility that has a gasoline throughput less than or equal to 75,700 liters per day. Gasoline throughput shall be the maximum calculated design throughput as may be limited by compliance with an enforceable condition under Federal requirement or Federal, State or local law, and discoverable by the Administrator and any other person.

Condensate means hydrocarbon liquid separated from natural gas that condenses due to changes in the temperature or pressure, or both, and remains liquid at standard conditions.

Custody transfer means the transfer of produced petroleum and/or condensate, after processing and/or treatment in the producing operations, from storage vessels or automatic transfer facilities to pipelines or any other forms of transportation.

Fill means the introduction of VOL into a storage vessel but not necessarily to complete capacity.

Gasoline service station means any site where gasoline is dispensed to motor vehicle fuel tanks from stationary storage tanks.

Maximum true vapor pressure means the equilibrium partial pressure exerted by the volatile organic compounds (as defined in 40 CFR 51.100) in the stored VOL at the temperature equal to the highest calendar-month average of the VOL storage temperature for VOL's stored above or below the ambient temperature or at the local maximum monthly average temperature as reported by the National Weather Service for VOL's stored at the ambient temperature, as determined:

(1) In accordance with methods described in American Petroleum Institute Bulletin 2517, Evaporation Loss From External Floating Roof Tanks, (incorporated by reference—see §60.17); or

(2) As obtained from standard reference texts; or

(3) As determined by ASTM D2879–83, 96, or 97 (incorporated by reference—see §60.17);

(4) Any other method approved by the Administrator.

Petroleum means the crude oil removed from the earth and the oils derived from tar sands, shale, and coal.

Petroleum liquids means petroleum, condensate, and any finished or intermediate products manufactured in a petroleum refinery.

Process tank means a tank that is used within a process (including a solvent or raw material recovery process) to collect material discharged from a feedstock storage vessel or equipment within the process before the material is transferred to other equipment within the process, to a product or by-product storage vessel, or to a vessel used to store recovered solvent or raw material. In many process tanks, unit operations such as reactions and blending are conducted. Other process tanks, such as surge control vessels and bottoms receivers, however, may not involve unit operations.

Reid vapor pressure means the absolute vapor pressure of volatile crude oil and volatile nonviscous petroleum liquids except liquified petroleum gases, as determined by ASTM D323–82 or 94 (incorporated by reference—see §60.17).

Storage vessel means each tank, reservoir, or container used for the storage of volatile organic liquids but does not include:

- (1) Frames, housing, auxiliary supports, or other components that are not directly involved in the containment of liquids or vapors;
- (2) Subsurface caverns or porous rock reservoirs; or
- (3) Process tanks.

Volatile organic liquid (VOL) means any organic liquid which can emit volatile organic compounds (as defined in 40 CFR 51.100) into the atmosphere.

Waste means any liquid resulting from industrial, commercial, mining or agricultural operations, or from community activities that is discarded or is being accumulated, stored, or physically, chemically, or biologically treated prior to being discarded or recycled.

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989; 65 FR 61756, Oct. 17, 2000; 68 FR 59333, Oct. 15, 2003]

§ 60.112b Standard for volatile organic compounds (VOC).

(a) The owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 5.2 kPa but less than 76.6 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 27.6 kPa but less than 76.6 kPa, shall equip each storage vessel with one of the following:

- (1) A fixed roof in combination with an internal floating roof meeting the following specifications:
 - (i) The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.
 - (ii) Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:

(A) A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.

(B) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.

(C) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.

(iii) Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.

(iv) Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.

(v) Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

(vi) Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.

(vii) Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.

(viii) Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.

(ix) Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

(2) An external floating roof. An external floating roof means a pontoon-type or double-deck type cover that rests on the liquid surface in a vessel with no fixed roof. Each external floating roof must meet the following specifications:

(i) Each external floating roof shall be equipped with a closure device between the wall of the storage vessel and the roof edge. The closure device is to consist of two seals, one above the other. The lower seal is referred to as the primary seal, and the upper seal is referred to as the secondary seal.

(A) The primary seal shall be either a mechanical shoe seal or a liquid-mounted seal. Except as provided in §60.113b(b)(4), the seal shall completely cover the annular space between the edge of the floating roof and tank wall.

(B) The secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion except as allowed in §60.113b(b)(4).

(ii) Except for automatic bleeder vents and rim space vents, each opening in a noncontact external floating roof shall provide a projection below the liquid surface. Except for automatic bleeder vents, rim space vents, roof drains, and leg sleeves, each opening in the roof is to be equipped with a gasketed cover, seal, or lid that is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. Automatic bleeder vents are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. Rim vents are to be set to open when the

roof is being floated off the roof legs supports or at the manufacturer's recommended setting. Automatic bleeder vents and rim space vents are to be gasketed. Each emergency roof drain is to be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening.

(iii) The roof shall be floating on the liquid at all times (i.e., off the roof leg supports) except during initial fill until the roof is lifted off leg supports and when the tank is completely emptied and subsequently refilled. The process of filling, emptying, or refilling when the roof is resting on the leg supports shall be continuous and shall be accomplished as rapidly as possible.

(3) A closed vent system and control device meeting the following specifications:

(i) The closed vent system shall be designed to collect all VOC vapors and gases discharged from the storage vessel and operated with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background and visual inspections, as determined in part 60, subpart VV, §60.485(b).

(ii) The control device shall be designed and operated to reduce inlet VOC emissions by 95 percent or greater. If a flare is used as the control device, it shall meet the specifications described in the general control device requirements (§60.18) of the General Provisions.

(4) A system equivalent to those described in paragraphs (a)(1), (a)(2), or (a)(3) of this section as provided in §60.114b of this subpart.

(b) The owner or operator of each storage vessel with a design capacity greater than or equal to 75 m³ which contains a VOL that, as stored, has a maximum true vapor pressure greater than or equal to 76.6 kPa shall equip each storage vessel with one of the following:

(1) A closed vent system and control device as specified in §60.112b(a)(3).

(2) A system equivalent to that described in paragraph (b)(1) as provided in §60.114b of this subpart.

(c) *Site-specific standard for Merck & Co., Inc.'s Stonewall Plant in Elkton, Virginia.* This paragraph applies only to the pharmaceutical manufacturing facility, commonly referred to as the Stonewall Plant, located at Route 340 South, in Elkton, Virginia ("site").

(1) For any storage vessel that otherwise would be subject to the control technology requirements of paragraphs (a) or (b) of this section, the site shall have the option of either complying directly with the requirements of this subpart, or reducing the site-wide total criteria pollutant emissions cap (total emissions cap) in accordance with the procedures set forth in a permit issued pursuant to 40 CFR 52.2454. If the site chooses the option of reducing the total emissions cap in accordance with the procedures set forth in such permit, the requirements of such permit shall apply in lieu of the otherwise applicable requirements of this subpart for such storage vessel.

(2) For any storage vessel at the site not subject to the requirements of 40 CFR 60.112b (a) or (b), the requirements of 40 CFR 60.116b (b) and (c) and the General Provisions (subpart A of this part) shall not apply.

[52 FR 11429, Apr. 8, 1987, as amended at 62 FR 52641, Oct. 8, 1997]

§ 60.113b Testing and procedures.

The owner or operator of each storage vessel as specified in §60.112b(a) shall meet the requirements of paragraph (a), (b), or (c) of this section. The applicable paragraph for a particular storage vessel depends on the control equipment installed to meet the requirements of §60.112b.

(a) After installing the control equipment required to meet §60.112b(a)(1) (permanently affixed roof and internal floating roof), each owner or operator shall:

(1) Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.

(2) For Vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in §60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.

(3) For vessels equipped with a double-seal system as specified in §60.112b(a)(1)(ii)(B):

(i) Visually inspect the vessel as specified in paragraph (a)(4) of this section at least every 5 years; or

(ii) Visually inspect the vessel as specified in paragraph (a)(2) of this section.

(4) Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraphs (a)(2) and (a)(3)(ii) of this section and at intervals no greater than 5 years in the case of vessels specified in paragraph (a)(3)(i) of this section.

(5) Notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs (a)(1) and (a)(4) of this section to afford the Administrator the opportunity to have an observer present. If the inspection required by paragraph (a)(4) of this section is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.

(b) After installing the control equipment required to meet §60.112b(a)(2) (external floating roof), the owner or operator shall:

(1) Determine the gap areas and maximum gap widths, between the primary seal and the wall of the storage vessel and between the secondary seal and the wall of the storage vessel according to the following frequency.

(i) Measurements of gaps between the tank wall and the primary seal (seal gaps) shall be performed during the hydrostatic testing of the vessel or within 60 days of the initial fill with VOL and at least once every 5 years thereafter.

(ii) Measurements of gaps between the tank wall and the secondary seal shall be performed within 60 days of the initial fill with VOL and at least once per year thereafter.

(iii) If any source ceases to store VOL for a period of 1 year or more, subsequent introduction of VOL into the vessel shall be considered an initial fill for the purposes of paragraphs (b)(1)(i) and (b)(1)(ii) of this section.

(2) Determine gap widths and areas in the primary and secondary seals individually by the following procedures:

(i) Measure seal gaps, if any, at one or more floating roof levels when the roof is floating off the roof leg supports.

(ii) Measure seal gaps around the entire circumference of the tank in each place where a 0.32-cm diameter uniform probe passes freely (without forcing or binding against seal) between the seal and the wall of the storage vessel and measure the circumferential distance of each such location.

(iii) The total surface area of each gap described in paragraph (b)(2)(ii) of this section shall be determined by using probes of various widths to measure accurately the actual distance from the tank wall to the seal and multiplying each such width by its respective circumferential distance.

(3) Add the gap surface area of each gap location for the primary seal and the secondary seal individually and divide the sum for each seal by the nominal diameter of the tank and compare each ratio to the respective standards in paragraph (b)(4) of this section.

(4) Make necessary repairs or empty the storage vessel within 45 days of identification in any inspection for seals not meeting the requirements listed in (b)(4) (i) and (ii) of this section:

(i) The accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 Cm^2 per meter of tank diameter, and the width of any portion of any gap shall not exceed 3.81 cm.

(A) One end of the mechanical shoe is to extend into the stored liquid, and the other end is to extend a minimum vertical distance of 61 cm above the stored liquid surface.

(B) There are to be no holes, tears, or other openings in the shoe, seal fabric, or seal envelope.

(ii) The secondary seal is to meet the following requirements:

(A) The secondary seal is to be installed above the primary seal so that it completely covers the space between the roof edge and the tank wall except as provided in paragraph (b)(2)(iii) of this section.

(B) The accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm^2 per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm.

(C) There are to be no holes, tears, or other openings in the seal or seal fabric.

(iii) If a failure that is detected during inspections required in paragraph (b)(1) of §60.113b(b) cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in §60.115b(b)(4). Such extension request must include a demonstration of unavailability of alternate storage capacity and a specification of a schedule that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.

(5) Notify the Administrator 30 days in advance of any gap measurements required by paragraph (b)(1) of this section to afford the Administrator the opportunity to have an observer present.

(6) Visually inspect the external floating roof, the primary seal, secondary seal, and fittings each time the vessel is emptied and degassed.

(i) If the external floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before filling or refilling the storage vessel with VOL.

(ii) For all the inspections required by paragraph (b)(6) of this section, the owner or operator shall notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the Administrator the opportunity to inspect the storage vessel prior to refilling. If the inspection required by paragraph (b)(6) of this section is not planned and the owner or operator could not have known about the inspection 30 days in advance of refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.

(c) The owner or operator of each source that is equipped with a closed vent system and control device as required in §60.112b (a)(3) or (b)(2) (other than a flare) is exempt from §60.8 of the General Provisions and shall meet the following requirements.

(1) Submit for approval by the Administrator as an attachment to the notification required by §60.7(a)(1) or, if the facility is exempt from §60.7(a)(1), as an attachment to the notification required by §60.7(a)(2), an operating plan containing the information listed below.

(i) Documentation demonstrating that the control device will achieve the required control efficiency during maximum loading conditions. This documentation is to include a description of the gas stream which enters the control device, including flow and VOC content under varying liquid level conditions (dynamic and static) and manufacturer's design specifications for the control device. If the control device or the closed vent capture system receives vapors, gases, or liquids other than fuels from sources that are not designated sources under this subpart, the efficiency demonstration is to include consideration of all vapors, gases, and liquids received by the closed vent capture system and control device. If an enclosed combustion device with a minimum residence time of 0.75 seconds and a minimum temperature of 816 °C is used to meet the 95 percent requirement, documentation that those conditions will exist is sufficient to meet the requirements of this paragraph.

(ii) A description of the parameter or parameters to be monitored to ensure that the control device will be operated in conformance with its design and an explanation of the criteria used for selection of that parameter (or parameters).

(2) Operate the closed vent system and control device and monitor the parameters of the closed vent system and control device in accordance with the operating plan submitted to the Administrator in accordance with paragraph (c)(1) of this section, unless the plan was modified by the Administrator during the review process. In this case, the modified plan applies.

(d) The owner or operator of each source that is equipped with a closed vent system and a flare to meet the requirements in §60.112b (a)(3) or (b)(2) shall meet the requirements as specified in the general control device requirements, §60.18 (e) and (f).

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989]

§ 60.114b Alternative means of emission limitation.

(a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in emissions at least equivalent to the reduction in emissions achieved by any requirement in §60.112b, the Administrator will publish in the Federal Register a notice permitting the use of the alternative means for purposes of compliance with that requirement.

(b) Any notice under paragraph (a) of this section will be published only after notice and an opportunity for a hearing.

(c) Any person seeking permission under this section shall submit to the Administrator a written application including:

(1) An actual emissions test that uses a full-sized or scale-model storage vessel that accurately collects and measures all VOC emissions from a given control device and that accurately simulates wind and accounts for other emission variables such as temperature and barometric pressure.

(2) An engineering evaluation that the Administrator determines is an accurate method of determining equivalence.

(d) The Administrator may condition the permission on requirements that may be necessary to ensure operation and maintenance to achieve the same emissions reduction as specified in §60.112b.

§ 60.115b Reporting and recordkeeping requirements.

The owner or operator of each storage vessel as specified in §60.112b(a) shall keep records and furnish reports as required by paragraphs (a), (b), or (c) of this section depending upon the control equipment installed to meet the requirements of §60.112b. The owner or operator shall keep copies of all reports and records required by this section, except for the record required by (c)(1), for at least 2 years. The record required by (c)(1) will be kept for the life of the control equipment.

(a) After installing control equipment in accordance with §60.112b(a)(1) (fixed roof and internal floating roof), the owner or operator shall meet the following requirements.

(1) Furnish the Administrator with a report that describes the control equipment and certifies that the control equipment meets the specifications of §60.112b(a)(1) and §60.113b(a)(1). This report shall be an attachment to the notification required by §60.7(a)(3).

(2) Keep a record of each inspection performed as required by §60.113b (a)(1), (a)(2), (a)(3), and (a)(4). Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).

(3) If any of the conditions described in §60.113b(a)(2) are detected during the annual visual inspection required by §60.113b(a)(2), a report shall be furnished to the Administrator within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.

(4) After each inspection required by §60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in §60.113b(a)(3)(ii), a report shall be furnished to the Administrator within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of §60.112b(a)(1) or §60.113b(a)(3) and list each repair made.

(b) After installing control equipment in accordance with §60.112b(a)(2) (external floating roof), the owner or operator shall meet the following requirements.

(1) Furnish the Administrator with a report that describes the control equipment and certifies that the control equipment meets the specifications of §60.112b(a)(2) and §60.113b(b)(2), (b)(3), and (b)(4). This report shall be an attachment to the notification required by §60.7(a)(3).

(2) Within 60 days of performing the seal gap measurements required by §60.113b(b)(1), furnish the Administrator with a report that contains:

(i) The date of measurement.

(ii) The raw data obtained in the measurement.

(iii) The calculations described in §60.113b (b)(2) and (b)(3).

(3) Keep a record of each gap measurement performed as required by §60.113b(b). Each record shall identify the storage vessel in which the measurement was performed and shall contain:

(i) The date of measurement.

(ii) The raw data obtained in the measurement.

(iii) The calculations described in §60.113b (b)(2) and (b)(3).

(4) After each seal gap measurement that detects gaps exceeding the limitations specified by §60.113b(b)(4), submit a report to the Administrator within 30 days of the inspection. The report will identify the vessel and contain the information specified in paragraph (b)(2) of this section and the date the vessel was emptied or the repairs made and date of repair.

(c) After installing control equipment in accordance with §60.112b (a)(3) or (b)(1) (closed vent system and control device other than a flare), the owner or operator shall keep the following records.

(1) A copy of the operating plan.

(2) A record of the measured values of the parameters monitored in accordance with §60.113b(c)(2).

(d) After installing a closed vent system and flare to comply with §60.112b, the owner or operator shall meet the following requirements.

(1) A report containing the measurements required by §60.18(f) (1), (2), (3), (4), (5), and (6) shall be furnished to the Administrator as required by §60.8 of the General Provisions. This report shall be submitted within 6 months of the initial start-up date.

(2) Records shall be kept of all periods of operation during which the flare pilot flame is absent.

(3) Semiannual reports of all periods recorded under §60.115b(d)(2) in which the pilot flame was absent shall be furnished to the Administrator.

§ 60.116b Monitoring of operations.

(a) The owner or operator shall keep copies of all records required by this section, except for the record required by paragraph (b) of this section, for at least 2 years. The record required by paragraph (b) of this section will be kept for the life of the source.

(b) The owner or operator of each storage vessel as specified in §60.110b(a) shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel.

(c) Except as provided in paragraphs (f) and (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure greater than or equal to 3.5 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ storing a liquid with a maximum true vapor pressure greater than or equal to 15.0 kPa shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.

(d) Except as provided in paragraph (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure that is normally less than 5.2 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ storing a liquid with a maximum true vapor pressure that is normally less than 27.6 kPa shall notify the Administrator within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range.

(e) Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.

(1) For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

(2) For crude oil or refined petroleum products the vapor pressure may be obtained by the following:

(i) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see §60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).

(ii) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.

(3) For other liquids, the vapor pressure:

(i) May be obtained from standard reference texts, or

(ii) Determined by ASTM D2879–83, 96, or 97 (incorporated by reference—see §60.17); or

(iii) Measured by an appropriate method approved by the Administrator; or

(iv) Calculated by an appropriate method approved by the Administrator.

(f) The owner or operator of each vessel storing a waste mixture of indeterminate or variable composition shall be subject to the following requirements.

(1) Prior to the initial filling of the vessel, the highest maximum true vapor pressure for the range of anticipated liquid compositions to be stored will be determined using the methods described in paragraph (e) of this section.

(2) For vessels in which the vapor pressure of the anticipated liquid composition is above the cutoff for monitoring but below the cutoff for controls as defined in §60.112b(a), an initial physical test of the vapor pressure is required; and a physical test at least once every 6 months thereafter is required as determined by the following methods:

(i) ASTM D2879–83, 96, or 97 (incorporated by reference—see §60.17); or

(ii) ASTM D323–82 or 94 (incorporated by reference—see §60.17); or

(iii) As measured by an appropriate method as approved by the Administrator.

(g) The owner or operator of each vessel equipped with a closed vent system and control device meeting the specification of §60.112b or with emissions reductions equipment as specified in 40 CFR 65.42(b)(4), (b)(5), (b)(6), or (c) is exempt from the requirements of paragraphs (c) and (d) of this section.

[52 FR 11429, Apr. 8, 1987, as amended at 65 FR 61756, Oct. 17, 2000; 65 FR 78276, Dec. 14, 2000; 68 FR 59333, Oct. 15, 2003]

§ 60.117b Delegation of authority.

(a) In delegating implementation and enforcement authority to a State under section 111(c) of the Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.

(b) Authorities which will not be delegated to States: §§60.111b(f)(4), 60.114b, 60.116b(e)(3)(iii), 60.116b(e)(3)(iv), and 60.116b(f)(2)(iii).

[52 FR 11429, Apr. 8, 1987, as amended at 52 FR 22780, June 16, 1987]

**Indiana Department of Environmental Management
Office of Air Quality**

Attachment D

Title 40: Protection of Environment

PART 60—STANDARDS OF PERFORMANCE FOR NEW STATIONARY SOURCES

Subpart VVa—Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006

Source: 72 FR 64883, Nov. 16, 2007, unless otherwise noted.

§ 60.480a Applicability and designation of affected facility.

(a)(1) The provisions of this subpart apply to affected facilities in the synthetic organic chemicals manufacturing industry.

(2) The group of all equipment (defined in §60.481a) within a process unit is an affected facility.

(b) Any affected facility under paragraph (a) of this section that commences construction, reconstruction, or modification after November 7, 2006, shall be subject to the requirements of this subpart.

(c) Addition or replacement of equipment for the purpose of process improvement which is accomplished without a capital expenditure shall not by itself be considered a modification under this subpart.

(d)(1) If an owner or operator applies for one or more of the exemptions in this paragraph, then the owner or operator shall maintain records as required in §60.486a(i).

(2) Any affected facility that has the design capacity to produce less than 1,000 Mg/yr (1,102 ton/yr) of a chemical listed in §60.489 is exempt from §§60.482–1a through 60.482–11a.

(3) If an affected facility produces heavy liquid chemicals only from heavy liquid feed or raw materials, then it is exempt from §§60.482–1a through 60.482–11a.

(4) Any affected facility that produces beverage alcohol is exempt from §§60.482–1a through 60.482–11a.

(5) Any affected facility that has no equipment in volatile organic compounds (VOC) service is exempt from §§60.482–1a through 60.482–11a.

(e) *Alternative means of compliance* —(1) *Option to comply with part 65.* (i) Owners or operators may choose to comply with the provisions of 40 CFR part 65, subpart F, to satisfy the requirements of §§60.482–1a through 60.487a for an affected facility. When choosing to comply with 40 CFR part 65, subpart F, the requirements of §§60.485a(d), (e), and (f), and 60.486a(i) and (j) still apply. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in 40 CFR 65.1.

(ii) *Part 60, subpart A.* Owners or operators who choose to comply with 40 CFR part 65, subpart F must also comply with §§60.1, 60.2, 60.5, 60.6, 60.7(a)(1) and (4), 60.14, 60.15, and 60.16 for that equipment. All sections and paragraphs of subpart A of this part that are not mentioned in this paragraph (e)(1)(ii) do not apply to owners or operators of equipment subject to this subpart complying with 40 CFR part 65, subpart F, except that provisions required to be met prior to implementing 40 CFR part 65 still apply. Owners and operators who choose to comply with 40 CFR part 65, subpart F, must comply with 40 CFR part 65, subpart A.

(2) *Part 63, subpart H.* (i) Owners or operators may choose to comply with the provisions of 40 CFR part 63, subpart H, to satisfy the requirements of §§60.482–1a through 60.487a for an affected facility. When choosing to comply with 40 CFR part 63, subpart H, the requirements of §60.485a(d), (e), and (f), and §60.486a(i) and (j) still apply.

(ii) *Part 60, subpart A.* Owners or operators who choose to comply with 40 CFR part 63, subpart H must also comply with §§60.1, 60.2, 60.5, 60.6, 60.7(a)(1) and (4), 60.14, 60.15, and 60.16 for that equipment. All sections and paragraphs of subpart A of this part that are not mentioned in this paragraph (e)(2)(ii) do not apply to owners or operators of equipment subject to this subpart complying with 40 CFR part 63, subpart H, except that provisions required to be met prior to implementing 40 CFR part 63 still apply. Owners and operators who choose to comply with 40 CFR part 63, subpart H, must comply with 40 CFR part 63, subpart A.

(f) *Stay of standards.* (1) Owners or operators that start a new, reconstructed, or modified affected source prior to November 16, 2007 are not required to comply with the requirements in this paragraph until EPA takes final action to require compliance and publishes a document in the Federal Register.

(i) The definition of “capital expenditure” in §60.481a of this subpart. While the definition of “capital expenditure” is stayed, owners or operators should use the definition found in §60.481 of subpart VV of this part.

(ii) [Reserved]

(2) Owners or operators are not required to comply with the requirements in this paragraph until EPA takes final action to require compliance and publishes a document in the Federal Register.

(i) The definition of “process unit” in §60.481a of this subpart. While the definition of “process unit” is stayed, owners or operators should use the following definition:

Process unit means components assembled to produce, as intermediate or final products, one or more of the chemicals listed in §60.489 of this part. A process unit can operate independently if supplied with sufficient feed or raw materials and sufficient storage facilities for the product.

(ii) The method of allocation of shared storage vessels in §60.482–1a(g) of this subpart.

(iii) The standards for connectors in gas/vapor service and in light liquid service in §60.482–11a of this subpart.

[72 FR 64883, Nov. 16, 2007, as amended at 73 FR 31375, June 2, 2008]

§ 60.481a Definitions.

As used in this subpart, all terms not defined herein shall have the meaning given them in the Clean Air Act (CAA) or in subpart A of part 60, and the following terms shall have the specific meanings given them.

Capital expenditure means, in addition to the definition in 40 CFR 60.2, an expenditure for a physical or operational change to an existing facility that:

(a) Exceeds P, the product of the facility's replacement cost, R, and an adjusted annual asset guideline repair allowance, A, as reflected by the following equation: $P = R \times A$, where:

(1) The adjusted annual asset guideline repair allowance, A, is the product of the percent of the replacement cost, Y, and the applicable basic annual asset guideline repair allowance, B, divided by 100 as reflected by the following equation:

$$A = Y \times (B \div 100);$$

(2) The percent Y is determined from the following equation: $Y = 1.0 - 0.575 \log X$, where X is 2006 minus the year of construction; and

(3) The applicable basic annual asset guideline repair allowance, B, is selected from the following table consistent with the applicable subpart:

Table for Determining Applicable Value for B

Subpart applicable to facility	Value of B to be used in equation
VVa	12.5
GGGa	7.0

Closed-loop system means an enclosed system that returns process fluid to the process.

Closed-purge system means a system or combination of systems and portable containers to capture purged liquids. Containers for purged liquids must be covered or closed when not being filled or emptied.

Closed vent system means a system that is not open to the atmosphere and that is composed of hard-piping, ductwork, connections, and, if necessary, flow-inducing devices that transport gas or vapor from a piece or pieces of equipment to a control device or back to a process.

Connector means flanged, screwed, or other joined fittings used to connect two pipe lines or a pipe line and a piece of process equipment or that close an opening in a pipe that could be connected to another pipe. Joined fittings welded completely around the circumference of the interface are not considered connectors for the purpose of this regulation.

Control device means an enclosed combustion device, vapor recovery system, or flare.

Distance piece means an open or enclosed casing through which the piston rod travels, separating the compressor cylinder from the crankcase.

Double block and bleed system means two block valves connected in series with a bleed valve or line that can vent the line between the two block valves.

Duct work means a conveyance system such as those commonly used for heating and ventilation systems. It is often made of sheet metal and often has sections connected by screws or crimping. Hard-piping is not ductwork.

Equipment means each pump, compressor, pressure relief device, sampling connection system, open-ended valve or line, valve, and flange or other connector in VOC service and any devices or systems required by this subpart.

First attempt at repair means to take action for the purpose of stopping or reducing leakage of organic material to the atmosphere using best practices.

Fuel gas means gases that are combusted to derive useful work or heat.

Fuel gas system means the offsite and onsite piping and flow and pressure control system that gathers gaseous stream(s) generated by onsite operations, may blend them with other sources of gas, and transports the gaseous stream for use as fuel gas in combustion devices or in-process combustion equipment, such as furnaces and gas turbines, either singly or in combination.

Hard-piping means pipe or tubing that is manufactured and properly installed using good engineering judgment and standards such as ASME B31.3, Process Piping (available from the American Society of Mechanical Engineers, P.O. Box 2300, Fairfield, NJ 07007–2300).

In gas/vapor service means that the piece of equipment contains process fluid that is in the gaseous state at operating conditions.

In heavy liquid service means that the piece of equipment is not in gas/vapor service or in light liquid service.

In light liquid service means that the piece of equipment contains a liquid that meets the conditions specified in §60.485a(e).

In-situ sampling systems means nonextractive samplers or in-line samplers.

In vacuum service means that equipment is operating at an internal pressure which is at least 5 kilopascals (kPa) (0.7 psia) below ambient pressure.

In VOC service means that the piece of equipment contains or contacts a process fluid that is at least 10 percent VOC by weight. (The provisions of §60.485a(d) specify how to determine that a piece of equipment is not in VOC service.)

Initial calibration value means the concentration measured during the initial calibration at the beginning of each day required in §60.485a(b)(1), or the most recent calibration if the instrument is recalibrated during the day (i.e., the calibration is adjusted) after a calibration drift assessment.

Liquids dripping means any visible leakage from the seal including spraying, misting, clouding, and ice formation.

Open-ended valve or line means any valve, except safety relief valves, having one side of the valve seat in contact with process fluid and one side open to the atmosphere, either directly or through open piping.

Pressure release means the emission of materials resulting from system pressure being greater than set pressure of the pressure relief device.

Process improvement means routine changes made for safety and occupational health requirements, for energy savings, for better utility, for ease of maintenance and operation, for correction of design deficiencies, for bottleneck removal, for changing product requirements, or for environmental control.

Process unit means the components assembled and connected by pipes or ducts to process raw materials and to produce, as intermediate or final products, one or more of the chemicals listed in §60.489. A process unit can operate independently if supplied with sufficient feed or raw materials and sufficient storage facilities for the product. For the purpose of this subpart, process unit includes any feed, intermediate and final product storage vessels (except as specified in §60.482–1a(g)), product transfer racks, and connected ducts and piping. A process unit includes all equipment as defined in this subpart.

Process unit shutdown means a work practice or operational procedure that stops production from a process unit or part of a process unit during which it is technically feasible to clear process material from a process unit or part of a process unit consistent with safety constraints and during which repairs can be accomplished. The following are not considered process unit shutdowns:

(1) An unscheduled work practice or operational procedure that stops production from a process unit or part of a process unit for less than 24 hours.

(2) An unscheduled work practice or operational procedure that would stop production from a process unit or part of a process unit for a shorter period of time than would be required to clear the process unit or part of the process unit of materials and start up the unit, and would result in greater emissions than delay of repair of leaking components until the next scheduled process unit shutdown.

(3) The use of spare equipment and technically feasible bypassing of equipment without stopping production.

Quarter means a 3-month period; the first quarter concludes on the last day of the last full month during the 180 days following initial startup.

Repaired means that equipment is adjusted, or otherwise altered, in order to eliminate a leak as defined in the applicable sections of this subpart and, except for leaks identified in accordance with §§60.482-2a(b)(2)(ii) and (d)(6)(ii) and (d)(6)(iii), 60.482-3a(f), and 60.482-10a(f)(1)(ii), is re-monitored as specified in §60.485a(b) to verify that emissions from the equipment are below the applicable leak definition.

Replacement cost means the capital needed to purchase all the depreciable components in a facility.

Sampling connection system means an assembly of equipment within a process unit used during periods of representative operation to take samples of the process fluid. Equipment used to take nonroutine grab samples is not considered a sampling connection system.

Sensor means a device that measures a physical quantity or the change in a physical quantity such as temperature, pressure, flow rate, pH, or liquid level.

Storage vessel means a tank or other vessel that is used to store organic liquids that are used in the process as raw material feedstocks, produced as intermediates or final products, or generated as wastes. Storage vessel does not include vessels permanently attached to motor vehicles, such as trucks, railcars, barges or ships.

Synthetic organic chemicals manufacturing industry means the industry that produces, as intermediates or final products, one or more of the chemicals listed in §60.489.

Transfer rack means the collection of loading arms and loading hoses, at a single loading rack, that are used to fill tank trucks and/or railcars with organic liquids.

Volatile organic compounds or VOC means, for the purposes of this subpart, any reactive organic compounds as defined in §60.2 Definitions.

Effective Date Note: At 73 FR 31376, June 2, 2008, in §60.481a, the definitions of “capital expenditure” and “process unit” were stayed until further notice.

§ 60.482-1a Standards: General.

(a) Each owner or operator subject to the provisions of this subpart shall demonstrate compliance with the requirements of §§60.482-1a through 60.482-10a or §60.480a(e) for all equipment within 180 days of initial startup.

(b) Compliance with §§60.482-1a to 60.482-10a will be determined by review of records and reports, review of performance test results, and inspection using the methods and procedures specified in §60.485a.

(c)(1) An owner or operator may request a determination of equivalence of a means of emission limitation to the requirements of §§60.482-2a, 60.482-3a, 60.482-5a, 60.482-6a, 60.482-7a, 60.482-8a, and 60.482-10a as provided in §60.484a.

(2) If the Administrator makes a determination that a means of emission limitation is at least equivalent to the requirements of §§60.482-2a, 60.482-3a, 60.482-5a, 60.482-6a, 60.482-7a, 60.482-8a, or 60.482-10a, an owner or operator shall comply with the requirements of that determination.

(d) Equipment that is in vacuum service is excluded from the requirements of §§60.482-2a through 60.482-10a if it is identified as required in §60.486a(e)(5).

(e) Equipment that an owner or operator designates as being in VOC service less than 300 hr/yr is excluded from the requirements of §§60.482–2a through 60.482–11a if it is identified as required in §60.486a(e)(6) and it meets any of the conditions specified in paragraphs (e)(1) through (3) of this section.

(1) The equipment is in VOC service only during startup and shutdown, excluding startup and shutdown between batches of the same campaign for a batch process.

(2) The equipment is in VOC service only during process malfunctions or other emergencies.

(3) The equipment is backup equipment that is in VOC service only when the primary equipment is out of service.

(f)(1) If a dedicated batch process unit operates less than 365 days during a year, an owner or operator may monitor to detect leaks from pumps, valves, and open-ended valves or lines at the frequency specified in the following table instead of monitoring as specified in §§60.482–2a, 60.482–7a, and 60.483.2a:

Operating time (percent of hours during year)	Equivalent monitoring frequency time in use		
	Monthly	Quarterly	Semiannually
0 to <25	Quarterly	Annually	Annually.
25 to <50	Quarterly	Semiannually	Annually.
50 to <75	Bimonthly	Three quarters	Semiannually.
75 to 100	Monthly	Quarterly	Semiannually.

(2) Pumps and valves that are shared among two or more batch process units that are subject to this subpart may be monitored at the frequencies specified in paragraph (f)(1) of this section, provided the operating time of all such process units is considered.

(3) The monitoring frequencies specified in paragraph (f)(1) of this section are not requirements for monitoring at specific intervals and can be adjusted to accommodate process operations. An owner or operator may monitor at any time during the specified monitoring period (e.g., month, quarter, year), provided the monitoring is conducted at a reasonable interval after completion of the last monitoring campaign. Reasonable intervals are defined in paragraphs (f)(3)(i) through (iv) of this section.

(i) When monitoring is conducted quarterly, monitoring events must be separated by at least 30 calendar days.

(ii) When monitoring is conducted semiannually (*i.e.* , once every 2 quarters), monitoring events must be separated by at least 60 calendar days.

(iii) When monitoring is conducted in 3 quarters per year, monitoring events must be separated by at least 90 calendar days.

(iv) When monitoring is conducted annually, monitoring events must be separated by at least 120 calendar days.

(g) If the storage vessel is shared with multiple process units, the process unit with the greatest annual amount of stored materials (predominant use) is the process unit the storage vessel is assigned to. If the storage vessel is shared equally among process units, and one of the process units has equipment subject to this subpart, the storage vessel is assigned to that process unit. If the storage vessel is shared equally among process units, none of which have equipment subject to this subpart of this part, the storage vessel is assigned to any process unit subject to subpart VV of this part. If the predominant use of the storage vessel varies from year to year, then the owner or operator must estimate the predominant use initially and reassess every 3 years. The owner or

operator must keep records of the information and supporting calculations that show how predominant use is determined. All equipment on the storage vessel must be monitored when in VOC service.

Effective Date Note: At 73 FR 31376, June 2, 2008, in §60.482–1a, paragraph (g) was stayed until further notice.

§ 60.482-2a Standards: Pumps in light liquid service.

(a)(1) Each pump in light liquid service shall be monitored monthly to detect leaks by the methods specified in §60.485a(b), except as provided in §60.482–1a(c) and (f) and paragraphs (d), (e), and (f) of this section. A pump that begins operation in light liquid service after the initial startup date for the process unit must be monitored for the first time within 30 days after the end of its startup period, except for a pump that replaces a leaking pump and except as provided in §60.482–1a(c) and paragraphs (d), (e), and (f) of this section.

(2) Each pump in light liquid service shall be checked by visual inspection each calendar week for indications of liquids dripping from the pump seal, except as provided in §60.482–1a(f).

(b)(1) The instrument reading that defines a leak is specified in paragraphs (b)(1)(i) and (ii) of this section.

(i) 5,000 parts per million (ppm) or greater for pumps handling polymerizing monomers;

(ii) 2,000 ppm or greater for all other pumps.

(2) If there are indications of liquids dripping from the pump seal, the owner or operator shall follow the procedure specified in either paragraph (b)(2)(i) or (ii) of this section. This requirement does not apply to a pump that was monitored after a previous weekly inspection and the instrument reading was less than the concentration specified in paragraph (b)(1)(i) or (ii) of this section, whichever is applicable.

(i) Monitor the pump within 5 days as specified in §60.485a(b). A leak is detected if the instrument reading measured during monitoring indicates a leak as specified in paragraph (b)(1)(i) or (ii) of this section, whichever is applicable. The leak shall be repaired using the procedures in paragraph (c) of this section.

(ii) Designate the visual indications of liquids dripping as a leak, and repair the leak using either the procedures in paragraph (c) of this section or by eliminating the visual indications of liquids dripping.

(c)(1) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in §60.482–9a.

(2) A first attempt at repair shall be made no later than 5 calendar days after each leak is detected. First attempts at repair include, but are not limited to, the practices described in paragraphs (c)(2)(i) and (ii) of this section, where practicable.

(i) Tightening the packing gland nuts;

(ii) Ensuring that the seal flush is operating at design pressure and temperature.

(d) Each pump equipped with a dual mechanical seal system that includes a barrier fluid system is exempt from the requirements of paragraph (a) of this section, provided the requirements specified in paragraphs (d)(1) through (6) of this section are met.

(1) Each dual mechanical seal system is:

(i) Operated with the barrier fluid at a pressure that is at all times greater than the pump stuffing box pressure; or

(ii) Equipped with a barrier fluid degassing reservoir that is routed to a process or fuel gas system or connected by a closed vent system to a control device that complies with the requirements of §60.482-10a; or

(iii) Equipped with a system that purges the barrier fluid into a process stream with zero VOC emissions to the atmosphere.

(2) The barrier fluid system is in heavy liquid service or is not in VOC service.

(3) Each barrier fluid system is equipped with a sensor that will detect failure of the seal system, the barrier fluid system, or both.

(4)(i) Each pump is checked by visual inspection, each calendar week, for indications of liquids dripping from the pump seals.

(ii) If there are indications of liquids dripping from the pump seal at the time of the weekly inspection, the owner or operator shall follow the procedure specified in either paragraph (d)(4)(ii)(A) or (B) of this section prior to the next required inspection.

(A) Monitor the pump within 5 days as specified in §60.485a(b) to determine if there is a leak of VOC in the barrier fluid. If an instrument reading of 2,000 ppm or greater is measured, a leak is detected.

(B) Designate the visual indications of liquids dripping as a leak.

(5)(i) Each sensor as described in paragraph (d)(3) is checked daily or is equipped with an audible alarm.

(ii) The owner or operator determines, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system, or both.

(iii) If the sensor indicates failure of the seal system, the barrier fluid system, or both, based on the criterion established in paragraph (d)(5)(ii) of this section, a leak is detected.

(6)(i) When a leak is detected pursuant to paragraph (d)(4)(ii)(A) of this section, it shall be repaired as specified in paragraph (c) of this section.

(ii) A leak detected pursuant to paragraph (d)(5)(iii) of this section shall be repaired within 15 days of detection by eliminating the conditions that activated the sensor.

(iii) A designated leak pursuant to paragraph (d)(4)(ii)(B) of this section shall be repaired within 15 days of detection by eliminating visual indications of liquids dripping.

(e) Any pump that is designated, as described in §60.486a(e)(1) and (2), for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of paragraphs (a), (c), and (d) of this section if the pump:

(1) Has no externally actuated shaft penetrating the pump housing;

(2) Is demonstrated to be operating with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background as measured by the methods specified in §60.485a(c); and

(3) Is tested for compliance with paragraph (e)(2) of this section initially upon designation, annually, and at other times requested by the Administrator.

(f) If any pump is equipped with a closed vent system capable of capturing and transporting any leakage from the seal or seals to a process or to a fuel gas system or to a control device that complies with the requirements of §60.482-10a, it is exempt from paragraphs (a) through (e) of this section.

(g) Any pump that is designated, as described in §60.486a(f)(1), as an unsafe-to-monitor pump is exempt from the monitoring and inspection requirements of paragraphs (a) and (d)(4) through (6) of this section if:

(1) The owner or operator of the pump demonstrates that the pump is unsafe-to-monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with paragraph (a) of this section; and

(2) The owner or operator of the pump has a written plan that requires monitoring of the pump as frequently as practicable during safe-to-monitor times, but not more frequently than the periodic monitoring schedule otherwise applicable, and repair of the equipment according to the procedures in paragraph (c) of this section if a leak is detected.

(h) Any pump that is located within the boundary of an unmanned plant site is exempt from the weekly visual inspection requirement of paragraphs (a)(2) and (d)(4) of this section, and the daily requirements of paragraph (d)(5) of this section, provided that each pump is visually inspected as often as practicable and at least monthly.

§ 60.482-3a Standards: Compressors.

(a) Each compressor shall be equipped with a seal system that includes a barrier fluid system and that prevents leakage of VOC to the atmosphere, except as provided in §60.482-1a(c) and paragraphs (h), (i), and (j) of this section.

(b) Each compressor seal system as required in paragraph (a) of this section shall be:

(1) Operated with the barrier fluid at a pressure that is greater than the compressor stuffing box pressure; or

(2) Equipped with a barrier fluid system degassing reservoir that is routed to a process or fuel gas system or connected by a closed vent system to a control device that complies with the requirements of §60.482-10a; or

(3) Equipped with a system that purges the barrier fluid into a process stream with zero VOC emissions to the atmosphere.

(c) The barrier fluid system shall be in heavy liquid service or shall not be in VOC service.

(d) Each barrier fluid system as described in paragraph (a) shall be equipped with a sensor that will detect failure of the seal system, barrier fluid system, or both.

(e)(1) Each sensor as required in paragraph (d) of this section shall be checked daily or shall be equipped with an audible alarm.

(2) The owner or operator shall determine, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system, or both.

(f) If the sensor indicates failure of the seal system, the barrier system, or both based on the criterion determined under paragraph (e)(2) of this section, a leak is detected.

(g)(1) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in §60.482-9a.

(2) A first attempt at repair shall be made no later than 5 calendar days after each leak is detected.

(h) A compressor is exempt from the requirements of paragraphs (a) and (b) of this section, if it is equipped with a closed vent system to capture and transport leakage from the compressor drive shaft back to a process or fuel gas system or to a control device that complies with the requirements of §60.482-10a, except as provided in paragraph (i) of this section.

(i) Any compressor that is designated, as described in §60.486a(e)(1) and (2), for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of paragraphs (a) through (h) of this section if the compressor:

(1) Is demonstrated to be operating with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the methods specified in §60.485a(c); and

(2) Is tested for compliance with paragraph (i)(1) of this section initially upon designation, annually, and at other times requested by the Administrator.

(j) Any existing reciprocating compressor in a process unit which becomes an affected facility under provisions of §60.14 or §60.15 is exempt from paragraphs (a) through (e) and (h) of this section, provided the owner or operator demonstrates that recasting the distance piece or replacing the compressor are the only options available to bring the compressor into compliance with the provisions of paragraphs (a) through (e) and (h) of this section.

§ 60.482-4a Standards: Pressure relief devices in gas/vapor service.

(a) Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as determined by the methods specified in §60.485a(c).

(b)(1) After each pressure release, the pressure relief device shall be returned to a condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as soon as practicable, but no later than 5 calendar days after the pressure release, except as provided in §60.482-9a.

(2) No later than 5 calendar days after the pressure release, the pressure relief device shall be monitored to confirm the conditions of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, by the methods specified in §60.485a(c).

(c) Any pressure relief device that is routed to a process or fuel gas system or equipped with a closed vent system capable of capturing and transporting leakage through the pressure relief device to a control device as described in §60.482-10a is exempted from the requirements of paragraphs (a) and (b) of this section.

(d)(1) Any pressure relief device that is equipped with a rupture disk upstream of the pressure relief device is exempt from the requirements of paragraphs (a) and (b) of this section, provided the owner or operator complies with the requirements in paragraph (d)(2) of this section.

(2) After each pressure release, a new rupture disk shall be installed upstream of the pressure relief device as soon as practicable, but no later than 5 calendar days after each pressure release, except as provided in §60.482-9a.

§ 60.482-5a Standards: Sampling connection systems.

(a) Each sampling connection system shall be equipped with a closed-purge, closed-loop, or closed-vent system, except as provided in §60.482-1a(c) and paragraph (c) of this section.

(b) Each closed-purge, closed-loop, or closed-vent system as required in paragraph (a) of this section shall comply with the requirements specified in paragraphs (b)(1) through (4) of this section.

(1) Gases displaced during filling of the sample container are not required to be collected or captured.

(2) Containers that are part of a closed-purge system must be covered or closed when not being filled or emptied.

(3) Gases remaining in the tubing or piping between the closed-purge system valve(s) and sample container valve(s) after the valves are closed and the sample container is disconnected are not required to be collected or captured.

(4) Each closed-purge, closed-loop, or closed-vent system shall be designed and operated to meet requirements in either paragraph (b)(4)(i), (ii), (iii), or (iv) of this section.

(i) Return the purged process fluid directly to the process line.

(ii) Collect and recycle the purged process fluid to a process.

(iii) Capture and transport all the purged process fluid to a control device that complies with the requirements of §60.482–10a.

(iv) Collect, store, and transport the purged process fluid to any of the following systems or facilities:

(A) A waste management unit as defined in 40 CFR 63.111, if the waste management unit is subject to and operated in compliance with the provisions of 40 CFR part 63, subpart G, applicable to Group 1 wastewater streams;

(B) A treatment, storage, or disposal facility subject to regulation under 40 CFR part 262, 264, 265, or 266;

(C) A facility permitted, licensed, or registered by a state to manage municipal or industrial solid waste, if the process fluids are not hazardous waste as defined in 40 CFR part 261;

(D) A waste management unit subject to and operated in compliance with the treatment requirements of 40 CFR 61.348(a), provided all waste management units that collect, store, or transport the purged process fluid to the treatment unit are subject to and operated in compliance with the management requirements of 40 CFR 61.343 through 40 CFR 61.347; or

(E) A device used to burn off-specification used oil for energy recovery in accordance with 40 CFR part 279, subpart G, provided the purged process fluid is not hazardous waste as defined in 40 CFR part 261.

(c) In-situ sampling systems and sampling systems without purges are exempt from the requirements of paragraphs (a) and (b) of this section.

§ 60.482-6a Standards: Open-ended valves or lines.

(a)(1) Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve, except as provided in §60.482–1a(c) and paragraphs (d) and (e) of this section.

(2) The cap, blind flange, plug, or second valve shall seal the open end at all times except during operations requiring process fluid flow through the open-ended valve or line.

(b) Each open-ended valve or line equipped with a second valve shall be operated in a manner such that the valve on the process fluid end is closed before the second valve is closed.

(c) When a double block-and-bleed system is being used, the bleed valve or line may remain open during operations that require venting the line between the block valves but shall comply with paragraph (a) of this section at all other times.

(d) Open-ended valves or lines in an emergency shutdown system which are designed to open automatically in the event of a process upset are exempt from the requirements of paragraphs (a), (b), and (c) of this section.

(e) Open-ended valves or lines containing materials which would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system as specified in paragraphs (a) through (c) of this section are exempt from the requirements of paragraphs (a) through (c) of this section.

§ 60.482-7a Standards: Valves in gas/vapor service and in light liquid service.

(a)(1) Each valve shall be monitored monthly to detect leaks by the methods specified in §60.485a(b) and shall comply with paragraphs (b) through (e) of this section, except as provided in paragraphs (f), (g), and (h) of this section, §60.482-1a(c) and (f), and §§60.483-1a and 60.483-2a.

(2) A valve that begins operation in gas/vapor service or light liquid service after the initial startup date for the process unit must be monitored according to paragraphs (a)(2)(i) or (ii), except for a valve that replaces a leaking valve and except as provided in paragraphs (f), (g), and (h) of this section, §60.482-1a(c), and §§60.483-1a and 60.483-2a.

(i) Monitor the valve as in paragraph (a)(1) of this section. The valve must be monitored for the first time within 30 days after the end of its startup period to ensure proper installation.

(ii) If the existing valves in the process unit are monitored in accordance with §60.483-1a or §60.483-2a, count the new valve as leaking when calculating the percentage of valves leaking as described in §60.483-2a(b)(5). If less than 2.0 percent of the valves are leaking for that process unit, the valve must be monitored for the first time during the next scheduled monitoring event for existing valves in the process unit or within 90 days, whichever comes first.

(b) If an instrument reading of 500 ppm or greater is measured, a leak is detected.

(c)(1)(i) Any valve for which a leak is not detected for 2 successive months may be monitored the first month of every quarter, beginning with the next quarter, until a leak is detected.

(ii) As an alternative to monitoring all of the valves in the first month of a quarter, an owner or operator may elect to subdivide the process unit into two or three subgroups of valves and monitor each subgroup in a different month during the quarter, provided each subgroup is monitored every 3 months. The owner or operator must keep records of the valves assigned to each subgroup.

(2) If a leak is detected, the valve shall be monitored monthly until a leak is not detected for 2 successive months.

(d)(1) When a leak is detected, it shall be repaired as soon as practicable, but no later than 15 calendar days after the leak is detected, except as provided in §60.482-9a.

(2) A first attempt at repair shall be made no later than 5 calendar days after each leak is detected.

(e) First attempts at repair include, but are not limited to, the following best practices where practicable:

(1) Tightening of bonnet bolts;

(2) Replacement of bonnet bolts;

(3) Tightening of packing gland nuts;

(4) Injection of lubricant into lubricated packing.

(f) Any valve that is designated, as described in §60.486a(e)(2), for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of paragraph (a) of this section if the valve:

- (1) Has no external actuating mechanism in contact with the process fluid,
- (2) Is operated with emissions less than 500 ppm above background as determined by the method specified in §60.485a(c), and
- (3) Is tested for compliance with paragraph (f)(2) of this section initially upon designation, annually, and at other times requested by the Administrator.

(g) Any valve that is designated, as described in §60.486a(f)(1), as an unsafe-to-monitor valve is exempt from the requirements of paragraph (a) of this section if:

- (1) The owner or operator of the valve demonstrates that the valve is unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with paragraph (a) of this section, and
- (2) The owner or operator of the valve adheres to a written plan that requires monitoring of the valve as frequently as practicable during safe-to-monitor times.

(h) Any valve that is designated, as described in §60.486a(f)(2), as a difficult-to-monitor valve is exempt from the requirements of paragraph (a) of this section if:

- (1) The owner or operator of the valve demonstrates that the valve cannot be monitored without elevating the monitoring personnel more than 2 meters above a support surface.
- (2) The process unit within which the valve is located either:
 - (i) Becomes an affected facility through §60.14 or §60.15 and was constructed on or before January 5, 1981; or
 - (ii) Has less than 3.0 percent of its total number of valves designated as difficult-to-monitor by the owner or operator.
- (3) The owner or operator of the valve follows a written plan that requires monitoring of the valve at least once per calendar year.

§ 60.482-8a Standards: Pumps, valves, and connectors in heavy liquid service and pressure relief devices in light liquid or heavy liquid service.

(a) If evidence of a potential leak is found by visual, audible, olfactory, or any other detection method at pumps, valves, and connectors in heavy liquid service and pressure relief devices in light liquid or heavy liquid service, the owner or operator shall follow either one of the following procedures:

- (1) The owner or operator shall monitor the equipment within 5 days by the method specified in §60.485a(b) and shall comply with the requirements of paragraphs (b) through (d) of this section.
- (2) The owner or operator shall eliminate the visual, audible, olfactory, or other indication of a potential leak within 5 calendar days of detection.

(b) If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.

(c)(1) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in §60.482-9a.

(2) The first attempt at repair shall be made no later than 5 calendar days after each leak is detected.

(d) First attempts at repair include, but are not limited to, the best practices described under §§60.482–2a(c)(2) and 60.482–7a(e).

§ 60.482-9a Standards: Delay of repair.

(a) Delay of repair of equipment for which leaks have been detected will be allowed if repair within 15 days is technically infeasible without a process unit shutdown. Repair of this equipment shall occur before the end of the next process unit shutdown. Monitoring to verify repair must occur within 15 days after startup of the process unit.

(b) Delay of repair of equipment will be allowed for equipment which is isolated from the process and which does not remain in VOC service.

(c) Delay of repair for valves and connectors will be allowed if:

(1) The owner or operator demonstrates that emissions of purged material resulting from immediate repair are greater than the fugitive emissions likely to result from delay of repair, and

(2) When repair procedures are effected, the purged material is collected and destroyed or recovered in a control device complying with §60.482–10a.

(d) Delay of repair for pumps will be allowed if:

(1) Repair requires the use of a dual mechanical seal system that includes a barrier fluid system, and

(2) Repair is completed as soon as practicable, but not later than 6 months after the leak was detected.

(e) Delay of repair beyond a process unit shutdown will be allowed for a valve, if valve assembly replacement is necessary during the process unit shutdown, valve assembly supplies have been depleted, and valve assembly supplies had been sufficiently stocked before the supplies were depleted. Delay of repair beyond the next process unit shutdown will not be allowed unless the next process unit shutdown occurs sooner than 6 months after the first process unit shutdown.

(f) When delay of repair is allowed for a leaking pump, valve, or connector that remains in service, the pump, valve, or connector may be considered to be repaired and no longer subject to delay of repair requirements if two consecutive monthly monitoring instrument readings are below the leak definition.

§ 60.482-10a Standards: Closed vent systems and control devices.

(a) Owners or operators of closed vent systems and control devices used to comply with provisions of this subpart shall comply with the provisions of this section.

(b) Vapor recovery systems (for example, condensers and absorbers) shall be designed and operated to recover the VOC emissions vented to them with an efficiency of 95 percent or greater, or to an exit concentration of 20 parts per million by volume (ppmv), whichever is less stringent.

(c) Enclosed combustion devices shall be designed and operated to reduce the VOC emissions vented to them with an efficiency of 95 percent or greater, or to an exit concentration of 20 ppmv, on a dry basis, corrected to 3 percent oxygen, whichever is less stringent or to provide a minimum residence time of 0.75 seconds at a minimum temperature of 816 °C.

(d) Flares used to comply with this subpart shall comply with the requirements of §60.18.

(e) Owners or operators of control devices used to comply with the provisions of this subpart shall monitor these control devices to ensure that they are operated and maintained in conformance with their designs.

(f) Except as provided in paragraphs (i) through (k) of this section, each closed vent system shall be inspected according to the procedures and schedule specified in paragraphs (f)(1) and (2) of this section.

(1) If the vapor collection system or closed vent system is constructed of hard-piping, the owner or operator shall comply with the requirements specified in paragraphs (f)(1)(i) and (ii) of this section:

(i) Conduct an initial inspection according to the procedures in §60.485a(b); and

(ii) Conduct annual visual inspections for visible, audible, or olfactory indications of leaks.

(2) If the vapor collection system or closed vent system is constructed of ductwork, the owner or operator shall:

(i) Conduct an initial inspection according to the procedures in §60.485a(b); and

(ii) Conduct annual inspections according to the procedures in §60.485a(b).

(g) Leaks, as indicated by an instrument reading greater than 500 ppmv above background or by visual inspections, shall be repaired as soon as practicable except as provided in paragraph (h) of this section.

(1) A first attempt at repair shall be made no later than 5 calendar days after the leak is detected.

(2) Repair shall be completed no later than 15 calendar days after the leak is detected.

(h) Delay of repair of a closed vent system for which leaks have been detected is allowed if the repair is technically infeasible without a process unit shutdown or if the owner or operator determines that emissions resulting from immediate repair would be greater than the fugitive emissions likely to result from delay of repair. Repair of such equipment shall be complete by the end of the next process unit shutdown.

(i) If a vapor collection system or closed vent system is operated under a vacuum, it is exempt from the inspection requirements of paragraphs (f)(1)(i) and (f)(2) of this section.

(j) Any parts of the closed vent system that are designated, as described in paragraph (l)(1) of this section, as unsafe to inspect are exempt from the inspection requirements of paragraphs (f)(1)(i) and (f)(2) of this section if they comply with the requirements specified in paragraphs (j)(1) and (2) of this section:

(1) The owner or operator determines that the equipment is unsafe to inspect because inspecting personnel would be exposed to an imminent or potential danger as a consequence of complying with paragraphs (f)(1)(i) or (f)(2) of this section; and

(2) The owner or operator has a written plan that requires inspection of the equipment as frequently as practicable during safe-to-inspect times.

(k) Any parts of the closed vent system that are designated, as described in paragraph (l)(2) of this section, as difficult to inspect are exempt from the inspection requirements of paragraphs (f)(1)(i) and (f)(2) of this section if they comply with the requirements specified in paragraphs (k)(1) through (3) of this section:

(1) The owner or operator determines that the equipment cannot be inspected without elevating the inspecting personnel more than 2 meters above a support surface; and

(2) The process unit within which the closed vent system is located becomes an affected facility through §§60.14 or 60.15, or the owner or operator designates less than 3.0 percent of the total number of closed vent system equipment as difficult to inspect; and

(3) The owner or operator has a written plan that requires inspection of the equipment at least once every 5 years. A closed vent system is exempt from inspection if it is operated under a vacuum.

(l) The owner or operator shall record the information specified in paragraphs (l)(1) through (5) of this section.

(1) Identification of all parts of the closed vent system that are designated as unsafe to inspect, an explanation of why the equipment is unsafe to inspect, and the plan for inspecting the equipment.

(2) Identification of all parts of the closed vent system that are designated as difficult to inspect, an explanation of why the equipment is difficult to inspect, and the plan for inspecting the equipment.

(3) For each inspection during which a leak is detected, a record of the information specified in §60.486a(c).

(4) For each inspection conducted in accordance with §60.485a(b) during which no leaks are detected, a record that the inspection was performed, the date of the inspection, and a statement that no leaks were detected.

(5) For each visual inspection conducted in accordance with paragraph (f)(1)(ii) of this section during which no leaks are detected, a record that the inspection was performed, the date of the inspection, and a statement that no leaks were detected.

(m) Closed vent systems and control devices used to comply with provisions of this subpart shall be operated at all times when emissions may be vented to them.

§ 60.482-11a Standards: Connectors in gas/vapor service and in light liquid service.

(a) The owner or operator shall initially monitor all connectors in the process unit for leaks by the later of either 12 months after the compliance date or 12 months after initial startup. If all connectors in the process unit have been monitored for leaks prior to the compliance date, no initial monitoring is required provided either no process changes have been made since the monitoring or the owner or operator can determine that the results of the monitoring, with or without adjustments, reliably demonstrate compliance despite process changes. If required to monitor because of a process change, the owner or operator is required to monitor only those connectors involved in the process change.

(b) Except as allowed in §60.482-1a(c), §60.482-10a, or as specified in paragraph (e) of this section, the owner or operator shall monitor all connectors in gas and vapor and light liquid service as specified in paragraphs (a) and (b)(3) of this section.

(1) The connectors shall be monitored to detect leaks by the method specified in §60.485a(b) and, as applicable, §60.485a(c).

(2) If an instrument reading greater than or equal to 500 ppm is measured, a leak is detected.

(3) The owner or operator shall perform monitoring, subsequent to the initial monitoring required in paragraph (a) of this section, as specified in paragraphs (b)(3)(i) through (iii) of this section, and shall comply with the requirements of paragraphs (b)(3)(iv) and (v) of this section. The required period in which monitoring must be conducted shall be determined from paragraphs (b)(3)(i) through (iii) of this section using the monitoring results from the preceding monitoring period. The percent leaking connectors shall be calculated as specified in paragraph (c) of this section.

(i) If the percent leaking connectors in the process unit was greater than or equal to 0.5 percent, then monitor within 12 months (1 year).

(ii) If the percent leaking connectors in the process unit was greater than or equal to 0.25 percent but less than 0.5 percent, then monitor within 4 years. An owner or operator may comply with the requirements of this paragraph by monitoring at least 40 percent of the connectors within 2 years of the start of the monitoring period, provided all connectors have been monitored by the end of the 4-year monitoring period.

(iii) If the percent leaking connectors in the process unit was less than 0.25 percent, then monitor as provided in paragraph (b)(3)(iii)(A) of this section and either paragraph (b)(3)(iii)(B) or (b)(3)(iii)(C) of this section, as appropriate.

(A) An owner or operator shall monitor at least 50 percent of the connectors within 4 years of the start of the monitoring period.

(B) If the percent of leaking connectors calculated from the monitoring results in paragraph (b)(3)(iii)(A) of this section is greater than or equal to 0.35 percent of the monitored connectors, the owner or operator shall monitor as soon as practical, but within the next 6 months, all connectors that have not yet been monitored during the monitoring period. At the conclusion of monitoring, a new monitoring period shall be started pursuant to paragraph (b)(3) of this section, based on the percent of leaking connectors within the total monitored connectors.

(C) If the percent of leaking connectors calculated from the monitoring results in paragraph (b)(3)(iii)(A) of this section is less than 0.35 percent of the monitored connectors, the owner or operator shall monitor all connectors that have not yet been monitored within 8 years of the start of the monitoring period.

(iv) If, during the monitoring conducted pursuant to paragraphs (b)(3)(i) through (iii) of this section, a connector is found to be leaking, it shall be re-monitored once within 90 days after repair to confirm that it is not leaking.

(v) The owner or operator shall keep a record of the start date and end date of each monitoring period under this section for each process unit.

(c) For use in determining the monitoring frequency, as specified in paragraphs (a) and (b)(3) of this section, the percent leaking connectors as used in paragraphs (a) and (b)(3) of this section shall be calculated by using the following equation:

$$\%C_L = C_L / C_T * 100$$

Where:

$\%C_L$ = Percent of leaking connectors as determined through periodic monitoring required in paragraphs (a) and (b)(3)(i) through (iii) of this section.

C_L = Number of connectors measured at 500 ppm or greater, by the method specified in §60.485a(b).

C_T = Total number of monitored connectors in the process unit or affected facility.

(d) When a leak is detected pursuant to paragraphs (a) and (b) of this section, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in §60.482-9a. A first attempt at repair as defined in this subpart shall be made no later than 5 calendar days after the leak is detected.

(e) Any connector that is designated, as described in §60.486a(f)(1), as an unsafe-to-monitor connector is exempt from the requirements of paragraphs (a) and (b) of this section if:

(1) The owner or operator of the connector demonstrates that the connector is unsafe-to-monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with paragraphs (a) and (b) of this section; and

(2) The owner or operator of the connector has a written plan that requires monitoring of the connector as frequently as practicable during safe-to-monitor times but not more frequently than the periodic monitoring schedule otherwise applicable, and repair of the equipment according to the procedures in paragraph (d) of this section if a leak is detected.

(f) *Inaccessible, ceramic, or ceramic-lined connectors* . (1) Any connector that is inaccessible or that is ceramic or ceramic-lined (e.g., porcelain, glass, or glass-lined), is exempt from the monitoring requirements of paragraphs (a) and (b) of this section, from the leak repair requirements of paragraph (d) of this section, and from the recordkeeping and reporting requirements of §§63.1038 and 63.1039. An inaccessible connector is one that meets any of the provisions specified in paragraphs (f)(1)(i) through (vi) of this section, as applicable:

(i) Buried;

(ii) Insulated in a manner that prevents access to the connector by a monitor probe;

(iii) Obstructed by equipment or piping that prevents access to the connector by a monitor probe;

(iv) Unable to be reached from a wheeled scissor-lift or hydraulic-type scaffold that would allow access to connectors up to 7.6 meters (25 feet) above the ground;

(v) Inaccessible because it would require elevating the monitoring personnel more than 2 meters (7 feet) above a permanent support surface or would require the erection of scaffold; or

(vi) Not able to be accessed at any time in a safe manner to perform monitoring. Unsafe access includes, but is not limited to, the use of a wheeled scissor-lift on unstable or uneven terrain, the use of a motorized man-lift basket in areas where an ignition potential exists, or access would require near proximity to hazards such as electrical lines, or would risk damage to equipment.

(2) If any inaccessible, ceramic, or ceramic-lined connector is observed by visual, audible, olfactory, or other means to be leaking, the visual, audible, olfactory, or other indications of a leak to the atmosphere shall be eliminated as soon as practical.

(g) Except for instrumentation systems and inaccessible, ceramic, or ceramic-lined connectors meeting the provisions of paragraph (f) of this section, identify the connectors subject to the requirements of this subpart. Connectors need not be individually identified if all connectors in a designated area or length of pipe subject to the provisions of this subpart are identified as a group, and the number of connectors subject is indicated.

Effective Date Note: At 73 FR 31376, June 2, 2008, §60.482–1 1a was stayed until further notice.

§ 60.483-1a Alternative standards for valves—allowable percentage of valves leaking.

(a) An owner or operator may elect to comply with an allowable percentage of valves leaking of equal to or less than 2.0 percent.

(b) The following requirements shall be met if an owner or operator wishes to comply with an allowable percentage of valves leaking:

(1) An owner or operator must notify the Administrator that the owner or operator has elected to comply with the allowable percentage of valves leaking before implementing this alternative standard, as specified in §60.487a(d).

(2) A performance test as specified in paragraph (c) of this section shall be conducted initially upon designation, annually, and at other times requested by the Administrator.

(3) If a valve leak is detected, it shall be repaired in accordance with §60.482–7a(d) and (e).

(c) Performance tests shall be conducted in the following manner:

(1) All valves in gas/vapor and light liquid service within the affected facility shall be monitored within 1 week by the methods specified in §60.485a(b).

- (2) If an instrument reading of 500 ppm or greater is measured, a leak is detected.
- (3) The leak percentage shall be determined by dividing the number of valves for which leaks are detected by the number of valves in gas/vapor and light liquid service within the affected facility.
- (d) Owners and operators who elect to comply with this alternative standard shall not have an affected facility with a leak percentage greater than 2.0 percent, determined as described in §60.485a(h).

§ 60.483-2a Alternative standards for valves—skip period leak detection and repair.

- (a)(1) An owner or operator may elect to comply with one of the alternative work practices specified in paragraphs (b)(2) and (3) of this section.
- (2) An owner or operator must notify the Administrator before implementing one of the alternative work practices, as specified in §60.487(d)a.
- (b)(1) An owner or operator shall comply initially with the requirements for valves in gas/vapor service and valves in light liquid service, as described in §60.482–7a.
- (2) After 2 consecutive quarterly leak detection periods with the percent of valves leaking equal to or less than 2.0, an owner or operator may begin to skip 1 of the quarterly leak detection periods for the valves in gas/vapor and light liquid service.
- (3) After 5 consecutive quarterly leak detection periods with the percent of valves leaking equal to or less than 2.0, an owner or operator may begin to skip 3 of the quarterly leak detection periods for the valves in gas/vapor and light liquid service.
- (4) If the percent of valves leaking is greater than 2.0, the owner or operator shall comply with the requirements as described in §60.482–7a but can again elect to use this section.
- (5) The percent of valves leaking shall be determined as described in §60.485a(h).
- (6) An owner or operator must keep a record of the percent of valves found leaking during each leak detection period.
- (7) A valve that begins operation in gas/vapor service or light liquid service after the initial startup date for a process unit following one of the alternative standards in this section must be monitored in accordance with §60.482–7a(a)(2)(i) or (ii) before the provisions of this section can be applied to that valve.

§ 60.484a Equivalence of means of emission limitation.

- (a) Each owner or operator subject to the provisions of this subpart may apply to the Administrator for determination of equivalence for any means of emission limitation that achieves a reduction in emissions of VOC at least equivalent to the reduction in emissions of VOC achieved by the controls required in this subpart.
- (b) Determination of equivalence to the equipment, design, and operational requirements of this subpart will be evaluated by the following guidelines:
- (1) Each owner or operator applying for an equivalence determination shall be responsible for collecting and verifying test data to demonstrate equivalence of means of emission limitation.
- (2) The Administrator will compare test data for demonstrating equivalence of the means of emission limitation to test data for the equipment, design, and operational requirements.

(3) The Administrator may condition the approval of equivalence on requirements that may be necessary to assure operation and maintenance to achieve the same emission reduction as the equipment, design, and operational requirements.

(c) Determination of equivalence to the required work practices in this subpart will be evaluated by the following guidelines:

(1) Each owner or operator applying for a determination of equivalence shall be responsible for collecting and verifying test data to demonstrate equivalence of an equivalent means of emission limitation.

(2) For each affected facility for which a determination of equivalence is requested, the emission reduction achieved by the required work practice shall be demonstrated.

(3) For each affected facility, for which a determination of equivalence is requested, the emission reduction achieved by the equivalent means of emission limitation shall be demonstrated.

(4) Each owner or operator applying for a determination of equivalence shall commit in writing to work practice(s) that provide for emission reductions equal to or greater than the emission reductions achieved by the required work practice.

(5) The Administrator will compare the demonstrated emission reduction for the equivalent means of emission limitation to the demonstrated emission reduction for the required work practices and will consider the commitment in paragraph (c)(4) of this section.

(6) The Administrator may condition the approval of equivalence on requirements that may be necessary to assure operation and maintenance to achieve the same emission reduction as the required work practice.

(d) An owner or operator may offer a unique approach to demonstrate the equivalence of any equivalent means of emission limitation.

(e)(1) After a request for determination of equivalence is received, the Administrator will publish a notice in the Federal Register and provide the opportunity for public hearing if the Administrator judges that the request may be approved.

(2) After notice and opportunity for public hearing, the Administrator will determine the equivalence of a means of emission limitation and will publish the determination in the Federal Register.

(3) Any equivalent means of emission limitations approved under this section shall constitute a required work practice, equipment, design, or operational standard within the meaning of section 111(h)(1) of the CAA.

(f)(1) Manufacturers of equipment used to control equipment leaks of VOC may apply to the Administrator for determination of equivalence for any equivalent means of emission limitation that achieves a reduction in emissions of VOC achieved by the equipment, design, and operational requirements of this subpart.

(2) The Administrator will make an equivalence determination according to the provisions of paragraphs (b), (c), (d), and (e) of this section.

§ 60.485a Test methods and procedures.

(a) In conducting the performance tests required in §60.8, the owner or operator shall use as reference methods and procedures the test methods in appendix A of this part or other methods and procedures as specified in this section, except as provided in §60.8(b).

(b) The owner or operator shall determine compliance with the standards in §§60.482–1a through 60.482–11a, 60.483a, and 60.484a as follows:

(1) Method 21 shall be used to determine the presence of leaking sources. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 of appendix A-7 of this part. The following calibration gases shall be used:

(i) Zero air (less than 10 ppm of hydrocarbon in air); and

(ii) A mixture of methane or n-hexane and air at a concentration no more than 2,000 ppm greater than the leak definition concentration of the equipment monitored. If the monitoring instrument's design allows for multiple calibration scales, then the lower scale shall be calibrated with a calibration gas that is no higher than 2,000 ppm above the concentration specified as a leak, and the highest scale shall be calibrated with a calibration gas that is approximately equal to 10,000 ppm. If only one scale on an instrument will be used during monitoring, the owner or operator need not calibrate the scales that will not be used during that day's monitoring.

(2) A calibration drift assessment shall be performed, at a minimum, at the end of each monitoring day. Check the instrument using the same calibration gas(es) that were used to calibrate the instrument before use. Follow the procedures specified in Method 21 of appendix A-7 of this part, Section 10.1, except do not adjust the meter readout to correspond to the calibration gas value. Record the instrument reading for each scale used as specified in §60.486a(e)(7). Calculate the average algebraic difference between the three meter readings and the most recent calibration value. Divide this algebraic difference by the initial calibration value and multiply by 100 to express the calibration drift as a percentage. If any calibration drift assessment shows a negative drift of more than 10 percent from the initial calibration value, then all equipment monitored since the last calibration with instrument readings below the appropriate leak definition and above the leak definition multiplied by (100 minus the percent of negative drift/divided by 100) must be re-monitored. If any calibration drift assessment shows a positive drift of more than 10 percent from the initial calibration value, then, at the owner/operator's discretion, all equipment since the last calibration with instrument readings above the appropriate leak definition and below the leak definition multiplied by (100 plus the percent of positive drift/divided by 100) may be re-monitored.

(c) The owner or operator shall determine compliance with the no-detectable-emission standards in §§60.482-2a(e), 60.482-3a(i), 60.482-4a, 60.482-7a(f), and 60.482-10a(e) as follows:

(1) The requirements of paragraph (b) shall apply.

(2) Method 21 of appendix A-7 of this part shall be used to determine the background level. All potential leak interfaces shall be traversed as close to the interface as possible. The arithmetic difference between the maximum concentration indicated by the instrument and the background level is compared with 500 ppm for determining compliance.

(d) The owner or operator shall test each piece of equipment unless he demonstrates that a process unit is not in VOC service, i.e., that the VOC content would never be reasonably expected to exceed 10 percent by weight. For purposes of this demonstration, the following methods and procedures shall be used:

(1) Procedures that conform to the general methods in ASTM E260-73, 91, or 96, E168-67, 77, or 92, E169-63, 77, or 93 (incorporated by reference—see §60.17) shall be used to determine the percent VOC content in the process fluid that is contained in or contacts a piece of equipment.

(2) Organic compounds that are considered by the Administrator to have negligible photochemical reactivity may be excluded from the total quantity of organic compounds in determining the VOC content of the process fluid.

(3) Engineering judgment may be used to estimate the VOC content, if a piece of equipment had not been shown previously to be in service. If the Administrator disagrees with the judgment, paragraphs (d)(1) and (2) of this section shall be used to resolve the disagreement.

(e) The owner or operator shall demonstrate that a piece of equipment is in light liquid service by showing that all the following conditions apply:

(1) The vapor pressure of one or more of the organic components is greater than 0.3 kPa at 20 °C (1.2 in. H₂O at 68 °F). Standard reference texts or ASTM D2879–83, 96, or 97 (incorporated by reference—see §60.17) shall be used to determine the vapor pressures.

(2) The total concentration of the pure organic components having a vapor pressure greater than 0.3 kPa at 20 °C (1.2 in. H₂O at 68 °F) is equal to or greater than 20 percent by weight.

(3) The fluid is a liquid at operating conditions.

(f) Samples used in conjunction with paragraphs (d), (e), and (g) of this section shall be representative of the process fluid that is contained in or contacts the equipment or the gas being combusted in the flare.

(g) The owner or operator shall determine compliance with the standards of flares as follows:

(1) Method 22 of appendix A–7 of this part shall be used to determine visible emissions.

(2) A thermocouple or any other equivalent device shall be used to monitor the presence of a pilot flame in the flare.

(3) The maximum permitted velocity for air assisted flares shall be computed using the following equation:

$$V_{\max} = K_1 + K_2 H_T$$

Where:

V_{\max} = Maximum permitted velocity, m/sec (ft/sec).

H_T = Net heating value of the gas being combusted, MJ/scm (Btu/scf).

K_1 = 8.706 m/sec (metric units) = 28.56 ft/sec (English units).

K_2 = 0.7084 m⁴/(MJ-sec) (metric units) = 0.087 ft⁴/(Btu-sec) (English units).

(4) The net heating value (HT) of the gas being combusted in a flare shall be computed using the following equation:

$$H_T = K \sum_{i=1}^n C_i H_i$$

Where:

K = Conversion constant, 1.740×10^{-7} (g-mole)(MJ)/(ppm-scm-kcal) (metric units) = 4.674×10^{-6} [(g-mole)(Btu)/(ppm-scf-kcal)] (English units).

C_i = Concentration of sample component “i,” ppm

H_i = net heat of combustion of sample component “i” at 25 °C and 760 mm Hg (77 °F and 14.7 psi), kcal/g-mole.

(5) Method 18 of appendix A–6 of this part or ASTM D6420–99 (2004) (where the target compound(s) are those listed in Section 1.1 of ASTM D6420–99, and the target concentration is between 150 parts per billion by volume and 100 ppmv) and ASTM D2504–67, 77, or 88 (Reapproved 1993) (incorporated by reference-see §60.17) shall be used to determine the concentration of sample component “i.”

(6) ASTM D2382–76 or 88 or D4809–95 (incorporated by reference-see §60.17) shall be used to determine the net heat of combustion of component “i” if published values are not available or cannot be calculated.

(7) Method 2, 2A, 2C, or 2D of appendix A–7 of this part, as appropriate, shall be used to determine the actual exit velocity of a flare. If needed, the unobstructed (free) cross-sectional area of the flare tip shall be used.

(h) The owner or operator shall determine compliance with §60.483–1a or §60.483–2a as follows:

(1) The percent of valves leaking shall be determined using the following equation:

$$\%V_L = (V_L / V_T) * 100$$

Where:

$\%V_L$ = Percent leaking valves.

V_L = Number of valves found leaking.

V_T = The sum of the total number of valves monitored.

(2) The total number of valves monitored shall include difficult-to-monitor and unsafe-to-monitor valves only during the monitoring period in which those valves are monitored.

(3) The number of valves leaking shall include valves for which repair has been delayed.

(4) Any new valve that is not monitored within 30 days of being placed in service shall be included in the number of valves leaking and the total number of valves monitored for the monitoring period in which the valve is placed in service.

(5) If the process unit has been subdivided in accordance with §60.482–7a(c)(1)(ii), the sum of valves found leaking during a monitoring period includes all subgroups.

(6) The total number of valves monitored does not include a valve monitored to verify repair.

§ 60.486a Recordkeeping requirements.

(a)(1) Each owner or operator subject to the provisions of this subpart shall comply with the recordkeeping requirements of this section.

(2) An owner or operator of more than one affected facility subject to the provisions of this subpart may comply with the recordkeeping requirements for these facilities in one recordkeeping system if the system identifies each record by each facility.

(3) The owner or operator shall record the information specified in paragraphs (a)(3)(i) through (v) of this section for each monitoring event required by §§60.482–2a, 60.482–3a, 60.482–7a, 60.482–8a, 60.482–11a, and 60.483–2a.

(i) Monitoring instrument identification.

(ii) Operator identification.

(iii) Equipment identification.

(iv) Date of monitoring.

(v) Instrument reading.

(b) When each leak is detected as specified in §§60.482–2a, 60.482–3a, 60.482–7a, 60.482–8a, 60.482–11a, and 60.483–2a, the following requirements apply:

(1) A weatherproof and readily visible identification, marked with the equipment identification number, shall be attached to the leaking equipment.

(2) The identification on a valve may be removed after it has been monitored for 2 successive months as specified in §60.482–7a(c) and no leak has been detected during those 2 months.

(3) The identification on a connector may be removed after it has been monitored as specified in §60.482–11a(b)(3)(iv) and no leak has been detected during that monitoring.

(4) The identification on equipment, except on a valve or connector, may be removed after it has been repaired.

(c) When each leak is detected as specified in §§60.482–2a, 60.482–3a, 60.482–7a, 60.482–8a, 60.482–11a, and 60.483–2a, the following information shall be recorded in a log and shall be kept for 2 years in a readily accessible location:

(1) The instrument and operator identification numbers and the equipment identification number, except when indications of liquids dripping from a pump are designated as a leak.

(2) The date the leak was detected and the dates of each attempt to repair the leak.

(3) Repair methods applied in each attempt to repair the leak.

(4) Maximum instrument reading measured by Method 21 of appendix A–7 of this part at the time the leak is successfully repaired or determined to be nonrepairable, except when a pump is repaired by eliminating indications of liquids dripping.

(5) “Repair delayed” and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.

(6) The signature of the owner or operator (or designate) whose decision it was that repair could not be effected without a process shutdown.

(7) The expected date of successful repair of the leak if a leak is not repaired within 15 days.

(8) Dates of process unit shutdowns that occur while the equipment is unrepaired.

(9) The date of successful repair of the leak.

(d) The following information pertaining to the design requirements for closed vent systems and control devices described in §60.482–10a shall be recorded and kept in a readily accessible location:

(1) Detailed schematics, design specifications, and piping and instrumentation diagrams.

(2) The dates and descriptions of any changes in the design specifications.

(3) A description of the parameter or parameters monitored, as required in §60.482–10a(e), to ensure that control devices are operated and maintained in conformance with their design and an explanation of why that parameter (or parameters) was selected for the monitoring.

(4) Periods when the closed vent systems and control devices required in §§60.482-2a, 60.482-3a, 60.482-4a, and 60.482-5a are not operated as designed, including periods when a flare pilot light does not have a flame.

(5) Dates of startups and shutdowns of the closed vent systems and control devices required in §§60.482-2a, 60.482-3a, 60.482-4a, and 60.482-5a.

(e) The following information pertaining to all equipment subject to the requirements in §§60.482-1a to 60.482-11a shall be recorded in a log that is kept in a readily accessible location:

(1) A list of identification numbers for equipment subject to the requirements of this subpart.

(2)(i) A list of identification numbers for equipment that are designated for no detectable emissions under the provisions of §§60.482-2a(e), 60.482-3a(i), and 60.482-7a(f).

(ii) The designation of equipment as subject to the requirements of §60.482-2a(e), §60.482-3a(i), or §60.482-7a(f) shall be signed by the owner or operator. Alternatively, the owner or operator may establish a mechanism with their permitting authority that satisfies this requirement.

(3) A list of equipment identification numbers for pressure relief devices required to comply with §60.482-4a.

(4)(i) The dates of each compliance test as required in §§60.482-2a(e), 60.482-3a(i), 60.482-4a, and 60.482-7a(f).

(ii) The background level measured during each compliance test.

(iii) The maximum instrument reading measured at the equipment during each compliance test.

(5) A list of identification numbers for equipment in vacuum service.

(6) A list of identification numbers for equipment that the owner or operator designates as operating in VOC service less than 300 hr/yr in accordance with §60.482-1a(e), a description of the conditions under which the equipment is in VOC service, and rationale supporting the designation that it is in VOC service less than 300 hr/yr.

(7) The date and results of the weekly visual inspection for indications of liquids dripping from pumps in light liquid service.

(8) Records of the information specified in paragraphs (e)(8)(i) through (vi) of this section for monitoring instrument calibrations conducted according to sections 8.1.2 and 10 of Method 21 of appendix A-7 of this part and §60.485a(b).

(i) Date of calibration and initials of operator performing the calibration.

(ii) Calibration gas cylinder identification, certification date, and certified concentration.

(iii) Instrument scale(s) used.

(iv) A description of any corrective action taken if the meter readout could not be adjusted to correspond to the calibration gas value in accordance with section 10.1 of Method 21 of appendix A-7 of this part.

(v) Results of each calibration drift assessment required by §60.485a(b)(2) (i.e., instrument reading for calibration at end of monitoring day and the calculated percent difference from the initial calibration value).

(vi) If an owner or operator makes their own calibration gas, a description of the procedure used.

(9) The connector monitoring schedule for each process unit as specified in §60.482–11a(b)(3)(v).

(10) Records of each release from a pressure relief device subject to §60.482–4a.

(f) The following information pertaining to all valves subject to the requirements of §60.482–7a(g) and (h), all pumps subject to the requirements of §60.482–2a(g), and all connectors subject to the requirements of §60.482–11a(e) shall be recorded in a log that is kept in a readily accessible location:

(1) A list of identification numbers for valves, pumps, and connectors that are designated as unsafe-to-monitor, an explanation for each valve, pump, or connector stating why the valve, pump, or connector is unsafe-to-monitor, and the plan for monitoring each valve, pump, or connector.

(2) A list of identification numbers for valves that are designated as difficult-to-monitor, an explanation for each valve stating why the valve is difficult-to-monitor, and the schedule for monitoring each valve.

(g) The following information shall be recorded for valves complying with §60.483–2a:

(1) A schedule of monitoring.

(2) The percent of valves found leaking during each monitoring period.

(h) The following information shall be recorded in a log that is kept in a readily accessible location:

(1) Design criterion required in §§60.482–2a(d)(5) and 60.482–3a(e)(2) and explanation of the design criterion; and

(2) Any changes to this criterion and the reasons for the changes.

(i) The following information shall be recorded in a log that is kept in a readily accessible location for use in determining exemptions as provided in §60.480a(d):

(1) An analysis demonstrating the design capacity of the affected facility,

(2) A statement listing the feed or raw materials and products from the affected facilities and an analysis demonstrating whether these chemicals are heavy liquids or beverage alcohol, and

(3) An analysis demonstrating that equipment is not in VOC service.

(j) Information and data used to demonstrate that a piece of equipment is not in VOC service shall be recorded in a log that is kept in a readily accessible location.

(k) The provisions of §60.7(b) and (d) do not apply to affected facilities subject to this subpart.

§ 60.487a Reporting requirements.

(a) Each owner or operator subject to the provisions of this subpart shall submit semiannual reports to the Administrator beginning 6 months after the initial startup date.

(b) The initial semiannual report to the Administrator shall include the following information:

(1) Process unit identification.

(2) Number of valves subject to the requirements of §60.482–7a, excluding those valves designated for no detectable emissions under the provisions of §60.482–7a(f).

(3) Number of pumps subject to the requirements of §60.482–2a, excluding those pumps designated for no detectable emissions under the provisions of §60.482–2a(e) and those pumps complying with §60.482–2a(f).

(4) Number of compressors subject to the requirements of §60.482–3a, excluding those compressors designated for no detectable emissions under the provisions of §60.482–3a(i) and those compressors complying with §60.482–3a(h).

(5) Number of connectors subject to the requirements of §60.482–11a.

(c) All semiannual reports to the Administrator shall include the following information, summarized from the information in §60.486a:

(1) Process unit identification.

(2) For each month during the semiannual reporting period,

(i) Number of valves for which leaks were detected as described in §60.482–7a(b) or §60.483–2a,

(ii) Number of valves for which leaks were not repaired as required in §60.482–7a(d)(1),

(iii) Number of pumps for which leaks were detected as described in §60.482–2a(b), (d)(4)(ii)(A) or (B), or (d)(5)(iii),

(iv) Number of pumps for which leaks were not repaired as required in §60.482–2a(c)(1) and (d)(6),

(v) Number of compressors for which leaks were detected as described in §60.482–3a(f),

(vi) Number of compressors for which leaks were not repaired as required in §60.482–3a(g)(1),

(vii) Number of connectors for which leaks were detected as described in §60.482–11a(b)

(viii) Number of connectors for which leaks were not repaired as required in §60.482–11a(d), and

(ix)–(x) [Reserved]

(xi) The facts that explain each delay of repair and, where appropriate, why a process unit shutdown was technically infeasible.

(3) Dates of process unit shutdowns which occurred within the semiannual reporting period.

(4) Revisions to items reported according to paragraph (b) of this section if changes have occurred since the initial report or subsequent revisions to the initial report.

(d) An owner or operator electing to comply with the provisions of §§60.483–1a or 60.483–2a shall notify the Administrator of the alternative standard selected 90 days before implementing either of the provisions.

(e) An owner or operator shall report the results of all performance tests in accordance with §60.8 of the General Provisions. The provisions of §60.8(d) do not apply to affected facilities subject to the provisions of this subpart except that an owner or operator must notify the Administrator of the schedule for the initial performance tests at least 30 days before the initial performance tests.

(f) The requirements of paragraphs (a) through (c) of this section remain in force until and unless EPA, in delegating enforcement authority to a state under section 111(c) of the CAA, approves reporting requirements or an alternative means of compliance surveillance adopted by such state. In that event, affected sources within the

state will be relieved of the obligation to comply with the requirements of paragraphs (a) through (c) of this section, provided that they comply with the requirements established by the state.

§ 60.488a Reconstruction.

For the purposes of this subpart:

(a) The cost of the following frequently replaced components of the facility shall not be considered in calculating either the "fixed capital cost of the new components" or the "fixed capital costs that would be required to construct a comparable new facility" under §60.15: Pump seals, nuts and bolts, rupture disks, and packings.

(b) Under §60.15, the "fixed capital cost of new components" includes the fixed capital cost of all depreciable components (except components specified in §60.488a(a)) which are or will be replaced pursuant to all continuous programs of component replacement which are commenced within any 2-year period following the applicability date for the appropriate subpart. (See the "Applicability and designation of affected facility" section of the appropriate subpart.) For purposes of this paragraph, "commenced" means that an owner or operator has undertaken a continuous program of component replacement or that an owner or operator has entered into a contractual obligation to undertake and complete, within a reasonable time, a continuous program of component replacement.

§ 60.489a List of chemicals produced by affected facilities.

Process units that produce, as intermediates or final products, chemicals listed in §60.489 are covered under this subpart. The applicability date for process units producing one or more of these chemicals is November 8, 2006.

**Indiana Department of Environmental Management
Office of Air Quality**

Attachment E

Subpart III—Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

Source: 71 FR 39172, July 11, 2006, unless otherwise noted.

What This Subpart Covers

§ 60.4200 Am I subject to this subpart?

(a) The provisions of this subpart are applicable to manufacturers, owners, and operators of stationary compression ignition (CI) internal combustion engines (ICE) as specified in paragraphs (a)(1) through (3) of this section. For the purposes of this subpart, the date that construction commences is the date the engine is ordered by the owner or operator.

(1) Manufacturers of stationary CI ICE with a displacement of less than 30 liters per cylinder where the model year is:

(i) 2007 or later, for engines that are not fire pump engines,

(ii) The model year listed in table 3 to this subpart or later model year, for fire pump engines.

(2) Owners and operators of stationary CI ICE that commence construction after July 11, 2005 where the stationary CI ICE are:

(i) Manufactured after April 1, 2006 and are not fire pump engines, or

(ii) Manufactured as a certified National Fire Protection Association (NFPA) fire pump engine after July 1, 2006.

(3) Owners and operators of stationary CI ICE that modify or reconstruct their stationary CI ICE after July 11, 2005.

(b) The provisions of this subpart are not applicable to stationary CI ICE being tested at a stationary CI ICE test cell/stand.

(c) If you are an owner or operator of an area source subject to this subpart, you are exempt from the obligation to obtain a permit under 40 CFR part 70 or 40 CFR part 71, provided you are not required to obtain a permit under 40 CFR 70.3(a) or 40 CFR 71.3(a) for a reason other than your status as an area source under this subpart. Notwithstanding the previous sentence, you must continue to comply with the provisions of this subpart applicable to area sources.

(d) Stationary CI ICE may be eligible for exemption from the requirements of this subpart as described in 40 CFR part 1068, subpart C (or the exemptions described in 40 CFR part 89, subpart J and 40 CFR part 94, subpart J, for engines that would need to be certified to standards in those parts), except that owners and operators, as well as manufacturers, may be eligible to request an exemption for national security.

Emission Standards for Manufacturers

§ 60.4201 What emission standards must I meet for non-emergency engines if I am a stationary CI internal combustion engine manufacturer?

(a) Stationary CI internal combustion engine manufacturers must certify their 2007 model year and later non-emergency stationary CI ICE with a maximum engine power less than or equal to 2,237 kilowatt (KW) (3,000 horsepower (HP)) and a displacement of less than 10 liters per cylinder to the certification emission standards for new nonroad CI engines in 40 CFR 89.112, 40 CFR 89.113, 40 CFR 1039.101, 40 CFR 1039.102, 40 CFR 1039.104, 40 CFR 1039.105, 40 CFR 1039.107, and 40 CFR 1039.115, as applicable, for all pollutants, for the same model year and maximum engine power.

(b) Stationary CI internal combustion engine manufacturers must certify their 2007 through 2010 model year non-emergency stationary CI ICE with a maximum engine power greater than 2,237 KW (3,000 HP) and a displacement of less than 10 liters per cylinder to the emission standards in table 1 to this subpart, for all pollutants, for the same maximum engine power.

(c) Stationary CI internal combustion engine manufacturers must certify their 2011 model year and later non-emergency stationary CI ICE with a maximum engine power greater than 2,237 KW (3,000 HP) and a displacement of less than 10 liters per cylinder to the certification emission standards for new nonroad CI engines in 40 CFR 1039.101, 40 CFR 1039.102, 40 CFR 1039.104, 40 CFR 1039.105, 40 CFR 1039.107, and 40 CFR 1039.115, as applicable, for all pollutants, for the same maximum engine power.

(d) Stationary CI internal combustion engine manufacturers must certify their 2007 model year and later non-emergency stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder to the certification emission standards for new marine CI engines in 40 CFR 94.8, as applicable, for all pollutants, for the same displacement and maximum engine power.

§ 60.4202 What emission standards must I meet for emergency engines if I am a stationary CI internal combustion engine manufacturer?

(a) Stationary CI internal combustion engine manufacturers must certify their 2007 model year and later emergency stationary CI ICE with a maximum engine power less than or equal to 2,237 KW (3,000 HP) and a displacement of less than 10 liters per cylinder that are not fire pump engines to the emission standards specified in paragraphs (a)(1) through (2) of this section.

(1) For engines with a maximum engine power less than 37 KW (50 HP):

(i) The certification emission standards for new nonroad CI engines for the same model year and maximum engine power in 40 CFR 89.112 and 40 CFR 89.113 for all pollutants for model year 2007 engines, and

(ii) The certification emission standards for new nonroad CI engines in 40 CFR 1039.104, 40 CFR 1039.105, 40 CFR 1039.107, 40 CFR 1039.115, and table 2 to this subpart, for 2008 model year and later engines.

(2) For engines with a maximum engine power greater than or equal to 37 KW (50 HP), the certification emission standards for new nonroad CI engines for the same model year and maximum engine power in 40 CFR 89.112 and 40 CFR 89.113 for all pollutants beginning in model year 2007.

(b) Stationary CI internal combustion engine manufacturers must certify their 2007 model year and later emergency stationary CI ICE with a maximum engine power greater than 2,237 KW (3,000 HP) and a displacement of less than 10 liters per cylinder that are not fire pump engines to the emission standards specified in paragraphs (b)(1) through (2) of this section.

(1) For 2007 through 2010 model years, the emission standards in table 1 to this subpart, for all pollutants, for the same maximum engine power.

(2) For 2011 model year and later, the certification emission standards for new nonroad CI engines for engines of the same model year and maximum engine power in 40 CFR 89.112 and 40 CFR 89.113 for all pollutants.

(c) Stationary CI internal combustion engine manufacturers must certify their 2007 model year and later emergency stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less

than 30 liters per cylinder that are not fire pump engines to the certification emission standards for new marine CI engines in 40 CFR 94.8, as applicable, for all pollutants, for the same displacement and maximum engine power.

(d) Beginning with the model years in table 3 to this subpart, stationary CI internal combustion engine manufacturers must certify their fire pump stationary CI ICE to the emission standards in table 4 to this subpart, for all pollutants, for the same model year and NFPA nameplate power.

§ 60.4203 How long must my engines meet the emission standards if I am a stationary CI internal combustion engine manufacturer?

Engines manufactured by stationary CI internal combustion engine manufacturers must meet the emission standards as required in §§60.4201 and 60.4202 during the useful life of the engines.

Emission Standards for Owners and Operators

§ 60.4204 What emission standards must I meet for non-emergency engines if I am an owner or operator of a stationary CI internal combustion engine?

(a) Owners and operators of pre-2007 model year non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder must comply with the emission standards in table 1 to this subpart. Owners and operators of pre-2007 model year non-emergency stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder must comply with the emission standards in 40 CFR 94.8(a)(1).

(b) Owners and operators of 2007 model year and later non-emergency stationary CI ICE with a displacement of less than 30 liters per cylinder must comply with the emission standards for new CI engines in §60.4201 for their 2007 model year and later stationary CI ICE, as applicable.

(c) Owners and operators of non-emergency stationary CI ICE with a displacement of greater than or equal to 30 liters per cylinder must meet the requirements in paragraphs (c)(1) and (2) of this section.

(1) Reduce nitrogen oxides (NO_x) emissions by 90 percent or more, or limit the emissions of NO_x in the stationary CI internal combustion engine exhaust to 1.6 grams per KW-hour (g/KW-hr) (1.2 grams per HP-hour (g/HP-hr)).

(2) Reduce particulate matter (PM) emissions by 60 percent or more, or limit the emissions of PM in the stationary CI internal combustion engine exhaust to 0.15 g/KW-hr (0.11 g/HP-hr).

§ 60.4205 What emission standards must I meet for emergency engines if I am an owner or operator of a stationary CI internal combustion engine?

(a) Owners and operators of pre-2007 model year emergency stationary CI ICE with a displacement of less than 10 liters per cylinder that are not fire pump engines must comply with the emission standards in table 1 to this subpart. Owners and operators of pre-2007 model year non-emergency stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder that are not fire pump engines must comply with the emission standards in 40 CFR 94.8(a)(1).

(b) Owners and operators of 2007 model year and later emergency stationary CI ICE with a displacement of less than 30 liters per cylinder that are not fire pump engines must comply with the emission standards for new nonroad CI engines in §60.4202, for all pollutants, for the same model year and maximum engine power for their 2007 model year and later emergency stationary CI ICE.

(c) Owners and operators of fire pump engines with a displacement of less than 30 liters per cylinder must comply with the emission standards in table 4 to this subpart, for all pollutants.

(d) Owners and operators of emergency stationary CI ICE with a displacement of greater than or equal to 30 liters per cylinder must meet the requirements in paragraphs (d)(1) and (2) of this section.

(1) Reduce NO_x emissions by 90 percent or more, or limit the emissions of NO_x in the stationary CI internal combustion engine exhaust to 1.6 grams per KW-hour (1.2 grams per HP-hour).

(2) Reduce PM emissions by 60 percent or more, or limit the emissions of PM in the stationary CI internal combustion engine exhaust to 0.15 g/KW-hr (0.11 g/HP-hr).

§ 60.4206 How long must I meet the emission standards if I am an owner or operator of a stationary CI internal combustion engine?

Owners and operators of stationary CI ICE must operate and maintain stationary CI ICE that achieve the emission standards as required in §§60.4204 and 60.4205 according to the manufacturer's written instructions or procedures developed by the owner or operator that are approved by the engine manufacturer, over the entire life of the engine.

Fuel Requirements for Owners and Operators

§ 60.4207 What fuel requirements must I meet if I am an owner or operator of a stationary CI internal combustion engine subject to this subpart?

(a) Beginning October 1, 2007, owners and operators of stationary CI ICE subject to this subpart that use diesel fuel must use diesel fuel that meets the requirements of 40 CFR 80.510(a).

(b) Beginning October 1, 2010, owners and operators of stationary CI ICE subject to this subpart with a displacement of less than 30 liters per cylinder that use diesel fuel must use diesel fuel that meets the requirements of 40 CFR 80.510(b) for nonroad diesel fuel.

(c) Owners and operators of pre-2011 model year stationary CI ICE subject to this subpart may petition the Administrator for approval to use remaining non-compliant fuel that does not meet the fuel requirements of paragraphs (a) and (b) of this section beyond the dates required for the purpose of using up existing fuel inventories. If approved, the petition will be valid for a period of up to 6 months. If additional time is needed, the owner or operator is required to submit a new petition to the Administrator.

(d) Owners and operators of pre-2011 model year stationary CI ICE subject to this subpart that are located in areas of Alaska not accessible by the Federal Aid Highway System may petition the Administrator for approval to use any fuels mixed with used lubricating oil that do not meet the fuel requirements of paragraphs (a) and (b) of this section. Owners and operators must demonstrate in their petition to the Administrator that there is no other place to use the lubricating oil. If approved, the petition will be valid for a period of up to 6 months. If additional time is needed, the owner or operator is required to submit a new petition to the Administrator.

(e) Stationary CI ICE that have a national security exemption under §60.4200(d) are also exempt from the fuel requirements in this section.

Other Requirements for Owners and Operators

§ 60.4208 What is the deadline for importing or installing stationary CI ICE produced in the previous model year?

(a) After December 31, 2008, owners and operators may not install stationary CI ICE (excluding fire pump engines) that do not meet the applicable requirements for 2007 model year engines.

(b) After December 31, 2009, owners and operators may not install stationary CI ICE with a maximum engine power of less than 19 KW (25 HP) (excluding fire pump engines) that do not meet the applicable requirements for 2008 model year engines.

(c) After December 31, 2014, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 19 KW (25 HP) and less than 56 KW (75 HP) that do not meet the applicable requirements for 2013 model year non-emergency engines.

(d) After December 31, 2013, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 56 KW (75 HP) and less than 130 KW (175 HP) that do not meet the applicable requirements for 2012 model year non-emergency engines.

(e) After December 31, 2012, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 130 KW (175 HP), including those above 560 KW (750 HP), that do not meet the applicable requirements for 2011 model year non-emergency engines.

(f) After December 31, 2016, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 560 KW (750 HP) that do not meet the applicable requirements for 2015 model year non-emergency engines.

(g) In addition to the requirements specified in §§60.4201, 60.4202, 60.4204, and 60.4205, it is prohibited to import stationary CI ICE with a displacement of less than 30 liters per cylinder that do not meet the applicable requirements specified in paragraphs (a) through (f) of this section after the dates specified in paragraphs (a) through (f) of this section.

(h) The requirements of this section do not apply to owners or operators of stationary CI ICE that have been modified, reconstructed, and do not apply to engines that were removed from one existing location and reinstalled at a new location.

§ 60.4209 What are the monitoring requirements if I am an owner or operator of a stationary CI internal combustion engine?

If you are an owner or operator, you must meet the monitoring requirements of this section. In addition, you must also meet the monitoring requirements specified in §60.4211.

(a) If you are an owner or operator of an emergency stationary CI internal combustion engine, you must install a non-resettable hour meter prior to startup of the engine.

(b) If you are an owner or operator of a stationary CI internal combustion engine equipped with a diesel particulate filter to comply with the emission standards in §60.4204, the diesel particulate filter must be installed with a backpressure monitor that notifies the owner or operator when the high backpressure limit of the engine is approached.

Compliance Requirements

§ 60.4210 What are my compliance requirements if I am a stationary CI internal combustion engine manufacturer?

(a) Stationary CI internal combustion engine manufacturers must certify their stationary CI ICE with a displacement of less than 10 liters per cylinder to the emission standards specified in §60.4201(a) through (c) and §60.4202(a), (b) and (d) using the certification procedures required in 40 CFR part 89, subpart B, or 40 CFR part 1039, subpart C, as applicable, and must test their engines as specified in those parts. For the purposes of this subpart, engines certified to the standards in table 1 to this subpart shall be subject to the same requirements as engines certified to the standards in 40 CFR part 89. For the purposes of this subpart, engines certified to the standards in table 4 to this subpart shall be subject to the same requirements as engines certified to the standards in 40 CFR part 89, except that engines with NFPA

nameplate power of less than 37 KW (50 HP) certified to model year 2011 or later standards shall be subject to the same requirements as engines certified to the standards in 40 CFR part 1039.

(b) Stationary CI internal combustion engine manufacturers must certify their stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder to the emission standards specified in §60.4201(d) and §60.4202(c) using the certification procedures required in 40 CFR part 94 subpart C, and must test their engines as specified in 40 CFR part 94.

(c) Stationary CI internal combustion engine manufacturers must meet the requirements of 40 CFR 1039.120, 40 CFR 1039.125, 40 CFR 1039.130, 40 CFR 1039.135, and 40 CFR part 1068 for engines that are certified to the emission standards in 40 CFR part 1039. Stationary CI internal combustion engine manufacturers must meet the corresponding provisions of 40 CFR part 89 or 40 CFR part 94 for engines that would be covered by that part if they were nonroad (including marine) engines. Labels on such engines must refer to stationary engines, rather than or in addition to nonroad or marine engines, as appropriate. Stationary CI internal combustion engine manufacturers must label their engines according to paragraphs (c)(1) through (3) of this section.

(1) Stationary CI internal combustion engines manufactured from January 1, 2006 to March 31, 2006 (January 1, 2006 to June 30, 2006 for fire pump engines), other than those that are part of certified engine families under the nonroad CI engine regulations, must be labeled according to 40 CFR 1039.20.

(2) Stationary CI internal combustion engines manufactured from April 1, 2006 to December 31, 2006 (or, for fire pump engines, July 1, 2006 to December 31 of the year preceding the year listed in table 3 to this subpart) must be labeled according to paragraphs (c)(2)(i) through (iii) of this section:

(i) Stationary CI internal combustion engines that are part of certified engine families under the nonroad regulations must meet the labeling requirements for nonroad CI engines, but do not have to meet the labeling requirements in 40 CFR 1039.20.

(ii) Stationary CI internal combustion engines that meet Tier 1 requirements (or requirements for fire pumps) under this subpart, but do not meet the requirements applicable to nonroad CI engines must be labeled according to 40 CFR 1039.20. The engine manufacturer may add language to the label clarifying that the engine meets Tier 1 requirements (or requirements for fire pumps) of this subpart.

(iii) Stationary CI internal combustion engines manufactured after April 1, 2006 that do not meet Tier 1 requirements of this subpart, or fire pumps engines manufactured after July 1, 2006 that do not meet the requirements for fire pumps under this subpart, may not be used in the U.S. If any such engines are manufactured in the U.S. after April 1, 2006 (July 1, 2006 for fire pump engines), they must be exported or must be brought into compliance with the appropriate standards prior to initial operation. The export provisions of 40 CFR 1068.230 would apply to engines for export and the manufacturers must label such engines according to 40 CFR 1068.230.

(3) Stationary CI internal combustion engines manufactured after January 1, 2007 (for fire pump engines, after January 1 of the year listed in table 3 to this subpart, as applicable) must be labeled according to paragraphs (c)(3)(i) through (iii) of this section.

(i) Stationary CI internal combustion engines that meet the requirements of this subpart and the corresponding requirements for nonroad (including marine) engines of the same model year and HP must be labeled according to the provisions in part 89, 94 or 1039, as appropriate.

(ii) Stationary CI internal combustion engines that meet the requirements of this subpart, but are not certified to the standards applicable to nonroad (including marine) engines of the same model year and HP must be labeled according to the provisions in part 89, 94 or 1039, as appropriate, but the words "stationary" must be included instead of "nonroad" or "marine" on the label. In addition, such engines must be labeled according to 40 CFR 1039.20.

(iii) Stationary CI internal combustion engines that do not meet the requirements of this subpart must be labeled according to 40 CFR 1068.230 and must be exported under the provisions of 40 CFR 1068.230.

(d) An engine manufacturer certifying an engine family or families to standards under this subpart that are identical to standards applicable under parts 89, 94, or 1039 for that model year may certify any such family that contains both nonroad (including marine) and stationary engines as a single engine family and/or may include any such family containing stationary engines in the averaging, banking and trading provisions applicable for such engines under those parts.

(e) Manufacturers of engine families discussed in paragraph (d) of this section may meet the labeling requirements referred to in paragraph (c) of this section for stationary CI ICE by either adding a separate label containing the information required in paragraph (c) of this section or by adding the words "and stationary" after the word "nonroad" or "marine," as appropriate, to the label.

(f) Starting with the model years shown in table 5 to this subpart, stationary CI internal combustion engine manufacturers must add a permanent label stating that the engine is for stationary emergency use only to each new emergency stationary CI internal combustion engine greater than or equal to 19 KW (25 HP) that meets all the emission standards for emergency engines in §60.4202 but does not meet all the emission standards for non-emergency engines in §60.4201. The label must be added according to the labeling requirements specified in 40 CFR 1039.135(b). Engine manufacturers must specify in the owner's manual that operation of emergency engines is limited to emergency operations and required maintenance and testing.

(g) Manufacturers of fire pump engines may use the test cycle in table 6 to this subpart for testing fire pump engines and may test at the NFPA certified nameplate HP, provided that the engine is labeled as "Fire Pump Applications Only".

(h) Engine manufacturers, including importers, may introduce into commerce uncertified engines or engines certified to earlier standards that were manufactured before the new or changed standards took effect until inventories are depleted, as long as such engines are part of normal inventory. For example, if the engine manufacturers' normal industry practice is to keep on hand a one-month supply of engines based on its projected sales, and a new tier of standards starts to apply for the 2009 model year, the engine manufacturer may manufacture engines based on the normal inventory requirements late in the 2008 model year, and sell those engines for installation. The engine manufacturer may not circumvent the provisions of §§60.4201 or 60.4202 by stockpiling engines that are built before new or changed standards take effect. Stockpiling of such engines beyond normal industry practice is a violation of this subpart.

(i) The replacement engine provisions of 40 CFR 89.1003(b)(7), 40 CFR 94.1103(b)(3), 40 CFR 94.1103(b)(4) and 40 CFR 1068.240 are applicable to stationary CI engines replacing existing equipment that is less than 15 years old.

§ 60.4211 What are my compliance requirements if I am an owner or operator of a stationary CI internal combustion engine?

(a) If you are an owner or operator and must comply with the emission standards specified in this subpart, you must operate and maintain the stationary CI internal combustion engine and control device according to the manufacturer's written instructions or procedures developed by the owner or operator that are approved by the engine manufacturer. In addition, owners and operators may only change those settings that are permitted by the manufacturer. You must also meet the requirements of 40 CFR parts 89, 94 and/or 1068, as they apply to you.

(b) If you are an owner or operator of a pre-2007 model year stationary CI internal combustion engine and must comply with the emission standards specified in §§60.4204(a) or 60.4205(a), or if you are an owner or operator of a CI fire pump engine that is manufactured prior to the model years in table 3 to this subpart and must comply with the emission standards specified in §60.4205(c), you must demonstrate compliance according to one of the methods specified in paragraphs (b)(1) through (5) of this section.

(1) Purchasing an engine certified according to 40 CFR part 89 or 40 CFR part 94, as applicable, for the same model year and maximum engine power. The engine must be installed and configured according to the manufacturer's specifications.

(2) Keeping records of performance test results for each pollutant for a test conducted on a similar engine. The test must have been conducted using the same methods specified in this subpart and these methods must have been followed correctly.

(3) Keeping records of engine manufacturer data indicating compliance with the standards.

(4) Keeping records of control device vendor data indicating compliance with the standards.

(5) Conducting an initial performance test to demonstrate compliance with the emission standards according to the requirements specified in §60.4212, as applicable.

(c) If you are an owner or operator of a 2007 model year and later stationary CI internal combustion engine and must comply with the emission standards specified in §60.4204(b) or §60.4205(b), or if you are an owner or operator of a CI fire pump engine that is manufactured during or after the model year that applies to your fire pump engine power rating in table 3 to this subpart and must comply with the emission standards specified in §60.4205(c), you must comply by purchasing an engine certified to the emission standards in §60.4204(b), or §60.4205(b) or (c), as applicable, for the same model year and maximum (or in the case of fire pumps, NFPA nameplate) engine power. The engine must be installed and configured according to the manufacturer's specifications.

(d) If you are an owner or operator and must comply with the emission standards specified in §60.4204(c) or §60.4205(d), you must demonstrate compliance according to the requirements specified in paragraphs (d)(1) through (3) of this section.

(1) Conducting an initial performance test to demonstrate initial compliance with the emission standards as specified in §60.4213.

(2) Establishing operating parameters to be monitored continuously to ensure the stationary internal combustion engine continues to meet the emission standards. The owner or operator must petition the Administrator for approval of operating parameters to be monitored continuously. The petition must include the information described in paragraphs (d)(2)(i) through (v) of this section.

(i) Identification of the specific parameters you propose to monitor continuously;

(ii) A discussion of the relationship between these parameters and NO_x and PM emissions, identifying how the emissions of these pollutants change with changes in these parameters, and how limitations on these parameters will serve to limit NO_x and PM emissions;

(iii) A discussion of how you will establish the upper and/or lower values for these parameters which will establish the limits on these parameters in the operating limitations;

(iv) A discussion identifying the methods and the instruments you will use to monitor these parameters, as well as the relative accuracy and precision of these methods and instruments; and

(v) A discussion identifying the frequency and methods for recalibrating the instruments you will use for monitoring these parameters.

(3) For non-emergency engines with a displacement of greater than or equal to 30 liters per cylinder, conducting annual performance tests to demonstrate continuous compliance with the emission standards as specified in §60.4213.

(e) Emergency stationary ICE may be operated for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State, or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Maintenance checks and readiness testing of such units is limited to 100 hours per year. There is no time limit on the use of emergency stationary ICE in emergency situations. Anyone may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or

operator maintains records indicating that Federal, State, or local standards require maintenance and testing of emergency ICE beyond 100 hours per year. For owners and operators of emergency engines meeting standards under §60.4205 but not §60.4204, any operation other than emergency operation, and maintenance and testing as permitted in this section, is prohibited.

Testing Requirements for Owners and Operators

§ 60.4212 What test methods and other procedures must I use if I am an owner or operator of a stationary CI internal combustion engine with a displacement of less than 30 liters per cylinder?

Owners and operators of stationary CI ICE with a displacement of less than 30 liters per cylinder who conduct performance tests pursuant to this subpart must do so according to paragraphs (a) through (d) of this section.

(a) The performance test must be conducted according to the in-use testing procedures in 40 CFR part 1039, subpart F.

(b) Exhaust emissions from stationary CI ICE that are complying with the emission standards for new CI engines in 40 CFR part 1039 must not exceed the not-to-exceed (NTE) standards for the same model year and maximum engine power as required in 40 CFR 1039.101(e) and 40 CFR 1039.102(g)(1), except as specified in 40 CFR 1039.104(d). This requirement starts when NTE requirements take effect for nonroad diesel engines under 40 CFR part 1039.

(c) Exhaust emissions from stationary CI ICE that are complying with the emission standards for new CI engines in 40 CFR 89.112 or 40 CFR 94.8, as applicable, must not exceed the NTE numerical requirements, rounded to the same number of decimal places as the applicable standard in 40 CFR 89.112 or 40 CFR 94.8, as applicable, determined from the following equation:

$$\text{NTE requirement for each pollutant} = (1.25) \times (\text{STD}) \quad (\text{Eq. 1})$$

Where:

STD = The standard specified for that pollutant in 40 CFR 89.112 or 40 CFR 94.8, as applicable.

Alternatively, stationary CI ICE that are complying with the emission standards for new CI engines in 40 CFR 89.112 or 40 CFR 94.8 may follow the testing procedures specified in §60.4213 of this subpart, as appropriate.

(d) Exhaust emissions from stationary CI ICE that are complying with the emission standards for pre-2007 model year engines in §60.4204(a), §60.4205(a), or §60.4205(c) must not exceed the NTE numerical requirements, rounded to the same number of decimal places as the applicable standard in §60.4204(a), §60.4205(a), or §60.4205(c), determined from the equation in paragraph (c) of this section.

Where:

STD = The standard specified for that pollutant in §60.4204(a), §60.4205(a), or §60.4205(c).

Alternatively, stationary CI ICE that are complying with the emission standards for pre-2007 model year engines in §60.4204(a), §60.4205(a), or §60.4205(c) may follow the testing procedures specified in §60.4213, as appropriate.

§ 60.4213 What test methods and other procedures must I use if I am an owner or operator of a stationary CI internal combustion engine with a displacement of greater than or equal to 30 liters per cylinder?

Owners and operators of stationary CI ICE with a displacement of greater than or equal to 30 liters per cylinder must conduct performance tests according to paragraphs (a) through (d) of this section.

(a) Each performance test must be conducted according to the requirements in §60.8 and under the specific conditions that this subpart specifies in table 7. The test must be conducted within 10 percent of 100 percent peak (or the highest achievable) load.

(b) You may not conduct performance tests during periods of startup, shutdown, or malfunction, as specified in §60.8(c).

(c) You must conduct three separate test runs for each performance test required in this section, as specified in §60.8(f). Each test run must last at least 1 hour.

(d) To determine compliance with the percent reduction requirement, you must follow the requirements as specified in paragraphs (d)(1) through (3) of this section.

(1) You must use Equation 2 of this section to determine compliance with the percent reduction requirement:

$$\frac{C_i - C_o}{C_i} \times 100 = R \quad (\text{Eq. 2})$$

Where:

C_i = concentration of NO_x or PM at the control device inlet,

C_o = concentration of NO_x or PM at the control device outlet, and

R = percent reduction of NO_x or PM emissions.

(2) You must normalize the NO_x or PM concentrations at the inlet and outlet of the control device to a dry basis and to 15 percent oxygen (O_2) using Equation 3 of this section, or an equivalent percent carbon dioxide (CO_2) using the procedures described in paragraph (d)(3) of this section.

$$C_{\text{adj}} = C_d \frac{5.9}{20.9 - \% \text{O}_2} \quad (\text{Eq. 3})$$

Where:

C_{adj} = Calculated NO_x or PM concentration adjusted to 15 percent O_2 .

C_d = Measured concentration of NO_x or PM, uncorrected.

5.9 = 20.9 percent O_2 - 15 percent O_2 , the defined O_2 correction value, percent.

$\% \text{O}_2$ = Measured O_2 concentration, dry basis, percent.

(3) If pollutant concentrations are to be corrected to 15 percent O_2 and CO_2 concentration is measured in lieu of O_2 concentration measurement, a CO_2 correction factor is needed. Calculate the CO_2 correction factor as described in paragraphs (d)(3)(i) through (iii) of this section.

(i) Calculate the fuel-specific F_o value for the fuel burned during the test using values obtained from Method 19, Section 5.2, and the following equation:

$$F_o = \frac{0.209}{F_c} \quad (\text{Eq. 4})$$

Where:

F_o = Fuel factor based on the ratio of O_2 volume to the ultimate CO_2 volume produced by the fuel at zero percent excess air.

0.209 = Fraction of air that is O_2 , percent/100.

F_d = Ratio of the volume of dry effluent gas to the gross calorific value of the fuel from Method 19, dm^3 / J ($dscf/10^6$ Btu).

F_c = Ratio of the volume of CO_2 produced to the gross calorific value of the fuel from Method 19, dm^3 / J ($dscf/10^6$ Btu).

(ii) Calculate the CO_2 correction factor for correcting measurement data to 15 percent O_2 , as follows:

$$X_{CO_2} = \frac{5.9}{F_o} \quad (\text{Eq. 5})$$

Where:

X_{CO_2} = CO_2 correction factor, percent.

5.9 = 20.9 percent O_2 - 15 percent O_2 , the defined O_2 correction value, percent.

(iii) Calculate the NO_x and PM gas concentrations adjusted to 15 percent O_2 using CO_2 as follows:

$$C_{adj} = C_d \frac{X_{CO_2}}{\%CO_2} \quad (\text{Eq. 6})$$

Where:

C_{adj} = Calculated NO_x or PM concentration adjusted to 15 percent O_2 .

C_d = Measured concentration of NO_x or PM, uncorrected.

$\%CO_2$ = Measured CO_2 concentration, dry basis, percent.

(e) To determine compliance with the NO_x mass per unit output emission limitation, convert the concentration of NO_x in the engine exhaust using Equation 7 of this section:

$$ER = \frac{C_d \times 1.912 \times 10^{-3} \times Q \times T}{KW\text{-hour}} \quad (\text{Eq. 7})$$

Where:

ER = Emission rate in grams per KW-hour.

C_d = Measured NO_x concentration in ppm.

1.912×10^{-3} = Conversion constant for ppm NO_x to grams per standard cubic meter at 25 degrees Celsius.

Q = Stack gas volumetric flow rate, in standard cubic meter per hour.

T = Time of test run, in hours.

KW-hour = Brake work of the engine, in KW-hour.

(f) To determine compliance with the PM mass per unit output emission limitation, convert the concentration of PM in the engine exhaust using Equation 8 of this section:

$$ER = \frac{C_{adj} \times Q \times T}{KW\text{-hour}} \quad (\text{Eq 8})$$

Where:

ER = Emission rate in grams per KW-hour.

C_{adj} = Calculated PM concentration in grams per standard cubic meter.

Q = Stack gas volumetric flow rate, in standard cubic meter per hour.

T = Time of test run, in hours.

KW-hour = Energy output of the engine, in KW.

Notification, Reports, and Records for Owners and Operators

§ 60.4214 What are my notification, reporting, and recordkeeping requirements if I am an owner or operator of a stationary CI internal combustion engine?

(a) Owners and operators of non-emergency stationary CI ICE that are greater than 2,237 KW (3,000 HP), or have a displacement of greater than or equal to 10 liters per cylinder, or are pre-2007 model year engines that are greater than 130 KW (175 HP) and not certified, must meet the requirements of paragraphs (a)(1) and (2) of this section.

(1) Submit an initial notification as required in §60.7(a)(1). The notification must include the information in paragraphs (a)(1)(i) through (v) of this section.

(i) Name and address of the owner or operator;

(ii) The address of the affected source;

(iii) Engine information including make, model, engine family, serial number, model year, maximum engine power, and engine displacement;

(iv) Emission control equipment; and

(v) Fuel used.

(2) Keep records of the information in paragraphs (a)(2)(i) through (iv) of this section.

(i) All notifications submitted to comply with this subpart and all documentation supporting any notification.

(ii) Maintenance conducted on the engine.

(iii) If the stationary CI internal combustion is a certified engine, documentation from the manufacturer that the engine is certified to meet the emission standards.

(iv) If the stationary CI internal combustion is not a certified engine, documentation that the engine meets the emission standards.

(b) If the stationary CI internal combustion engine is an emergency stationary internal combustion engine, the owner or operator is not required to submit an initial notification. Starting with the model years in table 5 to this subpart, if the emergency engine does not meet the standards applicable to non-emergency engines in the applicable model year, the owner or operator must keep records of the operation of the engine in emergency and non-emergency service that are recorded through the non-resettable hour meter. The owner must record the time of operation of the engine and the reason the engine was in operation during that time.

(c) If the stationary CI internal combustion engine is equipped with a diesel particulate filter, the owner or operator must keep records of any corrective action taken after the backpressure monitor has notified the owner or operator that the high backpressure limit of the engine is approached.

Special Requirements

§ 60.4215 What requirements must I meet for engines used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands?

(a) Stationary CI ICE that are used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands are required to meet the applicable emission standards in §60.4205. Non-emergency stationary CI ICE with a displacement of greater than or equal to 30 liters per cylinder, must meet the applicable emission standards in §60.4204(c).

(b) Stationary CI ICE that are used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands are not required to meet the fuel requirements in §60.4207.

§ 60.4216 What requirements must I meet for engines used in Alaska?

(a) Prior to December 1, 2010, owners and operators of stationary CI engines located in areas of Alaska not accessible by the Federal Aid Highway System should refer to 40 CFR part 69 to determine the diesel fuel requirements applicable to such engines.

(b) The Governor of Alaska may submit for EPA approval, by no later than January 11, 2008, an alternative plan for implementing the requirements of 40 CFR part 60, subpart IIII, for public-sector electrical utilities located in rural areas of Alaska not accessible by the Federal Aid Highway System. This alternative plan must be based on the requirements of section 111 of the Clean Air Act including any increased risks to human health and the environment and must also be based on the unique circumstances related to remote power generation, climatic conditions, and serious economic impacts resulting from implementation of 40 CFR part 60, subpart IIII. If EPA approves by rulemaking process an alternative plan, the provisions as approved by EPA under that plan shall apply to the diesel engines used in new stationary internal combustion engines subject to this paragraph.

§ 60.4217 What emission standards must I meet if I am an owner or operator of a stationary internal combustion engine using special fuels?

(a) Owners and operators of stationary CI ICE that do not use diesel fuel, or who have been given authority by the Administrator under §60.4207(d) of this subpart to use fuels that do not meet the fuel requirements of paragraphs (a) and (b) of §60.4207, may petition the Administrator for approval of alternative emission standards, if they can demonstrate that they use a fuel that is not the fuel on which the manufacturer of the engine certified the engine and that the engine cannot meet the applicable standards required in §60.4202 or §60.4203 using such fuels.

(b) [Reserved]

General Provisions

§ 60.4218 What parts of the General Provisions apply to me?

Table 8 to this subpart shows which parts of the General Provisions in §§60.1 through 60.19 apply to you.

Definitions

§ 60.4219 What definitions apply to this subpart?

As used in this subpart, all terms not defined herein shall have the meaning given them in the CAA and in subpart A of this part.

Combustion turbine means all equipment, including but not limited to the turbine, the fuel, air, lubrication and exhaust gas systems, control systems (except emissions control equipment), and any ancillary components and sub-components comprising any simple cycle combustion turbine, any regenerative/recuperative cycle combustion turbine, the combustion turbine portion of any cogeneration cycle combustion system, or the combustion turbine portion of any combined cycle steam/electric generating system.

Compression ignition means relating to a type of stationary internal combustion engine that is not a spark ignition engine.

Diesel fuel means any liquid obtained from the distillation of petroleum with a boiling point of approximately 150 to 360 degrees Celsius. One commonly used form is number 2 distillate oil.

Diesel particulate filter means an emission control technology that reduces PM emissions by trapping the particles in a flow filter substrate and periodically removes the collected particles by either physical action or by oxidizing (burning off) the particles in a process called regeneration.

Emergency stationary internal combustion engine means any stationary internal combustion engine whose operation is limited to emergency situations and required testing and maintenance. Examples include stationary ICE used to produce power for critical networks or equipment (including power supplied to portions of a facility) when electric power from the local utility (or the normal power source, if the facility runs on its own power production) is interrupted, or stationary ICE used to pump water in the case of fire or flood, etc. Stationary CI ICE used to supply power to an electric grid or that supply power as part of a financial arrangement with another entity are not considered to be emergency engines.

Engine manufacturer means the manufacturer of the engine. See the definition of "manufacturer" in this section.

Fire pump engine means an emergency stationary internal combustion engine certified to NFPA requirements that is used to provide power to pump water for fire suppression or protection.

Manufacturer has the meaning given in section 216(1) of the Act. In general, this term includes any person who manufactures a stationary engine for sale in the United States or otherwise introduces a new stationary engine into commerce in the United States. This includes importers who import stationary engines for sale or resale.

Maximum engine power means maximum engine power as defined in 40 CFR 1039.801.

Model year means either:

- (1) The calendar year in which the engine was originally produced, or
- (2) The annual new model production period of the engine manufacturer if it is different than the calendar year. This must include January 1 of the calendar year for which the model year is named. It may not begin before January 2 of the previous calendar year and it must end by December 31 of the named calendar year. For an engine that is converted to a stationary engine after being placed into service as a nonroad or other non-stationary engine, model year means the calendar year or new model production period in which the engine was originally produced.

Other internal combustion engine means any internal combustion engine, except combustion turbines, which is not a reciprocating internal combustion engine or rotary internal combustion engine.

Reciprocating internal combustion engine means any internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work.

Rotary internal combustion engine means any internal combustion engine which uses rotary motion to convert heat energy into mechanical work.

Spark ignition means relating to a gasoline, natural gas, or liquefied petroleum gas fueled engine or any other type of engine with a spark plug (or other sparking device) and with operating characteristics significantly similar to the theoretical Otto combustion cycle. Spark ignition engines usually use a throttle to regulate intake air flow to control power during normal operation. Dual-fuel engines in which a liquid fuel (typically diesel fuel) is used for CI and gaseous fuel (typically natural gas) is used as the primary fuel at an annual average ratio of less than 2 parts diesel fuel to 100 parts total fuel on an energy equivalent basis are spark ignition engines.

Stationary internal combustion engine means any internal combustion engine, except combustion turbines, that converts heat energy into mechanical work and is not mobile. Stationary ICE differ from mobile ICE in that a stationary internal combustion engine is not a nonroad engine as defined at 40 CFR 1068.30 (excluding paragraph (2)(ii) of that definition), and is not used to propel a motor vehicle or a vehicle used solely for competition. Stationary ICE include reciprocating ICE, rotary ICE, and other ICE, except combustion turbines.

Subpart means 40 CFR part 60, subpart IIII.

Useful life means the period during which the engine is designed to properly function in terms of reliability and fuel consumption, without being remanufactured, specified as a number of hours of operation or calendar years, whichever comes first. The values for useful life for stationary CI ICE with a displacement of less than 10 liters per cylinder are given in 40 CFR 1039.101(g). The values for useful life for stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder are given in 40 CFR 94.9(a).

Table 1 to Subpart IIII of Part 60—Emission Standards for Stationary Pre-2007 Model Year Engines With a Displacement of <10 Liters per Cylinder and 2007–2010 Model Year Engines >2,237 KW (3,000 HP) and With a Displacement of <10 Liters per Cylinder

[As stated in §§60.4201(b), 60.4202(b), 60.4204(a), and 60.4205(a), you must comply with the following emission standards]

Maximum engine power	Emission standards for stationary pre-2007 model year engines with a displacement of <10 liters per cylinder and 2007–2010 model year engines >2,237 KW (3,000 HP) and with a displacement of <10 liters per cylinder in g/KW-hr (g/HP-hr)				
	NMHC + NO _x	HC	NO _x	CO	PM
KW<8 (HP<11)	10.5 (7.8)			8.0 (6.0)	1.0 (0.75)
8≤KW<19 (11≤HP<25)	9.5 (7.1)			6.6 (4.9)	0.80 (0.60)
19≤KW<37 (25≤HP<50)	9.5 (7.1)			5.5 (4.1)	0.80 (0.60)
37≤KW<56 (50≤HP<75)			9.2 (6.9)		
56≤KW<75 (75≤HP<100)			9.2 (6.9)		
75≤KW<130 (100≤HP<175)			9.2 (6.9)		
130≤KW<225 (175≤HP<300)		1.3 (1.0)	9.2 (6.9)	11.4 (8.5)	0.54 (0.40)
225≤KW<450 (300≤HP<600)		1.3 (1.0)	9.2 (6.9)	11.4 (8.5)	0.54 (0.40)
450≤KW≤560 (600≤HP≤750)		1.3 (1.0)	9.2 (6.9)	11.4 (8.5)	0.54 (0.40)
KW>560 (HP>750)		1.3 (1.0)	9.2 (6.9)	11.4 (8.5)	0.54 (0.40)

Table 2 to Subpart IIII of Part 60—Emission Standards for 2008 Model Year and Later Emergency Stationary CI ICE <37 KW (50 HP) With a Displacement of <10 Liters per Cylinder

[As stated in §60.4202(a)(1), you must comply with the following emission standards]

Engine power	Emission standards for 2008 model year and later emergency stationary CI ICE <37 KW (50 HP) with a displacement of <10 liters per cylinder in g/KW-hr (g/HP-hr)			
	Model year(s)	NO _x + NMHC	CO	PM
KW<8 (HP<11)	2008+	7.5 (5.6)	8.0 (6.0)	0.40 (0.30)
8≤KW<19 (11≤HP<25)	2008+	7.5 (5.6)	6.6 (4.9)	0.40 (0.30)
19≤KW<37 (25≤HP<50)	2008+	7.5 (5.6)	5.5 (4.1)	0.30 (0.22)

Table 3 to Subpart IIII of Part 60—Certification Requirements for Stationary Fire Pump Engines

[As stated in §60.4202(d), you must certify new stationary fire pump engines beginning with the following model years:]

Engine power	Starting model year engine manufacturers must certify new stationary fire pump engines according to §60.4202(d)
KW<75 (HP<100)	2011
75≤KW<130 (100≤HP<175)	2010
130≤KW≤560 (175≤HP≤750)	2009
KW>560 (HP>750)	2008

Table 4 to Subpart IIII of Part 60—Emission Standards for Stationary Fire Pump Engines

[As stated in §§60.4202(d) and 60.4205(c), you must comply with the following emission standards for stationary fire pump engines]

Maximum engine power	Model year(s)	NMHC + NO_x	CO	PM
KW<8 (HP<11)	2010 and earlier	10.5 (7.8)	8.0 (6.0)	1.0 (0.75)
	2011+	7.5 (5.6)		0.40 (0.30)
8≤KW<19 (11≤HP<25)	2010 and earlier	9.5 (7.1)	6.6 (4.9)	0.80 (0.60)
	2011+	7.5 (5.6)		0.40 (0.30)
19≤KW<37 (25≤HP<50)	2010 and earlier	9.5 (7.1)	5.5 (4.1)	0.80 (0.60)
	2011+	7.5 (5.6)		0.30 (0.22)
37≤KW<56 (50≤HP<75)	2010 and earlier	10.5 (7.8)	5.0 (3.7)	0.80 (0.60)
	2011+ ¹	4.7 (3.5)		0.40 (0.30)
56≤KW<75 (75≤HP<100)	2010 and earlier	10.5 (7.8)	5.0 (3.7)	0.80 (0.60)
	2011+ ¹	4.7 (3.5)		0.40 (0.30)
75≤KW<130 (100≤HP<175)	2009 and earlier	10.5 (7.8)	5.0 (3.7)	0.80 (0.60)
	2010+ ²	4.0 (3.0)		0.30 (0.22)
130≤KW<225 (175≤HP<300)	2008 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2009+ ³	4.0 (3.0)		0.20 (0.15)
225≤KW<450 (300≤HP<600)	2008 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2009+ ³	4.0 (3.0)		0.20 (0.15)

450≤KW≤560 (600≤HP≤750)	2008 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2009+	4.0 (3.0)		0.20 (0.15)
KW>560 (HP>750)	2007 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2008+	6.4 (4.8)		0.20 (0.15)

¹For model years 2011–2013, manufacturers, owners and operators of fire pump stationary CI ICE in this engine power category with a rated speed of greater than 2,650 revolutions per minute (rpm) may comply with the emission limitations for 2010 model year engines.

²For model years 2010–2012, manufacturers, owners and operators of fire pump stationary CI ICE in this engine power category with a rated speed of greater than 2,650 rpm may comply with the emission limitations for 2009 model year engines.

³In model years 2009–2011, manufacturers of fire pump stationary CI ICE in this engine power category with a rated speed of greater than 2,650 rpm may comply with the emission limitations for 2008 model year engines.

Table 5 to Subpart IIII of Part 60—Labeling and Recordkeeping Requirements for New Stationary Emergency Engines

[You must comply with the labeling requirements in §60.4210(f) and the recordkeeping requirements in §60.4214(b) for new emergency stationary CI ICE beginning in the following model years:]

Engine power	Starting model year
19≤KW<56 (25≤HP<75)	2013
56≤KW<130 (75≤HP<175)	2012
KW≥130 (HP≥175)	2011

Table 6 to Subpart IIII of Part 60—Optional 3-Mode Test Cycle for Stationary Fire Pump Engines

[As stated in §60.4210(g), manufacturers of fire pump engines may use the following test cycle for testing fire pump engines:]

Mode No.	Engine speed ¹	Torque (percent) ²	Weighting factors
1	Rated	100	0.30
2	Rated	75	0.50
3	Rated	50	0.20

¹Engine speed: ±2 percent of point.

²Torque: NFPA certified nameplate HP for 100 percent point. All points should be ±2 percent of engine percent load value.

Table 7 to Subpart IIII of Part 60—Requirements for Performance Tests for Stationary CI ICE With a Displacement of ≥ 30 Liters per Cylinder

[As stated in §60.4213, you must comply with the following requirements for performance tests for stationary CI ICE with a displacement of ≥ 30 liters per cylinder:]

For each	Complying with the requirement to	You must	Using	According to the following requirements
1. Stationary CI internal combustion engine with a displacement of ≥ 30 liters per cylinder	a. Reduce NO_x emissions by 90 percent or more	i. Select the sampling port location and the number of traverse points;	(1) Method 1 or 1A of 40 CFR part 60, appendix A	(a) Sampling sites must be located at the inlet and outlet of the control device.
		ii. Measure O_2 at the inlet and outlet of the control device;	(2) Method 3, 3A, or 3B of 40 CFR part 60, appendix A	(b) Measurements to determine O_2 concentration must be made at the same time as the measurements for NO_x concentration.
		iii. If necessary, measure moisture content at the inlet and outlet of the control device; and,	(3) Method 4 of 40 CFR part 60, appendix A, Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348–03 (incorporated by reference, see §60.17)	(c) Measurements to determine moisture content must be made at the same time as the measurements for NO_x concentration.
		iv. Measure NO_x at the inlet and outlet of the control device	(4) Method 7E of 40 CFR part 60, appendix A, Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348–03 (incorporated by reference, see §60.17)	(d) NO_x concentration must be at 15 percent O_2 , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.
	b. Limit the concentration of NO_x in the stationary CI internal combustion engine exhaust.	i. Select the sampling port location and the number of traverse points;	(1) Method 1 or 1A of 40 CFR part 60, appendix A	(a) If using a control device, the sampling site must be located at the outlet of the control device.
		ii. Determine the O_2 concentration of the stationary internal combustion engine	(2) Method 3, 3A, or 3B of 40 CFR part 60, appendix A	(b) Measurements to determine O_2 concentration must be made at the same time as

		exhaust at the sampling port location; and,		the measurement for NO _x concentration.
		iii. If necessary, measure moisture content of the stationary internal combustion engine exhaust at the sampling port location; and,	(3) Method 4 of 40 CFR part 60, appendix A, Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348-03 (incorporated by reference, see §60.17)	(c) Measurements to determine moisture content must be made at the same time as the measurement for NO _x concentration.
		iv. Measure NO _x at the exhaust of the stationary internal combustion engine	(4) Method 7E of 40 CFR part 60, appendix A, Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348-03 (incorporated by reference, see §60.17)	(d) NO _x concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.
	c. Reduce PM emissions by 60 percent or more	i. Select the sampling port location and the number of traverse points;	(1) Method 1 or 1A of 40 CFR part 60, appendix A	(a) Sampling sites must be located at the inlet and outlet of the control device.
		ii. Measure O ₂ at the inlet and outlet of the control device;	(2) Method 3, 3A, or 3B of 40 CFR part 60, appendix A	(b) Measurements to determine O ₂ concentration must be made at the same time as the measurements for PM concentration.
		iii. If necessary, measure moisture content at the inlet and outlet of the control device; and	(3) Method 4 of 40 CFR part 60, appendix A	(c) Measurements to determine and moisture content must be made at the same time as the measurements for PM concentration.
		iv. Measure PM at the inlet and outlet of the control device	(4) Method 5 of 40 CFR part 60, appendix A	(d) PM concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.
	d. Limit the concentration of PM in the stationary CI internal combustion engine exhaust	i. Select the sampling port location and the number of traverse points;	(1) Method 1 or 1A of 40 CFR part 60, appendix A	(a) If using a control device, the sampling site must be located at the outlet of the control device.

		ii. Determine the O ₂ concentration of the stationary internal combustion engine exhaust at the sampling port location; and	(2) Method 3, 3A, or 3B of 40 CFR part 60, appendix A	(b) Measurements to determine O ₂ concentration must be made at the same time as the measurements for PM concentration.
		iii. If necessary, measure moisture content of the stationary internal combustion engine exhaust at the sampling port location; and	(3) Method 4 of 40 CFR part 60, appendix A	(c) Measurements to determine moisture content must be made at the same time as the measurements for PM concentration.
		iv. Measure PM at the exhaust of the stationary internal combustion engine	(4) Method 5 of 40 CFR part 60, appendix A	(d) PM concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.

Table 8 to Subpart IIII of Part 60—Applicability of General Provisions to Subpart IIII

[As stated in §60.4218, you must comply with the following applicable General Provisions:]

General Provisions citation	Subject of citation	Applies to subpart	Explanation
§60.1	General applicability of the General Provisions	Yes	
§60.2	Definitions	Yes	Additional terms defined in §60.4219.
§60.3	Units and abbreviations	Yes	
§60.4	Address	Yes	
§60.5	Determination of construction or modification	Yes	
§60.6	Review of plans	Yes	
§60.7	Notification and Recordkeeping	Yes	Except that §60.7 only applies as specified in §60.4214(a).
§60.8	Performance tests	Yes	Except that §60.8 only applies to stationary CI ICE with a displacement of (≥30 liters per cylinder and engines that are not certified.
§60.9	Availability of information	Yes	
§60.10	State Authority	Yes	

§60.11	Compliance with standards and maintenance requirements	No	Requirements are specified in subpart III.
§60.12	Circumvention	Yes	
§60.13	Monitoring requirements	Yes	Except that §60.13 only applies to stationary CI ICE with a displacement of ≥ 30 liters per cylinder.
§60.14	Modification	Yes	
§60.15	Reconstruction	Yes	
§60.16	Priority list	Yes	
§60.17	Incorporations by reference	Yes	
§60.18	General control device requirements	No	
§60.19	General notification and reporting requirements	Yes	

**Indiana Department of Environmental Management
Office of Air Quality**

Attachment F

Title 40: Protection of Environment

PART 63—NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR SOURCE CATEGORIES

Subpart ZZZZ—National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Source: 69 FR 33506, June 15, 2004, unless otherwise noted.

What This Subpart Covers

§ 63.6580 What is the purpose of subpart ZZZZ?

Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations.

[73 FR 3603, Jan. 18, 2008]

§ 63.6585 Am I subject to this subpart?

You are subject to this subpart if you own or operate a stationary RICE at a major or area source of HAP emissions, except if the stationary RICE is being tested at a stationary RICE test cell/stand.

(a) A stationary RICE is any internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work and which is not mobile. Stationary RICE differ from mobile RICE in that a stationary RICE is not a non-road engine as defined at 40 CFR 1068.30, and is not used to propel a motor vehicle or a vehicle used solely for competition.

(b) A major source of HAP emissions is a plant site that emits or has the potential to emit any single HAP at a rate of 10 tons (9.07 megagrams) or more per year or any combination of HAP at a rate of 25 tons (22.68 megagrams) or more per year, except that for oil and gas production facilities, a major source of HAP emissions is determined for each surface site.

(c) An area source of HAP emissions is a source that is not a major source.

(d) If you are an owner or operator of an area source subject to this subpart, your status as an entity subject to a standard or other requirements under this subpart does not subject you to the obligation to obtain a permit under 40 CFR part 70 or 71, provided you are not required to obtain a permit under 40 CFR 70.3(a) or 40 CFR 71.3(a) for a reason other than your status as an area source under this subpart. Notwithstanding the previous sentence, you must continue to comply with the provisions of this subpart as applicable.

(e) If you are an owner or operator of a stationary RICE used for national security purposes, you may be eligible to request an exemption from the requirements of this subpart as described in 40 CFR part 1068, subpart C.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3603, Jan. 18, 2008]

§ 63.6590 What parts of my plant does this subpart cover?

This subpart applies to each affected source.

(a) *Affected source.* An affected source is any existing, new, or reconstructed stationary RICE located at a major or area source of HAP emissions, excluding stationary RICE being tested at a stationary RICE test cell/stand.

(1) *Existing stationary RICE.*

(i) For stationary RICE with a site rating of more than 500 brake horsepower (HP) located at a major source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before December 19, 2002.

(ii) For stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.

(iii) For stationary RICE located at an area source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.

(iv) A change in ownership of an existing stationary RICE does not make that stationary RICE a new or reconstructed stationary RICE.

(2) *New stationary RICE.* (i) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after December 19, 2002.

(ii) A stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

(iii) A stationary RICE located at an area source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

(3) *Reconstructed stationary RICE.* (i) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after December 19, 2002.

(ii) A stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after June 12, 2006.

(iii) A stationary RICE located at an area source of HAP emissions is reconstructed if you meet the definition of reconstruction in §63.2 and reconstruction is commenced on or after June 12, 2006.

(b) *Stationary RICE subject to limited requirements.* (1) An affected source which meets either of the criteria in paragraphs (b)(1)(i) through (ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).

(i) The stationary RICE is a new or reconstructed emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.

(ii) The stationary RICE is a new or reconstructed limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.

(2) A new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis must meet the initial notification requirements of §63.6645(f) and the requirements of §63.6625(c),

63.6650(g), and 63.6655(c). These stationary RICE do not have to meet the emission limitations and operating limitations of this subpart.

(3) The following stationary RICE do not have to meet the requirements of this subpart and of subpart A of this part, including initial notification requirements:

(i) Existing spark ignition 2 stroke lean burn (2SLB) stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(ii) Existing spark ignition 4 stroke lean burn (4SLB) stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(iii) Existing emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(iv) Existing limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(v) Existing stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis;

(vi) Existing residential emergency stationary RICE located at an area source of HAP emissions;

(vii) Existing commercial emergency stationary RICE located at an area source of HAP emissions; or

(viii) Existing institutional emergency stationary RICE located at an area source of HAP emissions.

(c) Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines. No further requirements apply for such engines under this part.

(1) A new or reconstructed stationary RICE located at an area source;

(2) A new or reconstructed 2SLB stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;

(3) A new or reconstructed 4SLB stationary RICE with a site rating of less than 250 brake HP located at a major source of HAP emissions;

(4) A new or reconstructed spark ignition 4 stroke rich burn (4SRB) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;

(5) A new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis;

(6) A new or reconstructed emergency or limited use stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;

(7) A new or reconstructed compression ignition (CI) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9674, Mar. 3, 2010; 75 FR 37733, June 30, 2010; 75 FR 51588, Aug. 20, 2010]

§ 63.6595 When do I have to comply with this subpart?

(a) *Affected Sources.* (1) If you have an existing stationary RICE, excluding existing non-emergency CI stationary RICE, with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than June 15, 2007. If you have an existing non-emergency CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, an existing stationary CI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary CI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than May 3, 2013. If you have an existing stationary SI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary SI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than October 19, 2013.

(2) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions before August 16, 2004, you must comply with the applicable emission limitations and operating limitations in this subpart no later than August 16, 2004.

(3) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions after August 16, 2004, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(4) If you start up your new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions before January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart no later than January 18, 2008.

(5) If you start up your new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions after January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(6) If you start up your new or reconstructed stationary RICE located at an area source of HAP emissions before January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart no later than January 18, 2008.

(7) If you start up your new or reconstructed stationary RICE located at an area source of HAP emissions after January 18, 2008, you must comply with the applicable emission limitations and operating limitations in this subpart upon startup of your affected source.

(b) *Area sources that become major sources.* If you have an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP, the compliance dates in paragraphs (b)(1) and (2) of this section apply to you.

(1) Any stationary RICE for which construction or reconstruction is commenced after the date when your area source becomes a major source of HAP must be in compliance with this subpart upon startup of your affected source.

(2) Any stationary RICE for which construction or reconstruction is commenced before your area source becomes a major source of HAP must be in compliance with the provisions of this subpart that are applicable to RICE located at major sources within 3 years after your area source becomes a major source of HAP.

(c) If you own or operate an affected source, you must meet the applicable notification requirements in §63.6645 and in 40 CFR part 63, subpart A.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9675, Mar. 3, 2010; 75 FR 51589 Aug. 20, 2010]

Emission and Operating Limitations

§ 63.6600 What emission limitations and operating limitations must I meet if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

(a) If you own or operate an existing, new, or reconstructed spark ignition 4SRB stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 1a to this subpart and the operating limitations in Table 1b to this subpart which apply to you.

(b) If you own or operate a new or reconstructed 2SLB stationary RICE with a site rating of more than 500 brake HP located at major source of HAP emissions, a new or reconstructed 4SLB stationary RICE with a site rating of more than 500 brake HP located at major source of HAP emissions, or a new or reconstructed CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2a to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

(c) If you own or operate any of the following stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the emission limitations in Tables 1a, 2a, 2c, and 2d to this subpart or operating limitations in Tables 1b and 2b to this subpart: an existing 2SLB stationary RICE; an existing 4SLB stationary RICE; a stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis; an emergency stationary RICE; or a limited use stationary RICE.

(d) If you own or operate an existing non-emergency stationary CI RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2c to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 9675, Mar. 3, 2010]

§ 63.6601 What emission limitations must I meet if I own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 brake HP and less than or equal to 500 brake HP located at a major source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart. If you own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at major source of HAP emissions manufactured on or after January 1, 2008, you must comply with the emission limitations in Table 2a to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 9675, Mar. 3, 2010; 75 FR 51589 Aug. 20, 2010]

§ 63.6602 What emission limitations must I meet if I own or operate an existing stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions?

If you own or operate an existing stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions, you must comply with the emission limitations in Table 2c to this subpart which apply to you. Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

[75 FR 9675, Mar. 3, 2010, as amended at 75 FR 51589 Aug. 20, 2010]

§ 63.6603 What emission limitations and operating limitations must I meet if I own or operate an existing stationary RICE located at an area source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in §63.6620 and Table 4 to this subpart.

(a) If you own or operate an existing stationary RICE located at an area source of HAP emissions, you must comply with the requirements in Table 2d to this subpart and the operating limitations in Table 2b to this subpart which apply to you.

(b) If you own or operate an existing stationary non-emergency CI RICE greater than 300 HP located at area sources in areas of Alaska not accessible by the Federal Aid Highway System (FAHS) you do not have to meet the numerical CO emission limitations specified in Table 2d to this subpart. Existing stationary non-emergency CI RICE greater than 300 HP located at area sources in areas of Alaska not accessible by the FAHS must meet the management practices that are shown for stationary non-emergency CI RICE less than or equal to 300 HP in Table 2d to this subpart.

[75 FR 9675, Mar. 3, 2010, as amended at 75 FR 51589 Aug. 20, 2010]

§ 63.6604 What fuel requirements must I meet if I own or operate an existing stationary CI RICE?

If you own or operate an existing non-emergency, non-black start CI stationary RICE with a site rating of more than 300 brake HP with a displacement of less than 30 liters per cylinder that uses diesel fuel, you must use diesel fuel that meets the requirements in 40 CFR 80.510(b) for non-road diesel fuel. Existing non-emergency CI stationary RICE located in Guam, American Samoa, the Commonwealth of the Northern Mariana Islands, or at area sources in areas of Alaska not accessible by the FAHS are exempt from the requirements of this section.

[75 FR 9675, Mar. 3, 2010, as amended at 75 FR 51589 Aug. 20, 2010]

General Compliance Requirements

§ 63.6605 What are my general requirements for complying with this subpart?

(a) You must be in compliance with the emission limitations and operating limitations in this subpart that apply to you at all times.

(b) At all times you must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require you to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

[75 FR 9675, Mar. 3, 2010]

Testing and Initial Compliance Requirements

§ 63.6610 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?

If you own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions you are subject to the requirements of this section.

(a) You must conduct the initial performance test or other initial compliance demonstrations in Table 4 to this subpart that apply to you within 180 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions in §63.7(a)(2).

(b) If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004 and own or operate stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must demonstrate initial compliance with either the proposed emission limitations or the promulgated emission limitations no later than February 10, 2005 or no later than 180 days after startup of the source, whichever is later, according to §63.7(a)(2)(ix).

(c) If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004 and own or operate stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, and you chose to comply with the proposed emission limitations when demonstrating initial compliance, you must conduct a second performance test to demonstrate compliance with the promulgated emission limitations by December 13, 2007 or after startup of the source, whichever is later, according to §63.7(a)(2)(ix).

(d) An owner or operator is not required to conduct an initial performance test on units for which a performance test has been previously conducted, but the test must meet all of the conditions described in paragraphs (d)(1) through (5) of this section.

(1) The test must have been conducted using the same methods specified in this subpart, and these methods must have been followed correctly.

(2) The test must not be older than 2 years.

(3) The test must be reviewed and accepted by the Administrator.

(4) Either no process or equipment changes must have been made since the test was performed, or the owner or operator must be able to demonstrate that the results of the performance test, with or without adjustments, reliably demonstrate compliance despite process or equipment changes.

(5) The test must be conducted at any load condition within plus or minus 10 percent of 100 percent load.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3605, Jan. 18, 2008]

§ 63.6611 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a new or reconstructed 4SLB SI stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions?

If you own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions, you must conduct an initial performance test within 240 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions specified in Table 4 to this subpart, as appropriate.

[73 FR 3605, Jan. 18, 2008, as amended at 75 FR 51589 Aug. 20, 2010]

§ 63.6612 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate an existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing stationary RICE located at an area source of HAP emissions?

If you own or operate an existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing stationary RICE located at an area source of HAP emissions you are subject to the requirements of this section.

(a) You must conduct any initial performance test or other initial compliance demonstration according to Tables 4 and 5 to this subpart that apply to you within 180 days after the compliance date that is specified for your stationary RICE in §63.6595 and according to the provisions in §63.7(a)(2).

(b) An owner or operator is not required to conduct an initial performance test on a unit for which a performance test has been previously conducted, but the test must meet all of the conditions described in paragraphs (b)(1) through (4) of this section.

(1) The test must have been conducted using the same methods specified in this subpart, and these methods must have been followed correctly.

(2) The test must not be older than 2 years.

(3) The test must be reviewed and accepted by the Administrator.

(4) Either no process or equipment changes must have been made since the test was performed, or the owner or operator must be able to demonstrate that the results of the performance test, with or without adjustments, reliably demonstrate compliance despite process or equipment changes.

[75 FR 9676, Mar. 3, 2010, as amended at 75 FR 51589 Aug. 20, 2010]

§ 63.6615 When must I conduct subsequent performance tests?

If you must comply with the emission limitations and operating limitations, you must conduct subsequent performance tests as specified in Table 3 of this subpart.

§ 63.6620 What performance tests and other procedures must I use?

(a) You must conduct each performance test in Tables 3 and 4 of this subpart that applies to you.

(b) Each performance test must be conducted according to the requirements that this subpart specifies in Table 4 to this subpart. If you own or operate a non-operational stationary RICE that is subject to performance testing, you do not need to start up the engine solely to conduct the performance test. Owners and operators of a non-operational engine can conduct the performance test when the engine is started up again.

(c) [Reserved]

(d) You must conduct three separate test runs for each performance test required in this section, as specified in §63.7(e)(3). Each test run must last at least 1 hour.

(e)(1) You must use Equation 1 of this section to determine compliance with the percent reduction requirement:

$$\frac{C_i - C_o}{C_i} \times 100 = R \quad (\text{Eq. 1})$$

Where:

C_i = concentration of CO or formaldehyde at the control device inlet,

C_o = concentration of CO or formaldehyde at the control device outlet, and

R = percent reduction of CO or formaldehyde emissions.

(2) You must normalize the carbon monoxide (CO) or formaldehyde concentrations at the inlet and outlet of the control device to a dry basis and to 15 percent oxygen, or an equivalent percent carbon dioxide (CO₂). If pollutant concentrations are to be corrected to 15 percent oxygen and CO₂ concentration is measured in lieu of oxygen concentration measurement, a CO₂ correction factor is needed. Calculate the CO₂ correction factor as described in paragraphs (e)(2)(i) through (iii) of this section.

(i) Calculate the fuel-specific F_o value for the fuel burned during the test using values obtained from Method 19, section 5.2, and the following equation:

$$F_o = \frac{0.209 F_d}{F_c} \quad (\text{Eq. 2})$$

Where:

F_o = Fuel factor based on the ratio of oxygen volume to the ultimate CO₂ volume produced by the fuel at zero percent excess air.

0.209 = Fraction of air that is oxygen, percent/100.

F_d = Ratio of the volume of dry effluent gas to the gross calorific value of the fuel from Method 19, dsm³ / J (dscf/10⁶ Btu).

F_c = Ratio of the volume of CO₂ produced to the gross calorific value of the fuel from Method 19, dsm³ / J (dscf/10⁶ Btu).

(ii) Calculate the CO₂ correction factor for correcting measurement data to 15 percent oxygen, as follows:

$$X_{CO_2} = \frac{5.9}{F_o} \quad (\text{Eq. 3})$$

Where:

X_{CO₂} = CO₂ correction factor, percent.

5.9 = 20.9 percent O₂ - 15 percent O₂, the defined O₂ correction value, percent.

(iii) Calculate the NO_x and SO₂ gas concentrations adjusted to 15 percent O₂ using CO₂ as follows:

$$C_{adj} = C_d \frac{X_{CO_2}}{\%CO_2} \quad (\text{Eq. 4})$$

Where:

%CO₂ = Measured CO₂ concentration measured, dry basis, percent.

(f) If you comply with the emission limitation to reduce CO and you are not using an oxidation catalyst, if you comply with the emission limitation to reduce formaldehyde and you are not using NSCR, or if you comply with the emission limitation to limit the concentration of formaldehyde in the stationary RICE exhaust and you are not using an oxidation catalyst or NSCR, you must petition the Administrator for operating limitations to be established during the initial

performance test and continuously monitored thereafter; or for approval of no operating limitations. You must not conduct the initial performance test until after the petition has been approved by the Administrator.

(g) If you petition the Administrator for approval of operating limitations, your petition must include the information described in paragraphs (g)(1) through (5) of this section.

(1) Identification of the specific parameters you propose to use as operating limitations;

(2) A discussion of the relationship between these parameters and HAP emissions, identifying how HAP emissions change with changes in these parameters, and how limitations on these parameters will serve to limit HAP emissions;

(3) A discussion of how you will establish the upper and/or lower values for these parameters which will establish the limits on these parameters in the operating limitations;

(4) A discussion identifying the methods you will use to measure and the instruments you will use to monitor these parameters, as well as the relative accuracy and precision of these methods and instruments; and

(5) A discussion identifying the frequency and methods for recalibrating the instruments you will use for monitoring these parameters.

(h) If you petition the Administrator for approval of no operating limitations, your petition must include the information described in paragraphs (h)(1) through (7) of this section.

(1) Identification of the parameters associated with operation of the stationary RICE and any emission control device which could change intentionally (e.g., operator adjustment, automatic controller adjustment, etc.) or unintentionally (e.g., wear and tear, error, etc.) on a routine basis or over time;

(2) A discussion of the relationship, if any, between changes in the parameters and changes in HAP emissions;

(3) For the parameters which could change in such a way as to increase HAP emissions, a discussion of whether establishing limitations on the parameters would serve to limit HAP emissions;

(4) For the parameters which could change in such a way as to increase HAP emissions, a discussion of how you could establish upper and/or lower values for the parameters which would establish limits on the parameters in operating limitations;

(5) For the parameters, a discussion identifying the methods you could use to measure them and the instruments you could use to monitor them, as well as the relative accuracy and precision of the methods and instruments;

(6) For the parameters, a discussion identifying the frequency and methods for recalibrating the instruments you could use to monitor them; and

(7) A discussion of why, from your point of view, it is infeasible or unreasonable to adopt the parameters as operating limitations.

(i) The engine percent load during a performance test must be determined by documenting the calculations, assumptions, and measurement devices used to measure or estimate the percent load in a specific application. A written report of the average percent load determination must be included in the notification of compliance status. The following information must be included in the written report: the engine model number, the engine manufacturer, the year of purchase, the manufacturer's site-rated brake horsepower, the ambient temperature, pressure, and humidity during the performance test, and all assumptions that were made to estimate or calculate percent load during the performance test must be clearly explained. If measurement devices such as flow meters, kilowatt meters, beta analyzers, stain gauges, etc. are used, the model number of the measurement device, and an estimate of its accurate in percentage of true value must be provided.

§ 63.6625 What are my monitoring, installation, collection, operation, and maintenance requirements?

(a) If you elect to install a CEMS as specified in Table 5 of this subpart, you must install, operate, and maintain a CEMS to monitor CO and either oxygen or CO₂ at both the inlet and the outlet of the control device according to the requirements in paragraphs (a)(1) through (4) of this section.

(1) Each CEMS must be installed, operated, and maintained according to the applicable performance specifications of 40 CFR part 60, appendix B.

(2) You must conduct an initial performance evaluation and an annual relative accuracy test audit (RATA) of each CEMS according to the requirements in §63.8 and according to the applicable performance specifications of 40 CFR part 60, appendix B as well as daily and periodic data quality checks in accordance with 40 CFR part 60, appendix F, procedure 1.

(3) As specified in §63.8(c)(4)(ii), each CEMS must complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each successive 15-minute period. You must have at least two data points, with each representing a different 15-minute period, to have a valid hour of data.

(4) The CEMS data must be reduced as specified in §63.8(g)(2) and recorded in parts per million or parts per billion (as appropriate for the applicable limitation) at 15 percent oxygen or the equivalent CO₂ concentration.

(b) If you are required to install a continuous parameter monitoring system (CPMS) as specified in Table 5 of this subpart, you must install, operate, and maintain each CPMS according to the requirements in paragraphs (b)(1) through (8) of this section.

(1) The CPMS must complete a minimum of one cycle of operation for each successive 15-minute period. You must have a minimum of four successive cycles of operation to have a valid hour of data.

(2) Except for monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), you must conduct all monitoring in continuous operation at all times that the unit is operating. A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions.

(3) For purposes of calculating data averages, you must not use data recorded during monitoring malfunctions, associated repairs, out of control periods, or required quality assurance or control activities. You must use all the data collected during all other periods in assessing compliance. Any 15-minute period for which the monitoring system is out-of-control and data are not available for required calculations constitutes a deviation from the monitoring requirements.

(4) Determine the 3-hour block average of all recorded readings, except as provided in paragraph (b)(3) of this section.

(5) Record the results of each inspection, calibration, and validation check.

(6) You must develop a site-specific monitoring plan that addresses paragraphs (b)(6)(i) through (vi) of this section.

(i) Installation of the CPMS sampling probe or other interface at the appropriate location to obtain representative measurements;

(ii) Performance and equipment specifications for the sample interface, parametric signal analyzer, and the data collection and reduction systems;

(iii) Performance evaluation procedures and acceptance criteria (e.g., calibrations);

(iv) Ongoing operation and maintenance procedures in accordance with the general requirements of §63.8(c)(1), (c)(3), and (c)(4)(ii);

(v) Ongoing data quality assurance procedures in accordance with the general requirements of §63.8(d); and

(vi) Ongoing recordkeeping and reporting procedures in accordance with the general requirements of §63.10(c), (e)(1), and (e)(2)(i).

(7) You must conduct a performance evaluation of each CPMS in accordance with your site-specific monitoring plan.

(8) You must operate and maintain the CPMS in continuous operation according to the site-specific monitoring plan.

(c) If you are operating a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must monitor and record your fuel usage daily with separate fuel meters to measure the volumetric flow rate of each fuel. In addition, you must operate your stationary RICE in a manner which reasonably minimizes HAP emissions.

(d) If you are operating a new or reconstructed emergency 4SLB stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions, you must install a non-resettable hour meter prior to the startup of the engine.

(e) If you own or operate any of the following stationary RICE, you must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions:

(1) An existing stationary RICE with a site rating of less than 100 HP located at a major source of HAP emissions;

(2) An existing emergency or black start stationary RICE with a site rating of less than or equal to 500 HP located at a major source of HAP emissions;

(3) An existing emergency or black start stationary RICE located at an area source of HAP emissions;

(4) An existing non-emergency, non-black start stationary CI RICE with a site rating less than or equal to 300 HP located at an area source of HAP emissions;

(5) An existing non-emergency, non-black start 2SLB stationary RICE located at an area source of HAP emissions;

(6) An existing non-emergency, non-black start landfill or digester gas stationary RICE located at an area source of HAP emissions;

(7) An existing non-emergency, non-black start 4SLB stationary RICE with a site rating less than or equal to 500 HP located at an area source of HAP emissions;

(8) An existing non-emergency, non-black start 4SRB stationary RICE with a site rating less than or equal to 500 HP located at an area source of HAP emissions;

(9) An existing, non-emergency, non-black start 4SLB stationary RICE with a site rating greater than 500 HP located at an area source of HAP emissions that is operated 24 hours or less per calendar year; and

(10) An existing, non-emergency, non-black start 4SRB stationary RICE with a site rating greater than 500 HP located at an area source of HAP emissions that is operated 24 hours or less per calendar year.

(f) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing emergency stationary RICE located at an area source of HAP emissions, you must install a non-resettable hour meter if one is not already installed.

(g) If you own or operate an existing non-emergency, non-black start CI engine greater than or equal to 300 HP that is not equipped with a closed crankcase ventilation system, you must comply with either paragraph (g)(1) or paragraph (g)(2) of this section. Owners and operators must follow the manufacturer's specified maintenance requirements for operating and maintaining the open or closed crankcase ventilation systems and replacing the crankcase filters, or can request the Administrator to approve different maintenance requirements that are as protective as manufacturer requirements. Existing CI engines located at area sources in areas of Alaska not accessible by the FAHS do not have to meet the requirements of paragraph (g) of this section.

(1) Install a closed crankcase ventilation system that prevents crankcase emissions from being emitted to the atmosphere, or

(2) Install an open crankcase filtration emission control system that reduces emissions from the crankcase by filtering the exhaust stream to remove oil mist, particulates, and metals.

(h) If you operate a new, reconstructed, or existing stationary engine, you must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Tables 1a, 2a, 2c, and 2d to this subpart apply.

(i) If you own or operate a stationary CI engine that is subject to the work, operation or management practices in items 1 or 2 of Table 2c to this subpart or in items 1 or 4 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

(j) If you own or operate a stationary SI engine that is subject to the work, operation or management practices in items 6, 7, or 8 of Table 2c to this subpart or in items 5, 6, 7, 9, or 11 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Acid Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from Total Acid Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

(k) If you have an operating limitation that requires the use of a temperature measurement device, you must meet the requirements in paragraphs (k)(1) through (4) of this section.

(1) Locate the temperature sensor and other necessary equipment in a position that provides a representative temperature.

- (2) Use a temperature sensor with a minimum tolerance of 2.8 degrees Celsius (5 degrees Fahrenheit), or 1.0 percent of the temperature value, whichever is larger, for a noncryogenic temperature range.
- (3) Use a temperature sensor with a minimum tolerance of 2.8 degrees Celsius (5 degrees Fahrenheit), or 2.5 percent of the temperature value, whichever is larger, for a cryogenic temperature range.
- (4) Conduct a temperature measurement device calibration check at least every 3 months.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010; 75 FR 51589, Aug. 20, 2010]

§ 63.6630 How do I demonstrate initial compliance with the emission limitations and operating limitations?

- (a) You must demonstrate initial compliance with each emission and operating limitation that applies to you according to Table 5 of this subpart.
- (b) During the initial performance test, you must establish each operating limitation in Tables 1b and 2b of this subpart that applies to you.
- (c) You must submit the Notification of Compliance Status containing the results of the initial compliance demonstration according to the requirements in §63.6645.

Continuous Compliance Requirements

§ 63.6635 How do I monitor and collect data to demonstrate continuous compliance?

- (a) If you must comply with emission and operating limitations, you must monitor and collect data according to this section.
- (b) Except for monitor malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), you must monitor continuously at all times that the stationary RICE is operating.
- (c) You may not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities in data averages and calculations used to report emission or operating levels. You must, however, use all the valid data collected during all other periods.

§ 63.6640 How do I demonstrate continuous compliance with the emission limitations and operating limitations?

- (a) You must demonstrate continuous compliance with each emission limitation and operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you according to methods specified in Table 6 to this subpart.
- (b) You must report each instance in which you did not meet each emission limitation or operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you. These instances are deviations from the emission and operating limitations in this subpart. These deviations must be reported according to the requirements in §63.6650. If you change your catalyst, you must reestablish the values of the operating parameters measured during the initial performance test. When you reestablish the values of your operating parameters, you must also conduct a performance test to demonstrate that you are meeting the required emission limitation applicable to your stationary RICE.
- (c) [Reserved]

(d) For new, reconstructed, and rebuilt stationary RICE, deviations from the emission or operating limitations that occur during the first 200 hours of operation from engine startup (engine burn-in period) are not violations. Rebuilt stationary RICE means a stationary RICE that has been rebuilt as that term is defined in 40 CFR 94.11(a).

(e) You must also report each instance in which you did not meet the requirements in Table 8 to this subpart that apply to you. If you own or operate a new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing emergency stationary RICE, an existing limited use stationary RICE, or an existing stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart, except for the initial notification requirements: a new or reconstructed stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new or reconstructed emergency stationary RICE, or a new or reconstructed limited use stationary RICE.

(f) Requirements for emergency stationary RICE. (1) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, a new or reconstructed emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that was installed on or after June 12, 2006, or an existing emergency stationary RICE located at an area source of HAP emissions, you must operate the emergency stationary RICE according to the requirements in paragraphs (f)(1)(i) through (iii) of this section. Any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (f)(1)(i) through (iii) of this section, is prohibited. If you do not operate the engine according to the requirements in paragraphs (f)(1)(i) through (iii) of this section, the engine will not be considered an emergency engine under this subpart and will need to meet all requirements for non-emergency engines.

(i) There is no time limit on the use of emergency stationary RICE in emergency situations.

(ii) You may operate your emergency stationary RICE for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Maintenance checks and readiness testing of such units is limited to 100 hours per year. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that Federal, State, or local standards require maintenance and testing of emergency RICE beyond 100 hours per year.

(iii) You may operate your emergency stationary RICE up to 50 hours per year in non-emergency situations, but those 50 hours are counted towards the 100 hours per year provided for maintenance and testing. The 50 hours per year for non-emergency situations cannot be used for peak shaving or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity; except that owners and operators may operate the emergency engine for a maximum of 15 hours per year as part of a demand response program if the regional transmission organization or equivalent balancing authority and transmission operator has determined there are emergency conditions that could lead to a potential electrical blackout, such as unusually low frequency, equipment overload, capacity or energy deficiency, or unacceptable voltage level. The engine may not be operated for more than 30 minutes prior to the time when the emergency condition is expected to occur, and the engine operation must be terminated immediately after the facility is notified that the emergency condition is no longer imminent. The 15 hours per year of demand response operation are counted as part of the 50 hours of operation per year provided for non-emergency situations. The supply of emergency power to another entity or entities pursuant to financial arrangement is not limited by this paragraph (f)(1)(iii), as long as the power provided by the financial arrangement is limited to emergency power.

(2) If you own or operate an emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that was installed prior to June 12, 2006, you must operate the engine according to the conditions described in paragraphs (f)(2)(i) through (iii) of this section. If you do not operate the engine according to the requirements in paragraphs (f)(2)(i) through (iii) of this section, the engine will not be considered an emergency engine under this subpart and will need to meet all requirements for non-emergency engines.

(i) There is no time limit on the use of emergency stationary RICE in emergency situations.

(ii) You may operate your emergency stationary RICE for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by the manufacturer, the vendor, or the insurance company associated with the engine. Required testing of such units should be minimized, but there is no time limit on the use of emergency stationary RICE in emergency situations and for routine testing and maintenance.

(iii) You may operate your emergency stationary RICE for an additional 50 hours per year in non-emergency situations. The 50 hours per year for non-emergency situations cannot be used for peak shaving or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

[69 FR 33506, June 15, 2004, as amended at 71 FR 20467, Apr. 20, 2006; 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010, 75 FR 51591 Aug. 20, 2010]

Notifications, Reports, and Records

§ 63.6645 What notifications must I submit and when?

(a) You must submit all of the notifications in §§63.7(b) and (c), 63.8(e), (f)(4) and (f)(6), 63.9(b) through (e), and (g) and (h) that apply to you by the dates specified if you own or operate any of the following;

(1) An existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions.

(2) An existing stationary RICE located at an area source of HAP emissions.

(3) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions.

(4) A new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 HP located at a major source of HAP emissions.

(5) This requirement does not apply if you own or operate an existing stationary RICE less than 100 HP, an existing stationary emergency RICE, or an existing stationary RICE that is not subject to any numerical emission standards.

(b) As specified in §63.9(b)(2), if you start up your stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions before the effective date of this subpart, you must submit an Initial Notification not later than December 13, 2004.

(c) If you start up your new or reconstructed stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions on or after August 16, 2004, you must submit an Initial Notification not later than 120 days after you become subject to this subpart.

(d) As specified in §63.9(b)(2), if you start up your stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions before the effective date of this subpart and you are required to submit an initial notification, you must submit an Initial Notification not later than July 16, 2008.

(e) If you start up your new or reconstructed stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions on or after March 18, 2008 and you are required to submit an initial notification, you must submit an Initial Notification not later than 120 days after you become subject to this subpart.

(f) If you are required to submit an Initial Notification but are otherwise not affected by the requirements of this subpart, in accordance with §63.6590(b), your notification should include the information in §63.9(b)(2)(i) through (v), and a statement that your stationary RICE has no additional requirements and explain the basis of the exclusion (for example, that it operates exclusively as an emergency stationary RICE if it has a site rating of more than 500 brake HP located at a major source of HAP emissions).

(g) If you are required to conduct a performance test, you must submit a Notification of Intent to conduct a performance test at least 60 days before the performance test is scheduled to begin as required in §63.7(b)(1).

(h) If you are required to conduct a performance test or other initial compliance demonstration as specified in Tables 4 and 5 to this subpart, you must submit a Notification of Compliance Status according to §63.9(h)(2)(ii).

(1) For each initial compliance demonstration required in Table 5 to this subpart that does not include a performance test, you must submit the Notification of Compliance Status before the close of business on the 30th day following the completion of the initial compliance demonstration.

(2) For each initial compliance demonstration required in Table 5 to this subpart that includes a performance test conducted according to the requirements in Table 3 to this subpart, you must submit the Notification of Compliance Status, including the performance test results, before the close of business on the 60th day following the completion of the performance test according to §63.10(d)(2).

[73 FR 3606, Jan. 18, 2008, as amended at 75 FR 9677, Mar. 3, 2010; 75 FR 51591, Aug. 20, 2010]

§ 63.6650 What reports must I submit and when?

(a) You must submit each report in Table 7 of this subpart that applies to you.

(b) Unless the Administrator has approved a different schedule for submission of reports under §63.10(a), you must submit each report by the date in Table 7 of this subpart and according to the requirements in paragraphs (b)(1) through (b)(9) of this section.

(1) For semiannual Compliance reports, the first Compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.6595 and ending on June 30 or December 31, whichever date is the first date following the end of the first calendar half after the compliance date that is specified for your source in §63.6595.

(2) For semiannual Compliance reports, the first Compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date follows the end of the first calendar half after the compliance date that is specified for your affected source in §63.6595.

(3) For semiannual Compliance reports, each subsequent Compliance report must cover the semiannual reporting period from January 1 through June 30 or the semiannual reporting period from July 1 through December 31.

(4) For semiannual Compliance reports, each subsequent Compliance report must be postmarked or delivered no later than July 31 or January 31, whichever date is the first date following the end of the semiannual reporting period.

(5) For each stationary RICE that is subject to permitting regulations pursuant to 40 CFR part 70 or 71, and if the permitting authority has established dates for submitting semiannual reports pursuant to 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6 (a)(3)(iii)(A), you may submit the first and subsequent Compliance reports according to the dates the permitting authority has established instead of according to the dates in paragraphs (b)(1) through (b)(4) of this section.

(6) For annual Compliance reports, the first Compliance report must cover the period beginning on the compliance date that is specified for your affected source in §63.6595 and ending on December 31.

(7) For annual Compliance reports, the first Compliance report must be postmarked or delivered no later than January 31 following the end of the first calendar year after the compliance date that is specified for your affected source in §63.6595.

(8) For annual Compliance reports, each subsequent Compliance report must cover the annual reporting period from January 1 through December 31.

(9) For annual Compliance reports, each subsequent Compliance report must be postmarked or delivered no later than January 31.

(c) The Compliance report must contain the information in paragraphs (c)(1) through (6) of this section.

(1) Company name and address.

(2) Statement by a responsible official, with that official's name, title, and signature, certifying the accuracy of the content of the report.

(3) Date of report and beginning and ending dates of the reporting period.

(4) If you had a malfunction during the reporting period, the compliance report must include the number, duration, and a brief description for each type of malfunction which occurred during the reporting period and which caused or may have caused any applicable emission limitation to be exceeded. The report must also include a description of actions taken by an owner or operator during a malfunction of an affected source to minimize emissions in accordance with §63.6605(b), including actions taken to correct a malfunction.

(5) If there are no deviations from any emission or operating limitations that apply to you, a statement that there were no deviations from the emission or operating limitations during the reporting period.

(6) If there were no periods during which the continuous monitoring system (CMS), including CEMS and CPMS, was out-of-control, as specified in §63.8(c)(7), a statement that there were no periods during which the CMS was out-of-control during the reporting period.

(d) For each deviation from an emission or operating limitation that occurs for a stationary RICE where you are not using a CMS to comply with the emission or operating limitations in this subpart, the Compliance report must contain the information in paragraphs (c)(1) through (4) of this section and the information in paragraphs (d)(1) and (2) of this section.

(1) The total operating time of the stationary RICE at which the deviation occurred during the reporting period.

(2) Information on the number, duration, and cause of deviations (including unknown cause, if applicable), as applicable, and the corrective action taken.

(e) For each deviation from an emission or operating limitation occurring for a stationary RICE where you are using a CMS to comply with the emission and operating limitations in this subpart, you must include information in paragraphs (c)(1) through (4) and (e)(1) through (12) of this section.

(1) The date and time that each malfunction started and stopped.

(2) The date, time, and duration that each CMS was inoperative, except for zero (low-level) and high-level checks.

(3) The date, time, and duration that each CMS was out-of-control, including the information in §63.8(c)(8).

(4) The date and time that each deviation started and stopped, and whether each deviation occurred during a period of malfunction or during another period.

(5) A summary of the total duration of the deviation during the reporting period, and the total duration as a percent of the total source operating time during that reporting period.

(6) A breakdown of the total duration of the deviations during the reporting period into those that are due to control equipment problems, process problems, other known causes, and other unknown causes.

(7) A summary of the total duration of CMS downtime during the reporting period, and the total duration of CMS downtime as a percent of the total operating time of the stationary RICE at which the CMS downtime occurred during that reporting period.

(8) An identification of each parameter and pollutant (CO or formaldehyde) that was monitored at the stationary RICE.

(9) A brief description of the stationary RICE.

(10) A brief description of the CMS.

(11) The date of the latest CMS certification or audit.

(12) A description of any changes in CMS, processes, or controls since the last reporting period.

(f) Each affected source that has obtained a title V operating permit pursuant to 40 CFR part 70 or 71 must report all deviations as defined in this subpart in the semiannual monitoring report required by 40 CFR 70.6 (a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). If an affected source submits a Compliance report pursuant to Table 7 of this subpart along with, or as part of, the semiannual monitoring report required by 40 CFR 70.6(a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A), and the Compliance report includes all required information concerning deviations from any emission or operating limitation in this subpart, submission of the Compliance report shall be deemed to satisfy any obligation to report the same deviations in the semiannual monitoring report. However, submission of a Compliance report shall not otherwise affect any obligation the affected source may have to report deviations from permit requirements to the permit authority.

(g) If you are operating as a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must submit an annual report according to Table 7 of this subpart by the date specified unless the Administrator has approved a different schedule, according to the information described in paragraphs (b)(1) through (b)(5) of this section. You must report the data specified in (g)(1) through (g)(3) of this section.

(1) Fuel flow rate of each fuel and the heating values that were used in your calculations. You must also demonstrate that the percentage of heat input provided by landfill gas or digester gas is equivalent to 10 percent or more of the total fuel consumption on an annual basis.

(2) The operating limits provided in your federally enforceable permit, and any deviations from these limits.

(3) Any problems or errors suspected with the meters.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9677, Mar. 3, 2010]

§ 63.6655 What records must I keep?

(a) If you must comply with the emission and operating limitations, you must keep the records described in paragraphs (a)(1) through (a)(5), (b)(1) through (b)(3) and (c) of this section.

(1) A copy of each notification and report that you submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status that you submitted, according to the requirement in §63.10(b)(2)(xiv).

(2) Records of the occurrence and duration of each malfunction of operation (*i.e.*, process equipment) or the air pollution control and monitoring equipment.

(3) Records of performance tests and performance evaluations as required in §63.10(b)(2)(viii).

(4) Records of all required maintenance performed on the air pollution control and monitoring equipment.

(5) Records of actions taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

(b) For each CEMS or CPMS, you must keep the records listed in paragraphs (b)(1) through (3) of this section.

(1) Records described in §63.10(b)(2)(vi) through (xi).

(2) Previous (*i.e.*, superseded) versions of the performance evaluation plan as required in §63.8(d)(3).

(3) Requests for alternatives to the relative accuracy test for CEMS or CPMS as required in §63.8(f)(6)(i), if applicable.

(c) If you are operating a new or reconstructed stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, you must keep the records of your daily fuel usage monitors.

(d) You must keep the records required in Table 6 of this subpart to show continuous compliance with each emission or operating limitation that applies to you.

(e) You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate any of the following stationary RICE;

(1) An existing stationary RICE with a site rating of less than 100 brake HP located at a major source of HAP emissions.

(2) An existing stationary emergency RICE.

(3) An existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart.

(f) If you own or operate any of the stationary RICE in paragraphs (f)(1) or (2) of this section, you must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. If the engines are used for demand response operation, the owner or operator must keep records of the notification of the emergency situation, and the time the engine was operated as part of demand response.

(1) An existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions that does not meet the standards applicable to non-emergency engines.

(2) An existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines.

[69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010; 75 FR 51592, Aug. 20, 2010]

§ 63.6660 In what form and how long must I keep my records?

(a) Your records must be in a form suitable and readily available for expeditious review according to §63.10(b)(1).

(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.

(c) You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1).

[69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010]

Other Requirements and Information

§ 63.6665 What parts of the General Provisions apply to me?

Table 8 to this subpart shows which parts of the General Provisions in §§63.1 through 63.15 apply to you. If you own or operate a new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with any of the requirements of the General Provisions specified in Table 8: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing stationary RICE that combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, an existing emergency stationary RICE, or an existing limited use stationary RICE. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in the General Provisions specified in Table 8 except for the initial notification requirements: A new stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new emergency stationary RICE, or a new limited use stationary RICE.

[75 FR 9678, Mar. 3, 2010]

§ 63.6670 Who implements and enforces this subpart?

(a) This subpart is implemented and enforced by the U.S. EPA, or a delegated authority such as your State, local, or tribal agency. If the U.S. EPA Administrator has delegated authority to your State, local, or tribal agency, then that agency (as well as the U.S. EPA) has the authority to implement and enforce this subpart. You should contact your U.S. EPA Regional Office to find out whether this subpart is delegated to your State, local, or tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or tribal agency under 40 CFR part 63, subpart E, the authorities contained in paragraph (c) of this section are retained by the Administrator of the U.S. EPA and are not transferred to the State, local, or tribal agency.

(c) The authorities that will not be delegated to State, local, or tribal agencies are:

- (1) Approval of alternatives to the non-opacity emission limitations and operating limitations in §63.6600 under §63.6(g).
- (2) Approval of major alternatives to test methods under §63.7(e)(2)(ii) and (f) and as defined in §63.90.
- (3) Approval of major alternatives to monitoring under §63.8(f) and as defined in §63.90.
- (4) Approval of major alternatives to recordkeeping and reporting under §63.10(f) and as defined in §63.90.
- (5) Approval of a performance test which was conducted prior to the effective date of the rule, as specified in §63.6610(b).

§ 63.6675 What definitions apply to this subpart?

Terms used in this subpart are defined in the Clean Air Act (CAA); in 40 CFR 63.2, the General Provisions of this part; and in this section as follows:

Area source means any stationary source of HAP that is not a major source as defined in part 63.

Associated equipment as used in this subpart and as referred to in section 112(n)(4) of the CAA, means equipment associated with an oil or natural gas exploration or production well, and includes all equipment from the well bore to the point of custody transfer, except glycol dehydration units, storage vessels with potential for flash emissions, combustion turbines, and stationary RICE.

Black start engine means an engine whose only purpose is to start up a combustion turbine.

CAA means the Clean Air Act (42 U.S.C. 7401 *et seq.*, as amended by Public Law 101-549, 104 Stat. 2399).

Commercial emergency stationary RICE means an emergency stationary RICE used in commercial establishments such as office buildings, hotels, stores, telecommunications facilities, restaurants, financial institutions such as banks, doctor's offices, and sports and performing arts facilities.

Compression ignition means relating to a type of stationary internal combustion engine that is not a spark ignition engine.

Custody transfer means the transfer of hydrocarbon liquids or natural gas: After processing and/or treatment in the producing operations, or from storage vessels or automatic transfer facilities or other such equipment, including product loading racks, to pipelines or any other forms of transportation. For the purposes of this subpart, the point at which such liquids or natural gas enters a natural gas processing plant is a point of custody transfer.

Deviation means any instance in which an affected source subject to this subpart, or an owner or operator of such a source:

- (1) Fails to meet any requirement or obligation established by this subpart, including but not limited to any emission limitation or operating limitation;
- (2) Fails to meet any term or condition that is adopted to implement an applicable requirement in this subpart and that is included in the operating permit for any affected source required to obtain such a permit; or
- (3) Fails to meet any emission limitation or operating limitation in this subpart during malfunction, regardless or whether or not such failure is permitted by this subpart.
- (4) Fails to satisfy the general duty to minimize emissions established by §63.6(e)(1)(i).

Diesel engine means any stationary RICE in which a high boiling point liquid fuel injected into the combustion chamber ignites when the air charge has been compressed to a temperature sufficiently high for auto-ignition. This process is also known as compression ignition.

Diesel fuel means any liquid obtained from the distillation of petroleum with a boiling point of approximately 150 to 360 degrees Celsius. One commonly used form is fuel oil number 2. Diesel fuel also includes any non-distillate fuel with comparable physical and chemical properties (e.g. biodiesel) that is suitable for use in compression ignition engines.

Digester gas means any gaseous by-product of wastewater treatment typically formed through the anaerobic decomposition of organic waste materials and composed principally of methane and CO₂.

Dual-fuel engine means any stationary RICE in which a liquid fuel (typically diesel fuel) is used for compression ignition and gaseous fuel (typically natural gas) is used as the primary fuel.

Emergency stationary RICE means any stationary internal combustion engine whose operation is limited to emergency situations and required testing and maintenance. Examples include stationary RICE used to produce power for critical networks or equipment (including power supplied to portions of a facility) when electric power from the local utility (or the normal power source, if the facility runs on its own power production) is interrupted, or stationary RICE used to pump water in the case of fire or flood, etc. Stationary RICE used for peak shaving are not

considered emergency stationary RICE. Stationary RICE used to supply power to an electric grid or that supply non-emergency power as part of a financial arrangement with another entity are not considered to be emergency engines, except as permitted under §63.6640(f). All emergency stationary RICE must comply with the requirements specified in §63.6640(f) in order to be considered emergency stationary RICE. If the engine does not comply with the requirements specified in §63.6640(f), then it is not considered to be an emergency stationary RICE under this subpart.

Engine startup means the time from initial start until applied load and engine and associated equipment reaches steady state or normal operation. For stationary engine with catalytic controls, engine startup means the time from initial start until applied load and engine and associated equipment, including the catalyst, reaches steady state or normal operation.

Four-stroke engine means any type of engine which completes the power cycle in two crankshaft revolutions, with intake and compression strokes in the first revolution and power and exhaust strokes in the second revolution.

Gaseous fuel means a material used for combustion which is in the gaseous state at standard atmospheric temperature and pressure conditions.

Gasoline means any fuel sold in any State for use in motor vehicles and motor vehicle engines, or nonroad or stationary engines, and commonly or commercially known or sold as gasoline.

Glycol dehydration unit means a device in which a liquid glycol (including, but not limited to, ethylene glycol, diethylene glycol, or triethylene glycol) absorbent directly contacts a natural gas stream and absorbs water in a contact tower or absorption column (absorber). The glycol contacts and absorbs water vapor and other gas stream constituents from the natural gas and becomes "rich" glycol. This glycol is then regenerated in the glycol dehydration unit reboiler. The "lean" glycol is then recycled.

Hazardous air pollutants (HAP) means any air pollutants listed in or pursuant to section 112(b) of the CAA.

Institutional emergency stationary RICE means an emergency stationary RICE used in institutional establishments such as medical centers, nursing homes, research centers, institutions of higher education, correctional facilities, elementary and secondary schools, libraries, religious establishments, police stations, and fire stations.

ISO standard day conditions means 288 degrees Kelvin (15 degrees Celsius), 60 percent relative humidity and 101.3 kilopascals pressure.

Landfill gas means a gaseous by-product of the land application of municipal refuse typically formed through the anaerobic decomposition of waste materials and composed principally of methane and CO₂.

Lean burn engine means any two-stroke or four-stroke spark ignited engine that does not meet the definition of a rich burn engine.

Limited use stationary RICE means any stationary RICE that operates less than 100 hours per year.

Liquefied petroleum gas means any liquefied hydrocarbon gas obtained as a by-product in petroleum refining of natural gas production.

Liquid fuel means any fuel in liquid form at standard temperature and pressure, including but not limited to diesel, residual/crude oil, kerosene/naphtha (jet fuel), and gasoline.

Major Source, as used in this subpart, shall have the same meaning as in §63.2, except that:

(1) Emissions from any oil or gas exploration or production well (with its associated equipment (as defined in this section)) and emissions from any pipeline compressor station or pump station shall not be aggregated with emissions from other similar units, to determine whether such emission points or stations are major sources, even when emission points are in a contiguous area or under common control;

(2) For oil and gas production facilities, emissions from processes, operations, or equipment that are not part of the same oil and gas production facility, as defined in §63.1271 of subpart HHH of this part, shall not be aggregated;

(3) For production field facilities, only HAP emissions from glycol dehydration units, storage vessel with the potential for flash emissions, combustion turbines and reciprocating internal combustion engines shall be aggregated for a major source determination; and

(4) Emissions from processes, operations, and equipment that are not part of the same natural gas transmission and storage facility, as defined in §63.1271 of subpart HHH of this part, shall not be aggregated.

Malfunction means any sudden, infrequent, and not reasonably preventable failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner which causes, or has the potential to cause, the emission limitations in an applicable standard to be exceeded. Failures that are caused in part by poor maintenance or careless operation are not malfunctions.

Natural gas means a naturally occurring mixture of hydrocarbon and non-hydrocarbon gases found in geologic formations beneath the Earth's surface, of which the principal constituent is methane. Natural gas may be field or pipeline quality.

Non-selective catalytic reduction (NSCR) means an add-on catalytic nitrogen oxides (NO_x) control device for rich burn engines that, in a two-step reaction, promotes the conversion of excess oxygen, NO_x, CO, and volatile organic compounds (VOC) into CO₂, nitrogen, and water.

Oil and gas production facility as used in this subpart means any grouping of equipment where hydrocarbon liquids are processed, upgraded (*i.e.*, remove impurities or other constituents to meet contract specifications), or stored prior to the point of custody transfer; or where natural gas is processed, upgraded, or stored prior to entering the natural gas transmission and storage source category. For purposes of a major source determination, facility (including a building, structure, or installation) means oil and natural gas production and processing equipment that is located within the boundaries of an individual surface site as defined in this section. Equipment that is part of a facility will typically be located within close proximity to other equipment located at the same facility. Pieces of production equipment or groupings of equipment located on different oil and gas leases, mineral fee tracts, lease tracts, subsurface or surface unit areas, surface fee tracts, surface lease tracts, or separate surface sites, whether or not connected by a road, waterway, power line or pipeline, shall not be considered part of the same facility. Examples of facilities in the oil and natural gas production source category include, but are not limited to, well sites, satellite tank batteries, central tank batteries, a compressor station that transports natural gas to a natural gas processing plant, and natural gas processing plants.

Oxidation catalyst means an add-on catalytic control device that controls CO and VOC by oxidation.

Peaking unit or engine means any standby engine intended for use during periods of high demand that are not emergencies.

Percent load means the fractional power of an engine compared to its maximum manufacturer's design capacity at engine site conditions. Percent load may range between 0 percent to above 100 percent.

Potential to emit means the maximum capacity of a stationary source to emit a pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the stationary source to emit a pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is federally enforceable. For oil and natural gas production facilities subject to subpart HH of this part, the potential to emit provisions in §63.760(a) may be used. For natural gas transmission and storage facilities subject to subpart HHH of this part, the maximum annual facility gas throughput for storage facilities may be determined according to §63.1270(a)(1) and the maximum annual throughput for transmission facilities may be determined according to §63.1270(a)(2).

Production field facility means those oil and gas production facilities located prior to the point of custody transfer.

Production well means any hole drilled in the earth from which crude oil, condensate, or field natural gas is extracted.

Propane means a colorless gas derived from petroleum and natural gas, with the molecular structure C_3H_8 .

Residential emergency stationary RICE means an emergency stationary RICE used in residential establishments such as homes or apartment buildings.

Responsible official means responsible official as defined in 40 CFR 70.2.

Rich burn engine means any four-stroke spark ignited engine where the manufacturer's recommended operating air/fuel ratio divided by the stoichiometric air/fuel ratio at full load conditions is less than or equal to 1.1. Engines originally manufactured as rich burn engines, but modified prior to December 19, 2002 with passive emission control technology for NO_x (such as pre-combustion chambers) will be considered lean burn engines. Also, existing engines where there are no manufacturer's recommendations regarding air/fuel ratio will be considered a rich burn engine if the excess oxygen content of the exhaust at full load conditions is less than or equal to 2 percent.

Site-rated HP means the maximum manufacturer's design capacity at engine site conditions.

Spark ignition means relating to either: A gasoline-fueled engine; or any other type of engine a spark plug (or other sparking device) and with operating characteristics significantly similar to the theoretical Otto combustion cycle. Spark ignition engines usually use a throttle to regulate intake air flow to control power during normal operation. Dual-fuel engines in which a liquid fuel (typically diesel fuel) is used for CI and gaseous fuel (typically natural gas) is used as the primary fuel at an annual average ratio of less than 2 parts diesel fuel to 100 parts total fuel on an energy equivalent basis are spark ignition engines.

Stationary reciprocating internal combustion engine (RICE) means any reciprocating internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work and which is not mobile. Stationary RICE differ from mobile RICE in that a stationary RICE is not a non-road engine as defined at 40 CFR 1068.30, and is not used to propel a motor vehicle or a vehicle used solely for competition.

Stationary RICE test cell/stand means an engine test cell/stand, as defined in subpart P of this part, that tests stationary RICE.

Stoichiometric means the theoretical air-to-fuel ratio required for complete combustion.

Storage vessel with the potential for flash emissions means any storage vessel that contains a hydrocarbon liquid with a stock tank gas-to-oil ratio equal to or greater than 0.31 cubic meters per liter and an American Petroleum Institute gravity equal to or greater than 40 degrees and an actual annual average hydrocarbon liquid throughput equal to or greater than 79,500 liters per day. Flash emissions occur when dissolved hydrocarbons in the fluid evolve from solution when the fluid pressure is reduced.

Subpart means 40 CFR part 63, subpart ZZZZ.

Surface site means any combination of one or more graded pad sites, gravel pad sites, foundations, platforms, or the immediate physical location upon which equipment is physically affixed.

Two-stroke engine means a type of engine which completes the power cycle in single crankshaft revolution by combining the intake and compression operations into one stroke and the power and exhaust operations into a second stroke. This system requires auxiliary scavenging and inherently runs lean of stoichiometric.

[69 FR 33506, June 15, 2004, as amended at 71 FR 20467, Apr. 20, 2006; 73 FR 3607, Jan. 18, 2008; 75 FR 9679, Mar. 3, 2010; 75 FR 51592, Aug. 20, 2010]

Table 1a to Subpart ZZZZ of Part 63. Emission Limitations for Existing, New, and Reconstructed Spark Ignition, 4SRB Stationary RICE >500 HP Located at a Major Source of HAP Emissions

As stated in §§63.6600 and 63.6640, you must comply with the following emission limitations at 100 percent load plus or minus 10 percent for existing, new and reconstructed 4SRB stationary RICE >500 HP located at a major source of HAP emissions:

For each . . .	You must meet the following emission limitation, except during periods of startup . . .	During periods of startup you must . . .
1. 4SRB stationary RICE	a. Reduce formaldehyde emissions by 76 percent or more. If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004, you may reduce formaldehyde emissions by 75 percent or more until June 15, 2007 or	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply. ¹
	b. Limit the concentration of formaldehyde in the stationary RICE exhaust to 350 ppbvd or less at 15 percent O ₂	

¹Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.6(g) for alternative work practices.

[75 FR 9679, Mar. 3, 2010, as amended at 75 FR 51592, Aug. 20, 2010]

Table 1b to Subpart ZZZZ of Part 63. Operating Limitations for Existing, New, and Reconstructed Spark Ignition 4SRB Stationary RICE >500 HP Located at a Major Source of HAP Emissions and Existing Spark Ignition 4SRB Stationary RICE >500 HP Located at an Area Source of HAP Emissions

As stated in §§63.6600, 63.6630 and 63.6640, you must comply with the following operating limitations for existing, new and reconstructed 4SRB stationary RICE >500 HP located at a major source of HAP emissions and existing 4SRB stationary RICE >500 HP located at an area source of HAP emissions that operate more than 24 hours per calendar year:

For each . . .	You must meet the following operating limitation . . .
1. 4SRB stationary RICE complying with the requirement to reduce formaldehyde emissions by 76 percent or more (or by 75 percent or more, if applicable) and using NSCR; or	a. maintain your catalyst so that the pressure drop across the catalyst does not change by more than 2 inches of water at 100 percent load plus or minus; 10 percent from the pressure drop across the catalyst measured during the initial performance test and
4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 350 ppbvd or less at 15 percent O ₂ and using NSCR; or	b. maintain the temperature of your stationary RICE exhaust so the catalyst inlet temperature is greater than or equal to 750 °F and less than or equal to 1250 °F.
4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 2.7 ppmvd or less at 15 percent O ₂ and using NSCR.	
2. 4SRB stationary RICE complying with the requirement to reduce formaldehyde emissions by 76 percent or more (or by 75 percent or more, if applicable) and not using NSCR; or	Comply with any operating limitations approved by the Administrator.
4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 350 ppbvd or less at 15 percent O ₂ and not using NSCR; or	
4SRB stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust to 2.7 ppmvd or less at 15 percent O ₂ and using NSCR.	

[73 FR 3607, Jan. 18, 2008, as amended at 75 FR 51592 Aug. 20, 2010]

Table 2a to Subpart ZZZZ of Part 63—Emission Limitations for New and Reconstructed 2SLB and Compression Ignition Stationary RICE >500 HP and New and Reconstructed 4SLB Stationary RICE ≥250 HP Located at a Major Source of HAP Emissions

As stated in §§63.6600 and 63.6640, you must comply with the following emission limitations for new and reconstructed lean burn and new and reconstructed compression ignition stationary RICE at 100 percent load plus or minus 10 percent:

For each . . .	You must meet the following emission limitation, except during periods of startup . . .	During periods of startup you must . . .
1. 2SLB stationary RICE	a. Reduce CO emissions by 58 percent or more; or b. Limit concentration of formaldehyde in the stationary RICE exhaust to 12 ppmvd or less at 15 percent O ₂ . If you commenced construction or reconstruction between December 19, 2002 and June 15, 2004, you may limit concentration of formaldehyde to 17 ppmvd or less at 15 percent O ₂ until June 15, 2007	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply. ¹
2. 4SLB stationary RICE	a. Reduce CO emissions by 93 percent or more; or b. Limit concentration of formaldehyde in the stationary RICE exhaust to 14 ppmvd or less at 15 percent O ₂	
3. CI stationary RICE	a. Reduce CO emissions by 70 percent or more; or b. Limit concentration of formaldehyde in the stationary RICE exhaust to 580 ppbvd or less at 15 percent O ₂	

¹Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.6(g) for alternative work practices.

[75 FR 9680, Mar. 3, 2010]

Table 2b to Subpart ZZZZ of Part 63. Operating Limitations for New and Reconstructed 2SLB and Compression Ignition Stationary RICE >500 HP Located at a Major Source of HAP Emissions, New and Reconstructed 4SLB Stationary RICE ≥250 HP Located at a Major Source of HAP Emissions, Existing Compression Ignition Stationary RICE >500 HP, and Existing 4SLB Stationary RICE >500 HP Located at an Area Source of HAP Emissions

As stated in §§63.6600, 63.6601, 63.6630, and 63.6640, you must comply with the following operating limitations for new and reconstructed 2SLB and compression ignition stationary RICE located at a major source of HAP emissions; new and reconstructed 4SLB stationary RICE ≥250 HP located at a major source of HAP emissions; existing compression ignition stationary RICE >500 HP; and existing 4SLB stationary RICE >500 HP located at an area source of HAP emissions that operate more than 24 hours per calendar year:

For each . . .	You must meet the following operating limitation . . .
1. 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to reduce CO emissions and using an oxidation catalyst; or 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust and using an oxidation catalyst; or 4SLB stationary RICE and	a. maintain your catalyst so that the pressure drop across the catalyst does not change by more than 2 inches of water at 100 percent load plus or minus 10 percent from the pressure drop across the catalyst that was measured during the initial

CI stationary RICE complying with the requirement to limit the concentration of CO in the stationary RICE exhaust and using an oxidation catalyst	performance test; and b. maintain the temperature of your stationary RICE exhaust so that the catalyst inlet temperature is greater than or equal to 450 °F and less than or equal to 1350 °F. ¹
2. 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to reduce CO emissions and not using an oxidation catalyst; or 2SLB and 4SLB stationary RICE and CI stationary RICE complying with the requirement to limit the concentration of formaldehyde in the stationary RICE exhaust and not using an oxidation catalyst; or 4SLB stationary RICE and CI stationary RICE complying with the requirement to limit the concentration of CO in the stationary RICE exhaust and not using an oxidation catalyst	Comply with any operating limitations approved by the Administrator.

¹Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.8(g) for a different temperature range.

[75 FR 9680, Mar. 3, 2010, as amended at 75 FR 51593, Aug. 20, 2010]

Table 2c to Subpart ZZZZ of Part 63. Requirements for Existing Compression Ignition Stationary RICE Located at a Major Source of HAP Emissions and Existing Spark Ignition Stationary RICE ≤500 HP Located at a Major Source of HAP Emissions

As stated in §§63.6600, 63.6602, and 63.6640, you must comply with the following requirements for existing compression ignition stationary RICE located at a major source of HAP emissions and existing spark ignition stationary RICE ≤500 HP located at a major source of HAP emissions:

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
1. Emergency stationary CI RICE and black start stationary CI RICE. ¹	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ² b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary. ³	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply. ³
2. Non-Emergency, non-black start stationary CI RICE <100 HP	a. Change oil and filter every 1,000 hours of operation or annually, whichever comes first; ²	
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary. ³	
3. Non-Emergency, non-black start CI stationary RICE 100≤HP≤300 HP	Limit concentration of CO in the stationary RICE exhaust to 230 ppmvd or less at 15 percent O ₂	

4. Non-Emergency, non-black start CI stationary RICE 300<HP≤500	a. Limit concentration of CO in the stationary RICE exhaust to 49 ppmvd or less at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
5. Non-Emergency, non-black start stationary CI RICE >500 HP	a. Limit concentration of CO in the stationary RICE exhaust to 23 ppmvd or less at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
6. Emergency stationary SI RICE and black start stationary SI RICE. ¹	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ²	
	b. Inspect spark plugs every 1,000 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary. ³	
7. Non-Emergency, non-black start stationary SI RICE <100 HP that are not 2SLB stationary RICE	a. Change oil and filter every 1,440 hours of operation or annually, whichever comes first; ²	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 1,440 hours of operation or annually, whichever comes first, and replace as necessary. ³	
8. Non-Emergency, non-black start 2SLB stationary SI RICE <100 HP	a. Change oil and filter every 4,320 hours of operation or annually, whichever comes first; ²	
	b. Inspect spark plugs every 4,320 hours of operation or annually, whichever comes first;	
	c. Inspect all hoses and belts every 4,320 hours of operation or annually, whichever comes first, and replace as necessary. ³	
9. Non-emergency, non-black start 2SLB stationary RICE 100≤HP≤500	Limit concentration of CO in the stationary RICE exhaust to 225 ppmvd or less at 15 percent O ₂	
10. Non-emergency, non-black start 4SLB stationary RICE 100≤HP≤500	Limit concentration of CO in the stationary RICE exhaust to 47 ppmvd or less at 15 percent O ₂	
11. Non-emergency, non-black start 4SRB stationary RICE 100≤HP≤500	Limit concentration of formaldehyde in the stationary RICE exhaust to 10.3 ppmvd or less at 15	

	percent O ₂	
12. Non-emergency, non-black start landfill or digester gas-fired stationary RICE 100≤HP≤500	Limit concentration of CO in the stationary RICE exhaust to 177 ppmvd or less at 15 percent O ₂	

¹If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the work practice requirements on the schedule required in Table 2c of this subpart, or if performing the work practice on the required schedule would otherwise pose an unacceptable risk under Federal, State, or local law, the work practice can be delayed until the emergency is over or the unacceptable risk under Federal, State, or local law has abated. The work practice should be performed as soon as practicable after the emergency has ended or the unacceptable risk under Federal, State, or local law has abated. Sources must report any failure to perform the work practice on the schedule required and the Federal, State or local law under which the risk was deemed unacceptable.

²Sources have the option to utilize an oil analysis program as described in §63.6625(i) in order to extend the specified oil change requirement in Table 2c of this subpart.

³Sources can petition the Administrator pursuant to the requirements of 40 CFR 63.6(g) for alternative work practices.

[75 FR 9681, Mar. 3, 2010, as amended at 75 FR 51593, Aug. 20, 2010]

Table 2d to Subpart ZZZZ of Part 63. Requirements for Existing Stationary RICE Located at Area Sources of HAP Emissions

As stated in §§63.6603 and 63.6640, you must comply with the following requirements for existing stationary RICE located at area sources of HAP emissions:

For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
1. Non-Emergency, non-black start CI stationary RICE ≤300 HP	a. Change oil and filter every 1,000 hours of operation or annually, whichever comes first; ¹	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply.
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	
2. Non-Emergency, non-black start CI stationary RICE 300<HP≤500	a. Limit concentration of CO in the stationary RICE exhaust to 49 ppmvd at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
3. Non-Emergency, non-black start CI stationary	a. Limit concentration of CO	

RICE >500 HP	in the stationary RICE exhaust to 23 ppmvd at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 70 percent or more.	
4. Emergency stationary CI RICE and black start stationary CI RICE. ²	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ¹	
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	
5. Emergency stationary SI RICE; black start stationary SI RICE; non-emergency, non-black start 4SLB stationary RICE >500 HP that operate 24 hours or less per calendar year; non-emergency, non-black start 4SRB stationary RICE >500 HP that operate 24 hours or less per calendar year. ²	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ¹ b. Inspect spark plugs every 1,000 hours of operation or annually, whichever comes first; and c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	
6. Non-emergency, non-black start 2SLB stationary RICE	a. Change oil and filter every 4,320 hours of operation or annually, whichever comes first; ¹	
	b. Inspect spark plugs every 4,320 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 4,320 hours of operation or annually, whichever comes first, and replace as necessary.	
7. Non-emergency, non-black start 4SLB stationary RICE ≤500 HP	a. Change oil and filter every 1,440 hours of operation or annually, whichever comes first; ¹	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts	

	every 1,440 hours of operation or annually, whichever comes first, and replace as necessary.	
8. Non-emergency, non-black start 4SLB stationary RICE >500 HP	a. Limit concentration of CO in the stationary RICE exhaust to 47 ppmvd at 15 percent O ₂ ; or	
	b. Reduce CO emissions by 93 percent or more.	
9. Non-emergency, non-black start 4SRB stationary RICE ≤500 HP	a. Change oil and filter every 1,440 hours of operation or annually, whichever comes first; ¹	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 1,440 hours of operation or annually, whichever comes first, and replace as necessary.	
10. Non-emergency, non-black start 4SRB stationary RICE >500 HP	a. Limit concentration of formaldehyde in the stationary RICE exhaust to 2.7 ppmvd at 15 percent O ₂ ; or	
	b. Reduce formaldehyde emissions by 76 percent or more.	
11. Non-emergency, non-black start landfill or digester gas-fired stationary RICE	a. Change oil and filter every 1,440 hours of operation or annually, whichever comes first; ¹	
	b. Inspect spark plugs every 1,440 hours of operation or annually, whichever comes first; and	
	c. Inspect all hoses and belts every 1,440 hours of operation or annually, whichever comes first, and replace as necessary.	

¹Sources have the option to utilize an oil analysis program as described in §63.6625(i) in order to extend the specified oil change requirement in Table 2d of this subpart.

²If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the management practice requirements on the schedule required in Table 2d of this subpart, or if performing the management practice on the required schedule would otherwise pose an unacceptable risk under Federal, State, or local law, the management practice can be delayed until the emergency is over or the unacceptable risk under Federal, State, or local law has abated. The management practice should be performed as soon as practicable after

the emergency has ended or the unacceptable risk under Federal, State, or local law has abated. Sources must report any failure to perform the management practice on the schedule required and the Federal, State or local law under which the risk was deemed unacceptable.

[75 FR 9681, Mar. 3, 2010, as amended at 75 FR 51595, Aug. 20, 2010]

Table 3 to Subpart ZZZZ of Part 63. Subsequent Performance Tests

As stated in §§63.6615 and 63.6620, you must comply with the following subsequent performance test requirements:

For each . . .	Complying with the requirement to . . .	You must . . .
1. New or reconstructed 2SLB stationary RICE with a brake horsepower >500 located at major sources; new or reconstructed 4SLB stationary RICE with a brake horsepower ≥250 located at major sources; and new or reconstructed CI stationary RICE with a brake horsepower >500 located at major sources	Reduce CO emissions and not using a CEMS	Conduct subsequent performance tests semiannually. ¹
2. 4SRB stationary RICE with a brake horsepower ≥5,000 located at major sources	Reduce formaldehyde emissions	Conduct subsequent performance tests semiannually. ¹
3. Stationary RICE with a brake horsepower >500 located at major sources and new or reconstructed 4SLB stationary RICE with a brake horsepower 250≤HP≤500 located at major sources	Limit the concentration of formaldehyde in the stationary RICE exhaust	Conduct subsequent performance tests semiannually. ¹
4. Existing non-emergency, non-black start CI stationary RICE with a brake horsepower >500 that are not limited use stationary RICE; existing non-emergency, non-black start 4SLB and 4SRB stationary RICE located at an area source of HAP emissions with a brake horsepower >500 that are operated more than 24 hours per calendar year that are not limited use stationary RICE	Limit or reduce CO or formaldehyde emissions	Conduct subsequent performance tests every 8,760 hrs. or 3 years, whichever comes first.
5. Existing non-emergency, non-black start CI stationary RICE with a brake horsepower >500 that are limited use stationary RICE; existing non-emergency, non-black start 4SLB and 4SRB stationary RICE located at an area source of HAP emissions with a brake horsepower >500 that are operated more than 24 hours per calendar year and are limited use stationary RICE	Limit or reduce CO or formaldehyde emissions	Conduct subsequent performance tests every 8,760 hrs. or 5 years, whichever comes first.

¹After you have demonstrated compliance for two consecutive tests, you may reduce the frequency of subsequent performance tests to annually. If the results of any subsequent annual performance test indicate the stationary RICE is not in compliance with the CO or formaldehyde emission limitation, or you deviate from any of your operating limitations, you must resume semiannual performance tests.

[75 FR 9682, Mar. 3, 2010, as amended at 75 FR 51596, Aug. 20, 2010]

Table 4 to Subpart ZZZZ of Part 63—Requirements for Performance Tests

As stated in §§63.6610, 63.6611, 63.6612, 63.6620, and 63.6640, you must comply with the following requirements for performance tests for stationary RICE:

For each . . .	Complying with the requirement to . . .	You must . . .	Using . . .	According to the following requirements . . .

1. 2SLB, 4SLB, and CI stationary RICE	a. Reduce CO emissions	i. Measure the O ₂ at the inlet and outlet of the control device; and	(1) Portable CO and O ₂ analyzer	(a) Using ASTM D6522–00 (2005) ^a (incorporated by reference, see §63.14). Measurements to determine O ₂ must be made at the same time as the measurements for CO concentration.
		ii. Measure the CO at the inlet and the outlet of the control device	(1) Portable CO and O ₂ analyzer	(a) Using ASTM D6522–00 (2005) ^{ab} (incorporated by reference, see §63.14) or Method 10 of 40 CFR appendix A. The CO concentration must be at 15 percent O ₂ , dry basis.
2. 4SRB stationary RICE	a. Reduce formaldehyde emissions	i. Select the sampling port location and the number of traverse points; and	(1) Method 1 or 1A of 40 CFR part 60, appendix A §63.7(d)(1)(i)	(a) Sampling sites must be located at the inlet and outlet of the control device.
		ii. Measure O ₂ at the inlet and outlet of the control device; and	(1) Method 3 or 3A or 3B of 40 CFR part 60, appendix A, or ASTM Method D6522–00m (2005)	(a) Measurements to determine O ₂ concentration must be made at the same time as the measurements for formaldehyde concentration.
		iii. Measure moisture content at the inlet and outlet of the control device; and	(1) Method 4 of 40 CFR part 60, appendix A, or Test Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348–03	(a) Measurements to determine moisture content must be made at the same time and location as the measurements for formaldehyde concentration.
		iv. Measure formaldehyde at the inlet and the outlet of the control device	(1) Method 320 or 323 of 40 CFR part 63, appendix A; or ASTM D6348–03, ^c provided in ASTM D6348–03 Annex A5 (Analyte Spiking Technique), the percent R must be greater than or equal to 70 and less than or equal to 130	(a) Formaldehyde concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.
3. Stationary RICE	a. Limit the concentration of formaldehyde or CO in the stationary RICE exhaust	i. Select the sampling port location and the number of traverse points; and	(1) Method 1 or 1A of 40 CFR part 60, appendix A §63.7(d)(1)(i)	(a) If using a control device, the sampling site must be located at the outlet of the control device.
		ii. Determine the O ₂ concentration of the stationary RICE exhaust at the sampling port location; and	(1) Method 3 or 3A or 3B of 40 CFR part 60, appendix A, or ASTM Method D6522–00 (2005)	(a) Measurements to determine O ₂ concentration must be made at the same time and location as the measurements for formaldehyde concentration.
		iii. Measure moisture content of the stationary RICE exhaust at the sampling port location; and	(1) Method 4 of 40 CFR part 60, appendix A, or Test Method 320 of 40 CFR part 63, appendix A, or ASTM D 6348–03	(a) Measurements to determine moisture content must be made at the same time and location as the measurements for formaldehyde concentration.
		iv. Measure formaldehyde at the exhaust of the stationary RICE; or	(1) Method 320 or 323 of 40 CFR part 63, appendix A; or ASTM D6348–03, ^c provided in ASTM D6348–03 Annex A5 (Analyte Spiking Technique), the percent R must be greater than or equal to 70	(a) Formaldehyde concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour or longer runs.

			and less than or equal to 130	
		v. Measure CO at the exhaust of the stationary RICE	(1) Method 10 of 40 CFR part 60, appendix A, ASTM Method D6522-00 (2005), ^a Method 320 of 40 CFR part 63, appendix A, or ASTM D6348-03	(a) CO Concentration must be at 15 percent O ₂ , dry basis. Results of this test consist of the average of the three 1-hour longer runs.

^aYou may also use Methods 3A and 10 as options to ASTM-D6522-00 (2005). You may obtain a copy of ASTM-D6522-00 (2005) from at least one of the following addresses: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, or University Microfilms International, 300 North Zeeb Road, Ann Arbor, MI 48106. ASTM-D6522-00 (2005) may be used to test both CI and SI stationary RICE.

^bYou may also use Method 320 of 40 CFR part 63, appendix A, or ASTM D6348-03.

^cYou may obtain a copy of ASTM-D6348-03 from at least one of the following addresses: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, or University Microfilms International, 300 North Zeeb Road, Ann Arbor, MI 48106.

[75 FR 9682, Mar. 3, 2010, as amended at 75 FR 51597, Aug. 20, 2010]

Table 5 to Subpart ZZZZ of Part 63. Initial Compliance With Emission Limitations and Operating Limitations

As stated in §§63.6612, 63.6625 and 63.6630, you must initially comply with the emission and operating limitations as required by the following:

For each . . .	Complying with the requirement to . . .	You have demonstrated initial compliance if . . .
1. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Reduce CO emissions and using oxidation catalyst, and using a CPMS	i. The average reduction of emissions of CO determined from the initial performance test achieves the required CO percent reduction; and ii. You have installed a CPMS to continuously monitor catalyst inlet temperature according to the requirements in §63.6625(b); and iii. You have recorded the catalyst pressure drop and catalyst inlet temperature during the initial performance test.
2. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, non-emergency stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year	a. Reduce CO emissions and not using oxidation catalyst	i. The average reduction of emissions of CO determined from the initial performance test achieves the required CO percent reduction; and ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and iii. You have recorded the approved operating parameters (if any) during the initial performance test.
3. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, non-emergency	a. Reduce CO emissions, and using a CEMS	i. You have installed a CEMS to continuously monitor CO and either O ₂ or CO ₂ at both the inlet and outlet of the oxidation catalyst according to the

<p>stationary CI RICE >500 HP located at a major source of HAP, existing non-emergency stationary CI RICE >500 HP located at an area source of HAP, and existing non-emergency 4SLB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year</p>		<p>requirements in §63.6625(a); and ii. You have conducted a performance evaluation of your CEMS using PS 3 and 4A of 40 CFR part 60, appendix B; and iii. The average reduction of CO calculated using §63.6620 equals or exceeds the required percent reduction. The initial test comprises the first 4-hour period after successful validation of the CEMS. Compliance is based on the average percent reduction achieved during the 4-hour period.</p>
<p>4. Non-emergency 4SRB stationary RICE >500 HP located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year</p>	<p>a. Reduce formaldehyde emissions and using NSCR</p>	<p>i. The average reduction of emissions of formaldehyde determined from the initial performance test is equal to or greater than the required formaldehyde percent reduction; and ii. You have installed a CPMS to continuously monitor catalyst inlet temperature according to the requirements in §63.6625(b); and iii. You have recorded the catalyst pressure drop and catalyst inlet temperature during the initial performance test.</p>
<p>5. Non-emergency 4SRB stationary RICE >500 HP located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP located at an area source of HAP that are operated more than 24 hours per calendar year</p>	<p>a. Reduce formaldehyde emissions and not using NSCR</p>	<p>i. The average reduction of emissions of formaldehyde determined from the initial performance test is equal to or greater than the required formaldehyde percent reduction; and ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and iii. You have recorded the approved operating parameters (if any) during the initial performance test.</p>
<p>6. New or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE $250 \leq \text{HP} \leq 500$ located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP</p>	<p>a. Limit the concentration of formaldehyde in the stationary RICE exhaust and using oxidation catalyst or NSCR</p>	<p>i. The average formaldehyde concentration, corrected to 15 percent O₂, dry basis, from the three test runs is less than or equal to the formaldehyde emission limitation; and ii. You have installed a CPMS to continuously monitor catalyst inlet temperature according to the requirements in §63.6625(b); and iii. You have recorded the catalyst pressure drop and catalyst inlet temperature during the initial performance test.</p>
<p>7. New or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE $250 \leq \text{HP} \leq 500$ located at a major source of HAP, and existing non-emergency 4SRB stationary RICE >500 HP</p>	<p>a. Limit the concentration of formaldehyde in the stationary RICE exhaust and not using oxidation catalyst or NSCR</p>	<p>i. The average formaldehyde concentration, corrected to 15 percent O₂, dry basis, from the three test runs is less than or equal to the formaldehyde emission limitation; and ii. You have installed a CPMS to continuously monitor operating parameters approved by the Administrator (if any) according to the requirements in §63.6625(b); and iii. You have recorded the approved</p>

		operating parameters (if any) during the initial performance test.
8. Existing non-emergency stationary RICE 100≤HP≤500 located at a major source of HAP, and existing non-emergency stationary CI RICE 300<HP≤500 located at an area source of HAP	a. Reduce CO or formaldehyde emissions	i. The average reduction of emissions of CO or formaldehyde, as applicable determined from the initial performance test is equal to or greater than the required CO or formaldehyde, as applicable, percent reduction.
9. Existing non-emergency stationary RICE 100≤HP≤500 located at a major source of HAP, and existing non-emergency stationary CI RICE 300<HP≤500 located at an area source of HAP	a. Limit the concentration of formaldehyde or CO in the stationary RICE exhaust	i. The average formaldehyde or CO concentration, as applicable, corrected to 15 percent O ₂ , dry basis, from the three test runs is less than or equal to the formaldehyde or CO emission limitation, as applicable.

[75 FR 9684, Mar. 3, 2010, as amended at 75 FR 51598, Aug. 20, 2010]

Table 6 to Subpart ZZZZ of Part 63. Continuous Compliance With Emission Limitations, Operating Limitations, Work Practices, and Management Practices

As stated in §63.6640, you must continuously comply with the emissions and operating limitations and work or management practices as required by the following:

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
1. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, and new or reconstructed non-emergency CI stationary RICE >500 HP located at a major source of HAP	a. Reduce CO emissions and using an oxidation catalyst, and using a CPMS	i. Conducting semiannual performance tests for CO to demonstrate that the required CO percent reduction is achieved; ^a and ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and iii. Reducing these data to 4-hour rolling averages; and iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and
		v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.
2. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥250 HP located at a major source of HAP, and new or reconstructed non-emergency CI stationary RICE >500 HP located at a major source of HAP	a. Reduce CO emissions and not using an oxidation catalyst, and using a CPMS	i. Conducting semiannual performance tests for CO to demonstrate that the required CO percent reduction is achieved; ^a and ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and iii. Reducing these data to 4-hour rolling averages; and iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.
3. New or reconstructed non-emergency 2SLB stationary RICE >500 HP located at a major source of	a. Reduce CO emissions and using a CEMS	i. Collecting the monitoring data according to §63.6625(a), reducing the measurements

<p>HAP, new or reconstructed non-emergency 4SLB stationary RICE ≥ 250 HP located at a major source of HAP, new or reconstructed non-emergency stationary CI RICE > 500 HP located at a major source of HAP, existing non-emergency stationary CI RICE > 500 HP, existing non-emergency 4SLB stationary RICE > 500 HP located at an area source of HAP that are operated more than 24 hours per calendar year</p>		<p>to 1-hour averages, calculating the percent reduction of CO emissions according to §63.6620; and ii. Demonstrating that the catalyst achieves the required percent reduction of CO emissions over the 4-hour averaging period; and iii. Conducting an annual RATA of your CEMS using PS 3 and 4A of 40 CFR part 60, appendix B, as well as daily and periodic data quality checks in accordance with 40 CFR part 60, appendix F, procedure 1.</p>
<p>4. Non-emergency 4SRB stationary RICE > 500 HP located at a major source of HAP</p>	<p>a. Reduce formaldehyde emissions and using NSCR</p>	<p>i. Collecting the catalyst inlet temperature data according to §63.6625(b); and ii. Reducing these data to 4-hour rolling averages; and</p>
		<p>iii. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and</p>
		<p>iv. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.</p>
<p>5. Non-emergency 4SRB stationary RICE > 500 HP located at a major source of HAP</p>	<p>a. Reduce formaldehyde emissions and not using NSCR</p>	<p>i. Collecting the approved operating parameter (if any) data according to §63.6625(b); and ii. Reducing these data to 4-hour rolling averages; and</p>
		<p>iii. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.</p>
<p>6. Non-emergency 4SRB stationary RICE with a brake HP $\geq 5,000$ located at a major source of HAP</p>	<p>a. Reduce formaldehyde emissions</p>	<p>Conducting semiannual performance tests for formaldehyde to demonstrate that the required formaldehyde percent reduction is achieved.^a</p>
<p>7. New or reconstructed non-emergency stationary RICE > 500 HP located at a major source of HAP and new or reconstructed non-emergency 4SLB stationary RICE $250 \leq \text{HP} \leq 500$ located at a major source of HAP</p>	<p>a. Limit the concentration of formaldehyde in the stationary RICE exhaust and using oxidation catalyst or NSCR</p>	<p>i. Conducting semiannual performance tests for formaldehyde to demonstrate that your emissions remain at or below the formaldehyde concentration limit;^a and ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and</p>
		<p>iii. Reducing these data to 4-hour rolling averages; and</p>
		<p>iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and</p>
		<p>v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.</p>

<p>8. New or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP and new or reconstructed non-emergency 4SLB stationary RICE 250≤HP≤500 located at a major source of HAP</p>	<p>a. Limit the concentration of formaldehyde in the stationary RICE exhaust and not using oxidation catalyst or NSCR</p>	<p>i. Conducting semiannual performance tests for formaldehyde to demonstrate that your emissions remain at or below the formaldehyde concentration limit;^a and ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and</p>
		<p>iii. Reducing these data to 4-hour rolling averages; and</p>
		<p>iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.</p>
<p>9. Existing emergency and black start stationary RICE ≤500 HP located at a major source of HAP, existing non-emergency stationary RICE <100 HP located at a major source of HAP, existing emergency and black start stationary RICE located at an area source of HAP, existing non-emergency stationary CI RICE ≤300 HP located at an area source of HAP, existing non-emergency 2SLB stationary RICE located at an area source of HAP, existing non-emergency landfill or digester gas stationary SI RICE located at an area source of HAP, existing non-emergency 4SLB and 4SRB stationary RICE ≤500 HP located at an area source of HAP, existing non-emergency 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate 24 hours or less per calendar year</p>	<p>a. Work or Management practices</p>	<p>i. Operating and maintaining the stationary RICE according to the manufacturer's emission-related operation and maintenance instructions; or ii. Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.</p>
<p>10. Existing stationary CI RICE >500 HP that are not limited use stationary RICE, and existing 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year and are not limited use stationary RICE</p>	<p>a. Reduce CO or formaldehyde emissions, or limit the concentration of formaldehyde or CO in the stationary RICE exhaust, and using oxidation catalyst or NSCR</p>	<p>i. Conducting performance tests every 8,760 hours or 3 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and</p>
		<p>ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and</p>
		<p>iii. Reducing these data to 4-hour rolling averages; and</p>
		<p>iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and</p>
		<p>v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.</p>
<p>11. Existing stationary CI RICE >500 HP that are not limited use stationary RICE, and existing 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year and are not limited use stationary RICE</p>	<p>a. Reduce CO or formaldehyde emissions, or limit the concentration of formaldehyde or CO in the stationary RICE exhaust,</p>	<p>i. Conducting performance tests every 8,760 hours or 3 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent</p>

	and not using oxidation catalyst or NSCR	reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and
		ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.
12. Existing limited use CI stationary RICE >500 HP and existing limited use 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year	a. Reduce CO or formaldehyde emissions or limit the concentration of formaldehyde or CO in the stationary RICE exhaust, and using an oxidation catalyst or NSCR	i. Conducting performance tests every 8,760 hours or 5 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and
		ii. Collecting the catalyst inlet temperature data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the catalyst inlet temperature; and
		v. Measuring the pressure drop across the catalyst once per month and demonstrating that the pressure drop across the catalyst is within the operating limitation established during the performance test.
13. Existing limited use CI stationary RICE >500 HP and existing limited use 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate more than 24 hours per calendar year	a. Reduce CO or formaldehyde emissions or limit the concentration of formaldehyde or CO in the stationary RICE exhaust, and using an oxidation catalyst or NSCR	i. Conducting performance tests every 8,760 hours or 5 years, whichever comes first, for CO or formaldehyde, as appropriate, to demonstrate that the required CO or formaldehyde, as appropriate, percent reduction is achieved or that your emissions remain at or below the CO or formaldehyde concentration limit; and
		ii. Collecting the approved operating parameter (if any) data according to §63.6625(b); and
		iii. Reducing these data to 4-hour rolling averages; and
		iv. Maintaining the 4-hour rolling averages within the operating limitations for the operating parameters established during the performance test.

^aAfter you have demonstrated compliance for two consecutive tests, you may reduce the frequency of subsequent performance tests to annually. If the results of any subsequent annual performance test indicate the stationary RICE

is not in compliance with the CO or formaldehyde emission limitation, or you deviate from any of your operating limitations, you must resume semiannual performance tests.

[75 FR 9685, Mar. 3, 2010, as amended at 75 FR 51600, Aug. 20, 2010]

Table 7 to Subpart ZZZZ of Part 63. Requirements for Reports

As stated in §63.6650, you must comply with the following requirements for reports:

For each ...	You must submit a ...	The report must contain ...	You must submit the report ...
1. Existing non-emergency, non-black start stationary RICE $100 \leq \text{HP} \leq 500$ located at a major source of HAP; existing non-emergency, non-black start stationary CI RICE >500 HP located at a major source of HAP; existing non-emergency 4SRB stationary RICE >500 HP located at a major source of HAP; existing non-emergency, non-black start stationary CI RICE >300 HP located at an area source of HAP; existing non-emergency, non-black start 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP and operated more than 24 hours per calendar year; new or reconstructed non-emergency stationary RICE >500 HP located at a major source of HAP; and new or reconstructed non-emergency 4SLB stationary RICE $250 \leq \text{HP} \leq 500$ located at a major source of HAP	Compliance report	a. If there are no deviations from any emission limitations or operating limitations that apply to you, a statement that there were no deviations from the emission limitations or operating limitations during the reporting period. If there were no periods during which the CMS, including CEMS and CPMS, was out-of-control, as specified in §63.8(c)(7), a statement that there were not periods during which the CMS was out-of-control during the reporting period; or b. If you had a deviation from any emission limitation or operating limitation during the reporting period, the information in §63.6650(d). If there were periods during which the CMS, including CEMS and CPMS, was out-of-control, as specified in §63.8(c)(7), the information in §63.6650(e); or c. If you had a malfunction during the reporting period, the information in §63.6650(c)(4)	i. Semiannually according to the requirements in §63.6650(b)(1)–(5) for engines that are not limited use stationary RICE subject to numerical emission limitations; and ii. Annually according to the requirements in §63.6650(b)(6)–(9) for engines that are limited use stationary RICE subject to numerical emission limitations. i. Semiannually according to the requirements in §63.6650(b). i. Semiannually according to the requirements in §63.6650(b).
2. New or reconstructed non-emergency stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis	Report	a. The fuel flow rate of each fuel and the heating values that were used in your calculations, and you must demonstrate that the percentage of heat input provided by landfill gas or digester gas, is equivalent to 10 percent or more of the gross heat input on an annual basis; and	i. Annually, according to the requirements in §63.6650.
		b. The operating limits provided in your federally enforceable permit, and any deviations from these limits; and	i. See item 2.a.i.
		c. Any problems or errors suspected with the meters.	i. See item 2.a.i.

[75 FR 9687, Mar. 3, 2010, as amended at 75 FR 51603, Aug. 20, 2010]

Table 8 to Subpart ZZZZ of Part 63—Applicability of General Provisions to Subpart ZZZZ.

As stated in §63.6665, you must comply with the following applicable general provisions.

General provisions citation	Subject of citation	Applies to subpart	Explanation
§63.1	General applicability of the General Provisions	Yes.	
§63.2	Definitions	Yes	Additional terms defined in §63.6675.
§63.3	Units and abbreviations	Yes.	
§63.4	Prohibited activities and circumvention	Yes.	
§63.5	Construction and reconstruction	Yes.	
§63.6(a)	Applicability	Yes.	
§63.6(b)(1)–(4)	Compliance dates for new and reconstructed sources	Yes.	
§63.6(b)(5)	Notification	Yes.	
§63.6(b)(6)	[Reserved]		
§63.6(b)(7)	Compliance dates for new and reconstructed area sources that become major sources	Yes.	
§63.6(c)(1)–(2)	Compliance dates for existing sources	Yes.	
§63.6(c)(3)–(4)	[Reserved]		
§63.6(c)(5)	Compliance dates for existing area sources that become major sources	Yes.	
§63.6(d)	[Reserved]		
§63.6(e)	Operation and maintenance	No.	
§63.6(f)(1)	Applicability of standards	No.	
§63.6(f)(2)	Methods for determining compliance	Yes.	
§63.6(f)(3)	Finding of compliance	Yes.	
§63.6(g)(1)–(3)	Use of alternate standard	Yes.	
§63.6(h)	Opacity and visible emission standards	No	Subpart ZZZZ does not contain opacity or visible emission standards.
§63.6(i)	Compliance extension procedures and criteria	Yes.	
§63.6(j)	Presidential compliance exemption	Yes.	
§63.7(a)(1)–(2)	Performance test dates	Yes	Subpart ZZZZ contains performance test dates at §§63.6610, 63.6611, and 63.6612.
§63.7(a)(3)	CAA section 114 authority	Yes.	
§63.7(b)(1)	Notification of performance test	Yes	Except that §63.7(b)(1) only applies as specified in §63.6645.
§63.7(b)(2)	Notification of rescheduling	Yes	Except that §63.7(b)(2) only applies as

			specified in §63.6645.
§63.7(c)	Quality assurance/test plan	Yes	Except that §63.7(c) only applies as specified in §63.6645.
§63.7(d)	Testing facilities	Yes.	
§63.7(e)(1)	Conditions for conducting performance tests	No.	Subpart ZZZZ specifies conditions for conducting performance tests at §63.6620.
§63.7(e)(2)	Conduct of performance tests and reduction of data	Yes	Subpart ZZZZ specifies test methods at §63.6620.
§63.7(e)(3)	Test run duration	Yes.	
§63.7(e)(4)	Administrator may require other testing under section 114 of the CAA	Yes.	
§63.7(f)	Alternative test method provisions	Yes.	
§63.7(g)	Performance test data analysis, recordkeeping, and reporting	Yes.	
§63.7(h)	Waiver of tests	Yes.	
§63.8(a)(1)	Applicability of monitoring requirements	Yes	Subpart ZZZZ contains specific requirements for monitoring at §63.6625.
§63.8(a)(2)	Performance specifications	Yes.	
§63.8(a)(3)	[Reserved]		
§63.8(a)(4)	Monitoring for control devices	No.	
§63.8(b)(1)	Monitoring	Yes.	
§63.8(b)(2)–(3)	Multiple effluents and multiple monitoring systems	Yes.	
§63.8(c)(1)	Monitoring system operation and maintenance	Yes.	
§63.8(c)(1)(i)	Routine and predictable SSM	Yes.	
§63.8(c)(1)(ii)	SSM not in Startup Shutdown Malfunction Plan	Yes.	
§63.8(c)(1)(iii)	Compliance with operation and maintenance requirements	Yes.	
§63.8(c)(2)–(3)	Monitoring system installation	Yes.	
§63.8(c)(4)	Continuous monitoring system (CMS) requirements	Yes	Except that subpart ZZZZ does not require Continuous Opacity Monitoring System (COMS).
§63.8(c)(5)	COMS minimum procedures	No	Subpart ZZZZ does not require COMS.
§63.8(c)(6)–(8)	CMS requirements	Yes	Except that subpart ZZZZ does not require COMS.
§63.8(d)	CMS quality control	Yes.	
§63.8(e)	CMS performance evaluation	Yes	Except for §63.8(e)(5)(ii), which applies to

			COMS.
		Except that §63.8(e) only applies as specified in §63.6645.	
§63.8(f)(1)–(5)	Alternative monitoring method	Yes	Except that §63.8(f)(4) only applies as specified in §63.6645.
§63.8(f)(6)	Alternative to relative accuracy test	Yes	Except that §63.8(f)(6) only applies as specified in §63.6645.
§63.8(g)	Data reduction	Yes	Except that provisions for COMS are not applicable. Averaging periods for demonstrating compliance are specified at §§63.6635 and 63.6640.
§63.9(a)	Applicability and State delegation of notification requirements	Yes.	
§63.9(b)(1)–(5)	Initial notifications	Yes	Except that §63.9(b)(3) is reserved.
		Except that §63.9(b) only applies as specified in §63.6645.	
§63.9(c)	Request for compliance extension	Yes	Except that §63.9(c) only applies as specified in §63.6645.
§63.9(d)	Notification of special compliance requirements for new sources	Yes	Except that §63.9(d) only applies as specified in §63.6645.
§63.9(e)	Notification of performance test	Yes	Except that §63.9(e) only applies as specified in §63.6645.
§63.9(f)	Notification of visible emission (VE)/opacity test	No	Subpart ZZZZ does not contain opacity or VE standards.
§63.9(g)(1)	Notification of performance evaluation	Yes	Except that §63.9(g) only applies as specified in §63.6645.
§63.9(g)(2)	Notification of use of COMS data	No	Subpart ZZZZ does not contain opacity or VE standards.
§63.9(g)(3)	Notification that criterion for alternative to RATA is exceeded	Yes	If alternative is in use.
		Except that §63.9(g) only applies as specified in §63.6645.	
§63.9(h)(1)–(6)	Notification of compliance status	Yes	Except that notifications for sources using a CEMS are due 30 days after completion of performance evaluations. §63.9(h)(4) is reserved.
			Except that §63.9(h) only applies as specified in §63.6645.
§63.9(i)	Adjustment of submittal deadlines	Yes.	

§63.9(j)	Change in previous information	Yes.	
§63.10(a)	Administrative provisions for recordkeeping/reporting	Yes.	
§63.10(b)(1)	Record retention	Yes.	
§63.10(b)(2)(i)-(v)	Records related to SSM	No.	
§63.10(b)(2)(vi)-(xi)	Records	Yes.	
§63.10(b)(2)(xii)	Record when under waiver	Yes.	
§63.10(b)(2)(xiii)	Records when using alternative to RATA	Yes	For CO standard if using RATA alternative.
§63.10(b)(2)(xiv)	Records of supporting documentation	Yes.	
§63.10(b)(3)	Records of applicability determination	Yes.	
§63.10(c)	Additional records for sources using CEMS	Yes	Except that §63.10(c)(2)-(4) and (9) are reserved.
§63.10(d)(1)	General reporting requirements	Yes.	
§63.10(d)(2)	Report of performance test results	Yes.	
§63.10(d)(3)	Reporting opacity or VE observations	No	Subpart ZZZZ does not contain opacity or VE standards.
§63.10(d)(4)	Progress reports	Yes.	
§63.10(d)(5)	Startup, shutdown, and malfunction reports	No.	
§63.10(e)(1) and (2)(i)	Additional CMS Reports	Yes.	
§63.10(e)(2)(ii)	COMS-related report	No	Subpart ZZZZ does not require COMS.
§63.10(e)(3)	Excess emission and parameter exceedances reports	Yes.	Except that §63.10(e)(3)(i) (C) is reserved.
§63.10(e)(4)	Reporting COMS data	No	Subpart ZZZZ does not require COMS.
§63.10(f)	Waiver for recordkeeping/reporting	Yes.	
§63.11	Flares	No.	
§63.12	State authority and delegations	Yes.	
§63.13	Addresses	Yes.	
§63.14	Incorporation by reference	Yes.	
§63.15	Availability of information	Yes.	

**Indiana Department of Environmental Management
Office of Air Quality**

Addendum to the Technical Support Document (ATSD) for a
Significant Permit Revision (SPR) to a
Federally Enforceable State Operating Permit (FESOP)

Source Background and Description

Source Name:	POET Biorefining - Cloverdale, LLC
Source Location:	2265 East County Road 800 South, Cloverdale, IN 46120
County:	Putnam
SIC Code:	2869
Operation Permit No.:	F 133-28725-00003
Operation Permit Issuance Date:	March 26, 2010
Significant Permit Revision No.:	133-29592-00003
Permit Reviewer:	Jason R. Krawczyk

On September 29, 2010, the Office of Air Quality (OAQ) had a notice published in the Banner Graphic, Greencastle, Indiana, stating that POET Biorefining - Cloverdale, LLC had applied for a Significant Permit Revision to their Federally Enforceable State Operating Permit (FESOP). The source plans to construct and operate new emission units at their existing stationary ethanol production facility. The notice also stated that the OAQ proposed to issue a FESOP SPR for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

Comments and Responses

On October 28, 2010, Emily Davis, Legal Fellow, Clean Air Project, on behalf of the Natural Resource Defense Council (NRDC) submitted comments to IDEM, OAQ on the draft New Source Review and Federally Enforceable State Operating Permit Renewal.

The Technical Support Document (TSD) is used by IDEM, OAQ for historical purposes. IDEM, OAQ does not make any changes to the original TSD, but the Permit will have the updated changes. The comments and revised permit language are provided below with deleted language as ~~strikeouts~~ and new language **bolded**.

Comment 1:

The Draft Permit classifies POET - Cloverdale's plant as "Not 1 of 28 Source Categories" pursuant to the Clean Air Act's ("CAA") Prevention of Significant Deterioration ("PSD") program. Draft Permit § A.1; see also IDEM Office of Air Quality, *Technical Support Document (TSD) for a Significant Permit Revision to Federally Enforceable State Operating Permit (FESOP)* (undated) (hereinafter "TSD") at. 2. Consequently, the Draft Permit proposes to (a) pursuant to the PSD program, establish an annual potential to emit (PTE) major source threshold for particulate matter ("PM") and other criteria pollutants at 250 tons per year ("tpy"); and (b) discount fugitive emissions in the determination of PSD applicability. We write to oppose the Draft Permit in so much as it proposes to treat the Plant as a non-listed PSD source; this aspect of the Draft Permit is flatly unlawful. Moreover, NRDC has brought these and other issues surrounding the POET - Cloverdale plant before the Indiana Office of Environmental Adjudication (OEA) and is currently awaiting a decision. IDEM should not issue any additional permits for this facility until the OEA proceedings have been fully resolved.

Response to Comment 1:

The NRDC did petition for review of New Source Construction and Federally Enforceable State Operating Permit number 133-28725-00003, that IDEM issued on March 26, 2010 to POET Biorefining - Cloverdale, LLC. That administrative appeal is pending before the Indiana Office of Environmental Adjudication. There is no timetable for a final adjudication of the issues raised in that appeal. In addition, IDEM has no authority to stop the permitting process for any source due to a pending administrative appeal of a previous permit issued to that source. No changes have been made to the permit as a result of this comment.

Comment 2:

NRDC objects to the Draft Permit on the grounds that it violates Indiana's State Implementation Plan ("SIP"). On March 3, 2003, EPA approved Indiana's SIP; this approval became effective on April 2, 2003. As a result of the approval, Indiana's PSD rule at 326 Ind. Admin. Code 2-2 is federally enforceable under the Clean Air Act. Per 326 Ind. Admin. Code 2-2-1(gg), the term "Major stationary source" encompasses sources within certain listed categories of stationary sources "that emit or have the potential to emit one hundred (100) tons per year or more of any regulated NSR pollutant." *Id.* Among the listed stationary source categories are "Chemical process plants." 326 Ind. Admin. Code 2-2-1(gg)(1)(U). POET - Cloverdale, as an ethanol production facility, is a "chemical process plant" subject to the 100 tpy major stationary source threshold established in the SIP. *Id.* The Draft Permit is unlawful because it establishes a PM PTE limit of 250 tpy, yet still classifies the Plant as a "Minor Source, under PSD." 326 Ind. Admin. Code 2-2-1(gg)(1)(U) requires that POET - Cloverdale be subject to a PM PTE limit of 100 tpy or be classified and regulated as a major stationary source.

The TSD asserts that authority to treat ethanol production plants as one of the non-listed 28 source categories derives from a relatively recent EPA rulemaking and related changes that were made to the Code of Federal Regulations. TSD at 4. While it is true that on May 1, 2007, EPA adopted a rule changing the definition of "major emitting facility" in certain sections of the Code of Federal Regulations to exclude fuel ethanol plants, *see generally* 72 Fed. Reg. 24,060 *et seq.*, this change has not been incorporated into Indiana's SIP. It is settled law that federal rulemaking changes do not supersede an existing SIP. *See Environmental Defense v. EPA*, 467 F.3d 1329, 1335 (D.C. Cir. 2006) ("A current SIP, even one tied to outdated NAAQS, remains in force until replaced by another but later-approved SIP. The Clean Air Act provides that the current SIPs are legally sufficient until they are replaced by new SIPs."); *Duquesne Light Co. v. EPA*, 698 F.2d 456, 471 (D.C. Cir. 1983) ("[C]urrent SIPs remain in force until EPA grants formal approval to a revision."); *see also General Motors Corp. v. US*, 496 U.S. 530, 540 (1990) ("[T]he approved SIP is the applicable implementation plan during the time a SIP revision proposal is pending.") Accordingly, unless and until Indiana amends its SIP to incorporate EPA's Ethanol Rule, the requirements of the existing SIP continue to apply - including the requirement that "chemical process plants" such as POET Biorefining - Cloverdale are subject to a 100 tpy source threshold.

Response to Comment 2:

IDEM recognizes that the above mentioned comments were the same comments that NRDC submitted when this plant was initially permitted on March 26, 2010. Below is the same response that IDEM provided at that time. No changes have been made to the permit as a result of this comment.

Whenever Indiana's air state rules are not clear, IDEM seeks the guidance of the US EPA. Since the current Indiana SIP does not define what constitutes a "chemical process plant"; IDEM based its permit decision upon US EPA guidance. Using US EPA's guidance as basis for permitting decisions where there is no clear interpretation in Indiana's rule (SIP approved or not) has been the practice in IDEM.

Prior to July 2, 2007, US EPA considered fuel ethanol plants as chemical processing plants. IDEM considered the same interpretation. After US EPA reinterpreted the term "chemical process plant" which excluded fuel ethanol, again IDEM used the US EPA's interpretation. In this case, IDEM consistently used

the US EPA's interpretation (whether the basis is a guidance or federal rule) because the Indiana state rules do not define a "chemical process plant". Idem has sufficient authority under its current SIP to interpret the term "chemical process plant" pursuant to the current federal rule.

Comment 3:

Second, the NRDC objects to the Draft Permit on the grounds that the cited authority for the treatment of the Plant as a non-listed source—namely, EPA's Ethanol Rule and the changes made to 40 CFR §§ 51.165 and 52.21—is unlawful. The Ethanol Rule is currently subject to both a pending petition for review before the U.S. Court of Appeals for the District of Columbia Circuit and a pending administrative Petition for Reconsideration before EPA Administrator Lisa Jackson. The Ethanol Rule is unlawful because it violates the plain language of the Clean Air Act, which mandates a 100 tpy threshold for "chemical process plants" such as fuel ethanol facilities. Indeed, such facilities have been classified by EPA as chemical process plants for nearly 30 years. 42 U.S.C. § 7479. The Rule also violates the Clean Air Act's anti-backsliding provision, 42 U.S.C. § 7515, and ignores D.C. Circuit law by authorizing emissions increases in nonattainment areas. Further, the Ethanol Rule unlawfully amended the Clean Air Act's Section 302(j) list for fugitive emissions without a statutorily-mandated rulemaking. 42 U.S.C. § 7602(j).

Response to Comment 3:

The current federal rule, while under reconsideration, is not stayed. Until the U.S. Court of Appeals for the District of Columbia Circuit makes a decision or EPA Administrator Lisa Jackson makes a final reconsideration, the rule is in effect. No changes have been made to the permit as a result of this comment.

Comment 4:

Operating under a previous name, Putnam Ethanol, POET - Cloverdale received its initial operating permit for the Plant in October, 2004. This permit both classified the Plant as one of the 28 listed sources, and required it to count fugitives in limiting emissions under the 100 tpy major source threshold. The Technical Support Document accompanying the initial permit notes "[t]he source is in 1 of 28 source categories...the potential to emit PM, PM10, VOC, CO, and NOx from the entire source before control is greater than 100 tons/yr" *Technical Support Document (TSD) for a New Source Review and Federally Enforceable State Operating Permit; Permit No. F133-19163-00003*, at 10. Further, "the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are counted toward determination of PSD applicability." *Id.* at 5. This initial operating permit classified the Plant and set emissions levels as required by both federal law and the Indiana state SIP in limiting emissions to 100 tpy from the listed chemical process plant.

Response to Comment 4:

When Putnam Ethanol, LLC was initially permitted in October 2004, EPA had not finalized the revision to the definition of a "major stationary source" that excluded ethanol plants as chemical processing plants. However, once the plant was re-permitted after 2007, the status of the plant was changed based on the July 2, 2007 EPA's interpretation. This change has been consistently applied by IDEM to all ethanol plants. No changes have been made to the permit as a result of this comment.

Comment 5:

Finally, it is worth noting that while the Draft Permit establishes a 250-tpy PSD PTE major source threshold for the Plant, such an elevated permit limit is not necessary. The Draft Permit itself indicates that the Plant's PTE is lower than 100 tpy for each of the criteria pollutants, including PM. In fact, the PTE calculated for PM (presumably excluding fugitive emissions) is 78.48 tpy. The higher major source thresholds incorporated into the Draft Permit are not merely unlawful, they are wholly unnecessary.

Response to Comment 5:

The statement "The Draft Permit itself indicates that the Plant's PTE is lower than 100 tpy for each of the criteria pollutants, including PM." is incorrect. It has to be noted that it is the Plant's **Limited** PTE that is lower than 100 tpy. The Plant's uncontrolled and unlimited PTE is higher than 100 tpy. The limits specified in the permit are necessary to assure that the source is a PSD minor source and to render 326 IAC 2-2 not applicable. The mass limits specified are lawful because they are less than the major source threshold for this source.

No changes have been made to the permit as a result of this comment.

Additional Changes

IDEM, OAQ has decided to make additional revisions to the permit as described below, with deleted language as ~~strikeouts~~ and new language **bolded**.

- (a) The header of the permit has been revised to correct a typographical error as follows:

1st Significant Permit Revision No.: ~~F133-29562-00003~~ **F133-29592-00003**

- (b) Condition E.5.2 has been revised to include the updated portions of NESHAP ZZZZ, as revised on August 20, 2010 and effective October 19, 2010.

E.5.2 National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines [40 CFR Part 63, Subpart ZZZZ]

The Permittee shall comply with the following provisions of 40 CFR Part 63, Subpart ZZZZ (included as Attachment F) which are incorporated by reference as 326 IAC 20-82 for the reciprocating internal combustion engine:

EU044 is subject to the following portions of 40 CFR 63, Subpart ZZZZ:

- (1) 40 CFR 63.6580
- (2) 40 CFR 63.6585(a),(c),(d)
- (3) 40 CFR 63.6590(a)(2)(iii),(c)**(1)**
- (4) 40 CFR 63.6595(a)(7),(b),(c)
- (5) 40 CFR 63.6605
- (6) 40 CFR 63.6665
- (7) 40 CFR 63.6670
- (8) 40 CFR 63.6675
- ~~(9) Table 8~~

EU045 is subject to the following portions of 40 CFR 63, Subpart ZZZZ.

- (1) 40 CFR 63.6580
- (2) 40 CFR 63.6585(a),(c),(d)
- (3) 40 CFR 63.6590(a)~~(1)(2)(iii),(iv),(b)(3)~~**(2)(iii),(c)(1)**
- (4) 40 CFR 63.6595(a)(7),(b),(c)**
- ~~(5)(4)~~ 40 CFR 63.6605
- ~~(6)(5)~~ 40 CFR 63.6665
- ~~(7)(6)~~ 40 CFR 63.6670
- ~~(8)(7)~~ 40 CFR 63.6675
- ~~(8) Table 8~~

- (c) IDEM has replaced NESHAP ZZZZ, included as Attachment F to the permit with the revised version, effective October 19, 2010.

IDEM Contact

- (a) Questions regarding this proposed FESOP Renewal can be directed to Jason R. Krawczyk at the Indiana Department Environmental Management, Office of Air Quality, Permits Branch, 100 North Senate Avenue, MC 61-53 IGCN 1003, Indianapolis, Indiana 46204-2251 or by telephone at (317) 232-8427 or toll free at 1-800-451-6027 extension 2-8427.
- (b) A copy of the permit is available on the Internet at: <http://www.in.gov/ai/appfiles/idem-caats/>
- (c) For additional information about air permits and how the public and interested parties can participate, refer to the IDEM's Guide for Citizen Participation and Permit Guide on the Internet at: www.idem.in.gov

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Significant Permit Revision to a Federally Enforceable State Operating Permit (FESOP)

Source Description and Location

Source Name:	POET Biorefining - Cloverdale, LLC
Source Location:	2265 East County Road 800 South, Cloverdale, IN 46120
County:	Putnam
SIC Code:	2869
Operation Permit No.:	F 133-28725-00003
Operation Permit Issuance Date:	March 26, 2010
Significant Permit Revision No.:	133-29592
Permit Reviewer:	Jason R. Krawczyk

On August 23, 2010, the Office of Air Quality (OAQ) received an application from POET Biorefining - Cloverdale, LLC related to a modification to an existing ethanol production facility.

Existing Approvals

The source, under the name Putnam County Ethanol LLC, was issued FESOP No. 133-29592-00003 on March 26, 2010. The source has since received no additional approvals.

County Attainment Status

The source is located in Putnam County.

Pollutant	Designation
SO ₂	Better than national standards.
CO	Unclassifiable or attainment effective November 15, 1990.
O ₃	Unclassifiable or attainment effective June 15, 2004, for the 8-hour ozone standard. ¹
PM ₁₀	Unclassifiable effective November 15, 1990.
NO ₂	Cannot be classified or better than national standards.
Pb	Not designated.

¹Unclassifiable or attainment effective October 18, 2000, for the 1-hour ozone standard which was revoked effective June 15, 2005.

Unclassifiable or attainment effective April 5, 2005, for PM_{2.5}.

- (a) **Ozone Standards**
Volatile organic compounds (VOC) and Nitrogen Oxides (NO_x) are regulated under the Clean Air Act (CAA) for the purposes of attaining and maintaining the National Ambient Air Quality Standards (NAAQS) for ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to ozone. Putnam County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (b) **PM_{2.5}**
Putnam County has been classified as attainment for PM_{2.5}. On May 8, 2008 U.S. EPA promulgated the requirements for Prevention of Significant Deterioration (PSD) for PM_{2.5} emissions, and the effective date of these rules was July 15, 2008. Indiana has three years from the publication of these rules to revise its PSD rules, 326 IAC 2-2, to include those requirements.

The May 8, 2008 rule revisions require IDEM to regulate PM10 emissions as a surrogate for PM2.5 emissions until 326 IAC 2-2 is revised.

- (c) **Other Criteria Pollutants**
Putnam County has been classified as attainment or unclassifiable in Indiana for all criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2, 326 IAC 2-3, or 326 IAC 2-7, (see detailed explanation on page 4) and there is no applicable New Source Performance Standard that was in effect on August 7, 1980, fugitive emissions are not counted toward the determination of PSD, Emission Offset, and Part 70 Permit applicability.

The effective date of NSPS, Subpart Db was June 13, 2007.
The effective date of NSPS, Subpart Kb was April 8, 1987.
The effective date of NSPS, Subpart VVa was November 16, 2006.
The effective date of NSPS, Subpart IIII was July 11, 2006.

Status of the Existing Source

The table below summarizes the potential to emit of the entire source, prior to the proposed revision, after consideration of all enforceable limits established in the effective permits:

Process/Emission Unit	Potential To Emit of the Entire Source Prior to Revision (tons/year)								
	PM	PM10	PM2.5	SO ₂	NO _x	VOC	CO	Total HAPs	Single HAP (Acetaldehyde)
Emissions Units									
Grains Receiving (001, 002, 003, 042-044)	4.99	4.99	4.99	-	-	-	-	-	-
Grain Storage (004 - 007)	3.02	3.02	3.02	-	-	-	-	-	-
Scalper / Surge Bin (008 - 009)	1.05	1.05	1.05	-	-	-	-	-	-
Hammermill (010)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (011)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (012)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (013)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (014)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (015)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (016)	1.80	1.80	1.80	-	-	-	-	-	-
DDGS Storage Silo (039)	0.61	0.61	0.61	-	-	-	-	-	-
DDGS Silo Bypass (040)	0.61	0.61	0.61	-	-	-	-	-	-
DDGS Storage Building Flat Storage (041)	0.61	0.61	0.61	-	-	-	-	-	-
Fermentation Process (017 - 026)	-	-	-	-	-	6.58	-	1.40	1.37
Distillation and Dehydration Process (027 - 032)	-	-	-	-	-	4.86	-	4.27	3.68
Stillage Process (033-035, 038)**	52.25	40.46	40.46	56.97	50.29	46.40	65.63	8.23	4.23
Ethanol Loadout (045)	-	-	-	-	1.97	7.75	4.97	0.45	-
Boilers (036, 037)	2.42	9.67	9.67	0.76	38.18	7.00	25.46	2.43	-
Diesel Generator (046)	0.25	0.14	0.14	1.45	4.67	0.25	1.98	-	-
Diesel Fire Pump (047)	0.07	0.07	0.07	0.04	1.29	0.19	0.43	0.48	0.06
Space Heaters	0.02	0.08	0.08	0.01	1.10	0.06	0.92	0.02	-
Fugitive Emissions									
Uncaptured Grain Receiving Emissions* F001	10.27	3.37	3.37	-	-	-	-	-	-
Uncaptured DDGS Loading Emissions* F002	1.62	0.55	0.55	-	-	-	-	-	-
Truck Traffic* F003	20.54	4.01	0.60	-	-	-	-	-	-
Equipment Leaks* F004	-	-	-	-	-	15.57	-	0.93	-
Cooling Tower* F005	12.34	12.34	12.34	-	-	-	-	-	-
Storage Tanks* F006 (T001 - T005)	-	-	-	-	-	2.67	-	-	-
Total PTE of Source (non-Fugitive)	78.48	73.91	73.91	59.24	97.50	73.08	99.38	18.21	9.29
Title V Major Source Thresholds	NA	100	100	100	100	100	100	25	10
PSD Major Source Thresholds	250	250	250	250	250	250	250	NA	NA
negl. = negligible Under the Part 70 Permit program (40 CFR 70), particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers (PM10), not particulate matter (PM), is considered as a "regulated air pollutant". US EPA has directed states to regulate PM10 emissions as surrogate for PM2.5 emissions.									
* Fugitive PM, PM10, PM2.5, and VOC emissions are not counted toward the determination of PSD and Emission Offset applicability.									
** The wet scrubber (CE011) controlling EU017 through EU026 exhausts through the RTO and emits through stack SV012. Occasionally the RTO must be temporarily shut down for maintenance or other operational reasons. In this event, the DDGS dryers (EU034 and EU035) and fluid bed cooler (EU038) will be shut down, however, the fermentation process (EU017 through EU026) will continue to be operated in normal mode. The emissions from these sources will be controlled by the wet scrubber CE011 only and vent through stack SV011. Emissions exhausting through SV011 are limited to 400 hours per twelve (12) consecutive month period. Since the potential emissions from the DDGS fluid bed cooler (EU038) are controlled by baghouse CE014 and then exhaust to RTO CE012, no emissions calculations were performed since the emissions will be limited by permit conditions limiting the RTO emissions.									
*** Emissions limits were determined assuming a maximum of 1,140,742 tons grains received and 376,445 tons DDGS produced.									

This PTE table is from the TSD of NSR/FESOP 133-28725-0003, issued on March 26, 2010.

- (a) This existing source is not a major stationary source, under PSD (326 IAC 2-2), because no attainment regulated pollutant is emitted at a rate of 250 tons per year or more, and it is not one of the twenty-eight (28) listed source categories, as specified in 326 IAC 2-2-1(gg)(1).
- (b) Effective July 2, 2007, U.S. EPA has revised the definition of a "major stationary source" under 40 CFR Parts 51 and 52 PSD and Nonattainment New Source Review, and the definition of a "major source" under 40 CFR parts 70 and 71 (State and Federal Operating Permits). U.S. EPA has reinterpreted the component term "chemical process plants" within the statutory definition of "major emitting facility" in section 169(1) of the CAA to exclude wet and dry corn milling facilities that produce ethanol for fuel, or produce ethanol through a natural fermentation process that involves the use of such things as corn, sugar beets, sugar cane or cellulosic biomass as a feedstock regardless of whether the ethanol is produced for human consumption, fuel, or for an industrial purpose. Therefore, ethanol plants are no longer required to count fugitive emissions for purposes of determining whether a source is a major source under the PSD, nonattainment NSR, or Title V programs unless there is an applicable New Source Performance Standard that was in effect on August 7, 1980 for the ethanol plant, or the ethanol plant has a "nested" source category. POET Biorefining - Cloverdale, LLC does not have a "nested" source category; therefore, the entire source does not fall under one of the 28 listed source categories and fugitive emissions are not counted towards determining whether the source is a major source under the PSD, nonattainment NSR, or Title V programs.

Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-7, fugitive emissions are not counted toward the determination of Part 70 applicability.

- (c) This existing source is not a major source of HAPs, as defined in 40 CFR 63.41, because the Permittee has accepted limits on HAPs emissions to less than ten (10) tons per year for any single HAP and less than twenty-five (25) tons per year of a combination of HAPs. Therefore, this source is an area source under Section 112 of the Clean Air Act (CAA).

Description of Proposed Revision

The Office of Air Quality (OAQ) has reviewed an application, submitted by POET Biorefining - Cloverdale, LLC on August 23, 2010, relating to:

- (a) Change the name of the source from Putnam County Ethanol, LLC to POET Biorefining - Cloverdale, LLC. POET Biorefining recently purchased the fuel ethanol facility.
- (b) Increasing the maximum throughput rates of EU001 - EU003 from 30,000 bushels of corn per hour to 50,000 bushels of corn per hour. This is due to the fact that corn can be received by three (3) dump puts as opposed to only the (2), which are identified in the existing permit.
- (c) Adding a mash preparation scrubber (CE011) to control emissions generated by the slurry tank and yeast propagation tank emission units (EU017 & EU018).
- (d) Removing the secondary control device from the fermentation scrubber. The fermentation scrubber (CE012) will control emissions generated by the six (6) fermentation vessels (EU019 - EU024) and the two (2) beer wells (EU025 and EU026).
- (e) Replacing the permitted seven (7) chamber regenerative thermal oxidizer (RTO) with two (2) five (5) chamber RTOs to be identified as CE015 and CE016, which will exhaust to a common stack SV014.
- (f) Removing the previously permitted DDGS storage silo (EU039) and DDGS storage silo bypass (EU040) and associated baghouses CE015 and CE016 from the permit.

- (g) Several emission unit and stack IDs have been also been revised.

The following is a list of the new/modified emission units and pollution control devices:

- (a) Three (3) truck dump pits, collectively identified as EU001, originally constructed in March 2008, obtaining new operation approval in 2010, with a combined maximum throughput rate of 50,000 bushels of corn per hour, controlled by baghouse CE001, and exhausting through stack SV001.
- (b) One (1) grain handling operation, , originally constructed in March 2008, obtaining new operation approval in 2010, controlled by baghouse CE001, exhausting through stack SV001, and consisting of the following:
- (1) One (1) grain conveyor, identified as EU002, with a maximum throughput rate of 50,000 bushels of grain per hour.
 - (2) One (1) grain elevator, identified as EU003, with a maximum throughput rate of 50,000 bushels of grain per hour.
- (c) One (1) mash preparation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 for VOC/HAP controls, exhausting through stack SV011. This process consists of the following:
- (1) One (1) slurry tank, identified as EU017.
 - (2) One (1) yeast propagation tank, identified as EU018.
- Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.
- (d) One (1) fermentation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE012 for VOC/HAP controls, exhausting through stack SV012. This process consists of the following:
- (1) Six (6) fermenters, identified as EU019 through EU024.
 - (2) Two (2) beer wells, identified as EU025 and EU026.
- Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.
- (e) One (1) stillage process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum DDGS production of 567,648,0000 gallons per year; using two (2) 30 MMBtu/hr regenerative thermal oxidizers (CE015 & CE016) for VOC control, approved for construction in 2010, exhausting through stack SV014. This process consists of the following:
- (1) One (1) set of four (4) centrifuges, identified as EU033, originally constructed in March 2008.
 - (2) Two (2) natural gas fired DDGS dryers, identified as EU034 and EU035, originally constructed in March 2008, each with a maximum heat input rate of 83 MMBtu/hr, and each with a total maximum throughput rate of 25 tons of DDGS per hour.

- (f) One (1) DDGS fluid bed cooler, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU038, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE014) for particulate control, with emissions vented to and controlled by RTOs CE015 & CE016, and exhausting to stack SV014.
- (g) One (1) DDGS storage building/flat storage, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU039, using a baghouse (CE017) for particulate control, and exhausting to stack SV017.
- (h) One (1) ethanol loadout rack (two rail loadouts utilizing top loading only and one truck loadout utilizing submerged loading only), originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU043, with a maximum throughput rate of 118.25 million gallons per year. The loadout process is controlled by enclosed flare CE018, which is fueled by natural gas and has a maximum heat input capacity of 6.8 MMBtu per hour, and exhausting through stack SV018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

- (i) Two (2) natural gas fired boilers, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU036 and EU037, each with a rated heat capacity of 145.3 MMBtu/hr, exhausting to stacks SV015 and SV016.

Under NSPS, 40 CFR 60, Subpart Db, these units are considered affected facilities.

- (j) One (1) diesel generator, approved for construction in 2010, identified as EU044, with a rated capacity of 2,000 KW, exhausting to SV019.

Under NSPS, Subpart IIII, this unit is considered an affected source.
Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

- (k) Stationary fire pumps, including one (1) diesel fire pump, identified as EU045, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack SV020.

Under NSPS, Subpart IIII, this unit is considered an affected source.
Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

The following is a list of emission units and pollution control devices removed from the source:

- (a) One (1) DDGS storage silo, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU039, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE015) for particulate control, and exhausting to stack SV016.
- (b) One (1) DDGS storage silo bypass to flat storage with filter receiver, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU040, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE016) for particulate control, and exhausting to stack SV017.

Enforcement Issues

There are no pending enforcement actions related to this revision.

Emission Calculations

See Appendix A of this TSD for detailed emission calculations.

Permit Level Determination – FESOP Revision

The following table is used to determine the appropriate permit level under 326 IAC 2-8.11.1. This table reflects the PTE before controls of the proposed revision. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Process/Emission Unit	Potential To Emit of the Entire Source Before Controls of the Proposed Revision (tons/year)								
	PM	PM10	PM2.5	SO ₂	NO _x	VOC	CO	Total HAPs	Single HAP (Acetaldehyde)
Emissions Units									
Mash Preparation Scrubber (EU017 - EU018) (CE011)	-	-	-	-	-	286.44	-	13.04	11.51
Fermentation Process (019 - 026) (CE012)	-	-	-	-	-	1903.56	-	86.65	76.50
Distillation and Dehydration Process (027 - 032) (CE013)	-	-	-	-	-	178.08	-	6.57	5.40
Stillage Process: RTOs (CE015 & CE016), DDGS Dryers (034,035), Centrifuges (033), DDGS fluid bed cooler (038)	508.71	514.35	514.35	59.72	80.43	790.56	431.87	49.98	23.36
Total PTE of Source (non-Fugitive)	508.71	514.35	514.35	59.72	80.43	3158.64	431.87	156.24	116.77
Title V Major Source Thresholds	NA	100	100	100	100	100	100	25	10
PSD Major Source Thresholds	250	250	250	250	250	250	250	NA	NA
negl. = negligible Under the Part 70 Permit program (40 CFR 70), particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers (PM10), not particulate matter (PM), is considered as a "regulated air pollutant". US EPA has directed states to regulate PM10 emissions as surrogate for PM2.5 emissions. * Fugitive PM, PM10, PM2.5, and VOC emissions are not counted toward the determination of PSD and Emission Offset applicability. ** Emissions limits were determined assuming a maximum of 1,140,742 tons grains received and 376,445 tons DDGS produced.									

This FESOP is being revised through a FESOP Significant Permit Revision pursuant to 326 IAC 2-8-11.1(g)(2) because it involves adjustment to the existing source-wide emissions limitations to maintain the FESOP status of the source (see PTE of the Entire Source After The Issuance of the FESOP Revision Section).

PTE of the Entire Source After Issuance of the FESOP Revision

The table below summarizes the potential to emit of the entire source reflecting adjustment of existing limits, with updated emissions shown as **bold** values and previous emissions shown as ~~values~~.

Process/Emission Unit	Potential To Emit of the Entire Source to accommodate the Proposed Revision (tons/year)								
	PM	PM10	PM2.5	SO ₂	NO _x	VOC	CO	Total HAPs	Single HAP (Acetaldehyde)
negl. = negligible Under the Part 70 Permit program (40 CFR 70), particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers (PM10), not particulate matter (PM), is considered as a "regulated air pollutant". US EPA has directed states to regulate PM10 emissions as surrogate for PM2.5 emissions.									
* Fugitive PM, PM10, PM2.5, and VOC emissions are not counted toward the determination of PSD and Emission Offset applicability. ** Emissions limits were determined assuming a maximum of 1,140,742 tons grains received and 376,445 tons DDGS produced.									
(a)	The increasing in maximum throughput rates of EU001 - EU003 from 30,000 bushels of corn per hour to 50,000 bushels of corn per hour will not increase potential emissions since the overall maximum capacity of the facility will not increase. The increase from 30,000 bu/hr to 50,000 bu/yr is due to the fact that corn can be received by three (3) dump puts as opposed to the (2), which are currently identified in the existing permit.								
(b)	The previously permitted DDGS storage silo (EU039) and DDGS storage silo bypass (EU040) and associated baghouses CE015 and CE016 are being removed from the permit.								
(c)	A mash preparation scrubber (CE011) has been added to control emissions generated by the slurry tank and yeast propagation tank emission units (EU017 & EU018), which were originally controlled by fermentation scrubber CE012.								
(d)	The secondary control device for the fermentation scrubber is being removed. The fermentation scrubber (CE012) will control emissions generated by the six (6) fermentation vessels (EU019 - EU024) and the two (2) beer wells (EU025 and EU026).								
(e)	The existing permitted seven (7) chamber regenerative thermal oxidizer (RTO) has been replaced with two (2) five (5) chamber RTOs to be identified as CE015 and CE016, which will exhaust to a common stack SV014.								
(f)	Emission unit IDs have been revised.								

The table below summarizes the potential to emit of the entire source after issuance of this revision, reflecting all limits, of the emission units. Any control equipment is considered federally enforceable only after issuance of this FESOP permit revision, and only to the extent that the effect of the control equipment is made practically enforceable in the permit. Note: The table below was generated from the above table, with bold text un-bolded and strikethrough text deleted.

Process/Emission Unit	Potential To Emit of the Entire Source After Issuance of Revision (tons/year)								
	PM	PM10	PM2.5	SO ₂	NO _x	VOC	CO	Total HAPs	Single HAP (Acetaldehyde)
Emissions Units									
Grains Receiving (001, 002, 003, 042-044) (CE001)	4.99	4.99	4.99	-	-	-	-	-	-
Grain Storage (004 - 007) (CE002)	3.02	3.02	3.02	-	-	-	-	-	-
Scalper / Surge Bin (008 - 009) (CE003)	1.05	1.05	1.05	-	-	-	-	-	-
Hammermill (010) (CE004)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (011)(CE005)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (012) (CE006)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (013) (CE007)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (014) (CE008)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (015) (CE009)	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill (016) (CE010)	1.80	1.80	1.80	-	-	-	-	-	-
DDGS Storage Building Flat Storage (039)	0.61	0.61	0.61	-	-	-	-	-	-
Mash Preparation Scrubber (017 - 018)(CE011)	-	-	-	-	-	5.74	-	0.66	0.57
Fermentation Process (019 - 026) (CE012)	-	-	-	-	-	38.06	-	4.34	3.81
Distillation and Dehydration Process (027 - 032) (CE013)	-	-	-	-	-	3.55	-	3.29	2.72
Stillage Process: RTOs (CE015 & CE016), DDGS Dryers (034,035), Centrifuges (033), DDGS fluid bed cooler (038)	47.30	47.30	47.30	59.70	52.69	21.16	66.14	4.82	2.32
Ethanol Loadout (043) (CE018)	-	-	-	-	1.97	7.75	4.97	0.45	-
Boilers (036, 037)	2.42	9.67	9.67	0.76	38.18	7.00	25.46	2.43	-
Diesel Generator (044)	0.25	0.14	0.14	1.45	4.67	0.25	1.98	-	-
Diesel Fire Pump (045)	0.07	0.07	0.07	0.04	1.29	0.19	0.43	0.48	0.06
Space Heaters	0.02	0.08	0.08	0.01	1.10	0.06	0.92	0.02	-
Fugitive Emissions									
Uncaptured Grain Receiving Emissions* F001	10.27	3.37	3.37	-	-	-	-	-	-
Uncaptured DDGS Loading Emissions* F002	1.62	0.55	0.55	-	-	-	-	-	-
Truck Traffic* F003	20.54	4.01	0.60	-	-	-	-	-	-
Equipment Leaks* F004	-	-	-	-	-	15.57	-	0.93	-
Cooling Tower* F005	12.34	12.34	12.34	-	-	-	-	-	-
Storage Tanks* F006 (T001 - T005)	-	-	-	-	-	2.67	-	-	-
Total PTE of Source (non-Fugitive)	72.31	79.52	79.52	61.96	99.91	83.75	99.89	17.23	9.47
Title V Major Source Thresholds	NA	100	100	100	100	100	100	25	10
PSD Major Source Thresholds	250	250	250	250	250	250	250	NA	NA
negl. = negligible Under the Part 70 Permit program (40 CFR 70), particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers (PM10), not particulate matter (PM), is considered as a "regulated air pollutant". US EPA has directed states to regulate PM10 emissions as surrogate for PM2.5 emissions. * Fugitive PM, PM10, PM2.5, and VOC emissions are not counted toward the determination of PSD and Emission Offset applicability. ** Emissions limits were determined assuming a maximum of 1,140,742 tons grains received and 376,445 tons DDGS produced.									

- (a) **FESOP Status**
 This revision to an existing Title V minor stationary source will not change the minor status, because the potential to emit criteria pollutants from the entire source will still be limited to less

than the Title V major source threshold levels. Therefore, the source will still be subject to the provisions of 326 IAC 2-8 (FESOP).

In order to comply with the requirements of 326 IAC 2-8-4 (FESOP), the source shall comply with the following:

Note: Changes in limits and emission unit IDs are shown in **bold** and ~~strike through~~ fonts or explained when necessary.

PM10 and PM2.5

- 1) Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM10 and PM2.5 emissions from the following units shall not exceed the emission limits listed in the table below:

Unit ID	Stack ID	Unit Description	Control ID	PM10 Emission Limit (lbs/hr)	PM10 Emission Equivalent (ton/yr)	PM2.5 Emission Limit (lbs/hr)	PM2.5 Emission Equivalent (ton/yr)
EU001, EU002, EU003, EU043, EU044 EU041, EU042	SV001	Grain Receiving, Handling & DDGS Loading	CE001	1.14 (Combined)	4.99 (Combined)	1.14 (Combined)	4.99 (Combined)
EU004, EU005 EU006, EU007	SV002	Grain Storage Silos	CE002	0.69 (Combined)	3.02 (Combined)	0.69 (Combined)	3.02 (Combined)
EU008, EU009	SV003	Scalper & Conveyor Transfer / Surge Bin	CE003	0.24 (Combined)	1.05 (Combined)	0.24 (Combined)	1.05 (Combined)
EU010	SV004	Hammermill #1	CE004	0.41	1.80	0.41	1.80
EU011	SV005	Hammermill #2	CE005	0.41	1.80	0.41	1.80
EU012	SV006	Hammermill #3	CE006	0.41	1.80	0.41	1.80
EU013	SV007	Hammermill #4	CE007	0.41	1.80	0.41	1.80
EU014	SV008	Hammermill #5	CE008	0.41	1.80	0.41	1.80
EU015	SV009	Hammermill #6	CE009	0.41	1.80	0.41	1.80
EU016	SV010	Hammermill #7	CE010	0.41	1.80	0.41	1.80
*	SV012 SV014	RTOs Common Stack	CE012 CE015 & CE016	9.68 10.80	42.40 47.30	9.68 10.80	42.40 47.30
EU039	SV016	DDGS Storage Silo	CE015	0.14	0.61	0.14	0.61
EU040	SV017	DDGS Silo Bypass to Silo Storage	CE016	0.14	0.61	0.14	0.61
EU044 EU039	SV018 SV017	DDGS Storage Bldg. / Flat Storage	CE017	0.14	0.61	0.14	0.61

Note: Emission limits are combined lb/hr limits for all emission units exhausting out of each stack.

Compliance with these PM10 and PM2.5 limits, combined with the PM10 and PM2.5 PTE from all other emissions units from the entire source shall limit the PM10 and PM2.5 emissions from the entire source to less than 100 tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not applicable.

VOC

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, VOC emissions from the following units shall not exceed the emission limits listed below:

- 1) The VOC emissions from Scrubber CE011, controlling the mash preparation process, shall not exceed 1.31 lbs/hr, which is the equivalent to 5.74 tons/yr.

This is a new limit due to the addition of the Mash Preparation Scrubber, which shall control emissions from the existing slurry tank and yeast propagation tank, previously

permitted and identified as EU017 and EU024, now identified as EU017 and EU018, respectively.

- 2) The VOC emissions from Scrubber CE012, controlling the fermentation process, shall not exceed 8.69 lbs/hr, which is the equivalent to 38.06 tons/yr.

Previously, the fermentation scrubber was identified as CE011, and had the option to exhaust either to the previously permitted RTO which was identified as CE012 or to the atmosphere during RTO downtime. When exhausting to the atmosphere, the scrubber was limited to 32.90 lbs/hr. RTO downtime was limited to 400 hours per twelve consecutive month period. The fermentation scrubber controls emissions from the six (6) fermenters and two (2) beer wells. This limit was changed due to the change in configuration of control.

- 3) The VOC emissions from Scrubber CE013, controlling the distillation and dehydration process, shall not exceed 0.81 lbs/hr, which is the equivalent to 3.55 tons/yr.

The distillation and dehydration scrubber's emission limit was changed to accommodate the configuration controls from the other processes.

- 4) The VOC emissions from the RTOs common stack SV014 shall not exceed 4.83 lbs/hr, which is the equivalent to 21.16 tons/yr.

This limit was revised due to the replacement of the one (1) RTO CE012 with two (2) RTOs, identified as CE015 and CE016.

- 5) The total combined load-out rate of denatured ethanol and E-85 associated with the ethanol loading rack (EU043) shall not exceed 118,250,000 gallons per twelve consecutive month period, with compliance determined at the end of each month.
- 6) The E-85 load-out rate associated with the ethanol loading rack (EU043) shall not exceed 14,300,000 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- 7) The Permittee shall use flare CE018 to control the emissions from the ethanol loading rack when loading denatured ethanol and/or E-85 to trucks.
- 8) The Permittee shall use flare CE018 to control the emissions from the ethanol loading rack when loading denatured ethanol and/or E-85 to railcars.
- 9) VOC emissions from flare CE018 exhaust associated with the loading rack (EU043) shall not exceed 0.131 pounds per thousand gallons.

Compliance with these VOC limits, combined with the VOC PTE from all other emission units from the entire source, shall limit the source-wide VOC emissions to less than 100 tons per year and therefore, render the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) not applicable.

CO

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, CO emissions shall not exceed the emission limits listed below:

- 1) CO emissions from the RTOs common stack SV014 shall not exceed 15.10 lbs/hr, which is the equivalent to 66.14 tons/yr.

This limit was revised due to the replacement of the one (1) RTO CE012 with two (2) RTOs, identified as CE015 and CE016.

- 2) The CO emissions from the flare CE018 exhaust associated with the ethanol loading rack (~~EU045~~) (**EU043**) shall not exceed 0.084 pounds per thousand gallons.

- 3) The boilers (EU036 and EU037) shall only burn natural gas.
- 4) The total input of the natural gas to the boilers (EU036 and EU037) shall not exceed 2545.7 MMCF per twelve (12) consecutive month period, with compliance determined at the end of each month and CO emissions shall not exceed 20 pounds per MMCF.
- 5) The diesel generator (~~EU046~~) (**EU044**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.
- 6) The diesel fire pump (~~EU047~~) (**EU045**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with these CO limits, combined with the CO PTE from all other units, the CO emissions from the entire source shall be limited to less than one hundred (100) tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not applicable.

NOx

Pursuant to 326 IAC 2-8-4 (FESOP), NOx emissions shall not exceed the emission limits listed below:

- 1) NOx emissions from the RTOs common stack SV014 shall not exceed 12.03 lbs/hr, which is the equivalent to 52.69 tons/yr.

This limit was revised due to the replacement of the one (1) RTO CE012 with two (2) RTOs, identified as CE015 and CE016.

- 2) The NOx emissions from the flare CE018 exhaust associated with the ethanol loading rack (~~EU045~~) (**EU043**) shall not exceed 0.0334 pounds per thousand gallons.
- 3) The boilers (EU036 and EU037) shall only burn natural gas.
- 4) The total input of the natural gas to the boilers (EU036 and EU037) shall not exceed 2545.7 MMCF per twelve (12) consecutive month period, with compliance determined at the end of each month and NOx emissions shall not exceed 30 pounds per MMCF.
- 5) The diesel generator (~~EU046~~) (**EU044**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.
- 6) The diesel fire pump (~~EU047~~) (**EU045**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with these NOx limits, combined with the NOx PTE from all other units, the NOx emissions from the entire source shall be limited to less than one hundred (100) tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not applicable.

SO2

Pursuant to 326 IAC 2-8-4 (FESOP), SO2 emissions shall not exceed the emission limits listed below:

- 1) SO2 emissions from the RTOs common stack SV014 shall not exceed 13.63 lbs/hr, which is the equivalent to 59.70 tons/yr.

This limit was revised due to the replacement of the one (1) RTO CE012 with two (2) RTOs, identified as CE015 and CE016.

- 2) The diesel generator (~~EU046~~) (**EU044**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with these SO2 limits, combined with the SO2 PTE from all other units, the SO2 emissions from the entire source shall be limited to less than one hundred (100) tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not

applicable.

Single HAP (Acetaldehyde)

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) and 326 IAC 2-4.1 (MACT) not applicable, Acetaldehyde emissions shall not exceed the emission limits listed below:

- 1) The Acetaldehyde emissions from Scrubber CE011, controlling the mash preparation process, shall not exceed 0.13 lbs/hr, which is the equivalent to 0.57 tons/yr.

This is a new limit due to the addition of the Mash Preparation Scrubber, which shall control emissions from the existing slurry tank and yeast propagation tank, previously permitted and identified as EU017 and EU024, now identified as EU017 and EU018, respectively.

- 2) The Acetaldehyde emissions from Scrubber CE012, controlling the fermentation process, shall not exceed 0.87 lbs/hr, which is the equivalent to 3.81 tons/yr.

Previously, the fermentation scrubber was identified as CE011, and had the option to exhaust either to the previously permitted RTO which was identified as CE012 or to the atmosphere during RTO downtime. When exhausting to the atmosphere, the scrubber was limited to 6.85 lbs/hr. RTO downtime was limited to 400 hours per twelve consecutive month period. The fermentation scrubber controls emissions from the six (6) fermenters and two (2) beer wells. This limit was changed due to the change in configuration of control.

- 3) The Acetaldehyde emissions from Scrubber CE013, controlling the distillation and dehydration process, shall not exceed 0.62 lbs/hr, which is the equivalent to 2.72 tons/yr.

The distillation and dehydration scrubber's emission limit was changed to accommodate the configuration controls from the other processes.

- 4) The Acetaldehyde emissions from the RTOs common stack SV014 shall not exceed 0.53 lbs/hr, which is the equivalent to 2.32 tons/yr.

This limit was revised due to the replacement of the one (1) RTO CE012 with two (2) RTOs, identified as CE015 and CE016.

- 5) The diesel fire pump (~~EU047~~) (**EU045**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.

Compliance with these Acetaldehyde limits, combined with the Acetaldehyde PTE from all other units, the Acetaldehyde emissions from the entire source shall be limited to less than ten (10) tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program) and 326 IAC 2-2 (PSD) are not applicable.

Combined HAPs

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) and 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) not applicable, HAP emissions shall not exceed the emission limits listed below:

- 1) The HAP emissions from Scrubber CE011, controlling the mash preparation process, shall not exceed 0.15 lbs/hr, which is the equivalent to 0.66 tons/yr. This is a new limit due to the addition of the Mash Preparation Scrubber.

This is a new limit due to the addition of the Mash Preparation Scrubber, which shall

control emissions from the existing slurry tank and yeast propagation tank, previously permitted and identified as EU017 and EU024, now identified as EU017 and EU018, respectively.

- 2) The HAP emissions from Scrubber CE012, controlling the fermentation process, shall not exceed 0.99 lbs/hr, which is the equivalent to 4.34 tons/yr.

Previously, the fermentation scrubber was identified as CE011, and had the option to exhaust either to the previously permitted RTO which was identified as CE012 or to the atmosphere during RTO downtime. When exhausting to the atmosphere, the scrubber was limited to 6.98 lbs/hr. RTO downtime was limited to 400 hours per twelve consecutive month period. The fermentation scrubber controls emissions from the six (6) fermenters and two (2) beer wells. This limit was changed due to the change in configuration of control.

- 3) The HAP emissions from Scrubber CE013, controlling the distillation and dehydration process, shall not exceed 0.75 lbs/hr, which is the equivalent to 3.29 tons/yr.

The distillation and dehydration scrubber's emission limit was changed to accommodate the configuration controls from the other processes.

- 4) The HAP emissions from the RTOs common stack SV014 shall not exceed 1.10 lbs/hr, which is the equivalent to 4.82 tons/yr.

This limit was revised due to the replacement of the one (1) RTO CE012 with two (2) RTOs, identified as CE015 and CE016.

- 5) The denatured ethanol load-out rate associated with the ethanol loading rack (~~EU045~~) **(EU043)** shall not exceed 103,950,000 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- 6) The E-85 load-out rate associated with the ethanol loading rack (~~EU045~~) **(EU043)** shall not exceed 14,300,000 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- 7) The Permittee shall use flare CE018 to control the emissions from the ethanol loading rack when loading denatured ethanol and/or E-85 to trucks.
- 8) The Permittee shall use flare CE018 to control the emissions from the ethanol loading rack when loading denatured ethanol and/or E-85 to railcars.

Compliance with these HAP limits, combined with the limited HAP PTE from other units, the HAP emissions from the entire source shall be limited to less than twenty-five (25) tons per year. Therefore, the requirements of 326 IAC 2-7 (Part 70 Program), 326 IAC 2-2 (PSD), and 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) are not applicable.

(b) PSD Minor Source

This modification to an existing PSD minor stationary source will not change the PSD minor status, because the potential to emit of all attainment regulated pollutants from the entire source will continue to be less than the PSD major source threshold levels. Therefore, pursuant to 326 IAC 2-2, the PSD requirements do not apply.

In order to render the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable, the source shall comply with the following:

Unit	Stack ID	Unit Description	Control ID	PM Emission Limit (lbs/hr)	PM Emission Equivalent (ton/yr)
EU001, EU002, EU003, EU043 , EU044 EU041, EU042	SV001	Grain Receiving, Handling & DDGS Loading	CE001	1.14	4.99
EU004, EU005, EU006, EU007	SV002	Grain Storage Silos	CE002	0.69	3.02
EU008, EU009	SV003	Scalper and Conveyor Transfer / Surge Bin	CE003	0.24	1.05
EU010	SV004	Hammermill #1	CE004	0.41	1.80
EU011	SV005	Hammermill #2	CE005	0.41	1.80
EU012	SV006	Hammermill #3	CE006	0.41	1.80
EU013	SV007	Hammermill #4	CE007	0.41	1.80
EU014	SV008	Hammermill #5	CE008	0.41	1.80
EU015	SV009	Hammermill #6	CE009	0.41	1.80
EU016	SV010	Hammermill #7	CE010	0.41	1.80
*	SV012 SV014	RTOs Common Stack	CE012 CE015 & CE016	12.50 10.80	54.75 47.30
EU039	SV016	DDGS Storage Silo	CE015	0.14	0.61
EU040	SV017	DDGS Silo Bypass to Silo Storage	CE016	0.14	0.61
EU041 EU039	SV018 SV017	DDGS Storage Bldg. / Flat Storage	CE017	0.14	0.61

Note: Emission limits are combined lb/hr limits for all emission units exhausting out of each stack.

Compliance with these PM limits, combined with the PM PTE from other emission units shall limit the PM emissions from the entire source to less than 250 tons per year and therefore, render the requirements of 326 IAC 2-2 (PSD) not applicable.

Federal Rule Applicability Determination

New Source Performance Standards (NSPS)

- (a) Ethanol is one of the chemicals listed in 40 CFR 60.489. Therefore, the new mash preparation process, consisting of existing emission units EU017 and EU018, is subject to the requirements of Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006 (326 IAC 12-1, 40 CFR 60.480a - 60.489a, Subpart VVa).

Nonapplicable portions of the NSPS will not be included in the permit. The ethanol production plant is subject to the following portions of 40 CFR 60, Subpart VVa.

- (1) 40 CFR 60.480a
- (2) 40 CFR 60.481a
- (3) 40 CFR 60.482-1a
- (4) 40 CFR 60.482-2a
- (5) 40 CFR 60.482-3a
- (6) 40 CFR 60.482-4a
- (7) 40 CFR 60.482-5a
- (8) 40 CFR 60.482-6a
- (9) 40 CFR 60.482-7a
- (10) 40 CFR 60.482-8a
- (11) 40 CFR 60.482-9a
- (12) 40 CFR 60.482-10a

- (13) 40 CFR 60.482-11a
- (14) 40 CFR 60.483-1a
- (15) 40 CFR 60.483-2a
- (16) 40 CFR 60.484a
- (17) 40 CFR 60.485a
- (18) 40 CFR 60.486a
- (19) 40 CFR 60.487a
- (20) 40 CFR 60.488a
- (21) 40 CFR 60.489a

The provisions of 40 CFR 60, Subpart A – General Provisions, which are incorporated as 326 IAC 12-1, apply to this source, except when otherwise specified in 40 CFR 60, Subpart VVa.

- (b) There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) included for this proposed revision.

National Emission Standards for Hazardous Air Pollutants (NESHAP)

- (c) The requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Chemical Manufacturing Area Sources, 40 CFR 63.11494, Subpart VVVVVV, are not included for this FESOP, because the source does not process, produce, or use any of the HAPs listed in Table 1 to this subpart in concentrations greater than 0.1 percent for the listed carcinogens or greater than 1.0 percent for the listed noncarcinogens. The source has provided a technical justification with acetaldehyde concentrations from research and development efforts in March 2010 to attest to this determination.
- (d) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs) (326 IAC 14, 326 IAC 20 and 40 CFR Part 63) included for this proposed revision.

Compliance Assurance Monitoring (CAM)

- (e) Pursuant to 40 CFR 64.2, Compliance Assurance Monitoring (CAM) is not included in the permit, because the potential to emit of the source is limited to less than the Title V major source thresholds and the source is not required to obtain a Part 70 or Part 71 permit.

State Rule Applicability Determination

The following state rules are applicable to the proposed revision:

- (a) 326 IAC 2-8-4 (FESOP)
This revision to an existing Title V minor stationary source will not change the minor status, because the potential to emit criteria pollutants from the entire source will still be limited to less than the Title V major source threshold levels. Therefore, the source will still be subject to the provisions of 326 IAC 2-8 (FESOP). See PTE of the Entire Source After Issuance of the FESOP Revision Section above.
- (b) 326 IAC 2-2 (Prevention of Significant Deterioration (PSD))
This modification to an existing PSD minor stationary source will not change the PSD minor status, because the potential to emit of all attainment regulated pollutants from the entire source will continue to be less than the PSD major source threshold levels. Therefore, pursuant to 326 IAC 2-2, the PSD requirements do not apply. See PTE of the Entire Source After Issuance of the FESOP Revision Section above.
- (c) 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP))
The proposed revision is not subject to the requirements of 326 IAC 2-4.1, since the unlimited potential to emit of HAPs from the new/modified units is less than ten (10) tons per year for any

single HAP and less than twenty-five (25) tons per year of a combination of HAPs.

- (d) 326 IAC 2-6 (Emission Reporting)
 Pursuant to 326 IAC 2-6-1, this source is not subject to this rule, because it is not required to have an operating permit under 326 IAC 2-7 (Part 70), it is not located in Lake, Porter, or LaPorte County, and it does not emit lead into the ambient air at levels equal to or greater than 5 tons per year. Therefore, 326 IAC 2-6 does not apply.
- (e) 326 IAC 5-1 (Opacity Limitations)
 Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:
 - (1) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
 - (2) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.
- (f) 326 IAC 6-4 (Fugitive Dust Emissions Limitations)
 Pursuant to 326 IAC 6-4 (Fugitive Dust Emissions Limitations), the source shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4.
- (g) 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations)
 The source shall continue to comply with the requirements of 326 IAC 6-5 since the potential fugitive particulate emissions continue to be greater than 25 tons per year. Pursuant to 326 IAC 6-5, fugitive particulate matter emissions shall be controlled according to the Fugitive Dust Control Plan, which is included as Attachment A to the permit

Grain Handling Process

- (h) 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes)
 - (1) Pursuant to 326 IAC 6-3-2, particulate emissions from each of following operations shall not exceed the pound per hour limit listed in the table below:

Unit ID	Unit Description	Max. Throughput Rate (tons/hr)	Particulate Emission Limit (lbs/hr)
EU001	Three (3) Truck Dump Pits	1,400	82.02
EU002	Grain Conveyor	1,400	82.02
EU003	Grain Elevator	1,400	82.02
EU004	Grain Storage Silo	1,400	82.02
EU005	Grain Storage Silo	1,400	82.02
EU006	Grain Storage Silo	1,400	82.02
EU007	Grain Storage Silo	1,400	82.02

The pounds per hour limitations were calculated using the following equations:

Interpolation and extrapolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P^{0.11} - 40 \quad \text{where } E = \text{rate of emission in pounds per hour; and } P = \text{process weight rate in tons per hour}$$

- (2) Pursuant to 326 IAC 6-3-2(e)(3), when the process weight exceeds 200 tons per hour, the maximum allowable emission may exceed the emission limits shown in the table above, provided the concentration of particulate matter in the gas discharged to the atmosphere is less than 0.10 pounds per 1,000 pounds of gases.

Mash Preparation Process

- (i) 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills)
Pursuant to 326 IAC 8-5-6, the Permittee shall comply with the following:
 - (1) The VOC emissions from the mash preparation process shall be controlled at all times by wet scrubber CE011.
 - (2) The overall control efficiency for the mash preparation wet scrubber (CE011) (including the capture efficiency and adsorption efficiency) shall be at least 98%, or the VOC outlet concentration shall not exceed 20 ppmv.

Evaporation Process, DDGS Dryer and Cooling Process

- (j) 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills),
Pursuant to 326 IAC 8-5-6, the Permittee shall comply with the following:
 - (1) The VOC emissions from the DDGS Dryers (EU034 and EU035), shall be controlled by the RTOs identified as CE015 and CE016 at all times.
 - (2) The overall control efficiency, including the capture efficiency and destruction efficiency, of RTOs CE015 and CE016 shall each be at least 98%, or the VOC outlet concentration shall not exceed 10 ppmv.
- (k) 326 IAC 12 (New Source Performance Standards)
See Federal Rule Applicability Section of this TSD.
- (l) 326 IAC 20 (Hazardous Air Pollutants)
See Federal Rule Applicability Section of this TSD.

Compliance Determination, Monitoring and Testing Requirements
--

- (a) The compliance determination and monitoring requirements applicable to this proposed revision are as follows:

Stack ID / Control ID	Parameter	Frequency	Range	Excursions and Exceedances
CE011	Flow Rate	Daily	3 gal/min	Response Steps
	Pressure Drop		1.0 - 12.0 Inches	
CE012	Flow Rate	Daily	30 100 gal/min	
	Pressure Drop		1.0 - 12.0 Inches	
CE012 CE015	Temperature	Continuous	3 hr avg. > 1400° F	
	Duct Pressure / Fan Amperage	Daily	To be determined during stack test	
CE016	Temperature	Continuous	3 hr avg. > 1400° F	
	Duct Pressure / Fan Amperage	Daily	To be determined during stack test	
SV012 SV014	Visible Emissions	Daily	Normal - Abnormal	
CE014 - and CE017	Pressure Drop	Daily	1.0 - 12.0 Inches	
CE015, CE016, CE017	Visible Emissions	Daily	Normal - Abnormal	
SV016	Visible Emissions	Daily	Normal - Abnormal	
CE018 & SV019 SV018	Visible Emissions	Daily	Normal - Abnormal	
CE018	Flame Presence	When EU045 EU043 is in operation		

- (1) Scrubber CE011 is being added to control the emissions from the new mash preparation process and will be required to monitor flow rate and pressured drops daily.
- (2) Existing scrubber CE012, previously identified as CE011, controlling the emissions from the existing fermentation process, is having the flow rate revised from 30 gallons per minute to 100 gallons per minute.
- (3) The existing RTO (CE012) exhausting through SV012, is being replaced by two RTOs (CE015 and CE016), which will exhaust through common stack SV014. Therefore the same monitoring requirements from CE012 will now be applied to each of the new RTOs.
- (4) The previously permitted DDGS Storage Silo (EU039) and DDGS Silo Bypass (EU040), controlled by baghouses CE015 and CE016, and exhausting to stacks SV016 and SV017 are being removed from the source.
- (5) The Stack ID for enclosed flare CE018, previously identified as SV019, is being re-identified as SV018. The ethanol loadout operation previously identified as EU045, and controlled by CE018, is being re-identified as EU043.
- (6) There are no other revisions to compliance or monitoring conditions.

(b) The testing requirements applicable to this proposed revision are as follows:

Emission Unit / Stack ID	Timeframe for Testing	Pollutant(s)	Frequency of Testing
CE012	Within 60 days after achieving maximum capacity but not later than 180 days after initial start-up	VOC, Acetaldehyde	Once every five (5) years
SV012 SV014 (Common Stack)	180 days after publication of revised test method or within 180 days after initial start-up, whichever is later	PM10, PM2.5	
	Within 60 days after achieving maximum capacity but not later than 180 days after initial start-up	PM, VOC, NOx, CO, Acetaldehyde	
CE015, CE016, CE017	Within 60 days after achieving maximum capacity but not later than 180 days after initial start-up	PM	
	180 days after publication of revised test method or within 180 days after initial start-up, whichever is later	PM10, PM2.5	

- 1) Scrubber CE012 will be added for the new Mash Preparation operations and will be required to be sampled for VOC and Acetaldehyde emissions.
- 2) SV014 is the common stack for new RTO's CE015 and CE016, replacing the previously permitted RTO (CE012) exhausting through SV012, and is required to be sampled for PM, PM10, PM2.5, VOC, NOx, CO, and Acetaldehyde.
- 3) Existing baghouses CE015 and CE016 are being removed since the operations they control; previously permitted DDGS Storage Silo (EU039) and DDGS Storage Silo Bypass (EU040) are being removed from the source.
- 4) There are no other revisions to testing conditions.

Proposed Changes

(a) The following changes listed below are due to the proposed revision. Deleted language appears as ~~strikethrough~~ text and new language appears as **bold** text:

- (1) All references to Putnam County Ethanol, LLC have been removed from the permit and replaced with **POET Biorefining - Cloverdale, LLC**.
- (2) The following permit revisions have been made:

...
A.1 General Information [326 IAC 2-8-3(b)]

 The Permittee owns and operates a stationary ethanol production facility.

...
 General Source Phone Number: (765) 795-3235
 ...

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

 This stationary source consists of the following emission units and pollution control devices:

Grain Handling Process

- (a) ~~Two (2)~~ **Three (3)** truck dump pits, collectively identified as EU001, originally constructed in March 2008, obtaining new operation approval in 2010, with a combined maximum throughput rate of ~~30,000~~ **50,000** bushels of corn per hour, controlled by baghouse CE001, and exhausting through stack SV001.
- (b) One (1) grain handling operation, , originally constructed in March 2008, obtaining new operation approval in 2010, controlled by baghouse CE001, exhausting through stack SV001, and consisting of the following:
 - (1) One (1) grain conveyor, identified as EU002, with a maximum throughput rate of ~~30,000~~ **50,000** bushels of grain per hour.
 - (2) One (1) grain elevator, identified as EU003, with a maximum throughput rate of ~~30,000~~ **50,000** bushels of grain per hour.
- ...
- (g) One (1) DDGS truck loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU043~~ **EU041**, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.
- (h) One (1) DDGS rail loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU044~~ **EU042**, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.

Mash Preparation, Fermentation, Distillation, and Dehydration Process:

- (i) **One (1) mash preparation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 for VOC/HAP controls, exhausting through stack SV011. This process consists of the following:**
 - (1) **One (1) slurry tank, identified as EU017.**
 - (2) **One (1) yeast propagation tank, identified as EU018.**

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

- ~~(j)~~ (j) One (1) fermentation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber ~~CE011~~ and regenerative thermal oxidizer (RTO) CE012 for VOC/HAP controls, exhausting through stack ~~SV011 or~~ SV012. This process consists of the following:
 - ~~(1)~~ ~~One (1) slurry tank, identified as EU017~~
 - ~~(2)~~ ~~One (1) yeast propagation tank, identified as EU024.~~
 - ~~(3)~~ (1) Six (6) fermenters, identified as ~~EU018~~ EU019 through ~~EU023~~ EU024.
 - ~~(4)~~ (2) Two (2) beer wells, identified as EU025 and EU026.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

~~Note: The RTO must occasionally be temporarily shut down for maintenance or other operational reasons. In this event, the DDGS dryers and fluid bed cooler will be shut down, however, the fermentation system will continue to be operated in normal mode. The emissions from these sources will be controlled by the wet scrubber CE011 only and vent through stack SV011.~~

- ~~(j)~~(k) One (1) distillation and dehydration process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum ethanol production of 72,000 gallons per hour, using wet scrubber CE013 for VOC control, exhausting through stack SV013. This process consists of the following:
...
- ~~(k)~~(l) One (1) stillage process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum DDGS production of 567,648,0000 gallons per year; using a ~~42 MMBtu/hr regenerative thermal oxidizer CE012~~ **two (2) 30 MMBtu/hr regenerative thermal oxidizers (CE015 & CE016)** for VOC control, approved for construction in 2010, exhausting through stack ~~SV012~~ **SV014**. This process consists of the following:
...
- ~~(l)~~(m) One (1) DDGS fluid bed cooler, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU038, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE014) for particulate control, with emissions vented to and controlled by RTOs ~~CE012~~ **CE015 & CE016**, and exhausting to stack ~~SV012~~ **SV014**.
...
- ~~(m)~~ One (1) DDGS storage silo, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU039, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE015) for particulate control, and exhausting to stack SV016.
- ~~(n)~~ One (1) DDGS storage silo bypass to flat storage with filter receiver, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU040, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE016) for particulate control, and exhausting to stack SV017.
- ~~(o)~~(n) One (1) DDGS storage building/flat storage, originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU044~~ **EU039**, using a baghouse (CE017) for particulate control, and exhausting to stack ~~SV018~~ **SV017**.
...
- ~~(p)~~(o) One (1) ethanol loadout rack (two rail loadouts utilizing top loading only and one truck loadout utilizing submerged loading only), originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU045~~ **EU043**, with a maximum throughput rate of 118.25 million gallons per year. The loadout process is controlled by enclosed flare CE018, which is fueled by natural gas and has a maximum heat input capacity of 6.8 MMBtu per hour, and exhausting through stack ~~SV019~~ **SV018**.
...
- ~~(q)~~(p) Two (2) natural gas fired boilers, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU036 and EU037, each with a rated heat

capacity of 145.3 MMBtu/hr, exhausting to stacks ~~SV014~~ **SV015** and ~~SV015~~ **SV016**.

...

- ~~(p)~~ **(q)** One (1) diesel generator, approved for construction in 2010, identified as ~~EU046~~ **EU044**, with a rated capacity of 2,000 KW, exhausting to ~~SV020~~ **SV019**.

...

A.3 Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities:

...

- (h) Stationary fire pumps, including one (1) diesel fire pump, identified as ~~EU047~~ **EU045**, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack ~~SV024~~ **SV020**.

...

SECTION D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emissions Unit Description:

Grain and Handling Process:

- (a) ~~Two (2)~~ **Three (3)** truck dump pits, collectively identified as EU001, originally constructed in March 2008, obtaining new operation approval in 2010, with a combined maximum throughput rate of ~~30,000~~ **50,000** bushels of corn per hour, controlled by baghouse CE001, and exhausting through stack SV001.

- (b) One (1) grain handling operation, originally constructed in March 2008, obtaining new operation approval in 2010, controlled by baghouse CE001, exhausting through stack SV001, and consisting of the following:

- (1) One (1) grain conveyor, identified as EU002, with a maximum throughput rate of ~~30,000~~ **50,000** bushels of grain per hour.

- (2) One (1) grain elevator, identified as EU003, with a maximum throughput rate of ~~30,000~~ **50,000** bushels of grain per hour.

...

- (g) One (1) DDGS truck loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU043~~ **EU041**, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.

- (h) One (1) DDGS rail loadout process, originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU044~~ **EU042**, with a maximum throughput rate of 400 tons of DDGS per hour, using a baghouse (CE001) for particulate control, and exhausting to stack SV001.

(The information describing the process contained in this emissions unit description box is descriptive information and does not constitute enforceable conditions.)

...

D.1.1 FESOP and PSD Limits [326 IAC 2-8-4] [326 IAC 2-2]

- (a) In order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM emissions from the following units shall not exceed the emission limits listed in the table below:

Unit ID	Stack ID	Unit Description	Baghouse ID	PM Emission Limit (lbs/hr)
EU001, EU002, EU003, EU043 , EU044 EU041, EU042	SV001	Grain Receiving, Handling & DDGS Loading	CE001	1.14 (Combined)

...

- (b) Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM10 and PM2.5 emissions from the following units shall not exceed the emission limits listed in the table below:

Unit ID	Stack ID	Unit Description	Baghouse ID	PM10 Emission Limit (lbs/hr)	PM2.5 Emission Limit (lbs/hr)
EU001, EU002, EU003, EU043 , EU044 EU041, EU042	SV001	Grain Receiving, Handling & DDGS Loading	CE001	1.14 (Combined)	1.14 (Combined)

...

D.1.2 Particulate Emission Limitations [326 IAC 6-3-2]

- (a) Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), particulate emissions from each of following operations shall not exceed the pound per hour limit listed in the table below:

Unit ID	Stack ID	Unit Description	Max. Throughput Rate (tons/hr)	Particulate Emission Limit (lbs/hr)
EU001	SV001	Two (2) Three (3) Truck Dump Pits	840 1,400	75.35 82.02
EU002		Grain Conveyor	840 1,400	75.35 82.02
EU003		Grain Elevator	840 1,400	75.35 82.02
EU043		DDGS Truck Loading	400	66.31
EU044		DDGS Rail Loading	400	66.31
EU004	SV002	Grain Storage Silo	840 1,400	75.35 82.02
EU005		Grain Storage Silo	840 1,400	75.35 82.02
EU006		Grain Storage Silo	840 1,400	75.35 82.02
EU007		Grain Storage Silo	840 1,400	75.35 82.02

...

D.1.4 Particulate Control

- (a) In order to comply with Conditions D.1.1(a) and (b), and D.1.2, the baghouses for particulate control shall be in operation and control emissions from the emission units at all times that the emission units are in operation as listed in the table below, when these units are in operation:

Unit ID	Unit Description	Baghouse ID
EU001, EU002, EU003, EU043 , EU044 EU041, EU042	Grain Receiving, Handling & DDGS Loading	CE001

...

D.1.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11]

- (a) In order to demonstrate compliance with Conditions D.1.1(a) and D.1.2, the Permittee shall perform testing within sixty (60) days after achieving maximum capacity but not later

than one hundred eighty (180) days after initial start-up according to what is listed below, and utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

- (1) PM testing for baghouse CE001, which shall be controlling emissions from the grain receiving and handling, (EU001 through EU003) and DDGS loading (~~EU042 and EU044~~) (**EU041 and EU042**).

...

- (b) In order to demonstrate compliance with Conditions D.1.1(b), the Permittee shall perform testing within one hundred eighty (180) days of publication of the new or revised condensible PM test method(s) referenced in the U.S. EPA's Final Rule for Implementation of the New Source Review (NSR) Program for Particulate Matter Less Than 2.5 Micrometers (PM2.5), signed on May 8th, 2008 or within 180 days after initial start-up, whichever is later. This testing shall be conducted utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing. PM10 and PM2.5 includes filterable and condensible PM.

- (1) PM10 and PM2.5 testing for baghouse CE001, which shall be controlling emissions from the grain receiving and handling, (EU001 through EU003) and DDGS loading (~~EU042 and EU044~~) (**EU041 and EU042**).

...

D.1.6 Visible Emissions Notations

- (a) Visible emission notations of the baghouse stack exhausts (stacks SV001 through ~~SV016~~ **SV010**) shall be performed once per day during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.

...

D.1.7 Baghouse Parametric Monitoring

The Permittee shall record the pressure drop across the baghouses (CE001 through CE010) used in conjunction with the grain receiving, handling, DDGS loading operations (EU001 through EU003, ~~EU043, and EU044~~ **EU041, and EU042**), the grain storage silos (EU004 through EU007), scalper and conveyor transfer / surge bin (EU008 and EU009), and hammermills (EU010 through EU016), at least once per day when these units are in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 0.5 to 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Response to Excursions or Exceedances. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

...

SECTION D.2 EMISSIONS UNIT OPERATION CONDITIONS - **Mash Preparation**, Fermentation, Distillation, and Dehydration Process

Facility Description [326 IAC 2-8-4(10)]:

Mash Preparation, Fermentation, Distillation, and Dehydration Process:

(i) **One (1) mash preparation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 for VOC/HAP controls, exhausting through stack SV011. This process consists of the following:**

- (1) **One (1) slurry tank, identified as EU017.**
- (2) **One (1) yeast propagation tank, identified as EU018.**

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

~~(j)~~ One (1) fermentation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 and regenerative thermal oxidizer (RTO) CE012 for VOC/HAP controls, exhausting through stack SV011 or SV012. This process consists of the following:

- ~~(1)~~ One (1) slurry tank, identified as EU017
- ~~(2)~~ One (1) yeast propagation tank, identified as EU024.
- ~~(3)~~ (1) Six (6) fermenters, identified as EU018 EU019 through EU023 EU024.
- ~~(4)~~ (2) Two (2) beer wells, identified as EU025 and EU026.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

~~Note: The RTO must occasionally be temporarily shut down for maintenance or other operational reasons. In this event, the DDGS dryers and fluid bed cooler will be shut down, however, the fermentation system will continue to be operated in normal mode. The emissions from these sources will be controlled by the wet scrubber CE011 only and vent through stack SV011.~~

~~(k)~~ One (1) distillation and dehydration process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum ethanol production of 72,000 gallons per hour, using wet scrubber CE013 for VOC control, exhausting through stack SV013. This process consists of the following:

- (1) One degas column, identified as EU027.
- (2) One (1) beer stripper, identified as EU028.
- (3) One (1) rectifier column, identified as EU029.

- (4) One (1) side stripper, identified as EU030.
- (5) One (1) set of three (3) molecular sieve, identified as EU031.
- (6) One (1) set of three (3) evaporators, identified as EU032.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

...

D.2.1 FESOP VOC and HAP Emissions [326 IAC 2-2] [326 IAC 2-8-4] [326 IAC 2-4.1]

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) and 326 IAC 2-4.1 (Major Sources of Hazardous Air Pollutants (HAP)) not applicable:

(a) Mash Preparation Process:

- (1) VOC emissions from scrubber CE011 shall not exceed 1.31 lb/hr.**
- (2) Combined HAP emissions from scrubber CE011 shall not exceed 0.15 lb/hr.**
- (3) Acetaldehyde emissions from scrubber CE011 shall not exceed 0.13 lb/hr.**

(a)(b) Fermentation Process:

- ~~(1) When utilizing wet scrubber CE011 and RTO CE012 (exhausting to SV012):~~
 - ~~(i) VOC emissions shall not exceed 11.10 lbs/hr for stack SV012.~~
 - ~~(ii) Acetaldehyde emissions shall not exceed 1.00 lbs/hr for stack SV012.~~
 - ~~(iii) Total HAP emissions shall not exceed 1.96 lbs/hr for stack SV012.~~
- ~~(2) When RTO is shut down and process is only utilizing wet scrubber CE011 (exhausting to SV011):~~
 - ~~(i) VOC emissions from scrubber CE011 shall not exceed 32.9 lb/hr.~~
 - ~~(ii) Acetaldehyde emissions from scrubber CE011 shall not exceed 6.85 lb/hr.~~
 - ~~(iii) Combined HAP emissions from scrubber CE011 shall not exceed 6.98 lb/hr.~~
 - ~~(iv) The RTO (CE012) downtime shall not exceed 400 hours per twelve (12) consecutive month period.~~
- (1) VOC emissions from scrubber CE012 shall not exceed 8.69 lb/hr.**
- (2) Combined HAP emissions from scrubber CE012 shall not exceed 0.99 lb/hr.**
- (3) Acetaldehyde emissions from scrubber CE012 shall not exceed 0.87 lb/hr.**

~~(b)~~(c) Distillation and Dehydration Process:

- (1) VOC emissions from scrubber CE013 shall not exceed ~~4.44~~ **0.81** lb/hr.
- (2) Combined HAP emissions from scrubber CE013 shall not exceed ~~0.97~~ **0.75** lb/hr.
- (3) Acetaldehyde emissions from scrubber CE013 shall not exceed ~~0.84~~ **0.62** lb/hr.
- ...

D.2.2 VOC Emissions [326 IAC 8-5-6]

Pursuant to 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills), the Permittee shall comply with the following:

- (a) The VOC emissions from the mash preparation process shall be controlled at all times by wet scrubber CE011.**
- (b) The overall control efficiency for the mash preparation wet scrubber (CE011) (including the capture efficiency and adsorption efficiency) shall be at least 98%, or the VOC outlet concentration shall not exceed 20 ppmv.**
- ~~(a)~~(c) The VOC emissions from the fermentation process shall be controlled at all times by wet scrubber ~~CE014~~ **CE012**.
- ~~(b)~~(d) The overall control efficiency for the fermentation wet scrubber (~~CE014~~) **(CE012)** (including the capture efficiency and adsorption efficiency) shall be at least 98%, or the VOC outlet concentration shall not exceed 20 ppmv.
- ~~(c)~~(e) The VOC emissions from the distillation and dehydration process shall be controlled by wet scrubber CE013.
- ~~(d)~~(f) The overall control efficiency for the distillation and dehydration wet scrubber (CE013) (including the capture efficiency and adsorption efficiency) shall be at least 98%, or the VOC outlet concentration shall not exceed 20 ppmv.
- ...

D.2.4 VOC and HAP Control

In order to comply with Conditions D.2.1 and D.2.2, the following shall apply:

- (a) The wet scrubber CE011 shall be in operation and control emissions from the mash preparation process at all times that this process is in operation.**
- ~~(a)~~(b) The wet scrubber ~~CE014~~ **CE012** shall be in operation and control emissions from the fermentation process at all times that this process is in operation.
- ~~(b)~~(c) The wet scrubber CE013 shall be in operation and control emissions from the distillation and dehydration process at all times that this process is in operation.

D.2.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

In order to demonstrate compliance with Conditions D.2.1 and D.2.2, the Permittee shall perform VOC (including emission rate, destruction efficiency, and capture efficiency) and acetaldehyde testing for scrubbers CE011, **CE012**, and CE013 within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in

accordance with Section C - Performance Testing.

D.2.6 Parametric Monitoring [326 IAC 8-5-6]

- (a) The Permittee shall monitor and record the flow rate of scrubbers CE011, **CE012**, and CE013 at least once per day when the associated processes are in operation. When for any one reading, the flow rate of any scrubber is less than the normal minimum stated in the table below, or a minimum established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. A flow rate that is below the above mentioned minimum is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

Scrubber ID	Associated Process	Minimum Flow Rate
CE011	Fermentation Mash Preparation	30 3 gallons per minute
CE012	Fermentation	100 gallons per minute
CE013	Distillation & Dehydration	30 gallons per minute

- (b) The Permittee shall monitor and record the pressure drop across the scrubbers CE011, **CE012**, and CE013 at least once per day when the associated processes are in operation. When for any one reading, the pressure drop across a scrubber is outside the normal range of 1.0 and 12.0 inches of water, or a minimum established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C - Response to Excursions or Exceedances. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

...

D.2.8 Record Keeping Requirements

- (a) ~~To document compliance with Condition D.2.1(a)(2)(iv), the Permittee shall maintain monthly records of the number of hours RTO CE012 is shut-down.~~
- (b)(a) To document compliance with Condition D.2.6, the Permittee shall maintain once per day records of the flow rate and pressure drop for scrubbers CE011, **CE012**, and CE013 during normal operation. The Permittee shall include in its daily record when a flow rate reading or pressure drop reading is not taken and the reason for the lack of flow rate reading or pressure drop reading (e.g. the process did not operate that day).
- (c)(b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2.9 Reporting Requirements

~~A quarterly summary of the information to document compliance with Condition D.2.1(a)(2)(iv) shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or its equivalent, within thirty (30) days after the end of the six (6) month period being reported. The report submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-4.~~

SECTION D.3 EMISSIONS UNIT OPERATION CONDITIONS - Evaporation Process, DDGS Dryer and Cooling Process

Facility Description [326 IAC 2-8-4(10)]:

Evaporation Process, DDGS Dryer, & Cooling Process:

~~(k)~~(l) One (1) stillage process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum DDGS production of 567,648,0000 gallons per year; using a ~~42 MMBtu/hr regenerative thermal oxidizer CE012~~ **two (2) 30 MMBtu/hr regenerative thermal oxidizers (CE015 & CE016)** for VOC control, approved for construction in 2010, exhausting through stack ~~SV012~~ **SV014**. This process consists of the following:

- (1) One (1) set of four (4) centrifuges, identified as EU033, originally constructed in March 2008.
- (2) Two (2) natural gas fired DDGS dryers, identified as EU034 and EU035, originally constructed in March 2008, each with a maximum heat input rate of 83 MMBtu/hr, and each with a total maximum throughput rate of 25 tons of DDGS per hour.

~~(h)~~(m) One (1) DDGS fluid bed cooler, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU038, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE014) for particulate control, with emissions vented to and controlled by RTOs ~~CE012~~ **CE015 & CE016**, and exhausting to stack ~~SV012~~ **SV014**.

Note: The RTO must occasionally be temporarily shut down for maintenance or other operational reasons. In this event, the DDGS dryers and fluid bed cooler will be shut down.

~~(m)~~ One (1) DDGS storage silo, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU039, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE015) for particulate control, and exhausting to stack SV016.

~~(n)~~ One (1) DDGS storage silo bypass to flat storage with filter receiver, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU040, with a maximum throughput rate of 40 tons of DDGS per hour, using a baghouse (CE016) for particulate control, and exhausting to stack SV017.

~~(o)~~(n) One (1) DDGS storage building/flat storage, originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU044~~ **EU039**, using a baghouse (CE017) for particulate control, and exhausting to stack ~~SV048~~ **SV017**.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

D.3.1 PSD Minor Limits [326 IAC 2-2]

(a) In order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits for the RTOs ~~(CE012)~~ **(CE015 & CE016)** which ~~is~~ **are** used to control emissions from the DDGS dryers (EU034 and EU035), the DDGS fluid bed cooler (EU038), and the set of centrifuges (EU033):

(1) PM emissions shall not exceed ~~12.50~~ **10.80** lbs/hr for stack ~~SV012~~ **SV014**.

(b) In order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM emissions from the following units shall not exceed the emission limits listed in the table below:

Unit	Stack ID	Unit Description	Control ID	PM Emission Limit (lbs/hr)
EU039	SV016	DDGS Storage Silo	CE015	0.14
EU040	SV017	DDGS Silo Bypass to Silo Storage	CE016	0.14
EU044 EU039	SV018 SV017	DDGS Storage Bldg. / Flat Storage	CE017	0.14

...

D.3.2 FESOP Limits [326 IAC 2-8-4]

(a) Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits for the RTOs (~~CE012~~) **(CE015 and CE016)** which ~~is~~ **are** used to control emissions from the DDGS dryers (EU034 and EU035), ~~and~~ the DDGS **fluid bed** cooler (EU038), ~~and the set of centrifuges (EU033)~~:

- (1) PM10 emissions shall not exceed ~~9.68~~ **10.80** lbs/hr for stack ~~SV012~~ **SV014**.
- (2) PM2.5 emissions shall not exceed ~~9.68~~ **10.80** lb/hrs for stack ~~SV012~~ **SV014**.
- (3) VOC emissions shall not exceed ~~11.10~~ **4.83** lbs/hr for stack ~~SV012~~ **SV014**.
- (4) CO emissions shall not exceed ~~15.70~~ **15.10** lbs/hr for stack ~~SV012~~ **SV014**.
- (5) SO2 emissions shall not exceed 13.63 lbs/hr for stack ~~SV012~~ **SV014**.
- (6) NOx emissions shall not exceed 12.03 lbs/hr for stack ~~SV012~~ **SV014**.
- (7) Acetaldehyde emissions shall not exceed ~~4.00~~ **0.53** lbs/hr for stack ~~SV012~~ **SV014**.
- (9) Total HAP emissions shall not exceed ~~4.97~~ **1.10** lbs/hr for stack ~~SV012~~ **SV014**.

(b) Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, PM10 and PM2.5 emissions from the following units shall not exceed the emission limits listed in the table below:

Unit ID	Stack ID	Unit Description	Control ID	PM10 Emission Limit (lbs/hr)	PM2.5 Emission Limit (lbs/hr)
EU039	SV016	DDGS Storage Silo	CE015	0.14	0.14
EU040	SV017	DDGS Silo Bypass to Silo Storage	CE016	0.14	0.14
EU044 EU039	SV018 SV017	DDGS Storage Bldg. / Flat Storage	CE017	0.14	0.14

...

D.3.3 VOC Emissions [326 IAC 8-5-6]

Pursuant to 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills), the Permittee shall comply with the following:

- (a) The VOC emissions from the DDGS Dryers (EU034 and EU035), shall be controlled by the RTOs identified as ~~CE012~~ **CE015 and CE016** at all times.
- (b) The overall control efficiency, including the capture efficiency and destruction efficiency, of ~~the CE012 RTOs CE015 and CE016~~ shall each be at least 98%, or the VOC outlet

concentration shall not exceed 10 ppmv.

D.3.4 Particulate Emission Limitations [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), particulate emissions from each of following operations shall not exceed the pound per hour limit listed in the table below:

Unit ID	Unit Description	Max. Throughput Rate (tons/hr)	Particulate Emission Limit (lbs/hr)
EU034	DDGS Dryer	25	35.43
EU035	DDGS Dryer	25	35.43
EU038	DDGS Cooler	40	42.53
EU039	DDGS Storage Silo	40	42.53
EU040	DDGS Storage Silo Bypass	40	42.53
EU044 EU039	DDGS Storage Bldg. / Flat Storage	40	42.53

...

D.3.6 VOC and HAP Control

In order to comply with Conditions ~~D.3.1~~ **D.3.2** and D.3.3, the thermal oxidizers ~~CE012~~ **CE015 and CE016** shall be in operation and control emissions from the DDGS dryers (EU034 and EU035) and the DDGS **fluid bed** cooler (EU038), at all times that these units are in operation.

D.3.7 Particulate Control

...

(b) In order to comply with the Conditions in D.3.1(b), D.3.2(b), and D.3.4, the baghouses (~~CE015, CE016, and CE017~~) for particulate control shall be in operation and control emissions from the ~~DDGS Storage Silo (EU039), DDGS Silo Bypass (EU040), and DDGS Storage Building / Flat Storage (EU044)~~ **(EU039)** at all times ~~these this units are is~~ in operation.

...

D.3.8 Testing Requirements [326 IAC 2-8-5(a)(1),(4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

In order to demonstrate compliance with Conditions D.3.1, D.3.2, D.3.3, and D.3.4, the Permittee shall perform:

- (a) PM testing for the RTO **common** stack (~~SV012~~) **(SV014)** within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.
- (b) PM10 and PM2.5 testing for the RTO **common** stack (~~SV012~~) **(SV014)**, within one hundred eighty (180) days of publication of the new or revised condensible PM test method(s) referenced in the U.S. EPA's Final Rule for Implementation of the New Source Review (NSR) Program for Particulate Matter Less Than 2.5 Micrometers (PM2.5), signed on May 8th, 2008 or within 180 days after initial start-up, whichever is later. This testing shall be conducted utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing. PM10 and PM2.5 includes filterable and condensible PM.
- (c) PM testing for the ~~DDGS Storage Silo (EU039), DDGS Silo Bypass (EU040), and DDGS Storage Building / Flat Storage (EU044)~~ **(EU039)** within sixty (60) days after achieving

maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

- (d) PM10 and PM2.5 testing for the ~~DDGS Storage Silo (EU039), DDGS Silo Bypass (EU040), and DDGS Storage Building / Flat Storage (EU041)~~ **(EU039)**, within one hundred eighty (180) days of publication of the new or revised condensible PM test method(s) referenced in the U.S. EPA's Final Rule for Implementation of the New Source Review (NSR) Program for Particulate Matter Less Than 2.5 Micrometers (PM2.5), signed on May 8th, 2008 or within 180 days of start-up, whichever is later. This testing shall be conducted utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing. PM10 and PM2.5 includes filterable and condensible PM.
- (e) VOC (including emission rate, destruction efficiency, and capture efficiency), NOx, CO, and Acetaldehyde testing for the RTO **common** stack (~~SV012~~) **(SV014)** within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of the most recent valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

...

D.3.9 Visible Emissions Notations

- (a) Visible emission notations of the stack exhausts from ~~SV012, SV016, SV017, and SV018~~ **SV014 and SV017**, shall be performed once per day during normal daylight operations. A trained employee or a trained contractor shall record whether emissions are normal or abnormal.

...

D.3.10 Baghouse Parametric Monitoring

The Permittee shall record the pressure drop across the baghouses CE014, CE015, CE016, and CE017 used in conjunction with the DDGS cooling operation (EU038), ~~DDGS Storage Silo (EU039), DDGS Silo Bypass (EU040), and DDGS Storage Building / Flat Storage (EU041)~~ **(EU039)** at least once per day when the emissions units are in operation. When for any one reading, the pressure drops across the baghouses are outside the normal range of 0.5 to 6.0 inches of water or a range established during the most recent stack tests, the Permittee shall take reasonable response steps in accordance with Section C- Response to Excursions or Exceedances. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Response to Excursions or Exceedances shall be considered a deviation from this permit.

...

D.3.12 Thermal Oxidation Temperature [326 IAC 8-5-6]

- (a) A continuous monitoring system shall be calibrated, maintained, and operated on **both** the RTOs (~~CE012~~) **(CE015 and CE016)** for measuring operating temperature. For the purpose of this condition, continuous means no less than once per minute. The output of this system shall be recorded as 3-hour average. From the date of issuance of this permit until the approved stack test results are available, the Permittee shall operate ~~the~~ **Both RTOs (CE012) (CE015 and CE016)** at or above the 3-hour average temperature of 1,400°F.

- (b) The Permittee shall determine the 3-hour average temperatures from the most recent valid stack test that demonstrates compliance with limits in Conditions D.3.2 and D.3.3 as approved by IDEM.
- (c) On and after the date the approved stack test results are available, the Permittee shall operate ~~the both RTOs (CE012)~~ **(CE015 and CE016)** at or above the 3-hour average temperature as observed during the compliant stack test.

D.3.13 Parametric Monitoring [326 IAC 8-5-6]

- ...
- (b) The duct pressure or fan amperage shall be observed at least once per day when the RTOs ~~is~~ **are** in operation. On and after the date the approved stack test results are available, the duct pressure or fan amperage shall be maintained within the normal range as established in most recent compliant stack test.
- ...

D.3.14 Record Keeping Requirements

- (a) To document compliance with Condition D.3.9, the Permittee shall maintain records of once per day visible emission notations of stacks ~~SV012, SV015, SV016, and SV017~~ **SV014 and SV017**. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g. the process did not operate that day).
 - (b) To document compliance with Condition D.3.10, the Permittee shall maintain once per day records of the pressure drop across the baghouses ~~CE014, CE015, CE016, and CE017~~. The Permittee shall include in its daily record when a pressure drop reading is not taken and the reason for the lack of the pressure drop reading (e.g. the process did not operate that day).
 - (c) To document compliance with Condition D.3.12, the Permittee shall maintain continuous temperature records for the RTOs ~~(CE012)~~ **(CE015 and CE016)** and the 3-hour average temperature used to demonstrate compliance during the most recent compliant stack test.
 - (d) To document compliance with Condition D.3.13, the Permittee shall maintain daily records of the duct pressure or fan amperage for the RTOs ~~(CE012)~~ **(CE015 and CE016)**. The Permittee shall include in its daily record when a duct pressure reading or fan amperage reading is not taken and the reason for the lack of a duct pressure reading or fan amperage reading (e.g. the process did not operate that day).
- ...

SECTION D.4 EMISSIONS UNIT OPERATION CONDITIONS - Denatured Ethanol Loading Racks

Facility Description [326 IAC 2-8-4(10)]:

Denatured Ethanol Storage and Loadout Racks:

- ~~(p)~~**(o)** One (1) ethanol loadout rack (two rail loadouts utilizing top loading only and one truck loadout utilizing submerged loading only), originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU045~~ **EU043**, with a maximum throughput rate of 118.25 million gallons per year. The loadout process is controlled by enclosed flare CE018, which is fueled by natural gas and has a maximum heat input capacity of 6.8 MMBtu per hour, and exhausting through stack ~~SV019~~ **SV018**.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

...

D.4.1 FESOP Limits [326 IAC 2-8-4] [326 IAC 2-2]

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits for the ethanol loading rack (EU045):

- (a) The total combined load-out rate of denatured ethanol and E-85 associated with the ethanol loading rack (~~EU045~~) (**EU043**) shall not exceed 118,250,000 gallons per twelve consecutive month period, with compliance determined at the end of each month.
- (b) The E-85 load-out rate associated with the ethanol loading rack (~~EU045~~) (**EU043**) shall not exceed 14,300,000 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.
- (c) VOC emissions associated with the loading rack (~~EU045~~) (**EU043**) shall not exceed 0.131 pounds per thousand gallons.
- (d) The NOx emissions associated with the ethanol loading rack (~~EU045~~) (**EU043**) shall not exceed 0.0334 pounds per thousand gallons.
- (e) The CO emissions associated with the ethanol loading rack (~~EU045~~) (**EU043**) shall not exceed 0.084 pounds per thousand gallons.

...

D.4.2 VOC Emissions [326 IAC 8-5-6]

Pursuant to 326 IAC 8-5-6 (Fuel Grade Ethanol Production at Dry Mills), the Permittee shall comply with the following:

- (a) The Permittee shall use flare CE018 to control the emissions from the ethanol loading rack (~~EU045~~) (**EU043**) when loading denatured ethanol and/or E-85 to trucks.
- (b) The Permittee shall use flare CE018 to control emissions from the ethanol loading rack (~~EU045~~) (**EU043**) when loading denatured ethanol and/or E-85 to railcars.

...

D.4.4 VOC Control

In order to comply with Conditions D.4.1 and D.4.2, the enclosed flare CE018 shall be in operation and control emissions from the ethanol loading rack (~~EU045~~) (**EU043**) at all times when denatured ethanol and/or E-85 is being loaded to trucks or railcars.

...

D.4.5 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11] [326 IAC 8-5-6]

In order to demonstrate compliance with Conditions D.4.1(e), (f), and (g), and D.4.2(c) associated with the ethanol loading rack (~~EU045~~) (**EU043**), the Permittee shall perform VOC (including emission rate, destruction efficiency, and capture efficiency), CO, and NOx testing for enclosed flare CE018 within sixty (60) days after achieving maximum capacity but not later than one hundred eighty (180) days after initial start-up, utilizing methods as approved by the Commissioner. These tests shall be repeated at least once every five (5) years from the date of

the last valid compliance demonstration. Testing shall be conducted in accordance with Section C - Performance Testing.

...

D.4.6 Visible Emissions Notations

- (a) Visible emission notations of the flare (CE018) stack exhaust (~~SV019~~) (**SV018**) shall be performed once per day during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.

...

D.4.7 Flare Pilot Flame [326 IAC 8-5-6]

In order to comply with Conditions D.4.1 and D.4.2, the Permittee shall monitor the presence of a flare pilot flame using a thermocouple or any other equivalent device to detect the presence of a flame when the ethanol loading rack (~~EU045~~) (**EU043**) is in operation and loading denatured ethanol and/or E-85 to trucks or railcars.

...

D.4.8 Record Keeping Requirements

- (a) To document compliance with Condition D.4.1(a), the Permittee shall maintain monthly records of the amount of denatured ethanol and E-85 loaded out by truck and rail at the ethanol loading rack (~~EU045~~) (**EU043**).
- (b) To document compliance with Condition D.4.1(b), the Permittee shall maintain monthly records of the amount of E-85 loaded out by truck and rail at the ethanol loading rack (~~EU045~~) (**EU043**).
- ~~(b)~~(c) To document compliance with Condition D.4.6, the Permittee shall maintain records of once per day visible emission notations of stack ~~SV019~~ **SV018**. The Permittee shall include in its daily record when a visible emission notation is not taken and the reason for the lack of visible emission notation (e.g. the process did not operate that day).
- ~~(c)~~(d) To document compliance with Condition D.4.7, the Permittee shall maintain records of temperature or other parameters sufficient to demonstrate the presence of a pilot flame when the ethanol loading rack is in operation.
- ~~(d)~~(e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

...

SECTION D.5 - EMISSIONS UNIT OPERATION CONDITIONS - Natural Gas Fired Combustion Units

Facility Description [326 IAC 2-8-4(10)]:

Natural Gas Fired Combustion Units:

- ~~(q)~~(p) Two (2) natural gas fired boilers, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU036 and EU037, each with a rated heat capacity of 145.3 MMBtu/hr, exhausting to stacks ~~SV014~~ **SV015** and ~~SV015~~ **SV016**.

Under NSPS, 40 CFR 60, Subpart Db, these units are considered affected facilities.

...

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

...

SECTION D.6 - EMISSIONS UNIT OPERATION CONDITIONS - Diesel Fired Combustion Units

Facility Description [326 IAC 2-8-4(10)]:

- (q) One (1) diesel generator, approved for construction in 2010, identified as ~~EU046~~ **EU044**, with a rated capacity of 2,000 KW, exhausting to ~~SV020~~ **SV019**.

Under NSPS, Subpart IIII, this unit is considered an affected source.

Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

Insignificant Activities:

- (h) Stationary fire pumps, including one (1) diesel fire pump, identified as ~~EU047~~ **EU045**, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack ~~SV021~~ **SV020**.

Under NSPS, Subpart IIII, this unit is considered an affected source.

Under NESHAP, Subpart ZZZZ, this unit is considered an affected source.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.6.1 FESOP Limits [326 IAC 2-8-4] [326 IAC 2-2]

Pursuant to 326 IAC 2-8-4 (FESOP), and in order to render the requirements of 326 IAC 2-2 (PSD) not applicable, the Permittee shall comply with the following emission limits:

- (a) The diesel generator (~~EU046~~) (**EU044**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.
- (b) The diesel fire pump (~~EU047~~) (**EU045**) shall be limited to 250 operating hours per twelve (12) consecutive month period with compliance determined at the end of each month.

...

D.6.2 Record Keeping Requirements

- (a) To document compliance with Condition D.6.1(a), the Permittee shall maintain records of the number of hours that the diesel generator (~~EU046~~) (**EU044**) operates each month.
- (b) To document compliance with Condition D.6.1(b), the Permittee shall maintain records of the number of hours that the diesel fire pump (~~EU047~~) (**EU045**) operates each month.

D.6.3 Reporting Requirements

The monthly hours of operation of the diesel generator (~~EU046~~) (**EU044**) and diesel fire pump (~~EU047~~) (**EU045**) shall be submitted quarterly to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or its equivalent, within thirty (30) days after the end of the six (6) month period being reported. The report submitted by the Permittee does require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1.

...

SECTION E.1 FACILITY OPERATION CONDITIONS - 40 CFR 60, Subpart Db - Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units

Facility Description [326 IAC 2-8-4(10)]:

~~(p)~~**(p)** Two (2) natural gas fired boilers, originally constructed in March 2008, obtaining new operation approval in 2010, identified as EU036 and EU037, each with a rated heat capacity of 145.3 MMBtu/hr, exhausting to stacks ~~SV014~~ **SV015** and ~~SV015~~ **SV016**.

Under NSPS, 40 CFR 60, Subpart Db, these units are considered affected facilities.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

...

SECTION E.3 FACILITY OPERATION CONDITIONS - 40 CFR 60, Subpart VVa - Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006

Facility Description [326 IAC 2-8-4(10)]:

(i) **One (1) mash preparation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber CE011 for VOC/HAP controls, exhausting through stack SV011. This process consists of the following:**

(1) One (1) slurry tank, identified as EU017.

(2) One (1) yeast propagation tank, identified as EU018.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

~~(j)~~**(j)** One (1) fermentation process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum throughput rate of 73,900 gallons per hour, using wet scrubber ~~CE011~~ and ~~regenerative thermal oxidizer (RTO) CE012~~ for VOC/HAP controls, exhausting through stack ~~SV011~~ or SV012. This process consists of the following:

~~(1)~~ One (1) slurry tank, identified as EU017

~~(2)~~ One (1) yeast propagation tank, identified as EU024.

~~(3)~~**(1)** Six (6) fermenters, identified as ~~EU018~~ EU019 through ~~EU023~~ EU024.

~~(4)~~**(2)** Two (2) beer wells, identified as EU025 and EU026.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

~~Note: The RTO must occasionally be temporarily shut down for maintenance or other operational reasons. In this event, the DDGS dryers and fluid bed cooler will be shut down, however, the~~

~~fermentation system will continue to be operated in normal mode. The emissions from these sources will be controlled by the wet scrubber CE011 only and vent through stack SV011.~~

~~(k)~~ (k) One (1) distillation and dehydration process, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum ethanol production of 72,000 gallons per hour, using wet scrubber CE013 for VOC control, exhausting through stack SV013. This process consists of the following:

- (1) One degas column, identified as EU027.
- (2) One (1) beer stripper, identified as EU028.
- (3) One (1) rectifier column, identified as EU029.
- (4) One (1) side stripper, identified as EU030.
- (5) One (1) set of three (3) molecular sieve, identified as EU031.
- (6) One (1) set of three (3) evaporators, identified as EU032.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

~~(o)~~ (o) One (1) ethanol loadout rack (two rail loadouts utilizing top loading only and one truck loadout utilizing submerged loading only), originally constructed in March 2008, obtaining new operation approval in 2010, identified as ~~EU045~~ **EU043**, with a maximum throughput rate of 118.25 million gallons per year. The loadout process is controlled by enclosed flare CE018, which is fueled by natural gas and has a maximum heat input capacity of 6.8 MMBtu per hour, and exhausting through stack ~~SV019~~ **SV018**.

Under NSPS, Subpart VVa, the pumps, compressors, pressure relief devices in gas/vapor service, sampling connection systems, open-ended valves or lines, and valves of this process are considered to be affected facilities.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

...

SECTION E.4 FACILITY OPERATION CONDITIONS - 40 CFR 60, Subpart IIII - Standards of Performance for Stationary Compression Ignition (CI) Internal Combustion Engines (ICE)

Facility Description [326 IAC 2-8-4(10)]:

Emission Units:

~~(q)~~ (q) One (1) diesel generator, approved for construction in 2010, identified as ~~EU046~~ **EU044**, with a rated capacity of 2,000 KW, exhausting to ~~SV020~~ **SV019**.

...

Insignificant Activities:

(h) Stationary fire pumps, including one (1) diesel fire pump, identified as ~~EU047~~ **EU045**, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack ~~SV024~~ **SV020**.

...

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

...

E.4.2 Standards of Performance for Stationary Compression Ignition Internal Combustion Engines [40 CFR 60, Subpart IIII]

The Permittee shall comply with the following provisions of 40 CFR Part 60, Subpart IIII (included as Attachment E) which are incorporated by reference as 326 IAC 12 for the stationary compression ignition (CI) internal combustion engines (ICE):

~~EU046~~ **EU044** is subject to the following portions of 40 CFR 60, Subpart IIII:

...

~~EU047~~ **EU045** is subject to the following portions of 40 CFR 60, Subpart IIII.

...

SECTION E.5 FACILITY OPERATION CONDITIONS - 40 CFR 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE)

Facility Description [326 IAC 2-8-4(10)]:

Emission Units:

~~(r)~~(q) One (1) diesel generator, approved for construction in 2010, identified as ~~EU046~~ **EU044**, with a rated capacity of 2,000 KW, exhausting to ~~SV020~~ **SV019**.

...

Insignificant Activities:

(h) Stationary fire pumps, including one (1) diesel fire pump, identified as ~~EU047~~ **EU045**, originally constructed in March 2008, obtaining new operation approval in 2010, with a maximum power output rate of 600 horsepower, and exhausting to stack ~~SV024~~ **SV020**.

...

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

...

E.5.2 National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines [40 CFR Part 63, Subpart ZZZZ]

The Permittee shall comply with the following provisions of 40 CFR Part 63, Subpart ZZZZ (included as Attachment F) which are incorporated by reference as 326 IAC 20-82 for the reciprocating internal combustion engine:

~~EU046~~ **EU044** is subject to the following portions of 40 CFR 63, Subpart ZZZZ:

...

~~EU047~~ **EU045** is subject to the following portions of 40 CFR 63, Subpart ZZZZ.

...

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

FESOP Quarterly Report

Source Name: ~~Putnam County Ethanol, LLC~~ **POET Biorefining – Cloverdale, LLC**
Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
Mailing Address: ~~2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120~~
FESOP No.: 133-28725-00003
Facility: Ethanol Loadout Rack (~~EU045~~) **(EU043)**
Parameter: Total Denatured Ethanol and E-85 Loaded
Limit: The total combined load-out rate of denatured ethanol and E-85 associated with the ethanol loading rack (~~EU045~~) **(EU043)** shall not exceed 118,250,000 gallons per twelve consecutive month period, with compliance determined at the end of each month.

...

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

FESOP Quarterly Report

Source Name: ~~Putnam County Ethanol, LLC~~ **POET Biorefining – Cloverdale, LLC**
Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
Mailing Address: ~~2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120~~
FESOP No.: 133-28725-00003
Facility: Ethanol Loadout Rack (~~EU045~~) **(EU043)**
Parameter: Total E-85 Loaded
Limit: The E-85 load-out rate associated with the ethanol loading rack (~~EU045~~) **(EU043)** shall not exceed 14,300,000 gallons per twelve (12) consecutive month period, with compliance determined at the end of each month.

...

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH**

FESOP Quarterly Report

Source Name: _____ POET Biorefining - Cloverdale, LLC
Source Address: _____ 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
Mailing Address: _____ 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
FESOP No.: _____ 133-28725-00003
Facility: _____ CE012
Parameter: _____ Hours of Operation
Limit: _____ The RTO (CE012) downtime shall not exceed 400 hours per twelve (12) consecutive month period.

QUARTER: _____ YEAR: _____

Month	Column 1 This Month	Column 2 Previous 11 Months	Column 1 + Column 2 12 Month Total
	Hours of Operation	Hours of Operation	Hours of Operation
Month 1			
Month 2			
Month 3			

_____ No deviation occurred in this quarter.

_____ Deviation/s occurred in this quarter.

_____ Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

...

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

FESOP Quarterly Report

Source Name: POET Biorefining – Cloverdale, LLC
Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
~~Mailing Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120~~
FESOP No.: 133-28725-00003
Facility: Diesel Generator (~~EU046~~) (**EU044**)
Parameter: Hours of Operation
Limit: Shall not exceed 250 hours per twelve (12) consecutive month period with compliance determined at the end of each month.

...

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE AND ENFORCEMENT BRANCH

FESOP Quarterly Report

Source Name: POET Biorefining – Cloverdale, LLC
Source Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120
~~Mailing Address: 2265 East County Road 800 South, Suite #1, Cloverdale, IN 46120~~
FESOP No.: 133-28725-00003
Facility: Diesel Fire Pump (~~EU047~~) (**EU045**)
Parameter: Hours of Operation
Limit: Shall not exceed 250 hours per twelve (12) consecutive month period with compliance determined at the end of each month.

...

- (3) IDEM, OAQ has included the replacement of an instrument as an acceptable action. Therefore the Section D Parametric Monitoring conditions have been revised as follows:

...

The instruments used for determining the flow rate and pressure drop shall comply with Section C - Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated **or replaced** at least once every six (6) months.

...

- (4) IDEM, OAQ has decided to remove the last sentence dealing with the need for certification from the forms because the Conditions requiring the forms already address this issue. Therefore the following action has been performed on all the reporting forms:

~~Attach a signed certification to complete this report.~~

- (5) IDEM, OAQ has decided to remove all references to the source mailing address. IDEM, OAQ will continue to maintain records of the mailing address.

...

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary ethanol production facility.

...

Mailing Address: 111 Monument Circle, Ste. 900, Indianapolis, IN 46204

...

Conclusion and Recommendation

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant. An application for the purposes of this review was received on August 23, 2010.

The construction and operation of this proposed revision shall be subject to the conditions of the attached proposed FESOP Significant Permit Revision No. 133-29592-00003. The staff recommends to the Commissioner that this FESOP Significant Permit Revision be approved.

IDEM Contact

- (a) Questions regarding this proposed permit can be directed to Jason R. Krawczyk at the Indiana Department Environmental Management, Office of Air Quality, Permits Branch, 100 North Senate Avenue, MC 61-53 IGCN 1003, Indianapolis, Indiana 46204-2251 or by telephone at (317) 232-8427 or toll free at 1-800-451-6027 extension 2-8427.
- (b) A copy of the findings is available on the Internet at: <http://www.in.gov/ai/appfiles/idem-caats/>
- (c) For additional information about air permits and how the public and interested parties can participate, refer to the IDEM's Guide for Citizen Participation and Permit Guide on the Internet at: www.in.gov/idem

**Appendix A: Emission Calculations
Emissions Summary**

Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010

Process, Emission Units, Stack	Control Device	Potential to Emit Before Control								
		PM	PM10	PM2.5	VOC	NOx	SO2	CO	Single HAP	Combined HAPs
Grain Receiving and Handling (EU001 - EU003, EU041 - EU042) (SV001)	CE001	495.57	495.57	495.57	-	-	-	-	-	-
Grain Storage (EU004 - EU007) (SV002)	CE002	300.34	300.34	300.34	-	-	-	-	-	-
Scalper, Conveyor Transfer & Surge Bin (EU008 - EU009) (SV003)	CE003	105.12	105.12	105.12	-	-	-	-	-	-
Hammermill #1 (EU010) (SV004)	CE004	180.21	180.21	180.21	-	-	-	-	-	-
Hammermill #2 (EU011) (SV005)	CE005	180.21	180.21	180.21	-	-	-	-	-	-
Hammermill #3 (EU012) (SV006)	CE006	180.21	180.21	180.21	-	-	-	-	-	-
Hammermill #4 (EU013) (SV007)	CE007	180.21	180.21	180.21	-	-	-	-	-	-
Hammermill #5 (EU014) (SV008)	CE008	180.21	180.21	180.21	-	-	-	-	-	-
Hammermill #6 (EU015) (SV009)	CE009	180.21	180.21	180.21	-	-	-	-	-	-
Hammermill #7 (EU016) (SV010)	CE010	180.21	180.21	180.21	-	-	-	-	-	-
DDGS Storage Building / Flat Storage (EU039) (SV017)	CE017	60.07	60.07	60.07	-	-	-	-	-	-
Mash Preparation Scrubber (EU017-EU018) (SV011)	CE011	-	-	-	286.89	-	-	-	11.51	13.04
Fermentation Scrubber (EU019-EU026) (SV012)	CE012	-	-	-	1903.56	-	-	-	76.50	86.65
Distillation Scrubber (EU027 - EU032) (SV013)	CE013	-	-	-	178.08	-	-	-	5.40	6.57
RTOs (CE015 & CE016) DDGS Dryers (EU034, EU035) & Centrifuges (EU033) (SV014)	CE015 & CE016	508.71	514.35	514.35	790.56	80.43	59.72	431.87	23.36	49.98
Ethanol Loadout (EU043), including Flare (SV018)	CE018	-	-	-	386.76	7.02	-	17.66	-	22.50
Boilers (EU036, EU037) (SV015, SV016)	N/A	2.42	9.67	9.67	7.00	38.18	0.76	25.46	-	2.43
Generator (EU044) (SV019)	N/A	8.81	5.05	5.05	8.88	163.70	50.94	69.26	-	0.14
Fire Pump (EU045) (SV020)	N/A	2.32	2.32	2.32	6.61	45.20	1.35	15.07	2.02	16.96
Space Heaters	N/A	0.02	0.08	0.08	0.06	1.10	0.01	0.92	-	0.02
Fugitive Emissions										
Uncaptured Emissions From Grain Handling (F001)*	N/A	10.27	3.37	3.37	-	-	-	-	-	-
Uncaptured Emissions From DDGS Handling (F002)*	N/A	1.62	0.55	0.55	-	-	-	-	-	-
Truck Traffic (F003)*	N/A	40.92	7.98	1.19	-	-	-	-	-	-
Equipment Leaks (F004)*	N/A	-	-	-	152.06	-	-	-	0.00	0.74
Cooling Towers (F005)*	N/A	12.34	12.34	12.34	-	-	-	-	-	-
Storage Tanks (T001 - T005)*	N/A	-	-	-	2.67	-	-	-	-	-
Total Fugitive:	-	65.14	24.23	17.43	154.72	0.00	0.00	0.00	0.00	0.74
Total (Non-Fugitive):	-	2744.82	2754.01	2754.01	3568.39	335.63	112.77	560.23	118.78	199.03

Notes:

*Fugitive PM/PM10/PM2.5, VOC, and HAP emissions are not counted toward the determination of PSD and Emission Offset applicability.

**Appendix A: Emission Calculations
Emissions Summary (continued)**

Process, Emission Units, Stack	Control Device	Potential to Emit After Control (ton/yr)								
		PM	PM10	PM2.5	VOC	NOx	SO2	CO	Single HAP	Combined HAPs
Grain Receiving and Handling (EU001 - EU003, EU041 - EU042) (SV001)	CE001	4.96	4.96	0.84	-	-	-	-	-	-
Grain Storage (EU004 - EU007) (SV002)	CE002	3.00	3.00	0.51	-	-	-	-	-	-
Scalper, Conveyor Transfer & Surge Bin (EU008 - EU009) (SV003)	CE003	1.05	1.05	0.18	-	-	-	-	-	-
Hammermill #1 (EU010) (SV004)	CE004	1.80	1.80	0.31	-	-	-	-	-	-
Hammermill #2 (EU011) (SV005)	CE005	1.80	1.80	0.31	-	-	-	-	-	-
Hammermill #3 (EU012) (SV006)	CE006	1.80	1.80	0.31	-	-	-	-	-	-
Hammermill #4 (EU013) (SV007)	CE007	1.80	1.80	0.31	-	-	-	-	-	-
Hammermill #5 (EU014) (SV008)	CE008	1.80	1.80	0.31	-	-	-	-	-	-
Hammermill #6 (EU015) (SV009)	CE009	1.80	1.80	0.31	-	-	-	-	-	-
Hammermill #7 (EU016) (SV010)	CE010	1.80	1.80	0.31	-	-	-	-	-	-
DDGS Storage Building / Flat Storage (EU039) (SV017)	CE017	0.60	0.60	0.10	-	-	-	-	-	-
Mash Preparation Scrubber (EU017-EU018) (SV011)	CE011	-	-	-	5.74	-	-	-	0.58	0.65
Fermentation Scrubber (EU019-EU026) (SV012)	CE012	-	-	-	38.07	-	-	-	3.82	4.33
Distillation Scrubber (EU027 - EU032) (SV013)	CE013	-	-	-	3.56	-	-	-	2.70	3.29
RTOs (CE015 & CE016) DDGS Dryers (EU034, EU035) & Centrifuges (EU033) (SV014)	CE014 & CE015	52.56	58.21	58.21	21.15	80.43	59.72	116.51	2.34	6.62
Ethanol Loadout (EU043), including Flare (SV018)	CE018	-	-	-	7.74	7.02	-	17.66	-	0.45
Boilers (EU036, EU037) (SV015, SV016)	N/A	2.42	9.67	9.67	7.00	38.18	0.76	25.46	-	2.43
Generator (EU044) (SV019)	N/A	8.81	5.05	5.05	8.88	163.70	50.94	69.26	-	0.14
Fire Pump (EU045) (SV020)	N/A	2.32	2.32	2.32	6.61	45.20	1.35	15.07	2.02	16.96
Space Heaters	N/A	0.02	0.08	0.08	0.06	1.10	0.01	0.92	-	0.02
Fugitive Emissions										
Uncaptured Emissions From Grain Handling (F001)*	N/A	10.27	3.37	3.37	-	-	-	-	-	-
Uncaptured Emissions From DDGS Handling (F002)*	N/A	1.62	0.55	0.55	-	-	-	-	-	-
Truck Traffic (F003)*	N/A	20.54	4.01	0.60	-	-	-	-	-	-
Equipment Leaks (F004)*	N/A	-	-	-	12.51	-	-	-	-	0.74
Cooling Towers (F005)*	N/A	12.34	12.34	12.34	-	-	-	-	-	-
Storage Tanks (T001 - T005)*	N/A	-	-	-	2.67	-	-	-	-	-
Total Fugitive:	-	44.76	20.26	16.84	15.18	0.00	0.00	0.00	0.00	0.74
Total (Non-Fugitive):	-	88.36	97.56	79.11	98.80	335.63	112.77	244.87	11.45	35.63

Notes:

*Fugitive PM/PM10/PM2.5, VOC, and HAP emissions are not counted toward the determination of PSD and Emission Offset applicability.

**Appendix A: Emission Calculations
Emissions Summary (continued)**

Process, Emission Units, Stack	Control Device	Limited Potential to Emit (ton/yr)								
		PM	PM10	PM2.5	VOC	NOx	SO2	CO	Single HAP	Combined HAPs
Grain Receiving and Handling (EU001 - EU003, EU041 - EU042) (SV001)	CE001	4.99	4.99	4.99	-	-	-	-	-	-
Grain Storage (EU004 - EU007) (SV002)	CE002	3.02	3.02	3.02	-	-	-	-	-	-
Scalper, Conveyor Transfer & Surge Bin (EU008 - EU009) (SV003)	CE003	1.05	1.05	1.05	-	-	-	-	-	-
Hammermill #1 (EU010) (SV004)	CE004	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill #2 (EU011) (SV005)	CE005	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill #3 (EU012) (SV006)	CE006	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill #4 (EU013) (SV007)	CE007	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill #5 (EU014) (SV008)	CE008	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill #6 (EU015) (SV009)	CE009	1.80	1.80	1.80	-	-	-	-	-	-
Hammermill #7 (EU016) (SV010)	CE010	1.80	1.80	1.80	-	-	-	-	-	-
DDGS Storage Building / Flat Storage (EU039) (SV017)	CE017	0.61	0.61	0.61	-	-	-	-	-	-
Mash Preparation Scrubber (EU017-EU018) (SV011)	CE011	-	-	-	5.74	-	-	-	0.57	0.66
Fermentation Scrubber (EU019-EU026) (SV012)	CE012	-	-	-	38.06	-	-	-	3.81	4.34
Distillation Scrubber (EU027 - EU032) (SV013)	CE013	-	-	-	3.55	-	-	-	2.72	3.29
RTOs (CE015 & CE016) DDGS Dryers (EU034, EU035) & Centrifuges (EU033) (SV014)	CE014 & CE015	47.30	47.30	47.30	21.16	52.69	59.70	66.14	2.32	4.82
Ethanol Loadout (EU043), including Flare (SV018)	CE018	-	-	-	7.75	1.97	-	4.97	-	0.45
Boilers (EU036, EU037) (SV015, SV016)	N/A	2.42	9.67	9.67	7.00	38.18	0.76	25.46	-	2.43
Generator (EU044) (SV019)	N/A	0.25	0.14	0.14	0.25	4.67	1.45	1.98	-	0.00
Fire Pump (EU045) (SV020)	N/A	0.07	0.07	0.07	0.19	1.29	0.04	0.43	0.06	0.48
Space Heaters	N/A	0.02	0.08	0.08	0.06	1.10	0.01	0.92	-	0.02
Fugitive Emissions										
Uncaptured Emissions From Grain Handling (F001)*	N/A	10.27	3.37	3.37	-	-	-	-	-	-
Uncaptured Emissions From DDGS Handling (F002)*	N/A	1.62	0.55	0.55	-	-	-	-	-	-
Truck Traffic (F003)*	N/A	20.54	4.01	0.60	-	-	-	-	-	-
Equipment Leaks (F004)*	N/A	-	-	-	12.51	-	-	-	-	0.74
Cooling Towers (F005)*	N/A	12.34	12.34	12.34	-	-	-	-	-	-
Storage Tanks (T001 - T005)*	N/A	-	-	-	2.67	-	-	-	-	-
Total Fugitive:	-	44.76	20.26	16.84	15.18	0.00	0.00	0.00	0.00	0.74
Total (non-Fugitive):	-	72.31	79.52	79.52	83.75	99.91	61.96	99.89	9.47	17.23

Notes:

*Fugitive PM/PM10/PM2.5, VOC, and HAP emissions are not counted toward the determination of PSD and Emission Offset applicability.

Appendix A: Emission Calculations
 Natural Gas HAPs Combustion Emissions Summary

Company Name: POET Biorefining - Cloverdale, LLC
 Address: 2265 East County Road 800 South, Cloverdale, IN 46120
 FESOP: F 133-29592-00003
 Pit ID: 133-00003
 Reviewer: Jason R. Krawczyk
 Date: September 21, 2010

Combustion HAP Calculations

Pollutant	Emission Factor* (lb/MMBtu)	RTOs		Dryers		Boilers		Heaters	
		60.0 MMBtu/hr		166.0 MMBtu/hr		290.6 MMBtu/hr		2.5 MMBtu/hr	
		Potential to Emit Emissions		Potential to Emit Emissions		Potential to Emit Emissions		Potential to Emit Emissions	
		(lb/hr)	(ton/yr)	(lb/hr)	(ton/yr)	(lb/hr)	(ton/yr)	(lb/hr)	(ton/yr)
2-Methylnaphthalene	2.40E-08	1.4E-06	6.0E-06	4.0E-06	1.7E-05	6.97E-06	3.05E-05	6.00E-08	2.63E-07
3-Methylchloranthrene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
7,12-Dimethylbenz(a)anthracene	1.60E-08	9.6E-07	4.0E-06	2.7E-06	1.1E-05	4.65E-06	2.04E-05	4.00E-08	1.75E-07
Acenaphthene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
Acenaphthylene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
Anthracene	2.40E-09	1.4E-07	6.0E-07	4.0E-07	1.7E-06	6.97E-07	3.05E-06	6.00E-09	2.63E-08
Benz(a)anthracene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
Benzene	2.10E-06	1.3E-04	5.3E-04	3.5E-04	1.5E-03	6.10E-04	2.67E-03	5.25E-06	2.30E-05
Benzo(a)pyrene	1.20E-09	7.2E-08	3.0E-07	2.0E-07	8.3E-07	3.49E-07	1.53E-06	3.00E-09	1.31E-08
Benzo(b)fluoranthene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
Benzo(g,h,i)perylene	1.20E-09	7.2E-08	3.0E-07	2.0E-07	8.3E-07	3.49E-07	1.53E-06	3.00E-09	1.31E-08
Benzo(k)fluoranthene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
Chrysene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
Dibenzo(a,h)anthracene	1.20E-09	7.2E-08	3.0E-07	2.0E-07	8.3E-07	3.49E-07	1.53E-06	3.00E-09	1.31E-08
Dichlorobenzene	1.20E-06	7.2E-05	3.0E-04	2.0E-04	8.3E-04	3.49E-04	1.53E-03	3.00E-06	1.31E-05
Fluoranthene	3.00E-09	1.8E-07	7.5E-07	5.0E-07	2.1E-06	8.72E-07	3.82E-06	7.50E-09	3.29E-08
Fluorene	2.80E-09	1.7E-07	7.0E-07	4.6E-07	1.9E-06	8.14E-07	3.56E-06	7.00E-09	3.07E-08
Formaldehyde	7.50E-05	4.5E-03	1.9E-02	1.2E-02	5.2E-02	2.18E-02	9.55E-02	1.88E-04	8.21E-04
Hexane	1.80E-03	1.1E-01	4.5E-01	3.0E-01	1.2E+00	5.23E-01	2.29E+00	4.50E-03	1.97E-02
Indeno(1,2,3-cd)pyrene	1.80E-09	1.1E-07	4.5E-07	3.0E-07	1.2E-06	5.23E-07	2.29E-06	4.50E-09	1.97E-08
Naphthalene	6.10E-07	3.7E-05	1.5E-04	1.0E-04	4.2E-04	1.77E-04	7.76E-04	1.53E-06	6.68E-06
Phenanthrene	1.70E-08	1.0E-06	4.3E-06	2.8E-06	1.2E-05	4.94E-06	2.16E-05	4.25E-08	1.86E-07
Pyrene	5.00E-09	3.0E-07	1.3E-06	8.3E-07	3.5E-06	1.45E-06	6.36E-06	1.25E-08	5.48E-08
Toluene	3.40E-06	2.0E-04	8.5E-04	5.6E-04	2.4E-03	9.88E-04	4.33E-03	8.50E-06	3.72E-05
Arsenic	2.40E-07	1.4E-05	6.0E-05	4.0E-05	1.7E-04	6.97E-05	3.05E-04	6.00E-07	2.63E-06
Cadmium	1.10E-06	6.6E-05	2.8E-04	1.8E-04	7.6E-04	3.20E-04	1.40E-03	2.75E-06	1.20E-05
Chromium	1.40E-06	8.4E-05	3.5E-04	2.3E-04	9.7E-04	4.07E-04	1.78E-03	3.50E-06	1.53E-05
Cobalt	8.40E-08	5.0E-06	2.1E-05	1.4E-05	5.8E-05	2.44E-05	1.07E-04	2.10E-07	9.20E-07
Manganese	3.80E-07	2.3E-05	9.5E-05	6.3E-05	2.6E-04	1.10E-04	4.84E-04	9.50E-07	4.16E-06
Mercury	2.60E-07	1.6E-05	6.5E-05	4.3E-05	1.8E-04	7.56E-05	3.31E-04	6.50E-07	2.85E-06
Nickel	2.10E-05	1.3E-03	5.3E-03	3.5E-03	1.5E-02	6.10E-03	2.67E-02	5.25E-05	2.30E-04
Totals		0.11	0.48	0.32	1.32	0.55	2.43	0.00	0.02

*Emission Factors are from AP-42, 5th Edition, Section 1.4, "Natural Gas Combustion," 7/98

The RTO (CE012) is limited to 400 hours down time. Therefore the emissions exhausting to CE012 are based on 8,360 hours of operation.

**Appendix A: Emission Calculations
PM and PM10 Emissions
From the Grain Receiving, Handling, and Hammermilling Operations
and the DDGS Handling Operations**

**Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010**

Process Data

Grain required for 110.00 Mmgal EtOH 40,740,774 bushel/yr
Ethanol Grain Density 56 lb/bushel
Total grain receiving throughput 1,140,742 ton/yr

1. Potential to Emit PM/PM10/PM2.5 - Captured Emissions:

Baghouse ID	Process Description	Outlet Grain Loading (gr/dscf)	Maximum Air Flow Rate (scfm)	PTE of PM/PM10 after Control (lbs/hr)	PTE of PM/PM10 after Control (tons/yr)	PTE of PM2.5 after Control (lbs/hr)	PTE of PM2.5 after Control (tons/yr)	Control Efficiency (%)	PTE of PM/PM10/PM2.5 before Control (tons/yr)
CE001*	Grain & DDGS Handling (EU001 - EU003, EU043 - EU044)	0.004	33,000	1.13	4.96	0.19	0.84	99%	495.57
CE002*	Grain Storage (EU004 - EU007)	0.004	20,000	0.69	3.00	0.12	0.51	99%	300.34
CE003*	Scalper, Conveyor Transfer & Surge Bin (EU008 - EU009)	0.004	7,000	0.24	1.05	0.04	0.18	99%	105.12
CE004*	Hammermill #1 (EU010)	0.004	12,000	0.41	1.80	0.07	0.31	99%	180.21
CE005*	Hammermill #2 (EU011)	0.004	12,000	0.41	1.80	0.07	0.31	99%	180.21
CE006*	Hammermill #3 (EU012)	0.004	12,000	0.41	1.80	0.07	0.31	99%	180.21
CE007*	Hammermill #4 (EU013)	0.004	12,000	0.41	1.80	0.07	0.31	99%	180.21
CE008*	Hammermill #5 (EU014)	0.004	12,000	0.41	1.80	0.07	0.31	99%	180.21
CE009*	Hammermill #6 (EU015)	0.004	12,000	0.41	1.80	0.07	0.31	99%	180.21
CE010*	Hammermill #7 (EU016)	0.004	12,000	0.41	1.80	0.07	0.31	99%	180.21
CE017*	DDGS Storage Building / Flat Storage (EU039)	0.004	4,000	0.14	0.60	0.02	0.10	99%	60.07
Total				5.07	22.23	0.86	3.78		2,222.54

Note:

Assume all PM emissions equal PM10 emissions.

*Assume controlled PM2.5 emissions equal 17% PM/PM10 emissions (AP-42 Table 9.9.1-1 Reference 40).

Methodology:

PTE of PM/PM10 after Control (lbs/hr) = Grain Loading (gr/dscf) x Max. Air Flow Rate (scfm) x 60 mins/hr x 1/7000 lb/gr

PTE of PM/PM10 after Control (tons/yr) = Grain Loading (gr/dscf) x Max. Air Flow Rate (scfm) x 60 mins/hr x 1/7000 lb/gr x 8760 hr/yr x 1 ton/2000 lbs

PTE of PM2.5 after Control (lbs/hr) = Grain Loading (gr/dscf) x Max. Air Flow Rate (scfm) x 60 mins/hr x 1/7000 lb/gr * 0.17

PTE of PM2.5 after Control (tons/yr) = Grain Loading (gr/dscf) x Max. Air Flow Rate (scfm) x 60 mins/hr x 1/7000 lb/gr x 8760 hr/yr x 1 ton/2000 lbs * 0.17

PTE of PM/PM10/PM2.5 before Control (tons/yr) = PTE of PM/PM10 after Control (tons/yr) / (1-Control Efficiency)

2. Potential to Emit PM/PM10/PM2.5 - Fugitive Emissions:

Unit ID	Unit Description	Annual Throughput Limit (tons/yr)	Uncontrolled PM Emission Factor (lbs/ton)	Uncontrolled PM10 Emission Factor (lbs/ton)	Baghouse ID	Capture Efficiency (%)	Fugitive PM Emissions (tons/yr)	Fugitive PM10/PM2.5 Emissions (tons/yr)
F001	Uncaptured Emissions From Grain Handling	1,140,742	0.180	0.0590	CE001	90%	10.27	3.37
F002	Uncaptured Emissions From DDGS Handling	376,445	0.086	0.0290	CE001	90%	1.62	0.55
Total							11.89	3.91

Note:

Emission factors are from AP-42, Chapter 9.9.1-1 and AP-42, Chapter 9.9.1-2. Assume all the grain receiving and loadout is by truck, which is the worst case scenario.

Assume PM10 emissions equal to PM2.5 emissions.

Methodology

Fugitive PM/PM10/PM2.5 (tons/yr) = Annual Throughput Limit (tons/yr) x Uncontrolled Emission Factor (lbs/ton) x (1-Capture Efficiency%) x 1 ton/2000 lbs

Appendix A: Emission Calculations

VOC and HAP Emissions

From the Mash Preparation Scrubber (Stack SV011)

Company Name: POET Biorefining - Cloverdale, LLC

Address: 2265 East County Road 800 South, Cloverdale, IN 46120

FESOP: F 133-29592-00003

Plt ID: 133-00003

Reviewer: Jason R. Krawczyk

Date: September 21, 2010

Scrubber VOC Control Efficiency = 98.00%
Scrubber HAP Control Efficiency = 95.00%

Uncontrolled	lb/hr	ton/yr
VOC	65.5	286.89
Acetaldehyde	2.6	11.51
Propionaldehyde	0.17	0.76
Methanol	0.09	0.38
Formaldehyde	0.09	0.38
Total Uncontrolled HAP	2.98	13.04

Controlled / Limited	lb/hr	ton/yr
VOC	1.31	5.74
Acetaldehyde	0.131	0.58
Propionaldehyde	0.009	0.04
Methanol	0.004	0.02
Formaldehyde	0.004	0.02
Total Controlled HAP	0.15	0.65

Note:

Controlled VOC and HAP emission rates based on performance tests at similar facilities and provided by source. Emission factors will be verified via stack test.

Methodology:

Uncontrolled (lb/hr) = Controlled (lb/hr) / (100% - Control Efficiency)

Uncontrolled (ton/yr) = Controlled (ton/yr) / (100% - Control Efficiency)

Controlled (lb/hr) = Provided Emission Rate based on performance tests at similar facilities

Controlled (ton/yr) = Controlled (lb/hr) * 8,760 hours / 2,000 lbs

Appendix A: Emission Calculations

VOC and HAP Emissions

From the Fermentation Scrubber (Stack SV012)

Company Name: POET Biorefining - Cloverdale, LLC

Address: 2265 East County Road 800 South, Cloverdale, IN 46120

FESOP: F 133-29592-00003

Plt ID: 133-00003

Reviewer: Jason R. Krawczyk

Date: September 21, 2010

Scrubber VOC Control Efficiency = 98.00%
Scrubber HAP Control Efficiency = 95.00%

Uncontrolled	lb/hr	ton/yr
VOC	434.6	1903.6
Acetaldehyde	17.5	76.5
Propionaldehyde	1.16	5.08
Methanol	0.58	2.54
Formaldehyde	0.58	2.54
Total Uncontrolled HAP	19.78	86.7

Controlled / Limited	lb/hr	ton/yr
VOC	8.69	38.07
Acetaldehyde	0.87	3.82
Propionaldehyde	0.06	0.25
Methanol	0.03	0.13
Formaldehyde	0.03	0.13
Total Controlled HAP	0.99	4.3

Note:

Controlled VOC and HAP emission rates based on performance tests at similar facilities and provided by source. Emission factors will be verified via stack test.

Methodology:

Uncontrolled (lb/hr) = Controlled (lb/hr) / (100% - Control Efficiency)

Uncontrolled (ton/yr) = Controlled (ton/yr) / (100% - Control Efficiency)

Controlled (lb/hr) = Provided Emission Rate based on performance tests at similar facilities

Controlled (ton/yr) = Controlled (lb/hr) * 8,760 hours / 2,000 lbs

Appendix A: Emission Calculations

VOC and HAP Emissions

From the Distillation Scrubber (Stack SV013)

Company Name: POET Biorefining - Cloverdale, LLC

Address: 2265 East County Road 800 South, Cloverdale, IN 46120

FESOP: F 133-29592-00003

Plt ID: 133-00003

Reviewer: Jason R. Krawczyk

Date: September 21, 2010

Scrubber VOC Control Efficiency = 98.00%
Scrubber HAP Control Efficiency = 50.00%

Uncontrolled	lb/hr	ton/yr
VOC	40.7	178.1
Acetaldehyde	1.2	5.4
Propionaldehyde	0.09	0.39
Methanol	0.09	0.39
Formaldehyde	0.09	0.39
Total Uncontrolled HAP	1.5	6.6

Controlled / Limited	lb/hr	ton/yr
VOC	0.81	3.56
Acetaldehyde	0.62	2.70
Propionaldehyde	0.04	0.20
Methanol	0.04	0.20
Formaldehyde	0.04	0.20
Total Controlled HAP	0.75	3.29

Note:

Controlled VOC and HAP emission rates based on performance tests at similar facilities and provided by source. Emission factors will be verified via stack test.

Methodology:

Uncontrolled (lb/hr) = Controlled (lb/hr) / (100% - Control Efficiency)

Uncontrolled (ton/yr) = Controlled (ton/yr) / (100% - Control Efficiency)

Controlled (lb/hr) = Provided Emission Rate based on performance tests at similar facilities

Controlled (ton/yr) = Controlled (lb/hr) * 8,760 hours / 2,000 lbs

**Appendix A: Emission Calculations
DDGS Dryers and RTOs**

Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010

1. DDGS Dryers Combustion Emissions

Heat Input Capacity MMBtu/hr	Throughput MMCF/yr
166.0	1,454.2

Pollutant	PM*	PM10**	PM2.5	SO ₂	NOx***	VOC	CO
Emission Factor in lbs/MMCF	1.9	7.6	7.6	0.6	81.7	5.5	82.3
Emission Factor, lb/MMBtu	0.0019	0.0076	0.0076	0.0006	0.0817	0.0055	0.0823
Hourly Emissions Limit (lbs/hour)	0.315	1.262	1.262	0.100	13.562	0.913	13.662
Potential to Emit in tons/yr	1.4	5.5	5.5	0.4	59.4	4.0	59.8

Note:
HAP emissions are included on the HAPs Combustions Emissions Summary sheet.

Methodology:
Emission factors are from AP-42, Chapter 1.4, Tables 1.4-1, 1.4-2, and 1.4-3 (AP-42, 3/98).
*PM emission factor is filterable PM only.
**PM10 emission factor is condensable and filterable PM10 combined.
***NOx emission factor based on stack test results from a similar source. POET Biorefining - Cloverdale, LLC will verify emission rate via stack test.
Assume PM10 = PM2.5
MMBtu = 1,000,000 Btu
MMCF = 1,000,000 Cubic Feet of Gas

2. RTO Combustion Emissions (Two (2) 5-Chamber RTOs each rated at 30 MMBtu/hr)

Heat Input Capacity MMBtu/hr	Throughput MMCF/yr
60.0	525.6

Pollutant	PM*	PM10*	PM2.5	SO ₂	NOx	VOC	CO**
Emission Factor in lbs/MMCF	1.9	7.6	7.6	0.6	80	5.5	82.3
Emission Factor, lb/MMBtu	0.0019	0.0076	0.0076	0.0006	0.0800	0.0055	0.0823
Hourly Emissions Limit (lbs/hour)	0.114	0.456	0.456	0.036	4.800	0.330	4.938
Potential to Emit in tons/yr	0.50	2.00	2.00	0.16	21.02	1.45	21.63

Note:
HAP emissions are included on the HAPs Combustions Emissions Summary sheet.

Methodology:
Emission factors are from AP-42, Chapter 1.4, Tables 1.4-1, 1.4-2, and 1.4-3 (AP-42, 3/98).
*PM emission factor is filterable PM only.
**PM10 emission factor is condensable and filterable PM10 combined.
***NOx emission factor based on manufacturer's guarantee. POET Biorefining - Cloverdale, LLC will verify emission rate via stack test.
Assume PM10 = PM2.5
MMBtu = 1,000,000 Btu
MMCF = 1,000,000 Cubic Feet of Gas

**Appendix A: Emission Calculations
DDGS Dryers and RTO (Continued)**

3. Process Emissions

Particulate Emissions

Control ID	Emissions Units	Outlet Grain Loading (gr/dscf)	Maximum Air Flow Rate (scfm)	PTE of PM/PM10/PM2.5 after Control (lbs/hr)	PTE of PM/PM10/PM2.5 after Control (tons/yr)	Control Efficiency (%)	PTE of PM/PM10/PM2.5 before Control (lbs/yr)	PTE of PM/PM10/PM2.5 before Control (ton/yr)
CE014 & CE015	EU033, EU034, EU035	0.135	100,000	11.57	50.68	90%	115.71	506.83

Note:
The PM/PM10/PM2.5 emission factors for the dryers are based on an engineering estimate and will be verified via a stack test.

Methodology:

PTE before Control (lbs/yr) = Outlet Grain Loading (gr/dscf) * Maximum Air Flow Rate (scfm) * 60 minutes / 7,000 grains.
PTE before Control (tons/yr) = PTE before Control (lbs/hr) * 8,760 hours / 2,000 lbs.
PTE after Control (lbs/hr) = PTE before Control (lbs/hr) * (1 - Control Efficiency (%)).
PTE after Control (tons/yr) = PTE before Control (lbs/hr) * 8,760 hours / 2,000 lbs.

CO Emissions

Control ID	Emissions Units	PTE of CO before Control		Control Efficiency (%)	PTE of CO after Control	
		(lb/hr)	(ton/year)		(lb/hr)	(ton/year)
CE014 & CE015	EU034, EU035	80.0	350.4	90.0%	8.0	35.0

Note:
CO emission rate before controls based on CO emission rates of similar sources. CO emission rate will be verified via a stack test.

Methodology:

PTE of CO before Control (ton/yr) = PTE of CO before Control (lb/hr) * 8,760 hrs / 2,000 lbs.
PTE of CO after Control (lb/hr) = PTE of CO before Control (lb/hr) * (1 - Control Efficiency (%)).
PTE of CO after Control (tons/yr) = PTE of CO after Control (lb/hr) * 8,760 hrs / 2,000 lbs.

VOC and HAP Emissions

Control ID	Analyte	PTE before Control		Control Efficiency (%)	PTE after Control	
		lb/hr	ton/year		lb/hr	ton/year
CE014 & CE015	VOC	179.3	785.1	98.0%	3.59	15.7
	Acetaldehyde	5.3	23.4	90%	0.53	2.3
	Acrolein	1.7	7.3	90%	0.17	0.7
	Methanol	1.7	7.3	90%	0.17	0.7
	Formaldehyde	2.3	10.2	90%	0.23	1.0
	Total HAP	11.0	48.2	90%	1.10	4.82

Note:
The VOC and HAP after control (lb/hr) emission rates for the RTO are based on emission rates observed at a similar source. VOC and Acetaldehyde emission rates will be verified via stack test.

Methodology:

PTE before Control (lb/hr) = PTE after Control (lb/hr) / (1 - Control Efficiency (%))
PTE before Control (tons/yr) = PTE before Control (lb/hr) * 8,760 hrs / 2,000 lbs.
PTE after Control (ton/yr) = PTE after Control (lb/hr) * 8,760 hrs / 2,000 lbs.

SO2 Emissions

Ethanol Production Limit (MMgal/yr)	Emission Factor (lb/gal)	Emission Rate (lb/hr)	Emission Rate (ton/yr)
118.25	0.001	13.50	59.13

Note:
SO₂ emission factor based on testing at similar plant.

Methodology:

Emission Rate (lb/hr) = Ethanol Production Limit (MMGal/yr) * Emission Factor (lb/gal) / 8,760 hrs.
Emission Rate (ton/yr) = Emission Rate (lb/hr) * 8,760 hrs / 2,000 lbs.

**Appendix A: Emission Calculations
Emissions from Loading Rack
and Flare Combustion**

**Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010**

1. Emission Factors: AP-42

Ethanol will be shipped by truck and by rail. Railcars will be dedicated fleets, but the trucks may be used to carry gasoline prior to filling with ethanol. Railcars and trucks will be filled by submerged loading process and the truck loading process is controlled by flare CE012, which has a control efficiency of 98% for VOC and HAPs.

According to AP-42, Chapter 5.2 - Transportation and Marketing of Petroleum Liquids (01/95), the VOC emission factors for the truck and rail loading rack can be estimated from the following equation:

$$L = 12.46 \times (SPM)/T$$

where:

- L = loading loss (lbs/kgal)
- S = a saturation factor (see AP-42, Table 5.2-1)
- P = true vapor pressure of the liquid loaded (psia)
- M = molecular weight of vapors
- T = temperature of the bulk liquid loaded (degree R)

Previous Stored Liquid	*S	P (psia)	M (lbs/mole lbs)	T (degree R)	L (lbs/kgal)
Gasoline (RVP15 normal)	1.0	7.29	60.00	512	10.65
Gasoline (RVP15 clean cargo)	0.5	7.29	60.00	512	5.33
E-85 Ethanol (normal)	0.6	1.73	56.46	512	1.42
E-85 Ethanol (clean cargo)	0.5	1.73	56.46	512	1.19
Denatured Ethanol (normal)	0.6	0.71	49.76	512	0.51
Denatured Ethanol (clean cargo)	0.5	0.71	49.76	512	0.43

The emission factor for loading denatured ethanol to rail which previously contained denatured ethanol
= L (Denatured ethanol, normal) = Denatured Ethanol 0.51 (lbs/kgal)

The emission factor for loading E-85 to trucks which stored gasoline previously
= L (gasoline, normal) - L (gasoline, clean cargo) + L (E-85, clean cargo) = E-85 6.51

Therefore, the emission factor for loading denatured ethanol to trucks which stored gasoline previously
= L (gasoline, normal) - L (gasoline, clean cargo) + L (denatured ethanol, clean cargo) = Denatured Ethanol 5.75

True vapor pressure and the molecular weight are calculated within Tanks 4.0.9d software for Indianapolis, IN meteorological data.
Gasoline service is assuming RVP15 gasoline
Denatured ethanol is assumed to be 95% ethanol and 5% RVP15 gasoline
E-85 ethanol is assumed to be 70% ethanol and 30% RVP15 gasoline

2. Unlimited Potential to Emit VOC Before Control:

(1) Assume truck loadout = :

Denatured Loadout : 90%
E-85 = 10%
200 Proof EtOH 110.00 MMgal/yr
Denatured Loadout : 103.95 MMgal/yr (90% of 200 Proof @ 5% Denaturant)
E-85 = 14.30 MMgal/yr (10% of 200 Proof @ 30% Denaturant)
Total Loadout = 118.25 MMgal/yr

Denatured Ethanol Loading Rate limit for truck: 118.25 MMgal/yr
PTE of VOC before Control (tons/yr) = 118.25 MMgal/yr x 5.75 lbs/kgal x 1 ton/2000 lbs = **340.2 tons/yr**

E-85 Loading Rate limit for truck: 14.30 MMgal/yr
PTE of VOC before Control (tons/yr) = 14.3 MMgal/yr x 6.51 lbs/kgal x 1 ton/2000 lbs = **46.6 tons/yr**

(2) Assume all ethanol loaded out via rail:
Loading Rate limit for rail: 118.25 MMgal/yr
PTE of VOC before Control (tons/yr) = 118.25 MMgal/yr x 0.51 lbs/kgal x 1 ton/2000 lbs = **30.4 tons/yr**

**Appendix A: Emission Calculations
Emissions from Loading Rack
and Flare Combustion (Continued)**

3. Limited Potential to Emit VOC after Control:

Annual Production Limit:	118.25 MMgal/yr
Railcar Limited Throughput	118.25 MMgal/yr
Truck Throughput (worst case)	118.25 MMgal/yr
Flare Control Efficiency:	98%

(1) Assume truck loadout = :
Denatured Loadout = 90%
E-85 = 10%

Limited PTE of VOC from denatured ethanol truck loading (tons/yr) = 5.75 lbs/kgal x 118.25 kgal/yr x (1-98%) x 1 tons/2000 lbs = **6.80 tons/yr**
 Limited PTE of VOC from E-85 truck loading (tons/yr) = 0.51 lbs/kgal x 14,300 kgal/yr x (1-98%) x 1 tons/2000 lbs = **0.93 tons/yr**

Total = 7.74 tons/yr

(2) Assume all denatured ethanol is loaded to railcars (controlled by flare):

PTE of VOC (tons/yr) = 0.51 lb/kg * Annual Production Limit (MMgal/yr) * 1000 gallons * (1- Flare Control Efficiency) * 1 ton / 2000 lbs **0.61 tons/yr**

Worst Case Scenario = 7.74 tons/yr

4. Potential to Emit HAPs:

HAP emissions are mainly from the unloading process for trucks, which may have been used to ship gasoline previously.

HAP	*HAP Fraction	PTE of HAPs before Control (tons/yr)	Limited PTE of HAPs after Control (tons/yr)
Benzene	2.50E-03	0.97	1.93E-02
Carbon Disulfide	2.00E-05	0.01	1.55E-04
Cumene	1.00E-04	0.04	7.74E-04
Ethyl benzene	5.00E-05	0.02	3.87E-04
n-Hexane	5.00E-02	19.34	3.87E-01
Toluene	5.00E-03	1.93	3.87E-02
Xylene	5.00E-04	0.19	3.87E-03
Total	0.058	22.50	0.45

* This is the HAP fraction for gasoline vapors.

Methodology:

PTE of HAPs before Control (tons/yr) = PTE of VOC before Control (tons/yr) x HAP %

Limited PTE of HAPs after Control (tons/yr) = Limited PTE of VOC by Trucks (tons/yr) x HAP %

**Appendix A: Emission Calculations
Emissions from Loading Rack
and Flare Combustion (Continued)**

5. Potential to Emit (NOx and CO) from Flare Combustion

Maximum Heat Input Capacity	6.8 MMBtu/hr
Maximum Loadout Rate	48.00 kgal/hr
Annual Limited Loadout Rate	118,250 kgal/yr

Emission Factor (lbs/kgal)	**NO _x	**CO
	0.0334	0.084
Unlimited Potential to Emit in tons/yr	7.02	17.66
Limited Potential to Emit in tons/yr	1.97	4.97

*PM, PM10, and SO₂ emission factors are negligible due to the smokeless design and minimal H₂S levels.

**Emission factors for NO_x and CO are based on the information provided by the flare manufacturer (John Zink Company).

Methodology:

Unlimited PTE of NO_x and CO (tons/yr) = Max. Load-out Rate (kgal/hr) x Emission Factor (lbs/kgal) x 8760 hr/yr x 1 ton/2000 lbs

Limited PTE of NO_x and CO (tons/yr) = Annual Production Limit (kgal/yr) x Emission Factor (lbs/kgal) x 1 ton/2000 lbs

Limited PTE of PM/PM10 and SO₂ (tons/yr) = Unlimited PTE (tons/yr) x Annual Production Limit (Mgal/yr) / (Max. Load-out Rate Mgal/hr x 8760 hr/yr)

**Appendix A: Emission Calculations
Two (2) Natural Gas Fired Boilers**

**Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010**

Heat Input Capacity MMBtu/hr	Unlimited Throughput MMCF/yr
290.6	2,545.7

Pollutant	PM	PM10*	PM2.5*	SO ₂	NOx	VOC	CO**
Emission Factor in lbs/MMCF	1.9	7.6	7.6	0.6	30	5.5	20.0
Emission Factor, lb/MMBtu	0.0019	0.0076	0.0076	0.0006	0.03	0.0055	0.02
Hourly Emissions Limit (lbs/hour)	0.552	2.209	2.209	0.174	8.718	1.598	5.812
Potential to Emit in tons/yr	2.42	9.67	9.67	0.76	38.18	7.00	25.5

Note:
HAP emissions are included on the HAPs Combustions Emissions Summary sheet.

Methodology:
Emission factors are from AP-42, Chapter 1.4, Tables 1.4-1, 1.4-2, and 1.4-3 (AP-42, 3/98).
*PM10 and PM2.5 emission factors are condensable and filterable PM combined.
**CO emission factor based on performance test data of a similar unit.
Assume PM10 = PM2.5
MMBtu = 1,000,000 Btu
MMCF = 1,000,000 Cubic Feet of Gas

Appendix A: Emission Calculations
Large Reciprocating Internal Combustion Engines - Diesel Fuel
Output Rating (>600 HP)

Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010

Emissions calculated based on output rating (hp)

Output Horsepower Rating (hp)	2875.0
Unlimited Hours of Operation per Year	8760
Unlimited Potential Throughput (hp-hr/yr)	25,185,000
Limited Hours of Operation per Year	250
Limited Potential Throughput (hp-hr/yr)	718,750
Sulfur Content (S) of Fuel (% by weight)	0.500

	Pollutant						
	PM*	PM10*	PM2.5*	SO2	NOx	VOC	CO
Emission Factor in lb/hp-hr	7.00E-04	4.01E-04	4.01E-04	4.05E-03 (.00809S)	1.30E-02 **see below	7.05E-04	5.50E-03
Unlimited Potential Emissions in tons/yr	8.81	5.05	5.05	50.94	163.70	8.88	69.26
Limited Potential Emission in tons/yr	0.25	0.14	0.14	1.45	4.67	0.25	1.98

*PM10 emission factor in lb/hp-hr was calculated using the emission factor in lb/MMBtu and a brake specific fuel consumption of 7,000 Btu / hp-hr (AP-42 Table 3.3-1).

**NOx emission factor: uncontrolled = 0.024 lb/hp-hr, controlled by ignition timing retard = 0.013 lb/hp-hr

Hazardous Air Pollutants (HAPs)

	Pollutant						
	Benzene	Toluene	Xylene	Formaldehyde	Acetaldehyde	Acrolein	Total PAH HAPs***
Emission Factor in lb/hp-hr****	5.43E-06	1.97E-06	1.35E-06	5.52E-07	1.76E-07	5.52E-08	1.48E-06
Unlimited Potential Emission in tons/yr	6.84E-02	2.48E-02	1.70E-02	6.95E-03	2.22E-03	6.95E-04	1.87E-02
Limited Potential Emission in tons/yr	1.95E-03	7.07E-04	4.86E-04	1.98E-04	6.34E-05	1.98E-05	5.33E-04

***PAH = Polyaromatic Hydrocarbon (PAHs are considered HAPs, since they are considered Polycyclic Organic Matter)

****Emission factors in lb/hp-hr were calculated using emission factors in lb/MMBtu and a brake specific fuel consumption of 7,000 Btu / hp-hr (AP-42 Table 3.3-1).

Unlimited Potential Emissions of Total HAPs (ton/yr)	1.39E-01
Limited Potential Emission of Total HAPs (tons/yr)	3.96E-03

Methodology

Emission Factors are from AP 42 (Supplement B 10/96) Tables 3.4-1 , 3.4-2, 3.4-3, and 3.4-4

Potential Throughput (hp-hr/yr) = [Output Horsepower Rating (hp)] * [Limited Hours of Operation per Year]

Limited Potential Emission (tons/yr) = [Potential Throughput (hp-hr/yr)] * [Emission Factor (lb/hp-hr)] / [2,000 lb/ton]

Unlimited Potential Emissions (tons/yr) =

**Appendix A: Emission Calculations
Internal Combustion Engines
From the Diesel Fire Pump**

**Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010**

**Emission Factors NSPS for Model Year (MY) 2008 and Earlier - Emergency Fire Pumps
Between 225 and 450 kw (300 to 600 hp)**

Nox + NMHC	10.5 g/kwh	7.8 g/hp-hr
CO	3.5 g/kwh	2.6 g/hp-hr
PM-10/PM-2.5/TSP	0.54 g/kwh	0.4 g/hp-hr

Emission Factors from AP-42 Gasoline and Diesel Industrial Engines, Table 3.3-1 (10-96)

SOx Emission Factors	0.00205 lb/hp-hr	0.0005125 lb/hp-hr	LSD fuel assume 75% reduction in emissions
TOC Emission Factor	0.0025141 lb/hp-hr		

A. Potential emissions from emergency fire pumps (EFP).

	Horsepower	Kilowatts	MMBtu/hr		
Rated Capacity:	600	447	1.53		
Limited hours of Operation:	250				
Annual Fuel Use Limitation:	382	MMBtu/yr	=	2,748	Gal/yr

Emission Calculations	NOx (TPY)	CO (TPY)	SOx (TPY)	PM/PM10 (TPY)	TOC (TPY)
Fire Pump (Unlimited)	45.20	15.07	1.35	2.32	6.61
Fire Pump (Limited)	1.29	0.43	0.04	0.07	0.19

B. HAP Emissions

Pollutant	Emission Factor (lb/hp-hr)	Unlimited Emissions (ton/yr)	Limited Emissions (TPY)
<i>Hazardous Air Pollutants:</i>			
Benzene	9.33E-04	2.45E+00	7.00E-02
Toluene	4.09E-04	1.07E+00	3.07E-02
Xylenes	2.85E-04	7.49E-01	2.14E-02
Propylene	2.58E-03	6.78E+00	1.94E-01
1,3-Butadiene	3.91E-05	1.03E-01	2.93E-03
Formaldehyde	1.18E-03	3.10E+00	8.85E-02
Acetaldehyde	7.67E-04	2.02E+00	5.75E-02
Acrolein	9.25E-05	2.43E-01	6.94E-03
POM	Various Factors	4.42E-01	1.26E-02
TOTAL HAZARDOUS AIR POLLUTANTS		16.960	0.48

Methodology:

- A factor of 453.54 g/lb was used to convert g/hp-hr to lb/hp-hr
- HAPs Emission Factors (lb/MMBtu) [AP-42 Gasoline and Diesel Industrial Engines, Table 3.3-2 (10-96)]
- SOx emission factor from AP-42 Gasoline and Diesel Industrial Engines. Reduction of 75% based upon average fuel sulfur content through year 2005 of 2000 ppm and required use of Low Sulfur Diesel (LSD) with a maximum sulfur content of 500 ppm. EPA 420-R-04-0007: Final Regulatory Analysis: Control of Emissions from Nonroad Diesel Engines, page 3-91.
- Emission (tons/yr) = [Maximum Operationg (hp-hr/yr) x Emission Factor (g/hp-hr) / 453.54] / (2,000 lb/ton)

**Appendix A: Emissions Calculations
Natural Gas Combustion Only**

**Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010**

Heat Input Capacity
MMBtu/hr

Potential Throughput
MMCF/yr

2.5

21.9

Emission Factor in lb/MMCF	Pollutant					
	PM*	PM10*	SO2	NOx	VOC	CO
	1.9	7.6	0.6	100 **see below	5.5	84
Potential Emission in tons/yr	0.02	0.08	0.01	1.10	0.06	0.92

Note:

*PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

**Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

HAP emissions are included on the HAPs Combustions Emissions Summary sheet.

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

**Appendix A: Emission Calculations
Fugitive Emissions From Roads**

Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010

1. Paved Roads

$$E = [(k \times (sL/2)^{0.65}) \times (W/3)^{1.5} - C](1 - (P/4N))$$

AP-42, Section 13.2.2-1

Factor	Description	Source	Summer Months			Winter Months		
			PM Value	PM ₁₀ Value	PM _{2.5} Value	PM Value	PM ₁₀ Value	PM _{2.5} Value
E =	Emission factor (lb/VMT, vehicle miles traveled)	Calculation, above	0.95	0.19	0.03	2.35	0.46	0.07
k =	PM Particle size multiplier (lb/VMT)	AP-42, Section 13.2.1	0.082	0.016	0.0024	0.082	0.016	0.0024
sL =	Road surface silt loading (g/m ²)	AP-42, Section 13.2.1-2	0.60	0.60	0.60	2.40	2.40	2.4
C =	Vehicle exhaust emission factor		0.0005	0.0005	0.0004	0.0005	0.0005	0.0004
P =	Number of "wet" days in an averaging period		120	120	120	120	120	120
N =	Number of days in the averaging period		365	365	365	365	365	365
W =	Average vehicle weight (ton)		27.5	27.5	27.5	27.5	27.5	27.5

Average Annual Emission Factors

	Non-Winter Months	Winter Months	Average Factor
PM	9	3	1.30
PM ₁₀	9	3	0.25
PM _{2.5}	9	3	0.04

PM Emissions from Paved Roads

Activity	Quantity Transported per truck	No. of Trucks (truck/yr)	Miles Traveled per Truck (miles/truck)	Annual Mileage (VMT/yr)	Uncontrolled PM Emissions (lb/yr)	Uncontrolled PM Emissions (tpy)	Controlled PM Emissions* (tpy)
Grain delivery	25 ton	45,630	0.90	41,067	53539.68	26.77	13.38
DDGS haul out	25 ton	15,058	0.90	13,552	17668.21	8.83	4.42
Ethanol haul out	8,000 gal	14,781	0.50	7,391	9635.11	4.82	2.41
Denaturant delivery	8,000 gal	1,031	0.50	516	672.07	0.34	0.17
Total						40.76	20.38

*Periodic sweeping will be done to provide control (50%) to PM/PM₁₀/PM_{2.5} emissions.

PM₁₀ Emissions from Paved Roads

Activity	Quantity Transported per truck	No. of Trucks (truck/yr)	Miles Traveled per Truck (miles/truck)	Annual Mileage (VMT/yr)	Uncontrolled PM ₁₀ Emissions (lb/yr)	Uncontrolled PM ₁₀ Emissions (tpy)	Controlled PM ₁₀ Emissions* (tpy)
Grain delivery	25 ton	45,630	0.90	41,067	10,433	5.22	2.61
DDGS haul out	25 ton	15,058	0.90	13,552	3,443	1.72	0.86
Ethanol haul out	8,000 gal	14,781	0.50	7,391	1,877	0.94	0.47
Denaturant delivery	8,000 gal	1,031	0.50	516	131	0.07	0.03
Total						7.94	3.97

*Periodic sweeping will be done to provide control (50%) to PM/PM₁₀/PM_{2.5} emissions.

PM_{2.5} Emissions from Paved Roads

Activity	Quantity Transported per truck	No. of Trucks (truck/yr)	Miles Traveled per Truck (miles/truck)	Annual Mileage (VMT/yr)	Uncontrolled PM _{2.5} Emissions (lb/yr)	Uncontrolled PM _{2.5} Emissions (tpy)	Controlled PM _{2.5} Emissions* (tpy)
Grain delivery	25 ton	45,630	0.90	41,067	1,554	0.78	0.39
DDGS haul out	25 ton	15,058	0.90	13,552	513	0.26	0.13
Ethanol haul out	8,000 gal	14,781	0.50	7,391	280	0.14	0.07
Denaturant delivery	8,000 gal	1,031	0.50	516	20	0.01	0.00
Total						1.18	0.59

*Periodic sweeping will be done to provide control (50%) to PM/PM₁₀/PM_{2.5} emissions.

2. Unpaved Roads

According to AP-42, Section 13.2.2 Unpaved Roads, November 2006, the PM/PM₁₀ emission factors

$$E = [k (s/12)^3 (W/3)^3]^{0.75} [(365-P)/365]$$

Factor	Description	PM	PM ₁₀	PM _{2.5}
E =	Emission Factor (lb/VMT)	2.18	0.56	0.06
k =	Particle size multiplier (dimensionless)	4.9	1.5	0.15
s =	surface material silt content (%) (Table 13.2.2-1)	4.8	4.8	4.8
W =	mean vehicle weight (tons)	5.0	5.0	5.0
a =	Equation constants (Table 13.2.2-2)	0.7	0.9	0.9
b =	Equation constants (Table 13.2.2-2)	0.45	0.45	0.45
P =	Number of days with at least 0.01 in of precipitation	120	120	120

Total length of unpaved maintenance roads = 0.10 miles

Emission Area	Vehicle Weight (tons)	Unpaved Total VMT ¹	Total Vehicle Emissions (lb/yr)	Total Vehicle Emissions (tpy)
Maintenance Roads (PM)	5.00	146	318	0.16
Maintenance Roads (PM ₁₀)	5.00	146	81	0.04
Maintenance Roads (PM _{2.5})	5.00	146	8	0.00

[1] Conservatively assumes 2 vehicles per day round trip on all maintenance roads

Methodology

Total Vehicle Emissions (tons/yr) = Unpaved Total VMT (miles/yr) x PM/PM₁₀/PM_{2.5} Emission Factors x 1 ton/2000 lbs

**Emission Calculations
VOC and HAP Emissions
From Equipment Leaks**

Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010

1. Fugitive VOC Emissions:

Process Stream	Equipment Component Source	Product	Component Count	Emission Factor (lb/comp-hr)	Uncontrolled Rate		Subpart VVa Control Effectiveness	Controlled Rate (lb/hr)	TOC Weight (%)	Emitted Water (lb/hr)	Controlled TOC		
					(lb/hr)	(ton/yr)					(lb/hr)	(ton/yr)	
EU027 - EU033 Distillation	Valves	Gas/Vapor	54	0.013134	0.71	3.11	92.00%	0.06	100.00%	0.000	0.057	0.249	
	Valves	Light Liquid	934	0.0089	8.31	36.41	88.00%	1.00	100.00%	0.000	0.998	4.369	
	Pump Seals	Light Liquid	12	0.04378	0.53	2.30	75.00%	0.13	100.00%	0.000	0.131	0.575	
	Compressors	Gas/Vapor	0	0.5016	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Relief Valves	Gas/Vapor	15	0.2288	3.43	15.03	92.00%	0.27	100.00%	0.000	0.275	1.203	
	Sampling Connections	All	0	0.033	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Open Ended Lines	All	0	0.00374	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Connectors	All	1830	0.004026	7.37	32.27	93.00%	0.52	100.00%	0.000	0.516	2.259	
	EU017 - EU026 Fermentation	Valves	Gas/Vapor	2	0.013134	0.03	0.12	92.00%	0.00	15.00%	0.002	0.000	0.001
		Valves	Light Liquid	195	0.0089	1.74	7.60	88.00%	0.21	15.00%	0.177	0.031	0.137
Pump Seals		Light Liquid	10	0.04378	0.44	1.92	75.00%	0.11	15.00%	0.093	0.016	0.072	
Compressors		Gas/Vapor	0	0.5016	0.00	0.00		0.00	15.00%	0.000	0.000	0.000	
Relief Valves		Gas/Vapor	0	0.2288	0.00	0.00	92.00%	0.00	15.00%	0.000	0.000	0.000	
Sampling Connections		All	0	0.033	0.00	0.00		0.00	15.00%	0.000	0.000	0.000	
Open Ended Lines		All	0	0.00374	0.00	0.00		0.00	15.00%	0.000	0.000	0.000	
Connectors		All	632	0.004026	2.54	11.14	93.00%	0.18	15.00%	0.151	0.027	0.117	
T001 , T005 Denaturant Tanks	Valves	Gas/Vapor	3	0.013134	0.04	0.17	92.00%	0.00	100.00%	0.000	0.003	0.014	
	Valves	Light Liquid	38	0.0089	0.34	1.48	88.00%	0.04	100.00%	0.000	0.041	0.178	
	Pump Seals	Light Liquid	2	0.04378	0.09	0.38	75.00%	0.02	100.00%	0.000	0.022	0.096	
	Compressors	Gas/Vapor	0	0.5016	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Relief Valves	Gas/Vapor	8	0.2288	1.83	8.02	92.00%	0.15	100.00%	0.000	0.146	0.641	
	Sampling Connections	All	0	0.033	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Open Ended Lines	All	0	0.00374	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Connectors	All	297	0.004026	1.20	5.24	93.00%	0.08	100.00%	0.000	0.084	0.367	
T002 - T004 Non-denaturant tanks (200- Proof Tanks)	Valves	Gas/Vapor	4	0.013134	0.05	0.23	92.00%	0.00	100.00%	0.000	0.004	0.018	
	Valves	Light Liquid	64	0.0089	0.57	2.49	88.00%	0.07	100.00%	0.000	0.068	0.299	
	Pump Seals	Light Liquid	2	0.04378	0.09	0.38	75.00%	0.02	100.00%	0.000	0.022	0.096	
	Compressors	Gas/Vapor	0	0.5016	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Relief Valves	Gas/Vapor	16	0.2288	3.66	16.03	92.00%	0.29	100.00%	0.000	0.293	1.283	
	Sampling Connections	All	0	0.033	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Open Ended Lines	All	0	0.00374	0.00	0.00		0.00	100.00%	0.000	0.000	0.000	
	Connectors	All	438	0.004026	1.76	7.72	93.00%	0.12	100.00%	0.000	0.123	0.541	
Totals					34.72	152.06		3.28		0.42	2.86	12.51	

Methodology

* Component count provided by source.

** Emission factors are from Protocol for Equipment leak Emission Estimates, EPA-453/R-95-017, Table 2-1 and Table 5-2

2. Fugitive HAP Emissions:

Fugitive HAP Emissions (tons/yr) = Controlled TOC (tons/yr) x HAP Fraction

HAP	HAP Fraction*	Fugitive HAP Emissions (tons/yr)
Acetaldehyde **	2.00E-04	2.50E-03
Methanol	2.00E-04	2.50E-03
Benzene	2.50E-03	3.13E-02
Carbon Disulfide	2.00E-05	2.50E-04
Cumene	1.00E-03	1.25E-02
Ethylbenzene	5.00E-05	6.26E-04
n-Hexane	5.00E-02	6.26E-01
Toluene	5.00E-03	6.26E-02
Xylenes	5.00E-04	6.26E-03
Total		0.74

**Appendix A: Emission Calculations
PM/PM10 Emissions
From the the Cooling Tower (F005)**

**Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010**

1. Process Description:

Type of Cooling Tower: Induced Draft
Circulation Flow Rate: 45,000 gal/min
Total Drift: 0.005% of the circulating flow
Total Dissolved Solids: 2,500 ppm
Density: 8.345 lbs/gal

Note: The information above was provided by the cooling tower manufacturer for the same units located at a similar source.

2. Potential to Emit PM/PM10:

Assume all the dissolved solids become PM10 emissions and assume PM emissions are equal to PM10 emissions.

$$\text{PTE of PM/PM10 (lbs/hr)} = 33,000 \text{ gal/min} \times 60 \text{ min/hr} \times 0.005\% \times 8.345 \text{ lbs/gal} \times 2,500 \text{ ppm} \times 1/1,000,000 \text{ ppm} = \mathbf{2.82 \text{ lbs/hr}}$$

$$\text{PTE of PM/PM10 (tons/yr)} = 2.07 \text{ lbs/hr} \times 8760 \text{ hr/yr} \times 1 \text{ ton}/2000 \text{ lbs} = \mathbf{12.34 \text{ tons/yr}}$$

**Appendix A: Emission Calculations
VOC Emissions
Storage Tanks**

**Company Name: POET Biorefining - Cloverdale, LLC
Address: 2265 East County Road 800 South, Cloverdale, IN 46120
FESOP: F 133-29592-00003
Plt ID: 133-00003
Reviewer: Jason R. Krawczyk
Date: September 21, 2010**

Tank ID	lb/year	lb/hr	Tons/year
T001	2,005.93	0.23	1.00
T002	955.94	0.11	0.48
T003	360.13	0.04	0.18
T004	360.13	0.04	0.18
T005	1,654.21	0.19	0.83
Total:			2.67

Emissions were calculated using Tanks 4.0.9d software and submitted by the source.



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

SENT VIA U.S. MAIL: CONFIRMED DELIVERY AND SIGNATURE REQUESTED

TO: Dave Brooks
POET Biorefining – Cloverdale, LLC
2265 East CR 800 S
Cloverdale, IN 46120

DATE: November 5, 2010

FROM: Matt Stuckey, Branch Chief
Permits Branch
Office of Air Quality

SUBJECT: Final Decision
Significant Permit Revision
133-29592-00003

Enclosed is the final decision and supporting materials for the air permit application referenced above. Please note that this packet contains the original, signed, permit documents.

The final decision is being sent to you because our records indicate that you are the contact person for this application. However, if you are not the appropriate person within your company to receive this document, please forward it to the correct person.

A copy of the final decision and supporting materials has also been sent via standard mail to:
Rafe Christopherson (POET Design & Construction)
OAQ Permits Branch Interested Parties List

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178, or toll-free at 1-800-451-6027 (ext. 3-0178), and ask to speak to the permit reviewer who prepared the permit. If you think you have received this document in error, please contact Joanne Smiddie-Brush of my staff at 1-800-451-6027 (ext 3-0185), or via e-mail at jbrush@idem.IN.gov.

Final Applicant Cover letter.dot 11/30/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

November 5, 2010

TO: Putnam County Public Library

From: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

Subject: **Important Information for Display Regarding a Final Determination**

Applicant Name: POET Biorefining – Cloverdale, LLC
Permit Number: 133-29592-00003

You previously received information to make available to the public during the public comment period of a draft permit. Enclosed is a copy of the final decision and supporting materials for the same project. Please place the enclosed information along with the information you previously received. To ensure that your patrons have ample opportunity to review the enclosed permit, **we ask that you retain this document for at least 60 days.**

The applicant is responsible for placing a copy of the application in your library. If the permit application is not on file, or if you have any questions concerning this public review process, please contact Joanne Smiddie-Brush, OAQ Permits Administration Section at 1-800-451-6027, extension 3-0185.

Enclosures
Final Library.dot 11/30/07



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

Mitchell E. Daniels Jr.
Governor

Thomas W. Easterly
Commissioner

100 North Senate Avenue
Indianapolis, Indiana 46204
(317) 232-8603
Toll Free (800) 451-6027
www.idem.IN.gov

TO: Interested Parties / Applicant

DATE: November 5, 2010

RE: POET Biorefining – Cloverdale, LLC / 133-29592-00003

FROM: Matthew Stuckey, Branch Chief
Permits Branch
Office of Air Quality

In order to conserve paper and reduce postage costs, IDEM's Office of Air Quality is now sending many permit decisions on CDs in Adobe PDF format. The enclosed CD contains information regarding the company named above.

This permit is also available on the IDEM website at:
<http://www.in.gov/ai/appfiles/idem-caats/>

If you would like to request a paper copy of the permit document, please contact IDEM's central file room at:

Indiana Government Center North, Room 1201
100 North Senate Avenue, MC 50-07
Indianapolis, IN 46204
Phone: 1-800-451-6027 (ext. 4-0965)
Fax (317) 232-8659

Please Note: *If you feel you have received this information in error, or would like to be removed from the Air Permits mailing list, please contact Patricia Pear with the Air Permits Administration Section at 1-800-451-6027, ext. 3-6875 or via e-mail at PPEAR@IDEM.IN.GOV.*

Enclosures
CD Memo.dot 11/14/08

Mail Code 61-53

IDEM Staff	MIDENNEY 11/5/2010 POET Biorefining- Cloverdale, LLC 133-29592-00003 (final)		AFFIX STAMP HERE IF USED AS CERTIFICATE OF MAILING	
Name and address of Sender		Indiana Department of Environmental Management Office of Air Quality – Permits Branch 100 N. Senate Indianapolis, IN 46204	Type of Mail: CERTIFICATE OF MAILING ONLY	

Line	Article Number	Name, Address, Street and Post Office Address	Postage	Handing Charges	Act. Value (If Registered)	Insured Value	Due Send if COD	R.R. Fee	S.D. Fee	S.H. Fee	Rest. Del. Fee	Remarks
1		Dave Brooks POET Biorefining- Cloverdale, LLC 2265 East CR 800 S Cloverdale IN 46120 (Source CAATS) VIA CONFIRMED DELIVERY										
2		Cloverdale Town Council P.O. Box 222 Cloverdale IN 46120 (Local Official)										
3		Putnam County Commissioners One West Washington Street Greencastle IN 46135 (Local Official)										
4		Putnam Co Public Library 103 E Poplar Street Greencastle IN 46135-0116 (Library)										
5		Putnam County Health Department 209 W. Liberty Street Rm. 13, Courthouse, 4th Floor Greencastle IN 46135-1502 (Health Department)										
6		Mr. Richard Monday 545 E. Margaret Dr. Terre Haute IN 47801 (Affected Party)										
7		J.P. Roehm PO Box 303 Clinton IN 47842 (Affected Party)										
8		Mr. Tim Thomas c/o Boilermakers Local 374 6333 Kennedy Ave. Hammond IN 46333 (Affected Party)										
9		Mr. Rafe Christopherson POET Design & Construction 4615 N Lewis Ave Sioux Falls SD 57104 (Source & addl contact)										
10		Mr. Colin OBrien Natural Resources Defense Council 1200 New York Avenue NW, Ste. 400 Washington DC 20005 (Affected Party)										
11		Emily Davis Natural Resources Defense Council 1200 New York Ave. NW Ste 400 Washington DC 20005 (Affected Party)										
12												
13												
14												
15												

Total number of pieces Listed by Sender 10	Total number of Pieces Received at Post Office	Postmaster, Per (Name of Receiving employee)	The full declaration of value is required on all domestic and international registered mail. The maximum indemnity payable for the reconstruction of nonnegotiable documents under Express Mail document reconstructing insurance is \$50,000 per piece subject to a limit of \$50,000 per occurrence. The maximum indemnity payable on Express mail merchandise insurance is \$500. The maximum indemnity payable is \$25,000 for registered mail, sent with optional postal insurance. See Domestic Mail Manual R900, S913, and S921 for limitations of coverage on insured and COD mail. See International Mail Manual for limitations of coverage on international mail. Special handling charges apply only to Standard Mail (A) and Standard Mail (B) parcels.
--	--	--	--