INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We make Indiana a cleaner, healthier place to live

Evan Bayh
Governor

Michael O'Connor
Commissioner

100 North Senate Avenue
P.O. Box 6015
Indianapolis, Indiana 46206-6015
Telephone 317-232-8603
Environmental Helpline 1-800-451-6027

December 20, 2001

VIA CERTIFIED MAIL

Mr. Matt Gertz
Koch Materials Company
2820 E. Durbin St.
Warsaw, IN 46580

Re: Registered Construction and Operation Status,
CP 085-6192, Plt ID 085-00066

Dear Mr. Gertz:

The application from Koch Materials Company received on June 26,1996, has been reviewed. Based on the data submitted and the provisions in Sections 1 and 2 of 326 IAC 2-1, it has been determined that the following, to be located at 2820 E. Durbin St. in the city of Warsaw, Indiana, is classified as registered:

One (1) boiler, fueled by natural gas only, identified as B-1, heat capacity is 6.28 MMBtu per hour. Stack height is 20 feet with a diameter of 16 inches.

One (1) hot water heater, fueled by natural gas only, identified as WH-1, heat capacity is 3.00 MMBtu per hour. Two (2) stacks each having a height of 13 feet with a diameter of 16 inches.

One (1) hot oil heater, fueled by natural gas only, identified as HO-1, heat capacity is 4.40 MMBtu per hour. Stack height is 15 feet with a diameter of 12 inches.

One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-1, heat capacity is 1.25 MMBtu per hour. Stack height is 22 feet with a diameter of 10.75 inches.

One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-2, heat capacity is 1.25 MMBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.

One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-3, heat capacity is 1.25 MMBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.

One (1) loading rack, product name is asphalt emulsion, truck rack annual throughput is 93,440.0 Mgal per year

One (1) loading rack, product name is polymer modified asphalt, truck rack annual throughput is 16,700.0 Mgal per year.

Three (3) emulsion loading racks, identified as 1, 2, 3, each have a throughput of 18,000 gallons per hour.

One (1) emulsion loading racks, identified as 4, having a throughput of 8,000 gallons per hour.

Tank 101
Used to store asphalt cement
Storage capacity: 20,000 gallons
Annual throughput: 877,400 gallon per year
Diameter: 10.50 feet
Height: 31.00 feet

Tank 102
Used to store asphalt cement
Storage capacity: 84,000 gallons
Annual throughput: 3,685,100 gallon per year
Diameter: 29.67 feet
Height: 16.00 feet

Tank 103
Used to store asphalt cement
Storage capacity: 84,000 gallons
Annual throughput: 3,685,100 gallon per year
Diameter: 29.67 feet
Height: 16.00 feet

Tank 104
Used to store asphalt cement
Storage capacity: 168,000 gallons
Annual throughput: 7,370,100 gallon per year
Diameter: 29.89 feet
Height: 32.00 feet

Tank 105
Used to store asphalt cement
Storage capacity: 500,000 gallons
Annual throughput: 33,447,300 gallon per year
Diameter: 51.00feet
Height: 32.00 feet

Tank 106
Used to store asphalt cement
Storage capacity: 500,000 gallons
Annual throughput: 33,447,300 gallon per year
Diameter: 51.00 feet
Height: 32.00feet

Tank 107
Used to store asphalt cement
Storage capacity: 24,681gallons
Annual throughput: 1,082,800 gallon per year
Diameter: 10.50 feet
Height: 38.00 feet

Tank 120
Used to store asphalt cement
Storage capacity: 25,000 gallons
Annual throughput: 15,656,600 gallon per year
Diameter: 10.50 feet
Height: 38.00 feet

Tank 140

Used to store asphalt cement batch
Storage capacity: 1,500 gallons
Annual throughput: 1,043,800 gallon per year
Diameter: 7.00 feet
Height: 7.50 feet
Controlled by potassium permanganate canister (H2S control)

Tank 150

Used to store asphalt cement batch
Storage capacity: 24,000 gallons
Annual throughput: 16,700,400 gallon per year
Diameter: 16.00 feet
Height: 16.00 feet
Controlled by potassium permanganate canister (H2S control)

Tank 201

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 202

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 203

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 204

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 205

Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 206

Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 207
Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 208
Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 209
Used to store asphalt emulsion
Storage capacity: 124,000 gallons
Annual throughput: 15,500,500 gallon per year
Diameter: 29.67 feet
Height: 24.00 feet

Tank 210
Used to store asphalt emulsion
Storage capacity: 124,000 gallons
Annual throughput: 15,500,500 gallon per year
Diameter: 29.67 feet
Height: 24.00 feet

Tank 211
Used to store asphalt emulsion
Storage capacity: 31,500 gallons
Annual throughput: 3,937,700 gallon per year
Diameter: 15.39 feet
Height: 24.00 feet

Tank 212
Used to store asphalt emulsion
Storage capacity: 48,000 gallons
Annual throughput: 6,000,200 gallon per year
Diameter: 16.00 feet
Height: 32.00 feet

Tank 400
Used to store fuel oil
Storage capacity: 20,135 gallons
Annual throughput: 14,016,000 gallon per year
Diameter: 10.50 feet
Height: 31.00 feet

Tank 401
Used to store: fuel oil
Storage capacity: 10,410 gallons
Annual throughput: currently not in use
Diameter: 10.50 feet
Height: 16.00 feet

Tank 410

Used to store: CR-1
Storage capacity: 20,135 gallons
Annual throughput: currently not in use
Diameter: 10.50 feet
Height: 16.00 feet

The following conditions shall be applicable:

Tanks 102, 103, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210 and 212 are subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.110), Subpart K. There are no specific requirements that apply to these tanks. (copy enclosed)

Tanks 105, 106, are subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.110a), Subpart Ka. There are no specific requirements that apply to these tanks. (copy enclosed)

Tank 104 is subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.116b(b) Subpart Kb. This rule requires the source owner/operator to keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. (copy enclosed)

Any change or modification which may increase the potential particulate matter, sulfur dioxide, oxides of nitrogen, carbon monoxide and volatile organic compounds emissions to 25 tons per year or more from the equipment covered in this registration must be approved by the Office of Air Management (OAM) before such change may occur.

Sincerely,

Paul Dubenetzky, Chief
Permits Branch
Office of Air Management

paf

Enclosure: NSPS Subparts K, Ka, Kb

cc: File - Kosciusko County
Kosciusko County Health Department
Air Compliance - Pat Powlen Name
Permit Tracking - Janet bley
Data Support Section - Nancy Landau
Office of Enforcement

Indiana Department of Environmental Management (IDEM)
Office of Air Management

Technical Support Document (TSD) for Registered Emission Unit/s

Koch Materials Company
2820 E. Durbin St.
Warsaw, IN 46580

The Office of Air Management (OAM) has reviewed an application from Koch Materials Company relating to the construction and operation of the following:

One (1) boiler, fueled by natural gas only, identified as B-1, heat capacity is 6.28 MMBtu per hour. Stack height is 20 feet with a diameter of 16 inches.

One (1) hot water heater, fueled by natural gas only, identified as WH-1, heat capacity is 3.00 MMBtu per hour. Two (2) stacks each having a height of 13 feet with a diameter of 16 inches.

One (1) hot oil heater, fueled by natural gas only, identified as HO-1, heat capacity is 4.40 MMBtu per hour. Stack height is 15 feet with a diameter of 12 inches.

One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-1, heat capacity is 1.25 MMBtu per hour. Stack height is 22 feet with a diameter of 10.75 inches.

One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-2, heat capacity is 1.25 MMBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.

One (1) direct-fire immersion heater, fueled by natural gas only, identified as IM-3, heat capacity is 1.25 MMBtu per hour. Stack height is 33 feet with a diameter of 10.75 inches.

One (1) loading rack, product name is asphalt emulsion, truck rack annual throughput is 93,440.0 Mgal per year.

One (1) loading rack, product name is polymer modified asphalt, truck rack annual throughput is 16,700.0 Mgal per year.

Three (3) emulsion loading racks, identified as 1, 2, 3, each have a throughput of 18,000 gallons per hour.

One (1) emulsion loading racks, identified as 4, having a throughput of 8,000 gallons per hour.

Tank 101
Used to store asphalt cement
Storage capacity: 20,000 gallons
Annual throughput: 877,400 gallon per year
Diameter: 10.50 feet
Height: 31.00 feet

Tank 102

Used to store asphalt cement
Storage capacity: 84,000 gallons
Annual throughput: 3,685,100 gallon per year
Diameter: 29.67 feet
Height: 16.00 feet

Tank 103

Used to store asphalt cement
Storage capacity: 84,000 gallons
Annual throughput: 3,685,100 gallon per year
Diameter: 29.67 feet
Height: 16.00 feet

Tank 104

Used to store asphalt cement
Storage capacity: 168,000 gallons
Annual throughput: 7,370,100 gallon per year
Diameter: 29.89 feet
Height: 32.00 feet

Tank 105

Used to store asphalt cement
Storage capacity: 500,000 gallons
Annual throughput: 33,447,300 gallon per year
Diameter: 51.00feet
Height: 32.00 feet

Tank 106

Used to store asphalt cement
Storage capacity: 500,000 gallons
Annual throughput: 33,447,300 gallon per year
Diameter: 51.00 feet
Height: 32.00feet

Tank 107

Used to store asphalt cement
Storage capacity: 24,681gallons
Annual throughput: 1,082,800 gallon per year
Diameter: 10.50 feet
Height: 38.00 feet

Tank 120

Used to store asphalt cement
Storage capacity: 25,000 gallons
Annual throughput: 15,656,600 gallon per year
Diameter: 10.50 feet
Height: 38.00 feet

Tank 140

Used to store asphalt cement batch
Storage capacity: 1,500 gallons
Annual throughput: 1,043,800 gallon per year
Diameter: 7.00 feet
Height: 7.50 feet
Controlled by potassium permanganate canister (H2S control)

Tank 150

Used to store asphalt cement batch
Storage capacity: 24,000 gallons
Annual throughput: 16,700,400 gallon per year
Diameter: 16.00 feet
Height: 16.00 feet
Controlled by potassium permanganate canister (H2S control)

Tank 201

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 202

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 203

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 204

Used to store asphalt emulsion
Storage capacity: 42,000 gallons
Annual throughput: 5,250,200 gallon per year
Diameter: 15.39 feet
Height: 32.00 feet

Tank 205

Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 206

Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 207

Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 208

Used to store asphalt emulsion
Storage capacity: 63,000 gallons
Annual throughput: 7,875,300 gallon per year
Diameter: 21.50 feet
Height: 24.00 feet

Tank 209

Used to store asphalt emulsion
Storage capacity: 124,000 gallons
Annual throughput: 15,500,500 gallon per year
Diameter: 29.67 feet
Height: 24.00 feet

Tank 210
Used to store asphalt emulsion
Storage capacity: 124,000 gallons
Annual throughput: 15,500,500 gallon per year
Diameter: 29.67 feet
Height: 24.00 feet

Tank 211
Used to store asphalt emulsion
Storage capacity: 31,500 gallons
Annual throughput: 3,937,700 gallon per year
Diameter: 15.39 feet
Height: 24.00 feet

Tank 212
Used to store asphalt emulsion
Storage capacity: 48,000 gallons
Annual throughput: 6,000,200 gallon per year
Diameter: 16.00 feet
Height: 32.00 feet

Tank 400
Used to store fuel oil
Storage capacity: 20,135 gallons
Annual throughput: 14,016,000 gallon per year
Diameter: 10.50 feet
Height: 31.00 feet

Tank 401
Used to store: fuel oil
Storage capacity: 10,410 gallons
Annual throughput: currently not in use
Diameter: 10.50 feet
Height: 16.00 feet

Tank 410
Used to store: CR-1
Storage capacity: 20,135 gallons
Annual throughput: currently not in use
Diameter: 10.50 feet
Height: 16.00 feet

Enforcement Issue

IDEM is aware that these facilities mentioned above have been constructed and operated prior to receipt of the proper permit. IDEM is reviewing this matter and will take appropriate action. This proposed registration is intended to satisfy the requirements of the construction permit rules.

Recommendation

The staff recommends to the Commissioner that the construction and operation be approved. This recommendation is based on the following facts and conditions:

A complete application for the purposes of this review was received on June 26, 1996.

Total Potential and Allowable Emissions

Pollutant	Potential Emissions	
	(lb/day)	(ton/yr)
PM	4.9	0.9
NOx	41.6	7.6
VOC	40.0	7.3
CO	8.8	1.6
HAPs	1.1x10^-4	4.8x10^4

See attached spreadsheet(s) for detailed calculations and refer to the application itself since some of the calculations were used.

Potential emissions are used for the permitting determination.

Allowable emissions (as defined in the Indiana Rule) of volatile organic compounds and oxides of nitrogen are less than 25 tons per year, but greater than 15 and 25 pounds per day (respectively). Therefore, pursuant to 326 IAC 2-1, a registration is required.

According to Koch Materials Company tanks 301 thru 306 and 340, 341,350, 500, 501, 520 and 530 were not included in the total tanks emissions since the thanks do not emit volatile organic compounds.

County Attainment Status

Kosciusko County has been classified as attainment or unclassifiable for criteria pollutants.

Federal Rule Applicability

This source is not covered by NSPS Subpart I - Standards of Performance for Hot Mix Asphalt Facilities because this source is not a hot mix asphalt plant.

Tanks 102, 103, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210 and 212 are subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.110), Subpart K. There are no specific requirements that apply to these tanks. (copy enclosed)

Tanks 105, 106, are subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.110a), Subpart Ka. There are no specific requirements that apply to these tanks. (copy enclosed)

Tank 104 is subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.116b(b) Subpart Kb. This rule requires the source owner/operator to keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. (copy enclosed)

NSPS tank rule applicability

Tank ID and year	Capacity gallons	PSIA	NSPS Applicability	NSPS Nonapplicability	Requirements
101, 1975	20,000	0.035		Subpart K is not applicable since the capacity is less than 40,000 gallons.	
102, 103 1975	84,000	0.035	Subpart K is applicable because each capacity is greater than 65,000 gallons.		None because the reid vapor pressure is less than 1.0 psia.
104 1992	168,000 636 m^3	0.035 0.2 kPa	Subpart Kb 60.116b(b)is applicable since the capacity is greater than 40 m^3.		60.116b Records shall be kept showing the dimension of the storage tank and capacity of the tank.
105, 106 1979	500,000	0.035	Subpart Ka is applicable because each capacity is greater than 40,000 gallons.		None because the reid vapor pressure is less than 1.0 psia.
107 1975	24,681	0.035		Subpart K is not applicable since the capacity is less than 40,000 gallons.	
120 1975	25,000	0.035		Subpart K is not applicable since the capacity is less than 40,000 gallons.	
140 1982	1,500	0.035		Subpart Ka is not applicable since the capacity is less than 40,000 gallons.	
150 1982	24,000	0.035		Subpart Ka is not applicable since the capacity is less than 40,000 gallons.	

Tank ID and year	Capacity gallons	PSIA	NSPS Applicability	NSPS Nonapplicability	Requirements
201, 202, 203, 204 1975	42,000	0.0012	Subpart K is applicable because each capacity is greater than 40,000 gallons.		None because the reid vapor pressure is less than 1.0 psia.
205, 206, 207, 208 1975	63,000	0.0012	Subpart K is applicable because each capacity is greater than 40,000 gallons.		None because the reid vapor pressure is less than 1.0 psia.
209, 210 1975	124,000	0.0012	Subpart K is applicable because each capacity is greater than 65,000 gallons.		None because the reid vapor pressure is less than 1.0 psia.
211 1975	31,500	0.0012		Subpart K is not applicable since the capacity is less than 40,000 gallons.	
212 1975	48,000	0.0012	Subpart K is applicable because each capacity is greater than 40,000 gallons.		None because the reid vapor pressure is less than 1.0 psia.
400 1975	20,135	0.0012		Subpart K is not applicable since the capacity is less than 40,000 gallons.	
401 1975	10,410	0.00006		Subpart K is not applicable since the capacity is less than 40,000 gallons.	
410 1983	10,410	0.00006		Subpart Ka is not applicable since the capacity is less than 40,000 gallons.	

State Rule Applicability

326 IAC 8-4-3 Petroleum sources: petroleum liquid storage facilities

All tanks are exempt from 326 IAC 8-4-3 petroleum liquid storage facilities because the true vapor pressure for each tank is less than 1.52 psi.

Air Toxic Emissions

Indiana presently requests applicants to provide information on emissions of 189 hazardous air pollutant as set out in the Clean Air Act Amendments. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries in the state. They are listed as air toxics on the Office of Air Management (OAM) Construction Permit Application Form Y.

The Koch Materials Company will emit levels of air toxics less than those which constitutes a major source according to Title III of the 1990 Amendments to Clean Air Act.

Air Toxic Analysis

Pollutant	Stack/Vent	Rate (lb/hr)	Rate @ 8760 hr/yr (ton/yr)
Benzene	tank 400	4.3x10^-8	1.9x10^-7
Biphenyl	tank 400	5.3x10^-5	2.3X10^-4
Ethylbenzene	tank 400	6.9x10^-7	3.0x10^-6
Hexane	tank 400	5.3x10^-9	2.3x10^-8
Naphthalene	all PMAC/AC and emulsion tanks and loading racks	5.3x10^-5	2.3x10^-4
TOTAL		1.1x10^-4	4.8x10^4

Air Toxic Stack/Vent

Stack /Vent ID	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (^{0}F)
n/a				
n/a				

Methodology: Rate ton/yr = (rate lb/hr)*(8760 hr/yr)*(1 ton/2000 lb)

Conclusion

The construction of the equipment listed on page 1thru 10 will be subject to the conditions of the attached proposed **Registration No. CP-085-6192, Plt ID No. 085-00066.**

Appendix A: Emission Calculations
Natural Gas Combustion Only
MM Btu/hr 0.3 - < 10
Commercial Boiler

Company Name: **Koch Materials Company**
Address City IN Zip: **Warsaw, IN**
CP: **085-6192**
Plt ID: **085-00066**
Reviewer: Peggy Flickinger
Date: 08/16/96

15 heaters

Heat Input Capacity MMBtu/hr	Potential Throughput MMCF/yr
17.4	152.7

	Pollutant					
	PM	PM10	SO2	NOx	VOC	CO
Emission Factor in lb/MMCF	12.0	12.0	0.6	100.0	5.3	21.0
Potential Emission in tons/yr	0.9	0.9	0.0	7.6	0.4	1.6
total emissions tons/yr:						

Methodology

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Emission Factors for NOx: uncontrolled = 100, Low Nox Burner = 17, Flue gas recirculation = 36

Emission Factors for CO: uncontrolled = 21, Low NOx Burner = 27, Flue gas recirculation = ND

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, and 1.4-3, SCC #1-03-006-03

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton
Emission (tons/yr) = total number of combustion units x emission

Koch Materials Company
Warsaw, IN
Reviewer: Peggy Flickinger

CP '085-6192
Plt ID '085-00066

EMISSIONS SUMMARY

Equipment	PM	PM10	SO2	NOx	VOC	CO
15 combustion units	0.9	0.9	0.0	7.6	0.4	1.6
23 tanks	0.0	0.0	0.0	0.0	5.3	0.0
loading rack	0.0	0.0	0.0	0.0	1.3	0.0
loading rack	0.0	0.0	0.0	0.0	0.3	0.0
tons/yr	0.9	0.9	0.0	7.6	7.3	1.6
lbs/day	4.9	4.9	0.0	41.6	40.0	8.8
lbs/hr	0.2	0.2	0.0	1.7	1.7	0.4

or operators' control, compliance may be determined using available data for the 7-day period.

(e) Each owner or operator subject to § 60.104(b) who has demonstrated compliance with one of the provisions of § 60.104(b) but at a later date seeks to comply with another of the provisions of § 60.104(b) shall begin conducting daily performance tests as specified under paragraph (d) of this section immediately upon electing to become subject to one of the other provisions of § 60.104(b). The owner or operator shall furnish the Administrator a written notification of the change in a quarterly report that must be submitted for the quarter in which the change occurred.

[54 FR 34030, Aug. 17, 1989, as amended at 55 FR 40178, Oct. 2, 1990]

§ 60.109 Delegation of authority.

(a) In delegating implementation and enforcement authority to a State under section 111(c) of the Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.

(b) Authorities which shall not be delegated to States:

(1) Section 60.105(a)(13)(iii).

(2) Section 60.106(i)(12).

[54 FR 34031, Aug. 17, 1989, as amended at 55 FR 40178, Oct. 2, 1990]

Subpart K—Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978

§ 60.110 Applicability and designation of affected facility.

(a) Except as provided in § 60.110(b), the affected facility to which this subpart applies is each storage vessel for petroleum liquids which has a storage capacity greater than 151,412 liters (40,000 gallons).

(b) This subpart does not apply to storage vessels for petroleum or condensate stored, processed, and/or treated at a drilling and production facility prior to custody transfer.

(c) Subject to the requirements of this subpart is any facility under paragraph (a) of this section which:

(1) Has a capacity greater than 151,416 liters (40,000 gallons), but not exceeding 246,052 liters (65,000 gallons), and commences construction or modification after March 8, 1974, and prior to May 19, 1978.

(2) Has a capacity greater than 246,052 liters (65,000 gallons) and commences construction or modification after June 11, 1973, and prior to May 19, 1978.

[42 FR 37937, July 25, 1977, as amended at 45 FR 23379, Apr. 4, 1980]

§ 60.111 Definitions.

As used in this subpart, all terms not defined herein shall have the meaning given them in the Act and in subpart A of this part.

(a) *Storage vessel* means any tank, reservoir, or container used for the storage of petroleum liquids, but does not include:

(1) Pressure vessels which are designed to operate in excess of 15 pounds per square inch gauge without emissions to the atmosphere except under emergency conditions,

(2) Subsurface caverns or porous rock reservoirs, or

(3) Underground tanks if the total volume of petroleum liquids added to and taken from a tank annually does not exceed twice the volume of the tank.

(b) *Petroleum liquids* means petroleum, condensate, and any finished or intermediate products manufactured in a petroleum refinery but does not mean Nos. 2 through 6 fuel oils as specified in ASTM D396-78, gas turbine fuel oils Nos. 2-GT through 4-GT as specified in ASTM D2880-78, or diesel fuel oils Nos. 2-D and 4-D as specified in ASTM D975-78. (These three methods are incorporated by reference—see §60.17.)

(c) *Petroleum refinery* means each facility engaged in producing gasoline, kerosene, distillate fuel oils, residual fuel oils, lubricants, or other products through distillation of petroleum or through redistillation, cracking, extracting, or reforming of unfinished petroleum derivatives.

(d) *Petroleum* means the crude oil removed from the earth and the oils derived from tar sands, shale, and coal.

(e) *Hydrocarbon* means any organic compound consisting predominantly of carbon and hydrogen.

(f) *Condensate* means hydrocarbon liquid separated from natural gas which condenses due to changes in the temperature and/or pressure and remains liquid at standard conditions.

(g) *Custody transfer* means the transfer of produced petroleum and/or condensate, after processing and/or treating in the producing operations, from storage tanks or automatic transfer facilities to pipelines or any other forms of transportation.

(h) *Drilling and production facility* means all drilling and servicing equipment, wells, flow lines, separators, equipment, gathering lines, and auxiliary nontransportation-related equipment used in the production of petroleum but does not include natural gasoline plants.

(i) *True vapor pressure* means the equilibrium partial pressure exerted by a petroleum liquid as determined in accordance with methods described in American Petroleum Institute Bulletin 2517, Evaporation Loss from External Floating-Roof Tanks, Second Edition, February 1980 (incorporated by reference—see §60.17).

(j) *Floating roof* means a storage vessel cover consisting of a double deck, pontoon single deck, internal floating cover or covered floating roof, which rests upon and is supported by the petroleum liquid being contained, and is equipped with a closure seal or seals to close the space between the roof edge and tank wall.

(k) *Vapor recovery system* means a vapor gathering system capable of collecting all hydrocarbon vapors and gases discharged from the storage vessel and a vapor disposal system capable of processing such hydrocarbon vapors and gases so as to prevent their emission to the atmosphere.

(l) *Reid vapor pressure* is the absolute vapor pressure of volatile crude oil and volatile nonviscous petroleum liquids, except liquified petroleum gases, as determined by ASTM D323-82 (incorporated by reference—see § 60.17).

[39 FR 9317, Mar. 8, 1974; 39 FR 13776, Apr. 17, 1974, as amended at 39 FR 20794, June 14, 1974; 45 FR 23379, Apr. 4, 1980; 48 FR 3737, Jan. 27, 1983; 52 FR 11429, Apr. 8, 1987]

§ 60.112 Standard for volatile organic compounds (VOC).

(a) The owner or operator of any storage vessel to which this subpart applies shall store petroleum liquids as follows:

(1) If the true vapor pressure of the petroleum liquid, as stored, is equal to or greater than 78 mm Hg (1.5 psia) but not greater than 570 mm Hg (11.1 psia), the storage vessel shall be equipped with a floating roof, a vapor recovery system, or their equivalents.

(2) If the true vapor pressure of the petroleum liquid as stored is greater than 570 mm Hg (11.1 psia), the storage vessel shall be equipped with a vapor recovery system or its equivalent.

[39 FR 9317, Mar. 8, 1974; 39 FR 13776, Apr. 17, 1974, as amended at 45 FR 23379, Apr. 4, 1980]

§ 60.113 Monitoring of operations.

(a) Except as provided in paragraph (d) of this section, the owner or operator subject to this subpart shall maintain a record of the petroleum liquid stored, the period of storage, and the maximum true vapor pressure of that liquid during the respective storage period.

(b) Available data on the typical Reid vapor pressure and the maximum expected storage temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517, unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).

(c) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa (2.0 psia) or whose physical properties preclude determination by the recommended method is to be determined from available data and recorded if the estimated true vapor pressure is greater than 6.9 kPa (1.0 psia).

(d) The following are exempt from the requirements of this section:

(1) Each owner or operator of each affected facility which stores petroleum liquids with a Reid vapor pressure of less than 6.9 kPa (1.0 psia) provided the

maximum true vapor pressure does not exceed 6.9 kPa (1.0 psia).

(2) Each owner or operator of each affected facility equipped with a vapor recovery and return or disposal system in accordance with the requirements of § 60.112.

[45 FR 23379, Apr. 4, 1980]

Subpart Ka—Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984

§ 60.110a Applicability and designation of affected facility.

(a) Except as provided in paragraph (b) of this section, the affected facility to which this subpart applies is each storage vessel for petroleum liquids which has a storage capacity greater than 151,416 liters (40,000 gallons) and for which construction is commenced after May 18, 1978.

(b) Each petroleum liquid storage vessel with a capacity of less than 1,589,873 liters (420,000 gallons) used for petroleum or condensate stored, processed, or treated prior to custody transfer is not an affected facility and, therefore, is exempt from the requirements of this subpart.

[45 FR 23379, Apr. 4, 1980]

§ 60.111a Definitions.

In addition to the terms and their definitions listed in the Act and subpart A of this part the following definitions apply in this subpart:

(a) *Storage vessel* means each tank, reservoir, or container used for the storage of petroleum liquids, but does not include:

(1) Pressure vessels which are designed to operate in excess of 204.9 kPa (15 psig) without emissions to the atmosphere except under emergency conditions.

(2) Subsurface caverns or porous rock reservoirs, or

(3) Underground tanks if the total volume of petroleum liquids added to and taken from a tank annually does not exceed twice the volume of the tank.

(b) *Petroleum liquids* means petroleum, condensate, and any finished or intermediate products manufactured in a petroleum refinery but does not mean Nos. 2 through 6 fuel oils as specified in ASTM D396-78, gas turbine fuel oils Nos. 2-GT through 4-GT as specified in ASTM D2880-78, gas turbine fuel oils Nos. 2-GT through 4-GT as specified in ASTM D2880-78, or diesel fuel oils Nos. 2-D and 4-D as specified in ASTM D975-78. (These three methods are incorporated by reference—see § 60.17.)

(c) *Petroleum refinery* means each facility engaged in producing gasoline, kerosene, distillate fuel oils, residual fuel oils, lubricants, or other products through distillation of petroleum or through redistillation, cracking, extracting, or reforming of unfinished petroleum derivatives.

(d) *Petroleum* means the crude oil removed from the earth and the oils derived from tar sands, shale, and coal.

(e) *Condensate* means hydrocarbon liquid separated from natural gas which condenses due to changes in the temperature or pressure, or both, and remains liquid at standard conditions.

(f) *True vapor pressure* means the equilibrium partial pressure exerted by a petroleum liquid such as determined in accordance with methods described in American Petroleum Institute Bulletin 2517, Evaporation Loss from External Floating-Roof Tanks, Second Edition, February 1980 (incorporated by reference—see § 60.17).

(g) *Reid vapor pressure* is the absolute vapor pressure of volatile crude oil and nonviscous petroleum liquids, except liquified petroleum gases, as determined by ASTM D323-82 (incorporated by reference—see § 60.17).

(h) *Liquid-mounted seal* means a foam or liquid-filled primary seal mounted in contact with the liquid between the tank wall and the floating roof continuously around the circumference of the tank.

(i) *Metallic shoe seal* includes but is not limited to a metal sheet held vertically against the tank wall by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.

(j) *Vapor-mounted seal* means a foam-filled primary seal mounted continuously around the circumference of the tank so there is an annular vapor space underneath the seal. The annular vapor space is bounded by the bottom of the primary seal, the tank wall, the liquid surface, and the floating roof.

(k) *Custody transfer* means the transfer of produced petroleum and/or condensate, after processing and/or treating in the producing operations, from storage tanks or automatic transfer facilities to pipelines or any other forms of transportation.

[45 FR 23379, Apr. 4, 1980, as amended at 48 FR 3737, Jan. 27, 1983; 52 FR 11429, Apr. 8, 1987]

§ 60.112a Standard for volatile organic compounds (VOC).

(a) The owner or operator of each storage vessel to which this subpart applies which contains a petroleum liquid which, as stored, has a true vapor pressure equal to or greater than 10.3 kPa (1.5 psia) but not greater than 76.6 kPa (11.1 psia) shall equip the storage vessel with one of the following:

(1) An external floating roof, consisting of a pontoon-type or double-deck-type cover that rests on the surface of the liquid contents and is equipped with a closure device between the tank wall and the roof edge. Except as provided in paragraph (a)(1)(ii)(D) of this section, the closure device is to consist of two seals, one above the other. The lower seal is referred to as the primary seal and the upper seal is referred to as the secondary seal. The roof is to be floating on the liquid at all times (i.e., off the roof leg supports) except during initial fill and when the tank is completely emptied and subsequently refilled. The process of emptying and refilling when the roof is resting on the leg supports shall be continuous and shall be accomplished as rapidly as possible.

(i) The primary seal is to be either a metallic shoe seal, a liquid-mounted seal, or a vapor-mounted seal. Each seal is to meet the following requirements:

(A) The accumulated area of gaps between the tank wall and the metallic shoe seal or the liquid-mounted seal shall not exceed 212 cm^2 per meter of tank diameter (10.0 in^2 per ft of tank diameter) and the width of any portion of any gap shall not exceed 3.81 cm (1½ in).

(B) The accumulated area of gaps between the tank wall and the vapor-mounted seal shall not exceed 21.2 cm^2 per meter of tank diameter (1.0 in^2 per ft of tank diameter) and the width of any portion of any gap shall not exceed 1.27 cm (½ in).

(C) One end of the metallic shoe is to extend into the stored liquid and the other end is to extend a minimum vertical distance of 61 cm (24 in) above the stored liquid surface.

(D) There are to be no holes, tears, or other openings in the shoe, seal fabric, or seal envelope.

(ii) The secondary seal is to meet the following requirements:

(A) The secondary seal is to be installed above the primary seal so that it completely covers the space between the roof edge and the tank wall except as provided in paragraph (a)(1)(ii)(B) of this section.

(B) The accumulated area of gaps between the tank wall and the secondary seal used in combination with a metallic shoe or liquid-mounted primary seal shall not exceed 21.2 cm^2 per meter of tank diameter (1.0 in^2 per ft. of tank diameter) and the width of any portion of any gap shall not exceed 1.27 cm (½ in.). There shall be no gaps between the tank wall and the secondary seal used in combination with a vapor-mounted primary seal.

(C) There are to be no holes, tears or other openings in the seal or seal fabric.

(D) The owner or operator is exempted from the requirements for secondary seals and the secondary seal gap criteria when performing gap measurements or inspections of the primary seal.

(iii) Each opening in the roof except for automatic bleeder vents and rim space vents is to provide a projection below the liquid surface. Each opening in the roof except for automatic bleeder vents, rim space vents and leg sleeves is to be equipped with a cover, seal or lid which is to be maintained in a closed position at all times (i.e., no

visible gap) except when the device is in actual use or as described in pargraph (a)(1)(iv) of this section. Automatic bleeder vents are to be closed at all times when the roof is floating, except when the roof is being floated off or is being landed on the roof leg supports. Rim vents are to be set to open when the roof is being floated off the roof legs supports or at the manufacturer's recommended setting.

(iv) Each emergency roof drain is to be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening.

(2) A fixed roof with an internal floating type cover equipped with a continuous closure device between the tank wall and the cover edge. The cover is to be floating at all times, (i.e., off the leg supports) except during initial fill and when the tank is completely emptied and subsequently refilled. The process of emptying and refilling when the cover is resting on the leg supports shall be continuous and shall be accomplished as rapidly as possible. Each opening in the cover except for automatic bleeder vents and the rim space vents is to provide a projection below the liquid surface. Each opening in the cover except for automatic bleeder vents, rim space vents, stub drains and leg sleeves is to be equipped with a cover, seal, or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. Automatic bleeder vents are to be closed at all times when the cover is floating except when the cover is being floated off or is being landed on the leg supports. Rim vents are to be set to open only when the cover is being floated off the leg supports or at the manufacturer's recommended setting.

(3) A vapor recovery system which collects all VOC vapors and gases discharged from the storage vessel, and a vapor return or disposal system which is designed to process such VOC vapors and gases so as to reduce their emission to the atmosphere by at least 95 percent by weight.

(4) A system equivalent to those described in paragraphs (a)(1), (a)(2), or (a)(3) of this section as provided in § 60.114a.

(b) The owner or operator of each storage vessel to which this subpart applies which contains a petroleum liquid which, as stored, has a true vapor pressure greater than 76.6 kPa (11.1 psia), shall equip the storage vessel with a vapor recovery system which collects all VOC vapors and gases discharged from the storage vessel, and a vapor return or disposal system which is designed to process such VOC vapors and gases so as to reduce their emission to the atmosphere by at least 95 percent by weight.

[45 FR 23379, Apr. 4, 1980, as amended at 45 FR 83229, Dec. 18, 1980]

§ 60.113a Testing and procedures.

(a) Except as provided in § 60.8(b) compliance with the standard prescribed in § 60.112a shall be determined as follows or in accordance with an equivalent procedure as provided in § 60.114a.

(1) The owner or operator of each storage vessel to which this subpart applies which has an external floating roof shall meet the following requirements:

(i) Determine the gap areas and maximum gap widths between the primary seal and the tank wall and between the secondary seal and the tank wall according to the following frequency:

(A) For primary seals, gap measurements shall be performed within 60 days of the initial fill with petroleum liquid and at least once every five years thereafter. All primary seal inspections or gap measurements which require the removal or dislodging of the secondary seal shall be accomplished as rapidly as possible and the secondary seal shall be replaced as soon as possible.

(B) For secondary seals, gap measurements shall be performed within 60 days of the initial fill with petroleum liquid and at least once every year thereafter.

(C) If any storage vessel is out of service for a period of one year or more, subsequent refilling with petroleum liquid shall be considered initial fill for the purposes of paragraphs (a)(1)(i)(A) and (a)(1)(i)(B) of this section.

(D) Keep records of each gap measurement at the plant for a period of at least 2 years following the date of measurement. Each record shall identify the vessel on which the measurement was performed and shall contain the date of the seal gap measurement, the raw data obtained in the measurement process required by paragraph (a)(1)(ii) of this section and the calculation required by paragraph (a)(1)(iii) of this section.

(E) If either the seal gap calculated in accord with paragraph (a)(1)(iii) of this section or the measured maximum seal gap exceeds the limitations specified by § 60.112a of this subpart, a report shall be furnished to the Administrator within 60 days of the date of measurements. The report shall identify the vessel and list each reason why the vessel did not meet the specifications of § 60.112a. The report shall also describe the actions necessary to bring the storage vessel into compliance with the specifications of § 60.112a.

(ii) Determine gap widths in the primary and secondary seals individually by the following procedures:

(A) Measure seal gaps, if any, at one or more floating roof levels when the roof is floating off the roof leg supports.

(B) Measure seal gaps around the entire circumference of the tank in each place where a ⅛" diameter uniform probe passes freely (without forcing or binding against seal) between the seal and the tank wall and measure the circumferential distance of each such location.

(C) The total surface area of each gap described in paragraph (a)(1)(ii)(B) of this section shall be determined by using probes of various widths to accurately measure the actual distance from the tank wall to the seal and multiplying each such width by its respective circumferential distance.

(iii) Add the gap surface area of each gap location for the primary seal and the secondary seal individually. Divide the sum for each seal by the nominal diameter of the tank and compare each ratio to the appropriate ratio in the standard in § 60.112a(a)(1)(i) and § 60.112a(a)(1)(ii).

(iv) Provide the Administrator 30 days prior notice of the gap measurement to afford the Administrator the opportunity to have an observer present.

(2) The owner or operator of each storage vessel to which this subpart applies which has a vapor recovery and return or disposal system shall provide the following information to the Administrator on or before the date on which construction of the storage vessel commences:

(i) Emission data, if available, for a similar vapor recovery and return or disposal system used on the same type of storage vessel, which can be used to determine the efficiency of the system. A complete description of the emission measurement method used must be included.

(ii) The manufacturer's design specifications and estimated emission reduction capability of the system.

(iii) The operation and maintenance plan for the system.

(iv) Any other information which will be useful to the Administrator in evaluating the effectiveness of the system in reducing VOC emissions.

[45 FR 23379, Apr. 4, 1980, as amended at 52 FR 11429, Apr. 8, 1987]

§ 60.114a Alternative means of emission limitation.

(a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in emissions at least equivalent to the reduction in emissions achieved by any requirement in § 60.112a, the Administrator will publish in the FEDERAL REGISTER a notice permitting the use of the alternative means for purposes of compliance with that requirement.

(b) Any notice under paragraph (a) of this section will be published only after notice and an opportunity for a hearing.

(c) Any person seeking permission under this section shall submit to the Administrator a written application including:

(1) An actual emissions test that uses a full-sized or scale-model storage vessel that accurately collects and measures all VOC emissions from a given control device and that accurately simulates wind and accounts for other emission variables such as temperature and barometric pressure.

(2) An engineering evaluation that the Administrator determines is an accurate method of determining equivalence.

(d) The Administrator may condition the permission on requirements that may be necessary to ensure operation and maintenance to achieve the same emissions reduction as specified in § 60.112a.

(e) The primary vapor-mounted seal in the "Volume-Maximizing Seal" manufactured by R.F.I. Services Corporation is approved as equivalent to the vapor-mounted seal required by § 60.112a(a)(1)(i) and must meet the gap criteria specified in § 60.112a(a)(1)(i)(B). There shall be no gaps between the tank wall and any secondary seal used in conjunction with the primary seal in the "Volume-Maximizing Seal".

[52 FR 11429, Apr. 8, 1987]

§ 60.115a Monitoring of operations.

(a) Except as provided in paragraph (d) of this section, the owner or operator subject to this subpart shall maintain a record of the petroleum liquid stored, the period of storage, and the maximum true vapor pressure of that liquid during the respective storage period.

(b) Available data on the typical Reid vapor pressure and the maximum expected storage temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517, unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).

(c) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa (2.0 psia) or whose physical properties preclude determination by the recommended method is to be determined from available data and recorded if the estimated true vapor pressure is greater than 6.9 kPa (1.0 psia).

(d) The following are exempt from the requirements of this section:

(1) Each owner or operator of each storage vessel storing a petroleum liquid with a Reid vapor pressure of less than 6.9 kPa (1.0 psia) provided the maximum true vapor pressure does not exceed 6.9 kPa (1.0 psia).

(2) Each owner or operator of each storage vessel equipped with a vapor recovery and return or disposal system in accordance with the requirements of § 60.112a (a)(3) and (b).

[45 FR 23379, Apr. 4, 1980]

Subpart Kb—Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984

SOURCE: 52 FR 11429, Apr. 8, 1987, unless otherwise noted.

§ 60.110b Applicability and designation of affected facility.

(a) Except as provided in paragraphs (b), (c), and (d) of this section, the affected facility to which this subpart applies is each storage vessel with a capacity greater than or equal to 40 cubic meters (m^3) that is used to store volatile organic liquids (VOL's) for which construction, reconstruction, or modification is commenced after July 23, 1984.

(b) Except as specified in paragraphs (a) and (b) of § 60.116b, storage vessels with design capacity less than 75 m^3 are exempt from the General Provisions (part 60, subpart A) and from the provisions of this subpart.

(c) Except as specified in paragraphs (a) and (b) of § 60.116b, vessels either with a capacity greater than or equal to 151 m^3 storing a liquid with a maximum true vapor pressure less than 3.5 kPa or with a capacity greater than or equal to 75 m^3 but less than 151 m^3 storing a liquid with a maximum true vapor pressure less than 15.0 kPa are exempt from the General Provisions (part 60, subpart A) and from the provisions of this subpart.

(d) This subpart does not apply to the following:

(1) Vessels at coke oven by-product plants.

(2) Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.

(3) Vessels permanently attached to mobile vehicles such as trucks, railcars, barges, or ships.

(4) Vessels with a design capacity less than or equal to 1,589.874 m^3 used for petroleum or condensate stored, processed, or treated prior to custody transfer.

(5) Vessels located at bulk gasoline plants.

(6) Storage vessels located at gasoline service stations.

(7) Vessels used to store beverage alcohol.

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989]

§ 60.111b Definitions.

Terms used in this subpart are defined in the Act, in subpart A of this part, or in this subpart as follows:

(a) *Bulk gasoline plant* means any gasoline distribution facility that has a gasoline throughput less than or equal to 75,700 liters per day. Gasoline throughput shall be the maximum calculated design throughput as may be limited by compliance with an enforceable condition under Federal requirement or Federal, State or local law, and discoverable by the Administrator and any other person.

(b) *Condensate* means hydrocarbon liquid separated from natural gas that condenses due to changes in the temperature or pressure, or both, and remains liquid at standard conditions.

(c) *Custody transfer* means the transfer of produced petroleum and/or condensate, after processing and/or treatment in the producing operations, from storage vessels or automatic transfer facilities to pipelines or any other forms of transportation.

(d) *Fill* means the introduction of VOL into a storage vessel but not necessarily to complete capacity.

(e) *Gasoline service station* means any site where gasoline is dispensed to motor vehicle fuel tanks from stationary storage tanks.

(f) *Maximum true vapor pressure* means the equilibrium partial pressure exerted by the stored VOL at the temperature equal to the highest calendar-month average of the VOL storage temperature for VOL's stored above or below the ambient temperature or at the local maximum monthly average temperature as reported by the National Weather Service for VOL's stored at the ambient temperature, as determined:

(1) In accordance with methods described in American Petroleum Institute Bulletin 2517, Evaporation Loss From External Floating Roof Tanks, (incorporated by reference—see § 60.17); or

(2) As obtained from standard reference texts; or

(3) As determined by ASTM Method D2879-83 (incorporated by reference—see § 60.17);

(4) Any other method approved by the Administrator.

(g) *Reid vapor pressure* means the absolute vapor pressure of volatile crude oil and volatile nonviscous petroleum liquids except liquified petroleum gases, as determined by ASTM D323-82 (incorporated by reference—see § 60.17).

(h) *Petroleum* means the crude oil removed from the earth and the oils derived from tar sands, shale, and coal.

(i) *Petroleum liquids* means petroleum, condensate, and any finished or intermediate products manufactured in a petroleum refinery.

(j) *Storage vessel* means each tank, reservoir, or container used for the storage of volatile organic liquids but does not include:

(1) Frames, housing, auxiliary supports, or other components that are not directly involved in the containment of liquids or vapors; or

(2) Subsurface caverns or porous rock reservoirs.

(k) *Volatile organic liquid (VOL)* means any organic liquid which can emit volatile organic compounds into the atmosphere except those VOL's that emit only those compounds which the Administrator has determined do not contribute appreciably to the formation of ozone. These compounds are identified in EPA statements on ozone abatement policy for SIP revisions (42 FR 35314, 44 FR 32042, 45 FR 32424, and 45 FR 48941).

(l) *Waste* means any liquid resulting from industrial, commercial, mining or agricultural operations, or from community activities that is discarded or is being accumulated, stored, or physically, chemically, or biologically

reated prior to being discarded or recycled.

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989]

60.112b Standard for volatile organic compounds (VOC).

(a) The owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m^3 containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 5.2 kPa but less than 76.6 kPa or with a design capacity greater than or equal to 75 m^3 but less than 151 m^3 containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 27.6 kPa but less than 76.6 kPa, shall equip each storage vessel with one of the following:

(1) A fixed roof in combination with an internal floating roof meeting the following specifications:

(i) The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.

(ii) Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:

(A) A foam- or liquid-filled seal (mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.

(B) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.

(C) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.

(iii) Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.

(iv) Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.

(v) Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

(vi) Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.

(vii) Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.

(viii) Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.

(ix) Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

(2) An external floating roof. An external floating roof means a pontoon-type or double-deck type cover that rests on the liquid surface in a vessel with no fixed roof. Each external floating roof must meet the following specifications:

(i) Each external floating roof shall be equipped with a closure device between the wall of the storage vessel and the roof edge. The closure device is to consist of two seals, one above the other. The lower seal is referred to as the primary seal, and the upper seal is referred to as the secondary seal.

(A) The primary seal shall be either a mechanical shoe seal or a liquid-mounted seal. Except as provided in §60.113b(b)(4), the seal shall completely cover the annular space between the edge of the floating roof and tank wall.

(B) The secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion except as allowed in §60.113b(b)(4).

(ii) Except for automatic bleeder vents and rim space vents, each opening in a noncontact external floating roof shall provide a projection below the liquid surface. Except for automatic bleeder vents, rim space vents, roof drains, and leg sleeves, each opening in the roof is to be equipped with a gasketed cover, seal, or lid that is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. Automatic bleeder vents are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. Rim vents are to be set to open when the roof is being floated off the roof legs supports or at the manufacturer's recommended setting. Automatic bleeder vents and rim space vents are to be gasketed. Each emergency roof drain is to be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening.

(iii) The roof shall be floating on the liquid at all times (i.e., off the roof leg supports) except during initial fill until the roof is lifted off leg supports and when the tank is completely emptied and subsequently refilled. The process of filling, emptying, or refilling when the roof is resting on the leg supports shall be continuous and shall be accomplished as rapidly as possible.

(3) A closed vent system and control device meeting the following specifications:

(i) The closed vent system shall be designed to collect all VOC vapors and gases discharged from the storage vessel and operated with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background and visual inspections, as determined in part 60, subpart VV, §60.485(b).

(ii) The control device shall be designed and operated to reduce inlet VOC emissions by 95 percent or greater. If a flare is used as the control device, it shall meet the specifications described in the general control device requirements (§60.18) of the General Provisions.

(4) A system equivalent to those described in paragraphs (a)(1), (a)(2), or (a)(3) of this section as provided in §60.114b of this subpart.

(b) The owner or operator of each storage vessel with a design capacity greater than or equal to 75 m^3 which contains a VOL that, as stored, has a maximum true vapor pressure greater than or equal to 76.6 kPa shall equip each storage vessel with one of the following:

(1) A closed vent system and control device as specified in §60.112b(a)(3).

(2) A system equivalent to that described in paragraph (b)(1) as provided in §60.114b of this subpart.

§60.113b Testing and procedures.

The owner or operator of each storage vessel as specified in §60.112b(a) shall meet the requirements of paragraph (a), (b), or (c) of this section. The applicable paragraph for a particular storage vessel depends on the control equipment installed to meet the requirements of §60.112b.

(a) After installing the control equipment required to meet §60.112b(a)(1) (permanently affixed roof and internal floating roof), each owner or operator shall:

(1) Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or de-

fects in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.

(2) For Vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in § 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.

(3) For vessels equipped with a double-seal system as specified in § 60.112b(a)(1)(ii)(B):

(i) Visually inspect the vessel as specified in paragraph (a)(4) of this section at least every 5 years; or

(ii) Visually inspect the vessel as specified in paragraph (a)(2) of this section.

(4) Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraphs (a)(2) and (a)(3)(ii) of this section and at intervals no greater than 5 years in the case of vessels specified in paragraph (a)(3)(i) of this section.

(5) Notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs (a)(1) and (a)(4) of this section to afford the Administrator the opportunity to have an observer present. If the inspection required by paragraph (a)(4) of this section is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.

(b) After installing the control equipment required to meet § 60.112b(a)(2) (external floating roof), the owner or operator shall:

(1) Determine the gap areas and maximum gap widths, between the primary seal and the wall of the storage vessel and between the secondary seal and the wall of the storage vessel according to the following frequency.

(i) Measurements of gaps between the tank wall and the primary seal (seal gaps) shall be performed during the hydrostatic testing of the vessel or within 60 days of the initial fill with VOL and at least once every 5 years thereafter.

(ii) Measurements of gaps between the tank wall and the secondary seal shall be performed within 60 days of the initial fill with VOL and at least once per year thereafter.

(iii) If any source ceases to store VOL for a period of 1 year or more, subsequent introduction of VOL into the vessel shall be considered an initial fill for the purposes of paragraphs (b)(1)(i) and (b)(1)(ii) of this section.

(2) Determine gap widths and areas in the primary and secondary seals individually by the following procedures:

(i) Measure seal gaps, if any, at one or more floating roof levels when the roof is floating off the roof leg supports.

(ii) Measure seal gaps around the entire circumference of the tank in each place where a 0.32-cm diameter uniform probe passes freely (without forcing or binding against seal) between the seal and the wall of the storage vessel and measure the circumferential distance of each such location.

(iii) The total surface area of each gap described in paragraph (b)(2)(ii) of this section shall be determined by using probes of various widths to measure accurately the actual distance from the tank wall to the seal and multiplying each such width by its respective circumferential distance.

(3) Add the gap surface area of each gap location for the primary seal and the secondary seal individually and divide the sum for each seal by the nominal diameter of the tank and compare each ratio to the respective standards in paragraph (b)(4) of this section.

(4) Make necessary repairs or empty the storage vessel within 45 days of identification in any inspection for seals not meeting the requirements listed in (b)(4) (i) and (ii) of this section:

(i) The accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 Cm^2 per meter of tank diameter, and the width of any portion of any gap shall not exceed 3.81 cm.

(A) One end of the mechanical shoe is to extend into the stored liquid, and the other end is to extend a minimum vertical distance of 61 cm above the stored liquid surface.

(B) There are to be no holes, tears, or other openings in the shoe, seal fabric, or seal envelope.

(ii) The secondary seal is to meet the following requirements:

(A) The secondary seal is to be installed above the primary seal so that it completely covers the space between the roof edge and the tank wall except as provided in paragraph (b)(2)(iii) of this section.

(B) The accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm^2 per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm.

(C) There are to be no holes, tears, or other openings in the seal or seal fabric.

(iii) If a failure that is detected during inspections required in paragraph (b)(1) of § 60.113b(b) cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in § 60.115b(b)(4). Such extension request must include a demonstration of unavailability of alternate storage capacity and a specification of a schedule that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.

(5) Notify the Administrator 30 days in advance of any gap measurements required by paragraph (b)(1) of this section to afford the Administrator the opportunity to have an observer present.

(6) Visually inspect the external floating roof, the primary seal, secondary seal, and fittings each time the vessel is emptied and degassed.

(i) If the external floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before filling or refilling the storage vessel with VOL.

(ii) For all the inspections required by paragraph (b)(6) of this section, the owner or operator shall notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the Administrator the opportunity to inspect the

storage vessel prior to refilling. If the inspection required by paragraph (b)(6) of this section is not planned and the owner or operator could not have known about the inspection 30 days in advance of refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.

(c) The owner or operator of each source that is equipped with a closed vent system and control device as required in §60.112b (a)(3) or (b)(2) (other than a flare) is exempt from §60.8 of the General Provisions and shall meet the following requirements.

(1) Submit for approval by the Administrator as an attachment to the notification required by §60.7(a)(1) or, if the facility is exempt from §60.7(a)(1), as an attachment to the notification required by §60.7(a)(2), an operating plan containing the information listed below.

(i) Documentation demonstrating that the control device will achieve the required control efficiency during maximum loading conditions. This documentation is to include a description of the gas stream which enters the control device, including flow and VOC content under varying liquid level conditions (dynamic and static) and manufacturer's design specifications for the control device. If the control device or the closed vent capture system receives vapors, gases, or liquids other than fuels from sources that are not designated sources under this subpart, the efficiency demonstration is to include consideration of all vapors, gases, and liquids received by the closed vent capture system and control device. If an enclosed combustion device with a minimum residence time of 0.75 seconds and a minimum temperature of 816 °C is used to meet the 95 percent requirement, documentation that those conditions will exist is sufficient to meet the requirements of this paragraph.

(ii) A description of the parameter or parameters to be monitored to ensure that the control device will be operated in conformance with its design and an explanation of the criteria used for selection of that parameter (or parameters).

(2) Operate the closed vent system and control device and monitor the parameters of the closed vent system and control device in accordance with the operating plan submitted to the Administrator in accordance with paragraph (c)(1) of this section, unless the plan was modified by the Administrator during the review process. In this case, the modified plan applies.

(d) The owner or operator of each source that is equipped with a closed vent system and a flare to meet the requirements in §60.112b (a)(3) or (b)(2) shall meet the requirements as specified in the general control device requirements, §60.18 (e) and (f).

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989]

§60.114b Alternative means of emission limitation.

(a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in emissions at least equivalent to the reduction in emissions achieved by any requirement in §60.112b, the Administrator will publish in the FEDERAL REGISTER a notice permitting the use of the alternative means for purposes of compliance with that requirement.

(b) Any notice under paragraph (a) of this section will be published only after notice and an opportunity for a hearing.

(c) Any person seeking permission under this section shall submit to the Administrator a written application including:

(1) An actual emissions test that uses a full-sized or scale-model storage vessel that accurately collects and measures all VOC emissions from a given control device and that accurately simulates wind and accounts for other emission variables such as temperature and barometric pressure.

(2) An engineering evaluation that the Administrator determines is an accurate method of determining equivalence.

(d) The Administrator may condition the permission on requirements that may be necessary to ensure operation and maintenance to achieve the same emissions reduction as specified in §60.112b.

§60.115b Reporting and recordkeeping requirements.

The owner or operator of each storage vessel as specified in §60.112b(a) shall keep records and furnish reports as required by paragraphs (a), (b), or (c) of this section depending upon the control equipment installed to meet the requirements of §60.112b. The owner or operator shall keep copies of all reports and records required by this section, except for the record required by (c)(1), for at least 2 years. The record required by (c)(1) will be kept for the life of the control equipment.

(a) After installing control equipment in accordance with §60.112b(a)(1) (fixed roof and internal floating roof), the owner or operator shall meet the following requirements.

(1) Furnish the Administrator with a report that describes the control equipment and certifies that the control equipment meets the specifications of §60.112b(a)(1) and §60.113b(a)(1). This report shall be an attachment to the notification required by §60.7(a)(3).

(2) Keep a record of each inspection performed as required by §60.113b (a)(1), (a)(2), (a)(3), and (a)(4). Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).

(3) If any of the conditions described in §60.113b(a)(2) are detected during the annual visual inspection required by §60.113b(a)(2), a report shall be furnished to the Administrator within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.

(4) After each inspection required by §60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in §60.113b(a)(3)(ii), a report shall be furnished to the Administrator within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of §61.112b(a)(1) or §60.113b(a)(3) and list each repair made.

(b) After installing control equipment in accordance with §61.112b(a)(2) (external floating roof), the owner or operator shall meet the following requirements.

(1) Furnish the Administrator with a report that describes the control equipment and certifies that the control equipment meets the specifications of §60.112b(a)(2) and §60.113b(b)(2), (b)(3), and (b)(4). This report shall be an attachment to the notification required by §60.7(a)(3).

(2) Within 60 days of performing the seal gap measurements required by §60.113b(b)(1), furnish the Administrator with a report that contains:

(i) The date of measurement.

(ii) The raw data obtained in the measurement.

(iii) The calculations described in §60.113b (b)(2) and (b)(3).

(3) Keep a record of each gap measurement performed as required by §60.113b(b). Each record shall identify the storage vessel in which the measurement was performed and shall contain:

(i) The date of measurement.

(ii) The raw data obtained in the measurement.

(iii) The calculations described in §60.113b (b)(2) and (b)(3).

(4) After each seal gap measurement that detects gaps exceeding the limitations specified by §60.113b(b)(4), submit a report to the Administrator within 30 days of the inspection. The report will identify the vessel and contain the information specified in paragraph (b)(2) of this section and the date the vessel was emptied or the repairs made and date of repair.

(c) After installing control equipment in accordance with §60.112b (a)(3) or (b)(1) (closed vent system and control device other than a flare), the owner or operator shall keep the following records.

(1) A copy of the operating plan.

(2) A record of the measured values of the parameters monitored in accordance with § 60.113b(c)(2).

(d) After installing a closed vent system and flare to comply with § 60.112b, the owner or operator shall meet the following requirements.

(1) A report containing the measurements required by § 60.18(f) (1), (2), (3), (4), (5), and (6) shall be furnished to the Administrator as required by § 60.8 of the General Provisions. This report shall be submitted within 6 months of the initial start-up date.

(2) Records shall be kept of all periods of operation during which the flare pilot flame is absent.

(3) Semiannual reports of all periods recorded under § 60.115b(d)(2) in which the pilot flame was absent shall be furnished to the Administrator.

§ 60.116b Monitoring of operations.

(a) The owner or operator shall keep copies of all records required by this section, except for the record required by paragraph (b) of this section, for at least 2 years. The record required by paragraph (b) of this section will be kept for the life of the source.

(b) The owner or operator of each storage vessel as specified in § 60.110b(a) shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. Each storage vessel with a design capacity less than 75 m^3 is subject to no provision of this subpart other than those required by this paragraph.

(c) Except as provided in paragraphs (f) and (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m^3 storing a liquid with a maximum true vapor pressure greater than or equal to 3.5 kPa or with a design capacity greater than or equal to 75 m^3 but less than 151 m^3 storing a liquid with a maximum true vapor pressure greater than or equal to 15.0 kPa shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.

(d) Except as provided in paragraph (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m^3 storing a liquid with a maximum true vapor pressure that is normally less than 5.2 kPa or with a design capacity greater than or equal to 75 m^3 but less than 151 m^3 storing a liquid with a maximum true vapor pressure that is normally less than 27.6 kPa shall notify the Administrator within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor vapor pressure values for each volume range.

(e) Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.

(1) For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

(2) For crude oil or refined petroleum products the vapor pressure may be obtained by the following:

(i) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see § 60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).

(ii) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.

(3) For other liquids, the vapor pressure:

(i) May be obtained from standard reference texts, or

(ii) Determined by ASTM Method D2879-83 (incorporated by reference—see § 60.17); or

(iii) Measured by an appropriate method approved by the Administrator; or

(iv) Calculated by an appropriate method approved by the Administrator.

(f) The owner or operator of each vessel storing a waste mixture of indeterminate or variable composition shall be subject to the following requirements.

(1) Prior to the initial filling of the vessel, the highest maximum true vapor pressure for the range of anticipated liquid compositions to be stored will be determined using the methods described in paragraph (e) of this section.

(2) For vessels in which the vapor pressure of the anticipated liquid composition is above the cutoff for monitoring but below the cutoff for controls as defined in § 60.112b(a), an initial physical test of the vapor pressure is required; and a physical test at least once every 6 months thereafter is required as determined by the following methods:

(i) ASTM Method D2879-83 (incorporated by reference—see § 60.17); or

(ii) ASTM Method D323-82 (incorporated by reference—see § 60.17); or

(iii) As measured by an appropriate method as approved by the Administrator.

(g) The owner or operator of each vessel equipped with a closed vent system and control device meeting the specifications of § 60.112b is exempt from the requirements of paragraphs (c) and (d) of this section.

§ 60.117b Delegation of authority.

(a) In delegating implementation and enforcement authority to a State under section 111(c) of the Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.

(b) Authorities which will not be delegated to States: §§ 60.111b(f)(4), 60.114b, 60.116b(e)(3)(iii), 60.116b(e)(3)(iv), and 60.116b(f)(2)(iii).

[52 FR 11429, Apr. 8, 1987, as amended at 52 FR 22780, June 16, 1987]

Subpart L—Standards of Performance for Secondary Lead Smelters

§ 60.120 Applicability and designation of affected facility.

(a) The provisions of this subpart are applicable to the following affected facilities in secondary lead smelters: Pot furnaces of more than 250 kg (550 lb) charging capacity, blast (cupola) furnaces, and reverberatory furnaces.

(b) Any facility under paragraph (a) of this section that commences construction or modification after June 11, 1973, is subject to the requirements of this subpart.

[42 FR 37937, July 25, 1977]

§ 60.121 Definitions.

As used in this subpart, all terms not defined herein shall have the meaning given them in the Act and in subpart A of this part.

(a) *Reverberatory furnace* includes the following types of reverberatory furnaces: stationary, rotating, rocking, and tilting.

(b) *Secondary lead smelter* means any facility producing lead from a leadbearing scrap material by smelting to the metallic form.

(c) *Lead* means elemental lead or alloys in which the predominant component is lead.

[39 FR 9317, Mar. 8, 1974; 39 FR 13776, Apr. 17, 1974]

§ 60.122 Standard for particulate matter.

(a) On and after the date on which the performance test required to be conducted by § 60.8 is completed, no owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from a blast (cupola) or reverberatory furnace any gases which:

(1) Contain particulate matter in excess of 50 mg/dscm (0.022 gr/dscf).

(2) Exhibit 20 percent opacity or greater.

(b) On and after the date on which the performance test required to be conducted by § 60.8 is completed, no owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmos