



Joseph E. Kernan
Governor

Lori F. Kaplan
Commissioner

May 3, 2004

100 North Senate Avenue
P.O. Box 6015
Indianapolis, Indiana 46206-6015
(317) 232-8603
(800) 451-6027
www.in.gov/idem

TO: Interested Parties / Applicant

RE: Edward C. Levy Co, Inc / 089-6260-00339

FROM: Paul Dubenetzky
Chief, Permits Branch
Office of Air Quality

Notice of Decision: Approval – Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 and IC 13-15-6-1(b) or IC 13-15-6-1(a) require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204.

For an **initial Title V Operating Permit**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **thirty (30)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(b).

For a **Title V Operating Permit renewal**, a petition for administrative review must be submitted to the Office of Environmental Adjudication within **fifteen (15)** days from the receipt of this notice provided under IC 13-15-5-3, pursuant to IC 13-15-6-1(a).

The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and

- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

Pursuant to 326 IAC 2-7-18(d), any person may petition the U.S. EPA to object to the issuance of an initial Title V operating permit, permit renewal, or modification within sixty (60) days of the end of the forty-five (45) day EPA review period. Such an objection must be based only on issues that were raised with reasonable specificity during the public comment period, unless the petitioner demonstrates that it was impracticable to raise such issues, or if the grounds for such objection arose after the comment period.

To petition the U.S. EPA to object to the issuance of a Title V operating permit, contact:

U.S. Environmental Protection Agency
401 M Street
Washington, D.C. 20406

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.



Joseph E. Kernan
Governor

Lori F. Kaplan
Commissioner

100 North Senate Avenue
P.O. Box 6015
Indianapolis, Indiana 46206-6015
(317) 232-8603
(800) 451-6027
www.in.gov/idem

PART 70 OPERATING PERMIT OFFICE OF AIR QUALITY

**Edward C. Levy Company, Inc.,
a contractor of ISG-Indiana Harbor, Inc.
3001 Dickey Road
East Chicago, Indiana 46312**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17. **This permit also addresses certain new source review requirements for existing equipment and is intended to fulfill the new source review procedures pursuant to 326 IAC 2-2 and 326 IAC 2-7-10.5, applicable to those conditions.**

Operation Permit No.: T089-6260-00339	
Issued by: Original signed by Janet G. McCabe, Assistant Commissioner Office of Air Quality	Issuance Date: May 3, 2004 Expiration Date: May 3, 2009

TABLE OF CONTENTS

A	SOURCE SUMMARY	5
A.1	General Information [326 IAC 2-7-4(c)][326 IAC 2-7-5(15)][326 IAC 2-7-1(22)]	
A.2	Part 70 Source Definition [326 IAC 2-7-1(22)]	
A.3	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]	
A.4	Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)][326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.5	Part 70 Permit Applicability [326 IAC 2-7-2]	
B	GENERAL CONDITIONS	8
B.1	Definitions [326 IAC 2-7-1]	
B.2	Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]	
B.3	Enforceability [326 IAC 2-7-7]	
B.4	Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]	
B.5	Severability [326 IAC 2-7-5(5)]	
B.6	Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	
B.7	Duty to Provide Information [326 IAC 2-7-5(6)(E)]	
B.8	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]	
B.9	Annual Compliance Certification [326 IAC 2-7-6(5)]	
B.10	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3)and (13)][326 IAC 2-7-6(1)and(6)] [326 IAC 1-6-3]	
B.11	Emergency Provisions [326 IAC 2-7-16]	
B.12	Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]	
B.13	Prior Permits Superseded [326 IAC 2-1.1-9.5]	
B.14	Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]	
B.15	Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]	
B.16	Permit Renewal [326 IAC 2-7-4]	
B.17	Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]	
B.18	Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]	
B.19	Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]	
B.20	Source Modification Requirement [326 IAC 2-7-10.5]	
B.21	Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]	
B.22	Transfer of Ownership or Operational Control [326 IAC 2-7-11]	
B.23	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]	
C	SOURCE OPERATION CONDITIONS.....	18
	Emission Limitations and Standards [326 IAC 2-7-5(1)]	
C.1	Opacity [326 IAC 5-1]	
C.2	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.3	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	
C.4	Fugitive Dust Emissions [326 IAC 6-4]	
C.5	Fugitive Dust Emissions [326 IAC 6-1-11.1]	
C.6	Operation of Equipment [326 IAC 2-7-6(6)]	
C.7	Stack Height [326 IAC 1-7]	
C.8	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	Testing Requirements [326 IAC 2-7-6(1)]	
C.9	Performance Testing [326 IAC 3-6]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.10	Compliance Requirements [326 IAC 2-1.1-11]	

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.12 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]
- C.13 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11]
[326 IAC 2-7-5(3)][326 IAC 2-7-6(1)]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]
- C.16 Compliance Response Plan - Preparation, Implementation, Records, and Reports
[326 IAC 2-7-5] [326 IAC 2-7-6]
- C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)]
[326 IAC 2-6]
- C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection

- C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

D.1 FACILITY OPERATION CONDITIONS 27

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Nonattainment Area Particulate Limitations [326 IAC 6-1-2]
- D.1.2 Prevention of Significant Deterioration (PSD)[326 IAC 2-2]
- D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.4 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.5 Visible Emissions Notations
- D.1.6 Continuous Compliance Plan [326 IAC 6-1-10.1]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.7 Record Keeping Requirements
- D.1.8 Reporting Requirements

D.2 FACILITY OPERATION CONDITIONS 32

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.2.1 Nonattainment Area Particulate Limitations [326 IAC 6-1-2]
- D.2.2 Volatile Organic Liquid Storage Vessels [326 IAC 8-9]
- D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]
- D.2.4 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]
- D.2.5 Volatile Organic Compounds (VOC) [326 IAC 8-3-8]

Compliance Determination Requirement

- D.2.6 Particulate Control

Record Keeping and Reporting Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.2.7 Record Keeping Requirements

Certification	35
Emergency Occurrence Report	36
Quarterly Report.....	38
Quarterly Deviation and Compliance Monitoring Report	39

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1, A.3, and A.4 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary steel slag processing source.

Responsible Official:	Dave Oram
Source Address:	3001 Dickey Road, East Chicago, Indiana 46312
Mailing Address:	3001 Dickey Road, East Chicago, Indiana 46312
General Source Phone Number:	219-391-3136
SIC Code:	3295
County Location:	Lake
Source Location Status:	Nonattainment for SO ₂ , and ozone Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Major Source, under PSD and Emission Offset Rules; Major Source, Section 112 of the Clean Air Act 1 of 28 Source Categories under PSD and Emission Offset Rules

A.2 Part 70 Source Definition [326 IAC 2-7-1(22)]

ISG-Indiana Harbor, Inc. is a fully integrated steelmaking and finishing facility consists of a source with on-site contractors:

- (a) ISG-Indiana Harbor, Inc., (089-00318) the primary operation, is located at, 3001 Dickey Road, East Chicago, Indiana 46312; and
- (b) Edward C. Levy, Inc. (089-00339), the supporting operation (a steel slag processing facility), is located at 3001 Dickey Road, East Chicago, Indiana 46312.

IDEM has determined that ISG-Indiana Harbor, Inc. and Edward C. Levy, Inc. are under the common control of ISG-Indiana Harbor, Inc. These two plants are considered one source due to contractual control. Therefore, the term "source" in the Part 70 documents refers to both ISG-Indiana Harbor, Inc. and Edward C. Levy, Inc., as one source.

Separate Part 70 permits will be issued to ISG-Indiana Harbor, Inc. and Edward C. Levy, Inc. solely for administrative purposes. For permitting purposes, ISG-Indiana Harbor, Inc. is assigned Permit No. 089-7099-00318 and Edward C. Levy, Inc. is assigned Permit No. 089-6260-00339.

A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

Edward C. Levy, Inc. consists of the following emission units and pollution control devices:

- (a) One (1) conveyor, rated capacity of 825 tons per hour, installed in 1986.
- (b) Three (3) conveyors, rated capacity of 700 tons per hour, each, installed in 1986.
- (c) Three (3) conveyors, rated capacity of 500 tons per hour, each, installed in 1986.

- (d) One (1) conveyor, rated capacity of 500 tons per hour, installed in 1988.
- (e) One (1) conveyor, rated capacity of 300 tons per hour, installed in 1992.
- (f) One (1) conveyor, rated capacity of 270 tons per hour, installed in 1992.
- (g) Two (2) conveyors, rated capacity of 150 tons per hour, each, installed in 1986.
- (h) One (1) conveyor, rated capacity of 140 tons per hour, installed in 1986.
- (i) Two (2) conveyors, rated capacity of 100 tons per hour, each, installed in 1986.
- (j) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1987.
- (k) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1990.
- (l) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1986.
- (m) One (1) screen, rated capacity of 900 tons per hour, installed in 1986.
- (n) One (1) screen, rated capacity of 700 tons per hour, installed in 1986.
- (o) One (1) screen, rated capacity of 700 tons per hour, installed in 1987.
- (p) Two (2) screens, rated capacity of 350 tons per hour, each, installed in 1986.
- (q) Two (2) screens, rated capacity of 200 tons per hour, each, installed in 1988.
- (r) One (1) screen, rated capacity of 500 tons per hour, installed in 1986.
- (s) One (1) crusher, rated capacity of 300 tons per hour, installed in 1986.
- (t) Two (2) crushers, rated capacity of 140 tons per hour, each, installed in 1986.
- (u) One (1) stacking conveyor, rated capacity of 200 tons per hour, installed in 1986.
- (v) Three (3) radial stacking conveyors, rated capacity of 500 tons per hour, each, installed in 1986.
- (w) One (1) radial stacking conveyor, rated capacity of 480 tons per hour, installed in 1986.
- (x) One (1) ballast stacker, rated capacity of 510 tons per hour, installed in 1990.

A.4 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

Edward C. Levy, Inc. also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (a) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons.[326 IAC 8-9]
- (b) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. [326 IAC 8-3-2 (Cold Cleaner Operations)] [326 IAC 8-3-5][326 IAC 8-3-8]
- (c) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches soldering equipment, welding equipment. [326 IAC 6-1-2]

A.5 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.3 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.4 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Provide Information [326 IAC 2-7-5(6)(E)]

- (a) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit.
- (b) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.9 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the

status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The initial certification shall cover the time period from the date of final permit issuance through December 31 of the same year. All subsequent certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than April 15 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
- (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.10 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

The PMP extension notification does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall implement the PMPs, including any required record keeping as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and Northwest Regional Office, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or

Telephone Number: 317-233-5674 (ask for Compliance Section)

Facsimile Number: 317-233-5967

Northwest Regional Office Telephone Number: 219-881-6712

Northwest Regional Office Facsimile Number: 219-881-6745

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification, which shall be submitted by the Permittee, does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
 - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
 - (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
 - (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
 - (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this

permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.13 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted

by this permit.

- (b) All previous registrations and permits are superseded by this permit.

B.14 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.15 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ, determines any of the following:
- (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.16 Permit Renewal [326 IAC 2-7-4]

- (a) The application for renewal shall be submitted using the application form or forms

prescribed by IDEM, OAQ, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

(b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]

(1) A timely renewal application is one that is:

(A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and

(B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

(2) If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

(c) Right to Operate After Application for Renewal [326 IAC 2-7-3]
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as being needed to process the application.

(d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]
If IDEM, OAQ, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.17 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

(a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

(b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]
- (d) No permit amendment or modification is required for the addition, operation or removal of a nonroad engine, as defined in 40 CFR 89.2.

B.18 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
[326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.19 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:
 - (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
 - (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
 - (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and
 - (5) The Permittee maintains records on-site which document, on a rolling five (5)

year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
- (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification, which shall be submitted, is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

B.20 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

B.21 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2][IC 13-30-3-1][IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample

or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The application, which shall be submitted by the Permittee, does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of twenty percent (20%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.2 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.3 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.4 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.5 Fugitive Dust Emissions [326 IAC 6-1-11.1]

- (a) Pursuant to 326 IAC 6-1-11.1 (Lake County Fugitive Particulate Matter Control Requirements), the particulate matter emissions from source wide activities shall meet the following requirements:
 - (1) The average instantaneous opacity of fugitive particulate emissions from a paved road shall not exceed ten percent (10%).
 - (2) The average instantaneous opacity of fugitive particulate emissions from an unpaved road shall not exceed ten percent (10%).
 - (3) The average instantaneous opacity of fugitive particulate emissions from batch transfer shall not exceed ten percent (10%).
 - (4) The opacity of fugitive particulate emissions from continuous transfer of material onto and out of storage piles shall not exceed ten percent (10%) on a three (3) minute average.
 - (5) The opacity of fugitive particulate emissions from storage piles shall not exceed ten percent (10%) on a six (6) minute average.
 - (6) There shall be a zero (0) percent frequency of visible emission observations of a material during the inplant transportation of material by truck or rail at any time.

- (7) The opacity of fugitive particulate emissions from the inplant transportation of material by front end loaders and skip hoists shall not exceed ten percent (10%).
- (8) There shall be a zero (0) percent frequency of visible emission observations from a building enclosing all or part of the material processing equipment, except from a vent in the building.
- (9) The PM10 emissions from building vents shall not exceed twenty-two thousandths (0.022) grains per dry standard cubic foot and ten percent (10%) opacity.
- (10) The opacity of particulate emissions from dust handling equipment shall not exceed ten percent (10%).
- (11) Any facility or operation not specified in 326 IAC 6-1-11.1(d) shall meet a twenty percent (20%), three (3) minute average opacity standard.
- (12) PM10 emissions from each material processing stack shall not exceed 0.022 grains per dry standard cubic foot and ten percent (10%) opacity
- (13) Fugitive particulate matter from the material processing facilities shall not exceed ten percent (10%) opacity
- (14) Slag and kish handling activities at integrated iron and steel plants shall comply with the following particulate emissions limits:
 - (A) The opacity of fugitive particulate emissions from transfer from pots and trucks into pits shall not exceed twenty percent (20%) on a six (6) minute average.
 - (B) The opacity of fugitive particulate emissions from transfer from pits into front end loaders and from transfer from front end loaders into trucks shall comply with the fugitive particulate emission limits in 326 IAC 6-1-11.1(d)(9).

Material processing facilities include crushers, screens, grinders, mixers, dryers, belt conveyors, bucket elevators, bagging operations, storage bins, and truck or railroad car loading stations.

The Permittee shall achieve these limits by controlling fugitive particulate matter emissions according to the Fugitive Dust Control Plan, submitted on July 10, 1996.

- (b) The source is subject to 326 IAC 6-1-11.2 because it is subject to the requirements of 326 IAC 6-1-11.1 and 326 IAC 6-1-10.1(d). Pursuant to this rule, the source shall comply with parts (h), (i), (k), (l), (m), (o), (p) and (q) of this rule.

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.7 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted. The provisions of 326 IAC 1-7-1(3), 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4 and 326 IAC 1-7-5(a), (b), and

(d) are not federally enforceable.

C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
- (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
- (2) If there is a change in the following:
- (A) Asbestos removal or demolition start date;
- (B) Removal or demolition contractor; or
- (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Demolition and renovation**
The Permittee shall thoroughly inspect the affected facility or part of the facility where the demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).

- (g) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.9 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ, not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the Permittee submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.10 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification, which shall be submitted by the Permittee, does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.12 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.13 Pressure Gauge and Other Instrument Specifications [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

- (a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (2%) of full scale reading.
- (b) Whenever a condition in this permit requires the measurement of a flow rate, the instrument employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent (2%) of full scale reading.
- (c) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within ninety (90) days after the date of issuance of this permit.

The ERP does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) If the ERP is disapproved by IDEM, OAQ, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.

- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the Permittee must comply with the applicable requirements of 40 CFR 68.

C.16 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. If a Permittee is required to have an Operation, Maintenance and Monitoring (OMM) Plan (or Parametric Monitoring Plan and Start-up, Shutdown, and Malfunction (SSM) Plan) under 40 CFR 60/63, such plans shall be deemed to satisfy the requirements for a CRP for those compliance monitoring conditions. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
 - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan (or Parametric Monitoring Plan and Start-up, Shutdown, and Malfunction (SSM) Plan) and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan (or Parametric Monitoring Plan and Start-up, Shutdown, and Malfunction (SSM) Plan) to include such response steps taken.

The OMM Plan (or Parametric Monitoring and SSM Plan) shall be submitted within the time frames specified by the applicable 40 CFR60/63 requirements.

- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
 - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that

the emissions unit or control device be shut down, and it will be ten (10) days or more until the unit or device will be shut down, the Permittee shall promptly notify the IDEM, OAQ of the expected date of the shut down. The notification shall also include the status of the applicable compliance monitoring parameter with respect to normal, and the results of the response actions taken up to the time of notification.

- (4) Failure to take reasonable response steps shall be considered a deviation from the permit.
 - (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
 - (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
 - (e) The Permittee shall record all instances when, in accordance with Section D, response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
 - (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.
- C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]
-
- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
 - (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
 - (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

(a) The Permittee shall submit an annual emission statement certified pursuant to the requirements of 326 IAC 2-6. This statement must be received in accordance with the compliance schedule specified in 326 IAC 2-6-3 and must comply with the minimum requirements specified in 326 IAC 2-6-4. The submittal should cover the period identified in 326 IAC 2-6. The emission statement shall meet the following requirements:

- (1) Indicate estimated actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
- (2) Indicate estimated actual emissions of regulated pollutants (as defined by 326 IAC 2-7-1(32)) ("Regulated pollutant which is used only for purposes of Section 19 of this rule") from the source, for purposes of Part 70 fee assessment.

The statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) The emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

(a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

(b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

(a) The Permittee shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) The report required in (a) of this condition and reports required by conditions in Section D

of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

Stratospheric Ozone Protection

C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (a) One (1) conveyor, rated capacity of 825 tons per hour, installed in 1986.
- (b) Three (3) conveyors, rated capacity of 700 tons per hour, each, installed in 1986.
- (c) Three (3) conveyors, rated capacity of 500 tons per hour, each, installed in 1986.
- (d) One (1) conveyor, rated capacity of 500 tons per hour, installed in 1988.
- (e) One (1) conveyor, rated capacity of 300 tons per hour, installed in 1992.
- (f) One (1) conveyor, rated capacity of 270 tons per hour, installed in 1992.
- (g) Two (2) conveyors, rated capacity of 150 tons per hour, each, installed in 1986.
- (h) One (1) conveyor, rated capacity of 140 tons per hour, installed in 1986.
- (i) Two (2) conveyors, rated capacity of 100 tons per hour, each, installed in 1986.
- (j) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1987.
- (k) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1990.
- (l) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1986.
- (m) One (1) screen, rated capacity of 900 tons per hour, installed in 1986.
- (n) One (1) screen, rated capacity of 700 tons per hour, installed in 1986.
- (o) One (1) screen, rated capacity of 700 tons per hour, installed in 1987.
- (p) Two (2) screens, rated capacity of 350 tons per hour, each, installed in 1986.
- (q) Two (2) screens, rated capacity of 200 tons per hour, each, installed in 1988.
- (r) One (1) screen, rated capacity of 500 tons per hour, installed in 1986.
- (s) One (1) crusher, rated capacity of 300 tons per hour, installed in 1986.
- (t) Two (2) crushers, rated capacity of 140 tons per hour, each, installed in 1986.
- (u) One (1) stacking conveyor, rated capacity of 200 tons per hour, installed in 1986.
- (v) Three (3) radial stacking conveyors, rated capacity of 500 tons per hour, each, installed in 1986.
- (w) One (1) radial stacking conveyor, rated capacity of 480 tons per hour, installed in 1986.
- (x) One (1) ballast stacker, rated capacity of 510 tons per hour, installed in 1990.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Nonattainment Area Particulate Limitations [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2 (g) The crushing, sizing, storing and transporting of mineral materials shall be limited to the following:

- (a) All mineral aggregate operations, where the process is totally enclosed, and thus it is practical to measure the emissions therefrom, shall comply with the 0.03 grain per dry standard cubic feet per minute in 326 IAC 6-1-2 (a).
- (b) In addition, 326 IAC 2, 326 IAC 5-1, and 326 IAC 6-4 shall apply in all cases to mineral aggregate operations.

D.1.2 Prevention of Significant Deterioration (PSD)[326 IAC 2-2]

The input of steel mill slag to the crushing, screening and conveying plant shall not exceed 675,330 tons per twelve (12) consecutive month period. This will ensure limiting particulate matter emissions from the entire plant to less than 25 tons per year and that of particulate matter less than 10 micron size diameter to less than 15 tons per year, including fugitives. Therefore, the requirements of 326 IAC 2-2 will not apply.

D.1.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.4 Particulate Matter (PM)

Pursuant to 326 IAC 6-1-11.1 (Lake County Fugitive Particulate Matter Control Requirements), opacity from the activities specified in Section C-Fugitive Dust Emissions shall be determined as follows:

- (a) **Paved Roads and Parking Lots**
The average instantaneous opacity shall be the average of twelve (12) instantaneous opacity readings, taken for four (4) vehicle passes, consisting of three (3) opacity readings for each vehicle pass. The three (3) opacity readings for each vehicle pass shall be taken as follows:
 - (1) The first will be taken at the time of emission generation.
 - (2) The second will be taken five (5) seconds later.
 - (3) The third will be taken five (5) seconds later or ten (10) seconds after the first.The three (3) readings shall be taken at the point of maximum opacity. The observer shall stand approximately fifteen (15) feet from the plume and at approximately right angles to the plume. Each reading shall be taken approximately four (4) feet above the surface of the roadway or parking area.
- (b) **Unpaved Roads and Parking**
The fugitive particulate emissions from unpaved roads shall be controlled by the implementation of a work program and work practice under the fugitive dust control plan.
- (c) **Batch Transfer**
The average instantaneous opacity shall consist of the average of three (3) opacity readings taken five (5) seconds, ten (10) seconds, and fifteen (15) seconds after the end of one (1) batch loading or unloading operation. The three (3) readings shall be taken at the point of maximum opacity. The observer shall stand approximately fifteen (15) feet from the plume and at approximately right angles to the plume.
- (d) **Continuous Transfer**
The opacity shall be determined using 40 CFR 60, Appendix A, Method 9. The opacity readings shall be taken at least four (4) feet from the point of origin.

- (e) **Wind Erosion from Storage Piles**
The opacity shall be determined using 40 CFR 60, Appendix A, Method 9, except that the opacity shall be observed at approximately four (4) feet from the surface at the point of maximum opacity. The observer shall stand approximately fifteen (15) feet from the plume and at approximately right angles to the plume. The limitations may not apply during periods when application of fugitive particulate control measures are either ineffective or unreasonable due to sustained very high wind speeds. During such periods, the company must continue to implement all reasonable fugitive particulate control measures and maintain records documenting the application of measures and the basis for a claim that meeting the opacity limitation was not reasonable given prevailing wind conditions.
- (f) **Wind Erosion from Exposed Areas**
The opacity shall be determined using 40 CFR 60, Appendix A, Method 9.
- (g) **Material Transported by Truck or Rail**
Compliance with this limitation shall be determined by 40 CFR 60, Appendix A, Method 22, except that the observation shall be taken at approximately right angles to the prevailing wind from the leeward side of the truck or railroad car. Material transported by truck or rail that is enclosed and covered shall be considered in compliance with the inplant transportation requirement.
- (h) **Material Transported by Front End Loader or Skip Hoist**
Compliance with this limitation shall be determined by the average of three (3) opacity readings taken at five (5) second intervals. The three (3) opacity readings shall be taken as follows:
- (1) The first will be taken at the time of emission generation.
 - (2) The second will be taken five (5) seconds later.
 - (3) The third will be taken five (5) seconds later or ten (10) seconds after the first.
- The three (3) readings shall be taken at the point of maximum opacity. The observer shall stand at least fifteen (15) feet from the plume approximately and at right angles to the plume. Each reading shall be taken approximately four (4) feet above the surface of the roadway or parking area.
- (i) **Material Processing Limitations**
Compliance with all opacity limitations from material processing equipment shall be determined using 40 CFR 60, Appendix A, Method 9. Compliance with all visible emissions limitations from material processing equipment shall be determined using 40 CFR 60, Appendix A, Method 22. Compliance with all particulate matter limitations from material processing equipment shall be determined using 40 CFR 60, Appendix A, Method 5 or 17.
- (j) **Dust Handling Equipment**
Compliance with this standard shall be determined by 40 CFR 60, Appendix A, Method 9.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.5 Visible Emissions Notations

- (a) Visible emissions notations of the exhausts from the hoppers, the screens, crushers and the conveyor transfer points shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.

- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.

D.1.6 Continuous Compliance Plan [326 IAC 6-1-10.1]

Pursuant to 326 IAC 6-1-10.1(l)(21), a CCP shall also be submitted by any source in Lake County for facilities that perform manufacturing operations in a building or structure such that the total uncontrolled PM10 emissions from all such operations amount to ten (10) tons per year or more and that could potentially escape into the atmosphere through roof vents and other openings. The uncontrolled PM10 emissions shall be estimated with AP-42, "Compilation of Air Pollutant Emission Factors, Volume I, (Stationary Point and Area Sources)", 4th Edition, September 1985, (and succeeding amendments) emission factors or other documentable emission factors acceptable to the commissioner.

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.7 Record Keeping Requirements

- (a) To document compliance with Condition D.1.5, the Permittee shall maintain records of visible emission notations of the hoppers, the screens, crushers and the conveyor transfer points exhaust once per shift.
- (b) To document compliance with Condition D.1.2, the Permittee shall maintain records at the plant of the steel mill slag input.
- (c) Pursuant to 326 IAC 6-1-11.1 (Lake County Fugitive Particulate Matter Control Requirements):

The source shall keep the following documentation to show compliance with each of its control measures and control practices:

- (1) A map or diagram showing the location of all emission sources controlled, including the location, identification, length, and width of roadways.
- (2) For each application of water or chemical solution to roadways, the following shall be recorded:
 - (A) The name and location of the roadway controlled
 - (B) Application rate
 - (C) Time of each application
 - (D) Width of each application
 - (E) Identification of each method of application

- (F) Total quantity of water or chemical used for each application
- (G) For each application of chemical solution, the concentration and identity of the chemical
- (H) The material data safety sheets for each chemical
- (3) For application of physical or chemical control agents not covered by 326 IAC 6-1-11.1(B), the following:
 - (A) The name of the agent
 - (B) Location of application
 - (C) Application rate
 - (D) Total quantity of agent used
 - (E) If diluted, percent of concentration
 - (F) The material data safety sheets for each chemical
- (4) A log recording incidents when control measures were not used and a statement of explanation.
- (5) Copies of all records required by this section shall be submitted to the department within twenty (20) working days of a written request by the department.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.8 Reporting Requirements

- (a) Pursuant to 326 IAC 6-1-11.1 (Lake County Fugitive Particulate Matter Control Requirements), a quarterly report shall be submitted, stating the following:
 - (1) The dates any required control measures were not implemented
 - (2) A listing of those control measures
 - (3) The reasons that the control measures were not implemented
 - (4) Any corrective action taken

The reports shall be submitted within thirty (30) calendar days following the end of each calendar quarter and in accordance with Section C – General Reporting Requirements of this permit.

- (b) A quarterly summary of the information to document compliance with operation Condition D.1.2 shall be submitted to the addresses listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the calendar quarter being reported. This report shall include the monthly input of steel mill slag. All records and reports shall use calendar months. The report submitted by the Permittee does require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).

SECTION D.2 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

Insignificants:

- (a) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons.[326 IAC 8-9]
- (b) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. [326 IAC 8-3-2 (Cold Cleaner Operations)] [326 IAC 8-3-5][326 IAC 8-3-8]
- (c) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches soldering equipment, welding equipment. [326 IAC 6-1-2]

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Nonattainment Area Particulate Limitations [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2 (Nonattainment Area Particulate Limitations), the particulate matter emissions from the brazing equipment, cutting torches, soldering equipment, welding equipment, shall not exceed 0.03 grains per dry standard cubic foot (gr/dscf).

D.2.2 Volatile Organic Liquid Storage Vessels [326 IAC 8-9]

Pursuant to 326 IAC 8-9-1, the Permittee is required to keep records on the information in 326 IAC 8-9-6(a)-(b) for all storage vessels.

D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-3-2]

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations), for cold cleaning operations existing as of January 1, 1980, located in Clark, Elkhart, Floyd, Lake, Marion, Porter and St. Joseph Counties and which have potential emissions of one hundred (100) tons per year or greater of VOC, the Permittee shall:

- (a) Equip the cleaner with a cover;
- (b) Equip the cleaner with a facility for draining cleaned parts;
- (c) Close the degreaser cover whenever parts are not being handled in the cleaner;
- (d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;
- (e) Provide a permanent, conspicuous label summarizing the operation requirements;
- (f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

D.2.4 Volatile Organic Compounds (VOC) [326 IAC 8-3-5]

Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), for cold cleaner degreaser operations without remote solvent reservoirs existing as of July 1, 1990, located in Clark, Elkhart, Floyd, Lake, Marion, Porter or St. Joseph Counties, the Permittee shall ensure that the following requirements are met:

- (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:

- (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F));
 - (B) The solvent is agitated; or
 - (C) The solvent is heated.
- (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.
- (3) Provide a permanent, conspicuous label which lists the operating requirements outlined in subsection (b).
- (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure which does not cause excessive splashing.
- (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):
- (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
 - (B) A water cover when solvent is used is insoluble in, and heavier than, water.
 - (C) Other systems of demonstrated equivalent control such as a refrigerated chiller or carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.

D.2.5 Volatile Organic Compounds (VOC) [326 IAC 8-3-8] (Material requirements for cold cleaning degreasers)

Pursuant to 326 IAC 8-3-8 (Material requirements for cold cleaning degreasers), the users, providers, and manufacturers of solvents for use in cold cleaning degreasers in Clark, Floyd, Lake, and Porter Counties, except for solvents intended to be used to clean electronic components shall do the following:

- (a) On and after November 1, 1999, no person shall Operate a cold cleaning degreaser with a solvent vapor pressure that exceeds two (2) millimeters of mercury (thirty-eight thousandths (0.038) pound per square inch) measured at twenty (20) degrees Celsius (sixty-eight (68) degrees Fahrenheit).
- (b) On and after May 1, 2001, no person shall Operate a cold cleaning degreaser with a solvent vapor pressure that exceeds one (1) millimeter of mercury (nineteen-thousandths (0.019) pound per square inch) measured at twenty (20) degrees Celsius (sixty-eight (68) degrees Fahrenheit).

- (c) On and after November 1, 1999, all persons subject to the requirements of 326 IAC 8-3-8 (c)(1)(B) and (c)(2)(B) shall maintain each of the following records for each purchase:
- (1) The name and address of the solvent supplier.
 - (2) The date of purchase.
 - (3) The type of solvent.
 - (4) The volume of each unit of solvent.
 - (5) The total volume of the solvent.
 - (6) The true vapor pressure of the solvent measured in millimeters of mercury at twenty (20) degrees Celsius (sixty-eight (68) degrees Fahrenheit).
- (d) All records required by 326 IAC 8-3-8 (d) shall be retained on-site for the most recent three (3) year period and shall be reasonably accessible for an additional two (2) year period.

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.2.6 Record Keeping Requirements

Pursuant to 326 IAC 8-9, the Permittee must keep records of the following:

- (a) The vessel identification number;
- (b) The vessel dimensions; and
- (c) The vessel capacity.

Records shall be maintained for the life of the vessel.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

PART 70 OPERATING PERMIT CERTIFICATION

Source Name: Edward C. Levy Company, Inc., a contractor of ISG-Indiana Harbor, Inc.
Source Address: 3001 Dickey Road, East Chicago, Indiana 46312
Mailing Address: 3001 Dickey Road, East Chicago, Indiana 46312
Part 70 Permit No.: T089-6260-00339

**This certification shall be included when submitting monitoring, testing reports/results
or other documents as required by this permit.**

Please check what document is being certified:

- Annual Compliance Certification Letter
- Test Result (specify) _____
- Report (specify) _____
- Notification (specify) _____
- Affidavit (specify) _____
- Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Phone:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH
100 North Senate Avenue
P.O. Box 6015
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**PART 70 OPERATING PERMIT
EMERGENCY OCCURRENCE REPORT**

Source Name: Edward C. Levy Company, Inc., a contractor of ISG-Indiana Harbor, Inc.
Source Address: 3001 Dickey Road, East Chicago, Indiana 46312
Mailing Address: 3001 Dickey Road, East Chicago, Indiana 46312
Part 70 Permit No.: T089-6260-00339

This form consists of 2 pages

Page 1 of 2

- 9** This is an emergency as defined in 326 IAC 2-7-1(12)
- C The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
 - C The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____

Title / Position: _____

Date: _____

Phone: _____

A certification is not required for this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

Part 70 Quarterly Report

Source Name: Edward C. Levy Company, Inc., a contractor of ISG-Indiana Harbor, Inc.
Source Address: 3001 Dickey Road, East Chicago, Indiana 46312
Mailing Address: 3001 Dickey Road, East Chicago, Indiana 46312
Part 70 Permit No.: T089-6260-00339
Facility: Crushing, screening, conveying and transporting steel mill slag
Parameter: Input of Steel Mill Slag
Limit: 675,330 tons per twelve (12) consecutive month period

Quarter: _____

YEAR: _____

Month	Tons of Slag	Tons of Slag	Tons of Slag
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR QUALITY
 COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
 QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Edward C. Levy Company, Inc., a contractor of ISG-Indiana Harbor, Inc.
 Source Address: 3001 Dickey Road, East Chicago, Indiana 46312
 Mailing Address: 3001 Dickey Road, East Chicago, Indiana 46312
 Part 70 Permit No.: T089-6260-00339

Months: _____ **to** _____ **Year:** _____

<p>This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".</p>	
<p>☑ NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.</p>	
<p>☑ THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD</p>	
<p>Permit Requirement (specify permit condition #)</p>	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
<p>Permit Requirement (specify permit condition #)</p>	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	
Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed By: _____

Title/Position: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Quality

Addendum to the Technical Support Document for a Part 70 Operating Permit

Source Name: Edward C. Levy Company, Inc., a contractor of ISG-Indiana Harbor, Inc.
Source Location: 3001 Dickey Road, East Chicago, Indiana 46312
County: Lake
SIC Code: 3295
Operation Permit No.: T 089-6260-00339
Permit Reviewer: Teresa Freeman

On November 20, 2003, the Office of Air Quality (OAQ) had a notice published in The Post Tribune in Merrillville, Indiana and The Times in Munster, Indiana, stating that Edward C. Levy Company, Inc., had applied for a Part 70 Operating Permit to operate a steel slag processing facility. The notice also stated that OAQ proposed to issue a permit for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of sixty (60) days to provide comments on whether or not this permit should be issued as proposed.

Upon further review, the OAQ has decided to make the following revisions to the permit (bolded language has been added, the language with a line through it has been deleted). The Table Of Contents has been modified to reflect these changes. Miscellaneous grammar and spelling corrections have been made throughout the permit also.

Change 1:

On December 31, 2003, IDEM adopted a revision to 326 IAC 1-4-1 redesignating Lake County as attainment for PM₁₀. Therefore, condition A.1 is revised as follows:

A.1 General Information ~~[326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]~~

The Permittee owns and operates a stationary steel slag processing source.

Responsible Official:	Dave Oram
Source Address:	3001 Dickey Road, East Chicago, Indiana 46312
Mailing Address:	3001 Dickey Road, East Chicago, Indiana 46312
General Source Phone Number:	219-391-3136
SIC Code:	3295
County Location:	Lake
Source Location Status:	Nonattainment for PM₁₀ [*] , SO ₂ , and ozone Attainment for all other criteria pollutants
Source Status:	Part 70 Permit Program Major Source, under PSD and Emission Offset Rules; Major Source, Section 112 of the Clean Air Act 1 of 28 Source Categories under PSD and Emission Offset Rules

~~*Lake County has been federally redesignated in 40 CFR 81.315 as attainment for PM₁₀. The Air Pollution Control Board will be making the same redesignation in state rules.~~

Change 2:

Condition A.3 and D.1 Description Box have been changed to correct the equipment capacities of items (l) and (r) as follows:

A.3 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
[326 IAC 2-7-5(15)]

- (l) One (1) conveyor, rated capacity of ~~22~~**100** tons per hour, installed in 1986.
- (m) One (1) screen, rated capacity of 900 tons per hour, installed in 1986.
- (n) One (1) screen, rated capacity of 700 tons per hour, installed in 1986.
- (o) One (1) screen, rated capacity of 700 tons per hour, installed in 1987.
- (p) Two (2) screens, rated capacity of 350 tons per hour, each, installed in 1986.
- (q) Two (2) screens, rated capacity of 200 tons per hour, each, installed in 1988.
- (r) One (1) screen, rated capacity of ~~56~~ **500** tons per hour, installed in 1986.
- (s) One (1) crusher, rated capacity of 300 tons per hour, installed in 1986.
- (t) Two (2) crushers, rated capacity of 140 tons per hour, each, installed in 1986.
- (u) One (1) stacking conveyor, rated capacity of 200 tons per hour, installed in 1986.
- (v) Three (3) radial stacking conveyors, rated capacity of 500 tons per hour, each, installed in 1986.
- (w) One (1) radial stacking conveyors, rated capacity of 480 tons per hour, installed in 1986.

Change 3:

The (b) in condition B.12 was identified and numbering corrected.

B.12 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

- (a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- ~~(e)~~(b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- ~~(d)~~(c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false,

or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.

~~(e)~~ (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:

- (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
- (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
- (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
- (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.

~~(f)~~ (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions)

~~(g)~~ (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]

~~(h)~~(g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

Change 4:

The title of condition B.21, Inspection and Entry, has been revised to include an additional rule cite as follows:

B.21 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2][IC 13-30-3-1][**IC 13-17-3-2**]

Change 5:

Corrected Fugitive Dust Plan submittal date in condition C.5 (a) (14).

C.5 Fugitive Dust Emissions [326 IAC 6-1-11.1]

(14) Slag and kish handling activities at integrated iron and steel plants shall comply with the following particulate emissions limits:

- (A) The opacity of fugitive particulate emissions from transfer from pots and trucks into pits shall not exceed twenty percent (20%) on a six (6) minute average.
- (B) The opacity of fugitive particulate emissions from transfer from pits into front end loaders and from transfer from front end loaders into trucks shall comply with the fugitive particulate emission limits in 326 IAC 6-1-11.1(d)(9).

Material processing facilities include crushers, screens, grinders, mixers, dryers, belt conveyors, bucket elevators, bagging operations, storage bins, and truck or railroad car loading stations.

The Permittee shall achieve these limits by controlling fugitive particulate matter emissions according to the Fugitive Dust Control Plan, submitted on ~~November 22, 1993~~ **July 10, 1996**.

Change 6:

IDEM has revised the condition C.7 in order to clarify what parts of the regulation are not federally enforceable as follows:

C.7 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted. The provisions of **326 IAC 1-7-1(3)**, 326 IAC 1-7-2, 326 IAC 1-7-3(c) and (d), 326 IAC 1-7-4(d), (e), and (f), and 326 IAC 1-7-5(a), (b), and (d) are not federally enforceable.

Change 7:

In condition C.9, the term "source" is replaced with "Permittee" as follows:

C.9 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ, not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the ~~source~~ **Permittee** submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Change 8:

In condition C.15, the rule cite has been changed and the term "source" is replaced with "Permittee" as follows:

C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.245]

If a regulated substance, as defined in 40 CFR 68, is present at a source in more than a threshold quantity, the ~~source~~ **Permittee** must comply with the applicable requirements of 40 CFR 68.

Change 9:

Condition C.16 - Compliance Response Plan - Preparation, Implementation, Records, and Reports has been modified to apply only to situations where the emissions unit will continue to operate for an extended time while the compliance monitoring parameter is out of range. It is intended to

provide OAQ an opportunity to assess the situation and determine whether any additional actions are necessary to demonstrate compliance with applicable requirements. In addition if a source is required to have an Operation, Maintenance and Monitoring (OMM) Plan (or Parametric Monitoring Plan and Start-up, Shutdown, and Malfunction (SSM) Plan) under 40 CFR 60/63, such plans shall be deemed to satisfy the requirements for a CRP. The changes to condition C.16 are as follows:

C.16 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5]
[326 IAC 2-7-6]

(a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. **If a Permittee is required to have an Operation, Maintenance and Monitoring (OMM) Plan (or Parametric Monitoring Plan and Start-up, Shutdown, and Malfunction (SSM) Plan) under 40 CFR 60/63, such plans shall be deemed to satisfy the requirements for a CRP for those compliance monitoring conditions.** A CRP shall be submitted to IDEM, upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:

- (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
- (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan **or Operation, Maintenance and Monitoring (OMM) Plan (or Parametric Monitoring Plan and Start-up, Shutdown, and Malfunction (SSM) Plan) and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan or Operation, Maintenance and Monitoring (OMM) Plan (or Parametric Monitoring Plan and Start-up, Shutdown, and Malfunction (SSM) Plan) to include such response steps taken.**

The OMM Plan (or Parametric Monitoring and SSM Plan) shall be submitted within the time frames specified by the applicable 40 CFR60/63 requirement.

(b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:

- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
- (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
- (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, **and it will be ten (10) days or more until the unit or device will be shut down, the Permittee shall promptly notify** the IDEM, OAQ ~~shall be promptly notified~~ of the expected date of the shut down. **The notification shall also include** the status of the applicable compliance monitoring parameter with respect to normal, and the results of the **response** actions taken up to the time of notification.
- (4) Failure to take reasonable response steps shall be considered a deviation from the permit.

Change 10:

IDEM has revised condition C.18, since the rule revisions to 326 IAC 2-6 are not effective, the provisions that will be required by the revised rule will not be incorporated at this time. The condition will be revised so that the Permittee is required to follow the requirements of the rule, including the revised rule when it becomes effective, instead of requiring in the condition that the emission statement to be submitted on April 15th (or July 1st). Once the rule becomes effective, the Permittee may request an amendment to the operating permit in order to incorporate specific requirements of the revised rule.

C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

(a) The Permittee shall submit an annual emission statement certified pursuant to the requirements of 326 IAC 2-6. ~~that must be received by April 15 of each year and This~~ **statement must be received in accordance with the compliance schedule specified in 326 IAC 2-6-3** and must comply with the minimum requirements specified in 326 IAC 2-6-4. **The submittal should cover the period identified in 326 IAC 2-6.** The annual emission statement shall meet the following requirements:

- (1) Indicate estimated actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
- (2) Indicate estimated actual emissions of regulated pollutants (as defined by 326 IAC 2-7-1(32)) ("Regulated pollutant which is used only for purposes of Section 19 of this rule") from the source, for purposes of Part 70 fee assessment.

~~(b) The annual emission statement covers the twelve (12) consecutive month time period starting December 1 and ending November 30. The annual emission statement must be submitted to:~~

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

~~(c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.~~

~~(e) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.~~

Change 11:

In condition C.20, the term "source" is replaced with "Permittee" as follows:

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

(a) The ~~source~~ **Permittee** shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported.

This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Change 12:

D.1.9 was incorrectly numbered, should read D.1.8:

D.1.98 Reporting Requirements

Change 13:

Rule cites were added to D.2 Description Box.

Facility Description [326 IAC 2-7-5(15)]:

Insignificants:

- (a) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons. **[326 IAC 8-9]**
- (b) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6. [326 IAC 8-3-2 (Cold Cleaner Operations)] **[326 IAC 8-3-5] [326 IAC 8-3-8]**
- (c) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches, soldering equipment, welding equipment. **[326 IAC 6-1-2]**

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Change 14:

D.2.6 is not a valid condition. There is no grinding and machining operations at this facility.

~~**Compliance Determination Requirement**~~

~~**D.2.6 Particulate Control**~~

~~In order to comply with D.2.1, the control equipment for particulate control shall be in operation and control emissions from the grinding and machining operations at all times that the grinding and machining operations are in operation.~~

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.2.76 Record Keeping Requirements

Pursuant to 326 IAC 8-9, the Permittee must keep records of the following:

- (a) The vessel identification number;
- (b) The vessel dimensions; and
- (c) The vessel capacity.

Records shall be maintained for the life of the vessel.

Change 15:

Corrected Name on all forms to:

Source Name: Edward C. Levy **Company, Inc.**, a contractor of ISG-Indiana Harbor, Inc.

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Part 70 Operating Permit

Source Background and Description

Source Name: Edward C. Levy Company, Inc., a contractor of ISG-Indiana Harbor, Inc.
Source Location: 3001 Dickey Road, East Chicago, Indiana 46312
County: Lake
SIC Code: 3295
Operation Permit No.: T 089-6260-00339
Permit Reviewer: Teresa Freeman

The Office of Air Quality (OAQ) has reviewed a Part 70 permit application from Edward C. Levy Company, Inc. relating to the operation of a steel slag processing facility.

Source Definition

ISG-Indiana Harbor, Inc. is a fully integrated steelmaking and finishing facility consists of a source with on-site contractors:

- (a) ISG-Indiana Harbor, Inc., (089-00318) the primary operation, is located at, 3001 Dickey Road, East Chicago, Indiana 46312; and
- (b) Edward C. Levy Company, Inc. (089-00339), the supporting operation (a steel slag processing facility), is located at 3001 Dickey Road, East Chicago, Indiana 46312.

IDEM has determined that ISG-Indiana Harbor, Inc. and Edward C. Levy Company, Inc. are under the common control of ISG-Indiana Harbor, Inc. These two plants are considered one source due to contractual control. Therefore, the term "source" in the Part 70 documents refers to both ISG-Indiana Harbor, Inc. and Edward C. Levy Company, Inc., as one source.

Separate Part 70 permits will be issued to ISG-Indiana Harbor, Inc. and Edward C. Levy Company, Inc. solely for administrative purposes. For permitting purposes, ISG-Indiana Harbor, Inc. is assigned Permit No. 089-7099-00318 and Edward C. Levy Company, Inc. is assigned Permit No. 089-6260-00339.

Permitted Emission Units and Pollution Control Equipment

Edward C. Levy Company, Inc. operates a slag processing operations with a maximum capacity of 700 tons per hour and uncontrolled emissions, consisting of the following:

- (a) One (1) conveyor, rated capacity of 825 tons per hour, installed in 1986.
- (b) Three (3) conveyors, rated capacity of 700 tons per hour, each, installed in 1986.
- (c) Three (3) conveyors, rated capacity of 500 tons per hour, each, installed in 1986.
- (d) One (1) conveyor, rated capacity of 500 tons per hour, installed in 1988.

- (e) Two (2) conveyors, rated capacity of 150 tons per hour, each, installed in 1986.
- (f) One (1) conveyor, rated capacity of 140 tons per hour, installed in 1986.
- (g) Two (2) conveyors, rated capacity of 100 tons per hour, each, installed in 1986.
- (h) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1987.
- (i) Two (2) conveyors, rated capacity of 100 tons per hour, each, installed in 1986.
- (j) One (1) screen, rated capacity of 900 tons per hour, installed in 1986.
- (k) One (1) screen, rated capacity of 700 tons per hour, installed in 1986.
- (l) One (1) screen, rated capacity of 700 tons per hour, installed in 1987.
- (m) Two (2) screens, rated capacity of 350 tons per hour, each, installed in 1986.
- (n) Two (2) screens, rated capacity of 200 tons per hour, each, installed in 1988.
- (o) One (1) screen, rated capacity of 56 tons per hour, installed in 1986.
- (p) One (1) crusher, rated capacity of 300 tons per hour, installed in 1986.
- (q) Two (2) crushers, rated capacity of 140 tons per hour, each, installed in 1986.
- (r) One (1) stacking conveyor, rated capacity of 200 tons per hour, installed in 1986.
- (s) Three (3) radial stacking conveyors, rated capacity of 500 tons per hour, each, installed in 1986.
- (t) One (1) radial stacking conveyors, rated capacity of 480 tons per hour, installed in 1986.

Unpermitted Emission Units and Pollution Control Equipment

Edward C. Levy Company, Inc. also consists of the following unpermitted facilities/units:

- (a) One (1) conveyor, rated capacity of 300 tons per hour, installed in 1992.
- (b) One (1) conveyor, rated capacity of 270 tons per hour, installed in 1992.
- (c) One (1) conveyor, rated capacity of 100 tons per hour, installed in 1990.
- (d) One (1) ballast stacker, rated capacity of 510 tons per hour, installed in 1990.

Insignificant Activities

Insignificant Activities

Edward C. Levy Company, Inc. also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Propane for liquefied petroleum gas, or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) Btu per hour.
- (b) Equipment powered by internal combustion engines of capacity equal to or less than

- 500,000 Btu/hr, except where total capacity of equipment operated by one stationary source exceeds 2,000,000 Btu/hr.
- (c) A petroleum fuel, other than gasoline, dispensing facility, having a storage capacity of less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.
 - (d) Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons.
 - (e) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6.
 - (f) The following equipment related to manufacturing activities not resulting in the emission of HAPs: brazing equipment, cutting torches soldering equipment, welding equipment.
 - (g) Cutting 200,000 linear feet or less of one inch (1") plate or equivalent.
 - (h) Using 80 tons or less of welding consumables.
 - (i) Any operation using aqueous solutions containing less than 1% by weight of VOCs excluding HAPs.
 - (j) Gasoline generators not exceeding 110 horsepower.
 - (k) Diesel generators not exceeding 1,600 horsepower.

Existing Approvals

Edward C. Levy Company, Inc. has stated that the City of East Chicago permitted the source when it was constructed in 1986. After the State assumed responsibility for air permitting responsibilities in 1990, the owners of Edward C. Levy Company, Inc. began paying fees to the State. The State informed the Permittee that a "State" permit would be issued through the Title V Program.

Enforcement Issue

- (a) IDEM is aware that equipment has been constructed and operated prior to receipt of the proper permit. The subject equipment is listed in this Technical Support Document under the condition entitled Unpermitted Emission Units and Pollution Control Equipment.
- (b) IDEM is reviewing this matter and will take appropriate action. This proposed permit is intended to satisfy the requirements of the construction permit rules.

Recommendation

The staff recommends to the Commissioner that the Part 70 permit be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively incomplete Part 70 permit application for the purposes of this review was received on July 10, 1996. Additional information received on October 21, 1996 makes the Part 70 permit application administratively complete.

A notice of completeness letter was mailed to Edward C. Levy Company, Inc. on December 9,

1996.

Emission Calculations

The input of slag to the crushing and screening facilities shall not exceed 675,330 tons per year, equivalent to PM emissions after controls of less than twenty-five (25) tons per year including fugitive emissions. This input limit will also assure that the PM₁₀ emissions are less than fifteen (15) tons per year, including fugitives. This throughput limit was calculated as follows from the ratio of the limiting case (PM):

Offset Sig. Level :

$$(25 \text{ TPY}) / 227 \text{ TPY PTE after controls} * 700 \text{ TPH} * 8,760 \text{ hrs/yr} = < 675,330 \text{ TPY}$$

$$(15 \text{ TPY}) / 55 \text{ TPY PTE after controls} * 700 \text{ TPH} * 8,760 \text{ hrs/yr} = 1, 672, 363 \text{ TPY}$$

See Appendix A of this document for detailed emissions calculations.

Potential To Emit -ISG Indiana Harbor, Inc. and Edward C. Levy Company, Inc.

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA.”

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	greater than 100
PM-10	greater than 100
SO ₂	greater than 100
VOC	greater than 25
CO	greater than 100
NO _x	greater than 100
Total HAPs	greater than 25

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of PM₁₀, SO₂, CO and NO_x are equal to or greater than 100 tons per year and the potential to emit (as defined in 326 IAC 2-1.1-1(16)) of VOC is equal to or greater than 25 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of any single HAP is equal to or greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination HAPs is greater than or equal to twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (c) Fugitive Emissions
 Since this type of operation is one of the twenty-eight (28) listed source categories under 326 IAC 2-2, the fugitive emissions are counted toward determination of PSD and

Emission Offset applicability.

Actual Emissions-Edward C. Levy Company, Inc.

The following table shows the actual emissions from Edward C. Levy Company, Inc. This information reflects the 2001 OAQ emission data for Edward C. Levy Company, Inc. only.

Pollutant	Actual Emissions (tons/year)
PM	1.09
PM-10	1.09
SO ₂	no data
VOC	no data
CO	no data
NO _x	no data
HAP	no data

County Attainment Status

The source is located in Lake County.

Pollutant	Status
PM-10	Moderate nonattainment*
SO ₂	Marginal Nonattainment
NO ₂	Attainment
Ozone	Severe Nonattainment
CO	Attainment
Lead	Attainment or unclassifiable

*Lake County has been federally redesignated in 40 CFR 81.315 as attainment for PM10. The Air Pollution Control Board will be making the same redesignation in state rules.

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Lake County has been designated as nonattainment for ozone. Therefore, VOC emissions were reviewed pursuant to the requirements for Emission Offset, 326 IAC 2-3.
- (b) Lake County has been classified as nonattainment for PM10 (see table above) and SO₂. Therefore, these emissions were reviewed pursuant to the requirements for Emission Offset, 326 IAC 2-3.
- (c) Lake County has been classified as attainment or unclassifiable for all other pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (d) Fugitive Emissions
 Since this type of operation is one of the twenty-eight (28) listed source categories under 326 IAC 2-2, the fugitive emissions are counted toward determination of PSD and Emission Offset applicability.

Part 70 Permit Conditions

This source is subject to the requirements of 326 IAC 2-7, pursuant to which the source has to meet the following:

- (a) Emission limitations and standards, including those operational requirements and limitations that assure compliance with all applicable requirements at the time of issuance of Part 70 permits.
- (b) Monitoring and related record keeping requirements which assume that all reasonable information is provided to evaluate continuous compliance with the applicable requirements.

Federal Rule Applicability

- (a) Edward C. Levy Company, Inc., is not subject to the requirements of the New Source Performance Standard, 326 IAC 12, 40 CFR 60.670 through 60.676, Subpart OOO (Standards of Performance for Nonmetallic Mineral Processing Plants) since the slag material being crushed is not a nonmetallic mineral pursuant to 40 CFR 60.671.
- (b) Edward C. Levy Company, Inc., is not subject to the requirements of the New Source Performance Standard, 326 IAC 12, 40 CFR 60.380 through 60.686, Subpart LL (Standards of Performance for Metallic Mineral Processing Plants) since the operations are not producing metallic mineral concentrates from ore. None of these slag crushing and/or screening operations are performed in a mine or pit.
- (c) The storage tanks (insignificant activities) with a capacity of 1000 gallons of diesel fuel each are not subject to 40 CFR 60.110b, Subpart Kb since the capacity is less than 40 cubic meters.
- (d) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14, 40 CFR Part 61 and 40 CFR Part 63) applicable to Edward C. Levy Company, Inc.
- (e) The requirements of Section 112(j) of the Clean Air Act (40 CFR Part 63.50 through 63.56) are not applicable to Edward C. Levy Company, Inc. because they do not have one or more units that belong to one or more source categories affected by the Section 112(j) Maximum Achievable Control Technology (MACT) Hammer date of May 15, 2002.

State Rule Applicability - Entire Source

326 IAC 2-2 (PSD) and 326 IAC 2-3 (Emission Offset)

The input of steel mill slag to the crushing, screening and conveying plant shall not exceed 675,330 tons per twelve (12) consecutive month period. This will ensure limiting particulate matter emissions from the entire plant to less than 25 tons per year and that of particulate matter less than 10 micron size diameter to less than 15 tons per year, including fugitives. Therefore, the requirements of 326 IAC 2-2 (PSD) and 326 IAC 2-3 (Emission Offset), do not apply.

326 IAC 2-6 (Emission Reporting)

This source is subject to 326 IAC 2-6 (Emission Reporting), because it has the potential to emit more than one hundred (100) tons per year (Lake County) of PM10. Pursuant to this rule, the Permittee must annually submit an emission statement for the source. The annual statement must be received by April 15 of each year and contain the minimum requirement as specified in 326 IAC 2-6-4. The submittal should cover the period defined in 326 IAC 2-6-2(8)(Emission Statement Operating Year).

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of twenty percent (20%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 6-1-2 (g) Mineral Aggregate Operations: (Nonattainment Area PM Limitations)

- (a) Pursuant to 326 IAC 6-1-2 (g), the crushing, sizing, storing and transporting of mineral materials shall be limited to the following:
 - (1) All mineral aggregate operations, where the process is totally enclosed, and thus it is practical to measure the emissions therefrom, shall comply with the 0.03 grain per dry standard cubic feet per minute in 326 IAC 6-1-2 (a).
 - (2) In addition, 326 IAC 2, 326 IAC 5-1, and 326 IAC 6-4 shall apply in all cases to mineral aggregate operations.
- (b) Pursuant to 326 IAC 6-1-2 (Nonattainment Area Particulate Limitations), the particulate matter emissions from the brazing equipment, cutting torches, soldering equipment, welding equipment shall not exceed 0.03 grains per dry standard cubic foot (gr/dscf).

326 IAC 6-1-10.1 (Lake County PM10 Emission Requirements)

Pursuant to 326 IAC 6-1-10.1(l)(21), a CCP shall also be submitted by any source in Lake County for facilities that perform manufacturing operations in a building or structure such that the total uncontrolled PM₁₀ emissions from all such operations amount to ten (10) tons per year or more and that could potentially escape into the atmosphere through roof vents and other openings. The uncontrolled PM₁₀ emissions shall be estimated with AP-42, "Compilation of Air Pollutant Emission Factors, Volume I, (Stationary Point and Area Sources)", 4th Edition, September 1985, (and succeeding amendments) emission factors or other documentable emission factors acceptable to the commissioner.

326 IAC 6-1-11.1 (Lake County Fugitive Particulate Matter Control Requirements)

- (a) Pursuant to 326 IAC 6-1-11.1 (Lake County Fugitive Particulate Matter Control Requirements), the particulate matter emissions from source wide activities shall meet the following requirements:
 - (1) The average instantaneous opacity of fugitive particulate emissions from a paved road shall not exceed ten percent (10%).
 - (2) The average instantaneous opacity of fugitive particulate emissions from an unpaved road shall not exceed ten percent (10%).
 - (3) The average instantaneous opacity of fugitive particulate emissions from batch transfer shall not exceed ten percent (10%).
 - (4) The opacity of fugitive particulate emissions from continuous transfer of material onto and out of storage piles shall not exceed ten percent (10%) on a three (3) minute average.
 - (5) The opacity of fugitive particulate emissions from storage piles shall not exceed ten percent (10%) on a six (6) minute average.
 - (6) There shall be a zero (0) percent frequency of visible emission observations of a material during the inplant transportation of material by truck or rail at any time.

- (7) The opacity of fugitive particulate emissions from the inplant transportation of material by front end loaders and skip hoists shall not exceed ten percent (10%).
- (8) There shall be a zero (0) percent frequency of visible emission observations from a building enclosing all or part of the material processing equipment, except from a vent in the building.
- (9) The PM10 emissions from building vents shall not exceed twenty-two thousandths (0.022) grains per dry standard cubic foot and ten percent (10%) opacity.
- (10) The opacity of particulate emissions from dust handling equipment shall not exceed ten percent (10%).
- (11) Any facility or operation not specified in 326 IAC 6-1-11.1(d) shall meet a twenty percent (20%), three (3) minute average opacity standard.
- (12) PM10 emissions from each material processing stack shall not exceed 0.022 grains per dry standard cubic foot and ten percent (10%) opacity
- (13) Fugitive particulate matter from the material processing facilities shall not exceed ten percent (10%) opacity
- (14) Slag and kish handling activities at integrated iron and steel plants shall comply with the following particulate emissions limits:
 - (A) The opacity of fugitive particulate emissions from transfer from pots and trucks into pits shall not exceed twenty percent (20%) on a six (6) minute average.
 - (B) The opacity of fugitive particulate emissions from transfer from pits into front end loaders and from transfer from front end loaders into trucks shall comply with the fugitive particulate emission limits in 326 IAC 6-1-11.1(d)(9).

Material processing facilities include crushers, screens, grinders, mixers, dryers, belt conveyors, bucket elevators, bagging operations, storage bins, and truck or railroad car loading stations.

- (b) The Permittee shall achieve these limits by controlling fugitive particulate matter emissions according to the Fugitive Dust Control Plan, submitted on November 22, 1993.

326 IAC 6-1-11.2 (Lake County Particulate Matter Contingency Measures)

The source is subject to 326 IAC 6-1-11.2 because it is subject to the requirements of 326 IAC 6-1-11.1 and 326 IAC 6-1-10.1(d). Pursuant to this rule, the source shall comply with parts (h), (i), (k), (l), (m), (o), (p) and (q) of this rule.

326 IAC 6-3-2 (Particulate Emissions Limitations)

Limitations established by 326 IAC 6-3 do not apply if limitations established at 326 IAC 6-1 or 326 IAC 12 apply. Since the requirements of 326 IAC 6-1 apply to this source, 326 IAC 6-3 is not applicable.

326 IAC 6-4 (Fugitive Dust Emissions)

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

326 IAC 8-3-2 (Cold Cleaner Operations)

Pursuant to 326 IAC 8-3-2 (Cold Cleaner Operations) for cold cleaning operations constructed after January 1, 1980, the owner or operator shall:

- (a) Equip the cleaner with a cover;
- (b) Equip the cleaner with a facility for draining cleaned parts;
- (c) Close the degreaser cover whenever parts are not being handled in the cleaner;
- (d) Drain cleaned parts for at least fifteen (15) seconds or until dripping ceases;
- (e) Provide a permanent, conspicuous label summarizing the operation requirements;
- (f) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, in such a manner that greater than twenty percent (20%) of the waste solvent (by weight) can evaporate into the atmosphere.

326 IAC 8-3-5 (Volatile Organic Compounds (VOC))

Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), for cold cleaner degreaser operations without remote solvent reservoirs existing as of July 1, 1990, located in Clark, Elkhart, Floyd, Lake, Marion, Porter or St. Joseph Counties, the Permittee shall ensure that the following requirements are met:

- (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:
 - (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F));
 - (B) The solvent is agitated; or
 - (C) The solvent is heated.
- (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.
- (3) Provide a permanent, conspicuous label, which lists the operating requirements outlined in subsection (b).
- (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure, which does not cause excessive splashing.
- (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):

- (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
- (B) A water cover when solvent is used is insoluble in, and heavier than, water.
- (C) Other systems of demonstrated equivalent control such as a refrigerated chiller of carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.

326 IAC 8-3-8 (Volatile Organic Compounds (VOC))

Pursuant to 326 IAC 8-3-8 (Material requirements for cold cleaning degreasers), the users, providers, and manufacturers of solvents for use in cold cleaning degreasers in Clark, Floyd, Lake, and Porter Counties, except for solvents intended to be used to clean electronic components shall do the following:

- (a) On and after November 1, 1999, no person shall Operate a cold cleaning degreaser with a solvent vapor pressure that exceeds two (2) millimeters of mercury (thirty-eight thousandths (0.038) pound per square inch) measured at twenty (20) degrees Celsius (sixty-eight (68) degrees Fahrenheit).
- (b) On and after May 1, 2001, no person shall Operate a cold cleaning degreaser with a solvent vapor pressure that exceeds one (1) millimeter of mercury (nineteen-thousandths (0.019) pound per square inch) measured at twenty (20) degrees Celsius (sixty-eight (68) degrees Fahrenheit).
- (c) On and after November 1, 1999, all persons subject to the requirements of 326 IAC 8-3-8 (c)(1)(B) and (c)(2)(B) shall maintain each of the following records for each purchase:
 - (1) The name and address of the solvent supplier.
 - (2) The date of purchase.
 - (3) The type of solvent.
 - (4) The volume of each unit of solvent.
 - (5) The total volume of the solvent.
 - (6) The true vapor pressure of the solvent measured in millimeters of mercury at twenty (20) degrees Celsius (sixty-eight (68) degrees Fahrenheit).

326 IAC 8-9 (Volatile Organic Liquid Storage Vessels)

Pursuant to 326 IAC 8-9-1, the Permittee is required to keep records on the information in 326 IAC 8-9-6(a)-(b) for all storage vessels

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as

grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

Edward C. Levy Company, Inc. has the following applicable compliance monitoring conditions:

- (a) Visible emissions notations of the exhausts from the hoppers, the screens, and the conveyor transfer points shall be performed once per shift during normal daylight operations. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit
- (b) Pursuant to 326 IAC 6-1-10.1(l)(21), a CCP shall also be submitted by any source in Lake County for facilities that perform manufacturing operations in a building or structure such that the total uncontrolled PM₁₀ emissions from all such operations amount to ten (10) tons per year or more and that could potentially escape into the atmosphere through roof vents and other openings. The uncontrolled PM₁₀ emissions shall be estimated with AP-42, "Compilation of Air Pollutant Emission Factors, Volume I, (Stationary Point and Area Sources)", 4th Edition, September 1985, (and succeeding amendments) emission factors or other documentable emission factors acceptable to the commissioner.
- (c) Records must be kept of slag input.

Conclusion

The operation of this a steel slag processing operation shall be subject to the conditions of the attached proposed Part 70 Permit No. 089-6260-00339.

Appendix A: Emission Calculations

PM-10 Calculations

Company Name: Edward C. Levy
Address City IN Zip: 3001 Dickey Rd, East Chicago, Indiana 46312
Permit No. 089-6260
Plt ID: 089-00339
Reviewer: Teresa Freeman
Date: May 7, 2001

emissions before controls

		PM-10				
Storage		** see page 2 **			4.91 tons/yr	AP-42 Ch.11.2.3 (Fourth edition, no update)
Transporting		** see page 3 **			88.86 tons/yr	AP-42 Ch. 13.2.2 (Supplement E, 9/98)
Loading/Unloading	700 ton/hr x	0.0016 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	4.95 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Crushing (primary)	300 ton/hr x	0.0007 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	0.92 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Crushing (secondary) ¹	200 ton/hr x	0.0024 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	2.10 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Crushing (tertiary) ¹	0 ton/hr x	0.0024 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	0.00 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Screening ¹	700 ton/hr x	0.015 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	45.99 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Conveyor Transfer	700 ton/hr x	0.0014 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	4.29 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Total emissions before controls:					152.03 tons/yr	

See AP-42 (1/95) Table 11.19.2-2, notes c and d before using these emission factors (PM10 emission factors differ from those listed above).

¹PM10 emission factors are calculated by dividing the TSP emission factors by 2.1 (approximately 47.5% of the TSP factors).

* * emissions after controls * *

Storage	4.91 tons/yr x	10% emitted after controls =	0.49 tons/yr
Transporting	88.86 tons/yr x	50% emitted after controls =	44.43 tons/yr
Loading & Unloading	4.95 tons/yr x	100% emitted after controls =	4.95 tons/yr
Crushing (primary)	0.92 tons/yr x	10% emitted after controls =	0.09 tons/yr
Crushing (secondary)	2.10 tons/yr x	10% emitted after controls =	0.21 tons/yr
Crushing (tertiary)	0.00 tons/yr x	10% emitted after controls =	0.00 tons/yr
Screening	45.99 tons/yr x	10% emitted after controls =	4.60 tons/yr
Conveying	4.29 tons/yr x	10% emitted after controls =	0.43 tons/yr
Total emissions after controls:			55.20 tons/yr

** fugitive vs. nonfugitive **

Storage	4.91 tons/yr x	10% emitted after controls =	0.49 tons/yr
Transporting	88.86 tons/yr x	50% emitted after controls =	44.43 tons/yr
Loading / Unloading	4.95 tons/yr x	100% emitted after controls =	4.95 tons/yr
Total fugitive emissions:			49.87 tons/yr
Crushing (primary)	0.92 tons/yr x	10% emitted after controls =	0.09 tons/yr
Crushing (secondary)	2.10 tons/yr x	10% emitted after controls =	0.21 tons/yr
Crushing (tertiary)	0.00 tons/yr x	10% emitted after controls =	0.00 tons/yr
Screening	45.99 tons/yr x	10% emitted after controls =	4.60 tons/yr
Conveying:	4.29 tons/yr x	10% emitted after controls =	0.43 tons/yr
Total nonfugitive emissions:			5.33 tons/yr

** storage **

Storage emissions, which result from wind erosion, are determined by the following calculations:

$$E_f = 1.7 \cdot (s/1.5) \cdot (365-p) / 235 \cdot (f/15)$$

= 1.85 lb/acre/day

where s = 1.6 % silt content of material

p = 125 days of rain greater than or equal to 0.01 inches

f = 15 % of wind greater than or equal to 12 mph

$$E_p (\text{storage}) = E_f \cdot sc \cdot (40 \text{ cuft/ton}) / (2000 \text{ lb/ton}) / (43560 \text{ sqft/acre}) / (25 \text{ ft}) \cdot (365 \text{ day/yr})$$

= 4.91 tons/yr

where sc = 1,000,000 tons storage capacity

Note: This calculation is from AP-42, Fourth edition. The calculations were not included in subsequent editions of AP-42, therefore, it is up to the permit reviewers discretion to use this calculation.

**** unpaved roads ****

The following calculations determine the amount of emissions created by unpaved roads, based on 8760 hours of use and AP-42, Ch 13.2.2 (Supplement E, 9/98).

Two methods are provided for calculating emissions. The first does not consider natural mitigation due to precipitation.

$$\begin{aligned}
 &9.63 \text{ trip/hr} \times \\
 &0.93 \text{ mile/trip} \times \\
 &1 \text{ (round trip) } \times \\
 &8760 \text{ hr/yr} = \qquad \qquad \qquad 78453.684 \text{ miles per year}
 \end{aligned}$$

Method 2:

$$\begin{aligned}
 E_f &= \{k \cdot (s/12)^{0.8} \cdot [(W/3)^b] / [(M_{dry}/0.2)^c] \cdot [(365-p)/365]\} \\
 &= 2.27 \text{ lb/mile}
 \end{aligned}$$

- where k = 2.6 (particle size multiplier for PM-10) (k= 10 for PM-30 or TSP)
- s = 6 mean % silt content of unpaved roads
- b = 0.4 Constant for PM-10 (b = 0.5 for PM-30 or TSP)
- c = 0.3 Constant for PM-10 (c = 0.4 for PM-30 or TSP)
- W = 24 tons average vehicle weight
- M = 0.2 surface material moisture content, % (default is 0.2 for dry conditions)
- p = 125 least 0.254mm of precipitation (See

$$\frac{2.27 \text{ lb/mi} \times 78453.684 \text{ mi/yr}}{2000 \text{ lb/ton}} = 88.86 \text{ tons/yr}$$

**** aggregate handling ****

The following calculations determine the amount of emissions created by truck loading and unloading of aggregate, based on 8760 hours of use and AP-42, Ch 13.2.4 (Fifth edition, 1/95).

$$\begin{aligned}
 E_f &= k \cdot (0.0032)^2 \cdot (U/5)^{1.3} / (M/2)^{1.4} \\
 &= 0.0016 \text{ lb/ton}
 \end{aligned}$$

- where k = 0.35 (particle size multiplier)
- U = 10 mile/hr mean wind speed
- M = 2.93 % material moisture content

Appendix A: Emission Calculations

PM Emissions Calculations

Company Name: Edward C. Levy
Address City IN Zip: 3001 Dickey Rd, East Chicago, Indiana 46312
Permit No.: 089-6260
Pit ID: 089-00339
Reviewer: Teresa Freeman
Date: May 7, 2001

****emissions before controls**
(PM)**

Storage		** see page 5 **			12.41 tons/yr	AP-42 Ch.11.2.3 (Fourth edition, no update)
Transporting		** see page 6 **			408.84 tons/yr	AP-42 Ch. 13.2.2 (Supplement E, 9/98)
Loading & Unloading	700 ton/hr x	0.0034 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	10.47 tons/yr	AP-42 Ch.13.2.4 (Fifth edition, 1/95) calculated
Crushing (primary)	300 ton/hr x	0.0007 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	0.92 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Crushing (secondary) ¹	200 ton/hr x	0.00504 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	4.42 tons/yr	AP-42 Ch.11.19.2 based on Fire ver.6.22 EF for PM-10 of 0.15 lb/ton of raw material
Crushing (tertiary) ¹	0 ton/hr x	0.00504 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	0.00 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
Screening 2 ¹	700 ton/hr x	0.0315 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	96.58 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)
	700 ton/hr x	0.00294 lb/ton	/ 2000 lb/ton x	8760 hr/yr =	9.01 tons/yr	AP-42 Ch.11.19.2 (Fifth edition, 1/95)

Total emissions before controls: 542.66 tons/yr

See AP-42 (1/95) Table 11.19.2-2, notes c and d before using these emission factors (PM10 emission factors differ from those listed above).

¹PM10 emission factors are calculated by dividing the TSP emission factors by 2.1 (approximately 47.5% of the TSP factors).

*** * emissions after controls * ***

Storage	12.41 tons/yr x	10% emitted after controls =	1.24 tons/yr
Transporting	408.84 tons/yr x	50% emitted after controls =	204.42 tons/yr
Loading & Unloading	10.47 tons/yr x	100% emitted after controls =	10.47 tons/yr
Crushing (primary)	0.92 tons/yr x	10% emitted after controls =	0.09 tons/yr
Crushing (secondary)	4.42 tons/yr x	10% emitted after controls =	0.44 tons/yr
Crushing (tertiary)	0.00 tons/yr x	10% emitted after controls =	0.00 tons/yr
Screening	96.58 tons/yr x	10% emitted after controls =	9.66 tons/yr
Conveying	9.01 tons/yr x	10% emitted after controls =	0.90 tons/yr

Total emissions after controls: 227.23 tons/yr

** fugitive vs. nonfugitive **

Storage	12.41 tons/yr x	10% emitted after controls =	1.24 tons/yr
Transporting	408.84 tons/yr x	50% emitted after controls =	204.42 tons/yr
Loading / Unloading	10.47 tons/yr x	100% emitted after controls =	10.47 tons/yr
Total fugitive emissions:			216.14 tons/yr
Crushing (primary)	0.92 tons/yr x	10% emitted after controls =	0.09 tons/yr
Crushing (secondary)	4.42 tons/yr x	10% emitted after controls =	0.44 tons/yr
Crushing (tertiary)	0.00 tons/yr x	10% emitted after controls =	0.00 tons/yr
Screening	96.58 tons/yr x	10% emitted after controls =	9.66 tons/yr
Conveying:	9.01 tons/yr x	10% emitted after controls =	0.90 tons/yr
Total nonfugitive emissions:			11.09 tons/yr

** storage **

Storage emissions, which result from wind erosion, are determined by the following calculations:

$$E_f = 1.7 \cdot (s/1.5) \cdot (365-p) / 235 \cdot (f/15)$$

$$= 1.85 \text{ lb/acre/day}$$

- where s = 1.6 % silt content of material
- p = 125 days of rain greater than or equal to 0.01 inches
- f = 15 % of wind greater than or equal to 12 mph

$$E_p (\text{storage}) = E_f \cdot sc \cdot (40 \text{ cuft/ton}) / (2000 \text{ lb/ton}) / (43560 \text{ sqft/acre}) / (25 \text{ ft}) \cdot (365 \text{ day/yr})$$

$$= 12.41 \text{ tons/yr}$$

where sc = 1,000 ,000 tons storage capacity

Note: This calculation is from AP-42, Fourth edition. The calculations were not included in subsequent editions of AP-42, therefore, it is up to the permit reviewers discretion to use this calculation.

** unpaved roads **

The following calculations determine the amount of emissions created by unpaved roads, based on 8760 hours of use and AP-42, Ch 13.2.2 (Supplement E, 9/98). Two methods are provided for calculating emissions. The first does not consider natural mitigation due to precipitation.

$$\begin{aligned}
 &9.3 \text{ trip/hr} \times \\
 &0.93 \text{ mile/trip} \times \\
 &1 \text{ (round trip) } \times \\
 &8760 \text{ hr/yr} = \qquad \qquad \qquad 75765.24 \text{ miles per year}
 \end{aligned}$$

Method 1:

$$\begin{aligned}
 E_f &= k \cdot [(s/12)^{0.8}] \cdot [(W/3)^b] / [(M/0.2)^c] \\
 &= 0.00 \text{ lb/mile}
 \end{aligned}$$

where k = 10 (particle size multiplier for PM-10) (k= 10 for PM-30 or TSP)
 s = 8 mean % silt content of unpaved roads
 b = 0.5 Constant for PM-10 (b = 0.5 for PM-30 or TSP)
 c = 0.4 Constant for PM-10 (c = 0.4 for PM-30 or TSP)
 W = tons average vehicle weight
 M = 0.2 surface material moisture content, % (default is 0.2 for dry conditions)

$$\frac{0.00 \text{ lb/mi} \times 75765.24 \text{ mi/yr}}{2000 \text{ lb/ton}} = 0.00 \text{ tons/yr}$$

Method 2:

$$\begin{aligned}
 E_f &= \{k \cdot [(s/12)^{0.8}] \cdot [(W/3)^b] / [(M_{dry}/0.2)^c]\} \cdot [(365-p)/365] \\
 &= 10.79 \text{ lb/mile}
 \end{aligned}$$

where k = 10 (particle size multiplier for PM-10) (k=10 for PM-30 or TSP)
 s = 6 mean % silt content of unpaved roads
 b = 0.5 Constant for PM-10 (b = 0.5 for PM-30 or TSP)
 c = 0.4 Constant for PM-10 (c = 0.4 for PM-30 or TSP)
 W = 25 tons average vehicle weight
 M_{dry} = 0.2 surface material moisture content, % (default is 0.2 for dry conditions)
 p = 125 number of days with at least 0.254mm of precipitation (See Figure 13.2.2-1)

$$\frac{10.79 \text{ lb/mi} \times 75765.24 \text{ mi/yr}}{2000 \text{ lb/ton}} = 408.84 \text{ tons/yr}$$

Note: The permit reviewer can choose the method he/she wants to use. See AP-42 13.2.2 for further information. Cell J13 should reference G100 if Method 1 is used or N100 if Method 2 is used.

** aggregate handling **

The following calculations determine the amount of emissions created by truck loading and unloading of aggregate, based on 8760 hours of use and AP-42, Ch 13.2.4 (Fifth edition, 1/95).

$$\begin{aligned}
 E_f &= k \cdot (0.0032) \cdot (U/5)^{1.3} / (M/2)^{1.4} \\
 &= 0.0034 \text{ lb/ton}
 \end{aligned}$$

where k = 0.74 (particle size multiplier)
 U = 10 mile/hr mean wind speed
 M = 2.93 % material moisture content