

**PART 70 OPERATING PERMIT
and ENHANCED NEW SOURCE REVIEW
OFFICE OF AIR MANAGEMENT**

**Countrymark Cooperative, Inc.
US 24 West
Peru, Indiana 46959**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 and 326 IAC 2-1-3.2 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T 103-7974-00011	
Issued by: Felicia R. George, Assistant Commissioner Office of Air Management	Issuance Date:

TABLE OF CONTENTS

A SOURCE SUMMARY 4

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] 4

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] 4

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] . . 5

A.4 Part 70 Permit Applicability [326 IAC 2-7-2] 5

B GENERAL CONDITIONS 6

B.1 Permit No Defense [326 IAC 2-1-10] [IC 13] 6

B.2 Definitions [326 IAC 2-7-1] 6

B.3 Permit Term [326 IAC 2-7-5(2)] 6

B.4 Enforceability [326 IAC 2-7-7(a)] 6

B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)] 6

B.6 Severability [326 IAC 2-7-5(5)] 6

B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)] 6

B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)] 6

B.9 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)] 7

B.10 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] 7

B.11 Annual Compliance Certification [326 IAC 2-7-6(5)] 7

B.12 Preventive Maintenance Plan [326 IAC 2-7-5][326 IAC 2-7-6][326 IAC 1-6-3] 8

B.13 Emergency Provisions [326 IAC 2-7-16] 9

B.14 Permit Shield [326 IAC 2-7-15] 10

B.15 Multiple Exceedances [326 IAC 2-7-5(1)(E)] 11

B.16 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)] 11

B.17 Permit Modification, Reopening, Revocation and Reissuance, or Termination 12

B.18 Permit Renewal [326 IAC 2-7-4] 12

B.19 Administrative Permit Amendment [326 IAC 2-7-11] 13

B.20 Minor Permit Modification [326 IAC 2-7-12] 13

B.21 Significant Permit Modification [326 IAC 2-7-12(d)] 14

B.22 Permit Revision Under Economic Incentives and Other Programs 14

B.23 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-7-20(b)] 14

B.24 Operational Flexibility [326 IAC 2-7-20] 15

B.25 Construction Permit Requirement [326 IAC 2] 16

B.26 Inspection and Entry [326 IAC 2-7-6(2)] 16

B.27 Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11] 16

B.28 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)] 17

B.29 Enhanced New Source Review [326 IAC 2] 17

B.30 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 Federal Register 8313] . . . 17

C SOURCE OPERATION CONDITIONS 18

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Major Source 18

C.2 Opacity [326 IAC 5-1] 18

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9] 18

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2] 18

C.5 Fugitive Dust Emissions [326 IAC 6-4] 18

C.6 Operation of Equipment [326 IAC 2-7-6(6)] 18

C.7	Asbestos Abatement Projects - Accreditation [326 IAC 14-10] [326 IAC 18]	18
Testing Requirements [326 IAC 2-7-6(1)]		
C.8	Performance Testing [326 IAC 3-2.1]	19
Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]		
C.9	Compliance Schedule [326 IAC 2-7-6(3)]	19
C.10	Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]	19
C.11	Monitoring Methods [326 IAC 3]	20
C.12	Throughput Specifications	20
C.13	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]	20
Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]		
C.14	Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]	21
C.15	Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]	21
C.16	Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5(3)] . . .	22
C.17	Actions Related to Noncompliance Demonstrated by a Stack Test	23
Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]		
C.18	Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]	23
C.19	Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]	24
C.20	General Record Keeping Requirements [326 IAC 2-7-5(3)(B)]	24
C.21	General Reporting Requirements [326 IAC 2-7-5(3)(C)]	25
Stratospheric Ozone Protection		
C.22	Compliance with 40 CFR 82 and 326 IAC 22-1	26
D.1	FACILITY OPERATION CONDITIONS - Entire Source	27
Emission Limitations and Standards [326 IAC 2-7-5(1)]		
D.1.1	Hazardous Air Pollutants	27
D.1.2	Preventive Maintenance Plan [326 IAC 2-7-5(13)]	28
Compliance Determination Requirements		
D.1.3	Testing Requirements [326 IAC 2-7-6(1)]	28
Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]		
D.1.4	Flow Gauge Notations	28
D.1.5	Broken Flow Gauge Detection	28
Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19] [326 IAC 13-3-4] [40CFR Part 60.110]		
D.1.6	Record Keeping Requirements	29
D.1.7	Reporting Requirements	29
Certification Form		30
Compliance Report Form		31

Countrymark Cooperative, Inc.
Peru, Indiana
Permit Reviewer:MES

Page 4 of 38
OP No. T 103-7974-00011

Emergency/Deviation Occurrence Report 32
Quarterly Report Form 34

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM), and presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates a stationary bulk storage and wholesale petroleum products distribution source.

Responsible Official: Joe Sudholt
Source Address: U.S. 24 West, Peru, Indiana 46959
Mailing Address: 1200 Refinery Road, Mt. Vernon, Indiana 47620
SIC Code: 5171
County Location: Miami
County Status: Attainment for all criteria pollutants
Source Status: Part 70 Permit Program
Major, under PSD Rules;
Minor Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

- (a) Two (2) storage tanks, identified as Tanks 90 and 92, installed in 1953, capacity: 993,500 gallons of gasoline or distillates, each.
- (b) One (1) storage tank, identified as Tank 91, installed in 1953, vented to Tank 94, capacity: 414,300 of gasoline or distillates.
- (c) One (1) storage tank, identified as Tank 93, installed in 1953, capacity: 2,235,400 gallons of gasoline or distillates.
- (d) One (1) storage tank, identified as Tank 94, installed in 1953, capacity: 2,290,000 gallons of gasoline or distillates.
- (e) One (1) storage tank, identified as Tank 95, installed in 1956, capacity: 2,187,800 gallons of gasoline or distillates.
- (f) One (1) storage tank, identified as Tank 96, installed in 1958, capacity: 2,231,300 gallons of gasoline or distillates.
- (g) Two (2) storage tanks, identified as Tanks 97E and 97W, installed in 1979, capacity: 19,400 gallons of gasoline or distillates, each.
- (h) One (1) storage tank, identified as Tank 98, installed in 1988, capacity: 8,200 gallons of gasoline or distillates.
- (i) One (1) storage tank, identified as Sump Tank, installed in 1953, capacity: 1,000 gallons of gasoline mixture.

- (j) One (1) gasoline and distillate truck loading rack, identified as loading rack, installed in 1953, throughput capacity: 42,600 gallons of gasoline and/or distillates per hour.
- (k) Fugitives from pump seals, valves and flanges.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source does not currently have any insignificant activities, as defined in 326 IAC 2-7-1 (21) that have applicable NSPS or NESHAP requirements.

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONDITIONS

B.1 Permit No Defense [326 IAC 2-1-10] [IC 13]

- (a) Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7.
- (b) This prohibition shall not apply to alleged violations of applicable requirements for which the Commissioner has granted a permit shield in accordance with 326 IAC 2-1-3.2 or 326 IAC 2-7-15.

B.2 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.

B.3 Permit Term [326 IAC 2-7-5(2)]

This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.

B.4 Enforceability [326 IAC 2-7-7(a)]

- (a) All terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM.
- (b) Unless otherwise stated, terms and conditions of this permit, including any provisions to limit the source's potential to emit, are enforceable by the United States Environmental Protection Agency (U.S. EPA) and citizens under the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.6 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall furnish to IDEM, OAM, within a reasonable time, any information that IDEM, OAM, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit.
- (c) Upon request, the Permittee shall also furnish to IDEM, OAM, copies of records required to be kept by this permit. For information claimed to be confidential, the Permittee shall furnish such records to IDEM, OAM, along with a claim of confidentiality under 326 IAC 17. If requested by IDEM, OAM, or the U.S. EPA, the Permittee shall furnish such confidential records directly to the U.S. EPA along with a claim of confidentiality under 40 CFR 2, Subpart B.

B.9 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit constitutes a violation of the Clean Air Act and is grounds for:
 - (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance, or modification; or
 - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

B.10 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]

- (a) Any application form, report, or compliance certification submitted under this permit shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this permit, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.11 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
- (1) The identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining compliance of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAM, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.12 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
[326 IAC 1-6-3]

-
- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission units and associated emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;

- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM.

B.13 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-7-16.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Management, Compliance Section), or
Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967
 - (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice, either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAM, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAM, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value.

Any operation shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

B.14 Permit Shield [326 IAC 2-7-15]

- (a) This condition provides a permit shield as addressed in 326 IAC 2-7-15.
- (b) Compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that:
 - (1) The applicable requirements are included and specifically identified in this permit, or;
 - (2) The permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable.
- (c) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAM, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (d) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application.
- (e) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (f) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (g) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAM, has issued the modifications. [326 IAC 2-7-12(c)(7)]

- (h) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAM, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.15 Multiple Exceedances [326 IAC 2-7-5(1)(E)]

Any exceedance of a permit limitation or condition contained in this permit, which occurs contemporaneously with an exceedance of an associated surrogate or operating parameter established to detect or assure compliance with that limit or condition, both arising out of the same act or occurrence, shall constitute a single potential violation of this permit.

B.16 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within ten (10) calendar days from the date of the discovery of the deviation.

- (b) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent.
- (c) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

B.17 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)]
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAM, determines any of the following:
- (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAM, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]

- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAM, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAM, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.18 Permit Renewal [326 IAC 2-7-4]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAM, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due. [326 IAC 2-5-3]
 - (2) If IDEM, OAM, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-7-3]
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAM, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAM, any additional information identified as being needed to process the application.

- (d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]
If IDEM, OAM, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.19 Administrative Permit Amendment [326 IAC 2-7-11]

- (a) An administrative permit amendment is a Part 70 permit revision that makes changes of the type specified under 326 IAC 2-7-11(a).
- (b) An administrative permit amendment may be made by IDEM, OAM, consistent with the procedures specified under 326 IAC 2-7-11(c).
- (c) The Permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.20 Minor Permit Modification [326 IAC 2-7-12]

- (a) A permit modification is any revision to this permit that cannot be accomplished as an administrative permit amendment under 326 IAC 2-7-11.
- (b) Minor modification to this permit shall follow the procedures specified under 326 IAC 2-7-12(b), except as provided by 326 IAC 2-7-12(c).
- (c) An application requesting the use of minor modification procedures shall meet the requirements of 326 IAC 2-7-12(b) and shall include the information required in 326 IAC 2-7-12(b)(3) (A) through (E).
- (d) The Permittee may make the change proposed in its minor permit modification application immediately after it files such application provided that the change has received any approval required by 326 IAC 2-1. After the Permittee makes the change allowed under minor permit modification procedures, and until IDEM, OAM, takes any of the actions specified in 326 IAC 2-7-12(b)(6)(A) through (C), the Permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this period, the Permittee need not comply with the existing permit terms and conditions it seeks to modify. If the Permittee fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to modify may be enforced against it. [326 IAC 2-7-12(b)(7)]

B.21 Significant Permit Modification [326 IAC 2-7-12(d)]

- (a) Significant modification procedures shall be used for applications requesting permit modifications that do not qualify as minor permit modifications or as administrative amendments.
- (b) Every significant change in existing monitoring permit terms or conditions and every relaxation of reporting or record keeping permit terms or conditions of this permit shall be considered significant.
- (c) Nothing in 326 IAC 2-7-12(d) shall be construed to preclude the Permittee from making changes consistent with 326 IAC 2-7 that would render existing permit compliance terms and conditions irrelevant.

- (d) Significant modifications of this permit shall meet all requirements of 326 IAC 2-7, including those for application, public participation, review by affected states, review by the U.S. EPA, and availability of the permit shield, as they apply to permit issuance and renewal.

B.22 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
[326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1)(D)(i) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.23 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-7-20(b)]

The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a) and the following additional conditions:

- (a) For each such change, the required written notification shall include a brief description of the change within the source, the date on which the change will occur, any change in emissions, and any permit term or condition that is no longer applicable as a result of the change.
- (b) The permit shield, described in 326 IAC 2-7-15, shall not apply to any change made under 326 IAC 2-7-20(b).

B.24 Operational Flexibility [326 IAC 2-7-20]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-1 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20 (b), (c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAM, in the notices specified in 326 IAC 2-7-20(b), (c)(1), and (e)(2).

- (b) For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAM, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.25 Construction Permit Requirement [326 IAC 2]

Except as allowed by Indiana P.L. 130-1996 Section 12, as amended by P.L. 244-1997, modification, construction, or reconstruction shall be approved as required by and in accordance with 326 IAC 2.

B.26 Inspection and Entry [326 IAC 2-7-6(2)]

Upon presentation of IDEM identification cards, credentials, and other documents as may be required by law, the Permittee shall allow IDEM, OAM, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements. [326 IAC 2-7-6(6)]

B.27 Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11]

Pursuant to 326 IAC 2-1-6 and 326 IAC 2-7-11:

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAM, Permits Branch, within thirty (30) days of the change. Notification shall include a written agreement containing a specific date for transfer of permit responsibility, coverage, and liability between the Permittee and the new owner.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an administrative amendment pursuant to 326 IAC 2-7-11.
- (c) IDEM, OAM, shall reserve the right to issue a new permit.

B.28 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]

- (a) The Permittee shall pay annual fees to IDEM, OAM, within thirty (30) calendar days of receipt of a billing, or in a time period consistent with the fee schedule established in 326 IAC 2-7-19.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) If the Permittee does not receive a bill from IDEM, OAM, thirty (30) calendar days before the due date, the Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAM, Technical Support and Modeling Section), to determine the appropriate permit fee. The applicable fee is due April 1 of each year.

B.29 Enhanced New Source Review [326 IAC 2]

The requirements of the construction permit rules in 326 IAC 2 are satisfied by this permit for any previously unpermitted facilities and facilities to be constructed within eighteen (18) months after the date of issuance of this permit, as listed in Sections A.2 and A.3.

B.30 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 Federal Register 8313]

Notwithstanding the conditions of this permit specifying practices for applicable requirements, other credible evidence may also be used to establish compliance or noncompliance with applicable requirements.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Major Source

Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration), this source is a major source.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Visible Emissions Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), visible emissions shall meet the following, unless otherwise stated in this permit:

- (a) Visible emissions shall not exceed an average of forty percent (40%) opacity in twenty-four (24) consecutive readings, as determined in 326 IAC 5-1-4.
- (b) Visible emissions shall not exceed sixty percent (60%) opacity for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2][326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

All air pollution control equipment listed in this permit shall be operated at all times that the emission units vented to the control equipment are in operation, as described in Section D of this permit.

C.7 Asbestos Abatement Projects - Accreditation [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart

Prior to the commencement of any demolition or renovation activities, the Permittee shall use an Indiana accredited asbestos inspector to inspect thoroughly the affected facility or part of the facility where the demolition or renovation operation will occur for the presence of asbestos, including Category I and Category II nonfriable asbestos containing material. The requirement that the inspector be accredited is federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.8 Performance Testing [326 IAC 3-2.1]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-2.1 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing methods approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days before the intended test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.9 Compliance Schedule [326 IAC 2-7-6(3)]

The Permittee:

- (a) Will continue to comply with such requirements that become effective during the term of this permit;
- (b) Has submitted a statement that the Permittee will continue to comply with such requirements; and
- (c) Has certified that all facilities at this source are in compliance with all applicable requirements.

C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit. If due to circumstances beyond its control, this schedule cannot be met, the Permittee shall notify:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, no more than ninety (90) days after receipt of this permit, with full justification of the reasons for the inability to meet this date and a schedule which it expects to meet. If a denial of the request is not received before the monitoring is fully implemented, the schedule shall be deemed approved.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.11 Monitoring Methods [326 IAC 3]

Any monitoring or testing performed to meet the requirements of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

C.12 Throughput Specifications

Whenever a condition in this permit requires the measurement of throughput across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ($\pm 2\%$) of full scale reading.

C.13 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) asbestos removal or demolition start date;
 - (B) removal or demolition contractor; or
 - (3) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (e) Procedures for Asbestos Emission Control
The Permittee shall comply with the emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are mandatory for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.14 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within ninety (90) days after the date of issuance of this permit.
- (c) If the ERP is disapproved by IDEM, OAM, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP. If after this time, the Permittee does not submit an approvable ERP, then IDEM, OAM, shall supply such a plan.
- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.

- (f) Upon direct notification by IDEM, OAM, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.15 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present in more than the threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall:

- (a) Submit:
 - (1) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or
 - (2) As a part of the compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and
 - (3) A verification to IDEM, OAM, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.
- (b) Provide annual certification to IDEM, OAM, that the Risk Management Plan is being properly implemented.

C.16 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5(3)]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
 - (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of:
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and

- (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
 - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

C.17 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.

- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected facility.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.18 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

- (a) The Permittee shall submit a certified, annual emission statement that must be received by July 1 of each year and must comply with the minimum requirements specified in 326 IAC 2-6-4. The annual emission statement shall meet the following requirements:
 - (1) Indicate actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
 - (2) Indicate actual emissions of other regulated pollutants from the source, for purposes of Part 70 fee assessment.
- (b) The annual emission statement covers the twelve (12) consecutive month time period starting January 1 and ending December 31. The annual emission statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

C.19 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]

- (a) With the exception of performance tests conducted in accordance with Section C- Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.

- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.20 General Record Keeping Requirements [326 IAC 2-7-5(3)(B)]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location and available within one (1) hour upon verbal request of an IDEM, OAM, representative, for a minimum of three (3) years. They may be stored elsewhere for the remaining two (2) years providing they are made available within thirty (30) days after written request.
- (b) Records of required monitoring information shall include, where applicable:
 - (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this permit;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan -

Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.

- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.21 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) To affirm that the source has met all the requirements stated in this permit the source shall submit a Quarterly Compliance Report. Any deviation from the requirements and the date(s) of each deviation must be reported.

- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

- (d) Unless otherwise specified in this permit, any semi-annual report shall be submitted within thirty (30) days of the end of the reporting period.

- (e) All instances of deviations must be clearly identified in such reports. A reportable deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:

- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
- (2) An emergency as defined in 326 IAC 2-7-1(12); or
- (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
- (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred or failure to monitor or record the required compliance monitoring is a deviation.

- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.

- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

Stratospheric Ozone Protection

C.22 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1 FACILITY OPERATION CONDITIONS

- (a) Two (2) storage tanks, identified as Tanks 90 and 92, installed in 1953, capacity: 993,500 gallons of gasoline or distillates, each.
- (b) One (1) storage tank, identified as Tank 91, installed in 1953, vented to Tank 94, capacity: 414,300 of gasoline or distillates.
- (c) One (1) storage tank, identified as Tank 93, installed in 1953, capacity: 2,235,400 gallons of gasoline or distillates.
- (d) One (1) storage tank, identified as Tank 94, installed in 1953, capacity: 2,290,000 gallons of gasoline or distillates.
- (e) One (1) storage tank, identified as Tank 95, installed in 1956, capacity: 2,187,800 gallons of gasoline or distillates.
- (f) One (1) storage tank, identified as Tank 96, installed in 1958, capacity: 2,231,300 gallons of gasoline or distillates.
- (g) Two (2) storage tanks, identified as Tanks 97E and 97W, installed in 1979, capacity: 19,400 gallons of gasoline or distillates, each.
- (h) One (1) storage tank, identified as Tank 98, installed in 1988, capacity: 8,200 gallons of gasoline or distillates.
- (i) One (1) storage tank, identified as Sump Tank, installed in 1953, capacity: 1,000 gallons of gasoline mixture.
- (j) One (1) gasoline and distillate truck loading rack, identified as loading rack, installed in 1953, throughput capacity: 42,600 gallons of gasoline and/or distillates per hour.
- (k) Fugitives from pump seals, valves and flanges.

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Hazardous Air Pollutants

The hazardous air pollutant emissions from the entire source shall be limited as follows to make the requirements of 40CFR Part 63 Subpart R [National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)] not applicable.

The input of gasoline to the entire source is limited to 98,280,098 gallons per consecutive twelve (12) monthly rolling period. One (1) gallon of gasoline is equivalent to one (1) gallon of gasoline delivered to the loading rack. One (1) gallon of gasoline throughput to Tank 94 is equivalent to eight hundred thousandths (0.800) gallon of gasoline.

One (1) gallon of gasoline throughput to Tanks 91 and/or 92 is equivalent to eight hundred and thirty-three thousandths (0.833) gallons of gasoline. This limitation is equivalent to both a potential to emit of 24.0 tons of combined HAPs and a greatest single HAP of 6.88 tons per consecutive twelve (12) monthly rolling period.

D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for the gasoline loading rack.

Compliance Determination Requirements

D.1.3 Testing Requirements [326 IAC 2-7-6(1)]

Testing of these facilities are not specifically required by this permit. However, if testing is required, compliance with the HAPs limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing. If necessary, the emission factors combined with the calculation of HAPs used to determine the gasoline throughput limit would be verified. This does not preclude testing requirements on these facilities under 326 IAC 2-7-5 and 326 IAC 2-7-6.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.4 Flow Gauge Notations

- (a) Daily flow notations of the gasoline loading rack flow gauges shall be performed during normal daylight operations. A trained employee shall record whether the flow rates are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the range of flow rates for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal flow rate is observed.

D.1.5 Broken Flow Gauge Detection

In the event that flow gauge failure has been observed:

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced.

- (b) Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion.

**Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19][326 IAC 13-3-4]
[40CFR Part 60.110]**

D.1.6 Record Keeping Requirements

- (a) The Permittee shall maintain records at the facility of the materials used that contain any HAPs. The records shall be complete and sufficient to establish compliance with the HAP usage limits and/or HAP emission limits that may be established in this permit. The records shall contain a minimum of the following:

- (1) The HAP/VOC ratio of each fuel received;

- (2) The weight of HAPs emitted for each compliance period, considering capture and control efficiency, if applicable; and

- (3) Identification of the facility or facilities associated with the usage of each HAP.

- (b) Transfer documents shall be kept for all gasoline distributed to Clark or Floyd Counties between May 1 and September 15 of each year unless the gasoline is being dispensed into motor vehicles or purchased by a consumer at a retail or wholesale outlet. All compliant fuel shall be segregated from noncompliant fuel and labeled. Records shall be maintained for a minimum of two (2) years. These records shall accompany every shipment of gasoline after it has been dispensed by the refinery, and shall contain at minimum, the following:

- (1) The date of all transfers.

- (2) The volume of the gasoline that was transferred.

- (3) The volume and percentage of ethanol if ethanol blended, with a date and location of blending.

- (4) The location and time of transfer.

- (5) A statement certifying that the gasoline has an RVP of seven and eight-tenths (7.8) pounds per square inch of less per gallon or is ethanol blended or is certified as RFG.

- (c) The Permittee shall maintain records at the source sufficient to demonstrate compliance with 40CFR Part 60.110 (NSPS Subpart K) for Storage Tanks, 97E and 97W, only.

D.1.7 Reporting Requirements

A semi-annual summary of the information to document compliance with Condition D.1.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting form located at the end of this permit, or their equivalent, within thirty (30) days after the end of the six (6) month period being reported.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
CERTIFICATION**

Source Name: Countrymark Cooperative, Inc.
Source Address: US 24 West, Peru, Indiana 46959
Mailing Address: 1200 Refinery Road, Mt. Vernon, Indiana 47620
Part 70 Permit No.: T 103 - 7974 - 00011

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Emergency/Deviation Occurrence Reporting Form
- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR MANAGEMENT
 COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
 QUARTERLY COMPLIANCE REPORT**

Source Name: Countrymark Cooperative, Inc.
 Source Address: US 24 West, Peru, Indiana 46959
 Mailing Address: 1200 Refinery Road, Mt. Vernon, Indiana 47620
 Part 70 Permit No.: T 103 - 7974 - 00011

Months: _____ **to** _____ **Year:** _____

This report is an affirmation that the source has met all the requirements stated in this permit. This report shall be submitted quarterly. Any deviation from the requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify zero in the column marked "No Deviations".

LIST EACH COMPLIANCE REQUIREMENT EXISTING FOR THIS SOURCE:

Requirement (eg. Permit Condition D.1.3)	Number of Deviations	Date of each Deviations	No Deviations

Form Completed By: _____
 Title/Position: _____
 Date: _____
 Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION
P.O. Box 6015
100 North Senate Avenue
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**PART 70 OPERATING PERMIT
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: Countrymark Cooperative, Inc.
Source Address: US 24 West, Peru, Indiana 46959
Mailing Address: 1200 Refinery Road, Mt. Vernon, Indiana 47620
Part 70 Permit No.: T 103 - 7974 - 00011

This form consists of 2 pages

Page 1 of 2

Check either No. 1 or No.2	
9 1.	This is an emergency as defined in 326 IAC 2-7-1(12)
C	The Permittee must notify the Office of Air Management (OAM), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
C	The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16
9 2.	This is a deviation, reportable per 326 IAC 2-7-5(3)(c)
C	The Permittee must submit notice in writing within ten (10) calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency/Deviation:
Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____
Title / Position: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
 OFFICE OF AIR MANAGEMENT
 COMPLIANCE DATA SECTION**

Part 70 Quarterly Report Submitted Semiannually

Source Name: Countrymark Cooperative, Inc.
 Source Address: US 24 West, Peru, Indiana 46959
 Mailing Address: 1200 Refinery Road, Mt. Vernon Indiana 46620
 Part 70 Permit No.: T 103-7974-00011
 Facility: Gasoline Loading Rack and Total for Storage Tanks 91, 92 and 94
 Parameter: Throughput of gasoline, equivalent to overall source single HAP potential to emit limited to 6.88 tons per consecutive 12-monthly rolling period, and combined HAPs potential to emit limited to 24.0 tons per consecutive 12-monthly rolling period.
 Limit: 98,280,098 gallons per consecutive 12-monthly rolling period, where one (1) gallon of gasoline is equivalent to one (1) gallon of gasoline to the loading rack, one (1) gallon of gasoline throughput to Tank 94 is equivalent to eight hundred thousandths (0.800) gallon of gasoline and one (1) gallon of gasoline throughput to Tanks 91 and/or 92 is equivalent to eight hundred and thirty-three thousandths (0.833) gallons of gasoline.

YEAR: _____

Month	Equivalent Gallons This Month	Equivalent Gallons Previous 11 Months	Equivalent Gallons 12 Month Total
	Loading Rack & Tanks 91, 92 & 94	Loading Rack & Tanks 91, 92 & 94	Loading Rack & Tanks 91, 92 & 94

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.
 Deviation has been reported on: _____

Submitted by: _____
 Title / Position: _____
 Signature: _____
 Date: _____
 Phone: _____

Indiana Department of Environmental Management Office of Air Management

Technical Support Document (TSD) for a Part 70 Operating Permit and Enhanced New Source Review (ENSR)

Source Background and Description

Source Name: Countrymark Cooperative, Inc.
Source Location: US 24 West, Peru, Indiana 46959
County: Miami
SIC Code: 5171
Operation Permit No.: T 103 - 7974 - 00011
Permit Reviewer: Frank P. Castelli/MES

The Office of Air Management (OAM) has reviewed a Part 70 permit application from Countrymark Cooperative, Inc. relating to the operation of a bulk storage and wholesale petroleum products distribution source.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) Two (2) storage tanks, identified as Tanks 90 and 92, installed in 1953, capacity: 993,500 gallons of gasoline or distillates, each.
- (b) One (1) storage tank, identified as Tank 91, installed in 1953, vented to Tank 94, capacity: 414,300 of gasoline or distillates.
- (c) One (1) storage tank, identified as Tank 93, installed in 1953, capacity: 2,235,400 gallons of gasoline or distillates.
- (d) One (1) storage tank, identified as Tank 94, installed in 1953, capacity: 2,290,000 gallons of gasoline or distillates.
- (e) One (1) storage tank, identified as Tank 95, installed in 1956, capacity: 2,187,800 gallons of gasoline or distillates.

- (f) One (1) storage tank, identified as Tank 96, installed in 1958, capacity: 2,231,300 gallons of gasoline or distillates.
- (g) Two (2) storage tanks, identified as Tanks 97E and 97W, installed in 1979, capacity: 19,400 gallons of gasoline or distillates, each.
- (h) One (1) storage tank, identified as Tank 98, installed in 1988, capacity: 8,200 gallons of gasoline or distillates.
- (i) One (1) storage tank, identified as Sump Tank, installed in 1953, capacity: 1,000 gallons of distillates.
- (j) One (1) gasoline and distillate truck loading rack, identified as loading rack, installed in 1953, throughput capacity: 42,600 gallons of gasoline and/or distillates per hour (373,176,000 gallons per year).
- (k) Fugitives from pump seals, valves and flanges.

Unpermitted Emission Units and Pollution Control Equipment Requiring ENSR

- (l) One (1) storage tank, identified as Fuel Use Tank, capacity: 270 gallons of distillates.
- (m) One (1) storage tank, identified as Cetane Tank, capacity: 1,000 gallons of Cetane Additive.
- (n) One (1) storage tank, identified as 90+ Tank, , installed in 1995, capacity: 270 gallons of distillates.
- (o) One (1) storage tank, identified as Office Fuel Tank, capacity: 3,000 gallons of distillates.

New Emission Units and Pollution Control Equipment Requiring ENSR

There are no new facilities to be reviewed under the ENSR process.

Insignificant Activities

List all insignificant activities which are indicated in the application.

- (a) Fuel oil-fired combustion sources with heat input equal to or less than two million (2,000,000) British thermal units per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight.
- (b) Paved and unpaved roads and parking lots with public access.
- (c) On-site fire and emergency response training approved by the department.
- (d) Miscellaneous maintenance painting
- (e) Miscellaneous construction

Existing Approvals

The source has been operating under previous approvals including, but not limited to, the following: list permits, registrations, modifications, exemptions, etc.

- (a) OP 52-10-82-0080 issued on April 6, 1979,
- (b) OP 52-04-82-0082 issued on April 24, 1979, and
- (c) OP 52-12-90-0113 issued on April 13, 1987.

All conditions from previous approvals were incorporated into this Part 70 permit.

Enforcement Issue

- (a) IDEM is aware that equipment has been constructed and operated prior to receipt of the proper permit. The subject equipment is listed in this Technical Support Document under the condition entitled *Unpermitted Emission Units and Pollution Control Equipment Requiring ENSR*.
- (b) IDEM is reviewing this matter and will take appropriate action. This proposed permit is intended to satisfy the requirements of the construction permit rules.

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the Part 70 permit be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete Part 70 permit application for the purposes of this review was received on December 16, 1996. Additional information was received on March 30, 1998.

A notice of completeness letter was mailed to the source on February 19, 1997.

Emission Calculations

See pages 1 through 12 of 12 of Appendix A of this document for detailed emissions calculations.

Potential Emissions

Pursuant to 326 IAC 1-2-55, Potential Emissions are defined as "emissions of any one (1) pollutant which would be emitted from a facility, if that facility were operated without the use of pollution control equipment unless such control equipment is necessary for the facility to produce its normal product or is integral to the normal operation of the facility."

Pollutant	Potential Emissions (tons/year)
PM	0.000
PM ₁₀	0.000
SO ₂	0.000
VOC	3,044
CO	0.000
NO _x	0.000

Note: For the purpose of determining Title V applicability for particulates, PM₁₀, not PM, is the regulated pollutant in consideration.

HAP's	Potential Emissions (tons/year)
Benzene	greater than 10
Ethyl benzene	less than 10
Hexane	greater than 10
Toluene	greater than 10
Xylene	greater than 10
2,2,4 Trimethylpentane	greater than 10
Naphtalene	less than 10
TOTAL	greater than 25

- (a) The potential emissions (as defined in 326 IAC 1-2-55) of volatile organic compounds are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) The potential emissions (as defined in 326 IAC 1-2-55) of any single HAP is equal to or greater than ten (10) tons per year and the potential emissions (as defined in 326 IAC 1-2-55) of a combination HAPs is greater than or equal to twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.

(c) Fugitive Emissions

Since this type of operation is not one of the twenty-eight (28) listed source categories since the storage capacity of petroleum products is less than three-hundred thousand (300,000) barrels under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are not counted toward determination of PSD and Emission Offset applicability.

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the applicant supplied actual emissions data.

Pollutant	Actual Emissions (tons/year)
PM	0.005
PM ₁₀	1.13
SO ₂	0.355
VOC	338
CO	0.012
NO _x	0.005
Benzene	1.36
Ethyl benzene	0.652
Hexane	2.67
Toluene	3.94
Xylene	3.49
2,2,4 Trimethylpentane	1.12
Naphthalene	0.331

Limited Potential to Emit

The table below summarizes the total potential to emit, reflecting all limits, of the significant emission units. The entire source throughput of gasoline is limited to 98,280,098 gallons of gasoline per year.

One (1) gallon of gasoline is equivalent to one (1) gallon of gasoline delivered to the loading rack. One (1) gallon of gasoline throughput to Tank 94 is equivalent to eight hundred thousandths (0.800) gallon of gasoline. One (1) gallon of gasoline throughput to Tanks 91 and/or 92 is equivalent to eight hundred and thirty-three thousandths (0.833) gallons of gasoline. This limitation is equivalent to both a potential to emit of 24.0 tons of combined HAPs and a greatest single HAP of 6.88 tons per consecutive twelve (12) monthly rolling period.

Process/facility	Limited Potential to Emit (tons/year)						
	PM	PM ₁₀	SO ₂	VOC	CO	NO _x	HAPs
Loading rack & storage tanks	0.00	0.00	0.00	590	0.00	0.00	24.0
Insignificant activities	5.00	4.00	5.00	1.00	1.00	1.00	neg
Total Emissions	5.00	4.00	5.00	591	1.00	1.00	24.0

County Attainment Status

The source is located in Miami County.

Pollutant	Status
TSP	attainment
PM ₁₀	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
CO	attainment
Lead	attainment

Volatile organic compounds (VOC) and oxides of nitrogen (NO_x) are precursors for the formation of ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Miami County has been designated as attainment or unclassifiable for ozone.

Federal Rule Applicability

- (a) This source is not subject to the New Source Performance Standards (326 IAC 12) (40 CFR 60.500 through 60.506, Subpart XX, Standards of Performance for Bulk Gasoline Terminals) because the truck loading rack has been constructed, reconstructed or modified before the rule applicability date of December 17, 1980.
- (b) Storage Tanks 90 through 96 and Sump, are not subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Parts 60. 110, 110a - 115a or 110b - 117b, Subparts K, Ka, and Kb, because these significant emission units were all constructed between 1953 and 1958, prior to the earliest applicability date of June 11, 1973 for Subpart K, Ka or Kb.
- (c) Storage Tanks 97E and 97W constructed in 1979 with capacities of 19,400 gallons, each, are subject to Subpart K since they were constructed after June 11, 1973. and will be required to keep records of their dimensions.
- (d) Storage Tanks 98 and 90+ Additives, constructed in 1988 and 1995 are not subject to Subpart Kb since their capacities are less than 40 cubic meters (10,567 gallons). Fuel Use, Office Fuel and Cetane storage tanks with unknown construction dates are not subject to Subpart Kb since their capacities are less than 40 cubic meters (10,567 gallons).
- (e) This facility is not subject to Gasoline Distribution NESHAP 40 CFR Part 63 Subpart R, Gasoline Distribution. Countrymark Cooperative, Inc. has agreed to limit the input of gasoline to the entire source to 98,280,098 gallons per consecutive twelve (12) monthly rolling period. One (1) gallon of gasoline is equivalent to one (1) gallon of gasoline delivered to the loading rack. One (1) gallon of gasoline throughput to Tank 94 is equivalent to eight hundred thousandths (0.800) gallon of gasoline. One (1) gallon of gasoline throughput to Tanks 91 and/or 92 is equivalent to eight hundred and thirty-three thousandths (0.833) gallons of gasoline. This limits the emissions of HAPs to below the major source levels of 10 tons per year for any given individual HAP and 25 tons per year for a combination of all HAPs. See page 7 through 12 of 12 of Appendix A. Therefore, the requirements of this rule do not apply.

State Rule Applicability - Entire Source

326 IAC 2-6 (Emission Reporting)

This source is subject to 326 IAC 2-6 (Emission Reporting), because it has the potential to emit more than one-hundred (100) tons per year of volatile organic compounds (VOC) in Miami County. Pursuant to this rule, the owner/operator of the source must annually submit an emission statement for the source. The annual statement must be received by July 1 of each year and contain the minimum requirement as specified in 326 IAC 2-6-4. The submittal should cover the period defined in 326 IAC 2-6-2(8)(Emission Statement Operating Year).

326 IAC 5-1 (Visible Emissions Limitations)

Pursuant to 326 IAC 5-1-2 (Visible Emissions Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), visible emissions shall meet the following, unless otherwise stated in this permit:

- (a) Visible emissions shall not exceed an average of forty percent (40%) opacity in twenty-four (24) consecutive readings as determined by 326 IAC 5-1-4,
- (b) Visible emissions shall not exceed sixty percent (60%) opacity for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) in a six (6) hour period.

326 IAC 13-3 (Control of gasoline Reid Vapor Pressure)

Pursuant to this rule all gasoline distributed to Clark or Floyd Counties between May 1 and September 15 of each year, must meet the federal requirements of Reformulated Gas (RFG) that complies with seven and eight-tenths (7.8) pounds per square inch low Reid Vapor Pressure (RVP) gasoline, federal reformulated gasoline, or ethanol blended low RVP gasoline. Transfer documents are required as specified in 326 IAC 13-3-4 (Record keeping requirements)

State Rule Applicability - Individual Facilities

326 8-4-3 (Petroleum liquid storage facilities)

- (a) This source is not subject to the requirements of 326 8-4-3 because the Storage Tanks 90 through 96, Sump and 97 E and 97W were all constructed prior to the applicability date of January 1, 1980.
- (b) Storage Tanks 98 and 90+ Additives constructed in 1988 and 1995 with capacities of 8,200 and 270 gallons are also not subject to this rule since their capacities are less than 39,000 gallons.
- (c) Fuel Use, Office Fuel and Cetane Tanks with unknown construction dates having capacities of 270, 3,000 and 1,000 gallons, respectively, are also not subject to this rule since their capacities are all less than 39,000 gallons.

326 8-4-4 (Bulk gasoline terminals)

The loading rack at this source is not subject to the requirements of 326 8-4-4 since it was constructed in 1953, prior to the January 1, 1980 applicability date of this rule.

326 8-4-5 (Petroleum sources gasoline plants)

The loading rack at this source is not subject to the requirements of 326 8-4-4 since it was constructed in 1953, prior to the January 1, 1980 applicability date of this rule.

326 8-4-6 (Petroleum sources: gasoline dispensing facilities)

The loading rack at this source is not subject to the requirements of 326 8-4-6 since it was constructed in 1953, prior to the July 1, 1989 applicability date of this rule.

326 8-1-6 (General provisions relating to VOC rules: general reduction requirements for new facilities)

Although this source has a potential to emit more than 25 tons per year of VOC, it is not subject to the requirements of 326 8-1-6 since all facilities that have the potential to emit more than 25 tons per year were constructed prior to January 1, 1980. Therefore, the entire source is not subject to this rule.

326 IAC 8-6 (Organic solvent emission limitations)

Although this source has a potential to emit more than 100 tons per year of VOC, it is not subject to the requirements of 326 8-6 since all facilities that have the potential to emit more than 100 tons per year were constructed prior to October 7, 1974. Therefore, the entire source is not subject to this rule.

326 IAC 8 (Volatile Organic Compound Rules)

There are no other 326 IAC 8 rules that apply.

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in permit Section D are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in permit Section D. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

- (a) Maintain records of the throughput of gasoline to the loading rack and Storage Tanks 91, 92 and 94.
- (b) For all gasoline distributed to Clark or Floyd Counties between May 1 and September 15 of each year, transfer documents must be prepared.

These monitoring conditions are necessary because the gasoline throughput limit is necessary to avoid the applicability of NESHAP Subpart R and 326 IAC 2-7 (Part 70).

Air Toxic Emissions

Indiana presently requests applicants to provide information on emissions of the 187 hazardous air pollutants set out in the Clean Air Act Amendments of 1990. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Management (OAM) Part 70 Application Form GSD-08.

- (a) This source will emit levels of air toxics less than those which constitute a major source according to Section 112 of the 1990 Amendments to the Clean Air Act.
- (b) See attached air toxic calculations supplied by the applicant in pages 5 and 10 of 10 of Appendix A.

Conclusion

The operation of this bulk storage and wholesale petroleum products distribution source shall be subject to the conditions of the attached proposed Part 70 Permit No. T 103-7974-00011.

Indiana Department of Environmental Management Office of Air Management

Addendum to the Technical Support Document for a Part 70 Operating Permit

Source Name: Countrymark Cooperative, Inc.
 Source Location: US 24 West, Peru, Indiana 46959
 County: Miami
 SIC Code: 5171
 Operation Permit No.: T 103 - 7974 - 00011
 Permit Reviewer: Frank P. Castelli/MES

On April 25, 1998, the Office of Air Management (OAM) had a notice published in the Peru Daily Tribune, Peru, Indiana, stating that Countrymark Cooperative, Inc. had applied for a Part 70 Operating Permit to operate a bulk storage and wholesale petroleum products distribution source. The notice also stated that OAM proposed to issue a Part 70 Operating Permit for this operation and provided information on how the public could review the proposed Part 70 Operating Permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this Part 70 Operating Permit should be issued as proposed.

Upon further review, the OAM has decided to make the following changes to the Part 70 Operating Permit:

1. In Conditions A.2(j), D.1(j), the annual capacity has been removed and only the full hourly capacity has been retained. Therefore, the Conditions have been revised as follows:

- (j) One (1) gasoline and distillate truck loading rack, identified as loading rack, installed in 1953, throughput capacity: 42,600 gallons of gasoline and/or distillates per hour (~~373,176,000 gallons per year~~).

2. Condition B.14 has been revised from:

B.14 Permit Shield [326 IAC 2-7-15]

(a) Compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided either of the following:

- (1) The applicable requirements are included and specifically identified in this permit;
- (2) IDEM, OAM, in acting on the Part 70 permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the Part 70 permit includes the determination or a concise summary thereof.

(b) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application.

- (c) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement, IDEM, OAM, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAM, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAM, as issued the modification. [326 IAC 2-7-12(b)(8)]

to:

B.14 Permit Shield [326 IAC 2-7-15]

- (a) This condition provides a permit shield as addressed in 326 IAC 2-7-15.
- (b) Compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that:
 - (1) The applicable requirements are included and specifically identified in this permit, or;
 - (2) The permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable.

- (c) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAM, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (d) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application.
- (e) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408 (a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (f) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (g) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAM, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (h) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAM, has issued the modification. [326 IAC 2-7-12(b)(8)]

3. Condition B.30 has been added and is as follows:

B.30 Credible Evidence [326 IAC 2-7-5(3)] [326 IAC 2-7-6] [62 Federal Register 8313]
Notwithstanding the conditions of this permit specifying practices for applicable requirements, other credible evidence may also be used to establish compliance or noncompliance with applicable requirements.

4. Condition A.5 has been deleted.

~~A.5 — Prior Permit Conditions Superseded [326 IAC 2]
The terms and conditions of this permit incorporate all the current applicable~~

~~requirements for all emission units located at this source, and supersede all terms and conditions in all registrations and permits, including construction permits, issued prior to the date of issuance of this permit. All terms and conditions in such registrations and permits are no longer in effect.~~

On May 28, 1998, Mickey Smith of Countrymark Cooperative, Inc. submitted comments on the proposed Part 70 Operating Permit. The comments are as follows:

Comment 1:

I am requesting consideration of "Insignificant Activity" status for the following tanks: Office Fuel, 90+ Additive, Fuel Use. We feel that these tanks do not merit independent records in the annual report and that the small amount of emissions are being covered by including their volumes with the tanks they draw from and the loading rack volumes.

Comment 2:

We have discontinued our MMT additive which was stored in Tank 98. Tank 98 is now being used for Cetane Additive and the 1,000 gallon portable tank previously identified as "Cetane Additive" has been removed from service.

Responses 1 and 2:

These tanks qualify as insignificant activities and have been removed from Sections A.2 and D.1. Also, the Cetane Additive tank has been removed from the equipment list. The equipment list in these sections has been revised as follows:

- (a) Two (2) storage tanks, identified as Tanks 90 and 92, installed in 1953, capacity: 993,500 gallons of gasoline or distillates, each.
- (b) One (1) storage tank, identified as Tank 91, installed in 1953, vented to Tank 94, capacity: 414,300 of gasoline or distillates.
- (c) One (1) storage tank, identified as Tank 93, installed in 1953, capacity: 2,235,400 gallons of gasoline or distillates.
- (d) One (1) storage tank, identified as Tank 94, installed in 1953, capacity: 2,290,000 gallons of gasoline or distillates.
- (e) One (1) storage tank, identified as Tank 95, installed in 1956, capacity: 2,187,800 gallons of gasoline or distillates.
- (f) One (1) storage tank, identified as Tank 96, installed in 1958, capacity: 2,231,300 gallons of gasoline or distillates.
- (g) Two (2) storage tanks, identified as Tanks 97E and 97W, installed in 1979, capacity: 19,400 gallons of gasoline or distillates, each.

- (h) One (1) storage tank, identified as Tank 98, installed in 1988, capacity: 8,200 gallons of gasoline or distillates.
- (i) One (1) storage tank, identified as Sump Tank, installed in 1953, capacity: 1,000 gallons of ~~distillates~~ **gasoline mixture**.
- (j) One (1) gasoline and distillate truck loading rack, identified as loading rack, installed in 1953, throughput capacity: 42,600 gallons of gasoline and/or distillates per hour.
- (k) Fugitives from pump seals, valves and flanges.
- ~~(l) One (1) storage tank, identified as Fuel Use Tank, capacity: 270 gallons of distillates.~~
- ~~(m) One (1) storage tank, identified as Cetane Tank, capacity: 1,000 gallons of Cetane Additive.~~
- ~~(n) One (1) storage tank, identified as 90+ Tank, installed in 1995, capacity: 270 gallons of distillates.~~
- ~~(o) One (1) storage tank, identified as Office Fuel Tank, capacity: 3,000 gallons of distillates.~~

And as a result of this change, these three (3) tanks should have originally been classified as the following Insignificant Activities:

- (a) A petroleum fuel, other than gasoline, dispensing facility, having a storage capacity of less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.
- (b) The following VOC and HAP storage containers:
 - Storage tanks with capacity less than or equal to 1,000 gallons and annual throughputs less than 12,000 gallons.

Company Name: Countrymark Cooperative, Inc.
 Address City IN Zip: US 24 West, Peru, IN 46959
 Part 70: T 103-7974
 Pit ID: 103-00011
 Reviewer: Frank P. Castelli
 Date: December 16, 1996

Loading Rack

		Throughput kgal/hr	
Gasoline		42.600	VOC Control 0.0%
SCC 4-06-001-36			
AIRS		VOC	
Emission Factors lbs/kgal		12.0	
Percentage of Emissions		100.00%	
Potential Emissions lbs/hr		511.200	
Potential Emissions lbs/day		12268.80	
Potential Emissions tons/yr		2239.06	

Worst Case All Gasoline

Loading Rack

		Throughput kgal/hr	
Kerosene		42.600	VOC Control 0.0%
SCC 4-06-001-39			
AIRS		VOC	
Emission Factors lbs/kgal		0.04	
Percentage of Emissions		100.00%	
Potential Emissions lbs/hr		1.704	
Potential Emissions lbs/day		40.90	
Potential Emissions tons/yr		7.46	

Loading Rack

		Throughput kgal/hr	
Distillate Oil		42.600	VOC Control 0.0%
SCC 4-06-001-40			
AIRS		VOC	
Emission Factors lbs/kgal		0.03	
Percentage of Emissions		100.00%	
Potential Emissions lbs/hr		1.278	
Potential Emissions lbs/day		30.67	
Potential Emissions tons/yr		5.60	

Storage Tanks 90

		Standing Throughput kgal/hr	Working Throughput kgal/hr	
		993.500	18.300	VOC Control 0.0%
AP-42				
AIRS		VOC	VOC	
Emission Factors lbs/kgal		0.00005	0.03000	
Percentage of Emissions		100.00%	100.00%	
Potential Emissions lbs/hr		0.050	0.549	
Potential Emissions lbs/day		1.19	13.18	
Potential Emissions tons/yr		0.218	2.405	

Storage Tank 92	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	993.500	18.300

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00035	10.00000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.348	183.000
Potential Emissions lbs/day	8.35	4392.00
Potential Emissions tons/yr	1.523	801.540

Storage Tank 91	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	414.300	18.300

Standing VOC Control Vented to Tank 94
Working VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00350	10.00000
Percentage of Emissions	0.00%	96.00%
Potential Emissions lbs/hr	0.000	175.680
Potential Emissions lbs/day	0.00	4216.32
Potential Emissions tons/yr	0.000	769.478

Storage Tank 93	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	2235.400	18.300

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.112	0.549
Potential Emissions lbs/day	2.68	13.18
Potential Emissions tons/yr	0.490	2.405

Storage Tank 94	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	0.000	18.300

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00350	9.60000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.000	175.680
Potential Emissions lbs/day	0.00	4216.32
Potential Emissions tons/yr	0.000	769.478

Storage Tank 95	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	2187.800	18.300		

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.109	0.549
Potential Emissions lbs/day	2.63	13.18
Potential Emissions tons/yr	0.479	2.405

Storage Tank 96	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	2231.300	18.300		

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.11157	0.549
Potential Emissions lbs/day	2.6776	13.18
Potential Emissions tons/yr	0.489	2.405

Storage Tank 97E	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	19.400	0.146		

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00033	0.66000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00640	0.096
Potential Emissions lbs/day	0.1536	2.31
Potential Emissions tons/yr	0.0280	0.422

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Storage Tank 97W	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	19.400	0.146		

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00033	0.66000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00640	0.096
Potential Emissions lbs/day	0.1536	2.31
Potential Emissions tons/yr	0.0280	0.422

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Storage Tank 98	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	8.200	1.1300		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00350	10.0		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.02870	11.300		
Potential Emissions lbs/day	0.6888	271.20		
Potential Emissions tons/yr	0.1257	49.494		

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Fuel Use Tank	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	0.270	0.300		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00350	10.0		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.00095	3.000		
Potential Emissions lbs/day	0.0227	72.00		
Potential Emissions tons/yr	0.0041	13.140		

Note: Maximum throughput of this company use tank is based on the gravity rate

Cetane Tank	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	1.000	0.041		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00005	0.03		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.00005	0.001		
Potential Emissions lbs/day	0.0012	0.03		
Potential Emissions tons/yr	0.0002	0.005		

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

90+ Tank	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	0.270	0.0011		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00350	10.0		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.00095	0.011		
Potential Emissions lbs/day	0.0227	0.26		
Potential Emissions tons/yr	0.0041	0.048		

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Office Fuel Tank	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	3.000	0.007

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00015	0.000
Potential Emissions lbs/day	0.0036	0.01
Potential Emissions tons/yr	0.0007	0.001

Note: Maximum throughput of this tank is based on the maximum burner rate

Sump Tank	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	1.000	0.002

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00350	10.0
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00350	0.020
Potential Emissions lbs/day	0.0840	0.48
Potential Emissions tons/yr	0.0153	0.088

Note: Maximum throughput of this drain tank is based on the existing percentage of maximum terminal throughput

Worst Case VOC = Worst Case Loading Rack plus all standing losses from tanks plus worst case working loss since only one (1) storage tank can be filled at a time.

	VOC
Potential Emissions tons/yr	3044.0

HAPs Emission Calculations (tons per year)

Fraction of VOC Emissions		Ethyl		Hexane	Toluene	Xylenes	2,2,4, Tri-	Naphthalene	Total HAPs
		Benzene	Benzene				methylpentane		
		0.00403	0.00194	0.0079	0.01167	0.01127	0.00333	0.00056	
Process	Loading Rack	9.02	4.34	17.69	26.13	25.23	7.46	1.25	91.13
Working Only	Tank 90	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 92	3.230	1.555	6.332	9.354	9.033	2.669	0.449	32.623
	Tank 91	3.101	1.493	6.079	8.980	8.672	2.562	0.431	31.318
	Tank 93	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 94	3.101	1.493	6.079	8.980	8.672	2.562	0.431	31.318
	Tank 95	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 96	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 97E	0.002	0.001	0.003	0.005	0.005	0.001	0.000	0.017
	Tank 97W	0.002	0.001	0.003	0.005	0.005	0.001	0.000	0.017
	Tank 98	0.199	0.096	0.391	0.578	0.558	0.165	0.028	2.014
	Fuel Use Tank	0.053	0.025	0.104	0.153	0.148	0.044	0.007	0.535
	Cetane Tank	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	90+ Tank	0.000	0.000	0.000	0.001	0.001	0.000	0.000	0.002
	Office Fuel Tank	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Sump	0.000	0.000	0.001	0.001	0.001	0.000	0.000	0.004	
	Worst Case	3.23	1.55	6.33	9.35	9.03	2.67	0.45	32.62
Standing Only	Tank 90	0.00088	0.00042	0.00172	0.00254	0.00245	0.00072	0.00012	0.009
	Tank 92	0.00614	0.00295	0.01203	0.01777	0.01716	0.00507	0.00085	0.062
	Tank 91	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.000
	Tank 93	0.00197	0.00095	0.00387	0.00571	0.00552	0.00163	0.00027	0.020
	Tank 94	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.000
	Tank 95	0.00193	0.00093	0.00379	0.00559	0.00540	0.00160	0.00027	0.020
	Tank 96	0.00197	0.00095	0.00386	0.00570	0.00551	0.00163	0.00027	0.020
	Tank 97E	0.00011	0.00005	0.00022	0.00033	0.00032	0.00009	0.00002	0.001
	Tank 97W	0.00011	0.00005	0.00022	0.00033	0.00032	0.00009	0.00002	0.001
	Tank 98	0.00051	0.00024	0.00099	0.00147	0.00142	0.00042	0.00007	0.005
	Fuel Use Tank	0.00002	0.00001	0.00003	0.00005	0.00005	0.00001	0.00000	0.000
	Cetane Tank	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.000
	90+ Tank	0.00002	0.00001	0.00003	0.00005	0.00005	0.00001	0.00000	0.000
	Office Fuel Tank	0.00000	0.00000	0.00001	0.00001	0.00001	0.00000	0.00000	0.000
Sump	0.00006	0.00003	0.00012	0.00018	0.00017	0.00005	0.00001	0.001	
	Total Standing Loss	0.014	0.007	0.027	0.040	0.038	0.011	0.002	0.139
	Worst Case HAPs	12.27	5.91	24.05	35.52	34.31	10.14	1.70	123.9

Throughput Limit to be Less Than Major Source HAPs Levels of 10 TPY for a single HAP and 25 TPY for a Combination of All HAPs

Loading Rack

Gasoline	VOC
SCC 4-06-001-36	
AIRS	VOC
Emission Factors lbs/kgal	12.0
Percentage of Emissions	100.00%
Potential Emissions lbs/hr	134.630
Potential Emissions lbs/day	3231.13
Potential Emissions tons/yr	589.68

Throughput
kgal/hr
11.219

VOC Control 0.0%

Limit to be stated as 98,280,098 gallons of gasoline to the entire source.

Worst Case All Gasoline

Loading Rack

Kerosene	VOC
SCC 4-06-001-39	
AIRS	VOC
Emission Factors lbs/kgal	0.04
Percentage of Emissions	100.00%
Potential Emissions lbs/hr	0.449
Potential Emissions lbs/day	10.77
Potential Emissions tons/yr	1.97

Throughput
kgal/hr
11.219

VOC Control 0.0%

Loading Rack

Distillate Oil	VOC
SCC 4-06-001-40	
AIRS	VOC
Emission Factors lbs/kgal	0.03
Percentage of Emissions	100.00%
Potential Emissions lbs/hr	0.337
Potential Emissions lbs/day	8.08
Potential Emissions tons/yr	1.47

Throughput
kgal/hr
11.219

VOC Control 0.0%

Storage Tanks 90

	Standing Throughput kgal/hr	Working Throughput kgal/hr
	993.500	18.300
AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.050	0.549
Potential Emissions lbs/day	1.19	13.18
Potential Emissions tons/yr	0.218	2.405

VOC Control 0.0%

Storage Tanks 92	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	993.500	11.219		

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00035	10.00000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.348	112.192
Potential Emissions lbs/day	8.35	2692.61
Potential Emissions tons/yr	1.523	491.400

Limit to be stated as 98,280,098 gallons of gasoline for entire source, where 1 gal of gasoline = 0.833 gal

Storage Tank 91	Standing Throughput	Working Throughput	Standing VOC Control	100.0%	Vented to Tank 64
	kgal/hr	kgal/hr			
	414.300	11.219	Working VOC Control	4.0%	

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00350	10.00000
Percentage of Emissions	0.00%	96.00%
Potential Emissions lbs/hr	0.000	107.702
Potential Emissions lbs/day	0.00	2584.86
Potential Emissions tons/yr	0.000	471.737

Limit to be stated as 98,280,098 gallons of gasoline for entire source, where 1 gal of gasoline = 0.833 gal

Storage Tank 93	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	2235.400	18.300		

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.112	0.549
Potential Emissions lbs/day	2.68	13.18
Potential Emissions tons/yr	0.490	2.405

Storage Tank 94	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	0.000	11.219		

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00350	9.60000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.000	107.702
Potential Emissions lbs/day	0.00	2584.86
Potential Emissions tons/yr	0.000	471.737

Limit to be stated as 98,280,098 gallons of gasoline for entire source, where 1 gal of gasoline = 0.800 gal

Storage Tank 95	Standing Throughput	Working Throughput
	kgal/hr	kgal/hr
	2187.800	18.300

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.109	0.549
Potential Emissions lbs/day	2.63	13.18
Potential Emissions tons/yr	0.479	2.405

Storage Tank 96	Standing Throughput	Working Throughput
	kgal/hr	kgal/hr
	2231.300	18.300

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.11157	0.549
Potential Emissions lbs/day	2.6776	13.18
Potential Emissions tons/yr	0.489	2.405

Storage Tank 97E	Standing Throughput	Working Throughput
	kgal/hr	kgal/hr
	19.400	0.146

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00033	0.66000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00640	0.096
Potential Emissions lbs/day	0.1536	2.31
Potential Emissions tons/yr	0.0280	0.422

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Storage Tank 97W	Standing Throughput	Working Throughput
	kgal/hr	kgal/hr
	19.400	0.146

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00033	0.66000
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00640	0.096
Potential Emissions lbs/day	0.1536	2.31
Potential Emissions tons/yr	0.0280	0.422

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Storage Tank 98	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	8.200	1.1300		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00350	10.0		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.02870	11.300		
Potential Emissions lbs/day	0.6888	271.20		
Potential Emissions tons/yr	0.1257	49.494		

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Fuel Use Tank	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	0.270	0.300		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00350	10.0		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.00095	3.000		
Potential Emissions lbs/day	0.0227	72.00		
Potential Emissions tons/yr	0.0041	13.140		

Note: Maximum throughput of this company use tank is based on the gravity rate

Cetane Tank	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	1.000	0.0410		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00005	0.03		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.00005	0.001		
Potential Emissions lbs/day	0.0012	0.03		
Potential Emissions tons/yr	0.0002	0.005		

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

90+ Tank	Standing Throughput	Working Throughput	VOC Control	0.0%
	kgal/hr	kgal/hr		
	0.270	0.0011		
AP-42	VOC	VOC		
Emission Factors lbs/kgal	0.00350	10.0		
Percentage of Emissions	100.00%	100.00%		
Potential Emissions lbs/hr	0.00095	0.011		
Potential Emissions lbs/day	0.0227	0.26		
Potential Emissions tons/yr	0.0041	0.048		

Note: Maximum throughput of this additive tank is based on the existing percentage of maximum terminal throughput

Office Fuel Tank	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	3.000	0.0070

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00005	0.03
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00015	0.000
Potential Emissions lbs/day	0.0036	0.01
Potential Emissions tons/yr	0.0007	0.001

Note: Maximum throughput of this tank is based on burner rate

Sump Tank	Standing	Working
	Throughput kgal/hr	Throughput kgal/hr
	1.000	0.0020

VOC Control

AP-42	VOC	VOC
Emission Factors lbs/kgal	0.00350	10.0
Percentage of Emissions	100.00%	100.00%
Potential Emissions lbs/hr	0.00350	0.020
Potential Emissions lbs/day	0.0840	0.48
Potential Emissions tons/yr	0.0153	0.088

Note: Maximum throughput of this drain tank is based on the existing percentage of maximum throughput

Worst Case VOC = Worst Case Loading Rack plus all standing losses from tanks plus worst case working loss since only one (1) storage tank can be filled at a time.

	VOC
Potential Emissions tons/yr	1084.5

HAPs Emission Calculations (tons per year)

Fraction of VOC Emissions		Ethyl		Hexane	Toluene	Xylenes	2,2,4, Tri-		Total HAPs
		Benzene	Benzene				methylpentane	Naphthalene	
		0.00403	0.00194	0.0079	0.01167	0.01127	0.00333	0.00056	
Process	Loading Rack	2.38	1.14	4.66	6.88	6.65	1.96	0.33	24.00
Working Only	Tank 90	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 92	1.980	0.953	3.882	5.735	5.538	1.636	0.275	20.000
	Tank 91	1.901	0.915	3.727	5.505	5.316	1.571	0.264	19.200
	Tank 93	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 94	1.901	0.915	3.727	5.505	5.316	1.571	0.264	19.200
	Tank 95	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 96	0.010	0.005	0.019	0.028	0.027	0.008	0.001	0.098
	Tank 97E	0.002	0.001	0.003	0.005	0.005	0.001	0.000	0.017
	Tank 97W	0.002	0.001	0.003	0.005	0.005	0.001	0.000	0.017
	Tank 98	0.199	0.096	0.391	0.578	0.558	0.165	0.028	2.014
	Fuel Use Tank	0.053	0.025	0.104	0.153	0.148	0.044	0.007	0.535
	Cetane Tank	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	90+ Tank	0.000	0.000	0.000	0.001	0.001	0.000	0.000	0.002
	Office Fuel Tank	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	Sump	0.000	0.000	0.001	0.001	0.001	0.000	0.000	0.004
	Worst Case	1.98	0.95	3.88	5.73	5.54	1.64	0.28	20.00
Standing Only	Tank 90	0.00088	0.00042	0.00172	0.00254	0.00245	0.00072	0.00012	0.009
	Tank 92	0.00614	0.00295	0.01203	0.01777	0.01716	0.00507	0.00085	0.062
	Tank 91	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.000
	Tank 93	0.00197	0.00095	0.00387	0.00571	0.00552	0.00163	0.00027	0.020
	Tank 94	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.000
	Tank 95	0.00193	0.00093	0.00379	0.00559	0.00540	0.00160	0.00027	0.020
	Tank 96	0.00197	0.00095	0.00386	0.00570	0.00551	0.00163	0.00027	0.020
	Tank 97E	0.00011	0.00005	0.00022	0.00033	0.00032	0.00009	0.00002	0.001
	Tank 97W	0.00011	0.00005	0.00022	0.00033	0.00032	0.00009	0.00002	0.001
	Tank 98	0.00051	0.00024	0.00099	0.00147	0.00142	0.00042	0.00007	0.005
	Fuel Use Tank	0.00002	0.00001	0.00003	0.00005	0.00005	0.00001	0.00000	0.000
	Cetane Tank	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.00000	0.000
	90+ Tank	0.00002	0.00001	0.00003	0.00005	0.00005	0.00001	0.00000	0.000
	Office Fuel Tank	0.00000	0.00000	0.00001	0.00001	0.00001	0.00000	0.00000	0.000
	Sump	0.00006	0.00003	0.00012	0.00018	0.00017	0.00005	0.00001	0.001
	Total Standing Loss	0.014	0.007	0.027	0.040	0.038	0.011	0.002	0.139
	Worst Case HAPs	2.38	1.14	4.66	6.88	6.65	1.96	0.33	24.00