

**FEDERALLY ENFORCEABLE STATE  
OPERATING PERMIT (FESOP)**

**OFFICE OF AIR MANAGEMENT**

**SPX Corporation - Contech Division  
520 South Byrkit Ave  
Mishawaka, Indiana 46544**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 and 326 IAC 2-1-3.2, as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F141-8988-00044	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

## SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-8-3(b)]

---

The Permittee owns and operates a stationary magnesium die casting plant for the production of automotive steering components.

Responsible Official: Ronald E. Veverka  
Source Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
Mailing Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
SIC Code: 3364  
County Location: St. Joseph  
County Status: Attainment for all criteria pollutants  
Source Status: Federally Enforceable State Operating Permit (FESOP)  
Minor Source, under PSD Rules;  
Minor Source, Section 112 of the Clean Air Act

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

---

This stationary source consists of the following emission units and pollution control devices:

- (a) Eight (8) electric powered magnesium die casting machines, identified as DCM-1 through DCM-8, with a total maximum capacity of melting 3,950 pounds of magnesium ingot per hour, and exhausting uncontrolled through twelve (12) exhaust fans (S/V ID S01); and
- (b) Four (4) aluminum shotblasting units, identified as TB-01, HB-01, HB-02, and HB-03, each with a maximum capacity of finishing 3950 pounds of magnesium castings per hour, all controlled by a high efficiency wet scrubber (CD-01), and all exhausted through one (1) stack (S/V ID S02).

### A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

---

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6: (Two (2) cold cleaner degreasers, identified as WS#1 and WS#2.); and
- (b) One (1) stick welding machine, and one (1) Metal Inert Gas (MIG) welding unit used for maintenance purposes with PM-10 emissions less than twenty-five (25) pounds per day

**A.4 FESOP Applicability [326 IAC 2-8-2]**

---

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM) for a Federally Enforceable State Operating Permit (FESOP).

**A.5 Prior Permit Conditions**

---

- (a) This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits.
- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAM, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued.

**SECTION B GENERAL CONDITIONS**

**B.1 Permit No Defense [326 IAC 2-1-10] [IC 13]**

---

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

**B.2 Definitions [326 IAC 2-8-1]**

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2, and 326 IAC 2-7 shall prevail.

**B.3 Permit Term [326 IAC 2-8-4(2)]**

---

This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.

**B.4 Enforceability [326 IAC 2-8-6]**

---

- (a) All terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM.
- (b) Unless otherwise stated, terms and conditions of this permit, including any provisions to limit the source's potential to emit, are enforceable by the United States Environmental Protection Agency (U.S. EPA) and citizens under the Clean Air Act.

**B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]**

---

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

**B.6 Severability [326 IAC 2-8-4(4)]**

---

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

**B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]**

---

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:
- Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015
- (b) The Permittee shall furnish to IDEM, OAM, within a reasonable time, any information that IDEM, OAM, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit.
- (c) Upon request, the Permittee shall also furnish to IDEM, OAM, copies of records required to be kept by this permit. If the Permittee wishes to assert a claim of confidentiality over any of the furnished records, the Permittee must furnish such records to IDEM, OAM, along with a claim of confidentiality under 326 IAC 17. If requested by IDEM, OAM, or the U.S. EPA, to furnish copies of requested records directly to U. S. EPA, and if the Permittee is making a claim of confidentiality regarding the furnished records, the Permittee must furnish such confidential records directly to the U.S. EPA along with a claim of confidentiality under 40 CFR 2, Subpart B.

B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAM may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit constitutes a violation of the Clean Air Act and is grounds for:
- (1) Enforcement action;
  - (2) Permit termination, revocation and reissuance, or modification; and
  - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

B.11 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Any application form, report, or compliance certification submitted under this permit shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this permit, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.

- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.12 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
- (1) The identification of each term or condition of this permit that is the basis of the certification;
  - (2) The compliance status;
  - (3) Whether compliance was based on continuous or intermittent data;
  - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
  - (5) Such other facts as specified in Sections D of this permit, IDEM, OAM, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.13 Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each facility:
- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM, .

B.14 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
  - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM , within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Management, Compliance Section) or,  
Telephone No.: 317-233-5674 (ask for Compliance Section)  
Facsimile No.: 317-233-5967

Failure to notify IDEM, OAM , by telephone or facsimile within four (4) daytime business hours after the beginning of the emergency, or after the emergency is discovered or reasonably should have been discovered, shall constitute a violation of 326 IAC 2-8 and any other applicable rules. [326 IAC 2-8-12(f)]

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
  - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
  - (e) IDEM, OAM , may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
  - (f) Failure to notify IDEM, OAM , by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
  - (g) Operations may continue during an emergency only if the following conditions are met:
    - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
    - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
      - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and

- (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within ten (10) calendar days from the date of the discovery of the deviation.

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
  - (2) An emergency as defined in 326 IAC 2-7-1(12); or
  - (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
  - (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.

- (c) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)]

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAM determines any of the following:
  - (1) That this permit contains a material mistake.
  - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
  - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAM , to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAM , at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAM , may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

B.17 Permit Renewal [326 IAC 2-8-3(h)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAM and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]
  - (1) A timely renewal application is one that is:
    - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
    - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due. [326 IAC 2-5-3]
  - (2) If IDEM, OAM upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.

- (c) **Right to Operate After Application for Renewal [326 IAC 2-8-9]**  
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAM takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAM, any additional information identified as needed to process the application.

**B.18 Permit Amendment or Modification [326 IAC 2-8-10] [326 IAC 2-8-11]**

---

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11 whenever the Permittee seeks to amend or modify this permit.

- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule.

- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request.  
[326 IAC 2-8-10(b)(3)]

**B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-8-11(b)(2)]**

---

Notwithstanding 326 IAC 2-8-11(b)(1)(D)(i) and 326 IAC 2-8-11(c)(1), minor permit modification procedures may be used for modifications of this permit involving the use of economic incentives, marketable permits, emissions trading, and other similar approaches to the extent that such minor permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated by U.S. EPA.

**B.20 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-8-15(b)]**

---

The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-8-15(a) and the following additional condition:

For each such change, the required written notification shall include a brief description of the change within the source, the date on which the change will occur, any change in emissions, and any permit term or condition that is no longer applicable as a result of the change.

**B.21 Operational Flexibility [326 IAC 2-8-15]**

---

- (a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-1 has been obtained;

(3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);

(4) The Permittee notifies the:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V  
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)  
77 West Jackson Boulevard  
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

(5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAM , in the notices specified in 326 IAC 2-8-15(b), (c)(1), and (d).

(b) For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) Emission Trades [326 IAC 2-8-15(c)]  
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).

- (d) Alternative Operating Scenarios [326 IAC 2-8-15(d)]  
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAM or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.22 Construction Permit Requirement [326 IAC 2]

Except as allowed by Indiana P.L. 130-1996 Section 12, as amended by P.L. 244-1997, modification, construction, or reconstruction shall be approved as required by and in accordance with 326 IAC 2.

B.23 Inspection and Entry [326 IAC 2-8-5(a)(2)]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, the Permittee shall allow IDEM, OAM, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.  
[326 IAC 2-8-5(a)(4)]
  - (1) The Permittee may assert a claim that, in the opinion of the Permittee, information removed or about to be removed from the source by IDEM, OAM, or an authorized representative, contains information that is confidential under IC 5-14-3-4(a). The claim shall be made in writing before or at the time the information is removed from the source. In the event that a claim of confidentiality is so asserted, neither IDEM, OAM, nor an authorized representative, may disclose the information unless and until IDEM, OAM, makes a determination under 326 IAC 17-1-7 through 326 IAC 17-1-9 that the information is not entitled to confidential treatment and that determination becomes final. [IC 5-14-3-4; IC 13-14-11-3; 326 IAC 17-1-7 through 326 IAC 17-1-9]

- (2) The Permittee, and IDEM, OAM, acknowledge that the federal law applies to claims of confidentiality made by the Permittee with regard to information removed or about to be removed from the source by U.S. EPA. [40 CFR Part 2, Subpart B]

**B.24 Transfer of Ownership or Operation [326 IAC 2-1-6][326 IAC 2-8-10]**

Pursuant to 326 IAC 2-1-6 and 2-8-10:

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAM, Permits Branch, within thirty (30) days of the change. Notification shall include a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current Permittee and the new owner.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an administrative amendment pursuant to 326 IAC 2-8-10. The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) IDEM, OAM shall reserve the right to issue a new permit.

**B.25 Annual Fee Payment [326 IAC 2-8-4(6)][326 IAC 2-8-16]**

- (a) The Permittee shall pay annual fees to IDEM, OAM, within thirty (30) calendar days of receipt of a billing. If the Permittee does not receive a bill from IDEM, OAM the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAM, Technical Support and Modeling Section), to determine the appropriate permit fee.

**SECTION C SOURCE OPERATION CONDITIONS**

Entire Source

**Emissions Limitations and Standards [326 IAC 2-8-4(1)]**

**C.1 Overall Source Limit [326 IAC 2-8]**

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

- (a) Pursuant to 326 IAC 2-8:
  - (1) The potential to emit any regulated pollutant from the entire source shall be limited to less than one-hundred (100) tons per three hundred sixty-five (365) consecutive day period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable;
  - (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per three hundred sixty-five (365) consecutive day period; and

- (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per three hundred sixty-five (365) consecutive day period.
- (b) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.
- (c) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Visible Emissions Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), visible emissions shall meet the following, unless otherwise stated in this permit:

- (a) Visible emissions shall not exceed an average of thirty percent (30%) opacity in twenty-four (24) consecutive readings as determined by 326 IAC 5-1-4,
- (b) Visible emissions shall not exceed sixty percent (60%) opacity for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-8-5(a)(4)]

All air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
  - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
  - (2) If there is a change in the following:
    - (A) Asbestos removal or demolition start date;
    - (B) Removal or demolition contractor; or
    - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management  
Asbestos Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) **Procedures for Asbestos Emission Control**  
The Permittee shall comply with the emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are mandatory for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Indiana Accredited Asbestos Inspector**  
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

### **Testing Requirements [326 IAC 2-8-4(3)]**

#### **C.8 Performance Testing [326 IAC 3-6]**

---

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing methods approved by the IDEM,OAM.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

#### **Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

##### C.9 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment no more than ninety (90) days after receipt of this permit. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend compliance schedule an additional ninety (90) days provided the Permittee notify:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule with full justification of the reasons for inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

##### C.10 Maintenance of Monitoring Equipment [326 IAC 2-8-4(3)(A)(iii)]

- (a) In the event that a breakdown of the monitoring equipment occurs, a record shall be made of the times and reasons of the breakdown and efforts made to correct the problem. To the extent practicable, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less frequent than required in Section D of this permit until such time as the monitoring equipment is back in operation. In the case of continuous monitoring, supplemental or intermittent monitoring of the parameter should be implemented at intervals no less than one (1) hour until such time as the continuous monitor is back in operation.
- (b) The Permittee shall install, calibrate, quality assure, maintain, and operate all necessary monitors and related equipment. In addition, prompt corrective action shall be initiated whenever indicated.

**C.11 Monitoring Methods [326 IAC 3]**

---

Any monitoring or testing performed to meet the applicable requirements of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

**C.12 Pressure Gauge Specifications**

---

Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ( $\pm 2\%$ ) of full scale reading.

**Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

**C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]**

---

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Management  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

within ninety (90) days from the date of issuance of this permit.

The ERP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) If the ERP is disapproved by IDEM, OAM, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.
- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAM, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

**C.14 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]**

---

If a regulated substance, subject to 40 CFR 68, is present in a process in more than the threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall:

- (a) Submit:

- (1) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or
  - (2) As a part of the compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and
  - (3) A verification to IDEM, OAM, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.
- (b) Provide annual certification to IDEM, OAM, that the Risk Management Plan is being properly implemented.

All documents submitted pursuant to this condition shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.15 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-8-4][326 IAC 2-8-5]  
[326 IAC 1-6]

---

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
- (1) This condition;
  - (2) The Compliance Determination Requirements in Section D of this permit;
  - (3) The Compliance Monitoring Requirements in Section D of this permit;
  - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
  - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM, . The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of :
    - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
    - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.

- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
  - (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
  - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
  - (3) An automatic measurement was taken when the process was not operating; or
  - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]  
[326 IAC 2-8-5]

---

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected facility.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

## **Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]**

### **C.17 Monitoring Data Availability**

---

- (a) With the exception of performance tests conducted in accordance with Section C-Performance Testing all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements in (a) above.

### **C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5]**

---

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAM, representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Records of required monitoring information shall include, where applicable:
  - (1) The date, place, and time of sampling or measurements;
  - (2) The dates analyses were performed;
  - (3) The company or entity performing the analyses;
  - (4) The analytic techniques or methods used;
  - (5) The results of such analyses; and
  - (6) The operating conditions existing at the time of sampling or measurement.

- (c) Support information shall include, where applicable:
  - (1) Copies of all reports required by this permit;
  - (2) All original strip chart recordings for continuous monitoring instrumentation;
  - (3) All calibration and maintenance records;
  - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)]

- (a) To affirm that the source has met all the compliance monitoring requirements stated in this permit the source shall submit a Semi-annual Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported.
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Management  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (d) Unless otherwise specified in this permit, any semi-annual report shall be submitted within thirty (30) days of the end of the reporting period.
- (e) All instances of deviations as described in Section B- Deviations from Permit Requirements Conditions must be clearly identified in such reports.
- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.

- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

### Stratospheric Ozone Protection

#### C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

### SECTION D.1

### FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]-Melt and Blast Operations consisting of:

- (a) Eight (8) electric powered magnesium die casting machines, identified as DCM-1 through DCM-8, with a total maximum capacity of melting 3,950 pounds of magnesium ingot per hour, and exhausting uncontrolled through twelve (12) exhaust fans (S/V ID S01); and
- (b) Four (4) aluminum shotblasting units, identified as TB-01, HB-01, HB-02, and HB-03, each with a maximum capacity of finishing 3950 pounds of magnesium castings per hour, all controlled by a high efficiency wet scrubber (CD-01), and all exhausted through one (1) stack (S/V ID S02).

### Emission Limitations and Standards [326 IAC 2-8-4(1)]

#### D.1.1 Particulate Matter (PM) [326 IAC 6-3]

- (a) The particulate matter (PM) emissions from the eight (8) die casting machines (DCM-1 - DCM-8) shall not exceed a total of 6.47 pounds per hour when operating at a total process weight rate of 3950 pounds of magnesium per hour.

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and  
P = process weight rate in tons per hour

**D.1.2 Particulate Matter (PM) [326 IAC 6-1-2] [326 IAC 6-1-7]**

---

Pursuant to 326 IAC 6-1-2 (Particulate Emissions Limitations), the particulate matter (PM) emissions from the four (4) shotblasting units (TB-01, HB-01, HB-02, and HB-03) shall be limited to 0.03 grains per dry standard cubic foot (gr/dscf). This is equivalent to a particulate matter emission rate of 1.36 pounds per hour.

**D.1.3 Preventive Maintenance Plan [326 IAC 2-8-4(9)]**

---

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for each facility and any control device.

**Compliance Determination Requirements**

**D.1.4 Testing Requirements [326 IAC 2-8-5(a)(1), (4)]**

---

During the period between 24 and 36 months after issuance of this permit, the Permittee shall perform PM testing on the wet scrubber (CD-01) controlling the four (4) shotblasting units (TB-01, HB-01, HB-02, and HB-03) utilizing Methods 5 or 17 (40 CFR 60, Appendix A) or other methods as approved by the Commissioner to verify compliance with Condition D.1.2. This test shall be repeated at least once every five (5) years from the date of this valid compliance demonstration. In addition to these requirements, IDEM may require compliance testing when necessary to determine if the facility is in compliance.

**Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]**

**D.1.5 Particulate Matter (PM)**

---

To verify compliance with Condition D.1.2, the wet scrubber for PM control shall be in operation at all times when each of the four (4) shotblasting units (TB-01, HB-01, HB-02, and HB-03) are in operation and exhausting to the outside atmosphere.

**D.1.6 Scrubber Operating Condition**

---

- (a) The Permittee shall monitor and record the pressure drop and flow rate of the scrubber, at least once daily. The Preventive Maintenance Plan for the scrubber shall contain troubleshooting contingency and corrective actions for when the pressure drop and flow rate readings are outside of the normal range for any one reading.
- (b) The instruments used for determining the pressure drop and flow rate shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAM, and shall be calibrated at least once every six (6) months..
- (c) An inspection shall be performed each calendar quarter of the scrubber. Defective scrubber part(s) shall be replaced. A record shall be kept of the results of the inspection and the number of scrubber part(s) replaced.
- (d) In the event that a scrubber's failure has been observed:
  - (i) The affected process will be shut down immediately until the failed unit has been replaced.

- (ii) Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated, For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion

## **Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]**

### **D.1.7 Record Keeping Requirements**

---

- (a) To document compliance with Condition D.1.6, the Permittee shall maintain the following:
  - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
    - (A) Inlet and outlet differential static pressure; and
    - (B) Flow rate.
  - (2) Documentation of all response steps implemented, per event .
  - (3) Operation and preventive maintenance logs, including work purchases orders, shall be maintained.
  - (4) Quality Assurance/Quality Control (QA/QC) procedures.
  - (5) Operator standard operating procedures (SOP).
  - (6) Manufacturer's specifications or its equivalent.
  - (7) Equipment "troubleshooting" contingency plan.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

## **SECTION D.2**

### **FACILITY OPERATION CONDITIONS**

Facility Description [326 IAC 2-8-4(10)] - The following specifically regulated insignificant activities:

- (a) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6: (Two (2) cold cleaner degreasers, identified as WS#1 and WS#2).
- (b) One (1) stick welding machine, and one (1) Metal Inert Gas (MIG) welding unit used for maintenance purposes

## **Emissions Limitations and Standards**

### **D.2.1 Volatile Organic Compounds (VOC)**

---

- (a) Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaner degreaser facility shall ensure that the following control equipment requirements are met:

- (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:
    - (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)));
    - (B) The solvent is agitated; or
    - (C) The solvent is heated.
  - (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury) or six-tenths (0.6) pounds per square inch measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.
  - (3) Provide a permanent, conspicuous label which lists the operating requirements outlined in subsection (b).
  - (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure which does not cause excessive splashing.
  - (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury) or six-tenths (0.6) pounds per square inch measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):
    - (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
    - (B) A water cover when solvent is used is insoluble in, and heavier than, water.
    - (C) Other systems of demonstrated equivalent control such as a refrigerated chiller or carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.
- (b) Pursuant to 326 IAC 8-3-5(b) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaning facility shall ensure that the following operating requirements are met:
- (1) Close the cover whenever articles are not being handled in the degreaser.
  - (2) Drain cleaned articles for at least fifteen (15) seconds or until dripping ceases.

- (3) Store waste solvent only in covered containers and prohibit the disposal or transfer of waste solvent in any manner in which greater than twenty percent (20%) of the waste solvent by weight could evaporate.

#### D.2.2 Particulate Matter (PM) [326 IAC 6-3]

Pursuant to 326 IAC 6-3 (Process Operations), the allowable PM emission rate from the two (2) welding units shall not exceed allowable PM emission rate based on the following equation:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and  
P = process weight rate in tons per hour

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR MANAGEMENT  
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
CERTIFICATION**

Source Name: SPX Corporation-Contech Division  
Source Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
Mailing Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
FESOP No.: F141-8988-00044

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.**

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify) \_\_\_\_\_
- 9 Report (specify) \_\_\_\_\_
- 9 Notification (specify) \_\_\_\_\_
- 9 Other (specify) \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR MANAGEMENT  
COMPLIANCE DATA SECTION  
P.O. Box 6015  
100 North Senate Avenue  
Indianapolis, Indiana 46206-6015  
Phone: 317-233-5674  
Fax: 317-233-5967**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: SPX Corporation-Contech Division  
Source Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
Mailing Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
FESOP No.: F141-8988-00044

**This form consists of 2 pages**

**Page 1 of 2**

Check either No. 1 or No.2
<b>9</b> 1. This is an emergency as defined in 326 IAC 2-7-1(12) CThe Permittee must notify the Office of Air Management (OAM), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and CThe Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16
<b>9</b> 2. This is a deviation, reportable per 326 IAC 2-7-5(3)(c) CThe Permittee must submit notice in writing within ten (10) calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency/Deviation:
Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

**Page 2 of 2**

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation?    Y    N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO <sub>2</sub> , VOC, NO <sub>x</sub> , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
 OFFICE OF AIR MANAGEMENT  
 COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)  
 SEMI-ANNUAL COMPLIANCE MONITORING REPORT**

Source Name: SPX Corporation-Contech Division  
 Source Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
 Mailing Address: 520 South Byrkit Ave, Mishawaka, IN 46544  
 FESOP No.: F141-8988-00044:

Months: \_\_\_\_\_ to \_\_\_\_\_ Year: \_\_\_\_\_

This report is an affirmation that the source has met all the compliance monitoring requirements stated in this permit. This report shall be submitted semi-annually. Any deviation from the compliance monitoring requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD

9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD.

Compliance Monitoring Requirement (eg. Permit Condition D.1.3)	Number of Deviations	Date of each Deviation

Form Completed By: \_\_\_\_\_  
 Title/Position: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

# Indiana Department of Environmental Management Office of Air Management

## Technical Support Document (TSD) for a Federally Enforceable State Operating Permit (FESOP)

### Source Background and Description

Source Name: SPX Corporation - Contech Division  
Source Location: 520 South Byrkit Ave., Mishawaka, IN 46544  
County: St. Joseph  
SIC Code: 3364  
Operation Permit No.: F141-8988-00044  
Permit Reviewer: Jeremy Magliaro/EVP

The Office of Air Management (OAM) has reviewed a Federally Enforceable State Operating Permit (FESOP) application from the Contech Division of SPX Corporation relating to the operation of a non-ferrous, magnesium die casting plant for the production of automotive steering components.

### Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) Eight (8) electric powered magnesium die casting machines, identified as DCM-1 through DCM-8, with a total maximum capacity of melting 3,950 pounds of magnesium ingot per hour, and exhausting uncontrolled through twelve (12) exhaust fans (S/V ID S01); and
- (b) Four (4) aluminum shotblasting units, identified as TB-01, HB-01, HB-02, and HB-03, each with a maximum capacity of finishing 3950 pounds of magnesium castings per hour, all controlled by a high efficiency wet scrubber (CD-01), and all exhausted through one (1) stack (S/V ID S02).

### Unpermitted Emission Units and Pollution Control Equipment Requiring ENSR

There are no unpermitted facilities operating at this source during this review process.

### New Emission Units and Pollution Control Equipment Requiring ENSR

There are no new facilities to be reviewed under the ENSR process.

### Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (1) Fluxing of molten magnesium and dross removal with PM-10 emissions less than twenty-five (25) pounds per day;
- (2) Five (5) ink jet printing stations, identified as IJ-1 through IJ-5, with total VOC emissions less than fifteen (15) pounds per day;

- (3) Degreasing operations that do not exceed 145 gallons per 12 months, except if subject to 326 IAC 20-6 (Two (2) cold cleaner degreasers, identified as WS#1 and WS#2.)
- (4) One (1) wastewater storage tank with a maximum storage capacity of 5,000 gallons;
- (5) One (1) stick welding machine, and one (1) Metal Inert Gas (MIG) welding unit used for maintenance purposes with PM-10 emissions less than twenty-five (25) pounds per day; and
- (6) Miscellaneous wet machining operations emitting no PM-10 emissions, including:
  - (a) one (1) kingsbury machining center;
  - (b) one (1) 720 AF and 720 BB machining center; and
  - (c) one 723 broach machining center.

### **Existing Approvals**

The source has been operating under previous approvals including, but not limited to, the following:

- (1) CP-141-2001-00044, issued on June 12, 1991; and
- (2) CP-141-3110-00044, issued on June 8, 1994.

All conditions from previous approvals were incorporated into this FESOP.

### **Enforcement Issue**

There are no enforcement actions pending.

### **Recommendation**

The staff recommends to the Commissioner that the FESOP be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP application for the purposes of this review was received on September 17, 1997

### **Emission Calculations**

See Appendix A of this document for detailed emissions calculations from shotblasting (1 page).

The calculations submitted by the applicant have been verified and found to be accurate and correct. These calculations are provided below:

#### Die Casting Machines Emissions Calculations

Maximum raw material usage/Average raw material usage = 3950 lbs/hr /1336 lbs/hr = 2.96  
Average die spray usage = 1995 usage/1995 hours of operation = 4020 gal/6000 hrs  
= 0.67 gal/hr  
Maximum die spray usage = 0.67 gal/hr\*2.96 = 1.98 gal/hr

Average production = 561,232 pieces/600 hrs = 885 pieces per hour;  
 Production rate at Max production = 885 pieces/hr \* 2.96 = 2616 pieces/hr

PM Emission factor = (max die spray usage)\*(density)\*(%non-volatile) / max production rate  
 = (1.98 gal/hr)\*(8.3 lbs/gal)\*(35% non-volatile) / 2616 pieces/hr  
 = 0.0022 lbs/piece...\*(2616 pieces/hr)\*(8760 hrs/yr)\*(1 ton/2000 lbs) = 25.2 tons PM/yr;

Ink Jet Printing VOC Emissions

Average ink usage = 143 gal/yr;  
 Maximum ink usage (based on 1995 ink purchases) = (143 gal/yr)\*(2.96)\*(1 yr/250 days)\*  
 (1 day/24 hrs) = 0.07 gal/hr\*(8760 hrs/yr) = 618.0 gal/yr;

VOC Emission factor = (max usage)\*(density)\*(% volatile by weight)  
 VOC Emissions = (0.07 gal/hr)\*(7.51 lb/gal)\*(85%) = 0.447 lb VOC/hr\*(24 hrs/day)  
 = 10.73 lb VOC/day\*(365 day/yr)(1 ton/2000 lbs)  
 = 1.96 tons VOC/yr;

These printing operations qualify as insignificant activities.

Degreasing Operations VOC Emissions

The applicant states maximum VOC usage at the two (2) degreasers identified as WS#1 and WS#2 to be 0.81 tons VOC/yr each. These two (2) cold cleaner degreasers qualify as insignificant activities.

**Potential Emissions**

Pursuant to 326 IAC 1-2-55, Potential Emissions are defined as “emissions of any one (1) pollutant which would be emitted from a facility, if that facility were operated without the use of pollution control equipment unless such control equipment is necessary for the facility to produce its normal product or is integral to the normal operation of the facility.”

Pollutant	Potential Emissions (tons/year)
PM	226.19
PM-10	226.19
SO <sub>2</sub>	--
VOC	3.58
CO	--
NO <sub>x</sub>	--

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Potential Emissions (tons/year)
methanol	negligible
TOTAL	negligible

Note: The negligible methanol emissions occur at the insignificant ink-jet printing operations (see Insignificant Activities).

- (a) The potential emissions (as defined in 326 IAC 1-2-55) of PM10 are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) This source, otherwise required to obtain a Title V permit, has agreed to accept a permit with federally enforceable limits that restrict its PTE to below the Title V emission levels. Therefore, this source will be issued a Federally Enforceable State Operating Permit (FESOP), pursuant to 326 IAC 2-8.

**Limited Potential to Emit**

- (a) The source has accepted a federally enforceable limit on potential to emit PM10 of 99 tons per year (by using a wet scrubber to control PM10 emissions from the shotblasting units), consisting of:
  - (i) 99 tons per year for the significant activities.
- (b) The table below summarizes the total limited potential to emit of the significant and insignificant emission units.

Process/facility	Limited Potential to Emit (tons/year)						
	PM	PM-10	SO <sub>2</sub>	VOC	CO	NO <sub>x</sub>	HAPs
Die Casting Machines	28.33	28.33	--	--	--	--	--
Shotblasting	5.95	5.95	--	--	--	--	--
Insignificant Activities*	negl.	negl.	--	3.58	--	--	negl.
<b>Total Emissions</b>	<b>34.28</b>	<b>34.28</b>	--	<b>3.58</b>	--	--	<b>9.0 -single HAP 24.0 -total HAP</b>

\* Includes emissions from the ink jet printing operations and the two (2) cold cleaner degreasing operations (WS#1+ #2), and the two (2) maintenance welders.  
 \* The limited potential to emit PM/PM10 from the die casting machines and the shotblasting units is based on compliance with 326 IAC 6-3-2 (Process Operations) and 326 IAC 6-1-2 (Nonattainment Area Limitations), respectively.

**County Attainment Status**

The source is located in St. Joseph County.

Pollutant	Status
PM-10	attainment
SO <sub>2</sub>	attainment
NO <sub>2</sub>	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO<sub>x</sub>) are precursors for the formation of ozone. Therefore, VOC and NO<sub>x</sub> emissions are considered when evaluating the rule applicability relating to the ozone standards. St. Joseph County has been designated as attainment for ozone.

**Federal Rule Applicability**

- (a) The New Source Performance Standard (326 IAC 12), 40 CFR Part 60, Subpart QQ (Publication Rotogravure Printing), is not applicable to this source because this source does not perform publication rotogravure printing as defined in the rule.

- (b) The National Emission Standard for Hazardous Air Pollutants (NESHAPs), 40 CFR Part 63 Subpart KK (Printing Operations) is not applicable to this source because this source does not perform publication rotogravure, product and packaging rotogravure, or wide web flexographic printing as defined in the rule.

### **State Rule Applicability - Entire Source**

#### 326 IAC 2-6 (Emission Reporting)

This source is located in St. Joseph County and the potential to emit VOC is less than ten (10) tons per year. The source potential to emit PM10 including federally enforceable limits, is less than one-hundred (100) tons per year including fugitive emissions. Therefore, 326 IAC 2-6 (Emission Reporting) does not apply.

#### 326 IAC 5-1 (Visible Emissions Limitations)

Pursuant to 326 IAC 5-1-2 (Visible Emissions Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), visible emissions shall meet the following, unless otherwise stated in this permit:

- (a) Visible emissions shall not exceed an average of thirty percent (30%) opacity in twenty-four (24) consecutive readings as determined by 326 IAC 5-1-4,
- (b) Visible emissions shall not exceed sixty percent (60%) opacity for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) in a six (6) hour period.

#### 326 IAC 6-4 (Fugitive Dust Emissions)

This source is subject to 326 IAC 6-4 for fugitive dust emissions. Pursuant to 326 IAC 6-4 (Fugitive Dust Emissions), fugitive dust shall not be visible crossing the boundary or property line of a source. Observances of visible emissions crossing property lines may be refuted by factual data expressed in 326 IAC 6-4-2(1), (2) or (3).

### **State Rule Applicability - Individual Facilities**

#### 326 IAC 6-1-2 (Particulate matter nonattainment area limitations)

- (a) Pursuant to 326 IAC 6-1-1(3), the four (4) shotblasting facilities (TB-01, HB-01, HB-02, and HB-03) are subject to 326 IAC 6-1-2(a) (General sources: particulate emission limitations) because they have the potential to emit PM greater than 100 tons per year, and they are not specifically regulated by 326 IAC 6-1-18 (St. Joseph County PM Limitations). Therefore, pursuant to 326 IAC 6-1-2(a) (General Source Requirements), these four (4) shotblasting facilities shall not discharge into the atmosphere any gases which contain particulate matter in excess of 0.03 grains per dry standard cubic foot (dscf). This is equivalent to an emission rate of 1.36 pounds of PM per hour.

The four (4) shotblasting facilities (TB-01, HB-01, HB-02, and HB-03) are all controlled by a high efficiency wet scrubber (CD-01) with an outlet emission rate of 0.46 pounds of PM per hour. Therefore, these facilities are in compliance with 326 IAC 6-1-2(a) (General Source Requirements). The wet scrubber shall be in operation at all times that each shotblaster is in operation, in order to comply with this rule.

- (b) Pursuant to 326 IAC 6-1-1(3), the eight (8) die casting machines are not subject to 326 IAC 6-1-2 (General sources: particulate emission limitations) because the facilities have potential PM emissions less than 100 tons per year and actual PM emissions less than 10 tons per year. Therefore, the regulations under 326 IAC 6-1-2 (General sources: particulate emission limitations) do not apply.

326 IAC 6-1-18 (St. Joseph County PM Limitations)

This source is not specifically regulated and does not have any specifically regulated facilities listed in 326 IAC 6-1-18 (St. Joseph County limitation). Therefore, this rule does not apply.

326 IAC 6-3-2 (Process Operations)

- (a) The particulate matter (PM) and PM10 emissions from the eight (8) die casting machines (DCM-1 - DCM-8), shall not exceed a total of 6.47 pounds per hour when operating at a total process weight rate of 3950 pounds of magnesium per hour; and

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

$$E = 4.10(1.975)^{0.67} = 6.47 \text{ lbs PM/hr or } 28.33 \text{ tons per year;}$$

The eight (8) die casting machines DCM-1 - DCM-8 have potential PM emissions of 25.2 tons per year in compliance with 326 IAC 6-3-2 (Process Operations).

- (b) The particulate matter (PM) and PM10 emissions from the four (4) shotblasting units (TB-01, HB-01, HB-02, and HB-03) are regulated by 326 IAC 6-1-2 (Particulate Emissions Limitations). Therefore, 326 IAC 6-3-2 (Process Operations), does not apply.
- (c) Pursuant to 326 IAC 6-3 (Process Operations), the allowable PM emission rate from the maintenance welding units shall not exceed allowable PM emission rate based on the following equation:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

326 IAC 8-3-5 (Cold Cleaner Degreaser Operation and Control)

The two (2) cold cleaner degreasers identified as WS#1 and WS#2 (see Insignificant Activities), must comply with 326 IAC 8-3-5 (Cold Cleaner Degreaser Operation and Control).

- (a) Pursuant to 326 IAC 8-3-5(a) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaner degreaser facility shall ensure that the following control equipment requirements are met:

- (1) Equip the degreaser with a cover. The cover must be designed so that it can be easily operated with one (1) hand if:
- (A) The solvent volatility is greater than two (2) kiloPascals (fifteen (15) millimeters of mercury or three-tenths (0.3) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F));
- (B) The solvent is agitated; or
- (C) The solvent is heated.

- (2) Equip the degreaser with a facility for draining cleaned articles. If the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury) or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), then the drainage facility must be internal such that articles are enclosed under the cover while draining. The drainage facility may be external for applications where an internal type cannot fit into the cleaning system.
  - (3) Provide a permanent, conspicuous label which lists the operating requirements outlined in subsection (b).
  - (4) The solvent spray, if used, must be a solid, fluid stream and shall be applied at a pressure which does not cause excessive splashing.
  - (5) Equip the degreaser with one (1) of the following control devices if the solvent volatility is greater than four and three-tenths (4.3) kiloPascals (thirty-two (32) millimeters of mercury) or six-tenths (0.6) pounds per square inch) measured at thirty-eight degrees Celsius (38°C) (one hundred degrees Fahrenheit (100°F)), or if the solvent is heated to a temperature greater than forty-eight and nine-tenths degrees Celsius (48.9°C) (one hundred twenty degrees Fahrenheit (120°F)):
    - (A) A freeboard that attains a freeboard ratio of seventy-five hundredths (0.75) or greater.
    - (B) A water cover when solvent is used is insoluble in, and heavier than, water.
    - (C) Other systems of demonstrated equivalent control such as a refrigerated chiller or carbon adsorption. Such systems shall be submitted to the U.S. EPA as a SIP revision.
- (b) Pursuant to 326 IAC 8-3-5(b) (Cold Cleaner Degreaser Operation and Control), the owner or operator of a cold cleaning facility shall ensure that the following operating requirements are met:
- (1) Close the cover whenever articles are not being handled in the degreaser.
  - (2) Drain cleaned articles for at least fifteen (15) seconds or until dripping ceases.
  - (3) Store waste solvent only in covered containers and prohibit the disposal or transfer of waste solvent in any manner in which greater than twenty percent (20%) of the waste solvent by weight could evaporate.

326 IAC 8-5-5 (Graphic Arts Operations)

This rule applies to packaging rotogravure, publication rotogravure, and flexographic printing facilities. This source only utilizes an insignificant ink jet printing operation which does not qualify as a rotogravure or flexographic printing operation. Therefore, 326 IAC 8-5-5 (Graphic Arts Operations), is not applicable.

## Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

1. The four (4) shotblasting systems (TB-01, HB-01, HB-02, and HB-03) have applicable compliance monitoring conditions as specified below:
  - (a) Daily visible emissions notations of the wet scrubber shall be performed during normal daylight operations. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Preventive Maintenance Plan for this unit shall contain troubleshooting contingency and corrective actions for when an abnormal emission is observed.
  - (b) The Permittee shall monitor and record the pressure drop and flow rate of the scrubber controlling the four (4) shotblasting systems (TB-01, HB-01, HB-02, and HB-03), at least once daily when any of the four (4) the shot blasting systems are in operation. The Preventive Maintenance Plan for the scrubber shall contain troubleshooting contingency and corrective actions for when the pressure drop and flow rate readings are outside of the normal range for any one reading.

These monitoring conditions are necessary because the wet scrubber for the shotblasting systems must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-8 (FESOP).

## Air Toxic Emissions

Indiana presently requests applicants to provide information on emissions of the 187 hazardous air pollutants (HAPs) set out in the Clean Air Act Amendments of 1990. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Management (OAM) FESOP Application Form GSD-08.

- (a) This source will emit levels of air toxics less than those which constitute a major source according to Section 112 of the 1990 Clean Air Act Amendments.

**Conclusion**

The operation of this magnesium die casting plant for the production of automotive steering components. shall be subject to the conditions of the attached proposed **FESOP No. F141-8988-00044.**

**Indiana Department of Environmental Management  
Office of Air Management**

Addendum to the  
Technical Support Document for Federally Enforceable State Operating  
Permit (FESOP)

**Source Name:** SPX Corporation - Contech Division  
**Source Location:** 520 South Byrkit Ave., Mishawaka, IN 46544  
**County:** St. Joseph  
**SIC Code:** 3364  
**Operation Permit No.:** F141-8988-00044  
**Permit Reviewer:** Jeremy Magliaro/EVP

On August 10, 1998, the Office of Air Management (OAM) had a notice published in the South Bend Tribune, South Bend, Indiana, stating that SPX Corporation - Contech Division had applied for a Federally Enforceable State Operating Permit (FESOP) to operate a magnesium die casting plant for the production of automotive steering components. The notice also stated that OAM proposed to issue a FESOP for this operation and provided information on how the public could review the proposed FESOP and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this FESOP should be issued as proposed.

Upon further review, the OAM has decided to make the following changes to the FESOP (new language is indicated by a **boldface**, deleted language is indicated by a ~~strikeout~~):

1. The wet scrubber identified as CD-01 controlling the four (4) shotblasting machines (TB-01, HB-01, HB-02, and HB-03) has not had a performance test in the past five (5) years. Therefore, Condition D.1.4 (Testing Requirements) on page 25 of 32 has been changed to include a PM testing requirement to verify compliance with Condition D.1.2 as follows:

D.1.4 Testing Requirements [326 IAC 2-8-5(a)(1), (4)]

~~The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM limits specified in Conditions D.1.1 and D.1.2 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.~~ **During the period between 24 and 36 months after issuance of this permit, the Permittee shall perform PM testing on the wet scrubber (CD-01) controlling the four (4) shotblasting units (TB-01, HB-01, HB-02, and HB-03) utilizing Methods 5 or 17 (40 CFR 60, Appendix A) or other methods as approved by the Commissioner to verify compliance with Condition D.1.2. This test shall be repeated at least once every five (5) years from the date of this valid compliance demonstration. In addition to these requirements, IDEM may require compliance testing when necessary to determine if the facility is in compliance.**

2. The following language has been added into Condition D.1.5 on page 25 of 32 to include a reference to operating condition D.1.2:

**D.1.5 Particulate Matter (PM)**

---

**To verify compliance with Condition D.1.2**, the wet scrubber for PM control shall be in operation at all times when each of the four (4) shotblasting units (TB-01, HB-01, HB-02, and HB-03) are in operation and exhausting to the outside atmosphere.

**Appendix A: Process Particulate Emissions**

**Company Name:** SPX Corporation-Contech Division  
**Address City IN Zip:** 520 South Byrkit Ave, Mishawaka, IN 46544  
**FESOP:** F141-8988  
**Plt ID:** 141-00044  
**Reviewer:** JM/EVP  
**Date:** May 30, 1998

Potential Uncontrolled Emissions (tons/year)						
A. Scrubbers						
Process	No. of Units	Grain Loading per Actual Standard Cubic Foot of Outlet Air	Flow Rate (gpm)	Liquid to Air Ratio (gpm/1,000 acfm)	Control Efficiency	Total (tons/yr)
CD-01	1	0.00800	35.0	5.2	99.00%	200.99
Potential Controlled Emissions (tons/year)						
A. Scrubbers						
Process	No. of Units	Grain Loading per Actual Standard Cubic Foot of Outlet Air	Flow Rate (gpm)	Liquid to Air Ratio (gpm/1,000 acfm)	Control Efficiency	Total (tons/yr)
CD-01	1	0.00800	35.0	5.2	99.00%	2.01

Methodology:

Uncontrolled Potential Emissions:

Scrubber (tons/yr) = No. Units \* Loading (grains/acf) \* Flow Rate (gpm) \* 1/Liquid to Air Ratio (gpm/1,000 acfm) \* 1 lb/7,000 grains \* 60 min/hr \* 8760 hr/yr \* 1 ton/2,000 lbs \* 1/(1-Control Efficiency)

Potential Emissions (controlled):

Scrubber (tons/yr) = No. Units \* Loading (grains/acf) \* Flow Rate (gpm) \* 1/Liquid to Air Ratio (gpm/1,000 acfm) \* 1 lb/7,000 grains \* 60 min/hr \* 8760 hr/yr \* 1 ton/2,000 lbs

**Compliance with 326 IAC 6-1-2 (PM Emissions Limitations)**

The following calculations determine compliance with 326 IAC 6-1-2 (for counties listed in 326 IAC 6-1-7), which limits stack emissions to 0.03 gr/dscf (when in counties listed in 326 IAC 6-1-7),

$$\frac{2.01 \text{ ton/yr} * 2000 \text{ lb/ton} * 7000 \text{ gr/lb}}{525,600 \text{ min/yr} * 5,282 \text{ dscf/min}} = 0.010 \text{ gr/dscf} \quad (\text{will comply})$$

Note: Allowable particulate emissions under 326 IAC 6-1-2 equate to 5.95 tons per year, or 1.36 lbs/hr.

$$\text{SCFM} = \frac{6,690 \text{ acfm} * (460 + 68) * (1.0 - 0.2)}{(460 + 75)}$$

$$= 5,282 \text{ scfm}$$

Assumes exhaust gas temperature of 75F, exhaust gas moisture content of 20% and exhaust gas flow of 6690 acfm.